

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396503
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Hong; Jong Pyo

Method of manufacturing a three-fold tie with body folded twice by gatefold

Abstract

A three-fold tie with a body folded twice by a gatefold, includes: a body of fabric where body part fabric is folded once by a gatefold and folded once more by a gatefold so that both ends overlap; a blade portion of fabric where sword-shaped blade part fabric is folded once by a gatefold so that both ends overlap and fabric part of the overlapped upper end is folded inward once more; and a tail portion of fabric where sword-shaped tail part fabric is folded once by a gatefold so that both ends overlap and fabric part of the overlapped upper end is folded inward once more.

Inventors:	Hong; Jong Pyo (Seoul, KR)
Applicant:	Hong; Jong Pyo (Seoul, KR)
Family ID:	1000008782732
Appl. No.:	18/596680
Filed:	March 06, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240206575 A1	Jun. 27, 2024

Foreign Application Priority Data

KR	10-2020-0098136	Aug. 05, 2020
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc US 18018268 ABANDONED WO PCT/KR2021/010278 20210804 child-doc US 18596680

Publication Classification

Int. Cl.: A41D25/00 (20060101)

U.S. Cl.:

CPC A41D25/001 (20130101);

Field of Classification Search

CPC: A41D (25/06); A41D (25/001); A41D (25/00); A41D (25/16)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1599950	12/1925	Blanchard	N/A	N/A
1782183	12/1929	Strauss	N/A	N/A
1885956	12/1931	Simson	N/A	N/A
2086365	12/1936	Rehor	N/A	N/A
2179133	12/1938	Rehor	N/A	N/A
2205105	12/1939	Naftali	N/A	N/A
2304935	12/1941	Langsdorf	N/A	N/A
2413398	12/1945	Whitman	N/A	N/A
2504843	12/1949	Kaplan	N/A	N/A
2611900	12/1951	Hertz	N/A	N/A
2887687	12/1958	Bergheim	N/A	N/A
3657743	12/1971	Bucci	N/A	N/A
3720958	12/1972	Cowdrey	N/A	N/A
4123802	12/1977	Ackerman	N/A	N/A
4506389	12/1984	Franklin	N/A	N/A
4694509	12/1986	Grubman	N/A	N/A
5012530	12/1990	Ackerman	N/A	N/A
6205587	12/2000	Shiffler	N/A	N/A
6233741	12/2000	Loree et al.	N/A	N/A
6243874	12/2000	Yoon	N/A	N/A
6550650	12/2002	Fortier	N/A	N/A
6687914	12/2003	Conyers	2/144	A41D 25/00
8117671	12/2011	Kim	N/A	N/A
2009/0172863	12/2008	Somma	N/A	N/A
2009/0265833	12/2008	Kim	N/A	N/A
2018/0263318	12/2017	David	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1284108	12/2002	EP	N/A
2899071	12/2006	FR	N/A
2295764	12/1995	GB	N/A
10-1993-0007393	12/1992	KR	N/A

OTHER PUBLICATIONS

International Search Report for PCT/KR2021/010278 mailed Nov. 11, 2021 from Korean Intellectual Property Office. cited by applicant

Primary Examiner: Hoey; Alissa L

Attorney, Agent or Firm: Revolution IP, PLLC

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a Continuation of U.S. patent application Ser. No. 18/018,268 filed on Jan. 27, 2023, which is a National Stage Patent Application of PCT International Patent Application No. PCT/KR2021/010278 filed on Aug. 4, 2021, which claims priority to Korean Patent Application No. 10-2020-0098136 filed on Aug. 5, 2020, which are all hereby incorporated by reference in their entirety.

BACKGROUND OF THE INVENTION

(1) The present invention relates to a tie to enable more people to experience an elegant knot of a seven-fold tie.

(2) What is Gatefold?

(3) FIG. 1 shows a plan view of square fabric. The fabric is folded like a double door when folded along a dotted line. This is a gatefold. Three panels are formed by a gatefold, wherein the left and right panels are half the width of the center panel and folded inward to meet in the middle without overlapping. In FIG. 1, the square fabric is folded once by a gatefold. In FIG. 2, the fabric is folded once more by a gatefold after the process in FIG. 1. FIG. 3 is a cross section of the square fabric when folded once by a gatefold. FIG. 4 is a cross section of the square fabric when folded twice by a gatefold.

(4) What Makes the Knot of Seven-Fold Ties Different

(5) A knot of a tie is made within a body so its shape is determined by the combination of the structure (e.g., how body part fabric is folded) and components of the body. FIG. 11 is a cross section of a body 711 of a seven-fold tie. FIG. 9 is a cross section of a body 311 of a three-fold tie. As can be seen in FIG. 11, the body 711 of the seven-fold tie has a structure where body part fabric 7001 is folded once by a gatefold and folded once more by a gatefold so that both ends overlap, which is a structure where the body part fabric 7001 is folded twice by a gatefold. Meanwhile the body 311 of the three-fold tie has a structure where body part fabric 3001 is folded once by a gatefold so that both ends overlap and a fabric part 3106 of the overlapped upper end is folded inward once more. For reference, folding the fabric part 3106 of the overlapped upper end inward once more is for finishing (Explanation 1), and has little effect on the thickness of the body 311. Thus interlining 301 is inserted into the body 311 of the three-fold tie where the body part fabric 3001 is folded once by a gatefold to compensate for the thickness of the tie. As such, the body 711 of the seven-fold tie and the body 311 of the three-fold tie have different structures and components, and thus knots of the two different types of ties are distinctly different. The shape of the knot of the three-fold tie is determined by the combination of the interlining 301 and the body part fabric 3001 folded once by a gatefold within the body 311. Thus, the elegance of good fabric is not fully contained in the knot due to the interlining 301 inserted to compensate for the thickness of the three-fold tie. Meanwhile the seven-fold tie is made only by folding the fabric without interlining, and thus the elegance of good fabric is intact in the knot thereof. This is why the knot of

seven-fold ties gives differentiated elegance.

(6) (Explanation 1) Finishing: when the body part fabric **3001** is folded once by a gatefold within the body **311** of the three-fold tie so that both ends overlap, a section of the fabric part **3106** of the overlapped upper end is exposed to the outside. Thus, it is necessary to fold the fabric part **3106** of the overlapped upper end inward once more so that the section of the fabric part **3106** is not exposed to the outside.

(7) What Makes Seven-Fold Ties Expensive

(8) Reliance on Overseas Production

(9) Domestic tie manufacturing plants have been intensively producing three-fold ties for a long time, a product of mass production. The manufacturing process is designed accordingly. Thus, producing handicrafts such as seven-fold ties which are difficult to produce and require long time effort has been discouraged. Seven-fold ties may be manufactured domestically, and there have been such attempts. However, the quality of manufactured products is poor due to the absence of skilled manufacturers.

(10) Meanwhile production based on artisan culture has been developed in European countries such as Italy and France, and thus people in those countries are familiar with making seven-fold ties which require craftsmanship.

(11) For this reason, there is a difference in quality comparing seven-fold ties made by skilled artisans overseas with seven-fold ties made by unskilled domestic workers. Thus, there is no choice but to have seven-fold ties made by skilled artisans overseas.

(12) If seven-fold ties are made by skilled artisans overseas, expensive labor costs have to be paid to the makers. In addition, expensive overseas shipping costs and custom duties that would not have to be paid for domestic production are added to the production cost of products.

(13) A Relatively Large Amount of Fabric Required to Produce Seven-Fold Ties

(14) Table 1 compares the amounts of fabric required to make one piece of three-fold tie and one piece of seven-fold tie. As can be seen in Table 1, about 60 cm of fabric (based on a fabric with a width of 100 cm) is required to make one piece of a seven-fold tie. This is close to three times the amount of fabric required to make one piece of three-fold tie (22 cm).

(15) TABLE-US-00001 TABLE 1 The amount of fabric required to make one piece of tie (based on a fabric with a width of 100 cm) Three-fold tie About 22 cm Seven-fold tie About 60 cm Compared to a three-fold tie, about 3 times as much fabric is required

(16) In FIG. **18**, a pattern **700** of a seven-fold tie and a pattern **300** of a three-fold tie are superimposed. As can be seen in FIG. **18**, the seven-fold tie requires a relatively large amount of fabric compared to the three-fold tie. A large difference in the amount of fabric may be seen particularly in the blade portion and the tail portion.

(17) A Large Amount of Time Required to Produce Seven-Fold Ties

(18) Seven-fold ties are handicrafts and it take a lot of production time per unit product. This causes its supply to be limited, and the limited supply naturally leads to an increase in selling price.

(19) Standardized Structure and Manufacturing Method of Ties

(20) The structure and manufacturing method of three-fold ties and seven-fold ties are standardized.

(21) Details of the Production of Three-Fold Ties

(22) Three-Fold Tie with Lining

(23) Prepare fabric and a pattern **300** of a three-fold tie to produce a tie.

(24) After the preparing step, cut the fabric to fit the pattern **300**.

(25) After the cutting step, add a lining to blade part fabric **3000** and tail part fabric **3002**.

(26) After the adding step, place tie interlining **301** on the center of the cut fabric as shown in FIG. **6**.

(27) After the placing step, fold the fabric by a gatefold once so that both ends overlap as shown in FIG. **7**.

- (28) After the folding step, fold fabric part of the overlapped upper end inward for finishing as shown in FIG. 8.
- (29) After the folding step, sew the interlining **301** and left and right panels formed by folding the fabric by a gatefold with a long single thread to fix them.
- (30) After the sewing step, fix a blade portion **310** and a tail portion **312** using a bar tack.
- (31) After the fixing step, attach a keeper loop, brand label, care label, etc. to the tie according to one's preferences.
- (32) Three-Fold Tie without Lining (Sfoderato Three-Fold Tie)
- (33) Prepare fabric and a pattern **300** of a three-fold tie to produce a tie.
- (34) After the preparing step, cut the fabric to fit the pattern **300**.
- (35) After the cutting step, roll up and sew edges of blade part fabric **3000** and tail part fabric **3002**.
- (36) After the rolling up and sewing step, place tie interlining **301** on the center of the cut fabric as shown in FIG. 6.
- (37) After the placing step, fold the fabric by a gatefold once so that both ends overlap as shown in FIG. 7.
- (38) After the folding step, fold fabric part of the overlapped upper end inward for finishing as shown in FIG. 8.
- (39) After the folding step, sew the interlining **301** and left and right panels formed by folding the fabric by a gatefold with a long single thread to fix them.
- (40) After the sewing step, fix a blade portion **310** and a tail portion **312** using a bar tack.
- (41) After the fixing step, cut the interlining **301** from the bottom of the bar tack.
- (42) After the cutting step, attach a keeper loop, brand label, care label, etc. to the tie according to one's preferences.
- (43) Details of the Production of Seven-Fold Ties
- (44) Prepare fabric and a pattern **700** of a seven-fold tie to produce a tie.
- (45) After the preparing step, cut the fabric to fit the pattern **700**.
- (46) After the cutting step, adding a lining to blade part fabric **7000** and tail part fabric **7002**. When a Sfoderato method is used to produce the tie, roll up and sew edges of the blade part fabric **7000** and the tail part fabric **7002**.
- (47) After the adding step, fold the blade part fabric **7000** and the tail part fabric **7002** seven times, and fold body part fabric **7001** once by a gatefold and fold once more by a gatefold so that both ends overlap.
- (48) After the folding step, sew left and right panels formed by folding the fabric with a long single thread to fix them.
- (49) After the sewing step, fix a blade portion **710** and a tail portion **712** using a bar tack.
- (50) After the fixing step, attach a keeper loop, brand label, care label, etc. to the tie according to one's preferences.
- (51) What is Sfoderato Tie?
- (52) Sfoderato is an Italian word. It is translated into "without a lining." Thus, Sfoderato ties literally mean "ties without a lining." As linings may be seen on the inside of jackets, linings may also be seen on the back of a blade portion and a tail portion of a tie. Sfoderato ties are ties without this kind of linings. For Sfoderato ties, linings are not used but edges of blade part fabric and tail part fabric are rolled up and sewn.
- SUMMARY OF THE INVENTION
- (53) A knot of a seven-fold tie presents differentiated elegance. However, seven-fold ties are too expensive for many people to enjoy. For this reason, seven-fold ties are consumed only by some enthusiasts or a few people who can afford to buy them. This invention is for making more people experience the elegant knot of seven-fold ties.
- (54) FIG. 10 shows a pattern **700** of a seven-fold tie. The seven-fold tie is divided into three parts as follows: a body **711**, a blade portion **710** and a tail portion **712**. A knot of a tie is made within a

body, so the body **711** is a main factor that makes a knot of a seven-fold tie elegant while other two parts are not. However, the blade portion **710** and tail portion **712** are main factors that increase the price of the seven-fold tie. Thus, it is necessary to change the structure of the blade portion **710** and the tail portion **712** while maintaining that of the body **711**. The structure of the blade portion **710** and the tail portion **712** is changed to that of a three-fold tie.

(55) FIG. **12** is a plan view of a pattern (one continuous fabric piece) **100** of the invented tie to solve the problem. As can be seen in FIG. **12**, the pattern (one continuous fabric piece) **100** includes a body part (**111**), a head part (**110**), and a tail part (**112**). The body part **111** has a structure of a seven-fold tie where body part fabric **1001** is folded once by a first gatefold and folded once more by a second gatefold so that both ends overlap, which is a structure where the body part fabric **1001** is folded twice by the first and second gatefolds. The blade and tail portions **710** and **712** in FIG. **10** which increase the cost of seven-fold tie are produced by changing the structure thereof to that of a three-fold tie which is a structure where sword-shaped blade and tail part fabrics **1000** and **1002** are folded once by a gatefold so that both ends overlap and fabric parts **1106** and **1126** of overlapped upper ends are folded inward once more for finishing. In FIG. **12**, the head part located at a middle portion of the continuous fabric piece has a tapered end at a first end portion of the middle portion with a first step difference having a width narrower than a width of the middle portion. The first step difference forms one of a right angle, an acute angle, or an obtuse angle with respect to a longitudinal edge of the continuous fabric piece. The tail part has a tapered end at a second end portion of the middle portion with a second step difference having a width narrower than the width of the middle portion. The body part is divided into seven panels by six longitudinal folding lines consisting of a first, second, third, fourth, fifth, and sixth folding lines. The head part includes the third, fourth, and fifth folding lines extending from the body part. The tail part includes the third, fourth, and fifth folding lines extending from the body part. The one continuous fabric piece is folded by the first gatefold along the second and fifth folding lines such that outer ends of the continuous fabric piece are folded inwardly up to a longitudinal center region of the body part without overlapping. After the first gatefold is performed, the second folding line becomes a first outer edge of the one continuous fabric piece, and the fifth folding line becomes a second outer edge of the one continuous fabric piece as such the fifth folding line of the head, body, and tail parts is folded during the step of performing the first gatefold. The one continuous fabric piece is folded by the second gatefold along the third and fourth folding lines such that outer ends of the first gatefold are folded inwardly with overlapping, thereby forming a thickness suitable for making knots.

(56) Regarding the connection between the body **111** and the blade portion **110** and between the body **111** and the tail portion **112**, the body **111** is connected to the blade portion **110** while sections **1111** and **1101** are symmetrical in one part of the body **111**, and the body **111** is connected to the tail portion **112** while sections **1111** and **1121** are symmetrical in the other part of the body **111**, wherein the sections **1101**, **1121** and **1111** are sections of fabric parts exposed to the outside of the blade portion **110**, the tail portion **112** and the body **111**, respectively.

(57) Why are the blade portion **110** and the tail portion **112** of the invention produced in the structure of a three-fold tie? This is because the three-fold tie is a product of mass production. A series of production processes are efficiently optimized for the three-fold tie. Thus, it is the most efficient to make the blade portion and the tail portion in a three-fold tie structure.

(58) Why is the body part fabric **1001** folded by a gatefold twice within the body **111** of the invention? This is because the body part fabric **7001** is folded by a gatefold twice within the body **711** of the seven-fold tie. When the body part fabric is folded twice by a gatefold, the body has a thickness suitable for making knots. However, when the body part fabric is folded only once by a gatefold, the body is so thin that interlining needs to be added thereto. When the body part fabric is folded three times by a gatefold, the body is so thick that a knot is not properly made.

(59) The tie invented to solve the problem has the same body structure as a seven-fold tie, and thus

it enables the same experience as a knot of a seven-fold tie. However, a blade portion and a tail portion of the tie are made in a three-fold tie structure, which enables the reduction of production costs. In detail, domestic production became possible by lowering the production difficulty. Thus, there is no need to have products manufactured overseas while paying expensive labor costs, overseas shipping costs, and customs duties. In addition, the production time per unit product was reduced compared to seven-fold ties. This allows a larger supply and prevent an increase in selling price due to the scarcity of products. Lastly, the amount of fabric required for production per unit product is reduced compared to seven-fold ties. FIG. 19 is a plan view in which the pattern 700 of the seven-fold tie and the pattern 100 of the present invention are superimposed. As can be seen in FIG. 19, a large amount of fabric is saved in the blade portion 110 and the tail portion 112.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a plan view showing that square fabric is folded once by a gatefold.
- (2) FIG. 2 is a plan view showing that square fabric that has already been folded once by a gatefold is folded once more by a gatefold.
- (3) FIG. 3 is a cross section of square fabric when folded once by a gatefold.
- (4) FIG. 4 is a cross section of square fabric when folded twice by a gatefold.
- (5) FIG. 5 is a plan view of a pattern 300 of a three-fold tie.
- (6) FIG. 6 is a plan view in which interlining 301 is placed on the center of the fabric cut to fit the pattern 300 of the three-fold tie.
- (7) FIG. 7 is a plan view in which the fabric cut to fit the pattern 300 of the three-fold tie is folded once by a gatefold so that both ends overlap.
- (8) FIG. 8 is a plan view in which fabric cut to fit the pattern 300 of the three-fold tie is folded once by a gatefold so that both ends overlap and a fabric part of the overlapped upper end is folded inward once more.
- (9) FIG. 9 is a cross section of a body 311 of the three-fold tie.
- (10) FIG. 10 is a plan view of a pattern 700 of a seven-fold tie.
- (11) FIG. 11 is a cross section of a body 711 of the seven-fold tie.
- (12) FIG. 12 is a plan view of a pattern 100 of the invented tie.
- (13) FIG. 13 is a plan view in which the fabric cut to fit the pattern 100 of the invented tie is folded once by a gatefold.
- (14) FIG. 14 is a plan view of the invented tie.
- (15) FIG. 15 is a cross section of a blade portion 110 of the invented tie.
- (16) FIG. 16 is a cross section of a body 111 of the invented tie.
- (17) FIG. 17 is a cross section of a tail portion 112 of the invented tie.
- (18) FIG. 18 is a plan view in which a pattern 300 of a three-fold tie and a pattern 700 of a seven-fold tie are superimposed.
- (19) FIG. 19 is a plan view in which the pattern 100 of the invented tie and the pattern 700 of the seven-fold tie are superimposed.

DESCRIPTION OF NUMERALS

- (20) 100: Pattern of invented tie 110: Blade portion of invented tie 111: Body of invented tie 112: Tail portion of invented tie 1000: Blade part fabric of invented tie 1001: Body part fabric of invented tie 1002: Tail part fabric of invented tie 1101: Section of fabric part exposed to outside of blade portion 110 of invented tie 1102: Section of fabric part not exposed to outside of blade portion 110 of invented tie 1111: Section of fabric part exposed to outside of body 111 of invented tie 1112: Section of fabric part not exposed to outside of body 111 of invented tie 1121: Section of fabric part exposed to outside of tail portion 112 of invented tie 1122: Section of fabric part not

exposed to outside of tail portion **112** of invented tie **1103**: Section of fabric part **1106** of overlapped upper end within blade portion **110** of invented tie **1104**: Section of fabric part of overlapped lower end within blade portion **110** of invented tie **1123**: Section of fabric part **1126** of overlapped upper end within tail portion **112** of invented tie **1124**: Section of fabric part of overlapped lower end within tail portion **112** of invented tie **1105**: Section of fabric part **1106** of overlapped upper end folded inward within blade portion **110** of invented tie **1125**: Section of fabric part **1126** of overlapped upper end folded inward within tail portion **112** of invented tie **1106**: Fabric part of overlapped upper end within blade portion **110** of invented tie **1107**: Fabric part of overlapped upper end folded inward within blade portion **110** of invented tie **1126**: Fabric part of overlapped upper end within tail portion **112** of invented tie **1127**: Fabric part of overlapped upper end folded inward within tail portion **112** of invented tie **300**: Pattern of three-fold tie **301**: Interlining of three-fold tie **310**: Blade portion of three-fold tie **311**: Body of three-fold tie **312**: Tail portion of three-fold tie **3000**: Blade part fabric of three-fold tie **3001**: Body part fabric of three-fold tie **3002**: Tail part fabric of three-fold tie **3103**: Section of fabric part **3106** of overlapped upper end within body **311** of three-fold tie **3104**: Section of fabric part of overlapped lower end within body **311** of three-fold tie **3105**: Section of fabric part **3106** of overlapped upper end folded inward within body **311** of three-fold tie **3106**: Fabric part of overlapped upper end within body **311** of three-fold tie **3107**: Fabric part of overlapped upper end folded inward within body **311** of three-fold tie **700**: Pattern of seven-fold tie **710**: Blade portion of seven-fold tie **711**: Body of seven-fold tie **712**: Tail portion of seven-fold tie **7000**: Blade part fabric of seven-fold tie **7001**: Body part fabric of seven-fold tie **7002**: Tail part fabric of seven-fold tie

DETAILED DESCRIPTION OF THE INVENTION

Best Mode for Carrying Out the Invention

- (21) Prepare fabric and a pattern **100** of invented tie to produce a tie.
- (22) After the preparing step, cut the fabric to fit the pattern **100**.
- (23) After the cutting step, add a lining to blade part fabric **1000** and tail part fabric **1002**.
- (24) After the adding step, fold the cut fabric once by a gatefold as shown in FIG. **13**. Fold only the body part fabric **1001** in one part of the tie, and fold not only the body part fabric **1001** but also the blade part fabric **1000** and the tail part fabric **1002** for finishing of the blade portion **110** and the tail portion **112** in the other part of the tie.
- (25) After the folding step, fold the entire fabric once more by a gatefold so that both ends overlap.
- (26) After the folding step, sew left and right panels formed by folding the fabric by a gatefold with a long single thread to fix them.
- (27) After the sewing step, fix a blade portion **110** and a tail portion **112** using a bar tack.
- (28) After the fixing step, attach a keeper loop, brand label, care label, etc. to the tie according to one's preferences.

Mode for Carrying Out the Invention

- (29) Prepare fabric and a pattern **100** of invented tie to produce a tie.
- (30) After the preparing step, cut the fabric to fit the pattern **100**.
- (31) After the cutting step, roll up and sew edges of blade part fabric **1000** and tail part fabric **1002**.
- (32) After the rolling up and sewing step, fold the cut fabric once by a gatefold as shown in FIG. **13**. Fold only the body part fabric **1001** in one part of the tie, and fold not only the body part fabric **1001** but also the blade part fabric **1000** and the tail part fabric **1002** for finishing of the blade portion **110** and the tail portion **112** in the other part of the tie.
- (33) After the folding step, fold the entire fabric once more by a gatefold so that both ends overlap.
- (34) After the folding step, sew left and right panels formed by folding the fabric by a gatefold with a long single thread to fix them.
- (35) After the sewing step, fix a blade portion **110** and a tail portion **112** using a bar tack.
- (36) After the fixing step, attach a keeper loop, brand label, care label, etc. to the tie according to one's preferences.

(37) Ties are a favorite product for many people around the world. According to Euromonitor, the US tie market is projected to hit \$758.5 (million) and \$769.0 (million) in 2022 and 2023, respectively. In addition, since the present invention is invented based on current technology, it may be produced right away. Based on the two factors mentioned above, the present invention is industrially applicable.

Claims

1. A method of manufacturing a three-fold tie, the method comprising: forming one continuous fabric piece comprising: a body part at a middle portion of the continuous fabric piece; a head part having a tapered end at a first end portion of the middle portion with a first step difference having a width narrower than a width of the middle portion; and a tail part having a tapered end at a second end portion of the middle portion with a second step difference having a width narrower than the width of the middle portion, wherein the body part is divided into seven panels by six longitudinal folding lines consisting of a first, second, third, fourth, fifth, and sixth folding lines, the head part includes only the third, fourth, and fifth folding lines extending from the body part, and the tail part includes only the third, fourth, and fifth folding lines extending from the body part; performing a first gatefold on the one continuous fabric piece along the second and fifth folding lines such that outer ends of the continuous fabric piece are folded inwardly up to a longitudinal center region of the body part without overlapping, wherein, after the first gatefold is performed, the second folding line becomes a first outer edge of the one continuous fabric piece, and the fifth folding line becomes a second outer edge of the one continuous fabric piece as such the fifth folding line of the head, body, and tail parts is folded during the step of performing the first gatefold; and performing a second gatefold on the one continuous fabric piece along the third and fourth folding lines such that outer ends of the first gatefold are folded inwardly with overlapping, thereby forming a thickness suitable for making knots.
 2. The method of claim 1, wherein the first step difference forms one of a right angle, an acute angle, or an obtuse angle with respect to a longitudinal edge of the continuous fabric piece.
 3. The method of claim 1, wherein the second step difference forms one of a right angle, an acute angle, or an obtuse angle with respect to a longitudinal edge of the continuous fabric piece.
 4. The method of claim 1, further comprising sewing the overlapped portions formed by the second gatefold with a single thread.
-