

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396785
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Miller; Brock et al.

System of medical devices and method for pericardial puncture

Abstract

A system for pericardial puncture includes a medical device having an elongate shaft extending between a proximal end and a distal end, and having a distally facing electrode at the distal end of the shaft. An impedance meter is electrically connectable with the electrode for measuring an impedance associated with the electrode. A display is provided for displaying an indication of a position of the electrode. The indication of the position is based on of the impedance.

Inventors: Miller; Brock (Toronto, CA), Gravett; Matthew (Milton, CA), Fok; Kai-Lon (Mississauga, CA), Abou-Marie; Rund (Mississauga, CA)

Applicant: Boston Scientific Medical Device Limited (Ballybrit, IE)

Family ID: 1000008782708

Assignee: Boston Scientific Medical Device Limited (Galway, IE)

Appl. No.: 17/393499

Filed: August 04, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220047324 A1	Feb. 17, 2022

Related U.S. Application Data

us-provisional-application US 63064435 20200812

Publication Classification

Int. Cl.: A61B18/14 (20060101); A61B18/12 (20060101); A61B18/00 (20060101)

U.S. Cl.:

CPC **A61B18/1477** (20130101); **A61B18/1206** (20130101); A61B2018/00083 (20130101);
A61B2018/00351 (20130101); A61B2018/00755 (20130101)

Field of Classification Search

CPC: A61B (17/3478); A61B (18/1206); A61B (18/1477); A61B (18/1487); A61B
(2017/00247); A61B (2018/00083); A61B (2018/00351); A61B (2018/00363); A61B
(2018/00601); A61B (2018/00755); A61B (2018/00875); A61B (2090/065)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
175254	12/1875	Oberly	N/A	N/A
827626	12/1905	Gillet	N/A	N/A
848711	12/1906	Weaver	N/A	N/A
1072954	12/1912	Junn	N/A	N/A
1279654	12/1917	Charlesworth	N/A	N/A
1918094	12/1932	Geekas	N/A	N/A
1996986	12/1934	Weinberg	N/A	N/A
2021989	12/1934	De Master	N/A	N/A
2146636	12/1938	Lipchow	N/A	N/A
3429574	12/1968	Williams	N/A	N/A
3448739	12/1968	Stark et al.	N/A	N/A
3575415	12/1970	Fulp et al.	N/A	N/A
3595239	12/1970	Petersen	N/A	N/A
4129129	12/1977	Amrine	N/A	N/A
4244362	12/1980	Anderson	N/A	N/A
4401124	12/1982	Guess et al.	N/A	N/A
4639252	12/1986	Kelly et al.	N/A	N/A
4641649	12/1986	Walinsky et al.	N/A	N/A
4669467	12/1986	Willett et al.	N/A	N/A
4682596	12/1986	Bales et al.	N/A	N/A
4790311	12/1987	Ruiz	N/A	N/A
4790809	12/1987	Kuntz	N/A	N/A
4793350	12/1987	Mar et al.	N/A	N/A
4807620	12/1988	Strul et al.	N/A	N/A
4832048	12/1988	Cohen	N/A	N/A
4840622	12/1988	Hardy	N/A	N/A
4863441	12/1988	Lindsay et al.	N/A	N/A
4884567	12/1988	Elliott et al.	N/A	N/A
4892104	12/1989	Ito et al.	N/A	N/A
4896671	12/1989	Cunningham et al.	N/A	N/A
4928693	12/1989	Goodin et al.	N/A	N/A
4936281	12/1989	Stasz	N/A	N/A
4960410	12/1989	Pinchuk	N/A	N/A
4977897	12/1989	Hurwitz	N/A	N/A

4998933	12/1990	Eggers	606/41	A61B 18/1492
5006119	12/1990	Acker et al.	N/A	N/A
5019076	12/1990	Yamanashi et al.	N/A	N/A
5047026	12/1990	Rydell	N/A	N/A
5081997	12/1991	Bosley et al.	N/A	N/A
5098431	12/1991	Rydell	N/A	N/A
5112048	12/1991	Kienle	N/A	N/A
5154724	12/1991	Andrews	N/A	N/A
5201756	12/1992	Horzewski et al.	N/A	N/A
5209741	12/1992	Spaeth	N/A	N/A
5211183	12/1992	Wilson	N/A	N/A
5221256	12/1992	Mahurkar	N/A	N/A
5230349	12/1992	Langberg	N/A	N/A
5281216	12/1993	Klicek	N/A	N/A
5300068	12/1993	Rosar et al.	N/A	N/A
5300069	12/1993	Hunsberger et al.	N/A	N/A
5314418	12/1993	Takano et al.	N/A	N/A
5318525	12/1993	West et al.	N/A	N/A
5327905	12/1993	Avitall	N/A	N/A
5364393	12/1993	Auth et al.	N/A	N/A
5372596	12/1993	Klicek et al.	N/A	N/A
5380304	12/1994	Parker	N/A	N/A
5397304	12/1994	Truckai	N/A	N/A
5403338	12/1994	Milo	N/A	N/A
5423809	12/1994	Klicek	N/A	N/A
5425382	12/1994	Golden et al.	N/A	N/A
5490859	12/1995	Mische et al.	N/A	N/A
5497774	12/1995	Swartz et al.	N/A	N/A
5507751	12/1995	Goode et al.	N/A	N/A
5509411	12/1995	Littmann et al.	N/A	N/A
5514131	12/1995	Edwards	606/41	A61N 1/403
5540681	12/1995	Strul et al.	N/A	N/A
5545200	12/1995	West et al.	N/A	N/A
5555618	12/1995	Winkler	N/A	N/A
5571088	12/1995	Lennox et al.	N/A	N/A
5575766	12/1995	Swartz et al.	N/A	N/A
5575772	12/1995	Lennox	N/A	N/A
5599347	12/1996	Hart et al.	N/A	N/A
5605162	12/1996	Mirzaee et al.	N/A	N/A
5617878	12/1996	Taheri	N/A	N/A
5622169	12/1996	Golden et al.	N/A	N/A
5624430	12/1996	Eton et al.	N/A	N/A
5667488	12/1996	Lundquist et al.	N/A	N/A
5673695	12/1996	McGee et al.	N/A	N/A
5674208	12/1996	Berg et al.	N/A	N/A
5683366	12/1996	Eggers et al.	N/A	N/A
5720744	12/1997	Eggleston et al.	N/A	N/A
5741249	12/1997	Moss et al.	N/A	N/A
5766135	12/1997	Terwilliger	N/A	N/A
5779688	12/1997	Imran et al.	N/A	N/A

5810764	12/1997	Eggers et al.	N/A	N/A
5814028	12/1997	Swartz et al.	N/A	N/A
5830214	12/1997	Flom et al.	N/A	N/A
5836875	12/1997	Webster, Jr.	N/A	N/A
5849011	12/1997	Jones et al.	N/A	N/A
5851210	12/1997	Torossian	N/A	N/A
5885227	12/1998	Finlayson	N/A	N/A
5888201	12/1998	Stinson et al.	N/A	N/A
5893848	12/1998	Negus et al.	N/A	N/A
5893885	12/1998	Webster, Jr.	N/A	N/A
5904679	12/1998	Clayman	N/A	N/A
5916210	12/1998	Winston	N/A	N/A
5921957	12/1998	Killion et al.	N/A	N/A
5931818	12/1998	Werp et al.	N/A	N/A
5944023	12/1998	Johnson et al.	N/A	N/A
5951482	12/1998	Winston et al.	N/A	N/A
5957842	12/1998	Littmann et al.	N/A	N/A
5964757	12/1998	Ponzi	N/A	N/A
5967976	12/1998	Larsen et al.	N/A	N/A
5989276	12/1998	Houser et al.	N/A	N/A
6007555	12/1998	Devine	N/A	N/A
6009877	12/1999	Edwards	N/A	N/A
6013072	12/1999	Winston et al.	N/A	N/A
6017340	12/1999	Cassidy et al.	N/A	N/A
6018676	12/1999	Davis et al.	N/A	N/A
6030380	12/1999	Auth et al.	N/A	N/A
6032674	12/1999	Eggers et al.	N/A	N/A
6048340	12/1999	Miyagi	606/41	A61B 18/1492
6048349	12/1999	Winston et al.	N/A	N/A
6053870	12/1999	Fulton, III	N/A	N/A
6053904	12/1999	Scribner et al.	N/A	N/A
6056747	12/1999	Saadat et al.	N/A	N/A
6063093	12/1999	Winston et al.	N/A	N/A
6093185	12/1999	Ellis et al.	N/A	N/A
6106515	12/1999	Winston et al.	N/A	N/A
6106520	12/1999	Laufer et al.	N/A	N/A
6117131	12/1999	Taylor	N/A	N/A
6142992	12/1999	Cheng et al.	N/A	N/A
6146380	12/1999	Racz et al.	N/A	N/A
6155264	12/1999	Ressemann et al.	N/A	N/A
6156031	12/1999	Aita et al.	N/A	N/A
6171305	12/2000	Sherman	N/A	N/A
6179824	12/2000	Eggers et al.	N/A	N/A
6193676	12/2000	Winston et al.	N/A	N/A
6193715	12/2000	Wrublewski et al.	N/A	N/A
6210408	12/2000	Chandrasekaran et al.	N/A	N/A
6217575	12/2000	DeVore et al.	N/A	N/A
6221061	12/2000	Engelson et al.	N/A	N/A
6228076	12/2000	Winston et al.	N/A	N/A
6245054	12/2000	Fuimaono et al.	N/A	N/A

6267758	12/2000	Daw et al.	N/A	N/A
6283983	12/2000	Makower et al.	N/A	N/A
6292678	12/2000	Hall et al.	N/A	N/A
6293945	12/2000	Parins et al.	N/A	N/A
6296615	12/2000	Brockway et al.	N/A	N/A
6296636	12/2000	Cheng et al.	N/A	N/A
6302898	12/2000	Edwards et al.	N/A	N/A
6304769	12/2000	Arenson et al.	N/A	N/A
6315777	12/2000	Comben	N/A	N/A
6328699	12/2000	Eigler et al.	N/A	N/A
6360128	12/2001	Kordis et al.	N/A	N/A
6364877	12/2001	Goble et al.	N/A	N/A
6385472	12/2001	Hall et al.	N/A	N/A
6394976	12/2001	Winston et al.	N/A	N/A
6395002	12/2001	Ellman et al.	N/A	N/A
6419674	12/2001	Bowser et al.	N/A	N/A
6428551	12/2001	Hall et al.	N/A	N/A
6450989	12/2001	Dubrul et al.	N/A	N/A
6475214	12/2001	Moaddeb	N/A	N/A
6485485	12/2001	Winston et al.	N/A	N/A
6508754	12/2002	Liprie et al.	N/A	N/A
6524303	12/2002	Garibaldi	N/A	N/A
6530923	12/2002	Dubrul et al.	N/A	N/A
6554827	12/2002	Chandrasekaran et al.	N/A	N/A
6562031	12/2002	Chandrasekaran et al.	N/A	N/A
6562049	12/2002	Norlander et al.	N/A	N/A
6565562	12/2002	Shah	606/41	A61B 18/1492
6607529	12/2002	Jones et al.	N/A	N/A
6632222	12/2002	Edwards et al.	N/A	N/A
6639999	12/2002	Cookingham et al.	N/A	N/A
6650923	12/2002	Lesh et al.	N/A	N/A
6651672	12/2002	Roth	N/A	N/A
6662034	12/2002	Segner et al.	N/A	N/A
6663621	12/2002	Winston et al.	N/A	N/A
6702811	12/2003	Stewart et al.	N/A	N/A
6709444	12/2003	Makower	N/A	N/A
6723052	12/2003	Mills	N/A	N/A
6733511	12/2003	Hall et al.	N/A	N/A
6740103	12/2003	Hall et al.	N/A	N/A
6752800	12/2003	Winston et al.	N/A	N/A
6755816	12/2003	Ritter et al.	N/A	N/A
6811544	12/2003	Schaer	N/A	N/A
6814733	12/2003	Schwartz et al.	N/A	N/A
6820614	12/2003	Bonutti	N/A	N/A
6834201	12/2003	Gillies et al.	N/A	N/A
6842639	12/2004	Winston et al.	N/A	N/A
6852109	12/2004	Winston et al.	N/A	N/A
6855143	12/2004	Davison et al.	N/A	N/A
6860856	12/2004	Ward et al.	N/A	N/A
6869431	12/2004	Maguire et al.	N/A	N/A

6911026	12/2004	Hall et al.	N/A	N/A
6951554	12/2004	Johansen et al.	N/A	N/A
6951555	12/2004	Suresh et al.	N/A	N/A
6955675	12/2004	Jain	N/A	N/A
6970732	12/2004	Winston et al.	N/A	N/A
6980843	12/2004	Eng et al.	N/A	N/A
7029470	12/2005	Francischelli et al.	N/A	N/A
7056294	12/2005	Khairkhahan et al.	N/A	N/A
7083566	12/2005	Tornes et al.	N/A	N/A
7112197	12/2005	Hartley et al.	N/A	N/A
7335197	12/2007	Sage et al.	N/A	N/A
7618430	12/2008	Scheib	N/A	N/A
7651492	12/2009	Wham	N/A	N/A
7666203	12/2009	Chanduszko et al.	N/A	N/A
7678081	12/2009	Whiting et al.	N/A	N/A
7682360	12/2009	Guerra	N/A	N/A
7828796	12/2009	Wong et al.	N/A	N/A
7896872	12/2010	Finch	606/41	A61B 18/1482
7900928	12/2010	Held et al.	N/A	N/A
8192425	12/2011	Mirza et al.	N/A	N/A
8257323	12/2011	Joseph et al.	N/A	N/A
8388549	12/2012	Paul et al.	N/A	N/A
8500697	12/2012	Kurth et al.	N/A	N/A
9179932	12/2014	Davies	N/A	A61B 17/3478
9504398	12/2015	Krishnan	N/A	A61B 5/1076
11339579	12/2021	Stearns	N/A	N/A
2001/0012934	12/2000	Chandrasekaran et al.	N/A	N/A
2001/0021867	12/2000	Kordis et al.	N/A	N/A
2002/0019644	12/2001	Hastings et al.	N/A	N/A
2002/0022781	12/2001	McIntire et al.	N/A	N/A
2002/0022836	12/2001	Goble et al.	N/A	N/A
2002/0035361	12/2001	Houser et al.	N/A	N/A
2002/0087153	12/2001	Roschak et al.	N/A	N/A
2002/0087156	12/2001	Maguire et al.	N/A	N/A
2002/0111618	12/2001	Stewart et al.	N/A	N/A
2002/0123749	12/2001	Jain	N/A	N/A
2002/0147485	12/2001	Mamo et al.	N/A	N/A
2002/0169377	12/2001	Khairkhahan et al.	N/A	N/A
2002/0188302	12/2001	Berg et al.	N/A	N/A
2002/0198521	12/2001	Maguire	N/A	N/A
2003/0032929	12/2002	McGuckin	N/A	N/A
2003/0040742	12/2002	Underwood et al.	N/A	N/A
2003/0144658	12/2002	Schwartz et al.	N/A	N/A
2003/0158480	12/2002	Tornes et al.	N/A	N/A
2003/0163153	12/2002	Scheib	N/A	N/A
2003/0225392	12/2002	McMichael et al.	N/A	N/A
2004/0015162	12/2003	McGaffigan	N/A	N/A
2004/0024396	12/2003	Eggers	N/A	N/A
2004/0030328	12/2003	Eggers et al.	N/A	N/A
2004/0044350	12/2003	Martin et al.	N/A	N/A

2004/0073243	12/2003	Sepetka et al.	N/A	N/A
2004/0077948	12/2003	Violante et al.	N/A	N/A
2004/0116851	12/2003	Johansen et al.	N/A	N/A
2004/0127963	12/2003	Uchida et al.	N/A	N/A
2004/0133113	12/2003	Krishnan	N/A	N/A
2004/0133130	12/2003	Ferry et al.	N/A	N/A
2004/0143256	12/2003	Bednarek	N/A	N/A
2004/0147950	12/2003	Mueller et al.	N/A	N/A
2004/0181213	12/2003	Gondo	N/A	N/A
2004/0230188	12/2003	Cioanta et al.	N/A	N/A
2005/0004585	12/2004	Hall et al.	N/A	N/A
2005/0010208	12/2004	Winston et al.	N/A	N/A
2005/0049628	12/2004	Schweikert et al.	N/A	N/A
2005/0059966	12/2004	McClurken et al.	N/A	N/A
2005/0065507	12/2004	Hartley et al.	N/A	N/A
2005/0085806	12/2004	Auge et al.	N/A	N/A
2005/0096529	12/2004	Cooper et al.	N/A	N/A
2005/0101984	12/2004	Chanduszko et al.	N/A	N/A
2005/0119556	12/2004	Gillies et al.	N/A	N/A
2005/0137527	12/2004	Kunin	N/A	N/A
2005/0149012	12/2004	Penny et al.	N/A	N/A
2005/0203504	12/2004	Wham et al.	N/A	N/A
2005/0203507	12/2004	Truckai et al.	N/A	N/A
2005/0261607	12/2004	Johansen et al.	N/A	N/A
2005/0288631	12/2004	Lewis et al.	N/A	N/A
2006/0041253	12/2005	Newton et al.	N/A	N/A
2006/0074398	12/2005	Whiting et al.	N/A	N/A
2006/0079769	12/2005	Whiting et al.	N/A	N/A
2006/0079787	12/2005	Whiting et al.	N/A	N/A
2006/0079884	12/2005	Manzo et al.	N/A	N/A
2006/0085054	12/2005	Zikorus et al.	N/A	N/A
2006/0089638	12/2005	Carmel et al.	N/A	N/A
2006/0106375	12/2005	Werneth et al.	N/A	N/A
2006/0135962	12/2005	Kick et al.	N/A	N/A
2006/0142756	12/2005	Davies et al.	N/A	N/A
2006/0189972	12/2005	Grossman	N/A	N/A
2006/0241586	12/2005	Wilk	N/A	N/A
2006/0247672	12/2005	Vidlund et al.	N/A	N/A
2006/0264927	12/2005	Ryan	N/A	N/A
2006/0276710	12/2005	Krishnan	N/A	N/A
2007/0060879	12/2006	Weitzner et al.	N/A	N/A
2007/0066975	12/2006	Wong et al.	N/A	N/A
2007/0118099	12/2006	Trout, III	N/A	N/A
2007/0123964	12/2006	Davies et al.	N/A	N/A
2007/0167775	12/2006	Kochavi et al.	N/A	N/A
2007/0208256	12/2006	Marilla	N/A	N/A
2007/0225681	12/2006	House	N/A	N/A
2007/0270791	12/2006	Wang et al.	N/A	N/A
2008/0039865	12/2007	Shaher et al.	N/A	N/A
2008/0042360	12/2007	Veikley	N/A	N/A

2008/0086120	12/2007	Mirza et al.	N/A	N/A
2008/0097213	12/2007	Carlson et al.	N/A	N/A
2008/0108987	12/2007	Bruszewski et al.	N/A	N/A
2008/0146918	12/2007	Magnin et al.	N/A	N/A
2008/0171934	12/2007	Greenan et al.	N/A	N/A
2008/0208121	12/2007	Youssef et al.	N/A	N/A
2008/0275439	12/2007	Francischelli et al.	N/A	N/A
2009/0105742	12/2008	Kurth et al.	N/A	N/A
2009/0138009	12/2008	Viswanathan et al.	N/A	N/A
2009/0163850	12/2008	Betts et al.	N/A	N/A
2009/0177114	12/2008	Chin et al.	N/A	N/A
2009/0264977	12/2008	Bruszewski et al.	N/A	N/A
2010/0087789	12/2009	Leeflang et al.	N/A	N/A
2010/0125282	12/2009	Machek et al.	N/A	N/A
2010/0168684	12/2009	Ryan	N/A	N/A
2010/0179632	12/2009	Bruszewski et al.	N/A	N/A
2010/0191142	12/2009	Paul et al.	N/A	N/A
2010/0194047	12/2009	Sauerwine	N/A	N/A
2011/0046619	12/2010	Ducharme	N/A	N/A
2011/0152716	12/2010	Chudzik et al.	N/A	N/A
2011/0160592	12/2010	Mitchell	N/A	N/A
2011/0190763	12/2010	Urban et al.	N/A	N/A
2012/0232546	12/2011	Mirza et al.	N/A	N/A
2012/0265055	12/2011	Melsheimer et al.	N/A	N/A
2012/0330156	12/2011	Brown et al.	N/A	N/A
2013/0184551	12/2012	Paganelli et al.	N/A	N/A
2013/0184735	12/2012	Fischell et al.	N/A	N/A
2013/0282084	12/2012	Mathur et al.	N/A	N/A
2014/0100561	12/2013	Biadillah	606/33	A61B 18/1492
2014/0206987	12/2013	Urbanski et al.	N/A	N/A
2014/0296769	12/2013	Hyde et al.	N/A	N/A
2016/0058504	12/2015	Davies	600/424	A61B 8/4494
2016/0220741	12/2015	Garrison et al.	N/A	N/A
2019/0021763	12/2018	Zhou et al.	N/A	N/A
2019/0247035	12/2018	Gittard et al.	N/A	N/A

Primary Examiner: Peffley; Michael F

Attorney, Agent or Firm: Nelson Mullins Riley & Scarborough LLP

Background/Summary

FIELD

(1) This document relates to medical devices. More specifically, this document relates to systems of medical devices that can be used in pericardial puncture, and related methods.

SUMMARY

(2) The following summary is intended to introduce the reader to various aspects of the detailed description, but not to define or delimit any invention.

- (3) Systems for pericardial puncture are disclosed. According to some aspects, a system for pericardial puncture includes a medical device having an elongate shaft extending between a proximal end and a distal end, and having an electrode at the distal end of the shaft. An impedance meter is electrically connectable with the electrode for measuring an impedance associated with the electrode. A display is provided for displaying an indication of a position of the medical device. The indication of the position is based on of the impedance.
- (4) In some examples, the indication of the position of the medical device is an indication of whether the medical device is in contact with a target tissue.
- (5) In some examples, the medical device is an introducer and the shaft has a lumen extending therethrough from the proximal end to the distal end. The shaft can include a metallic tube and an electrically insulative sheathing on the tube. The electrode can include an electrically exposed section of the tube. The shaft can include an electrical conductor extending proximally from the electrode for electrically connecting the electrode to the impedance meter.
- (6) In some examples, the system further includes a puncture device advanceable through the lumen from the proximal end to the distal end. The puncture device can be a radiofrequency puncture device and the system can further include a radiofrequency generator electrically connectable with the electrode for delivering radiofrequency energy to the electrode.
- (7) In some examples, the medical device is a puncture device. The system can further include a radiofrequency generator electrically connectable with the electrode for delivering radiofrequency energy from the electrode to puncture tissue. Alternatively, the puncture device can include a sharp tip.
- (8) Methods for pericardial puncture are also disclosed. According to some aspects, a method for pericardial puncture includes: a. advancing an introducer towards a pericardium; b. advancing a puncture device through the introducer towards the pericardium; c. puncturing the pericardium with the puncture device; and d. during at least one of step a., step b., and step c., measuring an impedance to assess a position of the introducer and/or a position of the puncture device.
- (9) In some examples, step d. is carried out during step a., and the impedance is an impedance associated with an electrode at a distal end of the introducer. In step d., the position of the distal end of the introducer can be assessed. Step d. can include determining whether the distal end of the introducer is in contact with the pericardium.
- (10) In some examples, step d. is carried out during step c., and the impedance is an impedance associated with a puncturing tip of the puncture device. In step d., the position of the puncturing tip of the puncture device can be assessed. Step d. can include determining whether the puncturing tip has punctured the pericardium.
- (11) In some examples, the method further includes: e. displaying an indication of the position of the introducer and/or the position of the puncture device. Step e. can include displaying an indication of whether the introducer has contacted the pericardium. Step e. can include displaying an indication of whether the puncture device has punctured the pericardium.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The accompanying drawings are for illustrating examples of articles, methods, and apparatuses of the present disclosure and are not intended to be limiting. In the drawings:
- (2) FIG. 1 is a perspective view of an example system of medical devices in an assembled state;
- (3) FIG. 2 is a perspective view of the puncture device and introducer of the system of FIG. 1, in an unassembled state.
- (4) FIG. 3 is a cross-section taken along line 3-3 in FIG. 2;
- (5) FIG. 4 is an end view of the introducer of FIG. 2;

(6) FIG. 5 is a schematic drawing showing a step of a method for pericardial puncture; and
(7) FIG. 6 is a schematic drawing showing a step subsequent to that of FIG. 5.

DETAILED DESCRIPTION

(8) Various apparatuses or processes or compositions will be described below to provide an example of an embodiment of the claimed subject matter. No example described below limits any claim and any claim may cover processes or apparatuses or compositions that differ from those described below. The claims are not limited to apparatuses or processes or compositions having all of the features of any one apparatus or process or composition described below or to features common to multiple or all of the apparatuses or processes or compositions described below. It is possible that an apparatus or process or composition described below is not an embodiment of any exclusive right granted by issuance of this patent application. Any subject matter described below and for which an exclusive right is not granted by issuance of this patent application may be the subject matter of another protective instrument, for example, a continuing patent application, and the applicants, inventors or owners do not intend to abandon, disclaim or dedicate to the public any such subject matter by its disclosure in this document.

(9) Generally disclosed herein is a system that can be used in pericardial puncture procedures. The system is configured to provide an indication of a position of a medical device of the system, and more particularly, to provide an indication that a medical device of the system is in contact with a target tissue (e.g. the pericardium of the heart) or has punctured the target tissue. For example, the system can include an introducer that is percutaneously advanced towards the heart, and the system can provide an indication of whether the distal end of the introducer is in contact with the heart (and thus advancement can be stopped). In order to provide an indication of the position of the medical device, the medical device can include an electrode that is positioned to contact or approach the heart. The system can further include an impedance meter for measuring an impedance associated with the electrode (i.e. for measuring the impedance of an electrical circuit of which the electrode is a part). As the medical device is advanced towards the heart, the impedance can be monitored. When the electrode contacts or approaches the heart, the impedance will change, and this change can provide an indication that the medical device is in contact with the heart. The system can further include a display connected to the impedance meter for displaying an indication of the position of the introducer. For example, based on the impedance measured by the impedance meter, the display can be a visual display that displays text or symbols to indicate that the medical device is in contact with the heart, or an auditory display that generates a sound to indicate that the medical device is in contact with the heart. In an alternative example, the system can include a puncture device that is advanced towards the heart through an introducer and then is used to puncture the pericardium, and the system can provide an indication of whether the distal end of the puncture device is in contact with the heart or whether the distal end of the puncture device has passed through the pericardium (and thus advancement can be stopped).

(10) Referring now to FIG. 1, an example system **100** of medical devices is shown. The system **100** generally includes a pair of medical devices, namely a puncture device **102** and an introducer **104**. The puncture device **102** is receivable in and advanceable through the introducer **104**. The introducer **104** can serve to atraumatically guide the puncture device **102** towards a target location in a patient's body (e.g. the heart), and the puncture device **102** can then puncture a target tissue at the target location (e.g. puncture the pericardium). As will be described in further detail below, the introducer **104** includes an electrode **106**, and the system further includes an impedance meter **108** (shown in dotted line in FIG. 1) that is electrically connectable with the electrode **106** for measuring an impedance associated with the electrode **106**. The impedance meter **108** can be any device that measures impedance, for example an ohm-meter or an LCR meter. The system **100** further includes a display **110** for displaying an indication of a position of the introducer **104** based on of the impedance measured by the impedance meter **108**. In the example shown, the impedance meter **108** and display **110** are part of a single unit **112** (e.g. a single handheld or desktop unit).

(11) Referring now to FIG. 2, in the example shown, the puncture device **102** is a mechanical puncture device, and includes elongate shaft **114** (also referred to herein as a “puncture device shaft”) extending between a proximal end **116** (also referred to herein as a “puncture device proximal end”) and a distal end **118** (also referred to herein as a “puncture device distal end”). A puncturing tip **120** is at the distal end, for puncturing tissue. In the example shown, the puncturing tip **120** is a sharp tip. The sharp tip can be, for example, beveled, pyramidal, or conical (as shown). A hub **122** (also referred to herein as a “puncture device hub”) is at the proximal end **116**, for handling and manipulating the puncture device **102**.

(12) In alternative examples, the puncture device can be a radiofrequency (RF) puncture device. In such examples, the puncturing tip can include an RF puncture electrode, and the system can include an RF generator to which the RF puncture electrode is electrically connectable for the delivery of RF energy to the RF puncture electrode. In such examples, the distal end of the puncture device can be blunt.

(13) Referring still to FIG. 2, in the example shown, the introducer **104** includes elongate shaft **124** (also referred to herein as an “introducer shaft”) extending between a proximal end **126** (shown in FIG. 3, and also referred to herein as an “introducer proximal end”) and a distal end **128** (also referred to herein as an “introducer distal end”). The distal end **128** of the shaft **104** is generally blunt, in order to avoid damaging tissue. A hub **130** (also referred to herein as an “introducer hub”) is at the proximal end **126** of the shaft **124**, for handling and manipulating the introducer **104**.

(14) Referring to FIGS. 3 and 4, the introducer **104** includes a lumen **132** extending therethrough, from the proximal end **126** of the shaft **124** to the distal end **128** of the shaft **124**. The puncture device **102** (not shown in FIGS. 3 and 4) is advanceable through the lumen **132**, from the proximal end **126** of the shaft **124** to the distal end **128** of the shaft **124**, to position the puncturing tip **120** of the puncture device **102** proud of the distal end **128** of the shaft **124**.

(15) Referring still to FIGS. 3 and 4, as mentioned above, the introducer includes an electrode **106**, which is at the distal end **128** of the shaft **124** and is distally facing. More specifically, in the example shown, the shaft **124** includes an electrically conductive tube **134** (e.g. a steel tube or other metallic tube), and an electrically insulative sheathing **136** (e.g. a high-density polyethylene sheathing or other polymeric sheathing) on the tube **134**. At the distal end **128**, the tube **134** is electrically exposed, and the electrically exposed section of the tube **134** forms the electrode **106**. The remainder of the tube **134** provides an electrical conductor that extends proximally from the electrode **106**, for electrically connecting the electrode **106** to the impedance meter **108**, via an insulated wire **138**.

(16) In alternative examples, the electrode can be of another configuration. For example, the electrode can be a standalone metallic element at or near the distal end of the shaft, and a wire or other electrical conductor can extend proximally from the electrode for connecting the electrode to the impedance meter.

(17) Referring now to FIGS. 5 and 6, in use, the introducer **104** can be advanced percutaneously towards the pericardium **140** of the heart. For example, the introducer **104** can be advanced via the subxiphoid approach, with the puncture device (not shown in FIGS. 5 and 6) shrouded within the lumen **132** (not visible in FIGS. 5 and 6) in order to prevent tissue coring, or extending slightly proud of the introducer to facilitate passage through adipose tissue. As the introducer **104** is advanced, the impedance associated with the electrode **106** (i.e. the impedance of an electrical circuit of which the electrode **106** is a part) can be measured by the impedance meter **108**, to assess the position of the introducer **104**. More specifically, referring first to FIG. 5, as the introducer **104** is advanced, the impedance meter **108** can continuously measure the impedance associated with the electrode **106**. When the electrode **106** (not visible in FIG. 6) contacts the pericardium **140** of the heart, as shown in FIG. 6, the impedance will change, and this change can be used as an indication of the position of the electrode **106** relative to the pericardium, which can in turn be used as an indication of the position of the distal end **128** of the introducer **104**. As the introducer **104** is

advanced, the impedance meter **108** can communicate with the display **110**, and based on the impedance, the display **110** can display an indication of the position of the introducer **104**. For example, as shown in FIGS. **5** and **6**, the display **110** can display an indication of whether or not the electrode **106** is in contact with the pericardium **140** of the heart. This can be done by displaying text, or by a change in color, or by illumination or a light, or by the emission of a sound. Alternatively, the display **110** can display raw impedance measurements, which can then be interpreted by a user in order to determine whether or not the electrode **106** is in contact with the pericardium **140** of the heart.

(18) When the display **110** indicates that the introducer **104** is in contact with the heart, the method can proceed. That is, the puncture device **102** can be advanced out of the lumen **132**, to puncture the pericardium.

(19) In an alternative example (not shown), the electrode can be on the puncture device. For example, in the case of a mechanical puncture device, the electrode can be part of the puncturing tip. In the case of an RF puncture device, the RF electrode can also serve as the electrode for impedance measurement. The system can then measure impedance to assess the position of the puncture device. More specifically, as the puncture device passes through the pericardium, the impedance associated with the electrode will change and can be measured to assess the position of the puncturing tip, to determine whether the puncturing tip has punctured the pericardium. The display can then display an indication of whether the puncture device has punctured the pericardium.

(20) As mentioned above, in the example shown, the impedance meter and display are part of a single unit. In alternative examples, the impedance meter and display may be provided in separate units. For example, the impedance meter can be built into the hub of the introducer, and the display can be provided as a standalone display.

(21) In any of the above examples, the puncture device and/or the introducer can include one or more radiopaque markers, to facilitate viewing under fluoroscopy.

(22) While the above description provides examples of one or more processes or apparatuses or compositions, it will be appreciated that other processes or apparatuses or compositions may be within the scope of the accompanying claims.

(23) To the extent any amendments, characterizations, or other assertions previously made (in this or in any related patent applications or patents, including any parent, sibling, or child) with respect to any art, prior or otherwise, could be construed as a disclaimer of any subject matter supported by the present disclosure of this application, Applicant hereby rescinds and retracts such disclaimer. Applicant also respectfully submits that any prior art previously considered in any related patent applications or patents, including any parent, sibling, or child, may need to be re-visited.

Claims

1. A system for pericardial puncture comprising: a medical assembly comprising, an introducer having an elongate shaft extending between a proximal end and a distal end and defining a single lumen therethrough, the elongate shaft having a longitudinal axis extending between the proximal end and the distal end, the elongate shaft comprising: an electrically conductive metallic tube; a polymeric, electrically insulative sheathing on the metallic tube, the insulative sheathing having a tapered portion surrounding a distal portion of the electrically conductive metallic tube; the introducer having a distally facing electrode at the distal end of the shaft, the electrode comprising a distal end portion of the metallic tube that is electrically exposed through the polymeric insulative sheathing, the electrode encircling the lumen and being coaxial with the longitudinal axis of the elongate shaft, and an elongated puncture device disposed within the lumen and extendable from the distal end of the shaft; an impedance meter electrically connectable with the electrode for measuring an impedance associated with the electrode; and a display for displaying an indication of

a position of the medical assembly device, wherein the indication of the position is based on of the impedance.

2. The system of claim 1, wherein the indication of the position of the medical assembly is an indication of whether the medical is in contact with a target tissue.
 3. The system of claim 1, wherein the shaft comprises an electrical conductor extending proximally from the electrode for electrically connecting the electrode to the impedance meter.
 4. The system of claim 1, wherein the puncture device is a radiofrequency puncture device; and the system further comprises a radiofrequency generator electrically connectable with the electrode for delivering radiofrequency energy to the electrode.
 5. The system of claim 1, wherein the puncture device comprises a sharp tip.
 6. The system of claim 1, wherein the indication of a position of the medical assembly device includes an indication of whether or not the electrode is in contact with a pericardium of the heart.
 7. The system of claim 6, wherein the indication of whether or not the electrode is in contact with the pericardium of the heart is displayed text.
 8. A method for pericardial puncture, comprising: a. advancing an introducer towards a pericardium, the introducer having a distal end with a distalmost tip, the introducer having an elongate shaft, the elongate shaft having a longitudinal axis extending between the proximal end and the distal end, the elongate shaft comprising: an electrically conductive metallic tube; a polymeric, electrically insulative sheathing on the metallic tube, the insulative sheathing having a tapered portion surrounding a distal portion of the electrically conductive metallic tube; the introducer including a distally facing electrode at the distalmost tip, the electrode comprising a distal end portion of the metallic tube that is electrically exposed through the polymeric insulative sheathing, and the electrode being coaxial with the longitudinal axis of the elongate shaft; b. advancing a puncture device through the introducer towards the pericardium, the puncture device including a puncturing tip having a puncturing tip electrode; c. puncturing the pericardium with the puncture device; and d. during at least one of step a., step b., and step c., measuring an impedance to assess a position of the introducer and a position of the puncture device, the impedance associated with the distally facing electrode and the puncturing tip electrode.
 9. The method of claim 8, wherein in step d., the position of the distal end of the introducer is assessed.
 10. The method of claim 8, wherein step d. comprises determining whether the distal end of the introducer is in contact with the pericardium.
 11. The method of claim 8, wherein step d. comprises determining whether the puncturing tip has punctured the pericardium.
 12. The method of claim 8, further comprising: e. displaying an indication of the position of the introducer and/or the position of the puncture device.
 13. The method of claim 12, wherein step e. comprises displaying an indication of whether the introducer has contacted the pericardium, wherein the indication includes text, illumination, or light.
 14. The method of claim 12, wherein step e. comprises displaying an indication of whether the puncture device has punctured the pericardium, wherein the indication includes text, illumination, or light.
-