

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396846
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Konno; Mark A.

Methods of implanting a prosthetic heart valve within another

Abstract

The invention is a cardiac implant, and associated methods therefore, configured to repair and/or replace a native heart valve, and having a support frame configured to be reshaped into an expanded/changed form in order to receive and/or support an expandable prosthetic heart valve therein. The implant may be configured to have a generally rigid and/or expansion-resistant configuration when initially implanted to replace/repair a native valve (or other prosthetic heart valve), but to assume a generally non-rigid and/or expanded/expandable form when subjected to an outward force such as that provided by a dilation balloon. The implant may be configured to have a generally D-shaped configuration when initially implanted, but to assume a generally circular form when subjected to an outward force such as that provided by a dilation balloon.

Inventors:	Konno; Mark A. (Laguna Beach, CA)
Applicant:	Edwards Lifesciences Corporation (Irvine, CA)
Family ID:	1000008782740
Assignee:	EDWARDS LIFESCIENCES CORPORATION (Irvine, CA)
Appl. No.:	17/410974
Filed:	August 24, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20210378821 A1	Dec. 09, 2021

Related U.S. Application Data

continuation parent-doc US 16600362 20191011 US 11103348 20210831 child-doc US 17410974
continuation parent-doc US 14038357 20130926 US 9636219 20170502 child-doc US 15498213

Publication Classification

Int. Cl.: A61F2/24 (20060101); A61F2/958 (20130101)

U.S. Cl.:

CPC A61F2/2418 (20130101); A61F2/2409 (20130101); A61F2/2412 (20130101);
A61F2/2433 (20130101); A61F2/2427 (20130101); A61F2/958 (20130101);
A61F2220/0075 (20130101); A61F2230/0034 (20130101); A61F2250/001 (20130101);
A61F2250/0071 (20130101)

Field of Classification Search

CPC: A61F (2/2409); A61F (2/2412); A61F (2/2418); A61F (2250/0082); A61F (2250/0098);
A61F (2250/006)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3656185	12/1971	Carpentier	N/A	N/A
4055861	12/1976	Carpentier et al.	N/A	N/A
4164046	12/1978	Cooley	N/A	N/A
4217665	12/1979	Bex et al.	N/A	N/A
4602911	12/1985	Ahmadi et al.	N/A	N/A
5041130	12/1990	Cosgrove et al.	N/A	N/A
5061277	12/1990	Carpentier et al.	N/A	N/A
5064431	12/1990	Gilbertson et al.	N/A	N/A
5104407	12/1991	Lam et al.	N/A	N/A
5201880	12/1992	Wright et al.	N/A	N/A
5258021	12/1992	Duran	N/A	N/A
5306296	12/1993	Wright et al.	N/A	N/A
5450860	12/1994	O'Connor	N/A	N/A
5496336	12/1995	Cosgrove et al.	N/A	N/A
5593435	12/1996	Carpentier et al.	N/A	N/A
5607471	12/1996	Seguin et al.	N/A	N/A
5674279	12/1996	Wright et al.	N/A	N/A
5776189	12/1997	Khalid	N/A	N/A
5824066	12/1997	Gross	N/A	N/A
5855602	12/1998	Angell	606/1	A61F 2/2427
5888240	12/1998	Carpentier et al.	N/A	N/A
5972030	12/1998	Garrison et al.	N/A	N/A
6102945	12/1999	Campbell	N/A	N/A
6143024	12/1999	Campbell et al.	N/A	N/A
6159240	12/1999	Sparer et al.	N/A	N/A
6183512	12/2000	Howanec, Jr. et al.	N/A	N/A

6187040	12/2000	Wright	N/A	N/A
6217610	12/2000	Carpentier et al.	N/A	N/A
6231602	12/2000	Carpentier et al.	N/A	N/A
6250308	12/2000	Cox	N/A	N/A
6258122	12/2000	Tweden et al.	N/A	N/A
6332893	12/2000	Mortier et al.	N/A	N/A
6348068	12/2001	Campbell et al.	N/A	N/A
6391054	12/2001	Carpentier et al.	N/A	N/A
6406493	12/2001	Tu et al.	N/A	N/A
6419696	12/2001	Ortiz et al.	N/A	N/A
6425916	12/2001	Garrison et al.	N/A	N/A
6602288	12/2002	Cosgrove et al.	N/A	N/A
6602289	12/2002	Colvin et al.	N/A	N/A
6619291	12/2002	Hlavka et al.	N/A	N/A
6709456	12/2003	Langberg et al.	N/A	N/A
6718985	12/2003	Hlavka et al.	N/A	N/A
6719786	12/2003	Ryan et al.	N/A	N/A
6726717	12/2003	Alfieri et al.	N/A	N/A
6764510	12/2003	Vidlund et al.	N/A	N/A
6797002	12/2003	Spence et al.	N/A	N/A
6800090	12/2003	Alferness et al.	N/A	N/A
6802860	12/2003	Cosgrove et al.	N/A	N/A
6805710	12/2003	Bolling et al.	N/A	N/A
6805711	12/2003	Quijano et al.	N/A	N/A
6858039	12/2004	McCarthy	N/A	N/A
6918917	12/2004	Nguyen et al.	N/A	N/A
6921407	12/2004	Nguyen et al.	N/A	N/A
6942694	12/2004	Liddicoat et al.	N/A	N/A
6955689	12/2004	Ryan et al.	N/A	N/A
6966924	12/2004	Holmberg	N/A	N/A
6986775	12/2005	Morales et al.	N/A	N/A
7101395	12/2005	Tremulis et al.	N/A	N/A
7118595	12/2005	Ryan et al.	N/A	N/A
7125421	12/2005	Tremulis et al.	N/A	N/A
7166126	12/2006	Spence et al.	N/A	N/A
7166127	12/2006	Spence et al.	N/A	N/A
7261732	12/2006	Justino	N/A	N/A
7276084	12/2006	Yang et al.	N/A	N/A
7294148	12/2006	McCarthy	N/A	N/A
7381218	12/2007	Schreck	N/A	N/A
7393360	12/2007	Spenser et al.	N/A	N/A
7399315	12/2007	Iobbi	N/A	N/A
7452376	12/2007	Lim et al.	N/A	N/A
7462191	12/2007	Spenser et al.	N/A	N/A
7470285	12/2007	Nugent et al.	N/A	N/A
7510575	12/2008	Spenser et al.	N/A	N/A
7524330	12/2008	Berrekouw	N/A	N/A
7534261	12/2008	Friedman	N/A	N/A
7556646	12/2008	Yang et al.	N/A	N/A
7585321	12/2008	Cribier	N/A	N/A

7625403	12/2008	Krivoruchko	N/A	N/A
7780723	12/2009	Taylor	N/A	N/A
7806927	12/2009	Styrc	N/A	N/A
7871436	12/2010	Ryan et al.	N/A	N/A
8226707	12/2011	White	N/A	N/A
8246677	12/2011	Ryan	N/A	N/A
8496700	12/2012	Edoga et al.	N/A	N/A
8500802	12/2012	Lane et al.	N/A	N/A
2001/0021874	12/2000	Carpentier et al.	N/A	N/A
2002/0062150	12/2001	Campbell et al.	N/A	N/A
2003/0033009	12/2002	Gabbay	N/A	N/A
2003/0040793	12/2002	Marquez	N/A	N/A
2003/0199971	12/2002	Tower et al.	N/A	N/A
2004/0193261	12/2003	Berrekouw	N/A	N/A
2004/0210305	12/2003	Shu et al.	N/A	N/A
2004/0249452	12/2003	Adams et al.	N/A	N/A
2004/0249453	12/2003	Cartledge et al.	N/A	N/A
2005/0096739	12/2004	Cao	N/A	N/A
2005/0131533	12/2004	Alfieri et al.	N/A	N/A
2005/0240200	12/2004	Bergheim	N/A	N/A
2005/0251251	12/2004	Cribier	N/A	N/A
2005/0256567	12/2004	Lim et al.	N/A	N/A
2005/0256568	12/2004	Lim et al.	N/A	N/A
2005/0267572	12/2004	Schoon et al.	N/A	N/A
2005/0278022	12/2004	Lim	N/A	N/A
2006/0015178	12/2005	Moaddeb et al.	N/A	N/A
2006/0015179	12/2005	Bulman-Fleming et al.	N/A	N/A
2006/0020336	12/2005	Liddicoat	N/A	N/A
2006/0025858	12/2005	Alameddine	N/A	N/A
2006/0030885	12/2005	Hyde	N/A	N/A
2006/0052867	12/2005	Revuelta et al.	N/A	N/A
2007/0016287	12/2006	Cartledge et al.	N/A	N/A
2007/0067029	12/2006	Gabbay	N/A	N/A
2007/0100441	12/2006	Kron et al.	N/A	N/A
2007/0142907	12/2006	Moaddeb et al.	N/A	N/A
2007/0162111	12/2006	Fukamachi et al.	N/A	N/A
2007/0244546	12/2006	Francis	N/A	N/A
2008/0027483	12/2007	Cartledge et al.	N/A	N/A
2008/0114452	12/2007	Gabbay	N/A	N/A
2008/0161910	12/2007	Revuelta et al.	N/A	N/A
2008/0161911	12/2007	Revuelta et al.	N/A	N/A
2008/0183273	12/2007	Mesana et al.	N/A	N/A
2008/0200980	12/2007	Robin et al.	N/A	N/A
2008/0208327	12/2007	Rowe	604/509	A61F 2/2427
2008/0208329	12/2007	Bishop et al.	N/A	N/A
2008/0215144	12/2007	Ryan et al.	N/A	N/A
2008/0228263	12/2007	Ryan	N/A	N/A
2008/0243246	12/2007	Ryan et al.	N/A	N/A
2008/0269878	12/2007	Iobbi	N/A	N/A
2008/0275549	12/2007	Rowe	N/A	N/A

2009/0005863	12/2008	Goetz et al.	N/A	N/A
2009/0082857	12/2008	Lashinski et al.	N/A	N/A
2009/0093876	12/2008	Nitzan et al.	N/A	N/A
2009/0192602	12/2008	Kuehn	N/A	N/A
2009/0192603	12/2008	Kuehn	N/A	N/A
2009/0192604	12/2008	Gloss	N/A	N/A
2009/0192606	12/2008	Gloss et al.	N/A	N/A
2009/0216322	12/2008	Le et al.	N/A	N/A
2009/0281609	12/2008	Benichou et al.	N/A	N/A
2010/0076548	12/2009	Konno	N/A	N/A
2010/0076549	12/2009	Keidar et al.	N/A	N/A
2011/0166636	12/2010	Rowe	N/A	N/A
2011/0178597	12/2010	Navia et al.	N/A	N/A
2011/0264207	12/2010	Bonhoeffer	623/2.18	A61F 2/2409

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
0338994	12/1988	EP	N/A
1034753	12/1999	EP	N/A
1755459	12/2006	EP	N/A
1804726	12/2006	EP	N/A
1958598	12/2007	EP	N/A
2009108355	12/2008	WO	N/A

Primary Examiner: Ganesan; Suba

Background/Summary

CROSS REFERENCE TO RELATED PATENT APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 16/600,362, filed Oct. 11, 2019, now U.S. Pat. No. 11,103,348, which is a divisional of U.S. application Ser. No. 15/498,213, filed Apr. 26, 2017, which is a continuation of U.S. application Ser. No. 14/038,357, filed Sep. 26, 2013, now U.S. Pat. No. 9,636,219, which is a continuation of U.S. application Ser. No. 12/234,559, filed Sep. 19, 2008, now U.S. Pat. No. 9,314,335, the entire disclosures all of which are incorporated herein by reference for all purposes. The present application is also related to U.S. patent application Ser. No. 12/234,580, filed Sep. 19, 2008, now U.S. Pat. No. 8,287,591, the entire disclosure which is incorporated herein by reference for all purposes.

FIELD OF THE INVENTION

(1) The present invention relates to prosthetic cardiac implants for heart valve replacement and/or repair, and more particularly to a prosthetic heart valve and a prosthetic annuloplasty ring configured to receive an expandable prosthetic heart valve therein.

BACKGROUND OF THE INVENTION

(2) In humans and other vertebrate animals, the heart is a hollow muscular organ having four pumping chambers separated by four heart valves: aortic, mitral (or bicuspid), tricuspid, and pulmonary. The valves open and close in response to a pressure gradient during each cardiac cycle of relaxation and contraction to control the flow of blood to a particular region of the heart and/or to blood vessels (pulmonary, aorta, etc.)

(3) These valves are comprised of a dense fibrous ring known as the annulus, and leaflets or cusps

attached to the annulus. For some valves, there is also a complex of chordae tendineae and papillary muscles securing the leaflets. The size of the leaflets or cusps is such that when the heart contracts the resulting increased blood pressure formed within heart chamber forces the leaflets open to allow flow from the heart chamber. As the pressure in the heart chamber subsides, the pressure in the subsequent chamber or blood vessel becomes dominant, and presses back against the leaflets. As a result, the leaflets or cusps come in apposition to each other, thereby closing the passage.

(4) Heart valve disease is a widespread condition in which one or more of the valves of the heart fails to function properly. Diseased heart valves may be categorized as either stenotic, wherein the valve does not open sufficiently to allow adequate forward flow of blood through the valve, and/or incompetent, wherein the valve does not close completely, causing excessive backward flow of blood through the valve when the valve is closed. Valve disease can be severely debilitating and even fatal if left untreated.

(5) Various surgical techniques may be used to replace or repair a diseased or damaged valve. In a traditional valve replacement operation, the damaged leaflets are typically excised and the annulus sculpted to receive a replacement prosthetic valve. In a traditional valve repair, surgeons insert a ring around the valve to bring the valves into contact with each other, a procedure known as “annuloplasty.”

(6) In many patients who suffer from dysfunction of the mitral and/or tricuspid valve(s) of the heart, surgical repair of the valve (i.e., “valvuloplasty”) is a desirable alternative to valve replacement. Remodeling of the valve annulus (i.e., “annuloplasty”) is central to many reconstructive valvuloplasty procedures. In 1968, Dr. Alain Carpentier published studies which demonstrated that such remodeling of the valve annulus might be accomplished by implantation of a prosthetic ring (i.e. “annuloplasty ring”) to stabilize the annulus and to correct or prevent valvular insufficiency that may result from defect dysfunction of the valve annulus. The annuloplasty ring is designed to support the functional changes that occur during the cardiac cycle: maintaining coaptation and valve integrity to prevent reverse flow while permitting good hemodynamics during forward flow. Annuloplasty procedures are performed not only to repair damaged or diseased annuli, but also in conjunction with other procedures, such as leaflet repair.

(7) The annuloplasty ring typically comprises an inner substrate of a metal such as stainless or titanium, or a flexible material such as silicone rubber or Dacron cordage, covered with a biocompatible fabric or cloth to allow the ring to be sutured to the heart tissue. Annuloplasty rings may be stiff or flexible, may be split or continuous, and may have a variety of shapes, including circular, D-shaped (including kidney-shaped), or C-shaped. Examples are seen in U.S. Pat. Nos. 4,042,979; 4,290,151; 4,489,446; 4,602,911; 5,041,130; 5,061,277; 5,104,407; 5,201,880; 5,258,021; 5,607,471; and 6,187,040, the contents of each of which is hereby incorporated by reference in its entirety.

(8) For some patients, however, the condition of the native heart valve requires complete replacement using a prosthetic heart valve. Prosthetic heart valves have been known for some time, and have been successfully implanted using traditional open-chest surgical approaches, minimally-invasive procedures, and so-called percutaneous methods.

(9) A prosthetic heart valve typically comprises a support structure (such as a ring and/or stent) with a valve assembly deployed therein. The support structure is often rigid, and can be formed of various biocompatible materials, including metals, plastics, ceramics, etc. Two primary types of “conventional” heart valve replacements or prostheses are known. One is a mechanical-type heart valve that uses a ball and cage arrangement or a pivoting mechanical closure supported by a base structure to provide unidirectional blood flow, such as shown in U.S. Pat. No. 6,143,025 to Stobie, et al. and U.S. Pat. No. 6,719,790 to Brendzel, et al., the entire disclosures of which are hereby expressly incorporated by reference. The other is a tissue-type or “bioprosthetic” valve having flexible leaflets supported by a base structure and projecting into the flow stream that function

much like those of a natural human heart valve and imitate their natural flexing action to coapt against each other and ensure one-way blood flow.

(10) In tissue-type valves, a whole xenograft valve (e.g., porcine) or a plurality of xenograft leaflets (e.g., bovine pericardium) can provide fluid occluding surfaces. Synthetic leaflets have been proposed, and thus the term “flexible leaflet valve” refers to both natural and artificial “tissue-type” valves. In a typical tissue-type valve, two or more flexible leaflets are mounted within a peripheral support structure that usually includes posts or commissures extending in the outflow direction to mimic natural fibrous commissures in the native annulus. Components of the valve are usually assembled with one or more biocompatible fabric (e.g., Dacron) coverings, and a fabric-covered sewing ring is provided on the inflow end of the peripheral support structure.

(11) In many bioprosthetic-type valves, a metallic or polymeric structure provides base support for the flexible leaflets, which extend therefrom. One such support is a “support frame,” sometimes called a “wireform” or “stent,” which has a plurality (typically three) of large radius cusps supporting the cusp region of the flexible leaflets (i.e., either a whole xenograft valve or three separate leaflets). The ends of each pair of adjacent cusps converge somewhat asymptotically to form upstanding commissures that terminate in tips, each extending in the opposite direction as the arcuate cusps and having a relatively smaller radius. The support frame typically describes a conical tube with the commissure tips at the small diameter end. This provides an undulating reference shape to which a fixed edge of each leaflet attaches (via components such as fabric and sutures) much like the natural fibrous skeleton in the aortic annulus. One example of the construction of a flexible leaflet valve is seen in U.S. Pat. No. 6,585,766 to Huynh, et al. (issued Jul. 1, 2003), in which the exploded view of FIG. 1 illustrates a fabric-covered wireform 54 and a fabric-covered support stent 56 on either side of a leaflet subassembly 52. The contents of U.S. Pat. No. 6,585,766 are hereby incorporated by reference in their entirety. Other examples of valve and related assemblies/systems are found in U.S. Pat. No. 7,137,184, which issued on Nov. 21, 2006, the contents of which are hereby incorporated by reference in their entirety.

(12) Sometimes the need for complete valve replacement may arise after a patient has already had an earlier valve replacement or repair using an annuloplasty ring for the same valve. For example, a native heart valve that was successfully repaired using an annuloplasty ring may suffer further damage years after the annuloplasty ring was implanted. Similarly, a prosthetic heart that was successfully implanted to replace a native valve may itself suffer damage and/or wear and tear many years after initially being implanted.

(13) Implanting a prosthetic heart valve into a patient with a previously-implanted prosthetic heart valve or annuloplasty ring typically involves additional steps from a similar procedure in a patient with no previously-implanted heart valve or annuloplasty ring. Implanting the prosthetic heart valve directly within a previously-implanted prosthetic heart valve is generally impractical, in part because the new prosthetic heart valve (including the support structure and valve assembly) will have to reside within the annulus of the previously-implanted heart valve, and traditional prosthetic heart valves are not configured to easily receive such a valve-within-a-valve implantation in a manner which provides secure seating for the new valve while also having a large enough annulus within the new valve to support proper blood flow therethrough. Implanting the prosthetic heart valve directly within a previously-implanted annuloplasty ring is generally impractical, largely because most prosthetic heart valves have a generally circular shape whereas most annuloplasty rings are generally non-circular (including “D” and dog-bone shapes). Implanting a prosthetic heart valve in a patient who previously had a prosthetic heart valve or annuloplasty ring generally requires the previously-implanted heart valve or annuloplasty ring to be removed during the same procedure in which the new prosthetic heart valve is implanted. In such cases, a surgeon can use a traditional surgical approach to install the prosthetic valve, which can involve the surgeon cutting out the previously-implanted heart valve or annuloplasty ring from the heart valve annulus, and then implanting the new prosthetic valve into the heart valve annulus.

(14) Percutaneous and minimally-invasive heart valve replacement has been developed recently, wherein a prosthetic heart valve is advanced percutaneously (e.g., via the femoral artery or other desired approaches) or via other approaches (i.e., minimally-invasive “keyhole” surgery, including approaches via the apex of the heart, etc.) into the heart valve annulus, and then expanded within the heart valve annulus. Various expandable valves are being tested, primarily that use balloon- or self-expanding stents as anchors. For the purpose of inclusivity, the entire field will be denoted herein as the delivery and implantation of expandable valves, regardless of whether the delivery method involves percutaneous, minimally-invasive, or other delivery methods. These valves typically include a scaffold or frame that expands radially outward into direct anchoring contact with the annulus, sometimes assisted with barbs. Examples of percutaneous heart valves and delivery systems and methods therefore are described in U.S. Pat. No. 5,411,552, issued May 2, 1995; U.S. Pat. No. 5,840,081, issued Nov. 24, 1998; U.S. Pat. No. 6,168,614, issued Jan. 2, 2001; and U.S. Pat. No. 6,582,462, issued Jun. 24, 2003; and also in U.S. patent application Ser. No. 11/280,062, filed Nov. 16, 2005; U.S. patent application Ser. No. 11/488,510, filed Jul. 18, 2006; and U.S. patent application Ser. No. 11/542,087, filed Oct. 2, 2006; the contents of each of which are hereby incorporated by reference in their entirety.

(15) Percutaneous heart valve replacement is often performed without cutting out the native heart valve, wherein the prosthetic heart valve is expanded in the native heart valve annulus and the native valve leaflets are pressed against the valve annulus walls by the expanded prosthetic heart valve. However, in cases where a previously-implanted prosthetic heart valve or annuloplasty ring is present, deploying a prosthetic heart valve within the native heart valve annulus may be impractical. The shape and structure of the previously-installed prosthetic heart valve or annuloplasty ring may interfere with the proper placement, deployment, and functioning of the new prosthetic heart valve.

(16) There is thus a need for a prosthetic heart valve which will properly replace a damaged heart valve, but will also enable a replacement expandable prosthetic heart valve to be deployed therein at a later time. There is also a need for an annuloplasty prosthesis and implantation device which will properly reshape/repair a damaged heart valve, but will also enable a prosthetic heart valve to be deployed therein at a later time. The current invention meets this need.

SUMMARY OF THE INVENTION

(17) The invention is a prosthetic heart valve and an annuloplasty ring configured to receive a prosthetic heart valve, such as a catheter-deployed (transcatheter) prosthetic heart valve, therein. In one embodiment, the prosthetic heart valve has a support structure which is generally resistant to expansion when deployed in the patient's native heart valve annulus to replace the native heart valve (or to replace another prosthetic heart valve), but is configured to transform to a generally expanded and/or expandable configuration in order to receive a prosthetic heart valve therein. In another embodiment, the annuloplasty ring has a generally non-circular shape when deployed in the patient's native heart valve to correct heart valve function, but is configured to assume a generally circular configuration when subjected to a dilation force such as that provided by a dilation balloon used to deploy a prosthetic valve. The annuloplasty ring or prosthetic heart valve of the invention can be deployed using various surgical techniques (e.g., traditional open-chest, minimally-invasive, percutaneous, etc.) to correct heart valve function, and the expandable prosthetic valve can be deployed within the same native valve annulus at a much later time. The annuloplasty ring is configured to accept and even improve deployment of the prosthetic valve within the native valve annulus. The transformation from expansion-resistant to expanded/expandable, and/or from generally non-circular shape to generally circular configuration, can be achieved by subjecting the heart valve or annuloplasty ring support structure to an outward force, such as a dilation force, which may be provided by a dilation balloon used to deploy a replacement prosthetic valve.

(18) The prosthetic heart valve structure may be generally rigid prior to dilation, and may be configured to become generally non-rigid, and even generally elastic, when subjected to an

outward force. The elasticity may assist in holding a percutaneously-introduced prosthetic valve within the current prosthetic valve structure.

(19) The prosthetic valve can be initially deployed in the patient's valve annulus using various surgical techniques (e.g., traditional open-chest, minimally-invasive, percutaneous, etc.) to correct heart valve function. If the heart valve function declines further after deployment of the prosthetic valve, a new replacement prosthetic valve can be deployed within the previously-deployed prosthetic valve without the need to excise the previously-deployed prosthetic valve. Deployment of the replacement prosthetic valve within the previously-deployed prosthetic valve can occur at a much later time from initial deployment of the previously-deployed prosthetic valve. The prosthetic valve of the current invention is configured to be deployed in a patient and, at a later time, to accept and even improve deployment of a replacement prosthetic valve within the same valve annulus.

(20) In one embodiment, the structure can include a core comprising a spring, a plastically deformable material (including breakable materials), etc. The core may be formed as a single piece (possibly with one or more weakened sections configured to fail when subjected to a sufficient force), or may be formed from several segments connected at seams. The core may form an inner lumen through which further attachment devices may be passed, such as elastic and/or inelastic cords.

(21) A prosthetic valve according to an embodiment of the invention may include a cover configured to hold the core together after it has been dilated. For example, where a core breaks into multiple pieces during dilation, the cover can serve to keep the pieces from separating from the prosthetic valve. The cover can also serve to hold the core and/or other portions of the support frame in a desired shape, and may have elastic properties.

(22) In an embodiment of the invention, the prosthetic valve is a stented bioprosthetic valve configured to expand and contract dynamically within the patient's annulus. The dynamic motion of the annulus can enable the valve opening to expand during periods of peak demand, and reduce the annular restriction to the increased flow. The expansion can also decrease leaflet stresses associated with potential higher gradients. The expansion can also permit later placement of an expandable prosthetic valve within the stented bioprosthetic valve.

(23) In an embodiment of the invention, a prosthetic valve has a support structure having a generally rigid and/or expansion-resistant portion including a core. The prosthetic valve may include plastically deformable materials configured to maintain the prosthetic valve support structure in the generally rigid and/or expansion-resistant shape for deployment. The plastically deformable materials may be configured to break or otherwise plastically deform and no longer maintain the support structure in the generally rigid and/or expansion-resistant configuration when subjected to a dilation force. The support structure may form a continuous loop, and may include elastically deformable material configured to provide tension about the continuous loop after the support structure has been dilated by a dilation balloon.

(24) A method for repairing a patient's heart function according to an embodiment of the invention can include: providing a prosthetic heart valve configured to have a generally rigid and/or expansion-resistant support structure upon implantation and also configured to assume a generally non-rigid and/or expanded/expandable configuration upon dilation; and implanting the prosthetic heart valve in a heart valve annulus. The method may also include deploying an expandable prosthetic heart valve within the previously-deployed heart valve and heart valve annulus. Deploying the expandable prosthetic heart valve within the previously-deployed prosthetic valve and heart valve annulus may include dilating the previously-deployed prosthetic valve to cause the previously-deployed prosthetic valve to assume a generally non-rigid and/or expanded/expandable shape.

(25) Dilating a previously-deployed prosthetic heart valve may include using a dilation balloon, such as the type currently used for dilation of native heart valves, which can be advanced within the previously-deployed prosthetic heart valve and expanded to a desired pressure and/or diameter. As

a general rule, dilation balloons used for dilation of native valves are formed from generally inelastic material to provide a generally fixed (i.e., pre-set) outer diameter when inflated. Once such balloons are inflated to their full fixed diameter, they will not appreciably expand further (prior to rupturing) even if additional volume/pressure is added therein. Typical pressures for inflating such balloons are between 1 and 6 atmospheres, with pre-set inflated outer diameters of such balloons being on the order of 18 to 33 millimeters. The dilation balloon may be expanded to a desired pressure (e.g., 1-6 atmospheres) sufficient to fully inflate the dilation balloon to its desired diameter and to dilate and expand the previously-deployed prosthetic heart valve.

(26) A typical surgically-implanted prosthetic heart valve will withstand dilation pressures of several atmospheres such as provided by most dilation balloons without expanding and/or becoming elastic. By contrast, the prosthetic heart valve of the current invention is configured to become expanded and/or generally elastic when subjected to sufficient pressure provided by a dilation balloon. If the dilation balloon is expanded, using sufficient pressure, to an expanded outer diameter larger than the inner diameter of the prosthetic heart valve of the invention, the prosthetic heart valve will expand in diameter and/or become elastic.

(27) In one embodiment, the dilation balloon is configured with a pre-set inflated outer diameter which is larger, such as by 10-20% or more, than the inner diameter of the previously-deployed prosthetic heart valve. As an example, if the previously-deployed prosthetic heart valve of the invention has an inner diameter of 23 mm, a dilation balloon having an inflated diameter of 24-27 mm may be inflated within the prosthetic heart valve to cause it to expand and/or become elastic.

(28) Prosthetic heart valves according to various embodiments of the invention can be configured to be generally rigid prior to dilation, but become expanded and/or elastic when subjected to a sufficient dilation pressure. For example, a prosthetic heart valve could be configured to withstand naturally occurring dilation pressures that may occur during beating of the heart, but to become expanded and/or elastic when subjected to a desired pressure (e.g., from a dilation balloon), such as a pressure of 1 atmosphere, 2 atmospheres, 3 atmospheres, 4 atmospheres, 5 atmospheres, or 6 atmospheres, depending on the particular application.

(29) Note that the dilation balloon inflated diameters and inflated pressures, as well as the pressures at which the prosthetic heart valve of the invention would become expanded and/or elastic, set forth above are by way of example, and that the use of balloons with other pressures and diameters, and of prosthetic heart valves configured to change shape and/or expand and/or become elastic when subjected to other pressures and expanded balloon diameters, are also within the scope of the invention.

(30) An annuloplasty ring is being developed having a structure that can expand and/or otherwise change configuration in order to accept a percutaneously-delivered prosthetic heart valve therein. Such an annuloplasty ring is disclosed in U.S. patent application Ser. No. 12/234,580, filed Sep. 19, 2008 and entitled "Annuloplasty Ring Configured to Receive a Percutaneous Prosthetic Heart Valve Implantation," the entire contents of which are incorporated herein by reference. In an embodiment of the invention, the annuloplasty ring defines a first inner orifice area when deployed in the patient's native heart valve to correct heart valve function, but is configured to define a second inner orifice area when subjected to a dilation force such as that provided by a dilation balloon used to deploy a prosthetic valve, with the second (dilated) orifice area being larger than the first (pre-dilation) orifice area. In an annuloplasty ring which is generally circular both before and after dilation, the first inner orifice area has a corresponding first inner diameter, and the second inner orifice area has a corresponding second inner diameter, with the second (post-dilation) inner diameter being larger than the first (pre-dilation) inner diameter.

(31) In one embodiment, the annuloplasty ring has a generally curved portion and a generally straight portion, with the generally curved portion being generally rigid and the generally straight portion being generally flexible. The annuloplasty ring may form a continuous loop or a discontinuous loop, and/or may be generally "D"-shaped (including kidney shapes) or otherwise

generally non-circular. The ring may include upward and/or downward structures, such as bows, when viewed from the side.

(32) In an embodiment of the invention, an annuloplasty ring is a discontinuous structure having a generally rigid curved portion and two generally straight portions extending therefrom, with the generally straight portions aligned with each other to form a generally straight (but discontinuous) structure.

(33) An embodiment of the invention includes a first generally rigid section, a second generally rigid section, and a restraint configured to prevent movement of the first generally rigid section with respect to the second generally rigid section, with the restraint further configured to permit movement of the first generally rigid section with respect to the second generally rigid section when the annuloplasty ring is subjected to a dilation force. The restraint may be configured to permit rotational movement of the first generally rigid section with respect to the second generally rigid section when the annuloplasty ring is subjected to the dilation force. The restraint may comprise a lock configured to fail when the annuloplasty ring is subjected to a dilation force. The restraint may comprise suture, an elastic material or structure such as a spring, a plastically deformable material (including breakable materials), etc.

(34) An annuloplasty ring according to an embodiment of the invention may include a movable connection between the first generally rigid section and the second generally rigid section, wherein the movable connection is configured to survive application of the dilatation force. The movable connection may comprise a hinge, a generally flexible material such as tether, etc.

(35) In an embodiment of the invention, an annuloplasty ring has a generally non-circular shape and has a generally rigid portion defining at least half of the circumference of the generally non-circular shape, and the annuloplasty ring is configured to assume a generally circular shape when dilated by a balloon catheter. The annuloplasty ring may include plastically deformable materials configured to maintain the annuloplasty ring in the generally non-circular shape. The plastically deformable materials may be configured to break or otherwise plastically deform and no longer maintain the annuloplasty ring in the generally non-circular shape when subjected to a dilation force. The annuloplasty ring may form a continuous loop, and may include elastically deformable material configured to provide tension within the continuous loop.

(36) A method for repairing a patient's heart function according to an embodiment of the invention can include: providing an annuloplasty ring having a generally non-circular configuration but configured to assume a generally circular configuration when subjected to a dilatational force; and implanting the annuloplasty ring in a heart valve annulus. The method may also include deploying an expandable prosthetic heart valve within the annuloplasty ring and heart valve annulus. Deploying the expandable prosthetic heart valve within the annuloplasty ring and heart valve annulus may include dilating the annuloplasty ring to cause the annuloplasty ring to assume a generally circular shape.

(37) The generally non-circular configuration of the ring may be a "D"- or kidney-shape, so-called dog-bone shape, etc.

(38) Dilating an annuloplasty ring may include using a dilation balloon, such as the type currently used for dilation of native heart valves, which can be advanced within the annuloplasty ring and expanded to a desired pressure and/or diameter. As a general rule, dilation balloons used for dilation of native valves are formed from generally inelastic material to provide a generally fixed (i.e., pre-set) outer diameter when inflated. Once such balloons are inflated to their full fixed diameter, they will not appreciably expand further (prior to rupturing) even if additional volume/pressure is added therein. Typical pressures for inflating such balloons are between 1 and 6 atmospheres, with pre-set inflated outer diameters of such balloons being on the order of 18 to 33 millimeters. The dilation balloon may be expanded to a desired pressure (e.g., 1-6 atmospheres) sufficient to fully inflate the dilation balloon to its desired diameter and to dilate and expand the native valve and annuloplasty ring.

(39) A typical rigid annuloplasty ring will withstand dilation pressures of several atmospheres such as provided by most dilation balloons without expanding and/or becoming elastic. By contrast, the annuloplasty ring of the current invention is configured to change shape and/or become expanded and/or generally elastic when subjected to sufficient pressure provided by a dilation balloon. If the dilation balloon is expanded, using sufficient pressure, to an expanded outer diameter larger than the inner diameter of the native valve and annuloplasty ring, the annuloplasty ring will expand in diameter and/or change shape and/or become elastic.

(40) In one embodiment, the dilation balloon is configured with a pre-set inflated outer diameter which is larger, such as by 10-20% or more, than the inner diameter of the annuloplasty ring. As an example, if the annuloplasty ring of the invention has an inner diameter of 23 mm, a dilation balloon having an inflated diameter of 24-27 mm may be inflated within the annuloplasty ring to cause it to expand and/or become elastic.

(41) Annuloplasty rings according to various embodiments of the invention can be configured to be generally rigid prior to dilation, but change shape and/or become expanded and/or elastic when subjected to a sufficient dilation pressure. For example, an annuloplasty ring could be configured to withstand naturally occurring dilation pressures that may occur during beating of the heart, but to become expanded and/or elastic when subjected to a desired pressure (e.g., from a dilation balloon), such as a pressure of 1 atmosphere, 2 atmospheres, 3 atmospheres, 4 atmospheres, 5 atmospheres, or 6 atmospheres, depending on the particular application.

(42) Note that the dilation balloon inflated diameters and inflated pressures, as well as the pressures at which the annuloplasty ring of the invention would become expanded and/or elastic, set forth above are by way of example, and that the use of balloons with other pressures and diameters, and of annuloplasty rings configured to change shape and/or expand and/or become elastic when subjected to other pressures and expanded balloon diameters, are also within the scope of the invention.

(43) Other features and advantages of the present invention will become apparent from the following detailed description, taken in conjunction with the accompanying drawings which illustrate, by way of example, the principles of the invention.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 depicts a prosthetic heart valve deployed in a heart according to an embodiment of the invention;

(2) FIGS. 2A-2C depict perspective, top, and side views, respectively, of a prosthetic heart valve according to an embodiment of the invention;

(3) FIG. 2D depicts a top view of the prosthetic heart valve of FIGS. 2A-2C after the prosthetic heart valve has been dilated;

(4) FIGS. 3A-3C depict side, top (in cross section), and close-up sectional views, respectively, of a prosthetic heart valve support structure according to an embodiment of the invention;

(5) FIG. 3D depicts a top view of the prosthetic heart valve support structure of FIGS. 3A-3C after the prosthetic heart valve support structure has been dilated;

(6) FIGS. 4A-4B depict top views of a prosthetic heart valve support structure in pre-dilation and post-dilation configurations, respectively, according to an embodiment of the invention;

(7) FIGS. 5A-5B depict top views of a prosthetic heart valve support structure in pre-dilation and post-dilation configurations, respectively, according to an embodiment of the invention;

(8) FIGS. 6A-6C depict top, side, and close-up sectional views, respectively, of a prosthetic heart valve support structure according to an embodiment of the invention;

(9) FIG. 6D depicts a top view of the prosthetic heart valve support structure of FIGS. 6A-6C after

the prosthetic heart valve support structure has been dilated;

(10) FIGS. 6E and 6F depict close-up top views of a portion, in expanded and unexpanded configurations, respectively, of a prosthetic heart valve support structure according to an embodiment of the invention;

(11) FIGS. 7A and 7B depict top views of unexpanded and expanded configurations, respectively, of a prosthetic heart valve support structure according to an embodiment of the invention;

(12) FIG. 8A depicts an expandable prosthetic heart valve deployment catheter configured for annuloplasty ring dilation and expandable prosthetic heart valve deployment according to an embodiment of the invention;

(13) FIG. 8B depicts the expandable prosthetic heart valve deployment catheter of FIG. 8A positioned within a previously-deployed prosthetic heart valve in a heart valve annulus of a patient according to an embodiment of the invention;

(14) FIG. 8C depicts the expandable prosthetic heart valve deployment catheter of FIG. 8A dilating the previously-deployed prosthetic heart valve and deploying an expandable prosthetic heart valve therewithin according to an embodiment of the invention;

(15) FIG. 8D depicts the expandable prosthetic heart valve deployment catheter of FIG. 8A being withdrawn from the patient according to an embodiment of the invention;

(16) FIG. 9A depicts an expandable prosthetic heart valve deployment catheter configured for dilation of a previously-deployed prosthetic heart valve and for deployment of an expandable prosthetic heart valve according to an embodiment of the invention;

(17) FIG. 9B depicts the expandable prosthetic heart valve deployment catheter of FIG. 9A with the dilation balloon positioned within the previously-deployed prosthetic heart valve in the heart valve annulus according to an embodiment of the invention;

(18) FIG. 9C depicts the expandable prosthetic heart valve deployment catheter of FIG. 9A dilating the previously-deployed prosthetic heart valve according to an embodiment of the invention;

(19) FIG. 9D depicts the expandable prosthetic heart valve deployment catheter of FIG. 9A with the dilation balloon deflated after dilation of the previously-deployed prosthetic heart valve according to an embodiment of the invention;

(20) FIG. 10 depicts an annuloplasty ring deployed in a heart according to an embodiment of the invention;

(21) FIG. 11A depicts a top view of an annuloplasty ring according to an embodiment of the invention;

(22) FIG. 11B depicts a top view of the annuloplasty ring of FIG. 11A after the annuloplasty ring has been dilated;

(23) FIG. 12A depicts a top view of an annuloplasty ring according to a further embodiment of the invention;

(24) FIG. 12B depicts a top view of the annuloplasty ring of FIG. 12A after the annuloplasty ring has been dilated;

(25) FIGS. 13A and 13B depict perspective and top views, respectively, of an annuloplasty ring according to a further embodiment of the invention;

(26) FIGS. 13C and 13D depict perspective and top views, respectively, of the annuloplasty ring of FIGS. 13A and 13B after the annuloplasty ring has been dilated;

(27) FIG. 14A depicts a perspective view of an annuloplasty ring according to a further embodiment of the invention;

(28) FIG. 14B depicts a perspective view of the annuloplasty ring of FIG. 14A after the annuloplasty ring has been dilated;

(29) FIG. 15A depicts a prosthetic heart valve deployment catheter configured for annuloplasty ring dilation and prosthetic heart valve deployment according to an embodiment of the invention;

(30) FIG. 15B depicts the prosthetic heart valve deployment catheter of FIG. 15A positioned within a heart valve annulus of a patient according to an embodiment of the invention;

- (31) FIG. 15C depicts the prosthetic heart valve deployment catheter of FIG. 15A dilating the annuloplasty ring and deploying the prosthetic heart valve according to an embodiment of the invention;
- (32) FIG. 15D depicts the prosthetic heart valve deployment catheter of FIG. 15A being withdrawn from the patient according to an embodiment of the invention;
- (33) FIG. 16A depicts a prosthetic heart valve deployment catheter configured for annuloplasty ring dilation and prosthetic heart valve deployment according to an embodiment of the invention;
- (34) FIG. 16B depicts the prosthetic heart valve deployment catheter of FIG. 16A with the proximal dilation balloon positioned within the heart valve annulus according to an embodiment of the invention;
- (35) FIG. 16C depicts the prosthetic heart valve deployment catheter of FIG. 16A dilating the annuloplasty ring according to an embodiment of the invention;
- (36) FIG. 16D depicts the prosthetic heart valve deployment catheter of FIG. 16A with the proximal dilation balloon deflated according to an embodiment of the invention;
- (37) FIGS. 17A-17C depict side, top (in cross-section), and close-up sectional views, respectively, of an annuloplasty ring according to an embodiment of the invention;
- (38) FIG. 17D depicts a top view, in cross-section, of the annuloplasty ring of FIGS. 17A-17C after the annuloplasty ring has been dilated;
- (39) FIGS. 18A and 18B depict top views, in pre-dilation and post-dilation configurations, of an annuloplasty ring according to an embodiment of the invention;
- (40) FIGS. 19A-19C depict top, side, and cross-sectional views, respectively, of an annuloplasty ring according to an embodiment of the invention;
- (41) FIG. 19D depicts a top view, in expanded configuration, of the annuloplasty ring of FIGS. 19A-19C; and
- (42) FIGS. 19E and 19F depict close-up top views, in undilated and dilated configurations, respectively, of an annuloplasty ring according to an embodiment of the invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

(43) With reference to FIG. 1, a prosthetic heart valve **10** according to the invention is depicted in a heart **12**. The heart **12** has four chambers, known as the right atrium **14**, right ventricle **16**, left atrium **18**, and left ventricle **20**. The general anatomy of the heart **12**, which is depicted as viewed from the front of a patient, will be described for background purposes. The heart **12** has a muscular outer wall **22**, with an interatrial septum **24** dividing the right atrium **14** and left atrium **18**, and a muscular interventricular septum **26** dividing the right ventricle **16** and left ventricle **20**. At the bottom end of the heart **12** is the apex **28**.

(44) Blood flows through the superior vena cava **30** and the inferior vena cava **32** into the right atrium **14** of the heart **12**. The tricuspid valve **34**, which has three leaflets **36**, controls blood flow between the right atrium **14** and the right ventricle **16**. The tricuspid valve **34** is closed when blood is pumped out from the right ventricle **16** through the pulmonary valve **38** to the pulmonary artery **40** which branches into arteries leading to the lungs (not shown). Thereafter, the tricuspid valve **34** is opened to refill the right ventricle **16** with blood from the right atrium **14**. Lower portions and free edges **42** of leaflets **36** of the tricuspid valve **34** are connected via tricuspid chordae tendineae **44** to papillary muscles **46** in the right ventricle **16** for controlling the movements of the tricuspid valve **34**.

(45) After exiting the lungs, the newly-oxygenated blood flows through the pulmonary veins **48** and enters the left atrium **18** of the heart **12**. The mitral valve in a normal heart controls blood flow between the left atrium **18** and the left ventricle **20**. Note that in the current figure, the native mitral valve has been replaced with the prosthetic heart valve **10**, which is accordingly a prosthetic mitral valve **50**. The prosthetic mitral valve **50** is closed during ventricular systole when blood is ejected from the left ventricle **20** into the aorta **52**. Thereafter, the prosthetic mitral valve **50** is opened to refill the left ventricle **20** with blood from the left atrium **18**. Blood from the left ventricle **20** is

pumped by power created from the musculature of the heart wall **22** and the muscular interventricular septum **26** through the aortic valve **62** into the aorta **52** which branches into arteries leading to all parts of the body.

(46) In the particular embodiment depicted, the prosthetic heart valve **10** is deployed to replace a native mitral valve, and more particularly is secured (via, e.g., sutures) adjacent and around the mitral valve annulus **64**. Depending on the particular application, including the method by which the prosthetic heart valve **10** was implanted, the particular native valve (mitral, tricuspid, etc.) and/or some or all of its associated structures may be entirely or partially removed prior to or during implantation of the prosthetic heart valve **10**, or the native valve and/or some or all associated structures may simply be left in place with the prosthetic heart valve **10** installed over the native valve. For example, a native mitral valve typically has two leaflets (anterior leaflet and posterior leaflet), lower portions and free edges of which are connected via mitral chordae tendineae to papillary muscles **60** in the left ventricle **20** for controlling the movements of the mitral valve. Not all of these structures (i.e., mitral valve leaflets, chordae tendineae) are depicted in FIG. **1** because, in the particular embodiment, the native mitral valve and many associated structures (chordae, etc.) have been removed prior to or during implantation of the prosthetic heart valve **10**. However, in many prosthetic valve implantations, surgeons choose to preserve many of the chordae tendineae, etc., even when excising the native valve.

(47) Although FIG. **1** depicts a prosthetic mitral valve, note that the invention can be applied to prosthetic valves (and systems and methods therefore) configured to replacement of any heart valves, including aortic, mitral, tricuspid, and pulmonary valves.

(48) FIGS. **2A-2C** depict a prosthetic heart valve **70** according to an embodiment of the invention, where the prosthetic heart valve **70** comprises a support frame **72** and valve structure **74**. In the particular embodiment depicted, the valve structure **74** comprises three heart valve leaflets **76**. The prosthetic heart valve **70** has an inner diameter **78a** of a valve orifice **80** through which blood may flow in one direction, but the valve leaflets **76** will prevent blood flow in the opposite direction. The support frame **74** is generally rigid and/or expansion-resistant in order to maintain the particular shape (which in this embodiment is generally round) and diameter **78a** of the valve orifice **80** and also to maintain the respective valve leaflets **76** in proper alignment in order for the valve structure **74** to properly close and open. The particular support frame **74** also includes commissure supports **75**. In the particular embodiment depicted in FIGS. **2A-2C**, the support frame **74** defines a generally rigid and/or expansion-resistant ring **82** which encircles the valve **70** and defines a generally round valve orifice **80**, but other shapes are also within the scope of the invention, depending on the particular application (including issues such as the particular native valve to be replaced, etc.) The particular prosthetic heart valve **70** includes visualization markers **73** (such as radiopaque markers, etc.), which in the current embodiment are on the support frame **74** and correspond to the ring **82** and also to the commissure supports **75** (and hence to the commissures), which can aid in proper placement of a subsequently-deployed expandable prosthetic heart valve within the valve orifice **80** of the prosthetic heart valve **70**.

(49) When the prosthetic heart valve **70** of FIGS. **2A-2C** is subjected to a dilation force (such as that from a dilation balloon, which may provide pressures of 1 to 5 atmospheres), the prosthetic heart valve will be expanded somewhat. The support frame **74** will transition from the generally rigid and/or expansion-resistant configuration of FIGS. **2A-2C** to a generally non-rigid and expanded configuration depicted in FIG. **2D**. Note that the ring **82**, which was generally rigid and/or expansion-resistant, is now generally non-rigid and is expanded, and the valve orifice **80** has accordingly been enlarged to a larger inner diameter **78b**. The larger inner diameter **78b** is configured to receive an expandable prosthetic heart valve therein. The overall result is that the “post-dilation” prosthetic heart valve **70** of FIG. **2D** has a generally larger inner diameter circular opening **78b**. The actual inner diameters will depend on the particular application, including aspects of the particular patient's heart (e.g., native valve and/or annulus diameter, etc.). As an

example, the pre-dilation inner diameter **78a** for a mitral valve may be between 25-33 mm, or for an aortic valve 18-28 mm. The post-dilation inner diameter **78b** will be larger, and more specifically large enough to accommodate the outer diameter of an expandable prosthetic valve therein.

(50) In some procedures where an expandable prosthetic heart valve is used to replace/repair a previously-deployed prosthetic heart valve, it may be desirable for the expandable prosthetic heart valve to have a deployed (expanded) inner diameter (and corresponding expandable prosthetic heart valve orifice area) approximately equal to the pre-dilation inner diameter **78a** (and corresponding pre-dilation prosthetic valve orifice area) of the previously-deployed prosthetic heart valve **70**. Such consistency between inner diameters/orifice areas can be useful in maintaining proper blood flow, so that the expandable prosthetic heart valve will provide the same blood flow as was provided by the previously-deployed prosthetic heart valve. Note that the term “valve orifice area” refers to the area of the valve orifice when the valve portion is in the fully open configuration (e.g., with the valve leaflets in their fully open configuration so that the effective orifice area is at its maximum size).

(51) For example, Edwards Lifesciences has Sapien™ expandable prosthetic heart valves having outer diameters of 23 and 26 mm, respectively, which have corresponding inner diameters of about 20 and 23 mm, respectively. Accordingly, the post-dilation inner diameter **78b** of the (previously-deployed) prosthetic heart valve may be on the order of 23 and 26 mm (respectively) to accommodate such expandable prosthetic heart valves. This corresponds to a post-dilation inner diameter **78b** being about 10 to 20% larger than the pre-dilation inner diameter **78a**. Accordingly, embodiments of the invention include a prosthetic heart valve having a post-dilation inner diameter **78b** that is about 10, 15, or 20%, or between 5-25%, 10-20%, or 13-17% of the pre-dilation inner diameter **78a**.

(52) Note that the invention is not limited to the above differences between pre- and post-dilation inner diameters. For example, there may be applications where much smaller and/or much larger post-dilation inner diameters may be required. In some cases an expandable prosthetic heart valve will have an outer diameter only slightly larger than its inner diameter, so that less expansion of the previously-deployed prosthetic heart valve inner diameter is required in order to accommodate the expandable prosthetic heart valve. In other cases an expandable prosthetic heart valve may have an outer diameter that is much larger than its inner diameter, so that a greater expansion of the previously-deployed prosthetic heart valve inner diameter is necessary to accommodate the expandable prosthetic heart valve. There may also be applications where it may be desirable to deploy an expandable prosthetic heart valve having a smaller or larger inner diameter than was provided by the (previously-deployed and pre-dilation) prosthetic heart valve.

(53) Note that, depending on the particular embodiment, a prosthetic heart valve **70** according to the invention may return to its pre-dilation inner diameter **78a** after being subject to dilation such as from a balloon dilation catheter. However, the balloon dilation will have rendered the “post-dilation” prosthetic heart valve **70** into a generally non-rigid and/or expansion-friendly configuration, so that the “post-dilation” prosthetic heart valve **70** will be forced with relative ease into a larger diameter (such as **78b**) when an expandable (e.g., balloon-expandable, self-expanding, etc.) prosthetic heart valve is deployed within the valve orifice **80** of the prosthetic heart valve **70**.

(54) FIGS. 3A-3C depicts a prosthetic heart valve **90** having a valve structure **92** and support frame **94** according to a further embodiment of the invention, with the prosthetic heart valve **90** having a valve orifice **96** having an inner diameter **98a**. The support frame **94** has a generally rigid and expansion-resistant core **100** formed from a single core element **102** which is bent or otherwise formed into a generally circular shape with opposing ends **104a**, **104b** meeting at a seam **106** so as to form the complete circle. The seam **106** may include adhesive, solder, welds, etc. in order to secure the two ends **104a**, **104b** together. The prosthetic heart valve **90** includes a covering **108** around the support core **96**. The covering **108** may be a cloth-like material, and may be a sewing

ring configured to be sewn to the native heart valve annulus during deployment of the prosthetic heart valve **90**. The covering **108** is generally flexible, and may be generally elastic. The covering **108** (or a portion thereof) may also be generally compressible, especially in the portion facing inward toward the valve orifice **96**, which can assist in seating an expandable valve therein. A compressible material may be applied onto or within the covering **108** in a position to provide a compressible region on the surface facing inward toward the valve orifice **96**.

(55) When the prosthetic heart valve **90** is subject to a dilation force such as that from a dilation balloon catheter, the support frame **94** will become non-rigid and expanded. More particularly, the seam **106** of the core **100** will rupture, so that the opposing ends **104a**, **104b** will be separated by an opening **110**, and the core **100** will assume a generally C-shaped configuration as depicted in FIG. 3D. The covering **108** will stretch or otherwise expand circumferentially to accommodate the enlarged/expanded core **100**, and the prosthetic heart valve **90** will have an enlarged inner diameter **98b** for the valve orifice **96**. Depending on the particular embodiment, including the particular construction of the core **100** and/or covering, the (post-dilation) prosthetic heart valve **90** may provide an inward (i.e., compressive) force toward the valve orifice **96**. For example, the core **100** may be formed of a generally resilient spring-like material and/or memory material, and may be biased somewhat toward its non-dilated configuration (i.e., with the opposing ends **104a**, **104b** touching each other as in FIGS. 3A-3C). The covering **108** may also (or alternatively) be elastic and, after dilation of the prosthetic heart valve **90**, may provide an inward pull on the core **100** so as to bias the opposing ends **104a**, **104b** toward each other. This inward pressure can help to seat an expandable heart valve that may be deployed within the prosthetic heart valve **90**. In an embodiment where compressible material is provided (e.g., as part of the covering **108**) facing inward toward the valve orifice **96**, then the compressible material can provide additional assistance in seating an expandable heart valve within the prosthetic heart valve **90**.

(56) FIG. 4A depicts a further embodiment of a support frame **120** for use with a prosthetic heart valve according to the invention. The support frame **120** is generally circular and defines an inner diameter **122a**, and has a generally rigid core **124** formed from a single core element **126** which is bent or otherwise formed into a generally circular shape with opposing ends **128a**, **128b** which meet and connect at an overlapping section **130** having a length **132a**. The overlapping section **130** may include adhesive, solder, welds, mechanical connections, etc. in order to secure the overlapping ends **128a**, **128b** together. In the particular embodiment depicted, the overlapping section **130** has a ratchet-like assembly formed from interacting portions **134a**, **134b** at or adjacent the opposing ends **128a**, **128b**. The support frame **120** may include a covering (not shown) around the core **124**.

(57) FIG. 4B depicts the support frame **120** of FIG. 4A after it has been subjected to a dilation force. The support frame **120** has been expanded to a larger inner diameter **122b**, with the core **124** enlarged so that the overlapping section **130** is smaller, having a new shorter length **132b**. The dilation force caused the interacting portions **134a**, **134b** to temporarily release their connection to permit the relative movement of the overlapping ends **128a**, **128b**, but with the dilation force removed the interacting portions **134a**, **134b** once again form a connection, so that the support frame **120** is again generally rigid. Note that, depending on the particular application, a support frame could be formed similar to that of FIGS. 4A-4B but with the interacting portions configured so that no fixed connection is formed between the overlapping ends after dilation, so that the support frame will be generally non-rigid after the dilation force has been applied. In such an embodiment, the support frame may be configured to provide (after dilation) an inward (compressive) force upon any expandable prosthetic valve that may be deployed within the valve orifice of the original (and now dilated) prosthetic valve. This inward compressive force may help to seat and otherwise hold the expandable prosthetic valve in its desired position within the native valve annulus and also within the now-dilated (prior) prosthetic valve.

(58) FIGS. 5A-5B depict a further embodiment of a support frame **120** for use with a prosthetic

heart valve according to the invention. The support frame **120** is similar to that depicted in FIG. 4A, except the overlapping section **130** includes a sliding mechanical connection **136** having a slot **137** secured to one opposing end **128a**, the second opposing end **128b** having been passed through the slot **137** to form the overlapping section **130**, and also including a spring **138** extending from the slot **137** to the second opposing end **128b**. The spring **138** permits expansion and/or contraction of the support frame **120**, with the spring **138** generally biasing the support frame **120** toward a smaller diameter, such as the smaller inner diameter **122a** of FIG. 5A, but also permitting the support frame **120** to be expanded, when subject to an outside force such as a dilation balloon and/or expandable prosthetic valve, to a larger diameter such as the inner diameter **122b** of FIG. 5B. Note that the spring **138** can also permit the support frame **120** (and associated valve annulus) to move with physiological annular dynamic motion, e.g., to make smaller expansions and/or contractions in response to normal valve function/heart movement as the patient's heart beats and pumps blood through the valve. The support frame **120** may include a covering (not shown) around the core **124**. The support frame **120** may be formed of various materials, including elgiloy. The spring **138** can be configured to provide a specific force in opposing expansion of the support frame **120**, and may be configured so that the force provided is insufficient to oppose the dilation force from a dilation balloon and/or expandable stent which might be expanded within the support frame **120**. The spring **138** could be formed from traditional coil springs, compressible materials, pleated sewing rings, accordion sewing rings, and other configurations configured to provide a spring-like force.

(59) In another embodiment of the invention, a prosthetic heart valve includes a support frame having a rigid and/or expansion-resistant core configured to separate into a plurality of pieces when subjected to a dilation force. Such a rigid and/or expansion-resistant core could be formed as a single piece, which might include one or more weak points that are subject to separation when subjected to a dilation force. In one embodiment a rigid and/or expansion-resistant core could be formed from a plurality of segments positioned in edge-to-edge fashion and configured to separate when subjected to a dilation force. FIGS. 6A-6C depict one such embodiment of a support frame **140** for use with a prosthetic heart valve according to the invention. The support frame **140** is generally circular (although other shapes are within the scope of the invention) and defines an orifice **141** having an inner diameter **142a**, and has a generally rigid and/or expansion-resistant core **144** formed from multiple core segments **146** which are arranged in edge-to-edge fashion to form the generally circular shape of the core **144**. Each segment **146** has an inner lumen **148**, with the segments **146** when assembled into the core **144** forming a continuous core lumen **150**.

(60) Adjacent segments **146** join at seams **152**, which may include adhesive, solder, welds, etc. in order to secure and/or seal the seam **152** between the adjacent segments **146**. The support frame **140** has a pre-dilation cord **154** and a post-dilation cord **156** passing through the core lumen **150**. The pre-dilation cord **154** may be a generally inelastic cord which is sufficiently tight to hold adjacent segments together and to prevent unwanted dilation of the support frame **140**. A covering (not shown) may also be included to cover the core **144**. The covering may be formed of cloth, and may be elastic.

(61) Both the seams **152** and pre-dilation cord **154** are configured to fail or stretch when subjected to a dilation force, such as that provided by a dilation balloon, whereupon the support frame **140** will assume the expanded configuration depicted in FIG. 6D, with an enlarged inner diameter **142b**. For example, the pre-dilation cord **154** may be an inelastic cord configured to fail when subject to a selected force, such as 1, 2, 3, 4, or more atmospheres, which are within the range of forces provided by many dilation balloons used in percutaneously-deployed heart valve procedures. In one embodiment, the seams **152** are merely sealed, with the sealant providing little if any securement against separation of adjacent segments **146**. In such an embodiment, the pre-dilation cord **154** may serve as the sole device to hold the core segments **146** together in the rigid and/or expansion-resistant (pre-dilation) configuration. Once the pre-dilation cord **154** fails or stretches

due to the dilation pressure, essentially all of the seams **152** will separate so that adjacent segments **146** separate with spaces **158** separating the adjacent segments **146**. The remaining portions of the pre-dilation cord **154** remain within the support frame **140** after dilation.

(62) The post-dilation cord **156** remains intact after dilation and may serve to hold the support frame **140** together post-dilation. The post-dilation cord **156** could be elastic, and/or could be inelastic and have a larger diameter, and possibly a higher failure strength, than the pre-dilation cord **154**. If the post-dilation cord **156** is elastic, it may provide an inward compressive force into the central orifice **141**. If the post-dilation cord **156** is generally inelastic, it will remain intact after dilation either because its strength was too great to be ruptured by the dilation balloon or because it had a diameter that was larger than that of the inflated dilation balloon.

(63) In a variation of the embodiment of FIGS. **6A-6D**, the pre-dilation cord **154** could be left out of the support frame **140**, and the seams **152** themselves could have adhesive or other connections that serve to hold the segments **146** together prior to dilation. In a further variation, the pre-dilation cord **154** could be left out of the support frame, with a post-dilation cord **156** configured to be elastic and with sufficient strength/elasticity to provide an inward compressive force into the central orifice with sufficient strength to hold the segments **146** together prior to dilation, but with the inward compressive force weak enough to permit the support frame **140** to be dilated and to permit an expandable prosthetic heart valve to be deployed therein. Accordingly, the post-dilation cord **156** would serve as both pre-dilation cord and post-dilation cord.

(64) Visualization references (such as the visualization markers **73** from FIGS. **2A-2D**) may be included on or in various portions of the device. For example, visualization references may be placed on, in, or adjacent the support frame **140**, core **144**, segments **146**, pre-dilation cord **154**, and/or post-dilation cord **156**, etc. in the device of FIGS. **6A-6D**. Such visualization references can help a user to properly position a dilation balloon and/or subsequently-deployed expandable prosthetic heart valve within the previously-deployed prosthetic heart valve having the support frame **140**. For example, visualization markers positioned at the generally rigid support frame **140** (or more specifically at the segments **146** and/or the pre-dilation cord **154** and/or post-dilation cord **156**) could be used to guide delivery and expansion of a dilation balloon, and also to confirm that the support frame **140** has been dilated. The visualization markers could also be used to guide delivery and expansion of the expandable prosthetic heart valve within the support frame **140**, and to confirm proper deployment of the expandable prosthetic heart valve.

(65) The support frame **140** may have segments **146** having ends **146a**, **146b** which interlock and/or otherwise interact in order to hold the segments **146** together and/or in alignment. As depicted in the close-up view of FIG. **6E**, adjacent segments **146** may include interconnecting ends **146a**, **146b**, with one end **146a** having a member **147** configured to be received within the lumen **148** or other opening in an end **146b** of an adjacent segment **146**. The interconnecting ends **146a**, **146b** keep the adjacent segments **146** in a desired alignment so that the segment ends **146a**, **146b** cannot slide sideways with respect to the member **147** and lumen **148**, but does permit the segments **146** to be pulled apart, as depicted in FIG. **6F**, in order to permit expansion of the support frame **140** (as was depicted in FIG. **6D**). The pulling apart of the segments **146** may be opposed by various structures set forth herein which oppose and/or restrict dilation of a support frame, such as one or more elastic and/or inelastic cords **155** configured to oppose and/or restrict dilation of the support frame as was depicted in FIGS. **6A-6D**.

(66) FIGS. **7A-7B** depict a further embodiment of the invention, with a prosthetic heart valve **160** having a valve structure **162** formed from three (3) leaflets **164** spaced around the valve orifice **166**. The support frame **168** includes a core **170** formed from three (3) segments **172**. At the base/perimeter of the valve structure **162**, the edges **165** of each leaflet **164** coincide with the edges of each respective segment **172** as well as the seams **174** (and the commissure supports, if present). Adjacent segments **172** are connected to each other at the seams **174**, such as with adhesive(s), weld(s), etc., in order to form the rigid and/or expansion-resistant (pre-dilation) support frame **168**.

Adjacent segments **172** are also connected via individual inelastic cords **176** and elastic cords **178** extending between the adjacent segments **172**. As depicted in FIG. 7A, the (pre-dilation) prosthetic valve **160** has a valve orifice **166** having an inner diameter **180a**. A cloth cover (not shown) or similar covering will also typically be included to cover the support frame **168** and its associated elements (e.g., inelastic cords **176** and elastic cords **178**).

(67) When the prosthetic heart valve **160** of FIG. 7A is subjected to a dilation force, the seams **174** between the segments **172** will fail and the support frame **168** will separate into the three segments **172**, as depicted in FIG. 7B. Note that in this particular embodiment the inelastic cords **176** do not serve to hold adjacent segments against each other, but instead permit adjacent segments to separate when subjected to a dilation force. The inelastic cords **176** prevent excessive separation between any adjacent segments **172** as the dilation balloon (or other dilation force) is applied, with the result being that the segments **172** will all be spaced generally equally apart from each other once the full dilation force is applied. After the dilation force is removed, the elastic cords **178** will serve to pull the adjacent segments toward each other and to provide a generally inward (compressive) pressure to the valve orifice **166** but while also maintaining the post-dilation inner diameter **180b** (FIG. 7B) at a larger size than the pre-dilation diameter **180a** (FIG. 7A). Because the leaflets **164** were positioned with their base edges coinciding with the seams **174** between segments **172**, the leaflets **164** can remain generally intact after dilation and still permit the segments **172** to separate to form the enlarged inner diameter **180b**. Note, however, that deploying a new expandable prosthetic valve within the prosthetic heart valve **160** will generally involve deploying an expandable heart valve support stent that will crush the leaflets **164** of the current prosthetic heart valve **160** against the support frame **168**, walls of the native valve annulus, and/or lumen.

(68) If the prosthetic heart valve **160** includes commissure supports (not shown) on the support frame **168**, the commissure supports can be positioned on or adjacent the seams **174** between segments **172**, and the commissure supports can also be configured to split lengthwise when the prosthetic heart valve **160** is dilated so that one-half of each commissure support will remain with the adjacent segment **172** on either side of said commissure support. In such an embodiment, the edges of the valve leaflets **164** can be secured (e.g., during assembly of the prosthetic heart valve **160**) to the respective half of each commissure support, so that when the prosthetic heart valve **160** is dilated adjacent leaflets **164** can separate from adjacent leaflets **164**, but each leaflet **164** will still remain secured via its edges to its respective commissure support halves.

(69) There are many variations of the above-cited embodiments, including various combinations of the various embodiments. For example, the pre-dilation cord **154** and/or post-dilation cord **156** of FIGS. 6A-6D could be used with the core **100** of FIGS. 3A-3D in order to provide inward compressive force after the core **100** was dilated. The post-dilation cord **156** of FIGS. 6A-6D could be replaced by a cover **108** such as that depicted in FIGS. 3A-3D, with the cover **108** serving to hold the post-dilation core assembly (including any segments and/or pieces thereof) together and also (if formed from elastic material) providing an inward compressive force to the valve orifice.

(70) FIG. 8A depicts an expandable prosthetic heart valve deployment catheter **220** configured for (prior) prosthetic heart valve dilation and (replacement) expandable prosthetic heart valve deployment. The deployment catheter **220** has an elongated main body **222**, a proximal end **224**, and a distal end **226**. The proximal end **224** includes a handle **228**. The distal end **226** includes a dilation balloon **230** upon which an expandable prosthetic valve **232** is mounted. In the particular embodiment depicted, the expandable prosthetic valve **232** includes a stent **234**. The distal end **226** may also include one or more radiopaque markers **233** or similar visibility markers to improve visibility of the device within the patient when using fluoroscopy or other viewing technologies.

(71) FIGS. 8B-8D depict deployment of an expandable prosthetic heart valve **232** within a heart valve annulus **236** where a prosthetic heart valve **10** has previously been deployed. The previously-deployed prosthetic heart valve **10** may have been deployed using any methods, including methods currently known in the art such as traditional (open chest) surgery, minimally-invasive (e.g.,

keyhole) surgery, and percutaneous surgery. Depending on the particular application, the previously-deployed prosthetic heart valve **10** can be deployed in the patient years prior to, days prior to, hours prior to, or immediately prior to deployment of the expandable prosthetic heart valve **232** as depicted in FIGS. **8B-8D**.

(72) FIG. **8B** depicts the expandable prosthetic heart valve deployment catheter **220** of FIG. **8A** with the distal end **226** advanced so that the dilation balloon **230** and expandable prosthetic heart valve **232** are positioned within the previously-deployed prosthetic heart valve **10** in the patient's heart **240**. The previously-deployed prosthetic heart valve **10** is seen in cross-section to show the generally rigid and/or expansion-resistant support frame **238**.

(73) In the particular embodiment depicted in FIG. **8B**, the deployment catheter **220** has been advanced over a guide wire **242**, which was advanced into the patient's heart **240** and previously-deployed prosthetic heart valve **10** prior to advancement of the deployment catheter **220** into the patient. Note that the use of a guide wire **242** is optional. Other guide devices could also be used, in addition to or in lieu of a guide wire. For example, a guide catheter could be used, wherein a guide catheter is advanced to a desired position within a patient, and the deployment catheter is then advanced into the patient inside of the guide catheter until the distal end of the deployment catheter extends from a distal opening in the guide catheter. A deployment catheter could also be used without any sort of guide wire or guide catheter, so that the deployment catheter is guided by itself into the desired treatment location.

(74) As depicted in FIG. **8C**, once the dilation balloon **230** and expandable prosthetic heart valve **232** are properly positioned within the heart valve annulus **234** and previously-deployed prosthetic heart valve **10**, the dilation balloon **230** is expanded. The expanding dilation balloon **230** forces the stent **234** to expand outwardly, and crushes the leaflets **244** of the previously-deployed prosthetic heart valve **10** against the heart valve annulus **236**. The force from the expanding dilation balloon **230** also dilates the previously-deployed prosthetic heart valve **10** and heart valve annulus **236**, forcing the support frame **238** of the previously-deployed prosthetic heart valve **10** to expand and/or become non-rigid.

(75) In FIG. **8D**, the dilation balloon **230** is deflated or otherwise reduced in diameter, with the new expandable prosthetic valve **232** deployed in the heart valve annulus **236** and previously-deployed prosthetic heart valve **10**, and also held in place by the stent **234**. The outward pressure from the expanded stent **232**, along with the inward pressure from the heart valve annulus **236** and from any elastic portions (such as core, cords, and/or covers) of the previously-deployed prosthetic heart valve **10** or from the now-crushed previously-deployed prosthetic heart valve leaflets **244**, combine to firmly seat the new expandable prosthetic valve **232** in the desired position in the heart valve annulus **236** and previously-deployed prosthetic heart valve **10**. The deployment catheter **220** with the dilation balloon **230** can then be withdrawn from the heart **240**, leaving the new expandable prosthetic heart valve **232** in its deployed position within the patient and the previously-deployed prosthetic heart valve **10**.

(76) In a further embodiment of the invention, the previously-deployed prosthetic heart valve **10** is dilated in a separate step from deployment of the expandable prosthetic heart valve **232**. FIG. **9A** depicts an expandable prosthetic heart valve deployment catheter **220** configured for previously-deployed prosthetic heart valve dilation and expandable prosthetic heart valve deployment using two separate balloons, and more specifically a distal balloon **230a** and a proximal balloon **230b**. The distal balloon **230a** is configured to deploy the new expandable prosthetic valve **232**, which is positioned on the distal balloon **230a**, whereas the proximal balloon **230b** is configured for dilation of the previously-deployed prosthetic heart valve **10**.

(77) FIGS. **9B-9D** depict dilation of the previously-deployed prosthetic heart valve **10** and valve annulus **236** using the proximal balloon **230b**. In FIG. **9B**, the deployment catheter **220** has been advanced into the heart **230** with the distal balloon **230a** (with expandable prosthetic valve **232** thereon) advanced past the previously-deployed prosthetic heart valve **10**, and the proximal balloon

230b positioned within the previously-deployed prosthetic heart valve **10** and valve annulus **236**. (78) The proximal balloon **230b** is inflated or otherwise expanded, as depicted in FIG. **9C**, thereby dilating the previously-deployed prosthetic heart valve **10** and valve annulus **236**. The support frame **238** of the previously-deployed prosthetic heart valve **10** is expanded and/or assumes a generally non-rigid configuration, similarly to the changes previously discussed with respect to the dilation discussed in FIG. **8C** above.

(79) After dilation of the previously-deployed prosthetic heart valve **10**, the proximal balloon **230b** is deflated or otherwise reduced in diameter, as depicted in FIG. **9D**. The deployment catheter **220** may then be withdrawn from the patient until the proximal balloon **230b** is proximal of the previously-deployed prosthetic heart valve **10** and the distal balloon **230a** is positioned within the previously-deployed prosthetic heart valve **10**. The distal balloon **230a** will be positioned within the previously-deployed prosthetic heart valve **10** in a similar fashion to that depicted for balloon **230** in FIG. **8B**. The distal balloon **230a** will then be expanded to deploy the expandable prosthetic valve **232** in essentially the same manner as was discussed and depicted in FIGS. **8B-8D**. The distal balloon **230a** will serve to deploy the new expandable prosthetic valve **232**, and may also serve to further dilate the previously-deployed prosthetic heart valve **10** and/or native valve annulus **236**.

(80) Note that the expandable prosthetic valve may be self-expanding, in which case the deployment catheter may not have a dilation balloon as depicted in FIGS. **8A-8D** and **9A-9D**. Moreover, such a self-expanding prosthetic heart valve could be deployed with or without prior dilation of the previously-deployed prosthetic heart valve. For example, a self-expanding prosthetic heart valve may provide sufficient outward radial force to dilate the previously-deployed prosthetic heart valve and/or to hold a now-dilated previously-deployed prosthetic heart valve in an expanded configuration in order to provide sufficient room for the self-expanding prosthetic heart valve in its expanded configuration.

(81) With reference to FIG. **10**, an annuloplasty ring device **1010** according to the invention is depicted in a heart **12**. In the particular embodiment depicted, the annuloplasty ring **1010** is deployed in the mitral valve **1050**, and more particularly is secured (via, e.g., sutures) adjacent and around the mitral valve annulus **64**. The mitral valve **1050** has two leaflets (anterior leaflet **1054a** and posterior leaflet **1054p**), lower portions and free edges **1056** of which are connected via mitral chordae tendineae **1058** to papillary muscles **60** in the left ventricle **20** for controlling the movements of the mitral valve **1050**. The annuloplasty ring **1010** provides a desired shape to the mitral valve annulus **64**, thereby providing proper alignment and closure of the mitral valve leaflets **1054a**, **1054p**.

(82) FIG. **11A** depicts a top view of an annuloplasty ring **1070** according to an embodiment of the invention, where the annuloplasty ring **1010** is generally “D”-shaped and has a generally rigid portion **1072** and generally flexible portion **1074**. In the particular embodiment depicted in FIG. **11A**, the generally rigid portion **1072** is generally curved, but the generally flexible portion **1074** is generally straight.

(83) When the annuloplasty ring **1070** of FIG. **11A** is subjected to a dilation force (such as that from a dilation balloon), the annuloplasty ring **1070** will transition from the generally “D”-shaped configuration of FIG. **11A** to the generally circular shape of FIG. **11B**. While the generally rigid portion **1072** has remained generally unchanged in shaped (i.e., is still generally curved), the generally flexible portion **1074** has transitioned from the generally straight configuration of FIG. **11A** to the generally curved configuration of FIG. **11B**. The overall result is that the “post-dilation” annuloplasty ring **1070** of FIG. **11B** has a generally circular opening **1076** when viewed from the top.

(84) FIG. **12A** depicts a top view of an annuloplasty ring **1080** according to a further embodiment of the invention, where the annuloplasty ring **1080** is generally “D”-shaped and has a generally rigid portion **1082** and a generally flexible portion **1084** which has two separate generally flexible portions **1084a**, **1084b**. The annuloplasty ring **1080** of FIG. **12A** is accordingly discontinuous in

structure (as opposed to the continuous structure of FIGS. 11A-11B). In the particular embodiment depicted in FIG. 12A, the generally rigid portion **1082** is generally curved, but each of the generally flexible portions **1084a**, **1084b** are generally straight and are also generally aligned so that the generally flexible portion **1084** is generally straight.

(85) When the annuloplasty ring **1080** of FIG. 12A is subjected to a dilation force (such as that from a dilation balloon), the annuloplasty ring **1080** will transition from the generally “D”-shaped configuration of FIG. 12A to the generally circular (but still discontinuous) shape of FIG. 12B. While the generally rigid portion **1082** has remained generally unchanged in shaped (i.e., is still generally curved), the generally flexible portions **1084a**, **1084b** have transitioned from the generally straight configurations of FIG. 12A to the generally curved configurations of FIG. 12B. The overall result is that the “post-dilation” annuloplasty ring **1080** of FIG. 12B is generally circular but discontinuous when viewed from the top, providing a generally circular opening **1086**.

(86) FIGS. 13A-13D depict a further embodiment of the invention, where an annuloplasty ring **1090** has a first generally rigid portion **1092** and second generally rigid portion **1094**. As depicted in FIGS. 13A-13B, the annuloplasty ring **1090** in its pre-dilation configuration is generally D-shaped, with the second generally rigid portion **1094** being shorter than the first generally rigid portion **1092**. The second generally rigid portion **1092** defines a curve **1096** which is directed inward with respect to the ring opening **1098**.

(87) The first generally rigid portion **1092** and second generally rigid portion **1094** of the annuloplasty ring **1090** are held together via a movable connection, which in the particular embodiment is formed by two hinges **1100** secured to either end of the first generally rigid portion **1092** and second generally rigid portion **1094**. The hinges **1100** permit the second generally rigid portion **1094** to rotate relative to the first generally rigid portion **1092** when an outward force, such as that provided from an expanded dilation balloon, is applied to the annuloplasty ring **1090**. When the second generally rigid portion **1094** is rotated relative to the first generally rigid portion **1092** responsive to such an outward force, the annuloplasty ring **1090** will transform from the generally D-shaped configuration of FIGS. 13A-13B to the generally circular configuration of FIGS. 13C-13D.

(88) In order to prevent unwanted rotation of the second generally rigid portion **1094** with respect to the first generally rigid portion **1092**, a lock or other restraint **1102** is provided. The restraint **1102** prevents rotation of the second generally rigid portion **1094** with respect to the first generally rigid portion **1092** prior to application of a dilatation force. However, the restraint **1102** is configured to fail or open or otherwise release upon application of a significant dilation force (such as that provided by a dilation balloon) to permit movement (which in the particular embodiment depicted is in the form of rotation) of the second generally rigid section **1094** with respect to the first generally rigid section **1092** when the annuloplasty ring **1090** is subjected to the dilation force.

(89) In the particular embodiment of FIG. 13A, the restraint **1102** comprises lines of suture **1104** tied between the first generally rigid portion **1092** and second generally rigid portion **1094**. Other types of restraints are also within the scope of the invention, including elastically deformable materials and/or structures such as springs, and plastically deformable materials (including breakable materials) such as suture, metals, plastics, etc.

(90) In a further embodiment of the invention depicted in FIGS. 14A-14B, the annuloplasty ring **1110** has a restraint **1116** that is a plastically deformable material (e.g., a bendable metal) that prevents relative movement/rotation of the two generally rigid sections **1112**, **1114** prior to application of the dilation force, but upon application of the dilation force permits relative rotational or other movement while still providing a connection between the sections **1112**, **1114**. The restraint **1116** may be a wire-like connection that can be bent to a desired shape in order to permit the two generally rigid sections **1112**, **1114** to rotate relative to each other.

(91) FIG. 15A depicts a prosthetic heart valve deployment catheter **1120** configured for annuloplasty ring dilation and prosthetic heart valve deployment. The deployment catheter **1120**

has an elongated main body **1122**, a proximal end **1124**, and a distal end **1126**. The proximal end **1124** includes a handle **1128**. The distal end **1126** includes a dilation balloon **1130** upon which an expandable prosthetic valve **1132** is mounted. In the particular embodiment depicted, the prosthetic valve **1132** includes a stent **1134**. The distal end **1126** may also include one or more radiopaque markers **1133** or similar visibility markers to improve visibility of the device within the patient when using fluoroscopy or other viewing technologies.

(92) FIGS. **15B-15D** depict deployment of a prosthetic heart valve **1132** within a heart valve annulus **1136** for a heart valve **1138** where an annuloplasty ring **1010** has previously been deployed. The annuloplasty ring **1010** may have been deployed using any methods, including methods currently known in the art such as traditional (open chest) surgery, minimally-invasive (e.g., keyhole) surgery, and percutaneous surgery. The annuloplasty ring **1010** encircles the heart valve **1138**. Depending on the particular application, the annuloplasty ring **1010** can be deployed in the patient years prior to, days prior to, hours prior to, or immediately prior to deployment of the prosthetic heart valve **1132** as depicted in FIGS. **15B-15D**.

(93) FIG. **15B** depicts the prosthetic heart valve deployment catheter **1120** of FIG. **15A** with the distal end **1126** advanced so that the dilation balloon **1130** and expandable prosthetic heart valve **1132** are positioned within the heart valve **1138** in the patient's heart **1140**. The annuloplasty ring **1010** is seen in cross-section, with a cross section of the ring first portion **1010a** at the right side of the valve annulus **1136**, and a cross section of the ring second portion **1010b** at the left side of the valve annulus **1136**. Note that the ring second portion **1010b** is depicted as extending somewhat more inward with respect to the valve annulus **1134**, which might be the case where the ring **1010** is generally D-shaped and otherwise similar to that depicted in FIGS. **11A-11B** and **13A-13C**, with the ring first portion **1010a** corresponds to ring portions **1072** (FIG. **11A**), **1092** (FIG. **13A**), and the ring second portion **1010b** corresponds to ring portions **1074** (FIG. **11A**), **1094** (FIG. **13A**), respectively.

(94) In the particular embodiment depicted in FIG. **15B**, the deployment catheter **1120** has been advanced over a guide wire **1142**, which was advanced into the patient's heart **1140** and heart valve **1138** prior to advancement of the deployment catheter **1120** into the patient. Note that the use of a guide wire **1142** is optional. Other guide devices could also be used, in addition to or in lieu of a guide wire. For example, a guide catheter could be used, wherein a guide catheter is advanced to a desired position within a patient, and the deployment catheter is then advanced into the patient inside of the guide catheter until the distal end of the deployment catheter extends from a distal opening in the guide catheter. A deployment catheter could also be used without any sort of guide wire or guide catheter, so that the deployment catheter is guided by itself into the desired treatment location.

(95) As depicted in FIG. **15C**, once the dilation balloon **1130** and prosthetic heart valve **1132** are properly positioned within the heart valve annulus **1134**, the dilation balloon **1130** is expanded. The expanding dilation balloon **1130** forces the stent **1134** to expand outwardly, and crushes the native valve leaflets **1144** against the heart valve annulus **1136**. The force from the expanding dilation balloon **1130** dilates the heart valve annulus **1136**, and also forces the annuloplasty ring **1010** to expand and/or assume a more circular shape, which in the particular embodiment depicted involves displacing the ring second portion **1010b** outward to a much greater extent than the outward movement of the ring first portion **1010a**.

(96) In FIG. **15D**, the dilation balloon **1130** is deflated or otherwise reduced in diameter, with the prosthetic valve **1132** deployed in the heart valve annulus **1136** and held in place by the stent **1134**. The outward pressure from the expanded stent **1132**, along with the inward pressure from the heart valve annulus **1136**, from the now-crushed native valves **1144**, and/or from the now-dilated annuloplasty ring **1010**, combine to firmly seat the prosthetic valve **1132** in the desired position in the heart valve annulus **1136**. The deployment catheter **1120** with the dilation balloon **1130** can then be withdrawn from the heart **1140**, leaving the prosthetic heart valve **1132** in its deployed position

in the patient.

(97) In a further embodiment of the invention, the native heart valve **1138** is dilated in a separate step from deployment of the prosthetic heart valve **1132**. FIG. **16A** depicts a prosthetic heart valve deployment catheter **1120** configured for annuloplasty ring dilation and prosthetic heart valve deployment using two separate balloons, and more specifically a distal balloon **1130a** and a proximal balloon **1130b**. The distal balloon **1130a** is configured to deploy the prosthetic valve **1132**, which is positioned on the distal balloon **1130a**, whereas the proximal balloon **1130b** is configured for dilation.

(98) FIGS. **16B-16D** depict dilation of the native valve **1138**, valve annulus **1136**, and annuloplasty ring **1010** using the proximal balloon **1130b**. In FIG. **16B**, the deployment catheter **1120** has been advanced into the heart **1130** with the distal balloon **1130a** (with prosthetic valve **1132** thereon) advanced past the native heart valve **1138**, and the proximal balloon **1130b** positioned within the native heart valve **1138** and valve annulus **1136**.

(99) The proximal balloon **1130b** is inflated or otherwise expanded, as depicted in FIG. **16C**, thereby dilating the native valve **1138**, valve annulus **1136**, and annuloplasty ring **1010**. The annuloplasty ring **1010** is expanded and/or assumes a more circular form, similarly to the changes previously discussed with respect to the dilation discussed in FIG. **15C** above.

(100) After dilation of the native valve **1138**, the proximal balloon **1130b** is deflated or otherwise reduced in diameter, as depicted in FIG. **16D**. The deployment catheter **1120** may then be withdrawn from the patient until the proximal balloon **1130b** is proximal of the valve annulus **1138** and the distal balloon **1130a** is positioned within the valve annulus **1138**. The distal balloon **1130a** will be positioned within the valve annulus **1138** in a similar fashion to that depicted for balloon **1130** in FIG. **15B**. The distal balloon **1130a** will then be expanded to deploy the prosthetic valve **1132** in essentially the same manner as was discussed and depicted in FIGS. **15B-15D**. The distal balloon **1130a** will serve to deploy the prosthetic valve **1132**, and may also serve to further dilate the native valve native valve **1138**, valve annulus **1136**, and annuloplasty ring **1010**.

(101) Note that the expandable prosthetic valve may be self-expanding, in which case the deployment catheter may not have a dilation balloon as depicted in FIGS. **15A-15D** and **16A-16D**. Moreover, such a self-expanding prosthetic heart valve could be deployed with or without prior dilation of the annuloplasty ring. For example, a self-expanding prosthetic heart valve may provide sufficient outward radial force to dilate the annuloplasty ring and/or to hold the now-dilated annuloplasty ring in an expanded configuration in order to provide sufficient room for the self-expanding prosthetic heart valve in its expanded configuration.

(102) FIGS. **17A-17C** depict an annuloplasty ring prosthetic heart valve **1150** having a support frame **1152** according to a further embodiment of the invention, with the annuloplasty ring **1150** having an orifice **1154** having an inner diameter **1156a**. The support frame **1152** has a generally rigid and expansion-resistant core **1158** formed from a single core element **1160** which is bent or otherwise formed into a desired shape (which in the particular embodiment is generally circular) with opposing ends **1162a**, **1162b** meeting at a seam **1164** so as to form the complete loop around the annuloplasty ring **1150**. The seam **1164** may include adhesive, solder, welds, etc. in order to secure the two ends **1162a**, **1162b** together. The annuloplasty ring **1150** includes a covering **1166** around the support core **1158**. The covering **1166** may be a cloth-like material, and may be a sewing ring configured to be sewn to the native heart valve annulus during deployment of the annuloplasty ring **1150**. The covering **1166** is generally flexible, and may be generally elastic. The covering **1166** (or a portion thereof) may also be generally compressible, especially in the portion facing inward toward the orifice **1154**, which can assist in seating an expandable valve therein. A compressible material may be applied onto or within the covering **1166** in a position to provide a compressible region on the surface facing inward toward the orifice **1154**.

(103) When the annuloplasty ring **1150** is subject to a dilation force such as that from a dilation balloon catheter, the support frame **1152** will become non-rigid and expanded. More particularly,

the seam **1164** of the core **1158** will rupture, so that the opposing ends **1162a**, **1162b** will be separated by an opening **1168**, and the core **1158** will assume a generally C-shaped configuration as depicted in FIG. 17D. The covering **1166** will stretch or otherwise expand circumferentially to accommodate the enlarged/expanded core **1158**, and the annuloplasty ring **1150** will have an enlarged inner diameter **1156b** for the orifice **1154**. Depending on the particular embodiment, including the particular construction of the core **1158** and/or covering **1166**, the (post-dilation) annuloplasty ring **1150** may provide an inward (i.e., compressive) force toward the orifice **1154**. For example, the core **1158** may be formed of a generally resilient spring-like material and/or memory material, and may be biased somewhat toward its non-dilated configuration (i.e., with the opposing ends **1162a**, **1162b** touching each other as in FIGS. 17A-17C). The covering **1166** may also (or alternatively) be elastic and, after dilation of the annuloplasty ring **1150**, may provide an inward pull on the core **1160** so as to bias the opposing ends **1162a**, **1162b** toward each other. This inward pressure can help to seat an expandable heart valve that may be deployed within the annuloplasty ring **1150** and native heart valve. In an embodiment where compressible material is provided (e.g., as part of the covering **1166**) facing inward toward the orifice **1154**, then the compressible material can provide additional assistance in seating an expandable heart valve within the annuloplasty ring **1150**.

(104) In some procedures where an expandable prosthetic heart valve is used to replace a native valve that has a previously-deployed annuloplasty ring, it may be desirable for the expandable prosthetic heart valve to have a deployed (expanded) orifice having a cross-sectional area approximately equal to the orifice cross-sectional area of the native valve. Such consistency between orifice areas can be useful in maintaining proper blood flow, so that the expandable prosthetic heart valve will provide the same blood flow as was provided by the native heart valve. For example, Edwards Lifesciences has Sapien™ expandable prosthetic heart valves having outer diameters of 23 and 26 mm, respectively, which have corresponding inner diameters of about 20 and 23 mm, respectively, which correspond to orifice areas of about 315 and 415 square mm, respectively. Accordingly, the post-dilation orifice area of the native valve orifice with annuloplasty ring may be on the order of 315 and 415 square mm (respectively) to accommodate such expandable prosthetic heart valves. In that several embodiments of annuloplasty rings herein are generally circular in shape after dilation, the post-dilation native valve orifice will generally be circular and require diameters of about 20 and 23 mm to accommodate the above-discussed Sapien™ expandable prosthetic heart valves. The dilated native valve orifice will generally be smaller than the dilated annuloplasty ring orifice area due to portions of the native valve (such as leaflets, etc) that can project inward of the annuloplasty ring.

(105) In order to accommodate an expandable prosthetic heart valve, an annuloplasty ring according to some embodiments of the current invention will have a dilated inner orifice area that is larger by about 10%, 15%, 25%, 30%, or more than the pre-dilation inner orifice area. Where an annuloplasty ring is generally circular both prior to a after dilation, the annuloplasty ring post-dilation inner diameter may be larger by about 15%, 20%, 25%, 30%, 35%, or more than the pre-dilation inner diameter.

(106) Note that the invention is not limited to the above differences between pre- and post-dilation inner diameters and/or orifice areas of the annuloplasty ring. For example, there may be applications where much smaller and/or much larger post-dilation inner diameters may be required. In some cases an expandable prosthetic heart valve will have an outer diameter only slightly larger than its inner diameter, so that less expansion of the native valve orifice (and accordingly of the annuloplasty ring) is required in order to accommodate the expandable prosthetic heart valve. In other cases an expandable prosthetic heart valve may have an outer diameter that is much larger than its inner diameter, so that a greater expansion of the native heart valve and associated annuloplasty ring is necessary to accommodate the expandable prosthetic heart valve. There may also be applications where it may be desirable to deploy an expandable prosthetic heart valve

having a smaller or larger inner diameter than was provided by the native valve.

(107) FIGS. **18A-18B** depict a further embodiment of the invention, wherein a support frame **1170** configured for use with an annuloplasty ring (such as the ring **1150** in FIGS. **17A-17D**) according to the invention. The particular support frame **1170** is generally circular (although other shapes are within the scope of the invention) and defines an inner diameter **1172a**, and has a generally rigid core **1174** formed from a single core element **1176** which is bent or otherwise formed into a generally circular shape with opposing ends **1178a**, **1178b** which meet and connect at an overlapping section **1180** having a length **1182a**. The overlapping section **1180** may include adhesive, solder, welds, mechanical connections, ratchet-like assemblies, interacting portions, etc. in order to secure the overlapping ends **1178a**, **1178b** together. In the particular embodiment of FIGS. **18A-18B**, the overlapping section **1180** includes a sliding mechanical connection **1184** having a slot **1186** secured to one opposing end **1178a**, the second opposing end **1178b** having been passed through the slot **1186** to form the overlapping section **1180**, and also including a spring **1188** extending from the slot **1186** to the second opposing end **1178b**. The spring **1188** permits expansion and/or contraction of the support frame **1170**, with the spring **1188** generally biasing the support frame **1170** toward a smaller diameter, such as the smaller inner diameter **1172a** of FIG. **18A**. The mechanical connection **1184** also permits the support frame **1170** to be expanded when subject to an outside force such as a dilation balloon and/or expandable prosthetic valve. When the support frame is expanded **1170**, the overlapping section **1180** shortens to a smaller length **1182b**, and the inner diameter increases to a larger inner diameter **1172b** as depicted in FIG. **18B**. Note that the spring **1188** can also permit the support frame **1170** (and associated annuloplasty ring) to move with physiological annular dynamic motion, e.g., to make smaller expansions and/or contractions in response to normal valve function/heart movement as the patient's heart beats and pumps blood through the valve. The support frame **1170** may include a covering (not shown) around the core **1174**, with the covering providing a surface through which suture can be passed to secure the annuloplasty ring to the native valve annulus. The support frame **1170** may be formed of various materials, including Elgiloy. The spring **1188** can be configured to provide a specific force in opposing expansion of the support frame **1170**, and may be configured so that the force provided is insufficient to oppose the dilation force from a dilation balloon and/or expandable stent which might be expanded within the support frame **1170**. The spring **1188** could be formed from traditional coil springs, compressible materials, pleated sewing rings, accordion sewing rings, and other configurations configured to provide a spring-like force.

(108) Although a spring-like configuration that survives dilation is depicted in FIGS. **18A-18B**, other embodiments are also within the scope of the invention. For example, a support structure may have overlapping portions having interacting portions that hold the overlapping portions together, but that will temporarily release their connection to permit the relative movement of the overlapping ends when subject to a dilation force, and then for the interacting portions to re-establish their connection once the dilation force is removed so that the support frame will again be generally rigid. Such an embodiment is generally rigid prior to dilation, becomes elastically expandable during dilation, and then becomes substantially rigid again after dilation. In a further embodiment, a support frame could be formed but with the interacting portions configured so that no fixed connection is formed between the overlapping ends after dilation, so that the support frame will be generally non-rigid after the dilation force has been applied. In such an embodiment, the support frame may be configured to provide (after dilation) an inward (compressive) force upon any expandable prosthetic valve that may be deployed within the annuloplasty ring. This inward compressive force may help to seat and otherwise hold the expandable prosthetic valve in its desired position within the native valve annulus and also within the now-dilated annuloplasty ring.

(109) In another embodiment of the invention, an annuloplasty ring includes a support frame having a rigid and/or expansion-resistant core configured to separate into a plurality of pieces when subjected to a dilation force. Such a rigid and/or expansion-resistant core could be formed as a

single piece, which might include one or more weak points that are subject to separation when subjected to a dilation force. In one embodiment a rigid and/or expansion-resistant core could be formed from a plurality of segments positioned in edge-to-edge fashion and configured to separate when subjected to a dilation force. FIGS. **19A-19C** depict one such embodiment of a support frame **1190** for use with a prosthetic heart valve according to the invention. The support frame **1190** is generally circular (although other shapes are within the scope of the invention) and defines an orifice **1191** having an inner diameter **1192a**, and has a generally rigid and/or expansion-resistant core **1194** formed from multiple core segments **1196** which are arranged in edge-to-edge fashion to form the generally circular shape of the core **1194**. Each segment **1196** has an inner lumen **1198**, with the segments **1196** when assembled into the core **1194** forming a continuous core lumen **1200**. (110) Adjacent segments **1196** join at seams **1202**, which may include adhesive, solder, welds, etc. in order to secure and/or seal the seam **1202** between the adjacent segments **1196**. The support frame **1190** has a pre-dilation cord **1204** and a post-dilation cord **1206** passing through the core lumen **1200**. The pre-dilation cord **1204** may be a generally inelastic cord which is sufficiently tight to hold adjacent segments together and to prevent unwanted dilation of the support frame **1190**. A covering (not shown) may also be included to cover the core **1194**. The covering may be formed of cloth, and may be elastic.

(111) Both the seams **1202** and pre-dilation cord **1204** are configured to fail or stretch when subjected to a dilation force, such as that provided by a dilation balloon, whereupon the support frame **1190** will assume the expanded configuration depicted in FIG. **19D**, with an enlarged inner diameter **1192b**. For example, the pre-dilation cord **1204** may be an inelastic cord configured to fail when subject to a selected force, such as 1, 2, 3, 4, or more atmospheres, which are within the range of forces provided by many dilation balloons used in percutaneously-deployed heart valve procedures. In one embodiment, the seams **1202** are merely sealed, with the sealant providing little if any securement against separation of adjacent segments **1196**. In such an embodiment, the pre-dilation cord **1204** may serve as the sole device to hold the core segments **1196** together in the rigid and/or expansion-resistant (pre-dilation) configuration. Once the pre-dilation cord **1204** fails or stretches due to the dilation pressure, essentially all of the seams **1202** will separate so that adjacent segments **1196** separate with spaces **1208** separating the adjacent segments **1196**. The remaining portions of the pre-dilation cord **1204** remain within the support frame **1190** after dilation.

(112) The post-dilation cord **1206** remains intact after dilation and can serve to hold the support frame **1190** together post-dilation. The post-dilation cord **1206** could be elastic, and/or could be inelastic and have a larger diameter, and possibly a higher failure strength, than the pre-dilation cord **1204**. If the post-dilation cord **1206** is elastic, it may provide an inward compressive force into the central orifice **1191**. If the post-dilation cord **1206** is generally inelastic, it will remain intact after dilation either because its strength was too great to be ruptured by the dilation balloon or because it had a diameter that was larger than that of the inflated dilation balloon.

(113) In a variation of the embodiment of FIGS. **19A-19D**, the pre-dilation cord **1204** could be left out of the support frame **1190**, and the seams **1202** themselves could have adhesive or other connections that serve to hold the segments **1196** together prior to dilation. In a further variation, the pre-dilation cord **1194** could be left out of the support frame, with a post-dilation cord **1206** configured to be elastic and with sufficient strength/elasticity to provide an inward compressive force into the central orifice with sufficient strength to hold the segments **1196** together prior to dilation, but with the inward compressive force weak enough to permit the support frame **1190** to be dilated and to permit an expandable prosthetic heart valve to be deployed therein. Accordingly, the post-dilation cord **1206** would serve as both pre-dilation cord and post-dilation cord.

(114) Visualization references may be included on or in various portions of the device according to various embodiments of the invention. For example, visualization references may be placed on, in, or adjacent the support frame **1190**, core **1194**, segments **1196**, pre-dilation cord **1204**, and/or post-dilation cord **1206**, etc. in the device of FIGS. **19A-19D**. Such visualization references can help a

user to properly position a dilation balloon and/or expandable prosthetic heart valve within the annuloplasty ring having the support frame **1190**. For example, visualization markers positioned at the generally rigid support frame **1190** (or more specifically at the segments **1196** and/or the pre-dilation cord **1204** and/or post-dilation cord **1206**) could be used to guide delivery and expansion of a dilation balloon, and also to confirm that the support frame **1190** and annuloplasty ring have been dilated. The visualization markers could also be used to guide delivery and expansion of the expandable prosthetic heart valve within the annuloplasty ring and support frame **1190**, and to confirm proper deployment of the expandable prosthetic heart valve.

(115) The support frame **1190** may have segments **1196** having ends **1196a**, **1196b** which interlock and/or otherwise interact in order to hold the segments **1196** together and/or in alignment. As depicted in the close-up view of FIG. **19E**, adjacent segments **1196** may include interconnecting ends **1196a**, **1196b**, with one end **1196a** having a member **1197** configured to be received within the lumen **1198** or other opening in an end **1196b** of an adjacent segment **1196**. The interconnecting ends **1196a**, **1196b** keep the adjacent segments **1196** in a desired alignment so that the segment ends **1196a**, **1196b** cannot slide sideways with respect to the member **1197** and lumen **1148**, so that the general shape of the support frame **1190** is maintained. The interconnecting ends **1196a**, **1196b** do permit the adjacent segments **1196** to be pulled apart, as depicted in FIG. **19F**, in order to permit expansion of the support frame **1190** (as was depicted in FIG. **19D**). The pulling apart of the segments **1196** may be opposed by various structures set forth herein which oppose and/or restrict dilation of a support frame, such as one or more elastic and/or inelastic cords **1205** configured to oppose and/or restrict dilation of the support frame **1190** as was depicted in FIGS. **19A-19D**.

(116) Further embodiments of the invention may include an annuloplasty ring having a support frame including a core formed from segments connected end-to-end to form seams, with adjacent segments further connected via one or more individual inelastic and/or inelastic cords and elastic cords which extend only between adjacent segments. When the annuloplasty ring is subjected to a dilation force, the seams between the segments will fail and the support frame will separate into the individual segments **1172**. In one particular embodiment the inelastic cords do not serve to hold adjacent segments against each other, but instead permit adjacent segments to separate when subjected to a dilation force. The inelastic cords prevent excessive separation between any adjacent segments as the dilation balloon (or other dilation force) is applied, with the result being that the segments will all be spaced generally equally apart from each other once the full dilation force is applied. After the dilation force is removed, the elastic cords will serve to pull the adjacent segments toward each other and to provide a generally inward (compressive) pressure to the valve orifice while also permitting the post-dilation inner diameter of the annuloplasty ring to be a larger size than the pre-dilation diameter.

(117) There are many variations of the above-cited embodiments, including various combinations of the various embodiments. For example, the pre-dilation cord **1204** and/or post-dilation cord **1206** of FIGS. **19A-19D** could be used with the core **1150** of FIGS. **17A-17D** in order to provide inward compressive force after the core **1150** was dilated. The post-dilation cord **1206** of FIGS. **19A-19D** could be replaced by a cover **1158** such as that depicted in FIGS. **17A-17D**, with the cover **1158** serving to hold the post-dilation core assembly (including any segments and/or pieces thereof) together and also (if formed from elastic material) providing an inward compressive force to the orifice.

(118) Note that, depending on the particular embodiment, an annuloplasty ring according to the invention may return to its pre-dilation inner diameter and/or shape after being subject to dilation such as from a balloon catheter. However, in such an embodiment, the balloon dilation will have rendered the “post-dilation” annuloplasty ring into a generally non-rigid and/or expansion-friendly configuration, such that a “post-dilation” annuloplasty ring will be forced with relative ease into a larger diameter and/or different shape when an expandable (e.g., balloon-expandable, self-expanding, etc.) prosthetic heart valve is deployed within the valve orifice of the native valve and

annuloplasty ring.

(119) While the invention has been described with reference to particular embodiments, it will be understood that various changes and additional variations may be made and equivalents may be substituted for elements thereof without departing from the scope of the invention or the inventive concept thereof. In addition, many modifications may be made to adapt a particular situation or device to the teachings of the invention without departing from the essential scope thereof. Therefore, it is intended that the invention not be limited to the particular embodiments disclosed herein, but that the invention will include all embodiments falling within the scope of the appended claims.

Claims

1. A method of implanting a replacement prosthetic heart valve within an implanted prosthetic heart valve, comprising: accessing a first prosthetic heart valve pre-implanted in vivo at a native annulus, the first prosthetic heart valve having a support frame defining a circumferential shape surrounding a valve orifice as seen when view from above, the support frame providing circumferential support for a valve structure including a plurality of flexible heart valve leaflets that coapt against each other within the valve orifice to prevent blood flow in one direction therethrough, wherein the support frame is configured to transition from a first configuration that is expansion-resistant and has a first diameter valve orifice to a second configuration in which the valve orifice has expanded to a larger second diameter only upon being subjected to a radially expansive force of at least 1 atm, wherein the support frame is generally rigid and expansion-resistant in the first configuration and generally non-rigid and expandable in the second configuration, and wherein in the first configuration the heart valve leaflets are functional and in the second configuration the heart valve leaflets are non-functional; deploying an expandable second prosthetic heart valve within the first prosthetic heart valve; and expanding and anchoring the second prosthetic heart valve within the first prosthetic heart valve in the second configuration.
2. The method of claim 1, wherein the second prosthetic heart valve has an expanded inner diameter approximately equal to the first diameter of the first prosthetic heart valve.
3. The method of claim 1, wherein the support frame has a ring surrounding an inflow end and a plurality of commissure posts corresponding to the number of heart valve leaflets extending in an outflow direction and supporting the leaflets, and the ring includes a plurality of radiopaque visualization markers, one each circumferentially aligned with each of the commissure posts.
4. The method of claim 3, wherein the support frame defines at least one weak point configured to rupture upon being subjected to the radially expansive force and permit the support frame to transition from the first configuration to the second configuration, wherein the at least one weak point is formed by an inelastic pre-dilation cord configured to fail from the radially expansive force.
5. The method of claim 1, further including inflating a dilatation balloon in vivo to apply a radially expansive force of at least 1 atmosphere within the valve orifice to cause the support frame to transition from the first configuration to the second configuration, wherein the dilatation balloon is configured to apply a radially expansive force of between 1-6 atmospheres.
6. The method of claim 1, wherein the second diameter is 5-25% larger than the first diameter.
7. The method of claim 6, wherein the second diameter is 10-20% larger than the first diameter.
8. The method of claim 1, further including inflating a dilatation balloon in vivo to apply a radially expansive force of at least 1 atmosphere within the valve orifice to cause the support frame to transition from the first configuration to the second configuration, wherein the support frame defines at least one weak point configured to rupture upon inflation of the dilatation balloon and permit the support frame to transition from the first configuration to the second configuration.
9. The method of claim 8, wherein the at least one weak point is a seam formed by adhesive, solder,

or a weld.

10. The method of claim 1, wherein the support frame defines at least one weak point configured to rupture upon n being subjected to the radially expansive force and permit the support frame to transition from the first configuration to the second configuration, wherein the at least one weak point is formed by an inelastic pre-dilation cord configured to fail from the radially expansive force.

11. The method of claim 10, further including a post-dilation cord extending around the support frame and having a higher failure strength than the pre-dilation cord, wherein the post-dilation cord remains intact after failure of the pre-dilation cord.

12. A method of implanting a replacement prosthetic heart valve within an implanted prosthetic heart valve, comprising: accessing a first prosthetic heart valve pre-implanted in vivo at a native annulus, the first prosthetic heart valve having a support frame defining a circumferential shape surrounding a valve orifice as seen when view from above, the support frame providing circumferential support for a valve structure including a plurality of flexible heart valve leaflets that coapt against each other within the valve orifice to prevent blood flow in one direction therethrough, wherein the support frame has a weak point that is configured to rupture to transition the support frame from a first configuration that is generally rigid and expansion-resistant to a second configuration that is generally non-rigid and expandable only upon being subjected to a radially expansive force of at least 1 atm, and wherein in the first configuration the heart valve leaflets are functional and in the second configuration the heart valve leaflets are non-functional; deploying an expandable second prosthetic heart valve within the first prosthetic heart valve; and expanding and anchoring the second prosthetic heart valve within the first prosthetic heart valve in the second configuration.

13. The method of claim 12, wherein the second prosthetic heart valve has an expanded inner diameter approximately equal to the first diameter of the first prosthetic heart valve.

14. The method of claim 12, wherein the support frame has a ring surrounding an inflow end and a plurality of commissure posts corresponding to the number of heart valve leaflets extending in an outflow direction and supporting the leaflets, and the ring includes a plurality of radiopaque visualization markers, one each circumferentially aligned with each of the commissure posts.

15. The method of claim 14, wherein the at least one weak point is formed by an inelastic pre-dilation cord configured to fail from the radially expansive force.

16. The method of claim 12, further including inflating a dilatation balloon in vivo to apply a radially expansive force of at least 1 atmosphere within the valve orifice to cause the support frame to transition from the first configuration to the second configuration, wherein the dilatation balloon is configured to apply a radially expansive force of between 1-6 atmospheres.

17. The method of claim 12, wherein the second diameter is 5-25% larger than the first diameter.

18. The method of claim 12, wherein the at least one weak point is a seam formed by adhesive, solder, or a weld.

19. The method of claim 12, wherein the at least one weak point is formed by an inelastic pre-dilation cord configured to fail from the radially expansive force.

20. The method of claim 19, further including a post-dilation cord extending around the support frame and having a higher failure strength than the pre-dilation cord, wherein the post-dilation cord remains intact after failure of the pre-dilation cord.
