

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397386
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Zuo; Douquan et al.

Device and method for automatically extruding and installing electromagnetic-loaded interference threaded connection component

Abstract

A device and a method for automatically extruding and installing an electromagnetic-loaded interference threaded connection component are provided, where the device includes a base, and a U-shaped frame and a console are fixedly connected at a top of the base; the console is located inside the U-shaped frame, and an overlapping plate group is stored at a top of the console; a front of the U-shaped frame is provided with a control panel.

Inventors: Zuo; Douquan (Mianyang, CN), Liu; Jie (Chongqing, CN), Fu; Yaoming (Deyang, CN), Ma; Guoling (Yuncheng, CN), Jin; Shaoqing (Cangzhou, CN)

Applicant: CIVIL AVIATION FLIGHT UNIVERSITY OF CHINA (Deyang, CN)

Family ID: 1000008782790

Assignee: CIVIL AVIATION FLIGHT UNIVERSITY OF CHINA (Deyang, CN)

Appl. No.: 19/008862

Filed: January 03, 2025

Prior Publication Data

Document Identifier	Publication Date
US 20250135590 A1	May. 01, 2025

Foreign Application Priority Data

CN	202310624693.0	May. 30, 2023
----	----------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/CN2024/098863 20240613 PENDING child-doc US 19008862

Publication Classification

Int. Cl.: B23P19/06 (20060101)

U.S. Cl.:

CPC B23P19/06 (20130101);

Field of Classification Search

CPC: B23P (19/02); B23P (19/06); B23P (19/062)

References Cited

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
201664846	12/2009	CN	N/A
103612115	12/2013	CN	N/A
105690065	12/2015	CN	N/A
206732638	12/2016	CN	N/A
105690065	12/2017	CN	B23P 19/02
110355321	12/2018	CN	N/A
210099439	12/2019	CN	N/A
111843435	12/2019	CN	N/A
112378785	12/2020	CN	N/A
113714851	12/2020	CN	N/A
114932400	12/2021	CN	N/A
218193607	12/2022	CN	N/A
116038310	12/2022	CN	N/A
116460562	12/2022	CN	N/A
H09108958	12/1996	JP	N/A
2012086341	12/2011	JP	N/A
2015000462	12/2014	JP	N/A

OTHER PUBLICATIONS

Kang, Yong-Gang; CN-105690065-B Machine Translation (Year: 2016). cited by examiner
Zhang Yanzhao , Cao Zengqiang , Qiu Jianping , Zheng Pengyu, “Analyzing Factors that Influence the Installation Quality of Interference-fit Hi-lock Bolt Connection” Mechanical Science and Technology for Aerospace Engineering No. 8, Aug. 15, 2012 (Aug. 15, 2012), Full Text. cited by applicant

Yang Xiaona et al. “Experimental study on the installation process of titanium alloy interference bolts based on stress wave loading” Journal of Northwestern Polytechnical University, vol. 35, No. 3, Jun. 30, 2017 (Jun. 30, 2017), pp. 462-468, ISSN: 1000-2758, p. 462, Section 1.1 to p. 463, Section 2.1. cited by applicant

Primary Examiner: Holly; Lee A

Attorney, Agent or Firm: JEEN IP LAW, LLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of PCT/CN2024/098863, filed on Jun. 13, 2024 and claims priority of Chinese Patent Application No. 202310624693.0, filed on May 30, 2023, the entire contents of which are incorporated herein by reference.

TECHNICAL FIELD

(1) The disclosure relates to the technical field of threaded connection component extrusion, and in particular to a device and a method for automatically extruding and installing an electromagnetic-loaded interference threaded connection component.

BACKGROUND

(2) Electromagnetic-loaded means that the capacitor is used for charging, and the capacitor is discharged with the setting of the required voltage. The coil of the driving head passes through the current, forming eddy current, generating magnetic field, and the magnetic force is repelled at the same level, generating driving force, impacting the high lock bolt and forming automatic extrusion installing. When two composite laminates or titanium alloy plates for aviation are overlapped in different kinds, electromagnetic-loaded equipment is generally used for interference connection, which is also called interference fit assembly.

(3) Interference of interference extrusion installing refers to the fit between bolt interference fit polished rod part and connecting plate hole; the diameter of the polished rod is a little larger than the hole. For the traditional pneumatic loading mode, the general interference amount of metal interference installing is 0.05%-1.5%, and the general interference amount of composite material installing is 0.05%-1.2%. Interference amount is the percentage of the difference between the hole diameter and the polished rod diameter and the polished rod diameter. However, the existing electromagnetic-loaded extrusion devices mostly use electromagnetic-loaded guns to impact the high-lock bolts. By clicking the discharge button, millisecond impact loading may be carried out, which will realize the interference extrusion installing of the bare rod part of the high-lock bolts on two overlapping plates, and the maximum interference amount of interference installing may reach 2.5%.

(4) In the related art, the existing electromagnetic-loaded gun has some defects in the process of extruding and installing the overlapping plate. For example, when the electromagnetic-loaded gun impacts the high lock bolt, the stability and positioning between the high lock bolt and the overlapping plate cannot be guaranteed. However, in the prior art, although there is a fixing mechanism for fastening the overlapping plate, the fastening mechanism may not realize the synchronous positioning processing of the high lock bolt and the overlapping plate, so that the high lock bolt is prone to slight deviation or the high lock bolt may not accurately correspond to the connecting hole on the overlapping plate during electromagnetic-loaded impact, thereby reducing the subsequent interference fit assembly effect.

SUMMARY

(1) Technical Problems to be Solved

(5) Aiming at the shortcomings of the prior art, the disclosure provides a device and a method for automatically extruding and installing an electromagnetic-loaded interference threaded connection component, which not only clamp the two sides of stacked overlapping plates, but also position the connecting holes of multiple overlapping plates, so as to ensure that the connecting holes overlap and improve the positioning of subsequent high-lock bolt insertion. The arrangement of the impact assembly may elastically position and clamp the end cap part of the high lock bolt, so as to ensure the stability of the high lock bolt and ensure the high lock bolt to be vertically downward, and avoid the problem that the high lock bolt inclines and affects the interference fit assembly effect.

(2) Technical Scheme

(6) In order to achieve the above purpose, the disclosure provides the following technical scheme: a device for automatically extruding and installing an electromagnetic-loaded interference threaded connection component, including a base, where a U-shaped frame and a console are fixedly connected at a top of the base; the console is located inside the U-shaped frame, and an overlapping plate group is stored at a top of the console; a front of the U-shaped frame is provided with a control panel, a lifting plate is connected between two sides of an inner wall of the U-shaped frame in a sliding way, an electromagnetic-loaded assembly is arranged on the lifting plate, both sides of a top of the U-shaped frame are fixedly connected with first electric telescopic rods, and telescopic ends of the two first electric telescopic rods are fixed on a top of the lifting plate; where an impact end of the electromagnetic-loaded assembly is detachably provided with an impact assembly for positioning a high lock bolt, and both sides of a bottom of the lifting plate are provided with reinforcing assemblies for fastening the overlapping plate group located on the console; clamping plates for clamping two sides of the overlapping plate group are slidably connected to both sides of the top of the console, and a bottom of the U-shaped frame is provided with a driving assembly for horizontally driving two groups of the clamping plates; an inside of the base is fixedly connected with a sleeve, and an inside of the sleeve is provided with a positioning assembly for positioning connecting holes on the overlapping plate group; the console is internally provided with a through hole.

(7) Optionally, the electromagnetic-loaded assembly includes a housing fixed in the lifting plate; a movable plate and a driving plate are respectively arranged in the housing, and an impact head is installed at a bottom of the driving plate; a bottom of the impact head is provided with a installing hole, and an inside of the installing hole is provided with internal threads; an inner surface of the installing hole is fixedly connected with a T-shaped impact rod, and a bottom end of the T-shaped impact rod extends to a bottom of the installing hole; a tension spring is fixedly connected between a top of the T-shaped impact rod and a top of the installing hole.

(8) Optionally, opposite sides of the movable plate and the driving plate are respectively provided with a loading coil and an induction coil, and multiple buffers are arranged between a top of the movable plate and a top of an inner wall of the housing; an inside of the impact head is provided with a guiding groove; an inside of the guiding groove is connected with a guiding plate in a sliding way, and a top of the guiding plate is fixedly connected with a guiding rod; a top end of the guiding rod is fixed on the top of the inner wall of the housing.

(9) Optionally, the impact assembly includes an annular plate, and a top of the annular plate is fixedly connected with a threaded sleeve inserted into the installing hole; a bottom of the annular plate is provided with at least three hidden openings, and an outer surface of the annular plate is provided with three movable grooves; the bottom of the annular plate is fixedly connected with three abutting rods, and positioning pieces are arranged in the three movable grooves.

(10) Optionally, each of the positioning pieces includes a rotating shaft rotating in each of the movable groove; an outer surface of the rotating shaft is fixedly connected with a T-shaped block; a bottom of the T-shaped block is fixedly connected with a V-shaped positioning block; a rotating end of the rotating shaft is provided with a torsion spring.

(11) Optionally, each of the reinforcing assemblies includes a U-shaped frame fixed on a side of the bottom of the lifting plate; an inside of the U-shaped frame is slidably connected with a moving block, and a bottom of the moving block is fixedly connected with an L-shaped reinforcing block; a bottom of the L-shaped reinforcing block extends to a bottom of the U-shaped frame, and one side of the L-shaped reinforcing block is set as an inclined surface; a compression spring is fixedly connected between a top of the moving block and a top of an inner wall of the U-shaped frame.

(12) Optionally, the positioning assembly includes a sliding block sliding inside the sleeve; a top of the sliding block is detachably provided with a positioning rod; a top end of the positioning rod extends to an outside of the sleeve, and the top end of the positioning rod is arranged in a

chamfered shape; a bottom of the sleeve is fixedly connected with a telescopic cylinder, and a telescopic end of the telescopic cylinder is fixedly connected with a bottom of the sliding block; and the top of the sliding block is provided with a threaded hole, and a bottom of the positioning rod is provided with external threads.

(13) A method for automatically extruding and installing an electromagnetic-loaded interference threaded connection component is provided, including following steps: S1, firstly, stacking two overlapping plates or three overlapping plates to be extruded and installed, overlapping the connecting holes on multiple overlapping plates to form an overlapping plate group, and driving the sliding block to be inserted into the connecting holes by overlapping multiple the overlapping plates through the telescopic cylinder for positioning; S2, driving two groups of clamping plates to move in opposite directions through a driving assembly, clamping and reinforcing a whole body at both sides of the overlapping plate group, and after clamping and fixing, driving the positioning rod to retract downwards and hide through the telescopic cylinder; S3, inserting an end cap part of a high lock bolt required for an extrusion installing into an impact assembly, and driving a T-shaped block to turn down through an arrangement of a torsion spring, thereby driving a V-shaped positioning block to turn down to position and clamp the end cap part of the high lock bolt; S4, driving a lifting plate to move downwards through two first electric telescopic rods, and further driving an electromagnetic-loaded assembly and two reinforcing assemblies to move downwards; through downward movement of the two reinforcing assemblies, further positioning and clamping a position of the extrusion installing of the overlapping plate group, and inserting a threaded section of the high lock bolt into the connecting hole on the overlapping plates; and S5, finally, charging the capacitor with required voltage through a cable, and inducing eddy current by a loading coil when discharging to form a magnetic field; by using electromagnetic repulsion generated between the loading coil and an induction coil, moving the induction coil and an impact head downward to form millisecond impact loading; finally, performing the extrusion installing of the high locking bolt in the impact assembly in the connecting holes on the overlapping plate group, so as to form an installing work of the electromagnetic-loaded interference threaded connection component.

(3) Beneficial Effects

(14) Compared with the prior art, the disclosure provides a device and a method for automatically extruding and installing an electromagnetic-loaded interference threaded connection component, which have the following beneficial effects.

(15) First, according to the disclosure, the driving assembly drives two groups of clamping plates in opposite directions, so that both sides of stacked overlapping plates are clamped, and the stability of extrusion installing is improved; moreover, the positioning assembly is used for inserting into the connecting holes of the overlapping plates and positioning the connecting holes of multiple overlapping plates, so that the overlapping treatment of the connecting holes is ensured, and the positioning of subsequent high-lock bolt insertion is improved; and through the arrangement of the impact assembly, the end cap part of the high lock bolt is elastically positioned and clamped, so that the stability of the high lock bolt is ensured, the high lock bolt is ensured to be vertically downward, and the problem that the high lock bolt inclines and affects the interference fit assembly effect is avoided.

(16) Second, according to the disclosure, the two reinforcing assemblies are installed at the bottom of the lifting plate in a symmetrical way, so that when the lifting plate moves downwards, not only the electromagnetic-loaded assembly is driven to move downwards, but also the two reinforcing assemblies are driven to move downwards synchronously, so that the L-shaped reinforcing blocks in the two reinforcing assemblies are used for pressing and positioning the two sides of the installing position of the overlapping plate group, which has the function of synchronous positioning processing, effectively avoiding the problem that the overlapping plate group deviates during extrusion installing, which affects the interference fit assembly effect, and further improving

the extrusion installing.

(17) Third, according to the disclosure, the telescopic cylinder drives the sliding block up and down, so that the positioning rod is driven to move up and down; through the upward movement of the positioning rod, the positioning rod is inserted into the connecting hole on the overlapping plate group through the through hole to form positioning treatment; moreover, because the positioning rod and the sliding block are detachably installed, it is convenient for workers to replace different types of positioning rods according to the inner diameters of the connecting holes of different overlapping plate groups, and the positioning treatment of different types of overlapping plate groups is met.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a schematic structural diagram of a device for automatically extruding and installing an electromagnetic-loaded interference threaded connection component proposed by the disclosure.
- (2) FIG. 2 is a structural side view of a device for automatically extruding and installing an electromagnetic-loaded interference threaded connection component proposed by the disclosure.
- (3) FIG. 3 is a schematic diagram of the combination of a U-shaped frame and a console in a device for automatically extruding and installing an electromagnetic-loaded interference threaded connection component proposed by the disclosure.
- (4) FIG. 4 is a schematic structural diagram of a lifting plate in a device for automatically extruding and installing an electromagnetic-loaded interference threaded connection component.
- (5) FIG. 5 is a schematic assembly diagram of an electromagnetic-loaded assembly and an impact assembly in a device for automatically extruding and installing an electromagnetic-loaded interference threaded connection component proposed by the disclosure.
- (6) FIG. 6 is a structural sectional view of an electromagnetic-loaded assembly in a device for automatically extruding and installing an electromagnetic-loaded interference threaded connection component proposed by the disclosure.
- (7) FIG. 7 is a schematic structural diagram of an impact assembly in a device for automatically extruding and installing an electromagnetic-loaded interference threaded connection component proposed by the disclosure.
- (8) FIG. 8 is an exploded view of the structure of the impact assembly in a device for automatically extruding and installing an electromagnetic-loaded interference threaded connection component proposed by the disclosure.
- (9) FIG. 9 is a structural bottom view of an annular plate in a device for automatically extruding and installing an electromagnetic-loaded interference threaded connection component proposed by the disclosure.
- (10) FIG. 10 is a schematic structural diagram of a console in a device for automatically extruding and installing an electromagnetic-loaded interference threaded connection component proposed by the disclosure.
- (11) FIG. 11 is a structural bottom view of a console in a device for automatically extruding and installing an electromagnetic-loaded interference threaded connection component proposed by the disclosure.
- (12) FIG. 12 is a schematic structural diagram of a driving assembly in a device for automatically extruding and installing an electromagnetic-loaded interference threaded connection component proposed by the disclosure.
- (13) FIG. 13 is a schematic structural diagram of a positioning assembly in a device for automatically extruding and installing an electromagnetic-loaded interference threaded connection component proposed by the disclosure.

(14) In the figures: **1.** base; **2.** U-shaped frame; **3.** console; **4.** overlapping plate group; **5.** lifting plate; **6.** electromagnetic-loaded assembly; **61.** housing; **62.** movable plate; **63.** driving plate; **64.** impact head; **65.** installing hole; **66.** T-shaped impact rod; **67.** tension spring; **68.** loading coil; **69.** induction coil; **610.** buffer; **611.** guiding groove; **612.** guiding plate; **613.** guiding rod; **7.** impact assembly; **71.** annular plate; **72.** threaded sleeve; **73.** movable groove; **74.** abutting rod; **75.** rotating shaft; **76.** T-shaped block; **77.** V-shaped positioning block; **8.** reinforcing assembly; **81.** U-shaped frame; **82.** moving block; **83.** L-shaped reinforcing block; **84.** compression spring; **9.** clamping plate; **10.** driving assembly; **101.** guiding rod; **102.** sliding frame; **103.** second electric telescopic rod; **104.** connecting frame; **105.** conversion plate; **11.** sleeve; **12.** positioning assembly; **121.** sliding block; **122.** positioning rod; **123.** telescopic cylinder; **13.** through hole; **14.** high lock bolt; **15.** first electric telescopic rod.

DESCRIPTION OF EMBODIMENTS

(15) In the following, the technical scheme in the embodiment of the disclosure will be clearly and completely described with reference to the attached drawings. Obviously, the described embodiment is only a part of the embodiment of the disclosure, but not the whole embodiment. Based on the embodiments in the present disclosure, all other embodiments obtained by ordinary technicians in the field without creative labor belong to the scope of protection of the present disclosure.

Embodiment 1

(16) As shown in FIG. 1-FIG. 13, a device for automatically extruding and installing an electromagnetic-loaded interference threaded connection component includes a base **1**, where a U-shaped frame **2** and a console **3** are fixedly connected at a top of the base **1**; the console **3** is located inside the U-shaped frame **2**, and an overlapping plate group **4** is stored at a top of the console **3**; a front of the U-shaped frame **2** is provided with a control panel, a lifting plate **5** is connected between two sides of an inner wall of the U-shaped frame **2** in a sliding way, an electromagnetic-loaded assembly **6** is arranged on the lifting plate **5**, both sides of a top of the U-shaped frame **2** are fixedly connected with first electric telescopic rods **15**, and telescopic ends of the two first electric telescopic rods **15** are fixed on a top of the lifting plate **5**; where an impact end of the electromagnetic-loaded assembly **6** is detachably provided with an impact assembly **7** for positioning a high lock bolt **14**, and both sides of a bottom of the lifting plate **5** are provided with reinforcing assemblies **8** for fastening the overlapping plate group **4** located on the console **3**; clamping plates **9** for clamping two sides of the overlapping plate group **4** are slidably connected to both sides of the top of the console **3**, and a bottom of the U-shaped frame **2** is provided with a driving assembly **10** for horizontally driving two groups of the clamping plates **9**; an inside of the base **1** is fixedly connected with a sleeve **11**, and an inside of the sleeve **11** is provided with a positioning assembly **12** for positioning connecting holes on the overlapping plate group **4**; the console **3** is internally provided with a through hole **13**.

(17) By driving the two groups of clamping plates **9** in opposite directions by the driving assembly **10**, the two sides of the stacked overlapping plates are clamped, and the positioning assembly **12** is arranged to be inserted into the connecting holes of the overlapping plates to position the connecting holes of multiple overlapping plates, thereby improving the overlapping effect of the connecting holes.

(18) Through the downward impact of the electromagnetic-loaded assembly **6** on the impact assembly **7**, the high lock bolt **14** below the impact assembly **7** is punched into the connecting holes on multiple overlapping plates, and the impact assembly **7** may also elastically position and clamp the end cap part of the high lock bolt **14**, so as to ensure the stability of the high lock bolt **14** and the vertical downward direction of the high lock bolt **14**, and avoid the problem that the high lock bolt **14** inclines and affects the interference fit assembly effect.

(19) The center of the through hole **13** coincides with the axes of the electromagnetic-loaded assembly **6** and the impact assembly **7**, so as to improve the positioning of subsequent extrusion

installing.

(20) The overlapping plate group **4** is multiple stacked overlapping plates, preferably two or three, and one side of each overlapping plate is provided with a connecting hole, which is convenient for subsequent extrusion installing by the high lock bolt **14**.

(21) As shown in FIG. **6**, the electromagnetic-loaded assembly **6** includes a housing **61** fixed in the lifting plate **5**; a movable plate **62** and a driving plate **63** are respectively arranged in the housing **61**, and an impact head **64** is installed at a bottom of the driving plate **63**; a bottom of the impact head **64** is provided with a installing hole **65**, and an inside of the installing hole **65** is provided with internal threads; an inner surface of the installing hole **65** is fixedly connected with a T-shaped impact rod **66**, and a bottom end of the T-shaped impact rod **66** extends to a bottom of the installing hole **65**; a tension spring **67** is fixedly connected between a top of the T-shaped impact rod **66** and a top of the installing hole **65**.

(22) The installing hole **65** facilitates the detachable installing of the impact assembly **7** and the impact head **64**, and the T-shaped impact rod **66** is arranged to press the protruding parts on one side of the three T-shaped blocks **76** in the impact assembly **7**, so that the three T-shaped blocks **76** turn over and lose contact with the high lock bolt **14**, so as to facilitate the extrusion installing of the high lock bolt **14**, and the T-shaped impact rod **66** is driven to reset by the tension of the tension spring **67** itself;

(23) When the impact head **64** impacts downwards, the T-shaped impact rod **66** will move downwards, and the tension spring **67** will form a certain force storage. After the impact head **64** moves downwards, the T-shaped impact rod **66** is inserted into the annular plate **71** by the inertia of the downward movement, and the protruding parts of the three T-shaped blocks **76** are pressed.

(24) As shown in FIG. **6**, opposite sides of the movable plate **62** and the driving plate **63** are respectively provided with a loading coil **68** and an induction coil **69**, and multiple buffers **610** are arranged between a top of the movable plate **62** and a top of an inner wall of the housing **61**; an inside of the impact head **64** is provided with a guiding groove **611**; an inside of the guiding groove **611** is connected with a guiding plate **612** in a sliding way, and a top of the guiding plate **612** is fixedly connected with a guiding rod **613**; a top end of the guiding rod **613** is fixed on the top of the inner wall of the housing **61**.

(25) The electromagnetic-loaded assembly **6** further includes an input power supply, a boosting transformer, a rectifying element, a current-limiting resistor and a capacitor arranged on the housing **61**. When in use, it is only necessary to charge the capacitor after the input power is boosted by the boosting transformer and rectified by the rectifier element, and discharge the loading coil **68** through the cable after the discharge switch is closed after reaching the specified voltage; the electromagnetic repulsion generated between the loading coil **68** and the induction coil **69** moves the induction coil **69** and the impact head **64** downward to form millisecond impact loading. Through the downward movement of the impact head **64**, the high lock bolt **14** in the impact assembly **7** is extruded and installed in the connecting holes of the overlapping plate group **4** to form the extrusion installing of multiple overlapping plates.

(26) The guiding rod **613** is arranged to improve the guiding function of the impact head **64**, and the guiding rod **613** slides in the guiding groove **611** with the guiding plate **612**, so as to further improve its guiding effect and electromagnetic impact effect. The buffer **610** adopts the buffer mechanism of the prior art, which is used for buffering the high speed during loading, and preventing the device from moving forward greatly during loading, so that the recoil force is greatly reduced and the damage is prevented.

(27) Referring to FIG. **7**-FIG. **8**, the impact assembly **7** includes an annular plate **71**, and a top of the annular plate **71** is fixedly connected with a threaded sleeve **72** inserted into the installing hole **65**; a bottom of the annular plate **71** is provided with at least three hidden openings, and an outer surface of the annular plate **71** is provided with three movable grooves **73**; the bottom of the annular plate **71** is fixedly connected with three abutting rods **74**, and positioning pieces are

arranged in the three movable grooves **73**.

(28) The arrangement of the threaded sleeve **72** is used to screw into the installing hole **65** on the electromagnetic-loaded assembly **6**, so that the impact assembly **7** and the impact end of the electromagnetic-loaded assembly is detachably installed, which is convenient for workers to replace different types of impact assemblies **7** according to different types of high lock bolts **14**, and has good disassembly and replacement functions;

(29) The arrangement of three positioning pieces is used to elastically position and clamp the end cap part of the high lock bolt **14** to ensure the stability of the high lock bolt **14**. Through the arrangement of the three abutting rods **74**, the end cap part of the high lock bolt **14** used for positioning and clamping is abutted to ensure that the high lock bolt **14** is vertically downward, and the problem that the high lock bolt **14** is inclined is avoided.

(30) As shown in FIG. 7-FIG. 8, each of the positioning pieces includes a rotating shaft **75** rotating in each of the movable groove **73**; an outer surface of the rotating shaft **75** is fixedly connected with a T-shaped block **76**; a bottom of the T-shaped block **76** is fixedly connected with a V-shaped positioning block **77**; a rotating end of the rotating shaft **75** is provided with a torsion spring.

(31) The T-shaped block **76** is driven to turn down by the torsion spring, and then the V-shaped positioning block **77** is driven to turn down; when the T-shaped block **76** is turned down, the protruding part on one side of the T-shaped block **76** will be inserted into the hidden opening; the hole of the annular plate **71** is shielded by the protruding parts of the three T-shaped blocks **76**, which is convenient for the impact of the T-shaped impact rod **66** in the electromagnetic-loaded assembly **6**.

(32) The downward impact of the T-shaped impact rod **66** may extrude the protruding parts of the three T-shaped blocks **76**, so that the three T-shaped blocks **76** are reversed and lose the positioning and clamping of the end cap of the high lock bolt **14**; and the inner surfaces of the three V-shaped positioning blocks **77** are all arc-shaped, so that the high lock bolt **14** is smoothly separated from the three V-shaped positioning blocks **77** during impact loading.

(33) By turning the three V-shaped positioning blocks **77** downward, the end cap part of the high lock bolt **14** is positioned and clamped, which not only ensures the stability of the high lock bolt **14**, but also facilitates the coincidence of the high lock bolt **14** and the connecting holes on the overlapping plate group **4**, and improves the positioning of the subsequent extrusion installing.

(34) As shown in FIG. 12, the driving assembly **10** includes two guiding rods **101** fixed between the two sides of the inner wall of the U-shaped frame **2**, and two sliding frames **102** are slidably connected between the outer surfaces of the two guiding rods **101**; the tops of the two sliding frames **102** are respectively fixedly connected with the bottoms of the two groups of clamping plates **9**; there are two groups of chutes for the horizontal sliding of the sliding frame **102** in the console **3**. One side of the inner wall of the U-shaped frame **2** is fixedly connected with a second electric telescopic rod **103**, and the telescopic end of the second electric telescopic rod **103** is fixedly connected with one of the sliding frames **102**; a connecting frame **104** is rotatably connected to the bottom of the two sliding frames **102**, and a conversion plate **105** is hinged between one end of the two connecting frames **104**. The conversion plate **105** rotates on the outer surface of the sleeve **11**.

(35) The second electric telescopic rod **103** is connected with an external power supply and a control switch for driving one of the sliding frames **102** to slide horizontally; a connecting frame **104** is rotatably connected to the bottom of the two sliding frames **102**, and a conversion plate **105** is hinged between the two connecting frames **104**, so that one of the sliding frames **102** may drive one of the connecting frames **104** to move in a fan shape when sliding; and through the arrangement of the conversion plate **105**, the fan-shaped motion force is transmitted to another connecting frame **104** to form a fan-shaped motion, and finally the other sliding frame **102** is driven to move horizontally, and the two sliding frames **102** slide symmetrically.

(36) Through the relative movement of the two sliding frames **102**, two groups of clamping plates **9**

is driven to move in the opposite direction, so as to clamp and reinforce the whole body on both sides of the overlapping plate group **4**, improve the stability of extrusion installing, and synchronously drive the two groups of clamping plates **9**, which not only avoids the installing of multiple electric drivers, but also improves the synchronization of fastening the overlapping plate group **4**, and prevents the center of the connecting hole on the fastened overlapping plate group **4** from overlapping with the through hole **13**, thus affecting the high lock.

(37) The disclosure also relates to a method for automatically extruding and installing an electromagnetic-loaded interference threaded connection component, including following steps: S1, firstly, stacking two overlapping plates or three overlapping plates to be extruded and installed, overlapping the connecting holes on multiple overlapping plates to form an overlapping plate group **4**, and driving the sliding block **121** to be inserted into the connecting holes by overlapping multiple the overlapping plates through the telescopic cylinder **123** for positioning; S2, driving two groups of clamping plates **9** to move in opposite directions through a driving assembly **10**, clamping and reinforcing a whole body at both sides of the overlapping plate group **4**, and after clamping and fixing, driving the positioning rod **122** to retract downwards and hide through the telescopic cylinder **123**; S3, inserting an end cap part of a high lock bolt required for an extrusion installing into an impact assembly **7**, and driving a T-shaped block **76** to turn down through an arrangement of a torsion spring, thereby driving a V-shaped positioning block **77** to turn down to position and clamp the end cap part of the high lock bolt; S4, driving a lifting plate **5** to move downwards through two first electric telescopic rods **15**, and further driving an electromagnetic-loaded assembly **6** and two reinforcing assemblies **8** to move downwards; through downward movement of the two reinforcing assemblies **8**, further positioning and clamping a position of the extrusion installing of the overlapping plate group **4**, and inserting a threaded section of the high lock bolt **14** into the connecting hole on the overlapping plates; and S5, finally, charging the capacitor with required voltage through a cable, and inducing eddy current by a loading coil **68** when discharging to form a magnetic field; by using electromagnetic repulsion generated between the loading coil **68** and an induction coil **69**, moving the induction coil **69** and an impact head **64** downward to form millisecond impact loading; finally, performing the extrusion installing of the high locking bolt **14** in the impact assembly **7** in the connecting holes on the overlapping plate group **4**, so as to form an installing work of the electromagnetic-loaded interference threaded connection component.

(38) The working principle of a device for automatically extruding and installing an electromagnetic-loaded interference threaded connection component is as follows: S1, firstly, two overlapping plates or three overlapping plates to be extruded and installed are stacked to form an overlapping plate group **4**, and during the stacking process, the connecting holes on multiple overlapping plates are overlapped, the telescopic cylinder **123** is stated to drive the sliding block **121** to move up and down; through the upward movement of the sliding block **121**, the positioning rod **122** is driven to be inserted into the overlapping connecting holes of multiple overlapping plates through the through hole **13** for positioning; S2, by starting the second electric telescopic rod **103**, one of the sliding frames **102** is driven to slide horizontally, and the bottom of both sliding frames **102** are connected with a connecting frame **104** in a rotating way, and a conversion plate **105** is hinged between the two connecting frames **104**, so that one sliding frame **102** may drive the other sliding frame **102** to move horizontally when sliding; and the two sliding frames **102** slide symmetrically, so that the two groups of clamping plates **9** are driven to move in the opposite direction through the movement of the two sliding frames **102** in the opposite direction, thereby clamping and reinforcing the whole body on both sides of the overlapping plate group **4**; after clamping and fixing, through the telescopic cylinder **123** drives the positioning rod **122** to retract and hide; S3, the end cap part of the high lock bolt **14** required for extrusion installing is inserted into the impact assembly **7**, and through the arrangement of the torsion spring, the T-shaped block **76** is driven to turn down, and then the V-shaped positioning block **77** is driven to turn down; the

end cap part of the high lock bolt **14** is positioned and clamped by the downward turning of the three V-shaped positioning blocks **77** to ensure the positioning and verticality; S4, the lifting plate is driven to move up and down by starting the two first electric telescopic rods **15**, and the electromagnetic-loaded assembly **6** and the two reinforcing assemblies **8** are driven to move down by the downward movement of the lifting plate; through the downward movement of the two reinforcing assemblies **8**, the overlapping plate group **4** is further positioned and clamped, and the downward movement of the electromagnetic-loaded assembly **6** may make the high lock bolt **14** located in the connecting holes on the overlapping plates; and S5, finally, the input power is boosted by the boosting transformer and rectified by the rectifier element to charge the capacitor; after reaching the specified voltage, the discharge switch is closed, and the loading coil **68** is discharged through the cable; the electromagnetic repulsion generated between the loading coil **68** and the induction coil **69** moves the induction coil **69** and the impact head **64** downward to form millisecond impact loading; through the downward movement of the impact head **64**, the high lock bolt **14** in the impact assembly **7** is extruded and installed in the connecting hole of the overlapping plate group **4**, thus forming the extrusion installing of multiple overlapping plates.

Embodiment 2

Different from Embodiment 1

(39) as shown in FIG. **4**, each of the reinforcing assemblies **8** includes a U-shaped frame **81** fixed on a side of the bottom of the lifting plate **5**; an inside of the U-shaped frame **81** is slidably connected with a moving block **82**, and a bottom of the moving block **82** is fixedly connected with an L-shaped reinforcing block **83**; a bottom of the L-shaped reinforcing block **83** extends to a bottom of the U-shaped frame **81**, and one side of the L-shaped reinforcing block **83** is set as an inclined surface; a compression spring **84** is fixedly connected between a top of the moving block **82** and a top of an inner wall of the U-shaped frame **81**.

(40) The moving block **82** is extruded by the elastic force of the compression spring **84**, so that the moving block **82** moves downwards, and the L-shaped reinforcing block **83** is driven to move downwards by the downward movement of the moving block **82**. The L-shaped reinforcing block **83** is used for pressing the connection position of the combined overlapping plate group **4**, so as to avoid the deviation of the overlapping plate group **4** in the squeezing installing process and affect the squeezing installing effect. Because one side of the two L-shaped reinforcing blocks **83** is set as an inclined surface, it is convenient to form a mutual squeezing force on both sides of the overlapping plate group **4** during the pressing process, so as to ensure the stability of two overlapped overlapping plates.

(41) There are two reinforcing assemblies **8**, which are symmetrically installed at the bottom of the lifting plate **5**, so that when the lifting plate moves downwards, the electromagnetic-loaded assembly **6** and the two reinforcing assemblies **8** are all driven to move downwards, so that both sides of the installing position of the overlapping plate group **4** are pressed and positioned by the two reinforcing assemblies **8**, so as to avoid the offset of the overlapping plate group **4** in the extrusion installing process and affect the extrusion installing effect, further improve its extrusion installing positioning and reduce the extrusion installing error.

Embodiment 3

Different from Embodiment 1

(42) as shown in FIG. **13**, the positioning assembly **12** includes a sliding block **121** sliding inside the sleeve **11**; a top of the sliding block **121** is detachably provided with a positioning rod **122**; a top end of the positioning rod **122** extends to an outside of the sleeve **11**, and the top end of the positioning rod **122** is arranged in a chamfered shape; a bottom of the sleeve **11** is fixedly connected with a telescopic cylinder **123**, and a telescopic end of the telescopic cylinder **123** is fixedly connected with a bottom of the sliding block **121**; and the top of the sliding block **121** is provided with a threaded hole, and a bottom of the positioning rod **122** is provided with external threads.

- (43) The diameter of the positioning rod **122** is equal to the inner diameter of the connecting holes on the overlapping plate group **4**, and is used for overlapping and positioning the connecting holes on the overlapping plate group **4** to ensure the stability of subsequent installing. And the positioning rod **122** is detachably installed with the sliding block **121**, so that workers may conveniently replace different types of positioning rods **122** according to the inner diameters of the connecting holes of different overlapping plate groups **4**, and the positioning processing of different types of overlapping plate groups **4** is met; the bottom end of the positioning rod **122** is just screwed into the threaded hole at the top of the sliding block **121**, so as to form the threaded installing of the positioning rod **122**, and conversely, the positioning rod **122** is disassembled.
- (44) The telescopic cylinder **123** is connected with an external power supply and a control switch for driving the sliding block **121** to move up and down; the up-and-down movement of the sliding block **121** may drive the positioning rod **122** to move up and down; through the upward movement of the positioning rod **122**, the positioning rod **122** is inserted into the connecting hole of the overlapping plate group **4** through the through hole **13** to form the positioning treatment, and on the contrary, the positioning rod **122** is retracted downward into the sleeve **11**, thus facilitating the installing of the overlapping plate group **4**.
- (45) It should be noted that the term “including” or any other variation thereof is intended to cover non-exclusive inclusion, so that a process, method, article or equipment including a series of elements includes not only those elements, but also other elements not explicitly listed, or elements inherent to such process, method, article or equipment. Without further restrictions, an element defined by the phrase “including one” does not exclude the existence of other identical elements in the process, method, article or equipment including the element.
- (46) Although embodiments of the present disclosure have been shown and described, it will be understood by those skilled in the art that various changes, modifications, substitutions and variations may be made to these embodiments without departing from the principles and spirit of the present disclosure, the scope of which is defined by the appended claims and their equivalents.

Claims

1. A device for automatically extruding and installing an electromagnetic-loaded interference threaded connection component, comprising: a base (**1**), wherein a U-shaped frame (**2**) and a console (**3**) are fixedly connected at a top of the base (**1**); the console (**3**) is located inside the U-shaped frame (**2**), and an overlapping plate group (**4**) is stored at a top of the console (**3**); a front of the U-shaped frame (**2**) is provided with a control panel, a lifting plate (**5**) is connected between two sides of an inner wall of the U-shaped frame (**2**) in a sliding way, an electromagnetic-loaded assembly (**6**) is arranged on the lifting plate (**5**), both sides of a top of the U-shaped frame (**2**) are fixedly connected with first electric telescopic rods (**15**), and telescopic ends of the two first electric telescopic rods (**15**) are fixed on a top of the lifting plate (**5**); wherein an impact end of the electromagnetic-loaded assembly (**6**) is detachably provided with an impact assembly (**7**) for positioning a high lock bolt (**14**), and both sides of a bottom of the lifting plate (**5**) are provided with reinforcing assemblies (**8**) for fastening the overlapping plate group (**4**) located on the console (**3**); clamping plates (**9**) for clamping two sides of the overlapping plate group (**4**) are slidably connected to both sides of the top of the console (**3**), and a bottom of the U-shaped frame (**2**) is provided with a driving assembly (**10**) for horizontally driving two groups of the clamping plates (**9**); an inside of the base (**1**) is fixedly connected with a sleeve (**11**), and an inside of the sleeve (**11**) is provided with a positioning assembly (**12**) for positioning connecting holes on the overlapping plate group (**4**); the console (**3**) is internally provided with a through hole (**13**), and the electromagnetic-loaded assembly (**6**) comprises a housing (**61**) fixed in the lifting plate (**5**); a movable plate (**62**) and a driving plate (**63**) are respectively arranged in the housing (**61**), and an impact head (**64**) is installed at a bottom of the driving plate (**63**); a bottom of the impact head (**64**)

is provided with an installing hole (65), and an inside of the installing hole (65) is provided with internal threads; an inner surface of the installing hole (65) is fixedly connected with a T-shaped impact rod (66), and a bottom end of the T-shaped impact rod (66) extends to a bottom of the installing hole (65); a tension spring (67) is fixedly connected between a top of the T-shaped impact rod (66) and a top of the installing hole (65); opposite sides of the movable plate (62) and the driving plate (63) are respectively provided with a loading coil (68) and an induction coil (69), and a plurality of buffers (610) are arranged between a top of the movable plate (62) and a top of an inner wall of the housing (61); an inside of the impact head (64) is provided with a guiding groove (611); an inside of the guiding groove (611) is connected with a guiding plate (612) in a sliding way, and a top of the guiding plate (612) is fixedly connected with a guiding rod (613); a top end of the guiding rod (613) is fixed on the top of the inner wall of the housing (61); the impact assembly (7) comprises an annular plate (71), and a top of the annular plate (71) is fixedly connected with a threaded sleeve (72) inserted into the installing hole (65); a bottom of the annular plate (71) is provided with at least three hidden openings, and an outer surface of the annular plate (71) is provided with three movable grooves (73); the bottom of the annular plate (71) is fixedly connected with three abutting rods (74), and positioning pieces are arranged in the three movable grooves (73); each of the positioning pieces comprises a rotating shaft (75) rotating in each of the movable groove (73); an outer surface of the rotating shaft (75) is fixedly connected with a T-shaped block (76); a bottom of the T-shaped block (76) is fixedly connected with a V-shaped positioning block (77); a rotating end of the rotating shaft (75) is provided with a torsion spring.

2. The device for automatically extruding and installing the electromagnetic-loaded interference threaded connection component according to claim 1, wherein each of the reinforcing assemblies (8) comprises a U-shaped frame (81) fixed on a side of the bottom of the lifting plate (5); an inside of the U-shaped frame (81) is slidably connected with a moving block (82), and a bottom of the moving block (82) is fixedly connected with an L-shaped reinforcing block (83); a bottom of the L-shaped reinforcing block (83) extends to a bottom of the U-shaped frame (81), and one side of the L-shaped reinforcing block (83) is set as an inclined surface; a compression spring (84) is fixedly connected between a top of the moving block (82) and a top of an inner wall of the U-shaped frame (81).

3. The device for automatically extruding and installing the electromagnetic-loaded interference threaded connection component according to claim 2, wherein the positioning assembly (12) comprises a sliding block (121) sliding inside the sleeve (11); a top of the sliding block (121) is detachably provided with a positioning rod (122); a top end of the positioning rod (122) extends to an outside of the sleeve (11), and the top end of the positioning rod (122) is arranged in a chamfered shape; a bottom of the sleeve (11) is fixedly connected with a telescopic cylinder (123), and a telescopic end of the telescopic cylinder (123) is fixedly connected with a bottom of the sliding block (121); and the top of the sliding block (121) is provided with a threaded hole, and a bottom of the positioning rod (122) is provided with external threads.
