

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398558
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Venkatesan; Arun Srinivasan et al.

Floating connection fastening system

Abstract

A floating connection fastening system employs a semi-flexible floating bushing having a sleeve with an axial slot which captures a fastener having a head, an unthreaded shank portion, a threaded portion and an intermediate reamer. An adapter mounts to the bushing/fastener assembly and receives a driver bit. The adapter defines an offset clearance. The floating connection is installed by driving the fastener through a non-load bearing member so as to form a bore and embed the fastener into a load bearing member. The floating bushing has a flange which engages the surface of the non-load bearing member. The installation may be performed in essentially a one-step procedure.

Inventors: Venkatesan; Arun Srinivasan (Feeding Hills, MA), Gillis; Timothy F. (Florence, MA), Enko; Frederick A. (Westfield, MA), Dicaire; Mark A. (Boylston, MA)

Applicant: OMG Building Products LLC (Agawam, MA)

Family ID: 1000008782788

Assignee: OMG Building Products LLC (Agawam, MA)

Appl. No.: 18/473400

Filed: September 25, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240011287 A1	Jan. 11, 2024

Related U.S. Application Data

continuation parent-doc US 16519388 20190723 US 11808034 child-doc US 18473400
us-provisional-application US 62815546 20190308

Publication Classification

Int. Cl.: E04B2/82 (20060101); F16B5/02 (20060101); F16B25/00 (20060101)

U.S. Cl.:

CPC E04B2/82 (20130101); F16B5/0275 (20130101); F16B25/0063 (20130101);

Field of Classification Search

CPC: E04B (2/82); E04B (2/825); E04B (2001/2652); F16B (25/0083); F16B (5/0283); F16B (5/0275); F16B (25/0063); F16B (5/0241); F16B (43/005); F16B (43/00); F16B (19/02); F16B (35/048); F16B (25/0031)

USPC: 411/21; 411/25; 411/42; 411/60.2; 411/378; 411/533; 411/546; 411/528; 411/531; 52/285.2; 52/506.5; 52/506.05; 81/44; 81/451-458

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1099668	12/1913	Rosenberg	N/A	N/A
1119843	12/1913	Law	N/A	N/A
3869216	12/1974	Cseke	N/A	N/A
3881293	12/1974	Conville	N/A	N/A
4486134	12/1983	White	411/383	F16B 5/0283
4862556	12/1988	Grass	N/A	N/A
4902179	12/1989	Harker	N/A	N/A
5906080	12/1998	diGirolamo et al.	N/A	N/A
5987837	12/1998	Nelson	52/404.2	F16B 25/0089
5997229	12/1998	Akers	N/A	N/A
6155145	12/1999	Oh	81/125	B25B 23/10
6196778	12/2000	Wakai	N/A	N/A
6360842	12/2001	Combest	N/A	N/A
6582171	12/2002	Bondarowicz et al.	N/A	N/A
6595733	12/2002	Willert	N/A	N/A
6623492	12/2002	Berube et al.	N/A	N/A
7828502	12/2009	Chretien et al.	N/A	N/A
8210784	12/2011	Hartmann	N/A	N/A
8262330	12/2011	Ishino et al.	N/A	N/A
8458972	12/2012	Stodola	52/284	E04B 2/825
8828067	12/2013	Tipirneni et al.	N/A	N/A
9017329	12/2014	Tyber et al.	N/A	N/A
9360032	12/2015	Dicaire	N/A	N/A
10228012	12/2018	Holt	N/A	F16B 41/002
2003/0077118	12/2002	Kobusch et al.	N/A	N/A
2005/0008449	12/2004	Horita	N/A	N/A
2007/0122253	12/2006	Murtha	N/A	N/A
2008/0226420	12/2007	Huang	N/A	N/A

2010/0239387	12/2009	Gray	411/531	E04B 1/2608
2011/0229285	12/2010	Fluckiger	N/A	N/A
2012/0017529	12/2011	Shadwell et al.	N/A	N/A
2015/0336246	12/2014	Peters	81/439	H01F 7/02
2018/0100532	12/2017	Mugan	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
0292742	12/1987	EP	N/A
2868855	12/2014	EP	N/A
3667107	12/2019	EP	B25B 15/005

Primary Examiner: Fulton; Kristina R

Assistant Examiner: Wong; Jock

Attorney, Agent or Firm: Alix, Yale & Ristas, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation of U.S. patent application Ser. No. 16/519,388, filed on Jul. 23, 2019, for Floating Connection Fastening System, which claims the priority of U.S. Provisional Patent Application No. 62/815,546, filed on Mar. 8, 2019, the entire contents of which is incorporated herein by reference.

BACKGROUND

(1) This disclosure relates generally to devices and techniques for implementing a floating connection. More particularly, this disclosure relates to fastening systems which employ a floating connection to secure a non-load bearing wall to a truss or load bearing structure.

(2) In some construction techniques, interior non-load bearing walls are typically framed approximately 1½ inch to ¾ inch below the load bearing components, such as, for example, floor joists, floor trusses, roof trusses, etc. The gap allows the load bearing components to deflect under pre-designed loads. The non-load bearing wall still requires bracing against lateral movement which is the principal objective of fastening between the non-load bearing wall and the truss or load bearing structures.

(3) It is a well-known characteristic that if the non-load bearing walls are built flush to the underside of the load bearing components, the walls potentially become load bearing or quasi-load bearing. Such characteristics result in the transfer of load to structural components which, over time, typically result in dips in floors, cracking of finished work and failure of various components.

(4) It is also possible that the load bearing structure may deflect upwardly relative to a partition wall. In the latter instance, the wall may be displaced upwardly or otherwise displaced.

Consequently, for many installations, it is desired to implement a floating connection between a non-load bearing wall and a load bearing member by both creating a gap between the top of the non-load bearing wall and the underside of the load bearing member and/or creating a gap at the underside of the wall top plate between the head or flange of the fastener and the underside of the top plate so that, upon driving, the fastener sits proud relative to the bottom of the top plate.

(5) As used herein, the phrase “floating connection” refers to a connection which accommodates relative vertical movement between connected structures, but limits movement in the lateral and transverse direction.

(6) One technique for implementing a floating connection between a generally vertical non-load

bearing wall and a generally horizontal load bearing wall involves usage of a specially configured fastener. One such representative fastener has a head with a flange-like tapered underside and a shank which has a non-threaded axially extended portion adjacent the flange. The unthreaded portion has a slip surface or Teflon™-like coating to facilitate sliding along the unthreaded portion. The fastener has an intermediate knurl and a threaded portion at the distal end. The head and flange have a diameter which is greater than the unthreaded portion. Upon driving the fastener in the top plate assembly of the non-load bearing interior wall, the knurl forms a bore which is equal to or slightly greater than the diameter of the unthreaded portion of the fastener. The fastener is driven into the truss or support member so that the thread engages into the support member and the head only engages against the underside of the top plate or projects below the underside of the top plate to form a slight gap which is typically on the order of ½ to ¾ inches. The unthreaded portion of the fastener thus slides in the bore relative to the non-load bearing member.

(7) U.S. Pat. No. 9,360,032 discloses a fastener assembly specifically configured to connect a non-load bearing wall to a truss. The fastener assembly comprises a fastener which has a head and an axially extending shank which has an unthreaded shank portion and a threaded shank portion adjacent the distal end. A sleeve is retained on the fastener and disposed about the unthreaded shank portion. The sleeve is axially displaceable or slidable along the unthreaded shank portion. The sleeve is typically a plastic member with one end engageable against the upper end of the threaded portion and the other end engageable against a flange or a tapered neck disposed adjacent the head.

(8) The unthreaded shank portion extends an axial length which is greater than the longitudinal length of the sleeve. The disclosed fastener assembly of U.S. Pat. No. 9,360,032 is employed for implementing a floating connection between a non-load bearing wall and a load bearing component.

(9) It should be appreciated that the floating connection for all installations is replicated numerous times to complete the installation.

(10) The present disclosure involves a fastening system for efficiently implementing a floating connection between a non-load bearing member and a load bearing member to provide a reliable and durable floating connection.

SUMMARY

(11) In one embodiment, a floating connection installation system includes an adapter, a fastener and a bushing. The adapter has an offset enclosure defining a central first axis, and a proximal opening. A coaxial driving bit extends through the adapter at least partially into the enclosure. A distal reference flange of the adapter defines an abutment surface. The fastener has an elongate shank extending from an enlarged head, and the shank has threading on at least a portion thereof. The bushing includes a sleeve defining a second central axis and is mounted on the fastener coaxial thereto. The bushing also has a proximal locating flange disposed about the second central axis and a distal opening. The adapter bit is engageable with the head of the fastener in a driving position. Driving the fastener into a first building member bores a hole through the first building member and embeds the fastener into a second building member with the sleeve within the hole bored in the first building member.

(12) In another embodiment, a method of installing a floating connection between a load bearing member and a non-load bearing member includes first providing an adapter with a central driver bit and a distal reference surface defining an offset clearance. The driver bit is engaged with a head of a fastener that is mounted by a bushing having a sleeve. The fastener is driven with the bit, which thereby forms a bore in the non-load bearing member and threads a distal portion of the fastener into a load bearing member with the sleeve of the bushing received in the bore.

(13) In yet another embodiment, a method of installing a floating connection between a load bearing member and a non-load bearing member includes providing a composite fastener with an elongate shank having threading and a distal head. A bushing with a proximal sleeve and distal

flange is mounted on the shank. An installation tool with an axial bit extending through a central proximal opening in a collar is provided. The collar extends to a proximal reference end. The composite fastener is engaged with the installation tool by engaging the head of the fastener with the bit. The installation tool and fastener are rotatably locked and the bushing is rotatable relative to each of the installation tool and fastener. The fastener is driven through a non-load bearing member until the proximal reference end abuts a surface of the non-load bearing member with the fastener threadedly embedded into the load bearing member and the proximal sleeve within the bore.

(14) The adapter opening has a polygonal axially extending shape. A driver bit is received in the adapter and extends through the opening to define an offset clearance relative to the reference flange.

(15) A preferred fastener has a head, an unthreaded portion, a reamer and a distal threaded portion.

(16) In some embodiments, the fastener is driven to a proud position offset or spaced from the non-load bearing member pre-established by the adapter.

(17) In one embodiment, the slot extends entirely through the bushing to define a notch in the locating flange and the adapter has a key engageable in the floating sleeve notch.

(18) In some embodiments, when the locating flange is received in a coupling recess of a reference flange in the bushing, the reference flange and the locating flange have coplanar surfaces.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a perspective view of a floating connection assembly comprising a fastener, a floating bushing and a driver attachment assembly in engaged relationship;

(2) FIG. 2 is a second perspective view of the floating connection assembly of FIG. 1;

(3) FIG. 3 is an elevational view of the floating connection assembly of FIG. 1;

(4) FIG. 4 is an opposite elevational view of the floating connection assembly of FIG. 3;

(5) FIG. 5 is a third perspective view of the floating connection assembly of FIG. 1;

(6) FIG. 6 is an exploded perspective view of the floating connection assembly of FIG. 5;

(7) FIG. 7 is a central sectional view of the floating connection assembly of FIG. 1;

(8) FIG. 8 is an enlarged sectional view of the driver attachment assembly of FIG. 7;

(9) FIG. 9 is an enlarged perspective view of the floating bushing of FIG. 7;

(10) FIG. 10 is an enlarged perspective view of the fastener of FIG. 7;

(11) FIG. 11 is a perspective view, partly broken away and partly representational, of a driver, an attachment assembly, a fastener and a floating bushing in assembled driving relationship;

(12) FIG. 12 is a representational sectional view of an installed floating connection;

(13) FIG. 13 is a representational elevational view of the installed floating connection of FIG. 12;

(14) FIG. 14 is a representational sectional view of the installed floating connection of FIG. 12 from a 90° perspective thereof;

(15) FIG. 15 is a perspective view of the floating connection of FIG. 12;

(16) FIG. 16 is a second perspective view of the installed floating connection of FIG. 15;

(17) FIG. 17 is an enlarged perspective view of a second embodiment of an offset cap;

(18) FIG. 18 is a sectional view through the offset cap of FIG. 17;

(19) FIG. 19 is a perspective view of a second embodiment of a floating bushing; and

(20) FIG. 20 is a perspective view of a floating connection assembly comprising a second embodiment of the offset cap and the floating bushing of FIG. 19.

DETAILED DESCRIPTION

(21) With reference to the drawings wherein like numerals represent like parts throughout the several figures, a floating connection fastening system employs a fastener 10, a floating bushing 20 (FIG. 9) or 30 (FIG. 19) mounted to or capturing the fastener, and a driver offset adapter 50 which

mounts a driver bit **60** and receives the fastener/sleeve assembly. A driver **70** (FIG. **11**) has a chuck which engages the driver bit and rotatably drives the fastener. The principal innovative components are the floating bushings **20**, **30** and the cooperating adapter **50**. As described herein, “upper” and “lower” refer to preferred installation orientations for descriptive purposes and should not be deemed limiting.

(22) With additional reference to FIGS. **6** and **10**, the connection system is described in terms of a representative preferred fastener **10** configured to form a bore and to connect a non-load bearing member to a load bearing member. The fastener **10** preferably has a six inch axial length which includes a hex head **12** and an integral retaining washer or a flange **13** adjacent a tapered frusto-conical neck **14**. Other head, retainer flange/neck configurations are possible. An unthreaded cylindrical shank portion **15** axially extends approximately 4 inches from the neck **14**. A threaded portion **18** extends to a threaded distal tip **19**. The fastener preferably has an intermediate reamer **16** having diametrically protruding bore forming blades. In a preferred embodiment, the maximum diameter of the head **12** and the unthreaded portion **15** are 0.26 inches and 0.020 inches, respectively. The major diameters of the reamer **16** and threaded portion **18** are 0.24 inches and 0.26 inches, respectively. Naturally, other fastener configurations which have an unthreaded shank portion and have different dimensions are possible.

(23) A slidable bushing **20** or **30** is configured to mount onto and surround the unthreaded shank portion **15** of the fastener to thereby capture the fastener prior to installation. The bushing **20** or **30** essentially functions to axially slide relative to the unthreaded shank portion **15** which, post installation, may axially move. Each bushing **20**, **30** is preferably formed from plastic and has a semi-flexible sleeve **21**, **31** which extends approximately $\frac{7}{8}$ to one inch with an outer diameter less than the outside diameter of the head flange **13**. Each sleeve **21**, **31** in a normal non-flexed condition has an inner diameter greater than the diameter of the unthreaded portion **15** and less than the maximum diameters of the flange **13** and reamer **16**. The bushing **20** or **30** axially retains the fastener by the opposed sleeve ends **23**, **25** or **33**, **35**, respectively engaging the reamer **16** and the flange **13** and/or the neck **14**.

(24) With additional reference to FIG. **9**, bushing **20** is a semi-flexible plastic member having a lower quasi-annular flange **22** defining a notch **24** and a generally perpendicularly projecting semi-flexible sleeve **21**. The sleeve **21** has a longitudinal slot **26** extending from the notch to the terminus of the sleeve. As shown in FIGS. **9** and **11**, for example, the slot **26** defines a circumferential gap that provides a circumferential spacing **70** between a first longitudinal edge **72** and a second longitudinal edge **74** of the sleeve **21**. The sleeve **21** has a cylindrical inner surface **28** interrupted by the slot **26**. The sleeve **21** is configured so that it can be easily snapped over the unthreaded portion **15** of the fastener and is retained to the fastener by the flange **22** engaging the lower portion of the fastener neck/flange and the upper end **23** engaging an upper projecting portion of the reamer **16** and by the resilience of the sleeve which returns to its normal shape. The notch **24** may also facilitate capturing the fastener. Upon installation, the sleeve **21** is driven into the fastener bore of the non-load bearing member and flange **22** engages the underside surface of the non-load bearing member.

(25) With additional reference to FIG. **19**, semi-flexible bushing **30** is similar in form and function to bushing **20** except that sleeve **31** has an exterior thread **39**. Bushing **30** has a lower flange **32** with a notch **34** and sleeve **31** is traversed by a longitudinal slot **36**. The inner surface **38** substantially cylindrical except for the axial slot. As shown in FIG. **19**, for example, the slot **36** defines a circumferential gap that provides a circumferential spacing **70** between a first longitudinal edge **72** and a second longitudinal edge **74** of the sleeve **21**. Again, bushing **30** is configured so that sleeve **31** snaps over and slides along and is rotatable about the unthreaded upper portion **15** of the fastener and is also axially slidable along with the unthreaded upper portion. Upon installation, the sleeve **31** is rotatably driven into the fastener formed bore of the non-load bearing member and flange **32** engages the underside surface of the non-load bearing member.

(26) The offset adapter **50** functions to receive a driver bit **60** to form an attachment assembly **65** rotatably couplable with the fastener **10** captured by the receivably mounted bushing **20** or **30**. With reference to FIG. **11**, upon mounting the assembly **65** to a torque driver **70** and driving the attachment assembly/fastener/bushing, a pre-established proud head position of the fastener is ultimately implemented, as illustrated in FIGS. **12-16**.

(27) With additional reference to FIGS. **5-8**, the offset adapter **50** comprises a bell-like enclosure or cap having a central axis A. The enclosure terminates at an annular reference flange **52** normal to and coaxial with the axis A. The enclosure has a quasi-cylindrical portion **54** which upwardly tapers to form a central axial opening **56**. The opening **56** has a polygonal shape complementary to a shank portion of the driver bit. A coupling recess **58** coaxial with axis A is formed at the end of the adapter. Coupling recess **58** is complementary to the flange **22** or **32** of the bushing **20** or **30**.

(28) With reference to FIGS. **19** and **20**, for adapter **50'**, a key **59** projects radially inwardly to interrupt the recess **58**. The key **59** (FIG. **20**) is generally complementary with the notch **24** or **34** of the bushing flange **22** or **32** so that upon reception of the coupled flange **22** or **32** by the adapter **50'**, the adapter **50** and bushing **20** or **30** are rotatably locked. In some embodiments wherein the sleeve has no exterior threads (such as sleeve **21**), the key is omitted and there is no rotational locking between the cap or adapter **50** and the bushing **20**. Upon driving the fastener, there may be limited rotation of the bushing **20** due to friction between the flange **22** and the adapter **50**.

(29) The driver bit **60** has a socket **62** adapted to engage the hex head **12** of the fastener. Naturally, the bit/fastener head engagement may be configured differently if the fastener torque engagement portion has a different structure. The bit has a polygonal shank portion **64** of uniform polygonal cross-section is closely received in the opening **56**. The bit **60** and adapter **50** are thus rotatably fixed. The bit shank axially projects from the adapter and has a proximal engagement end **66**. With reference to FIG. **11**, the bit shank end **66** is received by the chuck **72** of a torque driver **70** which may be of numerous conventional forms.

(30) The driver bit is retained to the housing so that it forms an interior stop with a clearance C as indicated in FIG. **8**. Because of the pre-established clearance C, when the fastener is driven, the reference flange **52** ultimately engages the underside of the header H or support member, and the fastener head is torqued to drive the fastener **10** (and sleeve) so that the flange **22** or **32** carried by the cap in coupling recess **58** ultimately engages the underside of the non-load bearing member and the head essentially sits proud relative to the non-load bearing member or is offset by clearance C.

(31) With reference to FIGS. **12-16** the bushing **20** and captured fastener **10** are installed as a unit. Upon driving and installing the fastener **10**, the bushing **20** remains mounted to the fastener, and the bushing and fastener function to provide the floating connection installation between a load bearing structure, such as a truss, and a non-load bearing structure, such as a partition or interior wall. The installation is accomplished in a one-step procedure in which the fastener **10** forms a bore B in the header H or non-load bearing member as it is driven into the load bearing member such as truss T. The sleeve **21** of the bushing is forced into the bore B during the driving step via a combination of friction from the fastener and a direct pushing force from the adapter **50**. The sleeve **21** is received along with the adjacent unthreaded portion of the fastener in the fastener bore B of the non-load bearing member. Upon installation, the sleeve **21** or **31** does not extend the entire axial length of the formed bore B.

(32) The bushing **30** rotates with the driver and adapter **50'** as the fastener is driven. The exterior surface of sleeve **31** and the thread **39** frictionally engage the non-load bearing member bore B. Sleeve **31** may slightly thread or engage into the structure adjacent the non-load bearing member bore.

(33) When installed by the embodiment of the adapter **50** (without a key like element **59** in the adapter **50'**), the bushing **20**, for the most part, does not rotate or only slightly rotates when the fastener is driven. Once the fastener is threaded into the load bearing member, the unthreaded portion of the fastener is slidable relative to the inner surface of the sleeve **21** or **31**. The attachment

assembly 65 comprising adapter 50 and driver bit 60 is disengaged from the fastener head 12 of the implemented floating connection and is reusable with multiple captured fastener/bushings for multiple subsequent floating connection installations.

(34) For preferred embodiments, wherein the floating bushing 20 does not have an exterior thread, it is not required that the bushing rotate with the adapter. For such embodiments, the described key/notch configuration and engagement is not required.

(35) While preferred embodiments of the foregoing floating connection fastening system have been set forth for purposes of illustration, the foregoing description should not be deemed a limitation of the invention herein. Accordingly, various modifications, adaptations and alternatives may occur to one skilled in the art without departing from the spirit and the scope of the present invention.

Claims

1. A floating connection installation system, comprising: an adapter comprising an offset enclosure defining a central first axis and a proximal opening with a coaxial driving bit extending therethrough at least partially into the enclosure and having a distal reference flange defining an abutment surface; a fastener with an elongate shank extending from an enlarged head, the shank having threading on at least a portion thereof; and a bushing having a sleeve defining a second central axis mounted on the fastener coaxial thereto, and having a proximal locating flange disposed about said second central axis and a distal opening, wherein the adapter bit is engageable with the head of the fastener in a driving position, the fastener comprises a bore forming reamer and the bushing is mounted between the reamer and the head, and driving the fastener into a first building member bores a hole through the first building member and embeds the fastener into a second building member with the sleeve within the hole bored in the first building member.
2. The system of claim 1, wherein the locating flange abuts a portion of the reference flange in the driving position.
3. The system of claim 2, wherein the locating flange and reference flange are not rotationally fixed to one another in the driving position.
4. The system of claim 1, wherein the distal reference flange has locating coupling recess configured to receive at least a portion of the locating flange in abutment with a surface thereof.
5. The system of claim 4, wherein the fastener and bushing are not rotationally fixed to one another in the driving position.
6. The assembly of claim 1, wherein the reference flange is substantially perpendicular to the first axis.
7. The assembly of claim 1, wherein the bit terminates at a distal end positioned within the enclosure to define a clearance relative to said reference flange.
8. The assembly of claim 1, wherein the fastener comprises a threaded distal portion and an unthreaded proximal portion and the bushing is aligned on the unthreaded portion.
9. The assembly of claim 1, wherein the bit is rotationally fixed relative to the reference flange.
10. The assembly of claim 1, wherein a clearance position is established by the relationship between said reference flange and said driver bit and the fastener is driven to the clearance position offset from said non-load bearing member.
11. The assembly of claim 1, wherein the fastener has an axial length defined between a proximal end and distal end, and has a threaded distal portion with an axial length that is less than half of an overall axial length of the fastener, and when the fastener is fully installed with the adapter, an outer portion of the head projects away from the locating flange.
12. A floating connection installation system, comprising: an adapter comprising an offset enclosure defining a central first axis and a proximal opening with a coaxial driving bit extending therethrough at least partially into the enclosure and having a distal reference flange defining an abutment surface; a fastener with an elongate shank extending from an enlarged head, the shank

having threading on at least a portion thereof; and a bushing having a sleeve defining a second central axis mounted on the fastener coaxial thereto, and having a proximal locating flange disposed about said second central axis and a distal opening, wherein the adapter bit is engageable with the head of the fastener in a driving position, driving the fastener into a first building member bores a hole through the first building member and embeds the fastener into a second building member with the sleeve within the hole bored in the first building member, and the sleeve is interrupted by an axial slot extending from a distal end.

13. The assembly of claim 12, wherein the axial slot extends from the distal end to the proximal end and through the locating flange.

14. The assembly of claim 12, wherein the fastener comprises a bore forming reamer and the bushing is mounted between the reamer and head.

15. The system of claim 12, wherein the locating flange abuts a portion of the reference flange in the driving position.

16. The system of claim 12, wherein the locating flange and reference flange are not rotationally fixed to one another in the driving position.

17. The system of claim 12, wherein the distal reference flange has a locating coupling recess configured to receive at least a portion of the locating flange in abutment with a surface thereof.

18. The system of claim 17, wherein the fastener and bushing are not rotationally fixed to one another in the driving position.

19. The assembly of claim 12, wherein the bit terminates at a distal end positioned within the enclosure to define a clearance relative to said reference flange.

20. The assembly of claim 12, wherein a clearance position is established by the relationship between said reference flange and said driver bit and the fastener is driven to the clearance position offset from said non-load bearing member.

21. The assembly of claim 12, wherein the fastener has an axial length defined between a proximal end and distal end, and has a threaded distal portion with an axial length that is less than half of an overall axial length of the fastener, and when the fastener is fully installed with the adapter, an outer portion of the head projects away from the locating flange.

22. A method of installing a floating connection between a load bearing member and a non-load bearing member, comprising: providing an adapter with a central driver bit and a distal reference surface defining an offset clearance; engaging the driver bit with a head of a fastener, the fastener being mounted by a bushing having a sleeve; and driving the fastener with the bit and thereby forming a bore in the non-load bearing member and threading a distal portion of the fastener into a load bearing member with the sleeve of the bushing received in the bore.

23. The method of claim 22, wherein the step of driving drives the fastener to an installation position with the sleeve entirely retained in the bore of the non-load bearing member.

24. The method of claim 23, wherein the head of the fastener is spaced from the non-load bearing member by the offset clearance in the installation position.

25. The method of claim 24, wherein a proximal end of the bushing abuts a portion of the adapter when the fastener is engaged with the driver bit.

26. The method of claim 23, wherein the distal reference surface comprises a reference flange and the proximal end of the bushing comprises a locating flange, and the step of engaging engages the locating flange against a portion of the reference flange.

27. The method of claim 26, further comprising driving the fastener until the reference flange engages a surface of the non-load bearing member.

28. The method of claim 27, wherein the locating flange abuts the surface of the non-load bearing member in the installation position.

29. A method of installing a floating connection between a load bearing member and a non-load bearing member, comprising: providing a composite fastener with an elongate shank having threading and a distal head, and a bushing with a proximal sleeve and distal flange mounted on the

shank; providing an installation tool with an axial bit extending through a central proximal opening in a collar, the collar extending to a proximal reference end; engaging the composite fastener and installation tool by engaging the head of the fastener with the bit, wherein the installation tool and fastener are rotatably locked and the bushing is rotatable relative to each of the installation tool and fastener; and driving the fastener through a non-load bearing member, thereby boring a hole through the non-loadbearing member and continuing driving the fastener until the proximal reference end abuts a surface of the non-load bearing member with fastener threadedly embedded into the load bearing member and the proximal sleeve within the bore.
