

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399604
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Bao; Xintong et al.

Electronic device control method and electronic device

Abstract

This application provides an electronic device control method and an electronic device. The method includes: displaying a first interface, the first interface including: a first thumbnail and a first quantity of controls, the first thumbnail corresponding to a first file, the first thumbnail having a first size, and the first quantity of controls including a first control; sending a printing instruction to a printing device in response to a first operation on the first control; and displaying a second interface in response to a second operation acting on the first interface, the second interface including: a second thumbnail and a second quantity of controls, the second quantity of controls including the first control, the second thumbnail corresponding to the first file, the second thumbnail having a second size, the second size being smaller than the first size, the second quantity being greater than the first quantity.

Inventors:	Bao; Xintong (Shenzhen, CN), Wang; Long (Shenzhen, CN)
Applicant:	Honor Device Co., Ltd. (Shenzhen, CN)
Family ID:	1000008782672
Assignee:	Honor Device Co., Ltd. (Shenzhen, CN)
Appl. No.:	18/280297
Filed (or PCT Filed):	December 13, 2022
PCT No.:	PCT/CN2022/138789
PCT Pub. No.:	WO2023/130920
PCT Pub. Date:	July 13, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240160339 A1	May. 16, 2024

Foreign Application Priority Data

CN202210023693.0Jan. 10, 2022

Publication Classification

Int. Cl.: G06F3/048 (20130101); G06F3/0484 (20220101); G06F3/0488 (20220101); H04N1/00 (20060101)

U.S. Cl.:

CPCG06F3/0484 (20130101); G06F3/0488 (20130101); H04N1/00424 (20130101); H04N1/00482 (20130101);

Field of Classification Search

CPC:G06F (3/048)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6621590	12/2002	Livingston	358/452	G06F 3/1256
7757180	12/2009	Nakai	715/835	G06F 3/0486
7952736	12/2010	Kasatani	358/1.14	H04N 1/32053
9338323	12/2015	Tsujimoto	N/A	G06F 21/608
9734538	12/2016	Hong	N/A	G06Q 10/10
10200548	12/2018	Kimura	N/A	G06F 3/1204
12200345	12/2024	Chen	N/A	G06N 3/084
2003/0030846	12/2002	Mori	358/400	H04N 1/00408
2003/0065531	12/2002	Satomi	705/26.35	G06Q 30/06
2004/0052543	12/2003	Kato	399/83	G03G 15/5075
2004/0126122	12/2003	Kanamoto	399/20	H04N 1/2175
2004/0184069	12/2003	Mifune	358/1.15	G06K 15/00
2006/0129539	12/2005	Nakatomi	N/A	G06F 16/16
2006/0288304	12/2005	Nomoto	715/781	G06F 16/168
2010/0097628	12/2009	Masuda	358/1.14	G06F 21/608

2011/0279363	12/2010	Shoji	345/156	H04N 1/00482
2011/0292075	12/2010	Sukenori	345/629	G06T 11/60
2012/0050779	12/2011	Tani	358/1.13	H04N 1/00477
2012/0069376	12/2011	Tsujimoto	358/1.13	H04N 1/00464
2014/0089840	12/2013	Nakagawa	715/810	G06F 3/04847
2015/0009534	12/2014	Morita	358/1.15	H04N 1/00458
2015/0146243	12/2014	Tsujimoto	358/1.15	H04N 1/4433
2015/0350467	12/2014	Kodimer	358/1.13	H04N 1/00307
2017/0374210	12/2016	Channa	N/A	G06F 21/608
2018/0024696	12/2017	Lee	345/175	H04N 5/74
2018/0183952	12/2017	Imaoka	N/A	H04N 1/00411
2019/0356773	12/2018	Tam	N/A	H04M 1/72463
2020/0026396	12/2019	Murakami	N/A	G06F 3/1288
2020/0336622	12/2019	Kunimi	N/A	H04N 1/6027
2020/0341623	12/2019	Yin	N/A	G06F 3/0486
2021/0409553	12/2020	Nagai	N/A	G06F 3/0488
2022/0023761	12/2021	Li	N/A	A63F 13/5255
2022/0365661	12/2021	Dong	N/A	G06F 3/0488
2022/0374118	12/2021	Liang et al.	N/A	N/A
2022/0413671	12/2021	Liu	N/A	G06F 3/0488

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101150638	12/2007	CN	H04N 1/00222
101571793	12/2008	CN	N/A
101998009	12/2010	CN	H04N 1/00222
111338519	12/2019	CN	N/A
111708499	12/2019	CN	N/A
112162814	12/2020	CN	N/A
113194454	12/2020	CN	N/A
114115756	12/2021	CN	N/A

OTHER PUBLICATIONS

Park et al., Design and Implementation of Digital Photo Kiosk System with Auto Color-Correction Module, 2005, IEEE, 7 pages. (Year: 2005). cited by examiner
Julio Nobrega, A Method and System for Displaying a Playable Thumbnail Preview, 2018, IP.com, 2 pages. (Year: 2018). cited by examiner

Primary Examiner: Pham; Linh K

Attorney, Agent or Firm: Leydig, Voit & Mayer, Ltd.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is a national stage of International Application No. PCT/CN2022/138789, filed on Dec. 13, 2022, which claims priority to Chinese Patent Application No. 202210023693.0, filed on Jan. 10, 2022, both of which are hereby incorporated by reference in their entireties.

TECHNICAL FIELD

(2) This application relates to the field of terminal technologies, and in particular, to an electronic device control method and an electronic device.

BACKGROUND

(3) A user may control, through an electronic device, a printer for printing. Currently, when the printer is controlled through the electronic device for printing, an interface layout is not convenient for viewing, resulting in poor user experience.

SUMMARY

(4) This application provides an electronic device control method and an electronic device, which is helpful to reduce operation complexity of a user, improve a degree of intelligence of a terminal device, and finally improve user experience.

(5) According to a first aspect, an embodiment of this application provides an electronic device control method. The method is applicable to an electronic device. Specifically, the method includes: displaying, by the electronic device, a first interface, the first interface including: a first thumbnail and a first quantity of controls, the first thumbnail corresponding to a first file, the first thumbnail having a first size, and the first quantity of controls including a first control; where the first control is a print control, a user triggers the print control, and the electronic device sends a printing instruction to a printing device, the printing instruction indicating printing the first file; and performing, by the user, a first operation on the first interface, the first operation being a swipe-up operation, and displaying, by the electronic device, a second interface, the second interface including: a second thumbnail and a second quantity of controls, the second quantity of controls including the first control, the second thumbnail corresponding to the first file, the second thumbnail having a second size, the second size being smaller than the first size, the second quantity being greater than the first quantity, the second interface being of a same size as the first interface.

(6) As can be seen, in the above embodiment, the user performs a second operation in the first interface, so that more controls are displayed in the second interface than in the first interface, so as to provide more control items for the user. In addition, the first thumbnail is reduced to the second thumbnail, preventing occlusion of the thumbnail by the control, which is convenient for the user to view and improves user experience.

(7) In a possible implementation, in response to the second operation acting on the first interface, the first thumbnail is reduced from the first size to the second size to obtain the second thumbnail;

and the first quantity of controls move according to the second operation, and a third quantity of controls are added to the second interface to obtain the second quantity of controls, where a sum of the first quantity and the third quantity is the second quantity.

(8) In a possible implementation, in the first interface, the first thumbnail is located on an upper side of the first quantity of controls, and the second operation is a swipe-up operation. The user performs the swipe-up operation on the first interface to drag out more controls.

(9) In a possible implementation, after the displaying a second interface in response to a second operation acting on the first interface, the first interface is displayed in response to a third operation acting on the second interface. The third operation may be a swipe-down operation. The user performs the swipe-down operation in the second interface to reduce a quantity of the controls and enlarge the second thumbnail to the first thumbnail, so that the electronic device displays the first interface.

(10) In a possible implementation, the first quantity of controls further include a second control, a third control, and a fourth control, and a third interface is displayed in response to a fourth operation acting on the second control, the third interface including: an option of a printing device; a fourth interface is displayed in response to a fifth operation acting on the third control, the fourth interface including: an option of print copies; and a fifth interface is displayed in response to a sixth operation acting on the fourth control, the fifth interface including: an option of a printing range; where the sending a printing instruction to a printing device in response to a first operation on the first control includes: sending, in response to the first operation on the first control, a printing instruction carrying a first printing parameter to a printing device selected in the third interface, the first printing parameter including print copies selected in the fourth interface and a printing range selected in the fifth interface. The second control may be a printing device selection control, the third control may be a print copies selection control, and the fourth control may be a printing range selection control.

(11) In a possible implementation, the second quantity of controls further include a fifth control, a sixth control, a seventh control, and an eighth control, and a sixth interface is displayed in response to a seventh operation acting on the fifth control, the sixth interface including: an option of a paper type; a seventh interface is displayed in response to an eighth operation acting on the sixth control, the seventh interface including: an option of a paper size; an eighth interface is displayed in response to a ninth operation acting on the seventh control, the eighth interface including: an option of a printing manner, the printing manner including: double-sided printing and single-sided printing; and a ninth interface is displayed in response to a tenth operation acting on the eighth control, the ninth interface including: an option of a color mode, the option of the color mode including: a black-white mode and a colored mode; where the sending a printing instruction to a printing device in response to a first operation on the first control includes: sending, in response to the first operation on the first control, a printing instruction carrying a second printing parameter to the printing device, the second printing parameter including: a paper type selected in the sixth interface, a paper type selected in the seventh interface, a printing manner selected in the eighth interface, and a color mode selected in the ninth interface. The fifth control may be a paper type selection control, the sixth control may be a paper size selection control, the seventh control may be a printing manner selection control, and the eighth control may be a color mode selection control.

(12) In a possible implementation, the first quantity of controls further include a ninth control, the ninth control corresponding to a background image, an icon of the ninth control being displayed as a third thumbnail of the corresponding background image, the user may determine a to-be-selected background according to the third thumbnail and select the ninth control corresponding to the background, and in response to an eleventh operation on the ninth control, the first thumbnail is displayed on a background image selected by the eleventh operation, the background image selected by the eleventh operation being the background image corresponding to the ninth control selected by the eleventh operation.

- (13) In a possible implementation, the second quantity of controls further include a tenth control, the tenth control corresponding to a position relationship between the first thumbnail and the background image, an icon of the tenth control being a schematic diagram of the corresponding position relationship, the user may determine a to-be-selected position relationship according to the schematic diagram and select the tenth control corresponding to the position relationship, and in response to a twelfth operation on the tenth control and according to a position relationship selected by the twelfth operation, the first thumbnail is displayed on the background image selected by the eleventh operation, the position relationship selected by the twelfth operation being the position relationship corresponding to the tenth control selected by the twelfth operation.
- (14) In a possible implementation, the first thumbnail is located on an upper side of the first quantity of controls, and a tenth interface is displayed in response to a thirteenth operation acting on the first interface, the tenth interface including the first thumbnail and a fourth quantity of controls, where the first thumbnail has the first size, and the fourth quantity of controls are located on an upper side of the first thumbnail.
- (15) In a possible implementation, the thirteenth operation is a swipe-down operation.
- (16) According to a second aspect, an embodiment of this application provides an electronic device, the electronic device including a memory configured to store a computer program instruction and a processor configured to execute the program instruction. When the computer program instruction is executed by the processor, the electronic device is triggered to perform the method according to any one of the first aspect.
- (17) According to a third aspect, an embodiment of this application provides a computer-readable storage medium, the computer-readable storage medium including a stored program. When the program runs, a device in which the computer-readable storage medium is located is controlled to perform the printing method according to any one of the first aspect.
- (18) According to a fourth aspect, an embodiment of this application provides a computer program product, the computer program product including an executable instruction, the executable instruction, when executed on a computer, causing the computer to perform the printing method according to any one of the first aspect.
- (19) According to a fifth aspect, an embodiment of this application further provides a chip, the chip being coupled to a memory and configured to execute a computer program stored in the memory to perform any possible method according to any one of the above aspects.
- (20) It may be understood that, the electronic device according to the second aspect, the computer-readable storage medium according to the third aspect, the computer program product according to the fourth aspect, and the chip according to the fifth aspect that are provided above are all configured to perform the corresponding method provided above. Therefore, for beneficial effects that can be achieved, refer to beneficial effects in the corresponding method provided above, and details are not described herein again.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a schematic diagram of an application scenario according to an embodiment of this application;
- (2) FIG. 2 is a schematic structural diagram of a mobile phone according to an embodiment of this application;
- (3) FIG. 3a is a schematic diagram of a graphical user interface of a first electronic device according to an embodiment of this application;
- (4) FIG. 3b is a schematic diagram of a graphical user interface of a second electronic device according to an embodiment of this application;

- (5) FIG. 3c is a schematic diagram of a graphical user interface of a third electronic device according to an embodiment of this application;
- (6) FIG. 3d is a schematic diagram of a graphical user interface of a fourth electronic device according to an embodiment of this application;
- (7) FIG. 4a is a schematic diagram of a graphical user interface of a fifth electronic device according to an embodiment of this application;
- (8) FIG. 4b is a schematic diagram of a graphical user interface of a sixth electronic device according to an embodiment of this application;
- (9) FIG. 4c is a schematic diagram of a graphical user interface of a seventh electronic device according to an embodiment of this application;
- (10) FIG. 4d is a schematic diagram of a graphical user interface of an eighth electronic device according to an embodiment of this application;
- (11) FIG. 4e is a schematic diagram of a graphical user interface of a ninth electronic device according to an embodiment of this application;
- (12) FIG. 5a is a schematic diagram of a graphical user interface of a tenth electronic device according to an embodiment of this application;
- (13) FIG. 5b is a schematic diagram of a graphical user interface of an eleventh electronic device according to an embodiment of this application;
- (14) FIG. 5c is a schematic diagram of a graphical user interface of a twelfth electronic device according to an embodiment of this application;
- (15) FIG. 5d is a schematic diagram of a graphical user interface of a thirteenth electronic device according to an embodiment of this application;
- (16) FIG. 5e is a schematic diagram of a graphical user interface of a fourteenth electronic device according to an embodiment of this application;
- (17) FIG. 5f is a schematic diagram of a graphical user interface of a fifteenth electronic device according to an embodiment of this application;
- (18) FIG. 5g is a schematic diagram of a graphical user interface of a sixteenth electronic device according to an embodiment of this application;
- (19) FIG. 6a is a schematic diagram of a graphical user interface of a seventeenth electronic device according to an embodiment of this application;
- (20) FIG. 6b is a schematic diagram of a graphical user interface of an eighteenth electronic device according to an embodiment of this application;
- (21) FIG. 6c is a schematic diagram of a graphical user interface of a nineteenth electronic device according to an embodiment of this application;
- (22) FIG. 7a is a schematic diagram of a graphical user interface of a twentieth electronic device according to an embodiment of this application;
- (23) FIG. 7b is a schematic diagram of a graphical user interface of a twenty-first electronic device according to an embodiment of this application;
- (24) FIG. 7c is a schematic diagram of a graphical user interface of a twenty-second electronic device according to an embodiment of this application;
- (25) FIG. 7d is a schematic diagram of a graphical user interface of a twenty-third electronic device according to an embodiment of this application;
- (26) FIG. 7e is a schematic diagram of a graphical user interface of a twenty-fourth electronic device according to an embodiment of this application;
- (27) FIG. 7f is a schematic diagram of a graphical user interface of a twenty-fifth electronic device according to an embodiment of this application;
- (28) FIG. 7g is a schematic diagram of a graphical user interface of a twenty-sixth electronic device according to an embodiment of this application;
- (29) FIG. 8a is a schematic diagram of a graphical user interface of a twenty-seventh electronic device according to an embodiment of this application;

(30) FIG. 8b is a schematic diagram of a graphical user interface of a twenty-eighth electronic device according to an embodiment of this application;

(31) FIG. 8c is a schematic diagram of a graphical user interface of a twenty-ninth electronic device according to an embodiment of this application;

(32) FIG. 8d is a schematic diagram of a graphical user interface of a thirtieth electronic device according to an embodiment of this application;

(33) FIG. 9a is a schematic diagram of a graphical user interface of a thirty-first electronic device according to an embodiment of this application;

(34) FIG. 9b is a schematic diagram of a graphical user interface of a thirty-second electronic device according to an embodiment of this application;

(35) FIG. 9c is a schematic diagram of a graphical user interface of a thirty-third electronic device according to an embodiment of this application;

(36) FIG. 9d is a schematic diagram of a graphical user interface of a thirty-fourth electronic device according to an embodiment of this application;

(37) FIG. 9e is a schematic diagram of a graphical user interface of a thirty-fifth electronic device according to an embodiment of this application;

(38) FIG. 10a is a schematic diagram of a graphical user interface of a thirty-sixth electronic device according to an embodiment of this application;

(39) FIG. 10b is a schematic diagram of a graphical user interface of a thirty-seventh electronic device according to an embodiment of this application;

(40) FIG. 10c is a schematic diagram of a graphical user interface of a thirty-eighth electronic device according to an embodiment of this application;

(41) FIG. 10d is a schematic diagram of a graphical user interface of a thirty-ninth electronic device according to an embodiment of this application;

(42) FIG. 10e is a schematic diagram of a graphical user interface of a fortieth electronic device according to an embodiment of this application;

(43) FIG. 10f is a schematic diagram of a graphical user interface of a forty-first electronic device according to an embodiment of this application;

(44) FIG. 11a is a schematic diagram of a graphical user interface of a forty-second electronic device according to an embodiment of this application;

(45) FIG. 11b is a schematic diagram of a graphical user interface of a forty-third electronic device according to an embodiment of this application;

(46) FIG. 12a is a schematic diagram of a graphical user interface of a forty-fourth electronic device according to an embodiment of this application;

(47) FIG. 12b is a schematic diagram of a graphical user interface of a forty-fifth electronic device according to an embodiment of this application;

(48) FIG. 13a is a schematic diagram of a graphical user interface of a forty-sixth electronic device according to an embodiment of this application;

(49) FIG. 13b is a schematic diagram of a graphical user interface of a forty-seventh electronic device according to an embodiment of this application;

(50) FIG. 14a is a schematic diagram of a graphical user interface of a forty-eighth electronic device according to an embodiment of this application;

(51) FIG. 14b is a schematic diagram of a graphical user interface of a forty-ninth electronic device according to an embodiment of this application;

(52) FIG. 14c is a schematic diagram of a graphical user interface of a fiftieth electronic device according to an embodiment of this application;

(53) FIG. 14d is a schematic diagram of a graphical user interface of a fifty-first electronic device according to an embodiment of this application;

(54) FIG. 15 is a schematic diagram of a graphical user interface of a fifty-second electronic device according to an embodiment of this application;

(55) FIG. 16a is a schematic diagram of a graphical user interface of a fifty-third electronic device according to an embodiment of this application;

(56) FIG. 16b is a schematic diagram of a graphical user interface of a fifty-fourth electronic device according to an embodiment of this application;

(57) FIG. 16c is a schematic diagram of a graphical user interface of a fifty-fifth electronic device according to an embodiment of this application;

(58) FIG. 17a is a schematic diagram of a graphical user interface of a fifty-sixth electronic device according to an embodiment of this application;

(59) FIG. 17b is a schematic diagram of a graphical user interface of a fifty-seventh electronic device according to an embodiment of this application;

(60) FIG. 17c is a schematic diagram of a graphical user interface of a fifty-eighth electronic device according to an embodiment of this application;

(61) FIG. 17d is a schematic diagram of a graphical user interface of a fifty-ninth electronic device according to an embodiment of this application;

(62) FIG. 17e is a schematic diagram of a graphical user interface of a sixtieth electronic device according to an embodiment of this application;

(63) FIG. 17f is a schematic diagram of a graphical user interface of a sixty-first electronic device according to an embodiment of this application;

(64) FIG. 17g is a schematic diagram of a graphical user interface of a sixty-second electronic device according to an embodiment of this application;

(65) FIG. 17h is a schematic diagram of a graphical user interface of a sixty-third electronic device according to an embodiment of this application;

(66) FIG. 17i is a schematic diagram of a graphical user interface of a sixty-fourth electronic device according to an embodiment of this application;

(67) FIG. 18a is a schematic diagram of a graphical user interface of a sixty-fifth electronic device according to an embodiment of this application;

(68) FIG. 18b is a schematic diagram of a graphical user interface of a sixty-sixth electronic device according to an embodiment of this application;

(69) FIG. 18c is a schematic diagram of a graphical user interface of a sixty-seventh electronic device according to an embodiment of this application;

(70) FIG. 18d is a schematic diagram of a graphical user interface of a sixty-eighth electronic device according to an embodiment of this application;

(71) FIG. 18e is a schematic diagram of a graphical user interface of a sixty-ninth electronic device according to an embodiment of this application;

(72) FIG. 18f is a schematic diagram of a graphical user interface of a seventieth electronic device according to an embodiment of this application; and

(73) FIG. 19 is a flowchart of an electronic device control method according to an embodiment of this application.

DESCRIPTION OF EMBODIMENTS

(74) Technical solutions in embodiments of this application are described below with reference to the accompanying drawings in the embodiments of this application. In the descriptions of the embodiments of this application, “I” means “or” unless otherwise specified. For example, A/B may represent A or B. In this specification, “and/or” describes only an association relationship for describing associated objects and indicates that three relationships may exist. For example, A and/or B may represent the following three cases: Only A exists, both A and B exist, and only B exists. In addition, in the descriptions of the embodiments of this application, “a plurality of” represents two or more.

(75) The terms “first” and “second” below are merely intended for descriptive purposes, and cannot be understood as an indication or implication of relative importance or implicit indication of the quantity of indicated technical features. Therefore, a feature limited by “first”, “second” or “third”

may explicitly or implicitly include one or more of the features.

(76) A photographing method provided in the embodiments of this application is applicable to a terminal device such as a mobile phone, a tablet computer, a wearable device, an in-vehicle device, an augmented reality (AR) device/virtual reality (VR) device, a notebook computer, an ultra-mobile personal computer (UMPC), a netbook, or a personal digital assistant (PDA). No limitation is imposed on the specific type of the terminal device in the embodiments of this application.

(77) For example, FIG. 1 is a schematic structural diagram of a terminal device **100** according to an embodiment of this application. The electronic device **100** may include a processor **110**, an external memory interface **120**, an internal memory **121**, a universal serial bus (USB) interface **130**, a charging management module **140**, a power management module **141**, a battery **142**, an antenna **1**, an antenna **2**, a mobile communication module **150**, a wireless communication module **160**, an audio module **170**, a speaker **170A**, a phone receiver **170B**, a microphone **170C**, a headset jack **170D**, a sensor module **180**, a key **190**, a motor **191**, an indicator **192**, a camera **193**, a display screen **194**, a subscriber identification module (SIM) card interface **195**, and the like. The sensor module **180** may include a pressure sensor **180A**, a gyroscope sensor **180B**, a barometric pressure sensor **180C**, a magnetic sensor **180D**, an acceleration sensor **180E**, a range sensor **180F**, a proximity light sensor **180G**, a fingerprint sensor **180H**, a temperature sensor **180J**, a touch sensor **180K**, an ambient light sensor **180L**, a bone conduction sensor **180M**, and the like.

(78) It may be understood that an example structure in this embodiment of this application does not constitute a specific limitation on the terminal device **100**. In some other embodiments of this application, the terminal device **100** may include more or fewer components than those shown in the figure, or combine some components, or split some components, or have different component arrangements. The components shown in the figure may be implemented by hardware, software, or a combination of software and hardware.

(79) A software system of the terminal device **100** may use a layered architecture, an event driven architecture, a micro-core architecture, a micro-service architecture, or a cloud architecture. In this embodiment of this application, an Android system of the layered architecture is used as an example to illustrate a software structure of the terminal device **100**.

(80) FIG. 2 is a block diagram of a software structure of the terminal device **100** according to an embodiment of this application. In the layered architecture, software is divided into several layers, and each layer has a clear role and task. The layers communicate with each other through a software interface. In some embodiments, the Android system is divided into four layers, which are a program application layer, an application framework layer, an Android runtime and system library, and a kernel layer from top to bottom. The application layer may include a series of application packages. As shown in FIG. 2, the application packages may include applications such as Camera, Gallery, Calendar, Calls, Map, Navigation, WLAN, Bluetooth, Music, Video, and Messages.

(81) The application framework layer provides an application programming interface (API) and a programming framework for an application at the application layer. The application framework layer includes some predefined functions.

(82) As shown in FIG. 2, the application framework layer may include a window manager, a content provider, a view system, a phone manager, a resource manager, a notification manager, and the like.

(83) The Android runtime includes a kernel library and a virtual machine. The Android runtime is responsible for scheduling and managing the Android system.

(84) The core library includes two parts: one part is a performance function that the Java language needs to invoke, and the other part is a core library of Android.

(85) The application layer and the application framework layer are run in the virtual machine. The virtual machine executes Java files of the application layer and the application framework layer as binary files. The virtual machine is used for executing functions such as object lifecycle

management, stack management, thread management, security and exception management, and garbage collection.

(86) The system library may include a plurality of function modules, for example, a surface manager, a media library (media libraries), a three-dimensional graphics processing library (for example, OpenGL ES), a 2D graphics engine (for example, SGL), and the like.

(87) The kernel layer is a layer between hardware and software. The kernel layer includes at least a display driver, a camera driver, an audio driver, and a sensor driver.

(88) The hardware layer may include various types of sensors, for example, the various types of sensors described in FIG. 1, the acceleration sensor, the gyroscope sensor, and the touch sensor in this embodiment of this application.

(89) With reference to the electronic devices described above in FIG. 1 and FIG. 2, in the embodiments of this application, physical elements related to the electronic device **100** mainly include hardware components such as a sensor, a decision support systems (DSS) display chip, a touch display screen, and a fingerprint recognition module; kernel software layers such as a screen management module, a display driver, a fingerprint driver, and accidental touch prevention; application framework layer functions such as accidental touch input prevention, screen control, an always on display (AOD) service, and power management; and application layer services such as a special adaptation application (camera), a third-party application, system hibernation, and AOD.

(90) The following illustrates working processes of software and hardware of the electronic device **100** with reference to a photographing method in the embodiments of this application. The photographing method provided in the embodiments of this application is mainly implemented through mutual cooperation between a touch panel (TP) module, one or more of the foregoing physical elements, and software architecture layers of the electronic device **100**.

(91) The TP module receives a touch operation performed by a user on the touch display screen, and transfers the touch operation performed by the user to a physical status recognition module in the system library. A physical status monitoring module performs monitoring, recognizes the touch operation performed by the user, and so on. The physical status monitoring module transfers the touch operation performed by the user to a state machine management module of the electronic device, and controls a window management system at an FWK layer by using the state machine management module, to control a series of actions, display, and the like of the electronic device.

(92) In addition, implementation of the entire process further requires collaborative participation of a plurality of other modules and sensors, for example, a skin module at an application layer. The skin module is configured to control a display interface of a touchscreen and the like. Details are not described again in this application.

(93) For ease of understanding, in the following embodiments of this application, with reference to the accompanying drawings and application scenarios, an electronic device having the structures shown in FIG. 1 and FIG. 2 is used as an example to specifically describe the electronic device control method provided in this application. First, a printing scenario is taken as an example.

(94) The electronic device has a function of generating a printing task according to a printing object. The printing object may be an image, a file, a memo, and the like. For example, the printing object is an image, and an album application for browsing images is installed on the electronic device. A user may enter an album interface by clicking an icon of the album application. The album interface has images displayed according to a preset size and a preset arrangement rule. The images in the album interface may be selected through an operation such as long press. FIG. 3a is a schematic diagram of selecting an image in the album interface of the electronic device. The user, after selecting an image A, an image B, and an image C in the album interface, enters an interface **30a** as shown in FIG. 3a, a share control **31** is provided in the interface **30a**, the user clicks the share control **31**, and the electronic device displays an interface **30b** as shown in FIG. 3b. In the interface **30b**, a print control **32** and some other controls **33** are provided. The user may enter a task of printing an image object by triggering the print control **32**.

(95) In another example, the printing object is a file. The user enters an interface **30c** as shown in FIG. **3c**, a file manager is displayed in the interface **30c**, and the user selects a printing object **36** in the file manager by long press or another operation, and after triggering a share function of the printing object **36**, enters an interface **30d** as shown in FIG. **3d**. A task preview area **34** is provided in the interface **30d**. The user may enter a printing task corresponding to a file by triggering a print control **35** for the printing object **36** in the task preview area **34**.

(96) The above manners of entering the printing task are only examples, and the manner of entering the printing task is not limited in this application. The electronic device may further provide another manner of entering the printing task. Details are not described herein again.

(97) As an example, on the basis of FIG. **3b**, after a printing task corresponding to an image is entered, an interface **40a** shown in FIG. **4a** may be obtained. The interface **40a** includes at least a preview area **41** and a control area **42**.

(98) The preview area **41** is used for displaying a preview result corresponding to a printing object, that is, a preview object. The preview area **41** includes a fully displayed first preview object **411** and an incompletely displayed second preview object **412**. In the preview area **41**, a complete preview object may also be viewed by swiping in a preview object arrangement direction. For example, the user may swipe to the left in the preview area **41** to display, in the preview area **41**, a third preview object not displayed in the interface **40a**. Each preview object includes a selection control **413**. After the printing task is entered, the selection control of each preview object is selected, and the user may cancel the selection of the preview object by clicking the selection control **413**.

(99) The control area **42** is used for displaying a control, and the control may specifically include a start print control **421** and a printing parameter control. The printing parameter control may include: a printer selection control **422**, a copies selection control **423**, a range selection control **424**, and the like. When a printing parameter needs to be adjusted, the control may be clicked to trigger display of a control window on the interface **40a** for the user to select.

(100) As an example, the control displayed in the control area **42** of the interface **40a** may be a common control, which may be the printer selection control **422**, the copies selection control **423**, and the range selection control **424**, or another control in an image printing scenario. The user, after confirming a printing object and a printing parameter, may click the start print control **421** to trigger the electronic device to send a printing instruction to the printing device.

(101) There is a sign **43** above the control area **42**. The sign **43** is used for indicating that other undisplayed controls may also be provided in the control area **42** in addition to currently provided controls. The user swipes up with a single point in the interface **40a** on the basis of FIG. **4a** in further combination with FIG. **4b**. In response to the swiping operation, the interface **40a** changes to an interface **40c** as shown in FIG. **4c**. In the interface **40c**, an area occupied by the control area **42** in an entire display interface becomes larger, and the following controls hidden in **40a** are displayed: a paper type selection control **425**, a paper size selection control **426**, a printing manner selection control **427**, and a color mode selection control **428**. When the user clicks the above four controls, the corresponding control window can also be displayed.

(102) In **40c**, due to enlargement of the control area **42**, an area occupied by the preview area **41** in the display interface becomes smaller. The preview object in the preview area **41** also becomes smaller accordingly. A complete first preview object **411**, a complete second preview object **412**, and an incomplete third preview object **414** are displayed in the preview area **41**. Similarly, a complete third preview object may be displayed in the preview area **41** by swiping in the preview object arrangement direction.

(103) In an example of FIG. **4c**, seven controls are provided in the control area **42**. As an optional example, in order to provide more controls, a scroll bar may also be added to the control area **42** of **40c**. As shown in FIG. **4d**, in an interface **40d**, seven controls and a scroll bar **44** are displayed in the control area **42**. When the user pulls down the scroll bar **44**, hidden controls may be displayed,

such as a printing direction and a page margin.

(104) As an example, the user clicks the copies selection control **423** in the interface **40c**, **50a** as shown in FIG. **5a** is displayed, a copies selection window **51** is provided in the interface **50a**, copies required for printing may be selected in the copies selection window **51**, an OK control **511** is then clicked, the copies selection window **51** disappears, and the electronic device goes back to the interface **40c**.

(105) As an example, the user clicks the paper type selection control **425** in the interface **40c**, **50b** as shown in FIG. **5b** is displayed, a paper selection window **52** is provided in the interface **50b**, and a required paper type for printing may be selected in the paper selection window **52**. For example, the user selects plain paper, the paper selection window **52** disappears, and the electronic device goes back to the interface **40c**. The paper type is plain paper. In another example, the user clicks a cancel control **521**, the electronic device goes back to the interface **40c**, and the paper type remains the same as that before the paper selection window **52** pops up.

(106) As an example, the user clicks the printing manner selection control **427** in the interface **40c**, **50c** as shown in FIG. **5c** is displayed, a printing manner selection window **53** is provided in the interface **50c**, and a required printing manner, including double-sided printing or single-sided printing, may be selected in the printing manner selection window **53**. For example, in **50c**, the user selects single-sided printing, the printing manner selection window **53** disappears, and the electronic device goes back to the interface **40c**. The printing manner is single-sided printing. In another example, the user clicks a cancel control **531**, the electronic device goes back to the interface **40c**, and the printing manner remains the same as that before the printing manner selection window **53** pops up.

(107) As an example, the first preview object, the second preview object, and the third preview object have all been selected, and the user clicks the range selection control **424** in the interface **40c** to display an interface **50d** as shown in FIG. **5d**. A first range selection window **54** is provided in **50d**. A required printing range may be selected in the first range selection window **54**. The first range selection window may provide an option to print all, or provide an option to select a start page and an end page separately. For example, the user selects print all in **50d**. The user clicks the OK control **541** in **50d** again after selecting the printing range, the first range selection window **54** disappears, and the electronic device goes back to the interface **40c**.

(108) As an example, the first preview object and the third preview object have been selected, while the second preview object is not selected. In such a scenario, the user clicks the range selection control **424** in the interface **40c**, an interface **50e** as shown in FIG. **5e** is displayed, and another second range selection window **55** different from the first range selection window **54** is provided in the interface **50e**. An all print option **551**, a custom print option **552**, and a continuous print option **553** are provided in the second range selection window **55**. Optionally, the user selects the all print option **551** and clicks the OK control **554**, and the second range selection window **55** disappears. Go back to the interface **40c**. Optionally, the user selects the custom print option **552** and clicks the OK control **554**, and the second range selection window **55** disappears. Go back to the interface **40c**. Since the user selects the first preview object and the third preview object before entering the second range selection window **55**, a printing range corresponding to the custom print option **552** is images corresponding to the first preview object and the third preview object. Optionally, the user selects the continuous print option **553** and selects a start page in a start page selection area and an end page in an end page selection area, and after the user clicks the OK control **554**, the second range selection window **55** disappears. Go back to the interface **40c**.

(109) As an example, the user clicks the paper size selection control **426** in the interface **40c**, an interface **50f** as shown in FIG. **5f** is displayed, and a paper size selection window **56** is provided in the interface **50f**. A paper size provided in the paper size selection window **56** is a paper size that can be provided by a printing device currently connected to the electronic device. For example, the user selects A4, the paper size selection window **56** disappears, and the electronic device goes back

to the interface **40c**. The paper size is A4. In another example, the user clicks a cancel control **561**, the electronic device goes back to the interface **40c**, and the paper size remains the same as that before the paper size selection window **56** pops up.

(110) As an example, the user clicks the color mode selection control **428** in the interface **40c**, an interface **50g** as shown in FIG. **5g** is displayed, a color mode selection window **57** is provided in **50g**, and two options of a colored mode and a black-white mode are provided in the color mode selection window **57**. Optionally, the user selects the black-white mode, and at the same time, a preview object in the preview area **42** is displayed in the black-white mode, the color mode selection window **57** disappears, and the electronic device goes back to the interface **40c**.

Optionally, the user clicks a cancel control **571**, the color mode selection window **57** disappears, the electronic device goes back to the interface **40c**, and the color mode remains the same as that before the color mode selection window **57** pops up.

(111) Still referring to FIG. **4c**, there is a sign **45** above the control area **42**. The sign **45** is used for indicating that the current control area **42** may contract downwards. As an example, as shown in FIG. **4e**, the user swipes down with a single point in the interface **40c**, the control area **42** contracts downwards, the controls in the control area **42** remain in a same size and are reduced in number, and the electronic device displays an interface as shown in FIG. **4a**.

(112) In the solution provided in the above embodiments, both the control area and the preview area are areas that can expand or contract. When the user operates the control area to expand or contract, a size of the preview object in the preview area may change accordingly. The preview object is larger when the control area is in a contracting state. The preview object is smaller when the control area is in an expanding state, and the preview object may correspondingly change according to control in the control area. Based on the above solution, occlusion of the preview object by the control area is prevented while a perfect control is provided.

(113) It should be noted that in the absence of an operation conflict, the single-point swipe-up operation and single-point swipe-down operation above may be operations generated at any position in the interface. For example, in the interface **40b** of FIG. **4b**, there is only a single-point swipe-up operation, that is, an operation of pulling out the control area **42**, so the single-point swipe-up operation may be generated at any position in the interface **40a**. In another example, in FIG. **4e**, there is only a single-point swipe-down operation, that is, an operation of retracting the control area **42**, so the single-point swipe-down operation may be generated at any position in the interface **40c**.

(114) A second printing scenario is taken as an example. Still in the example of selecting three images in a camera interface **30a** shown in FIG. **3** as printing objects, after a printing task is entered, the electronic device displays another printing task interface **60a** as shown in FIG. **6a**. The interface **60a** includes at least a control area **61** and a preview area **62**. Three frequently used controls are provided in the control area **61**, and a plurality of preview objects are displayed in the preview area **62**. Not all the preview objects are completely displayed in the preview area **62**, and the user may view, in the preview area **62**, all the preview objects by performing a swipe operation in the preview object arrangement direction.

(115) There is a sign **621** below the control area **61**. The sign **621** is used for indicating that the control area **61** is allowed to be retracted upwards. There is a sign **622** below the preview area **62**. The sign **622** is used for indicating that there is other content that can be dragged out below the preview area **62**. As an example, the user swipes up with a single point in the interface **60a**, and in response to the above operation, the electronic device displays an interface **60b** as shown in FIG. **6b**. In the interface **60b**, the control area **61** is retracted upwards, the preview area **62** is moved upwards, and a background selection area **63** is displayed.

(116) It should be noted that after the preview area **62** is moved up, the background selection area **63** is not content that may be uniquely displayed below the preview area **62**, and other content may also be displayed below the preview area **62** moved up. Only the background selection area **63** is

taken as an example for illustration.

(117) A plurality of preset backgrounds are provided in the background selection area **63**, and the user may swipe in a direction in which the plurality of backgrounds are arranged, to browse more backgrounds allowed to be selected. As an example, the user selects a background **631**, and the first preview object **411** currently selected in the preview area **62** is displayed over the background **631**.

(118) In the interface **60b**, a sign **623** is also displayed above the background selection area **62**. The sign **623** is used for indicating that the background selection area **63** is allowed to be swiped up to display more content. The user performs a single-point swipe-up operation in the interface **60b** to drag out a position selection area **65**, and the electronic device displays an interface **60c** as shown in FIG. **6c**. The position selection area **65** is used for providing a plurality of position options for the preview object in the background. In the example of the interface **60c**, a center option **651** is selected, and the first preview object is centered and displayed on the selected background **631**.

(119) As an example, the user performs a single-point swipe-down operation in the interface **60c**, and the display interface of the electronic device changes from **60c** to the interface **60b**. The user performs a single-point swipe-down operation on the interface **60b**, and the display interface of the electronic device changes from **60b** to **60a**.

(120) In this example, at least three states as shown in **60a**, **60b**, and **60c** may be displayed in the printing task. In the three states, a position and a size of the preview area may change differently according to the user's operation, so that the preview object cannot be covered when the user calls up more content. When the user contracts some content, the preview object can occupy a larger area for display, thereby realizing a variable layout under different control requirements, preventing coverage of the preview object and facilitating the user to view a preview effect.

(121) A short video scenario is taken as an example below to illustrate the solution of this application. A short video application is installed on the electronic device, and the user starts the short video application through a preset operation on the electronic device. When the electronic device plays back a short video, the electronic device displays an interface **70a** as shown in FIG. **7a**. The interface **70a** includes a video playback area **71**, an information display area **72**, and a comment area **73**. The video playback area **71** is used for displaying a short video on a current page. The information display area **72** is used for displaying video information, such as a video name, video introduction information, and a topic carried by a video. The comment area **73** is used for displaying comment information of a current video. The video playback area **71** and the comment area **73** may be displayed in different areas of a same layer, and the information display area **72** may cover the video playback area **71**. In another example, the information display area **72** may also be on a same layer as the video playback area **71** and the comment area **73**. A plurality of operation controls **74** are also provided in an interface **70a**. The operation controls **74** are all displayed on a top layer, and partially overlap with the video playback area **71**, the information display area **72**, and the comment area **73**.

(122) A proportion of the short video displayed in the above video playback area **71** is not limited, and the video playback area **71** may be filled with the short video when proportions of the short video and the video playback area **71** are the same. The video may be centered and displayed in the video playback area **71** when the proportions of the short video and the video playback area **71** are different.

(123) TopN comments may be displayed in the comment area **73** according to a quantity of likes of the short video currently played back or according to a quantity of comment replies. When there is no comment on the short video, the comment area **73** may be hidden or display information for prompting the user to make comments, for example, Come and speak your mind!

(124) Still referring to FIG. **7a**, there is a sign **75** above the comment area **73**. The sign **75** is used for indicating that there is other content below the comment area. This part of content may be content belonging to the comment area **73** or another functional area, such as recommendation information for recommending other highly praised videos of a current host. Expanded content is

taken as comment information for illustration below.

(125) As an example, the user performs the single-point swipe-up operation in the interface **70a**, and the single-point swipe-up operation is generated in the video playback area **71**, specifically as shown in FIG. **7b**. The operation triggers swiping up of the short video in the video playback area **71** and playback of next recommended short video.

(126) As an example, the user performs a single-point swipe-up operation as shown in FIG. **7c** in the interface **70a**, and a down point of the single-point swipe-up operation is in the comment area **73**. In response to the above single-point swipe-up operation, the electronic device displays an interface **70d** as shown in FIG. **7d**. In the interface **70d**, the comment area **73** is pulled out, the video playback area **71** moves upwards, the operation control **74** is hidden, the video playback area **71** is reduced, and the short video in the video playback area **71** is proportionally reduced and displayed.

(127) In the case of more video comments, all the comments cannot be fully displayed in the comment area **73** pulled out. The comment area **73** pulled out includes a scroll bar **731**, and all comments on a current short video may be previewed by pulling the scroll bar **731**.

(128) As an example, referring to FIG. **7e**, in the example, a down point of the single-point swipe-down operation falls in the video playback area **71**, and an up point falls in the comment area **73**. In response to this operation, the comment area **73** pulled out is contracted, and the electronic device displays the interface **70a** as shown in FIG. **7a**. In another example, referring to FIG. **7f**, the user performs a single-point swipe-down operation in an interface **70e**, and comment content in the comment area **73** is scrolled up. When the comment content in the comment area **73** is pulled to the top, the comment area **73** pulled out is contracted, and the electronic device displays the interface **70a** as shown in FIG. **7a**. In another example, in response to a single-point swipe-down operation in which both a down point and an up point fall in the video playback area **71**, a previous short video is displayed in the video playback area **71**.

(129) As an example, referring to FIG. **7g**, the user performs a single-point swipe-up operation **77** in the interface **70e**, and a down point and an up point of the operation fall in the video playback area **71**. In response to this operation, next short video is displayed in the video playback area **71**. When the video playback area **71** is switched from the current video to the next short video, the comment area **73** is automatically closed, and layout of the interface is the same as that of **70a**.

(130) It should be noted that the above operations are only used as an example to illustrate some of the operations allowed in the interface **70d**, and other operation manners or combinations of operation manners may also be used for performing the above operations. Details are not described herein again.

(131) The above embodiments provide layout changes in the task interface including the preview area in three different scenarios. It may be understood that, in addition to the above three scenarios, in other scenarios, in order to take into account both control and preview, interface layout schemes that correspondingly adapt to a size and a position of the preview area according to different operations all fall within the protection scope of the solution.

(132) Still in the printing scenario, this solution may also have other implementations.

(133) FIG. **8d** is another schematic diagram of entering a printing task. An interface **800d** as shown in FIG. **8d** may be entered by setting more connections in the electronic device, a print control **85** in the interface **800d** is triggered, and the interface **800a** as shown in FIG. **8a** is entered. Two entries are provided in the interface **800a**. The first entry is a printer connection entry **81**, and the other entry is a printing entry **82** for entering a printing task. The user touches the printing entry **82** to enter the printing task. After the second printing entry **82** is selected in the interface **800a**, the electronic device displays a printing task interface **800b** as shown in FIG. **8b**. Two types of printing functions are provided in the interface **800b**, which are specifically a first-type printing function **83** and a second-type printing function **84**. In the interface **800b**, the first-type printing function **83** includes: a document printing function **831**, a full-size-image printing function **832**, a picture

printing function **833**, and an album printing function **834**.

(134) In the interface **800b** shown in FIG. **8b**, there is also a sign control **835** in the printing function area **83**, and the sign control **835** is used for indicating that other functions not displayed in the interface **800b** may also be provided. The user clicks the sign control **835**, and the electronic device displays an interface **800c** as shown in FIG. **8c**. More printing functions that the electronic device can provide are displayed in the interface **800c**, including: a scanning function **835**, a collage printing function **836**, an area cropping printing function **837**, a custom printing function **838**, and an ID card printing function **839**. In some examples, there may be more or fewer functions than in the interface **800c**.

(135) As an example, the user triggers the document printing function **831**, and the electronic device displays an interface **900a** as shown in FIG. **9a**. The interface **900a** includes a preview box **91** and a control area **92**. A document adding control **911** is displayed at a preset position in the preview box **91**. The user clicks the document adding control **911**, and the electronic device displays a document selection interface **900e** as shown in FIG. **9e**. The user selects a to-be-printed document in the document selection interface **900e** and clicks a completion control **96**. The electronic device enters a printing interface with a same layout as the interface **40a** and displays the to-be-printed document selected by the user in the preview area **41**.

(136) As an example, the user triggers the picture printing function **833**, and the electronic device displays an interface **900c** as shown in FIG. **9c**. The interface **900c** includes: a preview box **93** and a control area **94**. A picture adding control **931** is displayed at a preset position in the preview box **93**. The user clicks the picture adding control **931**, and the electronic device displays a picture selection interface **900d** as shown in FIG. **9d**. The user selects a to-be-printed picture in the picture selection interface **900d** and clicks the completion control **95**. The electronic device enters a printing interface with a same layout as the interface **40a** and displays the to-be-printed picture selected by the user in the preview area **41**.

(137) In the above embodiments, a document may be printed through the document printing function **831** or printed in the manner shown in FIG. **3c**. Document printing services provided by the two are the same, and a difference is as follows. When the document is printed through the document printing function **831**, the printing task is entered first, and then a to-be-printed document is selected. When the document is printed in the manner shown in FIG. **3c**, the to-be-printed document is selected first, and then the printing task is entered.

(138) In the above embodiments, a picture may be printed through the picture printing function **833** or printed in the manner shown in FIG. **3b**. Picture printing services provided by the two are the same, and a difference is as follows. When the picture is printed through the picture printing function **833**, the printing task is entered first, and then a to-be-printed picture is selected. When the picture is printed in the manner shown in FIG. **3b**, the to-be-printed picture is selected first, and then the printing task is entered.

(139) As an example, the user triggers the scanning function **835**, and the electronic device displays an interface **100a** as shown in FIG. **10a**. The interface **100a** includes a preview area **11** and a control area **12**. The user clicks a scanning start control **121**, and the electronic device executes a scanning task and displays an interface **100b** as shown in FIG. **10b**. In the interface **100b**, a control in the control area **12** cannot be triggered, and the sign **111** is used for identifying a number of pages currently scanned, for example, 1/1 means that a currently scanned page number is the first page and a total of one page is scanned. After the scanning of the current page, the electronic device displays an interface **100c** as shown in FIG. **10c**. A scanning result, a scanning result thumbnail **124**, a rescan control **122**, and a continue scan control **123** are displayed in the preview area **11** of the interface **100c**.

(140) The user clicks the rescan control **122** in the interface **100c**, and the electronic device displays an interface **100d** as shown in FIG. **10d** to display prompt information **13** in the interface **100d** to prompt the user that this scanning result may not be retained in the case of rescanning and

ask the user whether to continue the rescanning. If the user selects “continue”, the electronic device clears content that has been scanned in the preview area **11** and enters the interface **100b** for rescanning. If the user selects “cancel”, the electronic device displays the interface **100c**.

(141) The user clicks the continue scan control **123** in the interface **100c**, and the electronic device enters an interface similar to the interface **100b** to continue scanning. The sign **111** is 2/2. After the current scanning is completed, the electronic device displays an interface **100f** shown in FIG. **10f**. A first-page scanning result thumbnail **124** and a second-page scanning result thumbnail **125** are displayed in the interface **100f**.

(142) The user may also click a control **14** in the interface **100c**, and the electronic device displays an interface **100e** as shown in FIG. **10e**. A control window **15** is displayed in the interface **100e**. If the user chooses to save as a picture, the scanning result may be saved to the electronic device in a format of a picture. If the user chooses to save as a PDF, the scanning result may be saved to the electronic device in a format of a PDF.

(143) As an example, the user triggers the album printing function **834**, and the electronic device displays an interface **110a** as shown in FIG. **11a**. The interface **110a** includes a preview box **21** and a control area **22**. The user clicks an add picture control **211**, and the electronic device displays an image selection interface. The user selects a to-be-printed image in the image selection interface, and the electronic device displays an interface **110b** as shown in FIG. **11b**. In the interface **110b**, the to-be-printed image is displayed in the preview box **21** in a “suitable” display manner. The preview box **21** is not filled up with the to-be-printed image, the user may click a fill control **23**, the preview box **21** may be filled up with a to-print control, and an excess part may be cropped.

(144) In the interface **110a**, the control area **22** also includes a printer selection control, a copies selection control, and a paper size selection control. A sign **24** is included above the control area **22**. The sign **24** is used for indicating that more controls may also be provided in the control area **22**, and controls currently hidden in the control area **22** in the interface **110a** may be pulled out through a preset operation. After the controls currently hidden in the control area **22** are pulled out, the electronic device displays the interface **110b** as shown in FIG. **11b**. In the interface **110b**, a size of each control remains unchanged, and the control area **22** expands. Correspondingly, the preview box **21** becomes smaller, and a preview object in the preview frame **21** becomes smaller. A manner in which an interface layout changes as a result of the pulling or retraction of the hidden controls in the control area **22** is similar to the manner in which the preview area in FIG. **4a** to FIG. **4e** adapts to changes in the control area. Details are not described herein again.

(145) In the interface **110b** as shown in FIG. **11b**, a printing parameter may be adjusted through a paper size selection control **221** and a paper direction selection control **222**. After the user triggers the start print control **223**, if a printer permits, the electronic device controls a printer to determine whether actually loaded paper meets a set printing parameter. If a judgment result is yes, the electronic device controls the printer to perform printing. If the judgment result is no, the electronic device displays prompt information: whether printing is continued when printing with paper of a current size may be different from a preview effect or printing fails, and the electronic device controls the printer to perform printing when the user confirms to continue printing.

(146) As an example, the user triggers the ID card printing function **839**, and the electronic device displays an interface **120a** as shown in FIG. **12a**. The interface **120a** includes a scanning position prompt box **30** and prompt information **31**. The user may scan an ID card by clicking “Got it” in the prompt information **31**. The ID card two sides, and after scanning of one side, the electronic device prompts the user to scan the other side of the ID card. After scanning of the two sides of the ID card, the electronic device displays an interface **120b** as shown in FIG. **12b**. In the interface **120b**, front and back images of the ID card obtained by scanning are displayed in a preview area **302**.

(147) The interface **120b** also includes a save control **304**, a retake control **331**, and a go-to-print control **332**. The user triggers the save control **304**, and the electronic device saves a scanning

result of the ID card in the preview area **302**. The user triggers the retake control, and the electronic device returns to scan the ID card again. The user triggers the go-to-print control **332**, and the electronic device enters an ID card printing task. The ID card printing task is similar to the picture printing task, and a difference is that the controls in the control area may be the same. Details are not described herein again.

(148) As an example, the user triggers the full-size-image printing function **832**. Full-size-image printing is used for enlarging a to-be-printed image, then dividing the image into a plurality of parts, and printing each part as a separate page. A magnification (i.e., a quantity of divisions) and a division manner may be selected. As shown in FIG. **13a**, an interface **130a** includes a preview area **401**, a magnification selection control **402**, and a print control **403**. Dotted lines in the preview area **401** are used for indicating a manner in which the to-be-printed image is divided. In this example, the magnification is four.

(149) The user triggers the print control **403** in the interface **130a**, and the electronic device displays an interface **130b** as shown in FIG. **13b**. The interface **130b** includes a preview area **404** and a control area **405**. Each part of the divided to-be-printed image is previewed in the preview area **404** as a preview object. The control area **405** further includes more controls that can be pulled out. A manner in which an interface layout changes as a result of the pulling or retraction of the hidden controls in the control area **405** is similar to the manner in which the preview area in FIG. **4a** to FIG. **4e** adapts to changes in the control area. Details are not described herein again.

(150) As an optional example, the user clicks the collage printing function **836**, and the electronic device displays an interface **140a** as shown in FIG. **14a**. A preview area **141** and a control area **142** are provided in the interface **140a**. An add picture control **143** is provided in the control area **142**. The user triggers the add picture control **143**, and the electronic device may display the image selection interface. After the user selects and confirms three images on the image selection interface, the electronic device enters an interface **140b** as shown in FIG. **14b**. In the interface **140b**, the three selected images are displayed in the preview area **141** as preview objects. Optionally, the user selects ten images, of which first nine images form a first collage in a 3×3 layout and the last image forms a second collage with eight blank images.

(151) A layout style selection control **144** is provided in the control area **142**. After the layout style selection control **144** is triggered, the electronic device enters an interface **140c** as shown in FIG. **14c**. Various optional layout styles are provided in the interface **140c**, for example, 3×3, 2×2, 2×3, and the like. The user selects a 2×2 layout. The electronic device displays an interface **140d** as shown in FIG. **14d**. In the interface **140d**, the three selected images are displayed in the 2×2 layout.

(152) Similarly, in a collage printing scenario, the control area **142** may further include more controls that can be pulled out. A manner in which an interface layout changes as a result of the pulling or retraction of the hidden controls in the control area **142** is similar to the manner in which the preview area in FIG. **4a** to FIG. **4e** adapts to changes in the control area. Details are not described herein again.

(153) As an optional example, the user clicks the custom printing function **838**, and the electronic device displays the image selection interface. After the user selects and confirms an image on the image selection interface, the electronic device displays an interface **150** as shown in FIG. **15**. The interface **150** includes a preview area **151**, a paper size selection control **152**, and a print control **153**. The user clicks the paper size selection control **152**, the electronic device displays a paper size selection window, and the user may customize a paper size for printing in the window. After the user determines the paper size, the electronic device or printer determines whether the printer supports the paper size selected by the user. If a judgment result is no, the paper size selection window may pop up again. If a judgment result is yes, the paper size selection window is closed. After the user clicks the print control **153**, the electronic device may prompt a size of paper needing to be loaded. The size is a paper size adjusted by the user in the paper size selection window.

(154) As an optional example, the user clicks the area cropping printing function **837**, and the

electronic device displays the image selection interface. After the user selects and confirms a plurality of images on the image selection interface, the electronic device displays an interface **160a** as shown in FIG. **16a**. The interface **160a** includes a first preview area **161**, an auxiliary function area **162**, a second preview area **163**, and a print control **164**.

(155) Thumbnails of the plurality of images selected by the user are displayed in the second preview area **163**, and the user clicks a thumbnail **165** to select an image corresponding to the thumbnail. The image selected by the user in the second preview area **163** is displayed in the first preview area **161**. A cropping grid is also displayed in the first preview area **161**, and the user may crop a preview object in the first preview area **161** by adjusting the cropping grid. The user adjusts the cropping grid to a state in an interface **160b** as shown in FIG. **16b**, and the electronic device displays, in response to this cropping operation, a cropping effect in the first preview area **161**, specifically an interface **160c** as shown in FIG. **16c**.

(156) The auxiliary function area **162** includes Reset, Apply to all, and Extract a title. The user triggers Reset in the interface **160c**, and the electronic device goes back to the interface **160a**. The user triggers Apply to all in the interface **160c**, and the electronic device applies the cropping effect in the first preview area **161** to the plurality of images selected in the image selection interface and displays prompt information: the cropping effect has been applied to all the images. The user triggers Extract a title in the interface **160c**, and the electronic device displays a watermark position selection window. This window provides options for watermarking, including “Put on Top”, “Put at Bottom”, and “Close”. The user triggers the print control **164**, and the electronic device displays a printing interface similar to that in FIG. **4a**. The preview object is a cropped image.

(157) In the interface **800b** shown in FIG. **8b**, the second-type printing function **84** includes a couplet printing function **841** and a red-envelope printing function **842**. In couplet printing function **841**, an externally provided printing material may also be accessed to provide more printing functions. The couplet printing function **841** is taken as an example for illustration.

(158) As an example, the user triggers the couplet printing function **841** in the second-type printing function **84** in the interface **80b** shown in FIG. **8b**. The electronic device displays an interface **170a** as shown in FIG. **17a**. The interface **170a** includes: a first control area **171**, a preview area **172**, and a second control area **173**. The first control area **171** includes a control for selecting an upper scroll, a lower scroll, and a horizontal scroll in a couplet. The preview area **172** is used for displaying a couplet being edited. The second control area **173** is used for providing a plurality of editing items (for example, background, text, and handwriting), and content in the plurality of editing items. When the electronic device enters the couplet printing function, the “upper scroll” in the first control area **171** and a background control **173b** and a background option **173a** in the second control area **173** are selected by default.

(159) As an example, the user clicks a text option **173c** in the second control area **173**, and the electronic device displays an interface **170b** as shown in FIG. **17b**. Optional text contents, optional fonts, and optional colors are displayed in the second control area **173** of the interface **170b**. In the example, a content **173e**, a font **173d**, and a color **173f** are selected. Each content provided includes an upper scroll, a lower scroll, and a horizontal scroll. After selecting a content, the upper scroll, the lower scroll, and the horizontal scroll may all be determined according to the selected content. For example, if the content **173e** is selected, the upper scroll is “custom character” the lower scroll is “custom character”, and the horizontal scroll is “custom character”. In the example, part of the preview area **172** is blocked by the second control area **173**.

(160) In another example, the user clicks a text option **173c** in the second control area **173**, and the electronic device displays an interface **170c** as shown in FIG. **17c**. In the example, in response to the operation of clicking the text option **173c**, the preview area **172** is adaptively zoomed out and displayed, and the second control area **173** does not block the preview area **172**. The interface **170c** has same functions as other controls in the interface **170b**. Details are not described herein again.

(161) The user clicks a control **176** in the interface **170c**, and a “preview” option and a “save”

option may pop up in the interface **170c**. The user clicks the “save” option, and the currently edited couplet may be saved in the form of three images corresponding to the upper scroll, the lower scroll, and the horizontal scroll respectively in an album. The user clicks the “preview” option, and the electronic device displays an interface **170d** as shown in FIG. **17d**. A preview effect of the entire couplet (including the upper scroll, the lower scroll, and the horizontal scroll) is displayed in the interface **170d**.

(162) As shown in FIG. **17b**, a control **173g** in the second control area **173** may also be clicked. The electronic device enters an interface **170e** as shown in FIG. **17e**. A virtual keyboard **174** and a custom content window **177** are displayed in the interface **170e**. The user operates the virtual keyboard **174** to enter custom text into the custom content window **177**. The user may also select a font and a color of the custom text in the second control area **173**.

(163) As shown in FIG. **17b**, the user may also select controls **173h** and **173i** to enter a handwriting function. As an example, the electronic device displays an interface **170f** as shown in FIG. **17f**. An editing area **178** is displayed in the interface **170f**. The editing area **178** also includes a control **178a**, a control **178b**, a control **178c**, and a control **178d**. The user writes in the editing area **178**, and after one unit of handwriting (for example, a character) has been written, the user may click the control **178d** to write next unit of the handwriting in the upper scroll. In this case, the first unit of the handwriting that has been written is displayed on the couplet in the preview area **172**. Alternatively, if the handwriting already exists in the preview area **172**, the control **178c** may be clicked to write a previous unit of the handwriting. During the writing, a delete control **178a** may be clicked to delete the currently edited handwriting, or a close control **178b** may be clicked to exit the editing.

(164) Optionally, each text has a corresponding position and size in the upper scroll in the preview area **172**. In FIG. **17f**, a size and a position of the first character of the upper scroll are shown in a virtual box **172a** (**172a** is only for illustration and may not be displayed in the interface **170f**). After the user finishes writing the first character and clicks the control **178d**, the first character currently written may be reduced or enlarged so that the written handwriting conforms to a size of **172a**, and then the reduced or enlarged handwriting is displayed at a location of **172a**. In an interface **170i** as shown in FIG. **17i**, after the user clicks the control **178d**, the written character “custom character” is displayed at the location of **172a** after zooming, and the user may write next character in the couplet in the editing area **178**.

(165) The editing area **178** further includes prompt information. The prompt information is displayed in the form of x/y. y indicates how many characters are included in the currently written upper scroll, and x is used for indicating a serial number of a currently written character in the upper scroll. In the example, the prompt information is 1/7. That is, there are 7 characters in the upper scroll, and the first character is currently being written. In the example, part of the preview area **172** is blocked by the second control area **173**.

(166) When the currently written character is the first character, the prompt information is 1/7, and the control **178c** may be grayed out. When the currently written character is the last character, the prompt information is 7/7, and the control **178d** may be changed from “next” to “complete”. In this case, the user clicks the control **178d**, and the editing area **178** is closed.

(167) In another example, after the handwriting function is entered, the electronic device displays an interface **170g** as shown in FIG. **17g**. In the example, in response to the user's operation of selecting the controls **173h** and **173i**, the preview area **172** is adaptively reduced, and the second control area **173** does not block the preview area **172**. After the editing area **178** is closed, the preview area **172** is restored to an original size.

(168) As shown in an interface **170h** shown in FIG. **17h**, the user clicks a print control **175**, and prompt information **179** is displayed to prompt the user a paper size required to print the upper scroll. The user chooses to start printing after placing the paper size in the printer, the electronic device sends a printing instruction to the printing device, and the printing device prints the upper

scroll. Paper that the user puts in the printer may be original paper without color.

(169) The printing device, after printing the upper scroll, returns information indicating that the printing has been completed to the electronic device, and the electronic device automatically jumps to an editing interface for the lower scroll. Similarly, the user, after editing the lower scroll, may print the lower scroll by clicking the print control **175**, the printing device, after printing the lower scroll, returns information indicating that the printing has been completed to the electronic device, and the electronic device automatically jumps to an editing interface for the horizontal scroll. The user, after editing the horizontal scroll, may print the horizontal scroll by clicking the print control **175**.

(170) Optionally, the size of the paper put into the printing device by the user does not match the paper size in the prompt information **179**. The printing device detects that the paper size of the current paper does not match the paper size required for printing, and may send corresponding information to the electronic device. The electronic device may display prompt information to prompt the user to change paper.

(171) Then, red-envelope printing is described. In the interface **800b** as shown in FIG. **8b**, the user clicks the red-envelope printing function **842**. An interface **180a** as shown in FIG. **18a** is entered. The interface **180a** includes a first control area **181**, a preview area **182**, and a second control area **183**. A variety of optional themes are provided in the first control area **181**, such as trend, the Spring Festival, and the Year of Tiger. Each theme has a corresponding background. In the example, the trend theme is selected. A background in the second control area **183** is the background corresponding to the trend theme. A thumbnail of a to-be-printed red envelope is displayed in the preview area **182**, in which dotted lines are used for indicating traces of folding and trimming. That is, the red envelope may be obtained by trimming and folding the printed paper according to the dotted lines. The traces of folding and trimming may be traces on the printed paper, or traces formed on the paper in a manner such as double-sided printing.

(172) The user may add text to the red envelope. The user may enter an interface **180b** shown in FIG. **18b** by clicking a “text” control in the second control area **183** of the interface **180a**. A text input box **184** is displayed on the interface **180b**, the user clicks the text input box **184**, and the electronic device displays an interface **180c** as shown in FIG. **18c**. A text input box **186**, a virtual keyboard **185**, and a second control area **183** are displayed in the interface **180c**. The user selects the font as “cursive script” in the second control area **183**, and enters “Happy New Year!” in the text input box **186** through the virtual keyboard **185**. After the user clicks the OK control, the entered text “Happy New Year!” is displayed in the preview area **182** in the font of cursive script. The user may move a position of the text input box **186** or move a position of the entered text.

(173) The user may also add a sticker to the red envelope. The user may enter an interface **180d** shown in FIG. **18d** by clicking a “sticker” control in the second control area **183** of the interface **180a**. An alternative picture that may be used as a sticker is displayed in the interface **180d**. In the example, the user selects a sticker **183a**, and a sticker **187** is displayed in the preview area **182**. The user may also move a position of the sticker **187** in the preview area **182**. The user may also click the control **183b**, and in response to the user's operation of clicking the control **183b**, clear the sticker in the preview area **182**.

(174) Still in the interface **180d**, the user clicks a control **188**, and a “preview” option and a “save” option may pop up. The user clicks the “save” option, and the currently edited red envelope may be saved in the album as an image. The user clicks the “preview” option to enter an interface **180e** as shown in FIG. **18e**. A preview effect **188a** of the printed red envelope is displayed in the interface **180e**. In the preview effect **188a**, dotted lines in the preview area **182** may also be displayed to facilitate cropping and folding by the user. Double-sided printing is also possible, the front is as shown in the preview effect **188a**, and the dotted lines in the preview area **182** are printed on the back.

(175) Still in the interface **180d**, the user clicks a control **189**, and the electronic device enters an

interface **180f** as shown in FIG. **18f**. In the interface **180f**, prompt information **182a** is displayed to prompt the user a paper size required to print the red envelope. The user chooses to start printing after preparing the paper size, the electronic device sends a printing instruction to the printing device, and the printing device prints the red envelop.

(176) FIG. **19** is a flowchart of a printing method according to an embodiment of this application. The method is applicable to the electronic device shown in FIG. **1**. As shown in FIG. **19**, the method mainly includes the following steps.

(177) **S191**: Display a first interface, the first interface including: a first thumbnail and a first quantity of controls, the first thumbnail corresponding to a first file, the first thumbnail having a first size, and the first quantity of controls including a first control.

(178) The first interface may be the interface **40a** as shown in FIG. **4a**. The first thumbnail may be a first preview object **411** and an incompletely displayed second preview object **412**. The first quantity of controls may include: a start print control **421**, a printer selection control **422**, a copies selection control **423**, and a range selection control **424**. The first control may be the start print control **421**.

(179) **S192**: Send a printing instruction to a printing device in response to a first operation on the first control, the printing instruction indicating printing the first file.

(180) The first operation may be an operation in which the user clicks the start print control **421**, the user clicks the start print control **421**, the electronic device sends an instruction to the printing device, and the printing device performs the printing task.

(181) **S193**: Display a second interface in response to a second operation acting on the first interface, the second interface including: a second thumbnail and a second quantity of controls, the second quantity of controls including the first control, the second thumbnail corresponding to the first file, the second thumbnail having a second size, the second size being smaller than the first size, the second quantity being greater than the first quantity, the second interface being of a same size as the first interface.

(182) In the interface **40b** as shown in FIG. **4b**, the above second operation may be a swipe-up operation in the interface **40b**. The second interface may be shown in the interface **40c** as shown in FIG. **4c**. The second thumbnail may be a complete first preview object **411**, a complete second preview object **412**, and an incomplete third preview object **414** in the interface **40c**. The second quantity of controls include: a start print control **421**, a printer selection control **422**, a copies selection control **423**, a range selection control **424**, a paper type selection control **425**, a paper size selection control **426**, a printing manner selection control **427**, and a color mode selection control **428**.

(183) As can be seen, in the above embodiment, the user performs a second operation on the first interface, so that more controls are displayed in the second interface than in the first interface, so as to provide more control items for the user. In addition, the first thumbnail is reduced to the second thumbnail, preventing occlusion of the thumbnail by the control, which is convenient for the user to view and improves user experience.

(184) In an implementation, the displaying a second interface in response to a second operation acting on the first interface includes: reducing, in response to the second operation acting on the first interface, the first thumbnail from the first size to the second size to obtain the second thumbnail; and the first quantity of controls move according to the second operation, and a third quantity of controls are added to the second interface to obtain the second quantity of controls, where a sum of the first quantity and the third quantity is the second quantity.

(185) Referring to FIG. **4a**, FIG. **4b**, and FIG. **4c**, the user drags out more controls through a swipe-up operation, and the preview area **41** and the preview object in the preview area **41** are also adaptively reduced, thereby preventing occlusion of the preview object by the controls. The third quantity of controls may include: a paper type selection control **425**, a paper size selection control **426**, a printing manner selection control **427**, and a color mode selection control **428**.

(186) In an implementation, the first thumbnail is located on an upper side of the first quantity of controls, and the second operation is a swipe-up operation.

(187) In an implementation, after the displaying a second interface in response to a second operation acting on the first interface, the first interface is displayed in response to a third operation acting on the second interface.

(188) As shown in FIG. 4e, the user swipes down in the second interface, some controls are retracted, and the preview area 41 and the preview area 41 are both enlarged and restored to the interface 40a as shown in FIG. 4a.

(189) In an implementation, the first quantity of controls further include a second control, a third control, and a fourth control, and a third interface is displayed in response to a fourth operation acting on the second control, the third interface including: an option of a printing device; a fourth interface is displayed in response to a fifth operation acting on the third control, the fourth interface including: an option of print copies; and a fifth interface is displayed in response to a sixth operation acting on the fourth control, the fifth interface including: an option of a printing range; where the sending a printing instruction to a printing device in response to a first operation on the first control includes: sending, in response to the first operation on the first control, a printing instruction carrying a first printing parameter to a printing device selected in the third interface, the first printing parameter including print copies selected in the fourth interface and a printing range selected in the fifth interface.

(190) The second control may be the printer selection control 422. The third control may be the copies selection control 423, and the fourth interface may be shown in FIG. 5a. The fourth control may be the range selection control 424, and the fifth interface may be shown in FIG. 5d or FIG. 5e.

(191) In an implementation, the second quantity of controls further include a fifth control, a sixth control, a seventh control, and an eighth control, and a sixth interface is displayed in response to a seventh operation acting on the fifth control, the sixth interface including: an option of a paper type; a seventh interface is displayed in response to an eighth operation acting on the sixth control, the seventh interface including: an option of a paper size; an eighth interface is displayed in response to a ninth operation acting on the seventh control, the eighth interface including: an option of a printing manner, the printing manner including: double-sided printing and single-sided printing; and a ninth interface is displayed in response to a tenth operation acting on the eighth control, the ninth interface including: an option of a color mode, the option of the color mode including: a black-white mode and a colored mode; where the sending a printing instruction to a printing device in response to a first operation on the first control includes: sending, in response to the first operation on the first control, a printing instruction carrying a second printing parameter to the printing device, the second printing parameter including: a paper type selected in the sixth interface, a paper type selected in the seventh interface, a printing manner selected in the eighth interface, and a color mode selected in the ninth interface.

(192) The fifth control may be the paper type selection control 425, and the sixth interface may be shown in FIG. 5b. The sixth control may be the paper size selection control 426, and the seventh interface may be shown in FIG. 5f. The seventh control may be the printing manner selection control 427, and the eighth interface may be shown in FIG. 5c. The eighth control may be the color mode selection control 428, and the ninth interface may be shown in FIG. 5e.

(193) In an implementation, the first quantity of controls further include a ninth control, the ninth control corresponds to a background image, an icon of the ninth control is displayed as a third thumbnail of the corresponding background image, in response to an eleventh operation on the ninth control, the first thumbnail is displayed on a background image selected by the eleventh operation, and the background image selected by the eleventh operation is the background image corresponding to the ninth control selected by the eleventh operation.

(194) In the example, the first interface may be shown in FIG. 6b. The first control may be the start print control. The ninth control may be a background selection control in the background selection

area **63**. Each background selection control corresponds to an optional background image. An icon of each background selection control is a thumbnail of the background image corresponding thereto, that is, the third thumbnail. In the example of FIG. **6b**, the user selects a background **631**, and the first preview object **411** is displayed over the background **631**. The second interface may be shown in FIG. **6c**.

(195) In an implementation, the second quantity of controls further include a tenth control, the tenth control corresponds to a position relationship between the first thumbnail and the background image, an icon of the tenth control is a schematic diagram of the corresponding position relationship, in response to a twelfth operation on the tenth control and according to a position relationship selected by the twelfth operation, the first thumbnail is displayed on the background image selected by the eleventh operation, and the position relationship selected by the twelfth operation is the position relationship corresponding to the tenth control selected by the twelfth operation.

(196) Referring to FIG. **6c**, the second quantity of controls may include controls in the background selection area **63** and the position selection area **65**. The tenth control may be a position selection control in the position selection area **65**. Each position selection control corresponds to a position relationship (the position relationship is used for representing a position relationship between the first thumbnail and a background thereof), and the icon of each position selection control is a schematic diagram of the position relationship corresponding thereto. In the schematic diagram of FIG. **6c**, the user clicks the center option **651**, and the first preview object is centered and displayed on the selected background **631**.

(197) In an implementation, the first thumbnail is located on an upper side of the first quantity of controls, and a tenth interface is displayed in response to a thirteenth operation acting on the first interface. The tenth interface includes the first thumbnail and a fourth quantity of controls. The first thumbnail has the first size, and the fourth quantity of controls are located on an upper side of the first thumbnail.

(198) In FIG. **6b**, the user causes, through a swipe-down operation, the electronic device to display the third interface as shown in FIG. **6a**. In the third interface, the fourth quantity of controls may include the control in the control area **61**.

(199) In an implementation, the thirteenth operation is a swipe-down operation.

(200) An embodiment of this application further provides an electronic device, including a memory configured to store a computer program instruction and a processor configured to execute the program instruction. When the computer program instruction is executed by the processor, the electronic device is triggered to perform the above related method steps to implement the method in the foregoing embodiments.

(201) An embodiment of this application further provides a computer-readable storage medium. The computer-readable storage medium stores a computer instruction, and the computer instruction, when running on a terminal device, causes the terminal device to perform the related method steps, to implement the method in the foregoing embodiments.

(202) An embodiment of this application further provides a computer storage medium. The computer storage medium stores a computer instruction, and the computer instruction, when running on a terminal device, causes the terminal device to perform the related method steps to implement the method in the foregoing embodiments.

(203) An embodiment of this application further provides a computer program product. When the computer program product runs on a computer, a computer is enabled to perform the related steps to implement the method in the foregoing embodiments.

(204) In addition, an embodiment of this application further provides an apparatus. The apparatus may be specifically a chip, a component, or a module. The apparatus may include a processor and a memory that are connected. The memory is configured to store computer-executable instructions. When the apparatus runs, the processor may execute the computer-executable instructions stored in

the memory, to cause the chip to perform the method in the foregoing method embodiments.

(205) The electronic device, the computer storage medium, the computer program product, or the chip provided in the embodiments of this application may be configured to perform the corresponding method provided above. Therefore, for beneficial effects that can be achieved, refer to the beneficial effects of the corresponding method provided above. Details are not described herein again.

(206) Based on the foregoing descriptions of the implementations, a person skilled in the art may understand that, for the purpose of convenient and brief description, division of the foregoing functional modules is taken as an example for illustration. In actual application, the foregoing functions may be allocated to different functional modules and implemented according to a requirement, that is, an inner structure of an apparatus is divided into different functional modules to implement all or some of the functions described above.

(207) In the several embodiments provided in this application, it should be understood that the disclosed apparatus and method may be implemented in other manners. For example, the described apparatus embodiment is merely exemplary. For example, the module or unit division is merely logical function division and may be other division in actual implementation. For example, a plurality of units or components may be combined or integrated into another apparatus, or some features may be ignored or not performed. In addition, the displayed or discussed mutual couplings or direct couplings or communication connections may be implemented through some interfaces. The indirect couplings or communication connections between the apparatuses or units may be implemented in electronic, mechanical, or other forms.

(208) The units described as separate parts may or may not be physically separate, and parts displayed as units may be one or more physical units, may be located in one place, or may be distributed in multiple different places. Some or all of the units may be selected according to actual needs to achieve the objectives of the solutions of the embodiments.

(209) In addition, functional units in the embodiments of this application may be integrated into one processing unit, or each of the units may be physically separated, or two or more units may be integrated into one unit. The integrated unit may be implemented in the form of hardware, or may be implemented in a form of a software functional unit.

(210) If the integrated unit is implemented in the form of a software functional unit and sold or used as an independent product, the integrated unit may be stored in a readable storage medium. Based on such understanding, the technical solutions in the embodiments of this application essentially, or the part contributing to the prior art, or all or some of the technical solutions may be implemented in the form of a software product. The software product is stored in a storage medium and includes several instructions for instructing a device (which may be a single-chip microcomputer, a chip, or the like) or a processor to perform all or some of the steps of the methods described in the embodiments of the present disclosure. The foregoing storage medium includes: any medium that may store program code, such as a USB flash drive, a removable hard disk, a read only memory (ROM), a random access memory (RAM), a magnetic disk, or a compact disc.

(211) The foregoing descriptions are merely specific implementations of this application, but are not intended to limit the protection scope of this application. Any variation or replacement readily figured out by a person skilled in the art within the technical scope disclosed in this application shall fall within the protection scope of this application. Therefore, the protection scope of this application shall be subject to the protection scope of the claims.

Claims

1. An electronic device, comprising: one or more processors; and a memory coupled to the one or more processors, wherein the memory is configured to store instructions that, when executed by the one or more processors, cause the electronic device to: display a first interface, the first interface

comprising a first thumbnail and a first quantity of controls, the first thumbnail corresponding to a first file, the first thumbnail having a first size, and the first quantity of controls comprising a first control; send a printing instruction to a printing device in response to a first operation on the first control, the printing instruction indicating printing the first file; and display a second interface in response to a second operation acting on the first interface, the second interface comprising a second thumbnail and a second quantity of controls, the second quantity of controls comprising the first control, the second thumbnail corresponding to the first file, the second thumbnail having a second size, the second size being smaller than the first size, the second quantity being greater than the first quantity, the second interface being of a same size as the first interface; wherein the first quantity of controls further comprises a ninth control, wherein the ninth control corresponds to a background image, wherein an icon of the ninth control is displayed as a third thumbnail of the corresponding background image, and the instructions, when executed by the one or more processors, further cause the electronic device to: display, in response to an eleventh operation on the ninth control, the first thumbnail on a background image selected by the eleventh operation, the background image selected by the eleventh operation being the background image corresponding to the ninth control selected by the eleventh operation.

2. The electronic device according to claim 1, wherein the instructions, when executed by the one or more processors, further cause the electronic device to be configured to: in response to the second operation acting on the first interface, reduce the first thumbnail from the first size to the second size to obtain the second thumbnail; and move the first quantity of controls according to the second operation, and add a third quantity of controls to the second interface to obtain the second quantity of controls, wherein a sum of the first quantity and the third quantity is the second quantity.

3. The electronic device according to claim 1, wherein the first thumbnail is located on an upper side of the first quantity of controls, and the second operation is a swipe-up operation.

4. The electronic device according to claim 1, wherein after the displaying the second interface in response to the second operation acting on the first interface, the instructions, when executed by the one or more processors, further cause the electronic device to be configured to: display the first interface in response to a third operation acting on the second interface.

5. The electronic device according to claim 1, wherein the first quantity of controls further comprises a second control, a third control, and a fourth control, and the instructions, when executed by the one or more processors, further cause the electronic device to be configured to: display a third interface in response to a fourth operation acting on the second control, the third interface comprising: an option of a printing device; display a fourth interface in response to a fifth operation acting on the third control, the fourth interface comprising: an option of print copies; display a fifth interface in response to a sixth operation acting on the fourth control, the fifth interface comprising: an option of a printing range; and in response to the first operation on the first control, send a printing instruction carrying a first printing parameter to a printing device selected in the third interface, the first printing parameter comprising print copies selected in the fourth interface and a printing range selected in the fifth interface.

6. The electronic device according to claim 5, wherein the second quantity of controls further comprises a fifth control, a sixth control, a seventh control, and an eighth control, and the instructions, when executed by the one or more processors, further cause the electronic device to be configured to: display a sixth interface in response to a seventh operation acting on the fifth control, the sixth interface comprising: an option of a paper type; display a seventh interface in response to an eighth operation acting on the sixth control, the seventh interface comprising: an option of a paper size; display an eighth interface in response to a ninth operation acting on the seventh control, the eighth interface comprising: an option of a printing manner, the printing manner comprising: double-sided printing and single-sided printing; display a ninth interface in response to a tenth operation acting on the eighth control, the ninth interface comprising: an option

of a color mode, the option of the color mode comprising: a black-white mode and a colored mode; and in response to the first operation on the first control, send a printing instruction carrying a second printing parameter to the printing device, the second printing parameter comprising: a paper type selected in the sixth interface, a paper type selected in the seventh interface, a printing manner selected in the eighth interface, and a color mode selected in the ninth interface.

7. The electronic device according to claim 1, wherein the second quantity of controls further comprises a tenth control, wherein the tenth control corresponds to a position relationship between the first thumbnail and the background image, wherein an icon of the tenth control is a schematic diagram of the corresponding position relationship, and the instructions, when executed by the one or more processors, further cause the electronic device to be configured to: display, in response to a twelfth operation on the tenth control and according to a position relationship selected by the twelfth operation, the first thumbnail on the background image selected by the eleventh operation, the position relationship selected by the twelfth operation being the position relationship corresponding to the tenth control selected by the twelfth operation.

8. The electronic device according to claim 1, wherein the first thumbnail is located on an upper side of the first quantity of controls, and the instructions, when executed by the one or more processors, further cause the electronic device to be configured to: display a tenth interface in response to a thirteenth operation acting on the first interface, the tenth interface comprising the first thumbnail and a fourth quantity of controls, wherein the first thumbnail has the first size, and the fourth quantity of controls are located on an upper side of the first thumbnail.

9. The electronic device according to claim 8, wherein the thirteenth operation is a swipe-down operation.

10. An electronic device control method, the method comprising: displaying a first interface, the first interface comprising a first thumbnail and a first quantity of controls, the first thumbnail corresponding to a first file, the first thumbnail having a first size, and the first quantity of controls comprising a first control; sending a printing instruction to a printing device in response to a first operation on the first control, the printing instruction indicating printing the first file; and displaying a second interface in response to a second operation acting on the first interface, the second interface comprising a second thumbnail and a second quantity of controls, the second quantity of controls comprising the first control, the second thumbnail corresponding to the first file, the second thumbnail having a second size, the second size being smaller than the first size, the second quantity being greater than the first quantity, and the second interface being of a same size as the first interface; wherein the first quantity of controls further comprises a ninth control, wherein the ninth control corresponds to a background image, wherein an icon of the ninth control is displayed as a third thumbnail of the corresponding background image, and method further comprises: displaying, in response to an eleventh operation on the ninth control, the first thumbnail on a background image selected by the eleventh operation, the background image selected by the eleventh operation being the background image corresponding to the ninth control selected by the eleventh operation.

11. The method according to claim 10, wherein the second quantity of controls further comprises a tenth control, wherein the tenth control corresponds to a position relationship between the first thumbnail and the background image, wherein an icon of the tenth control is a schematic diagram of the corresponding position relationship, and the method further comprises: displaying, in response to a twelfth operation on the tenth control and according to a position relationship selected by the twelfth operation, the first thumbnail on the background image selected by the eleventh operation, the position relationship selected by the twelfth operation being the position relationship corresponding to the tenth control selected by the twelfth operation.

12. The method according to claim 10, wherein the first thumbnail is located on an upper side of the first quantity of controls, and the method further comprises: displaying a tenth interface in response to a thirteenth operation acting on the first interface, the tenth interface comprising the

- first thumbnail and a fourth quantity of controls, wherein the first thumbnail has the first size, and the fourth quantity of controls are located on an upper side of the first thumbnail.
13. The method according to claim 12, wherein the thirteenth operation is a swipe-down operation.
14. A non-transitory computer-readable storage medium storing a program, wherein, when the program is executed, a computing device is controlled to perform operations comprising: displaying a first interface, the first interface comprising a first thumbnail and a first quantity of controls, the first thumbnail corresponding to a first file, the first thumbnail having a first size, and the first quantity of controls comprising a first control; sending a printing instruction to a printing device in response to a first operation on the first control, the printing instruction indicating printing the first file; and displaying a second interface in response to a second operation acting on the first interface, the second interface comprising a second thumbnail and a second quantity of controls, the second quantity of controls comprising the first control, the second thumbnail corresponding to the first file, the second thumbnail having a second size, the second size being smaller than the first size, the second quantity being greater than the first quantity, and the second interface being of a same size as the first interface; wherein the first quantity of controls further comprises a ninth control, wherein the ninth control corresponds to a background image, wherein an icon of the ninth control is displayed as a third thumbnail of the corresponding background image, and wherein, when the program is executed, the computing device is controlled to perform operations comprising: displaying, in response to an eleventh operation on the ninth control, the first thumbnail on a background image selected by the eleventh operation, the background image selected by the eleventh operation being the background image corresponding to the ninth control selected by the eleventh operation.
15. The computer-readable storage medium according to claim 14, wherein the second quantity of controls further comprises a tenth control, wherein the tenth control corresponds to a position relationship between the first thumbnail and the background image, wherein an icon of the tenth control is a schematic diagram of the corresponding position relationship, and wherein, when the program is executed, the computing device is controlled to perform operations comprising: displaying, in response to a twelfth operation on the tenth control and according to a position relationship selected by the twelfth operation, the first thumbnail on the background image selected by the eleventh operation, the position relationship selected by the twelfth operation being the position relationship corresponding to the tenth control selected by the twelfth operation.
16. The computer-readable storage medium according to claim 14, wherein the first thumbnail is located on an upper side of the first quantity of controls, and wherein, when the program is executed, the computing device is controlled to perform operations comprising: displaying a tenth interface in response to a thirteenth operation acting on the first interface, the tenth interface comprising the first thumbnail and a fourth quantity of controls, wherein the first thumbnail has the first size, and the fourth quantity of controls are located on an upper side of the first thumbnail.
17. The computer-readable storage medium according to claim 16, wherein the thirteenth operation is a swipe-down operation.
-