

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12400455
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Brakob; Christopher et al.

Risk-based adaptive responses to user activity in a retail environment

Abstract

The disclosed technology provides for automatically detecting and responding to potentially suspicious or risky activity in a retail environment. A method can include receiving, from monitoring devices in a retail environment, a stream of activity data, applying a model to the stream of activity data to identify a portion of the data corresponding to guest activity during a checkout process, identifying whether a risk event is associated with the activity, determining a guest risk impact score, selecting (i) a particular manual response from among candidate manual responses and (ii) a particular automated response from among candidate automated responses based on the risk impact score satisfying manual response criteria and/or automated response criteria, transmitting instructions to a POS terminal to implement the particular automated response, and/or transmitting instructions to implement the particular manual response to one or more mobile devices, that prompt employees to perform the manual response.

Inventors: Brakob; Christopher (Minneapolis, MN), Sommer; Ethan (Minneapolis, MN)

Applicant: Target Brands, Inc. (Minneapolis, MN)

Family ID: 1000008782689

Assignee: Target Brands, Inc. (Minneapolis, MN)

Appl. No.: 18/298124

Filed: April 10, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230386217 A1	Nov. 30, 2023

Related U.S. Application Data

us-provisional-application US 63346767 20220527

Publication Classification

Int. Cl.: G06V20/52 (20220101); G06Q20/20 (20120101); G06V10/70 (20220101); G06V20/40 (20220101)

U.S. Cl.:

CPC G06V20/52 (20220101); G06Q20/208 (20130101); G06V10/70 (20220101); G06V20/44 (20220101); G06V2201/07 (20220101)

Field of Classification Search

CPC: G06V (20/52); G06V (10/70); G06V (20/44); G06V (2201/07); G06Q (20/208)

USPC: 340/540

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7673797	12/2009	Edwards	235/383	G06Q 30/00
8856032	12/2013	Carlegren	705/16	G06Q 20/208
10339511	12/2018	Aziz	N/A	G06Q 20/382
11455641	12/2021	Shahidzadeh	N/A	H04L 67/306
2012/0323621	12/2011	Carlegren et al.	N/A	N/A
2014/0176719	12/2013	Migdal	348/150	G08B 29/188
2021/0280027	12/2020	Wen	N/A	G08B 13/19608
2023/0130735	12/2022	Perrucci	382/103	G06V 20/53

Primary Examiner: McNally; Kerri L

Attorney, Agent or Firm: Barnes & Thornburg LLP

Background/Summary

INCORPORATION BY REFERENCE (1) This application claims priority to U.S. Provisional Application Ser. No. 63/346,767 entitled “Risk-Based Adaptive Responses to User Activity in a Retail Environment,” filed on May 27, 2022, the disclosure of which is incorporated by reference in its entirety.

TECHNICAL FIELD

(1) This document generally describes devices, systems, and methods related to automatically detecting risky or suspicious user activity within a retail environment, such as through analysis of multiple different sensor signals monitoring the retail environment, and determining appropriate human and/or automated system responses in response to such automatically detected risky/suspicious activity.

BACKGROUND

(2) Retailer environments, such as grocery stores, receive many different types of customers. Some

customers can enter a store with the intention of purchasing items. Typically, customers enter a store, collect items they wish to purchase, and then proceed to a checkout lane to purchase the items they have collected. Occasionally customers may intentionally or unintentionally leave a store without paying for some items, though. For example, some customers may forget about items that are located underneath other items, such as items located in the bottom of a shopping cart, and may leave the store without processing those items as part of a checkout process. In other instances, customers may intentionally leave a store without paying for items, and may take measures to hide their activity, such as concealing items inside of a bag or clothing, or potentially swapping barcodes with other items of lower value so that the customer goes through the checkout process but pays for the lower value item identified by the barcode, even though they are leaving with the higher value physical item. Leaving a store without paying for the full value of the item may be considered shoplifting or stealing, and may be considered a shortage with regard to inventory levels in stores.

(3) Some customers can enter a store with intention to cause harm or raise physical and personal safety concerns. For example, a customer can enter the store with a gun holster on their belt, either intentionally (e.g., they intend to cause harm or fear in other customers in the store) or unintentionally (e.g., they forgot to take off the gun holster before entering the store). As another example, a customer can move around the store with body posture and actions intended or unintentionally causing physical or personal safety concerns. As another example, a customer may verbally or physically harass, assault, or abuse another customer or an employee of the store. Any of these actions can be considered safety risks in a store.

(4) Stores may be equipped with various technology that is capable of providing information on customers who enter and leave a store while engaging in risky or suspicious activity. For example, stores may have a camera security system installed that can capture video and/or images of customers who are in the stores. A person, such as a security officer or other employee in the store, may actively and continuously monitor the camera security system in an attempt to identify potential shortages, personal safety risks, or other security events/risks and respond. As mentioned above, customers can hide their activities so as to avoid detection, which can frustrate efforts of security officers to stop or otherwise prevent such activity from occurring.

SUMMARY

(5) The document generally describes technology for automatically detecting risky or suspicious user activity in a retail environment, such as a grocery store, using analysis of multiple different sensor signals that monitor the retail environment and determining appropriate human and/or automated system responses in response to such automatically detected risky and/or suspicious activity. Such responses can be automatically determined, updated/modified, and/or applied during or after a checkout process, such as while a customer (e.g., user, guest) is scanning items at a point of sale (POS) terminal and/or before the user leaves the retail environment. As an illustrative example, a customer who enters a store picks up an item in an electronics department and then a pack of candy before proceeding to a self-checkout lane, but only scans the pack of candy at the POS terminal before attempting to complete the transaction. This customer can be automatically flagged as engaging in suspicious activity. For example, the customer's actions can be automatically detected by devices throughout the store, such as cameras, RFID readers, location devices, scanners, sensors, and/or other devices working in concert to monitor and identify potentially suspicious or risky activity. While the customer is going through a checkout process, a computer system (e.g., an edge computing device, a remote computer system, a cloud-based system, etc.) can receive the data from the in-store devices and analyze the data to generate an activity profile for the customer. The computer system may link the profile to the customer via an objective identifier, such as payment information (e.g., credit card number, mobile wallet information, etc.), account information (e.g., phone number, email, username, password), or other objective information about the customer. The computer system can then assess the activity in the profile based on one or more risk factors to determine whether the customer's activity is risky,

suspicious, associated with a shortage event/theft, and/or associated with personal safety/harm. This assessment can be used by the computer system to automatically determine whether and/or how to respond to the activity of the customer, including determining whether such a response should be a human or manual response (e.g., alert worker on their mobile device to ask customer whether they need assistance, alert in-store security personnel) and/or whether such response should be an automated system response (e.g., provide prompt on POS terminal asking whether additional items need scanning before completing checkout process, flash assistance lights at POS terminal, decline to complete transaction until worker resolves potential discrepancy).

(6) The disclosed technology can escalate and elevate responses based on a variety of factors, such as the severity of the risky/suspicious activity, changes in the severity during the activity (e.g., customer becoming more agitated/hostile), and/or historical interactions with a customer that may warrant elevated/reduced responses. For example, the computer system can automatically determine that the particular customer has appeared on a watch list for the store both recently and frequently (e.g., the user was put on the watch list in the past for being associated with organized crime and/or other thefts). This factor can elevate a type of response (e.g., human or automated system response) and/or a severity of the response (e.g., monitoring the user, stopping a transaction during the checkout process, apprehending the user, etc.). Accordingly, the computer system can select an appropriate manual response, such as an employee in the store being prompted on their mobile device to apprehend the user at the self-checkout lane instead of merely monitoring the user, and/or can select an appropriate automated response, such as providing a prompt at a POS terminal of the self-checkout lane asking the customer to re-scan their item(s).

(7) The disclosed technology can apply more friction to the determination of type and severity of response to be taken before the customer leaves the store as the user activity is assessed as being more serious, suspicious, certain, and/or risky. In other words, the disclosed technology can escalate a response type and action to the customer's activity when the disclosed technology assesses the customer's activity as being more risky and/or suspicious. An escalated response that is automatically selected, using the disclosed technology, for a risky/suspicious situation can include, for example, apprehending the customer, stopping and/or cancelling their transaction, requiring an employee in the store to check the customer's bags and/or person before leaving the store, calling on law enforcement to intervene, generating a security casefile for the customer, adding the customer to a watch list for the store, etc.

(8) The disclosed technology can apply less friction to the determination of type and severity of response to be taken based on assessing the user activity as being less serious, suspicious, certain, and/or risky. The disclosed technology can provide deescalated responses in such scenarios. A deescalated response can include, for example, simply monitoring the customer during the current shopping experience and/or future shopping experiences. The response can also include prompting the customer to rescan their item(s) at the self-checkout lane. The response can include notifying the customer at the POS terminal that something appears wrong with their current transaction. As another example, the response can include prompting an employee of the store to approach and assist the customer. One or more other responses may also be generated and/or invoked according to the determined friction level.

(9) A variety of factors can be used to determine degrees of friction to apply, as well as the type of responses to deploy, including the value of items that are potentially at risk of being stolen. For example, during the checkout process, the computer system can receive transaction data. Based on analyzing the transaction data and other data received from devices in the store, the computer system can determine that it is possible the customer is engaging theft, can identify the items that are potentially being stolen, and can determine the value of those items. The value of those items can be compared to one or more thresholds and, if the value of the items is less than a threshold cost value, the computer system may determine that less friction should be applied to the determination of type and severity of response to the customer's actions. For instance, the computer

system may determine that prompting the customer at the POS of the self-checkout lane to re-scan their items may be sufficient in this example. If, on the other hand, the value of the items is greater than one or more thresholds, the computer system may determine that more friction should be applied to generate an escalated response, such as instructing an employee at their mobile device to approach the customer at the self-checkout lane and help the customer through the checkout process.

(10) One or more embodiments described herein can include a system for automatically detecting and responding to potentially suspicious or risky activity in a retail environment, the system including: one or more monitoring devices positioned throughout the retail environment that can be configured to generate a stream of activity data detailing activity within the retail environment, a point of sale (POS) terminal that includes at least (i) a scanner that can be configured to scan item identifiers during a checkout process, (ii) a display device that can be configured to display information during the checkout process, and (iii) a payment terminal that can be configured to receive and process payment information during the checkout process, a group of mobile devices that may be associated with employees within the retail environment, each of the group of mobile devices including at least (i) a wireless transceiver that can be configured to wirelessly transmit and receive information, (ii) a user interface that can be configured to output information to and to receive input from a corresponding user, and (iii) an indoor location module that can be configured to determine and transmit location information, and a computer system in communication with the one or more monitoring devices, the point of sale terminal, and the group of mobile devices. The computer system can be configured to perform operations including: receiving, from the one or more monitoring devices, the stream of activity data, applying a model to the stream of activity data to identify a portion of the stream of activity data corresponding to activity of a guest during the checkout process, the model being trained to identify features in the portion of the stream of activity data indicative of a risk event, identifying, based on the portion of the stream of activity data, whether a risk event is associated with the activity of the guest during the checkout process, determining a risk impact score for the guest based on a determination that the risk event is associated with the activity of the guest, determining a risk confidence score for the guest, the risk confidence score indicating a likelihood that the activity of the guest is associated with the risk event, generating a response friction level for the activity of the guest based on determining whether at least one of the impact score and the confidence score satisfy risk criteria, the response friction level corresponding to a escalation of a type of response to be taken for the activity of the guest, selecting (i) a particular manual response from among a group of candidate manual responses to the activity of the guest and (ii) a particular automated response from among a group of candidate automated responses to the activity of the guest based, at least in part, on the response friction level satisfying at least one of manual response criteria and automated response criteria, transmitting instructions to the POS terminal to implement the particular automated response, in which transmitting the instructions may cause the particular automated response to be provided using one or more of the scanner, the display device, and the payment terminal, selecting one or more mobile devices from among the group of mobile devices based, at least in part, on the location information for the mobile devices relative to a location of the POS terminal, and transmitting instructions to implement the particular manual response to the selected one or more mobile devices, in which transmitting the instructions may cause corresponding instructions to be outputted in the user interface at the selected one or more mobile devices to prompt corresponding employees to perform the manual response with regard to the guest at the POS terminal.

(11) In some implementations, the embodiments described herein can optionally include one or more of the following features. For example, the one or more monitoring devices can include at least one of cameras, RFID readers, location-based signaling devices, mobile devices, and point of sale (POS) terminal checkout lanes. The risk event can be a shortage event that includes at least one of theft, shoplifting, ticket switching, and sweethearting. The risk event can be a security event that

includes at least one of bodily harm, physical threat, verbal threat, terror, aggression, carrying a weapon in the retail environment, and assault. The stream of activity data can include unstructured data. The one or more monitoring devices can include a camera that can be configured to generate the stream of activity data that may include at least one of image data or video data. The one or more monitoring devices can include the POS terminal, the POS terminal being configured to generate the stream of activity data that can include transaction data during the checkout process. The one or more monitoring devices can include a location-based signaling device that can be configured to generate the stream of activity data that includes location-based data of at least one of (i) a mobile device of the guest as the guest moves throughout the retail environment and (ii) a shopping cart that the guest pushes throughout the retail environment. The stream of activity data can include system-based inferences, the POS terminal being configured to generate a system-based inference indicating that the guest likely performed ticket switching based on identifying, during the checkout process, a mismatch between an item identifier that the guest scanned with the scanning device and an item imaged during the checkout process. The computing system can be an edge computing device. The operations further can include identifying and associating a portion of the stream of activity data with a guest currently using the POS terminal during the checkout process.

(12) As another example, selecting the particular manual response from among the group of candidate manual responses to the activity of the guest can include selecting the manual response based on at least one of (i) the manual response being an expected response to the activity of the guest, (ii) the response friction level exceeding a threshold friction value, and (iii) labor resources in the retail environment satisfying a threshold labor availability condition to provide for manual response to the activity of the guest. Sometimes, selecting the particular automated response from among the group of candidate automated responses to the activity of the guest can include selecting the automated response based on at least one of (i) the automated response being an expected response to the activity of the guest, (ii) the response friction level being less than a threshold friction value, and (iii) labor resources in the retail environment not satisfying a threshold labor availability condition to provide for a manual response the activity of the guest.

(13) As another example, selecting the particular manual response from among the group of candidate manual responses to the activity of the guest can include selecting at least one of: instructions that, when outputted at the selected one or more mobile devices, prompt the corresponding employees to let the activity of the guest pass, instructions that, when outputted at the selected one or more mobile devices, prompt the corresponding employees to observe the guest, instructions that, when outputted at the selected one or more mobile devices, prompt the corresponding employees to approach the guest at the POS terminal and provide assistance during the checkout process, instructions that, when outputted at the selected one or more mobile devices, prompt the corresponding employees to investigate the activity, instructions that, when outputted at the selected one or more mobile devices, prompt the corresponding employees to approach the guest and perform a receipt check before the guest exits the retail environment, and instructions that, when outputted at the selected one or more mobile devices, prompt the corresponding employees to approach and apprehend the guest. In some implementations, (i) can be selected based on the response friction level being within a first range of friction values, (ii) can be selected based on the response friction level being within a second range of friction values greater than the first range of friction values, (iii) can be selected based on the response friction level being within a third range of friction values greater than the first and second ranges of friction values, (iv) can be selected based on the response friction level being within a fourth range of friction values greater than the first, second, and third ranges of friction values, (v) can be selected based on the response friction level being within a fifth range of friction values greater than the first, second, third, and fourth ranges of friction values, and (vi) can be selected based on the response friction level being within a sixth range of friction values greater than the first, second, third, fourth, and fifth ranges of

friction values.

(14) In some implementations, selecting the particular automated response from among the group of candidate automated responses to the activity of the guest can include selecting at least one of: instructions that, when executed by the POS terminal, causes POS terminal to perform no action and let the activity pass, instructions that, when executed by the POS terminal, causes POS terminal to present, at the display device, checkout tips to guide the guest through the checkout process, instructions that, when executed by the POS terminal, causes POS terminal to actuate a lane light at the POS terminal, in which actuating the lane light causes the lane light to flash, instructions that, when executed by the POS terminal, causes POS terminal to automate, at at least one of the display device and the payment terminal, a charge to a transaction of the guest, instructions that, when executed by the POS terminal, causes POS terminal to generate an alert that is transmitted to a mobile device of security personnel in the retail environment, and instructions that, when executed by the POS terminal, causes POS terminal to prevent the guest from (a) continuing to scan items with the scanner, (b) continuing the checkout process through the display device, or (c) completing the checkout process through the payment terminal. Sometimes, (i) can be selected based on the response friction level being within a first range of friction values, (ii) can be selected based on the response friction level being within a second range of friction values greater than the first range of friction values, (iii) can be selected based on the response friction level being within a third range of friction values greater than the first and second ranges of friction values, (iv) can be selected based on the response friction level being within a fourth range of friction values greater than the first, second, and third ranges of friction values, (v) can be selected based on the response friction level being within a fifth range of friction values greater than the first, second, third, and fourth ranges of friction values, and (vi) can be selected based on the response friction level being within a sixth range of friction values greater than the first, second, third, fourth, and fifth ranges of friction values.

(15) As another example, the operations can also include determining, based on execution of the selected (i) particular manual response and (ii) particular automated response and the stream of activity data received from the one or more monitoring devices, that the guest continues to perform the activity, adjusting, based on the determination that the guest continues to perform the activity, at least one of the risk impact score and the risk confidence score by a predetermined amount, increasing, based on the adjusted at least one risk impact score and risk confidence score, the response friction level, and selecting at least one of another manual response from among the group of candidate manual responses and another automated response from among the group of candidate automated responses based on the increased response friction level, in which the selected another manual response or another automated response is an escalation of the previously selected particular manual response or the particular automated response.

(16) Sometimes, determining a risk impact score for the guest can include: determining, based on transaction data received from the POS terminal during the checkout process, a value of an item associated with the activity of the guest and assigning the risk impact score above a threshold impact value based on the value of the item exceeding a threshold item cost value. Determining a risk impact score for the guest can also include: identifying, based on applying the model to the stream of activity data, a safety threat in the activity of the guest and assigning the risk impact score above a threshold impact value based on the identified safety threat satisfying safety risk criteria. Determining a risk confidence score for the guest may include: analyzing, based on applying the model to the stream of activity data, the portion of the stream of activity data to identify a weapon, the portion of the stream of activity data being image data, and assigning the risk confidence score above a threshold confidence value based on the identification of the weapon.

(17) In some implementations, determining whether at least one of the impact score and the confidence score satisfy risk criteria can include determining that at least one of the impact score and the confidence score exceed a safety risk threshold value. Determining whether at least one of

the impact score and the confidence score satisfy risk criteria can also include determining that at least one of the impact score and the confidence score exceed a shortage risk threshold value. Determining whether at least one of the impact score and the confidence score satisfy risk criteria can include: aggregating the impact score and the confidence score to generate a general risk score for the guest and determining that the risk criteria is satisfied based on a determination that the general risk score exceeds a general risk threshold value.

(18) Sometimes, generating a response friction level for the activity of the guest can include assigning a value to the response friction level that is above a threshold friction value based on at least one of the impact score and the confidence score satisfying the risk criteria. Generating a response friction level for the activity of the guest can also include assigning a value to the response friction level that is below a threshold friction value based on at least one of the impact score and the confidence score not satisfying the risk criteria. In some implementations, selecting (i) a particular manual response from among a group of candidate manual responses to the activity of the guest and (ii) a particular automated response from among a group of candidate automated responses to the activity of the guest can also include: retrieving, from a data store, a watch list for the retail environment, determining whether an objective identifier associated with the guest appears on the watch list, and selecting at least one of (i) and (ii) based on a determination that the objective identifier associated with the guest appears on the watch list. Moreover, determining a risk impact score for the guest can further be based on the activity of the guest satisfying risk impact criteria.

(19) One or more embodiments described herein can include a method for automatically detecting and responding to potentially suspicious or risky activity in a retail environment, the method including: receiving, from one or more monitoring devices positioned throughout a retail environment, a stream of activity data detailing activity within the retail environment, applying a model to the stream of activity data to identify a portion of the stream of activity data corresponding to activity of a guest during a checkout process, identifying, based on the portion of the stream of activity data, whether a risk event is associated with the activity of the guest during the checkout process, determining a risk impact score for the guest based on a determination that the risk event is associated with the activity of the guest, selecting (i) a particular manual response from among a group of candidate manual responses to the activity of the guest and (ii) a particular automated response from among a group of candidate automated responses to the activity of the guest based, at least in part, on the risk impact score satisfying at least one of manual response criteria and automated response criteria, transmitting instructions to a POS terminal to implement the particular automated response, in which transmitting the instructions causes the particular automated response to be provided using one or more of a scanner, a display device, and a payment terminal of the POS terminal, selecting one or more mobile devices from among a group of mobile devices based, at least in part, on location information for the mobile devices relative to a location of the POS terminal, and transmitting instructions to implement the particular manual response to the selected one or more mobile devices, in which transmitting the instructions causes corresponding instructions to be outputted in a user interface at the selected one or more mobile devices to prompt corresponding employees to perform the manual response with regard to the guest at the POS terminal.

(20) The system can optionally include one or more of the abovementioned features. The system can also optionally include one or more of the following features. For example, the method can also include determining a risk confidence score for the guest, the risk confidence score indicating a likelihood that the activity of the guest is associated with the risk event, generating a response friction level for the activity of the guest based on determining whether at least one of the impact score and the confidence score satisfy risk criteria, the response friction level corresponding to an escalation of a type of response to be taken for the activity of the guest, and selecting (i) the particular manual response from among the group of candidate manual responses to the activity of

the guest and (ii) the particular automated response from among the group of candidate automated responses to the activity of the guest based, at least in part, on the response friction level satisfying at least one of the manual response criteria and the automated response criteria. The model could have been trained to identify features in the portion of the stream of activity data indicative of a risk event. Moreover, the method can include determining the risk impact score based on the activity of the guest satisfying risk impact criteria.

(21) The devices, system, and techniques described herein may provide one or more of the following advantages. For example, the disclosed technology provides for automatically and efficiently leveraging existing resources in a retail environment to deter or otherwise prevent security events (e.g., shortages, theft, personal safety, physical harm, etc.) in real-time or near real-time. Labor resources (e.g., available employees on a store sales floor), for example, can be saved for responding to more serious security events and automated system responses can be used to respond to less serious security events (e.g., in situations where there is a labor shortage, for example) in real-time. As a result, available resources in the retail environment can be used to prevent one or more security events arising in the retail environment at or around the same time.

(22) The disclosed technology can also enhance and increase effectiveness/accuracy of checkout processes depending on real-time risks associated with the respective checkout processes. In so doing, the disclosed technology can provide for creating sufficient friction to deter and/or stop shortages or other security-related events in the retail environment.

(23) Similarly, the disclosed technology can provide for objectively responding to potential (and/or more certain) risks in the retail environment without targeting, tracking, or monitoring specific customers associated with the risks. Such technology can provide for objectively and accurately identifying and responding to risks in the retail environment without invoking human bias, profiling, and/or error that may arise when a human, such as a security officer, monitors customers in the retail environment. As a result, the disclosed technology provides for stopping security events in real-time and near real-time as well as preventing or deterring future security events.

(24) The disclosed technology can also provide for unique and custom response strategies per risky activity identified in the retail environment. The disclosed technology synthesizes and aggregates disparate data from various different devices in the retail environment (e.g., cameras, RFID readers, location signaling devices, POS terminals, user devices, checkout systems, etc.) in real-time and/or near real-time to make accurate risk assessments and determine appropriate responses to the risky activity. The disclosed technology provides for combining and correlating different forms of data, information, and system-generated inferences using objective factors. Labeling and classification techniques can be used to correlate the different types of information, which, at first blush, may not appear related to each other. As a result, security events (e.g., risky activity) can be more accurately identified, associated with customers, and leveraged to determine appropriate responses. The disclosed technology also leverages various risk rules, factors, and criteria to assess user activity and determine appropriate human and/or automated responses to the activity. As a result, the disclosed technology provides for stopping, preventing, and/or deterring such activity.

(25) Moreover, employees in the retail environment, such as security officers, may not have the ability or time to sift through robust amounts of data in various different data types/formats in real-time before a customer associated with risky activity leaves the store. As a result, the employees may inaccurately assess a level of risk that the customer's activity poses and may end up determining inappropriate responses to the activity (e.g., inefficient use of labor resources when a simple prompt at the POS terminal to rescan an item would have been more efficient/accurate). The employees may also determine a response too late, in that the customer associated with the risky activity may already leave the retail environment. Thus, the risky activity may not be stopped and/or deterred. Moreover, the employees can make mistakes about risky activity and how to respond based on making rushed and/or incomplete reviews of all the data to sift through. Such mistakes can include apprehending, monitoring, or profiling a customer who has not acted in any

risky or suspicious way in the retail environment. Such mistakes can result in alienating customers and fostering a poor user experience in the store. The disclosed technology, on the other hand, removes potential human error and inefficiencies to accurately and quickly make decisions about appropriate responses to take in real-time and/or near real-time.

(26) As another example, the disclosed technology provides for determining amount of friction to apply to a response decision and escalation of the response based on analysis of the risky activity attributed to the customer. The amount of friction and escalation can be determined objectively and without potential human bias and/or profiling of customers in the retail environment. The amount of friction and escalation can be determined based on thorough and quick analysis of robust amounts of disparate data that is attributed to the customer engaging in the risky activity. Therefore, the amount of friction and escalation can be accurate and objective metrics used to determine an appropriate response, whether human or automated system response, to the risky activity in real-time or near real-time.

(27) Similarly, risky activity can be attributed to customers in the retail environment using objective identifiers. This can eliminate potential human bias, profiling, tracking, or subjective monitoring of the customers in the retail environment. This technology can also eliminate human bias, error, and/or assumptions made when analyzing large amounts of data quickly, in little time, and trying to correlate that data with a particular customer to determine a responsive action before the particular customer leaves the retail environment. Moreover, the objective identifiers can be used to accurately and quickly identify customers during future activities in the retail environment. After all, a customer can change their appearance (e.g., hair color, clothes, posture, actions, etc.), but the customer (or another customer working with the customer in concert) may use the same account information (e.g., phone number, email, username, password) and/or payment information (e.g., credit card number, mobile wallet information) when engaging in activities in the retail environment. The disclosed technology therefore provides for quick, efficient, accurate, and objective assessment of large amounts of data to identify, stop, prevent, and/or deter the risky activity that is objectively attributed to the particular customer in the retail environment.

(28) As another example, stitching together disparate pieces of data and information can be advantageous to predict likelihood of future risky activity of customers who pose specific security threats. Such data-driven, objective predictions can be used by the in-store employees and/or the computer system to monitor customers who pose specific security threats and take actions to resolve security events involving the particular customers and/or to prevent/mitigate/deter potential future security events involving such customers. Similarly, such data-driven objective predictions can be made quickly and efficiently on the fly in real-time or near real-time at the POS terminal, on an edge computing device, and/or by a remote computing system at the retail environment. These predictions can be made as the customer performs a checkout process so that appropriate responses can be taken before the customer leaves the retail environment to prevent current risky activity and also to deter future risky activity by the customer or by others that the customer may be working in concert with.

(29) Associating unstructured data (e.g., raw data such as video feeds, images, location information) and system-based inferences (e.g., inferred conclusions such as a customer bypassing a scanner with a product) can also be advantageous to build robust, accurate, unbiased activity profiles. Such activity profiles can be assessed against various risk factors and criteria to determine an appropriate and unique response that may stop the current activity and/or prevent/deter future activity.

(30) The details of one or more implementations are set forth in the accompanying drawings and the description below. Other features and advantages will be apparent from the description and drawings, and from the claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1A is a conceptual diagram for determining a human and/or automated system response to risky user activity in a retail environment.
- (2) FIG. 1B is a conceptual diagram for determining a human and/or automated system response to user activity likely attributed to a shortage in a retail environment.
- (3) FIG. 1C is a conceptual diagram for determining a human and/or automated system response to user activity likely attributed to a safety risk in a retail environment.
- (4) FIG. 2 illustrates an example spectrum of human and automated system responses that can be invoked based on certainty of risk associated with user activity in a retail environment.
- (5) FIG. 3 illustrates an example timeline for invoking various human and/or automated system responses to user activity in a retail environment.
- (6) FIGS. 4A-B is a flowchart of a process for determining a response friction level to be used in determining an appropriate response to user activity in a retail environment.
- (7) FIGS. 5A-B is a flowchart of a process for selecting between human and automated system responses to user activity in a retail environment.
- (8) FIG. 6 is a system diagram of system components that can be used to perform the techniques described herein.
- (9) FIG. 7 is a schematic diagram that shows an example of a computing device and a mobile computing device.
- (10) Like reference symbols in the various drawings indicate like elements.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

- (11) This document generally relates to determining, in real-time and/or near real-time, appropriate human and/or automated system responses to invoke with regard to risky activity in a retail environment. Devices in the retail environment can generate data indicating potentially risky activity. A computer system can assess the data to determine whether the activity is risky and/or objectively attribute the activity to a particular customer in the retail environment. The computer system can then determine, in real-time or near real-time, an appropriate response to the activity based on the assessed risk and/or various other risk factors. Using the disclosed technology, safety and security events can be accurately and efficiently stopped, prevented, and/or deterred in real-time or near real-time while also leveraging available resources in the retail environment (e.g., labor resources, such as skills of the employees, quantity of employees currently working when a response is needed, etc.) and efficiencies/capabilities of devices in the retail environment (e.g., compute resources, POS terminals providing notifications to customers during checkout processes, POS terminals cancelling or stopping suspicious transactions during the checkout processes, etc.).
- (12) The risky activity can include shoplifting, theft, sweethearting, and other shortage/related events. The risky activity can also include personal safety threats, physical harm, bodily harm, assault, or other security and/or safety related events. The disclosed technology can be applied to a variety of establishments and/or retail environments, including but not limited to grocery stores, clothing stores, stores that sell a variety of different types of items, malls, and other types of retail environments/stores.
- (13) Referring to the figures, FIG. 1A is a conceptual diagram for determining a human and/or automated system response to risky user activity in a retail environment **100**. A computer system **102** can be in communication (e.g., wired and/or wireless) with an in-store employee device **104** via network(s) **105**. In some implementations, the computer system **102** can be in communication with multiple in-store employee devices. The computer system **102** can also be a remote computing system in communication with in-store employee devices that are associated with a plurality of retail environments or stores. For example, the computer system **102** can be a central computing

system configured to determine responses to various activities detected in different stores in a network of stores. In some implementations, each of the plurality of stores in the network can include a computer system that is configured to assess checkout activities and determine appropriate responses.

(14) The in-store employee device **104** can be a mobile device such as a smartphone, tablet, laptop, and/or computer. An in-store employee can use the device **104** in order to monitor activity in the store environment, including customers (e.g., guests) who pose specific security threats. The in-store employee, such as safety and security personnel, can be tasked with ensuring safety and security in the store environment. In some implementations, the device **104** can be in communication with a camera security system in the store environment **100**. The in-store employee can view an image data feed from the camera security system at the device **104**. The in-store employee can use the device **104** in order to identify customers who pose specific security threats, monitor them, and take some response action to such customers when they are engaged in or believed to be engaging in activity that poses a security threat (e.g., before the customers leave the retail environment **100**).

(15) The retail environment **100** can be any type of store, such as a grocery store, clothing store, or other type of store selling goods/products to be purchased by customers (e.g., users, guests). The retail environment **100** can include shelves **126A-N**. The shelves **126A-N** can be arranged into aisles that customers can move up and down. The shelves **126A-N** can include a variety of items that the customers can purchase. The retail environment **100** can also include point-of-sale (POS) checkout lanes **106A-N**. In some implementations, the POS checkout lanes **106A-N** can be self-checkout lanes. One or more of the POS checkout lanes **106A-N** can also be checkout counters with an employee who scans a customer's items from their cart or basket.

(16) The retail environment **100** can also include different devices and/or systems that are placed throughout the retail environment **100**. The devices and/or systems can be used to track movement of customers and items therein. The devices and/or systems can be edge devices that perform edge computing processing techniques. The devices and/or systems can generate unstructured data as well as inferences based on the unstructured data. The devices and/or systems can be in communication with the computer system **102** via network(s) **105**. The computer system **102** can be a central computing system, computer, server, and/or network of computers or servers. The devices and/or systems can transmit, to the computer system **102**, the unstructured data and inferences. The computer system **102**, as described herein, can further process the transmitted information to determine whether a customer, such as customer **120A**, is engaging in suspicious activity and generate an appropriate response to that activity.

(17) Still referring to FIG. **1A**, the devices and/or systems placed throughout the retail environment **100** can include cameras **108A-N**, location-based signaling devices **110A-N**, and RFID readers **114A-N**. One or more additional or fewer types of devices and/or systems can be placed throughout the retail environment **100**. Moreover, the devices and systems described herein can be positioned near and/or around aisles, shelves **126A-N**, departments, or other areas in the retail environment **100**. One or more of the devices and systems can also be positioned near and/or around entrances and exits of the retail environment **100**. Moreover, one or more of the devices and systems can be positioned near, around, and/or as part of the checkout lanes **106A-N**.

(18) The cameras **108A-N** can be configured to continuously capture image and/or video data of portions of the retail environment **100** within their field of views. One or more of the cameras **108A-N** can be high resolution cameras. One or more of the cameras **108A-N** can be low resolution cameras. One or more of the cameras **108A-N** can also be pan-tilt-zoom cameras. One or more of the cameras **108A-N** can be wide angle cameras to capture more activity in the retail environment **100**. The cameras **108A-N** can be any other camera configurations that are already installed in the retail environment **100**. For example, the cameras **108A-N** can be part of a security camera system or CCTV system.

(19) The location-based signaling devices **110A-N** can be configured to identify when customers pass the devices **110A-N** or are nearby the devices **110A-N**. The devices **110A-N** can generate timestamps indicating when a customer passes or is nearby. The devices **110A-N** can detect customer presence based on signals and/or location information from the customers' mobile devices. The devices **110A-N** can also detect customer presence based on location signals or other location information from sensors on a shopping cart or basket that the customer is bringing around the retail environment **100**. For example, customer **120A** has mobile device **112A**. Mobile device **112A** can be a cell phone, smartphone, laptop, tablet, or other mobile computing device that the customer **120A** may bring with them to the store. If the customer **120A** moves towards or comes into range with the location-based signaling device **110A**, the location-based signaling device **110A** can ping the mobile device **112A** and receive a mobile device identifier, such as a MAC address. The MAC address can be correlated with a timestamp generated by the device **110A** that indicates the customer **120A** was nearby. Thus, the location of the customer **120A** in the retail environment **100** at a particular time can be documented by the device **110A** using an objective identifier: the MAC address of the mobile device **112A**.

(20) The RFID readers **114A-N** can be configured to detect when an RFID tag comes within a vicinity or range of any one or more of the readers **114A-N**. RFID tags can be attached to shopping carts, baskets, other equipment used in the retail environment **100** as well as products, such as clothes, blankets, pillows, and other less-structured items for sale in the retail environment **100**. As an illustrative example, the customer **120A** can be pushing a shopping cart **118** around the retail environment **100**. The shopping cart **118** can have an RFID tag **116**, which can be used to identify the shopping cart **118**. Each shopping cart can have a unique RFID tag. Here, the customer **120A** pushes the shopping cart **118** past or near the RFID reader **114A**, and the reader **114A** can detect the RFID tag **116** on the shopping cart **118**. The reader **114A** can, for example, determine that the shopping cart **118** was near the shelf **126B** at a time at which the reader **114A** detected the RFID tag **116**. Similarly, when the customer **120A** moves the shopping cart **118** to the POS checkout lane **106N**, the RFID reader **114N** can detect the RFID tag **116** and identify that the shopping cart **118** is at the POS checkout lane **106N** at a particular time.

(21) Still referring to FIG. **1A**, one or more of the devices and/or systems **108A-N**, **110A-N**, **114A-N**, and **106A-N** can capture data corresponding to particular activity of the customer **120A** (block **A**, **130**). For example, the cameras **108A-N** can continuously capture image and/or video data in their designated locations. The location-based signaling devices **110A-N** can generate timestamps and indications of when customers, such as the customer **120A**, passes by or comes into a range of the devices **110A-N**. The RFID readers **114A-N** can similarly generate timestamps and indications of when shopping carts having RFID tags, such as the shopping cart **118** having the RFID tag **116**, come within range of the readers **114A-N**. The POS checkout lanes **106A-N** can also capture data such as scanned items, images of items in a customer's shopping cart, and transaction receipts/bills.

(22) In some implementations, one or more of the devices and/or systems **108A-N**, **110A-N**, **114A-N**, and **106A-N** can generate inferences based on the captured data. For example, the checkout lane **106N** can generate an inference as to whether the customer **120A** is likely shoplifting during a checkout process. The customer **120A** can scan products at the POS checkout lane **106N**. The POS checkout lane **106N** can include a camera configured to capture image data of an area around the POS checkout lane **106N**. Using edge computing, the POS checkout lane **106N** can analyze the image data and match it to barcodes of the products that the customer **120A** scanned. The POS checkout lane **106N** can determine that there is a mismatch between products that appear in the image data and products that are scanned. The mismatch can indicate that the customer **120A** may be shoplifting. Accordingly, the POS checkout lane **106N** can generate an inference that the customer **120N** may be engaged in activity that poses a security threat.

(23) As another example, the RFID reader **114A** can identify that customer **120A** passing by the shelf **126B** with the shopping cart **118** at a first time. The customer **120A** can continue moving

between the shelves **126B** and **126C**. Once the customer **120A** reaches the end of the shelves **126B** and **126C**, the customer **120A** can decide to turn around, walking back the same way that they came. Thus, when the customer **120A** reaches the end of the shelves **126B** and **126C**, the RFID reader **114A** can identify the shopping cart **118** at a second time. Using edge computing, the RFID reader **114A** can determine an amount of time that passed between the first time and the second time. The RFID reader **114A** can infer, based on the amount of time that passed, whether the customer **120A** spent longer between the shelves **126B** and **126C** than expected. If the customer **120A** spent longer than expected, the RFID reader **114A** can infer that the customer **120A** may be engaged in activity that poses a security threat.

(24) Alone, the RFID reader **114A**'s inference may not positively identify that the customer **120A** in fact engaged in activity that poses a security threat. However, in combination with image data from the camera **108N**, for example, the computer system **102** can determine that the customer **120A** spent a longer time than expected between the shelves **126B** and **126C** because the customer **120A** was looking at their mobile device **112A**. Thus, the customer **120A** did not in fact engage in activity that likely poses a security threat. As another example, in combination with the image data from the camera **108N**, the computer system **102** can determine that the customer **120A** spent a longer time because the customer **120A** was trying to swap barcodes on two products. Thus, the computer system **102** can positively identify that the customer **120A** engaged in activity that poses a security threat and accordingly determine an appropriate response.

(25) Any of the data captured and/or generated by the devices and/or systems **108A-N**, **110A-N**, **114A-N**, and **106A-N** can be transmitted to the computer system **102** (block B, **132**). The data can include unstructured data that is captured by the devices and/or systems **108A-N**, **110A-N**, **114A-N**, and **106A-N**. The data can also include inferences that are generated as described above. The data can be transmitted at predetermined times or time intervals (e.g., every 1 minute, every 3 minutes, every 5 minutes, every 10 minutes, every 30 minutes, every 1 hour, every 2 hours, every 6 hours, every 12 hours, every 24 hours, etc.). In some implementations, the data can be transmitted when requested by the computer system **102**. In yet some implementations, the data can be transmitted as it is captured, in real-time and/or near real-time. For example, the cameras **108A-N** can transmit live feeds of images and/or videos that are captured. As another example, the location-based signaling devices **110A-N** can transmit location data whenever movement is detected within ranges of such devices **110A-N**. The RFID readers **114A-N** can also transmit data whenever RFID tags **116** of shopping carts **118** are detected within ranges of such devices **114A-N**, for example. Moreover, the POS checkout lanes **106A-N** can transmit data, such as receipts, credit card information, scanned items, inferences, and other transaction data whenever a transaction is made at such checkout lanes **106A-N**. In yet some implementations, once a checkout process begins at a checkout lane **106A-N**, data captured/generated within a threshold amount of time from the checkout process can be requested by the computer system **102** from the devices and/or systems in the retail environment **100**. For example, the computer system **102** can request data that was captured/generated approximately 0 to 10 minutes before the checkout process began at the particular checkout lane **106A-N**. In some implementations, the threshold amount of time can vary depending on a size of the retail environment **100** (e.g., the larger a store, the more distance a customer may have to travel to get to the checkout lanes **106A-N**, so the longer the threshold amount of time). The threshold amount of time can also vary depending on other characteristics of the retail environment **100**, including but not limited to a level of busyness/foot traffic (e.g., the busier a store, the longer a customer may wait in line before they can begin the checkout process, so the longer the threshold amount of time).

(26) In block C, the computer system **102** can aggregate the received data into an activity profile (**134**). The computer system **102** can compile and filter all of the data that was received. The computer system **102** can also apply one or more machine learning-trained models to unstructured data to add structure to that data. Adding structure to the data can include labeling the data and

classifying the data based on those labels. For example, a model can be trained to identify, from image data, a person peeling a barcode off a product. The model can be applied to the image data received from the cameras **108A-N**. Using the model, the computer system **102** can identify a moment in which the customer **120A** in fact removed a barcode from one product and put it on another product. The computer system **102** can label this moment in the image data and classify it as a barcode swap or other activity that poses a security threat classifier. The computer system **102** can also apply a confidence value to this label indicating likelihood that the customer **120A** performed a fraudulent activity and/or gravity/seriousness/risk of the performed activity.

(27) Similarly, a model can be trained to identify, from POS transaction data and inferences, whether the customer **120A** did not scan all products in the shopping cart **118** and/or whether the customer **120A** scanned barcodes that do not match the products in the shopping cart **118** or otherwise at the POS checkout lane **106A**. Using the model, the computer system **102** can label and classify the POS transaction data as indicative of a security event, such as shoplifting.

(28) The activity profile can be associated with a particular customer, such as the customer **120A**. The association can be made by the computer system **102** using objective identifiers. The objective identifiers can include, but are not limited to, user account information (e.g., username, password, email address), phone number, credit card information, mobile wallet information, drivers license, license plate, email address, MAC address of the customer **120A**'s mobile device **112A**, etc. For example, the customer **120A** can go through a checkout process at the checkout lane **106N**. The customer **120A** can scan a barcode presented at their mobile device **112A** to apply a coupon to the products they are scanning to purchase, the barcode indicating the customer's mobile wallet information (e.g., payment information, customer ID or username, email address, MAC address, etc.). The computer system **102** can then associate transaction data during the checkout process with the particular customer **120A** based on the mobile wallet information. The computer system **102** can also associate any signals/data from the location-based signaling devices **110A-N** identifying the customer **120A**'s mobile device **112A** with the transaction data based on the mobile wallet information. Therefore, the activity profile can include any data that has been captured of the customer **120A** during their shopping trip in the retail environment **100**.

(29) In some implementations, the computer system **102** can create connections amongst the aggregated data in block C (**134**). The computer system **102** can apply one or more machine learning-trained models to the data. For example, the models can be trained to correlate data based on their labels and/or classifications. Thus, if image data and POS transaction data both are labeled as barcode swap, the computer system **102** can determine that these two pieces of data correlate with each other and generate a confidence level indicating likelihood that the customer **120A** has in fact engaged in ticket swapping.

(30) In block D (**136**), the computer system **102** can determine a risk impact score for the profile. The risk impact score can indicate a severity of the actions performed by the customer **120A** during their shopping trip in the retail environment **100**. Determining the risk impact score can be based on transaction data received from the checkout lane **106N** in real-time or near real-time. For example, if image data from the camera **108A** is processed to determine that the customer **120A** pockets an electronic device near the shelf **126A** and puts a book inside their cart **118** at or near the same time, the computer system **102** can analyze the customer **120A**'s transaction data to see whether the electronic device and/or the book is scanned and paid for. The computer system **102** can determine that no electronic device was scanned but a book that cost \$20 was scanned. The computer system **102** can determine that the electronic device has likely been stolen and that the electronic device costs approximately \$290. If the electronic device's cost exceeds some threshold cost value, then the computer system **102** can determine that the customer **120A** is stealing an expensive item and thus their activity has a greater impact on the retail environment **100**.

Accordingly, the computer system **102** can assign a high risk impact score to the activity profile associated with the customer **120A**. As another example, if the cost of the electronic device is less

than the threshold cost value (e.g., the electronic device costs the same as the scanned book or otherwise is an inexpensive item), then the computer system **102** can assign a lower risk impact score since the customer **120A** may not be engaging in as egregious of theft. As yet another example, the computer system **102** can assign a higher risk impact score if the customer **120A** is likely stealing products of a particular category (e.g., electronics, jewelry, or other expensive/costly product categories).

(31) As described throughout this disclosure, the disclosed techniques can be used to identify theft/shortage events as well as safety/security events. Accordingly, the computer system **102** can assign the risk impact score based on how threatening/serious the customer **120A**'s actions may be towards physical and/or personal safety/security in the retail environment **100**. For example, the computer system **102** can assign a higher risk impact score if the customer **120A** is likely causing harm or terror to other customers and employees in the retail environment **100** (and/or the customer **120A** is visibly carrying a weapon around). The computer system **102** can assign a lower risk impact score if, for example, the customer **120A** appears to bump into another customer by accident, causing the other customer to drop the products in their basket.

(32) The risk impact score can be a numeric value on a predetermined scale. For example, the risk impact score can be assigned a value between 1 and 5. The score can also be assigned a value between 1 and 100. One or more other scales can be used, including but not limited to 0 to 5, 0 to 10, 1 to 10, 1 to 50, 0 to 50, 0 to 100, etc. A higher numeric value can indicate a higher risk impact while a lower numeric value can indicate a lower risk impact. One or more other scales and/or values (e.g., Boolean, string, etc.) can be used to define the risk impact score, as described further below.

(33) In block E (**138**), the computer system **102** can determine a risk confidence score for the activity profile of the customer **120A**. The risk confidence score can indicate likelihood that the customer **120A** is engaging in risk activity in the retail environment, such as theft/a shortage event and/or a safety/security event. The risk confidence score can be determined based on analyzing the aggregated data in the activity profile. For example, the computer system **102** can receive/retrieve a watch list for the retail environment **100**. The watch list can indicate one or more customers who have been identified in the past as potentially engaging in risky/suspicious activity and thus should be monitored. If the activity profile indicates that the customer **120A** likely swapped barcodes between a pack of gum and a pair of headphones and the customer **120A** appears on the watch list for having repeatedly engaged in similar activities in the past, the computer system **102** can generate a high risk confidence score that the customer **120A** is involved in shoplifting or other shortage event. On the other hand, if this appears to be the customer **120A**'s first offense (e.g., the customer **120A** does not appear on the watch list), then the computer system **102** can assign a lower risk confidence score.

(34) The risk confidence score can be a numeric value, Boolean, and/or string value. For example, the risk confidence score can be a numeric/integer value between 0 and 1, where 1 indicates a highest risk confidence score (e.g., the customer **120A** is most likely engaging in a risky activity that should be apprehended/stopped) and 0 represents a lowest risk confidence score (e.g., the customer **120A** is less likely engaging in a risky activity that should be apprehended/stopped). One or more other scales can be used for defining the risk confidence score. For example, the score can be assigned a value between 1 to 5, 1 to 10, 1 to 50, 1 to 100, etc.

(35) In some implementations, blocks D and E can be performed at the same time. In some implementations, the computer system **102** can determine one risk score, which can be a combination of the risk impact score and the risk confidence score. In yet some implementations, the risk score can be determined as a weighted combination of the risk impact score and the risk confidence score. Sometimes, the computer system **102** can determine the risk score without first determining the risk impact score and the risk confidence score. Instead, the risk score can be determined based on performing similar assessments that the computer system **102** would perform

to determine each of the risk impact score in block D (136) and the risk confidence score in block E (138).

(36) In block F (140), the computer system 102 can generate a response friction level based on whether the impact score and/or the confidence score satisfy risk criteria. In some implementations, the computer system 102 can combine the impact score and the confidence score to generate a composite or overall risk score. The computer system 102 can then determine whether the overall risk score satisfies the risk criteria. In some implementations, only one of the impact score and the confidence score must satisfy the risk criteria for the computer system 102 to determine and generate an appropriate response friction level. For example, if the risk impact score is high because the customer 120A is shoplifting an expensive item but the risk confidence score is low because the customer 120A has not shoplifted in the past, the computer system 102 can still generate a high response friction level. This is because the retail environment 100 may have a shortage in the expensive item attributed to multiple thefts over the past several days by multiple other customers. The computer system 102 can identify the multiple thefts as part of group or organized crime and therefore may infer that the customer 120A is likely involved in the group or organized crime. Hence, the risk impact score can satisfy the risk criteria and a higher response friction level can be determined, by the computer system 102, for the activity profile of the customer 120A.

(37) As another example, if the risk impact score is low because the customer 120A may be carrying a bat inside the retail environment 100 but the risk confidence score is high because the customer 120A has been repeatedly apprehended by local law enforcement for assault, the risk confidence score can satisfy the risk criteria and the computer system can generate a high response friction level. After all, the customer 120A likely poses a significant safety threat to the retail environment 100.

(38) The higher the response friction level, the more serious the intervention or response to the customer 120A's activity. For example, a higher response friction level can be used to determine that the customer 120A should be apprehended before leaving the retail environment 100 and that their bags and/or body should be checked for shoplifted items. As another example, a lower response friction level can be used to determine that the checkout lane 106N should present a message prompting the customer 120A to rescan their item(s) before they can complete the checkout process. The response friction level can also be used to determine whether a human and/or automated system response is appropriate. Refer to FIGS. 2-3 for additional discussion about determining the intervention or response based on the response friction level.

(39) The response friction level can be a numeric, string, and/or Boolean value. In some implementations, for example, the response friction level can be assigned a numeric value on a predetermined scale. The predetermined scale can be, for example, 0 to 1, 0 to 5, 1 to 5, 0 to 10, 1 to 10, 0 to 100, 1 to 100, etc. In some implementations, the response friction level can be a Boolean value or string value, such as low, medium, high. One or more other values can also be assigned to the response friction level in block F (140).

(40) The computer system 102 can select a human and/or automated system response in block G (142) based on the response friction level. The computer system 102 can determine whether the type of activity in the activity profile warrants human and/or automated system responses. For example, it can be more efficient/effective to respond to petty theft by stopping the checkout process by the checkout lane 106N instead of having an employee approach the customer 120A at the checkout lane 106N and walk them through the checkout process. As another example, it can be typical/most effective to respond to potential assault by having an employee, such as security personnel, apprehend the customer 120A before they leave the retail environment 100. The computer system 102 can also determine whether sufficient labor resources are available to perform human responses before the customer 120A leaves the retail environment 100. Although described as human responses, the human responses can also be considered manual responses. For

example, there may not be enough employees working the sales floor to have one oversee the customer **120A** during the checkout process. Rather, it may be more labor resource efficient to save the few employees working the sales floor to respond to more serious/egregious activities, like assault or other safety risks. Refer to FIGS. 2-3 for additional discussion about the types of responses that can be selected in block G (**142**).

(41) Optionally, the computer system **102** can transmit response instructions to one or more devices in the retail environment (block H, **144**). For example, the computer system **102** can transmit an automated system response to the checkout lane **106N**, to be executed by system components of the checkout lane **106N** in real-time and/or near real-time. The computer system **102** can also transmit instructions for a human response to the in-store employee device **104**, to be executed by an employee of the device **104**. The instructions transmitted to the in-store employee device **104** can include a snapshot of the risky activity of the customer **120A** and objective identifiers that can be used to identify the customer **120A** before they leave the retail environment **100**. The instructions can include necessary information useful for the employee to objectively and unbiasedly identify and stop the customer **120A** at a time that the risky activity occurs or at a future time (e.g., before the customer **120A** leaves the retail environment **100**, a next time that the customer **120A** enters the retail environment **100**, etc.).

(42) As described herein, the techniques in blocks A-H (**130-144**) can be performed in real-time or near real-time. As a result, actions can be taken against the risky activities of the customer **120A** (and other customers in the retail environment **100**) as such activities occur. By doing so, the risky activities can be stopped. Performing the disclosed techniques in real-time or near real-time can also be beneficial to deter or otherwise prevent future risky activities from occurring in the retail environment, regardless of whether those activities are related to shortage events or security/safety events.

(43) FIG. 1B is a conceptual diagram for determining a human and/or automated system response to user activity likely attributed to a shortage in a store (e.g., retail environment). In the illustrative example of FIG. 1B, the customer **120A** can be performing a checkout process at the checkout lane **106N** in which they scan a book **152** instead of a cellphone **160A**. The cellphone **160A** can already be placed in the customer **120A**'s bags, which the customer **120A** might have done while walking through the store. For example, the customer **120A** might have walked through an electronics department **156** in the store, swiped the cellphone **160A** off a shelf **158**, and stashed the cellphone **160A** in a bag before continuing with their trip in the store. During checkout, the customer **120A** scans the book **152** instead of the cellphone **160A** so that the customer **120A** pays for only the book **152** and shoplifts the cellphone **160A**. The customer **120A** is engaging in shoplifting, which can be determined and responded to based on the techniques described herein.

(44) The computer system **102** can receive data about the user activity in the store in block A (**162**). The data can include image data **150**, transaction data **154**, and/or video data **155**. One or more other types of data can be received from devices and/or systems throughout the store, such as RFID signals from RFID readers and location-based signals of a mobile device of the customer **120A** from location-based signaling devices. Refer to FIG. 1A for additional discussion about other types of data and/or system-generated inferences that can be received in block A (**162**) and used to perform the techniques described herein.

(45) Here, the image data **150** can be captured by a camera at or near the checkout lane **106N**. The image data **150** can show the customer **120A** performing the checkout process at the checkout lane **106N**. In particular, the image data **150** shows the customer **120A** scanning the book **152** at the checkout lane **106N**.

(46) The transaction data **154** can be a receipt indicating what products were/are scanned by the customer **120A** at the checkout lane **106N** and how much each of those products cost. The transaction data **154** can also include other information, including but not limited to customer account information (e.g., username, email, password), credit card information, mobile wallet

information, and/or other payment information.

(47) The video data **155** can show the customer **120A** walking quickly past the shelf **158** holding the cellphones **160A-N** in the electronics department **156**. The video data **155** can show that the customer **120A** is making some quick, blurred actions near the cellphones **160A-N**.

(48) The data **150**, **154**, and **155** can be received by the computer system **102** and aggregated to determine an activity profile of the customer **120A**, as described in reference to FIG. **1A**. For example, in combination, the image data **150**, the transaction data **154**, and the video data **155** can indicate that the customer **120A** rushed past the electronics department **156** in an attempt to shoplift the cellphone **160A** and scanned the book **152** instead of the cellphone **160A** at the checkout lane **106N**, which was reflected as the only product purchased on the transaction data **154**. Therefore, as a combination of disparate data, the computer system **102** can determine that the customer **120A** likely is engaging in risky activity in the store and a severity of that activity, which can then be used to determine a type of response to be performed.

(49) In block B (**164**), the computer system **102** can determine a risk score based on identifying, from the data, user activity associated with a shortage. For example, the computer system **102** can aggregate and analyze the data. The computer system **102** can also determine a risk impact score and/or a risk confidence score based on the aggregated and analyzed data, as described in reference to FIG. **1A**. The risk score can, for example, be a combination of the risk impact score and the risk confidence score.

(50) The risk score can be determined based on identifying that the customer **120A** likely shoplifted the cellphone **160A** in the video data **155**, but only scanned the book **152** during the checkout process, as shown by the image data **150** and the transaction data **154**. Moreover, the risk score can be determined based on identifying that the book **152** only cost \$5.99 (see the transaction data **154**) but the customer **120A** shoplifted the cellphone **160A**, which is worth \$300. Since the cost of the shoplifted cellphone **160A** may exceed some threshold cost value, the computer system **102** can determine a high risk score. The computer system **102** can also determine that the customer **120A** is involved in a shortage and assign a high risk score based on analyzing the customer **120A**'s actions in the video data **155**. For example, the computer system **102** can identify aggressive posture (e.g., hunched shoulders, looking back and forth down the aisle, etc.) and fast movements of the customer **120A** around the shelf **158** in the video data **155**. These identifications can indicate a higher likelihood or confidence that the customer **120A** is engaging in risky activity, like a shortage. Accordingly, the computer system **102** can assign a high risk score (e.g., a risk score about a threshold score value).

(51) In block C (**166**), the computer system **102** can determine a human and/or automated response to the user activity based on the risk score. Part of determining the appropriate response can include determining a response friction level, as described in reference to FIG. **1A**. For example, the higher the risk score, the higher the response friction level. The higher the response friction level, the more serious action can be taken in response to the user activity that is detected. In block C, the computer system **102** can also determine whether a human response is more appropriate than an automated system response and vice versa, as described herein and in reference to FIG. **1A**.

(52) The computer system **102** can optionally transmit response instructions to the in-store employee device **104** of an employee in the store (block D, **168**) (e.g., assuming the computer system **102** determines that a human response is warranted and should be performed in block C).

(53) The computer system **102** can optionally transmit an automated system response to the checkout lane **106N** system in block E (**169**) (e.g., assuming the computer system **102** determines that an automated system response is warranted and should be performed in block C).

(54) FIG. **1C** is a conceptual diagram for determining a human and/or automated system response to user activity likely attributed to a safety risk in a store (e.g., retail environment). In this illustrative example, image data **172** captures a customer **120B** in the electronics department **156** seemingly carrying a weapon **170**. Video data **174** depicts the same customer **120B** suspiciously

exiting the store via store entrance **176**. In combination, the image data **172** and the video data **174** can indicate that the customer **120B** poses some security threat to the store.

(55) The computer system **102** can receive data about the user activity in the store in block A (**178**). As described throughout this disclosure, the data can include a variety of data types from a variety of data sources, devices, and/or systems (e.g., refer to FIG. **1A**). Some of the data received in block A (**178**) can include the image data **172** and the video data **174**. The image data **172** and the video data **174** can be associated with the customer **120B** using objective identifiers, as described in FIG. **1A**. As another example, the image data **172** and the video data **174** can be associated with the customer **120B** based on identifying objective visual features of the customer **120B** that appear in both data **172** and **174** (e.g., color of a sweater, posture, movements, hair color, hat, shoes, jacket, etc.).

(56) In block A (**178**), the computer system **102** can also receive a watch list for the store. The watch list can be used to determine whether the customer **120B** poses a significant safety/security threat to the store. This determination can then be used by the computer system **102** to determine an appropriate real-time or near real-time response to the customer **120B**'s activities. The watch list can be retrieved from a data store. In some implementations, the computer system **102** can already have access to the watch list in local memory/storage. The watch list can indicate one or more customers, via objective identifiers, that have been identified or associated with suspicious activity in the store over some predetermined period of time (e.g., a past day, a past 3 days, a past 5 days, a past week, a past 2 weeks, a past month, etc.). The watch list can rank customers based on the type of suspicious activity they are associated with and/or the severity of their activities. The more egregious the activity (e.g., assaulting customers and/or employees in the store multiple times in the past), the higher the customer may be ranked in the watch list. The watch list can also be updated on a daily basis or other predetermined basis. Whenever the watch list is updated, the computer system **102** can receive the updated watch list.

(57) In block B (**180**), the computer system **102** can determine a risk score based on identifying, from the data, user activity associated with a safety risk. As described in FIG. **1B**, the risk score can be determined based on determining a risk impact score and a risk confidence score. The risk score can be determined based on identifying a potential safety risk from a combination of the image data **172** and the video data **174** (and any other data that may be received by the computer system **102** and associated with the customer **120B**). The safety risk can be heightened based on identifying the particular customer **120B** on the watch list for the store. For example, the computer system **102** can determine whether the customer **120B** appears on the watch list using one or more objective identifiers attributed to the customer **120B**. The objective identifiers can include payment information (e.g., credit card information, mobile wallet information, user account information, MAC address, email, phone number, etc.) received at a checkout lane when the customer **120B** is performing a checkout process before leaving the store. The computer system **102** can determine whether any of the received objective identifiers appear on the watch list, thereby indicating that the customer **120B** has been flagged as a potential threat to the store. Similarly, the computer system **102** can determine the risk score based on identifying a likelihood that the user activity of the customer **120B** is attributed to a safety risk, such as personal or physical harm. The image data **172** and/or the video data **174** can be analyzed to identify aggressive actions and posture of the customer **120B** and/or positive identification of the weapon **170**.

(58) The computer system **102** can employ one or more machine learning trained models to analyze the data **172** and/or **174** and identify/extract features indicative of safety risks. For example, the computer system **102** can use a model with object detection techniques to identify one or more different types of weapons from image and/or video data. The computer system **102** can also use a model to objectively identify the customer **120B** across various different data types. As another example, the computer system **102** can use a model to identify and classify the customer **120B**'s actions. Classifying the customer **120B**'s actions can include identifying and labeling some actions

as typical (e.g., picking a product off a shelf at a constant pace) and other actions as atypical (e.g., running down an aisle, fast/blurred movements near a shelf, pacing, hunched over shoulders, looking back and forth up and down an aisle, etc.). Determinations and classifications made by the computer system **102** can be scored with confidence values that can indicate likelihood that the customer **120B** is associated with a safety risk in the store. Although the techniques described in reference to block B (**180**) in FIG. **1C** are described in the example of a safety risk use case, these techniques can also be used in the example of a shortage use case (see FIG. **1B**) or other use cases described herein. Moreover, any other techniques that are used for identifying safety risks or shortage events can be used by the computer system **102** in block B (**180**).

(59) The computer system **102** can determine a human and/or automated system response to the user activity based on the risk score in block C (**182**). As described further in reference to FIG. **1B**, the response can be determined based on assigning a response friction level to the user activity. The response friction level can be assigned a value based on a risk impact and/or confidence that the customer **120B** is engaging in a safety risk. The higher confidence, for example, that the customer **120B** has the weapon **170** on their body while in the store, the higher the response friction level and the more serious the response that is determined in block C (**182**). The response friction level and/or the risk score can also be used by the computer system **102** to determine whether to invoke a human and/or automated system response, as described in reference to FIGS. **1A-B**.

(60) Optionally, the computer system **102** can transmit response instructions to the in-store employee device **104** of an employee (block D, **184**), assuming the computer system **102** determined that a human response is warranted in block C (**182**). Optionally, the computer system **102** can transmit response instructions to a system or device in the store (block E, **186**), assuming the computer system **102** determined that an automated system response is warranted. Refer to FIGS. **1A-B** for further discussion.

(61) FIG. **2** illustrates an example spectrum of human and automated system responses (**216** and **218**, respectively) that can be invoked based on certainty of risk associated with user activity in a retail environment. A process **200** can be performed by the computer system **102** to assess user activity in the retail environment and determine an appropriate response to the activity in real-time and/or near real-time. The process **200** can begin with detections made by devices, systems, or other technology in the retail environment (**202**). For example, sensors **208** in the retail environment can collect data **210**, which can be used by the computer system **102** (or one or more of the sensors **208**) to generate insights **212** about user activity in the retail environment and corresponding inferences and decisions **214** about likelihood that the user is engaging in risky activity.

(62) The sensors **208** can include any of the devices and systems described herein, including but not limited to point-of-sale (POS) terminals in checkout lanes, cameras, RFID readers, location-based signaling devices, scanning devices, etc. The sensors **208** can detect and collect data **210** of various different types, including but not limited to WIFI signals, RFID signals, video data, image data, transaction data, location data, GPS signals, etc. Such seemingly disparate data can be aggregated and analyzed by the computer system **102** to generate the insights **212**. For example, the computer system **102** can use objective identifiers to associate any of the data **210** with a particular customer (e.g., user) in the retail environment (thereby creating an activity profile, as described in reference to FIG. **1A**). The computer system **102** can also generate insights **212** based on analyzing the aggregated data, such as identifying user activity most likely associated with swapping barcodes, shoplifting, causing harm to other customers, etc. The computer system **102** can accordingly make inferences and/or decisions as to whether the customer associated with the user activity is engaging in risky activity and a severity of that risky activity. The severity of the risky activity can be used to determine a response friction level, as described in reference to FIGS. **1A-C**.

(63) Accordingly, the computer system **102** can determine responses **204**, which include human responses **216** (e.g., manual responses) and/or automated system responses **218**, based on the

inferences and decisions **214**. The human responses **216** and the automated system responses **218** can become more severe/serious as the response friction level increased. In other words, if the computer system **102** infers that the customer is engaged in possibly risky activity (e.g., it is 50% certain that the customer shoplifted an item over a threshold value amount), the computer system **102** can determine a less severe human response **216** or automated system response **218** to that activity. As the possibility that the customer is engaging in risky activity increases to certain risky activity, the human response **216** and/or automated system response **218** that is generated and selected can become more severe. For example, as described herein, the computer system **102** can determine that the user activity escalates from possible risk to certain risk based on risk criteria such as increasing value of items involved in a shortage event attributed to the customer, increasing confidence that the customer is engaging in a shortage event or security event, and/or increasing confidence that the customer has engaged in similar risky activities in the past. One or more other criteria can also be used to determine a severity of the risky activity of the customer and whether to apply more friction (and thus a more severe response) in responding to the customer's activity.

(64) As shown in FIG. 2, the human responses **216** are depicted in increasing severity from possible risk to certain risk. If the computer system **102** determines possible risk for the particular customer's activity, the computer system **102** may simply select the human response **216** to let the activity pass—in other words, an employee in the retail environment may not be instructed/prompted to intervene. The next level/tier of the human responses **216** can include observing the customer. For example, the computer system **102** can generate instructions for an employee to observe video footage of the customer in real-time as the customer is performing a checkout process. The employee can be tasked with determining whether the customer performs any suspicious activities during the checkout process. The next level of the human responses **216** can be providing guest assistance, in which the computer system **102** can generate instructions prompting an employee to approach the customer during the current checkout process and assist them in completing the checkout process.

(65) As the computer system **102** determines greater certainty/confidence that the customer is engaging in risky activity (e.g., a shortage event and/or a safety/security event), the computer system **102** can select more severe human responses **216**, such as investigation. The computer system **102** can generate instructions prompting an employee to review a case file of data depicting the customer's activities over time to investigate whether the customer is engaging in risky activity. Other investigation instructions can also be generated and transmitted to a device of one or more employees in the retail environment.

(66) As the certainty/confidence that the customer is engaging in risky activity continues to increase, the computer system **102** can generate the human response **216** of performing a receipt check. Instructions can be transmitted to the device of an employee, prompting the employee to approach the customer after the checkout process and check their receipt against contents of their bags. This type of intervention/response can be performed in response to determining that the customer likely did shoplift product(s) and/or likely did shoplift products exceeding some threshold cost value.

(67) Once the computer system **102** is most certain (or within some threshold level of certainty) that the customer is engaging in risky activity, the computer system **102** can select a human automated response **216** that has the highest friction level: apprehending the customer. The computer system **102** can generate instructions that prompt an employee to approach the customer before they leave the retail environment and apprehend them. This can be considered a most severe response to customer activity that is selected when the computer system **102** is most certain the customer is engaging in risky activity and/or the risky activity is most serious/egregious. In some implementations, the most severe response to the customer's risky activity can include calling or otherwise contacting law enforcement to intervene.

(68) As described herein, the computer system **102** can determine a risk score associated with the

customer's risky activity. Each of the responses **216** and/or **218** can be assigned a range of values along a scale for the risk score. To determine which response to select in the spectrum (whether human response **216** or automated system response **218**), the computer system **102** can determine which range of values the risk score associated with the customer's risky activity falls within. For example, the first, least severe human response **216** of letting the activity pass can be associated with a range of 0 to 10 for the risk score. On the other hand, the most severe human response **216** of apprehending the customer can be associated with a range of 90 to 100 for the risk score. If the customer's activity has a risk score of 8, for example, and the computer system **102** determines that a human response **216** should be made (discussed further below), the computer system **102** can select the human response **216** of letting the activity pass. On the other hand, if the customer's activity has a risk score of 99 and the computer system **102** determines that a human response **216** should be made, the computer system **102** can select the human response **216** of apprehending the customer.

(69) Still referring to FIG. 2, the automated system responses **218** are depicted in increasing severity from possible risk to certain risk. For example, the less severe the risk (e.g., possible risk), the computer system **102** can select a response **218** such as letting the activity pass. The next level/tier of automated system response **218** can include sending help tips to be presented at a POS terminal of the checkout lane where the customer is completing the checkout process. The next level/tier of response **218** can include flashing a lane light at the checkout lane, which can provide an indication/warning to one or more employees near the checkout lane. The next level/tier of response **218** as the risk certainty increases can be performing an automated charge. As an illustrative example, if the computer system **102** has a confidence above a threshold value that the customer will be leaving with something they did not pay for and the computer system **102** has objective identifiers linking the customer to an online account or payment information, the computer system **102** can impose a charge for the item on the customer's account. Therefore, the customer would be charged the cost of the item that they are leaving the store with. In some implementations, the threshold value can be a 100% confidence. As other examples, the threshold value can be 90%, 95%, 99%, etc. The next level/tier of response **218** can be alerting safety and security personnel in the store. The safety and security personnel in the store can then review the alert and respond to the alert, which can be considered a human or manual response. A most severe automated system response **218** for a highest certainty of risky activity can include halting the transaction of the customer. For example, the computer system **102** can generate instructions that cause the POS terminal at the checkout lane to prevent the customer from scanning any more products and/or prevent the customer from completing the transaction by providing payment information. As described in reference to the human responses **216**, the computer system **102** can select an appropriate automated system response **218** based on a risk score assigned to the customer's activity and a range of values for the risk score that correspond to each automated system response **218**.

(70) One or more other human responses **216** and/or automated system responses **218** can be generated and selected by the computer system **102** along the spectrum of responses and for different levels of certainty/confidence in the risky activity. Moreover, the types of responses **216** and/or **218** that can be selected can vary depending on the type of risky activity. Shortage events, for example, may warrant certain types of responses (e.g., guest assistance, receipt check, etc.) and security events may warrant other types of responses (e.g., observe, investigate, apprehend, etc.).

(71) The computer system **102** can select human responses **216** or automated system responses **218** but not both (e.g., it can be more labor efficient to respond to a possible risk, such as petty theft, by flashing the lane light of the checkout lane instead of having an employee provide guest assistance to the customer at the checkout lane). Therefore, the human responses **216** and the automated system responses **218** can be invoked without relying on each other. In some implementations, the computer system **102** can select both human responses **216** and automated system responses **218**

(e.g., a most severe or most risky activity may warrant both halting the transaction as the automated system response **218** and apprehending the customer as the human response **216**).

(72) The computer system **102** can also compound one or more human responses **216** and/or automated system responses **218** over time, based on continuous assessment of the customer's activity. Moreover, the computer system **102** can compound one or more responses to then warrant more severe responses to the customer's activity. For example, the computer system **102** may decide that the customer is almost certainly engaging in shoplifting, but may not select the human response **216** of apprehending the customer until an employee first observes the activity of the customer. Therefore, if the employee observes the activity of the customer and determines that the customer is acting suspicious, the computer system **102** can then compound the human responses **216** and escalate the human responses **216** by instructing the employee to apprehend the customer next.

(73) The computer system **102** can also determine whether a human response **216** or an automated system response **218** is warranted based on analysis of the customer's activity (e.g., based on the insights **212** and/or the inference and decisions **214** described above). This determination can also be made based on available resources in the store. For example, if the store does not have sufficient labor resources (e.g., only a few employees are working on the sales floor and having one of the employees leave their post/task to deal with the customer may not be an efficient use of the available labor resources), the computer system **102** can determine that an automated system response **218** should be selected. On the other hand, if the computer system **102** determines that the customer is likely engaging in activity that typically warrants human intervention (e.g., the customer shoved another customer and caused harm to the other customer), the computer system **102** can select a human response **216** instead of an automated system response **218**. As yet another example, it can take a significant amount of time to apprehend a customer and document their case, regardless of whether the customer has posed a continuous threat to the store as part of an organized crime or the customer has stolen a \$5 lipstick once. Therefore, the computer system **102** can determine that it is more efficient use of labor resources to apprehend and document the customer likely associated with organized crime and let pass the customer who stole the \$5 lipstick.

(74) Therefore, when choosing whether to select a human response **216** or an automated system response **218**, the computer system **102** can (1) check whether an employee is nearby to respond, (2) whether sufficient labor resources are available to effectively and efficiently respond to the customer's activity, and/or (3) whether the customer's activity is one that typically is responded to by a human rather than a system. One or more other factors can be used to determine whether to select the human response **216** or the automated system response **218**, such as: cost of available labor resources, value of products involved in the customer's activity, type of products involved in the customer's activity, whether an automated system response **218** is a better response/more efficient/etc., whether the store is suffering from loss of the product involved in the customer's activity since this product has been stolen many times by other customers, trends in theft/security issues in the particular store and/or a network of stores, and/or organized crime that the customer may be associated with.

(75) The purpose of the process **200** is to select a human response **216** and/or automated system response **218** that can be effective in deterring current risks/threats as well as future behavior, such as organized crime. The process **200** can also be performed to efficiently use labor resources in such a way that has a positive impact on stopping current risky activity and preventing future risky activity.

(76) FIG. 3 illustrates an example timeline **300** for invoking various human and/or automated system responses to user activity in a retail environment. In the example of FIG. 3, human responses can include responses A, B, C1, C2, D, and N. Automated system responses can include responses V, W, X, Y1-Y5, and Z. Each of the responses can indicate a different type of response (or a dimension of responses) based on severity of the customer's activity. For example, human

response A and automated response V can correspond to a least severe customer activity (e.g., possibly risky activity, least risky activity, etc. On the other hand, the human response N and the automated response Z can correspond to a most severe customer activity (e.g., highest certainty of risky activity, most risky activity, etc.).

(77) Determining which of the human responses and/or automated responses to select in response to the customer activity can be based on a risk score assigned to that activity. Refer to FIGS. 1A-C for additional description about determining and assigning the risk score. The risk score can therefore indicate which response or responses should be implemented.

(78) For example, human response A (or multiple human responses that are grouped under the dimension of response A) can be selected if the customer's activity risk score is between 0 and 20. Human response B can be selected if the customer's activity risk score is between 20 and 40. Human responses C1-C2 can be selected if the customer's activity risk score is between 40 and 60. Human response D can be selected if the risk score is between 60 and 80. Human response N can be selected if the risk score is between 80 and 100. One or more other ranges of values can be used and associated with each of the human responses A-N. For example, human response A can be selected if the activity risk score is between 0 and 10, human response D can be selected if the risk score is between 50 and 95, and human response N can be selected if the risk score is between 95 and 100. The human responses A-N can also be assigned various other ranges of risk score values.

(79) In some implementations, each of the human responses A-N can correspond to one or more of the human responses **216** in FIG. 2. For example, human response A can include letting the activity pass. Human response B can include observing the activity. Human responses C1-C2 can include guest assistance and investigation. Human response D can include receipt check, and human response N can include apprehending the customer.

(80) As another example, automated response V can be selected if the customer's activity risk score is between 0 and 20. Automated response W can be selected if the customer's activity risk score is between 20 and 40. The response X can be selected if the risk score is between 40 and 60. Automated responses Y1-Y5 can be selected if the risk score is between 60 and 80. Response Z can be selected if the risk score is between 80 and 100. As described above in reference to the human responses, each of the automated responses V-Z can correspond to one or more different types of automated system responses. The score ranges for the automated responses V-Z can also vary, be the same, or different across the automated responses V-Z and/or in relation to the human responses A-N. Therefore, the ranges of risk score that correspond to different types of automated responses can be different than the ranges of risk score that correspond to different types of human responses.

(81) In some implementations, each of the automated responses V-Z can correspond to one or more of the automated system responses **218** in FIG. 2. For example, automated response V can include at least letting the activity pass. Response W can include sending help tips to the customer at the checkout lane. Response X can include flashing the lane light at the customer's checkout lane. Responses Y1-Y5 can include automating a charge and/or alerting security and safety personnel. Moreover, response Z can include halting the transaction. One or more other variations of human and automated system responses can be determined.

(82) When a response fails to have an intended effect, such as stopping or otherwise deterring/preventing the customer's activity, the computer system can escalate to a more serious response. In some implementations, as described herein, the computer system can only select human responses or only select automated system responses. In some implementations, as shown in the example of FIG. 3, the computer system can select a combination of both human and automated system responses.

(83) Here, the customer's activity risk score is 30/100. Because the risk score falls between the range of 20 to 40, the computer system can select human response B to respond to the customer's activity. For example, the human response B can include a variety of responses that can be applied to activity having a risk score between 20 and 40. The computer system can select a human

response of observing the customer, which can be one of the human responses B. If the selected human response B is a success and thus prevents or stops the customer's risk activity, then the computer system may not select another response to be applied. On the other hand, if the human response B does not work (e.g., does not deter the customer's activity), the computer system can resort to an escalated response. For example, the computer system can select one or more of the human responses C1-C2, D, and/or N. The computer system can also select one or more of the automated system responses V-Z. Optionally, the computer system can also increase the risk score. (84) Here, the human response B did not succeed in stopping the customer's activity (e.g., the customer continues scanning products during the checkout process and it is uncertain whether the customer is scanning the correct products). Thus, the computer system increases the risk score and escalates the response to automated system response X. The automated system response X can include, for example, flashing the lane light to bring attention of employees to the customer's checkout lane. In some implementations, the computer system may not escalate to any of the human responses C1-C2 because the computer system can determine that the store has limited available labor resources. Therefore, to efficiently use the available labor resources, the computer system can select an automated response.

(85) In this example, the response X may not succeed in stopping the customer's shoplifting. Therefore, the computer system increases the risk score and escalates the response by selecting human response D. Human response D can, for example, include having an employee check the customer's receipt once they complete the checkout process. At this point, when the employee checks the customer's receipt against the contents of their bags, the employee can discover that the customer has shoplifted. Therefore, the human response D was successful in stopping the shoplifting. Even if the store has limited available labor resources, the computer system may determine that human intervention is the appropriate way to escalate the response since automated responses may not be sufficient (e.g., automating a charge may not prevent or stop the customer from attempting to shoplift other products during the checkout process).

(86) FIGS. 4A-B is a flowchart of a process **400** for determining a response friction level to be used in determining an appropriate response to user activity in a retail environment. The response friction level can be determined based on analyzing data from devices in the retail environment that has been objectively attributed to a customer in the retail environment. The data can be analyzed to determine a risk impact score and a confidence score that the customer is likely engaging in risky activity that warrants some response/intervention before they leave the retail environment. The response friction level can be an aggregation or other combination of the risk impact score and the confidence score. The higher the response friction level, the more escalated a response may be to the customer. In other words, the higher response friction level can indicate that the customer is likely engaging in serious risky activity (e.g., the customer is shoplifting a smartphone that costs \$1,000 and the customer has shoplifted in the past) that warrants an immediate and more escalated response (e.g., human or manual response and/or automated system response) than a less serious risky activity (e.g., the customer is shoplifting a pack of cookies that costs \$3.99 and the customer has not shoplifted in the past).

(87) The process **400** can be performed by the computer system **102**. The process **400** can also be performed by one or more other computing systems, devices, computers, networks, cloud-based systems, and/or cloud-based services. For illustrative purposes, the process **400** is described from the perspective of a computer system.

(88) Referring to the process **400** in both FIGS. 4A-B, the computer system can receive data from devices in a store (e.g., retail environment) that corresponds to particular user activity (block **402**). As described in reference to FIGS. 1A-C, the computer system can receive seemingly disparate data such as image data, RFID readings, location-based signals, and/or transaction information from devices in the store, such as cameras, RFID readers, location-based signaling devices, and/or POS terminals in checkout lanes. The computer system can receive such data continuously (e.g., as

it is collected/detected). The computer system can also receive such data at predetermined time intervals (e.g., every 1 minute, every 5 minutes, every 10 minutes, every 30 minutes, every 1 hour, every 5 hours, every 10 hours, every 24 hours, etc.). The computer system can request data from monitoring devices in the store that correspond to a particular known objective identifier for the user. For example, the computer system can request data from monitoring devices that identify wireless signals associated with the user who was previously known to be a threat. Such wireless signals can include but are not limited to a MAC address. As another example, the computer system can request and receive data from monitoring devices in high-risk and/or high-dollar areas in the store in which those monitoring devices identify a threshold amount of location and/or product scanning activity associated with the user's mobile device and/or mobile application that is accessed at the user's device and linked to a user account with the store.

(89) In block **404**, the computer system can aggregate the data into an activity profile associated with an objective identifier of the customer. The computer system can associate user activity in the received data to a customer or customer using objective identifiers. The objective identifiers can include user account information, credit card information, other payment information, phone number, email address, clothing, body movement/mannerisms, and other features identified using object detection techniques. Although the process **400** is described in reference to a store, the process **400** can apply to any type of retail environment or other location public location where customers may purchase products, such as a mall. Therefore, transaction data that includes a same address or user account information can be associated with the particular customer having that address or user account information. Image data showing the customer in a same blue sweater in different locations in the store, including the checkout lane, can also be associated together with the transaction data into the activity profile for the particular customer.

(90) The computer system can determine a risk impact score of the activity profile in block **406**. The block **406** can be based on a variety of factors and/or conditions, including but not limited to a value of items associated with the activity profile (block **408**), presence of a personal safety threat in the activity profile (block **410**), and/or risk level (block **412**). The risk impact score can be a numeric value that is determined based on one or more factors. For example, the risk impact score can be determined based on the cost of products involved in the customer's activity (block **408**). If the customer is shoplifting products that exceed some threshold cost value, the computer system can assign a high risk impact score (e.g., a score above a threshold score value). On the other hand, if the customer is shoplifting a product that is less than some threshold cost value (e.g., the customer is shoplifting a book or several packs of gum), then the risk impact score can be assigned a low value. The risk impact score can therefore be a score value indicating an impact that the customer's activity may have on the store. The greater the impact of that activity, the higher the risk impact score.

(91) As another example, the risk impact score can be determined based on a physical risk to others in the store (block **410**). If the customer's activity exhibits signs of violence, harm, and/or fear (e.g., the customer is hunched over in image data with a weapon seemingly visible under their shirt), the computer system can assign a high risk impact score. After all, the customer's activity may have a big impact on the overall safety and security of the store.

(92) As yet another example, the risk impact score can be determined based on a risk of theft (block **412**). If the customer's activity most likely exhibits signs of theft (e.g., the customer is rushing through one or more aisles, their location is identified in an electronics department for a threshold amount of time but the transaction data indicates that the customer only purchased a book from the next aisle over, etc.), then the computer system can assign a high risk impact score. The high risk impact score indicates that the customer's activity may have a big impact on shortages in the store.

(93) In block **414**, the computer system can determine a confidence score that the activity in the activity profile corresponds to risky activity in the store. The risky activity can include theft or shoplifting, which is part of a shortage event in the store. The risky activity can include safety

and/or security events, such as physical harm, bodily harm, fear, terror, threats, and other types of safety and/or security events. The computer system can apply one or more machine learning trained models to the activity in the activity profile to identify and classify the activity. The activity can be classified as one or more types of activities, including various different types of risky activities as well as non-risky activity. The models can be trained for example, to identify one or more features in the activity that correspond to one or more types of activities, then label the features as such.

(94) As an illustrative example, a model can be trained to process transaction data in combination with image data of at least a checkout lane in the store. The model can correlate items recorded in the transaction data with items appearing in the image data during the checkout process. The model can then be trained to identify if any items appear in the image data that do not match items recorded in the transaction data. Identifying such items that do not appear in the image data can cause the model to generate output indicating a likelihood of theft/shoplifting during the checkout process. Accordingly, the model can generate a confidence score above a threshold value, the confidence score indicating a high likelihood that the activity in the activity profile corresponds to a shortage event in the store.

(95) As another illustrative example, a model can be trained to process image data of the customer moving throughout the store and determine a likelihood that the customer poses a security threat to the store. The model can be trained to identify actions or bodily movements made by the customer that are likely associated with security or safety threats. For example, the model can be trained to identify and label aggressive posturing, rapid movement in and around aisles or near shelves, turning their head back and forth/up and down an aisle, etc. As another example, the model can be trained to identify and label weapons and actions likely attributed to safety and security threats (e.g., running in the store, pushing or shoving someone, aggressively bumping into someone, punching someone, tripping someone, etc.).

(96) The models can be trained with training data sets that include data collected by the devices in the store, as described herein. The training data sets can also include data collected by devices at one or more other stores in a network of stores. Moreover, the training data sets can include data that has been labeled by humans and/or data that has been labeled automatically by the computer system or other computing systems.

(97) The models can generate, as output, confidence scores for the activity profile indicating likelihood or confidence that the activity in the activity profile is in fact risky activity. The confidence score can be a float value from 0 to 1. The confidence score can also be a numeric value on a predetermined scale, including but not limited to 0 to 5, 0 to 10, 0 to 50, 0 to 100, 1 to 5, 1 to 10, 1 to 50, 1 to 100, etc. In some implementations, the confidence score can also be percentage indicating likelihood/certainty that the activity is risky activity (e.g., 50% certain the activity is risky, 100% certain the activity is risky, etc.). A higher confidence score can indicate a higher confidence or likelihood that the activity in the activity profile is associated with a risky activity, such as a shortage or safety/security event. A higher confidence score can be assigned to the activity profile if, as an illustrative example, transaction data in combination with location data and image data clearly identifies the customer pocketing an item from a shelf and paying for another item during a self-checkout process. A lower confidence score can be assigned to the activity profile if, as another illustrative example, image data is too blurry to discern whether the customer has a gun on their hip or just a bag, and thus would not pose a security or safety risk in the store.

(98) Block **414** can include, for example, analyzing customer posture and/or actions in the data associated with the activity profile (block **416**). As described above, the computer system can employ one or more machine learning trained models to process the data and identify features in the data indicative of customer posture and/or actions most commonly associated with risky activity (e.g., theft, safety/security threats, etc.). For example, a model can be trained to distinguish activity of removing an item from a shelf and placing the item in a cart or basket from removing an item from the shelf and putting the item inside the customer's bag or clothes. The computer system

can then assign a higher confidence score (e.g., above a threshold score value) to the latter and a lower confidence score (e.g., below the threshold score value) to the former.

(99) The computer system can also determine price information of the item(s) in transaction data during a checkout process associated with the activity profile (block **418**). The computer system can apply one or more models to the received data to determine whether a shortage might have occurred (e.g., image data of the customer at the checkout lane shows the customer putting an item in a bag without first scanning the item). The computer system can verify this determination with the transaction data to see whether all items appearing in the image data have been accounted/paid for on a receipt (e.g., the transaction data). If the computer system identifies an item in the image data that does not appear on the receipt, the computer system can retrieve, from a data store, information about the identified item, which can include a price of the item. If the price of the item exceeds some threshold price value, which is not reflected on the receipt, then the computer system can generate a high confidence score that the customer is involved in a shortage. If the price of the item may not be discernible from the received data, then the computer system can assign a low confidence score, indicating a low likelihood that the customer is engaging in a shortage event in the store.

(100) The computer system can also identify a weapon on or near the customer in the data associated with the profile in block **420**. As described above, the computer system can employ one or more models that have been trained to analyze the received data and extract or identify portions of the data that may be indicative of weapons. Object detection techniques can be performed in some implementations to identify weapons in image data. If a weapon is discernible or otherwise easily recognizable in the received data, then the computer system can generate a high confidence score indicating that the customer is likely engaged in a security/safety event. If the weapon is less discernible in the data (e.g., image data is blurry and something that looks like a weapon blends in with the customer's clothing), the computer system can assign a low confidence score indicating that it is less certain whether the customer is engaging in a safety/security event.

(101) In some implementations, blocks **406-420** can be performed at a same time. In some implementations, blocks **414-420** can be performed before blocks **406-412**. In some implementations, blocks **414-420** can be performed at the start of the process **400** (e.g., before or after block **402**). Therefore, the computer system can first determine whether risky activity is apparent or likely in the data received for the store or in the activity profile (block **404**). The computer system can determine whether risky activity is apparent or likely based on applying one or more machine learning trained models to the received data. The models can be trained to identify and score various features in the received data that can indicate one or more types of risky activity. If risky activity is apparent or likely, then the computer system can continue through the process **400**. On the other hand, if risky activity is not apparent or not likely in the data received from the devices in the store (or in the activity profile), then the computer system may not perform the rest of the process **400**, which can provide for efficient use of compute resources and processing power at the computer system.

(102) Still referring to the process **400** in both FIGS. **4A-B**, the computer system can determine whether the impact score and/or the confidence score satisfy risk criteria in block **422**. In some implementations, the computer system can aggregate the impact score and the confidence score to determine an overall risk score for the user activity associated with the activity profile. For example, the two scores can be multiplied. The two scores can also be normalized in other ways. For example, a threshold-based trigger can be used to normalize the two scores and determine whether the normalized scores satisfy the risk criteria.

(103) The risk criteria can be based on one or more factors. For example, the risk criteria can be associated with factors relevant to shortage events in the store. The risk criteria can also be associated with factors relevant to safety/security events in the store. The impact score and/or the confidence score can satisfy the risk criteria, as an illustrative example, if the dollar value of items

involved in theft activity exceeds a threshold cost value. This can indicate that the theft associated with the customer's activity profile likely involves expensive items (or items that cost more than the threshold cost value), which makes the customer pose a greater risk to the store. Since the customer poses a greater risk, more serious action can and should be taken in response to the customer's activity. On the other hand, if the activity involves theft of an item that costs only \$2, the risk criteria may not be satisfied and the activity either may not require a response or may require a less serious response than if the cost of the stolen item was higher (e.g., exceeding the threshold cost value).

(104) As another illustrative example, the risk criteria can be satisfied if the confidence score exceeds a threshold score value. The threshold score value can be, in some implementations, 90-100% certainty that the activity poses a risk to the store. If the activity has a confidence score between 90-100%, the activity likely poses a serious risk to the store and therefore should be addressed with a more serious response/action. On the other hand, if the activity has a confidence score of 50% or less, then the activity may not pose as serious of a risk to the store and therefore may warrant no response or a less serious response than if the confidence score were higher.

(105) As another example, the computer system can determine whether the impact score and/or the confidence score exceeds a general risk threshold value (block **424**). If the general risk threshold value is exceeded, the risk criteria is satisfied. The general risk threshold value can pertain to both shortage and safety/security events in the store. Therefore, regardless of whether the activity in the activity profile is related to a shortage event or a safety/security event, the same general risk threshold value can be applied as the risk criteria. The general risk threshold value can be a numeric value on a same scale as the impact score and/or the confidence score. In some implementations, the impact score and the confidence score can be weighted and/or aggregated into a general risk score. Then the general risk score can be compared to the general risk threshold value to determine whether the risk criteria is satisfied in block **424**.

(106) The computer system can additionally or alternatively determine whether the impact score and/or the confidence score exceeds a safety risk threshold value (block **426**). The safety risk threshold value can be used in implementations in which the activity in the activity profile is associated with safety/security events in the store. For example, if the computer system analyzes image data and determines a weapon is likely present near/on the customer's body, then the computer system can classify the customer's activity as a safety/security event. The computer system can then apply the safety risk threshold value in block **426** to determine whether the activity satisfies the risk criteria. As mentioned above, the safety risk threshold value can be on a numeric scale that corresponds to the impact score or the confidence score. In some implementations, the safety risk threshold value can be on a numeric scale that corresponds to a general risk score, which can be an aggregation/weighting of the impact score and the confidence score.

(107) The computer system can additionally or alternatively determine whether the impact score and/or the confidence score exceeds a shortage risk threshold value (block **428**). The shortage risk threshold value can be used in implementations in which the activity in the activity profile is associated with shortage events (e.g., theft, shoplifting, sweethearting, etc.) in the store. For example, if the computer system analyzes image data and transaction data and determines the customer put an item inside their jacket and did not pay for it during a checkout process, then the computer system can classify the customer's activity as a shortage event. The computer system can then apply the shortage risk threshold value in block **428** to determine whether the activity satisfies the risk criteria. As mentioned above, the shortage risk threshold value can be on a numeric scale that corresponds to the impact score or the confidence score. In some implementations, the shortage risk threshold value can be on a numeric scale that corresponds to a general risk score, which can be an aggregation/weighting of the impact score and the confidence score.

(108) In some implementations, the computer system can determine which of the blocks **424-428** to perform based at least in part on analysis of the data associated with the activity profile (e.g., in

block **404**). For example, if the computer system determines that the user activity is likely associated with a shortage event, the computer system can perform block **424** and/or block **428**. If the computer system determines that the user activity is likely associated with a personal safety risk, the computer system can perform block **424** and/or block **426**.

(109) Referring to blocks **422-428**, if the computer system determines that the impact score and/or the confidence score satisfy the risk criteria (e.g., any of the scores exceed one or more of the threshold values in blocks **424-428**), the computer system can proceed to block **430**.

(110) In block **430**, the computer system can generate a response friction level for the activity profile that is above a threshold friction value. The computer system can then proceed to block **434**, described further below. The response friction level can be a numeric, Boolean, integer, and/or string value. The response friction level can be assigned along a sliding scale demonstrating that various different responses to the customer activity can be pursued as the friction level increases. Accordingly, the higher the impact score and/or the confidence score, the more response friction, and the more serious the response(s) to the activity. The response friction level can indicate a seriousness or escalation of the response to the activity. The higher the response friction level, the more serious or escalated the response. The lower the response friction level, the less serious or deescalated the response. In other words, the higher the response friction level, the greater the action(s) will be taken to stop the activity of the customer and prevent further risk to the store.

(111) As an illustrative example, a higher response friction level can cause the computer system to generate instructions for an in-store employee to approach the customer and apprehend them before they can leave the store. A higher response friction level can also cause the computer system to generate an automated system response to be executed by a checkout system that the customer is using. The automated system response can include, for example, halting the customer's checkout process and/or requiring the customer to rescan the items they are purchasing. On the other hand, a lower response friction level can cause the computer system to generate instructions for the in-store employee to simply monitor the customer or keep an eye out for the customer if and when they return to the store in the future. A lower response friction level can also cause the computer system to generate an automated system response to be executed by the checkout system that includes, for example, presenting tips to help the customer properly scan the items they wish to purchase. One or more other responses can be generated based on the response friction level, as shown and described in reference to FIGS. 2-3.

(112) Referring back to blocks **422-428**, if the computer system determines that the impact score and/or the confidence score do not satisfy the risk criteria (e.g., any of the scores do not exceed one or more of the threshold values in blocks **424-428**), the computer system can proceed to block **432**.

(113) In block **432**, the computer system can generate a response friction level for the activity profile that is below the threshold friction value. The computer system can then proceed to block **434**. The response friction level below the threshold friction value can indicate that a less serious response can be made to the customer's activity, as described above. Refer to FIGS. 2-3 for additional discussion.

(114) Next, in block **434**, the computer system can determine an appropriate response to the user activity associated with the activity profile based on the response friction level. As described further in reference to FIGS. 5A-B, determining the appropriate response can include determining whether the response should be a human response or an automated system response. A human response can be preferred in some scenarios, such as when the customer is carrying a weapon or imposing harm or physical threats on other customers in the store. An automated system response, on the other hand, can be preferred in some scenarios, such as when the store has a limited number of employees on the floor and the customer is likely engaging in petty theft. It can be more efficient use of the labor resources available in the store if the automated system response is invoked instead of detracting an employee from their task to check on the customer during their checkout process. The type of activity in the activity profile can suggest an appropriate response. Determining the

appropriate response can also include selecting a human or automated system response that corresponds to the response friction level that was determined in blocks **430** and **432**. For example, a higher response friction level can correspond to an escalated human response, such as approaching and apprehending the customer while a lower response friction level can correspond to a less serious human response, such as simply monitoring the customer over a security camera in the store. As another example, a higher response friction level can correspond to an escalated automated system response, such as halting the customer's checkout process altogether while a lower response friction level can corresponded to a less serious automated system response of simply presenting helpful tips to the customer at the customer's checkout system. One or more other responses can be determined in block **434**, as described and shown in reference to FIGS. **2**, **3**, and **5A-B**.

(115) The computer system can return the determined response in block **436**. Returning the determined response, as depicted and described in FIGS. **1A-C** can include transmitting instructions to an employee device to perform a human response. Returning the determined response can also include transmitting instructions to a checkout system used by the customer to execute an automated system response. The transmitted instructions can include objective identifiers for the customer (e.g., images of their hair, clothes, posture, email address, checkout system ID/location, location information in the store, transaction ID, MAC address, etc.), which can assist an employee (in the example of a human response) to objectively identify the customer and then carry out the human response. The transmitted instructions can also include information about the risky activity of the customer, such as whether the customer has a weapon, whether the customer assaulted or attacked someone while in the store, whether the customer likely has items in their clothing, whether the customer is hiding items on their body, whether the customer has scanned and/or purchased items, etc. Any of this information can be used to quickly and objectively identify and respond to the customer by the employee.

(116) The instructions transmitted to the checkout system can, for example, cause the checkout system to lock a display screen or POS terminal such that the customer cannot scan any more items or select options to complete a checkout process. The instructions transmitted to the checkout system can also cause the checkout system to deactivate one or more scanning devices or otherwise prevent the scanning devices from detecting barcodes and other identifiers. The instructions transmitted to the checkout system can also cause the checkout system to present one or more notifications on a display of the checkout system. The notifications can, for example, present the customer with tips about how to scan items and/or how to bag items during the checkout process. The notifications can also present the customer with messages that something was not scanned correctly or that it seems as if one or more items were not scanned. One or more other notifications can also be generated and presented at the checkout system, based on the response friction level associated with the customer's activity profile.

(117) FIGS. **5A-B** is a flowchart of a process **500** for selecting between human and automated system responses to user activity in a retail environment. The process **500** can be performed to determine whether a human response or an automated system response is preferred to respond to the particular user activity. This determination can be made based on a response friction level determined for the user's activity (e.g., refer to the process **400** in FIGS. **4A-B**), the user's activity, and whether the customer appears on a watch list for the retail environment. Some types of user activity may warrant human responses (e.g., carrying a gun or other weapon, assault, other personal safety risks), regardless of severity or certainty of the user's risky activity. Some types of user activity may warrant automated system responses, which can be based on availability of labor resources in the retail environment (e.g., the retail environment can be short-staffed during a lunch period and when ticket switching is identified at a self checkout lane, it may be more labor resource efficient to generate an automatic response at the POS terminal to stop the customer's checkout process and require them to rescan items than to instruct an employee of the retail environment to

leave their tasks/role to assist the customer and check whether they are in fact ticket switching.

(118) The process **500** can be performed by the computer system **102**. The process **500** can also be performed by one or more other computing systems, devices, computers, networks, cloud-based systems, and/or cloud-based services. For illustrative purposes, the process **500** is described from the perspective of a computer system.

(119) Referring to the process **500** in both FIGS. 5A-B, the computer system can receive an activity profile associated with a particular customer or guest, the respective response friction level, and a watch list for the store (e.g., retail environment) in block **502**. Any of this information can be received using objective identifiers associated with the customer of the activity profile. The computer system can receive the activity profile and the respective response friction level that were determined/generated in the process **400** of FIGS. 4A-B.

(120) The watch list can be retrieved from a data store. The watch list can be associated with the store and can indicate trends of which customers have been involved in risky activities in the store over some predetermined period of time. The predetermined period of time can be, for example, a past day, 3 days, 5 days, 7 days, 2 weeks, month, etc. The watch list can identify customers by their objective identifiers and can indicate what type of activity they have been associated with and how recent they performed such activity. For example, a customer who has shoplifted electronic devices every other day for a past 2 months can be put on the watch list and ranked higher in the watch list than another customer who stole an electronic device once over the past 2 months. As another example, a customer who has a history of violence (e.g., the customer was released from prison recently) and has been seen in the store with a weapon can be ranked higher in the watch list than a customer who has not been violent but has engaged in organized crime or other theft. The watch list can therefore be used by the computer system to determine how much of a risk the particular customer poses to the store. If the customer appears on the watch list and/or the customer is ranked high on the watch list (e.g., above a threshold watch list ranking), then the computer system can escalate a type of human or automated system response to the customer's activity.

(121) In block **504**, the computer system can retrieve a set of human responses and a set of automated responses to different types of activities in the store. Each store in a network of stores can have different sets of responses based on available resources, in some implementations. The computer system can use a unique identifier for the store to search a data store of responses that are associated with the store's unique identifier.

(122) Certain responses may be retrieved in block **504** based on short-term availability of labor resources. If a quantity of employees working the sales floor is below a threshold quantity of workers and/or the employees working the sales floor do not have the necessary skills/authority/job role to perform a human response (e.g., apprehending the customer and writing a report for law enforcement), then the computer system can retrieve just a set of automated responses and/or may retrieve a set of human responses that can be completed by the limited quantity of employees currently working. As another example, certain responses may be retrieved based on long-term availability of resources in the store. If the store does not have any self-checkout lanes, in some implementations, then the computer system can retrieve human responses and/or automated responses that can be performed by in-store systems other than self-checkout systems.

(123) The computer system can also retrieve the set or sets of responses based on the type of activity in the activity profile. For example, the computer system can retrieve a set of human responses and/or a set of automated responses that are typically used in response to theft. The computer system can retrieve a set of human responses and/or a set of automated responses that are typically used in response to physical or bodily harm. The computer system can retrieve a set of human responses and/or a set of automated responses that are typically used in response to general shortage events. The computer system can retrieve a set of human responses and/or a set of automated responses that are typically used in response to specific types of shortage events. Also, the computer system can retrieve a set of human responses and/or a set of automated responses that

are typically used in response to any type of safety/security event. The computer system can retrieve a set of human responses and/or a set of automated responses that are typically used in response to specific types of safety/security events.

(124) The computer system can determine whether activity in the activity profile satisfies human response criteria in block **506**. For example, the computer system can determine whether a type of the activity is associated with human responses (block **508**). If the type of activity in the activity profile is typically responded to using human intervention, then the block **508** can be met and the human response criteria can be satisfied. The computer system can analyze historic events and activity responses stored in the data store to determine whether a human response was typically invoked. The activity may be associated with human responses if, for example, the activity involves harm or weapons, in which a system in the store may not be able to stop the customer and confiscate their weapon but another person, such as an employee (e.g., safety and security personnel) can. The activity may also be associated with human responses if, for example, the activity is part of an organized crime of theft and presenting a prompt on a checkout system may not deter the customer or other organized customers from continuing to steal items from the store. The activity may also be associated with human responses if, for example, the customer is a repeat offender and has stolen items multiple times and has not been deterred in the past by automated responses (e.g., prompting the customer to re-scan items, halting the customer's transaction, etc.). One or more other examples of activity that typically is associated with human responses is also possible.

(125) The computer system can additionally or alternatively determine whether store resources are available for a human response in block **510**. The store resources can be available labor resources. If the store currently has less than a threshold quantity of employees working, then there may not be sufficient labor resources to prompt one of the employees to leave their task/role and respond to the customer's activity. As another example, if the employees currently working do not have the necessary skills to respond to the customer's activity (e.g., the employee is a student who re-stocks shelves and does not have experience in confronting and apprehending aggressive customers), then the store resources are not available for a human response. On the other hand, if the quantity of employees working the store is low but the customer is part of organized crime, is carrying a weapon, and/or is engaging in a big theft (e.g., theft of item(s) exceed(s) threshold cost value), then it can be an efficient use of the available labor resources to prompt one of the employees to approach and apprehend the customer. Doing so can stop the customer's current activity and potentially deter the customer from continuing this activity in the future. If, however, the customer is merely stealing tube of lipstick, it can be an inefficient use of the available labor resources if an employee were to respond to the customer. After all, it takes the same amount of time, energy, skills, and resources to apprehend and write a report about the customer involved in organized crime and the customer who stole the lipstick. However, apprehending and reporting the customer involved in organized crime can pose a greater risk to the store, and thus should be apprehended and reported to deter or otherwise prevent such organized crime from continuing.

(126) In some implementations, in block **510**, the computer system can determine whether the store has available system resources capable of performing automated system responses. For example, if the store does not have self-checkout systems, then one or more automated system responses may not be performed. Therefore, the computer system can determine that the activity should be responded to with human responses.

(127) The computer system can also determine whether the customer associated with the profile satisfies watch list criteria in the store's watch list (block **512**). A frequency and/or how recently the customer was identified as engaging in risky activity in the store and thus appears on the watch list can indicate whether the customer poses a significant enough risk to the store to warrant using labor resources in a human response. The higher the customer appears on the watch list, the more likely that a human response is warranted. If the customer appeared multiple times on one or more

watch lists over some predetermined period of time (e.g., a past 3 days, a past week, a past 2 weeks, a past month, etc.), then a human response is likely warranted. Similarly, if the customer appeared at least a threshold amount of times on the watch list, then a human response is likely warranted. In some implementations, the computer system can also retrieve a watch list for a nearby store or stores. If the customer appears in those watch lists, then the computer system can determine that a human response is warranted to stop the customer from continuing to hit multiple stores in a geographic area/location/region.

(128) As another example, the computer system can determine whether the cost of item(s) in the activity associated with the profile exceeds a threshold cost value (block **514**). The more expensive the item(s) involved in a shortage, for example, the more efficient it may be to use labor resources to stop the customer. As a result, the customer can be stopped from continuing to steal expensive items. As mentioned above, if the customer instead engages in occasional petty theft, then it may be an inefficient use of labor resources to monitor, apprehend, and/or report the customer.

(129) In block **516**, the computer system can determine likelihood that the customer associated with the activity profile is also associated with organized/group crime/activity. The computer system can, for example, analyze the watch list for the store and determine what activities the customer has been listed for. The computer system can also compare the customer's activities to those of other customers appearing on the watch list to find a correlation between customers, activities, and/or items involved in those activities. The computer system can also receive law enforcement reports describing organized crime in a geographic region of the store. The computer system can use the reports to analyze the customer's activity and determine whether it matches the profile of the organized crime. Similarly, the computer system can receive reports or watch lists from other stores in the same geographic region of the store. The computer system can analyze those reports and/or watch lists in relation to the customer's activity to determine whether they are associated with organized crime. The computer system can generate a confidence score indicating likelihood that the customer is engaged in organized crime. If the confidence score exceeds a threshold confidence value, the computer system can determine that the human response criteria is satisfied. Monitoring, apprehending, and/or reporting the customer can be beneficial to stop, deter, or otherwise prevent the organized crime.

(130) The computer system can additionally or alternatively determine in block **518** whether a weapon and/or bodily harm is likely or apparent in the activity associated with the profile. Based on analysis of data associated with the customer's activity profile (e.g., refer to the process **400** in FIGS. **4A-B**), the computer system can generate a likelihood value that the customer is carrying a weapon or engaging in physical violence. If the likelihood value exceeds some threshold value, then the computer system can determine that the human response criteria is satisfied. After all, a human response can be more effective in stopping a person wielding a gun or attacking another person than performing an automated system response like halting the person's transaction during a checkout process.

(131) In some implementations, the computer system can perform one or more of the blocks **508-518** as part of determining whether the activity in the profile satisfies the human response criteria in block **506**. In some implementations, one or more of the blocks **508-518** can be performed in order to perform subsequent blocks **508-518** as part of the determining in block **506**. In some implementations, the computer system can also determine which of the blocks **508-518** to perform based on the type of activity in the activity profile. For example, if the type of activity is associated with shortages/theft, then the computer system may perform blocks **508**, **510**, **514**, and/or **516**. As another example, if the type of activity is associated with safety risks, then the computer system can perform blocks **508**, **510**, **512**, **516**, and/or **518**. One or more other variations of performing the blocks **508-518** is also possible.

(132) Referring back to block **506**, if the computer system determines that the activity in the profile satisfies the human response criteria, the computer system can proceed to block **520**. In block **520**,

the computer system can select a human response from the set of human responses based on the response friction level associated with the profile. The selection of the human response can also be based on human response selection criteria. The human response selection criteria can indicate which types of human responses may be warranted for types of customer activity.

(133) As an example, if the response friction level associated with the profile is within a range of first values, the computer system can determine that a first human response selection criteria is satisfied and that a first type of human response can be selected. As another example, if the response friction level associated with the profile is within a range of second values, the computer system can determine that a second human response selection criteria is satisfied and that a second type of human response can be selected. As another example, if the response friction level associated with the profile is within a range of N values, the computer system can determine that an N human response selection criteria is satisfied and that an N type of human response can be selected. Refer to FIG. 3 for additional information about selecting the human response based on the response friction level falling within a range of values. Refer to FIG. 2 for additional information about selecting the human response along a sliding scale of response friction levels.

(134) The computer system can then transmit response instructions to a device of a human worker available to respond to the user activity in the store (block 522). The computer system can, for example, first determine which employee in the store is available to respond. For example, the computer system can determine which employee has prerequisite skills to perform the human response, which employee just completed a task in their job role and is available, which employee is physically closest to a location of the customer, which employee has performed similar human responses in the past, etc. Once the computer system determines which employee should respond to the customer's activity, the computer system can transmit the instructions to a mobile device of the employee. As described herein, the mobile device can be a user computing device, such as a cellphone, mobile phone, smartphone, laptop, tablet, and/or wearable device. Refer to block 436 in the process 400 in FIGS. 4A-B for additional discussion about the transmitted instructions.

(135) Referring back to block 506, if the computer system determines that the activity in the profile does not satisfy the human response criteria, the computer system can proceed to block 524. In block 524, the computer system can select an automated response from the set of automated system responses based on the response friction level associated with the profile. The selection of the human response can also be based on automated system response selection criteria. Refer to the discussion in block 520 about selecting the human response. Also refer to FIGS. 2-3 for additional discussion about selecting the automated system response.

(136) The computer system can then transmit the selected response to a checkout system or other device in the store where the customer is completing a checkout process (block 526). In some implementations, the selected automated response can also be transmitted to and performed by a user mobile device, mobile checkout device, scan-and-go devices, and/or smart shopping carts. For example, the automated response can be transmitted to the customer's mobile device, which was used by the customer to scan items in the store and/or pay for items during the checkout process. The automated response can be outputted or presented in a GUI display in a mobile application presented at the customer's mobile device. The mobile application, for example, can provide functionality for the customer to scan items for purchase in the store and maintain payment information so that the customer can pay with an e-wallet. As an illustrative example, an alert or other notification can be presented in the mobile application, that may prevent the customer from paying with their payment information. In some implementations, alerts or other similar automated responses can also be transmitted to and executed at employee devices such as employee devices and/or walkie-talkies or other radio communication devices. Refer to block 436 in the process 400 in FIGS. 4A-B for additional discussion about transmitting the selected response to the checkout system or other device in the store.

(137) In some implementations, even if a human response is warranted based on a determination in

block **506** that the human response criteria is satisfied, the computer system can also determine that an automated response should be invoked, or vice versa. Therefore, the computer system can blend together one or more human and/or automated responses. For example, the computer system can determine that the customer should be monitored by an employee during their checkout process. During the checkout process, the computer system can analyze image data and transaction data and determine that the customer is not scanning all the items they wish to purchase (instead the customer is pocketing some items and scanning others). Therefore, the computer system can select an automated response to also be performed in which the checkout system prompts the customer to re-scan their items. If the customer does not re-scan all their items, the computer system can escalate the responses by (i) selecting a human response to approach and apprehend the customer and/or (ii) selecting an automated response to completely halt the customer's transaction. Thus, the computer system can blend both human and automated responses based on how the customer's activity may develop, escalate, or otherwise not be deterred by a response that has been executed. As another example, the computer system can select an automated response of causing a lane light at the checkout lane to blink and a human response of an employee approaching the customer while the lane light is blinking to assist the customer through the checkout process. Accordingly, the computer system can select a human response in block **520** and also select an automated response in block **524**. The computer system can then perform both blocks **522** and **526**. Likewise, the computer system can select an automated system response in block **524** and also select a human response in block **520**. The computer system can then perform both blocks **522** and **526**.

(138) In some implementations, the computer system can determine whether an automated system response can be performed before determining whether the activity satisfies the human response criteria in block **506**. For example, if the activity in the profile can simply and efficiently be resolved with an automated system response, or the response friction level is below a threshold friction level, then blocks **506-518** can be skipped and the computer system can simply select an appropriate automated system response from the set of automated system responses. This can be a beneficial approach for efficiently using available compute resources and also saving limited labor resources.

(139) In some implementations, the computer system may store selected responses with the particular activity profile in a data store. The computer system can also store results from performing those responses with the activity profile. As a result, at future times, the computer system can retrieve information about the selected responses and/or results from invoking those responses, if and when the customer associated with the profile returns to the store. Prior human and/or automated responses can be leveraged to identify and select optimal responses to prevent and/or deter the particular customer from continuing to perform risky or suspicious activity in the future.

(140) FIG. **6** is a system diagram of system components that can be used to perform the techniques described herein. The computer system **102**, employee devices **104A-N**, checkout systems **106A-N**, cameras **108A-N**, location-based signaling devices **110A-N**, RFID readers **114A-N**, user devices **112A-N**, and data store **600** can be in communication (e.g., wired and/or wireless) via the network(s) **105**.

(141) The employee devices **104A-N** can include any type of mobile computing device, such as a mobile phone, smartphone, laptop, tablet, and/or wearable device. Each employee in a retail environment or store can be assigned an employee device **104A-N** using a unique employee ID. In some implementations, the employee devices **104A-N** can include personal computing devices of the employees rather than devices provided to them by the store.

(142) The cameras **108A-N**, as described in reference to FIG. **1A**, can be positioned throughout the store in various locations. The cameras **108A-N** can capture still image and/or videos of their designated/calibrated field of views. Moreover, the cameras **108A-N** can continuously capture image data. Some of the cameras **108A-N** can be triggered to capture image data when a particular

action occurs. For example, if a customer starts a checkout process at one of the checkout systems **106A-N**, a camera positioned near the checkout system can be activated to capture image data of the customer and the area surrounding the checkout system during the customer's checkout process. The cameras **108A-N** can already be installed in the store and part of a security camera system therein. In some implementations, the store can be retrofitted with other, new, and/or additional cameras. Moreover, the cameras **108A-N** can be configured to capture high resolution image data. The high resolution image data can be efficiently transmitted to and processed by the computer system **102** without losing the high resolution quality of the image data. Therefore, the high resolution image data can be used to accurately assess actions of customers' activities in the store. Sometimes, one or more of the cameras **108A-N** can also capture low resolution image data.

(143) The location-based signaling devices **110A-N** can be configured to ping (e.g., transmit a request to) any of the user devices **112A-N** as the user devices **112A-N** pass the devices **110A-N** in various locations throughout the store. By pinging the user devices **112A-N**, the user devices **112A-N** can transmit a mobile device identifier, such as a MAC address, to the location-based signaling devices **110A-N**. The MAC address can be correlated with a timestamp generated by the devices **110A-N** that indicates when and where the customer was located in the store. Therefore, the customer's location(s) in the store can be documented with objective identifiers, such as the MAC address, to be correlated with other data collected by other devices in the store.

(144) The RFID readers **114A-N** can be any type of device for detecting RFIDs as well as other types of unique identifiers that may be attached to items as well as baskets/carts in the store, including but not limited to barcodes, SKUs, labels, and other tags. The RFID readers **114A-N** can be configured to detect when an RFID tag comes within a vicinity or range of the readers **114A-N**. When an RFID tag is detected, the readers **114A-N** can generate timestamped data indicating a location of the particular RFID tag at a time it was detected. This information can be correlated with the other data collected by the other devices in the store (e.g., such as the MAC address of the customer from the location-based signaling devices **110A-N**) to analyze and assess the customer's activity.

(145) The user devices **112A-N** can include any type of mobile computing device, such as a mobile phone, smartphone, laptop, tablet, and/or wearable device. The user devices **112A-N** can be personal computing devices of the customers in the store. Each customer can have their own user device. The customers can open a mobile application associated with the store at their user devices **112A-N** and log into their personal accounts (e.g., via username, email, phone number, password, or other objective identifiers). The customers can use the mobile application to search for items in the store, add items to an online shopping cart, complete online orders, scan items in the store while they are shopping, and/or pay for their items during the checkout processes at the checkout systems **106A-N**. For example, the user devices **112A-N** can present mobile wallets with payment information, which can be used to simply and quickly complete a checkout process at a self-checkout lane and/or a manual checkout lane. Location data from the user devices **112A-N** and/or objective identifiers, such as MAC addresses, can be collected by the computer system **102** from the user devices **112A-N** and used to correlate the other data with a particular customer and analyze the customer's activity in the store, as described herein.

(146) The checkout systems **106A-N** can include self-checkout lanes and/or manual lanes worked by employees. The checkout systems **106A-N** can be used to perform checkout processes in the store at the end of a shopping trip. The checkout systems **106A-N** can each include a POS terminal **620**, scanning devices **622A-N**, display **624**, input devices **626A-N**, processor **628**, and communication interface **630**. In some implementations, the checkout systems **106A-N** can also include output devices that are different than the display **624**, such as speakers, another display screen, and/or a device for providing haptic feedback.

(147) The POS terminal **620** can be configured to identify products that are scanned using the one or more scanning devices **622A-N**. For example, the POS terminal **620** can receive a scan of an

item label from the one or more scanning devices **622A-N**. Using the scan of the label, the POS terminal **620** can retrieve/determine a price of the item associated with the label. The POS terminal **620** can add the determined price to the customer's bill (e.g., transaction, receipt). The POS terminal **620** can also receive payment information from the customer, including but not limited to discounts, offers, or other types of promotions. The POS terminal **620** can update the customer's transaction data and complete a checkout process upon receipt of the customer's payment information. The customer can, for example, scan, using the scanning devices **622A-N**, a barcode or other unique identifier presented on their user device **112A-N** representing their mobile wallet information. The POS terminal **620** can receive the scanned identifier and use that to look up the customer's mobile wallet information in the data store **600** and/or receive the mobile wallet information directly from the user device **112A-N**. The POS terminal **620** can then apply the mobile wallet information to the customer's transaction to complete the checkout process and therefore pay for the customer's items.

(148) The scanning devices **622A-N** can be integrated into a flatbed of the checkout systems **106A-N**. The scanning devices **622A-N** can also be standalone devices and/or handheld devices. In some implementations, scanning devices **622A-N** can include one or more cameras or other imaging devices integrated into the flatbed or other regions of the checkout systems **106A-N**. In such scenarios, the cameras or other imaging devices can be configured to capture images of items as the customer scans them. These images can be used by the computer system **102** to determine whether the customer is scanning all the items they are purchasing (and thus the items that appear in the customer's transaction data). The scanning devices **622A-N** can be barcode, SKU, or other label identifying devices. The scanning devices **622A-N** can also be LiDAR, infrared, and one or more other types of scanning devices and/or flatbed scanners. In some implementations, the one or more scanning devices **622A-N** can include a handheld scanner that the customer can direct towards a label, such as a barcode, attached to an item that the customer is purchasing. Moreover, in some implementations, the handheld scanner can include a camera that captures images of the item as it is being scanned, which can further be used by the computer system **102** to determine whether the customer is shoplifting or engaging in other risky activity during the checkout process.

(149) The display **624** can be any type of screen, such as a touch screen, LED screen, OLED screen, etc. The display **624** can output information about the customer's transaction. For example, the display **624** can output information about scanned items and their associated prices in real-time, as the customer scans the items. In some implementations, such as when the computer system **102** selects an automated system response to the customer's risky activity, the display **624** can present a notification that prompts the customer to re-scan items, check the contents of their basket/cart before completing the checkout process, etc. The customer can also input information at the display **624** about items being purchased, such as a quantity and/or weight of such items. The customer can also use the display **624** to look up items that the customer is purchasing (e.g., fresh produce that may not have barcodes or other identifying labels attached to them). In some implementations, the POS terminal **620** can be integrated with the display **624** and/or one or more of the scanning devices **622A-N**.

(150) The input devices **626A-N** can include keyboards, touchpads, touch screen displays, and/or microphones that can be used by the customer to provide information during the checkout process. For example, the customer can use the input devices **626A-N** to manually enter information about an item they are purchasing that does not have a label/barcode on it (e.g., fresh produce). The customer can also use the input devices **626A-N** to swipe a credit card, provide cash payment, and/or manually enter login information for the customer's account with the store (e.g., their mobile wallet information). In some implementations, the input devices **626A-N** can include the POS terminal **620**, the scanning devices **622A-N**, and/or the display **624**.

(151) The processor **628** can be configured to make real-time determinations of item identification and optionally item-to-label matching. The processor **628** can also be configured to make updates

to the customer's transaction data based on items scanned, promotions/offers added to the transaction, etc. In some implementations, the processor **628** can be an edge computing device. In some implementations, the processor **628** can deploy one or more machine learning models to identify an item from image data captured by one or more cameras **108A-N** at or near the checkout systems **106A-N**. The processor **628** can therefore quickly and accurately determine what item is being scanned by the customer and whether that item matches the scanned label. Such real-time determinations made at the edge can utilize less computational resources and avoid clogging network bandwidth, which can be beneficial to improve the computer system **102**'s ability to analyze the customer's activity and determine whether the activity is risky enough to warrant one or more human and/or automated responses.

(152) The communication interface **630** can be configured to provide communication over the network(s) **105** between the system components described herein.

(153) In some implementations, the checkout systems **106A-N** can also include light poles having cameras and/or lights attached thereto. The camera, for example, can face down over the flatbed of the respective checkout system **106A-N**. The camera can be a high resolution camera. In some implementations, the camera can have 1920×1080 resolution. The light can provide consistent lighting over the flatbed area. In some implementations, the light can also be activated as part of an automated system response when the customer is suspected of engaging in risky activity, such as paying for certain items and not paying for others during the checkout process. The camera can be configured to capture images of items as they are scanned by the scanning devices **622A-N**. These images can be used for identifying an item that the customer is purchasing in real-time to then determine, by the processor **628** and/or the computer system **102**, whether the customer is scanning and paying for all the items they are purchasing.

(154) The data store **600** can be any type of database, storage system, cloud-based storage, and/or memory for storing information about customers, information about stores, human responses, automated system responses, rules, watch lists, etc., as described further below.

(155) The computer system **102** can be any type of computing system, computing device, edge computing device, remote computing system, cloud-based system, and/or computer configured to perform the techniques described herein. The computer system **102** can include an activity profiler **602**, risk engine **604**, response friction level determiner **608**, response determiner **610**, output generator **612**, and communication interface **614**.

(156) The activity profiler **602** can be configured to receive data collected by the devices **106A-N**, **108A-N**, **110A-N**, **114A-N**, and/or **112A-N** and associate such data with a customer in the store. The activity profiler **602** can make the association using objective identifiers for the customer, as described herein. The associated activity (e.g., as shown in image data, transaction data, and other activity data described herein) can then be stored, in the data store **600**, as an activity profile **636A-N** for the customer. The activity profiler **602** can also be configured to retrieve (from the data store **600**) and apply one or more models **633A-N** to the data in the activity profile to identify a type of activity of the customer (e.g., shortage event, such as theft, safety/security event, etc.). For example, the models **633A-N** can be applied to image data in the profile to identify aggressive posturing of the customer and/or a weapon on the customer's body.

(157) The risk engine **604** can be configured to assess risk associated with the customer's activity in the activity profile. For example, the risk engine **604** can include an impact score determiner **616** and a confidence score determiner **618**. The impact score determiner **616** can be configured to determine a level of risk posed by the customer's activity, as described above in reference to FIGS. 4A-B. The confidence score determiner **618** can be configured to determine a likelihood or confidence that the customer's activity is risky/poses a threat to the store, as described above in reference to FIGS. 4A-B. The determiners **616** and **618** can generate the scores using scoring rules **634A-N** retrieved from the data store **600**. The rules **634A-N** can indicate ranges of values, values, and/or value scales that can be assigned to the customer's activity. The scores generated by the

determiners **616** and **618** can be stored in the activity profile **636A-N** of the customer in the data store **600**.

(158) The risk engine **604** can also use risk criteria **640A-N** corresponding to safety/security events and/or shortage events to determine a type of risk associated with the customer's activity. The determiners **616** and **618** can also use the risk criteria **640A-N** to determine a value for the impact score and/or confidence score assigned to the customer's activity. Moreover, in some implementations, the risk engine **604** can aggregate and/or weight the impact score and the confidence score to determine an overall risk score for the customer's activity. The overall risk score can then be used by the response friction level determiner **608** and/or the response determiner **610** to determine an appropriate response to the customer's activity.

(159) The response friction level determiner **608** can be configured to use the impact score, the confidence score, and/or the overall risk score to determine a response friction level for the customer's activity, as described further in reference to FIGS. **4A-B**. The determiner **608** can retrieve, from the data store **600**, friction level to response correlation rules **642A-N** to be used in determining the response friction level. In some implementations, the determiner **608** can also retrieve historic responses data from the activity profile **636A-N**. The historic responses data can be used to determine whether the customer has been resistant to responses in the past. If the customer has been resistant in the past, for example, the determiner **608** can generate a higher response friction level than if the customer had not been resistant in the past (or had not been responded to in the past). In some implementations, the determiner **608** can also retrieve watch lists **632A-N** for the store from the data store **600**. The determiner **608** can analyze the watch list **632A-N** to determine whether the customer has previously been added to the watch list **632A-N**. If the customer has been added to the watch list **632A-N** in the past, then the determiner **608** may generate a higher response friction level than if the customer had not been previously added to the watch list **632A-N**.

(160) The response determiner **610** can be configured to select a human response and/or automated system response based on at least the response friction level associated with the customer's activity in the activity profile **636A-N**. The determiner **610** can also determine the appropriate response based on the impact score, the confidence score, and/or the overall risk score attributed to the customer's activity by the risk engine **604**. The determiner **610** can also use the watch lists **632A-N** to determine the appropriate response. The determiner **610** can also retrieve or receive real-time information about available resources in the store (e.g., from a computing device in the store, from an employee device **104A-N**, from the data store **600**, etc.), which can be used to determine whether there are sufficient labor resources to execute a human responses or whether it would be preferred to save the labor resources and instead execute an automated system response. The determiner **610** can retrieve human responses **638A-N** and/or automated responses **644A-N** from the data store **600**. The determiner **610** can select any one or more of these retrieved responses as the appropriate response to the customer's activity. In some implementations, the determiner **610** can store the selected response in the corresponding activity profile **636A-N** in the data store **600**. The determiner **610** can also transmit the selected response to the output generator **612**. Refer to FIGS. **5A-B** for additional discussion about selecting the appropriate response.

(161) The output generator **612** can be configured to generate instructions for executing the selected response to the customer's activity. The generated instructions can then be transmitted, by the generator **612**, to one of the employee devices **104A-N** if the selected response is a human response. The generated instructions can also be transmitted to one of the checkout systems **106A-N** (or one or more other devices in the store) if the selected response is an automated system response. Refer to FIGS. **4A-B** for additional discussion about generating and transmitting the instructions for executing the response.

(162) Finally, the communication interface **614** can be configured to provide communication over the network(s) **105** between and amongst any of the system components described herein.

(163) FIG. **7** shows an example of a computing device **700** and an example of a mobile computing

device that can be used to implement the techniques described here. The computing device **700** is intended to represent various forms of digital computers, such as laptops, desktops, workstations, personal digital assistants, servers, blade servers, mainframes, and other appropriate computers. The mobile computing device is intended to represent various forms of mobile devices, such as personal digital assistants, cellular telephones, smart-phones, and other similar computing devices. The components shown here, their connections and relationships, and their functions, are meant to be exemplary only, and are not meant to limit implementations of the inventions described and/or claimed in this document.

(164) The computing device **700** includes a processor **702**, a memory **704**, a storage device **706**, a high-speed interface **708** connecting to the memory **704** and multiple high-speed expansion ports **710**, and a low-speed interface **712** connecting to a low-speed expansion port **714** and the storage device **706**. Each of the processor **702**, the memory **704**, the storage device **706**, the high-speed interface **708**, the high-speed expansion ports **710**, and the low-speed interface **712**, are interconnected using various busses, and can be mounted on a common motherboard or in other manners as appropriate. The processor **702** can process instructions for execution within the computing device **700**, including instructions stored in the memory **704** or on the storage device **706** to display graphical information for a GUI on an external input/output device, such as a display **716** coupled to the high-speed interface **708**. In other implementations, multiple processors and/or multiple buses can be used, as appropriate, along with multiple memories and types of memory. Also, multiple computing devices can be connected, with each device providing portions of the necessary operations (e.g., as a server bank, a group of blade servers, or a multi-processor system).

(165) The memory **704** stores information within the computing device **700**. In some implementations, the memory **704** is a volatile memory unit or units. In some implementations, the memory **704** is a non-volatile memory unit or units. The memory **704** can also be another form of computer-readable medium, such as a magnetic or optical disk.

(166) The storage device **706** is capable of providing mass storage for the computing device **700**. In some implementations, the storage device **706** can be or contain a computer-readable medium, such as a floppy disk device, a hard disk device, an optical disk device, or a tape device, a flash memory or other similar solid state memory device, or an array of devices, including devices in a storage area network or other configurations. A computer program product can be tangibly embodied in an information carrier. The computer program product can also contain instructions that, when executed, perform one or more methods, such as those described above. The computer program product can also be tangibly embodied in a computer- or machine-readable medium, such as the memory **704**, the storage device **706**, or memory on the processor **702**.

(167) The high-speed interface **708** manages bandwidth-intensive operations for the computing device **700**, while the low-speed interface **712** manages lower bandwidth-intensive operations. Such allocation of functions is exemplary only. In some implementations, the high-speed interface **708** is coupled to the memory **704**, the display **716** (e.g., through a graphics processor or accelerator), and to the high-speed expansion ports **710**, which can accept various expansion cards (not shown). In the implementation, the low-speed interface **712** is coupled to the storage device **706** and the low-speed expansion port **714**. The low-speed expansion port **714**, which can include various communication ports (e.g., USB, Bluetooth, Ethernet, wireless Ethernet) can be coupled to one or more input/output devices, such as a keyboard, a pointing device, a scanner, or a networking device such as a switch or router, e.g., through a network adapter.

(168) The computing device **700** can be implemented in a number of different forms, as shown in the figure. For example, it can be implemented as a standard server **720**, or multiple times in a group of such servers. In addition, it can be implemented in a personal computer such as a laptop computer **722**. It can also be implemented as part of a rack server system **724**. Alternatively, components from the computing device **700** can be combined with other components in a mobile device (not shown), such as a mobile computing device **750**. Each of such devices can contain one

or more of the computing device **700** and the mobile computing device **750**, and an entire system can be made up of multiple computing devices communicating with each other.

(169) The mobile computing device **750** includes a processor **752**, a memory **764**, an input/output device such as a display **754**, a communication interface **766**, and a transceiver **768**, among other components. The mobile computing device **750** can also be provided with a storage device, such as a micro-drive or other device, to provide additional storage. Each of the processor **752**, the memory **764**, the display **754**, the communication interface **766**, and the transceiver **768**, are interconnected using various buses, and several of the components can be mounted on a common motherboard or in other manners as appropriate.

(170) The processor **752** can execute instructions within the mobile computing device **750**, including instructions stored in the memory **764**. The processor **752** can be implemented as a chipset of chips that include separate and multiple analog and digital processors. The processor **752** can provide, for example, for coordination of the other components of the mobile computing device **750**, such as control of user interfaces, applications run by the mobile computing device **750**, and wireless communication by the mobile computing device **750**.

(171) The processor **752** can communicate with a user through a control interface **758** and a display interface **756** coupled to the display **754**. The display **754** can be, for example, a TFT (Thin-Film-Transistor Liquid Crystal Display) display or an OLED (Organic Light Emitting Diode) display, or other appropriate display technology. The display interface **756** can comprise appropriate circuitry for driving the display **754** to present graphical and other information to a user. The control interface **758** can receive commands from a user and convert them for submission to the processor **752**. In addition, an external interface **762** can provide communication with the processor **752**, so as to enable near area communication of the mobile computing device **750** with other devices. The external interface **762** can provide, for example, for wired communication in some implementations, or for wireless communication in other implementations, and multiple interfaces can also be used.

(172) The memory **764** stores information within the mobile computing device **750**. The memory **764** can be implemented as one or more of a computer-readable medium or media, a volatile memory unit or units, or a non-volatile memory unit or units. An expansion memory **774** can also be provided and connected to the mobile computing device **750** through an expansion interface **772**, which can include, for example, a SIMM (Single In Line Memory Module) card interface. The expansion memory **774** can provide extra storage space for the mobile computing device **750**, or can also store applications or other information for the mobile computing device **750**. Specifically, the expansion memory **774** can include instructions to carry out or supplement the processes described above, and can include secure information also. Thus, for example, the expansion memory **774** can be provide as a security module for the mobile computing device **750**, and can be programmed with instructions that permit secure use of the mobile computing device **750**. In addition, secure applications can be provided via the SIMM cards, along with additional information, such as placing identifying information on the SIMM card in a non-hackable manner.

(173) The memory can include, for example, flash memory and/or NVRAM memory (non-volatile random access memory), as discussed below. In some implementations, a computer program product is tangibly embodied in an information carrier. The computer program product contains instructions that, when executed, perform one or more methods, such as those described above. The computer program product can be a computer- or machine-readable medium, such as the memory **764**, the expansion memory **774**, or memory on the processor **752**. In some implementations, the computer program product can be received in a propagated signal, for example, over the transceiver **768** or the external interface **762**.

(174) The mobile computing device **750** can communicate wirelessly through the communication interface **766**, which can include digital signal processing circuitry where necessary. The communication interface **766** can provide for communications under various modes or protocols,

such as GSM voice calls (Global System for Mobile communications), SMS (Short Message Service), EMS (Enhanced Messaging Service), or MMS messaging (Multimedia Messaging Service), CDMA (code division multiple access), TDMA (time division multiple access), PDC (Personal Digital Cellular), WCDMA (Wideband Code Division Multiple Access), CDMA2000, or GPRS (General Packet Radio Service), among others. Such communication can occur, for example, through the transceiver **768** using a radio-frequency. In addition, short-range communication can occur, such as using a Bluetooth, WiFi, or other such transceiver (not shown). In addition, a GPS (Global Positioning System) receiver module **770** can provide additional navigation- and location-related wireless data to the mobile computing device **750**, which can be used as appropriate by applications running on the mobile computing device **750**.

(175) The mobile computing device **750** can also communicate audibly using an audio codec **760**, which can receive spoken information from a user and convert it to usable digital information. The audio codec **760** can likewise generate audible sound for a user, such as through a speaker, e.g., in a handset of the mobile computing device **750**. Such sound can include sound from voice telephone calls, can include recorded sound (e.g., voice messages, music files, etc.) and can also include sound generated by applications operating on the mobile computing device **750**.

(176) The mobile computing device **750** can be implemented in a number of different forms, as shown in the figure. For example, it can be implemented as a cellular telephone **780**. It can also be implemented as part of a smart-phone **782**, personal digital assistant, or other similar mobile device.

(177) Various implementations of the systems and techniques described here can be realized in digital electronic circuitry, integrated circuitry, specially designed ASICs (application specific integrated circuits), computer hardware, firmware, software, and/or combinations thereof. These various implementations can include implementation in one or more computer programs that are executable and/or interpretable on a programmable system including at least one programmable processor, which can be special or general purpose, coupled to receive data and instructions from, and to transmit data and instructions to, a storage system, at least one input device, and at least one output device.

(178) These computer programs (also known as programs, software, software applications or code) include machine instructions for a programmable processor, and can be implemented in a high-level procedural and/or object-oriented programming language, and/or in assembly/machine language. As used herein, the terms machine-readable medium and computer-readable medium refer to any computer program product, apparatus and/or device (e.g., magnetic discs, optical disks, memory, Programmable Logic Devices (PLDs)) used to provide machine instructions and/or data to a programmable processor, including a machine-readable medium that receives machine instructions as a machine-readable signal. The term machine-readable signal refers to any signal used to provide machine instructions and/or data to a programmable processor.

(179) To provide for interaction with a user, the systems and techniques described here can be implemented on a computer having a display device (e.g., a CRT (cathode ray tube) or LCD (liquid crystal display) monitor) for displaying information to the user and a keyboard and a pointing device (e.g., a mouse or a trackball) by which the user can provide input to the computer. Other kinds of devices can be used to provide for interaction with a user as well; for example, feedback provided to the user can be any form of sensory feedback (e.g., visual feedback, auditory feedback, or tactile feedback); and input from the user can be received in any form, including acoustic, speech, or tactile input.

(180) The systems and techniques described here can be implemented in a computing system that includes a back end component (e.g., as a data server), or that includes a middleware component (e.g., an application server), or that includes a front end component (e.g., a client computer having a graphical user interface or a Web browser through which a user can interact with an implementation of the systems and techniques described here), or any combination of such back

end, middleware, or front end components. The components of the system can be interconnected by any form or medium of digital data communication (e.g., a communication network). Examples of communication networks include a local area network (LAN), a wide area network (WAN), and the Internet.

(181) The computing system can include clients and servers. A client and server are generally remote from each other and typically interact through a communication network. The relationship of client and server arises by virtue of computer programs running on the respective computers and having a client-server relationship to each other.

(182) While this specification contains many specific implementation details, these should not be construed as limitations on the scope of the disclosed technology or of what may be claimed, but rather as descriptions of features that may be specific to particular embodiments of particular disclosed technologies. Certain features that are described in this specification in the context of separate embodiments can also be implemented in combination in a single embodiment in part or in whole. Conversely, various features that are described in the context of a single embodiment can also be implemented in multiple embodiments separately or in any suitable subcombination. Moreover, although features may be described herein as acting in certain combinations and/or initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination may be directed to a subcombination or variation of a subcombination. Similarly, while operations may be described in a particular order, this should not be understood as requiring that such operations be performed in the particular order or in sequential order, or that all operations be performed, to achieve desirable results. Particular embodiments of the subject matter have been described. Other embodiments are within the scope of the following claims.

Claims

1. A system for automatically detecting and responding to potentially suspicious or risky activity in a retail environment, the system comprising: one or more monitoring devices positioned throughout the retail environment that are configured to generate a stream of activity data detailing activity within the retail environment, wherein the stream of activity data includes unstructured data; a point of sale (POS) terminal that includes at least (i) a scanner configured to scan item identifiers during a checkout process, (ii) a display device configured to display information during the checkout process, and (iii) a payment terminal configured to receive and process payment information during the checkout process; a plurality of mobile devices that are associated with employees within the retail environment, each of the plurality of mobile devices including at least (i) a wireless transceiver configured to wirelessly transmit and receive information, (ii) a user interface configured to output information to and to receive input from a corresponding user, and (iii) an indoor location module configured to determine and transmit location information; a computer system in communication with the one or more monitoring devices, the point of sale terminal, and the plurality of mobile devices, wherein the computer system is configured to perform operations comprising: receiving, from the one or more monitoring devices, the stream of activity data; applying a model to the stream of activity data to identify a portion of the stream of activity data corresponding to activity of a guest during the checkout process, the model being trained to identify features in the portion of the stream of activity data indicative of a risk event; identifying, based on the portion of the stream of activity data, whether a risk event is associated with the activity of the guest during the checkout process; determining a risk impact score for the guest based on a determination that the risk event is associated with the activity of the guest; determining a risk confidence score for the guest, wherein the risk confidence score indicates a likelihood that the activity of the guest is associated with the risk event; generating a response friction level for the activity of the guest based on determining whether at least one of the impact

score and the confidence score satisfy risk criteria, wherein the response friction level corresponds to an escalation of a type of response to be taken for the activity of the guest; selecting (i) a particular manual response from among a plurality of candidate manual responses to the activity of the guest and (ii) a particular automated response from among a plurality of candidate automated responses to the activity of the guest based, at least in part, on the response friction level satisfying at least one of manual response criteria and automated response criteria; transmitting instructions to the POS terminal to implement the particular automated response, wherein transmitting the instructions causes the particular automated response to be provided using one or more of the scanner, the display device, and the payment terminal; selecting one or more mobile devices from among the plurality of mobile devices based, at least in part, on the location information for the mobile devices relative to a location of the POS terminal; and transmitting instructions to implement the particular manual response to the selected one or more mobile devices, wherein transmitting the instructions causes corresponding instructions to be outputted in the user interface at the selected one or more mobile devices to prompt corresponding employees to perform the manual response with regard to the guest at the POS terminal.

2. The system of claim 1, wherein the risk event is a shortage event or a security event, wherein the shortage event includes at least one of theft, shoplifting, ticket switching, and sweethearting, and wherein the security event includes at least one of bodily harm, physical threat, verbal threat, terror, aggression, carrying a weapon in the retail environment, and assault.

3. The system of claim 1, wherein the one or more monitoring devices comprises a camera configured to generate the stream of activity data that includes at least one of image data or video data.

4. The system of claim 1, wherein the one or more monitoring devices comprises the POS terminal, wherein the POS terminal is configured to generate the stream of activity data that includes transaction data during the checkout process.

5. The system of claim 1, wherein the one or more monitoring devices comprises a location-based signaling device that is configured to generate the stream of activity data that includes location-based data of at least one of (i) a mobile device of the guest as the guest moves throughout the retail environment and (ii) a shopping cart that the guest pushes throughout the retail environment.

6. The system of claim 1, wherein the stream of activity data includes system-based inferences, wherein the POS terminal is configured to generate a system-based inference indicating that the guest likely performed ticket switching based on identifying, by the POS terminal and during the checkout process, a mismatch between an item identifier that the guest scanned with the scanning device and an item imaged during the checkout process.

7. The system of claim 1, wherein the operations further comprise identifying and associating a portion of the stream of activity data with a guest currently using the POS terminal during the checkout process.

8. The system of claim 1, wherein: selecting the particular manual response from among the plurality of candidate manual responses to the activity of the guest comprises selecting the manual response based on at least one of (i) the manual response being an expected response to the activity of the guest, (ii) the response friction level exceeding a threshold friction value, and (iii) labor resources in the retail environment satisfying a threshold labor availability condition to provide for manual response to the activity of the guest, and selecting the particular automated response from among the plurality of candidate automated responses to the activity of the guest comprises selecting the automated response based on at least one of (i) the automated response being an expected response to the activity of the guest, (ii) the response friction level being less than a threshold friction value, and (iii) labor resources in the retail environment not satisfying a threshold labor availability condition to provide for a manual response the activity of the guest.

9. The system of claim 1, wherein selecting the particular manual response from among the plurality of candidate manual responses to the activity of the guest comprises selecting at least one

of: (i) instructions, based on the response friction level being within a first range of friction values, that, when outputted at the selected one or more mobile devices, prompt the corresponding employees to let the activity of the guest pass, (ii) instructions, based on the response friction level being within a second range of friction values greater than the first range of friction values, that, when outputted at the selected one or more mobile devices, prompt the corresponding employees to observe the guest, (iii) instructions, based on the response friction level being within a third range of friction values greater than the first and second ranges of friction values, that, when outputted at the selected one or more mobile devices, prompt the corresponding employees to approach the guest at the POS terminal and provide assistance during the checkout process, (iv) instructions, based on the response friction level being within a fourth range of friction values greater than the first, second, and third ranges of friction values, that, when outputted at the selected one or more mobile devices, prompt the corresponding employees to investigate the activity, (v) instructions, based on the response friction level being within a fifth range of friction values greater than the first, second, third, and fourth ranges of friction values, that, when outputted at the selected one or more mobile devices, prompt the corresponding employees to approach the guest and perform a receipt check before the guest exits the retail environment, and (vi) instructions, based on the response friction level being within a sixth range of friction values greater than the first, second, third, fourth, and fifth ranges of friction values, that, when outputted at the selected one or more mobile devices, prompt the corresponding employees to approach and apprehend the guest.

10. The system of claim 1, wherein selecting the particular automated response from among the plurality of candidate automated responses to the activity of the guest comprises selecting at least one of: (i) instructions, based on the response friction level being within a first range of friction values, that, when executed by the POS terminal, cause the POS terminal to perform no action and let the activity pass, (ii) instructions, based on the response friction level being within a second range of friction values greater than the first range of friction values, that, when executed by the POS terminal, cause the POS terminal to present, at the display device, checkout tips to guide the guest through the checkout process, (iii) instructions, based on the response friction level being within a third range of friction values greater than the first and second ranges of friction values, that, when executed by the POS terminal, cause the POS terminal to actuate a lane light at the POS terminal, wherein actuating the lane light causes the lane light to flash, (iv) instructions, based on the response friction level being within a fourth range of friction values greater than the first, second, and third ranges of friction values, that, when executed by the POS terminal, cause the POS terminal to automate, at at least one of the display device and the payment terminal, a charge to a transaction of the guest, (v) instructions, based on the response friction level being within a fifth range of friction values greater than the first, second, third, and fourth ranges of friction values, that, when executed by the POS terminal, cause the POS terminal to generate an alert that is transmitted to a mobile device of security personnel in the retail environment, and (vi) instructions, based on the response friction level being within a sixth range of friction values greater than the first, second, third, fourth, and fifth ranges of friction values, that, when executed by the POS terminal, cause the POS terminal to prevent the guest from (a) continuing to scan items with the scanner, (b) continuing the checkout process through the display device, or (c) completing the checkout process through the payment terminal.

11. The system of claim 1, wherein the operations further comprise: determining, based on execution of the selected (i) particular manual response and (ii) particular automated response and the stream of activity data received from the one or more monitoring devices, that the guest continues to perform the activity; adjusting, based on the determination that the guest continues to perform the activity, at least one of the risk impact score and the risk confidence score by a predetermined amount; increasing, based on the adjusted at least one risk impact score and risk confidence score, the response friction level; and selecting at least one of another manual response from among the plurality of candidate manual responses and another automated response from

among the plurality of candidate automated responses based on the increased response friction level, wherein the selected another manual response or another automated response is an escalation of the previously selected particular manual response or the particular automated response.

12. The system of claim 1, wherein determining a risk impact score for the guest comprises: determining, based on transaction data received from the POS terminal during the checkout process, a value of an item associated with the activity of the guest; and assigning the risk impact score above a threshold impact value based on the value of the item exceeding a threshold item cost value.

13. The system of claim 1, wherein determining a risk impact score for the guest comprises: identifying, based on applying the model to the stream of activity data, a safety threat in the activity of the guest; and assigning the risk impact score above a threshold impact value based on the identified safety threat satisfying safety risk criteria.

14. The system of claim 1, wherein determining a risk confidence score for the guest comprises: analyzing, based on applying the model to the stream of activity data, the portion of the stream of activity data to identify a weapon, wherein the portion of the stream of activity data is image data; and assigning the risk confidence score above a threshold confidence value based on the identification of the weapon.

15. The system of claim 1, wherein determining whether at least one of the impact score and the confidence score satisfy risk criteria comprises (i) determining that at least one of the impact score and the confidence score exceed a safety risk threshold value or (ii) determining that at least one of the impact score and the confidence score exceed a shortage risk threshold value.

16. The system of claim 1, wherein determining whether at least one of the impact score and the confidence score satisfy risk criteria comprises: aggregating the impact score and the confidence score to generate a general risk score for the guest; and determining that the risk criteria is satisfied based on a determination that the general risk score exceeds a general risk threshold value.

17. The system of claim 1, wherein generating a response friction level for the activity of the guest comprises assigning a value to the response friction level that is (i) above a threshold friction value based on at least one of the impact score and the confidence score satisfying the risk criteria or (ii) below the threshold friction value based on at least one of the impact score and the confidence score not satisfying the risk criteria.

18. The system of claim 1, selecting (i) a particular manual response from among a plurality of candidate manual responses to the activity of the guest and (ii) a particular automated response from among a plurality of candidate automated responses to the activity of the guest comprises: retrieving, from a data store, a watch list for the retail environment; determining whether an objective identifier associated with the guest appears on the watch list; and selecting at least one of (i) and (ii) based on a determination that the objective identifier associated with the guest appears on the watch list.

19. A method for automatically detecting and responding to potentially suspicious or risky activity in a retail environment, the method comprising: receiving, from one or more monitoring devices positioned throughout a retail environment, a stream of activity data detailing activity within the retail environment; applying a model to the stream of activity data to identify a portion of the stream of activity data corresponding to activity of a guest during a checkout process, wherein the model was trained to identify features in the portion of the stream of activity data indicative of a risk event; identifying, based on the portion of the stream of activity data, whether a risk event is associated with the activity of the guest during the checkout process; determining a risk impact score for the guest based on at least one of (i) a determination that the risk event is associated with the activity of the guest and (ii) the activity of the guest satisfying risk impact criteria; selecting (i) a particular manual response from among a plurality of candidate manual responses to the activity of the guest and (ii) a particular automated response from among a plurality of candidate automated responses to the activity of the guest based, at least in part, on the risk impact score satisfying at

least one of manual response criteria and automated response criteria; transmitting instructions to a POS terminal to implement the particular automated response, wherein transmitting the instructions causes the particular automated response to be provided using one or more of a scanner, a display device, and a payment terminal of the POS terminal; selecting one or more mobile devices from among a plurality of mobile devices based, at least in part, on location information for the mobile devices relative to a location of the POS terminal; and transmitting instructions to implement the particular manual response to the selected one or more mobile devices, wherein transmitting the instructions causes corresponding instructions to be outputted in a user interface at the selected one or more mobile devices to prompt corresponding employees to perform the manual response with regard to the guest at the POS terminal.

20. The method of claim 19, further comprising: determining a risk confidence score for the guest, wherein the risk confidence score indicates a likelihood that the activity of the guest is associated with the risk event; generating a response friction level for the activity of the guest based on determining whether at least one of the impact score and the confidence score satisfy risk criteria, wherein the response friction level corresponds to an escalation of a type of response to be taken for the activity of the guest; and selecting (i) the particular manual response from among the plurality of candidate manual responses to the activity of the guest and (ii) the particular automated response from among the plurality of candidate automated responses to the activity of the guest based, at least in part, on the response friction level satisfying at least one of the manual response criteria and the automated response criteria.
