

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12401109
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Chien; Heng-Chieh et al.

Antenna-in-package with heat dissipation structure

Abstract

An antenna-in-package with a heat dissipation structure includes a circuit board, an antenna substrate, a chip, a plurality of heat dissipation fins, a chassis, and dielectric fluid. The circuit board has a first surface and a second surface opposite to the first surface. The antenna substrate is disposed above the first surface of the circuit board. The chip is disposed between the antenna substrate and the first surface of the circuit board and is electrically connected to the antenna substrate. The plurality of heat dissipation fins protrude from the second surface of the circuit board. The chassis encapsulates the circuit board, the antenna substrate, the chip, and the plurality of heat dissipation fins. The dielectric fluid circulates and flows in the chassis through a cooling circulation device and is in direct contact with the plurality of heat dissipation fins.

Inventors: Chien; Heng-Chieh (New Taipei, TW), Yang; Shu-Jung (New Taipei, TW), Lo; Feng-Hsiang (Hsinchu County, TW), Chao; Yu-Lin (Hsinchu, TW)

Applicant: Industrial Technology Research Institute (Hsinchu, TW)

Family ID: 1000008782791

Assignee: Industrial Technology Research Institute (Hsinchu, TW)

Appl. No.: 18/474239

Filed: September 26, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250105486 A1	Mar. 27, 2025

Publication Classification

Int. Cl.: H01Q1/02 (20060101); H01Q9/04 (20060101); H01Q1/22 (20060101)

U.S. Cl.:

CPC **H01Q1/02** (20130101); **H01Q9/0407** (20130101); H01Q1/2283 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11482472	12/2021	Eid et al.	N/A	N/A
2018/0198290	12/2017	Rohera	N/A	H02J 1/108
2022/0273303	12/2021	Creamer	N/A	G16H 20/40
2022/0399249	12/2021	Dogiamis et al.	N/A	N/A
2024/0178163	12/2023	Tang	N/A	H01Q 13/106
2024/0222874	12/2023	Tai	N/A	H01Q 25/001

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
215579018	12/2021	CN	N/A
115810594	12/2022	CN	N/A
200425430	12/2003	TW	N/A
201926796	12/2018	TW	N/A
I672864	12/2018	TW	N/A

OTHER PUBLICATIONS

Xiaoxiong Gu et al., “Packaging and Antenna Integration for Silicon-Based Millimeter-Wave Phased Arrays: 5G and Beyond”, IEEE Journal of Microwaves, Jan. 7, 2021, pp. 123-134, vol. 1, No. 1. cited by applicant

Xiaoxiong Gu et al., “Electrical, Mechanical, and Thermal Co-Design”, Antenna-in-Package Technology and Applications, First Edition, 2020, pp. 89-113. cited by applicant

Primary Examiner: Lee; Wilson

Attorney, Agent or Firm: JCIPRNET

Background/Summary

TECHNICAL FIELD

(1) The disclosure relates to a package structure, and in particular, relates to an antenna-in-package with a heat dissipation structure.

BACKGROUND

(2) With the development of the 5G communication industry and low-orbit satellite applications, the introduction of high-power chips and the miniaturization trend of chips will cause the temperature of the antenna-in-package module to increase. Generally speaking, antenna-in-package modules transfer the heat generated by the chip to the air through thermal diffusion elements.

However, due to the module structure, the air flow within the module is poor, making it difficult to dissipate heat such that the energy conversion efficiency of the chip is reduced and the system energy consumption is increased. Therefore, how to improve the heat dissipation efficiency of the antenna-in-package module is an urgent problem that needs to be solved.

SUMMARY

(3) The disclosure provides an antenna-in-package with a heat dissipation structure having a favorable heat dissipation capability to improve the reliability of the antenna-in-package with the heat dissipation structure.

(4) An antenna-in-package with a heat dissipation structure according to an embodiment of the disclosure includes a circuit board, an antenna substrate, a chip, a plurality of heat dissipation fins, a chassis, and dielectric fluid. The circuit board has a first surface and a second surface opposite to the first surface. The antenna substrate is disposed above the first surface of the circuit board. The chip is disposed between the antenna substrate and the first surface of the circuit board and electrically connected to the antenna substrate. The plurality of heat dissipation fins protrude from the second surface of the circuit board. The chassis encapsulates the circuit board, the antenna substrate, the chip, and the plurality of heat dissipation fins. The dielectric fluid circulates and flows in the chassis through a cooling circulation device and is in direct contact with the plurality of heat dissipation fins.

(5) An antenna-in-package with a heat dissipation structure according to another embodiment of the disclosure includes a circuit board, an antenna substrate, a chip, a chassis, and dielectric fluid. The circuit board has a first surface and a second surface opposite to the first surface. The antenna substrate is disposed above the first surface of the circuit board. The antenna substrate includes an antenna layer disposed on a surface of the antenna substrate. The chip is disposed between the antenna substrate and the first surface of the circuit board and electrically connected to the antenna substrate. The chassis encapsulates the circuit board, the antenna substrate, and the chip. The dielectric fluid circulates and flows in the chassis through a cooling circulation device and is in direct contact with the antenna layer.

(6) An antenna-in-package with a heat dissipation structure according to another embodiment of the disclosure includes a chassis, a circuit board, an antenna substrate, a chip, a heat dissipation fin, and cooling fluid. The chassis includes a first space and a second space. The first space and the second space are isolated from each other by a heat dissipation plate. The circuit board is located in the first space and disposed on the heat dissipation plate. The antenna substrate is located in the first space and disposed above the circuit board. The chip is disposed between the antenna substrate and the circuit board and electrically connected to the antenna substrate. The heat dissipation fin is located in the second space and disposed on the heat dissipation plate. The cooling fluid is located in the second space and in contact with the heat dissipation fin. The cooling fluid absorbs heat from the heat dissipation fin to create a phase change.

(7) Based on the above, the antenna-in-package with the heat dissipation structure of the disclosure improves the heat dissipation efficiency thereof through the provision of the dielectric fluid or the cooling fluid, so that the antenna-in-package with the heat dissipation structure is adapted to be applied in the 5G communication industry and low-orbit satellite ground stations.

(8) In order to make the above-mentioned features and advantages of the disclosure clearer and easier to understand, the following embodiments are given and described in details with accompanying drawings as follows.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1A is a schematic cross-sectional view of an antenna-in-package with a heat dissipation

structure according to an embodiment of the disclosure.

(2) FIG. 1B is a partially enlarged schematic cross-sectional view of an embodiment of the antenna-in-package with the heat dissipation structure of FIG. 1A.

(3) FIG. 1C is a partially enlarged schematic cross-sectional view of another embodiment of the antenna-in-package with the heat dissipation structure of FIG. 1A.

(4) FIG. 1D is a partially enlarged schematic cross-sectional view of another embodiment of the antenna-in-package with the heat dissipation structure of FIG. 1A.

(5) FIG. 2 is a schematic cross-sectional view of an antenna-in-package with a heat dissipation structure according to another embodiment of the disclosure.

(6) FIG. 3 is a schematic cross-sectional view of an antenna-in-package with a heat dissipation structure according to another embodiment of the disclosure.

(7) FIG. 4 is a schematic cross-sectional view of an antenna-in-package with a heat dissipation structure according to another embodiment of the disclosure.

(8) FIG. 5 is a schematic cross-sectional view of an antenna-in-package with a heat dissipation structure according to another embodiment of the disclosure.

(9) FIG. 6 is a schematic cross-sectional view of an antenna-in-package with a heat dissipation structure according to another embodiment of the disclosure.

(10) FIG. 7 is a schematic cross-sectional view of an antenna-in-package with a heat dissipation structure according to another embodiment of the disclosure.

(11) FIG. 8 is a schematic cross-sectional view of an antenna-in-package with a heat dissipation structure according to another embodiment of the disclosure.

(12) FIG. 9 is a schematic cross-sectional view of an antenna-in-package with a heat dissipation structure according to another embodiment of the disclosure.

DETAILED DESCRIPTION OF DISCLOSED EMBODIMENTS

(13) Illustrative embodiments of the disclosure will be fully described below with reference to the drawings, but the disclosure may also be embodied in many different forms and should not be construed as being limited to the embodiments described herein. In the drawings, for clarity's sake, the size and thickness of various regions, parts, and layers may not be drawn to scale.

(14) Directional terms, such as “upper”, “lower”, “front”, “back”, “left”, “right”, etc., mentioned in the disclosure are only directions with reference to the drawings. Therefore, the used directional terms are used to illustrate, but not to limit, the disclosure.

(15) In the following embodiments, the same or similar elements are denoted by the same or similar referential numerals, and descriptions of the same technical contents are omitted. Moreover, the features in the different exemplary embodiments may be combined with each other in case of no confliction, and the simple equivalent changes and modifications made in accordance with the scope of the specification or the claims are still within the scope of the patent.

(16) It should be noted that although the terms “first,” “second,” “third,” etc. may be used herein for describing various elements, components, regions, layers, and/or portions, the elements, components, regions, and/or portions are not limited by these terms. These terms are used for separating one element, component, region, layer, or portion from another element, component, region, layer, or portion. Thus, the first element, component, region, layer, or portion discussed below may also be referred to as the second element, component, region, layer, or portion without departing from the scope of the invention.

(17) FIG. 1A is a schematic cross-sectional view of an antenna-in-package with a heat dissipation structure according to an embodiment of the disclosure. FIG. 1B is a partially enlarged schematic cross-sectional view of an embodiment of the region R of FIG. 1A. FIG. 1C is a partially enlarged schematic cross-sectional view of another embodiment of the region R of FIG. 1A. FIG. 1D is a partially enlarged schematic cross-sectional view of another embodiment of the region R of FIG. 1A.

(18) Referring to FIG. 1A, an antenna-in-package with a heat dissipation structure 10 includes a

circuit board **100**, an antenna substrate **110**, a chip **120**, a plurality of heat dissipation fins **130**, a chassis **140**, and a dielectric fluid **150**. The circuit board **100** has a first surface **100a** and a second surface **100b** opposite to the first surface **100a**. The antenna substrate **110** is disposed above the first surface **100a** of the circuit board **100**. The chip **120** is disposed between the antenna substrate **110** and the first surface **100a** of the circuit board **100** and is electrically connected to the antenna substrate **110**. The plurality of heat dissipation fins **130** protrude from the second surface **100b** of the circuit board **100**. The chassis **140** encapsulates the circuit board **100**, the antenna substrate **110**, the chip **120**, and the heat dissipation fins **130**. The dielectric fluid **150** circulates and flows in the chassis **140** through a cooling circulation device **160** and is in direct contact with the plurality of heat dissipation fins **130**.

(19) The detailed structures of the circuit board **100** and the antenna substrate **110** are omitted in FIG. **1A**. However, the circuit board **100** and the antenna substrate **110** may include structures such as conductive lines, insulating layers, via holes, active/passive components, etc., and the wiring design thereof may be based on actual requirements, and the disclosure is not limited thereto.

(20) The circuit board **100** may be electrically connected to the antenna substrate **110** through a conductive connecting member **170**. In some embodiments, the conductive connecting member **170** may be a solder ball, a conductive pillar, a conductive bump, or a similar conductive connecting member, but the disclosure is not limited thereto.

(21) The antenna substrate **110** has an upper surface **110a** and a lower surface **110b** that are opposite to each other, and the lower surface **110b** faces the first surface **100a** of the circuit board **100**. The antenna substrate **110** includes an antenna layer **112**, which is disposed on the upper surface **110a** of the antenna substrate **110**.

(22) The chip **120** is, for example, a radio frequency chip (RF IC), which includes a front surface **120a** and a back surface **120b** that are opposite to each other. The front surface **120a** of the chip **120** faces the lower surface **110b** of the antenna substrate **110** and may be electrically connected to the antenna substrate **110** through, for example, solder balls or other conductive structures.

(23) In some embodiments, the chassis **140** includes at least one inlet portion IN and at least one outlet portion OUT serving as an inlet and outlet for the dielectric fluid **150** to enter and exit the inside and outside of the chassis **140**. In FIG. **1A**, an inlet portion IN and an outlet portion OUT are schematically shown at the lower part of the chassis **140**, but the disclosure is not limited thereto. The number and position of the inlet portion and the outlet portion of the chassis **140** may be adjusted according to actual requirements.

(24) In some embodiments, the cooling circulation device **160** includes a pump **162** and a heat exchanger (fin, heat sink, etc.) **164** that are disposed on the outside of the chassis **140**. The dielectric fluid **150** may be drawn out from the at least one outlet portion OUT of the chassis **140** by the pump **162** and passed through the heat exchanger **164** so as to dissipate the heat of the dielectric fluid **150** to the outside, and the dielectric fluid **150** flowing through the heat exchanger **164** is then returned to the inside of the chassis **140** through the at least one inlet portion IN. Such a cyclic operation may improve the heat dissipation efficiency.

(25) The outlet portion OUT of the chassis **140** and the pump **162**, the pump **162** and the heat exchanger **164**, and the heat exchanger **164** and the inlet portion IN may be connected through pipes (not shown) to serve as channels for the dielectric fluid **150** to flow. In some embodiments, the heat exchanger **164** may be a fin heat sink or other suitable heat sinks, but the disclosure is not limited thereto.

(26) In some embodiments, the antenna-in-package with the heat dissipation structure **10** further includes a heat dissipation plate **132**, which is disposed on the second surface **100b** of the circuit board **100**, and the heat dissipation fins **130** are disposed on the heat dissipation plate **132**. In this way, the heat of the circuit board **100** may be dissipated through the heat dissipation plate **132** and the heat dissipation fins **130**. Then, through the dielectric fluid **150** being in direct contact with and the heat dissipation plate **132** and/or the heat dissipation fins **130**, the heat energy thereof may be

taken away and dissipated to the outside of the chassis **140** through the cooling circulation device **160**.

(27) In some embodiments, the surface of the heat dissipation plate **132** in contact with the dielectric fluid **150** may have a plurality of micro-bumps or micro-dimples (not shown) to increase the disturbance of the dielectric fluid **150** in the chassis **140**.

(28) In some embodiments, the circuit board **100** has a plurality of through holes TH, which are disposed corresponding to the chip **120**.

(29) In some embodiments, the antenna-in-package with the heat dissipation structure **10** further includes a heat dissipation block (heat slug) **134** disposed on the heat dissipation plate **132** and disposed in the through hole TH. In some embodiments, the heat dissipation block **134** penetrates the circuit board **100** and is in direct contact with the back surface **120b** of the chip **120**. In this way, the heat dissipation block **134** may conduct the heat generated by the chip **120** to the heat dissipation plate **132** and the heat dissipation fins **130**, and then dissipate the heat energy to the outside of the chassis **140** through the dielectric fluid **150**. However, the disclosure is not limited thereto. In other embodiments, a vapor chamber (not shown) or a thermal interface material (not shown) may be included between the chip **120** and the heat dissipation block **134** to enhance the heat dissipation effect of the chip **120**.

(30) FIG. 1A schematically shows that the heat dissipation fins and the heat dissipation blocks are disposed correspondingly, but it is not intended to limit the disclosure. The number and position of the heat dissipation fins may be adjusted according to actual requirements.

(31) In some embodiments, the antenna-in-package with the heat dissipation structure **10** further includes a baffle **141**, which is disposed on an inner surface of the chassis **140**, and the circuit board **100** is fixedly disposed on the baffle **141**. In this way, the circuit board **100**, the baffle **141**, and the heat dissipation plate **132** may divide the chassis **140** into a first space S11 and a second space S12. The first space S11 includes the circuit board **100**, the antenna substrate **110**, and the chip **120** disposed therein, and the second space S12 includes the heat dissipation plate **132** and the heat dissipation fins **130** disposed therein. In some embodiments, the dielectric fluid **150** flows in the second space S12 to contact the heat dissipation fins **130**. In other words, the dielectric fluid **150** is not in direct contact with the antenna substrate **110** and the chip **120**.

(32) In some embodiments, the dielectric fluid **150** may include a non-conductive fluid such as silicone oil, mineral oil, or fluorinated liquid. Fluorinated liquid may refer to fluorine-containing alkanes, ethers, or ketone liquids. For example, the fluorinated liquid may be selected from the group consisting of methyl perfluoropropane ether, methyl nonafluoroisobutyl ether, and methyl nonafluorobutyl ether, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-pentane, 1,1,1,2,2,4,5,5,5-nonafluoro-4-(trifluoromethyl)-3-pentanone and combinations thereof.

(33) In some embodiments, the materials of the heat dissipation fins **130**, the heat dissipation plate **132**, and the heat dissipation block **134** may be copper, aluminum, or other suitable thermally conductive materials.

(34) FIG. 1B to FIG. 1D show some embodiments of the heat dissipation fins **130**. In some embodiments, as shown in FIG. 1B, the heat dissipation fin **130** may include a first portion **130a**, a second portion **130b**, and a third portion **130c**. The first portion **130a** is in direct contact with the heat dissipation plate **132**. The second portion **130b** is located on a side wall of the first portion **130a**. The third portion **130c** is located on a bottom surface of the first portion **130a**. The porosity of the third portion **130c** is greater than the porosity of the second portion **130b**. For example, the second portion **130b** and the third portion **130c** may be metal materials with holes, such as foamed metals. The second portion **130b** may be a foamed metal with dense holes for increasing the contact area with the dielectric fluid so as to improve the heat conduction efficiency. The third portion **130c** may be a foamed metal with loose holes for increasing the disturbance of the dielectric fluid flow and reducing the possibility of fluid stasis on the back of the fin.

(35) In some embodiments, the porosity of the second portion **130b** may be greater than or equal to

the porosity of the first portion **130a**. For example, the first portion **130a** may be a metal material without holes, or the first portion **130a** may also be a foamed metal and have a similar porosity to the second portion **130b**.

(36) In the embodiment of FIG. **1C**, the heat dissipation fins **130** are similar to the embodiment of FIG. **1B**. The second portion **130b** may also extend to the bottom surface of the first portion **130a**, so that the second portion **130b** is located on the side wall and the bottom surface of the first portion **130a**, and the third portion **130c** may be located on a side wall and a bottom surface of the second portion **130b**. That is to say, the second portion **130b** is located between the first portion **130a** and the third portion **130c**, and the third portion **130c** is not in direct contact with the first portion **130a**.

(37) In the embodiment of FIG. **1D**, the heat dissipation fins **130** are similar to the embodiment of FIG. **1B**. The third portion **130c** may also extend to the side wall of the second portion **130b**, so that the third portion **130c** is in direct contact with the bottom surface and the side wall of the second portion **130b** and the bottom surface of the first portion **130a**.

(38) However, the heat dissipation fins **130** of the disclosure are not limited to the embodiments of FIG. **1B** to FIG. **1D**. In other embodiments, the heat dissipation fins **130** may also be metal heat dissipation materials without holes.

(39) In some embodiments, the heat dissipation plate **132** and the heat dissipation block **134** may be metal heat dissipation materials without holes.

(40) In some other embodiments, the heat dissipation plate **132**, the heat dissipation block **134** and/or the heat dissipation fins **130** may be a heat dissipation structure filled with a working fluid inside having phase change characteristics. Specifically, the heat dissipation structure is a metal chassis that encapsulates the working fluid inside. The metal chassis has a vacuum or near-vacuum sealed space inside and a capillary structure on the internal wall surface thereof, and the working fluid is located in the sealed space. When the vapor chamber structure is in contact with the heat source, the liquid phase working fluid absorbs heat and boils and vaporizes. Therefore, a pressure difference is created in the sealed space, causing the steam to flow to a lower temperature area. When the vapor phase working fluid is in contact with a relatively cold area, condensation will occur. Since the internal wall surface of the metal chassis has a capillary structure, the condensed working fluid may be guided back to the heat source. In this way, the working fluid may operate cyclically in a sealed space to achieve the purpose of heat dissipation. In some embodiments, the working fluid may be a fluid with a boiling point less than 70° C. under vacuum, but the disclosure is not limited thereto.

(41) In some embodiments, the chassis **140** may include a main body portion **142** and a top cover portion **144**. The main body portion **142** has an accommodating space constructed of side walls and a bottom plate, and the accommodating space is for components such as the circuit board **100**, the antenna substrate **110**, the heat dissipation plate **132**, and the heat dissipation fins **130** to be disposed therein. The main body portion **142** has an opening, which at least corresponds to the antenna layer **112** of the antenna substrate **110**. The top cover portion **144** is disposed in the opening of the main body portion **142** and is connected to the main body portion **142** to seal the accommodating space and encapsulate components such as the circuit board **100**, the antenna substrate **110**, the heat dissipation plate **132**, and the heat dissipation fins **130** therein. The antenna substrate **110** is closer to the top cover portion **144** than the circuit board **100**, and the upper surface **110a** of the antenna substrate **110** faces the top cover portion **144**.

(42) In some embodiments, the material of the top cover portion **144** is different from the material of the main body portion **142**. For example, the main body portion **142** may be a metal material to protect the antenna structure and have a favorable shielding effect on noise; the top cover portion **144** may be plastic insulating material such as PP polypropylene or other suitable non-magnetic materials, so that the antenna layer **112** may receive or transmit electromagnetic wave signals through the top cover portion **144**.

(43) FIG. 2 is a schematic cross-sectional view of an antenna-in-package with a heat dissipation structure according to another embodiment of the disclosure. The embodiment of FIG. 2 continues to use the referential numbers of the elements and a part of the content of the embodiment of FIG. 1, wherein the same or similar referential numbers are used to denote the same or similar elements, and the description of the same technical content are omitted. For the descriptions of the omitted part, reference may be made to the foregoing embodiments, and details are not repeated here.

(44) Referring to FIG. 2. The difference between an antenna-in-package with a heat dissipation structure **20** of FIG. 2 and the antenna-in-package with the heat dissipation structure **10** of FIG. 1 is that the dielectric fluid **150** flows in the space surrounded by the antenna substrate **110**, the baffle **141**, and the chassis **140**. Specifically, the baffle **141** of the antenna-in-package with the heat dissipation structure **20** is disposed on the inner surface of the chassis **140**, and the lower surface **110b** of the antenna substrate **110** is fixedly disposed on the baffle **141**, so that the antenna substrate **110** and the baffle **141** divide the chassis **140** into a first space S21 and a second space S22. The first space S21 includes the antenna substrate **110** disposed therein and the antenna layer **112** is exposed in the first space S21. The second space S22 includes the circuit board **100**, the chip **120**, the heat dissipation plate **132**, and the heat dissipation fins **130** disposed therein, and the dielectric fluid **150** flows in the second space S22. In other words, the dielectric fluid **150** may be in direct contact with the circuit board **100**, the heat dissipation plate **132**, the heat dissipation fins **130**, and the chip **120**. The dielectric fluid **150** may also be in direct contact with the conductive connecting member **170** to facilitate heat dissipation from the conductive connecting member **170**.

(45) In some embodiments, the dielectric fluid **150** may be in contact with the lower surface **110b** of the antenna substrate **110** instead of the upper surface **110a** of the antenna substrate **110**. That is, the dielectric fluid **150** may not be in contact with the antenna layer **112**.

(46) In some embodiments, the heat dissipation plate **132** of the antenna-in-package with the heat dissipation structure **20** has a plurality of via holes V. The via holes V may be located around the heat dissipation block **134** and correspond to the through holes TH of the circuit board **100**. Therefore, the dielectric fluid **150** may flow into the gap between the heat dissipation block **134** and the circuit board **100** through the plurality of via holes V, further allowing the dielectric fluid **150** to easily flow into the space between the circuit board **100** and the antenna substrate **110** (including the space between the chip **120** and the antenna substrate **110**) so as to improve the heat dissipation efficiency of the conductive connecting member **170** and the chip **120**. In other embodiments, the antenna-in-package with the heat dissipation structure **20** may not have the heat dissipation plate **132** and the heat dissipation block **134** such that the heat dissipation fins **130** of FIG. 2 are disposed in the through holes TH of the circuit board **100** and in direct or indirect contact with the chip **120** as shown in the heat dissipation fins **130** of the embodiment of FIG. 7 described later. In addition, in yet some other embodiments, the antenna-in-package with the heat dissipation structure **20** may not have the heat dissipation plate **132**, the heat dissipation block **134**, and the heat dissipation fins **130**. Therefore, the through holes TH of the circuit board **100** has the dielectric fluid **150** passing through and contacting the chip **120**.

(47) In some embodiments, the heat dissipation fins **130** may be as shown in the foregoing embodiments of FIG. 1B to FIG. 1D and are not repeated here. In some embodiments, the surface or the entirety of the heat dissipation block **134** may also have a similar structure to the second portion **130b** of the heat dissipation fins **130** shown in the foregoing embodiments of FIG. 1B to FIG. 1D. That is, the surface or the entirety of the heat dissipation block **134** may be a foamed metal with dense holes to improve heat conduction efficiency.

(48) In some embodiments, the antenna-in-package with the heat dissipation structure **20** further includes a flow disturbing object **180** disposed on the inner surface of the chassis **140** and located between the inlet portion IN and the outlet portion OUT of the chassis **140** and in contact with the dielectric fluid **150** to promote the disturbance of the dielectric fluid **150** in the chassis **140** and reduce the possibility of fluid bypass. In some embodiments, the flow disturbing object **180** may be

a foamed metal, so that the dielectric fluid **150** may pass through the holes of the flow disturbing object **180**. The dead zone generated on a side of the flow disturbing object **180** facing away from the flow direction of the dielectric fluid **150** may be reduced, while the disturbance of the dielectric fluid **150** may be promoted at the same time, so that the dielectric fluid **150** may flow uniformly in the second space **S22**, and the heat in the second space **S22** may be effectively taken away.

(49) Three flow disturbing objects **180** are schematically shown in FIG. 2, but it is not intended to limit the disclosure. The number, size, and location of disposition of the flow disturbing objects **180** may be adjusted according to actual requirements.

(50) FIG. 3 is a schematic cross-sectional view of an antenna-in-package with a heat dissipation structure according to another embodiment of the disclosure. The embodiment of FIG. 3 continues to use the referential numbers of the elements and a part of the content of the embodiment of FIG. 2, wherein the same or similar referential numbers are used to denote the same or similar elements, and the description of the same technical content are omitted. For the descriptions of the omitted part, reference may be made to the foregoing embodiments, and details are not repeated here.

(51) Referring to FIG. 3. The difference between an antenna-in-package with a heat dissipation structure **30** of FIG. 3 and the antenna-in-package with the heat dissipation structure **20** of FIG. 2 is that the antenna-in-package with the heat dissipation structure **30** also includes a vapor chamber **190** disposed between the chip **120** and the heat dissipation block **134**. In this way, the heat generated by the chip **120** may be first conducted to the vapor chamber **190**, and then transmitted to the dielectric fluid **150** through the heat dissipation block **134**, the heat dissipation plate **132**, and the heat dissipation fins **130**, and the heat energy may be dissipated to the outside of the chassis **140** through the dielectric fluid **150**.

(52) In FIG. 3, the vapor chamber **190** and the first surface **100a** of the circuit board **100** may be in direct contact through a thermal interface material (TIM) (not shown), but it is not intended to limit the disclosure as long as the vapor chamber **190** may be attached to the back surface **120b** of the chip **120**. That is to say, in other embodiments, a gap may exist between the vapor chamber **190** and the first surface **100a** of the circuit board **100**.

(53) In some embodiments, the dielectric fluid **150** may also be in direct contact with the vapor chamber **190**.

(54) In FIG. 3, the heat dissipation plate **132** is not disposed with a via hole, and the gap between the heat dissipation block **134** and the circuit board **100** may be filled with an insulated thermal interface material to promote heat conduction. However, it is not intended to limit the disclosure. The heat dissipation plate **132** may also have a plurality of via holes as shown in the embodiment of FIG. 2, so that the dielectric fluid may flow into the gap between the heat dissipation plate **132** and the circuit board **100**.

(55) Although there is no flow disturbing object shown in FIG. 3, the antenna-in-package with the heat dissipation structure **30** may also include a flow disturbing object to enhance the flow of the dielectric fluid **150** in the chassis **140**.

(56) FIG. 4 is a schematic cross-sectional view of an antenna-in-package with a heat dissipation structure according to another embodiment of the disclosure. The embodiment of FIG. 4 continues to use the referential numbers of the elements and a part of the content of the embodiment of FIG. 2, wherein the same or similar referential numbers are used to denote the same or similar elements, and the description of the same technical content are omitted. For the descriptions of the omitted part, reference may be made to the foregoing embodiments, and details are not repeated here.

(57) Referring to FIG. 4, an antenna-in-package with a heat dissipation structure **40** includes the circuit board **100**, the antenna substrate **110**, the chip **120**, the chassis **140**, and the dielectric fluid **150**. The circuit board **100** has the first surface **100a** and the second surface **100b** opposite to the first surface **100a**. The antenna substrate **110** is disposed above the first surface **100a** of the circuit board **100**. The antenna substrate **110** includes the antenna layer **112** disposed on the upper surface **110a** of the antenna substrate **110**. The chip **120** is disposed between the antenna substrate **110** and

the first surface **100a** of the circuit board **100** and is electrically connected to the antenna substrate **110**. The chassis **140** encapsulates the circuit board **100**, the antenna substrate **110**, and the chip **120**. The dielectric fluid **150** circulates and flows in the chassis **140** through the cooling circulation device **160** and is in direct contact with the antenna layer **112**.

(58) In FIG. **4**, since the circuit board **100**, the antenna substrate **110**, the chip **120**, and the dielectric fluid **150** are all located in the same space of the chassis **140**, the dielectric fluid **150** may flow throughout the chassis **140** and be in direct contact with the circuit board **100** and the antenna substrate **110**, and the chip **120**. The circuit board **100** and/or the antenna substrate **110** are fixedly disposed in the chassis **140**, and the connection thereof with the chassis **140** is omitted in FIG. **4**. In some embodiments, the circuit board **100** and/or the antenna substrate **110** may be fixedly disposed in the chassis **140** through support columns, bolts, etc., which is not limited in the disclosure.

(59) In some embodiments, the dielectric fluid **150** may fill up the chassis **140**.

(60) In some embodiments, a vertical distance between the antenna layer **112** and the top cover portion **144** of the chassis **140** is less than 2 cm, for example, between 1.0 cm and 2.0 cm.

(61) In FIG. **4**, the through holes TH of the circuit board **100** has the dielectric fluid **150** passing through without a heat dissipation block or a heat dissipation fin being disposed, but the disclosure is not limited thereto. In other embodiments, the heat dissipation block or the heat dissipation fins may be disposed in the through holes TH of the circuit board **100**.

(62) FIG. **5** is a schematic cross-sectional view of an antenna-in-package with a heat dissipation structure according to another embodiment of the disclosure. The embodiment of FIG. **5** continues to use the referential numbers of the elements and a part of the content of the embodiment of FIG. **4**, wherein the same or similar referential numbers are used to denote the same or similar elements, and the description of the same technical content are omitted. For the descriptions of the omitted part, reference may be made to the foregoing embodiments, and details are not repeated here.

(63) Referring to FIG. **5**, the difference between an antenna-in-package with a heat dissipation structure **50** of FIG. **5** and the antenna-in-package with the heat dissipation structure **40** of FIG. **4** is that the chassis **140** of the antenna-in-package with the heat dissipation structure **50** includes the inlet portion IN and two outlet portions OUT1 and OUT2. The inlet portion IN is disposed on the bottom plate of the chassis **140**, and the outlet portions OUT1 and OUT2 are disposed on the side walls of the chassis **140**. In some embodiments, the outlet portion OUT1 and the outlet portion OUT2 are opposite to each other, but the disclosure is not limited thereto.

(64) In some embodiments, a cooling circulation device **160a** may be disposed on the outside of the chassis **140** between the outlet portion OUT1 and the inlet portion IN. A cooling circulation device **160b** may be disposed on the outside of the chassis **140** between the outlet portion OUT2 and the inlet portion IN, so that the dielectric fluid **150** flowing out from different outlet portions may dissipate heat through different cooling circulation devices and then return to the inside of the chassis **140**. However, the disclosure is not limited thereto. The dielectric fluid **150** flowing out from different outlet portions may also be merged into one through pipeline design and returned to the inside of the chassis **140** through a single cooling circulation device.

(65) FIG. **6** is a schematic cross-sectional view of an antenna-in-package with a heat dissipation structure according to another embodiment of the disclosure. The embodiment of FIG. **6** continues to use the referential numbers of the elements and a part of the content of the embodiment of FIG. **4**, wherein the same or similar referential numbers are used to denote the same or similar elements, and the description of the same technical content are omitted. For the descriptions of the omitted part, reference may be made to the foregoing embodiments, and details are not repeated here.

(66) Referring to FIG. **6**, the difference between an antenna-in-package with a heat dissipation structure **60** of FIG. **6** and the antenna-in-package with the heat dissipation structure **40** of FIG. **4** is that the inlet portion IN and the outlet portion OUT are respectively disposed on the opposite side walls of the chassis **140**, and the position of the outlet portion OUT is higher than the position of the inlet portion IN.

(67) FIG. 7 is a schematic cross-sectional view of an antenna-in-package with a heat dissipation structure according to another embodiment of the disclosure. The embodiment of FIG. 7 continues to use the referential numbers of the elements and a part of the content of the embodiment of FIG. 4, wherein the same or similar referential numbers are used to denote the same or similar elements, and the description of the same technical content are omitted. For the descriptions of the omitted part, reference may be made to the foregoing embodiments, and details are not repeated here.

(68) Referring to FIG. 7, the difference between an antenna-in-package with a heat dissipation structure **70** of FIG. 7 and the antenna-in-package with the heat dissipation structure **40** of FIG. 4 is that the antenna-in-package with the heat dissipation structure **70** also includes the heat dissipation fins **130** disposed in the through holes TH of the circuit board **100**. The heat dissipation fins **130** may protrude from the second surface **100b** of the circuit board **100** to promote the disturbance of the dielectric fluid **150** and improve the heat dissipation efficiency.

(69) In some embodiments, the heat dissipation fins **130** may include foamed metals. For example, the heat dissipation fins **130** may be as shown in the embodiments of FIG. 1B to FIG. 1D.

(70) In some embodiments, there is a gap between the heat dissipation fins **130** and the circuit board **100**, so that the dielectric fluid **150** may flow therein, and the dielectric fluid **150** may easily flow into the space between the antenna substrate **110** and the circuit board **100**.

(71) In some embodiments, the back surface **120b** of the chip **120** may include a thermal interface material layer **122** to facilitate the connection with the heat dissipation fins **130**, but the disclosure is not limited thereto. In other embodiments, the heat dissipation fins **130** may be in direct contact with the back surface **120b** of the chip **120**. In yet some other embodiments, a vapor chamber (not shown) may be disposed between the heat dissipation fins **130** and the back surface **120b** of the chip **120**.

(72) In some embodiments, the thermal interface material layer **122** may be thermally conductive glue, a thermal pad, or other suitable thermal interface materials.

(73) Although there is no flow disturbing object shown in FIG. 7, the antenna-in-package with the heat dissipation structure **70** may also include the flow disturbing object to enhance the disturbance of the dielectric fluid **150** in the chassis **140**.

(74) FIG. 8 is a schematic cross-sectional view of an antenna-in-package with a heat dissipation structure according to another embodiment of the disclosure. The embodiment of FIG. 8 continues to use the referential numbers of the elements and a part of the content of the embodiment of FIG. 7, wherein the same or similar referential numbers are used to denote the same or similar elements, and the description of the same technical content are omitted. For the descriptions of the omitted part, reference may be made to the foregoing embodiments, and details are not repeated here.

(75) Referring to FIG. 8, the difference between an antenna-in-package with a heat dissipation structure **80** of FIG. 8 and the antenna-in-package with the heat dissipation structure **70** of FIG. 7 is that the antenna-in-package with the heat dissipation structure **80** also includes the heat dissipation plate **132**. The heat dissipation plate **132** is disposed above the second surface **100b** of the circuit board **100** and connected to the heat dissipation fins **130**. The surface of the heat dissipation plate **132** includes a plurality of micro-bumps **132a** or micro-dimples (for example, corresponding to the recessed area between two micro-bumps) to help promote the flow of the dielectric fluid **150** in the chassis **140**. The disclosure does not limit the shape of the micro-bumps **132a**, which may be columnar, spherical, hemispherical, etc., or the corresponding bump shape may be formed by forming micro-dimples.

(76) In some embodiments, the heat dissipation plate **132** may be a foamed metal to promote disturbance and heat conduction of the dielectric fluid **150** within the chassis **140**.

(77) In some embodiments, there is a gap between the heat dissipation plate **132** and the second surface **100b** of the circuit board **100**. Therefore, the dielectric fluid **150** may flow into the gap, thereby allowing the dielectric fluid **150** to flow through the gap between the circuit board and the heat dissipation fins **130** and further flow into the space between the antenna substrate **110** and the

circuit board **100** so as to improve the heat dissipation efficiency of the chip **120**.

(78) FIG. **8** schematically shows the inlet portion IN and the outlet portion OUT at the lower part of the chassis **140**, but the disclosure is not limited thereto. The number and position of the inlet portion and outlet portion of the chassis **140** may be adjusted according to actual requirements. In some embodiments, the inlet portion and the outlet portion of the chassis **140** may be configured similar to the embodiment of FIG. **5** or FIG. **6**.

(79) Although there is no flow disturbing object shown in FIG. **8**, the antenna-in-package with the heat dissipation structure **80** may also include the flow disturbing object to enhance the disturbance of the dielectric fluid **150** in the chassis **140**.

(80) FIG. **9** is a schematic cross-sectional view of an antenna-in-package with a heat dissipation structure according to another embodiment of the disclosure. The embodiment of FIG. **9** continues to use the referential numbers of the elements and a part of the content of the embodiment of FIG. **1**, wherein the same or similar referential numbers are used to denote the same or similar elements, and the description of the same technical content are omitted. For the descriptions of the omitted part, reference may be made to the foregoing embodiments, and details are not repeated here.

(81) Referring to FIG. **9**, an antenna-in-package with a heat dissipation structure **90** includes the circuit board **100**, the antenna substrate **110**, the chip **120**, a plurality of heat dissipation fins **930**, the chassis **140**, and cooling fluid **950**. The chassis **140** includes a first space **S91** and a second space **S92**. The first space **S91** and the second space **S92** are isolated from each other by a heat dissipation plate **932**. The circuit board **100** is located in the first space **S91** and is disposed on the heat dissipation plate **932**. The antenna substrate **110** is located in the first space **S91** and is disposed above the circuit board **100**. The chip **120** is disposed between the antenna substrate **110** and the circuit board **100** and is electrically connected to the antenna substrate **110**. The heat dissipation fins **930** are located in the second space **S92** and disposed on the heat dissipation plate **932**. The cooling fluid **950** is located in the second space **S92** and is in contact with the heat dissipation fins **930**. The cooling fluid **950** absorbs heat from the heat dissipation fins **930** to create a phase change.

(82) The cooling fluid **950** is in a state where the vapor phase and the liquid phase coexist in the second space **S92**. Specifically, the cooling fluid **950** may not fill up the second space **S92**, but may be in direct contact with at least part of the heat dissipation fins **930**, so that part of the liquid phase cooling fluid **950** absorbs heat from the heat dissipation fins **930** and vaporizes to form steam **950v**. The generation of steam creates a pressure difference in the second space **S92**, which prompts the steam to flow to a lower temperature area, and then to condense again into the liquid phase cooling fluid **950**. Such a cyclic operation may effectively conduct heat quickly.

(83) A pressure of the second space **S92** may be less than one atmosphere. In some embodiments, the second space **S92** may be in a near vacuum state. In some embodiments, the pressure of the second space **S92** is less than the pressure of the first space **S91**.

(84) In some embodiments, the cooling fluid **950** may be a volatile liquid with a low boiling point, such as ethanol, ammonia, perfluorocarbon, perfluoropolyether, or other suitable cooling fluid. In some embodiments, the boiling point of the cooling fluid **950** in the second space **S92** may be less than 70° C., for example, between 50° C. and 60° C., so as to improve the heat dissipation effect of the chip **120**.

(85) In some embodiments, the antenna-in-package with the heat dissipation structure **90** further includes a heat dissipation block **934** disposed on the heat dissipation plate **932** and disposed in the through hole TH. In some embodiments, the heat dissipation block **934** penetrates the circuit board **100** and is in direct contact with the back surface **120b** of the chip **120**. In this way, the heat dissipation block **934** may conduct the heat generated by the chip **120** to the heat dissipation fins **930**. Then, the cooling fluid **950** may continuously circulate in the second space **S92** to perform phase changes between liquid and vapor, so as to effectively conduct away the heat generated by the chip **120**.

(86) In some embodiments, the heat dissipation plate **932**, the heat dissipation fins **930**, and the heat dissipation block **934** are metal materials without holes. In some embodiments, the material of the heat dissipation plate **132**, the heat dissipation fins **930**, and the heat dissipation block **934** may be copper, aluminum, or other suitable thermally conductive materials.

(87) In some embodiments, a vapor chamber (not shown) may be included between the chip **120** and the heat dissipation block **934** to enhance the heat dissipation effect of the chip **120**. In some embodiments, a thermal interface material (not shown) may be included between the chip **120** and the heat dissipation block **934** to enhance the connection between the chip **120** and the heat dissipation block **934**.

(88) In some embodiments, the antenna-in-package with the heat dissipation structure **90** further includes external fins **931**, which are disposed on an outer surface of the chassis **140** and disposed corresponding to the second space **S92**. In this way, the heat of the cooling fluid **950** may further dissipate to the outside of the chassis **140** through the external fins **931**.

(89) In some embodiments, the surface of the heat dissipation fins **930** may have microstructures (not shown) for increasing the surface roughness thereof to assist the boiling of the cooling fluid **950**, so that the vaporized steam may easily escape from the surfaces of the heat dissipation fins **930** to allow the cooling fluid **950** to smoothly undergo a phase change cycle. In some embodiments, the microstructures may be formed by laying metal micro particles on the surfaces of the heat dissipation fins **930**, but the disclosure is not limited thereto.

(90) In summary, the antenna-in-package with the heat dissipation structure of the disclosure improves the heat dissipation efficiency thereof through the provision of dielectric fluid or cooling fluid, so that the antenna-in-package with the heat dissipation structure is adapted for application in the 5G communications industry and low-orbit satellite ground stations.

(91) Although the disclosure has been described with reference to the embodiments above, the embodiments are not intended to limit the disclosure. Any person skilled in the art can make some changes and modifications without departing from the spirit and scope of the disclosure. Therefore, the scope of the disclosure will be defined in the appended claims.

Claims

1. An antenna-in-package with a heat dissipation structure, comprising: a circuit board, having a first surface and a second surface opposite to the first surface; an antenna substrate, disposed above the first surface of the circuit board; a chip, disposed between the antenna substrate and the first surface of the circuit board, and electrically connected to the antenna substrate; a plurality of heat dissipation fins, protruding from the second surface of the circuit board; a chassis, encapsulating the circuit board, the antenna substrate, the chip, and the plurality of heat dissipation fins; and dielectric fluid, circulating and flowing in the chassis through a cooling circulation device, and being in direct contact with the plurality of heat dissipation fins.
2. The antenna-in-package with the heat dissipation structure according to claim 1, further comprising: a heat dissipation plate, disposed on the second surface of the circuit board, wherein the plurality of heat dissipation fins are disposed on the heat dissipation plate, and the dielectric fluid is in direct contact with the heat dissipation plate.
3. The antenna-in-package with the heat dissipation structure according to claim 2, further comprising: a baffle, disposed on an inner surface of the chassis, wherein the circuit board is fixedly disposed on the baffle, and the dielectric fluid flows in a space surrounded by the circuit board, the baffle, the heat dissipation plate, and the chassis to be in direct contact with the plurality of heat dissipation fins.
4. The antenna-in-package with the heat dissipation structure according to claim 2, further comprising: a heat dissipation block, disposed on the heat dissipation plate, and penetrating the circuit board.

5. The antenna-in-package with the heat dissipation structure according to claim 4, further comprising: a baffle, disposed on an inner surface of the chassis, wherein the antenna substrate is fixedly disposed on the baffle, and the dielectric fluid flows in a space surrounded by the antenna substrate, the baffle, and the chassis to be in direct contact with the plurality of heat dissipation fins.
6. The antenna-in-package with the heat dissipation structure according to claim 5, wherein the heat dissipation plate has a plurality of via holes, and the dielectric fluid flows into a gap between the heat dissipation block and the circuit board through the plurality of via holes.
7. The antenna-in-package with the heat dissipation structure according to claim 5, wherein the dielectric fluid is in direct contact with the chip.
8. The antenna-in-package with the heat dissipation structure according to claim 1, wherein the antenna substrate comprises an antenna layer disposed on an upper surface of the antenna substrate, and the antenna layer is not in contact with the dielectric fluid.
9. The antenna-in-package with the heat dissipation structure according to claim 1, further comprising: a vapor chamber, disposed on a back surface of the chip.
10. The antenna-in-package with the heat dissipation structure according to claim 1, wherein the chassis comprises at least one inlet portion and at least one outlet portion, the cooling circulation device comprises a pump and a heat exchanger that are disposed on an outside of the chassis, the dielectric fluid is drawn out from the at least one outlet portion of the chassis by the pump and passed through the heat exchanger to dissipate heat of the dielectric fluid to the outside, and the dielectric fluid flowing through the heat exchanger is then returned to an inside of the chassis through the at least one inlet portion.
11. The antenna-in-package with the heat dissipation structure according to claim 1, wherein each of the plurality of heat dissipation fins comprises: a first portion, being in direct contact with a heat dissipation plate; a second portion, located on a side wall of the first portion; and a third portion, located above a bottom surface of the first portion, wherein a porosity of the third portion is greater than a porosity of the second portion.
12. The antenna-in-package with the heat dissipation structure according to claim 1, wherein the dielectric fluid comprises silicone oil, mineral oil, or fluorinated liquid.
13. An antenna-in-package with a heat dissipation structure, comprising: a circuit board, having a first surface and a second surface opposite to the first surface; an antenna substrate, disposed above the first surface of the circuit board, wherein the antenna substrate comprises an antenna layer disposed on a surface of the antenna substrate; a chip, disposed between the antenna substrate and the first surface of the circuit board, and electrically connected to the antenna substrate; a chassis, encapsulating the circuit board, the antenna substrate, and the chip; dielectric fluid, circulating and flowing in the chassis through a cooling circulation device, and being in direct contact with the antenna layer.
14. The antenna-in-package with the heat dissipation structure according to claim 13, wherein the circuit board has a through hole corresponding to the chip, and the dielectric fluid flows through the through hole and is in contact with the chip.
15. The antenna-in-package with the heat dissipation structure according to claim 14, further comprising: a heat dissipation fin, disposed in the through hole of the circuit board, and protruding from the second surface of the circuit board.
16. The antenna-in-package with the heat dissipation structure according to claim 15, wherein the heat dissipation fin comprises a foamed metal.
17. The antenna-in-package with the heat dissipation structure according to claim 15, further comprising: a heat dissipation plate, disposed above the second surface of the circuit board, and connected to the heat dissipation fin, wherein a surface of the heat dissipation plate comprises a plurality of micro-bumps or micro-dimples.
18. The antenna-in-package with the heat dissipation structure according to claim 17, wherein the

dielectric fluid flows through a space between the heat dissipation plate and the circuit board.

19. The antenna-in-package with the heat dissipation structure according to claim 13, wherein the chassis comprises at least one inlet portion and at least one outlet portion, the cooling circulation device comprises a pump and a heat exchanger that are disposed on an outside of the chassis, the dielectric fluid is drawn out from the at least one outlet portion of the chassis by the pump and passed through the heat exchanger to dissipate heat of the dielectric fluid to the outside, and the dielectric fluid flowing through the heat exchanger is then returned to an inside of the chassis through the at least one inlet portion.

20. The antenna-in-package with the heat dissipation structure according to claim 19, further comprising: a flow disturbing object, disposed on an inner surface of the chassis, and located between the at least one inlet portion and the at least one outlet portion of the chassis to promote a disturbance of the dielectric fluid in the chassis, wherein the flow disturbing object is a foamed metal.

21. An antenna-in-package with a heat dissipation structure, comprising: a chassis, comprising a first space and a second space, wherein the first space and the second space are isolated from each other by a heat dissipation plate; a circuit board, located in the first space, and disposed on the heat dissipation plate; an antenna substrate, located in the first space, and disposed on the circuit board; a chip, disposed between the antenna substrate and the circuit board, and electrically connected to the antenna substrate; a heat dissipation fin, located in the second space, and disposed on the heat dissipation plate; and cooling fluid, located in the second space, and being in contact with the heat dissipation fin, wherein the cooling fluid absorbs heat from the heat dissipation fin to create a phase change.

22. The antenna-in-package with the heat dissipation structure according to claim 21, wherein a pressure of the second space is less than one atmosphere.

23. The antenna-in-package with the heat dissipation structure according to claim 21, wherein the cooling fluid comprises ethanol, ammonia, perfluorocarbon, or perfluoropolyether.

24. The antenna-in-package with the heat dissipation structure according to claim 21, wherein the cooling fluid is in a state where a vapor phase and a liquid phase coexist in the second space.

25. The antenna-in-package with the heat dissipation structure according to claim 21, wherein a surface of the heat dissipation fin has a microstructure to increase a surface roughness of the heat dissipation fin.

26. The antenna-in-package with the heat dissipation structure according to claim 21, further comprising: a heat dissipation block, disposed on the heat dissipation plate, and penetrating the circuit board to be in contact with the chip.
