

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396602
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Kataoka; Yoshihiko et al.

Dust removal device and dust removal method

Abstract

A dust removal device capable of normally dedusting a surface of a sheet-shaped object having an edge portion of a shape with protruding parts continuously arranged at predetermined intervals along the longitudinal direction, that is, a dust removal device discharging a gas to a surface of a sheet-shaped object **100** from a discharge outlet while drawing in the gas above the surface of the sheet-shaped object **100** through a suction inlet, the discharge outlet including a first discharge outlet **30** for discharging the gas to portions of the sheet-shaped object **100** other than the edge portion and a second discharge outlet **35** for discharging the gas to the edge portion **100b** of the sheet-shaped object **10**, and the suction inlet including a first suction inlet (**31, 32**) for drawing in the gas above the surface of the portions of the sheet-shaped object **100** other than the edge portion **100b** and a second suction inlet (**33, 34**) for drawing in the gas of the surface of the edge portion **100b** of the sheet-shaped object **100**.

Inventors:	Kataoka; Yoshihiko (Tokyo, JP), Shirane; Tomohiro (Tokyo, JP)
Applicant:	Hugle Development Inc. (Tokyo, JP)
Family ID:	1000008780523
Assignee:	Hugle Development Inc. (Tokyo, JP)
Appl. No.:	18/247317
Filed (or PCT Filed):	August 20, 2021
PCT No.:	PCT/JP2021/030511
PCT Pub. No.:	WO2022/070663
PCT Pub. Date:	April 07, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230380644 A1	Nov. 30, 2023

Foreign Application Priority Data

JP 2020-164827 Sep. 30, 2020

Publication Classification

Int. Cl.: A47L5/14 (20060101); A47L7/00 (20060101); A47L9/02 (20060101); B08B5/02 (20060101); B08B5/04 (20060101); B08B11/00 (20060101); H01M4/04 (20060101)

U.S. Cl.:

CPC A47L5/14 (20130101); A47L7/0047 (20130101); A47L9/02 (20130101); B08B5/023 (20130101); B08B5/043 (20130101); B08B11/00 (20130101); H01M4/04 (20130101);

Field of Classification Search

CPC: A47L (5/14); A47L (7/0047); A47L (9/02); B08B (5/023); B08B (5/043); B08B (11/00); B08B (5/046); B08B (5/026); H01M (4/04); Y02E (60/10); Y02P (70/50)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5596783	12/1996	Testone	15/309.1	B41F 23/002
6921438	12/2004	Lausevic	134/21	A47L 9/02
7111797	12/2005	Bezama	15/345	H01L 21/67028
2004/0003475	12/2003	Mariani	15/309.1	B08B 15/04

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
H5-138136	12/1992	JP	N/A
2004041851	12/2003	JP	N/A
2014100622	12/2013	JP	B08B 15/04

OTHER PUBLICATIONS

Machine translation of JP-2004041851-A (Year: 2004). cited by examiner
Machine translation of JP-2014100622-A (Year: 2014). cited by examiner

Primary Examiner: Bergner; Erin F

Attorney, Agent or Firm: Muncy, Geissler, Olds & Lowe, P.C.

Background/Summary

TECHNICAL FIELD

(1) The present invention relates to a dust removal device and dust removal method for discharging a gas toward a surface of a sheet-shaped object being conveyed while drawing in the gas above the

surface of the sheet-shaped object to thereby remove dust on the surface of the sheet-shaped object.

BACKGROUND ART

(2) Known in the past has been the dust removal device described in PTL 1. This dust removal device is arranged facing a sheet-shaped object wound on a guide roll (support part) and conveyed by rotation of the guide roll at a part abutting against that guide roll. In this dust removal device, a slit-shaped discharge outlet and a suction inlet (opening of suction box) which extend in directions perpendicular to the direction of conveyance of the sheet-shaped object (width direction of the sheet-shaped object) are formed at a predetermined interval so that the discharge outlet is positioned at the upstream side from the suction inlet in the conveyance direction. Further, in the process of the sheet-shaped object being conveyed, the dust removal device discharges air from the discharge outlet to the surface of the sheet-shaped object while drawing in air above the surface of the sheet-shaped object through the suction inlet. Dust sticking to the surface of the sheet-shaped object is dislodged by the air discharged from the discharge outlet and becomes airborne, and the airborne dust is drawn in from the suction inlet with the air. Due to this, the dust sticking to the surface of the sheet-shaped object is removed (dedusted).

CITATIONS LIST

Patent Literature

(3) PTL 1: Japanese Patent Publication No. H5-138136

SUMMARY

Technical Problem

(4) In this regard, for example, at the time of the production of secondary batteries (lithium ion batteries etc.), a sheet-shaped object **100** configured as an electrode film such as shown in FIG. **1** (for example, aluminum film, copper film) is used. In this sheet-shaped object **100**, an edge portion **100b** continuing from a sheet body **100a** in the width direction (traverse direction in FIG. **1**) has a shape with a plurality of tabs **101** (protruding parts) jutting out in the width direction continuously arranged at predetermined intervals in the longitudinal direction. Two types of single electrode film pieces **110a**, **110b** are cut out for each tab **101** from this sheet-shaped object **100**. Further, a predetermined number of these single electrode films **110a**, **110b**, as shown in FIG. **2**, are alternately stacked across insulating films **111**. Further, the final stack, as shown in FIG. **3**, is formed as a battery unit **200** having two electrode blocks **210a**, **210b** comprised of stacked tabs **101**.

(5) In the above-described process of production of a battery unit **200**, it is necessary to remove dust from the surface of the sheet-shaped object **100** (electrode film) used as the material. Therefore, the sheet-shaped object **100** may be dedusted by the above-mentioned conventional dust removal device.

(6) However, if dedusting a sheet-shaped object **100** of the above-mentioned structure using the above-mentioned conventional dust removal device, the edge portion **100b** of the sheet-shaped object **100** where the tabs **101** are arranged is not subjected to tension accompanying conveyance, so ends up flapping, bending, or being drawn into the suction inlet by the flow of the gas discharged from the discharge outlet or the flow of the gas being drawn through the suction inlet. As a result, the surface of the edge portion **100b** of the sheet-shaped object **100** cannot be normally dedusted.

(7) The present invention was made in consideration of these circumstances and provides a dust removal device capable of normally dedusting the surface of a sheet-shaped object having an edge portion of a shape with protruding parts continuously arranged at certain intervals along the longitudinal direction.

Solution to Problem

(8) The dust removal device according to the present invention is a dust removal device that is provided with a discharge outlet and suction inlet facing the surface of a sheet-shaped object being conveyed and arranged at a predetermined interval along the conveyance direction of the sheet-

shaped object and that discharges a gas from the discharge outlet to the surface of the sheet-shaped object while drawing in the gas above the surface of the sheet-shaped object through the suction inlet, wherein the discharge outlet includes a first discharge outlet which discharges the gas to a portion of the sheet-shaped object other than an edge portion in the width direction and a second discharge outlet which discharges the gas to the edge portion of the sheet-shaped object, and the suction inlet includes a first suction inlet which draws in the gas above the surface of the portion of the sheet-shaped object other than the edge portion and a second suction inlet which draws in the gas above the surface of the edge portion of the sheet-shaped object.

(9) According to this configuration, in the process of the sheet-shaped object being conveyed, the gas discharged from the first discharge outlet is blown to the portion of the sheet-shaped object other than the edge portion, and the gas discharged from the second discharge outlet is blown to the edge portion. At this time, the gas above the surface of the portion of the sheet-shaped object other than the edge portion is drawn in through the first suction inlet, and the gas above the surface of the edge portion is drawn in through the second suction inlet. In this way, the gas is blown out from different discharge outlets to the edge portion of the sheet-shaped object and the other portion while the gas above the surface of the edge portion of the sheet-shaped object and above the surface of the other portion is drawn in through different suction inlets, so it is possible for the gas to be blown to the edge portion of the sheet-shaped object at a strength suitable for the form of the edge portion and different from that of the other portion and for the gas to be drawn in from above the surface of the edge portion of the sheet-shaped object at a strength suitable for the form of the edge portion and different from that above the surface of the other portion.

(10) The dust removal device according to the present invention can be configured so that a supply path for the gas discharged from the first discharge outlet and a supply path for the gas discharged from the second discharge outlet differ.

(11) Due to this configuration, the gas supplied from different supply paths is discharged from the first discharge outlet and the second discharge outlet and respectively blown to the edge portion of the sheet-shaped object and the other portion. Due to this, the gas can be easily blown to the edge portion of the sheet-shaped object at a strength suitable for the form of the edge portion and different from that of the other portion.

(12) The dust removal device according to the present invention can be configured so that the opening area per unit length of the second discharge outlet is smaller than the opening area per unit length of the first discharge outlet.

(13) Due to this configuration, the gas can be blown to the edge portion of the sheet-shaped object in a weaker manner than to the other portion in the process of the sheet-shaped object being conveyed.

(14) The dust removal device according to the present invention can be configured so that the second discharge outlet includes a plurality of small holes aligned in a direction traversing the conveyance direction of the sheet-shaped object.

(15) Due to this configuration, the gas can be discharged from the second discharge outlet in a weaker manner in comparison with the case of extending in a slit shape.

(16) The dust removal device according to the present invention can be configured so as to have a gas discharge path with a shape that gradually expands from an opening facing the sheet-shaped object being conveyed to the second discharge outlet.

(17) Due to this configuration, the gas passes through the gas discharge path which gradually expands from the opening and is discharged from the second discharge outlet. The discharge pressure of the gas running from the opening along the inner peripheral wall of the gas discharge path and discharged from the peripheral edge portion of the second discharge outlet becomes smaller than the discharge pressure of the gas directly discharged from the portion of the second discharge outlet facing the opening without running along the inner peripheral wall of the gas discharge path. Due to this, the discharge pressure of the gas discharged from the portion of the

discharge outlet facing the opening can be kept at a desired pressure while lowering the discharge pressure of the gas discharged from the peripheral edge portion of the second discharge outlet. Due to the discharge pressure of the gas discharged from the peripheral edge portion of the second discharge outlet decreasing, a negative pressure state caused by the Bernoulli effect becomes difficult to produced at a region facing the peripheral edge portion of the second discharge outlet. Therefore, the edge portion of the sheet-shaped object being conveyed can be kept from flipping up due to a negative pressure state which could be produced by the Bernoulli effect when entering a region facing the peripheral edge portion of the second discharge outlet while dust sticking to the edge portion of the sheet-shaped object being conveyed can be reliably removed by the gas of the desired discharge pressure discharged from the portion of the second discharge outlet facing the opening.

(18) The dust removal device according to the present invention can be configured so that a cross-section of the gas discharge path vertical to the sheet-shaped object being conveyed has a shape which gradually expands in an arc shape.

(19) Due to this configuration, the gas runs along the inner peripheral wall of the gas discharge path with an arc-shaped cross-section gradually expanding from the opening and is discharged from the peripheral edge portion of the second discharge outlet and also is directly discharged from the portion of the second discharge outlet facing the opening. Due to this, as described earlier, the discharge pressure of the gas discharged from the portion of the second discharge outlet facing the opening can be kept at a desired pressure while lowering the discharge pressure of the gas discharged from the peripheral edge portion of the second discharge outlet.

(20) The dust removal device according to the present invention can be configured so that the second discharge outlet includes a plurality of slits which are arranged in a direction traversing the conveyance direction of the sheet-shaped object with each slit extending in a direction traversing the arrangement direction, and the dust removal device having a gas discharge path which is provided for each of the plurality of slits and extends from an opening facing the sheet-shaped object to the slit, and wherein a cross-section of the gas discharge path taken vertical to each slit has a shape which gradually expands from the opening to the slit.

(21) Due to this configuration, the gas runs from the opening through the gas discharge path gradually expanding from the opening, and is discharged from each of the plurality of slits. The discharge pressure of the gas running from the opening along the inner peripheral wall of the gas discharge path and discharged from the upstream end part of the slit in the conveyance direction of the conveyed sheet-shaped object is lower than the discharge pressure of the gas directly discharged from the portion of the slit facing the opening without running along the inner peripheral wall of the gas discharge path. Due to this, the discharge pressure of the gas discharged from a portion of each slit facing the opening can be kept at a desired pressure while the discharge pressure of the gas discharged from the upstream end part of the slit decreases. Due to the discharge pressure of the gas discharged from the upstream end part of each slit decreasing, a negative pressure state caused by the Bernoulli effect becomes difficult to produce at the region facing the upstream end part of the slit. Therefore, the edge portion of the sheet-shaped object being conveyed can be kept from flipping up due to a negative pressure state which could be produced by the Bernoulli effect when entering the region facing the upstream end part of each slit while dust sticking to the edge portion of the sheet-shaped object being conveyed can be reliably removed by the gas of the desired discharge pressure discharged from the portion of each slit facing the opening.

(22) Further, when the edge portion of the sheet-shaped object being conveyed enters the region facing the upstream end parts of the plurality of slits, the gas of a certain discharge pressure is discretely blown to the edge portion of the sheet-shaped object from the plurality of slits. For this reason, when the edge portion of the sheet-shaped object enters the region facing the upstream end parts of the plurality of slits in the conveyance direction, discharged air will not act simultaneously

on all of the front end portion of the edge portion. Accordingly, in the state where air of the desired discharge pressure is discharged from the portions of the slits facing the openings, the edge portion of the sheet-shaped object can be reliably kept from flipping up due to air acting on the edge portion.

(23) The dust removal device according to the present invention can be configured so that the shape of the cross-section gradually expands to in an arc shape.

(24) Due to this configuration, the gas runs from the opening along an inner peripheral wall of the gas discharge path with gradually expanding arc-shaped cross-section gradually expanding from the opening and is discharged from the upstream end part of each slit in the conveyance direction of the sheet-shaped object being conveyed and is also directly discharged from the portion of the slit facing the opening without running along the inside peripheral wall of the gas discharge path. Due to this, as explained above, the discharge pressure of the gas discharged from the portion of each slit facing the opening can be kept at a desired pressure while the discharge pressure of the gas discharged from the upstream end part of the slit decreases.

(25) The dust removal device according to the present invention can be configured so that each of the plurality of slits is formed inclining obliquely to the conveyance direction of the sheet-shaped object.

(26) Due to this configuration, the gas can be blown from a plurality of discretely arranged slits during conveyance of the sheet-shaped object not simply in the form of a plurality of lines but over a wider area on the sheet-shaped object than the edge portion.

(27) The dust removal device according to the present invention can be configured so that each of the plurality of slits is formed in a state overlapping the adjacent slit in view in the conveyance direction of the sheet-shaped object.

(28) Due to this configuration, the gas can be blown with no gaps to the edge portion of the sheet-shaped object from the plurality of discretely arranged slits during conveyance of the sheet-shaped object.

(29) The dust removal device according to the present invention can be configured so that the plurality of slits are arranged in parallel or arranged zig-zag in a direction traversing the conveyance direction of the sheet-shaped object.

(30) The dust removal device according to the present invention can be configured so that the opening area per unit length of the second suction inlet is smaller than the opening area per unit length of the first suction inlet.

(31) Due to this configuration, the gas can be drawn in from above the surface of the edge portion of the sheet-shaped object in the process of conveyance of the sheet-shaped object in a weaker manner than that above the surface of the other portions.

(32) The dust removal device according to the present invention can be configured so that the second suction inlet includes a plurality of small holes aligned in a direction traversing the conveyance direction of the sheet-shaped object.

(33) Due to this configuration, the gas can be drawn in through the second suction inlet in a weaker manner than if formed extending in a slit shape or extending in an elongated rectangular shape.

(34) A dust removal method for dedusting a sheet-shaped object having an edge portion with a shape with protruding parts continuously arranged at certain intervals in the longitudinal direction, the method using a dust removal device which is provided with a discharge outlet and suction inlet arranged facing the surface of the sheet-shaped object being conveyed and extending in a direction traversing the conveyance direction of the sheet-shaped object at a predetermined interval in the conveyance direction of the sheet-shaped object, and the method comprising a flow generation step of discharging a gas from the discharge outlet to the surface of the sheet-shaped object while drawing in a gas above the surface of the sheet-shaped object through the suction inlet, where, in the flow generation step, the discharge of the gas from the discharge outlet is weaker on the edge portion of the sheet-shaped object than portions of the sheet-shaped object other than the edge

portion, and

(35) the suction of the gas through the suction inlet is weaker on the surface of the edge portion than on the surface of portions of the sheet-shaped object other than the edge portion.

(36) Due to this configuration, in the process of conveyance of the sheet-shaped object, at an edge portion of a sheet-shaped object with a shape with protruding parts continuously arranged at certain intervals along the conveyance direction, the surface of a sheet-shaped object is dedusted by blowing a gas in a weaker manner compared to that of the other portions and drawing in the gas from above the surface of the edge portion in a weaker manner than that above the surface of the other portions. Due to this, the protruding parts can be kept from bending or being damaged during dedusting of the surface of the sheet-shaped object due to the being blown or drawn in.

Advantageous Effects of Invention

(37) According to the dust removal device according to the present invention, when blowing a gas on a surface of a sheet-shaped object being conveyed and drawing in the gas above the surface so as to dedust the surface of the sheet-shaped object, the gas can be blown on the edge portion of the sheet-shaped object at a strength appropriate for the form of the edge portion and different from that of the other portions, and the gas can be drawn in from above the surface of the edge portion of the sheet-shaped object at a strength appropriate for the form of the edge portion and different from that of the other portions. For this reason, when a sheet-shaped object having an edge portion with a shape with protruding parts continuously arranged at certain intervals along the longitudinal direction is being conveyed in the longitudinal direction while the surface of the sheet-shaped object is being dedusted, the protruding parts of the edge portion can be kept from bending or being damaged due to the gas discharged from the discharge outlets or the gas being drawn in through the suction inlets, and the surface of the sheet-shaped object having an edge portion with a shape with protruding parts continuously arranged at certain intervals along the longitudinal direction can be properly dedusted.

(38) According to the dust removal device and dust removal method according to the present invention, when a sheet-shaped object having an edge portion with a shape with protruding parts continuously arranged at certain intervals along the longitudinal direction is being conveyed in the longitudinal direction while the surface of the sheet-shaped object is being dedusted, a gas is blown to the edge portion of the sheet-shaped object in a weaker manner than the other portions, and the gas is drawn in from above the surface of the edge portion in a weaker manner than above the surface of the other portions. Due to this, the protruding parts can be kept from bending or being damaged due to the gas being blown or being drawn in during dedusting of the surface of the sheet-shaped object, and the surface of the sheet-shaped object having an edge portion with a shape with protruding parts continuously arranged at certain intervals along the longitudinal direction can be normally dedusted.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a view showing an electrode film as one example of a sheet-shaped object to be dedusted.

(2) FIG. 2 is a view showing a stacked state of single electrode films cut out from the electrode film shown in FIG. 1.

(3) FIG. 3 is a view showing a battery unit formed from a plurality of the single electrode film pieces stacked as shown in FIG. 2.

(4) FIG. 4 is a perspective view showing a dust removal device according to a first embodiment of the present invention.

(5) FIG. 5 is a side view showing the dust removal device according to the first embodiment of the

present invention.

(6) FIG. 6 is a plan view showing the dust removal device according to the first embodiment of the present invention.

(7) FIG. 7 is a front view showing the dust removal device according to the first embodiment of the present invention.

(8) FIG. 8 is a (first) disassembled perspective view showing the structure of the dust removal device according to the first embodiment of the present invention.

(9) FIG. 9 is a (second) disassembled perspective view showing the structure of the dust removal device according to the first embodiment of the present invention.

(10) FIG. 10 is a bottom view showing the dust removal device according to the first embodiment of the present invention.

(11) FIG. 11 is a cross-sectional view showing a cross-section of the dust removal device taken along the A-A line in FIG. 6, FIG. 7, and FIG. 10.

(12) FIG. 12 is a cross-sectional view showing a cross-section of the dust removal device taken along the B-B line in FIG. 6, FIG. 7, and FIG. 10.

(13) FIG. 13 is a view showing enlarged a relative positional relationship between the sheet-shaped object being dedusted and the discharge outlets and suction inlets of the dust removal device.

(14) FIG. 14 is a side view showing a dust removal device according to a second embodiment of the present invention.

(15) FIG. 15 is a bottom view showing the dust removal device according to the second embodiment of the present invention.

(16) FIG. 16 is a view showing the principle behind how the sheet-shaped object (tabs) flips up due to air discharged from the discharge outlet.

(17) FIG. 17 is a bottom view showing a dust removal device according to a third embodiment of the present invention.

(18) FIG. 18 is a partially cutaway bottom view showing partially enlarged the dust removal device according to the third embodiment of the present invention.

(19) FIG. 19 is a cross-sectional view showing a cross-section of the dust removal device taken along the A-A line in FIG. 18.

(20) FIG. 20 is a cross-sectional view showing enlarged a gas discharge path to a second discharge outlet (slit).

(21) FIG. 21 is a line graph showing the discharge pressure of air discharged from the second discharge outlet (slit).

(22) FIG. 22 is a bottom view showing a modification of the dust removal device according to the third embodiment.

(23) FIG. 23 is a bottom view showing another modification of the dust removal device according to the third embodiment.

(24) FIG. 24 is a view showing a modification of the second discharge outlet.

DESCRIPTION OF EMBODIMENTS

(25) Below, embodiments of the present invention will be explained using the drawings.

(26) A dust removal device according to a first embodiment of the present invention is shown in FIG. 4 to FIG. 13. Note that FIG. 4 is a perspective view showing the dust removal device, FIG. 5 is a side view showing the dust removal device, FIG. 6 is a plan view showing the dust removal device, and FIG. 7 is a front view showing the dust removal device. Further, FIG. 8 and FIG. 9 are respectively disassembled perspective views showing the dust removal device, and FIG. 10 is a bottom view showing the dust removal device. Moreover, FIG. 11 is a cross-sectional view showing a cross-section of the dust removal device taken along the A-A line in FIG. 6, FIG. 7, and FIG. 10, and FIG. 12 is a cross-sectional view showing a cross-section of the dust removal device taken along the B-B line in FIG. 6, FIG. 7, and FIG. 10. FIG. 13 is a view showing enlarged the relative positional relationship between the sheet-shaped object being dedusted and the discharge

outlet and suction inlet of the dust removal device.

(27) In FIG. 4 and FIG. 5, the sheet-shaped object **100** to be dedusted is wound over a conveyance roller **15** serving as a support part and conveyed in the longitudinal direction (conveyance direction Dcv) by rotation of the conveyance roller in a stretched state in which tension is applied. This sheet-shaped object **100** is, for example, an electrode film used in the production of a secondary battery in the same way as the above-described example (see FIG. 1 to FIG. 3). The shape of the edge portion **100b** continuing from the sheet body **100a** in the width direction is one where a plurality of tabs **101** (protruding parts) are continuously arranged at predetermined intervals along the longitudinal direction. Note that no tension is applied to the tabs **101** (edge portion **100b**) of the sheet-shaped object **10** conveyed by the conveyance roller **15**.

(28) The dust removal device **10** is arranged facing the surface of the sheet-shaped object **100** wound over the conveyance roller **15** (see FIG. 4 and FIG. 5). Further, as shown in FIG. 6 and FIG. 7 together with FIG. 4 and FIG. 5, the dust removal device **10** is provided with an elongated block-shaped dedusting head **11** which extends in the rotational axis direction of the conveyance roller (the width direction of the sheet-shaped object **100**, a direction perpendicular to the conveyance direction Dcv of the sheet-shaped object **100**, and the traverse direction in FIG. 6 and FIG. 7) and an exhaust duct unit **13** which extends along the upper surface of the dedusting head **11**. The exhaust duct unit **13** has a bottom which is open and a flange **13a** which is formed at the opening edge portion. The flange **13a** of the exhaust duct unit **13** is fastened to the upper surface of the dedusting head **11** by a plurality of bolts, whereby the dedusting unit **11** and the exhaust duct unit **13** are integrally joined and the inside of the exhaust duct unit **13** is formed with a space serving as an exhaust path. An exhaust port **14** is provided on a side surface of the exhaust duct unit **13**. The exhaust port **14** is connected to a suction mechanism (for example, a vacuum pump: not shown). By operation of the suction mechanism, air passing through the exhaust path of the exhaust duct unit **13** is discharged to the outside through the exhaust port **14**.

(29) A supply port **12** is provided at a side surface of the dedusting head **11**. The supply port **12** connects to a supply mechanism for supplying pressurized air (for example, a pressurizing pump: not shown). By operation of the supply mechanism, pressurized air is introduced into the dedusting head **11** (later explained ejection chamber **20**) through the supply port **12**. Further, the dedusting head **11** is provided with a supply pipe **16** which is inserted from the side surface. The supply pipe **16** is also connected to an outside supply mechanism (not shown). Pressurized air is introduced by operation of the supply mechanism. Note that the supply mechanism which is connected to the supply port **12** and the supply mechanism which is connected to the supply pipe **16** may be the same or may be different. At the surface of the dedusting head **11** facing the conveyance roller **15**, a guide plate **17** (sheet pressing mechanism) is fixed so as to press the edge portion **100b** of the sheet-shaped object **100** at which the tabs **101** are formed toward the conveyance roller **15** (support part) so as to guide the edge portion **100b** along the conveyance roller **15**.

(30) The dedusting head **11**, as shown in FIG. 8 and FIG. 9 together with FIG. 4 to FIG. 7, has a structure where a head block **11a** and a suction regulating plate **11b** are superposed. The head block **11a** is formed with, as spaces opening at the surface joined to the suction regulating plate **11b**, an ejection chamber **20**, front side first air suction chamber **21**, rear side first air suction chamber **22**, front side second air suction chamber **23**, and rear side second air suction chamber **24**. The air ejection chamber **20** extends in the longitudinal direction at the center of the head block **11a** in the width direction. The front side first air suction chamber **21** and front side second air suction chamber **23** which extend in the longitudinal direction of the head block **11a** are arranged aligned along the front side edge of the head block **11a** (corresponding to the upstream side of the sheet-shaped object **100** in the conveyance direction Dcv). The rear side first air suction chamber **22** and rear side second air suction chamber **24** which extend in the longitudinal direction of the head block **11a** are arranged aligned along the rear side edge of the head block **11a** (corresponding to the downstream side of the sheet-shaped object **100** in the conveyance direction Dcv). The front side

second air suction chamber **23** and rear side second air suction chamber **24** are respectively shorter than the front side first air suction chamber **21** and the rear side first air suction chamber **22**. Their lengths generally correspond to the width of the edge portion **100b** of the sheet-shaped object **100** to be dedusted on which the tabs **101** are formed (see FIG. 1). Further, the lengths of the front side first air suction chamber **21** and the rear side first air suction chamber **22** generally correspond to the width of the sheet body **100a** of the sheet-shaped object **100** (see FIG. 1).

(31) At the suction regulating plate **11b**, respectively passing through the same, front side first suction regulating holes **25** and rear side first suction regulating holes **26** constituted by pluralities of elongated holes and front side second suction regulating holes **27** and rear side second suction regulating holes **28** constituted by pluralities of small holes are formed. In addition, the total opening areas of the front side second suction regulating holes **27** and the rear side second suction regulating holes **28** are smaller than the total opening areas of the front side first suction regulating holes **25** and the rear side first suction regulating holes **26**. The head block **11a** and suction regulating plate **11b** are fixed together in a superposed state by a plurality of bolts together with the above-described exhaust duct unit **13** (flange **13a**). When the head block **11a** and the suction regulating plate **11b** are superposed in this way, the front side first air suction chamber **21** of the head block **11a** and the front side first suction regulating holes **25** of the suction regulating plate **11b** face each other, while the front side second air suction chamber **23** of the head block **11a** and the front side second suction regulating holes **27** of the suction regulating plate **11b** face each other. Further, the rear side first air suction chamber **22** of the head block **11a** and the rear side first suction regulating holes **26** of the suction regulating plate **11b** face each other, while the rear side second air suction chamber **24** of the head block **11a** and the rear side second suction regulating holes **28** of the suction regulating plate **11b** face each other. In addition, in the state where the head block **11a** and the suction regulating plate **11b** are superposed, the air ejection chamber **20** of the head block **11a** is closed by the suction regulating plate **11b**.

(32) As shown in FIG. 10 together with FIG. 4 to FIG. 9, the surface of the dedusting head **11** (head block **11a**) facing the conveyance roller **15** is formed with a slit-shaped first discharge outlet **30** extending in the longitudinal direction at the center in the width direction. Further, the surface is formed with an elongated rectangular front side first suction inlet **31** along the front side edge and is formed with an elongated rectangular rear side first suction inlet **32** along the rear side edge. In the state where the sheet-shaped object **100** is being conveyed by the conveyance roller **15**, the first discharge outlet front side first suction inlet **31**, and rear side first suction inlet **32** which are aligned at the dust removal device **10** in the conveyance direction Dcv at predetermined intervals face the sheet body **100a** of the sheet-shaped object **100**.

(33) In addition, as shown in FIG. 11, the first discharge outlet **30** communicates with the air ejection chamber **20** formed on the head block **11a**, and the pressurized air introduced from the supply port **12** to the air ejection chamber **20** (supply path for air) is discharged from the first discharge outlet **30**. Further, the front side first suction inlet **31** communicates with the space in the exhaust duct unit **13** (exhaust path) through the front side first air suction chamber **21** formed on the head block **11a** and the front side first suction regulating holes **25** formed on the suction regulating plate **11b**. Further, the rear side first suction inlet **32** communicates with the space in the exhaust duct unit **13** through the rear side first suction chamber **22** formed at the head block **11a** and the rear side first suction regulating holes **26** formed at the suction regulating plate **11b**. Along with air passing through the exhaust path (space) in the exhaust duct unit **13** being discharged to the outside through the exhaust port **14**, air is drawn in to the front side first suction inlet **31** and the rear side first suction inlet **32** which communicate with the space in the exhaust duct unit **13**.

(34) Returning to FIG. 10, at the guide plate **17** fixed to the surface of the dedusting head **11** (head block **11a**) facing the conveyance roller **15**, a front side second suction inlet **33** is formed aligned with the front side first suction inlet **31** in the longitudinal direction. The front side second suction inlet **33** is constituted by a plurality of small holes aligned on a straight line. The total opening area

per unit length is smaller than the opening area per unit length of the front side first suction inlet **31**. Further, at the guide plate **17**, the rear side second suction inlet **34** is formed aligned with the rear side first suction inlet **32** in the longitudinal direction. The rear side second suction inlet **34** is constituted by a plurality of small holes aligned on a straight line in the same way as the front side second suction inlet **33**. The total opening area per unit length is smaller than the opening area per unit length of the rear side first suction inlet **32**.

(35) In addition, as shown in FIG. **12**, the front side second suction inlet **33** formed on the guide plate **17** communicates with the space in the exhaust duct unit **13** (exhaust path) through the front side second air suction chamber **23** formed on the head block **11a** and the front side second suction regulating holes **27** formed on the suction regulating plate **11b**. Further, the rear side second suction inlet **34** formed on the guide plate **17** communicates with the space in the exhaust duct unit **13** through the rear side second air suction chamber **24** formed on the head block **11a** and the rear side second suction regulating holes **28** formed on the suction regulating plate **11b**. Along with air passing through the space in the exhaust duct unit **13** (exhaust path) being discharged to the outside through the exhaust port **14**, air is drawn in through the front side second suction inlet **33** and the rear side second suction inlet **34** which communicate with the space in the exhaust duct unit **13**.

(36) As shown in FIG. **10** and FIG. **12**, the supply pipe **16** is inserted into the head block **11a** of the dedusting head **11**. The closed end reaches the vicinity of the edge of the guide plate **17**. A second discharge outlet **35** is formed on the guide plate **17** at a predetermined position between the front side second suction inlet **33** and the rear side second suction inlet **34** but nearer to the front side second suction inlet **33** and parallel to the same. The second discharge outlet **35** is constituted by a plurality of small holes aligned on a straight line. The total opening area per unit length is smaller than the opening area per unit length of the first discharge outlet **30**. In addition, the second discharge outlet **35** formed at the guide plate **17** communicates with the supply pipe **16** inserted in the head block **11a**. The pressurized air introduced into the supply pipe **16** (other supply path for air) is discharged from the second discharge outlet **35**.

(37) The dust removal device **10** with the above-described structure dedusts the sheet-shaped object **100** in the following manner.

(38) The sheet-shaped object **100** is conveyed by rotation of the conveyance roller **15** in a state in which a certain tension is applied to the sheet body **100a**. When the sheet-shaped object **100** conveyed in this way passes through the dust removal device **10**, as shown in FIG. **13** along with FIG. **4** and FIG. **5**, the edge portion **100b** of the sheet-shaped object **100** where tabs **101** are continuously arranged is guided by the guide plate **17** along the conveyance roller **15** and moved while being pressed down toward the conveyance roller **15**.

(39) In the dust removal device **10**, due to the difference in the opening area per unit length of the first discharge outlet **30** and the second discharge outlet **35** and the difference in shape of the air ejection chamber **20** of the supply path to the first discharge outlet **30** and the supply pipe **16** of the air supply path to the second discharge outlet **35**, the strength of air discharge from the second discharge outlet **35** is weaker than the strength of air discharge from the first discharge outlet **30**. Further, due to the difference in the opening area per unit length of the front side first suction inlet **31** and rear side first suction inlet **32** and the front side second suction inlet **33** and rear side second suction inlet **34** and the difference in the opening area per unit length of the front side first suction regulating holes **25** and rear side first suction regulating holes **26** of the suction regulating plate **11b** and the front side second suction regulating holes **27** and rear side second suction regulating holes **28**, the strength of air suction through the front side second suction inlet **33** and the rear side second suction inlet **34** is weaker than the strength of air suction through the front side first suction inlet **31** and the rear side first suction inlet **32**.

(40) In addition, in the process of movement of the sheet-shaped object **100**, air discharged in a comparatively strong manner from the first discharge outlet **30** of the dust removal device **10** is blown mainly to the surface of the sheet body **100a** of the sheet-shaped object **100** while air above

the surface of the sheet body **100a** is drawn in through the front side first suction inlet **31** and rear side first suction inlet **32** in a comparatively strong manner (flow generation step). Dust dislodged mainly from the surface of the sheet body **100a** by air from the first discharge outlet **30** is drawn in together with air through the front side first suction inlet **31** and rear side suction inlet **32**. Due to this, mainly the surface of the sheet body **100a** of the sheet-shaped object **100** is dedusted.

(41) Further, the edge portion **100b** of the sheet shape **100** which is pressed down toward the conveyance roller **15** and guided along the conveyance roller **15** by the guide plate **17** when the sheet-shaped object **100** is moving, as shown in FIG. **13**, moves while facing the front side second suction inlet **33**, second discharge outlet **35**, and rear side second suction inlet **34**. During this process, air discharged in a comparatively weak manner from the second discharge outlet **35** is blown to the surface of the edge portion **100b** of the sheet-shaped object **100** while air above the surface of the edge portion **100b** of the sheet-shaped object **100** is drawn in through the front side second suction inlet **33** and rear side second suction inlet **34** in a comparatively weak manner (flow generation step). The dust dislodged by air from the second discharge outlet **35** from the surfaces of the tabs **101** (edge portion **100b**) of the sheet-shaped object **100** pressed down by the guide plate **17** is drawn in together with air through the front side second suction inlet **33** and rear side second suction inlet **34**. Due to this, the surfaces of the tabs **101** (edge portion **100b**) of the sheet-shaped object **100** are dedusted without the tabs flapping, bending, or being sucked into the suction inlets **33**, **34**.

(42) According to the above-described dust removal device **10**, it is possible to reliably dedust mainly the sheet body **100a** of the sheet-shaped object **100** using air discharged in a relatively strong manner from the first discharge outlet **30** and comparatively strong suction of air through the front side first suction inlet **31** and rear side first suction inlet **32**. On the other hand, the edge portion **100b** of the sheet-shaped object **100**, unlike the sheet body **100a**, is subjected to air discharge and suction at a strength appropriate for the form of the edge portion **100b** (form of arrangement of tabs **101** (protruding parts)), specifically, comparatively weak air discharge from the second discharge outlet and comparatively weak air suction through the front side second suction inlet **33** and rear side second suction inlet **34**. This makes it possible to keep the tabs **101** of the edge portion **100b** of the sheet-shaped object **100** from flapping, bending, or being sucked into the suction inlets. Further, because the edge portion **100b** constituted by the continuous tabs **101** is guided along the conveyance roller **15** and pressed down toward the conveyance roller **15** by the guide plate **17** while the sheet-shaped object **100** is being conveyed, the tabs **101** of the edge portion **100b** of the sheet-shaped object **100** are more reliably kept from flapping, bending, or being sucked into the suction inlets. The combination of the effects of an appropriate degree of air discharge and suction and the guide plate **17** pressing down on the conveyance roller **15** allows the edge portion **100b** of the sheet-shaped object **100** to be reliably dedusted normally.

(43) In the above-described dust removal device according to the first embodiment, two suction inlets (front side first suction inlet **31**, rear side first suction inlet **32**) are provided sandwiching the first discharge outlet **30**, but the present invention is not limited to this. Just one suction inlet of these may be provided as well. Further, in such a case, either the front side second suction inlet **33** or the rear side second suction inlet **34** may be provided.

(44) Note that the shapes of the second discharge outlet **35**, front side second suction inlet **33**, and rear side second suction inlet **34** are not limited to those described above. For example, these may be arranged in a non-parallel manner. Further, each may be constituted by a single hole, a plurality of small holes arranged in a separately dispersed manner, etc.

(45) In the first embodiment described earlier, a guide plate **17** was provided, but the guide plate **17** may be omitted. In this case, for example, the embodiment is configured like the dust removal device according to a second embodiment.

(46) The dust removal device according to the second embodiment of the present invention is configured as shown in FIG. **14** and FIG. **15**. The dust removal device according to the second

embodiment differs from the dust removal device according to the first embodiment (see FIG. 4 to FIG. 13) on the point that the guide plate 17 is omitted, the point that the second discharge outlet constituted by a plurality of small holes arranged on one straight line is directly formed at the supply pipe 16, and the point that the surface of the supply pipe 16 at which the second discharge outlet 35 is formed is exposed from the surface of the head block 11a of the dedusting head 11 facing the conveyance roller 15.

(47) In this dust removal device, in the same way as the first embodiment, it is possible to reliably dedust mainly the sheet body 100a of the sheet-shaped object 100 by air relatively strongly discharged from the first discharge outlet 30 and comparatively strong air suction through the front side first suction inlet 31 and rear side first suction inlet 32. On the other hand, the edge portion 100b of the sheet-shaped object 100, unlike the sheet body 100a, is subjected to air discharge and suction at a strength appropriate for the form of the edge portion 100b (form in which tabs 101 (protruding parts) are arranged), specifically comparatively weak air discharge from the second discharge outlet 35 formed at the portion of the supply pipe 16 exposed from the surface of the head block 11a and comparatively weak air suction through the front side second suction inlet 33 and rear side second suction inlet 34 formed on the surface of the head block 11a. Due to this, the edge portion 100b of the sheet-shaped object 100 can be properly dedusted without the tabs 101 of the edge portion 100b of the sheet-shaped object 100 flapping, bending, or being sucked into the suction inlets.

(48) Further, the supply pipe 16 is capable of being turned about the direction it extends in when inserted in the head block 11a. By turning the supply pipe 16, the direction of air discharged from the second suction inlet 35 can be adjusted. By this adjustment, air can be blown from a direction appropriate for normal dedusting to the edge portion 100b (continuous tabs 101) of the sheet-shaped object 100.

(49) In this regard, as shown in FIG. 16, the high speed flow of air discharged from the discharge outlet O (opening) of the dust removal device 10 (see the solid arrow in FIG. 16) causes the static pressure of the region along the flow to fall and enables a negative pressure BA to be obtained (Bernoulli effect). If a negative pressure BA is produced in the region along the flow of discharged air in this way, when the tabs 101 of the edge portion 100b of the sheet-shaped object 100 being conveyed by the conveyance roller enter the region facing the discharge outlet O, the front end portions of the tabs 101 end up being lifted up by the negative pressure BA. If the front end portions of the tabs 101 are lifted up even slightly in this way, the discharged air will enter the gaps causing the tabs 101 to suddenly flip up. As a result, the edge portion 100b (tabs 101) of the sheet-shaped object 100 cannot be appropriately dedusted.

(50) A dust removal device according to a third embodiment of the present invention, in consideration of these circumstances, is configured so that the tabs 101 (edge portion 100b) of the sheet-shaped object 100 being conveyed are kept from flipping up due to the negative pressure caused by the above-described Bernoulli effect.

(51) The dust removal device according to the third embodiment of the present invention 10 is configured as shown in FIG. 17 to FIG. 19. FIG. 17 is a bottom view showing the dust removal device, FIG. 18 is a partially cutaway bottom view showing partially enlarged the dust removal device, and FIG. 19 is a cross-sectional view showing a cross-section of the dust removal device taken along the A-A line in FIG. 18. The dust removal device according to the third embodiment differs from the dust removal device according to the first embodiment on the point that the second discharge outlet 40 is constituted by a plurality of slits 40a (see FIG. 4 to FIG. 13), and the structure for supplying high pressure air to the plurality of slits 40a of the second discharge outlet 40 and the structure for fixing the guide plate 17 to the dedusting head 11 differ from those of the dust removal device according to the first embodiment.

(52) In FIG. 17 and FIG. 18, at the surface of the dedusting head 11 (head block 11a) facing the conveyance roller 15 (sheet-shaped object 100 (tabs 101)), in the same way as the dust removal

device according to the first embodiment (see FIGS. **10** and **15**), a first discharge outlet **30**, front side first suction inlet **31**, and rear side first suction inlet **32** which extend in the longitudinal direction are formed. A first supply port **12a** and a second supply port **12b** are formed in the dedusting head **11** (head block **11a**). High pressure air introduced through the first supply port **12a** to the dedusting head **11** (head block **11a**) is, in the same way as the dust removal device **10** according to the first embodiment (see FIG. **11**), discharged from the first discharge outlet **30**. Further, in the same way as the dust removal device **10** according to the first embodiment, along with air of the exhaust duct unit **13** being discharged to the outside through the exhaust port **14**, air is drawn in through the front side first suction inlet **31** and the rear side first suction inlet **32**.

(53) In the dust removal device according to the third embodiment **10**, in particular, at the surface of the dedusting head **11** (head block **11a**) facing the conveyance roller **15**, the second discharge outlet **40** constituted by a plurality of slits **40a** is formed aligned with the first discharge outlet **30** in the direction it extends. The plurality of slits **40a** constituting the second discharge outlet **40** are arranged at predetermined intervals in the longitudinal direction of the dedusting head **11** of a direction traversing the conveyance direction Dcv of the sheet-shaped object **100** (direction perpendicular to the conveyance direction Dcv). Further, each of the plurality of slits **40a** extends in a direction traversing the direction of arrangement (longitudinal direction of the dedusting head **11** of the width direction of the sheet-shaped object **100**) and inclines obliquely to the conveyance direction Dcv of the sheet-shaped object **100**. Further, from the second supply port **12b**, as shown enlarged in FIG. **18**, a supply path **41** extends inside the dedusting head **11** (head block **11a**) toward each of the plurality of slits **40a** of the second discharge outlet **40**. In addition, high pressure air introduced from the second supply port **12b** passes through the supply path **41** and is discharged from each of the plurality of slits **40a** of the second discharge outlet **40** (details will be explained later).

(54) Further, as shown in FIG. **19** along with FIG. **17** and FIG. **18**, in the dedusting head **11**, the guide plate **17** is fixed by a fixation block **18**. The guide plate **17** presses down the tabs **101** (edge portion **100b**) of the sheet-shaped object **100** being conveyed by the rotating conveyance roller **15** toward the conveyance roller **15** side and guides them along the conveyance roller **15**.

(55) As shown in FIG. **19**, the front side second suction inlet **33** constituted by a plurality of small holes communicates with the exhaust duct unit **13** through the front side second air suction chamber **23** and front side suction regulating holes **27** of the dedusting head **11**. Further, the rear side second suction inlet **34** constituted by a plurality of small holes communicates with the exhaust duct unit **13** through the rear side second air suction chamber **24** and rear side suction regulating holes **28** of the dedusting head **11**. Due to this, along with air of the exhaust duct unit **13** being discharged to the outside through the exhaust port **14**, air is drawn in through the front side second suction inlet **33** and rear side second suction inlet **34**.

(56) Further, each of the plurality of slits **40a** constituting the second discharge outlet **40** communicates with the supply path **41**. In more detail, as shown in FIG. **20**, a connecting path **42a** extending from the supply path **41** connects through an opening **43** to a gas discharge path **42b** leading to each slit **40a**. A cross-section of the gas discharge path **42b** taken vertical to the slit **40a** (the cross-section shown in FIG. **20** taken along the A-A line in FIG. **18**) has a shape which gradually expands from the opening **43** to the slit **40a**, specifically, a shape that expands gradually to in an arc shape.

(57) In the above-described dust removal device according to the third embodiment **10**, in the same way as the first embodiment, it is possible to reliably dedust mainly the sheet body **100a** of the sheet-shaped object **100** using air discharged in a relatively strong manner from the first discharge outlet **30** and comparatively strong suction of air through the front side first suction inlet **31** and rear side first suction inlet **32**. On the other hand, the edge portion **100b** (tabs **101**) of the sheet-shaped object **100** is dedusted by air discharge from the plurality of slits **40a** of the second discharge outlet **40** and air suction through the front side second suction inlet **33** and rear side

second suction inlet **34**.

(58) The dedusting of the edge portion **100b** (tabs **101**) of the sheet-shaped object **100** will be explained in further detail.

(59) High pressure air running from the supply path **41** through the connecting path **42a**, as shown in FIG. **20**, runs through the gas discharge path **42b** which gradually expand from the opening **43** and is discharged from the slit **40a**. The discharge pressure of air discharged from the slit **40a** is distributed in the manner shown in FIG. **21**. That is, the discharge pressure P_{e1} of air running from the openings **43** along the inner peripheral walls of the gas discharge path **42b** and discharged from the upstream end part of the slit **40a** in the conveyance direction D_{cv} of the sheet-shaped object **100** (tabs **101**) being conveyed is lower than the discharge pressure P_c of air directly discharged from the portion of the slit **40a** facing the opening **43** without running along the inner peripheral wall of the gas discharge paths **42b**. Due to this, the pressure P_c of air discharged from the portions of the slit **40a** facing the opening **43** is kept at a desired pressure (lower than the discharge pressure from the first discharge outlet **30**) while the discharge pressure P_{e1} of air discharged from the upstream end part of the slit **40a** decreases.

(60) Due to the discharge pressure P_{e1} of air discharged from the upstream end part of the slit decreasing in this way, a negative pressure state caused by the Bernoulli effect becomes more difficult to produce at a region E_b facing the upstream end parts of the slit **40a**. Therefore, the tabs **101** of the sheet-shaped object **100** being conveyed are kept from flipping up due to a negative pressure state which could be produced by the Bernoulli effect when entering the region E_b facing the upstream end part of the slit **40a**, while dust sticking to the tabs **101** is reliably removed by air of the desired discharge pressure P_c discharged from the portion of the slit **40a** facing the opening **43**.

(61) Note that the discharge pressure P_{e2} of air discharged from the downstream end part of the slit **40a** (see FIG. **21**) also decreases in the same way. The tabs **101** of the sheet-shaped object **100** being conveyed are able to exit stably from a region facing the downstream end part of the slit without flapping.

(62) Further, in the above-described dust removal device **10**, when the tabs **101** of the sheet-shaped object **100** being conveyed enter the region E_b facing the upstream end parts of the plurality of slits **40a**, air of a certain discharge pressure P_{e1} is blown to the tabs **101** discretely from the plurality of slits **40a**. For this reason, when the tabs **101** of the sheet-shaped object **100** enter the region E_b facing the upstream end parts of the plurality of slits **40a**, discharged air will not act simultaneously on all of the front end portions of the tabs **101**. Accordingly, the tabs **101** can be reliably kept from flipping up due to air acting on the front end portions of the tabs **101** and in a state in which air of the desired discharge pressure P_c is discharged from the portions of the slits **40a** facing the openings **43**.

(63) Further, the plurality of slits **40a** constituting the second discharge outlet **40** incline obliquely to the conveyance direction D_{cv} of the sheet-shaped object **100** (tabs **101**), so when the tabs **101** of the sheet-shaped object **100** pass through the region facing the slits **40a**, the gas can be blown over a wider range on the tabs **101** from the discretely arranged plurality of slits **40a**.

(64) Note that the arrangement of the plurality of slits **40a** constituting the second discharge outlet **40** is not limited to the one described above (see FIG. **17** and FIG. **18**). For example, as shown in FIG. **22**, the plurality of slits **40a** may be arranged zig-zag in the width direction of the sheet-shaped object **100** (tabs **101**) being conveyed, that is, a direction traversing the conveyance direction of the sheet-shaped object **100** (perpendicular direction).

(65) Further, as shown in FIG. **23**, each of the plurality of slits **40a** constituting the second discharge outlet **40** can also be formed in a state overlapping adjacent slit **40a** in view in the conveyance direction D_{cv} of the sheet-shaped object **100** (tabs **101**). In this case, the gas can be blown with no gaps to the sheet-shaped object **100** (tabs **101**) from the discretely arranged plurality of slits **40a** during conveyance of the sheet-shaped object **100**. As a result, the surface of the sheet-

shaped object **100** (tabs **101**) can be reliably dedusted.

(66) Further, the configuration (shape) of the second discharge outlet **40** is not limited to the above-described plurality of slits **40a**. For example, as shown in FIG. **24**, the second discharge outlet can be formed as an elongated hole **45** extending in a direction traversing the conveyance direction Dcv of the sheet-shaped object **100** (tabs **101**) (for example, perpendicular direction), that is, in the width direction of the dedusting head **11**. In addition, in the dedusting head **11**, the connecting path **46a** extending from the supply path **41** connects through the opening **47** to a gas discharge path **46b** leading to the elongated hole. A cross-section of the gas discharge path **46b** taken vertical to the elongated hole **45** (shown by the broken line in FIG. **24**), in the same way as that described earlier (see FIG. **20**), has a shape which gradually expands from the opening **47** to the elongated hole **45**, specifically, a shape which gradually expands to in an arc shape.

(67) In a dust removal device **10** in which the second discharge outlet is constituted by an elongated hole **45** in this way, in the same way as described earlier, the discharge pressure of air running from the opening **47** along the inner peripheral wall of the gas discharge path **46b** and discharged from the upstream end part EG1 of the elongated hole **45** in the conveyance direction Dcv of the sheet-shaped object **100** (tabs **101**) being conveyed becomes lower than the discharge pressure of air directly discharged from the portion of the elongated hole **45a** facing the opening **47** without running along the inner peripheral wall of the gas discharge path **46b**. Due to this, the pressure of air discharged from the portion of the elongated hole **45** facing the opening **47** can be kept at a desired pressure (lower than the discharge pressure from the first discharge outlet **30**) while lowering the discharge pressure of air discharged from the upstream end part EG1 of the elongated hole **45**.

(68) Due to the discharge pressure of the gas discharged from the upstream end part EG1 of the elongated hole **45** (second discharge outlet) decreasing in this way, a negative pressure state caused by the Bernoulli effect becomes difficult to occur at a region Eb facing the upstream end part EG1 of the elongated hole **45** in the same way in the configuration described earlier. Therefore, the tabs **101** of the sheet-shaped object **100** being conveyed can be kept from flipping up due to a negative pressure state which can be produced by the Bernoulli effect when entering the region Eb facing the upstream end part EG1 of the elongated hole **45**, while dust sticking to the tabs **101** of the sheet-shaped object **100** being conveyed is reliably removed by the gas of the desired discharge pressure discharged from the portion of the elongated hole (second discharge outlet) facing the opening **47**. Note that the discharge pressure of air discharged from the downstream end part EG2 of the elongated hole also decreases in the same way and the tabs **101** of the sheet-shaped object **100** being conveyed are able to exit stably from the region facing the downstream end part EG2 of the elongated hole **45** without flapping.

(69) Further, note that if the second discharge outlet is constituted by an elongated hole **45** such as shown in FIG. **24**, unlike if the second discharge outlet **40** is constituted by a plurality of slits (see FIG. **17** to FIG. **20**), air discharged from the elongated hole **45** acts simultaneously on all of the front end portions of the tabs **101** of the sheet-shaped object **100** being conveyed when the tabs **101** enter the region Eb facing the upstream end part EG1 of the elongated hole **45**. Accordingly, considering this, it is necessary to adjust the discharge pressure of air discharged from the elongated hole **45** (discharge pressure of gas from the opening **47**).

(70) Note that the support part for supporting the sheet-shaped object **100** is not limited to a conveyance roller **15**, **55**. So long as it is something that the sheet-shaped object **100** being conveyed will contact, it may have a flat shape or may be one having a curved shape other than a cylindrical curve like that of the conveyance roller **15**, **55**. Further, the dust removal device **100** need not be arranged facing the support part supporting the sheet-shaped object **100** and may be arranged facing a surface portion of the sheet-shaped object **100** not particularly supported by the support part.

(71) Further, the sheet-shaped object to be dedusted may be a sheet-shaped object dispensed from a

roll or an unrolled sheet-shaped object.

(72) Further, the sheet-shaped object to be dedusted need only be one that is thin and wide enough to be influenced by the air flow through the discharge outlets and suction inlets and is not limited to a so-called sheet shape. Not only that, it may also be one called a film shape such as an electrode film used in the earlier described production of a secondary battery or may be one called a membrane shape.

(73) Above, embodiments of the present invention were explained, but these embodiments and modifications of parts were presented only as examples and are not intended to limit the scope of the invention. The new embodiments described above can be carried out in other various modes and can be subjected to various omissions, substitutions, or changes within a range that does not depart from the gist of the invention. These embodiments and modifications are encompassed by the scope and gist of the invention and by the inventions set forth in the claims

INDUSTRIAL APPLICABILITY

(74) The dust removal device and dust removal method according to the present invention have the effect of being able to properly dedust the surface of a sheet-shaped object having an edge portion of a shape with protruding parts (tabs) continuously arranged at certain intervals along the longitudinal direction and are useful as a dust removal device and dust removal method for discharging a gas to the surface of the sheet-shaped object to be conveyed while drawing the gas above the surface of the sheet-shaped object so as to remove dust from the surface of the sheet-shaped object.

REFERENCE SIGNS LIST

(75) **10** dust removal device **11** dedusting head **11a** head block **11b** suction regulating plate **12** supply port **12a** first air supply port **12b** second suction port **13** exhaust duct unit **13a** flange **14** exhaust port **15** conveyance roller **16** supply pipe **17** guide plate **18** guide fixation block **20** ejection chamber **21** front side first air suction chamber **22** rear side first air suction chamber **23** front side second air suction chamber **24** rear side second air suction chamber **25** front side first suction regulating hole **26** rear side first suction regulating hole **27** front side second suction regulating hole **28** rear side second suction regulating hole **30** first discharge outlet **31** front side first suction inlet **32** rear side first suction inlet **33** front side second suction inlet **34** rear side second suction inlet **35** second discharge outlet **40** second discharge outlet **40a** slit **41** supply path **42a**, **46a** connecting path **42b**, **46b** gas discharge path **43**, **47** opening **45** elongated hole **100** sheet-shaped object **100a** sheet body **100b** edge portion **101** tabs (protruding part)

Claims

1. A dust removal device that dusts a sheet-shaped object having an edge portion with a shape with protruding parts continuously arranged at certain intervals in the longitudinal direction and is provided with a discharge outlet and suction inlet facing the surface of the sheet-shaped object being conveyed and arranged at a predetermined interval along the conveyance direction of the sheet-shaped object and that discharges a gas from the discharge outlet to the surface of the sheet-shaped object while drawing in the gas above the surface of the sheet-shaped object through the suction inlet, wherein the discharge outlet includes a first discharge outlet which discharges the gas to a portion of the sheet-shaped object other than an edge portion in the width direction and a second discharge outlet which is separated from the first discharge outlet and discharges the gas to the edge portion of the sheet-shaped object more weakly than the first discharge outlet discharges the gas, and the suction inlet includes a first suction inlet which draws in the gas above the surface of the portion of the sheet-shaped object other than the edge portion, and a second suction inlet which is separated from the first suction inlet and draws in the gas above the surface of the edge portion of the sheet-shaped object more weakly than the first suction inlet draws in the gas.
2. The dust removal device according to claim 1 wherein a supply path for the gas discharged from

the first discharge outlet and a supply path for the gas discharged from the second discharge outlet differ.

3. The dust removal device according to claim 1 wherein the opening area per unit length of the second discharge outlet is smaller than the opening area per unit length of the first discharge outlet.

4. The dust removal device according to claim 3 wherein the second discharge outlet includes a plurality of small holes aligned in a direction traversing the conveyance direction of the sheet-shaped object.

5. The dust removal device according to claim 1 having a gas discharge path with a shape that gradually expands from an opening facing the sheet-shaped object being conveyed to the second discharge outlet.

6. The dust removal device according to claim 5 wherein a cross-section of the gas discharge path taken perpendicular to the sheet-shaped object being conveyed has a shape which gradually expands in an arc shape.

7. The dust removal device according to claim 1 wherein the second discharge outlet includes a plurality of slits which are arranged in a direction traversing the conveyance direction of the sheet-shaped object with each slit extending in a direction traversing the arrangement direction, and the dust removal device having a gas ejection path which is provided for each of the plurality of slits and extends from an opening facing the sheet-shaped object to the slit, and wherein a cross-section of the gas ejection path taken vertical to each slit has a shape which gradually expands from the opening to the slit.

8. The dust removal device according to claim 7 wherein the shape of the cross-section gradually expands in an arc shape.

9. The dust removal device according to claim 7 wherein each of the plurality of slits is formed inclining obliquely to the conveyance direction of the sheet-shaped object.

10. The dust removal device according to claim 9 wherein each of the plurality of slits is formed in a state overlapping the adjacent slit in view in the conveyance direction of the sheet-shaped object.

11. The dust removal device of claim 7 wherein the plurality of slits are arranged in parallel.

12. The dust removal device of claim 7 wherein the plurality of slits are arranged zig-zag in a direction traversing the conveyance direction of the sheet-shaped object.

13. The dust removal device of claim 1 wherein the opening area per unit length of the second suction inlet is lower than the opening area per unit length of the first suction inlet.

14. The dust removal device according to claim 13 wherein the second suction inlet includes a plurality of small holes aligned in a direction traversing the conveyance direction of the sheet-shaped object.

15. A dust removal method for dedusting a sheet-shaped object having an edge portion with a shape with protruding parts continuously arranged at certain intervals in the longitudinal direction, the method using a dust removal device according to claim 1 which is provided with the discharge outlet and the suction inlet arranged facing the surface of the sheet-shaped object being conveyed and extending in a direction traversing the conveyance direction of the sheet-shaped object at a predetermined interval in the conveyance direction of the sheet-shaped object, and the method comprising: a flow generation step of discharging a gas from the discharge outlets to the surface of the sheet-shaped object while drawing in a gas above the surface of the sheet-shaped object through the suction inlets, where, in the flow generation step, the discharge of the gas from the discharge outlets is weaker on the edge portion of the sheet-shaped object than portions of the sheet-shaped object other than the edge portion, and the suction of the gas through the suction inlets is weaker on the surface of the edge portion than on the surface of portions of the sheet-shaped object other than the edge portion.

16. The dust removal method according to claim 15 using the dust removal device according to claim 1 in which the discharge outlet includes the first discharge outlet for discharging the gas to portions of the sheet-shaped object other than the edge portion and the second discharge outlet for

discharging the gas to the edge portion of the sheet-shaped object, and in which the suction inlet includes the first suction inlet which draws in the gas above the surface of portions of the sheet-shaped object other than the edge portion and the second suction inlet which draws in the gas above the surface of the edge portion of the sheet-shaped object, where, in the flow generation step, the discharge of the gas from the second discharge outlet is weaker than discharge of the gas from the first discharge outlet, and the suction of the gas by the second suction inlet is weaker than the suction of the gas by the first suction inlet.
