

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396614
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Yang; Wenyong et al.

Tableware washing apparatus and filtering device thereof

Abstract

A filtering device and a tableware washing apparatus, the filtering device includes a rotary filter and a drive assembly. The rotary filter includes a columnar filtering screen configured to filter water from a washing process of the tableware washing apparatus; wherein a diameter of an external circle defined by each mesh of the columnar filtering screen is between 0.2 to 0.5 mm. The drive assembly is connected to the rotary filter and configured to drive the columnar filtering screen to rotate relative to contents within the columnar filtering screen at a relative speed of 100 to 1000 r/min, for separating at least a portion of residue on the columnar filtering screen from the columnar filtering screen.

Inventors: Yang; Wenyong (Foshan, CN), Xue; Weijun (Foshan, CN), Lee; Seungjun (Foshan, CN)

Applicant: Guangdong Midea White Home Appliance Technology Innovation Center Co., Ltd. (Foshan, CN); Foshan Shunde Midea Washing Appliances Mfg. Co., Ltd. (Foshan, CN); Midea Group Co., Ltd. (Foshan, CN)

Family ID: 1000008780551

Assignee: Guangdong Midea White Home Appliance Technology Innovation Center Co., Ltd. (Foshan, CN); Foshan Shunde Midea Washing Appliances Mfg. Co., Ltd. (Foshan, CN); Midea Group Co., Ltd. (Foshan, CN)

Appl. No.: 18/089384

Filed: December 27, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230135406 A1	May. 04, 2023

Related U.S. Application Data

Publication Classification

Int. Cl.: **A47L15/42** (20060101); **A47L15/14** (20060101); **B01D29/05** (20060101); **B01D33/11** (20060101); **B01D33/46** (20060101); **B01D33/52** (20060101); **B01D33/74** (20060101); **B01D33/80** (20060101); **B01D35/30** (20060101)

U.S. Cl.:

CPC **A47L15/4206** (20130101); **A47L15/14** (20130101); **A47L15/4204** (20130101); **A47L15/4208** (20130101); **A47L15/4225** (20130101); **B01D29/05** (20130101); **B01D33/11** (20130101); **B01D33/466** (20130101); **B01D33/52** (20130101); **B01D33/742** (20130101); **B01D33/801** (20130101); **B01D35/30** (20130101);

Field of Classification Search

CPC: A47L (15/4206); A47L (15/14); A47L (15/4204); A47L (15/4208); A47L (15/4225); B01D (29/05); B01D (33/11); B01D (33/466); B01D (33/52); B01D (33/742); B01D (33/801); B01D (35/30); B01D (29/23); B01D (29/86); B01D (2201/583); B01D (29/6476)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2016/0096196	12/2015	Papke	427/180	C09D 159/02
2016/0100738	12/2015	Blanchard et al.	N/A	N/A
2016/0150941	12/2015	Fountain et al.	N/A	N/A
2017/0159228	12/2016	Lv et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101558985	12/2008	CN	N/A
105286751	12/2015	CN	N/A
105342536	12/2015	CN	N/A
105534443	12/2015	CN	N/A
107242841	12/2016	CN	N/A
108577758	12/2017	CN	N/A
209301058	12/2018	CN	N/A
209377515	12/2018	CN	N/A
209377516	12/2018	CN	N/A
110881932	12/2019	CN	N/A
1386575	12/2003	EP	A47L 15/4206

20000003391	12/1999	KR	N/A
20100037453	12/2009	KR	N/A
WO 2019168379	12/2018	WO	N/A

OTHER PUBLICATIONS

Midea Group Co., Ltd., Chinese Office Action, CN Patent Application No. 202080018005.0, Jun. 3, 2024, 5 pgs. cited by applicant

Midea Group Co., Ltd., Extended European Search Report and Supplementary Search Report, EP20953602.8, Jun. 27, 2023, 17 pgs. cited by applicant

Midea Group Co., Ltd., ISRWO, PCT/CN2020/115686, Jun. 2, 2021, 14 pgs. cited by applicant

Midea Group Co., Ltd., IPRP, PCT/CN2020/115686, Mar. 21, 2023, 1 pgs. cited by applicant

Primary Examiner: Ali; Waqaas

Attorney, Agent or Firm: Morgan, Lewis & Bockius LLP

Background/Summary

CROSS REFERENCE (1) The present disclosure is a continuation application of International (PCT) Patent Application No. PCT/CN2020/115686, filed on Sep. 16, 2020, the entire contents of which are hereby incorporated by reference in their entirety.

TECHNICAL FIELD

(1) The present disclosure relates to the field of kitchen appliances, and in particular to a tableware washing apparatus and a filtering device.

BACKGROUND

(2) In recent years, more and more consumers choose to use tableware washing apparatus. A filtration system is one of the core systems of a tableware washing apparatus, and the filtration system may ensure the filtering effect while saving energy.

(3) In the related art, two means are adopted to improve the filtering effect of the filtration system: increasing the filtering area, and dividing a filtering screen into a coarse filtering screen and a fine filtering screen. Such means may be prone to clogging the filtering screen, resulting in unclean dishes. Therefore, the filtering effect of the filtration system may still not be guaranteed through the above means.

SUMMARY OF THE DISCLOSURE

(4) The present disclosure provides a filtration device and a tableware washing apparatus having a filtration device.

(5) A first aspect of the present disclosure provides a filtering device of a tableware washing apparatus, including: a rotary filter, including a columnar filtering screen configured to filter to water from a washing process of the tableware washing apparatus; wherein a diameter of an external circle defined by each mesh of the columnar filtering screen is between 0.2 to 0.5 mm; and a drive assembly, connected to the rotary filter and configured to drive the columnar filtering screen to rotate relative to contents within the columnar filtering screen at a relative speed of 100 to 1000 r/min, for separating at least a portion of residue on the columnar filtering screen from the columnar filtering screen.

(6) A second aspect of the present disclosure provides a tableware washing apparatus, including: an inner liner; a spray arm, received in the inner liner; and the filtering device as above, received in the inner liner and communicated with the spray arm.

(7) The present disclosure may improve the filtration performance and filtration effect of the

filtering device by driving at least a portion of the rotary filter with a drive assembly to rotate the columnar filtering screen relative to the contents of the columnar filtering screen, and by setting the diameter of the outer circle defined by the mesh of the columnar filtering screen to collect the residue at the bottom of the columnar filtering screen and reduce the possibility of blocking the flow of water caused by the residue gathering on the filtering screen in the direction of the flow of to-be-filtered water. In addition, the water volume of the tableware washing apparatus may be increased when the water filtered by the filtering device is pumped to the inner liner, thereby reducing the washing time or the water used for a single washing, and may save energy.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) In order to more clearly illustrate the technical solutions in the embodiments of the present disclosure, the following is a brief description of the accompanying drawings to be used in the description of the embodiments. It is obvious that the accompanying drawings in the following description are only some of the embodiments of the present disclosure, and other accompanying drawings may be obtained on the basis of these drawings for those skilled in the art without creative labor.
- (2) FIG. 1 is a perspective structural schematic view of a filtering device according to an embodiment of the present disclosure.
- (3) FIG. 2 is an exploded schematic view of the filtering device in FIG. 1.
- (4) FIG. 3 is a perspective schematic view of a partial structure of the filtering device in FIG. 1 along a viewing angle direction.
- (5) FIG. 4 is a plan schematic view of the partial structure of the filtering device in FIG. 3 along a viewing angle direction.
- (6) FIG. 5 is a perspective schematic view of the partial structure of the filtering device in FIG. 3 along another viewing angle direction.
- (7) FIG. 6 is a plan schematic view of the partial structure of the filtering device in FIG. 3 along another viewing angle direction.
- (8) FIG. 7 is an enlarged schematic view of area A circumscribed in FIG. 6.
- (9) FIG. 8 is a cross-sectional schematic view of the filtering device along B-B in FIG. 6.
- (10) FIG. 9 is a perspective schematic view of the partial structure of the filtering device in FIG. 3 along another viewing angle direction.
- (11) FIG. 10 is an enlarged schematic view of area C circumscribed in FIG. 9.
- (12) FIG. 11 is a cross-sectional schematic view of the filtering device along D-D in FIG. 6.
- (13) FIG. 12 is a cross-sectional schematic view of a partial structure of a filtering device according to an embodiment of the present disclosure.
- (14) FIG. 13 is a cross-sectional schematic view of a partial structure of a filtering device according to an embodiment of the present disclosure.
- (15) FIG. 14 is an enlarged schematic view of area E circumscribed in FIG. 13.
- (16) FIG. 15 is a cross-sectional structural schematic view of a filtering device according to an embodiment of the present disclosure.
- (17) FIG. 16 is a perspective schematic view of a partial structure of a filtering device according to an embodiment of the present disclosure.
- (18) FIG. 17 is an exploded schematic view of the partial structure of the filtering device in FIG. 16.
- (19) FIG. 18 is a plan schematic view of a filtering device according to an embodiment of the present disclosure.
- (20) FIG. 19 is a cross-sectional schematic view of the filtering device along F-F in FIG. 18

according to an embodiment of the present disclosure.

(21) FIG. **20** is a perspective structural schematic view of a cleaning element according to an embodiment of the present disclosure.

(22) FIG. **21** is a perspective schematic view of a partial structure of a filtering device according to another embodiment of the present disclosure.

(23) FIG. **22** is a cross-sectional schematic view of a filtering device according to another embodiment of the present disclosure.

(24) FIG. **23** is a perspective structural schematic view of a pulsator in FIG. **22**.

(25) FIG. **24** is an exploded schematic view of a filtering device according to another embodiment of the present disclosure.

(26) FIG. **25** is a cross-sectional schematic view of the filtering device along F-F in FIG. **18** according to another embodiment of the present disclosure.

(27) FIG. **26** is a perspective structural schematic view of a rotary filter in FIG. **24** along a viewing angle direction.

(28) FIG. **27** is a perspective structural schematic view of a rotary filter in FIG. **24** along another viewing angle direction.

(29) FIG. **28** is a schematic view of a relationship between residue and water flow direction at a first moment using the filtering device in FIG. **24**.

(30) FIG. **29** is a schematic view of a relationship between residue and water flow direction at a second moment using the filtering device in FIG. **24**.

(31) FIG. **30** is a schematic view of a relationship between residue and water flow direction at a third moment using the filtering device in FIG. **24**.

(32) FIG. **31** is a schematic view of a relationship between residue and water flow direction at a fourth moment using the filtering device in FIG. **24**.

(33) FIG. **32** is a cooperation relationship schematic view between a drive accommodating portion and a drive assembly according to an embodiment of the present disclosure.

(34) FIG. **33** is a perspective structural schematic view of a drive accommodating portion according to an embodiment of the present disclosure.

(35) FIG. **34** is a plan schematic view of a filtering device according to another embodiment of the present disclosure.

(36) FIG. **35** is a cross-sectional schematic view of the filtering device along G-G in FIG. **34** according to an embodiment of the present disclosure.

(37) FIG. **36** is a perspective structural schematic view of a filtering device according to further another embodiment of the present disclosure along a viewing angle direction.

(38) FIG. **37** is a perspective structural schematic view of the filtering device in FIG. **36** along another viewing angle direction.

(39) FIG. **38** is a perspective structural schematic view of a filtering device according to further another embodiment of the present disclosure.

(40) FIG. **39** is a plan schematic view of a filtering device according to further another embodiment of the present disclosure.

(41) FIG. **40** is a cross-sectional schematic view of the filtering device along H-H in FIG. **39**.

(42) FIG. **41** is a cooperation relationship schematic view between a water wheel and a cleaning element according to an embodiment of the present disclosure.

(43) FIG. **42** is a schematic view of a partial structure of a tableware washing apparatus according to an embodiment of the present disclosure.

DETAILED DESCRIPTION

(44) The following will be a clear and complete description of the technical solutions in the embodiments of the present disclosure in conjunction with the accompanying drawings in the embodiments of the present disclosure. Obviously, the described embodiments are only a part of the embodiments of the present disclosure, and not all of them. Based on the embodiments in the

present disclosure, all other embodiments obtained by those skilled in the art without creative labor fall within the scope of the present disclosure.

(45) The terms “first” and “second” in the present disclosure are intended for descriptive purposes only, and are not to be construed as indicating or implying relative importance or implicitly specifying the number of technical features indicated. In the description of the present disclosure, “plurality” means at least two, such as two, three, etc., unless otherwise expressly and specifically limited. In addition, the terms “including” and “having”, and any variations thereof, are intended to cover non-exclusive inclusion. For example, a process, method, system, product, or apparatus including a series of steps or units is not limited to the listed steps or units, but optionally further includes steps or units that are not listed, or optionally further includes other steps or units that are inherent to the process, method, product, or apparatus. The term “and/or” is simply a description of the associated relationship of associated objects, indicating that three relationships may exist, for example, A and/or B, which may mean: A alone, both A and B, and B alone. In addition, the character “/” in this specification generally indicates that the associated objects before and after “/” is in an “or” relationship.

(46) As shown in FIGS. 1-2 and FIG. 32, embodiments of the present disclosure provide a filtering device **10** of a tableware washing apparatus. The filtering device **10** includes a water cup assembly **100**, a plane filter **200** arranged on the water cup assembly **100**, a rotary filter **300** at least partially inserted in the water cup assembly **100**, and a drive assembly **400** connected to the rotary filter **300**. Both the plane filter **200** and the rotary filter **300** are configured to filter water from a washing process of the tableware washing apparatus. The rotary filter **300** includes a columnar filtering screen **330**. Therefore, the water can either be filtered by the plane filter **200** and out of the water cup assembly **100**, or enter the columnar filtering screen **330** through an opening on the plane filter **200**, filtered by the columnar filtering screen **330**, and out of the water cup assembly **100**. The drive assembly **400** is configured to drive/cause the columnar filtering screen **330** to rotate at a relative speed of 100 to 1000 r/min relative to contents in the columnar filtering screen **330** (components received in an internal space enclosed by the columnar filtering screen **330**), for separating at least a portion of residue on the columnar filtering screen from the columnar filtering screen **330**. In some embodiments, the drive assembly **400** may cause the columnar filtering screen **330** to rotate relative to the contents in the columnar filtering screen **330** at a relative speed of 150 to 700 r/min. The columnar filtering screen **330** rotating relative to the contents in the columnar filtering screen **330** herein means that the columnar filtering screen **330** rotates by itself driven by the drive assembly **400**, or the contents in the columnar filtering screen **330** is rotatable driven by the drive assembly **400**.

(47) In some embodiments, the mesh count of meshes of the columnar filtering screen **330** is about 50 to 70 mesh. Specifically, the diameter of an external circle defined by each mesh of the columnar filtering screen **330** is about 0.2 to 0.5 mm, and the mesh spacing ranges from about 0.4 to 0.6 mm. In some embodiments, the diameter of the external circle defined by the mesh of the columnar filtering screen **330** is about 0.2 to 0.4 mm. In some embodiments, the diameter of the external circle defined by the mesh of the columnar filtering screen **330** may be 0.3 to 0.4 mm, and the mesh spacing may range from 0.6 to 1.0 mm. It can be understood that the mesh spacing herein may refer to a spacing between each adjacent meshes.

(48) Conventionally, the filtering device **10** of the tableware washing apparatus may filter residues with a minimum particle size of about 0.3 mm. In the related art, a combination of coarse filtration and fine filtration is usually adopted for filtering, for example, a mesh aperture of 0.8 mm may be applied for coarse filtration, followed by a mesh aperture of 0.3 mm for fine filtration to improve the filtering effect. However, in the filtering process, the problem of mesh clogging still easily occurs, which causes a poor filtering effect.

(49) To improve the filtering effect, in some embodiments of the present disclosure, the plane filter **200** and the rotary filter **300** are adopted to filter the water, and at least a portion of the rotary filter

300 is driven by the drive assembly **400** to rotate the columnar filtering screen **330** relative to the contents inside the columnar filtering screen **330** at a relative speed of 100 to 1000 r/min. The diameter of the external circle defined by the mesh of the columnar filtering screen **330** (hereinafter referred to as the “mesh aperture”) is about 0.2 to 0.5 mm.

(50) It is known from the related art that when the mesh aperture of the filtering screen is larger, more residue will leach out of the filtering screen, and therefore more residue may still be present in the filtered water. Therefore, in order to improve the filtering effect, the mesh aperture of the filtering screen is usually designed to be small. However, if the mesh aperture is too small, it is difficult to form an aggregation of the residue and the residue tends to block the mesh, causing trapped air. In addition, if the rotation speed of the filtering screen is too small when rotating the contents inside the columnar filtering screen **330** relative to the columnar filtering screen **330**, water flow may be subjected to resistance, causing clogging. Therefore, a greater rotation speed of the filtering screen may be required when the mesh aperture is small, to mitigate the problem of difficult aggregation of residue and easy clogging. However, when the rotation speed of the filtering screen is too large, the residue tends to seep out of the filtering screen, resulting in poor filtering effect.

(51) Therefore, in some embodiments of the present disclosure, the columnar filtering screen **330** is configured to rotate at a relative speed of 100 to 1000 r/min relative to the contents in the columnar filtering screen **330**, and the mesh aperture diameter of the columnar filtering screen **330** is set to about 0.2-0.5 mm, such that while increasing the filtration area and improving the filtering speed, the residue can be gathered at the bottom of the columnar filtering screen **330**, reducing the possibility of the residue collecting on the filtering screen in the direction of the water flow and blocking the flow of water, and also reducing the possibility of the residue leaking out of the filtering screen due to the excessive rotation speed of the filtering screen, thereby improving the filtering performance and filtering effect of the filtering device **10**. In addition, it is possible to improve the water volume when the water filtered by the filtering device **10** is pumped through a pump to an inner liner of the tableware washing apparatus, thereby reducing the washing time or reducing the water used for a single washing, thus achieving energy saving and consumption reduction. In some embodiments, better filtering effect may be achieved by using the filtering device **10** mentioned in the present disclosure. In some embodiments, for example, a filtering effect of about 100% filtration may even be achieved when the diameter of the external circle defined by the mesh of the columnar filtering screen **330** is 0.3 mm and the columnar filtering screen **330** is rotated relative to the contents inside the columnar filtering screen **330** at a relative speed of 250 r/min.

(52) Referring specifically to FIGS. 1-2 and 4-5, in some embodiments, a first opening **250a** is defined on the plane filter **200**, and the columnar filtering screen **330** of the rotary filter **300** is disposed below the first opening **250a**. A second opening **110a** is defined on the water cup assembly **100** facing and communicated with the first opening **250a**, and a projection of an inner wall enclosing the first opening **250a** on the water cup assembly **100** is located in the second opening **110a**, thereby defining a return chamber **123a** between the water cup assembly **100** and the columnar filtering screen **330** of the rotary filter **300**. In this way, the water after the washing process can be filtered through the plane filter **200** and fall directly into the return chamber **123a**; also, can fall through the first opening **250a** into the rotary filter **300** and be filtered through the columnar filtering screen **330** of the rotary filter **300**, and thereafter enter the return chamber **123a**. The filtered water entering the return chamber **123a** can be subsequently discharged through an outlet pipe **150** of the water cup assembly **100**.

(53) Further referring to FIGS. 1-3, in some embodiments of the present disclosure, the water cup assembly **100** may include a tray **110**, a cup **120** connected to the tray **110**, a spray arm interface **130** arranged on the tray **110**, and a drive accommodating portion **140**, an outlet pipe **150**, a discharge pump accommodating portion **160**, and a water-extraction pump accommodating portion

170, each connected to the cup 120. The plane filter 200 is arranged on the tray 110, and the tray 110 is configured to collect the water filtered by the plane filter 200. The cup 120 is configured to accommodate the columnar filtering screen 330, and the drive accommodating portion 140 is configured to accommodate at least the motor 410 of the drive assembly (referring to FIG. 32). The outlet pipe 150 is communicated with the cup 120 such that the filtered water can be discharged through the outlet pipe 150. The discharge pump accommodating portion 160 is communicated with the cup 120 and is configured to accommodate a discharge pump (not shown) to discharge the residue from the cup 120 by the pumping action of the discharge pump. The water-extraction pump accommodating portion 170 is configured to accommodate a water-extraction pump (not shown). The water-extraction pump accommodating portion 170 is connected to the outlet pipe 150 through a line to transport the water in the cup 120 to the outside of the cup 120, specifically to the spray arm interface 130 on the tray 110, after being filtered by the columnar filtering screen 330, by the pumping action of the water-extraction pump.

(54) Referring to FIGS. 6, 9 and 12-13, in some embodiments, the outlet pipe 150, the water-extraction pump accommodating portion 170, and the discharge pump accommodating portion 160 are spaced along a circumference of the cup 120. The water-extraction pump accommodating portion 170 is arranged adjacent to the outlet pipe 150 to reduce the loss of water flow. The discharge pump accommodating portion 160 is arranged on a side of the water-extraction pump accommodating portion 170 away from the outlet pipe 150 and is disposed at a junction position between the drive accommodating portion 140 and the cup 120, thereby reducing mutual interference between the residue discharge process and the water discharge process, and saving the installation space of each component. The “junction position” herein means that the discharge pump accommodating portion 160 is disposed at a corner position formed by the intersection of the drive accommodating portion 140 and the cup 120.

(55) In some embodiments, the cup 120 may include a top surface and a bottom surface disposed opposite each other along an axial direction of the cup 120. The drive accommodating portion 140 does not protrude from a bottom surface of the cup 120 along the axial direction of the cup 120. In some embodiments, the drive accommodating portion 140 may not protrude from the top surface of the cup 120 along the axial direction of the cup 120. In some embodiments, referring to FIG. 2 and FIG. 11, the drive accommodating portion 140 may neither protrude from the top surface of the cup 120 nor protrude from the bottom surface of the cup 120 along the axial direction of the cup 120. With this structure, it is possible to add drive assemblies (e.g., including but not limited to the motor 410) without changing the original height of the washing apparatus, thereby saving space in the height direction and reducing the increase in the overall height of the washing apparatus due to installations of drive assemblies.

(56) The “not protruding” herein means, in the axial direction, below the top surface, or above the bottom surface, or flush with the top or bottom surface. For example, in some embodiments, the drive accommodating portion 140 may likewise include a top surface and a bottom surface disposed opposite each other along the axial direction of the cup 120. In this case, the top surface of the drive accommodating portion 140 is disposed between the top surface and the bottom surface of the cup 120 in the height direction, or a bottom surface of the drive accommodating portion 140 is disposed between the top surface and the bottom surface of the cup 120 in the height direction, or the top surface of the drive accommodating portion 140 is flush with the top surface of the cup 120 in the height direction, or the bottom surface of the drive accommodating portion 140 is flush with the bottom surface of the cup 120 in the height direction.

(57) With such a structure, the drive accommodating portion 140 does not protrude from the bottom surface of the cup 120 along the axial direction of the cup 120, such that a motor may be added without changing the original height of the filtering device 10, and the space along the height direction of the filtering device 10 may be saved, making the entire filtering device 10 more compact.

(58) The “bottom surface” herein refers to an outer surface of the cup **120** away from the tray **110**.
(59) Of course, in some embodiments, the drive accommodating portion **140** may protrude at least partially from the bottom surface of the cup **120** along the axial direction of the cup **120**. The ratio of the protruding height of the bottom surface of the drive accommodating portion **140** to the height of the motor is less than 1:1. With this structure, the drive accommodating portion **140** protrudes at least partially from the bottom surface of the cup **120** and the ratio of the protruding height to the height of the motor is less than 1:1, which may save space along the height direction of the filtering device **10** and makes the entire filtering device **10** more compact.

(60) In some embodiments, the ratio of the protruding height of the bottom surface of the drive accommodating portion **140** relative to the bottom surface of the cup **120** to the height of the motor is less than 1:5 or even less than 1:7. In some embodiments, the ratio of the protruding height of the bottom surface of the drive accommodating portion **140** relative to the bottom surface of the cup **120** to the height of the motor is 1:16 to 1:5, and in other embodiments the ratio may be 1:12 to 1:7. For example, in some embodiments, the height of the motor may be 50 to 80 mm, or in some embodiments the height of the motor may be 70 mm. Accordingly, the protruding height of the drive accommodating portion **140** relative to the bottom surface of the cup **120** may be 5 to 10 mm. In some embodiments, the protruding height of the drive accommodating portion **140** relative to the bottom surface of the cup **120** may be 5 mm. Taking the above range, such as less than 1:5 or 1:7, etc., the protrusion height of the drive accommodating portion **140** and the motor arranged in the drive accommodating portion **140** may be further reduced, thereby further saving space along the height direction of the filtering device **10** and making the entire filtering device **10** more compact.

(61) The “protruding height” herein refers to a distance between the bottom surface of the drive accommodating portion **140** and the bottom surface of the cup **120**.

(62) In some embodiments of the present disclosure, referring to specifically FIGS. 3-4, the tray **110** defines the second opening **110a**, and the water collected by the tray **110** after being filtered by the plane filter **200** can fall through the second opening **110a** to the bottom of the tray **110**. The spray arm interface **130** is arranged on the tray **110**, and the spray arm interface **130** and the second opening **110a** are disposed at intervals along a first direction X.

(63) In some embodiments, the tray **110** may be substantially elliptical in shape and have a long axis **111** and a short axis **112** that intersect with each other, where the long axis **111** may be set along the first direction X, i.e., the first direction X is the direction in which the long axis **111** of the tray **110** is located. The short axis **112** may be set in a second direction Y perpendicular to the first direction X, i.e., the second direction Y is the direction in which the short axis **112** of the tray **110** is located. In some embodiments, the ratio of the length of the long axis **111** and the short axis **112** may be 5:3, which may facilitate the arrangement of the spray arm interface **130** and increase the water-passing area when filtering, such that most of the water after washing can fall into the rotary filter **300** through the first opening **250a** on the plane filter **200**, and enter the return chamber **123a** after being filtered by the columnar filtering screen **330**, or enter directly into the return chamber **123a** filtered by the plane filter **200**.

(64) In some embodiments of the present disclosure, the tray **110** is elliptical. Of course, in other embodiments, the tray **110** may be configured in other shapes, such as round, square, rectangular, diamond-shaped, etc., as long as the tray **110** has enough space to arrange the spray arm interface **130** and define the second opening **110a** and can carry the plane filter **200**.

(65) In some embodiments of the present disclosure, the cup **120** is substantially columnar in shape. The columnar filtering screen **330** of the rotary filter **300** may be accommodated in the cup **120**, and a gap exists between an inner surface of the cup **120** and an outer surface of the columnar filtering screen **330**. The ratio of an inner diameter of the cup **120** to an inner diameter of the columnar filtering screen **330** is about 3:4 to 8:9, and the width of the gap between the inner surface of the cup **120** and the outer surface of the columnar filtering screen **330** along a radial direction of the cup **120** is about 10 to 20 mm. In some embodiments, the height of the cup **120** is

about 90 to 110 mm, the inner diameter of the cup **120** is about 80 to 100 mm, and the inner diameter of the columnar filtering screen **330** is about 60 to 80 mm. This size design may effectively reduce the problem of air extraction during the water return process, ensure the smooth flow of water such that the water can fill the return chamber **123a**, reduce the possibility of air adulteration in the return chamber **123a**, thereby ensuring the flow of the washing process and improving the filtration performance.

(66) Referring further to FIGS. 3-5, the cup **120** may substantially include a bottom wall **121** and a first peripheral wall **123** and a second peripheral wall **125** that are connected to the bottom wall **121**. The first peripheral wall **123** and the second peripheral wall **125** are connected to opposite sides of the bottom wall **121**, respectively. That is, the first peripheral wall **123** is connected to a side of the bottom wall **121**, and the second peripheral wall **125** is connected to the other side of the bottom wall **121** opposite to the side of the bottom wall **121**. That is, the first peripheral wall **123** extends toward a side of the bottom wall **121**, and the second bottom wall **125** extends toward the other side of the bottom wall **121**. The first peripheral wall **123** encloses a receiving cavity (not shown) for receiving the columnar filtering screen **330**. The columnar filtering screen **330** may be received in the receiving cavity, and the columnar filtering screen **330** may divide the receiving cavity into a filtration chamber for receiving the water inside the columnar filtering screen **330** and the return chamber **123a** disposed outside the columnar filtering screen **330**. The first peripheral wall **123** further defines a first water outlet **123b**, and the outlet pipe **150** is connected to the return chamber **123a** through the first water outlet **123b**. The second bottom wall **125** may enclose a discharge cavity **125a**, and the second bottom wall **125** may further define a discharge outlet **125b**. The discharge pump accommodating portion **160** is communicated with the discharge cavity **125a** through the discharge outlet **125b**. In conjunction with FIG. 11, the bottom wall **121** may further define a through hole **121a**, and the receiving cavity and the discharge cavity **125a** are communicated with each other through the through hole **121a**.

(67) In some embodiments, the first peripheral wall **123** and the second peripheral wall **125** may each be an annular peripheral wall. Of course, in other embodiments, the first peripheral wall **123** and the second peripheral wall **125** may also be other shapes.

(68) The first peripheral wall **123** and the second peripheral wall **125** may be integrally formed into one part, or separately formed, which is not limited herein.

(69) Referring further to FIGS. 3-5, the cup **120** may further include a support tab **127**, which is connected to the bottom wall **121** and extends from the bottom wall **121** toward the receiving cavity. The support tab **127** is arranged around the through hole **121a**. In some embodiments of the present disclosure, the inner surface of the columnar filtering screen **330** may be abutted against an outer surface of the support tab **127**, to support the columnar filtering screen **330** on the support tab **127**. The support tab **127** may be configured to support the columnar filtering screen **330** and may serve as a retaining wall to prevent the residue falling into the discharge cavity **125a** from adhering to the columnar filtering screen **330** again by the action of flowing water.

(70) The “supported on” herein may be understood to mean that the support tab **127** only serves as a support, not as a fixing part. Therefore, the columnar filtering screen **330** may be fixed to the support tab **127** or not be fixed. For example, the columnar filtering screen **330** may be rotated relative to the support tab **127**.

(71) After the filtered water has been filtered through the columnar filtering screen **330**, the water seeps out of the columnar filtering screen **330** into the return chamber **123a** and is delivered to the outside of the cup **120** through the first water outlet **123b**. In this case, at least a portion of the residue falls into the discharge cavity **125a** and is discharged through the pumping action of a discharge pump to the outside of the cup **120** through the discharge outlet **125b**.

(72) In some embodiments, the discharge outlet **125b** is defined at the bottom of the cup **120**. In some embodiments, the discharge outlet **125b** is defined at a lowest position at the bottom of the cup **120** to facilitate the collection and discharge of the residue. In addition, referring to FIG. 12, an

angle α between a line connecting the center of the discharge outlet **125b** and the center of the cup **120** and a line connecting the center of the first water outlet **123b** and the center of the cup **120** is greater than 90 degrees and less than or equal to 180 degrees. In some embodiments, the angle may be 180 degrees, in which case the discharge pump accommodating portion **160** and the outlet pipe **150** are arranged along the radial direction of the cup **120** on opposite sides of the cup **120**.

(73) In order to facilitate the discharge of the residue, in some embodiments of the present disclosure, further referring to FIG. 5, at least one guiding element **125c** may be arranged inside the discharge cavity **125a**. The at least one guiding element **125c** is arranged adjacent to the discharge outlet **125b** for guiding the residue during the discharge of the residue from the cup **120**.

(74) Referring further to FIG. 3 and FIGS. 9-10, in some embodiments, a recess **129** is defined on the bottom wall **121** toward the receiving cavity, and the recess **129** is arranged adjacent to and communicated with the first water outlet **123b**. The recess **129** is further communicated with the return chamber **123a**. The provision of such a recess **129** at a position adjacent to the first water outlet **123b** may effectively solve the problem of pumping air when pumping water through the pump subsequently, such that the water can adequately fill an outlet region of the cup **120** without mixing with air and ensuring the flow of water during the subsequent washing process.

(75) In some embodiments, in conjunction with FIGS. 13-14, the recess **129** may be disposed between the first peripheral wall **123** and the support tab **127**.

(76) In some embodiments, referring to FIG. 12, the recess **129** may extend along a circumference of the cup **120** for a length greater than the length of the first water outlet **123b** along the circumference of the cup **120**, thereby ensuring that filtered water can sink to the recess **129** and flow out of the cup **120** in a timely manner through the first water outlet **123b**. In this way, the filtered water can fill the outlet region of the cup without air in the process of pumping water through the pump, which can effectively reduce the probability of trapped air in the pump.

(77) In some embodiments of the present disclosure, referring to FIG. 6 and FIGS. 13-14, the recess **129** may include a first recess portion **129a** and a second recess portion **129d** that are from inside to outside sequentially arranged along the radial direction of the cup **120**. The first recess portion **129a** has a first bottom surface **129b** and the second recess portion **129d** has a second bottom surface **129e**. A recessed depth of the second bottom surface **129e** relative to the bottom wall **121** is greater than a recessed depth of the first bottom surface **129b** relative to the bottom wall **121**. The “recessed depth” herein means a vertical distance (i.e., the distance along the axial direction of the cup **120**) between the bottom surface (i.e., the first bottom surface **129b** or the second bottom surface **129e**) of the corresponding recess portion (first recess portion **129a** or second recess portion **129d**) and the bottom wall **121**. In some embodiments, the difference between the recessed depth of the first recess portion **129a** and the recessed depth of the second recess portion **129d** is about 5 to 8 mm. The design of two levels of recess portions to form the recess **129** may facilitate the injection molding process of the cup **120** and reduce the possibility of shrinkage and deformation of the recess **129** during the injection molding process of the cup **120**.

(78) Further referring to FIGS. 13-14, in some embodiments, the recessed depth of the second bottom surface **129e** relative to the bottom wall **121** may be further less than a recessed depth of a lowest point of an inner wall of the outlet pipe **150** at the first water outlet **123b** relative to the bottom wall **121**, thereby reducing the probability of trapped air during subsequent pumping, such that the water can adequately fill the outlet region of the cup **120** without mixing with air, ensuring the water flow of the washing process.

(79) In addition, in some embodiments, the first recess portion **129a** has an inclined surface **129c** connecting the bottom wall **121** and the first bottom surface **129b**. In some embodiments, an angle between the inclined surface **129c** and the first bottom surface **129b** is about 158.9° to 162.7°. The first recess portion **129a** is set with an inclined surface, which allows the filtered water to smoothly transitioned into the recess **129** through the inclined surface **129c** and flow into the outlet pipe **150** through the first water outlet **123b** and then out of the cup **120**.

(80) In some embodiments, referring to FIGS. 7, 9 and 12, an end of the outlet pipe 150 is connected to the cup 120 and communicated with the return chamber 123a through the first water outlet 123b. The other end of the outlet pipe 150 is arranged with a second water outlet 151, and the outlet pipe 150 defines an outlet channel 150a between the first water outlet 123b and the second water outlet 151. The cross-sectional area of the outlet channel 150a decreases in a direction from the first water outlet 123b to the second water outlet 151, in conjunction with FIGS. 7 and 12. The design of this structure of the outlet pipe 150 may effectively solve the problem of pumping air at the outlet location caused by the pump during the pumping process, such that the water adequately fills the outlet region without mixing with air, ensuring the flow of water during the washing process.

(81) In some embodiments, the ratio of the cross-sectional area of the outlet channel 150a at the first water outlet 123b to the cross-sectional area of the outlet channel 150a at the second water outlet 151 is about 1.63 to 1.99. The ratio setting may more effectively solve the problem of pumping air at the outlet location caused by the pump during the pumping process, thereby improving the flow rate during the washing process. Herein, the cross-sectional area is the area of the cross-section dissected parallel to the axial direction of the columnar filtering screen 330.

(82) In some embodiments, referring to FIG. 8, the cross-section of the outlet channel 150a at the first water outlet 123b is substantially elliptical in shape and the ratio of the lengths of the long and short axes of the elliptical is substantially 5:3. The elliptical design allows more filtered water to enter the outlet tube 150 at the same time as the water is being discharged, ensuring that the water fills the outlet region sufficiently without air admixture.

(83) In other embodiments, the cross-section of the outlet channel 150a at the first water outlet 123b may also be round, square, etc. In some embodiments, when a circular cross-section is adopted, the diameter of the circular cross-section is about 35 mm, i.e., the inner diameter of the outlet pipe 150 at that first water outlet 123b is about 35 mm.

(84) In some embodiments, the outlet channel 150a has a substantially circular cross-section at the second water outlet 151. In some embodiments, the diameter of the circular cross-section of the outlet channel 150a at the second water outlet 151 is about 26 mm. The circular cross-section of the outlet channel 150a at the second water outlet 151 facilitates connection to external pipeline and thus to the pump.

(85) Of course, in other embodiments, the shape of the cross-section of the outlet channel 150a at the first water outlet 123b and the second water outlet 151 and the size of the inner diameter of the outlet pipe 150 at the first water outlet 123b and the second water outlet 151 may be selected according to actual needs. The present disclosure is not limited herein specifically.

(86) Referring to FIG. 7 and FIG. 13, the outlet pipe 150 includes a diameter-inconsistent portion 153 and a diameter-consistent portion 155 connected from the inside to the outside in the radial direction of the cup 120, and the diameter-inconsistent portion 153 and the diameter-consistent portion 155 are communicated with each other. By setting the diameter-inconsistent portion 153 and the diameter-consistent portion 155, it may be ensured that the water adequately fills the outlet region without mixing air, and the connection with the external pipeline may be facilitated. In some embodiments of the present disclosure, the length of the diameter-consistent portion 155 may be greater than or equal to 15 mm. In other embodiments, the length of the diameter-consistent portion 155 may be greater than or equal to 20 mm.

(87) In conjunction with FIG. 13 and FIG. 15, the diameter-inconsistent portion 153 is connected to the first peripheral wall 123 and defines a first sub outlet channel 153a connected to the return chamber 123a of the receiving cavity through the first water outlet 123b. The cross-sectional area of the first sub outlet channel 153a gradually decreases in the direction from the first water outlet 123b to the second water outlet 151.

(88) The diameter-consistent portion 155 is arranged on a side of the outlet pipe 150 away from the return chamber 123a of the receiving cavity and defines a second sub outlet channel 155a

communicated with the first sub outlet channel **153a**, and the second water outlet **151** is arranged on the diameter-consistent portion **155**. The first sub outlet channel **153a** and the second sub outlet channel **155a** form the aforementioned outlet channel **150a**, and the cross-sectional area of the second sub outlet channel **155a** remains constant along the direction from the first water outlet **123b** toward the second water outlet **151**.

(89) In some embodiments, further referring to FIG. **13**, the diameter-inconsistent portion **153** has a first side **153b** and a second side **153c** in a cross-section perpendicular to the axial direction of the cup **120** and over the geometric center of the first water outlet **123b**. The first side **153b** is near the water-extraction pump accommodating portion **170** and the second side **153c** is away from the water-extraction pump accommodating portion **170**. The diameter-inconsistent portion **153** has a cross-sectional area between the first side **153b** and the first peripheral wall **123**. The diameter-inconsistent portion **153** forms a first intersection **153d** at the connection of the first side **153b** with the first peripheral wall **123** and a second intersection **153e** at the connection with the diameter-consistent portion **155**, while the diameter-inconsistent portion **153** forms a third intersection **153f** at the connection of the second side **153c** with the first peripheral wall **123** and a fourth intersection **153g** at the connection with the diameter-consistent portion **155**. In some embodiments, the length of a line between the first intersection **153d** and the second intersection **153e** is less than the length of a line between the third intersection **153f** and the fourth intersection **153g**, and the angle between the line between the first intersection **153d** and the second intersection **153e** and a tangent line of the first peripheral wall **123** at the first intersection **153d** is greater than the angle between the line between the third intersection **153f** and the fourth intersection **153g** and a tangent line of the first peripheral wall **123** at the third intersection **153f**. In addition, the angle between the diameter-inconsistent portion **153** on the first side **153b** and the diameter-consistent portion **155** may be less than the angle between the diameter-inconsistent portion **153** on the second side **153c** and the diameter-consistent portion **155**. With this structure, the connection between the outlet pipe **150** and the pump accommodated in the water-extraction pump accommodating portion **170** may be facilitated through the pipeline, and the stability and reliability of the connection or communication between the outlet pipe **150** and the pump may be ensured.

(90) Of course, in other embodiments, the diameter-inconsistent portion section **153** may be arranged symmetrically about the centerline of the outlet pipe **150**. That is, the length of the line between the first intersection **153d** and the second intersection **153e** is equal to the length of the line between the third intersection **153f** and the fourth intersection **153g**, and the angle between the line between the first intersection **153d** and the second intersection **153e** and the tangent line of the first peripheral wall **123** at the first intersection **153d** is equal to the angle between the line between the third intersection **153f** and the fourth intersection **153g** and the tangent line of the first peripheral wall **123** at the third intersection **153f**. The present disclosure is not specifically limited herein.

(91) In some embodiments, a side of the outlet pipe **150** away from the water-extraction pump accommodating portion **170** (i.e., the second side **153c** of the diameter-inconsistent portion **153**) may be tangential to an outer peripheral wall of the cup **120** (specifically, the outer surface of the first peripheral wall **123**), such that filtered water may enter the outlet pipe **150** more smoothly, thereby reducing the resistance to the water generated by the outlet pipe **150**.

(92) Referring to FIG. **15**, in some embodiments of the present disclosure, the height of the outlet channel **150a** along the axis of the columnar filtering screen **330** remains constant in the direction from the first water outlet **123b** to the second water outlet **151**, thereby reducing the installation height along the axis of the columnar filtering screen **330** and saving space in that direction, resulting in a lower installation height and more compact structure of the entire filtering device **10**.

(93) Further referring to FIGS. **1-2**, in some embodiments, the filtering device **10** further includes a spray arm adapter **500** arranged on the plane filter **200**, which is connected to and communicated with the spray arm adapter **130** on the tray **110**, for spraying the filtered water of the filtering

device **10** into the inner liner of the tableware washing apparatus through the spray arm adapter **500**.

(94) The plane filter **200** may include a face-shaped screen holder **250**, and a first face-shaped screen **210** and a second face-shaped screen **230** arranged side by side in the first direction X. The first opening **250a** is defined on the face-shaped screen holder **250**. The columnar filtering screen **330** is disposed below the face-shaped screen holder **250** and facing the first opening **250a**. Therefore, the water can fall from the first opening **250a** into the columnar filtering screen **330** below the face-shaped screen holder **250**. The spray arm adapter **500** is arranged on the face-shaped screen holder **250** and is spaced apart from the first opening **250a** along the first direction X.

(95) In some embodiments, the first face-shaped screen **210** and the second face-shaped screen **230** may both be plane screens. In other embodiments, the first face-shaped screen **210** and the second face-shaped screen **230** may be curved screens with curves, or one of the first face-shaped screen **210** and the second face-shaped screen **230** may be a plane screen and the other a curved screen. The present disclosure does not limit the shape of the first face-shaped screen **210** and the second face-shaped screen **230**.

(96) In some embodiments, referring to FIGS. **1-2** and **12**, the second face-shaped screen **230** is away from the spray arm adapter **500** along the first direction X compared to the first face-shaped screen **210**. The area of the first face-shaped screen **210** is greater than the area of the second face-shaped screen **230**. In conjunction with FIG. **16**, a first angle (**31**) may be formed between the first face-shaped screen **210** and a reference plane perpendicular to the axial direction of the first opening **250a**, and a second angle (**32**) may be formed between the second face-shaped screen **230** and the reference plane, the first angle (**31**) being less than the second angle (**32**).

(97) The above is embodiments in which the first face-shaped screen **210** and the second face-shaped screen **230** are separate structures, i.e., the first face-shaped screen **210** and the second face-shaped screen **230** are separately machined and stitched together. However, in other embodiments, the first face-shaped screen **210** and the second face-shaped screen **230** may each be of a one-piece structure; for example, the first face-shaped screen **210** and the second face-shaped screen **230** may be formed by bending the entire screen at a predetermined location. The present disclosure does not limit the way of forming and combining the first face-shaped screen **210** and the second face-shaped screen **230**.

(98) With the above structure design, the plane filter **200** is divided into a plurality of different face-shaped screens and spliced with each other through the face-shaped screen holder **250**, which may increase the filtration area, improve the filtering speed, reduce the probability of empty pumping caused by untimely water return, and facilitate the manufacture of the plane filter **200**. Moreover, because the inclination angles of the first face-shaped screen and the second face-shaped screen with different areas are not the same with respect to the reference plane, the distances between the first face-shaped screen and the second face-shaped screen at corresponding positions and the reference plane may be approximately equal, such that the water falls more smoothly into the tray **110** through the different positions of the plane filter **200** or into the columnar filtering screen **330** through the first opening **250a**.

(99) In some embodiments, the ratio of the first angle β_1 to the second angle β_2 may be 1:5 to 1:2. In some embodiments, the ratio of the first angle β_1 to the second angle β_2 is about 1:3.

(100) Referring further to FIG. **16**, in some embodiments of the present disclosure, the first angle β_1 and the second angle β_2 are set such that a distance from an outer edge of the first face-shaped screen **210** away from the second face-shaped screen **230** along the first direction X and/or the second direction Y perpendicular to the first direction X to the reference plane along the axial direction of the first opening **250a** is the same as a distance from an outer edge of the second face-shaped screen **230** away from the first face-shaped screen **210** along the first direction X and/or the second direction Y to the reference plane along the axial direction of the first opening **250a**, thereby allowing the water to fall more smoothly into the tray **110** through the different positions of

the plane filter **200** or into the columnar filtering screen **330** through the first opening **250a**.

(101) Specifically, in some embodiments, the opposing outer edges of the first face-shaped screen **210** and the second face-shaped screen **230** along the first direction X may be set at equal distances from the reference plane along the axial direction of the first opening **250a**. For example, referring to FIG. **16**, the first face-shaped screen **210** has a first outer edge **211** in the first direction, a projection of which in the reference plane is at a maximum distance h_1 from the center of the first opening **250a**, and a first angle β_1 exists between the first face-shaped screen **210** and the reference plane. In a similar manner, the second face-shaped screen **230** has a second outer edge **231** in the first direction, and the second outer edge **231** and the first outer edge **211** are disposed on opposite sides of the first opening **250a**, respectively. A projection of the second outer edge **231** in the reference plane is at a maximum distance h_2 from the center of the first opening **250a**, and a first angle β_2 exists between the second face-shaped screen **230** and the reference plane. Therefore, the first face-shaped screen **210** and the second face-shaped screen **230** satisfy the following relationship: $\tan \beta_1 \cdot h_1 = \tan \beta_2 \cdot h_2$.

(102) Of course, in other embodiments, the opposing outer edges of the first face-shaped screen **210** and the second face-shaped screen **230** along the second direction Y may be set at equal distances from the reference plane along the axial direction of the first opening **250a**. Specifically, in the embodiments shown in FIG. **16**, the entire plane filter **200** is arranged symmetrically about the first direction X. The first face-shaped screen **210** has two opposing third outer edges **213** in the second direction Y, and the two third outer edges **213** are equidistant from the reference plane along the axial direction of the first opening **250a**. Similarly, the second face-shaped screen **230** has two opposing fourth outer edges **233** in the second direction Y, and the two fourth outer edges **233** are equidistant from the reference plane along the axial direction of the first opening **250a**.

(103) In other embodiments, the first angle β_1 and the second angle β_2 are set such that the opposing outer edges of the first face-shaped screen **210** and the second face-shaped screen **230** along the first direction X are at equal distances from the reference plane along the axial direction of the first opening **250a**, and the opposing outer edges of the first face-shaped screen **210** and the second face-shaped screen **230** along the second direction Y are at equal distances from the reference plane along the axial direction of the first opening **250a**.

(104) Referring further to FIG. **16**, in some embodiments, a dividing line **220** of the first face-shaped screen **210** and the second face-shaped screen **230** is disposed on a side of the center of the first opening **250a** away from the spray arm adapter **500** and intersecting with the first opening **250a**. In other words, the dividing line **220** is off-center from the center of the first opening **250a**. The eccentric arrangement of the dividing line **220** facilitates the arrangement of the spray arm adapter **500** while allowing the water to fall smoothly into the columnar filtering screen **330**.

(105) In some embodiments, the number of first face-shaped screens **210** and the number of second face-shaped screens **230** are each two. The two first face-shaped screens **210** are arranged side by side in the second direction perpendicular to the first direction X, and the two second face-shaped screens **230** are arranged side by side in the second direction perpendicular to the first direction X. Moreover, the dividing line between one first face-shaped screen **210** and one second face-shaped screen **230** and the dividing line between the other first face-shaped screen **210** and the other second face-shaped screen **230** are symmetrically arranged about a line connecting the center of the first opening **250a** and the center of the spray arm adapter **500**. That is, the two first plane screens **210** are arranged symmetrically about the line connecting the center of the first opening **250a** and the center of the spray arm adaptor, and the two second plane screens **230** are arranged symmetrically about the line connecting the center of the first opening **250a** and the center of the spray arm adaptor.

(106) In some embodiments of the present disclosure, the mesh count of meshes of each of the first face-shaped screen **210** and the second face-shaped screen **230** is about 50 to 70 mesh. Specifically, in some embodiments, the diameter of an external circle defined by each mesh of each of the first

face-shaped screen **210** and the second face-shaped screen **230** is about 0.2 to 0.5 mm, and the mesh spacing ranges from about 0.4 to 0.6 mm. In some embodiments, the diameter of the external circle defined by each mesh of each of the first face-shaped screen **210** and the second face-shaped screen **230** is about 0.2 to 0.4 mm. With this design, the residue in the water can be effectively filtered. In some embodiments, the diameter of the external circle defined by each mesh of each of the first face-shaped screen **210** and the second face-shaped screen **230** may be 0.3 to 0.4 mm, and the mesh spacing ranges from 0.6 to 1.0 mm.

(107) Referring to FIG. 17, in some embodiments, the face-shaped screen holder **250** may include an outer frame **251**, an inner frame **253** embedded within the outer frame **251** and facing the first opening **250a**, and at least one support rib **255** connected between the outer frame **251** and the inner frame **253**. The outer frame **251** and the inner frame **253** enclose a receiving region for the first face-shaped screen **210** and the second face-shaped screen **230**, and the at least one support rib **255** divides the receiving region into regions for receiving the first face-shaped screen **210** and the second face-shaped screen **230**. Edges of the first face-shaped screen **210** and the second face-shaped screen **230** abut against the outer frame **251**, the inner frame **253**, and the at least one support rib **255**, respectively, such that the first face-shaped screen **210** and the second face-shaped screen **230** are supported on the face-shaped screen holder **250**.

(108) In the embodiments shown in FIG. 17, the number of first face-shaped screens **210** and the number of second face-shaped screens **230** are each two, and the number of support ribs **255** is four. The inner frame **253** is generally circular in shape and the four support ribs **255** are arranged around a circumference of the inner frame **253**, thereby dividing the receiving region into four regions (corresponding to the two first face-shaped screens **210** and two second face-shaped screens **230**), such that the first face-shaped screens **210** and the second face-shaped screens **230** are firmly supported on the face-shaped screen holder **250**. Moreover, the support ribs **255** are adopted to divide the receiving region to facilitate the processing and shaping of the filtering screens.

(109) As further shown in FIG. 17, in some embodiments, the face-shaped screen holder **250** may further include a support platform **257** connected between the outer frame **251** and the inner frame **253** and arranged adjacent to the first face-shaped screen **210**. The spray arm adapter **500** is arranged on the support platform **257**.

(110) Continuing with FIG. 2 and FIGS. 18-19, in some embodiments, the rotary filter **300** may include a columnar screen holder **310** and the columnar filtering screen **330**. The columnar screen holder **310** is inserted within the cup **120**. The columnar filtering screen **330** is supported on the columnar screen holder **310** and is arranged facing the first opening **250a** for filtering the water. The columnar filtering screen **330** is rotatable relative to the contents of the columnar filtering screen **330**.

(111) In some embodiments, the columnar screen holder **310** may be integrally molded with the inner frame **253**, which may make the whole filtering device better integrated and sealed, and may reduce the possibility of residue leaking out to the return chamber **123a** through the seams or fits of the inner frame **253** and the columnar screen holder **310**. Of course, in other embodiments, the columnar screen holder **310** may be separated from the inner frame **253** and may be rotatably connected to the inner frame **253**, thereby facilitating the rotation of the columnar screen holder **310** and the columnar filtering screen **330** supported thereon relative to the plane filter **200**.

(112) In some embodiments, the contents of the columnar filtering screen **330** are rotatable by the drive assembly **400**, thereby allowing the columnar filtering screen **330** to rotate relative to the contents. For example, in the embodiments shown in FIG. 2, the rotary filter **300** includes the columnar filtering screen **330**, the columnar screen holder **310**, and a cleaning element **350**, where the specific design of the columnar screen holder **310** and the columnar filtering screen **330** is as previously described and will not be repeated herein. In the embodiments, the columnar screen holder **310** may be integrally formed with the inner frame **253**. The cleaning element **350** is

accommodated within the columnar filtering screen **330** and is in contact with, or abutting against, an inner wall (or inner surface) of the columnar filtering screen **330**. In some embodiments, a bottom of the cleaning element **350** may further be in contact with and supported on the support tab **127**. Of course, in other embodiments, the cleaning element **350** may not be in contact with the support tab **127**.

(113) Referring further to FIGS. **18-19**, the drive assembly **400** may be connected to the cleaning element **350** to drive the cleaning element **350** to rotate for separating at least a portion of the residue from the columnar filtering screen **330** by the cleaning element **350**. In some embodiments, the drive assembly **400** may drive the cleaning element **350** to rotate relative to the columnar filtering screen **330** at a speed of about 150 to 400 r/min. Using the cleaning element **350** to rotate at this speed reduces the probability of failure to form a residue collection caused by residue being thrown out of the columnar filtering screen **330** due to excessive rotation speed, and also reduces the probability that resistance to the flow of water will be formed due to too little rotation speed. Referring to FIG. **20**, in some embodiments, the cleaning element **350** may include a mounting bracket **351** and a contact portion **353** arranged on the mounting bracket **351**. The mounting bracket **351** may be connected to the drive assembly **400** and rotatable under the drive of the drive assembly **400**, thereby driving the entire cleaning element **350** to rotate. The contact portion **353**, in turn, contacts the inner wall of the columnar filtering screen **330** such that at least a portion of the residue on the columnar filtering screen **330** can be scraped off to separate at least a portion of the residue from the columnar filtering screen **330**.

(114) In some embodiments, referring to FIG. **20**, the mounting bracket **351** may include a connection portion **3511** and a shelf portion **3513**. The connection portion **3511** is coaxially disposed with a motor of the drive assembly **400** and is rotatable under the drive of the motor. A side of the shelf portion **3513** is connected to the connection portion **3511**, and the contact portion **353** may be arranged on another side of the shelf portion **3513** away from the connection portion **3511**. The number of contact portions **353** is the same as the number of shelf portions **3513**, or to say, the contact portions **353** are in one-to-one correspondence with the shelf portions **3513**.

(115) In some embodiments, the shelf portion **3513** may be integrally formed with the connection portion **3511**. Of course, in other embodiments, the shelf portion **3513** may be molded separately from the connection portion **3511**. Moreover, the shape of the shelf portion **3513** is not limited to the frame structure with a hollow portion shown in the drawings, and in some embodiments, the shelf portion **3513** may be a solid (not hollow) structure.

(116) In some embodiments, the cleaning element **350** may include at least two shelf portions **3513**, and each shelf portion **3513** is arranged with a contact portion **353**. When the cleaning element **350** includes two shelf portions **3513**, the number of contact portions **353** is also two, and the two shelf portions **3513** may be arranged symmetrically about an axial direction of the connection portion **3511**, as shown in FIGS. **19-20**. Of course, in other embodiments, three or more shelf portions **3513** and three or more contact portions **353** may be arranged. For example, in the embodiments shown in FIG. **21**, the number of the shelf portions **3513** and the number of the contact portions **353** are each three, and the three shelf portions **3513** are evenly distributed at equal distances along the circumference of the connection portion **3511**. In some embodiments, the number of the shelf portion **3513** and the number of the contact portion **353** are each one. The present disclosure does not limit the number, material, and size of such shelf portion **3513** and contact portion **353**.

(117) In some embodiments, the contact portion **353** may be a scraper, and the contact portion **353** may be made of, for example, silicone, rubber, and other materials. In addition, the contact portion **353** has a height of about 40 to 60 mm and a width of about 0.9 to 1.1 mm. During rotation of the cleaning element **350**, the contact portion **353** may generate a torque of about 0.4 to 0.6 N*m to cause as much residue as possible to fall off or be separated from the columnar filtering screen **330**.

(118) In some embodiments, a wave wheel may be applied in place of the above cleaning element **350**. Referring to specifically FIGS. **22-23**, in the embodiments, the rotary filter **300** may include

the columnar screen holder **310**, the columnar filtering screen **330**, and a wave wheel **370**. The specific design of the columnar screen holder **310** and the columnar filtering screen **330** is as previously described and will not be repeated herein. In the embodiments, the columnar screen holder **310** may be integrally formed with the inner frame **253**. The wave wheel **370** is rotatably accommodated in the columnar filtering screen **330** and is disposed at a bottom of the columnar filtering screen **330**, i.e., on a side away from the plane filter **200**. The drive assembly **400** is connected to the wave wheel **370** to drive the wave wheel **370** to rotate relative to the columnar filtering screen **330** at a speed of about 500 to 700 r/min for stirring the water within the columnar filtering screen **330**, such that at least a portion of the residue cannot adhere to the columnar filtering screen **330**, thereby allowing at least a portion of the residue to be separated from the columnar filtering screen **330** and facilitating water penetration through the mesh of the columnar filtering screen **330** to the return chamber **123a** to achieve effective filtration. The use of the wave wheel **370** rotating at this speed reduces probability of failure to form a residue collection caused by residue being thrown out of the columnar filtering screen **330** due to excessive rotation speed, and also reduces the probability that resistance to the flow of water will be formed due to too little rotation speed.

(119) In some embodiments, the wave wheel **370** may have three blades, as shown in FIG. 23. Of course, in other embodiments, the wave wheel **370** may include five or more blades. The present disclosure does not limit the number of blades of the wave wheel **370** herein. Moreover, the shape of the wave wheel **370** is not limited to the shape shown in FIG. 23, and may take any suitable shape, as long as the wave wheel can stir the water in the columnar filtering screen **330**.

(120) The above is embodiments in which the contents of the columnar filtering screen **330** (e.g., the cleaning element **350** and the wave wheel **370**) can be rotated relative to the columnar filtering screen **330** such that at least a portion of the residue can be separated from the columnar filtering screen **330**. However, in other embodiments, it is also possible to separate at least a portion of the residue from the columnar filtering screen **330** by rotating the columnar filtering screen **330**. By rotating the columnar filtering screen **330**, a portion of the columnar filtering screen **330** adjacent to the first water outlet **123b** can be changed such that the residue can be dispersed to different positions of the columnar filtering screen **330**, thereby effectively reducing the possibility of local blockage caused by the residue collecting at a certain position of the columnar filtering screen **330**, facilitating the stripping and cleaning of at least a portion of the residue from the columnar filtering screen **330**, and improving the filtration performance of the filtering device **10** and improving the overall tableware washing apparatus.

(121) For example, referring to FIGS. 24-25, in some embodiments of the present disclosure, the rotary filter **300** may include a columnar screen holder **310** and a columnar filtering screen **330**, and the columnar filtering screen **330** is supported on the columnar screen holder **310**. The drive assembly **400** is connected to the columnar screen holder **310** and drives the columnar screen holder **310** to rotate, and the columnar screen holder **310** drives the columnar filtering screen **330** to rotate relative to the water in the columnar filtering screen **330**, such that at least a portion of the residue can be separated from the columnar filtering screen **330** by the rotation of the columnar filtering screen **330**. The rotation speed of the columnar filtering screen **330** is about 500 to 700 r/min. In addition, the height of the cup **120** is about 90 to 110 mm, the inner diameter of the cup **120** is about 80 to 100 mm, and the inner diameter of the columnar filtering screen **330** is about 60 to 80 mm. Driving the columnar filtering screen **330** to rotate at this speed, while matching the inner diameter of the cup **120** and the inner diameter of the columnar filtering screen **330**, may reduce the probability of failure to form a residue collection caused by residue being thrown out of the columnar filtering screen **330** due to excessive rotation speed, and also reduces the probability that resistance to the flow of water will be formed due to too little rotation speed, thereby effectively reducing the problem of pumping air in the water return process, ensuring smooth water flow and filling the return chamber, reducing the possibility of the air being mixed in the return

chamber **123a**, thus ensuring the washing process flow, improving the filtration performance, and achieving better filtering effect. In the embodiments, the outlet channel **150a** may be of the cross-section-inconsistent design shown in FIG. **13**.

(122) In the embodiments, further referring to FIGS. **26-27**, the columnar screen holder **310** includes a main part **311**, a positioning post **315**, and at least one connecting rib **313** connecting the main part **311** and the positioning post **315**. The main part **311** has a columnar frame structure and the columnar filtering screen **330** may be hung or supported on the main part **311**. The positioning post **315** is disposed at a position substantially at a central axis of the main part **311** to be connected to an output shaft of the drive assembly **400** (e.g., the output shaft **438** of the second spur gear **437** shown in FIG. **25**) and the inner frame **253** of the plane filter **200**. The positioning post **315** may define an assembly hole **317** at an end connected to the drive assembly **400**, and the output shaft of the drive assembly **400** may be inserted in the assembly hole **317**, thereby driving the positioning post **315** to rotate the columnar screen holder **310**, which in turn rotates the columnar filtering screen **330** arranged on the columnar screen holder **310**.

(123) In some embodiments, the number of the connecting ribs **313** is two or more. In the embodiments shown in FIGS. **26-27**, the columnar screen holder **310** includes three connecting ribs **313**, and the three connecting ribs **313** may be evenly distributed around a circumference of the positioning post **315**.

(124) FIGS. **28-31** illustrate a relative position of the residue in relation to the direction of water flow in the return chamber **123a** at different moments when filtering with the rotatable columnar filtering screen **330**. In this case, the filtered water flows out of the return chamber through the first outlet. As shown in FIG. **28**, at a first moment, after the filtration of the columnar filtering screen **330**, the residue is disposed at a first position P1. At this time, the residue adheres to the inner surface of the columnar filtering screen **330** due to the suction force near the first water outlet **123b** (suction force is generated by the pump). As shown in FIG. **29**, at a second moment, the columnar filtering screen **330** is rotated at an angle driven by the drive assembly **400** such that the residue is disposed at a second position P2. At this time, the water disposed in the return chamber reacts to the residue on the columnar filtering screen **330** due to the suction force of the pump, such that the residue begins to separate from the columnar filtering screen **330**. Subsequently, as shown in FIG. **30**, the columnar filtering screen **330** continues to rotate and at a third moment the residue reaches a third position P3 and is completely separated from the columnar filtering screen **330**. And at a fourth moment, as shown in FIG. **31**, the columnar filtering screen **330** is rotated to a predetermined position such that the residue is disposed in a fourth position P4, at which time the residue has been completely separated from the columnar filtering screen **330** without adhering to the inner surface of the columnar filtering screen **330**, and the residue further approaches the axial direction of the columnar filtering screen **330** and can fall into the discharge cavity **125a**.

Therefore, by rotating the columnar filtering screen **330**, the portion of the columnar filtering screen **330** adjacent to the first water outlet **123b** can be changed such that the residue can be dispersed to different positions of the columnar filtering screen **330**, thereby effectively reducing the possibility of local blockage caused by the residue collecting at a certain position of the columnar filtering screen **330**, facilitating the stripping and cleaning of at least a portion of the residue from the columnar filtering screen **330**, thus allowing the water to smoothly penetrate into the return chamber **123a** and flow into the outlet pipe **150**. In this way, the filtration performance of the filtering device **10** and the overall stability of the tableware washing apparatus can be improved.

(125) In the embodiments, the rotation of the columnar filtering screen **330** is driven by an external drive assembly **400**. Of course, in other embodiments, it is possible to drive the rotation of the columnar filtering screen **330** without an external drive, for example by the force of the water flow itself. The present disclosure does not limit the driving force of the columnar filtering screen **330** herein.

(126) Referring further to FIGS. 32 and 33, in some embodiments, the drive assembly 400 may include a motor 410 and a reduction mechanism 430. The motor 410 is arranged horizontally, i.e., an output shaft 411 of the motor 410 is perpendicular to the axial direction of the cup 120, thereby saving space in the height direction and making the entire filtering device 10 more compact.

(127) In some embodiments, the reduction mechanism 430 may be a reduction gear mechanism, which may include a first bevel gear 431, a second bevel gear 433, a first straight gear 435, and a second spur gear 437. The first bevel gear 431 and the first straight gear 435 are arranged coaxially. The second bevel gear 433 is connected to the output shaft 411 of the motor 410 and engages with the first bevel gear 431. The second spur gear 437 engages the first spur gear 435, and an output shaft 438 of the second spur gear 437 is inserted into the cup 120 from an outer surface (bottom surface) of the bottom of the cup 120 and is connected to a portion of the rotary filter 300 (e.g., the aforementioned columnar screen holder 310, cleaning element 350, or wave wheel 370), thereby driving the columnar filtering screen 330 to rotate relative to the contents. In some embodiments of the present disclosure, the reduction mechanism 430 may further include a cantilever assembly 439, and the cantilever assembly 439 is configured to hold down the first bevel gear 431 and the first spur gear 435.

(128) In some embodiments, the motor 410 has a mounting height along the axial direction of the cup 120 of substantially about 80 to 100 mm, and the motor 410 may be accommodated within the drive accommodating portion 140. In some embodiments, the top of the motor 410 does not protrude from the top surface of the cup 120, and the bottom of the motor 410 does not protrude from the bottom surface of the cup 120.

(129) Therefore, when this type of reduction mechanism is applied, the rotational motion can be converted into a right angle change of direction by means of multiple stages of gears (two bevel gears and two spur gears), and together with the motor being set horizontally, it is thus possible to incorporate the drive assembly 400 without changing the original height of the filtering device 10, thereby saving space along the height direction of the filtering device 10 and making the entire filtering device 10 more compact.

(130) Of course, in other embodiments, as described above, the bottom of the motor 410 may partially protrude from the bottom surface of the cup 120, as long as the ratio of the protruding height of the bottom surface of the drive accommodating portion 140 to the height of the motor is less than 1:1, thereby saving space along the height of the filtering device 10 and making the entire filtering device 10 more compact.

(131) Referring further to FIGS. 32 and 33, the drive accommodating section 140 is arranged facing the reduction mechanism 430. Specifically, in some embodiments, the drive accommodating portion 140 may include a motor mounting part 141, a first fixing part 143, a second fixing part 145, and a third fixing part 147. The motor 410 may be arranged on the motor mounting part 141. The first fixing part 143 has a generally circular outer profile and is intersected with the motor mounting portion 141, for arranging the coaxially fixed first bevel gear 431 and the first spur gear 435. The second fixing part 145 has a generally circular outer profile and is intersected with the first fixing part 143. The second fixing part 145 is disposed below the cup 120 and is configured to arrange the second spur gear 437. The third fixing part 147 has a generally circular outer contour and is intersected with both the motor mounting portion 141 and the first fixing part 143, for arranging the cantilever assembly 439. In the embodiments, the cantilever assembly 439 may extend from the third fixing part 147 to the first fixing part 143.

(132) Of course, in some embodiments, the third fixing portion 147 and the cantilever assembly 439 may be omitted or arranged in another manner, as long as the proper operation of the drive assembly is ensured. In some embodiments, referring to FIG. 19, an oil seal 600 may be arranged between the output shaft 438 of the second spur gear 437 and the cup 120. The oil seal 600 may ensure the rotation of the output shaft 438 and reduce the possibility of failure of the reduction mechanism 430 caused by water in the cup 120 seeping into the reduction mechanism 430.

(133) In the above embodiments, the reduction mechanism is implemented by a reduction gear mechanism. However, in other embodiments, the reduction mechanism may be implemented using other reduction mechanisms, such as a belt drive mechanism.

(134) For example, referring to FIGS. 34-37, in some embodiments of the present disclosure, the drive assembly **400** may include a motor **410a**, an active wheel **431a**, a driven wheel **433a**, and a belt **435a** connecting the active wheel **431a** and the driven wheel **433a**. In the embodiments, the motor **410a** is accommodated in the drive accommodating portion **140**, and an output shaft **411a** of the motor **410a** is arranged along the axial direction of the cup **120** and extends to the outside of the drive accommodating portion **140**. The active wheel **431a** is arranged on the outside of the drive accommodating portion **140** and is connected to the output shaft **411a** of the motor **410a**. The driven wheel **433a** is arranged on the outside of the drive accommodating portion **140** and is in transmission connection with the main wheel **431a** through the belt **435a**. In addition, an output shaft **438a** of the driven wheel **433a** is inserted inside the cup **120** from the outer surface of the bottom of the cup **120** and is connected to a portion of the rotary filter **300** (e.g., the aforementioned columnar screen holder **310**, the cleaning element **350**, or the wave wheel **370**), thereby driving the columnar filtering screen **330** to rotate relative to the contents. This type of reduction mechanism **430a** has a relatively simple structure and is easy to machine and manufacture.

(135) In the embodiments shown in FIGS. 34-37, the drive accommodating portion **140** accommodates only the motor **410a**, and the active wheel **431a**, driven wheel **433a**, and belt **435a** are arranged on the outside of the drive accommodating portion **140**. Of course, in other embodiments, the motor **410a**, the active wheel **431a**, the driven wheel **433a**, and the belt **435a** may all be accommodated inside the drive accommodating portion **140**. The present disclosure is not specifically limited in this regard.

(136) In some embodiments, referring to FIG. 35, an oil seal **600** may be arranged between the output shaft **438a** of the driven wheel **433a** and the cup **120**. The oil seal **600** may ensure the rotation of the output shaft **438a** and reduce the possibility of failure of the reduction mechanism **430a** caused by water in the cup **120** seeping into the reduction mechanism **430a**.

(137) Both of the above embodiments employ a motor to drive the rotation. However, in other embodiments, other drive methods may be used, such as pneumatic drive, liquid drive, etc.

(138) For example, in the embodiments shown in FIGS. 38-40, a liquid drive may be applied. Referring specifically to FIGS. 38-40, the drive assembly **400** may be implemented by a water wheel housing mechanism **430b**. The water wheel housing mechanism **430b** may include a water wheel housing **431b**, a water wheel **433b**, and a drain pipe **435b**. The water wheel housing **431b** is arranged on the tray **110**. The water wheel housing **431b** is substantially annular in structure, and the water wheel housing **431b** may enclose a drive fluid cavity **437b**. The number of the spray arm adapters **500** is at least two, and the drive fluid cavity **437b** is communicated with one of the at least two spray arm adapters **500** such that water delivered to one of the at least two spray arm adapters **500** (i.e., the spray arm adapter **500** connected to the drive fluid cavity **437b**) may further enter the drive fluid cavity **437b**.

(139) The water wheel **433b** may be accommodated in the drive fluid cavity **437b**, and the water wheel **433b** may be driven to rotate by the force exerted on the water wheel **433b** by the water entering the drive fluid cavity **437b**. In conjunction with FIG. 41, the water wheel **433b** is also connected to at least a portion of the rotary filter **300** (e.g., the aforementioned columnar screen holder **310**, cleaning element **350**, or wave wheel **370**), thereby driving the columnar filtering screen **330** to rotate relative to the contents within the columnar filtering screen **330**.

(140) Referring further to FIGS. 39-40, the drain pipe **435b** may be communicated with the drive fluid cavity **437b** and may further be communicated with the plane filter **200** or the columnar filtering screen **330** for discharging water from the drive fluid cavity **437b** onto the plane filter **200** or into the columnar filtering screen **330**. The water wheel housing mechanism **430b** to drive the

rotation may save the energy consumption of the filtering device **10**.

(141) In the above embodiments, the filtering device **10** includes both a plane filter **200** and a rotary filter **300** to filter the water through the plane filter **200** and the rotary filter **300**. However, in other embodiments, it may be possible to provide only the plane filter **200**, or only the rotary filter **300**, as long as the filtration performance requirements can be met.

(142) Embodiments of the present disclosure further provide a tableware washing apparatus. Referring to FIG. **42**, the tableware washing apparatus substantially includes a filtering device **10**, an inner liner **20**, and a spray arm as described in any of the above embodiments. In particular, the inner liner **20** is configured to define a washing chamber for receiving the dishes to be washed. Both the filtering device **10** and the spray arm are accommodated in the inner liner **20**, and a spray arm adapter **500** of the filtering device **10** is further connected to the spray arm. The filtering device **10** is arranged on an outer surface of the bottom of the inner liner **20** for collecting the washing water flowing from the washing chamber, filtering the washing water, and after filtering, delivering the filtered water to the inner liner again through the pumping action of a pump through the spray arm.

(143) Specifically, when the washing water (to-be-filtered water) falls into the filtering device **10** from the inner liner, it first enters the plane filter **200**. A portion of the water falls directly into the return chamber **123a** between the cup **120** and the columnar filtering screen **330** through the tray **110**. The rest of the water falls into the columnar filtering screen **330** through the first opening **250a** in the middle of the plane filter **200**, and discharged into the return chamber **123a** after filtered by the columnar filtering screen **330**. The filtered water in the return chamber **123a** is discharged through the outlet pipe **150** and transported to the spray arm interface **113** by the pumping action of the pump, and enters the spray arm adapter **500**, which can be sprayed into the inner liner again by the action of the spray arm.

(144) With the filtering device **10** and the tableware washing apparatus of the present disclosure, while increasing the filtration area and the filtering speed, it is possible to reduce the possibility of blocking the flow of water caused by the residue gathering on the filtering screen in the direction of the flow of water, and thus increase the water volume of the tableware washing apparatus when the water filtered by the filtration system is pumped out to the inner liner. Therefore, the performance and filtering effect of the filtering device **10** can be improved, thus reducing the washing time or the water used for a single washing, and achieving energy saving and consumption reduction.

(145) The above is only some embodiments of the present disclosure, not to limit the scope of the present disclosure. Any equivalent structure or equivalent process transformation made by using the content of the specification and the attached drawings of the present disclosure, or applied directly or indirectly in other related technical fields, are included in the scope of the present disclosure.

Claims

1. A filtering device for a tableware washing apparatus, comprising: a rotary filter comprising a columnar filtering screen configured to filter water from a washing process of the tableware washing apparatus, wherein a diameter of an external circle defined by each mesh of the columnar filtering screen is between 0.2 to 0.5 mm; and a drive assembly, connected to the rotary filter and configured to drive the columnar filtering screen to rotate relative to contents within the columnar filtering screen at a relative speed of 100 to 1000 r/min, configured to separate at least a portion of a residue on the columnar filtering screen from the columnar filtering screen, wherein the rotary filter further comprises a cleaning element, and the cleaning element is in contact with an inner wall of the columnar filtering screen; and the drive assembly is connected to the cleaning element and configured to drive the cleaning element to rotate relative to the columnar filtering screen to separate at least a portion of the residue from the columnar filtering screen by rotating the cleaning

element; and wherein the cleaning element comprises: a mounting bracket connected to the drive assembly and rotatable by the drive assembly; and a contact portion arranged on the mounting bracket and in contact with the inner wall of the columnar filtering screen, and wherein a height of the contact portion is between 40 to 60 mm, and a width of the contact portion is between 0.9 to 1.1 mm.

2. The filtering device according to claim 1, wherein the rotary filter further comprises a columnar screen holder, and the columnar filtering screen is fixed on the columnar screen holder; and the drive assembly is connected to the columnar screen holder and further configured to drive the columnar screen holder to rotate the columnar filtering screen relative to the water within the columnar filtering screen, to separate at least a portion of the residue from the columnar filtering screen by rotating the columnar filtering screen.

3. The filtering device according to claim 1, wherein the drive assembly comprises a motor; the cleaning element comprises: a mounting bracket, comprising: a connection portion, coaxially disposed with the motor and rotatable under drive of the motor; and a shelf portion, wherein a side of the shelf portion is connected to the connection portion; and a contact portion, arranged on another side of the shelf portion away from the connection portion and in contact with the inner wall of the columnar filtering screen.

4. The filtering device according to claim 1, wherein the rotary filter further comprises a wave wheel rotatably accommodated within the columnar filtering screen; and the drive assembly is connected to the wave wheel and configured to drive the wave wheel to rotate relative to the columnar filtering screen to stir the water within the columnar filtering screen to separate at least a portion of the residue from the columnar filtering screen.

5. The filtering device according to claim 1, wherein a mesh count of meshes of the columnar filtering screen is between 50 to 70 mesh.

6. A filtering device for a tableware washing apparatus, comprising: a rotary filter comprising a columnar filtering screen configured to filter water from a washing process of the tableware washing apparatus, wherein a diameter of an external circle defined by each mesh of the columnar filtering screen is between 0.2 to 0.5 mm; and a drive assembly, connected to the rotary filter and configured to drive the columnar filtering screen to rotate relative to contents within the columnar filtering screen at a relative speed of 100 to 1000 r/min, configured to separate at least a portion of a residue on the columnar filtering screen from the columnar filtering screen, further comprising a water cup assembly, wherein the water cup assembly comprises: a cup, wherein the columnar filtering screen is accommodated in the cup, and the cup comprises a bottom surface; and a drive accommodating portion, connected to the cup and configured to accommodate at least a motor of the drive assembly; wherein the drive accommodating portion does not protrude from the bottom surface of the cup along an axial direction of the cup; or wherein the drive accommodating portion protrudes at least partially from the bottom surface of the cup along the axial direction of the cup, and a ratio of a protruding height of a bottom surface of the drive accommodating portion relative to the bottom surface of the cup to a height of the motor is less than 1:1.

7. The filtering device according to claim 1, further comprising a water cup assembly, wherein the water cup assembly comprises: a cup, being columnar in shape, wherein the columnar filtering screen is accommodated in the cup; an outlet pipe, connected to the cup; and a discharge pump accommodating portion, communicated with the cup and configured to accommodate a discharge pump, to discharge residue within the cup by a pumping action of the discharge pump; wherein the discharge pump accommodating portion is disposed on a side of the cup, and the outlet pipe is disposed on another side of the cup opposite to the side along a radial direction of the cup.

8. The filtering device according to claim 1, further comprising a cup columnar in shape, wherein the columnar filtering screen is accommodated in the cup, and a ratio of an inner diameter of the cup to an inner diameter of the columnar filtering screen is between 3:4 to 8:9; and a gap exists between an inner surface of the cup and an outer surface of the columnar filtering screen, and a

width of the gap along a radial direction of the cup is between 10 to 20 mm.

9. The filtering device according to claim 8, wherein an inner diameter of the cup is 80 to 100 mm, and the inner diameter of the columnar filtering screen is 60 to 80 mm.

10. The filtering device according to claim 1, further comprising a water cup assembly, wherein the water cup assembly comprises: a cup, wherein the columnar filtering screen is accommodated in the cup, and the cup comprises a bottom surface; a drive accommodating portion, connected to the cup and configured to accommodate at least a motor of the drive assembly; and the drive accommodating portion comprises: a motor mounting part, configured to arrange the motor, wherein an output shaft of the motor is perpendicular to a radial direction of the cup; a first fixing part, intersected with the motor mounting part and configured to arrange a first bevel gear and a first spur gear that are coaxially fixed, wherein the first bevel gear is engaged with a second bevel gear connected to the output shaft of the motor; and a second fixing part, intersected with the first fixing part and disposed below the cup, wherein the second fixing part is configured to arrange a second spur gear, the second spur gear is engaged with the first spur gear, and an output shaft of the second spur gear is inserted into the cup from the bottom surface of the cup.

11. The filtering device according to claim 10, wherein an oil seal is arranged between the output shaft of the second spur gear and the cup.

12. The filtering device according to claim 1, further comprising a water cup assembly, wherein the water cup assembly comprises: a cup, wherein the columnar filtering screen is accommodated in the cup, and the cup comprises a bottom surface; a drive accommodating portion, connected to the cup and configured to accommodate at least a motor of the drive assembly; and the drive assembly comprises: a motor, arranged in the drive accommodating portion, wherein an output shaft of the motor is arranged along a radial direction of the cup and extends toward an outside of the drive accommodating portion; an active wheel, arranged outside the drive accommodating portion and connected to the output shaft of the motor; and a driven wheel, arranged outside the drive accommodating portion and in transmission connection with the active wheel, wherein an output shaft of the driven wheel is inserted into the cup from the bottom surface of the cup.

13. The filtering device according to claim 1, further comprising: a tray, wherein a spray arm interface is arranged on the tray; and at least two spray arm adapters, connected to the spray arm interface; wherein the drive assembly comprises: a water wheel housing, arranged on the tray and defining a drive fluid cavity, wherein the drive fluid cavity is communicated with one of the at least two spray arm adapters, such that water delivered to the one of the at least two spray arm adapters enters the drive fluid cavity; a water wheel, accommodated in the drive fluid cavity and rotatable under drive of a force exerted on the water wheel by the water entering the drive fluid cavity, wherein the water wheel is connected to at least a portion of the rotary filter for driving the columnar filtering screen to rotate relative to the contents within the columnar filtering screen; and a drain pipe, communicated with the drive fluid cavity and the columnar filtering screen for discharging water from the drive fluid cavity into the columnar filtering screen.

14. A filtering device for a tableware washing apparatus, comprising: a rotary filter comprising a columnar filtering screen configured to filter water from a washing process of the tableware washing apparatus, wherein a diameter of an external circle defined by each mesh of the columnar filtering screen is between 0.2 to 0.5 mm; and a drive assembly, connected to the rotary filter and configured to drive the columnar filtering screen to rotate relative to contents within the columnar filtering screen at a relative speed of 100 to 1000 r/min, configured to separate at least a portion of a residue on the columnar filtering screen from the columnar filtering screen, further comprising: a plane filter, connected to the rotary filter and comprising: a face-shaped screen holder, defining a first opening, wherein the columnar filtering screen is disposed below the face-shaped screen holder and facing the first opening, for allowing the water to fall from the first opening into the columnar filtering screen below the face-shaped screen holder; and a first face-shaped screen and a second face-shaped screen arranged side by side in a first direction, wherein an area of the first

face-shaped screen is greater than an area of the second face-shaped screen, a first angle is formed between the first face-shaped screen and a reference plane perpendicular to an axial direction of the first opening, and a second angle is formed between the second face-shaped screen and the reference plane, the first angle being less than the second angle.

15. The filtering device according to claim 14, wherein the first angle and the second angle are set such that a distance from an outer edge of the first face-shaped screen away from the second face-shaped screen along the first direction and/or a second direction to the reference plane along the axial direction of the first opening is the same as a distance from an outer edge of the second face-shaped screen away from the first face-shaped screen along the first direction and/or the second direction to the reference plane along the axial direction of the first opening, the second direction being perpendicular to the first direction.

16. The filtering device according to claim 14, further comprising a cup, wherein the columnar filtering screen is accommodated in the cup, and the face-shaped screen holder comprises: an outer frame; an inner frame, embedded within the outer frame and facing the first opening; and at least one support rib, connected between the outer frame and the inner frame, wherein edges of the first face-shaped screen and the second face-shaped screen abut against the outer frame, the inner frame, and the at least one support rib, respectively; wherein the rotary filter further comprises a columnar screen holder arranged in the cup, and the columnar filtering screen is fixed on the columnar screen holder; and the columnar screen holder is integrally molded with the inner frame or rotatably connected to the inner frame.

17. The filtering device according to claim 1, further comprising: a cup, comprising a peripheral wall, wherein the peripheral wall encloses a receiving cavity for receiving the columnar filtering screen, and the peripheral wall defines a first water outlet; and an outlet pipe, connected to the cup, wherein an end of the outlet pipe is connected to the cup and communicated with the receiving cavity through the first water outlet, and the other end of the outlet pipe defines a second water outlet, the outlet pipe defines an outlet channel; wherein a cross-sectional area of the outlet channel decreases along a direction from the first water outlet to the second water outlet, and a ratio of the cross-sectional area of the outlet channel at the first water outlet to the cross-sectional area of the outlet channel at the second water outlet is between 1.63 to 1.99.

18. The filtering device according to claim 1, further comprising a cup, wherein the cup comprises: a bottom wall; and a peripheral wall, connected to a side of the bottom wall, wherein the peripheral wall encloses a receiving cavity for receiving the columnar filtering screen, and the peripheral wall defines a first water outlet; and wherein a recess is defined on a side of the bottom wall toward the receiving cavity, and the recess is arranged adjacent to and communicated with the first water outlet.
