

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12397776
B2
August 26, 2025
Plaehn; Klaus et al.

Method for the automated guidance of a vehicle, journey control unit and vehicle

Abstract

A method for automated guidance of a vehicle along a specified setpoint trajectory at an actual speed, wherein the setpoint trajectory includes geometric trajectory variables, the method including ascertaining an actual deviation of the vehicle from the setpoint trajectory and outputting the ascertained actual deviation and generating manipulated variables such that the vehicle, in the case of automated control of a drive system and/or a braking system and/or a steering system of the vehicle, moves closer to the setpoint trajectory. The method also includes ascertaining whether an undesirable driving state is present when the vehicle moves closer to the setpoint trajectory, wherein the undesirable driving state is ascertained from the specified setpoint trajectory based on the geometric trajectory variable, and, if the presence of the undesirable driving state is identified, automatically controlling the vehicle based on generated stability variables and/or adapting the setpoint trajectory.

Inventors:	Plaehn; Klaus (Seelze, DE), Wulf; Oliver (Neustadt, DE), Boettcher; Jonas (Hannover, DE)
Applicant:	ZF CV SYSTEMS GLOBAL GMBH (Bern, CH)
Family ID:	1000008780521
Assignee:	ZF CV SYSTEMS GLOBAL GMBH (Bern, CH)
Appl. No.:	18/042000
Filed (or PCT Filed):	July 20, 2021
PCT No.:	PCT/EP2021/070203
PCT Pub. No.:	WO2022/037874
PCT Pub. Date:	February 24, 2022

Prior Publication Data

Document Identifier

US 20230322207 A1

Publication Date

Oct. 12, 2023

Foreign Application Priority Data

DE

10 2020 121 733.1

Aug. 19, 2020

Publication Classification

Int. Cl.: **B60W30/00** (20060101); **B60W10/04** (20060101); **B60W10/18** (20120101); **B60W10/20** (20060101); **B60W30/045** (20120101); **B60W50/00** (20060101); **B60W60/00** (20200101)

U.S. Cl.:

CPC **B60W30/045** (20130101); **B60W10/04** (20130101); **B60W10/18** (20130101); **B60W10/20** (20130101); **B60W50/0097** (20130101); **B60W60/001** (20200201); B60W2520/06 (20130101); B60W2520/10 (20130101); B60W2520/125 (20130101); B60W2520/14 (20130101); B60W2520/26 (20130101); B60W2530/10 (20130101); B60W2710/18 (20130101); B60W2710/20 (20130101); B60W2720/10 (20130101); B60W2720/18 (20130101)

Field of Classification Search

CPC: B60W (30/045); B60W (10/04); B60W (10/18); B60W (10/20); B60W (50/0097); B60W (60/001); B60W (2520/06); B60W (2520/10); B60W (2520/125); B60W (2520/14); B60W (2520/26); B60W (2530/10); B60W (2710/18); B60W (2710/20); B60W (2720/10); B60W (2720/18); B60W (2300/14); B60W (2520/18); B60W (2720/125); B60W (2720/14); B60W (10/184); B60W (30/02); B60Y (2200/147)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2006/0273657	12/2005	Wanke	303/146	B60T 8/17555
2007/0008090	12/2006	Gertsch	340/435	B60T 8/243
2007/0185638	12/2006	Odenthal	701/70	B60W 40/11
2012/0283907	12/2011	Lee	701/32.9	B60T 8/17557
2013/0218396	12/2012	Moshchuk	701/25	G08G 1/165
2014/0032049	12/2013	Moshchuk	701/42	G08G 1/166
2015/0105990	12/2014	Chimner	701/1	B60W 30/02
2017/0115662	12/2016	Mori	N/A	B60W 30/02
2018/0297587	12/2017	Kasaiezadeh Mahabadi	N/A	B60W 50/00

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
109017758	12/2017	CN	N/A
109050658	12/2017	CN	N/A
109552312	12/2018	CN	N/A
109823393	12/2018	CN	N/A
102012207548	12/2011	DE	N/A
102014008199	12/2014	DE	N/A
102015216236	12/2016	DE	N/A
102016005966	12/2016	DE	N/A
102018206018	12/2018	DE	N/A
2261093	12/2009	EP	N/A
3088281	12/2015	EP	B62D 1/28
3369634	12/2017	EP	N/A
3415389	12/2017	EP	B60W 30/02
3486135	12/2018	EP	N/A
WO-2005042321	12/2004	WO	B60T 8/17555
WO 2017102682	12/2016	WO	N/A

Primary Examiner: Nolan; Peter D

Assistant Examiner: Ning; Peter Y

Attorney, Agent or Firm: LEYDIG, VOIT & MAYER, LTD.

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application is a U.S. National Phase application under 35 U.S.C. § 371 of International Application No. PCT/EP2021/070203, filed on Jul. 20, 2021, and claims benefit to German Patent Application No. DE 10 2020 121 733.1, filed on Aug. 19, 2020. The International Application was published in German on Feb. 24, 2022 as WO 2022/037874 A1 under PCT Article 21(2).

FIELD

(2) The invention relates to a method for the automated guidance of a vehicle, to a journey control unit for carrying out the method, and to a vehicle.

BACKGROUND

(3) It is known from the prior art that vehicles controlled in an automated manner have a “virtual driver”, which is implemented by an electronic VD unit and in which there is defined in an automated manner a setpoint trajectory, along which the vehicle is to move in an automated manner. A surroundings acquisition system monitors here whether the vehicle is actually moving along the setpoint trajectory. If there is an actual deviation between the current position of the vehicle and the setpoint trajectory, manipulated variables are ascertained on the basis of this in a first motion control unit, with which corresponding actuators of a drive system and/or of a braking system and/or of a steering system are automatically controlled such that the position of the vehicle moves closer to the setpoint trajectory again. To fulfil this task, the first motion control unit has at

its disposal a model, parameters and measurement variables of the vehicle, as well as the methods from the field of control engineering.

(4) The problem here is that when the actuators are controlled with the manipulated variables, the stability of the vehicle can only be ensured at low actual vehicle speeds and on roadways with high friction values. However, an automatically controlled vehicle, for example a commercial vehicle or a bus, which is controlled in an automation stage according to an SAE level between 3 and 5, is also operated at high actual speeds and on roadways with low friction values. Therefore, with such a first motion control unit, a stable driving state cannot be ensured in every automated driving situation, such that undesirable driving states may occur.

(5) Stability control systems are also known that support a manual driver in stability-critical driving situations by means of automated intervention in the drive system and/or the braking system and/or the steering system, wherein this is described by way of example in WO 2017/102682 A1 or CN109017758A. However, these stability control systems are adapted to the behavior of the manual driver, such that they are not applicable in every driving situation to an automated driving situation with a setpoint trajectory specified automatically. The difference here is that the driver's reaction is not predictable, but the driver continues to monitor the driving situation and can also react to a system reaction.

(6) Furthermore, EP2261093A1 provides for monitoring a yaw rate for a future path of the vehicle depending on the driver's behavior. Based on current state parameters and the course of the road, a simulated trajectory is ascertained, along which the driver will probably guide the vehicle manually. Depending on this, a yaw rate-dependent evaluation of the driving state takes place. Also in US2007185638A, CN109050658A and CN109552312 A, the manually controlled vehicle is controlled on the basis of the yaw rate as part of an assistance function in order to set a stable driving state.

(7) In DE 102016005966A1, DE102014008199A1 and US2015105990A, yaw rate monitoring is further provided in which a correction steering angle is set to keep the vehicle stable. In US2007008090A, rollover prevention is also provided by predictively ascertaining a trajectory that is manually specified by the driver.

(8) In US2018297587A1 it is envisaged to determine an ideal state vector for the current point in time and for future points in time from automatically specified requirements for the drive system and/or the braking system and/or the steering system (also for the current point in time and/or for a point in time in the future). A setpoint yaw moment is then ascertained from this ideal state vector and this yaw moment is fed to a stability control system, which in turn influences the vehicle dynamics in an automated manner to avoid instability. Therefore, the driving state is ascertained based on automatically specified setpoint requirements, and a yaw moment-dependent stability control is performed.

SUMMARY

(9) In an embodiment, the present disclosure provides a method for automated guidance of a vehicle along a specified setpoint trajectory at an actual speed, wherein the setpoint trajectory includes geometric trajectory variables, the method comprising ascertaining an actual deviation of the vehicle from the setpoint trajectory, outputting the ascertained actual deviation and generating manipulated variables based on the ascertained actual deviation such that the vehicle, in the case of automated control of a drive system and/or a braking system and/or a steering system of the vehicle, moves closer to the setpoint trajectory based on the generated manipulated variables if the vehicle deviates from the setpoint trajectory, ascertaining whether an undesirable driving state is present at a current time and/or for a future time when the vehicle moves closer to the setpoint trajectory based on the generated manipulated variables, wherein the undesirable driving state is ascertained from the specified setpoint trajectory based on the geometric trajectory variable, and, if the presence of the undesirable driving state is identified at the current time and/or for a future

time, automatically controlling the vehicle based on generated stability variables and/or adapting the setpoint trajectory.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Subject matter of the present disclosure will be described in even greater detail below based on the exemplary figures. All features described and/or illustrated herein can be used alone or combined in different combinations. The features and advantages of various embodiments will become apparent by reading the following detailed description with reference to the attached drawings, which illustrate the following:

(2) FIG. 1 illustrates a schematic view of an automatically controllable vehicle;

(3) FIG. 1a illustrates an exemplary setpoint trajectory;

(4) FIG. 2 illustrates a detailed view of the vehicle according to FIG. 1;

(5) FIG. 3 illustrates a detailed view of an embodiment of the vehicle according to FIG. 1; and

(6) FIG. 4 and FIG. 5 show flow diagrams of a method according to an embodiment of the invention.

DETAILED DESCRIPTION

(7) In an embodiment, the present invention provides a method for automated guidance of a vehicle, which ensures safe and reliable operation of the vehicle. In an embodiment, the present invention also provides a journey control unit (also referred to herein as a travel control unit) and a vehicle.

(8) According to an embodiment of the invention, a method is provided for the automated guidance of a vehicle along a specified setpoint trajectory at an actual speed, wherein the setpoint trajectory is characterized by geometric or kinematic trajectory variables, the method comprising at least the following steps: ascertaining an actual deviation of the vehicle from the setpoint trajectory at a current time and/or for a future time within a specific time interval, preferably in a VD unit; outputting the ascertained actual deviation to a first motion control unit and generating manipulated variables on the basis of the ascertained actual deviation in such a way that, in the case of automated control of a drive system and/or a braking system and/or a steering system of the vehicle, the vehicle moves closer to the setpoint trajectory on the basis of the generated manipulated variables at a current time and/or for a future time within a specific time interval if the vehicle deviates from the setpoint trajectory, ascertaining (in a second motion control unit) whether an undesirable driving state is present at a current time and/or for a future time when the vehicle moves closer to the setpoint trajectory on the basis of the generated manipulated variables, wherein the undesirable driving state is ascertained from the specified setpoint trajectory on the basis of the geometric trajectory variables which characterize the setpoint trajectory; and if the presence of an undesirable driving state is determined at the current time and/or for a future time controlling the vehicle in an automated manner on the basis of generated stability variables and/or adapting the setpoint trajectory.

(9) In this case, the manipulated variables can be overwritten by the stability variables if an undesirable driving state is present, or the manipulated variables can be adapted accordingly on the basis of the stability variables in order to react to an undesirable driving state. The automated control of the vehicle can thus be adapted according to the ascertained driving state. Instead of or in addition to an adaptation on the basis of the stability variables, the setpoint trajectory can also be adapted directly, so that an adapted setpoint trajectory is already specified for the motion controller and an adaptation on the basis of the stability variables is no longer necessarily required. The vehicle then moves automatically along a specified path on which the currently detected undesirable driving states no longer occur or only occur to a lesser extent. This adapted setpoint

trajectory can then be fed back into the method according to an embodiment of the invention as a “specified trajectory”.

(10) Advantageously, this means that the setpoint trajectory, i.e., the path which is preferably described geometrically by individual setpoint positions and setpoint rotations of the vehicle assigned to them and which is to be followed in the future by automated control of the vehicle, can be used directly to check whether the vehicle is currently or in the future will be prone to instabilities or undesirable driving states. This eliminates the need for a more imprecise analysis of the processed and already issued requests, such that the path specified by the virtual driver is used directly to evaluate stability. This makes the ascertainment of an undesirable driving state more accurate and also independent of the actuators used or the preprocessing prior to the output of the individual requests to the drive system, braking system or steering system. Flexibility is thus increased. Overall, the aim of the method is no longer to support the human driver, e.g. in the case of high lateral dynamics or at a low friction value, but to support the “virtual driver” in exactly the same situations in precisely following the setpoint trajectory (setpoint position and setpoint rotation) specified by the human driver. The “virtual driver” is implemented here in the automatically controlled vehicle by the electronic VD unit. The VD unit defines here a setpoint trajectory along which the vehicle is to move automatically.

(11) Preferably, it is provided that in a method according to an embodiment of the invention: the ascertainment of an actual deviation of the vehicle from the setpoint trajectory is performed in a VD unit; the generation of manipulated variables on the basis of the ascertained actual deviation is carried out in a first motion control unit; and the ascertainment of whether an undesirable driving state is present at a current time and/or for a future time is carried out in a second motion control unit, wherein the generation of the manipulated variables in the first motion control unit is carried out independently of the ascertainment of the undesirable driving state in the second motion control unit and/or the ascertainment of an actual deviation in the VD unit is carried out independently of the ascertainment of the undesirable driving state in the second motion control unit.

(12) The second motion control unit thus advantageously provides a simple extension option for an existing automated control system in a vehicle with a “virtual driver”, who specifies in an automated manner the setpoint trajectory, and a first motion control unit, which automatically implements the movement along the setpoint trajectory, wherein this extension can additionally avoid stability-critical states. This makes it easy to retrofit a method or device according to an embodiment of the invention into a vehicle with an automated control system that does not have automated stability control, since the second motion control unit only has to be connected to the existing system via appropriate interfaces.

(13) Advantageously, however, to avoid stability-critical states during an automated journey, an independent solution can also be provided that can be designed independently of the conventional automated system in the vehicle, which is equipped with a virtual driver and a first motion control unit. The vehicle manufacturer in question can thus design and implement the automated system independently of the system that provides stability during the automated journey. This simplifies the effort for the vehicle manufacturer in question. In principle, however, it is also possible to integrate the individual components for stability into the components of the overall automated system if it is not necessary to retrofit or extend the existing system.

(14) Preferably, it is also provided that the ascertainment of whether an undesirable driving state is present at a current time and/or for a future time is additionally carried out on the basis of vehicle information about the vehicle and/or on the basis of a vehicle actual dynamic and/or on the basis of setpoint requirements for automated control of the drive system and/or the braking system and/or the steering system. Advantageously, this allows an exact comparison of the extent to which the actual behavior of the vehicle deviates from the setpoint behavior and the extent to which this can lead to instability. By additionally taking vehicle parameters into account, other factors influencing stability can also be used. The consideration of the setpoint requirements additionally leads to the

fact that in case of a deviation from the current setpoint trajectory, the setpoint dynamics currently requested in response to this can also be included. In particular, this means that a currently “requested” setpoint yaw rate can be included.

(15) Preferably, it is provided here that the setpoint requirements are ascertained on the basis of the actual deviation, wherein longitudinal setpoint requirements are used to correct a position and/or actual rotation of the vehicle deviating from the setpoint trajectory (setpoint position and setpoint rotation) in the direction of travel of the vehicle, and lateral setpoint requirements are used to correct a position and/or actual rotation of the vehicle deviating from the setpoint trajectory (setpoint position and setpoint rotation) perpendicular to the direction of travel. Advantageously, this allows a targeted separation into lateral and longitudinal motion components, which simplifies the subsequent analysis and also the adaptation of the control signals in the event of instability. If only lateral motion components are affected by an instability, these can be adapted in a simple manner without necessarily also noticeably changing longitudinal motion components, and vice versa.

(16) In conjunction with this, it is preferably further provided that a drive manipulated variable and/or a braking manipulated variable and/or a steering manipulated variable are ascertained as manipulated variables on the basis of the actual deviation, wherein the drive system of the vehicle can be automatically controlled on the basis of the drive manipulated variable and the braking system of the vehicle can be automatically controlled on the basis of the braking manipulated variable and the steering system of the vehicle can be automatically controlled on the basis of the steering manipulated variable, in order to approximate the position and/or the actual rotation of the vehicle to the setpoint trajectory (setpoint position and setpoint rotation). Accordingly, manipulated variables can be ascertained separately for each system and, on the basis of the driving state, can also be adapted independently of one another on the basis of the stability variables. This provides increased flexibility.

(17) Preferably, the presence of an undesirable driving state is therefore ascertained if it follows from the specified setpoint trajectory on the basis of the geometric trajectory variables that the vehicle is unstable at the current time and/or an unstable state is imminent for a future time. According to one embodiment, the presence of an undesirable driving state is ascertained here if a yaw rate deviation between a setpoint yaw rate and an actual yaw rate at the current time and/or for a future time exceeds a deviation limit value, wherein the setpoint yaw rate at the current time and/or for a future time follows indirectly or directly from the specified setpoint trajectory on the basis of the geometric trajectory variables. Advantageously, an (imminent) instability can thus be ascertained on the basis of the yaw behavior of the vehicle, which is derived from the geometric setpoint trajectory.

(18) Direct determination of the setpoint yaw rate from the specified setpoint trajectory means that the setpoint yaw rate is ascertained in time from the setpoint position and the setpoint rotation. In the case of an indirect determination of the setpoint yaw rate from the specified setpoint trajectory, reference can be made, for example, to the setpoint requirements that follow directly from the setpoint trajectory. The setpoint requirements can be used to take into account the actual current setpoint dynamics that result from deviations from the setpoint trajectory.

(19) Preferably, if the deviation limit value is exceeded on the basis of the yaw rate deviation, the following can be generated and output as a stability variable a first drive stability variable for limiting the actual speed of the vehicle and/or a first braking stability variable for reducing the actual speed of the vehicle

(20) in such a way that, in the case of automated control of the vehicle on the basis of the first drive stability variable and/or the first braking stability variable, the actual speed of the vehicle does not exceed a specified limit speed. The particular manipulated variable for the drive or the brakes can thus be specifically adapted on the basis of the yaw rate deviation, which in the case in question is effected exclusively by a change in the longitudinal movement (adaptation of the speed), so that an

effective reaction can be made to understeer or oversteer, for example.

(21) Additionally or alternatively, an intervention in the lateral movement of the vehicle can also be made in that, if the deviation limit value is exceeded, on the basis of the yaw rate deviation as a stability variable a second braking stability variable for wheel-specific braking of the vehicle and/or a first steering stability variable for steering the vehicle

(22) is generated and output in such a way that, during automated control of the vehicle on the basis of the second braking stability variable and/or the first steering stability variable, the actual yaw rate moves closer to the setpoint yaw rate. In this way, the yaw movement, which can or could lead to instability, is counteracted in a targeted manner without necessarily also changing a longitudinal movement of the vehicle.

(23) Preferably, it can also be provided in all cases that the first drive stability variable and/or the first braking stability variable and/or the second braking stability variable and/or the first steering stability variable are generated on the basis of a yaw rate deviation change in addition to or as an alternative to the yaw rate deviation, wherein the yaw rate deviation change indicates how the yaw rate deviation changes from the current time. This allows the changes in motion control to also be included in order to be able to react adequately to special driving states.

(24) Preferably, it is further provided that a second steering stability variable is generated and output for preventing an undesirable driving state, wherein the second steering stability variable is generated on the basis of the actual speed of the vehicle and/or a setpoint curve radius derived from the setpoint trajectory, and/or a braking yaw moment, wherein the braking yaw moment is ascertained on the basis of wheel slip, acting differently at the sides, of wheels of the vehicle, and/or a tilt angle of the vehicle with respect to the roadway, taking into account a current vehicle mass.

(25) Advantageously, this allows the current vehicle dynamics to be monitored even more precisely, in particular with regard to the vehicle's self-steering behavior, μ -split braking in the case of different friction values of the ground at the sides, and the vehicle's tilt behavior, all of which have an influence on the movement of the vehicle in the lateral direction. Accordingly, a countersteering can be engaged in a stabilizing manner on the basis of the steering stability variable in order to keep the vehicle stable on the specified setpoint trajectory. The necessary parameters (setpoint curve radius, wheel slip, tilt angle) are available to the system via the interfaces in the vehicle, since they are already detected and output as part of other stability control systems in the vehicle. Therefore, no additional components are required.

(26) Preferably, the presence of an undesirable driving state is furthermore ascertained if a lateral acceleration of the vehicle at the current time and/or for a future time exceeds a limit lateral acceleration, wherein the lateral acceleration at the current time is measured and/or for the future time is estimated from the specified setpoint trajectory on the basis of the geometric trajectory variables. This means that the method can also be used to react to such stability-critical situations in the lateral direction with appropriate intervention in the vehicle dynamics.

(27) Preferably, if the limit lateral acceleration is exceeded at the current time and/or for a future time, a second drive stability variable and/or a third braking stability variable is generated and output as a stability variable in such a way that, in the case of automated control of the vehicle, the lateral acceleration of the vehicle falls to or below the limit lateral acceleration on the basis of the third braking stability variable and/or the second drive stability variable. In this way, the longitudinal movement of the vehicle is adapted in a targeted manner in order to avoid excessive lateral acceleration.

(28) Preferably, it is also provided that the setpoint trajectory is adapted on the basis of a stability indicator, wherein the stability indicator indicates, on the basis of a current vehicle actual dynamic and the current setpoint trajectory, how probable an undesirable driving state is at a point in time between the current time and a future point in time. Advantageously, the undesirable driving state is thus quantitatively evaluated by a characteristic variable so that the setpoint trajectory can be

adapted in such a way that this undesirable driving state can be avoided as far as possible when the adapted setpoint trajectory is followed, and further corrective interventions on the basis of the stability variables can be omitted or at least reduced to a minimum.

(29) Preferably, the stability indicator is formed depending on at least one feature selected from the group consisting of: an articulation angle deviation between a current actual articulation angle and a setpoint articulation angle, a yaw rate deviation between an actual yaw rate and a setpoint yaw rate, the exceeding of a limit lateral acceleration, a wheel slip of the individual wheels of the vehicle, the presence of an ABS intervention, the presence of an ESC intervention and/or load information. All of these parameters and, if necessary, other parameters available in the vehicle can be used for a quantitative evaluation of the undesirable driving state.

(30) According to an embodiment of the invention, a travel control unit is further provided, which is designed for carrying out the method according to an embodiment of the invention, wherein the travel control unit at least comprises: a VD unit for defining a setpoint trajectory, wherein the setpoint trajectory is characterized by geometric trajectory variables, and for outputting an actual deviation if the vehicle deviates from the setpoint trajectory, a first motion control unit, wherein the first motion control unit is designed to generate manipulated variables on the basis of the actual deviation in such a way that, in the case of automated control of a drive system and/or a braking system and/or a steering system of the vehicle, the vehicle moves closer to the setpoint trajectory on the basis of the generated manipulated variables if the vehicle deviates from the setpoint trajectory, a second motion control unit, wherein the second motion control unit is designed to ascertain whether an undesirable driving state is present at a current time and/or for a future time when the vehicle moves closer to the setpoint trajectory on the basis of the generated manipulated variables, wherein the undesirable driving state can be ascertained from the specified setpoint trajectory on the basis of the geometric trajectory variables, wherein furthermore at least one logic unit is provided, wherein the at least one logic unit is designed to generate and output a logic signal for the automated control of the drive system and/or the braking system and/or the steering system of the vehicle, wherein the logic signal can be generated and output as a function of generated stability variables in the presence of an undesirable driving state, and/or the VD unit is designed to adapt the setpoint trajectory if an undesirable driving state is present.

(31) According to an embodiment of the invention, therefore, a retrofittable journey control unit is described that can be easily integrated into the existing infrastructure in a vehicle, for example by connecting to the existing interfaces in the vehicle, for example a CAN data bus. The journey control unit can, for example, be part of an electronic braking system in which individual variables are already ascertained and also used. This makes it easy to retrofit.

(32) The first and/or the second motion control unit can also be integrated here in the VD unit in which the setpoint trajectory is specified. It is also possible to combine the first motion control unit and the second motion control unit. However, in order to achieve full flexibility, it is advantageous to provide both control units separately from each other, such that, for example, only the second motion control unit, which can be used to detect an undesirable driving state and with the aid of which this undesirable driving state can be reacted to accordingly, may be added by the vehicle manufacturer to an existing first motion control unit. The function of the first motion control unit, which is used for stable driving, can therefore be extended by simply retrofitting the second motion control unit. It must be connected for this purpose to the corresponding existing interfaces in the vehicle.

(33) Preferably, it is also provided that the drive system and/or the braking system and/or the steering system are each assigned a logic unit, wherein the drive system can be automatically controlled with a drive logic signal, the braking system with a braking logic signal, and the steering system with a steering logic signal. The logic signal in question can be ascertained here via a system logic in the corresponding logic unit in order to control the vehicle accordingly on the basis of the stability variables in the event of an undesirable driving state, i.e. exclusively with the

generated stability variables, or the manipulated variables being adapted on the basis of the generated stability variables. In this way, a high degree of flexibility can be achieved, since the system logic can be used to decide individually for each lateral or longitudinal control component how to react to an instability or how the vehicle should move in relation to the setpoint trajectory. (34) Preferably, it is further provided that the second motion control unit comprises a yaw rate controller, wherein the yaw rate controller is designed to infer the presence of an undesirable driving state on the basis of an ascertained yaw rate deviation and to react by ascertaining and outputting a corresponding stability variable. Furthermore, the second motion control unit can comprise an RSC unit, wherein the RSC unit is designed to infer the presence of an undesirable driving state on the basis of an exceeding of the limit lateral acceleration and to react by ascertaining and outputting a corresponding stability variable.

(35) In addition, the second motion control unit can have a stabilization monitor, wherein the stabilization monitor is designed to form a stability indicator on the basis of a current actual vehicle dynamic and the current setpoint trajectory, wherein the stability indicator indicates, on the basis of time, how likely an undesirable driving state is at a time between the current time and the future time. This allows a quantitative assessment of the undesirable driving state, which the VD unit can use to adapt the setpoint trajectory.

(36) According to an embodiment of the invention, a vehicle with a journey control unit according to an embodiment of the invention is further provided for the automated guidance of the vehicle along a specified setpoint trajectory or an adapted setpoint trajectory.

(37) FIG. 1 schematically shows a vehicle 1 moving on a roadway 2. The vehicle 1 can be single-part or multi-part, i.e. consisting of a towing vehicle 1a and a trailer 1b, for example a commercial vehicle or a bus. The vehicle 1 can be controlled in an automated manner with the aid of a travel control device 3, wherein automation levels according to SAE level 3 to 5 are provided. Two journey control devices 3 are shown by way of example in FIGS. 2 and 3.

(38) The journey control device 3 therefore has a VD unit 3a (Virtual Driver) in which, on the basis of criteria, for example a detected road course or the current surroundings U around the vehicle 1, there is defined a setpoint trajectory TS along which the vehicle 1 is to move automatically in the future. The setpoint trajectory TS is a future path here that is to be followed by automated control of a drive system 6 and/or a braking system 7 and/or a steering system 8 in the vehicle 1. The setpoint trajectory TS is characterized here by kinematic trajectory variables kG, so that the planned movement of the vehicle 1 or the future path is described exclusively geometrically, i.e. there is a geometrically described setpoint trajectory TS.

(39) According to FIG. 1a, kinematic trajectory variables kG can be, for example, setpoint positions PSoll (required position), which are described by x-coordinates x and y-coordinates y of a preferably Cartesian coordinate system, as well as a setpoint rotation PhiSoll of the vehicle 1 at the respective times t0, t1, t2. The setpoint rotation PhiSoll indicates here how the vehicle 1 is oriented at the particular setpoint position PSoll. The setpoint position PSoll as well as the setpoint rotation PhiSoll can be described here relatively, i.e., in relation to the previous state, or absolutely, i.e., in relation to a starting point.

(40) Via the travel control device 3, the method shown as an example in FIG. 4 can be carried out as follows:

(41) The VD unit 3a first evaluates sensor signals S4 from sensors 4 of a surroundings acquisition system 5 to ascertain in a first step ST1 whether the vehicle 1 is actually moving along the geometrically defined setpoint trajectory TS. For this purpose, an actual deviation dTS between the vehicle 1 and the setpoint trajectory TS, i.e., a deviation between the current position P1 and an actual rotation PhiIst of the vehicle 1 from the geometric trajectory variables kG (PSoll, PhiSoll) defined in the setpoint trajectory TS, is determined. The actual deviation dTS can therefore be described geometrically by an x-deviation dx in the x-direction, a y-deviation dy in the y-direction (deviation between P1 and PSoll) and a rotational deviation dPhi. From this actual deviation dTS, it

can be concluded which change in motion is necessary or how the vehicle **1** is to be controlled so that it moves along the geometric setpoint trajectory TS again in the future.

(42) Both the setpoint trajectory TS and the actual deviation dTS (or related variables) are output from the VD unit **3a** in a trajectory signal S3a. The trajectory signal S3a is output to both a specification unit **3b** (motion control) and a second motion control unit **20**, the function of which will be explained in more detail later. The output can also be separate signals in the same way.

(43) Based on the actual deviation dTS, in a second step ST2 a setpoint speed vSoll and/or a setpoint acceleration aSoll (positive or negative) as longitudinal setpoint requirements AS11, which relate to the future desired longitudinal movement of the vehicle **1**, and a setpoint curve radius RSoll or a setpoint curve radius change dRSoll as lateral setpoint requirements AS12, which relate to the future desired lateral movement of the vehicle **1**, are ascertained in the specification unit **3b**, for example. The ascertainment follows in such a way that, when the drive system **6** and/or the braking system **7** and/or the steering system **8** are controlled, the vehicle **1** again moves closer to the defined setpoint trajectory TS (i.e. the setpoint position PSoll and the setpoint rotation PhiSoll) on the basis of these setpoint requirements AS11, AS12. The setpoint requirements AS11, AS12 are output via a specification signal S3b.

(44) The setpoint requirements AS11, AS12, which characterize the future desired movement of the vehicle **1**, are then transmitted to a first motion control unit **10** and also to the second motion control unit **20** in a third step ST3. According to the implementation in FIG. 2, the first motion control unit **10** and the second motion control unit **20** are separated from each other. The second motion control unit **20** can therefore be designed and operated completely independently of the first motion control unit **10**, so that the system can be variably retrofitted and extended. According to the embodiment of FIG. 3, however, both control units **10**, **20** can also be combined in an overall motion control unit **30**.

(45) The first motion control unit **10** is divided into a longitudinal controller **11** and a lateral controller **12**. The longitudinal setpoint requirements AS11 affecting the longitudinal movement of the vehicle **1** are processed in the longitudinal controller **11** and the lateral setpoint requirements AS12 affecting the lateral movement of the vehicle **1** are processed in the lateral controller **12**. Similarly, it can be provided that the specification unit **3b** is integrated in the first motion controller **10** and the corresponding setpoint requirements AS11, AS12 are output directly to the relevant controller **11**, **12** and in a further signal to the second motion control unit **20**.

(46) In a first sub-step ST3.1, the longitudinal controller **11** ascertains a drive manipulated variable GA10, for example a drive force or a related variable, and a braking manipulated variable GB10, for example a braking force or a related variable, on the basis of the longitudinal setpoint requirements AS11. The drive manipulated variable GA10 and the braking manipulated variable GB10 specify manipulated variables with which the relevant actuators in the vehicle **1**, preferably the drive motor, service brakes, sustained-action brakes, etc., are to be controlled in order to implement the longitudinal setpoint requirement AS11.

(47) In addition, in a second sub-step ST3.2, a steering manipulated variable GL10, for example a steering angle or a related variable, is ascertained by the lateral controller **12** on the basis of the lateral setpoint requirements AS12. The steering manipulated variable GL10 specifies a manipulated variable with which the relevant actuator of the vehicle **1**, preferably a servomotor of the steering system **8**, is to be controlled in order to implement the lateral component of the setpoint requirements AS12.

(48) The manipulated variables GA10, GB10, GL10 ascertained in this way are output in a fourth step ST4 via a first drive control signal SA10 or a first braking control signal SB10 or a first steering control signal SL10. The first drive control signal SA10 is transmitted to a first input 13A1 of a drive logic unit **13A**, the first braking control signal SB10 is transmitted to a first input 13B1 of a braking logic unit **13B**, and the first steering control signal SL10 is transmitted to a first input 13L1 of a steering logic unit **13L**.

(49) The particular logic unit **13A**, **13B**, **13L** is capable of outputting a logic signal **SVA**, **SVB**, **SVL** depending on the signals present at its inputs **13A1**, **13A2**, **13A3**, **13B1**, **13B2**, **13B3**, **13L1**, **13L2**, **13L3**. Depending on the particular logic signal **SVA**, **SVB**, **SVL**, a drive control unit **6a** of the drive system **6** or a braking control unit **7a** of the braking system **7**, or a steering control unit **8a** of the steering system **8** is subsequently controlled. How the logic signal **SVA**, **SVB**, **SVL** is ascertained in the corresponding logic unit **13A**, **13B**, **13L** depends on the control logic stored therein.

(50) If, in a fifth step **ST5**, the particular logic unit **13A**, **13B**, **13L** transmits the first drive control signal **SA10** or the first braking control signal **SB10** or the first steering control signal **SL10** as logic signals **SVA**, **SVB**, **SVL** to the corresponding control unit **6a**, **7a**, **8a** on the basis of the control logic implemented therein, these can control the corresponding actuators of the drive system **6**, i.e., for example, the drive motor of the vehicle **1**, or of the braking system **7**, i.e., for example, the service brakes and/or the sustained-action brakes, or of the steering system **8**, i.e., a servomotor, accordingly. In this way, the setpoint requirements **AS11**, **AS12**, which were issued on the basis of the detected actual deviation **dTS**, can be implemented in order to bring the position **P1** of the vehicle **1** and the actual rotation **Phi1st** closer to the setpoint trajectory **TS** in the future.

(51) In order to ensure stable driving even with such automated control of the vehicle **1** via the first motion control unit **10**, the second motion control unit **20** is provided, which preferably only intervenes if undesirable driving states **Z1u**, e.g. stability-critical driving states, are already present at the current time **t0** or if these are highly likely to occur in a specified time period **dt** between the current time **t0** and a future time **tZ**. To achieve this, the second motion control unit **20** is designed to evaluate the state of the vehicle **1** with regard to its stability on the basis of the setpoint trajectory **TS** specified via the trajectory signal **S3a** and the setpoint requirements **AS11**, **AS12** output via the specification signal **S3b** and additionally on the basis of vehicle information **IF** (vehicle model) and a vehicle actual dynamic **FD1st** (ego motion) and to specifically influence the motion of the vehicle **1** on the basis thereof.

(52) For this purpose, the second motion control unit **20** determines a driving state **Z1** in several stabilization steps, depending on which the manipulated variables **GA10**, **GB10**, **GL10** resulting from the setpoint requirements **AS11**, **AS12** are adapted. The driving state **Z1** can, for example, be an undesirable driving state **Z1u** in which the vehicle **1** is unstable at the current time **t0** and/or instability is imminent in the future within the specified time period **dt**.

(53) The second motion control unit **20** carries out the method steps described below (see FIG. 5) continuously and in parallel with the method steps according to FIG. 4, which are carried out by the first motion control unit **10**. As a result, the second motion control unit **20** is able to specifically adapt the above-described control of the vehicle **1** by the first motion control unit **10** if an undesirable driving state **Z1u** is present. The second motion control unit **20** has access here to any interfaces in the vehicle **1**, so that the second motion control unit **20** can read in vehicle information **IF** and/or the vehicle actual dynamics **FD1st** in a first stabilization step **ST51**.

(54) Here, vehicle information **IF** is understood to be information about the vehicle **1** that does not relate to the vehicle dynamics, but to the vehicle **1** itself. This includes configured vehicle parameters such as a wheelbase **A**, a track width **W** or a permissible total mass **zGM1** of the vehicle **1**, etc., but also vehicle parameters that can change during operation, e.g. a current total mass **M1** of the vehicle **1**, a maximum acceleration capacity **aMax** (positive or negative) or a brake pad wear **BV**, etc., which are measured, estimated or observed during operation. Furthermore, information as to whether the vehicle **1** has a hitched trailer **1b** can also be processed, or a vehicle height **FH** of the vehicle **1**.

(55) The vehicle actual dynamics **FD1st** is understood to be, among other things, the longitudinal movement of the vehicle **1** parallel to the direction of travel **FR**, which can be described, for example, by an actual speed **v1st**, an actual acceleration **a1st**, an actual distance **D1st** to an object in the direction of travel **FR**, etc. The vehicle actual dynamics **FD1st**, however, can also be specified

by variables describing the orientation of the vehicle **1**, for example by an actual yaw rate **G1st**, a tilt angle **N1st** with respect to the roadway **2**, or a relative orientation **ARel** of the vehicle **1** with respect to the direction of travel **FR**, or an actual articulation angle **KW1st** between a towing vehicle **1a** and trailer **1b**. Therefore, both the position and the orientation (pose) of the vehicle **1** in six degrees of freedom as well as their change via the respective derivatives can be ascertained from the vehicle actual dynamics **FD1st**.

(56) The vehicle actual dynamics **FD1st** can be ascertained here from sensor signals that measure or characterize a movement of the vehicle **1**, for example by wheel speed signals **S1c** from wheel speed sensors **1c** on wheels **1f** in the vehicle **1**, acceleration signals **S1d** from acceleration sensors **1d** (measuring transversely and longitudinally) in the vehicle **1**, and yaw rate signals **S1e** from a yaw rate sensor **1e** in the vehicle **1**. These sensors **1c**, **1d**, **1e** are here sensors that are already present in a braking system **7** that operates (partially) electrically, e.g. an EBS (electronic braking system), so that they can be accessed via a corresponding interface **1g**, e.g. a CAN interface. In addition, however, further sensors can also be provided in the vehicle **1**, via which, for example, a low actual speed **v1st**, the direction of travel **FR**, or the actual articulation angle **KW1st** between a towing vehicle **1a** and trailer **1b** can be ascertained, so that this information relating to the vehicle actual dynamics **FD1st** can also be accessed. The sensor signals of the individual sensors can also be fused here in order to achieve a higher accuracy and/or to check their plausibility.

(57) Depending on the vehicle information **IF** and/or the vehicle actual dynamics **FD1st**, the second motion control unit **20** can evaluate, in a plurality of stabilization steps, whether, in the presence of an actual deviation **dTS** for the specified setpoint trajectory **TS**, an implementation of the setpoint requirements **AS11**, **AS12** output by the specification unit **3b** leads or would lead to instabilities, or whether an undesirable driving state **Z1u** results or would result therefrom, and can respond accordingly.

(58) For this purpose, a yaw rate monitoring is performed in the second motion control unit **20** in a second stabilization step **STS2** via a yaw rate controller **21**. The yaw rate controller **21** is designed here to analyze the setpoint trajectory **TS** output by the **VD** unit **3a** in order to calculate therefrom a setpoint driving dynamic **FDSoll** for the current time **t0** and also for time points **t** within the specified time period **dt** up to the future time **tZ**, for example up to **t0+10 s**. The yaw rate controller **21** makes use here of the geometric trajectory variables **kG**, which characterize the future travel path or the setpoint trajectory **TS**, to estimate the setpoint driving dynamics **FDSoll**. Therefore, no requirements on the systems **6**, **7**, **8** in the vehicle **1** are evaluated, but directly the setpoint trajectory **TS** specified by the “Virtual Driver” (**VD** unit **3a**).

(59) For this purpose, a setpoint yaw rate **GSoll** can be ascertained from the geometric information (**PSoll**, **PhiSoll**) in the setpoint trajectory **TS**, in particular for the current time **t0**, e.g. via the single-track model. This setpoint yaw rate **GSoll** can be compared with the currently present actual yaw rate **G1st**, which follows from the transmitted vehicle actual dynamics **FD1st**, for example by determining a yaw rate deviation **dG** between the actual yaw rate **G1st** and the setpoint yaw rate **GSoll**. The driving state **Z1** can then be derived on the basis of the yaw rate deviation **dG**.

(60) It can be provided here that an undesirable driving state **Z1u** is output immediately for any yaw rate deviations **dG** other than zero (cf. **dGW=0**). However, it is also possible to allow a certain deviation from the setpoint yaw rate **GSoll** and to output an undesirable driving state **Z1u** only if, for example, the yaw rate deviation **dG** exceeds a defined deviation limit value **dGW**.

(61) Additionally or alternatively, the setpoint requirements **AS11**, **AS12** output by the specification unit **3b**, which are formed on the basis of the geometric setpoint trajectory **TS**, can also be taken into account in order to take into account the subsequently requested driving state of the vehicle **1** when determining the setpoint yaw rate **GSoll**.

(62) On the basis of the derived driving state **Z1** and thus the yaw rate deviation **dG**, the actual vehicle speed **v1st** can then be limited to a limit speed **vGrenz** in a first sub-step **STS2.1**. For this purpose, a first drive stabilization signal **SA21** with a first drive stability variable **GA21**, for

example a drive force limit, can be output from the yaw rate controller **21** to the second input **13A2** of the drive logic unit **13A**. Based on this, a drive logic signal SVA is output from the drive logic unit **13A** and is used to prevent the vehicle **1** from exceeding a specified limit speed v_{Grenz} linked to the drive force limit when the drive motor is controlled as an actuator of the drive system **6**. Thus, the drive manipulated variable GA**10** at the first input **13A1** of the drive logic unit **13A** is adapted in the presence of an undesirable driving state **Z1u**.

(63) If the limit speed v_{Grenz} is already exceeded, a first braking stabilization signal SB**21** with a first braking stability variable GB**21**, for example a braking force, is output from the yaw rate controller **21** to the second input **13B2** of the braking logic unit **13B**. Based on this, a braking logic signal SVB is output by the braking logic unit **13B** and is used to brake the vehicle **1** when the brakes and/or the sustained-action brakes are controlled as actuators of the braking system **7** in such a way that the vehicle **1** reaches or at least does not exceed the specified limit speed v_{Grenz} . In this way, the braking manipulated variable GB**10**, which results from the longitudinal setpoint requirement AS**11**, is specifically adapted on the basis of the driving state **Z1** or the undesirable driving state **Z1u**.

(64) In a second sub-step STS**2.2**, a setpoint yaw moment JSoll can be specified alternatively or additionally on the basis of the driving state **Z1** and can compensate for the yaw rate deviation dG . This setpoint yaw moment JSoll can be implemented, for example, by controlling the braking system **7** wheel-specifically in order to achieve steering braking. For this purpose, a second braking stabilization signal SBL with a second braking stability variable GBL, e.g. wheel-specific braking forces, can be output by the yaw rate controller **21** to the braking control device **7a** of the braking system **7**, which takes over this wheel-specific control of the brakes in order to thus compensate for the yaw rate deviation dG . In this way, too, the braking manipulated variable GB**10**, which results from the longitudinal setpoint requirement AS**11**, is specifically adapted on the basis of the driving state **Z1** or the undesirable driving state **Z1u**, since this results in a different braking force distribution to the individual wheels and, if necessary, also an adapted total braking force.

(65) Alternatively or additionally, the setpoint yaw moment JSoll can also be implemented by controlling the steering system **8** to effect a countersteering. In this way, it can be taken into account that the braking force for steering braking cannot be increased indefinitely at individual wheels via the second braking stabilization signal SBL or the second braking stability variable GBL, and that each reduction in the braking force at individual wheels results in a reduced overall braking force and thus an increased braking distance. In order to achieve such independent or at least assisting countersteering by the steering system **8**, a first steering stabilization signal SL**21** is generated by the yaw rate controller **21** with a first steering stability variable GL**21**, for example a steering angle with which the setpoint yaw moment JSoll can be effected fully or at least proportionally (in the case of a combination with steering braking).

(66) This first steering stabilization signal SL**21** is then output to the second input **13L2** of the steering logic unit **13L**. Based on this, a steering logic signal SVL is output by the steering logic unit **13L** and is used to steer the vehicle **1** when the steering system **8** is controlled, for example via a servomotor as actuator of the steering system **8**, in such a way that the setpoint yaw moment JSoll is fully or at least partially achieved. Depending on the driving situation, the first steering stabilization signal SL**21** can be superimposed at least proportionally on an already existing steering (steering control signal SL**10**) by the steering logic unit **13L**. In this way, too, the steering manipulated variable GL**10**, which results from the lateral setpoint requirement AS**11**, is specifically adapted on the basis of the driving state **Z1** or the undesirable driving state **Z1u**.

(67) The described monitoring of the yaw rate deviation dG can also be extended to other points in time t within the defined period between t_0 and dt . The geometrically described setpoint trajectory TS can be used to predict how the actual yaw rate G_{Ist} will behave in the future relative to the setpoint yaw rate G_{Soll} , which is derived from the setpoint trajectory TS, and how the yaw rate deviation dG will change over time. For example, by analyzing a yaw rate deviation change dG_C ,

an incipient understeer or oversteer or a maintenance of the setpoint trajectory TS but only with a sharply increasing steering angle can be detected. The geometric setpoint trajectory TS can therefore be used to predict whether, with regard to the yaw behavior of the vehicle **1**, an undesirable driving state **Z1u** is very likely to occur if, for example, the setpoint curve radius **RSoll** of the setpoint trajectory TS decreases further, or whether an undesirable driving state **Z1u** can be avoided if the setpoint curve radius **RSoll** increases again. The stabilization steps **STS2**, **STS2.1**, **STS2.2** can also be used to react adequately to this.

(68) In a third stabilization step **STS3**, a steering angle correction can be performed, which takes place in a correction unit **22**. In the case of low actual speeds **vIst** of the vehicle **1** and stable driving on roadways **2** with a high friction value, the steering manipulated variable **GL10**, which is instructed via the lateral setpoint requirement **AS12**, follows mainly from the vehicle geometry, i.e. for example the wheelbase **A**, the track width **W**, the actual articulation angle **KWIst**, etc., taking into account minor corrections. However, if more complex dynamics or higher actual speeds **vIst** and/or a roadway **2** with low friction values are present, further corrections are necessary. The driving state **Z1** without these further corrections can therefore be evaluated as an undesirable driving state **Z1u**, so that the following corrections are made by the correction unit **22**:

(69) In one variant (**STS3.1**), the self-steering behavior of the vehicle **1** can be taken into account according to a “linear bicycle model”, wherein the correction unit **22**, via a second steering stabilization signal **SLK**, outputs a second steering stability variable **GLK**, for example a steering angle, which is transmitted to a third input **13L3** of the steering logic unit **13L**. The second steering stability variable **GLK** is ascertained on the basis of the current vehicle actual dynamics **FDIst** and also on the basis of the vehicle information **IF**, which can be used to determine via the “linear bicycle model” how the steering angle or the steering manipulated variable **GL10** is to be adapted on the basis of the actual speed **vIst** of the vehicle **1** and/or the setpoint curve radius **RSoll** derived from the setpoint trajectory TS, in order to prevent or stop an undesirable driving state **Z1u**. In this case, the setpoint curve radius **RSoll** preferably follows from the lateral setpoint requirement **AS12**, which is also transmitted to the second motion control unit **20** and is ascertained by the specification unit **3b**. Via the steering logic unit **13L**, the lateral setpoint requirement **AS12** or the steering manipulated variable **GL10** can be adapted in a corresponding manner via a control logic implemented therein on the basis of the second steering stability variable **GLK**, whereupon a corresponding steering logic signal **SVL** is output.

(70) Furthermore, in the correction unit **22**, the behavior of the vehicle **1** on a friction coefficient split roadway **2** (μ -split) can be ascertained (**STS3.2**) on the basis of the vehicle actual dynamics **FDIst** via a dynamic model, which can lead to an undesirable driving state **Z1u** due to an acting braking yaw moment **JB**. For this purpose, for example, wheel slip **s1f** of wheels **1f** of the vehicle **1** can be used, said wheel slip being ascertained via the wheel speed signals **S1c** of the wheel speed sensors **1c**. From these, an actual yaw rate **GIst** of the vehicle **1** can be ascertained and this can be compared with the setpoint yaw rate **GSoll** resulting from the setpoint trajectory TS or the lateral setpoint demand **AS12**. From the yaw rate deviation **dG** resulting therefrom, a second steering stability variable **GLK** can also be ascertained by the correction unit **22** and describes which braking yaw moment **JB** is to be compensated by a steering system due to braking on the friction coefficient split roadway **2** in order to continue to ensure stable driving and to remedy the undesirable driving state **Z1u**. If the steering manipulated variable **GL10** is corrected or adapted with this second steering stability variable **GLK** in the steering logic unit **13L**, such a braking yaw moment **JB** can be compensated when the steering system **8** is controlled with a corresponding steering logic signal **SVL**.

(71) The correction unit **22** can also take into account the tilt angle **NIst** of the vehicle **1** relative to the roadway **2** (**STS3.3**). A higher tilt angle **NIst** must be compensated here by the steering system in order to maintain a stable driving state or to avoid an undesirable driving state **Z1u**. For this purpose, a model can be assumed in the correction unit **22** in which the tilt of the vehicle **1** or the

tilt angle N_{1st} and the current vehicle mass M_1 are used to determine the second steering stability variable GLK . If the steering manipulated variable GL_{10} is corrected with this second steering stability variable GLK in the steering logic unit **13L**, a tilt correction can take place when the steering system **8** is controlled with a corresponding steering logic signal SVL .

(72) In addition to the described corrections, further corrections by the correction unit **22** are also possible in order to react to undesirable driving states Z_{1u} .

(73) In addition to the yaw rate controller **21** and the correction unit **22**, the second motion control unit **20** also includes an RSC unit **23** (RSC, Roll Stability Control), which can be used in a fourth stabilization step STS_4 to prevent the vehicle **1** from tipping over as an undesirable driving state Z_{1u} . The RSC unit **23** monitors in particular a lateral acceleration a_q of the vehicle **1** at the current time t_0 , which follows, for example, from the acceleration signals S_{1d} of the acceleration sensors **1d**.

(74) If the lateral acceleration a_q exceeds a limit lateral acceleration a_{qG} , the RSC unit **23** concludes that an undesirable driving state Z_{1u} has occurred and thereupon outputs a second drive stability variable GA_{23} , for example a drive force limit, and/or a third braking stability variable GB_{23} , for example a braking force, which is output via corresponding signals SA_{23} , SB_{23} to third inputs **13A3**, **13B3** of the drive logic unit **13A** and the braking logic unit **13B**, respectively. A corresponding logic signal SVA , SVB is generated in the logic units **13A**, **13B** to appropriately control the drive system **6** and the braking system **7**, respectively, and to decelerate the vehicle **1** so that the lateral acceleration a_q falls back to or below the limit lateral acceleration a_{qG} and the undesirable driving state Z_{1u} is eliminated.

(75) In addition, the RSC unit **23** can also access the geometric or kinematic trajectory variables kG of the future motion of the vehicle **1** via the setpoint trajectory TS in order to evaluate whether the lateral acceleration a_q between the current time t_0 and the future time t_Z will exceed the limit lateral acceleration a_{qG} if the vehicle **1** continues to move, for example, at the current actual speed v_{1st} . The RSC unit **23** can then output the third braking stability variable GB_{23} and/or the second drive stability variable GA_{23} to the braking logic unit **13B** and the drive logic unit **13A**, respectively, even in advance, to prevent the exceeding of the limit lateral acceleration a_{qG} from occurring. In this way, an undesirable driving state Z_{1u} in the future can be ascertained and reacted to in advance.

(76) In a fifth stabilization step STS_5 , provision can be made to generate a return signal SR in a stabilization monitor **24** and to transmit this to the VD unit **3a**. The return signal SR is dependent here on the current and/or the future driving behavior or the current and/or the future driving state Z_1 of the vehicle **1**, which is continuously ascertained in the various units **21**, **22**, **23**. The current or future driving state Z_1 can therefore follow, for example, from: the yaw rate deviation dG as described for the second stabilization step STS_2 , and/or the imminent overturning of the vehicle **1** via the lateral acceleration a_q , as described for the fourth stabilization step STS_4 , and/or an articulation angle deviation dKW between the current actual articulation angle KW_{1st} and a setpoint articulation angle KW_{Soll} , which can be estimated from the setpoint trajectory TS , and/or a wheel slip s_{1f} of the individual wheels **1f** of the vehicle **1** and/or the presence of an ABS intervention E_{ABS} or an ESC intervention E_{ESC} and/or of load information BI , e.g. axle load information or center of gravity information or vibration information of the load, etc. Also the change of individual of the above-mentioned values over time can be considered in the return signal SR .

(77) The return signal SR may, for example, include a time-dependent stability indicator SI , which is ascertained by the stabilization monitor **24** based on the current vehicle actual dynamics FD_{1st} as well as the setpoint trajectory TS and which therefore evaluates the current and/or the future driving state Z_1 with the enumerated variables. For example, the stability indicator SI may be a value between 0% and 100% or 0 and 1 and may indicate a time-dependent probability of instability or an undesirable driving state Z_{1u} at a certain time t between the current time t_0 and the

future time tZ .

(78) The VD unit **3a** can use this return signal SR or the stability indicator SI for an adaptation of the current setpoint trajectory TS or the trajectory variables kG (PSoll(x, y), PhiSoll). Based on the adapted setpoint trajectory TSa, which is then also described exclusively by geometric variables (PSoll(x, y), PhiSoll), the VD unit **3a** can then determine and output an adapted actual deviation dTSa for the current time $t0$, which already takes into account the ascertained current and/or future driving state **Z1**. For the adapted setpoint trajectory TSa, the stability indicator SI then also changes accordingly. Based on the adapted actual deviation dTSa, setpoint requirements AS11, AS12 are then ascertained and output by the specification unit **3b**, and take into account the current and/or future driving state **Z1**. In this way, the manipulated variables GA10, GB10, GL10 are adapted in advance on the basis of the ascertained driving state **Z1**.

(79) Therefore, a stabilizing intervention by the second motion control unit **20** can be prevented by the second motion control unit **20** judging in advance, depending on the geometrically specified setpoint trajectory TS, whether an instability or an undesirable driving state **Z1u** would occur if this setpoint trajectory TS were to be maintained. The virtual driver, which is realized by the VD unit **3a**, can adapt its planned driving behavior accordingly by selecting and outputting an adapted setpoint trajectory TSa. Thus, limit values above which instability is considered possible can be adapted for future driving, since a predictive assessment is made. In addition, further parameters can be included.

(80) In the stabilization steps STS2, STS3, STS4, STS5, the movement of the vehicle **1** (manipulated variables GA10, GB10, GL10) originally specified by the first motion control unit **10** is thus adapted in situ or in anticipation on the basis of the driving state **Z1** in order to prevent or avoid an undesirable driving state **Z1u**, e.g. a detected or imminent instability. The individual stabilization steps STS2, STS3, STS4, STS5 are executed here in parallel.

(81) While subject matter of the present disclosure has been illustrated and described in detail in the drawings and foregoing description, such illustration and description are to be considered illustrative or exemplary and not restrictive. Any statement made herein characterizing the invention is also to be considered illustrative or exemplary and not restrictive as the invention is defined by the claims. It will be understood that changes and modifications may be made, by those of ordinary skill in the art, within the scope of the following claims, which may include any combination of features from different embodiments described above.

(82) The terms used in the claims should be construed to have the broadest reasonable interpretation consistent with the foregoing description. For example, the use of the article “a” or “the” in introducing an element should not be interpreted as being exclusive of a plurality of elements. Likewise, the recitation of “or” should be interpreted as being inclusive, such that the recitation of “A or B” is not exclusive of “A and B,” unless it is clear from the context or the foregoing description that only one of A and B is intended. Further, the recitation of “at least one of A, B and C” should be interpreted as one or more of a group of elements consisting of A, B and C, and should not be interpreted as requiring at least one of each of the listed elements A, B and C, regardless of whether A, B and C are related as categories or otherwise. Moreover, the recitation of “A, B and/or C” or “at least one of A, B or C” should be interpreted as including any singular entity from the listed elements, e.g., A, any subset from the listed elements, e.g., A and B, or the entire list of elements A, B and C.

LIST OF REFERENCE SIGNS (PART OF THE DESCRIPTION)

(83) **1** Vehicle **1a** Towing vehicle **1b** Trailer **1c** Wheel speed sensor **1d** Acceleration sensor **1e** Yaw rate sensor **1f** Wheels of the vehicle **1** **1g** Interface, for example CAN interface **2** Roadway **3** Journey control device **3a** VD unit (Virtual Driver) **3b** Specification unit (motion control) **4** Sensor **5** Surroundings acquisition system **6** Drive system **6a** Drive control unit **7** Braking system **7a** Braking control unit **8** Steering system **8a** Steering control unit **10** First motion control unit **11** Longitudinal controller **12** Lateral controller **13A** Drive logic unit **13A1**, **13A2**, **13A3** Inputs of the

drive logic unit **13B** Braking logic unit **13B1, 13B2, 13B3** Inputs of the braking logic unit **13L** Steering logic unit **13L1, 13L2, 13L3** Inputs of the steering logic unit **20** Second motion control unit **21** Yaw rate controller **22** Correction unit **23** RSC unit **24** Stabilization monitor aIst Actual acceleration aMax Maximum acceleration capacity aq Lateral acceleration aqG Limit lateral acceleration aSoll Setpoint acceleration A Wheelbase ARel Relative orientation of the vehicle **1** AS11 Longitudinal setpoint requirements AS12 Lateral setpoint requirements BI Loading information BV Braking wear dt Time period dG Yaw rate deviation dGC Yaw rate deviation change dGW Deviation limit value dPhi Rotation deviation dKW Articulation angle deviation dRSoll Setpoint curve radius change dTS Actual deviation dTSa Adapted actual deviation DIst Actual distance EABS ABS intervention EESC ESC intervention FDIst Vehicle actual dynamics FDSoll Vehicle setpoint dynamics FR Direction of travel GA10 Drive manipulated variable GA21 First drive stability variable GA23 Second drive stability variable GB10 Braking manipulated variable GB21 First braking stability variable GB23 Third braking stability variable GBL Second braking stability variable GIst Actual yaw rate GSoll Setpoint yaw rate GL10 Steering manipulated variable GL21 First steering stability variable GLK Second steering stability variable IF Vehicle information JB Braking yaw moment JSoll Setpoint yaw moment kG Trajectory variables KW Ist Actual articulation angle KWSoll Setpoint articulation angle M1 Current total mass of the vehicle **1** NIst Tilt angle P1 Position of the vehicle **1** PhiIst Actual rotation of the vehicle **1** PhiSoll Setpoint rotation of the vehicle **1** PSoll Setpoint position of the vehicle **1** RSoll Setpoint curve radius s1f Wheel slip S1c Wheel speed signal S1d Acceleration signal S1e Yaw rate signal S3a Trajectory signal S3b Specification signal S4 Sensor signal SA10 Drive control signal SA21 First drive stabilization signal SA23 Second drive stabilization signal SB10 Braking control signal SB21 First braking stabilization signal SB23 Third braking stabilization signal SBL Second braking stabilization signal SL10 Steering control signal SL21 First steering stabilization signal SLK Second steering stabilization signal SI Stability indicator SR Return signal SVA Drive logic signal SVB Braking logic signal SVL Steering logic signal t Time t0 Current time tZ Future time TS Setpoint trajectory TSa Adapted setpoint trajectory U Surroundings vIst Actual speed vSoll Setpoint speed W Track width x x-coordinate y y-coordinate zGM1 Permissible total mass of the vehicle **1** Z1 Driving state Z1u Undesirable driving state

Claims

1. A method for automated guidance of a vehicle along a specified setpoint trajectory at an actual speed, wherein the setpoint trajectory includes geometric trajectory variables, the method comprising: ascertaining an actual deviation of the vehicle from the setpoint trajectory; outputting the ascertained actual deviation to at least one controller and generating manipulated variables in the at least one controller based on the ascertained actual deviation such that the vehicle, in the case of automated control of a drive system and/or a braking system and/or a steering system of the vehicle, moves closer to the setpoint trajectory based on the generated manipulated variables if the vehicle deviates from the setpoint trajectory, ascertaining in the at least one controller whether an undesirable driving stability state is present for a future time when the vehicle moves closer to the setpoint trajectory based on the generated manipulated variables, wherein the undesirable driving stability state is ascertained from the specified setpoint trajectory based on the geometric trajectory variables; and if the presence of the undesirable driving stability state is identified for a future time, automatically controlling the vehicle based on stability variables generated in the at least one controller and/or adapting the setpoint trajectory.
2. The method as claimed in claim 1, wherein the ascertainment of whether the undesirable stability driving state is present for the future time is additionally carried out based on vehicle information about the vehicle and/or based on a vehicle actual dynamic of the vehicle and/or based on setpoint requirements for controlling the drive system and/or the braking system and/or the steering system.

3. The method as claimed in claim 2, wherein the setpoint requirements are ascertained based on the actual deviation, wherein a position and/or actual rotation of the vehicle deviating from the setpoint trajectory in the direction of travel of the vehicle is corrected via longitudinal setpoint requirements, and a position and/or actual rotation of the vehicle deviating perpendicularly to the direction of travel from the setpoint trajectory is corrected via lateral setpoint requirements.
4. The method as claimed in claim 3, wherein a drive manipulated variable and/or a braking manipulated variable and/or a steering manipulated variable are ascertained as manipulated variables based on the actual deviation, wherein each of: the drive system of the vehicle based on the drive manipulated variable, the braking system of the vehicle based on the braking manipulated variable, and the steering system of the vehicle based on the steering manipulated variable can be automatically controlled to bring the position and/or actual rotation of the vehicle closer to the setpoint trajectory.
5. The method as claimed in claim 1, wherein the presence of the undesirable driving stability state is ascertained if it follows from the specified setpoint trajectory based on the geometric trajectory variables that the vehicle is unstable at the current time and/or an unstable state is imminent for a future time.
6. The method as claimed in claim 1, wherein the presence of the undesirable driving stability state is ascertained if a yaw rate deviation between a setpoint yaw rate and an actual yaw rate at the current time and/or for a future time exceeds a deviation limit value, wherein the setpoint yaw rate at the current time and/or for a future time follows indirectly or directly from the specified setpoint trajectory based on the geometric trajectory variables.
7. The method as claimed in claim 6, wherein, if the deviation limit value is exceeded based on the yaw rate deviation, then one of: a first drive stability variable for limiting the actual speed of the vehicle and/or a first braking stability variable for reducing the actual speed of the vehicle is generated and output as a stability variable such that, during automated control of the vehicle based on the first drive stability variable and/or the first braking stability variable, the actual speed of the vehicle does not exceed a specified limit speed.
8. The method as claimed in claim 7, wherein the first drive stability variable and/or the first braking stability variable and/or the second braking stability variable and/or the first steering stability variable are generated based on a yaw rate deviation change, wherein the yaw rate deviation change indicates how the yaw rate deviation changes from the current time.
9. The method as claimed in claim 6, wherein, if the deviation limit value is exceeded based on the yaw rate deviation, then one of: a second braking stability variable for wheel-specific braking of the vehicle and/or a first steering stability variable for steering the vehicle is generated and output as a stability variable such that, during automated control of the vehicle, the actual yaw rate moves closer to the setpoint yaw rate based on the second braking stability variable and/or the first steering stability variable.
10. The method as claimed in claim 1, wherein a second steering stability variable is generated and output for preventing an undesirable driving state, wherein the second steering stability variable is generated based on: the actual speed of the vehicle and/or a setpoint curve radius derived from the setpoint trajectory, and/or a braking yaw moment, wherein the braking yaw moment is ascertained based on wheel slip, acting differently at sides of wheels of the vehicle, and/or a tilt angle of the vehicle with respect to the roadway, taking into account a current vehicle mass.
11. The method as claimed in claim 1, wherein the presence of the undesirable driving stability state is ascertained if a lateral acceleration of the vehicle exceeds a limit lateral acceleration at the current time and/or for a future time.
12. The method as claimed in claim 11, wherein the lateral acceleration is measured at the current time and/or is estimated for the future time from the specified setpoint trajectory based on the geometric trajectory variables.
13. The method as claimed in claim 11, wherein, if the limit lateral acceleration is exceeded at the

current time and/or for a future time, a second drive stability variable and/or a third braking stability variable is generated and output as a stability variable such that, in the case of automated control of the vehicle, based on the third braking stability variable and/or of the second drive stability variable, the lateral acceleration of the vehicle drops to or falls below the limit lateral acceleration.

14. The method as claimed in claim 1, wherein the setpoint trajectory is adapted based on a stability indicator, wherein the stability indicator indicates, based on a current vehicle actual dynamic and the current setpoint trajectory, in a time-dependent manner how probable the undesirable driving stability state is at a time between the current time and a future time.

15. The method as claimed in claim 14, wherein the stability indicator is determined depending on at least one feature selected from the group consisting of: an articulation angle deviation between a current actual articulation angle and a setpoint articulation angle, a yaw rate deviation between an actual yaw rate and a setpoint yaw rate, exceeding of a limit lateral acceleration, a wheel slip of one or more individual wheels of the vehicle, presence of an ABS intervention, presence of an ESC intervention and/or load information.

16. The method as claimed in claim 1, wherein the vehicle is automatically controlled based on generated stability variables such that the drive system and/or the braking system and/or the steering system of the vehicle is controlled exclusively with the generated stability variables, or the manipulated variables are adapted depending on the generated stability variables.

17. The method as claimed in claim 1, wherein the setpoint trajectory includes setpoint positions and setpoint rotations as geometric trajectory variables.

18. The method as claimed in claim 1, wherein the ascertainment of an actual deviation of the vehicle from the setpoint trajectory is carried out in a virtual driver; the generation of manipulated variables is carried out in a first motion controller of the at least one controllers based on the ascertained actual deviation; and the ascertainment of whether the undesirable driving stability state is present for the future time is carried out in a second motion controller of the at least one controllers, wherein the generation of the manipulated variables in the first motion controller is carried out independently of the ascertainment of the undesirable driving stability state in the second motion controller and/or the ascertainment of an actual deviation in the virtual driver is performed independently of the ascertainment of the undesirable driving stability state in the second motion controller.

19. A journey controller for carrying out the method as claimed in claim 1, wherein the journey controller comprises: a virtual driver for defining a setpoint trajectory, wherein the setpoint trajectory includes geometric trajectory variables, and for outputting an actual deviation if the vehicle deviates from the setpoint trajectory, a first motion controller, wherein the first motion controller is configured to generate manipulated variables based on the actual deviation such that the vehicle moves closer to the setpoint trajectory during automated control of a drive system and/or a braking system and/or a steering system of the vehicle based on the generated manipulated variables, if the vehicle deviates from the setpoint trajectory, a second motion controller, wherein the second motion controller is configured to ascertain whether an undesirable driving stability state is present for a future time when the vehicle moves closer to the setpoint trajectory based on the generated manipulated variables, wherein the undesirable driving stability state can be ascertained from the specified setpoint trajectory based on the geometric trajectory variables, wherein furthermore at least one logic unit is provided, wherein the at least one logic unit is configured to generate and output a logic signal for the automated control of the drive system and/or of the braking system and/or of the steering system of the vehicle, wherein the logic signal can be generated and output under the undesirable driving stability state based on generated stability variables, and/or the virtual driver is further configured to adapt the setpoint trajectory if the undesirable driving stability state is present.

20. The journey controller as claimed in claim 19, wherein the drive system and/or the braking

system and/or the steering system are each assigned a logic unit, wherein the drive system can be controlled automatically with a drive logic signal, the braking system can be controlled automatically with a braking logic signal, and the steering system can be controlled automatically with a steering logic signal.

21. The journey controller as claimed in claim 19, wherein the first motion controller and/or the second motion controller are integrated in the virtual driver; and/or the first motion controller and the second motion controller are combined; or at least the second motion controller is implemented separately from the virtual driver and the first motion controller.

22. The journey controller as claimed in claim 19, wherein the second motion controller comprises a yaw rate controller, wherein the yaw rate controller is configured to: infer the presence of the undesirable driving stability state if a yaw rate deviation between a setpoint yaw rate and an actual yaw rate at the current time and/or for a future time exceeds a deviation limit value, wherein the setpoint yaw rate at the current time and/or for a future time follows from the specified setpoint trajectory based on the geometric trajectory variables, and determine and output a stability variable based on the yaw rate deviation when the deviation limit value is exceeded.

23. The journey controller as claimed in claim 19, wherein the second motion controller comprises a roll stability control (RSC) unit, wherein the RSC unit is configured to: infer the presence of the undesirable driving stability state if a lateral acceleration of the vehicle exceeds a limit lateral acceleration at the current time and/or for a future time, and determine and output a stability variable when the limit lateral acceleration is exceeded.

24. The journey controller as claimed in claim 19, wherein the second motion controller has a stabilization monitor, wherein the stabilization monitor is configured to form a stability indicator based on a current vehicle actual dynamic and the current setpoint trajectory, wherein the stability indicator indicates, based on time, how likely the undesirable driving stability state is at a time between the current time and the future time.

25. The journey controller as claimed in claim 24, wherein the virtual driver is configured to adapt the setpoint trajectory based on the formed stability indicator.

26. A vehicle comprising a journey controller as claimed in claim 19 for automated guidance of the vehicle along a specified setpoint trajectory or an adapted setpoint trajectory.
