

# US Patent & Trademark Office

## Patent Public Search | Text View

---

|                      |                 |
|----------------------|-----------------|
| United States Patent | 12401087        |
| Kind Code            | B2              |
| Date of Patent       | August 26, 2025 |
| Inventor(s)          | Jo; Un          |

---

### Pouch, secondary battery comprising the same, and method for manufacturing the secondary battery

---

#### Abstract

A pouch applied to a secondary battery includes an accommodation part configured to accommodate an electrode assembly; a sealing part provided outside the accommodation part, the sealing part having a plurality of sealing surfaces configured to seal the accommodation part; and a protection part provided outside one or more of the plurality of sealing surfaces of the sealing part, the protection part being configured to protect the one or more sealing surfaces.

---

|                   |                                             |
|-------------------|---------------------------------------------|
| <b>Inventors:</b> | <b>Jo; Un (Daejeon, KR)</b>                 |
| <b>Applicant:</b> | <b>LG Energy Solution, Ltd. (Seoul, KR)</b> |
| <b>Family ID:</b> | <b>1000008780557</b>                        |
| <b>Assignee:</b>  | <b>LG Energy Solution, Ltd. (Seoul, KR)</b> |
| <b>Appl. No.:</b> | <b>18/139169</b>                            |
| <b>Filed:</b>     | <b>April 25, 2023</b>                       |

#### Prior Publication Data

|                            |                         |
|----------------------------|-------------------------|
| <b>Document Identifier</b> | <b>Publication Date</b> |
| US 20230268607 A1          | Aug. 24, 2023           |

#### Foreign Application Priority Data

|    |                 |               |
|----|-----------------|---------------|
| KR | 10-2018-0103911 | Aug. 31, 2018 |
|----|-----------------|---------------|

#### Related U.S. Application Data

continuation parent-doc US 16961422 US 11791517 WO PCT/KR2019/011090 20190829 child-doc US 18139169

---

## Publication Classification

**Int. Cl.:** H01M50/325 (20210101); H01M50/105 (20210101); H01M50/186 (20210101)

**U.S. Cl.:**

**CPC** H01M50/325 (20210101); H01M50/105 (20210101); H01M50/186 (20210101);

## Field of Classification Search

**CPC:** H01M (50/325); H01M (50/186); H01M (50/105)

**USPC:** 429/53

---

## References Cited

### U.S. PATENT DOCUMENTS

| Patent No.   | Issued Date | Patentee Name | U.S. Cl. | CPC         |
|--------------|-------------|---------------|----------|-------------|
| 7682735      | 12/2009     | Lee           | N/A      | N/A         |
| 2004/0121231 | 12/2003     | Kim           | N/A      | N/A         |
| 2005/0084749 | 12/2004     | Hwang et al.  | N/A      | N/A         |
| 2009/0311581 | 12/2008     | Park et al.   | N/A      | N/A         |
| 2010/0028772 | 12/2009     | Yang et al.   | N/A      | N/A         |
| 2011/0244315 | 12/2010     | Yoon          | N/A      | N/A         |
| 2013/0244093 | 12/2012     | Min et al.    | N/A      | N/A         |
| 2014/0212701 | 12/2013     | Hur           | N/A      | N/A         |
| 2015/0303414 | 12/2014     | Park et al.   | N/A      | N/A         |
| 2016/0315294 | 12/2015     | Kim           | N/A      | H01M 50/119 |
| 2018/0304504 | 12/2017     | Lee           | N/A      | N/A         |
| 2018/0342715 | 12/2017     | Ha et al.     | N/A      | N/A         |

### FOREIGN PATENT DOCUMENTS

| Patent No.  | Application Date | Country | CPC |
|-------------|------------------|---------|-----|
| 1508899     | 12/2003          | CN      | N/A |
| 1610166     | 12/2004          | CN      | N/A |
| 101517776   | 12/2008          | CN      | N/A |
| 102208673   | 12/2010          | CN      | N/A |
| 202495539   | 12/2011          | CN      | N/A |
| 202687165   | 12/2012          | CN      | N/A |
| 104064815   | 12/2013          | CN      | N/A |
| 105900274   | 12/2015          | CN      | N/A |
| 106207020   | 12/2015          | CN      | N/A |
| 2375469     | 12/2010          | EP      | N/A |
| 2760061     | 12/2013          | EP      | N/A |
| 2000173563  | 12/1999          | JP      | N/A |
| 2005116278  | 12/2004          | JP      | N/A |
| 2008251540  | 12/2007          | JP      | N/A |
| 2015069959  | 12/2014          | JP      | N/A |
| 2016015225  | 12/2015          | JP      | N/A |
| 20000075255 | 12/1999          | KR      | N/A |

|             |         |    |     |
|-------------|---------|----|-----|
| 20040005022 | 12/2003 | KR | N/A |
| 100958649   | 12/2009 | KR | N/A |
| 20130080071 | 12/2012 | KR | N/A |
| 20130119556 | 12/2012 | KR | N/A |
| 20130134963 | 12/2012 | KR | N/A |
| 20170092246 | 12/2016 | KR | N/A |
| 20170092740 | 12/2016 | KR | N/A |

## OTHER PUBLICATIONS

International Search Report for Application No. PCT/KR2019/011090, mailed Dec. 6, 2019, pp. 1-2. cited by applicant

Extended European Search Report including Written Opinion for Application No. EP19854733.3 dated Feb. 24, 2021, 11 pgs. cited by applicant

Search Reported dated Mar. 16, 2022 from the Office Action for Chinese Application No. 2019800083861 issued Mar. 24, 2022, 2 pgs. see p. 2, categorizing the cited references. cited by applicant

Search Reported dated Nov. 11, 2022 from the Office Action for Chinese Application No. 201980008386.1 issued Nov. 18, 2022. 3 pgs. cited by applicant

*Primary Examiner:* Martin; Matthew T

*Assistant Examiner:* St Wyrrough; Paul Christian

*Attorney, Agent or Firm:* Lerner David LLP

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) The present application is a continuation of U.S. patent application Ser. No. 16/961,422, filed on Jul. 10, 2020, which is a national phase entry under 35 U.S.C. § 371 of International Application No. PCT/KR2019/011090, filed Aug. 29, 2019, published in Korean, which claims the benefit of the priority of Korean Patent Application No. 10-2018-0103911, filed on Aug. 31, 2018, all of the disclosures of which are hereby incorporated by reference in their entirety.

### TECHNICAL FIELD

(1) The present invention relates a pouch, a secondary battery comprising the same, and method for manufacturing the secondary battery, and more particularly, to a pouch that is capable of protecting a sealing part and an accommodation part thereof without folding the sealing part and the accommodation part, a secondary battery comprising the same, and a method for manufacturing the secondary battery.

### BACKGROUND ART

(2) In general, secondary batteries refer to chargeable and dischargeable batteries, unlike primary batteries that are not chargeable. Such a secondary battery is being widely used in the high-tech electronic fields such as mobile phones, notebook computers, and camcorders.

(3) Such a secondary battery is classified into a can type secondary battery in which an electrode assembly is built in a metal can and a pouch type secondary battery in which an electrode assembly is built in a pouch. The pouch type secondary battery comprises an electrode assembly in which an electrode and a separator are alternately stacked, an electrolyte, and a pouch accommodating the electrode assembly and the electrolyte. Also, the pouch comprises an accommodation part

accommodating the electrode assembly and an electrolyte and a sealing part sealing the accommodation part.

(4) However, the pouch type secondary battery has a problem in that the sealing part and the accommodation part of the pouch are deformed while being easily folded by an external impact. Particularly, when the accommodation part is deformed, the electrode assembly accommodated in the accommodation part may be damaged to cause short circuit or ignition.

## DISCLOSURE OF THE INVENTION

### Technical Problem

(5) The present invention has been invented to solve the above problems. An object of the present invention is to provide a pouch that is capable of preventing a sealing part and an accommodation part thereof from being deformed by providing a protection part outside the pouch, thereby preventing an electrode assembly accommodated in the accommodation part from being damaged, a secondary battery comprising the pouch, and a method for manufacturing the secondary battery.

### Technical Solution

(6) To achieve the above-described objects, a pouch according to a first embodiment of the present invention comprises: an accommodation part configured to accommodate an electrode assembly; a sealing part provided outside the accommodation part, the sealing part having a plurality of sealing surfaces configured to seal the accommodation part; and a protection part provided outside one or more of the plurality of sealing surfaces of the sealing part, the protection part being configured to protect the one or more sealing surfaces.

(7) The protection part may be provided with one or more protrusions for reinforcing strength.

(8) The one or more protrusions may be provided by allowing a portion of the protection part to protrude outward or by attaching a component made of a synthetic resin material to the protection part.

(9) The protrusions may be disposed on both ends of the protection part, which are adjacent to the corner portion of the accommodation part.

(10) The protection part may be provided on the sealing surface of the plurality of sealing surfaces disposed on one side or each of both sides in a width direction of the pouch.

(11) The pouch may further comprise a gas pocket part configured to collect a gas generated in the accommodation part, wherein the accommodation part may be provided at one side in a width direction of the pouch, and the gas pocket part may be provided at another side in the width direction of the pouch, and the protection part may be provided on each of the sealing surface of the plurality of sealing surfaces disposed at one side of the accommodation part and the sealing surface of the plurality of sealing surfaces disposed at another side of the gas pocket part in the width direction of the pouch.

(12) A secondary battery according to a second embodiment of the present invention comprises: an electrode assembly; and a pouch comprising: an accommodation part in which the electrode assembly is disposed; a sealing part provided outside the accommodation part, the sealing part having a plurality of sealing surfaces configured to seal the accommodation part; and a protection part provided outside one or more of the plurality of sealing surfaces of the sealing part, the protection part being configured to protect the one or more sealing surfaces.

(13) The protection part may be removable from each of the sealing surfaces.

(14) The protection part may not be thermally fused.

(15) A method for manufacturing a secondary battery according to the second embodiment of the present invention comprises: a pouch sheet preparation step of preparing a pouch sheet on which an upper pouch and a lower pouch are formed with respect to a horizontal center line that equalizes the pouch sheet vertically; an accommodation part forming step of forming an upper accommodation part and a lower accommodation part, which respectively correspond to the upper pouch and the lower pouch; a protection part formation step of forming one or more protrusions that protrude outside from left and right ends of the upper pouch and the lower pouch to form a

protection part; an accommodation part formation step of folding the upper pouch and the lower pouch with respect to the horizontal center line so that the upper and lower accommodation parts are connected to each other to form an accommodation part; and a sealing part formation step of sealing a portion between the accommodation part and the protection part and upper and lower ends of the accommodation part to manufacture the secondary battery.

(16) The accommodation part forming step and the protection part formation step may be performed at the same time.

(17) The sealing part formation step may further comprise a process of further sealing a portion between the accommodation part and the sealing part to form a gas pocket part between the accommodation part and the sealing part, and the accommodation part and the gas pocket part may be connected to each other through a non-sealed path.

(18) The method may further comprise, after the sealing part formation step, a transfer step of accommodating the secondary battery in a tray to transfer the secondary battery, wherein the secondary battery may be accommodated so that the protection part is supported by a side surface of a bottom surface of the tray.

(19) The method may further comprise, after the transfer step, a protection part removing step of removing the protection part from each of the sealing surfaces of the pouch.

(20) The method may further comprise, after the removing step, a sealing part resealing step of resealing the sealing part from which the protection part is removed.

(21) In the sealing part formation step, the protection part may not be sealed.

#### Advantageous Effects

(22) The present invention has the feature in which the protection part is disposed outside the pouch. Due to this feature, the sealing part and the accommodation part, which are provided in the pouch, may be protected to prevent deformation such as the bucking or the folding of the sealing part and the accommodation part from occurring, in particular, prevent the electrode assembly accommodated in the accommodation part from being damaged.

(23) Also, the protection part of the present invention may further comprise the one or more protrusions. Thus, the protection part may be reinforced in strength to significantly prevent the sealing part and the accommodation part of the pouch from being deformed.

(24) Also, the protrusion of the present invention may be formed by allowing a portion of the protection part from protruding outside. Thus, the protrusion may be easily formed to simplify the process and reduce the process cost.

(25) The protrusion of the present invention may be detachably attached to one side of the protrusion part. Thus, the protrusion may be selectively attached or separated to improve convenience and efficiency of use.

(26) Also, the protrusion of the present invention may be formed at the end of the protection part, which is close or adjacent to the corner portion of the accommodation part. Thus, the corner portion of the accommodation part, which may be easily deformed, may be more stably protected to prevent the corner portion of the electrode assembly, which is disposed at the corner portion of the accommodation part, from being damaged.

(27) Also, the protection part of the present invention may be provided at one side or both sides of the pouch in the width direction. That is, the protection part may be formed at only the portion of the secondary battery, which contacts the jig or the tray, to simplify the process and reduce the process cost.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a perspective view of a pouch according to a first embodiment of the present

invention.

(2) FIG. 2 is a front view of the pouch according to the first embodiment of the present invention.

(3) FIG. 3 is a cross-sectional view taken along line A-A of FIG. 1;

(4) FIG. 4 is a perspective view of a secondary battery according to a second embodiment of the present invention.

(5) FIG. 5 is a front view illustrating a state in which a protection part is removed from the secondary battery according to the second embodiment of the present invention.

(6) FIG. 6 is a flowchart illustrating a method for manufacturing the second battery according to the second embodiment of the present invention.

(7) FIG. 7 is a perspective view illustrating a pouch sheet preparation step, an accommodation part forming step, and a protection part formation step.

(8) FIG. 8 is a perspective view illustrating an electrode assembly accommodation part formation step.

(9) FIG. 9 is a front view illustrating a sealing formation step.

(10) FIG. 10 is a side view illustrating a secondary battery transfer step.

(11) FIG. 11 is a front view illustrating a protection part removing step and a sealing part resealing step.

(12) FIG. 12 is a front view of a pouch according to a third embodiment of the present invention.

(13) FIG. 13 is a cross-sectional view of a pouch according to a fourth embodiment of the present invention.

(14) FIG. 14 is a perspective view of a pouch according to a fifth embodiment of the present invention.

#### MODE FOR CARRYING OUT THE INVENTION

(15) Hereinafter, embodiments of the present invention will be described in detail with reference to the accompanying drawings in such a manner that the technical idea of the present invention may easily be carried out by a person with ordinary skill in the art to which the invention pertains. The present invention may, however, be embodied in different forms and should not be construed as limited to the embodiments set forth herein. In the drawings, anything unnecessary for describing the present invention will be omitted for clarity, and also like reference numerals in the drawings denote like elements.

(16) [Pouch According to First Embodiment of the Present Invention]

(17) As illustrated in FIGS. 1 to 3, a pouch **120** according to a first embodiment of the present invention comprises an accommodation part **121** accommodating an electrode assembly **110** and a sealing part **122** provided along an edge of the accommodation part **121** to seal the accommodation part **121**.

(18) Here, the sealing part **122** comprises a plurality of sealing surfaces for sealing the accommodation part **121**. As illustrated in FIG. 1, the plurality of sealing surfaces comprise a first sealing surface **122a** disposed on each of both side surfaces in a width direction (in a left and right direction when viewed in FIG. 1) of the electrode assembly accommodation part **121** and a second sealing surface **122b** disposed on each of top and bottoms surfaces (upper and lower portions of the accommodation part when viewed in FIG. 1) of the accommodation part **121**.

(19) Also, the pouch **120** according to the first embodiment of the present invention comprises a gas pocket part **124** for collecting a gas generated in the accommodation part **121**. Referring to FIG. 1, the gas pocket part **124** is provided between the accommodation part **121** and the first sealing surface **122a** provided on the right surface of the pouch and is separated from the accommodation part **121** by an auxiliary sealing surface **122c** in which an inlet hole **122c-1** is defined.

(20) In summary, in the pouch **120** according to the first embodiment of the present invention, the accommodation part **121** is provided at a left side, and the gas pocket part **124** is provided at the right side. The sealing part **122** is disposed on edge surfaces of the accommodation part **121** and the

gas pocket part **124**, and the auxiliary sealing surface **122c** is disposed between the accommodation part **121** and the gas pocket part **124**.

(21) The pouch is transferred through a jig or a tray. Here, the sealing part and the accommodation part of the pouch may be buckled or folded by the jig or the tray. In particular, when the electrode assembly is accommodated in the accommodation part, even the electrode assembly may be damaged.

(22) In order to solve the above problems, the pouch **120** according to the first embodiment of the present invention comprises a protection part that protects the sealing part while increasing in a width of the sealing part.

(23) That is, the pouch **120** according to the first embodiment of the present invention comprises the protection part **123** that is provided outside one or more sealing surfaces of the sealing part **122** to protect the one or more sealing surfaces. A first sealing surface **122a** disposed outside the pouch **120** may increase in width, and simultaneously, be improved in strength of the first sealing surface **122a** to protect the first sealing surface **122a** through the protection part **123**.

(24) That is to say, in the pouch **120** according to the first embodiment, when the jig holds the pouch, the jig may hold the sealing part **122** and the protection part **123** together to prevent the accommodation part from being held, thereby preventing the accommodation part from being deformed. Also, referring to FIG. **10**, when the tray **30** transfers the pouch, the protection part **123** may be supported by a wall of the tray **30** to prevent the sealing part from being directly supported by the tray **30**, thereby preventing the sealing part **122** and the accommodation part **121** from being folded by folding of the protection part **123** due to an impact acting on the tray **30**.

(25) As described above, the pouch **120** according to the first embodiment of the present invention further comprises the protection part **123**. Thus, the deformation of the accommodation part **121** and the sealing part **122** may be prevented from being deformed to prevent the electrode assembly accommodated in the accommodation part from being damaged, thereby improving merchantability.

(26) The protection part **123** may be integrated with the sealing part **122**. That is, the protection part **123** may be integrated with the sealing part **122** when the pouch is manufactured through a pouch sheet, and thus, the process may be simplified, the manufacture may be easy, and the cost may be reduced.

(27) The protection part **123** may comprise one or more protrusions **123a** for reinforcing the strength. That is, a portion of a surface of the protection part **123** may be formed to protrude outside, thereby forming one or more protrusions **123a**. Accordingly, the strength of the protection part **123** may be reinforced through the protrusion **123a**, and thus, the strength of the sealing part **122** that is close or adjacent to the protection part **123** may be reinforced.

(28) Referring to the enlarged view of FIG. **3**, the protrusion **123a** may protrude toward front and rear sides of the protection part **123** to form a sealing space **123-1** therein. A reinforcement component **123b** made of a synthetic resin material having elastic restoring force may be inserted into the sealing space **123-1** to reinforce the strength of the protrusion **123a**. Here, the reinforcement component **123b** may be recovered from the protrusion **123a** and then reused when the protection part **123** is removed from the sealing part.

(29) An impact detection sensor that detects impact force transmitted from the tray may be inserted into the sealing space **123-1**. The impact detection sensor measures the impact force transmitted from the tray to the pouch, and when the measured impact force is equal to or greater than inputted impact force, the impact detection sensor outputs a signal to sort out normal and defective products. That is, when the impact force measured by the impact detection sensor is less than the inputted impact force, it may be determined that no deformation occurs in the protection part, and thus, the signal may not be outputted. When the measured impact force is equal to or greater than the inputted impact force, it may be determined that the deformation is highly likely to occur in the sealing part and the accommodation part together with the protection part, and thus, the signal may

be outputted.

(30) In particular, the protrusion **123a** has a circular shape when viewed in FIG. 2. That is, the circular protrusion **123a** may have a curved outer circumferential surface to effectively disperse a transmitted impact, thereby significantly preventing the protrusion **123a** from being folded.

(31) Here, although the circular protrusion is described as one embodiment of the present invention, the protrusion may have various shapes such as a triangular shape, a square shape, a polygon shape, a ring shape, and the like. That is, the protrusion of the present invention may be realized according to various embodiments.

(32) The protrusion **123a** may be disposed on one end or both ends of the protection part **123**, which is/are close or adjacent to the corner portion of the accommodation part **121**. That is, the pouch **120** has large buckling or folding at the corner portion of the accommodation part **121**, and thus, the protrusion **123a** is disposed on the end of the protection part **123**, which is close or adjacent to the corner portion of the accommodation part **121** to more stably protect the corner portion of the accommodation part **121**.

(33) When the transfer of the pouch **120** is completed, the protection part **123** may be removed from the sealing part **122**. That is, the protection part **123** is removed from the pouch **120** by cutting a portion between the first sealing surface **122a** and the protection part **123** to reduce a volume of the pouch **120**.

(34) A cutting line **123c** having a groove or protrusion shape may be formed between the first sealing surface **122a** and the protection part **123**, and the protection part may be easily cut from the pouch **120** through the cutting line **123c**.

(35) The protection unit **123** is not thermally fused. That is, since the protection part **123** is removed after the pouch is transferred, the protection part **123** is not thermally fused to simplify a process and reduce a process cost.

(36) Hereinafter, in descriptions of another embodiment of the present invention, constituents having the same function as the abovementioned embodiment have been given the same reference numeral in the drawings, and thus duplicated description will be omitted.

(37) [Secondary Battery According to Second Embodiment of the Present Invention]

(38) A secondary battery **100** according to a second embodiment of the present invention comprises the pouch **120** according to the first embodiment.

(39) That is, as illustrated in FIG. 4, the secondary battery **100** according to the second embodiment of the present invention comprises an electrode assembly **110** and a pouch **120** accommodating the electrode assembly **110**.

(40) Electrode Assembly

(41) The electrode assembly **110** comprises a plurality of electrodes that are stacked in a state of interposing a separator therebetween, and the plurality of electrodes comprise a positive electrode and a negative electrode. Also, the electrode assembly **110** comprises an electrode tab that is withdrawn out of the pouch **120**.

(42) Pouch

(43) The pouch **120** comprises an accommodation part **121** accommodating the electrode assembly **110**, a sealing part **122** provided along an edge of the accommodation part **121** to seal the accommodation part **121**, a gas pocket part **124** provided between the accommodation part **121** and the sealing part **122** to collect a gas generated in the accommodation part **121**, and a protection part **123** provided outside the sealing part **122** to protect the accommodation part **121** together with the sealing part **122**.

(44) Here, the pouch **120** has the same configuration and function as the pouch according to the first embodiment, and thus a detailed description thereof will be omitted.

(45) When the secondary battery **100** having the above-described configuration according to the second embodiment of the present invention is transferred, the sealing part and the accommodation part of the pouch may be prevented from being deformed, for example, buckled or folded by an



impact, thereby preventing the electrode assembly from being damaged.

(46) As illustrated in FIG. 5, in the secondary battery **100** according to the second embodiment of the present invention, when the protection part **123** is removed from the sealing part **122**, a sealing surface from which the protection part **123** is removed is resealed. That is, the sealing surface may be deformed while the protection part **123** is removed, and thus, sealing force may be reduced. In order to solve the above-described problem, the sealing surface may be resealed after the protection part **123** is removed, and thus, the sealing force of the pouch **120** may increase.

(47) A method for manufacturing the secondary battery having the above-described configuration according to the second embodiment of the present invention will be described as follows.

(48) [Method for Manufacturing Secondary Battery According to Second Embodiment of the Present Invention]

(49) As illustrated in FIG. 6, a method for manufacturing the secondary battery according to the second embodiment of the present invention comprises a pouch sheet preparation step (S10), an accommodation part forming step (S20), a protection part formation step (S30), an accommodation part formation step (S40), and a sealing part formation step (S50).

(50) Pouch Sheet Preparation Step

(51) As illustrated in FIG. 7, in the pouch sheet preparation step (S10), a pouch sheet **10** having a sheet shape is prepared, and a horizontal center line O that equalizes the pouch sheet **10** vertically is displayed on the pouch sheet **10**. Then, the pouch sheet **10** is separated into an upper pouch **11** and a lower pouch **12** on the basis of the horizontal center line O.

(52) Accommodation Part Forming Step

(53) In the accommodation part forming step (S20), each of an upper accommodation part **11a** and a lower accommodation part **12a**, which respectively correspond to the upper pouch **11** and the lower pouch **12**, is formed. That is, when the pouch sheet **10** is folded with respect to the horizontal center line O, the upper accommodation part **11a** of the upper pouch **11** and the lower accommodation part **12a** of the lower pouch **12** are formed to be connected to each other.

(54) Protection Part Formation Step

(55) In the protection part formation step (S30), a cutting line **123c** is displayed on each of left and right ends of the upper pouch **11** and the lower pouch **12** to form a protection part **123** having a predetermined width. Here, the width of the protection part is less than a width between the protection part and the accommodation part. This is done because the width between the protection part and the accommodation part becomes the sealing part so that the width of the sealing part is secured to be greater than that of the protection part to increase in sealing force.

(56) When the protection part **123** is formed, a portion of a surface of the protection part **123** is formed to protrude outward, thereby forming one or more protrusions **123a**. In particular, the protrusion **123a** is formed on a surface of the protection part **123**, which is close or adjacent to a corner portion of the accommodation part in which deformation largely occurs.

(57) Here, the protrusions **123a** formed on the protection parts **123** of the upper pouch **11** and the lower pouch **12** may be connected to each other when the pouch sheet **10** is folded with respect to the horizontal center line O.

(58) The accommodation part forming step (S20) and the protection part formation step (S30) may be performed at the same time to simplify the process. That is, the upper accommodation part **11a** and the lower accommodation part **12a**, which correspond to the upper pouch **11** and the lower pouch **12**, are formed, and simultaneously, the one or more protrusions **123a** are formed on the surface of the protection part **123**.

(59) Accommodation Part Formation Step

(60) In the accommodation part formation step (S40), as illustrated in FIG. 8, the pouch sheet **10** is folded with respect to the horizontal center line O. Then, the pouch **120** is formed while the upper pouch **11** and the lower pouch **12** are folded, and the accommodation part **121** is formed while the upper accommodation part **11a** and the lower accommodation part **12a** are connected to each other.

(61) Sealing Part Formation Step

(62) As illustrated in FIG. 9, in the sealing part formation step (S50), the electrode assembly **110** is accommodated in the accommodation part **121**, and then, upper and lower ends of the accommodation part **121** are sealed between the accommodation part **121** and the protection part **123**. Then, the accommodation part **121** may be sealed while the sealing part **122** is formed on an edge surface of the pouch **120**, and thus, the secondary battery **100** may be manufactured.

(63) Here, the sealing part formation step (S50) may further comprise a process of forming a gas pocket part between the accommodation part **121** and the sealing part. That is, in the gas pocket part formation process, sealing is further performed between the accommodation part **121** and the sealing part **122** to form an auxiliary sealing surface **122c** in which an inlet hole **122c-1** is formed. In summary, in the pouch **120**, the accommodation part **121** is formed at a left side, and the gas pocket part **124** is formed at a right side with respect to the auxiliary sealing surface **122c**.

(64) The protection part **123** may not be sealed because the protection part **123** is removed after the secondary battery is transferred, and thus, adding of unnecessary processes may be prevented.

(65) After the sealing part formation step (S50), a transfer step (S60) of transferring the secondary battery **100** to an activation process is further performed.

(66) Transfer Step

(67) That is, as illustrated in FIG. 10, in the transfer step (S60), the secondary battery **100** is accommodated in one or more trays **30** that move along a conveyor belt. Here, the secondary battery **100** is accommodated so that the protection part **123** is supported on a sidewall or a bottom surface of the tray **30** to prevent the sealing part **122** and the accommodation part **121** of the pouch **120** from being directly supported on the sidewall or the bottom surface of the tray, thereby significantly preventing the sealing part **122** and the accommodation part **121** of the pouch **120** from being deformed, for example, buckled or folded. In particular, the protection part **123** may comprise the one or more protrusions **123a** to significantly prevent the sealing part and the accommodation part of the pouch **120** from being deformed.

(68) After the transfer step (S60), a protection part removing step (S70) of removing the protection part may be further performed.

(69) Protection Part Removing Step

(70) That is, as illustrated in FIG. 11, in the protection part removing step (S70), when the transfer of the secondary battery **100** is completed, the function of the protection part **123** is lost, and thus, the protection part **123** may be cut to be removed from the sealing part **122**.

(71) After the removing step (S70), a sealing part resealing step (S80) of resealing the sealing part **122** from which the protection part **123** is removed may be further performed.

(72) Sealing Part Resealing Step

(73) That is, in the sealing part resealing step (S80), the sealing surface from which the protection part **123** is removed is resealed to increase in sealing force.

(74) In the method for manufacturing the secondary battery, which comprises the above-described steps, according to the second embodiment of the present invention, when the secondary battery is manufactured, the protection part may be formed to prevent the electrode assembly accommodated in the secondary battery from being damaged when the secondary battery is transferred, thereby significantly improving quality of the product.

(75) [Pouch According to Third Embodiment of the Present Invention]

(76) As illustrated in FIG. 12, in a pouch **120A** according to a third embodiment of the present invention, a protrusion **123a** is disposed on a protection part **123**. Here, the protrusion **123a** is lengthily disposed in a longitudinal direction of the protection part **123**.

(77) That is, in the pouch **120A** according to the third embodiment of the present invention, the protrusion **123a** disposed on the protection part **123** increases in length to improve strength of the protection part **123**.

(78) [Pouch According to Fourth Embodiment of the Present Invention]

(79) As illustrated in FIG. 13, in a pouch **120B** according to a fourth embodiment of the present invention, a protrusion **123a** is disposed on a protection part **123**. Here, the protrusion **123a** is provided as a separate component and thus is detachably attached to a surface of the protection part **123**.

(80) That is, the pouch **120B** according to the fourth embodiment of the present invention may comprise the protrusion **123a** that is detachably attached to the surface of the protection part **123** to increase in reusability and convenience. In particular, the protrusion **123a** may move to a portion that is weak in strength on the surface of the protection part and then be attached to the portion.

(81) [Pouch According to Fifth Embodiment of the Present Invention]

(82) As illustrated in FIG. 14, a pouch **120C** according to a fifth embodiment of the present invention, a protrusion **123a** is disposed on a protection part **123**. Here, the protrusion **123a** crosses front and rear surfaces of the protection part **123** in a zigzag manner without corresponding to the front and rear surfaces to increase in strength of an entire surface of the protection part **123** by using the minimum protrusion **123a**.

(83) Accordingly, the scope of the present invention is defined by the appended claims more than the foregoing description and the exemplary embodiments described therein. Various modifications made within the meaning of an equivalent of the claims of the invention and within the claims are to be regarded to be in the scope of the present invention.

## Claims

1. A secondary battery comprising: an electrode assembly; and a pouch comprising: an accommodation part configured to accommodate the electrode assembly; a sealing part provided outside the accommodation part, the sealing part having a plurality of sealing surfaces configured to seal the accommodation part; and a protection part integrated with an outer peripheral region of one or more of the plurality of sealing surfaces of the sealing part, the protection part being configured to protect the one or more sealing surfaces; and a gas pocket part configured to collect a gas generated in the accommodation part, wherein the protection part is provided with one or more protrusions for reinforcing strength, wherein the accommodation part is provided at one side in a width direction of the pouch, and the gas pocket part is provided at another side in the width direction of the pouch, wherein the protection part is provided on each of the sealing surface of the one or more sealing surfaces that is disposed at one side of the accommodation part and the sealing surface of the one or more sealing surfaces that is disposed at another side of the gas pocket part in the width direction of the pouch, and wherein the one or more protrusions protrude to form a sealing space therein.
2. The secondary battery of claim 1, wherein the protection part is removable from each of the sealing surfaces.
3. The secondary battery of claim 1, wherein the protection part is not thermally fused.
4. A method for manufacturing a secondary battery, the method comprising: a pouch sheet preparation step of preparing a pouch sheet on which an upper pouch and a lower pouch are formed with respect to a horizontal center line that equalizes the pouch sheet vertically; an accommodation part forming step of forming an upper accommodation part and a lower accommodation part, which respectively correspond to the upper pouch and the lower pouch; a protection part formation step of forming one or more protrusions that protrude outside from left and right ends of the upper pouch and the lower pouch to form a protection part; an accommodation part formation step of folding the upper pouch and the lower pouch with respect to the horizontal center line so that the upper and lower accommodation parts are connected to each other to form an accommodation part; and a sealing part formation step of sealing a portion between the accommodation part and the protection part and upper and lower ends of the accommodation part to manufacture the secondary battery, wherein the protection part is integrated with an outer peripheral region of the sealing part, wherein

the sealing part formation step further comprises a process of further sealing a portion between the accommodation part and the sealing part to form a gas pocket part between the accommodation part and the sealing part, wherein the accommodation part is provided at one side in a width direction of the pouch, and the gas pocket part is provided at another side in the width direction of the pouch, wherein the protection part is provided on each of the sealing surface of the one or more sealing surfaces that is disposed at one side of the accommodation part and the sealing surface of the one or more sealing surfaces that is disposed at another side of the gas pocket part in the width direction of the pouch, and wherein the one or more protrusions protrude to form a sealing space therein.

5. The method of claim 4, wherein the accommodation part and the gas pocket part are connected to each other through a non-sealed path.

6. The method of claim 4, further comprising, after the sealing part formation step, a transfer step of accommodating the secondary battery in a tray to transfer the secondary battery, wherein the secondary battery is accommodated so that the protection part is supported by a side surface of a bottom surface of the tray.

7. The method of claim 6, further comprising, after the transfer step, a protection part removing step of removing the protection part from each of the sealing surfaces of the pouch.

8. The method of claim 7, further comprising, after the removing step, a sealing part resealing step of resealing the sealing part from which the protection part is removed.

9. The method of claim 7, wherein, in the sealing part formation step, the protection part is not sealed.

---