

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402216
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Kim; Seunghak et al.

Electric range

Abstract

An electric range includes a heating part configured to heat an object based on an electromagnetic interaction. The heating part may include a core frame having a plurality of channels disposed radially on a lower surface thereof and a plurality of ferrite cores mounted onto the channels and disposed under the core frame. The core frame include a plurality of air gaps disposed between the plurality of channels. The plurality of air gaps are disposed radially, and the plurality of air gaps connect a center of the core frame and an edge of the core frame.

Inventors:	Kim; Seunghak (Seoul, KR), Cho; Junghyeon (Seoul, KR)
Applicant:	LG ELECTRONICS INC. (Seoul, KR)
Family ID:	1000008780443
Assignee:	LG ELECTRONICS INC. (Seoul, KR)
Appl. No.:	17/521523
Filed:	November 08, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220167470 A1	May. 26, 2022

Foreign Application Priority Data

KR	10-2020-0159559	Nov. 25, 2020
----	-----------------	---------------

Publication Classification

Int. Cl.: H05B6/12 (20060101); H05B6/36 (20060101)

U.S. Cl.:

CPC **H05B6/1263** (20130101); **H05B6/1254** (20130101); **H05B6/365** (20130101);
H05B2206/022 (20130101); H05B2213/07 (20130101)

Field of Classification Search

CPC: H05B (2206/022); H05B (2213/07); H05B (6/1254); H05B (6/1263); H05B (6/365)

USPC: 219/623; 219/620; 219/622; 219/624; 219/630; 219/632; 219/635

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2007/0278215	12/2006	Schilling	219/622	H05B 6/1263

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102404889	12/2011	CN	N/A
208025581	12/2017	CN	N/A
208312454	12/2018	CN	N/A
2490505	12/2011	EP	N/A
2770801	12/2016	EP	N/A
5919462	12/2015	JP	N/A
6730209	12/2019	JP	N/A
101420875	12/2013	KR	N/A
10-2016-0025173	12/2015	KR	N/A
2011138715	12/2010	WO	N/A

OTHER PUBLICATIONS

Translation of P2018147641, “Induction heating cooker”, Jul. 29, 2020, by WIPO. (Year: 2020).
cited by examiner

Translation of JP5919462B2, “Induction heating coil”, May 18, 2016, by WIPO. (Year: 2016).
cited by examiner

Search Report of European Patent Office in Appl'n No. 21208374.5, dated Mar. 28, 2022. cited by
applicant

Primary Examiner: Van; Quang T

Attorney, Agent or Firm: Bryan Cave Leighton Paisner LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims priority to and the benefit of Korean Patent Application No. 10-2020-0159559, filed on Nov. 25, 2020, which is hereby incorporated by reference as if fully set forth.

TECHNICAL FIELD

(2) Disclosed herein is an electric range, and one particular implementation relates to an electric range based on induction heating.

BACKGROUND

(3) Details in the background section do not constitute the related art but are given only as background information concerning the subject matter of the present disclosure.

(4) Various types of cooking appliances are used to heat food at homes or restaurants. For example, a cooking appliance may include a gas range using gas and an electric range using electricity. Also, an electric range may use a resistance heating method and an induction method.

(5) An electrical resistance heating method may generate heat by applying electric current to a metallic resistance wire or a non-metallic heat generation element such as silicon carbide to generate heat, and the generated heat is radiated or conducted to heat an object (e.g., a cooking vessel such as a pot, a frying pan and the like).

(6) An induction heating method may apply high-frequency power to a coil to generate a magnetic field around the coil, and an eddy current produced in the generated magnetic field is used to heat an object made of a metallic material.

(7) Thus, when electric current is supplied to a working coil or a heating coil, heat is generated by induction and may heat an object.

(8) The brackets that support various components of an electric range may have a plate-shaped structure. The plate-shaped structure may become deformed due to the load of the components or an external force. Accordingly, there is a growing need for a structure that can improve rigidity of the brackets.

(9) Additionally, a heating part of an induction heating-based electric range may generate heat as a result of electromagnetic interaction. In some examples, the temperature of the heat generated using an induction heating method may be less than the temperature of the heat generated with a heating part using an electrical resistance heating method.

(10) The heat generated in the heating part may transfer to another component. When the heat generated in the heating part transfers to a printed circuit board and a circuit element that are included in the electric range, the electric range may experience an operational error or damage.

(11) Accordingly, there is a growing need for an electric range having a structure that can suppress or reduce a transfer of heat generated in a heating part to a printed circuit board and a circuit element.

SUMMARY

(12) According to an embodiment of the present disclosure, an electric range having a structure that cools down heat generated in a heating part may be provided.

(13) According to an embodiment of the present disclosure, an electric range having a structure that may suppress or reduce a transfer of hot air generated in a heating part to a printed circuit board may be provided.

(14) According to an embodiment of the present, an electric range having a structure that improves blocking an electromagnetic field and electromagnetic waves may be provided.

(15) An electric range in one embodiment may include a heating part configured to heat an object based on an electromagnetic interaction. The heating part may include a core frame having a plurality of channels disposed radially on a lower or bottom surface thereof. The heating part may also include a plurality of ferrite cores mounted onto the channels and disposed under the core frame.

(16) The core frame may include a plurality of air gaps disposed among or between the plurality of channels. The plurality of air gaps may be disposed radially to communicate or connect a center of the core frame to communicate with an edge of the core frame.

(17) The plurality of air gaps may serve as a passage through which air flows, and may be disposed in a central portion of the core frame, such that air smoothly or evenly flows between a central portion of the heating part and an edge of the heating part through the plurality of air gaps, thereby effectively cooling the heating part.

(18) The core frame may have an open hole in or about a position of the edge thereof, in which the

open hole faces the air gap, and the open hole may be formed in a way that adjacent guide lines are spaced apart from one another in a circumferential direction of the core frame.

(19) Similar to the plurality of air gaps, the open hole may serve as a passage through which air flows such that air smoothly or evenly flows between the central portion of the heating part and outside of the heating part through the air gap and the open hole, thereby making effectively cooling the heating part.

(20) An electric range in one embodiment may include a case, a cover plate coupled to an upper end of the case to receive an object to be heated to be placed on an upper or top surface thereof. Further, plurality of heating parts may be disposed under the cover plate and may be configured to heat the object to be heated. Furthermore, a plurality of upper brackets may be disposed under the heating part and may be configured to support the heating part, and a base bracket may be disposed under the upper bracket to facilitate the mounting of a printed circuit board thereon.

(21) Each of the plurality of channels may include a mounting groove onto which a ferrite core may be mounted, and a guide line protruding from a lower or bottom surface of the core frame and forming the mounting groove. At least one of the plurality of air gaps may be formed in a way that the plurality of guide lines are spaced from one another in a circumferential direction in a central portion of the core frame.

(22) At least one of the plurality of guide lines may have a chamfering part configured to reduce a width of a front portion of the guide line in the central portion of the core frame, and the at least one of the plurality of air gaps may be formed in a way or manner that the chamfering parts adjacent to one another are spaced from one another in a circumferential direction of the core frame.

(23) The core frame may have a first inserting hole into which a working coil mounted onto the core frame may be inserted in a portion in which the at least one of the plurality of air gaps is formed.

(24) The core frame may further include a guide rail formed into a spiral or semi-circular shape on an upper surface of the core frame and configured to guide the working coil to allow the working coil to be wound spirally, and a plurality of second coupling parts may be formed to protrude from an outer circumference of the core frame. The plurality of second coupling parts may be disposed radially, and may be coupled to a first coupling part disposed on the upper bracket by a coupling tool.

(25) The core frame may have a mounting hole onto which a temperature sensor may be mounted, in a central portion thereof, and the upper bracket may have a cable inserting hole into which a cable of the temperature sensor may be inserted.

(26) The upper bracket may have a second inserting hole into which the working coil inserted into the core frame may be inserted, and a third inserting hole into which the working coil withdrawn from the core frame may be inserted.

(27) The second inserting hole and the third inserting hole may be formed in a portion of the upper bracket corresponding to an edge portion of the core frame.

(28) The electric range in one embodiment may further include a sensor bracket allowing the temperature sensor to be mounted thereon, and the temperature sensor may be detachably mounted onto the mounting hole.

(29) The cable inserting hole may be formed in or about a portion of the upper bracket corresponding to an edge portion of the core frame.

(30) A surface area of at least one of the air plurality of air gaps on the core frame may be greater than a cross section of the first inserting hole.

(31) An electric range according to embodiments of the present disclosure may facilitate air to flow smoothly or evenly through an air gap and an open hole in a diameter direction below a core frame. Accordingly, heated air may easily or quickly escape out of the core frame while cool air easily or quickly comes into a central portion of the core frame from outside of the core frame. Thus, an

additional passage hole for cooling may not be needed or may be omitted on a first upper plate of an upper bracket.

(32) Accordingly, since the additional passage hole described above is not formed or needed, a transfer of heat generated in the heating part to a printed circuit board disposed under the first upper plate through the passage hole may be effectively suppressed or reduced.

(33) Further, since the additional passage hole is not formed or needed, an electromagnetic field and electromagnetic waves generated in the heating part entering through the passage hole may be effectively suppressed or reduced at the printed circuit board disposed under an upper bracket, thereby improving EMC and EMI of the electric range.

(34) Furthermore, since a working coil is disposed in the plurality of air gaps and the open hole, a second inserting hole may be disposed at an edge of the core frame. Accordingly, less heat may transfer or flow from the heating part to the printed circuit board through the second inserting hole at the edge of the core frame, compared to an example in which the second inserting hole is disposed in the central portion of the core frame.

(35) Specific effects are described along with the above-described effects in the section of Detailed Description.

(36) Aspects, features, and advantages of the present disclosure are not limited to those described above. It is understood that other aspects, features, and advantages not mentioned above can be clearly understood from the following description and can be more clearly understood from the embodiments set forth herein. Additionally, it is understood that various aspects, features, and advantages described herein can be realized via means and combinations thereof that are described in the appended claims.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) The accompanying drawings constitute a part of the specification, illustrate one or more embodiments in the disclosure, and together with the specification, explain the disclosure:

(2) FIG. 1 is a perspective view showing an electric range according to an embodiment of the present disclosure;

(3) FIG. 2 is an exploded perspective view showing the electric range according to an embodiment of the present disclosure;

(4) FIG. 3 is a perspective view showing a base bracket and components mounted onto the base bracket according to an embodiment of the present disclosure;

(5) FIG. 4 is a front view showing the electric range according to an embodiment of the present disclosure;

(6) FIG. 5 is a cross-sectional view of the electric range according to the embodiment shown in FIG. 4;

(7) FIG. 6 is a perspective view showing the electric range according to the embodiment in FIG. 1;

(8) FIG. 7 is an exploded perspective view showing some of the components of the electric range according to the embodiment shown in FIG. 6;

(9) FIG. 8 is a perspective view showing an example heating part according to an embodiment of the present disclosure;

(10) FIG. 9 is a plan view showing an example heating part according to an embodiment of the present disclosure;

(11) FIG. 10 is a bottom view showing an example heating part according to an embodiment of the present disclosure; and

(12) FIG. 11 is a cross-sectional view according to an embodiment of FIG. 9 illustrated in an AA direction.

DETAILED DESCRIPTION

(13) Reference will now be made to the exemplary embodiments illustrated in the drawings, and specific language will be used here to describe the same. It will nevertheless be understood that no limitation of the scope of the invention is thereby intended. Alterations and further modifications of the inventive features illustrated here, and additional applications of the principles of the inventions as illustrated here, which would occur to a person skilled in the relevant art and having possession of this disclosure, are to be considered within the scope of the invention.

(14) The terms “first”, “second” and the like are used herein only to distinguish one component from another component. Thus, the components should not be limited by the terms. Certainly, a first component can be a second component unless stated to the contrary.

(15) Throughout the disclosure, each component can be provided as a single one or a plurality of ones, unless explicitly stated to the contrary.

(16) The singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless explicitly indicated otherwise. It should be further understood that the terms “comprise” or “include” and the like, set forth herein, are not interpreted as necessarily including all the stated components or steps but can be interpreted as excluding some of the stated components or steps or can be interpreted as including additional components or steps.

(17) Throughout the disclosure, the terms “A and/or B” as used herein can denote A, B or A and B, and the terms “C to D” can denote C or greater and D or less, unless stated to the contrary.

(18) Throughout the disclosure, “a vertical direction” refers to a vertical direction of an electric range when the electric range is disposed for normal use. “A horizontal direction” refers to a direction orthogonal to the vertical direction, and a forward and rearward direction refers to a direction orthogonal to both the vertical direction and the horizontal direction. “Bilateral direction” or “a lateral direction” has the same meaning as the horizontal direction, and these terms may be used interchangeably herein.

(19) Various terminology used herein can imply direct or indirect, full or partial, temporary or permanent, action or inaction. For example, when an element is referred to as being “on,” “connected” or “coupled” to another element, then the element can be directly on, connected or coupled to the other element or intervening elements can be present, including indirect or direct variants. In contrast, when an element is referred to as being “directly connected” or “directly coupled” to another element, there are no intervening elements present.

(20) FIG. 1 is a perspective view showing an electric range according to an embodiment of the present disclosure. FIG. 2 is an exploded perspective view showing the electric range according to an embodiment of the present disclosure.

(21) The electric range according to an embodiment of the present disclosure may heat an object based on induction heating. In this example, the object may be a cooking vessel containing a metallic material such as stainless steel, iron and the like.

(22) In one example, induction heating process, high-frequency power may be supplied to a working coil **31** to generate a magnetic field around the working coil **31**, and an object to be heated made of a metallic material may be heated using an eddy current generated by the generated magnetic field.

(23) That is, a heating part **30** having a structure with a working coil **31** adjacent to a ferrite core **330** may supply a high-frequency power to the working coil **31** to generate a magnetic field around the working coil **31**, and when an object to be heated is placed in an area of the generated magnetic field, an eddy current caused by the magnetic field may flow through the object to cause Joule heating, thereby heating the object. Accordingly, a cooking vessel may be the object to be heated by induction, and a food item contained in the cooking vessel may be heated and cooked.

(24) According to an embodiment of the present disclosure, an electric range may include a case **10**, a cover plate **20**, a heating part **30**, an upper bracket **40**, and a base bracket **50**.

(25) The case **10** may protect the electric range and the components constituting the electric range.

For example, the case **10** may be made of aluminum, but is not limited thereto.

(26) The case **10** may be thermally insulated to suppress release of heat generated by the working coil **31** to outside.

(27) Various components such as the heating part **30**, the working coil **31**, the upper bracket **40**, a control board **80** and the like constituting the electric range may be stored or disposed in the case **10**. The case **10** may include an opening, and the opening may be closed by the cover plate **20**. The case **10** may have a cubical shape (or any other suitable shape), which may be formed as a result of processing plate-shaped materials.

(28) The case **10** may include a first casing **110**, a second casing **120** and a third casing **130**.

(29) The first casing **110** may be configured to define a bottom surface of the case **10**. The first casing **110** may support the various components described above in accordance with embodiments of the electric range.

(30) The first casing **110** may include at least one of vent holes **111** through which air may flow or communicate, and the vent holes **111** may help cool a printed circuit board **51** and the circuit element components mounted onto the printed circuit board **51** disposed on the first casing **110**.

(31) The second casing **120** may bend from the first casing **110** to form or define lateral surfaces of the case **10**. The second casing **120** may bend from edges of the first casing **110** in an up-down or vertical direction to define the lateral or side walls of the electric range. The second casing **120** may surround the lateral or side walls of the base bracket **50**.

(32) The second casing **120** may be disposed on each side of the first casing **110** to form or define a substantially rectangular shape. The second casing **120** may improve or reinforce the rigidity of the case **10** entirely.

(33) That is, the second casing **120** bent from the first casing **110** may reduce or suppress the plate-shaped first casing **100** from bending (or deformed) or being damaged the by weight of the built-in or internal components thereof or an external force.

(34) The second casing **120** may further include a plurality of exhaust holes **121** formed into or defining slits. The plurality of exhaust holes **121** may be configured to communicate air from inside of the case **10** to outside of the case **10**. Accordingly, the exhaust holes **121** may cool the components stored or disposed in the case **10**.

(35) The third casing **130** may bend from the second casing **120**, and may support the upper bracket **40**. The third casing **130** may be disposed on each side of the first casing **110**.

(36) A first upper plate **41** forming a bottom surface of the upper bracket **40** may be mounted onto an upper or top surface of the third casing **130**, and the first upper plate **41** and the third casing **130** may be coupled to each other by a coupling tool such as a bolt and the like.

(37) The cover plate **20** may be coupled to an upper or top end or portion of the case **10**, and an object to be heated may be disposed on the upper or top surface of the cover plate **20**. The cover plate **20** may close the open upper or top portion of the case **10** and may protect the components stored or disposed in the case **10**.

(38) An object to be heated may be placed on the upper or top surface of the cover plate **20**, and a magnetic field generated in the heating part **30** may pass through the cover plate **20** and reach the object to be heated. The cover plate **20** may be made of a material containing ceramics, for example, but is not limited thereto.

(39) An input interface may be disposed on the upper or top surface of the cover plate **20**, and the input interface may receive an input from a user. The input interface may be disposed in an area of the upper or top surface of the cover plate **20**, and may display an image. It is understood that the input interface is not limited to any specific location.

(40) The input interface may receive a touch input from the user, and the electric range of the present disclosure may operate based on the received touch input.

(41) For example, the input interface may be a module for inputting a heating intensity or a heating period and the like desired by the user, and may be implemented as a physical button or a touch

panel and the like.

(42) For example, the input interface may be a thin film transistor liquid crystal display (TFT LCD), but is not limited thereto.

(43) The control board **80** may be disposed under the cover plate **20**, and the control board **80** may be used to input or provide an instruction to operate the electric range of the present disclosure. The control board **80** may include or be provided with a plurality of key switches, and the user may input an instruction or command to the control board **80** through the key switches to controlling the operation of the electric range of the present disclosure.

(44) In one embodiment of the electric range, an upper surface of the control board **80** may contact or be adjacent to the lower or bottom surface of the cover plate **20**. In this embodiment, the control board **80** may be disposed at or about a position corresponding to the position of the input interface.

(45) The control board **80** and the input interface may be connected to each other to facilitate electrostatic touch input. Thus, when a user inputs a control instruction on the input interface, the control instruction may be input or transmitted to the control board **80**.

(46) Additionally, a display may be disposed at or about an area on the upper or top surface of the cover plate **20**, and the display may display a driving state of the electric range. It is understood that the display is not limited to any specific location.

(47) A light display area may be formed on the upper or top surface of the cover plate **20**. A light source unit **91** may be disposed under the cover plate **20**, and the light rays emitted from the light source unit **91** may be delivered to the user through the light display area. In this case, the light display area and the light source unit **91** may be disposed in positions that correspond with each other. When a plurality of light source units **91** is provided, the same number of light display areas as the number of light source units **91** may be provided on the upper or top surface of the cover plate **20**.

(48) The electric range in an embodiment of the present disclosure may further include a cover bracket **70** for supporting the cover plate **20**. The cover bracket **70** is described hereinafter with reference to FIGS. 2, 4, and 5.

(49) The cover bracket **70** may be disposed outside the upper bracket **40** and the case **10**. The cover bracket **70** may be coupled to the case **10** and may support the cover plate **20**. For example, the cover bracket **70** may be coupled to the case **10** by a coupling tool such as a bolt and the like.

(50) A plurality of cover brackets **70** may be provided, and each of the plurality of cover brackets **70** may be disposed in a portion corresponding to each side of the cover plate **20** formed into a rectangular shape. Accordingly, a total of four cover brackets **70** may be provided such that each of the plurality of cover brackets **70** may be disposed on each side of the rectangle-shaped cover plate **20**.

(51) The cover bracket **70** may include a first cover plate **710** and a second cover plate **720**. The first cover plate **710** may be disposed to face the second casing **120** and may be coupled to the second casing **120**. The second cover plate **720** may be bent from the first cover plate **710** and may support the cover plate **20**.

(52) The cover plate **20** may be mounted onto an upper or top surface of the second cover plate **720**, and the second cover plate **720** and the cover plate **20** may be coupled to each other by an adhesive, for example. However, the method for coupling the second cover plate **720** and the cover plate **20** may not be limited.

(53) A plurality of heating parts **30** may be provided, disposed under the cover plate **20** to heat the object to be heated. In the embodiment, the plurality of heating parts **30** may be provided to operate based on an induction heating method.

(54) In another embodiment, some of the plurality of heating parts **30** may be based on induction heating, and the remaining heating parts may be provided as a highlight heating apparatus based on electrical resistance heating. That is, the electric range in one embodiment of the present disclosure

may be provided as a hybrid range.

(55) Hereunder, an electric range in accordance with an embodiment of the present disclosure is described with all of the plurality of heating parts **30** being based on induction heating is described.

(56) The heating parts **30** may be mounted onto the upper bracket **40**, and in one embodiment, a total of three heating parts **30** may be provided. It is understood that the number of the heating parts **30** may not be limited. When a plurality of heating parts **30** is provided, a plurality of upper brackets **40** supporting the heating parts **30** may be provided.

(57) The heating parts **30** may be provided with a core frame **320**, a working coil **31** may be spirally wound around an upper surface of the core frame **320**, and a ferrite core **330** may be mounted onto a lower or bottom surface of the core frame **320**. Accordingly, when the working coil **31** is supplied with high-frequency power, a magnetic field may be formed around the ferrite core **330**, and an eddy current may be formed in the object to be heated due to the magnetic field.

(58) The heating parts **30** are described below with reference to the following drawings.

(59) FIG. **3** is a perspective view showing a base bracket **50** and components mounted onto the base bracket **50** in one embodiment. FIG. **4** is a front view showing the electric range in one embodiment.

(60) FIG. **5** is a cross-sectional view of FIG. **4**. FIG. **6** is a perspective view showing the electric range in FIG. **1** without some components.

(61) The upper bracket **40** may be disposed under the heating part **30** and support the heating part **30**. In one embodiment, a plurality of upper brackets **40** may be provided. The upper brackets **40** may be made of aluminum, for example, but is not limited thereto.

(62) The upper bracket **40** may include a first upper plate **41** and a second upper plate **42**. The first upper plate **41** may form a bottom surface of the upper bracket **40**, and the heating part **30** may be mounted onto the first upper plate **41**.

(63) The first upper plate **41** may be provided to cover a printed circuit board **51** that may be disposed under the first upper plate **41** in the vertical or up-down direction. When a plurality of upper brackets **40** is provided, a single first upper plate **41**, or a plurality of first upper plates **41** that may be coupled to one another may cover the printed circuit board **51** depending on the surface area of the printed circuit board **51**.

(64) With the structure, the first upper plate **41** may block an electromagnetic field and electronic magnetic waves, generated from the heating part **30**, from reaching the printed circuit board **51** and other elements mounted onto the printed circuit board **51**.

(65) That is, the upper bracket **40** may improve the performance of electromagnetic compatibility (EMC) and electromagnetic interference (EMI) of the printed circuit board **51**.

(66) One or more second upper plates **42** may be formed by bending the first upper plate **41** in the vertical or up-down direction of the electric range. The second upper plates **42** may bend from edges of the first upper plate **41** in the vertical or up-down direction.

(67) The second upper plates **42** may be disposed on or about each side of the first upper plate **41** to form a substantially rectangular shape. When a plurality of upper brackets **40** is provided, the second upper plates **42** may be formed on each side of the first upper plate **41** except on or about mutually adjacent sides of the upper brackets **40**.

(68) The second upper plate **42** improve the rigidity of the upper bracket **40**. That is, the second upper plates **42** bent from the first upper plate **41** reduce the possibility of bending or damaging the plate-shaped first upper plate **41** due to the weight of the built-in components including the heating parts **30** or an external force.

(69) A light source unit **91** may be disposed on the upper bracket **40**. For example, the light source unit **91** may be disposed on the printed circuit board **51** disposed under the upper bracket **40**, and the upper bracket **40** may have an opening disposed at or about the position corresponding to a position of the light source unit **91**. In another embodiment, the light source unit **91** may be disposed on the bracket, and electrically connect to the printed circuit board **51** under the upper

bracket **40**.

(70) As described above, a light display area may be formed in a portion of the cover plate **20**, corresponding to the light source unit **91**. It is understood that the position of the light display area is not specifically limited.

(71) The light source unit **91** may be provided in a way or manner such that a plurality of LEDs may be aligned in a row, for example. The light source unit **91** may light up when the heating parts **30** operate to inform the user whether the heating parts **30** is in operation. Alternatively, at the light source unit **91**, various lit-up shapes, colors and the like of the plurality of LEDs may change to inform the user of the operation state of the electric range.

(72) The number of the light source units **91** may be determined based on the number of the heating parts **30**. As shown in FIG. 6, three light source units **91** may be provided based on the three heating parts **30**. However, the number of the light source units **91** is not limited.

(73) A base bracket **50** may be disposed under the upper bracket **40**, and may include a bottom plate **510** and a lateral plate **520**. The printed circuit board **51** may be mounted onto the base bracket **50**. The bottom plate **510** may form a bottom surface of the base bracket **50**, and the printed circuit board **51** may be mounted onto an upper or top surface of the base bracket **50** or the bottom plate **510**.

(74) The lateral plate **520** may be formed by bending from the bottom plate **510** in the vertical or up-down direction of the electric range. The lateral plate **520** may bend at or around the edges of the bottom plate **510** in the vertical or up-down direction.

(75) The lateral plate **520** may be disposed on each side of the bottom plate **510** formed to form a substantially rectangular shape. In one example, a plurality of upper brackets **40** may be provided, and the lateral plate **520** may be formed on each side of the bottom plate **510** except for the adjacent sides of the upper brackets **40**.

(76) The lateral plate **520** improves the rigidity of the base bracket **50**. That is, the lateral plate **520** bent from the bottom plate **510** may reduce the possibility of a bending or damaging the plate-shaped bottom plate **510** due to the weight of the built-in components such as the printed circuit board **51** and the like or an external force.

(77) The printed circuit board **51** may include a controller, receive power from an external power source, and may be configured to communicate with an external device in a wired or wireless manner.

(78) The printed circuit board **51** may electrically connect to the control board **80** to receive instructions input by a user on the control board **80**. The printed circuit board **51** may electrically connect to the light source unit **91** and the working coil **31** to control the operation of the light source unit **91** and the working coil **31**.

(79) Referring to FIG. 3, a heat sink **52**, active elements including an air blowing fan **53**, and passive elements may be mounted onto the printed circuit board **51**, and an electric circuit may be formed on the printed circuit board **51**.

(80) The heat sink **52** may cool down the heat inside the case **10** to protect the components stored or disposed in the case **10**. The heat sink **52** may be mounted onto the printed circuit board **51**, and cool down the heat generated on the printed circuit board. Further, the heat sink **52** may cool down the heat that is generated by an electromagnetic interaction as a result of the operation of the heating part **30**.

(81) For example, the heat sink **52** may have a plurality of cooling fins, and may include an air guide that may be configured to cover the cooling fins and to guide the flow of air to the cooling fins.

(82) The air blowing fan **53** may be mounted onto the printed circuit board **51**. In this example, as illustrated in FIG. 3, a guide wall for guiding the flow of air may be formed at or about an air outlet of the air blowing fan **53** in a direction in which the heat sink **52** may be disposed such that the air, forced to flow by the air blowing fan **53**, flows to the heat sink **52**.

(83) As a result of the operation of the air blowing fan **53**, air inside the case **10** may flow to the heat sink **52**, and the inside of the case **10** may be cooled by the heat sink **52**.

(84) FIG. **7** is an exploded perspective view showing some of the components of the electric range in accordance with an embodiment, shown in FIG. **6**. FIG. **8** is a perspective view showing a heating part **30** in one embodiment. In FIGS. **7** and **8**, a working coil **31** is omitted for clarity of description and illustrations.

(85) In one embodiment, the heating part **30** may be mounted onto the upper bracket **40** with one or more coupling parts may be formed at the corresponding portions of the heating part **30** and the upper bracket **40** to couple the heating part **30** and the upper bracket **40** accordingly.

(86) The upper bracket **40** may be provided with one or more first coupling parts **410** protruding from and coupled to the heating part **30**. The heating part **30** may be provided with one or more second coupling parts **310** corresponding to the first coupling parts **410**.

(87) A plurality of second coupling parts **310** may protrude from the outer circumference of the core frame **320**, and may be disposed radially and may be coupled to the first coupling part **410** disposed on the upper bracket **40** by a coupling tool.

(88) Each of the second coupling parts **310** may be disposed radially on an edge of the heating part **30** and may be spaced apart from one another in a circumferential direction. The same number of first coupling parts **410** as the number of second coupling parts **310** may be provided, and the second coupling parts **310** may be formed in positions corresponding to positions of the first coupling parts **410** on the upper bracket **40**.

(89) In one example, the first coupling part **410** and the second coupling part **310** may be fastened by a screw bolt **900**, and may be coupled to each other.

(90) The electric range in one embodiment may further include a temperature sensor **60** disposed at or about a central portion of the core frame **320**. The core frame **320** may have a mounting hole **321** onto which the temperature sensor **60** may be mounted, in the central portion thereof.

(91) The temperature sensor **60** may be electrically connected to the printed circuit board **51** provided under the upper bracket **40** by a cable. Accordingly, the cable connecting the temperature sensor **60** and the printed circuit board **51** may be installed in a way or manner that the cable passes through the upper bracket **40**. Accordingly, the upper bracket **40** may have a cable inserting hole **420** into which the cable of the temperature sensor **60** may be inserted.

(92) In one embodiment, the electric range may further include a sensor bracket **61** for the temperature sensor **60** to be mounted onto the core frame **320**. The temperature sensor **60** may be mounted onto the sensor bracket **61**, and the sensor bracket **61** may be detachably mounted onto the mounting hole **321**.

(93) The temperature sensor **60** may measure a temperature of the heating part **30** during the operation of the electric range of the present disclosure. The heating part **30** provided based on an induction heating method may not generate high-temperature heat on its own. However, the heating part **30** may generate heat due to the electromagnetic interaction, even with low temperature heat.

(94) The heat generated by the heating part **30** may adversely affect not only the heating part **30** but also the printed circuit board **51** disposed under the heating part **30** and various types of components included in the printed circuit board **51**. To reduce or prevent the effects of the heat, the temperature of the heating part **30** may be measured, and when the measured temperature exceeds a predetermined value, appropriate measures may be taken accordingly in the electric range.

(95) For example, the controller may receive information on the temperature of the heating part **30** measured by the temperature sensor **60**, and when the temperature of the heating part **30** exceeds the predetermined value, the controller may stop the operation of the electric range or control the air blowing fan **53** to increase the cooling capacity.

(96) The core frame **320** may have a first inserting hole **322** into which the working coil **31** mounted onto the core frame **320** may be inserted. The first inserting hole **322** may be formed at or

about a position spaced in a diameter or radial direction from the mounting hole **321** at or about the central portion of the core frame **320**.

(97) The working coil **31** may pass through the first inserting hole **322**, may be inserted into an upper surface of the central portion of the core frame **320**, may be wound spirally around a guide rail **324** disposed on the upper or top surface of the core frame **320**, and then may be withdrawn outward from an edge portion of the core frame **320**.

(98) The working coil **31** may be electrically connected to the printed circuit board **51** disposed under the upper bracket **40**. Accordingly, the upper bracket **40** may have an inserting hole into which the working coil **31** may be inserted through the inserting hole.

(99) The inserting hole may include a second inserting hole **431** and a third inserting hole **432**, and the second inserting hole **431** and the third inserting hole **432** may be formed on the upper bracket **40**. The working coil **31** inserted into the core frame **320** may be inserted into the second inserting hole **431**. The working coil **31** withdrawn from the core frame **320** may be inserted into the third inserting hole **432**.

(100) For example, for the working coil **31** to be disposed readily, the third inserting hole **432** may be provided at or near the edge of the core frame **320**.

(101) The working coil **31** may be inserted into the central portion of the core frame **320**, may be provided or move to the edge of the core frame **320** while being wound around the guide rail **324**, and may then be withdrawn outward from the edge of the core frame **320**.

(102) For the working coil **31** to be easily disposed in the electric range, the third inserting hole **432** may be formed in a portion of the upper or top bracket **40**, corresponding to the edge portion of the core frame **320**.

(103) The working coil **31** may pass through the second inserting hole **431** of the upper bracket **40** from the printed circuit board **51**, may pass through the first inserting hole **322** formed on the core frame **320**, and may be inserted into the upper or top surface of the central portion of the core frame **320**.

(104) The working coil **31** may move to the edge of the core frame **320** while being wound spirally around the guide rail **324** disposed on the upper surface of the core frame **320**. Thereafter, the working coil **31** may be withdrawn out of the core frame **320**.

(105) The working coil **31** withdrawn out of the core frame **320** may pass through the third inserting hole **432** formed on the upper bracket **40**, and may connect to the printed circuit board **51** again.

(106) The heating part **30** is further described with reference to FIG. **8** hereinafter.

(107) The heating part **30** may include a working coil **31**, a core frame **320**, and a ferrite core **330**. In FIG. **8**, the working coil **31** is omitted for clarity of description and illustration of the structure of the heating part **30**. The heating part **30** around which the working coil **31** is wound is illustrated in the other drawings. Accordingly, the subject matter of the present disclosure can be understood without difficulty by a person having ordinary skill in the art.

(108) The working coil **31** may be supplied with high-frequency power to generate a magnetic field. The working coil **31** may be made of a Litz wire exhibiting high durability, for example, but is not limited thereto.

(109) The ferrite core **330** may be mounted onto the lower or bottom surface of the core frame **320**, and the working coil **31** may be wound around the upper or top surface of the core frame **320**. A plurality of channels **323** may be provided radially on the lower or bottom surface of the core frame **320**. The ferrite core **330** may be mounted onto or in the channels **323**. The same number of the channels **323** as the number of the ferrite cores **330** may be provided.

(110) Each of the plurality of channels **323** may include a mounting groove **323a** onto which the ferrite core **330** may be mounted, and a guide line **323b** protruding from the lower or bottom surface of the core frame **320** to form or define the mounting groove **323a**.

(111) As illustrated in FIG. **8**, a ferrite core **330** may protrude further outward than the edge of the

core frame **320** in a diameter or radial direction of the core frame **320**. Accordingly, the guide line **323b** may only be formed at or about the edge portion, without the mounting groove **323a**.

(112) The plurality of channels **323** may be formed such that the plurality of ferrite cores **330** may be radially spaced apart by a predetermined distance from one another in the circumferential direction of the core frame **320**, as shown in FIG. **8**.

(113) As illustrated in FIG. **8**, the first inserting hole **322** into which the working coil **31** is inserted may be formed between two adjacent ferrite cores **330**, at or about the central portion of the core frame **320**. Accordingly, to prevent interference between the ferrite cores **330** and the first inserting hole **322**, the channel **323** disposed in a position adjacent to the first inserting hole **322** may be spaced apart in the circumferential direction by a distance greater than a diameter of the first inserting hole **322**, in the central portion of the core frame **320**, for example.

(114) The guide rails **324** around which the working coil **31** is wound may be formed on an upper or top surface of the ferrite core **330**. The guide rails **324** may protrude from the upper or top surface of the core frame **320** and may be formed into a spiral or semi-circular shape such that the working coil **31** mounted onto the core frame **320** may be guided by the guide rail **324** and wound spirally.

(115) A plurality of guide rails **324** may be provided in the diameter or radial direction of the core frame **320**. The working coil **31** may be mounted onto the grooves formed among the plurality of guide rails **324** and may be wound around the guide rails **324**.

(116) An adhesive may be applied to the guide rails **324** and the grooves among or between the guide rails **324**, to reliably fix or attach the working coil **31** to the upper or top surface of the core frame **320**, and the working coil **31** may adhere to the upper or top surface of the core frame **320**.

(117) For example, to electrically insulate the working coil **31**, the adhesive may be made of an insulating material.

(118) A space may be formed in or about a portion of the lower or bottom surface of the core frame **320**, in which the ferrite core **330** is not installed. Accordingly, the guide rails **324**, as illustrated in FIG. **8**, may be formed discontinuously in the circumferential direction of the core frame **320**.

(119) However, the guide rails **324** may be formed into a spiral or semi-circular shape from the central portion of the core frame toward the edge thereof, and the working coil **31** may be wound around the guide rails **324** to be disposed in a spiral or semi-circular shape from the central portion of the core frame toward the edge thereof.

(120) That is, the working coil **31** may be inserted into the upper or top surface of the core frame **320** by passing through the first inserting hole **322**, and may be wound around the guide rails **324** and to be formed into a spiral or semi-circular shape, and withdrawn outward from the edge of the core frame **320**.

(121) A plurality of ferrite cores **330** may be provided and mounted onto the channel **323**, and may be disposed under the core frame **320**. Each of the ferrite cores **330** may be coupled to the corresponding mounting groove **323a** of the channels **323** by an adhesive. However, a coupling method of the ferrite core **330** may not be limited.

(122) In one embodiment, when the working coil **31** is supplied with high-frequency power, a magnetic field may be generated around the ferrite core **330**, and when an object to be heated is placed in or about an area in which the magnetic field is generated, an eddy current may be generated and may cause Joule heat to heat the object.

(123) FIG. **9** is a plan view showing the heating part **30** in one embodiment of the present disclosure. FIG. **10** is a bottom view showing the heating part **30** in one embodiment of the present disclosure. FIG. **11** is a cross-sectional view showing FIG. **9** shown from an AA direction illustrated in FIG. **9**.

(124) When the working coil **31** is supplied with power, an electromagnetic field may be generated around the ferrite core **330**. Due to an electromagnetic interaction, heat may be generated in the heating part **30**. Additionally, heat may be generated around the ferrite core **330** disposed under the

heating part **30**.

(125) In one example, to cool down the heat generated around the ferrite core **330**, an additional passage hole to facilitate convection of air on the first upper plate **41** of the upper bracket **40** disposed under the ferrite core **330**, and the air may flow through the passage hole to cool the ferrite core **330** based on the convective heat transfer.

(126) However, when the heated air flows from the heating part **30** to the printed circuit board **51** disposed under the first upper plate **41** through the passage hole, the printed circuit board **51** and the components mounted onto the printed circuit board **51** may be heated, which may cause operational errors and failures of the electric range.

(127) Additionally, an electromagnetic field and electromagnetic waves generated in the heating part **30** may reach the printed circuit board **51** disposed under the first upper plate **41** through the passage hole without being blocked by the first upper plate **41**, causing deterioration or reduction of the EMC and EMI performances of the electric range.

(128) In one embodiment, to prevent or reduce the above described effects, air may be directed to flow smoothly or evenly among the plurality of ferrite cores **330**, such that the heat generated in the heating part **30** smoothly or evenly cools down over the first upper plate **41** of the upper bracket **40**.

(129) Thus, an additional passage hole for cooling may not be necessitated on the first upper plate **41**, and the first upper plate **41** may have a minimum number of through holes, and a convection-based transfer of the heat generated in the heating part **30** through the through holes to the printed circuit board **51** disposed under the first upper plate **41** may be suppressed or reduced. Additionally, the electromagnetic field and electromagnetic waves transmitted to the printed circuit board **51** may be suppressed or reduced.

(130) Referring to FIG. **10**, the core frame **320** may have a plurality of air gaps **325**. The plurality of air gaps **325** may be provided or disposed among or between the plurality of channels **323**, disposed radially, and may be configured to communicate or direct air flow from the center of the core frame **320** to the edge of the core frame **320**.

(131) Each of the air gaps **325** may be formed or disposed among or between a plurality of guide lines **232b** forming mounting grooves **323a** onto which the ferrite core **330** disposed under the core frame **320** may be mounted, in the circumferential direction of the core frame **320**.

(132) Each of the air gaps **325** may be formed in a way or manner that the guide lines **323b** may be spaced from one another radially at or about the central portion of the core frame **320**.

(133) The guide line **323b** may have a chamfering part **323b-1** configured to reduce the width of a front portion of the guide line **323b** at or about the central portion of the core frame **320**. In this example, the front denotes a direction toward the center of the core frame **320**.

(134) The air gaps **325** may be formed in a way or manner that the chamfering parts **323b-1** adjacent to one another may be spaced apart from one another in the circumferential direction of the core frame **320**. Accordingly, The plurality of air gaps **325** may be disposed at or about the central portion of the core frame **320** at regular intervals in the circumferential direction of the core frame **320**.

(135) Each of the air gaps **325** may be surrounded by an outer lateral surface of the chamfering part **323b-1** of the guide line **323b** and by a bottom surface of the core frame **320**, at or about the central portion of the core frame **320**, such that a front portion, a rear portion, and a lower portion may be open.

(136) The core frame **320** may have an open hole **326** at or about a position of the edge thereof, facing the air gap **325**. The open hole **326** may be formed in a way or manner that the adjacent guide lines **323b** may be spaced apart from one another in the circumferential direction of the core frame **320**.

(137) The open hole **326** may be surrounded by an outer lateral surface of another portion of the guide line **323b** other than the chamfering part **323b-1** of the guide line **323b** and by the bottom surface of the core frame **320** such that a front portion, a rear portion, and a lower portion may be

open.

(138) The air gap **325** and the open hole **326** may be disposed to face each other in the diameter or radial direction of the core frame **320**. Accordingly, air may flow smoothly or evenly from the center of the core frame **320** to the edge thereof, in a lower or bottom side portion of the core frame **320** in the diameter direction of the core frame **320** along the air gap **325** and the open hole **326**.

(139) For example, heated air in the central portion of the core frame **320** may move or flow to the edge of the core frame **320** along the air gap **325** and the open hole **326** such that the core frame **320** readily or quickly cools.

(140) Additionally, in one embodiment, the plurality of air gaps **325** and the plurality of open holes **326** may be radially and symmetrically disposed with respect to the center of the core frame **320**. Accordingly, air at the edge of the core frame **320** may sequentially pass or flow through an open hole **326**, an air gap **325**, the opposite open hole **326**, and the opposite air gap **325** to smoothly or evenly flow to the opposite edge.

(141) In one example, air may flow smoothly or evenly in the diameter direction of the core frame **320** through the air gap **325** and the open hole **326**, and below the core frame **320**. Accordingly, heated air may easily escape out of the core frame **320**, while cool air may easily come or flow into the central portion of the core frame **320** from outside of the core frame **320**. Thus, an additional passage hole for cooling may not be formed or necessitated on the first upper plate **41** of the upper bracket **40**.

(142) Since an additional passage hole is not formed or needed as described above, the heat generated in the heating part **30** may be suppressed or reduced from transferring or flowing through from the passage hole to the printed circuit board **51** disposed under the first upper plate **41** through the passage hole.

(143) Additionally, since an additional passage hole is not formed or needed, an electromagnetic field and electromagnetic waves generated in the heating part **30** may be suppressed or reduced from transmitting through from the passage to the printed circuit board **51** disposed under the upper bracket **40**, thereby ensuring improvement in the EMC and EMI of the electric range.

(144) The air gap **325** and the open hole **326** may have a radial and symmetrical structure, and the ferrite core **330** may also be provided radially and symmetrically with respect to the center of the core frame **320**. Accordingly, each ferrite core **330** and the working coil **31** disposed near or about the ferrite core **330**, in the symmetrical disposition corresponding to the plurality of ferrite cores **330**, may generate a more uniform magnetic field in the circumferential direction of the core frame **320** compared to an asymmetrical disposition corresponding to the plurality of ferrite cores **330**.

(145) The second inserting hole **431** may be formed or disposed in or about a portion of the upper bracket **40**, corresponding to the edge portion of the core frame **320**. Referring to FIG. 7, the second inserting hole **431** into which the working coil **31**, inserted from the printed circuit board **51** into the core frame **320**, may be inserted. The second inserting hole **431** may be formed or disposed in or about a portion of the first upper plate **41**, corresponding to the edge of the core frame **320**.

(146) Thus, when the second inserting hole **431** may be formed in or about a portion of the first upper plate **41** corresponding to the central portion of the core frame **320**, the heat generated in the heating part **30** may be suppressed or reduced from transferring or flowing to the printed circuit board **51** disposed under the first upper plate **41**.

(147) That is, less heat may transfer from the heating part **30** to the printed circuit board **51** through the second inserting hole **431** when the second inserting hole **431** may be disposed at or about the edge of the core frame **320** than when the second inserting hole **431** may be disposed in or about the central portion of the core frame **320**.

(148) Accordingly, the third inserting hole **432** may be formed in or about a portion of the upper bracket **40**, corresponding to the edge portion of the core frame **320**. Referring to FIG. 7, the third inserting hole **432** may be formed in or about a position of the first upper plate **41** corresponding to the edge of the core frame **320**.

(149) The first inserting hole **322** may be formed in or about a portion of the core frame **320**, where the air gap **25** may be formed, and the working coil **31** mounted onto the core frame **320** may be inserted into the first inserting hole **322**.

(150) In this example, the working coil **31** having passed through the second inserting hole **431** and inserted into an upper or top side of the first upper plate **41** may reach the first inserting hole **322** disposed in about the portion where the air gap **325** may be formed. Further, the working coil **31** may pass through the open hole **326** and the air gap **325** formed in the lower or bottom portion of the core frame **320**. The working coil **31** may also pass through the first inserting hole **322**, and may be wound around the guide rail **324** formed on the core frame **320**. Thus, the air gap **325** and the open hole **326** may serve as a passage in which the working coil **31** may be disposed.

(151) In one embodiment, since the working coil **31** may be disposed in the air gap **325** and the open hole **326**, the second inserting hole **431** may be disposed at or about the edge of the core frame **320**. Thus, the second inserting hole **431** at or about the edge of the core frame **320** may help reduce the amount of heat transferred or flowing from the heating part **30** to the printed circuit board **51**, compared to the second inserting hole **431** disposed in the central portion of the core frame **320**.

(152) The cable inserting hole **420** may be formed or disposed in or about a portion of the upper bracket **40** corresponding to the edge portion of the core frame **320**. Referring to FIG. 7, the cable inserting hole **420** may be formed or disposed on the first upper plate **41** in or about the portion corresponding to the edge portion of the core frame **320**.

(153) A cable connected to the temperature sensor **60** may pass through the air gap **325** and the open hole **326**. The cable may also pass through the cable inserting hole **420** at the edge of the core frame **320** and may be inserted into the printed circuit board **51** disposed under the first upper plate **41**. That is, the air gap **325** and the open hole **326** may serve as a passage through which the cable of the temperature sensor **60** may be disposed.

(154) In one embodiment, the cable may be disposed in or about the air gap **325** and the open hole **326**. Thus, the cable inserting hole **420** may be disposed at or about the edge of the core frame **320**. Accordingly, as described in reference to the second inserting hole **431** above, less heat may transfer or flow from the heating part **30** to the printed circuit board **51** through the cable inserting hole **420** at the edge of the core frame **320** than compared to the cable inserting hole **420** in the central portion of the core frame **320**.

(155) The surface area of the air gap **325** on the core frame **320** may be greater than the cross section of the first inserting hole **322**. In the example, the working coil **31** inserted into the first inserting hole **322** may be disposed reliably in the air gap **325** without being interrupted by the guide line **323b**.

(156) The embodiments are described above with reference to a number of illustrative embodiments thereof. However, the present disclosure is not intended to limit the embodiments and drawings set forth herein, and numerous other modifications and embodiments can be devised by one skilled in the art. Further, the effects and predictable effects based on the configurations in the disclosure are to be included within the range of the disclosure though not explicitly described in the description of the embodiments.

Claims

1. An electric range, comprising: a case; a cover plate coupled to an upper surface of the case; a plurality of heating parts disposed under the cover plate; a plurality of upper brackets disposed under the plurality of heating parts; a base bracket disposed under the plurality of upper brackets; a printed circuit board disposed on the base bracket, wherein each of the plurality of heating parts comprises: a core frame comprising a plurality of channels disposed radially on a lower surface of the core frame; and a plurality of ferrite cores disposed on the plurality of channels and under the

core frame, wherein the core frame comprises a plurality of air gaps respectively disposed between the plurality of channels, and wherein the plurality of air gaps are disposed radially from a center of the core frame to an edge of the core frame, wherein each of the plurality of channels comprises a guide line protruding from the lower surface of the core frame, wherein the guide line comprises a chamfering part that reduces a width of a front portion of the guide line adjacent the central portion of the core frame, and wherein the air gap is formed in a way that the chamfering parts adjacent to one another are spaced from one another in a circumferential direction of the core frame.

2. The electric range of claim 1, wherein each of the plurality of channels comprises: a mounting groove onto which at least one of the plurality of ferrite cores is mounted; and wherein the air gaps are disposed between each of the plurality of channels and extend from a central portion of the core frame.

3. The electric range of claim 2, wherein the core frame comprises a first inserting hole disposed at a portion where at least one of the plurality of air gaps is formed to receive a working coil that is attached to the core frame.

4. The electric range of claim 3, wherein the core frame further comprises: a guide rail having a spiral shape and disposed on the upper surface of the core frame to guide the working coil; and a plurality of second coupling parts protruding from an outer circumference of the core frame, wherein the plurality of second coupling parts are disposed radially, and wherein the plurality of second coupling parts are coupled to a plurality of first coupling parts disposed on the plurality of upper brackets.

5. The electric range of claim 3, wherein the core frame comprises a mounting hole on which a temperature sensor is mounted, wherein the at least one of the plurality of upper brackets comprises a cable inserting hole to receive a cable of the temperature sensor.

6. The electric range of claim 5, wherein the at least one of the plurality of upper brackets comprises a second inserting hole into which the working coil inserted into the core frame is inserted, and a third inserting hole into which the working coil withdrawn from the core frame is inserted.

7. The electric range of claim 6, wherein the second inserting hole and the third inserting hole are disposed about a portion of the at least one of the upper brackets corresponding to an edge portion of the core frame.

8. The electric range of claim 5, wherein the electric range further comprises a sensor bracket, wherein the temperature sensor is disposed on the sensor bracket, and wherein the temperature sensor is detachably mounted on the mounting hole.

9. The electric range of claim 5, wherein the cable inserting hole is disposed about a portion of the at least one of the plurality of upper brackets corresponding to an edge portion of the core frame.

10. The electric range of claim 3 wherein a surface area of each of the plurality of the plurality of air gaps, is greater than a cross section of the first inserting hole.

11. The electric range of claim 2, wherein the core frame comprises an open hole disposed about an edge portion of the core frame, wherein the open hole faces the at least one of the plurality of air gaps.

12. The electric range of claim 2, wherein the guide line comprises a plurality of guide lines, each of the plurality of guide lines being spaced apart from one another in a circumferential direction of the core frame.

13. The electric range of claim 1, wherein the plurality of air gaps are disposed at the central portion of the core frame at regular intervals in the circumferential direction of the core frame.

14. The electric range of claim 1, wherein each of the air gaps is surrounded by an outer lateral surface of the chamfering part of the guide line and by a bottom surface of the core frame, at the central portion of the core frame, such that a front portion, a rear portion, and a lower portion are opened.

15. An electric range, comprising: a case; a cover plate coupled to an upper surface of the case; a

plurality of heating parts disposed under the cover plate; a core frame comprising a plurality of channels disposed radially on a lower surface of the core frame; a plurality of ferrite cores disposed on the plurality of channels and under the core frame; and a plurality of upper brackets disposed under the plurality of heating parts; wherein the core frame comprises a plurality of air gaps respectively disposed between the plurality of channels, wherein the plurality of air gaps are disposed radially from a center of the core frame to an edge of the core frame, wherein each of the plurality of channels comprises a guide line protruding from the lower surface of the core frame, wherein the guide line comprises a chamfering part that reduces a width of a front portion of the guide line adjacent the central portion of the core frame, and wherein the air gap is formed in a way that the chamfering parts adjacent to one another are spaced from one another in a circumferential direction of the core frame.

16. The electric range of claim 15, wherein each of the plurality of channels comprises: a mounting groove onto which one of the plurality of ferrite cores is mounted; and wherein the air gaps are disposed between each of the plurality of channels and extend from a central portion of the core frame, wherein the core frame comprises a first inserting hole into which a working coil that is attached to the core frame is inserted, the first inserting hole disposed at a portion of the core frame where at least one of the plurality of air gaps is disposed.

17. The electric range of claim 16, wherein the core frame comprises a mounting hole, wherein a temperature sensor is mounted about a central portion of the core frame, wherein at least one of the plurality of upper brackets comprises a second inserting hole, wherein a cable of the temperature sensor is inserted into a cable inserting hole, wherein the working coil is inserted into a third inserting hole and the core frame, and wherein the working coil is withdrawn from the core frame and inserted into a fourth inserting hole.

18. The electric range of claim 17, wherein the core frame comprises an open hole about an edge portion of the core frame, and wherein the open hole faces the at least one of the plurality of air gaps.

19. The electric range of claim 16, wherein the guide line comprises a plurality of guide lines, each of the plurality of guide lines being spaced apart from one another in a circumferential direction of the core frame.
