

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396677
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Xu; Qiliang et al.

Portable electronic device having an integrated bio-sensor

Abstract

An electronic device includes a translucent layer that forms a portion of an exterior of the electronic device, an opaque material positioned on the translucent layer that defines micro-perforations, and a processing unit operable to determine information about a user via the translucent layer. The processing unit may be operable to determine the information by transmitting optical energy through a first set of the micro-perforations into a body part of the user, receiving a reflected portion of the optical energy from the body part of the user through a second set of the micro-perforations, and analyzing the reflected portion of the optical energy.

Inventors:	Xu; Qiliang (Livermore, CA), Huizar; Richard G. (Sunnyvale, CA)
Applicant:	Apple Inc. (Cupertino, CA)
Family ID:	1000008780402
Assignee:	Apple Inc. (Cupertino, CA)
Appl. No.:	17/461335
Filed:	August 30, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20210386363 A1	Dec. 16, 2021

Related U.S. Application Data

continuation parent-doc US 15942499 20180331 US 11109797 child-doc US 17461335
us-provisional-application US 62554140 20170905

Publication Classification

Int. Cl.: **A61B5/024** (20060101); **A61B5/00** (20060101); **A61B5/0205** (20060101); **A61B5/1455** (20060101); **G06F1/16** (20060101); **G06F1/3231** (20190101); **G06F1/3287** (20190101); A61B5/021 (20060101); A61B5/026 (20060101); A61B5/08 (20060101); A61B5/145 (20060101)

U.S. Cl.:

CPC **A61B5/443** (20130101); **A61B5/0059** (20130101); **A61B5/0205** (20130101); **A61B5/14551** (20130101); **A61B5/6898** (20130101); **G06F1/1616** (20130101); **G06F1/1637** (20130101); **G06F1/1662** (20130101); **G06F1/1684** (20130101); **G06F1/169** (20130101); **G06F1/3231** (20130101); **G06F1/3287** (20130101); A61B5/021 (20130101); A61B5/024 (20130101); A61B5/02427 (20130101); A61B5/026 (20130101); A61B5/0816 (20130101); A61B5/14542 (20130101); A61B2560/0462 (20130101); A61B2562/0238 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6115621	12/1999	Chin	N/A	N/A
6343223	12/2001	Chin et al.	N/A	N/A
6927844	12/2004	Higuchi et al.	N/A	N/A
7822469	12/2009	Lo	N/A	N/A
7890153	12/2010	Hoarau	N/A	N/A
7978332	12/2010	Wadman	N/A	N/A
8005624	12/2010	Starr	N/A	N/A
8731618	12/2013	Jarvis et al.	N/A	N/A
8761853	12/2013	Thaveeprungsriporn et al.	N/A	N/A
8780300	12/2013	Niioka et al.	N/A	N/A
8912480	12/2013	Pope et al.	N/A	N/A
8954135	12/2014	Yuen et al.	N/A	N/A
8994662	12/2014	Nakamura	N/A	N/A
9060700	12/2014	Cho et al.	N/A	N/A
9314197	12/2015	Eisen et al.	N/A	N/A
9531422	12/2015	Jang et al.	N/A	N/A
9603521	12/2016	Cho et al.	N/A	N/A
9620312	12/2016	Ely et al.	N/A	N/A
9622694	12/2016	Mao	N/A	N/A
9717425	12/2016	Kiani	N/A	N/A
10098577	12/2017	Besko	N/A	N/A
10132478	12/2017	Vasylyev	N/A	N/A
10376191	12/2018	Poeze	N/A	N/A
10436425	12/2018	Vasylyev	N/A	N/A
10537271	12/2019	Mao	N/A	N/A
10656714	12/2019	Ligtenberg	N/A	N/A

10758179	12/2019	Bruekers et al.	N/A	N/A
10830421	12/2019	Vasylyev	N/A	N/A
10871828	12/2019	Ligtenberg	N/A	N/A
2003/0036685	12/2002	Goodman	N/A	N/A
2010/0004518	12/2009	Vo et al.	N/A	N/A
2010/0004519	12/2009	Lamego	N/A	N/A
2010/0010326	12/2009	Dalvi	N/A	N/A
2010/0056880	12/2009	Cho	600/509	A61B 5/01
2011/0280042	12/2010	Pance	N/A	N/A
2013/0006074	12/2012	Pologe	N/A	N/A
2013/0060109	12/2012	Besko	N/A	N/A
2013/0063972	12/2012	Pance	N/A	N/A
2013/0169541	12/2012	Cabos et al.	N/A	N/A
2013/0261407	12/2012	Koyama et al.	N/A	N/A
2013/0317370	12/2012	Dalvi	N/A	N/A
2014/0066783	12/2013	Kiani	N/A	N/A
2014/0135612	12/2013	Yuen	600/407	A61B 5/6838
2014/0183342	12/2013	Shedletsky	250/215	H10K 50/828
2015/0342528	12/2014	Sudo et al.	N/A	N/A
2016/0022184	12/2015	Besko	N/A	N/A
2016/0061726	12/2015	Ness et al.	N/A	N/A
2016/0070339	12/2015	Crawford et al.	N/A	N/A
2016/0378071	12/2015	Rothkopf	N/A	N/A
2017/0254518	12/2016	Vasylyev	N/A	N/A
2017/0325698	12/2016	Allec	N/A	N/A
2018/0217668	12/2017	Ligtenberg	N/A	N/A
2018/0217669	12/2017	Ligtenberg	N/A	N/A
2018/0218859	12/2017	Ligtenberg	N/A	N/A
2019/0069835	12/2018	Xu et al.	N/A	N/A
2019/0142287	12/2018	Boscke	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1493255	12/2003	CN	N/A
101427125	12/2008	CN	N/A
101605495	12/2008	CN	N/A
102026575	12/2010	CN	N/A
102967362	12/2012	CN	N/A
103153172	12/2012	CN	N/A
103228205	12/2012	CN	N/A
103919536	12/2013	CN	N/A
104755020	12/2014	CN	N/A
105380634	12/2015	CN	N/A
105534513	12/2015	CN	N/A
105813554	12/2015	CN	N/A
2005122339	12/2004	JP	N/A
WO 99/039630	12/1998	WO	N/A
WO 15/200386	12/2014	WO	N/A

WO 16/040392	12/2015	WO	N/A
WO 16/066888	12/2015	WO	N/A
WO 16/079379	12/2015	WO	N/A
WO 16/166414	12/2015	WO	N/A
WO 16/176218	12/2015	WO	N/A
WO 17/023373	12/2016	WO	N/A

Primary Examiner: Bloch; Michael R

Attorney, Agent or Firm: Brownstein Hyatt Farber Schreck, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 15/942,499, filed Mar. 31, 2018, which is a nonprovisional patent application of and claims the benefit of U.S. Provisional Patent Application No. 62/554,140, filed Sep. 5, 2017, and titled “Portable Electronic Device Having an Integrated Bio-Sensor,” the disclosures of which are hereby incorporated herein by reference in their entirety.

FIELD

(1) The described embodiments generally relate to electronic devices and, more particularly, to determining a health metric or physiological condition using a bio-sensor that is integrated with the electronic device.

BACKGROUND

(2) Portable electronic devices, including notebook computers, tablet computers, and mobile phones, have become common and useful devices. Many traditional portable electronic devices are configured to receive input using a keyboard or similar input device. However, few, if any, traditional notebook computers include sophisticated sensors or sensing techniques to monitor the user.

(3) The present disclosure is directed to systems and techniques for integrating a bio-sensor into a surface of a portable electronic device.

SUMMARY

(4) The present disclosure relates to body sensing via translucent layers with opaque layers. The electronic device includes an opaque layer positioned on a translucent layer that defines micro-perforations. A light source transmits light or other optical energy through the micro-perforations into a body part of a user. A light receiver receives the light that is reflected back from the body part of the user through the micro-perforations. Information about the user's body is determined from the light that is reflected back.

(5) In some embodiments, a portable electronic device including an upper enclosure; a display positioned within the upper enclosure; a lower enclosure pivotally coupled to the upper enclosure and including a translucent layer defining an external surface and an opaque layer coupled to the translucent layer and defining an array of micro-perforations; a keyboard positioned within the lower enclosure; a bio-sensor positioned within the lower enclosure below the array of micro-perforations and including a light source operable to transmit light through the array of micro-perforations into a body part of a user and a light receiver operable to receive reflected light from the body part of the user; and a processing unit, communicably coupled to the light receiver and operable to determine a health metric based on the reflected light.

(6) In various examples, the bio-sensor is positioned along a side of the keyboard and the body part is a palm of a hand of the user. In numerous examples, the light source is a green LED, the bio-

sensor is configured to detect blood perfusion in the body part of the user and the health metric is at least one of a heart rate, a respiration rate, a blood oxygenation level, a blood volume estimate, or a blood pressure. In some examples, the light source is an infrared LED and the bio-sensor is configured to detect water content of the body part of the user.

(7) In numerous examples, the array of micro-perforations are configured to obscure the light source and the light receiver when the bio-sensor is not in operation. In some examples, each micro-perforation of the array of micro-perforations is approximately 30-70 microns in diameter and is spaced approximately 80-500 microns apart from an adjacent micro-perforation.

(8) In various examples, the translucent layer is at least one of glass or plastic and the opaque layer includes a layer of ink deposited on an internal surface of the translucent layer that is opposite to the external surface.

(9) In various embodiments, an electronic device includes a translucent layer that forms a portion of an exterior surface of the electronic device, an opaque material positioned along an interior surface of the translucent layer that defines an array of micro-perforations, a light source positioned below the translucent layer and configured to transmit light through the array of micro-perforations, a light receiver positioned below the translucent layer proximate to the light source and configured to detect reflected light from a body part and a processing unit operable to determine bio-information based on the reflected light detected by the light receiver.

(10) In some examples, the light source transmits the light through a first set of micro-perforations of the array of micro-perforations, the light receiver receives the reflected light through a second set of micro-perforations of the array of micro-perforations, the first set of micro-perforations extends along a first angle with respect to the exterior surface, and the second set of micro-perforations extends along a second angle with respect to the exterior surface that is different from the first angle. In such examples, the first set of micro-perforations may be angled toward the second set of micro-perforations.

(11) In numerous examples, the light source transmits the light through a first set of micro-perforations of the array of micro-perforations, the light receiver receives the reflected light through a second set of micro-perforations of the array of micro-perforations, and the first set of micro-perforations is configured to direct the light along a non-perpendicular angle with respect to the exterior surface. In various examples, the light source transmits the light through a first set of micro-perforations of the array of micro-perforations, the light receiver receives the reflected light through a second set of micro-perforations of the array of micro-perforations, and the second set of micro-perforations is configured to receive light substantially aligned with a non-perpendicular angle with respect to the exterior surface and block light that is not substantially aligned with the non-perpendicular angle.

(12) In some examples, the body part absorbs a portion of the light. The portion of the light absorbed by the body part may depend on a tissue density of the body part.

(13) In numerous embodiments, a method of sensing a physiological condition includes while operating a bio-sensor in a first mode, detecting a proximity of a body part of a user with respect to an exterior surface of a translucent layer by producing a first light emission through the translucent layer; when the body part is proximate to the exterior surface of the translucent layer, operating the bio-sensor in a second mode by producing a second light emission through the translucent layer; and determining the physiological condition by analyzing a portion of the second light emission reflected from the body part.

(14) In some examples, the first light emission of the first mode includes a non-visible light emission and the second light emission of the second mode includes a visible light emission. In various examples, an opaque layer is positioned along the translucent layer and defines an array of micro-perforations, the first and second light emissions are transmitted through the array of micro-perforations, and the opaque layer obscures the bio-sensor when the bio-sensor is operating in the first mode. In numerous examples, the bio-sensor uses power at a first rate while operating in the

first mode, the bio-sensor uses power at a second rate while operating in the second mode, and the second rate is greater than the first rate.

(15) In various examples, determining the physiological condition includes determining at least one of: a heart rate, a respiration rate, a blood oxygenation level, a blood volume estimate, or a blood pressure. In some examples, determining the physiological condition includes determining a photoplethysmogram for the user.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The disclosure will be readily understood by the following detailed description in conjunction with the accompanying drawings, wherein like reference numerals designate like structural elements.

(2) FIG. 1A depicts an example electronic device having an integrated bio-sensor.

(3) FIG. 1B depicts the example electronic device of FIG. 2 while the user is using a keyboard.

(4) FIG. 2 depicts a detail view of a sensing area of the electronic device.

(5) FIG. 3 depicts an alternative implementation of FIG. 2 where the opaque layer defines a micro-perforated transmission region and a micro-perforated receiving region.

(6) FIG. 4 depicts a cross-sectional view of the sensing area, taken along section A-A of FIG. 1A.

(7) FIG. 5 depicts a cross-sectional view of another embodiment of the sensing area taken along section A-A including micro-perforations that are angled transverse to a sensing surface.

(8) FIG. 6 depicts an optical schematic of a bio-sensor integrated with an electronic device.

(9) FIG. 7A depicts an example electronic device that is operable to transition from a low power state to an operating state upon detecting a user.

(10) FIG. 7B depicts the example electronic device of FIG. 7A after detection of the user and transition from the low power state to the operating state.

(11) FIG. 8 depicts an example electronic device that is operable to illuminate a keyboard and the trackpad upon detecting a user.

(12) FIG. 9 depicts an example electronic device that is operable to detect and display health information about a user.

(13) FIG. 10 depicts a flow chart illustrating an example process for sensing a physiological condition or health metric.

DETAILED DESCRIPTION

(14) Reference will now be made in detail to representative embodiments illustrated in the accompanying drawings. It should be understood that the following descriptions are not intended to limit the embodiments to one preferred embodiment. To the contrary, it is intended to cover alternatives, modifications, and equivalents as can be included within the spirit and scope of the described embodiments as defined by the appended claims.

(15) The description that follows includes sample systems, apparatuses, methods, and computer program products that embody various elements of the present disclosure. However, it should be understood that the described disclosure may be practiced in a variety of forms in addition to those described herein.

(16) The following disclosure relates to a bio-sensor that is integrated with an electronic device. In particular, the bio-sensor may be integrated into an enclosure of a notebook computer allowing the bio-sensor to measure a condition of the user while the device is in use. For example, the bio-sensor may be positioned adjacent to the keyboard along a region that corresponds to a location where a portion of the user's hand contacts the enclosure (e.g., the user's palm). As described herein, the enclosure may include a translucent layer or sheet that forms at least a portion of the exterior of the device. An opaque layer may be formed along an interior surface of the transparent

layer and may define an array of micro-perforations that are able to transmit light from the sensor but also obscure the bio-sensor from the user when it is not in operation.

(17) In some embodiments, the bio-sensor is configured to produce a light emission that is transmitted through the micro-perforations defined in the opaque layer. In an example mode of operation, the bio-sensor may be used to determine a health metric or a physiological condition by detecting the light that is reflected off the body part of a user (e.g., the palm of a user's hand). In another example mode of operation, the bio-sensor may be used to detect a proximity of the user's hand with respect to the device. In response to the user's hand being detected as proximate to the bio-sensor, the device may be configured to change operation of the bio-sensor, alter the operational state of the device, or perform some other function.

(18) The bio-sensor may include a variety of different light sources that transmit the light and/or a variety of different light receivers that receive the light. For example, the light may be transmitted by a light emitting diode (LED), a micro-LED, an organic light emitting diode (OLED), or other type of light source. The light source may be configured to emit a visible light emission (e.g., green or red) or a non-visible light emission (e.g., infrared or ultraviolet). The light may be received by a photodiode, photo-sensor, or other of light receiver.

(19) In some cases, a portion of the exterior of the device enclosure is defined by a translucent layer or substrate. For example, the upper surface of a notebook enclosure may be defined by the translucent layer, which may include one or more sheets of translucent material. The translucent layer may be formed of any translucent layer or translucent material including, for example, glass, sapphire, plastic, and so on. An opaque layer may be formed or positioned along an interior surface of the translucent layer to mask or visually obscure internal components of the device. The opaque layer may be any opaque layer or opaque material, such as paint, ink, and so on. The opaque layer may reduce or prevent the visibility of the bio-sensor components from the outside of the enclosure while allowing light to pass through the micro-perforations to perform the sensing operations. The opaque layer may also help direct the light along a particular direction to assist with sensing and/or optical noise reduction.

(20) The micro-perforations may be formed with a variety of different dimensions. The diameter or size of each perforation and the may be sufficiently small that the opaque layer blocks or obscures the visibility internal components and may also not be visually distinguishable from a portion of the opaque layer not having micro-perforations. At the same time, the diameter or size of each perforation may be sufficiently large to allow sensor light to pass to enable operation of the bio-sensor. The spacing or arrangement of the micro-perforations may also be adapted to achieve this functionality. For example, the micro-perforations may be approximately 30-70 microns across and may be spaced at least approximately 80-500 microns apart. In some implementations, the micro-perforations may be angled transverse with respect to the translucent layer. The angle of micro-perforations may determine a transmission direction or a receiving direction of the light passing through the translucent layer.

(21) The above transmission and receiving of light through the micro-perforations defined in the opaque layer on the translucent layer may be used to implement a variety of different sensors in an electronic device. Examples of such sensors include, but are not limited to, bio-sensors (e.g., health sensors, photoplethysmography (PPG) sensors), ambient light sensors, proximity sensors, infrared distance sensors, and so on. In some implementations, the electronic device may a single sensor to perform different sensing functions. For example, the device may be configured to operate the sensor in a first mode to detect the proximity of the user with respect to the device and to operate the same sensor in another mode to sense a physiological condition or determine a health metric associated with the user. In one example, the sensor may be used to adjust power levels of the electronic device (e.g., to switch an input and/or output component from a low power state to an active state) when the sensor detects that a user has moved into a position to use the electronic device. The sensor may also be used to illuminate an input device when the sensor detects that a

user has moved into a position to use the input component. The same sensor may be operated in a different, bio-sensing mode to detect health information about a user (e.g., determine a heart rate for the user, a photoplethysmogram for the user, and so on). A variety of different configurations and uses are possible and contemplated without departing from the scope of the present disclosure. (22) As described herein, the translucent (e.g., light transmissible) layer may be formed from one or more translucent materials including, for example, glass, ceramic, plastic, or a combination thereof. As used herein, the term translucent or translucent layer may be used to refer to a material or layer that allows the passage of light and does not require that the material or layer be transparent, clear, or otherwise free from features that scatter or absorb some amount of light. As used herein, the term translucent may generally refer to a material or layer that is optically transparent, partially, transparent, or otherwise able to transmit light.

(23) These and other embodiments are discussed below with reference to FIGS. **1-10**. However, those skilled in the art will readily appreciate that the detailed description given herein with respect to these Figures is for explanatory purposes only and should not be construed as limiting.

(24) FIG. **1A** depicts an example electronic device **100** that includes a bio-sensor. In particular, the electronic device **100** includes a bio-sensor or other type of sensor that is operable to sense a user through a translucent layer **102**. The translucent layer **102** may define an exterior surface of the device and area **101** along the exterior surface may correspond to the location of the bio-sensor that is positioned within the lower enclosure **108**. The bio-sensor may be configured to transmit light or other optical energy through micro-perforations defined in an opaque layer on the translucent layer **102** and receive a portion of the light back through the micro-perforations reflected back from the body part of a user.

(25) FIG. **1B** illustrates a body part of the user **110** (e.g., a user's hand) in a position associated with the use of the device **100**. In particular, the body part of the user **110** is positioned such that at least a portion (e.g., the user's palm) is contacting the lower enclosure **108** along the area **101**. As described in more detail below with respect to FIG. **6**, the bio-sensor may be configured to measure a property or condition of the body part of the user **110**, which may be used to determine a physiological condition or health metric. In accordance with some embodiments, the bio-sensor may also be operated in a proximity sensor mode to detect the presence or absence of the body part of the user **110**.

(26) As shown in FIGS. **1A** and **1B**, the electronic device **100** includes an upper enclosure **109**, a display **107** positioned within the upper enclosure **109**, a lower enclosure **108** pivotally coupled to the upper enclosure via a hinge **106**. The lower enclosure **108** may include the translucent layer **102** defining an exterior surface of the device **100**. An opaque layer may be positioned along an interior surface of the translucent layer **102** and define an array of micro-perforations (which are described in detail below with respect to FIG. **2**). A bio-sensor may be positioned within the lower enclosure **108**. The micro-perforations may obfuscate and/or otherwise hide the bio-sensor from view.

(27) The bio-sensor may include an optical energy source, such as a light source, operable to transmit light through the micro-perforations into the body part of the user **110**. The bio-sensor may also include an optical energy receiver, such as a light receiver, operable to receive reflected light from the body part of the user **110**. The electronic device may further include a processing unit, communicably coupled to the light receiver and operable to determine a physiological condition (i.e., information about the body part of the user **110**) based on the reflected light.

(28) As shown in FIGS. **1A** and **1B**, a keyboard **104** and trackpad **103** may be positioned within the lower enclosure **108**. The keyboard **104** may include an electromechanical keyboard, virtual keyboard, or other type of keyboard component/device configured to receive keystrokes from the user. The trackpad **103** may be an electromechanical trackpad, an electronic trackpad, virtual trackpad, or other touch-sensitive device configured to receive touch and/or force input from the user. The bio-sensor may be positioned below (e.g., adjacent) the keyboard **104** and along a side of the trackpad **103**. As stated previously, the location of the bio-sensor may correspond to a predicted

location of the user's palm during a normal or predicted typing position.

(29) In various implementations, the transmission and receiving of light through the micro-perforations may be used to implement a variety of different sensors or sensing modes for the electronic device **100**. In various examples, these sensors or sensing modes include, but are not limited to, health sensors, ambient light sensors, proximity sensors, infrared distance sensors, PPG sensors, and so on. The electronic device **100** may use one or more of these sensors or sensing modes in a variety of different ways.

(30) In one example, the electronic device **100** may transmit and receive light through the micro-perforations to implement a proximity sensor. The proximity sensor may detect that the body part of the user **110** is proximate to the area **101** when a portion of transmitted light is reflected and received. To the contrary, if the body part of the user **110** is not sufficiently close to the area **101**, the body part of the user **110** may not receive and/or reflect any portion of the transmitted light. If a portion of transmitted light is not reflected and received, the electronic device may determine that the body part of the user **110** is not proximate to the area **101**. In some implementations, a distance from the area **101** to the body part of the user **110** may be determined based on the amount of time between transmission and receiving of the light, indicating the amount of time taken by the light to travel from the area **101** to the body part of the user **110** and back again.

(31) As shown in FIG. 1A, the area **101** of the translucent layer **102** corresponding to the sensor may be positioned adjacent to input devices such as the trackpad **103** and/or the keyboard **104**. As such, when the user **110** is positioned to use the input devices, the proximity of the body part of the user **110** may be detected when the bio-sensor is operated as a proximity sensor or in a proximity-sensing mode. In some implementations, the electronic device **100** may be configured to use such a proximity sensor to determine to adjust power levels of the electronic device **100**. For example, the electronic device **100** may switch components, such as the trackpad **103**, the keyboard **104**, and/or a display **107**, in a low power state (such as a powered down state) in order to conserve power or battery life when the electronic device **100** is not in use. The electronic device **100** may determine that the electronic device **100** is not in use when the proximity detector has not detected the body part of the user **110** for a period of time, such as five minutes. When the proximity sensor detects the body part of the user **110** while the electronic device **100** is operating in the low power state, the electronic device may switch from the low power state to an active state. For example, the electronic device **100** may activate a component, such as the trackpad **103**, the keyboard **104**, and/or a display **107**. In another example implementation, the electronic device **100** may be configured with a light source operable to illuminate an input device, such as the trackpad **103** and/or the keyboard **104**. In order to conserve power or battery life, or to be less obtrusive, the electronic device **100** may illuminate the input device when the proximity sensor detects that the user's body part is in position to use the input device.

(32) By way of another example, the bio-sensor may transmit and receive light through the micro-perforations to measure a property or condition of the user **110** and used to determine a physiological condition or health metric. When light is transmitted into the body part of the user **110**, the body part of the user **110** may absorb a portion of the light. The portion of the light that is not absorbed by the body part of the user **110** may be reflected back. The portions of the light that are absorbed or reflected by the body part of the user **110** may be dependent on the tissue density (or other density) of portions of the body part of the user **110**. This may be used to measure, water content, perfusion, blood flow, and/or other health-related characteristics of the user **110**. The electronic device **100** may use the bio-sensor to determine a heart rate for the user **110**, a blood pressure for the user **110**, a blood perfusion in the user **110**, a water content of the user **110**, a blood oxygenation level of the user, a blood volume estimate for the user **110**, a respiration rate of the user **110**, a photoplethysmogram for the user **110**, and so on.

(33) As shown in FIGS. 1A and 1B, the area **101** of the translucent layer **102** corresponding to the sensor may be positioned adjacent to input devices such as the trackpad **103** and/or the keyboard

104. As such, when the user **110** is positioned to use the input devices, the body part of the user **110** may be positioned to be detected by the bio-sensor. The electronic device **100** may thus use the bio-sensor to discreetly monitor health information about the user **110** while the user is operating the electronic device **100** without forcing the user to specifically move into a position for monitoring. The electronic device **100** may continuously, periodically, and/or otherwise monitor the health information. The electronic device **100** may also communicate with one or more other electronic devices (such as an associated cellular telephone, wearable device, and so on) to monitor, process, store, and/or take various actions based on such health information.

(34) In some implementations, the bio-sensor may determine health information about the user **110** by transmitting and receiving multiple wavelengths of light. For example, the bio-sensor may transmit and receive green and red light. Different substances and/or colored materials may absorb light differently. For example, green, red, and/or infrared light may be absorbed differently by darker hair, tattoos, and so on. By determining health information by comparing multiple wavelengths of light that have been transmitted and reflected back by the body part of the user **110**, the electronic device **100** may determine more accurate health information than might be possible by using a single wavelength of light.

(35) In another example, the electronic device may utilize different sensors and/or different sensing modes having different wavelengths of light in different combinations. For example, the bio-sensor functioning as proximity sensor or in a proximity-sensing mode may use infrared light or another non-visible light source. When the bio-sensor is functioning as health sensor or in a health-sensing mode, the bio-sensor may use light in the visible spectrum. To prevent the light in the visible spectrum from being noticed by the user **110**, the electronic device **100** may first operate the bio-sensor in a proximity-sensing mode to detect the body part of the user **110** as the infrared light may not be visually discernible to the user. Once the electronic device **100** determines that the bio-sensor is covered by the body part of the user **110**, the electronic device **100** may then cause the bio-sensor to operate in a health-sensing mode using visible light.

(36) Further, in various examples, an electronic device may operate the bio-sensor in a proximity-sensing mode to guide the user **110** to an optimal position for operating the bio-sensor in a health-sensing mode. For example, health information such as heart rate or blood pressure may be most accurately detected optically from the palm of the hand. As such, the electronic device **100** may determine where the user's hand is with respect to the health sensor and may provide output to the user **110** to direct the user **110** to move his hand until it is in an optimal position for operating the bio-sensor in a health-sensing mode.

(37) In still other examples, the electronic device **100** may operate the bio-sensor as an ambient light sensor or in an ambient light-sensing mode. When operating in an ambient light-sensing mode, the bio-sensor may be configured to detect ambient (e.g., sunlight or visible light) to determine an ambient light level of an environment in which the electronic device **100** is present. The electronic device **100** may also use the ambient light-sensing mode to determine proximity of the user, as the ambient light sensor may not receive ambient light if blocked by the body part of the user **110**.

(38) Although a single sensor is described above as corresponding to the area **101** of the translucent layer **102**, it is understood that this is an example. In various implementations, the electronic device **100** may include any number of sensors that correspond to any number of different areas of the translucent layer **102**. Various configurations are possible and contemplated. For example, the area **101** is illustrated as being positioned to the right of the trackpad **103** in FIG. 1A, as shown. In some implementations, a second sensor may correspond to an additional area of the translucent layer **102** that is positioned to the left of the trackpad to mirror the area **101**.

(39) As illustrated in FIGS. 1A and 1B, the electronic device **100** may be a laptop or notebook computing device. However, it is understood that this is an example and that in other implementations the electronic device **100** may be any electronic device, such as a desktop

computing device, a tablet computing device, a wearable device, a smart phone, a digital media player, a display, a printer, a kitchen appliance, a cellular telephone, a mobile computing device and so on.

(40) The electronic device **100** may include a variety of components, shown or not shown. For example, the electronic device **100** may include a variety of different components such as one or more communication components, one or more non-transitory storage media (which may take the form of, but is not limited to, a magnetic storage medium; optical storage medium; magneto-optical storage medium; read only memory; random access memory; erasable programmable memory; flash memory; or the like), and so on without departing from the scope of the present disclosure. Various configurations are possible and contemplated.

(41) FIG. 2 depicts a detail view of the area **101** of the translucent layer **102** corresponding to the sensor. The translucent layer **102** may be formed of any kind of translucent layer or translucent material, such as glass, plastic, and so on. An opaque layer **211** may be formed on the translucent layer **102**. The opaque layer **211** (which may be any opaque layer or opaque material, such as light reflective, absorptive, or blocking paint, ink, and so on) may define a array or set of micro-perforations **212**.

(42) The opaque layer **211** may be visible through the translucent layer and may visually obscure or block the viewing of internal components through the translucent layer **102**. The opaque layer **211** may also prevent light that does not pass through the micro-perforations **212** from being visible through the translucent layer. The opaque layer **211** may be positioned on an exterior portion of the translucent layer **102**, an interior portion of the translucent layer **102**, within the translucent layer **102**, and so on. In implementations where the opaque layer **211** is positioned along an interior surface of the translucent layer **102** and/or within the translucent layer **102**, the opaque layer **211** may be visible through the translucent layer **102**.

(43) The micro-perforations **212** may be configured in a variety of different arrangements and with a variety of different dimensions. (The size and spacing of the micro-perforations **212**, **312** depicted in FIGS. 2 and 3 may be exaggerated for purposes of illustration and may not be representative or drawn to scale.) The dimensions may be sufficiently small that the opaque layer **211** blocks internal components and/or light that does not passing through the micro-perforations **212** from being visible through the translucent layer **102** while light is still able to pass through the micro-perforations **212**. In one example configuration, the micro-perforations **212** may have a size or diameter of approximately 30-70 microns. While the micro-perforations **212** are depicted as being circular in shape, the shape may vary depending on the implementation and may include other shapes including, rectilinear shapes, curved shapes, slits, and so on. The micro-perforations **212** may be spaced approximately 80-500 microns apart. Stated another way, each micro-perforation may approximately 80-500 microns from an adjacent micro-perforation.

(44) FIG. 2 illustrates a uniform arrangement of the micro-perforations **212**. In some examples, the electronic device **100** may use the same micro-perforations **212** for transmitting and receiving light. In other implementations, the electronic device **100** may use a first set of the micro-perforations **212** for transmitting light and a second set of the micro-perforations **212** for receiving light. In still other implementations, transmitting and receiving areas of micro-perforations **212** may be separated

(45) For example, FIG. 3 depicts an alternative implementation of the area **301** of the translucent layer **302** corresponding to the sensor of FIG. 2 where the opaque layer **311** defines a micro-perforation transmission region **320** and a micro-perforation receiving region **321**. In this implementation, a first set of the micro-perforations **312** defined in the micro-perforation transmission region **320** may be used for transmitting light and a second set of the micro-perforations **312** defined in the micro-perforation receiving region **321** may be used for receiving light. Further, the opaque layer **311** may also include a separation region **322** between the micro-perforation transmission region **320** and the micro-perforation receiving region **321** that does not

define micro-perforations **312**.

(46) FIG. **4** depicts a cross-sectional view of the area **101** of the translucent layer **102** corresponding to the sensor, taken along line A-A of FIG. **1A**. In this implementation, a bio-sensor may include an optical energy source, such as a light source **414** (such as an LED, an OLED, an incandescent light source, and/or other light source), configured to transmit light or other optical energy through the translucent layer **102** via one or more of the micro-perforations **212**. Similarly, the bio-sensor may include an optical energy receiver, such as a light receiver **415** (such as a photodiode and/or other image or light sensor), configured to receive light through the translucent layer **102** via one or more of the micro-perforations **212**. The light source **414** may transmit the light through the translucent layer **102** via one or more of the micro-perforations **212** into a body part of a user. Similarly, the light receiver **415** may receive light through the translucent layer **102** via one or more of the micro-perforations **212**, such as a portion of the light transmitted by the light source **414** after it is reflected back by the body part of the user.

(47) The light source **414** and the light receiver **415** may be connected to a processing unit **416** and/or other processor or controller via one or more electrical connections, such as a substrate **417** which may be a printed circuit board or similar component that provides structural support to the light source **414** and the light receiver **415**. The processing unit **416** may control light transmission by the light source **414**, light receiving by the light receiver **415**, determination of information about the body of the user based on light received by the light receiver **415**, and so on.

(48) Thus, as shown, the electronic device **100** may include a translucent layer **102** defining an external surface, an opaque layer **211** coupled to the translucent layer **102** and defining an array of micro-perforations **212**, and a bio-sensor positioned below the array of micro-perforations **212**. The bio-sensor may include a light source **414** operable to transmit light through the array of micro-perforations **212** into a body part of a user and a light receiver **415** operable to receive reflected light from the body part of the user. Further, the electronic device **100** may include a processing unit **416**, communicably coupled to the light receiver **415** and operable to determine a health metric based on the reflected light.

(49) Further as shown, the electronic device **100** may include a translucent layer **102** that forms a portion of an exterior surface of the electronic device **100**, an opaque material **211** positioned along an interior surface of the translucent layer **102** that defines an array of micro-perforations **212**, a light source **414** positioned below the translucent layer **102** and configured to transmit light through the array of micro-perforations **212**, and a light receiver **415** positioned below the translucent layer **102** proximate to the light source **414** and configured to detect reflected light from a body part. The electronic device **100** may also include a processing unit **416** operable to determine bio-information based on the reflected light detected by the light receiver **415**.

(50) FIG. **4** illustrates the micro-perforations **212** as angled orthogonal or perpendicular to the translucent layer **102**. In various implementations, the micro-perforations **212** may be arranged along a non-perpendicular angle to direct transmission and/or receiving of light.

(51) For example, FIG. **5** depicts an alternative implementation of FIG. **4** where the micro-perforations **512** are arranged along a non-perpendicular angle with respect to an exterior surface of the translucent layer **502**. The angle of the micro-perforations **512** may determine a transmission direction and/or a receive direction of the light or other optical energy passing through the translucent layer **502**.

(52) As shown in FIG. **5**, the micro-perforations **512A** associated with the light source **514** are angled differently than the micro-perforations **512B** associated with the light receiver **515**. Specifically, the micro-perforations **512A** extend along a first angle with respect to the exterior surface, which is a mirror of the micro-perforations **512B** that extend along a second angle with respect to the exterior surface. Stated another way, the micro-perforations **512A** associated with the light source **514** are angled transverse to the translucent layer **502** (and/or the substrate **517**) and toward the micro-perforations **512B** associated with the light receiver **515**, and vice versa. Thus,

the micro-perforations **512A** associated with the light source **514** may direct the light or light emission along the non-perpendicular angle shown. Similarly, the micro-perforations **512B** associated with the light receiver **515** may be configured to receive light substantially aligned with a non-perpendicular angle with respect to the exterior surface and block light that is not substantially aligned with the non-perpendicular angle. This may improve receiving and reflection of the light by a body part of the user and/or receiving of light reflected by the body part of the user.

(53) Thus, as shown, an electronic device may include a translucent layer **502** defining an external surface, an opaque layer **511** coupled to the translucent layer **502** and defining an array of micro-perforations **512A**, **512B**, and a bio-sensor positioned below the array of micro-perforations **512A**, **512B**. The bio-sensor may include a light source **514** operable to transmit light through the array of micro-perforations **512A** into a body part of a user and a light receiver **515** operable to receive reflected light from the body part of the user. Further, the electronic device **100** may include a processing unit **516**, communicably coupled to the light receiver **515** and operable to determine a health metric based on the reflected light.

(54) FIG. **6** depicts a simplified process of detecting information about a body **610** using optical energy **618**, **619** (such as light). An optical energy source, such as a light source **614**, may transmit optical energy **618** through a translucent layer **602** into a body **610**. The body **610** may absorb a portion of the optical energy **618**. The portion of the optical energy **618** not absorbed by the body **610** may be reflected **619** back to an optical energy receiver, such as a light receiver **615**, through the translucent layer **602**. The portions of the optical energy **618** that are absorbed or reflected **619** by the body **610** may be dependent on the tissue density (or other density) of portions of the body **610** and may be used to measure blood flow and/or other health-related characteristics of the body **610**.

(55) In various implementations, a bio-sensor may utilize this process of detecting physiological information (i.e., health-related information, physiological condition, or other information about a body **610**) to calculate a health metric or other health-related information. For example, physiological information may include, but is not limited to, the physiological conditions of heart rate, respiration rate, blood oxygenation level, blood volume estimate, blood pressure, and so on. Such a sensor may be implemented in the electronic device **100** of FIGS. **1A-1B**.

(56) As one example, an electronic device may include an array of light sources **614** and a detector or other light receiver **615** that are configured to function as an optical sensor or sensors. In one example, an optical sensor or sensors may be implemented as a pairing of one or more light sources **614** and the light receiver **615**. In one example implementation, the light receiver **615** may be configured to collect light and convert the collected light into an electrical sensor signal that corresponds to the amount of light incident on a surface of the light receiver **615**. In one embodiment, the light receiver **615** may be a photodetector, such as a photodiode. In other embodiments, the light receiver **615** may include a phototube, photosensor, or other light-sensitive device.

(57) In some cases, the one or more bio-sensors may operate as a PPG sensor or sensors. In some instances, a PPG sensor is configured to measure light and produce a sensor signal that can be used to estimate changes in the volume of a part of a user's body. In general, as light from the one or more light sources **614** passes through the user's skin and into the underlying tissue, some light is reflected, some is scattered, and some light is absorbed, depending on what the light encounters. The light that is received by the light receiver **615** may be used to generate a sensor signal, which may be used to estimate or compute a health metric or other physiological phenomena.

(58) The light sources **614** may operate at the same light wavelength range, or the light sources **614** can operate at different light wavelength ranges. In one example, two light sources may be used rather than the one light source **614** shown. A first of the two light sources may transmit light in the visible wavelength range while a second of the two light sources may emit light in the infrared

wavelength range. In some cases, a modulation pattern or sequence may be used to turn the light sources on and off and sample or sense the reflected light. In another example, three light sources may be used rather than the one light source **614** shown. The first of the three light sources in this example may include, for example, a green LED, which may be adapted for detecting blood perfusion in the body of the wearer. The second of the three light sources in this example may include, for example, an infrared LED, which may be adapted to detect changes in water content or other properties of the body. The third of the three light sources in this example may be a similar type or different types of LED element, depending on the sensing configuration.

(59) The bio-sensor or sensors (e.g., PPG) may be used to compute various health metrics or physiological conditions, including, without limitation, a heart rate, a respiration rate, blood oxygenation level, a blood volume estimate, blood pressure, or a combination thereof. In some instances, blood may absorb light more than surrounding tissue, so less reflected light will be sensed by the light receiver **615** of the PPG sensor when more blood is present. The user's blood volume increases and decreases with each heartbeat. Thus, in some cases, a PPG sensor may be configured to detect changes in blood volume based on the reflected light, and one or more physiological conditions or parameters of the user may be determined by analyzing the reflected light. Example physiological conditions include, but are not limited to, heart rate, respiration rate, blood hydration, oxygen saturation, blood pressure, perfusion, and others.

(60) While an example number of light sources **614** and/or light receivers **615** have been described, the number of light sources **614** and/or light receivers **615** may vary in different embodiments. For example, another embodiment may use more than one light receiver **615**. Another embodiment may also use fewer or more light sources **614**. In particular, in one example, the light receiver **615** may be shared between multiple light sources **614**. In one alternative embodiment, two light receivers **615** may be paired with two corresponding light sources **614** to form two bio-sensors. The two bio-sensors (light source **614**/light receiver **615** pairs) may be operated in tandem and used to improve the reliability of the sensing operation. For example, output of the two light receivers **615** may be used to detect a pulse wave of fluid (e.g., blood) as it passes beneath the respective light receivers **615**. Having two bio-sensor readings taken at different locations along the pulse wave may allow the device to compensate for noise created by, for example, movement of the user, stray light, and other effects.

(61) In some implementations, one or more of the light sources **614** and the light receiver **615** may also be used for optical data transfer with a base or other device. For example, the light receiver **615** may be configured to detect light produced by an external mating device, which may be interpreted or translated into a digital signal. Similarly, one or more of the light sources **614** may be configured to transmit light that may be interpreted or translated into a digital signal by an external device.

(62) FIGS. 7A-7B depict an example electronic device **700** that is operable to transition from a low power state to an operating state upon detecting a user **710**. As illustrated in FIG. 7A, a low power state may be a state where a display **707** is powered off. Powering off the display **707** may conserve power that would be wasted if the user **710** was not using the electronic device **700**.

(63) When the electronic device **700** is in the low power state, the electronic device **700** may detect a body part of the user **710** using a bio-sensor operating as a proximity detector or in a proximity-sensing mode within an area **701** of a translucent layer **702**. In response, the electronic device **700** may transition from the low power state to the operating state. As a result, the electronic device **700** may power on the display **707**, as illustrated in FIG. 7B.

(64) The electronic device **700** may operate in the low power state when the electronic device **700** has been inactive for a period of time. The inactive period of time may be configurable and may include a time ranging from less than a minute to 30 minutes or longer. The electronic device **700** may determine the electronic device **700** is not in use when the sensor does not detect the body part of a user **710**. When the electronic device **700** is in the operating state and determines the electronic

device **700** is not in use, the electronic device **700** may power off the display **707**, as illustrated in FIG. **7A**.

(65) FIG. **8** depicts an example electronic device **800** that is operable to illuminate a keyboard **804** upon detecting a user **810**. This may allow the user **810** to better see the keyboard **804**, use the electronic device in poorly lit or unlit conditions, and so on. In this example, the electronic device **800** is operable to detect a body part of the user **810** using the bio-sensor operating as a proximity and/or ambient light sensor or in a proximity- or ambient light-sensing mode. The bio-sensor may be configured to detect the proximity of the user or an ambient light condition over an area of a translucent layer **802** covered by the body part of the user **810**. Upon such a detection, the electronic device **800** may illuminate keyboard **804** and the trackpad **803**. As illumination **823** may not be needed when not in use and may be disturbing, such as by illuminating a dark room where the user **810** may be attempting to sleep, this configuration may prevent keyboard **804** illumination **823** when the user **810** does not desire the keyboard **804** illuminated.

(66) FIG. **9** depicts an example electronic device **900** that is operable to detect and display health information about a user **910**. In this example, the electronic device **900** is operable to determine a heart rate for the user **910** using a health or other bio-sensor corresponding to an area of a translucent layer **902** covered by a body part of a user **910**. The electronic device **900** may then display the determined heart rate for the user **910** on a display **907**. In some implementations, the bio-sensor may be used to determine a health metric or physiological condition of the user **910**, while the user **910** is typing or otherwise operating the device **900**.

(67) Additionally, the electronic device **900** may be able to record the heart rate of the user **910**. In this way, the heart rate may be monitored over time. The user's heart rate over time may be compared with the heart rate of other users and/or various other statistical information. For example, the user's heart rate over time may be compared to heart rate data indicating health problems, such as hypertension. The electronic device **900** may display such information, graphically or otherwise, to indicate changes in the user's health, steps the user **910** may take to improve the user's health, comparisons to other people of a similar age and/or other background to indicate the user's relative health, and so on.

(68) In other implementations, the electronic device **900** may monitor the user's heart rate over time to determine satisfaction or frustration levels. For example, a user's heart rate may increase when the user **910** is frustrated. When the electronic device **900** detects the user's heart rate has increased, the electronic device **900** may determine that the user **910** is frustrated and offer help tips regarding an application the user **910** is currently executing on the electronic device **900**. Various configurations are possible and contemplated.

(69) FIG. **10** depicts a flow chart illustrating an example method **1000** process for sensing a physiological condition. The example method **1000** may be performed by a device like the example electronic devices **100**, **700**, **800**, **900** of FIGS. **1A-1B** and **7A-9**.

(70) At **1010**, a bio-sensor of a device operates in a first mode. The first mode may be a proximity-sensing mode. As part of operating in the first mode, at **1020**, the bio-sensor produces a first light emission or other optical energy through micro-perforations defined in an opaque layer on a translucent layer into a body part of a user. At **1030**, the bio-sensor determines whether or not reflected first light from the body part of the user is received through the micro-perforations in the opaque layer on the translucent layer. If the bio-sensor determines reflected first light from the body part of the user is received, this indicates the body part is proximate. As such, the flow proceeds to **1040**. Otherwise, the flow returns to **1010** and the bio-sensor continues operating in the first mode.

(71) At **1040**, after the bio-sensor may be used to determine that the body part is proximate, the bio-sensor may switch to a second mode. The second mode may be a PPG sensing mode. As part of operating in the second mode, at **1050**, the bio-sensor may produce a second light emission or other optical energy through the micro-perforations into the body part. At **1060**, the bio-sensor receives

the second light reflected from the body part through the micro-perforations.

(72) At **1070**, the bio-sensor is used to determine a health metric, physiological condition, bio-information, or other information, using the reflected second light. The flow then returns to **1010** after the bio-sensor switches back to the first mode at **1080**.

(73) The bio-sensor may switch between the first and second modes for a variety of reasons. For example, the first and second types of light may be different types of light. In some implementations, the first light may be infrared light and the second light may be visible light (such as red colored light, green colored light, a combination thereof, and so on). As such, the bio-sensor may operate in the first mode using infrared light until the body part is detected because infrared light may not be visible to users. Once the bio-sensor is covered by the body part such that the second light would not be visible, the bio-sensor may switch to the second mode.

(74) By way of another example, the second mode may consume power at a second rate that is greater than a first rate of the first mode. In various implementations, transmission of the second light may consume more power than transmission of the first light. Thus, the bio-sensor may conserve power by operating in the first mode until the body part is detected so that power is not unnecessarily wasted by operating in the second mode when there is no body part from which to determine a physiological condition of a user.

(75) Although the example method **1000** is illustrated and described as including particular operations performed in a particular order, it is understood that this is an example. In various implementations, various orders of the same, similar, and/or different operations may be performed without departing from the scope of the present disclosure.

(76) For example, the example method **1000** describes transmitting first light in the first mode, second light in the second mode, and switching from the first mode to the second mode when the first light is received reflected back from a body part. However, in some implementations, the bio-sensor may transmit light in the second mode but not the first mode. In such implementations, the bio-sensor may use other information to determine when a body part is proximate. For example, the bio-sensor may monitor a capacitive sensor in the first mode. The capacitive sensor may provide an indication of a changed capacitance when the body part is proximate. When the bio-sensor receives such a signal, the bio-sensor may switch to the second mode and transmit light to determine the physiological condition. Various configurations are possible and contemplated without departing from the scope of the present disclosure.

(77) As described above and illustrated in the accompanying figures, the present disclosure relates to body sensing via translucent layers with opaque layers. An electronic device may optically detect information about a user's body by transmitting light or other optical energy through micro-perforations defined in an opaque layer on a translucent layer and determining what portion of the light is reflected back from the user's body through the micro-perforations. This may allow detection of a variety of different information about the user's body without visible sensors or sensor components. This sensing capability may be incorporated into the housing of an electronic device, such as the area of a laptop computing device around a keyboard and/or trackpad. Examples of sensors that may be implemented in this fashion include, but are not limited to, proximity sensors, infrared distance sensors, ambient light sensors, health sensors, and so on.

(78) In the present disclosure, the methods disclosed may be implemented as sets of instructions or software readable by a device. Further, it is understood that the specific order or hierarchy of steps in the methods disclosed are examples of sample approaches. In other embodiments, the specific order or hierarchy of steps in the method can be rearranged while remaining within the disclosed subject matter. The accompanying method claims present elements of the various steps in a sample order, and are not necessarily meant to be limited to the specific order or hierarchy presented.

(79) The described disclosure may be provided as a computer program product, or software, that may include a non-transitory machine-readable medium having stored thereon instructions, which may be used to program a computer system (or other electronic devices) to perform a process

according to the present disclosure. A non-transitory machine-readable medium includes any mechanism for storing information in a form (e.g., software, processing application) readable by a machine (e.g., a computer). The non-transitory machine-readable medium may take the form of, but is not limited to, a magnetic storage medium (e.g., floppy diskette, video cassette, and so on); optical storage medium (e.g., CD-ROM); magneto-optical storage medium; read only memory (ROM); random access memory (RAM); erasable programmable memory (e.g., EPROM and EEPROM); flash memory; and so on.

(80) The foregoing description, for purposes of explanation, used specific nomenclature to provide a thorough understanding of the described embodiments. However, it will be apparent to one skilled in the art that the specific details are not required in order to practice the described embodiments. Thus, the foregoing descriptions of the specific embodiments described herein are presented for purposes of illustration and description. They are not intended to be exhaustive or to limit the embodiments to the precise forms disclosed. It will be apparent to one of ordinary skill in the art that many modifications and variations are possible in view of the above teachings.

(81) For example, features implementing functions may also be physically located at various positions, including being distributed such that portions of functions are implemented at different physical locations. Also, as used herein, including in the claims, “or” as used in a list of items prefaced by “at least one of” indicates a disjunctive list such that, for example, a list of “at least one of A, B, or C” means A or B or C or AB or AC or BC or ABC (i.e., A and B and C). Further, the term “exemplary” does not mean that the described example is preferred or better than other examples.

Claims

1. An electronic device, comprising: an enclosure having, a first layer formed from a light-transmissive material and defining an exterior surface of the electronic device; and a second layer coupled to of the light-transmissive material of the first layer, the second layer formed from an opaque material and defining a set of micro-perforations; a keyboard coupled to the enclosure; a bio-sensor positioned along a bottom side of the keyboard and operable to, in a first mode, detect a hand of a user in a typing position with respect to the keyboard by emitting and receiving a first light through the first layer and through the set of micro-perforations of the second layer; in response to detecting the hand of the user in the typing position with respect to the keyboard, switch from the first mode to a second mode; in the second mode, emit and receive a second light through the first layer and through the set of micro-perforations of the second layer; and determine a physiological condition of the user by analyzing a portion of the second light reflected from the body part.
2. The electronic device of claim 1, wherein: the bio-sensor comprises, a non-visible light source; and a visible light source; the first light includes a non-visible light emission made by the non-visible light source; and the second light includes a visible light emission made by the visible light source.
3. The electronic device of claim 1, wherein: the bio-sensor operates in a low power state while operating in the first mode; and the bio-sensor switches to a higher power state before operating in the second mode.
4. The electronic device of claim 1, wherein: the electronic device is a laptop computing device; the enclosure is a lower enclosure of the laptop computing device; the lower enclosure is pivotally coupled to an upper enclosure; the upper enclosure includes a display; the bio-sensor is configured to operate in the first mode during at least first times when the display is active; and the bio-sensor is configured to operate in the second mode during at least second times when the display is active.
5. The electronic device of claim 1, wherein determining the physiological condition comprises determining at least one of: a heart rate, a respiration rate, a blood oxygenation level, a blood

volume estimate, or a blood pressure.

6. The electronic device of claim 1, wherein: the electronic device further comprises a trackpad positioned along the bottom side of the keyboard; and the bio-sensor is positioned along a lateral side of the trackpad.
