

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397677
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Lane; Cameron Thomas et al.

Power systems and controls for electric machines

Abstract

An electric machine and sitewide control system and method that use a trolley power system at a worksite is disclosed. The trolley power system allows electric machines at the worksite to draw power from the trolley power system to concurrently operate to perform tasks and recharge their batteries. This allows the batteries on electric machines to be smaller than they would otherwise be, since a fully charged battery is not needed when operational power can be drawn from the trolley power system. The trolley power system is segmented, such that if one segment is faulted, the other segments can operate to provide power to electric machines at the worksite. Additionally, a sitewide controller initiates operational changes, such as a change in speed, for the electric machines at the worksite to compensate for one or more faulted segments.

Inventors:	Lane; Cameron Thomas (Oro Valley, AZ), Strashny; Igor (Tucson, AZ)
Applicant:	Caterpillar Inc. (Peoria, IL)
Family ID:	1000008780848
Assignee:	Caterpillar Inc. (Peoria, IL)
Appl. No.:	17/804959
Filed:	June 01, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230391225 A1	Dec. 07, 2023

Publication Classification

Int. Cl.: B60L58/13 (20190101); G01R31/382 (20190101)

U.S. Cl.:

Field of Classification Search

CPC: B60L (58/13); B60L (2200/36); B60L (3/0023); B60L (50/53); G01R (31/382); G01R (19/2513); H01M (2220/20)

USPC: 320/132

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4707761	12/1986	Podobinski	327/91	H02H 3/087
8798803	12/2013	Bush	701/429	B60L 50/61
9811086	12/2016	Poeppel	N/A	G07C 5/0808
11161429	12/2020	Moriya et al.	N/A	N/A
2012/0136509	12/2011	Everett	701/2	G05D 1/0291
2013/0079959	12/2012	Swanson	701/19	B61C 17/12
2013/0144472	12/2012	Ruth	903/902	G05D 1/0278
2018/0118039	12/2017	Stockner	N/A	B60L 9/00
2018/0164814	12/2017	Poeppel	N/A	N/A
2018/0196106	12/2017	Sankavaram	N/A	N/A
2018/0287545	12/2017	Sieman	N/A	H02P 5/00
2020/0171966	12/2019	Steele	N/A	B60L 53/12

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2013200541	12/2013	AU	B60L 5/04
103072496	12/2012	CN	N/A
203032415	12/2012	CN	N/A
110208653	12/2018	CN	N/A
2004098822	12/2003	JP	N/A
2004359169	12/2003	JP	N/A
20210048619	12/2020	KR	N/A

OTHER PUBLICATIONS

G. M. Brown, B. J. Elbacher and W. G. Koellner, "Increased productivity with AC drives for mining excavators and haul trucks," Conference Record of the 2000 IEEE Industry Applications Conference. Thirty-Fifth IAS Annual Meeting and World Conference on Industrial Applications of Electrical Energy (Year: 2000). cited by examiner

Written Opinion and International Search Report for Int'l. Patent Appln. No.PCT/US2023/021804, mailed Aug. 23, 2023 (10 pgs). cited by applicant

Primary Examiner: Diao; M Baye

Attorney, Agent or Firm: Lee & Hayes

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates to providing power to a machine powered by electricity. More specifically, the present disclosure relates to fault-tolerant power systems to provide improved site-level uptime of electric machines.

BACKGROUND

(2) Machines, such as mining trucks, loaders, dozers, or other construction or mining equipment, are often powered by any variety of fuel (e.g., diesel, gasoline, etc.). Recently, there is interest in powering machines using electricity. These electric machines are used for building, construction, mining and other activities, such as at a worksite. For example, mining trucks are often used for hauling mined materials within mining sites. It is desirable to have a high uptime for these machines. As a result, a worksite, such as a mining site, may have a trolley power system to which electric machines may connect to power themselves and/or to charge their batteries. Such an arrangement has several advantages, including relatively high uptime of electric machines due to the electric machines not having to charge for long times at static charging stations. Additionally, such site arrangements may enable each of the electric machines to have smaller on-board batteries, since the electric machine is able to operate and charge itself while carrying out worksite tasks. This results in reduced weight of the electric machines, reduced cost of the electric machines, and/or improved reliability of the electric machines.

(3) While sitewide trolley power systems with electric machines that can be powered by such power systems present various advantages, such as environmental advantages, cost advantages, and productivity advantages, such a system may be particularly vulnerable to a single point failure of the trolley power distribution systems. In other words, a failure of the trolley power systems may result in sitewide failure in powering electric machines, which can cause considerable downtime and loss of revenue. It is, therefore, desirable to increase the reliability of trolley power distribution systems at a worksite.

(4) One mechanism for operating a single-track railway contact network is described in Chinese Patent No. 10,307,249 (hereinafter referred to as “the '249 reference”). The '249 reference describes a mechanism by which a faulted section of the contact network can be isolated. The '249 reference describes procedures to recover the faulted section of the contact network. However, the systems and methods described in the '249 reference does not pertain to the operation or control of an electric machine to enable continuous operation of the electric machine despite a fault in power delivery. Thus, the disclosure of the '249 reference does not describe how to operate electric machines at a worksite when there is a fault in power delivery via trolley power systems and how to size on-board batteries of electric machines.

(5) Examples of the present disclosure are directed toward overcoming one or more of the deficiencies noted above.

SUMMARY

(6) In an aspect of the present disclosure, a site controller includes one or more processors and one or more computer-readable media storing computer-executable instructions that, when executed by the one or more processors, cause the one or more processors to determine that a first segment of a plurality of segments of a trolley power system is faulted, determine that a first electric machine will approach the first segment, and determine, based at least in part on the first segment being faulted and the first electric machine approaching the first segment, that an operation of the first electric machine is to be changed. The instructions further cause the one or more processors to determine a value of a parameter associated with the operation that is to be changed; and send, to the first electric machine, the value of the parameter.

(7) In another aspect of the present disclosure, a method includes determining, by a site controller, that a first segment of a plurality of segments of a trolley power system is faulted and determining, by the site controller, that a first electric machine will approach the first segment. The method further includes determining, by the site controller and based at least in part on the first segment being faulted and the first electric machine approaching the first segment, that an operating speed of the first electric machine is to be reduced from an original speed to a new speed while the first electric machine is drawing power from a second segment and sending, by the site controller and to the first electric machine, a message indicating the new speed.

(8) In yet another aspect of the present disclosure, an electric machine, includes an antenna, a battery, and a controller configured to receive, from a site controller and via the antenna, a request for a state-of-charge (SOC) associated with the battery and determine the SOC. The controller is further configured to send, to the site controller and via the antenna, a message indicating the SOC, receive, from the site controller and via the antenna, a command to change speed of the electric machine from an original speed to a new speed, wherein the command is based at least in part on a segment of a trolley power system being rendered inoperable, and change, responsive to the command, the speed to the new speed.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a schematic illustration of an example worksite with an electric machine, in accordance with examples of the disclosure.

(2) FIG. 2 is a schematic illustration of the electric machine depicted in FIG. 1, according to examples of the disclosure.

(3) FIG. 3 is a flow diagram depicting an example method for communicating operational changes, responsive to a fault in the trolley power system, to the electric machine of FIG. 1, according to examples of the disclosure.

(4) FIG. 4 is a flow diagram depicting an example method for communicating a change in speed, responsive to a fault in the trolley power system, to the electric machine of FIG. 1, according to examples of the disclosure.

(5) FIG. 5 is a flow diagram depicting an example method for communicating a change in route, responsive to a fault in the trolley power system, to the electric machine of FIG. 1, according to examples of the disclosure.

(6) FIG. 6 is a flow diagram depicting an example method for receiving operational instruction and changing operations of the electric machine of FIG. 1, according to examples of the disclosure.

(7) FIG. 7 are charts illustrating the control of the electric machine of FIG. 1 when a fault in a segment of a trolley power system is encountered, according to examples of the disclosure.

(8) FIG. 8 is a block diagram of an example site controller that may modify operational parameters of the electric machine of FIG. 1, according to examples of the disclosure.

DETAILED DESCRIPTION

(9) Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts.

(10) FIG. 1 is a schematic illustration of an example worksite **100** with an electric machine **102**, in accordance with examples of the disclosure. The electric machine **102**, as depicted may travel on ground **104**, such as along paths on the worksite **100**. While the electric machine **102** may have a battery, as will be discussed in conjunction with FIG. 2 below, the electric machine **102** receives power from power facilities at the worksite **100**, such as a substation **106** or a plurality of substations **106**. The substations **106** may provide power from any suitable source, such as a commercial electric grid or from generation facilities (not shown) at the worksite **100**. It should be

understood that in some cases, the worksite **100** may include both electric machines **102**, as well as conventional machines (e.g., internal combustion engine machines) or any other type of machine (e.g., battery-only electric machines, hybrid machines, etc.).

(11) According to the disclosure herein, the electrical power from the substations **106** are provided to the electric machine **102** via one or more segments of a trolley power system **108(1)**, **108(2)** (hereinafter referred to in the singular as segment of the trolley power system **108** or segment **108** and in the plural as segments of the trolley power system **108** or segments **108**). Although two segments of the trolley power system **108** are shown here, it should be understood that there may be any number of segments of the trolley power system **108** at a worksite **100**. Each of the segments of the trolley power system **108** are electrically separate from each other, such that if one segment **108** is rendered inoperable, other segments **108** can still provide power to the electric machine **102**. Each of the segments **108** may be electrically connected to the same substation **106** or to separate substations **106**. Further still, some segments **108** may be electrically connected one substation **106**, while other segments **108** may be electrically connected to other substations **106**.

(12) The segments **108** may be configured to provide to the electric machine **102** any suitable type and/or magnitude of electrical power. In some cases, the segments **108** may provide alternating current (AC) power at any suitable frequency, voltage and current. In other cases, the segments **108** may provide direct current (DC) power at any suitable voltage and current. In one non-limiting example, the segments **108** may provide +1500 VDC and -1500 VDC to the electric machine **102**. These values are merely examples, and other electrical configurations for the segments **108** are available within the knowledge of those of ordinary skill in the art.

(13) Each of the segments of the trolley power system **108** may carry one or more power lines **110**, as held by one or more poles **112**. The power lines **110** may be constructed of any suitable conductor, such as cables of any suitable gauge, conductance, etc. Although the power lines **110** are depicted as not connected between the first segment **108(1)** and second segment **108(2)**, it should be understood that the power lines **110** may be physically connected between segments **108**, but electrically isolated between segments **108**. Such a configuration may entail having “dummy connectors” (not shown) between segments **108**, which are electrically isolated from one or both segments **108** between which they are disposed.

(14) The electric machine **102** includes a connector **114** that allows the electric machine **102** to be electrically and/or physically connected to a segment **108** and derive electrical power therefrom. As the electric machine **102** moves along the ground **104**, the connector **114** may receive power from a sequence of segments **108**. The connector **114** may be configured to capture and/or release the power lines **110** and receive power from those power lines **110**. In the case where the power lines **110** are discontinuous between segments, the connector **114** may be configured to release the power lines **110** of one segment **108** and capture the power lines **110** of the next segment **108**.

Alternatively, in the case of when the power lines **110** are continuous between segments **108**, such as via dummy connectors between segments **108**, the connector **114** may remain coupled to the power lines **110** between segments **108**, even if not drawing power while traversing portions of the dummy connectors.

(15) As depicted here, the power lines **110** of the segments of the trolley power system **108** are overhead. However, it should be understood that the power lines **110** may be provided in any suitable configuration, in accordance with the disclosure herein. For example, the power lines **110** may be provided as rigid rails that run along the side of paths on the worksite **100** or as cables that are on the ground **104**. Indeed, the power lines **110** may be in any suitable location relative to the electric machine **102** on the worksite **100**. Additionally, the connector **114** may be of any suitable configuration to accommodate any suitable configuration of the power lines **110**. For example, telescopic rods, spring-biased contactors, slot connectors, or the like may be used to make contact to any suitable configuration of power line **110** and conduct electrical power to the electric machine **102**. In some cases, where AC power is provided through the power lines **110**, the connectors may

even be inductively and/or capacitively coupled to the power lines **110**. Regardless of the exact type of power line **110** and/or connector **114**, the power delivery is partitioned into independent segments **108**, such that a fault in one segment **108** does not affect other segments **108**.

(16) The electric machine **102** may further be configured to communicate wirelessly, such as via antenna **116**. The antenna **116** allows the electric machine **102** to receive and/or send wireless signals **118** from/to a site control center **120** and/or a electronic device **122** having controller **124**. The controller **124**, or site controller **124**, may be configured to interact with one or more human operators **126**, such as via the electronic device **122** and/or the site control center **120**. The controller **124** may include any suitable combination of hardware, software, and/or firmware to provide the functionality discussed herein for managing the operations of electric machines **102**.

(17) The controller **124** is configured to receive information from one or more electric machines **102**, such as state-of-charge (SOC) values associated with the electric machines **102**. The controller **124** is further configured to generate task commands to send via the wireless signals **118** to one or more electric machines **102** at the worksite **100**. The controller **124** is further configured to send change in operation requests/commands to the electric machines **102** to effect a change in any variety of tasks being performed by the electric machines **102**. For example, the controller **124** is configured to request an electric machine **102** to change its speed or change its route within the worksite **100**. In some cases, the request to change operations of the electric machine **102** may automatically control the electric machine **102**, such as when the electric machine **102** is autonomously controlled. In other cases, the request to change operations of the electric machine **102** may be presented to a human operator of the electric machine **102**.

(18) The controller **124** may be controlled by the operator **126** (e.g., worksite manager, construction worker, miner, farmer, paver, etc.) via one or more human machine interface(s) (HMIs) of the electronic device **122**, in some cases. In other cases, the controller **124** may operate autonomously or semi-autonomously. The controller **124** may also be configured to provide worksite **100** level updates to the operator **126**, such as via the HMIs of the electronic device **122**. The human operator **126** may provide any variety of parameters, corresponding to desired operating characteristics of the electric machine **102**, such as current task, SOC, destination location, speed, etc. These parameters may be encoded by the controller **124** into a task request or command that is transmitted to the electric machines **102** via the wireless signal **118**.

(19) In some instances, the communications between the electronic device **122** having the controller **124** and the electric machines **102** may be via protocol based communications (e.g., direct Wi-Fi, Wi-Fi, the Internet, Bluetooth, etc.), and in other instances, the communications may be non-protocol-based communications (e.g., remote control). In examples of the disclosure, the worksite **100** with communications between one or more electronic devices **122** and one or more electric machines **102** may result in a worksite level network, such as a local area network (LAN) or a wide-area network (WAN). Although the electronic device **122** is depicted herein as a smartphone, it should be understood that the electronic device **122** may be any suitable type of electronic device. For example, the electronic device **122** may be a computer, a mobile device, a server, a tablet computer, a notebook computer, a handheld computer, a workstation, a desktop computer, a laptop, any variety of user equipment (UE), a network appliance, an e-reader, a wearable computer, a network node, a microcontroller, a smartphone, or another computing device. The controller **124** that operates on the electronic device **122** to enable it to control the operations of the electric machines **102**, such as with task and/or operation change requests or commands, may be pre-loaded on the electronic device **122** and/or downloaded to the electronic device **122** from any suitable location, such as a commercial application downloading website, a private corporate website, or the like.

(20) The controller **124** is further configured to identify when a segment of the trolley power system **108** is faulted or otherwise non-operational. In some cases, the controller **124** may receive a signal from any variety of sources to indicate that a particular segment **108** is not currently

supplying electrical power. For example, the segments of the trolley power system **108** themselves may include sensors **128** that can determine that the corresponding segment is not operational and wirelessly send a signal to the controller **124** indicating the same. In other cases, the substations **106** may indicate to the controller **124** particular segments **108** that may be not be operational. In yet other cases, the operator **126**, an operator of the electric machine **102**, and/or other site-level personnel may observe physical damage to one or more segments **108** and report the same to the controller **124**.

(21) According to examples of the disclosure, when the controller **124** identifies one or more segments **108** that are faulted, non-operational, or otherwise unable to deliver power to electric machines **102** at the worksite **100**, the controller **124** may determine changes to the operations of one or more electric machines **102** to minimize the impact of the non-operational segments **108**. The controller **124** further communicates these changes to the operation of the electric machines **102** to the respective electric machines **102**, such as via wireless signals **118**. The changes in the operations of each of the electric machines **102** may be to mitigate any disruption of the overall work being performed at the worksite **100**, such as by minimizing the downtime of each of the electric machines **102**. In some cases, the change in operations of an electric machine **102** may entail a change in speed, a change in route, a delay in performing a task, a change in the number of electric machines **102** deployed concurrently, or the like.

(22) It should be appreciated that electric machines **102** described herein may be large, heavy-duty machines that have limited range due to high amounts of energy required to power them, versus the limited space and weight available to store on-board batteries. As a result, a trolley line power system to transfer energy to the electric machines **102** while the electric machines **102** perform their allocated tasks provides power to both run the machine and charge the batteries, as disclosed herein. This results in several advantages, such as limiting the downtime of electric machines **102** at stationary charging stations and enabling electric machines **102** to have smaller and lighter on-board batteries. However, a dependence on trolley system-based charging at a sitewide level also presents potential risks, such as if the trolley charging system has a single point failure, then the whole sitewide operation is hampered or stopped until electric power is restored. Additionally, if there is a sitewide fault in the trolley power system, individual electric machines **102** must have sufficient on-board battery storage capacity to complete the rest of the task cycle or to travel it to a stationary charging station while not connected to the dynamic charging system, thereby obviating some of the advantages of having the sitewide trolley power systems. It should be understood that the disclosure herein, address and mitigate the risks associated with point failures in the dynamic trolley power systems. By segmenting the trolley power system into segments **108**, the overall risk of a single point failure is minimized. While one or some segments **108** are rendered inoperable, other segments **108** are still configured to provide power to electric machines **102** at the worksite **100** for work to continue. Through a chosen combination of variable electric machine speed capability, appropriate battery sizing, length of each segment **108**, and power capability of each segment **108** the worksite **100** can continue operation either at full or potentially reduced performance with one or more segments **108** unavailable, or otherwise non-operational.

(23) As disclosed herein, a single trolley power system can be electrically segmented such that if there is a failure in a single segment, that segment **108** is isolated. At that point, the electric machines **102** can still operate on the remaining operational segments of the trolley power system **108** to carry on sitewide work objectives. However, to compensate for one or more inoperable segments **108**, according to examples of the disclosure, electric machine **102** operations may be modified. For example, the controller **124** may modify electric machine **102** speeds and/or routes to compensate for any faulted segments **108**. The advantages of the systems and methods disclosed herein will be appreciated by those having ordinary skill in the art. In particular, the mechanisms disclosed herein allow for reduced battery sizing of on-board batteries of the electric machines **102**, resulting in reduced cost, reduced weight, greater reliability, better performance (e.g., greater power

dedicated to tasks relative to weight), etc. For example, on-board batteries of the electric machines **102** may be “right-sized” to allow the electric machines **102** to be able to traverse a single faulted segment of the trolley system **108**, with perhaps some additional safety margin. Additionally, risks are mitigated with a fault-tolerant and self-healing overall control mechanism, where tasks and operations are dynamically and/or automatically modified to compensate for any faulted segments **108**. This results in greater sitewide uptime and efficiency, greater deployment of capital resources, and greater return-on-capital (ROC) and return-on-investment (ROI) of worksite **100** machinery. (24) FIG. 2 is a schematic illustration of the electric machine **102** depicted in FIG. 1, according to examples of the disclosure. The electric machine **102**, although depicted as a mining truck type of machine, may be any suitable machine, such as any type of loader, dozer, dump truck, skid loader, excavator, backhoe, combine, crane, drilling equipment, trencher, tractor, any suitable stationary machine, any variety of generator, locomotive, marine engines, combinations thereof, or the like. The electric machine **102** is configured for propulsion using electricity, as received via the connector **114**.

(25) The electric machine **102** is illustrated as a mining truck, which is used, for example, for moving mined materials, heavy construction materials, and/or equipment, and/or for road construction, building construction, other mining, paving and/or construction applications. For example, the electric machine **102** is used in situations where materials, such as mineral ores, loose stone, gravel, soil, sand, concrete, and/or other materials of a worksite need to be transported over the ground **104** at the worksite **100**. As discussed herein, the electric machine **102** may also be in the form of a dozer, where the electric machine **102** is used to redistribute and/or move material on the ground **104**. Further still, the electric machine **102** may be in the form of a compaction machine that can traverse the ground **104** and impart vibrational forces to compact the ground **104**. Such a compaction machine includes drums, which may vibrate to impart energy to the ground **104** for compaction. For example, an electric machine is configured to compact freshly deposited asphalt and/or other materials disposed on and/or associated with the ground **104**, such as to build a road or parking lot. It should be understood that the electric machine **102** can be in the form of any other type of suitable construction, mining, farming, military, and/or transportation machine. In the interest of brevity, without individually discussing every type of construction and/or mining machine, it should be understood that the electric drive mechanisms, as described herein, are configured for use in a wide variety of electric machines **102**.

(26) As shown in FIG. 2, the electric machine **102** includes a frame **200** and wheels **202**. The wheels **202** are mechanically coupled to a drive train (not shown) to propel the electric machine **102**. When the wheels **202** of the electric machine **102** are caused to rotate, the electric machine **102** traverses the ground **104**. Although illustrated in FIG. 2 as having a hub with a rubber tire, in other examples, the wheels **202** may instead be in the form of drums, chain drives, combinations thereof, or the like.

(27) The frame **200** of the electric machine **102** is constructed from any suitable materials, such as iron, steel, aluminum, other metals, ceramics, plastics, the combination thereof, or the like. The frame **200** is of a unibody construction in some cases, and in other cases, is constructed by joining two or more separate body pieces. Parts of the frame **200** are joined by any suitable variety of mechanisms, including, for example, welding, bolts, screws, other fasteners, epoxy, combinations thereof, or the like.

(28) The electric machine **102** may include a hydraulic system **204** that move a dump box **206** or other moveable elements configured to move, lift, carry, and/or dump materials. The dump box **206** is used, for example, to pick up and carry dirt or mined ore from one location on the ground **104** to another location of the ground **104**. The dump box **206** is actuated by the hydraulic system **204**, or any other suitable mechanical system. In some cases, the hydraulic system **204** is powered by an electric motor (not shown), such as by powering hydraulic pump(s) (not shown) of the hydraulic system **204**. It should be noted that in other types of machines (e.g., machines other than a mining

truck) the hydraulic system **204** may be in a different configuration than the one shown herein, may be used to operate elements other than a dump box **206**, and/or may be omitted.

(29) With continued reference to FIG. **2**, the electric machine **102** also includes an operator station **208**. The operator station **208** is configured to seat an operator (not shown) therein. The operator seated in the operator station **208** interacts with various control interfaces and/or actuators within the operator station **208** to control movement of various components of the electric machine **102** and/or the overall movement of the electric machine **102** itself. Thus, control interfaces and/or actuators within the operator station **208** allow the control of the propulsion of the electric machine **102** by controlling operation of one or more motors **210**. A motor controller **212** may be controlled according to operator inputs received at the operator station **208**. In other cases, the motor controller **212** and other components of the electric machine may be controlled autonomously, such as by the controller **124** or other sitewide control system.

(30) The motors **210** are powered by a battery pack or battery **214**, with a battery controller **216**. The motors **210** may be of any suitable type, such as induction motors, permanent magnet motors, switched reluctance (SR) motors, combinations thereof, or the like. The motors **210** are of any suitable voltage, current, and/or power rating. The motors **210** when operating together are configured to propel the electric machine **102** as needed for tasks that are to be performed by the electric machine **102**. For example, the motors **210** may be rated for a range of about 500 volts to about 3000 volts. The motor controller **212** include one or more control electronics to control the operation of the motors **210**. In some cases, each motor **210** may be controlled by its own motor controller **212**. In other cases, all the motors of the electric machine **102** may be controlled by a single motor controller **212**. The motor controller **212** may further include one or more inverters or other circuitry to control the energizing of magnetic flux generating elements (e.g., coils) of the motors **210**. The motors **210** are mechanically coupled to a variety of drive train components, such as a drive shaft and/or axles or directly to the wheels **202** to rotate the wheels **202** and propel the electric machine **102**. The drivetrain includes any variety of other components including, but not limited to a gear reduction, a differential, connector(s), constant velocity (CV) joints, etc. Although not shown here, there may be one or more motors **210** that are not used for propulsion of the electric machine **102**, but rather to operate pumps and/or other auxiliary components, such as to operate the hydraulic systems **204**.

(31) According to examples of the disclosure, the power to energize the motors **210** is received from the battery **214**, the segments of the trolley power system **108**, or both the battery **214** and the segments **108**. In some cases, the motors **210** may operate solely from the segments of the power trolley system **108**. In other cases, the power received from the segments **108** to operate the motors **210** may be supplemented by power from the battery **214**. Additionally, in many cases, the motors **210** and other elements of the electric machine **102** may operate from the power received from the segments **108** while concurrently charging the battery **214** of the electric machine **102**.

(32) In some cases, when the electric machine **102** is operated with energy from the battery **214** only, the electric machine **102** may be operated in a derated mode. This derated mode may reduce the peak power consumed by the electric machine **102**, such that the peak power draw by the subcomponents (e.g., motors **210**, hydraulic systems **204**, etc.) do not exceed the power rating of the battery **214**. In this way, the electric machine **102** may prevent damaging and/or excessively depleting the battery **214** during its operation using energy only from the battery **214**. This derated mode may manifest in a reduced/limited speed, a reduced/limited force, or the like of actions performed by the electric machine **102**.

(33) The electric machine **102** may further optionally include a fuel tank **218** to store any variety of fuel, such as diesel, gasoline, or other hydrocarbon fuels. This fuel tank may be included only in the cases where the electrical machine **102** may have a supplementary power source, such as an internal combustion engine (not shown) or a fuel cell (not shown).

(34) The battery **214** may be of any suitable type and capacity. For example, the battery may be a

lithium ion battery, a lead-acid battery, an aluminum ion battery, a flow battery, a magnesium ion battery, a potassium ion battery, a sodium ion battery, a metal hydride battery, a nickel metal hydride battery, a cobalt metal hydride battery, a nickel-cadmium battery, a wet cell of any type, a dry cell of any type, a gel battery, combinations thereof, or the like. The battery **214** may be organized as a collection of electrochemical cells arranged to provide the voltage, current, and/or power requirements of the motors **210**. In some cases, the energy capacity of the battery **214** may be a threshold amount more than the energy required for the electric machine **102** to traverse a single segment **108** that may be inoperable. In other cases, the energy capacity of the battery **214** may be a threshold amount more than the energy required for the electric machine **102** to traverse two segments **108** that may be inoperable, or any other predetermined number of inoperable segments **108**. For example, if at a particular worksite **100**, each segment is approximately 1 kilometer (km) long, the battery **214** of the electric machine **102** may have sufficient capacity to propel the electric machine by 1.5 km.

(35) Indeed, the battery **214** capacity may be any suitable value relative to the energy needed to traverse a segment **108** on the worksite. For example, in some cases, the energy capacity of the battery **214** relative to the energy required by the corresponding electric machine **102** to traverse a typical single segment **108** at the worksite **100** may be in the range of about 1 to about 3. In other cases, the energy capacity of the battery **214** relative to the energy required by the corresponding electric machine **102** to traverse a typical single segment **108** at the worksite **100** may be in the range of about 1.1 to about 2.2. In still other cases, the energy capacity of the battery **214** relative to the energy required by the corresponding electric machine **102** to traverse a typical single segment **108** at the worksite **100** may be in the range of about 1.2 to about 1.7. These aforementioned ratios may generally be less than what would typically used for electric machines **102** that operate only from its on-board batteries, without the benefit of the trolley power system segments **108**. It should be understood that the aforementioned ratios are examples, and the disclosure contemplates battery **214** energy capacity ranges outside of the aforementioned ranges.

(36) The electric machine **102** may also include a regenerative braking system **222**, which allows the electric machine **102** to recapture some of its kinetic energy while braking, which would otherwise be wasted. The regenerative braking system **222**, when the electric machine is to slow down and/or stop, may apply a load to the wheels **202** that is further mechanically coupled to a generator or alternator. By this mechanism, the applied load of the regenerative braking system **222** opposes the torque of the wheels **202**, resulting in slowing down and/or stopping the electric machine **102**. At the same time, since the torque of the wheel drives an alternator/generator, the torque of the wheels and/or the kinetic energy of the electric machine **102** is at least partially transformed into electrical energy that is used to charge the battery **214**. In this way, instead of losing kinetic energy of the electric machine **102** to heat during braking, at least some of the kinetic energy of the electric machine **102** can be recouped and stored in the battery **214**.

(37) The electric machine **102** includes controller **220** that controls various aspects of the electric machine **102**. The controller **220** is configured to receive battery status (e.g., state-of-charge (SOC) or other charge related metrics) from the battery controller **216**, operator signal(s), such as an accelerator signal, based at least in part on the operator's interactions with one or more control interfaces and/or actuators of the electric machine **102**. In other cases, the controller **220** may receive control signals from a remote control system (e.g., controller **124**) by wireless signals **118**, received via an antenna **116**. The controller **220** uses the operator signal(s), regardless of whether they are received from an operator in the operator station **208** or from the controller **124**, to generate command signals to control various components of the electric machine **102**. For example, the controller **220** may control the motors **210** via the motor controller **212**, the hydraulic system **204**, and/or steering of the electric machine **102** via a steering controller **224**. It should be understood that the controller **220** may control any variety of other subsystems of the electric machine **102** that are not explicitly discussed here to provide the electric machine **102** with the

operational capability discussed herein.

(38) The controller **220**, according to example of this disclosure, may be configured to provide an indication of remaining energy to operate the electric machine **102** on an energy gauge **226**. The energy gauge **226**, according to examples of the disclosure, may be configured to display the amount of energy available to operate the electric machine **102** based at least in part on the amount of charge remaining in the battery **214**. In some cases, the energy gauge **226** may provide an indication of an estimated amount of time the electric machine **102** can be operated and/or an estimated amount of range the electric machine **102** has remaining. These estimates may be generated based on the amount of charge remaining in the battery **214**, the recent usage of energy by the electric machine **102**, and/or an estimate of the energy expended per unit time (e.g., power requirement) of a task in which the electric machine **102** is engaged. The energy gauge **226** may be configured to display, to an operator seated in the operator station **208**, the amount of energy, time, and/or range remaining for operating the electric machine **102**. Additionally or alternatively, the energy gauge **226** and/or the controller **220** and/or battery controller **216** may be configured to indicate, such as wirelessly via the antenna **116**, the amount of charge (e.g., SOC), energy, time, and/or range remaining for operating the electric machine **102** to a remote operating system (e.g., controller **124**).

(39) The controller **220** includes single or multiple microprocessors, field programmable gate arrays (FPGAs), digital signal processors (DSPs), and/or other components configured to control the electric machine **102**. Numerous commercially available microprocessors can be configured to perform the functions of the controller **220**. Various known circuits are operably connected to and/or otherwise associated with the controller **220** and/or the other circuitry of the electric machine **102**. Such circuits and/or circuit components include power supply circuitry, inverter circuitry, signal-conditioning circuitry, actuator driver circuitry, etc. The present disclosure, in any manner, is not restricted to the type of controller **220** or the positioning depicted of the controller **220** and/or the other components relative to the electric machine **102**. The controller **220** is configured to cooperate with the controller **124** to control the use of energy from the battery **214** in a manner that enhances the range of the electric machine **102** and/or advance sitewide objectives, particularly when there are one or more faulted segments **108**.

(40) The electric machine **102** further includes any number of other components within the operator station **208** and/or at one or more other locations on the frame **200**. These components include, for example, one or more of a location sensor (e.g., global positioning system (GPS)), an air conditioning system, a heating system, communications systems (e.g., radio, Wi-Fi connections), collision avoidance systems, sensors, cameras, etc. These systems are powered by any suitable mechanism, such as by using a direct current (DC) power supply powered by the battery **214**.

(41) It should be understood that the electric machine **102** as discussed herein, provides for control from a sitewide controller (e.g., controller **124**) via wireless or wired signaling. This control by the controller **124**, in cooperation with controller **220**, may provide instructions to a human operator in the operator station **208** of the electric machine **102** or automatically control the operations of the electric machine **102** via controller **220**. The change in operations (e.g., change in speed, change in route, or the like) of the electric machine **102** may be communicated by the controller **124** in response to one or more segments **108** at the worksite being rendered inoperable. For example, if a particular segment **108** on which the electric machine **102** is to use on its path is non-functioning, the controller **124** may reroute the electric machine **102** to avoid the faulted segment **108**. In other examples, the controller may cause the electric machine **102** to slow down (e.g., travel at half-speed) on segments **108** prior to and/or subsequent to the faulted segment **108** so that the electric machine **102** spends additional time drawing power from the functional segment **108** to charge its battery **214** more fully and operate from the energy stored in the battery **214** when traversing the path along the faulted segment **108**.

(42) It will be appreciated that the electric machine **102** is optimized to have smaller on-board

batteries due to the systems and methods as discussed herein, resulting in lower costs, improved reliability, and/or improved performance. At the same time, the electric machines **102**, as well as the overall worksite **100** is more robust to the ill effects of electrical failures of trolley systems, in accordance with the disclosure herein.

(43) FIG. **3** is a flow diagram depicting an example method **300** for communicating operational changes, responsive to a fault in a segment of the trolley power system **108**, to the electric machine **102** of FIG. **1**, according to examples of the disclosure. The processes of method **300** may be performed by the controller **124**, individually or in conjunction with the controller **220** and/or one or more other elements at worksite **100**. Method **300** allows the electric machine **102** to operate even when one or more segments **108** are non-operational at the worksite **100**.

(44) At block **302**, the controller **124** identifies information associated with any segments of the trolley power system **108** that are non-operational. In this sense, non-operational segments **108** are those segments **108** that are faulted and/or otherwise unable to deliver electrical power to the electric machines **102** at the worksite **100**. The controller **124** may identify if particular segment(s) **108** of all the segments **108** at a worksite **100** are non-operational by receiving communications from any variety of entities. In some cases, the controller **124** may receive a signal from any variety of sources to indicate that a particular segment **108** is not currently supplying electrical power.

(45) As one example, the segments **108** of the trolley power system **108** may report its operational status via sensors **128**. These sensors **128** may include voltmeters, ammeters, or any other suitable mechanism to determine whether electrical power is flowing through the power lines **110** of the segment **108**. The sensor **128** can determine whether the corresponding segment **108** is operational and wirelessly send a signal to the controller **124** indicating the operational status of the segment **108**. In some cases, the sensor **128** may periodically report operational status of the corresponding segment **108** to the controller **124**. In other cases, the sensor **128** may report, to the controller **124**, a change in operational status of the corresponding segment (e.g., a change from operational to non-operational).

(46) In other cases, the substations **106** may indicate to the controller **124** particular segments **108** that may be not be operational. The substations may recognize a fault in its own power delivery to one or more segments **108** and report the same to the controller **124**. In yet other cases, a human operator **126** may identify that a particular segment **108** or segments **108** are non-operational and log the same with the controller via the electronic device **122**. There may be other ways of the controller **124** identifying the segments **108** that are non-operational at the worksite **100**, according to examples of the disclosure, other than the mechanisms discussed here.

(47) At block **304**, the controller **124** determines one or more electric machines **102** that are to be affected by the non-operational segments of the trolley power system **108**. The controller **124** may assign each electric machine **102** at the worksite its current task, and therefore, the controller **124** will have information about the path that each of the electric machines will traverse on the ground **104** of the worksite **100**. Thus, the controller **124** can determine the electric machines **102** that will, or likely will, be affected by any non-operational segments **108** at the worksite **100**. The controller **124** can make an inventory of the electric machines **102** that are to be affected of any segment outages, and in some cases, the predicted time when the electric machine **102** is likely to be affected by the non-operational segments **108**.

(48) At block **306**, the controller **124** determines changes to the operation of each of the one or more electric machines **102** due to the non-operational segments of the trolley power system **108**. The controller **124** may determine any variety of changes to the operations of the electric machines **102** that are affected by outages of one or more segments **108**. These operational changes may be to mitigate any work stoppage at the worksite **100** due to the non-operational segments **108**. The operational changes may be based on a variety of factors, such as where particular electric machines **102** are currently located in the worksite **100**, if there are alternate routes that particular electric machines **102** may be rerouted to for completing its current and/or future tasks, the

topography of expected paths of particular electric machines **102**, etc. The operational changes of one or more electric machines **102** may entail changes in speed, changes in routes, instructions to halt its current operations, instructions to perform a different task that removes load from the non-operational segments **108**, etc. The controller **124** may be configured to determine different operational changes for different electric machines **102**. For example, the controller **124** may determine that some electric machines **102** may need to have a different operating speed, while other electric machines **102** may need to be rerouted, while yet other electric machines **102** may be temporarily idled and other non-electric machines may be deployed in their place.

(49) At block **308**, the controller **124** communicates the operation changes to each of the one or more electric machines **102** for which the operations are to be modified. The controller **124** may wirelessly and/or in a wired fashion transmit a message that includes parameters that are to be modified in the operation of the respective receiving electric machine **102**. For example, the controller **124** may transmit a message that instructs a particular electric machine to reduce its speed and provide a speed parameter that indicates that speed. In other cases, the controller **124** may transmit a message to another particular electric machine **102** to instruct that machine to traverse a different route, such as by sending parameters of destination coordinates and/or additional coordinates of waypoints.

(50) It should be noted that some of the operations of method **300** may be performed out of the order presented, with additional elements, and/or without some elements. Some of the operations of method **300** may further take place substantially concurrently and, therefore, may conclude in an order different from the order of operations shown above.

(51) It should be understood that the method **300** improves the robustness of worksite **100** operations, by allowing electric machines **102** to continue performing tasks, even when one or more segments **108** may not be providing electric power to the electric machines **102** at the worksite **100**. By coordinating changes to the operations of electric machines **102** responsive to fault(s) in power delivery, overall usable uptime of electric machines **102** is improved.

(52) FIG. **4** is a flow diagram depicting an example method **400** for communicating a change in speed, responsive to a fault in the trolley power system, to the electric machine of FIG. **1**, according to examples of the disclosure. The processes of method **400** may be performed by the controller **124**, individually or in conjunction with the controller **220** and/or one or more other elements at worksite **100**. Method **400** allows the electric machine **102** to operate at a different speed (e.g., a reduced speed), even when one or more segments **108** are non-operational at the worksite **100**.

(53) At block **402**, the controller **124** determines that a segment of the trolley power system **108** is non-operational. In this sense, a non-operational segment **108** is a segment **108** that is faulted and/or otherwise unable to deliver electrical power to the electric machines **102** at the worksite **100**. The controller **124** may identify if particular segment(s) **108** of all the segments **108** at a worksite **100** are non-operational by receiving communications from any variety of entities. In some cases, the controller **124** may receive a signal from any variety of sources, such as the sensors **128**, to indicate that a particular segment **108** is not currently supplying electrical power.

(54) At block **404**, the controller **124** identifies an electric machine **102** that is to approach the inoperable segment of the trolley power system **108**. The controller **124** identifies the electric machine **102** that is to approach the inoperable segment **108** based on the task(s) assigned to that electric machine **102** and the layout of the worksite **100**. Since the controller **124** had previously assigned tasks to the electric machine **102**, the controller will be able to determine whether the electric machine **102** is scheduled to operate using the faulted segment **108**. In some cases, the controller **124** may receive current location information about the electric machine **102**, such as GPS coordinates from the controller **220**, to ascertain whether the electric machine **102** will be approaching the inoperable segment **108**.

(55) At block **406**, the controller **124** determines the state-of-charge (SOC) of the battery **214** of the

electric machine **102**. This process may be optional, in some cases. The controller **220** and/or the battery controller **216** may determine and report the SOC to the controller **124**, such as via wireless signals **118**. The SOC may indicate the total amount of charge (e.g., coulombs of charge) of the battery **214** or charge as a percentage of the capacity of the battery **214**. In some cases, the SOC may be used to determine changes in the operating parameters of the electric machine **102**, but in other cases, the SOC may not be considered to determine changes in the operating parameters of the electric machine **102**, responsive to a fault in one or more segments **108**. In some cases, the controller **124** may also compare the current SOC level to the energy needs of the tasks assigned to the electric machine **102** in determining any changes to the operation of the electric machine **102**. For example, an electric machine **102** with a relatively high SOC may have a smaller change in its operating speed compared to another electric machine **102** with a relatively lower SOC when both the electric machines **102** are to complete similar types of tasks.

(56) At block **408**, the controller **124** determines, based at least in part on the SOC and the inoperable segment **108**, a change in speed to be implemented for the electric machine **102**. It should be noted that in some alternative cases, the SOC may not be considered in making the determination of the change in speed to be implemented for the electric machine **102**. The change in speed, such as a reduction in speed, for the electric machine **102** allows for the electric machine **102** to be connected to operational segment(s) **108** for a longer period of time, before the electric machine **102** comes to the inoperable segment **108**. This allows for the battery **214** of the electric machine **102** to be charged to a greater degree (e.g., greater SOC) before the electric machine **102** goes to the inoperable segment **108**. By charging up the battery **214** to a greater level, particularly a level that exceeds the change needed to traverse the inoperable segment **108**, the electric machine **102** is able to operate using its on-board battery **214** to traverse the ground **104** corresponding to the inoperable segment **108**, without having to draw power from the inoperable segment **108**.

(57) In some cases, the controller **124** may cause the electric machine **102** to slow down while connected to segments **108** prior to the segment(s) **108** that are inoperable. In other cases, the controller **124** may cause the electric machine **102** to slow down while connected to segments **108** after the segment(s) **108** that are inoperable. In yet other cases, the controller **124** may cause the electric machine **102** to slow down while connected to segments **108** both prior to and after the segment(s) **108** that are inoperable. As noted above, the battery **214** of the electric machine **102** and/or the SOC level thereon may be such that the electric machine **102** has sufficient charge to traverse the length of the inoperable segment(s) **108** even if a sufficient slowed-down operation prior to the inoperable segment(s) **108** is not possible.

(58) In some examples of the disclosure, the controller **124** may determine that the electric machine **102** ought to reduce its speed to a range between about 90% to about 10% of its original speed. In other cases, the controller **124** may determine that the electric machine **102** ought to reduce its speed to a range between about 70% to about 30%. In still other cases, the controller **124** may determine that the electric machine **102** ought to reduce its speed to a range between 40% and 60%.

(59) As an example, the controller **124** may determine that a particular electric machine **102** is to reduce its speed, responsive to an upcoming inoperable segment **108**, to 50% of its original speed. In this case, the electric machine **102** would spend twice as much time operating and charging its battery **214** on prior operable segments **108**, approximately resulting in twice as much or more charging from those segment(s) **108** prior to the inoperable segment **108**. For example, if a particular electric machine **102** in the form of a mining truck has a normal speed of 50 km/h, and it will be approaching an inoperable segment **108**, the controller **124** may determine that the electric machine **102** is to reduce its speed to 25 km/h (50% reduction). Correspondingly, if under the normal speed of operation, the battery **214** of the electric machine **102** would have an SOC of 27% by the time the electric machine **102** comes to the inoperable segment **108**, with the reduced speed implemented, the estimated SOC may be 60%, or so.

(60) As another example, the controller **124** may determine that a particular electric machine **102** is

to reduce its speed, responsive to an upcoming inoperable segment **108**, to 25% of its original speed. In this case, the electric machine **102** would spend four times as much time operating and charging its battery **214** on prior operable segments **108**, approximately resulting in quadruple or more charging from those segment(s) **108** prior to the inoperable segment **108**. For example, if a particular electric machine **102** in the form of a backhoe has a normal speed of 40 km/h, and it will be approaching an inoperable segment **108**, the controller **124** may determine that the electric machine **102** is to reduce its speed to 10 km/h (25% of original speed). Correspondingly, if under the normal speed of operation, the battery **214** of the electric machine **102** would have an SOC of 15% by the time the electric machine **102** comes to the inoperable segment **108**, with the reduced speed implemented, the estimated SOC may be 65%, or so.

(61) It should be understood that the amount of time spent on operable segments may not correspond linearly to the amount of charge (e.g., SOC) of a battery **214** of an electric machine **102**. This is because the battery **214** likely has some charge in it prior to dwelling on operable segments **108**. Additionally, the amount of energy and/or charge consumed may not scale linearly with speed. For example, operating at a lower speed may not result in the same percentage reduction of energy usage as the percentage reduction of the speed. This is because there are a variety of non-linear factors involved, such as static friction, dynamic friction, internal inefficiencies of motors **210**, limitations of on-board battery **214** charging rate capacity, etc. However, the controller **124** may, in some cases, have different speed-charge models and/or look-up tables that it can employ to estimate the charge benefits from speed reduction for any variety of corresponding types (e.g., mining trucks, dozers, etc.) of electric machines **102**.

(62) According to examples of the disclosure, the controller **124** may provide system-level (e.g., worksite **100** workflow) robustness when multiple segments **108** may be rendered inoperable. Thus, the controller **124** may provide different levels of speed adjustments and/or a combination of operational adjustments when more than one segment **108** may be inoperable. For example, if a particular electric machine **102** is approaching a single inoperable segment **108**, the controller may determine that that electric machine **102** is to reduce its speed by a first level. However, if the electric machine **102** is approaching two successive inoperable segments **108**, the controller **124** may determine that the electric machine **102** is to reduce its speed by a second level that is greater (i.e., lower operational speed) than the first level.

(63) At block **410**, the controller **124** communicates the request for the change in speed to the electric machine **102**. The controller **124** may wirelessly and/or in a wired fashion transmit a message that includes a speed parameter (e.g., speed level, percentage reduction from current speed, etc.) to which the electric machine **102** is to adjust its speed. For example, the controller **124** may transmit a message that instructs a particular electric machine to reduce its speed to 20 km/h and provide a speed parameter that indicates that speed. This message may be received by the controller **220** of the electric machine **102** and implemented in the case of an autonomously controlled electric machine **102** or displayed to an operator via one or more human-machine interfaces (HMI), in the case of a human operated electric machine **102**, to request the operator to reduce the speed of the electric machine **102** according to the instructions from the controller **124**.

(64) It should be noted that some of the operations of method **400** may be performed out of the order presented, with additional elements, and/or without some elements. Some of the operations of method **400** may further take place substantially concurrently and, therefore, may conclude in an order different from the order of operations shown above.

(65) FIG. 5 is a flow diagram depicting an example method for communicating a change in route, responsive to a fault in the trolley power system, to the electric machine of FIG. 1, according to examples of the disclosure. The processes of method **500** may be performed by the controller **124**, individually or in conjunction with the controller **220** and/or one or more other elements at worksite **100**. Method **500** allows the electric machine **102** to operate, such as by rerouting the electric machine **102**, even when one or more segments **108** are not operating at the worksite **100**.

(66) At block **502**, the controller **124** determines that a segment of the trolley power system **108** is inoperable. In this sense, an inoperable segment **108** is a segment **108** that is faulted and/or otherwise unable to deliver electrical power to the electric machines **102** at the worksite **100**. The controller **124** may identify if particular segment(s) **108** of all the segments **108** at a worksite **100** are inoperable by receiving communications from any variety of entities. In some cases, the controller **124** may receive a signal from any variety of sources, such as the sensors **128**, to indicate that a particular segment **108** is not currently supplying electrical power.

(67) At block **504**, the controller **124** identifies an electric machine **102** that is to approach the inoperable segment **108** of the trolley power system **108**. The controller **124** identifies the electric machine **102** that is to approach the inoperable segment **108** based on the task(s) assigned to that electric machine **102** and the layout of the worksite **100**. Since the controller **124** had previously assigned tasks to the electric machine **102**, the controller will be able to determine whether the electric machine **102** is scheduled to operate using the faulted segment **108**. In some cases, the controller **124** may receive current location information about the electric machine **102**, such as GPS coordinates from the controller **220**, to ascertain whether the electric machine **102** will be approaching the inoperable segment **108**.

(68) At block **506**, the controller **124** determines the state-of-charge (SOC) of the battery **214** of the electric machine **102**. This process may be optional, in some cases. The controller **220** and/or the battery controller **216** may determine and report the SOC to the controller **124**, such as via wireless signals **118**. The SOC may indicate the total amount of charge (e.g., coulombs of charge) of the battery **214** or charge as a percentage of the capacity of the battery **214**. In some cases, the SOC may be used to determine changes in the operating parameters of the electric machine **102**, but in other cases, the SOC may not be considered to determine changes in the operating parameters of the electric machine **102**, responsive to a fault in one or more segments **108**.

(69) At block **508**, the controller **124** determines, based at least in part on the SOC and the inoperable segment **108**, a new route for the electric machine **102**. It should be noted that in some alternative cases, the SOC may not be considered in making the determination of the change in route for the electric machine **102**. The change in route, such as an alternate route to avoid the inoperable segment **108**, for the electric machine **102** allows for the electric machine **102** to be connected to operational segment(s) **108** to perform its task(s). This allows for the battery **214** of the electric machine **102** to continue to be charged by avoiding the inoperable segment **108**. In alternative cases, the electric machine **102** may be sent to stationary chargers for charging. In some cases, non-electrically driven machines may be deployed in place of electric machines **102**, by the controller **124**, when one or more segments **108** are inoperable.

(70) At block **510**, the controller **124** communicates the request for the change in route to the electric machine **102**. The controller **124** may wirelessly and/or in a wired fashion transmit a route parameter (e.g., new destination, end coordinates, a heading, one or more waypoints, etc.) to which the electric machine **102** is to adjust its route. For example, the controller **124** may transmit a message that instructs the electric machine **102** to head to a new point at the worksite, indicated as a location coordinate. This message may be received by the controller **220** of the electric machine **102** and implemented in the case of an autonomously controlled electric machine **102** or displayed to an operator via one or more HMIs, in the case of a human operated electric machine **102**, to request the operator to reroute the electric machine **102** according to the instructions from the controller **124**.

(71) It should be noted that some of the operations of method **500** may be performed out of the order presented, with additional elements, and/or without some elements. Some of the operations of method **500** may further take place substantially concurrently and, therefore, may conclude in an order different from the order of operations shown above.

(72) FIG. **6** is a flow diagram depicting an example method **600** for receiving operational instruction and changing operations of the electric machine of FIG. **1**, according to examples of the

disclosure. The processes of method **600** may be performed by the controller **220**, individually or in conjunction with one or more other components of electric machine **102**. In general, the controller **220** receives instructions from the controller **124** and controls its electric machine **102** according to the instructions received from the controller **124**.

(73) At block **602**, the controller **220** receives, from the site controller **124**, a request for state of charge (SOC). This operation may be optional, as in some cases, change in operation of the electric machine **102** may not be based in part on the SOC. The controller **220** may receive the request for SOC wirelessly or in a wired fashion. The controller **220**, responsive to the request for SOC, may interact with the battery controller **216** to determine the SOC of the battery **214**.

(74) At block **604**, the controller **220** sends, to the site controller **124**, the SOC. The SOC level, either as a total amount of charge or as a percentage of the battery **214** capacity, may be sent to the controller **124** wirelessly or in a wired fashion. Again, this operation may be optional, since in some cases, the controller **124** may not consider the SOC of the battery **214** of the electric machine **102** in determining any operational changes for the electric machine **102**.

(75) At block **606**, the controller **220** receives, from the site controller **124**, a request for a change in operation. This request may be a message that instructs any variety of changes to the operation of the electric machine **102**, such as a change in speed, a change in rout, and/or to idle. The controller **220** may receive this message wirelessly or via wired channels from the controller **124**. The change in operations of the electric machine **102** may be instructed by the controller **124** based at least in part on one or more segments **108** at the worksite **100** being faulted, according to examples of the disclosure.

(76) At block **608**, the controller **220** implements the change in operation. In some cases, the controller **220** may display the requested change in operation to an operator in the operator station **208** via one or more HMIs. In other cases, the controller **220** may interact with one or more other controllers and/or systems of the electric machine **102**, such as the steering controller **224**, the hydraulic system **204**, etc., to implement the requested change(s) in operation of the electric machine **102**.

(77) It should be noted that some of the operations of method **600** may be performed out of the order presented, with additional elements, and/or without some elements. Some of the operations of method **600** may further take place substantially concurrently and, therefore, may conclude in an order different from the order of operations shown above.

(78) FIG. 7 are charts **700**, **710** illustrating the control of the electric machine of FIG. 1 when a fault in a segment of a trolley power system **108** is encountered, according to examples of the disclosure. Chart **700** depicts a situation where a segment **108** is rendered non-operational, but no change is made to the operation of an electric machine **102** approaching the non-operational segment **108**. As the electric machine **102** traverses a first segment of trolley power system **108**, the battery **214** charges according to curve **702**. However, this charging is during a normal operational speed, without taking into account that the subsequent segment **108** is faulted. Thus, the electric machine **102** does not slow down to replenish its battery **214** more completely, and as the curve **704** shows, when the electric machine **102** operates using its on-board battery **214**, it depletes the charge in its battery **214** while traversing the ground **104** corresponding to the non-operational segment **108**. In fact, because the electric machine could not traverse the entirety of the non-operational segment **108**, it could not reach a third operational segment **108**.

(79) In contrast to the chart **700**, the chart **710** demonstrates operation of the electric machine **102** according to the disclosure herein. The controller **124**, recognizing that the second segment cannot provide power to the electric machine **102** instructs the electric machine **102** to slow down, resulting the in the curve **712**. Due to the slower speed of the electric machine **102**, the curve **712** is steeper, as the electric machine **102** accumulates more charge in its battery **214** per unit distance while traversing the first segment **108**. Then, during the second segment **108**, which is inoperable, the electric machine **102** operates using its own on-board battery **214**. However, this time, because

the electric machine **102** attained a sufficient amount of charge its battery **214** while traversing the first segment **108**, according to examples of the disclosure, the electric machine **102** is able to traverse the second segment **108**, which is inoperable, as depicted in curve **714**. The electric machine **102** is, therefore able to make it to the third segment **108**, where the electric machine **102** can again charge its battery **214**, according to the curve **716**.

(80) As discussed herein, the controller **124**, by slowing down the electric machine **102** on operating segments **108**, can increase the charge to distance ratio, thereby increasing the end charge of the battery **214** when exiting the operating segment **108** relative to the scenario where the electric machine **102** is not slowed down. As a result of the additional charge in the battery **214**, the electric machine **102** is able to traverse faulted segments **108** without depleting its battery **214**. Thus, the disclosure herein, allows for more robust and fault-tolerant operations of electric machines **102** and further prevents electric machines **102** from being stranded, without power, while traversing faulted segments **108**.

(81) FIG. **8** is a block diagram of an example site controller **124** that may modify operational parameters of the electric machine of FIG. **1**, according to examples of the disclosure. The controller **124** includes one or more processor(s) **800**, one or more input/output (I/O) interface(s) **802**, one or more communication interface(s) **804**, one or more storage interface(s) **806**, and computer-readable media **810**. In examples, the processor(s), I/O interfaces **802**, communications interface(s) **804**, storage interface(s) **806**, and/or computer-readable memory **810** may be part of the electronic device **122**.

(82) In some implementations, the processors(s) **800** may include a central processing unit (CPU), a graphics processing unit (GPU), both CPU and GPU, a microprocessor, a digital signal processor or other processing units or components known in the art. Alternatively, or in addition, the functionally described herein can be performed, at least in part, by one or more hardware logic components. For example, and without limitation, illustrative types of hardware logic components that may be used include field-programmable gate arrays (FPGAs), application-specific integrated circuits (ASICs), application-specific standard products (ASSPs), system-on-a-chip systems (SOCs), complex programmable logic devices (CPLDs), etc. Additionally, each of the processor(s) **800** may possess its own local memory, which also may store program modules, program data, and/or one or more operating systems. The one or more processor(s) **800** may include one or more cores.

(83) The one or more input/output (I/O) interface(s) **802** may enable the controller **124** to detect interaction with a human operator **126**. For example, the operator **126** may provide task instructions to be executed by electric machines **102** at the worksite **100**. Thus, the I/O interface(s) **802** may include and/or enable the controller **124** to receive indications of what actions the electric machine **102** is to perform.

(84) The network interface(s) **804** may enable the controller **124** to communicate via the one or more network(s). The network interface(s) **804** may include a combination of hardware, software, and/or firmware and may include software drivers for enabling any variety of protocol-based communications, and any variety of wireline and/or wireless ports/antennas. For example, the network interface(s) **804** may comprise one or more of WiFi, cellular radio, a wireless (e.g., IEEE 802.1x-based) interface, a Bluetooth® interface, and the like. In some cases, if a remote control is used to control the electric machine **102**, one or more operator signals may be sent by the controller **124**.

(85) The storage interface(s) **806** may enable the processor(s) **800** to interface and exchange data with the computer-readable medium **810**, as well as any storage device(s) external to the controller **124**. The storage interface(s) **806** may further enable access to removable media.

(86) The computer-readable media **810** may include volatile and/or nonvolatile memory, removable and non-removable media implemented in any method or technology for storage of information, such as computer-readable instructions, data structures, program modules, or other data. Such

memory includes, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile discs (DVD) or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, RAID storage systems, or any other medium which can be used to store the desired information and which can be accessed by a computing device. The computer-readable media **810** may be implemented as computer-readable storage media (CRSM), which may be any available physical media accessible by the processor(s) **800** to execute instructions stored on the memory **810**. In one basic implementation, CRSM may include random access memory (RAM) and Flash memory. In other implementations, CRSM may include, but is not limited to, read-only memory (ROM), electrically erasable programmable read-only memory (EEPROM), or any other tangible medium which can be used to store the desired information, and which can be accessed by the processor(s) **800**. The computer-readable media **810** may have an operating system (OS) and/or a variety of suitable applications stored thereon. The OS, when executed by the processor(s) **800** may enable management of hardware and/or software resources of the controller **124**.

(87) Several components such as instruction, data stores, and so forth may be stored within the computer-readable media **810** and configured to execute on the processor(s) **802**. The computer readable media **810** may have stored thereon a site manager **812**, a segment manager **814**, a machine manager **816**, a task manager **818**, an operations manager **820**, and a communications manager **822**. It will be appreciated that each of the components **812**, **814**, **816**, **818**, **820**, **822** may have instructions stored thereon that when executed by the processor(s) **800** may enable various functions pertaining to operating the electric machine **102**, as described herein.

(88) The instructions stored in the site manager **812**, when executed by the processor(s) **800**, may configure the controller **124** to identify features of the worksite **100**, such as the locations, lengths, available power, etc. of the various segments of the trolley power system **108** deployed at the worksite **100**. The processor(s) **800** may also be configured to identify any topological features associated with the worksite **100**.

(89) The instructions stored in the segment manager **814**, when executed by the processor(s) **800**, may configure the controller **124** to identify the segments of the trolley power system **108** deployed at the worksite **100** and the operational status of those segments **108**. The processor(s) **800** may be configured to receive status updates associated with each of the segments **108** from any variety of sources, such as sensors **128** and/or substations **106**. The processor(s) **800** may be configured to identify when a particular segment **108** becomes faulted and when a faulted segment **108** is repaired and becomes operational.

(90) The instructions stored in the machine manager **816**, when executed by the processor(s) **800**, may configure the controller **124** to identify the locations, identities, and/or specifications of a variety of electric machines **102** deployed at the worksite **100**. The processor(s) **800** may also be configured to identify operating status associated with each of the electric machines **102**, such as a SOC of the batteries **214** of each of the electric machines **102**.

(91) The instructions stored in the task manager **818**, when executed by the processor(s) **800**, may configure the controller **124** to provide tasks to electric machines **102** at the worksite **100**. The tasks may be assigned based on overall goals at the worksite **100** and may take into account a variety of factors, such as machine availability, weather conditions, or the like.

(92) The instructions stored in the operations manager **820**, when executed by the processor(s) **800**, may configure the controller **124** to send updated parameters to change operations of one or more electric machines **102**. For example, the processor(s) **800** may determine and send, to an electric machine **102**, a speed parameter to update a prior speed of operation of that electric machine **102**. Similarly, the processor(s) **800** may determine and send parameters (e.g., destination, waypoints, etc.) associated with rerouting electric machines **102** deployed at the worksite **100**.

(93) The instructions stored in the communications manager **822**, when executed by the processor(s) **800**, may configure the controller **124** to communicate with the one or more electric

machines **102** at the worksite **100** by any suitable mechanisms, such as wired or wireless communications. The processor(s) **800** may be configured to receive status information from the electric machines **102**, such as state-of-charge (SOC) of their batteries **214**. The processor(s) **800** may also be configured to send requests for a change in operations to each of the electric machines **102**. For example, the processor(s) **800** may be able to transmit anew speed parameter to an electric machine **102** to cause that electric machine **102** to change its speed according to the speed parameter.

(94) The disclosure is described above with reference to block and flow diagrams of systems, methods, apparatuses, and/or computer program products according to the disclosure. It will be understood that one or more blocks of the block diagrams and flow diagrams, and combinations of blocks in the block diagrams and flow diagrams, respectively, can be implemented by computer-executable program instructions. Likewise, some blocks of the block diagrams and flow diagrams may not necessarily need to be performed in the order presented or may not necessarily need to be performed at all, according to some examples of the disclosure.

(95) Computer-executable program instructions may be loaded onto a general-purpose computer, a special-purpose computer, a processor, or other programmable data processing apparatus to produce a particular machine, such that the instructions that execute on the computer, processor, or other programmable data processing apparatus create means for implementing one or more functions specified in the flowchart block or blocks. These computer program instructions may also be stored in a computer-readable memory that can direct a computer or other programmable data processing apparatus to function in a particular manner, such that the instructions stored in the computer-readable memory produce an article of manufacture including instruction means that implement one or more functions specified in the flow diagram block or blocks. As an example, the disclosure may provide for a computer program product, comprising a computer usable medium having a computer readable program code or program instructions embodied therein, said computer readable program code adapted to be executed to implement one or more functions specified in the flow diagram block or blocks. The computer program instructions may also be loaded onto a computer or other programmable data processing apparatus to cause a series of operational elements or steps to be performed on the computer or other programmable apparatus to produce a computer-implemented process such that the instructions that execute on the computer or other programmable apparatus provide elements or steps for implementing the functions specified in the flow diagram block or blocks.

(96) It will be appreciated that each of the memories and data storage devices described herein can store data and information for subsequent retrieval. The memories and databases can be in communication with each other and/or other databases, such as a centralized database, or other types of data storage devices. When needed, data or information stored in a memory or database may be transmitted to a centralized database capable of receiving data, information, or data records from more than one database or other data storage devices. In other cases, the databases shown can be integrated or distributed into any number of databases or other data storage devices.

(97) Industrial Applicability

(98) The present disclosure describes systems and methods for providing risk-tolerant mechanisms for high electric machine usage at a worksite **100**. Electric machines **102** have on-board batteries **214** that traditionally need to be charged, such as at a stationary charging station. The charging of large batteries for large construction or farming equipment may take a relatively long time, particularly compared to refueling traditional diesel or gasoline powered machines. As a result, it is desirable to implement a trolley power system, where an electric machine **102** can dynamically draw power for its own operations and further to charge its on-board batteries **214**. The trolley power system, therefore, mitigates the need for charging downtime related to electrical machines **102**, resulting in greater deployment of machinery. This results in improved financial metrics related to capital expenditures, such as greater ROI and ROC, as well as greater productivity from

worksite **100** assets.

(99) In addition to worksite **100** efficiencies, a trolley power system introduces additional advantages with respect to the electric machines **102** themselves. Because the electric machines **102** can draw power while engaging in productive tasks, the on-board batteries of the electric machines **102** can be right-sized to smaller sizes. By having reduced size of the on-board batteries **214**, the electric machines **102** of this configuration have an additional advantage of reduced cost and weight and increased reliability compared to traditional electric machines.

(100) The trolley power system, however, may introduce reliability issues. For example, a single point failure may halt sitewide operations. However, the disclosure herein, provides a fault-tolerant system and method for powering electrical vehicles that is highly robust to single point failures within the trolley power systems. By dividing the trolley power system into segments **108**, single point failures in one segment can be isolated and other operational segments can be used to continue operations at the worksite **100**. Sitewide control can be used to modify the operations of electric machines **102** that may be affected by one or more segments **108** being rendered inoperable, but the sitewide activities can continue, mostly unhindered. This leads to improved levels of worker and capital efficiency, greater uptime and greater field usage of construction equipment, and greater efficiency of construction, mining, agriculture, and/or transportation projects.

(101) Although the systems and methods of electric machines **102** are discussed in the context of a mining trucks and other mining machinery, it should be appreciated that the systems and methods discussed herein may be applied to a wide array of machines and vehicles across a wide variety of industries, such as construction, mining, farming, transportation, military, combinations thereof, or the like. For example, the fault-tolerant mechanism disclosed herein may be applied to a compactor in the paving industry or a harvester in the farming industry.

(102) While aspects of the present disclosure have been particularly shown and described with reference to the examples above, it will be understood by those skilled in the art that various additional examples may be contemplated by the modification of the disclosed machines, systems and methods without departing from the spirit and scope of what is disclosed. Such examples should be understood to fall within the scope of the present disclosure as determined based upon the claims and any equivalents thereof.

(103) Recitation of ranges of values herein are merely intended to serve as a shorthand method of referring individually to each separate value falling within the range, unless otherwise indicated herein, and each separate value is incorporated into the specification as if it were individually recited herein. All methods described herein can be performed in any suitable order unless otherwise indicated herein.

Claims

1. A site controller, comprising: one or more processors; and one or more computer-readable media storing computer-executable instructions that, when executed by the one or more processors, cause the one or more processors to: determine that a first segment of a plurality of segments of a trolley power system is faulted; determine that a first electric machine will approach the first segment; determine, based at least in part on the first segment being faulted and the first electric machine approaching the first segment, that an operation of the first electric machine is to be changed; determine a value of a parameter associated with the operation that is to be changed; and send, to the first electric machine, the value of the parameter.
2. The site controller of claim 1, wherein the computer-executable instructions, when executed by the one or more processors, further cause the one or more processors to: receive, from the first electric machine, an indication of a state-of-charge (SOC) associated with a battery of the first electric machine, wherein the value of the parameter is further based at least in part on the SOC.

3. The site controller of claim 1, wherein to determine that the first segment of the plurality of segments of the trolley power system is faulted further comprises receiving an indication of a fault from a sensor associated with the first segment.
4. The site controller of claim 1, wherein the computer-executable instructions, when executed by the one or more processors, further cause the one or more processors to: identifying a current location of the first electric machine; and identifying a current task of the first electric machine, wherein to determine that a first electric machine will approach the first segment is based at least in part on the current location and the current task.
5. The site controller of claim 1, wherein the operation of the first electric machine to be changed comprises changing speed of the first machine from a first speed to a second speed.
6. The site controller of claim 5, wherein the parameter indicates the second speed.
7. The site controller of claim 5, wherein the second speed is 50% or less than the first speed.
8. The site controller of claim 1, wherein the operation of the first electric machine to be changed comprises changing a route of the first electric machine from a first route to a second route.
9. The site controller of claim 8, wherein the parameter indicates coordinates of a destination of the second route.
10. The site controller of claim 1, wherein the first electric machine includes a battery that has an energy capacity sufficient to move the first electric machine a distance that is no more than two times a length of the first segment.
11. A method, comprising: determining, by a site controller, that a first segment of a plurality of segments of a trolley power system is faulted; determining, by the site controller, that a first electric machine will approach the first segment; determining, by the site controller and based at least in part on the first segment being faulted and the first electric machine approaching the first segment, that an operating speed of the first electric machine is to be reduced from an original speed to a new speed while the first electric machine is drawing power from a second segment; and sending, by the site controller and to the first electric machine, a message indicating the new speed.
12. The method of claim 11, further comprising: receiving, by the site controller and from the first electric machine, an indication of a state-of-charge (SOC) associated with a battery of the first electric machine, wherein the new speed is further based at least in part on the SOC.
13. The method of claim 11, further comprising: determining, by the site controller, that a second electric machine will approach the first segment; determining, by the site controller and based at least in part on the first segment being faulted and the second electric machine approaching the first segment, that a second operating speed of the second electric machine is to be reduced from a second original speed to a second new speed; and sending, by the site controller and to the second electric machine, a second message indicating the second new speed.
14. The method of claim 13, wherein the second new speed is different from the new speed.
15. The method of claim 11, wherein the new speed is 50% or less than the original speed.
16. The method of claim 11, further comprising: determining, by the site controller, that a second electric machine will approach the first segment; determining, by the site controller and based at least in part on the first segment being faulted and the second electric machine approaching the first segment, that an original route of the second electric machine is to be modified to a new route; and sending, by the site controller and to the second electric machine, a second message indicating the new route.
17. The method of claim 11, further comprising: determining, by a site controller, that a third segment of the plurality of segments of the trolley power system is faulted; determining, by the site controller, that a second electric machine will approach the third segment; determining, by the site controller and based at least in part on the third segment being faulted and the second electric machine approaching the third segment, that a second operating speed of the second electric machine is to be reduced from a second original speed to a second new speed; and sending, by the

site controller and to the second electric machine, a second message indicating the second new speed, wherein the second new speed is different from the new speed.
