

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411314
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Yeh; Kuan-Ting et al.

Image capturing optical lens system, imaging apparatus and electronic device

Abstract

An image capturing optical lens system includes four lens elements, which are, in order from an object side to an image side along an optical path, a first lens element, a second lens element, a third lens element and a fourth lens element. The first lens element has an object-side surface being convex in a paraxial region thereof. The third lens element with positive refractive power has an object-side surface being convex in a paraxial region thereof and an image-side surface being concave in a paraxial region thereof. The fourth lens element has negative refractive power.

Inventors:	Yeh; Kuan-Ting (Taichung, TW), Chen; Wei-Yu (Taichung, TW)
Applicant:	LARGAN PRECISION CO., LTD. (Taichung, TW)
Family ID:	82561666
Assignee:	LARGAN PRECISION CO., LTD. (Taichung, TW)
Appl. No.:	18/581532
Filed:	February 20, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240192468 A1	Jun. 13, 2024

Foreign Application Priority Data

TW	110103723	Feb. 01, 2021
----	-----------	---------------

Related U.S. Application Data

continuation parent-doc US 17376250 20210715 US 11940597 child-doc US 18581532

Publication Classification

Int. Cl.: G02B13/00 (20060101); G02B9/34 (20060101)

U.S. Cl.:

CPC G02B13/004 (20130101); G02B9/34 (20130101);

Field of Classification Search

CPC: G02B (15/144); G02B (15/144109); G02B (15/144111); G02B (15/144509); G02B (15/144511); G02B (13/004); G02B (9/34)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4484802	12/1983	Kikuchi	N/A	N/A
7643225	12/2009	Tsai	N/A	N/A
7821725	12/2009	Sato	N/A	N/A
9667847	12/2016	Hsieh	N/A	N/A
9791666	12/2016	Hsieh	N/A	N/A
10139594	12/2017	Lin et al.	N/A	N/A
10306031	12/2018	Tseng et al.	N/A	N/A
10451840	12/2018	Jhang	N/A	N/A
11442256	12/2021	Chen	N/A	N/A
2002/0181121	12/2001	Kawakami	359/689	G02B 9/34
2010/0046096	12/2009	Hirao et al.	N/A	N/A
2016/0062082	12/2015	Engelhardt	N/A	N/A
2017/0235109	12/2016	Shin	N/A	N/A
2017/0351061	12/2016	Chang	N/A	N/A
2018/0210170	12/2017	Lee	N/A	N/A
2020/0174341	12/2019	Shinobu	N/A	N/A
2021/0063686	12/2020	Kim et al.	N/A	N/A
2021/0255426	12/2020	Tang	N/A	N/A
2022/0206274	12/2021	Huh et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101661148	12/2009	CN	N/A
110109234	12/2018	CN	N/A
110716299	12/2019	CN	N/A
110908097	12/2019	CN	N/A
111142237	12/2019	CN	N/A
111708147	12/2019	CN	N/A
211528803	12/2019	CN	N/A
111736313	12/2019	CN	N/A
112099209	12/2019	CN	N/A
112230393	12/2020	CN	N/A

2010008660	12/2009	JP	N/A
2011095301	12/2010	JP	N/A
2022000824	12/2021	WO	N/A
2022061676	12/2021	WO	N/A

Primary Examiner: Martinez; Joseph P

Attorney, Agent or Firm: McClure, Qualey & Rodack, LLP

Background/Summary

RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 17/376,250, filed Jul. 15, 2021, which claims priority to Taiwan Application Serial Number 110103723, filed Feb. 1, 2021, which is herein incorporated by reference.

BACKGROUND

Technical Field

(1) The present disclosure relates to an image capturing optical lens system and an imaging apparatus. More particularly, the present disclosure relates to an image capturing optical lens system and an imaging apparatus with compact size applicable to electronic devices.

Description of Related Art

(2) With recent technology of semiconductor process advances, performances of image sensors are enhanced, so that the smaller pixel size can be achieved. Therefore, optical lens assemblies with high image quality have become an indispensable part of many modern electronics. With rapid developments of technology, applications of electronic devices equipped with optical lens assemblies increase and there is a wide variety of requirements for optical lens assemblies. However, in a conventional optical lens assembly, it is hard to balance among image quality, sensitivity, aperture size, volume or field of view. Thus, there is a need for an image capturing optical lens system that can overcome the aforementioned difficulties.

SUMMARY

(3) According to one aspect of the present disclosure, an image capturing optical lens system includes four lens elements, the four lens elements being, in order from an object side to an image side along an optical path, a first lens element, a second lens element, a third lens element and a fourth lens element. The first lens element has an object-side surface being convex in a paraxial region thereof. The third lens element with positive refractive power has an object-side surface being convex in a paraxial region thereof and an image-side surface being concave in a paraxial region thereof. The fourth lens element has negative refractive power. When an Abbe number of the second lens element is V_2 , an Abbe number of the third lens element is V_3 , a focal length of the image capturing optical lens system is f , a curvature radius of an object-side surface of the fourth lens element is R_7 , a curvature radius of an image-side surface of the fourth lens element is R_8 , a central thickness of the first lens element is CT_1 , a central thickness of the second lens element is CT_2 , and an axial distance between the object-side surface of the first lens element and an image surface is TL , the following conditions are satisfied: $10 < V_2 + V_3 < 70$; $f/|R_7| + f/|R_8| < 6.0$; $0.30 < CT_1/CT_2 < 3.0$; and $0.5 < TL/f < 1.0$.

(4) According to one aspect of the present disclosure, an imaging apparatus includes the image capturing optical lens system of the aforementioned aspect and an image sensor disposed on the image surface of the image capturing optical lens system.

(5) According to one aspect of the present disclosure, an electronic device includes the imaging apparatus of the aforementioned aspect.

(6) According to one aspect of the present disclosure, an image capturing optical lens system includes four lens elements, the four lens elements being, in order from an object side to an image side along an optical path, a first lens element, a second lens element, a third lens element and a fourth lens element. The second lens element has an image-side surface being concave in a paraxial region thereof. The third lens element has an object-side surface being convex in a paraxial region thereof. When an Abbe number of the second lens element is V_2 , an Abbe number of the third lens element is V_3 , a focal length of the image capturing optical lens system is f , a curvature radius of the object-side surface of the third lens element is R_5 , a curvature radius of an image-side surface of the third lens element is R_6 , a curvature radius of an object-side surface of the fourth lens element is R_7 , a curvature radius of an image-side surface of the fourth lens element is R_8 , an axial distance between an object-side surface of the first lens element and the image-side surface of the fourth lens element is T_d , an axial distance between the image-side surface of the fourth lens element and an image surface is BL , a sum of all axial distances between adjacent lens elements of the image capturing optical lens system is ΣAT , and an axial distance between the second lens element and the third lens element is T_{23} , the following conditions are satisfied: $10 < V_2 + V_3 < 55$; $f/|R_7| + f/|R_8| < 6.0$; $0.5 < T_d/BL < 2.4$; $(R_5 + R_6)/(R_5 - R_6) < 0.7$; and $1.0 < \Sigma AT/T_{23} < 1.8$.

(7) According to one aspect of the present disclosure, an image capturing optical lens system includes four lens elements, the four lens elements being, in order from an object side to an image side along an optical path, a first lens element, a second lens element, a third lens element and a fourth lens element. The third lens element with positive refractive power has an object-side surface being convex in a paraxial region thereof and an image-side surface being concave in a paraxial region thereof. The fourth lens element has negative refractive power. When an Abbe number of the second lens element is V_2 , an Abbe number of the third lens element is V_3 , a focal length of the image capturing optical lens system is f , a curvature radius of an object-side surface of the fourth lens element is R_7 , a curvature radius of an image-side surface of the fourth lens element is R_8 , a central thickness of the first lens element is CT_1 , a central thickness of the second lens element is CT_2 , a sum of all axial distances between adjacent lens elements of the image capturing optical lens system is ΣAT , an axial distance between the second lens element and the third lens element is T_{23} , and an axial distance between an object-side surface of the first lens element and an image surface is TL , the following conditions are satisfied: $10 < V_2 + V_3 < 55$; $f/|R_7| + f/|R_8| < 6.0$; $0.30 < CT_1/CT_2 < 2.7$; $1.0 < \Sigma AT/T_{23} < 2.5$; and $TL/f < 1.40$.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a schematic view of an imaging apparatus according to the 1st embodiment of the present disclosure.

(2) FIG. 2 shows spherical aberration curves, astigmatic field curves and a distortion curve of the imaging apparatus according to the 1st embodiment.

(3) FIG. 3 is a schematic view of an imaging apparatus according to the 2nd embodiment of the present disclosure.

(4) FIG. 4 shows spherical aberration curves, astigmatic field curves and a distortion curve of the imaging apparatus according to the 2nd embodiment.

(5) FIG. 5 is a schematic view of an imaging apparatus according to the 3rd embodiment of the present disclosure.

(6) FIG. 6 shows spherical aberration curves, astigmatic field curves and a distortion curve of the imaging apparatus according to the 3rd embodiment.

(7) FIG. 7 is a schematic view of an imaging apparatus according to the 4th embodiment of the present disclosure.

- (8) FIG. 8 shows spherical aberration curves, astigmatic field curves and a distortion curve of the imaging apparatus according to the 4th embodiment.
- (9) FIG. 9 is a schematic view of an imaging apparatus according to the 5th embodiment of the present disclosure.
- (10) FIG. 10 shows spherical aberration curves, astigmatic field curves and a distortion curve of the imaging apparatus according to the 5th embodiment.
- (11) FIG. 11 is a schematic view of an imaging apparatus according to the 6th embodiment of the present disclosure.
- (12) FIG. 12 shows spherical aberration curves, astigmatic field curves and a distortion curve of the imaging apparatus according to the 6th embodiment.
- (13) FIG. 13 is a schematic view of an imaging apparatus according to the 7th embodiment of the present disclosure.
- (14) FIG. 14 shows spherical aberration curves, astigmatic field curves and a distortion curve of the imaging apparatus according to the 7th embodiment.
- (15) FIG. 15 is a schematic view of an imaging apparatus according to the 8th embodiment of the present disclosure.
- (16) FIG. 16 shows spherical aberration curves, astigmatic field curves and a distortion curve of the imaging apparatus according to the 8th embodiment.
- (17) FIG. 17 is a schematic view of the imaging apparatus with another reflective element according to the 3rd embodiment of the present disclosure.
- (18) FIG. 18 is a schematic view of the imaging apparatus with another reflective element according to the 7th embodiment of the present disclosure.
- (19) FIG. 19A is a schematic view of a light blocking element of an imaging apparatus according to the 9th embodiment of present disclosure.
- (20) FIG. 19B is a schematic view of another light blocking element of the imaging apparatus according to the 9th embodiment of present disclosure.
- (21) FIG. 20 is a schematic view of a first lens element of an imaging apparatus according to the 10th embodiment of present disclosure.
- (22) FIG. 21 is a schematic view of a first lens element of an imaging apparatus according to the 11th embodiment of present disclosure.
- (23) FIG. 22 is a schematic view of an imaging apparatus according to the 12th embodiment of the present disclosure.
- (24) FIG. 23A is a schematic view of one side of an electronic device according to the 13th embodiment of the present disclosure.
- (25) FIG. 23B is a schematic view of another side of the electronic device of FIG. 23A.
- (26) FIG. 23C is a system schematic view of the electronic device of FIG. 23A.
- (27) FIG. 24 is a schematic view of one side of an electronic device according to the 14th embodiment of the present disclosure.
- (28) FIG. 25 is a schematic view of one side of an electronic device according to the 15th embodiment of the present disclosure.
- (29) FIG. 26A is a schematic view of an arrangement of a light path folding element in the image capturing optical lens system of the present disclosure.
- (30) FIG. 26B is a schematic view of another arrangement of the light path folding element in the image capturing optical lens system of the present disclosure.
- (31) FIG. 26C is a schematic view of an arrangement of two light path folding elements in the image capturing optical lens system of the present disclosure.
- (32) FIG. 26D is a schematic view of another arrangement of the light path folding element in the image capturing optical lens system of the present disclosure.

DETAILED DESCRIPTION

- (33) The present disclosure provides an image capturing optical lens system, which includes four

lens elements, the four lens elements being, in order from an object side to an image side along an optical path, a first lens element, a second lens element, a third lens element and a fourth lens element.

(34) The first lens element can have positive refractive power, so that it is favorable for achieving the requirement of compactness by reducing the total track length of the image capturing optical lens system. The first lens element has an object-side surface being convex in a paraxial region thereof, so that the refractive power of the first lens element can be strengthened.

(35) The second lens element can have negative refractive power so as to balance aberrations generated when reducing the size of the image capturing optical lens system. The second lens element can have an image-side surface being concave in a paraxial region thereof, so that it is favorable for correcting aberrations, such as astigmatism.

(36) The third lens element can have positive refractive power. Therefore, it is favorable for balancing the arrangement of positive refractive power for reducing the total track length of the image capturing optical lens system so as to reduce the sensitivity and increase the yield rate of assembling. The third lens element has an object-side surface being convex in a paraxial region thereof, so that it is favorable for reducing the total track length of the image capturing optical lens system by adjusting the refractive power of the third lens element. The third lens element can have an image-side surface being concave in a paraxial region thereof, so that it is favorable for correcting aberrations of the image capturing optical lens system.

(37) The fourth lens element can have negative refractive power. It is favorable for correcting the light path close to the image surface of the image capturing optical lens system so as to provide a better incident angle on the image surface. The fourth lens element can have an image-side surface being concave in a paraxial region thereof, so that it is favorable for correcting astigmatism thereof. The image-side surface of the fourth lens element can include at least one inflection point in an off-axis region thereof, so that it is favorable for enhancing the variation of lens surface so as to correct off-axis aberrations. Further, the image-side surface of the fourth lens element can include at least one critical point in the off-axis region thereof so as to adjust the surface shape of the fourth lens element and further correct off-axis aberrations.

(38) When an Abbe number of the second lens element is V_2 , and an Abbe number of the third lens element is V_3 , the following condition is satisfied: $10 < V_2 + V_3 < 70$. Therefore, it is favorable for enhancing the correction of chromatic aberrations. Further, the following condition can be satisfied: $10 < V_2 + V_3 < 55$. Moreover, the following condition can be satisfied: $15 < V_2 + V_3 < 50$.

(39) When a focal length of the image capturing optical lens system is f , a curvature radius of an object-side surface of the fourth lens element is R_7 , and a curvature radius of the image-side surface of the fourth lens element is R_8 , the following condition is satisfied: $f/|R_7| + f/|R_8| < 6.0$. Therefore, it is favorable for avoiding overly large curvature on the lens element on the image side which will produce manufacturing difficulties or optical flare. Further, the following condition can be satisfied: $f/|R_7| + f/|R_8| < 5.0$. Moreover, the following condition can be satisfied: $0.30 < f/|R_7| + f/|R_8| < 4.0$.

(40) When a central thickness of the first lens element is CT_1 , and a central thickness of the second lens element is CT_2 , the following condition is satisfied: $0.30 < CT_1/CT_2 < 3.0$. Therefore, it is favorable for enhancing the structural strength of the first lens element and the second lens element so as to increase the productivity of the image capturing optical lens system. Further, the following condition can be satisfied: $0.30 < CT_1/CT_2 < 2.7$.

(41) When the focal length of the image capturing optical lens system is f , and an axial distance between the object-side surface of the first lens element and the image surface is TL , the following condition is satisfied: $TL/f < 2.50$. Therefore, it is favorable for providing a telephoto configuration with a shorter total track length. Further, the following condition can be satisfied: $TL/f < 2.0$. Moreover, the following condition can be satisfied: $TL/f < 1.40$. Furthermore, the following condition can be satisfied: $TL/f < 1.20$. Moreover, the following condition can be satisfied:

$$0.5 < TL/f < 1.0.$$

(42) When an axial distance between the object-side surface of the first lens element and the image-side surface of the fourth lens element is T_d , and an axial distance between the image-side surface of the fourth lens element and the image surface is BL , the following condition is satisfied: $0.5 < T_d/BL < 4.0$. Therefore, it is favorable for ensuring enough space between lens elements and the image surface while sufficiently utilizing the limited space in the image capturing optical lens system. Further, the following condition can be satisfied: $0.5 < T_d/BL < 2.4$.

(43) When a curvature radius of the object-side surface of the third lens element is R_5 , and a curvature radius of the image-side surface of the third lens element is R_6 , the following condition is satisfied: $(R_5+R_6)/(R_5-R_6) < 0.7$. Therefore, it is favorable for arranging the third lens element and the fourth lens element with better imaging quality. Further, the following condition can be satisfied: $(R_5+R_6)/(R_5-R_6) < -0.50$. Moreover, the following condition can be satisfied: $-10 < (R_5+R_6)/(R_5-R_6) < -0.75$.

(44) When a sum of all axial distances between adjacent lens elements of the image capturing optical lens system is ΣAT , and an axial distance between the second lens element and the third lens element is T_{23} , the following condition is satisfied: $1.0 < \Sigma AT/T_{23} < 2.5$. Therefore, it is favorable for arranging other elements between the second lens element and the third lens element while reducing the size of the light beam in the middle portion of the image capturing optical lens system so as to further reduce the overall size. Moreover, the following condition can be satisfied: $1.0 < \Sigma AT/T_{23} < 1.8$.

(45) When a maximum distance between an optical effective region of the object-side surface of the first lens element and the optical axis is Y_{11} , and a maximum image height of the image capturing optical lens system is $ImgH$, the following condition is satisfied: $0.60 < Y_{11}/ImgH < 1.20$. Therefore, it is favorable for controlling the size of the light beam so as to avoid an effective diameter of any single lens element being overly large which will affect the compactness of the image capturing optical lens system.

(46) When the focal length of the image capturing optical lens system is f , a focal length of the first lens element is f_1 , a focal length of the second lens element is f_2 , a focal length of the third lens element is f_3 , and a focal length of the fourth lens element is f_4 , the following condition is satisfied: $2.0 < (|f/f_1| + |f/f_2|)/(|f/f_3| + |f/f_4|) < 8.0$. Therefore, it is favorable for ensuring sufficient refractive power for light convergence on the image surface while miniaturizing the lens elements on the object side of the image capturing optical lens system.

(47) When the maximum image height of the image capturing optical lens system is $ImgH$, and an entrance pupil diameter of the image capturing optical lens system is EPD , the following condition is satisfied: $0.30 < ImgH/EPD < 0.80$. Therefore, it is favorable for controlling the size of the light beam so as to avoid excessively a large effective diameter of any single lens element which will affect the compactness of the image capturing optical lens system.

(48) When the focal length of the image capturing optical lens system is f , a curvature radius of the object-side surface of the first lens element is R_1 , and a curvature radius of the image-side surface of the second lens element is R_4 , the following condition is satisfied: $6.0 < (f/R_1) + (f/R_4)$. Therefore, it is favorable for enhancing image quality by correcting aberrations.

(49) When the focal length of the second lens element is f_2 , and the focal length of the fourth lens element is f_4 , the following condition is satisfied: $0 < f_2/f_4 < 1.25$. Therefore, it is favorable for ensuring sufficient refractive power for light focusing on the image surface with a compact arrangement of lens elements on the image side of the image capturing optical lens system.

(50) When the focal length of the image capturing optical lens system is f , and the maximum image height of the image capturing optical lens system is $ImgH$, the following condition is satisfied: $4.0 < f/ImgH$. Therefore, it is favorable for providing a longer focal length in a telephoto configuration of the image capturing optical lens system. Moreover, the following condition can be satisfied: $4.50 < f/ImgH < 10$.

(51) When half of a maximum field of view of the image capturing optical lens system is HFOV, the following condition is satisfied: $\tan(2 \times \text{HFOV}) < 0.60$. Therefore, it is favorable for enhancing the telephoto arrangement with a small field of view.

(52) When a minimum Abbe number of the lens elements of the image capturing optical lens system is $V_{\min}$, the following condition is satisfied: $10 < V_{\min} < 20$. Therefore, it is favorable for enhancing the correction of chromatic aberration.

(53) When an Abbe number of one of the lens elements is V_i , and a refractive index of the lens element is N_i , at least one of the lens elements of the image capturing optical lens system satisfies the following condition: $5.0 < V_i/N_i < 12.0$, wherein $i=1, 2, 3, 4$. Therefore, it is favorable for correcting chromatic aberration.

(54) The image capturing optical lens system can further include at least one reflective element. Therefore, it is favorable for enhancing the flexibility of space arrangement in the image capturing optical lens system. The reflective element can be located on an object side of the first lens element along the optical path and can have refractive power. One surface of the reflective element facing towards an imaged object is convex in a paraxial region thereof. Therefore, the arrangement of the refractive power and the aberration correction can be enhanced, and the image capturing optical lens system can have a convex outside appearance.

(55) The reflective element can be made of plastic material. When a glass transition temperature of a material of the reflective element is T_{gp} , and a refractive index of the reflective element is N_p , the following condition is satisfied: $92.5 < T_{gp}/N_p < 100$. Thus, it is favorable for increasing the yield rate by reducing the manufacturing difficulty of the reflective element.

(56) The image capturing optical lens system can include a light blocking element having a non-circular inner hole. Therefore, it is favorable for shielding the stray light so as to enhance the image quality.

(57) Each of the aforementioned features of the image capturing optical lens system can be utilized in various combinations for achieving the corresponding effects.

(58) According to the image capturing optical lens system of the present disclosure, the lens elements thereof can be made of glass or plastic materials. When the lens elements are made of glass materials, the distribution of the refractive power of the image capturing optical lens system may be more flexible to design. The glass lens element can either be made by grinding or molding. When the lens elements are made of plastic materials, manufacturing costs can be effectively reduced. Furthermore, surfaces of each lens element can be arranged to be aspheric (ASP), since the aspheric surface of the lens element is easy to form a shape other than a spherical surface so as to have more controllable variables for eliminating aberrations thereof, and to further decrease the required amount of lens elements in the image capturing optical lens system. Therefore, the total track length of the image capturing lens assembly can also be reduced. The aspheric surfaces may be formed by a plastic injection molding method, a glass molding method or other manufacturing methods.

(59) According to the image capturing optical lens system of the present disclosure, additives can be selectively added into any one (or more) material of the lens elements so as to change the transmittance of the lens element in a particular wavelength range. Therefore, the stray light and chromatic aberration can be reduced. For example, the additives can have the absorption ability for lights in a wavelength range of 600 nm-800 nm in the image capturing optical lens system so as to reduce extra red light or infrared lights, or the additives can have the absorption ability for lights in a wavelength range of 350 nm-450 nm in the image capturing optical lens system so as to reduce blue light or ultraviolet lights. Therefore, additives can prevent the image from interfering by lights in a particular wavelength range. Furthermore, the additives can be homogeneously mixed with the plastic material, and the lens elements can be made by the injection molding method.

(60) According to the image capturing optical lens system of the present disclosure, when a surface of the lens element is aspheric, it indicates that entire optical effective region of the surface of the

lens element or a part thereof is aspheric.

(61) According to the image capturing optical lens system of the present disclosure, when the lens elements have surfaces being convex and the convex surface position is not defined, it indicates that the aforementioned surfaces of the lens elements can be convex in the paraxial region thereof. When the lens elements have surfaces being concave and the concave surface position is not been defined, it indicates that the aforementioned surfaces of the lens elements can be concave in the paraxial region thereof. In the image capturing optical lens system of the present disclosure, if the lens element has positive refractive power or negative refractive power, or the focal length of the lens element, all can be referred to the refractive power, or the focal length, in the paraxial region of the lens element.

(62) According to the image capturing optical lens system of the present disclosure, a critical point is a non-axial point of the lens surface where its tangent is perpendicular to the optical axis; an inflection point is a point on a lens surface with a curvature changing from positive to negative or from negative to positive.

(63) According to the image capturing optical lens system of the present disclosure, the image surface thereof, based on the corresponding image sensor, can be flat or curved. In particular, the image surface can be a concave curved surface facing towards the object side. Furthermore, the image capturing optical lens system of the present disclosure can selectively include at least one image correcting element (such as a field flattener) inserted between the lens element closest to the image surface and the image surface, thus the effect of correcting image aberrations (such as field curvature) can be achieved. The optical properties of the aforementioned image correcting element, such as curvature, thickness, refractive index, position, surface shape (convex or concave, spherical or aspheric, diffraction surface and Fresnel surface, etc.) can be adjusted corresponding to the demands of the imaging apparatus. Generally, a preferred configuration of the image correcting element is to dispose a thin plano-concave element having a concave surface toward the object side on the position closed to the image surface.

(64) According to the image capturing optical lens system of the present disclosure, at least one element with light path folding function can be selectively disposed between the imaged object and the image surface, such as a prism or a mirror, etc. Therefore it is favorable for providing high flexible space arrangement of the image capturing optical lens system, so that the compactness of the electronic device would not be restricted by the optical total track length of the image capturing optical lens system. FIG. 26A is a schematic view of an arrangement of a light path folding element LF in the image capturing optical lens system of the present disclosure. FIG. 26B is a schematic view of another arrangement of the light path folding element LF in the image capturing optical lens system of the present disclosure. As shown in FIGS. 26A and 26B, the image capturing optical lens system includes, in order from an imaged object (not shown in drawings) to an image surface IM, a first optical axis OA1, the light path folding element LF and a second optical axis OA2, a lens group LG of the image capturing optical lens system and an IR-cut filter IRF, wherein the light path folding element LF can be disposed between the imaged object and a lens group LG of the image capturing optical lens system. The differences between FIG. 26A and FIG. 26B are, the object-side surface and the image-side surface of the light path folding element LF in FIG. 26A are both planar, and the object-side surface and the image-side surface of the light path folding element LF in FIG. 26B are both convex. Moreover, FIG. 26C is a schematic view of an arrangement of two light path folding elements LF1, LF2 in the image capturing optical lens system of the present disclosure. As shown in FIG. 26C, the image capturing optical lens system includes, in order from an imaged object (not shown in drawings) to an image surface IM, a first optical axis OA1, the light path folding element LF1, a second optical axis OA2, a lens group LG of the image capturing lens assembly, an IR-cut filter IRF, the light path folding element LF2 and a third optical axis OA3, wherein the light path folding element LF1 is disposed between the imaged object and the lens group LG of the image capturing lens assembly, and the light path folding element LF2 is disposed

between the IR-cut filter IRF and the image surface IM. The image capturing lens assembly can also be selectively disposed with three or more light path folding element, the type, amount and location of the light path folding element will not be limited to the present disclosure. Further, FIG. 26D is a schematic view of another arrangement of the light path folding element LF in the image capturing optical lens system of the present disclosure. In FIG. 26D, the image capturing optical lens system includes, in order from an imaged object (not shown in drawings) to an image surface IM, a first optical axis OA1, a lens group LG of the image capturing lens assembly, an IR-cut filter IRF, the light path folding element LF, a second optical axis OA2 and a third optical axis OA3, wherein the light path folding element LF can be disposed between the IR-cut filter IRF and the image surface IM, and the incident light can be folded by the light path folding element LF along the direction of the first optical axis OA1 to the direction of the second optical axis OA2, and then folded to the direction of the third optical axis OA3 to the image surface IM.

(65) Furthermore, according to the image capturing optical lens system of the present disclosure, the image capturing optical lens system can include at least one stop, such as an aperture stop, a glare stop or a field stop, for eliminating stray light and thereby improving image resolution thereof.

(66) According to the image capturing optical lens system of the present disclosure, the aperture stop can be configured as a front stop or a middle stop, wherein the front stop indicates that the aperture stop is disposed between an object and the first lens element, and the middle stop indicates that the aperture stop is disposed between the first lens element and the image surface. When the aperture stop is a front stop, a longer distance between an exit pupil of the image capturing optical lens system and the image surface can be obtained, and thereby obtains a telecentric effect and improves the image-sensing efficiency of the image sensor, such as CCD or CMOS. The middle stop is favorable for enlarging the field of view of the image capturing optical lens system and thereby provides a wider field of view for the same.

(67) According to the image capturing optical lens system of the present disclosure, an aperture control unit can be properly configured. The aperture control unit can be a mechanical element or a light controlling element, and the dimension and the shape of the aperture control unit can be electrically controlled. The mechanical element can include a moveable component such a blade group or a shielding plate. The light controlling element can include a screen component such as a light filter, an electrochromic material, a liquid crystal layer or the like. The amount of incoming light or the exposure time of the image can be controlled by the aperture control unit to enhance the image moderation ability. In addition, the aperture control unit can be the aperture stop of the image capturing optical lens system according to the present disclosure, so as to moderate the image quality by changing f-number such as changing the depth of field or the exposure speed.

(68) According to the image capturing optical lens system of the present disclosure, the image capturing optical lens system of the present disclosure can be applied to 3D (three-dimensional) image capturing applications, in products such as digital cameras, mobile devices, digital tablets, smart TVs, surveillance systems, motion sensing input devices, driving recording systems, rearview camera systems, wearable devices, unmanned aerial vehicles, and other electronic imaging products.

(69) According to the present disclosure, an imaging apparatus including the aforementioned image capturing optical lens system and an image sensor is provided, wherein the image sensor is disposed on the image surface of the image capturing optical lens system. Hence, the total track length of the image capturing optical lens system can be reduced efficiently by arranging the surface shape of the object-side surface of the third lens element, and the manufacturing difficulty or flare can be avoided by the arrangement of the surface shape of the fourth lens element. Moreover, the imaging apparatus can further include a barrel member, a holder member or a combination thereof.

(70) According to the present disclosure, an electronic device including the aforementioned

imaging apparatus is provided. Therefore, the image quality can be increased. Moreover, the electronic device can further include a control unit, a display, a storage unit, a random-access memory unit (RAM) or a combination thereof.

(71) According to the above description of the present disclosure, the following specific embodiments are provided for further explanation.

1st Embodiment

(72) FIG. 1 is a schematic view of an imaging apparatus according to the 1st embodiment of the present disclosure. FIG. 2 shows spherical aberration curves, astigmatic field curves and a distortion curve of the imaging apparatus according to the 1st embodiment. In FIG. 1, the imaging apparatus includes an image capturing optical lens system (its reference numeral is omitted) and an image sensor 170. The image capturing optical lens system includes, in order from an object side to an image side along an optical path, a stop 101, a first lens element 110, a second lens element 120, an aperture stop 100, a third lens element 130, a stop 102, a fourth lens element 140, a IR-cut filter 150 and an image surface 160, wherein the image sensor 170 is disposed on the image surface 160 of the image capturing optical lens system. The image capturing optical lens system includes four lens elements (110, 120, 130, 140) without additional one or more lens elements inserted between the first lens element 110 and the fourth lens element 140.

(73) The first lens element 110 with positive refractive power has an object-side surface 111 being convex in a paraxial region thereof and an image-side surface 112 being convex in a paraxial region thereof. The first lens element 110 is made of plastic material, and has the object-side surface 111 and the image-side surface 112 being both aspheric.

(74) The second lens element 120 with negative refractive power has an object-side surface 121 being concave in a paraxial region thereof and an image-side surface 122 being concave in a paraxial region thereof. The second lens element 120 is made of plastic material, and has the object-side surface 121 and the image-side surface 122 being both aspheric.

(75) The third lens element 130 with positive refractive power has an object-side surface 131 being convex in a paraxial region thereof and an image-side surface 132 being convex in a paraxial region thereof. The third lens element 130 is made of plastic material, and has the object-side surface 131 and the image-side surface 132 being both aspheric.

(76) The fourth lens element 140 with negative refractive power has an object-side surface 141 being planar in a paraxial region thereof and an image-side surface 142 being concave in a paraxial region thereof. The fourth lens element 140 is made of plastic material, and has the object-side surface 141 and the image-side surface 142 being both aspheric. Furthermore, the image-side surface 142 of the fourth lens element 140 includes at least one inflection point and at least one critical point in an off-axis region thereof.

(77) The IR-cut filter 150 is made of glass material, which is located between the fourth lens element 140 and the image surface 160 in order, and will not affect the focal length of the image capturing optical lens system.

(78) The equation of the aspheric surface profiles of the aforementioned lens elements of the 1st embodiment is expressed as follows:

(79) $X(Y) = (Y^2 / R) / (1 + \sqrt{1 - (1 + k) \times (Y / R)^2}) + \sum_i A_i \times (Y^i)$, where, X is the displacement in parallel with an optical axis from the intersection point of the aspheric surface and the optical axis to a point at a distance of Y from the optical axis on the aspheric surface; Y is the vertical distance from the point on the aspheric surface to the optical axis; R is the curvature radius; k is the conic coefficient; and A_i is the i-th aspheric coefficient.

(80) In the image capturing optical lens system according to the 1st embodiment, when a focal length of the image capturing optical lens system is f, an f-number of the image capturing optical lens system is F_{no} , and half of a maximum field of view of the image capturing optical lens system is HFOV, these parameters have the following values: f=12.02 mm; F_{no} =3.52; and HFOV=9.6

degrees.

(81) In the image capturing optical lens system according to the 1st embodiment, when half of a maximum field of view of the image capturing optical lens system is HFOV, the following condition is satisfied: $\tan(2 \times \text{HFOV}) = 0.35$.

(82) In the image capturing optical lens system according to the 1st embodiment, when an Abbe number of the first lens element **110** is V1, an Abbe number of the second lens element **120** is V2, an Abbe number of the third lens element **130** is V3, an Abbe number of the fourth lens element **140** is V4, a minimum Abbe number of the lens elements of the image capturing optical lens system is Vmin, a refractive index of the first lens element **110** is N1, a refractive index of the second lens element **120** is N2, a refractive index of the third lens element **130** is N3, and a refractive index of the fourth lens element **140** is N4, the following conditions are satisfied: $V2 + V3 = 37.8$; $V_{\min} = 14.0$; $V1/N1 = 36.48$; $V2/N2 = 14.59$; $V3/N3 = 8.22$; and $V4/N4 = 12.29$; wherein, according to the 1st embodiment, $V1 = 56.0$, $V2 = 23.8$, $V3 = 14.0$, $V4 = 20.4$, thus, the minimum Abbe number of the lens elements of the image capturing optical lens system $V_{\min} = V3$.

(83) In the image capturing optical lens system according to the 1st embodiment, when a central thickness of the first lens element **110** is CT1, and a central thickness of the second lens element **120** is CT2, the following condition is satisfied: $CT1/CT2 = 2.59$.

(84) In the image capturing optical lens system according to the 1st embodiment, when an axial distance between the first lens element **110** and the second lens element **120** is T12, an axial distance between the second lens element **120** and the third lens element **130** is T23, an axial distance between the third lens element **130** and the fourth lens element **140** is T34, and a sum of all axial distances between adjacent lens elements of the image capturing optical lens system is ΣAT , the following condition is satisfied: $\Sigma AT/T23 = 1.15$; wherein, according to the 1st embodiment, $\Sigma AT = T12 + T23 + T34$.

(85) In the image capturing optical lens system according to the 1st embodiment, when the focal length of the image capturing optical lens system is f, and an axial distance between the object-side surface **111** of the first lens element **110** and the image surface **160** is TL, the following condition is satisfied: $TL/f = 0.94$.

(86) In the image capturing optical lens system according to the 1st embodiment, when an axial distance between the object-side surface **111** of the first lens element **110** and the image-side surface **142** of the fourth lens element **140** is Td, and an axial distance between the image-side surface **142** of the fourth lens element **140** and the image surface **160** is BL, the following condition is satisfied: $Td/BL = 1.29$.

(87) In the image capturing optical lens system according to the 1st embodiment, when a maximum image height of the image capturing optical lens system is ImgH, and an entrance pupil diameter of the image capturing optical lens system is EPD, the following condition is satisfied: $\text{ImgH}/\text{EPD} = 0.60$.

(88) In the image capturing optical lens system according to the 1st embodiment, when a curvature radius of the object-side surface **131** of the third lens element **130** is R5, and a curvature radius of the image-side surface **132** of the third lens element **130** is R6, the following condition is satisfied: $(R5 + R6)/(R5 - R6) = -0.83$.

(89) In the image capturing optical lens system according to the 1st embodiment, when the focal length of the image capturing optical lens system is f, a curvature radius of the object-side surface **111** of the first lens element **110** is R1, and a curvature radius of the image-side surface **122** of the second lens element **120** is R4, the following condition is satisfied: $(f/R1) + (f/R4) = 7.51$.

(90) In the image capturing optical lens system according to the 1st embodiment, when the focal length of the image capturing optical lens system is f, a curvature radius of the object-side surface **141** of the fourth lens element **140** is R7, and a curvature radius of the image-side surface **142** of the fourth lens element **140** is R8, the following condition is satisfied: $f/|R7| + f/|R8| = 1.53$.

(91) In the image capturing optical lens system according to the 1st embodiment, when the focal

length of the image capturing optical lens system is f , and the maximum image height of the image capturing optical lens system is ImgH , the following condition is satisfied: $f/\text{ImgH}=5.89$.

(92) In the image capturing optical lens system according to the 1st embodiment, when the focal length of the image capturing optical lens system is f , a focal length of the first lens element **110** is f_1 , a focal length of the second lens element **120** is f_2 , a focal length of the third lens element **130** is f_3 , and a focal length of the fourth lens element **140** is f_4 , the following conditions are satisfied: $(|f/f_1|+|f/f_2|)/(|f/f_3|+|f/f_4|)=2.46$; and $f_2/f_4=0.41$.

(93) In the image capturing optical lens system according to the 1st embodiment, when a maximum distance between an optical effective region of the object-side surface **111** of the first lens element **110** and the optical axis is Y_{11} , and a maximum image height of the image capturing optical lens system is ImgH , the following condition is satisfied: $Y_{11}/\text{ImgH}=0.84$.

(94) The detailed optical data of the 1st embodiment are shown in Table 1 and the aspheric surface data are shown in Table 2 below.

(95) TABLE-US-00001 TABLE 1 1st Embodiment $f = 12.02$ mm, $F_{no} = 3.52$, $HFOV = 9.6$ deg.
Focal Surface # Curvature Radius Thickness Material Index Abbe # Length 0 Object Plano Infinity
1 Stop Plano -0.485 2 Lens 1 3.152 ASP 2.237 Plastic 1.534 56.0 4.90 3 -11.608 ASP 0.030 4
Lens 2 -100.000 ASP 0.865 Plastic 1.634 23.8 -4.95 5 3.251 ASP 0.258 6 Ape. Stop Plano 1.321 7
Lens 3 9.412 ASP 0.772 Plastic 1.704 14.0 12.26 8 -100.000 ASP 0.103 9 Stop Plano 0.099 10
Lens 4 ∞ ASP 0.650 Plastic 1.660 20.4 -11.94 11 7.877 ASP 4.000 12 IR-cut filter Plano 0.210
Glass 1.517 64.2 — 13 Plano 0.710 14 Image Plano — Reference wavelength is 587.6 nm (d-line).
Effective radius of Surface 1 (Stop 101) is 1.720 mm. Effective radius of Surface 9 (Stop 102) is 1.180 mm.

(96) TABLE-US-00002 TABLE 2 Aspheric Coefficients Surface # 2 3 4 5 $k = -1.2238E-01$
 $0.0000E+00$ $0.0000E+00$ $-2.3544E+00$ $A_4 = -3.7358E-04$ $3.0556E-02$ $1.9018E-02$ $-9.2731E-04$
 $A_6 = -5.7090E-05$ $-5.4082E-02$ $-4.5793E-02$ $2.3691E-04$ $A_8 = -9.2300E-05$ $6.3745E-02$
 $5.8774E-02$ $9.2831E-03$ $A_{10} = 2.1168E-05$ $-4.7262E-02$ $-4.4384E-02$ $-1.0666E-02$ $A_{12} =$
 $-4.4445E-06$ $2.1955E-02$ $2.1178E-02$ $9.6409E-03$ $A_{14} = 2.7818E-08$ $-5.8822E-03$
 $-5.8941E-03$ $-5.0747E-03$ $A_{16} = 6.8662E-04$ $7.1966E-04$ $1.1335E-03$ Surface # 7 8 10 11 k
 $= 0.0000E+00$ $0.0000E+00$ $0.0000E+00$ $0.0000E+00$ $A_4 = 9.5263E-03$ $1.6495E-02$
 $-4.3399E-02$ $-4.8054E-02$ $A_6 = 4.1220E-04$ $-2.4221E-02$ $-2.0658E-02$ $3.2871E-03$ $A_8 =$
 $-6.8598E-03$ $4.5044E-02$ $2.9780E-02$ $1.8298E-03$ $A_{10} = 2.0336E-02$ $-6.6503E-02$
 $-3.6447E-02$ $-1.1902E-03$ $A_{12} = -2.0508E-02$ $7.8895E-02$ $4.0633E-02$ $1.9531E-04$ $A_{14} =$
 $1.0941E-02$ $-5.0947E-02$ $-2.6742E-02$ $2.3916E-06$ $A_{16} = -2.3297E-03$ $1.4855E-02$
 $8.4750E-03$ $1.1705E-05$

(97) In Table 1, the curvature radius, the thickness and the focal length are shown in millimeters (mm). Surface numbers 0-14 represent the surfaces sequentially arranged from the object side to the image side along the optical axis. In Table 2, k represents the conic coefficient of the equation of the aspheric surface profiles. A_4 - A_{16} represent the aspheric coefficients ranging from the 4th order to the 16th order. The tables presented below for each embodiment correspond to schematic parameter and aberration curves of each embodiment, and term definitions of the tables are the same as those in Table 1 and Table 2 of the 1st embodiment. Therefore, an explanation in this regard will not be provided again.

2nd Embodiment

(98) FIG. 3 is a schematic view of an imaging apparatus according to the 2nd embodiment of the present disclosure. FIG. 4 shows spherical aberration curves, astigmatic field curves and a distortion curve of the imaging apparatus according to the 2nd embodiment. In FIG. 3, the imaging apparatus includes an image capturing optical lens system (its reference numeral is omitted) and an image sensor **270**. The image capturing optical lens system includes, in order from an object side to an image side along an optical path, a stop **201**, a first lens element **210**, a second lens element **220**, an aperture stop **200**, a third lens element **230**, a fourth lens element **240**, a IR-cut filter **250** and an

image surface **260**, wherein the image sensor **270** is disposed on the image surface **260** of the image capturing optical lens system. The image capturing optical lens system includes four lens elements (**210**, **220**, **230**, **240**) without additional one or more lens elements inserted between the first lens element **210** and the fourth lens element **240**.

(99) The first lens element **210** with positive refractive power has an object-side surface **211** being convex in a paraxial region thereof and an image-side surface **212** being convex in a paraxial region thereof. The first lens element **210** is made of glass material, and has the object-side surface **211** and the image-side surface **212** being both aspheric.

(100) The second lens element **220** with negative refractive power has an object-side surface **221** being convex in a paraxial region thereof and an image-side surface **222** being concave in a paraxial region thereof. The second lens element **220** is made of glass material, and has the object-side surface **221** and the image-side surface **222** being both aspheric.

(101) The third lens element **230** with positive refractive power has an object-side surface **231** being convex in a paraxial region thereof and an image-side surface **232** being convex in a paraxial region thereof. The third lens element **230** is made of plastic material, and has the object-side surface **231** and the image-side surface **232** being both aspheric.

(102) The fourth lens element **240** with negative refractive power has an object-side surface **241** being concave in a paraxial region thereof and an image-side surface **242** being convex in a paraxial region thereof. The fourth lens element **240** is made of plastic material, and has the object-side surface **241** and the image-side surface **242** being both aspheric.

(103) The IR-cut filter **250** is made of glass material, which is located between the fourth lens element **240** and the image surface **260** in order, and will not affect the focal length of the image capturing optical lens system.

(104) The detailed optical data of the 2nd embodiment are shown in Table 3 and the aspheric surface data are shown in Table 4 below.

(105) TABLE-US-00003 TABLE 3 2nd Embodiment $f = 12.56$ mm, $Fno = 3.67$, $HFOV = 9.2$ deg.
Focal Surface # Curvature Radius Thickness Material Index Abbe # Length 0 Object Plano Infinity
1 Stop Plano -0.575 2 Lens 1 2.832 ASP 2.483 Glass 1.543 62.9 4.85 3 -25.655 ASP 0.053 4 Lens
2 14.023 ASP 0.887 Glass 1.839 23.9 -3.39 5 2.295 ASP 0.289 6 Ape. Stop Plano 0.230 7 Lens 3
5.314 ASP 1.067 Plastic 1.704 14.0 13.73 8 10.822 ASP 0.239 9 Lens 4 -17.195 ASP 1.100 Plastic
1.634 23.8 -421.31 10 -18.835 ASP 0.500 11 IR-cut filter Plano 0.210 Glass 1.517 64.2 — 12
Plano 4.459 13 Image Plano — Reference wavelength is 587.6 nm (d-line). Effective radius of
Surface 1 (Stop 201) is 1.720 mm.

(106) TABLE-US-00004 TABLE 4 Aspheric Coefficients Surface # 2 3 4 5 $k = 1.9735E-02$
 $0.0000E+00$ $0.0000E+00$ $-2.6153E+00$ $A4 = 4.8240E-05$ $2.2265E-02$ $-6.2159E-03$
 $-1.6485E-03$ $A6 = 8.7141E-05$ $-3.0820E-02$ $-1.8168E-02$ $4.5682E-03$ $A8 = -6.5387E-05$
 $3.1698E-02$ $1.9755E-02$ $-6.7564E-03$ $A10 = 2.4119E-05$ $-1.5010E-02$ $-2.8225E-03$
 $4.1350E-02$ $A12 = -2.9079E-06$ $3.6399E-03$ $-4.8065E-03$ $-4.7894E-02$ $A14 = 1.3890E-08$
 $-1.0996E-03$ $1.9661E-03$ $2.0056E-02$ $A16 = 2.6999E-04$ $-1.6419E-04$ $-2.6443E-03$
Surface# 7 8 9 10 $k = 0.0000E+00$ $0.0000E+00$ $0.0000E+00$ $0.0000E+00$ $A4 = 1.3535E-02$
 $1.9683E-02$ $-2.2471E-02$ $-1.9684E-02$ $A6 = 3.8687E-03$ $5.6418E-03$ $6.4581E-03$
 $5.0626E-04$ $A8 = -4.6318E-03$ $1.3306E-02$ $-7.0628E-03$ $-1.4144E-03$ $A10 = 1.9445E-02$
 $-5.4764E-03$ $3.0400E-02$ $2.3628E-03$ $A12 = -1.1619E-02$ $2.5689E-02$ $-2.3075E-02$
 $-1.9859E-03$ $A14 = -5.2645E-03$ $-3.1855E-02$ $5.5594E-03$ $6.9409E-04$ $A16 =$
 $4.1752E-03$ $1.0095E-02$ $-6.1269E-04$ $-9.3026E-05$

(107) In the 2nd embodiment, the equation of the aspheric surface profiles of the aforementioned lens elements is the same as the equation of the 1st embodiment. Also, the definitions of these parameters shown in the following table are the same as those stated in the 1st embodiment with corresponding values for the 2nd embodiment, so an explanation in this regard will not be provided again.

(108) Moreover, these parameters can be calculated from Table 3 and Table 4 as the following values and satisfy the following conditions:

(109) TABLE-US-00005 2nd Embodiment f [mm] 12.56 $\Sigma AT/T23$ 1.56 Fno 3.67 TL/f 0.92 $HFOV$ [degrees] 9.2 Td/BL 1.23 $\tan(2 \times HFOV)$ 0.33 $ImgH/EPD$ 0.60 $V2 + V3$ 37.9 $(R5 + R6)/(R5 - R6) - 2.93$ $Vmin$ 14.0 $(f/R1) + (f/R4)$ 9.91 $V1/N1$ 40.78 $f/|R7| + f/|R8|$ 1.40 $V2/N2$ 12.97 $f/ImgH$ 6.16 $V3/N3$ 8.22 $(|f/f1| + |f/f2|)/(|f/f3| + |f/f4|)$ 6.67 $V4/N4$ 14.59 $f2/f4$ 0.01 $CT1/CT2$ 2.80 $Y11/ImgH$ 0.84

3rd Embodiment

(110) FIG. 5 is a schematic view of an imaging apparatus according to the 3rd embodiment of the present disclosure. FIG. 6 shows spherical aberration curves, astigmatic field curves and a distortion curve of the imaging apparatus according to the 3rd embodiment. In FIG. 5, the imaging apparatus includes an image capturing optical lens system (its reference numeral is omitted) and an image sensor 370. The image capturing optical lens system includes, in order from an object side to an image side along an optical path, a stop 301, a first lens element 310, a second lens element 320, an aperture stop 300, a third lens element 330, a stop 302, a fourth lens element 340, a reflective element 380, a IR-cut filter 350 and an image surface 360, wherein the image sensor 370 is disposed on the image surface 360 of the image capturing optical lens system. The image capturing optical lens system includes four lens elements (310, 320, 330, 340) without additional one or more lens elements inserted between the first lens element 310 and the fourth lens element 340.

(111) The first lens element 310 with positive refractive power has an object-side surface 311 being convex in a paraxial region thereof and an image-side surface 312 being concave in a paraxial region thereof. The first lens element 310 is made of plastic material, and has the object-side surface 311 and the image-side surface 312 being both aspheric.

(112) The second lens element 320 with negative refractive power has an object-side surface 321 being concave in a paraxial region thereof and an image-side surface 322 being concave in a paraxial region thereof. The second lens element 320 is made of plastic material, and has the object-side surface 321 and the image-side surface 322 being both aspheric.

(113) The third lens element 330 with positive refractive power has an object-side surface 331 being convex in a paraxial region thereof and an image-side surface 332 being concave in a paraxial region thereof. The third lens element 330 is made of plastic material, and has the object-side surface 331 and the image-side surface 332 being both aspheric.

(114) The fourth lens element 340 with negative refractive power has an object-side surface 341 being concave in a paraxial region thereof and an image-side surface 342 being concave in a paraxial region thereof. The fourth lens element 340 is made of plastic material, and has the object-side surface 341 and the image-side surface 342 being both aspheric. Furthermore, the image-side surface 342 of the fourth lens element 340 includes at least one inflection point in an off-axis region thereof.

(115) The reflective element 380 and the IR-cut filter 350 are made of glass material, which are located between the fourth lens element 340 and the image surface 360 in order, and will not affect the focal length of the image capturing optical lens system.

(116) The detailed optical data of the 3rd embodiment are shown in Table 5 and the aspheric surface data are shown in Table 6 below.

(117) TABLE-US-00006 TABLE 5 3rd Embodiment $f = 13.54$ mm, $Fno = 3.96$, $HFOV = 8.5$ deg.
Focal Surface # Curvature Radius Thickness Material Index Abbe # Length 0 Object Plano Infinity
1 Stop Plano -0.466 2 Lens 1 3.352 ASP 2.500 Plastic 1.534 56.0 6.43 3 100.000 ASP 0.150 4
Lens 2 -19.324 ASP 0.952 Plastic 1.669 19.5 -9.15 5 9.135 ASP 0.162 6 Ape. Stop Plano 1.348 7
Lens 3 9.172 ASP 1.000 Plastic 1.704 14.0 14.28 8 100.000 ASP 0.054 9 Stop Plano 0.119 10 Lens
4 -11.885 ASP 1.043 Plastic 1.639 23.3 -8.27 11 9.842 ASP 1.500 12 Prism Plano 2.800 Glass
1.517 64.2 — 13 Plano 0.300 14 IR-cut filter Plano 0.210 Glass 1.517 64.2 — 15 Plano 1.113 16
Image Plano — Reference wavelength is 587.6 nm (d-line). Effective radius of Surface 1 (Stop

301) is 1.720 mm. Effective radius of Surface 9 (Stop 302) is 1.180 mm.

(118) TABLE-US-00007 TABLE 6 Aspheric Coefficients Surface # 2 3 4 5 k = 7.4671E-02
0.0000E+00 0.0000E+00 -3.2150E+00 A4 = -2.1079E-04 9.2412E-03 7.0080E-03
-6.7604E-04 A6 = 3.2173E-06 -3.4865E-03 -5.8614E-03 -3.0851E-03 A8 = 2.8121E-06
1.3122E-03 5.9631E-03 5.8295E-03 A10 = -6.8590E-06 9.4108E-04 -4.2249E-03
-5.4802E-03 A12 = 2.6795E-06 -1.5055E-03 1.9194E-03 2.9898E-03 A14 =
-3.4309E-07 8.3135E-04 -3.8499E-04 -6.8007E-04 A16 = -1.7677E-04 -2.9186E-06
-6.5703E-06 Surface # 7 8 10 11 k = 0.0000E+00 0.0000E+00 0.0000E+00 0.0000E+00 A4
= -8.0245E-03 -5.4629E-03 -1.5498E-02 -1.2332E-02 A6 = -3.5856E-03 -3.0597E-02
-3.1572E-02 -6.8675E-04 A8 = 5.0568E-03 6.2123E-02 6.5914E-02 2.8672E-03 A10 =
-7.9177E-03 -9.2284E-02 -9.5345E-02 -2.1179E-03 A12 = 9.9165E-03 9.2755E-02
9.3974E-02 1.0625E-03 A14 = -6.4463E-03 -5.0830E-02 -5.1043E-02 -4.0833E-04 A16 =
1.5965E-03 1.1227E-02 1.1235E-02 7.9216E-05

(119) In the 3rd embodiment, the equation of the aspheric surface profiles of the aforementioned lens elements is the same as the equation of the 1st embodiment. Also, the definitions of these parameters shown in the following table are the same as those stated in the 1st embodiment with corresponding values for the 3rd embodiment, so an explanation in this regard will not be provided again.

(120) Moreover, these parameters can be calculated from Table 5 and Table 6 as the following values and satisfy the following conditions:

(121) TABLE-US-00008 3rd Embodiment f [mm] 13.54 Σ AT/T23 1.21 Fno 3.96 TL/f 0.98 HFOV [degrees] 8.5 Td/BL 1.24 $\tan(2 \times \text{HFOV})$ 0.31 ImgH/EPD 0.60 V2 + V3 33.5 (R5 + R6)/(R5 - R6) -1.20 Vmin 14.0 (f/R1) + (f/R4) 5.52 V1/N1 36.48 f/|R7| + f/|R8| 2.52 V2/N2 11.65 f/ImgH 6.64 V3/N3 8.22 (|f/f1| + |f/f2|)/(|f/f3| + |f/f4|) 1.39 V4/N4 14.21 f2/f4 1.11 CT1/CT2 2.63 Y11/ImgH 0.84 Tgp 556.00 Tgp/Np 366.56

(122) Specifically, in the foregoing table, a glass transition temperature of a material of the reflective element **380** is Tgp, and a refractive index of the reflective element **380** is Np.

(123) Furthermore, FIG. 17 is a schematic view of the imaging apparatus with another reflective element **380** according to the 3rd embodiment of the present disclosure. In FIG. 17, the reflective element **380** is disposed between the fourth lens element **340** and the IR-cut filter **350**, and is a prism for folding the incident light. It should be mentioned that a maximum image height H1 of the incident light folded by the reflective element **380** is 0.6 times of a maximum image height without the reflective element **380**, but the present disclosure is not limited thereto.

4th Embodiment

(124) FIG. 7 is a schematic view of an imaging apparatus according to the 4th embodiment of the present disclosure. FIG. 8 shows spherical aberration curves, astigmatic field curves and a distortion curve of the imaging apparatus according to the 4th embodiment. In FIG. 7, the imaging apparatus includes an image capturing optical lens system (its reference numeral is omitted) and an image sensor **470**. The image capturing optical lens system includes, in order from an object side to an image side along an optical path, a stop **401**, a first lens element **410**, a second lens element **420**, an aperture stop **400**, a third lens element **430**, a stop **402**, a fourth lens element **440**, a IR-cut filter **450** and an image surface **460**, wherein the image sensor **470** is disposed on the image surface **460** of the image capturing optical lens system. The image capturing optical lens system includes four lens elements (**410**, **420**, **430**, **440**) without additional one or more lens elements inserted between the first lens element **410** and the fourth lens element **440**.

(125) The first lens element **410** with positive refractive power has an object-side surface **411** being convex in a paraxial region thereof and an image-side surface **412** being concave in a paraxial region thereof. The first lens element **410** is made of plastic material, and has the object-side surface **411** and the image-side surface **412** being both aspheric.

(126) The second lens element **420** with negative refractive power has an object-side surface **421**

being concave in a paraxial region thereof and an image-side surface **422** being concave in a paraxial region thereof. The second lens element **420** is made of plastic material, and has the object-side surface **421** and the image-side surface **422** being both aspheric.

(127) The third lens element **430** with positive refractive power has an object-side surface **431** being convex in a paraxial region thereof and an image-side surface **432** being concave in a paraxial region thereof. The third lens element **430** is made of plastic material, and has the object-side surface **431** and the image-side surface **432** being both aspheric.

(128) The fourth lens element **440** with negative refractive power has an object-side surface **441** being convex in a paraxial region thereof and an image-side surface **442** being concave in a paraxial region thereof. The fourth lens element **440** is made of plastic material, and has the object-side surface **441** and the image-side surface **442** being both aspheric. Furthermore, the image-side surface **442** of the fourth lens element **440** includes at least one inflection point in an off-axis region thereof.

(129) The IR-cut filter **450** is made of glass material, which is located between the fourth lens element **440** and the image surface **460** in order, and will not affect the focal length of the image capturing optical lens system.

(130) The detailed optical data of the 4th embodiment are shown in Table 7 and the aspheric surface data are shown in Table 8 below.

(131) TABLE-US-00009 TABLE 7 4th Embodiment $f = 11.94$ mm, $Fno = 3.49$, $HFOV = 10.7$ deg.
Focal Surface # Curvature Radius Thickness Material Index Abbe # Length 0 Object Plano Infinity
1 Stop Plano -0.585 2 Lens 1 2.777 ASP 1.700 Plastic 1.545 56.1 5.21 3 100.000 ASP 0.152 4
Lens 2 -20.421 ASP 0.850 Plastic 1.639 23.5 -5.40 5 4.212 ASP 0.276 6 Ape. Stop Plano 0.950 7
Lens 3 6.739 ASP 1.000 Plastic 1.660 20.4 15.56 8 18.450 ASP 0.124 9 Stop Plano 0.040 10 Lens 4
 22.417 ASP 1.100 Plastic 1.544 56.0 -17.06 11 6.450 ASP 4.000 12 IR-cut filter Plano 0.210 Glass
 1.517 64.2 — 13 Plano 0.743 14 Image Plano — Reference wavelength is 587.6 nm (d-line).
Effective radius of Surface 1 (Stop 401) is 1.720 mm. Effective radius of Surface 9 (Stop 402) is
 1.180 mm.

(132) TABLE-US-00010 TABLE 8 Aspheric Coefficients Surface # 2 3 4 5 $k = 1.0155E-02$
 $0.0000E+00$ $0.0000E+00$ $3.6119E+00$ $A4 = -4.2149E-04$ $-4.3861E-03$ $-3.2648E-03$
 $3.3447E-03$ $A6 = 8.2866E-04$ $2.8520E-02$ $3.1388E-02$ $7.2585E-03$ $A8 = -5.0741E-04$
 $-3.2182E-02$ $-4.1086E-02$ $-1.0987E-02$ $A10 = 2.0773E-04$ $1.9758E-02$ $2.8984E-02$
 $4.0046E-03$ $A12 = -4.0512E-05$ $-5.9580E-03$ $-1.0796E-02$ $5.0493E-03$ $A14 = 3.3008E-06$
 $6.1526E-04$ $1.8417E-03$ $-5.2013E-03$ $A16 = 2.8596E-05$ $-8.7147E-05$ $1.3824E-03$ Surface #
7 8 10 11 $k = 0.0000E+00$ $0.0000E+00$ $0.0000E+00$ $0.0000E+00$ $A4 = 1.5841E-02$ $1.4738E-02$
 $-3.1808E-02$ $-3.0431E-02$ $A6 = 6.4878E-03$ $4.1595E-02$ $5.3300E-02$ $1.6877E-02$ $A8 =$
 $-2.0240E-02$ $-1.2282E-01$ $-1.5419E-01$ $-3.3516E-02$ $A10 = 2.8532E-02$ $1.8798E-01$
 $2.3312E-01$ $4.1720E-02$ $A12 = -2.1695E-02$ $-1.5332E-01$ $-1.8840E-01$ $-2.8710E-02$ $A14$
 $= 8.5801E-03$ $6.3946E-02$ $7.7650E-02$ $1.0162E-02$ $A16 = -1.3952E-03$ $-1.0775E-02$
 $-1.2861E-02$ $-1.4456E-03$

(133) In the 4th embodiment, the equation of the aspheric surface profiles of the aforementioned lens elements is the same as the equation of the 1st embodiment. Also, the definitions of these parameters shown in the following table are the same as those stated in the 1st embodiment with corresponding values for the 4th embodiment, so an explanation in this regard will not be provided again.

(134) Moreover, these parameters can be calculated from Table 7 and Table 8 as the following values and satisfy the following conditions:

(135) TABLE-US-00011 4th Embodiment f [mm] 11.94 $\Sigma AT/T23$ 1.26 Fno 3.49 TL/f 0.93 $HFOV$
[degrees] 10.7 Td/BL 1.25 $\tan(2 \times HFOV)$ 0.39 $ImgH/EPD$ 0.67 $V2 + V3$ 43.9 $(R5 + R6)/(R5 -$
 $R6)$ -2.15 $Vmin$ 20.4 $(f/R1) + (f/R4)$ 7.14 $V1/N1$ 36.30 $f/|R7| + f/|R8|$ 2.38 $V2/N2$ 14.34 $f/ImgH$
 5.23 $V3/N3$ 12.29 $(|f/f1| + |f/f2|)/(|f/f3| + |f/f4|)$ 3.07 $V4/N4$ 36.26 $f2/f4$ 0.32 $CT1/CT2$ 2.00

5th Embodiment

(136) FIG. 9 is a schematic view of an imaging apparatus according to the 5th embodiment of the present disclosure. FIG. 10 shows spherical aberration curves, astigmatic field curves and a distortion curve of the imaging apparatus according to the 5th embodiment. In FIG. 9, the imaging apparatus includes an image capturing optical lens system (its reference numeral is omitted) and an image sensor 570. The image capturing optical lens system includes, in order from an object side to an image side along an optical path, an aperture stop 500, a first lens element 510, a second lens element 520, a stop 501, a third lens element 530, a stop 502, a fourth lens element 540, a IR-cut filter 550 and an image surface 560, wherein the image sensor 570 is disposed on the image surface 560 of the image capturing optical lens system. The image capturing optical lens system includes four lens elements (510, 520, 530, 540) without additional one or more lens elements inserted between the first lens element 510 and the fourth lens element 540.

(137) The first lens element 510 with positive refractive power has an object-side surface 511 being convex in a paraxial region thereof and an image-side surface 512 being concave in a paraxial region thereof. The first lens element 510 is made of plastic material, and has the object-side surface 511 and the image-side surface 512 being both aspheric.

(138) The second lens element 520 with negative refractive power has an object-side surface 521 being concave in a paraxial region thereof and an image-side surface 522 being concave in a paraxial region thereof. The second lens element 520 is made of plastic material, and has the object-side surface 521 and the image-side surface 522 being both aspheric.

(139) The third lens element 530 with positive refractive power has an object-side surface 531 being convex in a paraxial region thereof and an image-side surface 532 being concave in a paraxial region thereof. The third lens element 530 is made of plastic material, and has the object-side surface 531 and the image-side surface 532 being both aspheric.

(140) The fourth lens element 540 with negative refractive power has an object-side surface 541 being concave in a paraxial region thereof and an image-side surface 542 being convex in a paraxial region thereof. The fourth lens element 540 is made of plastic material, and has the object-side surface 541 and the image-side surface 542 being both aspheric.

(141) The IR-cut filter 550 is made of glass material, which is located between the fourth lens element 540 and the image surface 560 in order, and will not affect the focal length of the image capturing optical lens system.

(142) The detailed optical data of the 5th embodiment are shown in Table 9 and the aspheric surface data are shown in Table 10 below.

(143) TABLE-US-00012 TABLE 9 5th Embodiment $f = 12.10$ mm, $Fno = 3.54$, $HFOV = 9.5$ deg.
 Focal Surface # Curvature Radius Thickness Material Index Abbe # Length 0 Object Plano Infinity
 1 Ape. Stop Plano -0.593 2 Lens 1 2.756 ASP 1.700 Plastic 1.545 56.1 5.17 3 100.000 ASP 0.129 4
 Lens 2 -100.000 ASP 0.790 Plastic 1.639 23.5 -5.02 5 3.322 ASP 0.310 6 Stop Plano 1.172 7 Lens
 3 4.034 ASP 0.981 Plastic 1.660 20.4 15.54 8 6.007 ASP 0.210 9 Stop Plano 0.194 10 Lens 4
 -6.573 ASP 0.649 Plastic 1.544 56.0 -26.02 11 -12.697 ASP 4.000 12 IR-cut filter Plano 0.210
 Glass 1.517 64.2 — 13 Plano 0.909 14 Image Plano — Reference wavelength is 587.6 nm (d-line).
 Effective radius of Surface 6 (Stop 501) is 1.170 mm. Effective radius of Surface 9 (Stop 502) is
 1.185 mm.

(144) TABLE-US-00013 TABLE 10 Aspheric Coefficients Surface # 2 3 4 5 $k = 1.5689E-01$
 $0.0000E+00$ $0.0000E+00$ $1.8156E+00$ $A4 = -6.8150E-04$ $1.0706E-02$ $8.3545E-03$ $2.5211E-04$
 $A6 = -1.4168E-04$ $-9.5208E-03$ $-1.1302E-02$ $-3.7217E-03$ $A8 = 9.6980E-05$ $1.5128E-02$
 $1.8527E-02$ $6.6058E-03$ $A10 = -2.5282E-05$ $-1.1799E-02$ $-1.5847E-02$ $-5.9111E-03$ $A12$
 $= 2.9856E-06$ $5.1041E-03$ $7.4184E-03$ $1.9231E-03$ $A14 = 3.6815E-07$ $-1.1607E-03$
 $-1.8165E-03$ $2.1159E-04$ $A16 = 1.1188E-04$ $1.8447E-04$ $-1.7870E-04$ Surface # 7 8 10 11 k
 $= 0.0000E+00$ $0.0000E+00$ $0.0000E+00$ $0.0000E+00$ $A4 = 8.3513E-03$ $1.5231E-02$

-2.171E-02 -1.9936E-02 A6 = -3.6837E-04 1.6132E-03 2.0843E-03 1.0817E-03 A8 = 2.2584E-03 1.0388E-03 -7.8798E-03 -2.2250E-03 A10 = -3.0237E-03 5.5471E-03 2.2036E-02 3.4829E-03 A12 = 1.8103E-03 -1.1114E-02 -2.7074E-02 -3.3634E-03 A14 = -5.7741E-04 6.9069E-03 1.4306E-02 1.4594E-03 A16 = 8.1690E-05 -1.4873E-03 -2.8310E-03 -2.3515E-04

(145) In the 5th embodiment, the equation of the aspheric surface profiles of the aforementioned lens elements is the same as the equation of the 1st embodiment. Also, the definitions of these parameters shown in the following table are the same as those stated in the 1st embodiment with corresponding values for the 5th embodiment, so an explanation in this regard will not be provided again.

(146) Moreover, these parameters can be calculated from Table 9 and Table 10 as the following values and satisfy the following conditions:

(147) TABLE-US-00014 5th Embodiment f [mm] 12.10 Σ AT/T23 1.36 Fno 3.54 TL/f 0.93 HFOV [degrees] 9.5 Td/BL 1.20 $\tan(2 \times \text{HFOV})$ 0.34 ImgH/EPD 0.60 V2 + V3 43.9 (R5 + R6)/(R5 - R6) -5.09 Vmin 20.4 (f/R1) + (f/R4) 8.03 V1/N1 36.30 f/|R7| + f/|R8| 2.79 V2/N2 14.34 f/ImgH 5.93 V3/N3 12.29 (|f/f1| + |f/f2|)/(|f/f3| + |f/f4|) 3.82 V4/N4 36.26 f2/f4 0.19 CT1/CT2 2.15 Y11/ImgH 0.84

6th Embodiment

(148) FIG. 11 is a schematic view of an imaging apparatus according to the 6th embodiment of the present disclosure. FIG. 12 shows spherical aberration curves, astigmatic field curves and a distortion curve of the imaging apparatus according to the 6th embodiment. In FIG. 11, the imaging apparatus includes an image capturing optical lens system (its reference numeral is omitted) and an image sensor 670. The image capturing optical lens system includes, in order from an object side to an image side along an optical path, a first lens element 610, a second lens element 620, an aperture stop 600, a third lens element 630, a fourth lens element 640, a IR-cut filter 650 and an image surface 660, wherein the image sensor 670 is disposed on the image surface 660 of the image capturing optical lens system. The image capturing optical lens system includes four lens elements (610, 620, 630, 640) without additional one or more lens elements inserted between the first lens element 610 and the fourth lens element 640.

(149) The first lens element 610 with positive refractive power has an object-side surface 611 being convex in a paraxial region thereof and an image-side surface 612 being convex in a paraxial region thereof. The first lens element 610 is made of plastic material, and has the object-side surface 611 and the image-side surface 612 being both aspheric.

(150) The second lens element 620 with negative refractive power has an object-side surface 621 being concave in a paraxial region thereof and an image-side surface 622 being concave in a paraxial region thereof. The second lens element 620 is made of plastic material, and has the object-side surface 621 and the image-side surface 622 being both aspheric.

(151) The third lens element 630 with positive refractive power has an object-side surface 631 being convex in a paraxial region thereof and an image-side surface 632 being concave in a paraxial region thereof. The third lens element 630 is made of plastic material, and has the object-side surface 631 and the image-side surface 632 being both aspheric.

(152) The fourth lens element 640 with negative refractive power has an object-side surface 641 being concave in a paraxial region thereof and an image-side surface 642 being concave in a paraxial region thereof. The fourth lens element 640 is made of plastic material, and has the object-side surface 641 and the image-side surface 642 being both aspheric. Furthermore, the image-side surface 642 of the fourth lens element 640 includes at least one inflection point and at least one critical point in an off-axis region thereof.

(153) The IR-cut filter 650 is made of glass material, which is located between the fourth lens element 640 and the image surface 660 in order, and will not affect the focal length of the image capturing optical lens system.

(154) The detailed optical data of the 6th embodiment are shown in Table 11 and the aspheric surface data are shown in Table 12 below.

(155) TABLE-US-00015 TABLE 11 6th Embodiment $f = 19.65$ mm, $Fno = 3.57$, $HFOV = 9.4$ deg.
Focal Surface # Curvature Radius Thickness Material Index Abbe # Length 0 Object Plano Infinity
1 Lens 1 8.948 ASP 2.357 Plastic 1.544 56.0 10.21 2 -13.279 ASP 0.050 3 Lens 2 -19.410 ASP
1.346 Plastic 1.639 23.5 -12.84 4 14.576 ASP 0.220 5 Ape. Stop Plano 6.096 6 Lens 3 9.369 ASP
2.049 Plastic 1.686 18.4 15.29 7 79.914 ASP 3.830 8 Lens 4 -38.844 ASP 0.622 Plastic 1.704 14.0
-10.75 9 9.465 ASP 4.000 10 IR-cut filter Plano 0.210 Glass 1.517 64.2 — 11 Plano 0.676 12
Image Plano — Reference wavelength is 587.6 nm (d-line).

(156) TABLE-US-00016 TABLE 12 Aspheric Coefficients Surface # 1 2 3 4 $k = 5.9507E-01$
0.0000E+00 0.0000E+00 -3.2707E+01 $A4 = -8.8785E-06$ 2.6045E-04 -1.6730E-03
-7.7081E-04 $A6 = 3.3324E-06$ 5.8615E-05 1.3190E-04 -4.0313E-06 $A8 = -1.7636E-06$
-3.5778E-05 -1.0591E-05 4.1554E-05 $A10 = -5.8212E-08$ 7.4250E-06 -3.9711E-07
-1.4088E-05 $A12 = 6.7254E-08$ -7.5316E-08 1.0763E-06 2.6805E-06 $A14 =$
-8.4833E-09 -1.1700E-07 -2.0899E-07 -2.7661E-07 $A16 = 3.3037E-10$ 8.5548E-09
1.1800E-08 1.1878E-08 Surface# 6 7 8 9 $k = 0.0000E+00$ 0.0000E+00 0.0000E+00
0.0000E+00 $A4 = -7.3040E-04$ -1.1632E-03 -1.6055E-02 -1.5543E-02 $A6 = -8.0747E-06$
4.4633E-06 1.7845E-03 2.2583E-03 $A8 = 1.0747E-06$ -4.2799E-07 -1.6293E-04
-2.8613E-04 $A10 = -5.6075E-07$ -4.1366E-07 9.9086E-06 3.0567E-05 $A12 = 9.9569E-08$
1.0149E-07 1.8061E-07 -2.3232E-06 $A14 = -8.7297E-09$ -1.0262E-08 -8.3706E-08
1.0464E-07 $A16 = 2.8394E-10$ 3.6520E-10 4.0992E-09 -2.0767E-09

(157) In the 6th embodiment, the equation of the aspheric surface profiles of the aforementioned lens elements is the same as the equation of the 1st embodiment. Also, the definitions of these parameters shown in the following table are the same as those stated in the 1st embodiment with corresponding values for the 6th embodiment, so an explanation in this regard will not be provided again.

(158) Moreover, these parameters can be calculated from Table 11 and Table 12 as the following values and satisfy the following conditions:

(159) TABLE-US-00017 6th Embodiment f [mm] 19.65 $\Sigma AT/T23$ 1.61 Fno 3.57 TL/f 1.09 $HFOV$ [degrees] 9.4 Td/BL 3.39 $\tan(2 \times HFOV)$ 0.34 $ImgH/EPD$ 0.60 $V2 + V3$ 41.9 $(R5 + R6)/(R5 - R6)$ -1.27 $Vmin$ 14.0 $(f/R1) + (f/R4)$ 3.54 $V1/N1$ 36.26 $f/|R7| + f/|R8|$ 2.58 $V2/N2$ 14.34 $f/ImgH$ 5.99 $V3/N3$ 10.90 $(|f/f1| + |f/f2|)/(|f/f3| + |f/f4|)$ 1.11 $V4/N4$ 8.22 $f2/f4$ 1.19 $CT1/CT2$ 1.75 $Y11/ImgH$ 0.96

7th Embodiment

(160) FIG. 13 is a schematic view of an imaging apparatus according to the 7th embodiment of the present disclosure. FIG. 14 shows spherical aberration curves, astigmatic field curves and a distortion curve of the imaging apparatus according to the 7th embodiment. In FIG. 13, the imaging apparatus includes an image capturing optical lens system (its reference numeral is omitted) and an image sensor 770. The image capturing optical lens system includes, in order from an object side to an image side along an optical path, a reflective element 780, a first lens element 710, a second lens element 720, an aperture stop 700, a third lens element 730, a fourth lens element 740, a IR-cut filter 750 and an image surface 760, wherein the image sensor 770 is disposed on the image surface 760 of the image capturing optical lens system. The image capturing optical lens system includes four lens elements (710, 720, 730, 740) without additional one or more lens elements inserted between the first lens element 710 and the fourth lens element 740.

(161) The first lens element 710 with positive refractive power has an object-side surface 711 being convex in a paraxial region thereof and an image-side surface 712 being convex in a paraxial region thereof. The first lens element 710 is made of plastic material, and has the object-side surface 711 and the image-side surface 712 being both aspheric.

(162) The second lens element 720 with negative refractive power has an object-side surface 721

being concave in a paraxial region thereof and an image-side surface **722** being concave in a paraxial region thereof. The second lens element **720** is made of plastic material, and has the object-side surface **721** and the image-side surface **722** being both aspheric.

(163) The third lens element **730** with positive refractive power has an object-side surface **731** being convex in a paraxial region thereof and an image-side surface **732** being concave in a paraxial region thereof. The third lens element **730** is made of plastic material, and has the object-side surface **731** and the image-side surface **732** being both aspheric.

(164) The fourth lens element **740** with negative refractive power has an object-side surface **741** being concave in a paraxial region thereof and an image-side surface **742** being concave in a paraxial region thereof. The fourth lens element **740** is made of plastic material, and has the object-side surface **741** and the image-side surface **742** being both aspheric. Furthermore, the image-side surface **742** of the fourth lens element **740** includes at least one inflection point and at least one critical point in an off-axis region thereof.

(165) The IR-cut filter **750** is made of glass material, which is located between the fourth lens element **740** and the image surface **760** in order, and will not affect the focal length of the image capturing optical lens system.

(166) The reflective element **780** is disposed on an object side of the first lens element **710** along the optical path, wherein the reflective element **780** has positive refractive power, one surface **781** of the reflective element **780** facing towards an imaged object is convex in a paraxial region thereof. The reflective element **780** is made of plastic material.

(167) The detailed optical data of the 7th embodiment are shown in Table 13 and the aspheric surface data are shown in Table 14 below.

(168) TABLE-US-00018 TABLE 13 7th Embodiment $f = 23.09$ mm, $Fno = 4.20$, $HFOV = 8.0$ deg.
Focal Surface # Curvature Radius Thickness Material Index Abbe # Length 0 Object Plano Infinity
1 Prism 17.129 8.000 Plastic 1.534 56.0 32.06 2 Plano 0.200 3 Lens 1 19.411 ASP 1.671 Plastic
1.534 56.0 16.20 4 -15.150 ASP 0.050 5 Lens 2 -28.667 ASP 0.827 Plastic 1.634 23.8 -14.79 6
14.096 ASP 0.184 7 Ape. Stop Plano 8.392 8 Lens 3 10.843 ASP 2.222 Plastic 1.678 17.6 18.27 9
79.914 ASP 3.637 10 Lens 4 -58.507 ASP 0.619 Plastic 1.704 14.0 -11.66 11 9.588 ASP 3.000 12
IR-cut filter Plano 0.210 Glass 1.516 64.2 — 13 Plano 0.555 14 Image Plano — Reference
wavelength is 587.6 nm (d-line).

(169) TABLE-US-00019 TABLE 14 Aspheric Coefficients Surface # 3 4 5 6 $k = -2.8524E+00$
 $0.0000E+00$ $0.0000E+00$ $-4.3351E+01$ $A4 = -1.7842E-05$ $1.1673E-03$ $-1.4985E-03$
 $-9.1057E-04$ $A6 = 2.1560E-07$ $-8.3078E-04$ $-5.4902E-04$ $-4.1964E-05$ $A8 = -1.4869E-05$
 $2.1616E-04$ $2.2378E-04$ $7.0557E-05$ $A10 = 4.6001E-06$ $-8.2765E-06$ $-2.0336E-05$
 $-2.2061E-05$ $A12 = -7.3799E-07$ $-5.5607E-06$ $-2.7154E-06$ $4.2236E-06$ $A14 = 5.9198E-08$
 $8.9193E-07$ $5.7089E-07$ $-4.9909E-07$ $A16 = -1.9946E-09$ $-4.1872E-08$ $-2.6650E-08$
 $2.6751E-08$ Surface# 8 9 10 11 $k = 0.0000E+00$ $0.0000E+00$ $0.0000E+00$ $0.0000E+00$ $A4 =$
 $-5.2375E-04$ $-9.5231E-04$ $-1.3183E-02$ $-1.3049E-02$ $A6 = 1.3809E-05$ $3.6623E-05$
 $1.4673E-03$ $1.7879E-03$ $A8 = -1.1965E-06$ $-2.6363E-06$ $-1.1231E-04$ $-2.0272E-04$ $A10 =$
 $-1.2228E-07$ $-2.7991E-07$ $6.2188E-07$ $1.6560E-05$ $A12 = 3.9502E-08$ $8.6377E-08$
 $9.2207E-07$ $-8.5939E-07$ $A14 = -3.3605E-09$ $-7.3717E-09$ $-8.6284E-08$ $2.4059E-08$ $A16 =$
 $9.1404E-11$ $2.0717E-10$ $2.5080E-09$ $-2.7470E-10$

(170) In the 7th embodiment, the equation of the aspheric surface profiles of the aforementioned lens elements is the same as the equation of the 1st embodiment. Also, the definitions of these parameters shown in the following table are the same as those stated in the 1st embodiment with corresponding values for the 7th embodiment, so an explanation in this regard will not be provided again.

(171) Moreover, these parameters can be calculated from Table 13 and Table 14 as the following values and satisfy the following conditions:

(172) TABLE-US-00020 7th Embodiment f [mm] 23.09 $\Sigma AT/T23$ 1.43 Fno 4.20 TL/f 0.93 $HFOV$

[degrees] 8.0 Td/BL 4.67 $\tan(2 \times \text{HFOV})$ 0.29 ImgH/EPD 0.60 $V2 + V3$ 41.5 $(R5 + R6)/(R5 - R6)$ -1.31 V_{min} 14.0 $(f/R1) + (f/R4)$ 2.83 $V1/N1$ 36.48 $f/|R7| + f/|R8|$ 2.80 $V2/N2$ 14.59 f/ImgH 7.04 $V3/N3$ 10.51 $(|f/f1| + |f/f2|)/(|f/f3| + |f/f4|)$ 0.92 $V4/N4$ 8.22 $f2/f4$ 1.27 $CT1/CT2$ 2.02 $Y11/\text{ImgH}$ 0.79 T_{gp} 143.00 $T_{\text{gp}}/N_{\text{p}}$ 93.23

(173) Furthermore, FIG. 18 is a schematic view of the imaging apparatus with another reflective element 780 according to the 7th embodiment of the present disclosure. In FIG. 18, the reflective element 780 is disposed on the object side of the first lens element 710 along the optical path, and is a prism for folding the incident light. It should be mentioned that a maximum image height H1 of the incident light folded by the reflective element 780 is 0.6 times of a maximum image height without the reflective element 780, but the present disclosure is not limited thereto.

8th Embodiment

(174) FIG. 15 is a schematic view of an imaging apparatus according to the 8th embodiment of the present disclosure. FIG. 16 shows spherical aberration curves, astigmatic field curves and a distortion curve of the imaging apparatus according to the 8th embodiment. In FIG. 15, the imaging apparatus includes an image capturing optical lens system (its reference numeral is omitted) and an image sensor 870. The image capturing optical lens system includes, in order from an object side to an image side along an optical path, a stop 801, a first lens element 810, a second lens element 820, an aperture stop 800, a third lens element 830, a fourth lens element 840, a IR-cut filter 850 and an image surface 860, wherein the image sensor 870 is disposed on the image surface 860 of the image capturing optical lens system. The image capturing optical lens system includes four lens elements (810, 820, 830, 840) without additional one or more lens elements inserted between the first lens element 810 and the fourth lens element 840.

(175) The first lens element 810 with positive refractive power has an object-side surface 811 being convex in a paraxial region thereof and an image-side surface 812 being convex in a paraxial region thereof. The first lens element 810 is made of plastic material, and has the object-side surface 811 and the image-side surface 812 being both aspheric.

(176) The second lens element 820 with negative refractive power has an object-side surface 821 being convex in a paraxial region thereof and an image-side surface 822 being concave in a paraxial region thereof. The second lens element 820 is made of plastic material, and has the object-side surface 821 and the image-side surface 822 being both aspheric.

(177) The third lens element 830 with positive refractive power has an object-side surface 831 being convex in a paraxial region thereof and an image-side surface 832 being concave in a paraxial region thereof. The third lens element 830 is made of plastic material, and has the object-side surface 831 and the image-side surface 832 being both aspheric.

(178) The fourth lens element 840 with positive refractive power has an object-side surface 841 being convex in a paraxial region thereof and an image-side surface 842 being convex in a paraxial region thereof. The fourth lens element 840 is made of plastic material, and has the object-side surface 841 and the image-side surface 842 being both aspheric.

(179) The IR-cut filter 850 is made of glass material, which is located between the fourth lens element 840 and the image surface 860 in order, and will not affect the focal length of the image capturing optical lens system.

(180) The detailed optical data of the 8th embodiment are shown in Table 15 and the aspheric surface data are shown in Table 16 below.

(181) TABLE-US-00021 TABLE 15 8th Embodiment $f = 12.30$ mm, $F_{\text{no}} = 3.60$, $\text{HFOV} = 9.4$ deg.

Focal Surface #	Curvature	Radius	Thickness	Material	Index	Abbe #	Length	0	Object	Plano	Infinity	
1	Stop	Plano	-0.625									
2	Lens 1	2.617	ASP	2.500	Plastic	1.544	55.9	4.13	3	-10.524	ASP	0.030
4	Lens 2	23.415	ASP	0.827	Glass	1.839	23.9	-2.40	5	1.823	ASP	0.330
6	Ape. Stop	Plano	0.200									
7	Lens 3	6.062	ASP	1.013	Plastic	1.704	14.0	11.98	8	20.072	ASP	0.109
9	Lens 4	17.200	ASP	1.100	Plastic	1.584	28.2	25.20	10	-100.000	ASP	0.500
11	IR-cut filter	Plano	0.210	Glass	1.517	64.2	—					
12	Plano	4.508										
13	Image	Plano	—									

Reference wavelength is 587.6 nm (d-line). Effective radius of

Surface 1 (Stop 801) is 1.720 mm.

(182) TABLE-US-00022 TABLE 16 Aspheric Coefficients Surface# 2 3 4 5 k = $-3.7079\text{E}-02$
 $0.0000\text{E}+00$ $0.0000\text{E}+00$ $-1.1687\text{E}+00$ $A4 = -3.0083\text{E}-04$ $3.6269\text{E}-02$ $2.0681\text{E}-03$ $8.9150\text{E}-03$
 $A6 = 1.8716\text{E}-06$ $-8.9619\text{E}-02$ $-5.8054\text{E}-02$ $-5.8307\text{E}-03$ $A8 = -2.0284\text{E}-05$ $1.4222\text{E}-01$
 $9.2919\text{E}-02$ $2.1259\text{E}-02$ $A10 = -2.1550\text{E}-05$ $-1.1977\text{E}-01$ $-6.0577\text{E}-02$ $1.9508\text{E}-02$ $A12 =$
 $1.2416\text{E}-05$ $5.6369\text{E}-02$ $1.3120\text{E}-02$ $6.3503\text{E}-03$ $A14 = -2.2556\text{E}-06$ $-1.5231\text{E}-02$
 $1.7719\text{E}-03$ $-6.1589\text{E}-02$ $A16 = 1.9304\text{E}-03$ $-8.2882\text{E}-04$ $3.5625\text{E}-02$ Surface# 7 8 9 10 k =
 $0.0000\text{E}+00$ $0.0000\text{E}+00$ $0.0000\text{E}+00$ $0.0000\text{E}+00$ $A4 = 3.4450\text{E}-02$ $4.6515\text{E}-02$ $1.0745\text{E}-02$
 $-2.0278\text{E}-02$ $A6 = -1.4202\text{E}-02$ $-3.1379\text{E}-02$ $-2.0807\text{E}-02$ $1.2707\text{E}-03$ $A8 = 1.3390\text{E}-03$
 $1.0290\text{E}-02$ $-9.2100\text{E}-03$ $-3.9188\text{E}-04$ $A10 = 3.9190\text{E}-02$ $6.4560\text{E}-02$ $9.8966\text{E}-02$
 $1.0269\text{E}-03$ $A12 = -3.4280\text{E}-02$ $-3.6504\text{E}-02$ $-8.1078\text{E}-02$ $1.9862\text{E}-04$ $A14 = 2.2093\text{E}-03$
 $-1.7447\text{E}-02$ $1.6010\text{E}-02$ $-5.9930\text{E}-04$ $A16 = 4.0198\text{E}-03$ $1.0948\text{E}-02$ $1.4588\text{E}-03$
 $1.6612\text{E}-04$

(183) In the 8th embodiment, the equation of the aspheric surface profiles of the aforementioned lens elements is the same as the equation of the 1st embodiment. Also, the definitions of these parameters shown in the following table are the same as those stated in the 1st embodiment with corresponding values for the 8th embodiment, so an explanation in this regard will not be provided again.

(184) Moreover, these parameters can be calculated from Table 15 and Table 16 as the following values and satisfy the following conditions:

(185) TABLE-US-00023 8th Embodiment f [mm] 12.30 Σ AT/T23 1.26 Fno 3.60 TL/f 0.92 HFOV [degrees] 9.4 Td/BL 1.17 $\tan(2 \times \text{HFOV})$ 0.34 ImgH/EPD 0.60 $V2 + V3$ 37.9 $(R5 + R6)/(R5 - R6)$ -1.87 $V_{\min}$ 14.0 $(f/R1) + (f/R4)$ 11.45 $V1/N1$ 36.23 $f/|R7| + f/|R8|$ 0.84 $V2/N2$ 12.97 f/ImgH 6.03 $V3/N3$ 8.22 $(|f/f1| + |f/f2|)/(|f/f3| + |f/f4|)$ 5.35 $V4/N4$ 17.83 $f2/f4$ -0.10 CT1/CT2 3.02 $Y11/\text{ImgH}$ 0.84

9th Embodiment

(186) FIG. 19A and FIG. 19B are schematic views of light blocking elements 990 of an imaging apparatus according to the 9th embodiment of present disclosure. In FIG. 19A and FIG. 19B, the imaging apparatus can includes the light blocking element 990, which can be disposed the image capturing optical lens system of the imaging apparatus of any one of the 1st to the 8th embodiment, and can be disposed between any two adjacent elements, but the present disclosure will not be limited thereto.

(187) In detail, in FIG. 19A, the light blocking element 990 includes an opening 9901 and two cutting side portions 9902, wherein two sides of the opening 9901 in FIG. 19A are arc-shaped; in FIG. 19B, the light blocking element 990 includes an opening 9901 and two cutting side portions 9902, wherein the opening 9901 in FIG. 19B is square-shaped. In FIG. 19A and FIG. 19B, the light blocking elements 990 have different shapes of non-circular inner holes, but the present disclosure will not be limited thereto.

10th Embodiment

(188) FIG. 20 is a schematic view of a first lens element 1010 of an imaging apparatus according to the 10th embodiment of present disclosure. In FIG. 20, the arrangement of the imaging apparatus is the same with the arrangement of the imaging apparatus according to the aforementioned 4th embodiment, except the first lens element 1010 includes two uniaxial trimmed sides 1011, which form a non-circular lens element, but the present disclosure will not be limited thereto.

11th Embodiment

(189) FIG. 21 is a schematic view of a first lens element 1110 of an imaging apparatus according to the 11th embodiment of present disclosure. In FIG. 21, the arrangement of the imaging apparatus is the same with the arrangement of the imaging apparatus according to the aforementioned 1st embodiment, except the first lens element 1110 includes four uniaxial trimmed sides 1111, which form a non-circular lens element, but the present disclosure will not be limited thereto.

12th Embodiment

(190) FIG. 22 is a schematic view of an imaging apparatus **10** according to the 12th embodiment of the present disclosure. In FIG. 22, the imaging apparatus **10** of the 12th embodiment is a camera module, the imaging apparatus **10** includes an imaging lens assembly **11**, a driving apparatus **12** and an image sensor **13**, wherein the imaging lens assembly **11** includes the image capturing optical lens system of the present disclosure and a lens barrel (not shown in drawings) for carrying the image capturing optical lens system. The imaging apparatus **10** can focus light from an imaged object via the imaging lens assembly **11**, perform image focusing by the driving apparatus **12**, and generate an image on the image sensor **13**, and the imaging information can be transmitted.

(191) The driving apparatus **12** can be an auto-focus module, which can be driven by driving systems, such as voice coil motors (VCM), micro electro-mechanical systems (MEMS), piezoelectric systems, and shape memory alloys etc. The image capturing optical lens system can obtain a favorable imaging position by the driving apparatus **12** so as to capture clear images when the imaged object is disposed at different object distances.

(192) The imaging apparatus **10** can include the image sensor **13** located on the image surface of the image capturing lens assembly, such as CMOS and CCD, with superior photosensitivity and low noise. Thus, it is favorable for providing realistic images with high definition image quality thereof.

(193) Moreover, the imaging apparatus **10** can further include an image stabilization module **14**, which can be a kinetic energy sensor, such as an accelerometer, a gyro sensor, and a Hall Effect sensor. In the 12th embodiment, the image stabilization module **14** is a gyro sensor, but is not limited thereto. Therefore, the variation of different axial directions of the image capturing optical lens system can adjusted so as to compensate the image blur generated by motion at the moment of exposure, and it is further favorable for enhancing the image quality while photographing in motion and low light situation. Furthermore, advanced image compensation functions, such as optical image stabilizations (OIS) and electronic image stabilizations (EIS) etc., can be provided.

13th Embodiment

(194) FIG. 23A is a schematic view of one side of an electronic device **20** according to the 13th embodiment of the present disclosure. FIG. 23B is a schematic view of another side of the electronic device **20** of FIG. 23A. FIG. 23C is a system schematic view of the electronic device **20** of FIG. 23A. In FIGS. 23A, 23B and 23C, the electronic device **20** according to the 13th embodiment is a smartphone, which include imaging apparatuses **10**, **10a**, **10b**, **10c**, **10d**, a flash module **21**, a focusing assisting module **22**, an image signal processor (ISP) **23**, a user interface **24** and an image software processor **25**, wherein each of the imaging apparatuses **10b**, **10c**, **10d** is a front camera. When the user captures images of an imaged object **26** via the user interface **24**, the electronic device **20** focuses and generates an image via at least one of the imaging apparatuses **10**, **10a**, **10b**, **10c**, **10d** while compensating for low illumination via the flash module **21** when necessary. Then, the electronic device **20** quickly focuses on the imaged object **26** according to its object distance information provided by the focusing assisting module **22**, and optimizes the image via the image signal processor **23** and the image software processor **25**. Thus, the image quality can be further enhanced. The focusing assisting module **22** can adopt conventional infrared or laser for obtaining quick focusing, and the user interface **24** can utilize a touch screen or a physical button for capturing and processing the image with various functions of the image processing software.

(195) Each of the imaging apparatuses **10**, **10a**, **10b**, **10c**, **10d** according to the 13th embodiment can include the image capturing optical lens system of the present disclosure, and can be the same or similar to the imaging apparatus **10** according to the aforementioned 12th embodiment, and will not describe again herein. In detail, according to the 13th embodiment, the imaging apparatuses **10**, **10a** can be wide angle imaging apparatus and ultra-wide angle imaging apparatus, respectively. The imaging apparatuses **10b**, **10c**, **10d** can be wide angle imaging apparatus, ultra-wide angle imaging apparatus and TOF (Time-Of-Flight) module, respectively, which will not be limited thereto.

Further, the connecting relationships between each of the imaging apparatuses **10a**, **10b**, **10c**, **10d** and other elements can be the same as the imaging apparatus **10** in FIG. **23C**, or can be adaptively adjusted according to the type of the imaging apparatuses, which will not be shown and detailed described again.

14th Embodiment

(196) FIG. **24** is a schematic view of one side of an electronic device **30** according to the 14th embodiment of the present disclosure. According to the 14th embodiment, the electronic device **30** is a smartphone, which include imaging apparatuses **30a**, **30b**, **30c** and a flash module **31**.

(197) The electronic device **30** according to the 14th embodiment can include the same or similar elements to that according to the 13th embodiment, and each of the imaging apparatuses **30a**, **30b**, **30c** according to the 14th embodiment can have a configuration which is the same or similar to that according to the 13th embodiment, and will not describe again herein. In detail, according to the 14th embodiment, each of the imaging apparatuses **30a**, **30b**, **30c** can include the image capturing optical lens system of the present disclosure, and can be the same or similar to the imaging apparatus **10** according to the aforementioned 12th embodiment, and will not describe again herein. In detail, the imaging apparatuses **30a**, **30b**, **30c** can be ultra-wide angle imaging apparatus, wide angle imaging apparatus and telephoto imaging apparatus (which can include light path folding element), respectively, or can be adaptively adjusted according to the type of the imaging apparatuses, which will not be limited to the arrangement.

15th Embodiment

(198) FIG. **25** is a schematic view of one side of an electronic device **40** according to the 15th embodiment of the present disclosure. According to the 15th embodiment, the electronic device **40** is a smartphone, which include imaging apparatuses **40a**, **40b**, **40c**, **40d**, **40e**, **40f**, **40g**, **40h**, **40i** and a flash module **41**.

(199) The electronic device **40** according to the 15th embodiment can include the same or similar elements to that according to the 13th embodiment, and each of the imaging apparatuses **40a**, **40b**, **40c**, **40d**, **40e**, **40f**, **40g**, **40h**, **40i** and the flash module **41** can have a configuration which is the same or similar to that according to the 13th embodiment, and will not describe again herein. In detail, according to the 15th embodiment, each of the imaging apparatuses **40a**, **40b**, **40c**, **40d**, **40e**, **40f**, **40g**, **40h**, **40i** can include the image capturing optical lens system of the present disclosure, and can be the same or similar to the imaging apparatus **10** according to the aforementioned 12th embodiment, and will not describe again herein.

(200) In detail, each of the imaging apparatuses **40a**, **40b** can be ultra-wide angle imaging apparatus, each of the imaging apparatuses **40c**, **40d** can be wide angle imaging apparatus, each of the imaging apparatuses **40e**, **40f** can be telephoto imaging apparatus, each of the imaging apparatuses **40g**, **40h** can be telephoto imaging apparatus (which can include light path folding element), the imaging apparatus **40i** can be TOF module, or can be adaptively adjusted according to the type of the imaging apparatuses, which will not be limited to the arrangement.

(201) The foregoing description, for purpose of explanation, has been described with reference to specific embodiments. It is to be noted that Tables show different data of the different embodiments; however, the data of the different embodiments are obtained from experiments. The embodiments were chosen and described in order to best explain the principles of the disclosure and its practical applications, to thereby enable others skilled in the art to best utilize the disclosure and various embodiments with various modifications as are suited to the particular use contemplated. The embodiments depicted above and the appended drawings are exemplary and are not intended to be exhaustive or to limit the scope of the present disclosure to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings.

Claims

1. An image capturing optical lens system comprising four lens elements, the four lens elements being, in order from an object side to an image side along an optical path: a first lens element, a second lens element, a third lens element and a fourth lens element; wherein the second lens element has negative refractive power; the third lens element has positive refractive power; the fourth lens element has an object-side surface being concave in a paraxial region thereof; wherein the image capturing optical lens system further comprises an aperture stop disposed between the second lens element and the fourth lens element; a curvature radius of an object-side surface of the third lens element and a curvature radius of an image-side surface of the third lens element have the same sign; an axial distance between the second lens element and the third lens element is greater than an axial distance between the third lens element and the fourth lens element; wherein an Abbe number of the second lens element is V_2 , an Abbe number of the third lens element is V_3 , a central thickness of the first lens element is CT_1 , a central thickness of the second lens element is CT_2 , and the following conditions are satisfied: $10 < V_2 + V_3 < 70$; and $0.30 < CT_1/CT_2 < 3.0$.
2. The image capturing optical lens system of claim 1, wherein the fourth lens element has an image-side surface comprising at least one inflection point in an off-axis region thereof.
3. The image capturing optical lens system of claim 1, wherein a sum of all axial distances between adjacent lens elements of the image capturing optical lens system is ΣAT , the axial distance between the second lens element and the third lens element is T_{23} , and the following condition is satisfied: $1.0 < \Sigma AT/T_{23} < 2.5$.
4. The image capturing optical lens system of claim 1, wherein a maximum image height of the image capturing optical lens system is $ImgH$, an entrance pupil diameter of the image capturing optical lens system is EPD , and the following condition is satisfied: $0.30 < ImgH/EPD < 0.80$.
5. The image capturing optical lens system of claim 1, wherein an absolute value of a focal length of the second lens element is greater than an absolute value of a focal length of the fourth lens element; an axial distance between the object-side surface of the first lens element and an image surface is TL , a focal length of the image capturing optical lens system is f , and the following condition is satisfied: $TL/f < 2.50$.
6. The image capturing optical lens system of claim 1, wherein a curvature radius of an object-side surface of the second lens element and a curvature radius of the object-side surface of the fourth lens element have the same sign.
7. The image capturing optical lens system of claim 1, wherein an Abbe number of the first lens element is greater than the Abbe number of the third lens element.
8. The image capturing optical lens system of claim 1, wherein a central thickness of the third lens element is greater than the central thickness of the second lens element.
9. The image capturing optical lens system of claim 1, further comprising: at least one reflective element.
10. The image capturing optical lens system of claim 9, wherein the reflective element is located on an object side of the first lens element along the optical path, the reflective element has refractive power, and one surface of the reflective element facing towards an imaged object is convex in a paraxial region thereof.
11. An imaging apparatus, comprising: the image capturing optical lens system of claim 1; and an image sensor disposed on an image surface of the image capturing optical lens system.
12. An electronic device, comprising: the imaging apparatus of claim 11.
13. An image capturing optical lens system comprising four lens elements, the four lens elements being, in order from an object side to an image side along an optical path: a first lens element, a second lens element, a third lens element and a fourth lens element; wherein the second lens element has negative refractive power; the third lens element has positive refractive power; wherein the image capturing optical lens system further comprises an aperture stop disposed between the second lens element and the third lens element; a curvature radius of an image-side

surface of the first lens element and a curvature radius of an object-side surface of the third lens element have the same sign; the curvature radius of the image-side surface of the first lens element and a curvature radius of an image-side surface of the fourth lens element have the same sign; an axial distance between the second lens element and the third lens element is greater than a central thickness of the fourth lens element; wherein an Abbe number of the second lens element is V_2 , an Abbe number of the third lens element is V_3 , and the following condition is satisfied:
 $10 < V_2 + V_3 < 70$.

14. The image capturing optical lens system of claim 13, wherein the first lens element has positive refractive power; the fourth lens element has negative refractive power.

15. The image capturing optical lens system of claim 13, wherein the fourth lens element has the image-side surface comprising at least one inflection point in an off-axis region thereof.

16. The image capturing optical lens system of claim 13, wherein a focal length of the second lens element is f_2 , a focal length of the fourth lens element is f_4 , and the following condition is satisfied: $0 < f_2/f_4 < 1.25$.

17. The image capturing optical lens system of claim 13, wherein a focal length of the image capturing optical lens system is f , a curvature radius of an object-side surface of the fourth lens element is R_7 , the curvature radius of the image-side surface of the fourth lens element is R_8 , and the following condition is satisfied: $f/|R_7| + f/|R_8| < 6.0$.

18. The image capturing optical lens system of claim 13, wherein a maximum distance between an optical effective region of an object-side surface of the first lens element and an optical axis is Y_{11} , a maximum image height of the image capturing optical lens system is $ImgH$, and the following condition is satisfied: $0.60 < Y_{11}/ImgH < 1.20$.

19. The image capturing optical lens system of claim 13, wherein a central thickness of the first lens element is a maximum among thickness of the four lens elements; the curvature radius of the object-side surface of the third lens element and the curvature radius of the image-side surface of the fourth lens element have the same sign.

20. The image capturing optical lens system of claim 13, further comprising: a light blocking element having a non-circular inner hole.
