

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412497
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Oh; ChangSeok et al.

Organic light emitting display device

Abstract

An organic light emitting display device can include an organic light emitting display panel including sub pixels; a support member below the organic light emitting display panel and formed of a metal material; a first flexible circuit film on one side of the organic light emitting display panel, and configured to be bent toward a bottom surface of the support member; a third flexible circuit film on one side of the organic light emitting display panel, and configured to be bent toward the bottom surface of the support member; and a low potential voltage line on the organic light emitting display panel to supply a low potential voltage to the sub pixels. The first and third flexible circuit films are electrically connected to the low potential voltage line, and the low potential voltage is applied to the low potential voltage line via the first and third flexible circuit films.

Inventors: Oh; ChangSeok (Daegu, KR), Yoon; Juhyun (Gimpo-si, KR), Choi; Yunjong (Yangsan-si, KR)

Applicant: LG Display Co., Ltd. (Seoul, KR)

Family ID: 81972211

Assignee: LG DISPLAY CO., LTD. (Seoul, KR)

Appl. No.: 18/236803

Filed: August 22, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230395005 A1	Dec. 07, 2023

Foreign Application Priority Data

KR	10-2020-0189702	Dec. 31, 2020
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc US 17501761 20211014 US 11769432 child-doc US 18236803

Publication Classification

Int. Cl.: **G09G3/00** (20060101); **G06F3/041** (20060101); **G09G3/3208** (20160101)

U.S. Cl.:

CPC **G09G3/035** (20200801); **G06F3/0418** (20130101); **G09G3/3208** (20130101);
G06F2203/04102 (20130101); G09G2300/0842 (20130101); G09G2310/08 (20130101)

Field of Classification Search

CPC: G09G (3/035); G09G (3/3208); G09G (2300/0842); G09G (2310/08); G09G (2300/0426); G09G (3/3655); G09G (3/3233); G09G (3/3258); G09G (3/3225); G09G (3/3291); G09G (3/3685); G06F (3/0418); G06F (2203/04102); G06F (3/0412); G06F (3/04164); H10K (59/131); H10K (59/1213); H10K (59/1315); H10K (2102/311); H10K (59/40); H10K (77/111); H10K (59/12); G02F (1/136286)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11024653	12/2020	Kim	N/A	N/A
11769432	12/2022	Oh	345/173	G09G 3/3208
2009/0310057	12/2008	Kang et al.	N/A	N/A
2010/0156857	12/2009	Nozaki	345/204	H04N 5/64
2014/0085281	12/2013	Lim	N/A	N/A
2014/0111116	12/2013	Shin	315/312	H05B 45/60
2016/0118454	12/2015	Park et al.	N/A	N/A
2016/0205391	12/2015	Kim	N/A	N/A
2018/0145278	12/2017	Zhai	N/A	C09J 201/00
2019/0278411	12/2018	Jeon et al.	N/A	N/A
2020/0098793	12/2019	Kim	N/A	H10D 86/411
2020/0100362	12/2019	Yamaguchi	N/A	N/A
2020/0212135	12/2019	Zhang	N/A	N/A
2020/0267838	12/2019	An	N/A	G06F 1/1647

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
10-2014-0012487	12/2013	KR	N/A
10-2016-0050149	12/2015	KR	N/A
10-2020-0034052	12/2019	KR	N/A
10-2020-0101116	12/2019	KR	N/A

Primary Examiner: Shah; Sujit

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a Continuation application of U.S. application Ser. No. 17/501,761 filed on Oct. 14, 2021 (Now U.S. Pat. No. 11,769,432 issued on Sep. 26, 2023), which claims priority to Korean Patent Application No. 10-2020-0189702 filed on Dec. 31, 2020 in the Korean Intellectual Property Office, the entire contents of all these applications being hereby expressly incorporated by reference into the present application.

BACKGROUND

Field

(1) The present disclosure relates to an organic light emitting display device to which a ground voltage is stably applied.

Description of the Related Art

(2) Unlike a liquid crystal display (LCD) device which includes a backlight, an organic light emitting display (OLED) device does not use a separate light source. Therefore, the organic light emitting display device can be manufactured to be light and thin, has process advantages and has a low power consumption due to the low voltage driving.

(3) The organic light emitting display device includes a self-emitting element and layers formed of organic thin films so that the flexibility and elasticity are superior to the other display devices. Thus, it is advantageous to be implemented as a flexible display device.

(4) Recently, In an information era, a display field which visually expresses electrical information signals has been rapidly developed and in response to this, various display devices having excellent performances such as thin-thickness, light weight, and low power consumption have been developed. The plastic organic light emitting display device uses a plastic film as a base material instead of a thick glass so that it is light-weight and has an excellent flexibility to be applied to various shapes such as a flexible display device.

(5) Specifically, a flexible display device which is manufactured to be capable of displaying images even though the flexible display device is bent or folded like papers is attracting attention as the next generation display device. The flexible display device utilizes a plastic thin film transistor substrate rather than glass to be classified into an unbreakable display device having a high durability, a bendable display device which is bent without being broken, a rollable display device which is rolled, and a foldable display device which is folded. Such a flexible display device has advantages in terms of space utilization, interior, and designs and has various application fields.

(6) Further, in recent years, products which include a built-in touch sensor to have a touch screen function which is operated by touching a screen, such as a mobile device, a PDA (personal digital assistant), and a computer notebook which are personal portable devices, have become indispensable. For example, the organic light emitting display device can further include a touch panel. There are an add-on type organic light emitting display device in which a touch panel is attached on an outer surface, an on-cell type organic light emitting display device in which a touch panel is deposited thereon, and an in-cell type organic light emitting display device with a built-in touch panel. According to the in-cell type with a built-in touch panel, the touch panel is embedded in the organic light emitting display device so that it is implemented with a thin thickness as compared with the add-on type and the on-cell type.

(7) In the meantime, a flexible display device, such as a foldable display device, is implemented with a thin thickness so that there can be a limitation in that a touch noise may be caused on the touch panel on the display panel due to a voltage fluctuation of a thin film transistor TFT during the

driving of the display panel.

(8) As the display device becomes larger in size, the low potential voltage (VSS) rises in a pixel located far from the driving circuit, and accordingly, the driving voltage and power consumption increase, and the luminance of the display device can become non-uniform. Further, due to the rise of the low potential voltage, a voltage difference can be caused between the low potential voltage applied to the display panel and the touch panel, which can cause a touch noise in the touch panel.

SUMMARY OF THE DISCLOSURE

(9) An object to be achieved by the present disclosure is to stably supply a low potential voltage to an organic light emitting display device.

(10) Another object to be achieved by the present disclosure is to provide an organic light emitting display device which supplies a constant ground voltage to a display panel to suppress influence of an electric field generated by a thin film transistor of the display panel on a touch panel disposed thereabove.

(11) Still another object to be achieved by the present disclosure is to reduce a voltage difference between a display panel and a touch panel to reduce a touch noise.

(12) Still another object to be achieved by the present disclosure is to provide a foldable display device with an improved touch performance.

(13) Objects of the present disclosure are not limited to the above-mentioned objects, and other objects, which are not mentioned above, can be clearly understood by those skilled in the art from the following descriptions.

(14) According to an aspect of the present disclosure, an organic light emitting display device includes an organic light emitting display panel including a plurality of sub pixels; a touch panel on the organic light emitting display panel; a support member which is disposed below the organic light emitting display panel and is formed of a metal material; a first flexible circuit film which is disposed on one side of the organic light emitting display panel and is bent toward a bottom surface of the support member; a second flexible circuit film which is disposed on one side of the touch panel and is bent toward the bottom surface of the support member; and a third flexible circuit film which is disposed on one side of the organic light emitting display panel and is bent toward the bottom surface of the support member to stabilize a low potential voltage. The first flexible circuit film, the second flexible circuit film, and the third flexible circuit film are grounded to the support member.

(15) Other detailed matters of the exemplary embodiments are included in the detailed description and the drawings.

(16) According to the present disclosure, a flexible circuit film including a conductive sheet is additionally disposed to stabilize a low potential voltage which is supplied to a cathode of the display panel to suppress the rising of the low potential voltage.

(17) According to the present disclosure, an organic light emitting display device which implements a ground structure which is electrically connected to a display panel and a ground using a support member formed of a metal material such as stainless steel (SUS) can be provided.

(18) According to the present disclosure, a voltage fluctuation and an electric field generated from the display panel are suppressed using a ground structure of the support member to reduce a noise of the touch panel.

(19) According to the present disclosure, a foldable display device which reduces a voltage difference between a display panel and a touch panel to reduce a touch noise and improve a touch performance can be provided.

(20) The effects according to the present disclosure are not limited to the contents exemplified above, and more various effects are included in the present specification.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The above and other aspects, features and other advantages of the present disclosure will be more clearly understood from the following detailed description taken in conjunction with the accompanying drawings, in which:

(2) FIG. 1 is a plan view of an organic light emitting display device according to an exemplary embodiment of the present disclosure;

(3) FIG. 2 is a rear view of an organic light emitting display device according to an exemplary embodiment of the present disclosure;

(4) FIG. 3A is a cross-sectional view taken along the line I-I' of FIG. 2;

(5) FIG. 3B is a cross-sectional view taken along the line II-II' of FIG. 2;

(6) FIG. 3C is a cross-sectional view taken along of FIG. 2;

(7) FIG. 4 is a plan view of an organic light emitting display device according to another exemplary embodiment of the present disclosure;

(8) FIG. 5 is a rear view of an organic light emitting display device according to another exemplary embodiment of the present disclosure;

(9) FIG. 6A is a cross-sectional view taken along the line IV-IV' of FIG. 5;

(10) FIG. 6B is a cross-sectional view taken along the line V-V' of FIG. 5;

(11) FIG. 7 is an enlarged cross-sectional view of an organic light emitting display device according to still another exemplary embodiment of the present disclosure;

(12) FIG. 8 is a rear view of an organic light emitting display device according to still another exemplary embodiment of the present disclosure;

(13) FIG. 9A is a cross-sectional view taken along the line VI-VI' of FIG. 8;

(14) FIG. 9B is a cross-sectional view taken along the line VII-VII' of FIG. 8; and

(15) FIGS. 10A and 10B are examples of noise sensitivity measuring graphs of a touch panel in an organic light emitting display device according to Exemplary Embodiment and Comparative Embodiment.

DETAILED DESCRIPTION OF THE EMBODIMENTS

(16) Advantages and characteristics of the present disclosure and a method of achieving the advantages and characteristics will be clear by referring to exemplary embodiments described below in detail together with the accompanying drawings. However, the present disclosure is not limited to the exemplary embodiments disclosed herein but will be implemented in various forms. The exemplary embodiments are provided by way of example only so that those skilled in the art can fully understand the disclosures of the present disclosure and the scope of the present disclosure. Therefore, the present disclosure will be defined only by the scope of the appended claims.

(17) The shapes, sizes, ratios, angles, numbers, and the like illustrated in the accompanying drawings for describing the exemplary embodiments of the present disclosure are merely examples, and the present disclosure is not limited thereto. Like reference numerals generally denote like elements throughout the specification. Further, in the following description of the present disclosure, a detailed explanation of known related technologies may be omitted to avoid unnecessarily obscuring the subject matter of the present disclosure. The terms such as “including,” “having,” and “consist of” used herein are generally intended to allow other components to be added unless the terms are used with the term “only”. Any references to singular can include plural unless expressly stated otherwise.

(18) Components are interpreted to include an ordinary error range even if not expressly stated.

(19) When the position relation between two parts is described using the terms such as “on”, “above”, “below”, and “next”, one or more parts can be positioned between the two parts unless the terms are used with the term “immediately” or “directly”.

(20) When an element or layer is disposed “on” another element or layer, another layer or another

element can be interposed directly on the other element or therebetween.

(21) Although the terms “first”, “second”, and the like are used for describing various components, these components are not confined by these terms. These terms are merely used for distinguishing one component from the other components and may not define order. Therefore, a first component to be mentioned below can be a second component in a technical concept of the present disclosure.

(22) Like reference numerals generally denote like elements throughout the specification.

(23) A size and a thickness of each component illustrated in the drawing are illustrated for convenience of description, and the present disclosure is not limited to the size and the thickness of the component illustrated.

(24) The features of various embodiments of the present disclosure can be partially or entirely adhered to or combined with each other and can be interlocked and operated in technically various ways, and the embodiments can be carried out independently of or in association with each other.

(25) Hereinafter, an organic light emitting display device according to exemplary embodiments of the present disclosure will be described in detail with reference to accompanying drawings. All the components of each organic light emitting display device according to all embodiments of the present disclosure are operatively coupled and configured.

(26) FIGS. 1 to 3C are views for explaining an organic light emitting display device according to an exemplary embodiment of the present disclosure. FIG. 1 is a plan view of an organic light emitting display device according to an exemplary embodiment of the present disclosure. FIG. 2 is a rear view of an organic light emitting display device according to an exemplary embodiment of the present disclosure. FIG. 3A is a cross-sectional view taken along the line I-I' of FIG. 2. FIG. 3B is a cross-sectional view taken along the line II-II' of FIG. 2. FIG. 3C is a cross-sectional view taken along the line III-III' of FIG. 2.

(27) An organic light emitting display device **100** according to an exemplary embodiment of the present disclosure includes a display panel **110**, a touch panel **130**, a support member **120**, a first flexible circuit film FF1, a second flexible circuit film FF2, a third flexible circuit film FF3, a first printed circuit board PCB1, and a second printed circuit board PCB2.

(28) Referring to FIG. 1, the organic light emitting display device **100** according to the exemplary embodiment of the present disclosure includes a display area DA and a non-display area NDA. The display area DA is an area where a plurality of pixels is disposed to substantially display images.

(29) In the display area DA, a plurality of pixels which includes an emission area to display images, a thin film transistor for driving the pixels, a capacitor, and the like can be disposed. One pixel can include a plurality of sub pixels SP. The sub pixel SP is a minimum unit which configures the display area and each sub pixel SP can be configured to emit light of a specific wavelength band. For example, each of the sub pixels SP can be configured to emit red light, green light, blue light, or white light. The non-display area NDA is disposed so as to enclose the display area DA. The non-display area NDA is an area where images are not substantially displayed and various wiring lines, driving ICs, and the like for driving the pixels and the driving elements disposed in the display area DA are disposed therein. For example, in the non-display area NDA, various driving ICs such as a gate driver IC and a data driver IC, VSS lines, and the like can be disposed.

(30) Referring to FIG. 1, the organic light emitting display device **100** according to the exemplary embodiment of the present disclosure can be a foldable display device which is folded in one direction. In this case, the organic light emitting display device **100** includes a folding area FA and a non-folding area NFA. The folding area FA is an area which is folded when the organic light emitting display device **100** is folded and is folded along a specific radius of curvature with respect to a folding axis.

(31) When the organic light emitting display device **100** is folded, if the folding area FA is folded with respect to the folding axis, the folding area FA can form a part of a circle or an oval. At this time, a radius of curvature of the folding area FA can refer to a radius of a circle or an oval formed by the folding area FA. When a top surface of the organic light emitting display device **100** on

which images are displayed is defined as a display surface and a bottom surface of the organic light emitting display device **100** which is an opposite surface of the display surface is defined as a rear surface, the folding area FA can be folded by a method selected from an out-folding method and an in-folding method. According to the out-folding method, the folding area is folded to expose the display surface of the organic light emitting display device **100** to the outside and according to the in-folding method, the folding area is folded such that display surfaces of the organic light emitting display device **100** face each other.

(32) The non-folding area NFA is an area which is not folded when the organic light emitting display device **100** is folded. For example, the non-folding area NFA maintains a flat state when the organic light emitting display device **100** is folded. The non-folding area NFA can be located on both sides of the folding area FA. For example, the non-folding area NFA can be an area extending to an X-axis direction with respect to the folding axis. At this time, the folding area FA can be defined between the non-folding areas NFA. Further, when the organic light emitting display device **100** is folded with respect to the folding axis, the non-folding areas NFA can overlap each other.

(33) In FIG. **1**, one folding area FA and two non-folding areas NFA are disposed. However, the number and the position of folding areas FA and non-folding areas NFA can vary in various forms, but it is not limited thereto.

(34) The display panel **110** is a panel in which images are implemented. Display elements for implementing images, circuit units for driving the display elements, and the like can be disposed in the display panel. The circuit units can include various thin film transistors, capacitors, wiring lines, driving ICs, and the like for driving the organic light emitting diode. For example, the circuit units can include various configurations such as a driving thin film transistor, a switching thin film transistor, a storage capacitor, a gate line, a data line, a gate driver IC, and a data driver IC, but are not limited thereto.

(35) Specifically, the display panel **110** includes a flexible substrate, a thin film transistor, and an organic light emitting diode.

(36) The flexible substrate can be a very thin plastic substrate to implement a flexibility of the organic light emitting display device **100**. The flexible substrate can be formed of an insulating material having a flexibility, and for example, the flexible substrate can be an insulating plastic substrate selected from polyimide, polyethersulfone, polyethylene terephthalate, and polycarbonate. However, it is not limited thereto and if a material is not broken even when the foldable display device **100** is repeatedly folded, not only the plastic, but also the other material having a flexibility can be used. The plastic substrate has a relatively weak barrier characteristic against moisture or oxygen so that in order to compensate therefor, the plastic substrate can have a structure in which a plastic film and an inorganic layer are laminated. For example, the flexible substrate can have a multi-layered structure in which a first plastic film, an inorganic layer, and a second plastic film are sequentially laminated, but is not limited thereto.

(37) A thin film transistor is disposed on the flexible substrate to drive the organic light emitting diode. The thin film transistor can be disposed in each of the plurality of pixel areas. For example, the driving thin film transistor includes a gate electrode, an active layer, a source electrode, and a drain electrode. Further, the thin film transistor can further include a gate insulating layer which insulates the gate electrode and the active layer and an interlayer insulating layer which insulates the gate electrode from the source and drain electrodes.

(38) A planarization layer can be disposed on the thin film transistor to planarize an upper surface.

(39) The organic light emitting diode is disposed on the planarization layer. The organic light emitting diode can include an anode, a cathode, and an organic light emitting layer disposed therebetween. In the organic light emitting diode, holes injected from the anode and electrons injected from the cathode are coupled on the organic light emitting layer to emit light. Images are displayed using the light emitted as described above.

(40) A low potential voltage line VSSL is disposed on the flexible substrate of the display panel **110** to correspond to the non-display area NDA. The low potential voltage line VSSL is disposed to enclose the display area DA along an outer periphery of the display panel **110**. The low potential voltage line VSSL can have a closed rectangular ring shape. The low potential voltage line VSSL is formed of a metal material having a high conductivity. The low potential voltage line VSSL is in contact with the cathode of the organic light emitting diode of the display panel **110** to apply a low potential voltage to the cathode. Referring to FIG. **1**, the low potential voltage line VSSL is connected to the first flexible circuit film FF**1** and the third flexible circuit film FF**3**. The low potential voltage line VSSL can be supplied with low potential voltages from the first flexible circuit film FF**1** and the third flexible circuit film FF**3**, respectively. The connection of the low potential voltage line VSSL and the flexible circuit films will be described below.

(41) The support member **120** is disposed below the display panel **110**. The flexible substrate has an excellent flexibility, but is relatively thin and has a weak rigidity as compared with a glass substrate. Therefore, when the flexible substrate is folded, it can be difficult to consistently maintain the shape and when various elements are disposed thereon, the flexible substrate can be sagged. In order to solve this problem, the support member **120** is disposed below the display panel **110**.

(42) The support member **120** includes a back plate. For example, the back plate can be a metal material such as stainless steel (SUS) or Invar and can be formed of a plastic material such as polymethylmethacrylate (PMMA), polycarbonate (PC), polyvinylalcohol (PVA), acrylonitrile butadiene-styrene (ABS), polyethylene terephthalate (PET), silicone, or polyurethane (PU).

(43) The support member **120** can further include a plate assembly. The plate assembly is disposed below the back plate. The plate assembly is disposed below the back plate to more firmly support the display panel **110**.

(44) The plate assembly includes a plate top and a plate bottom. The plate top and the plate bottom can be integrally formed and if necessary, the plate top or the plate bottom can be omitted.

(45) The plate bottom can include an opening pattern in a part corresponding to the folding area of the flexible display device **100**. Therefore, the rigidity of the display panel **110** is reinforced and the stress during the folding can be effectively relieved. For example, the plate bottom can be formed of a metal material such as stainless steel (SUS) or invar.

(46) The plate top can be disposed between the back plate and the plate bottom. The plate top is formed of a material having a high rigidity to enhance the rigidity of the display panel **110**. Further, the plate top can suppress a phenomenon that the opening pattern of the plate bottom is visible through the display panel **110**. For example, the plate top can be formed of a metal material such as stainless steel (SUS), invar, aluminum, or magnesium. As another example, the plate top can be formed of a plastic material such as polymethylmethacrylate (PMMA) or polycarbonate (PC).

(47) The touch panel **130** is disposed on the display panel **110**. The touch panel **130** means a panel which receives a touch input of a user with respect to the display device. For example, as the touch panel **130**, a capacitive type, a resistive film type, an ultrasonic type, or an infrared type can be used, and desirably, a capacitive type touch panel **130** can be used as the touch panel **130**. Even though in FIGS. **3A** to **3C**, it is illustrated that the touch panel **130** is disposed above the display panel **110**, the touch panel **130** can also be disposed below the display panel **110**. Further, the touch panel **130** can be integrally formed with the display panel **110**.

(48) The first flexible circuit film FF**1** is disposed at one side of the display panel **110**. The first flexible circuit film FF**1** transmits various signals from the first printed circuit board PCB**1** to the display panel **110**. In the first flexible circuit film FF**1**, a driving circuit (for example, an IC chip) can be mounted. The driving circuit DIC can generate a data signal or a gate signal corresponding to a driving power or various signals which are transmitted from the first printed circuit board PCB**1** and supply the data signal or the gate signal to the thin film transistor TFT formed on the display panel **110**. To this end, the driving circuit DIC can include both a data driver which

generates a data signal and a gate driver which generates a scan signal or the data driver and the gate driver can be separated from each other. In this case, the first flexible circuit film FF1 can transmit the signals output from the first printed circuit board PCB1 to the driving circuit DIC or transmit signals output from the driving circuit DIC to the thin film transistor TFT formed on the display panel 110. Even though in the present disclosure, it has been described that the driving circuit DIC can be disposed on the first flexible circuit film FF1, the driving circuit can be directly disposed on the lower substrate. The first flexible circuit film FF1 can be attached onto a pad unit provided in a non-display area NDA of the display panel 110 using an anisotropic conducting film ACF.

(49) The first printed circuit board PCB1 is attached to the first flexible circuit film FF1.

Specifically, the first printed circuit board PCB1 is attached to another side of the first flexible circuit film FF1 with respect to one side of the first flexible circuit film FF1 which is connected to the display panel 110. The first printed circuit board PCB1 transmits various signals to the thin film transistor TFT formed on the display panel 110. For example, a timing controller and the like can be disposed on the first printed circuit board PCB1. The timing controller can supply various signals to the driving circuit. For example, the timing controller generates a data driver control signal DDC and a gate driver control signal GDC to supply the signals to the driving circuit DIC.

(50) The second flexible circuit film FF2 is disposed at the other side of the touch panel 130. At this time, the other side of the touch panel 130 refers to a side portion of the touch panel 130 corresponding to an opposite side portion of one side of the display panel 110 to which the first flexible circuit film FF1 is attached. For example, referring to FIG. 1, the first flexible circuit film FF1 is disposed at an upper side portion of the display panel 110 and the second flexible circuit film FF2 is disposed at a lower side portion of the touch panel 130 opposite thereto. The second flexible circuit film FF2 transmits signals output from the second printed circuit board PCB2 to the touch panel 130. The second flexible circuit film FF2 can be attached onto a pad unit provided in the non-display area NDA of the touch panel 130 using an anisotropic conducting film ACF.

(51) The second printed circuit board PCB2 is attached to the second flexible circuit film FF2. Specifically, the second printed circuit board PCB2 is attached to another side of the second flexible circuit film FF2 with respect to one side of the second flexible circuit film FF2 which is connected to the touch panel 130. The second printed circuit board PCB2 transmits various signals to the touch electrode formed on the touch panel 130. For example, a touch controller and the like can be disposed on the second printed circuit board PCB2. The touch controller can supply the touch signal to the touch electrode of the touch panel 130. For example, the touch controller supplies a touch driving signal to the touch electrode of the touch panel 130 and receives a touch sensing signal from the sensing signal. The touch controller analyzes waveforms and amplitudes of the touch driving signal and the touch sensing signal to detect a position and an intensity of the touch input.

(52) The third flexible circuit film FF3 is disposed at the other side of the display panel 110. At this time, the other side of the touch panel 130 refers to a side portion corresponding to an opposite side portion of one side of the display panel 110 to which the first flexible circuit film FF1 is attached. For example, referring to FIG. 1, the first flexible circuit film FF1 is disposed at an upper side portion of the display panel 110 and the third flexible circuit film FF3 is disposed at a lower side portion of the display panel 110 opposite thereto. The third flexible circuit film FF3 can be attached onto a pad unit provided in a non-display area NDA of the display panel 110 using an anisotropic conducting film ACF.

(53) The third flexible circuit film FF3 is connected to the low potential voltage line VSSL to stabilize a low potential voltage. The third flexible circuit film FF3 is disposed in the other non-display area located at the opposite side of one side at which the first flexible circuit film FF1 which applies the low potential voltage is formed so that an additional low potential voltage can be supplied to the cathode by means of the low potential voltage line VSSL. To this end, the third

flexible circuit film FF3 includes a conductive sheet layer formed of a metal material having a low resistance. The third flexible circuit film FF3 is electrically connected to the cathode of the display panel **110** by means of the low potential voltage line VSSL to compensate for a high resistance of the cathode by the conductive sheet layer to suppress the rising of the low potential voltage VSS. Further, the third flexible circuit film FF3 directly supplies the low potential voltage to the cathode to suppress the rising of the low potential voltage of the cathode electrode.

(54) In the meantime, in the organic light emitting display device **100** according to the exemplary embodiment of the present disclosure, the flexible circuit film and the printed circuit board are independently disposed but a separate flexible circuit film and the printed circuit board are not attached to each other. Instead, the flexible circuit film and the printed circuit board are integrally formed so that a flexible printed circuit board FPCB in which the flexible circuit film itself can serve as a printed circuit board can be used.

(55) Hereinafter, a placement structure of components of the organic light emitting display device **100** according to the exemplary embodiment of the present disclosure will be described in more detail with reference to FIGS. 2 to 3C. In FIGS. 2 to 3C, in the organic light emitting display device **100** according to the exemplary embodiment of the present disclosure, a structure in which a first flexible circuit film FF1, a second flexible circuit film FF2, and a third flexible circuit film FF3 are bent in one direction to be disposed on a bottom surface of the support member **120** has been illustrated.

(56) Referring to FIGS. 2 to 3C, the first flexible circuit film FF1, the second flexible circuit film FF2, and the third flexible circuit film FF3 are bent in a lower direction of the display panel **110**. At least a part of each of the first flexible circuit film FF1, the second flexible circuit film FF2, and the third flexible circuit film FF3 which are bent is disposed to be opposite to the bottom surface of the support member **120**.

(57) At this time, all the first flexible circuit film FF1, the second flexible circuit film FF2, and the third flexible circuit film FF3 are electrically connected to the bottom surface of the support member **120** having a ground voltage.

(58) First, referring to FIG. 3A, the first printed circuit board PCB1 connected to the first flexible circuit film FF1 is attached onto the bottom surface of the support member **120** by means of a first conductive adhesive member **141**. The first conductive adhesive member **141** is a double-sided adhesive tape having a conductivity. By doing this, the first flexible circuit film FF1 can provide a ground line path between the first printed circuit board PCB1 and the display panel **110**. Accordingly, the first flexible circuit film FF1 can have a ground structure which is electrically connected to the ground of the support member **120** by means of the first printed circuit board PCB1 and the first conductive adhesive member **141**.

(59) Further, the second printed circuit board PCB2 connected to the second flexible circuit film FF2 is attached onto the bottom surface of the support member **120** by means of a second conductive adhesive member **142**. The second conductive adhesive member **142** is a double-sided adhesive tape having a conductivity. By doing this, the second flexible circuit film FF2 can provide a ground line path between the second printed circuit board PCB2 and the touch panel **130**. Accordingly, the second flexible circuit film FF2 can have a ground structure which is electrically connected to the ground of the support member **120** by means of the second printed circuit board PCB2 and the second conductive adhesive member **142**.

(60) Referring to FIG. 3B, the third flexible circuit film FF3 is attached to be in direct contact with the bottom surface of the support member **120** by means of a first conductive fiber tape **150**. The third flexible circuit film FF3 includes a flexible base layer FB, thin film lines TL1 and TL2 disposed on both surfaces of the flexible base layer FB, and an insulating layer ES which covers a part of the thin film lines TL1 and TL2. To be more specific, the third flexible circuit film FF3 includes a flexible base layer FB, a first thin film line TL1, a second thin film line TL2, and an insulating layer ES. The first thin film line TL1 is disposed on one surface of the flexible base layer

FB which faces the bottom surface of the support member **120** during the bending. The second thin film line TL2 is disposed on the other surface of the flexible base layer FB which is an opposite surface of one surface which faces the bottom surface of the support member **120** during the bending. Further, the insulating layer ES covers at least a part of the first thin film line TL1 and the second thin film line TL2.

(61) At this time, in the third flexible circuit film FF3, the first thin film line TL1 which faces the bottom surface of the support member **120** during the bending is in direct contact with the bottom surface of the support member **120**. Further, the first conductive fiber tape **150** is attached onto the second thin film line TL2 after bending the third flexible circuit film FF3 so that the third flexible circuit film FF3 and the support member **120** are in physical contact with each other to be fixed. The first conductive fiber tape **150** has an adhesiveness on one surface so that a bottom surface of the support member **120** and the other surface of the third flexible circuit film FF3 are simultaneously attached.

(62) Further, the first conductive fiber tape **150** can electrically connect the second thin film line TL2 formed on the other surface of the third flexible circuit film FF3 and the bottom surface of the support member **120**. By doing this, the third flexible circuit film FF3 can provide a ground line path between the support member **120** and the display panel **110**. Accordingly, the third flexible circuit film FF3 has a ground structure which is electrically connected to the ground of the support member **120** by means of a structure in which the support member **120** and the first thin film line TL1 are in direct contact with each other and a structure in which the support member **120** and the second thin film line TL2 are electrically connected by means of the first conductive fiber tape **150**.

(63) As described above, the first conductive fiber tape **150** bonds and electrically connects the third flexible circuit film FF3 and the bottom surface of the support member **120** to each other. Further, referring to FIG. 2, the first conductive fiber tape **150** covers at least a part of the third flexible circuit film FF3 and the second printed circuit board PCB2 and is attached to be in contact with the bottom surface of the support member **120**. The third flexible circuit film FF3 and the second printed circuit board PCB2 are attached to the support member **120** and fixed to each other by means of the first conductive fiber tape **150**.

(64) Further, the first conductive fiber tape **150** electrically connects the third flexible circuit film FF3, the second printed circuit board PCB2, and the support member **120**. By doing this, the ground voltage of the support member **120** can be applied to the second flexible circuit film FF2 and the third flexible circuit film FF3. In FIG. 2, it is illustrated that the first conductive fiber tape **150** does not cover the second flexible circuit film FF2, but it is not limited thereto and the first conductive fiber tape **150** can be attached to cover a part of the second flexible circuit film FF2.

(65) In the meantime, referring to FIG. 2, a second conductive fiber tape **155** which is attached to a part of the support member **120** to cover a part of the second printed circuit board PCB2 is disposed. The second conductive fiber tape **155** electrically connects the ground electrode formed in the second printed circuit board PCB2 and the support member **120** to reduce the resistance. Referring to FIG. 3C together, the second conductive fiber tape **155** can be attached to cover one side of the second printed circuit board PCB2 and one side surface of the support member **120**. For example, the second conductive fiber tape **155** can be continuously disposed so as to cover one surface and a side surface of the second printed circuit board PCB2 and parts of the bottom surface and the side surface of the support member **120**.

(66) FIGS. 4 to 6B are views for explaining an organic light emitting display device according to another exemplary embodiment of the present disclosure. Particularly, FIG. 4 is a plan view of an organic light emitting display device according to another exemplary embodiment of the present disclosure. FIG. 5 is a rear view of an organic light emitting display device according to another exemplary embodiment of the present disclosure. FIG. 6A is a cross-sectional view taken along the line IV-IV' of FIG. 5. FIG. 6B is a cross-sectional view taken along the line V-V' of FIG. 5. An organic light emitting display device **200** illustrated in FIGS. 4 to 6B is substantially the same as

the organic light emitting display device **100** illustrated in FIGS. **1** to **3B** except for a connection structure of the second flexible circuit film **FF2** and the third flexible circuit film **FF3**. Therefore, a description of repeated components will be omitted or may be briefly provided.

(67) An organic light emitting display device **200** according to another exemplary embodiment of the present disclosure includes a display panel **110**, a touch panel **130**, a support member **120**, a first flexible circuit film **FF1**, a second flexible circuit film **FF2**, a third flexible circuit film **FF3**, a first printed circuit board **PCB1**, and a second printed circuit board **PCB2**.

(68) Referring to FIG. **4**, the first flexible circuit film **FF1** is disposed on one side of the display panel **110** and is attached to the first printed circuit board **PCB1**. Further, the second flexible circuit film **FF2** is disposed on the other side of the touch panel **130** and the third flexible circuit film **FF3** is disposed on the other side of the display panel **110**. At this time, the second flexible circuit film **FF2** and the third flexible circuit film **FF3** are attached to the second flexible circuit board **PCB2**. The second printed circuit board **PCB2** supplies various touch signals to a touch electrode formed on the touch panel **130** by means of the second flexible circuit film **FF2**.

(69) Further, the second printed circuit board **PCB2** is connected to the support member **120** by means of the ground line. Specifically, the second printed circuit board **PCB2** is attached to the bottom surface of the support member **120** by means of the second conductive adhesive member **142**. By doing this, the ground line of the second printed circuit board **PCB2** and the support member **120** are electrically connected to each other by means of the second conductive adhesive member **142**. The second printed circuit board **PCB2** can apply the ground voltage of the support member **120** to the low potential voltage line **VSSL** by means of the third flexible circuit film **FF3**. By doing this, the third flexible circuit film **FF3** can provide a ground line path between the second printed circuit board **PCB2** and the display panel **110**.

(70) In the meantime, referring to FIG. **5**, the first conductive fiber tape **150** covers at least a part of the second printed circuit board **PCB2** and is attached to be in contact with the bottom surface of the support member **120**. The second printed circuit board **PCB2** is electrically connected to the support member **120** by means of the second conductive adhesive member **142** and is further connected to the support member **120** by means of the first conductive fiber tape **150** to compensate for the resistance. Therefore, the change in the ground voltage is minimized to apply the ground voltage to the low potential voltage line **VSSL** by means of the second printed circuit board **PCB2** and the third flexible circuit film **FF3**.

(71) FIG. **7** is an enlarged cross-sectional view of an organic light emitting display device according to still another exemplary embodiment of the present disclosure. An organic light emitting display device **300** illustrated in FIG. **7** is substantially the same as the organic light emitting display device **100** illustrated in FIGS. **1** to **3B** except for a structure of a support member **320** configured by a plate top **321** and a plate bottom **322**. Therefore, a description of repeated components will be omitted or may be briefly provided.

(72) Referring to FIG. **7**, a support member **320** includes a plate top **321** disposed below the display panel **110** and a plate bottom **322** disposed below the plate top **321**. The plate top **321** and the plate bottom **322** are formed of a metal material such as stainless steel **SUS** or **invar**.

(73) At this time, the first conductive fiber tape **150** attaches and electrically connects the second printed circuit board **PCB2** onto the rear surface of the support member **320**. Further, the second conductive fiber tape **355** also attaches and electrically connects the second printed circuit board **PCB2** to the support member **320**. Specifically, referring to FIG. **7**, the second conductive fiber tape **355** is disposed on one surface of the second printed circuit board **PCB2** so as to cover a part of the second printed circuit board **PCB2** and then disposed in parts of a bottom surface and a side surface of the support member **320**.

(74) Like the organic light emitting display device **300** illustrated in FIG. **7**, when the support member **320** includes the plate top **321** and the plate bottom **322**, the second conductive fiber tape **355** is in contact with a bottom surface, a side surface, and a part of a top surface of the plate

bottom **322** and a side surface and a part of the top surface of the plate top **321**. The second conductive fiber tape **355** is disposed to be simultaneously in contact with the plate bottom **322** and the plate top **321** to increase a contact area with the support member **320** to reduce a contact resistance. Further, the plate top **321** is disposed to be close to the display panel **110**, so that a noise radiated from the thin film transistor during the driving of the display panel **110** can be more easily reduced by the plate top **321** disposed therebelow.

(75) FIGS. **8** to **9B** are views for explaining an organic light emitting display device according to still another exemplary embodiment of the present disclosure. Particularly, FIG. **8** is a rear view of an organic light emitting display device according to still another exemplary embodiment of the present disclosure. FIG. **9A** is a cross-sectional view taken along the line VI-VI' of FIG. **8**. FIG. **9B** is a cross-sectional view taken along the line VII-VII' of FIG. **8**. An organic light emitting display device **400** illustrated in FIGS. **8** to **9B** is substantially the same as the organic light emitting display device **100** illustrated in FIGS. **1** to **3B** except that a carbon plate **460** is further included. Therefore, a description of repeated components will be omitted or may be briefly provided.

(76) Referring to FIGS. **8** to **9B**, the organic light emitting display device **400** according to still another exemplary embodiment of the present disclosure further includes a carbon plate **460** disposed below the support member **120**.

(77) The carbon plate **460** can be formed by immersing or dispersing a plurality of carbon fibers in a resin, but is not limited thereto. The carbon fiber does not absorb moisture so that it has an excellent moisture proof ability. Further, the carbon fiber has an excellent mechanical property so that it can implement a large mechanical rigidity even with a small thickness. Accordingly, an overall rigidity of the organic light emitting display device **400** can be improved. Further, the carbon plate **460** has a conductivity. Therefore, in the organic light emitting display device **400** according to still another exemplary embodiment of the present disclosure, the carbon plate **460** can provide a ground together with the support member **120**.

(78) One pair of carbon plates **460** can be provided so that the organic light emitting display device **400** can be folded. The carbon plate **460** has a large mechanical rigidity so that it can be difficult to fold the carbon plate. Therefore, the carbon plates **460** are disposed so as to correspond to the non-folding areas and are disposed to be spaced apart from each other to correspond to the folding area. In the meantime, one pair of carbon plates **460** is connected by a hinge structure to implement the folding.

(79) Referring to FIG. **9A**, the second printed circuit board PCB2 connected to the second flexible circuit film FF2 is attached onto the bottom surface of the carbon plate **460** by means of a second conductive adhesive member **142**. Accordingly, the second flexible circuit film FF2 can have a ground structure which is electrically connected to the ground of the carbon plate **460** by means of the second printed circuit board PCB2 and the second conductive adhesive member **142**. Further, the second printed circuit board PCB2 is fixed and is electrically connected to the carbon plate **460** by the first conductive fiber tape **150**. The first conductive fiber tape **150** attaches and electrically connects the second printed circuit board PCB2 onto the bottom surface of the carbon plate **460**. The first conductive fiber tape **150** covers at least a part of the second printed circuit board PCB2 and is attached to be in contact with the bottom surface of the carbon plate **460**.

(80) Referring to FIG. **9B**, a second conductive fiber tape **455** which is attached to a part of the carbon plate **460** to cover a part of the second printed circuit board PCB2 is disposed. The second conductive fiber tape **455** electrically connects the ground electrode formed in the second printed circuit board PCB2 and the carbon plate **460** to reduce the resistance. The second conductive fiber tape **455** is attached to cover one side of the second printed circuit board PCB2 and one side surface of the carbon plate **460**. For example, the second conductive fiber tape **455** can be continuously disposed so as to cover one surface and a side surface of the second printed circuit board PCB2, one surface and a side surface of the carbon plate **460**, and a part of the bottom surface of the support member **120**.

(81) The organic light emitting display device **400** according to still another exemplary embodiment of the present disclosure further includes the carbon plate **460** to improve a rigidity. When the carbon plate **460** is disposed below the support member **120** formed of a metal material, a ground structure which is electrically connected to the ground of the carbon plate **460** can be implemented using the printed circuit board and the flexible circuit film.

(82) Hereinafter, the effects of the present disclosure will be described in more detail with reference to Exemplary Embodiments and Comparative Embodiments. However, the following Exemplary Embodiments are set forth to illustrate the present disclosure, but the scope of the disclosure is not limited thereto.

Exemplary Embodiment

(83) Like the organic light emitting display device according to one exemplary embodiment of the present disclosure, when an organic light emitting display device having a structure in which the display panel and the support member were grounded by the first flexible circuit film, the touch panel and the support member were grounded by the second flexible circuit film, and the display panel and the support member were grounded by the third flexible circuit film which applies an additional low potential voltage was driven, a noise sensitivity generated in the touch panel was measured.

Comparative Embodiment

(84) Unlike Exemplary Embodiment, when an organic light emitting display device in which the first flexible circuit film and the second flexible circuit film were not grounded with the support member and the third flexible circuit film was not provided was driven, a noise sensitivity generated in the touch panel was measured.

(85) FIGS. **10A** and **10B** are noise sensitivity measuring graphs of a touch panel in an organic light emitting display device according to Exemplary Embodiment and Comparative Embodiment. FIG. **10A** is a noise sensitivity of a touch panel measured by means of a sensing electrode and FIG. **10B** is a noise sensitivity of a touch panel measured by means of a sensing electrode.

(86) Referring to FIGS. **10A** and **10B**, it is confirmed that when the first flexible circuit film, the second flexible circuit film, and the third flexible circuit film are connected to the support substrate to implement a ground structure which is electrically connected to the ground of the support member, a noise generated in the touch panel when the display panel operates is significantly reduced.

(87) The exemplary embodiments of the present disclosure can also be described as follows:

(88) According to an aspect of the present disclosure, there is provided an organic light emitting display device. The organic light emitting display device comprise an organic light emitting display panel including a plurality of sub pixels, a touch panel on the organic light emitting display panel, a support member which is disposed below the organic light emitting display panel and is formed of a metal material, a first flexible circuit film which is disposed on one side of the organic light emitting display panel and is bent toward a bottom surface of the support member, a second flexible circuit film which is disposed on one side of the touch panel and is bent toward the bottom surface of the support member, and a third flexible circuit film which is disposed on one side of the organic light emitting display panel and is bent toward the bottom surface of the support member to stabilize a low potential voltage. The first flexible circuit film, the second flexible circuit film, and the third flexible circuit film are grounded to the support member.

(89) The first flexible circuit film, the second flexible circuit film, and the third flexible circuit film can be electrically connected.

(90) The organic light emitting display device can further comprise a low potential voltage line disposed on the organic light emitting display panel to supply a low potential voltage to the plurality of sub pixels. The low potential voltage line can be electrically connected to the first flexible circuit film and the third flexible circuit film.

(91) The organic light emitting display device can further comprise a first printed circuit board

which is connected to the first flexible circuit film and includes a driving circuit supplying the low potential voltage to the low potential voltage line, and a second printed circuit board which is connected to the second flexible circuit film and includes the driving circuit supplying a touch signal to the touch panel. The first printed circuit board and the second printed circuit board can be electrically connected to the support member.

(92) The organic light emitting display device can further comprise a first conductive adhesive member bonding the first printed circuit board and the support member, and a second conductive adhesive member bonding the second printed circuit board and the support member.

(93) The organic light emitting display device can further comprise a first conductive fiber tape attached to cover at least a part of the second printed circuit board and the third flexible circuit film so that the second printed circuit board and the third flexible circuit film are in contact with the bottom surface of the support member.

(94) The first conductive fiber tape can be in contact with the second printed circuit board, the third flexible circuit film, and the support member to be electrically connected.

(95) The third flexible circuit film can include a flexible base layer, a first thin film line disposed on one surface of the flexible base layer to face the bottom surface of the support member during the bending, a second thin film line disposed on the other surface of the flexible base layer, and an insulating layer covering at least a part of the second thin film line. The first thin film line can be in direct contact with the support member, and the first conductive fiber tape can be attached to the second thin film line and the bottom surface of the support member.

(96) The organic light emitting display device can further comprise a second conductive fiber tape attached to the second printed circuit board and the support member to electrically connect the support member and a ground electrode formed on the second printed circuit board.

(97) The second conductive fiber tape can be continuously disposed to cover a part of a bottom surface and a side surface of the second printed circuit board and a part of the bottom surface and a side surface of the support member.

(98) The support member can include a plate top disposed below the organic light emitting display panel and a plate bottom disposed below the plate top, and the second conductive fiber tape can be in contact with a part of a bottom surface, a side surface, and a top surface of the plate bottom and be in contact with a part of a side surface and a top surface of the plate top.

(99) The organic light emitting display device can further comprise a carbon plate disposed below the support member, and a first conductive fiber tape attached to cover at least a part of the second printed circuit board and the third flexible circuit film so that the second printed circuit board and the third flexible circuit film are in contact with a bottom surface of the carbon plate.

(100) The organic light emitting display device can further comprise a second conductive fiber tape continuously disposed to cover a part of the second printed circuit board, a part of the carbon plate, and a part of the support member to electrically connect the second printed circuit board to the support member and the carbon plate.

(101) Although the exemplary embodiments of the present disclosure have been described in detail with reference to the accompanying drawings, the present disclosure is not limited thereto and can be embodied in many different forms without departing from the technical concept of the present disclosure. Therefore, the exemplary embodiments of the present disclosure are provided for illustrative purposes only but not intended to limit the technical concept of the present disclosure.

(102) The scope of the technical concept of the present disclosure is not limited thereto. Therefore, it should be understood that the above-described exemplary embodiments are illustrative in all aspects and do not limit the present disclosure. The protective scope of the present disclosure should be construed based on the following claims, and all the technical concepts in the equivalent scope thereof should be construed as falling within the scope of the present disclosure.

Claims

1. An organic light emitting display device, comprising: an organic light emitting display panel including a plurality of sub pixels; a support member disposed below the organic light emitting display panel and formed of a metal material; a first flexible circuit film disposed on one side of the organic light emitting display panel, and configured to be bent toward a bottom surface of the support member; a third flexible circuit film disposed on one side of the organic light emitting display panel, and configured to be bent toward the bottom surface of the support member; and a low potential voltage line disposed on the organic light emitting display panel to supply a low potential voltage to the plurality of sub pixels, wherein the first flexible circuit film and the third flexible circuit film are electrically connected to the low potential voltage line, wherein the low potential voltage is applied to the low potential voltage line via the first and third flexible circuit films, and wherein the first flexible circuit film and the third flexible circuit film are grounded to the support member, wherein the third flexible circuit film includes: a flexible base layer, a first thin film line disposed on one surface of the flexible base layer to face the bottom surface of the support member during bending, a second thin film line disposed on another surface of the flexible base layer, and an insulating layer covering at least a part of the second thin film line, and wherein the first thin film line is in direct contact with the support member.
2. The organic light emitting display device according to claim 1, wherein the third flexible circuit film is disposed on a first side of the organic light emitting display panel, the first flexible circuit film is disposed on a second side of the organic light emitting display panel opposite to the first side.
3. The organic light emitting display device according to claim 1, further comprising: a touch panel disposed on the organic light emitting display panel; and a second flexible circuit film disposed on one side of the touch panel, and configured to be bent toward the bottom surface of the support member.
4. The organic light emitting display device according to claim 1, wherein the low potential voltage line is disposed on the organic light emitting display panel in a closed loop surrounding the plurality of sub pixels.
5. The organic light emitting display device according to claim 4, wherein the first flexible circuit film and the third flexible circuit film supply the low potential voltage to opposite sides of the closed loop of the low potential voltage line.
6. The organic light emitting display device according to claim 3, further comprising: a first printed circuit board connected to the first flexible circuit film, and including a driving circuit configured to supply the low potential voltage to the low potential voltage line; and a second printed circuit board connected to the second flexible circuit film, and including the driving circuit configured to supply a touch signal to the touch panel, wherein the first printed circuit board and the second printed circuit board are electrically connected to the support member.
7. The organic light emitting display device according to claim 6, further comprising: a first conductive adhesive member bonding the first printed circuit board and the support member; and a second conductive adhesive member bonding the second printed circuit board and the support member.
8. The organic light emitting display device according to claim 7, wherein the second flexible circuit film and the third flexible circuit film are attached to the second printed circuit board.
9. The organic light emitting display device according to claim 8, further comprising: a first conductive fiber tape covering at least a part of the second printed circuit board, and attached to be in contact with the support member to be electrically connected.
10. The organic light emitting display device according to claim 1, wherein the support member includes a plate top disposed below the organic light emitting display panel and a plate bottom

disposed below the plate top.

11. The organic light emitting display device according to claim 6, further comprising: a carbon plate disposed below the support member; and a first conductive fiber tape attached to cover at least a part of the second printed circuit board and the third flexible circuit film, so that the second printed circuit board and the third flexible circuit film are in contact with a bottom surface of the carbon plate.

12. The organic light emitting display device according to claim 11, further comprising: a second conductive fiber tape continuously disposed to cover a part of the second printed circuit board, a part of the carbon plate, and a part of the support member to electrically connect the second printed circuit board to the support member and the carbon plate.

13. The organic light emitting display device according to claim 3, wherein an end portion of the first flexible circuit film is disposed on an upper surface of the organic light emitting display panel, wherein an end portion of the second flexible circuit film is disposed on an upper surface of the touch panel, and wherein an end portion of the third flexible circuit film is disposed on the upper surface of the organic light emitting display panel.

14. The organic light emitting display device according to claim 3, wherein the third flexible circuit film is connected to the second flexible circuit film via a second printed circuit board, and wherein the second printed circuit board is configured to supply a touch signal to the touch panel.

15. An organic light emitting display device, comprising: an organic light emitting display panel including a plurality of sub pixels; a touch panel disposed on the organic light emitting display panel; a support member disposed below the organic light emitting display panel and formed of a metal material; a first flexible circuit film disposed on one side of the organic light emitting display panel, and configured to be bent toward a bottom surface of the support member; a second flexible circuit film disposed on one side of the touch panel, and configured to be bent toward the bottom surface of the support member; a third flexible circuit film disposed on one side of the organic light emitting display panel, and configured to be bent toward the bottom surface of the support member; a second printed circuit board connected to the second flexible circuit film, and including a driving circuit configured to supply a touch signal to the touch panel; a low potential voltage line disposed on the organic light emitting display panel to supply a low potential voltage to the plurality of sub pixels; and a first conductive fiber tape attached to cover at least a part of the second printed circuit board and the third flexible circuit film so that the second printed circuit board and the third flexible circuit film are in contact with the bottom surface of the support member, wherein an upper surface of one side of the first conductive fiber tape contacts with the bottom surface of the second printed circuit board and the third flexible circuit film and an upper surface of the other side of the first conductive fiber tape contacts with the bottom surface of the support member, wherein the first flexible circuit film and the third flexible circuit film are electrically connected to the low potential voltage line, wherein the low potential voltage is applied to the low potential voltage line via the first and third flexible circuit films, and wherein the first flexible circuit film and the third flexible circuit film are grounded to the support member.

16. The organic light emitting display device according to claim 15, wherein the third flexible circuit film is disposed on a first side of the organic light emitting display panel, the first flexible circuit film is disposed on a second side of the organic light emitting display panel opposite to the first side.

17. The organic light emitting display device according to claim 15, wherein the low potential voltage line is disposed on the organic light emitting display panel in a closed loop surrounding the plurality of sub pixels.

18. The organic light emitting display device according to claim 17, wherein the first flexible circuit film and the third flexible circuit film supply the low potential voltage to opposite sides of the closed loop of the low potential voltage line.

19. The organic light emitting display device according to claim 15, further comprising: a first

printed circuit board connected to the first flexible circuit film, and including a driving circuit configured to supply the low potential voltage to the low potential voltage line; and wherein the first printed circuit board and the second printed circuit board are electrically connected to the support member.

20. The organic light emitting display device according to claim 19, further comprising: a first conductive adhesive member bonding the first printed circuit board and the support member; and a second conductive adhesive member bonding the second printed circuit board and the support member.

21. The organic light emitting display device according to claim 20, wherein the second flexible circuit film and the third flexible circuit film are attached to the second printed circuit board.

22. The organic light emitting display device according to claim 15, wherein an end portion of the first flexible circuit film is disposed on an upper surface of the organic light emitting display panel, wherein an end portion of the second flexible circuit film is disposed on an upper surface of the touch panel, and wherein an end portion of the third flexible circuit film is disposed on the upper surface of the organic light emitting display panel.

23. The organic light emitting display device according to claim 15, wherein the third flexible circuit film is electrically connected to the second flexible circuit film via the second printed circuit board, and wherein the second printed circuit board is configured to supply a touch signal to the touch panel.
