

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413055
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Royston; Clifton

Ignition suppression circuiting technology

Abstract

A cable system is provided which is configured with both electric wires and a fluid conduit running through the axial passage of a surrounding flexible sheath of the cable. The system allows for communication of electricity over the wires for electrical circuits and concurrent communication of a fire ignition suppressant fluid or gas through the fluid conduit, to all points in an electric circuit using the cable. One or both of a dye or scent can be included in the ignition suppressant fluid.

Inventors:	Royston; Clifton (Metairie, LA)
Applicant:	ISCT LLC (Madisonville, LA)
Family ID:	82446251
Assignee:	ISCT LLC (Madisonville, LA)
Appl. No.:	18/931870
Filed:	October 30, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250055267 A1	Feb. 13, 2025

Related U.S. Application Data

continuation parent-doc US 18752348 20240624 US 12184051 child-doc US 18931870
continuation parent-doc US 18538144 20231213 US 12191644 child-doc US 18752348
continuation parent-doc US 18347545 20230705 US 11855425 20231226 child-doc US 18538144
continuation parent-doc US 17713007 20220404 US 11728633 20230815 child-doc US 18347545
continuation parent-doc US 16834819 20200330 US 11295874 20220405 child-doc US 17713007
continuation-in-part parent-doc US 16230813 20181221 US 10607751 20200331 child-doc US 16834819
continuation-in-part parent-doc US 14913959 US 10170218 20190101 WO PCT/US2016/018978

Publication Classification

Int. Cl.: **H02G3/04** (20060101); **H01B7/04** (20060101); **H01B7/18** (20060101); **H01B7/295** (20060101); **H01B7/42** (20060101)

U.S. Cl.:

CPC **H02G3/0412** (20130101); **H01B7/04** (20130101); **H01B7/18** (20130101); **H01B7/295** (20130101); **H01B7/421** (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
729935	12/1902	Maccormac	N/A	N/A
1821887	12/1930	Fowle	428/592	H01B 5/107
1984553	12/1933	Staples	174/131R	H01B 5/107
2382120	12/1944	White	169/57	H01B 7/295
2879317	12/1958	Wreford	174/23R	H01B 9/001
3170026	12/1964	Woodson	N/A	N/A
3179181	12/1964	Banzato	N/A	N/A
3351706	12/1966	Gnerre	174/105R	H01B 9/024
3551581	12/1969	Goodman	N/A	N/A
3652797	12/1971	Goodman	219/137.9	H01B 9/001
3801724	12/1973	Goodman	439/190	H01B 9/001
3865967	12/1974	Pritchett	N/A	N/A
4836290	12/1988	Le Lande, Jr.	N/A	N/A
5269377	12/1992	Martin	166/385	E21B 17/206
6095252	12/1999	Draugelates	169/58	A62C 3/16
6167178	12/1999	Nave	385/103	G02B 6/4436
6655302	12/2002	Ross	N/A	N/A
7004677	12/2005	Ericksen et al.	N/A	N/A
8193450	12/2011	Kam	174/16.3	H02G 3/0456
9321362	12/2015	Woo et al.	N/A	N/A
9701210	12/2016	Woo	N/A	B60L 53/11
10170218	12/2018	Royston	N/A	H01B 7/295
11865386	12/2023	Malovec	N/A	N/A
2003/0094297	12/2002	Morrow	174/505	H02G 3/06
2004/0231724	12/2003	Mahaney	N/A	N/A

2006/0249298	12/2005	Reece	174/110R	H01B 13/145
2007/0179062	12/2006	Hirose	174/15.5	H01B 12/16
2010/0025053	12/2009	Chesley	N/A	N/A
2010/0080520	12/2009	Lind	385/101	H02G 3/0462
2010/0132964	12/2009	Whitney	N/A	N/A
2014/0221213	12/2013	Fukuda	174/15.5	H01B 12/16
2016/0200206	12/2015	Woo	320/109	B60L 53/11
2022/0231494	12/2021	Royston	N/A	H01B 7/421

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
109475766	12/2020	CN	N/A
3463593	12/2018	EP	N/A
99894	12/2009	RU	N/A
7684	12/2016	SK	N/A
7760	12/2016	SK	N/A
WO-2005/104143	12/2004	WO	N/A
WO-2017/208166	12/2016	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion, International Application No. PCT/US2016/018978, mailed Aug. 11, 2016. cited by applicant

Primary Examiner: Robinson; Krystal

Attorney, Agent or Firm: MARSHALL, GERSTEIN & BORUN LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a Continuation of U.S. patent application Ser. No. 18/752,348, filed on Jun. 24, 2024, which is a Continuation of U.S. patent application Ser. No. 18/538,144, filed on Dec. 13, 2023, which is a Continuation of U.S. patent application Ser. No. 18/347,545, filed on Jul. 5, 2023, which is a Continuation of U.S. patent application Ser. No. 17/713,007, filed on Apr. 4, 2022, which is a Continuation in Part of U.S. patent application Ser. No. 16/834,819, filed on Mar. 30, 2020, which is a Continuation in Part of U.S. patent application Ser. No. 16/230,813, filed on Dec. 21, 2018, which is a Continuation in Part of U.S. patent application Ser. No. 14/913,959, filed on Feb. 23, 2016, which is a U.S. National Stage Entry of International Application No. PCT/US16/18978, filed on Feb. 22, 2016, which claims priority to U.S. Provisional Patent Application No. 62/119,004, filed on Feb. 20, 2015, all of which are respectively included herein in their entirety by this reference thereto.

FIELD OF THE INVENTION

(1) The present device relates to electric systems using cable which is employed throughout the world for communication of electric wires from a buss to individual outlets and connections, as well as communications and other cabling systems. More particularly, the disclosed device and method relate to a cabling system including both electrical and/or communications wiring in concert with an adjacent fluid conduit employable for communication of a fire ignition suppressant fluid or gas such as Halon or a clean agent or inert gas, through the entire cabling system between a

main panel and junction boxes and electrical connection points along the conduit system.

BACKGROUND OF THE INVENTION

(2) Electricity delivery systems in buildings in the U.S. and most of the world have evolved for safety and servicing reasons to employ metal or polymeric conduits, which provide a pathway therethrough for electrical wiring. Such wiring is employed for carrying current from a buss to individual sockets and connectors for equipment requiring electrical power and in other configurations for communications cables running between points. Running the electric and other wiring through a system of conduits protects it from wear over years of use and additionally provides access to retrofit or run new wiring subsequent to the completion of the walls of a structure which will encase the wiring therein. Such conduit in some instances is employed for shielding the contained wiring from EMF which can be generated by wires carrying electricity and electrical signals.

(3) Electricity is conventionally run in individual circuits from a connection to the grid, through a circuit breaker connected to a central buss or other main connection. From the circuit breaker connection to the central buss, the electric wiring extends in a circuit to one or a plurality of remote connectors to which equipment requiring electricity engages. Such circuits may include junction boxes and other connectors downstream. By junction boxes is meant any box or mounting component adapted for joining wires or engaging sockets or distributing electric power or lighting or any electrical box used for any such purpose.

(4) The connection to components using electricity conventionally engages the appliance or device requiring electrical power, to the circuit, using sockets and junction boxes and switches which can also connect with light fixtures and other components of conventional electric systems. For safety reasons, each individual electrical circuit is conventionally wired to carry electricity at a particular amperage load that the equipment or devices anticipated to connect to the circuit will require during use. This is generally accomplished by increasing or decreasing the diameter or size of the wires running through the electrical conduits for larger or smaller current requirements for the equipment connecting to the respective circuit. This wire size requirement is also adjusted by the distance the circuit will travel from the connection to a circuit breaker at the main buss or junction box.

(5) A circuit breaker or fuse conventionally connects each circuit to the buss which is engaged to the power grid. The circuit breaker is generally sized to trip or open, to open the circuit should the amperage load, being drawn by equipment connected to points along the circuit, exceed the designed electrical load of the wiring for the circuit. Thus, the circuit breaker supplying a circuit will have a maximum amperage rating that will cause the circuit breaker to open should the electric load being drawn by equipment engaged to that circuit exceed the amperage rating of the circuit breaker.

(6) This safeguard, designed into electric systems, is an important factor in preventing circuit overload and resulting fires which such can cause. In many instances an electrical fire caused by a circuit drawing excess electric current can be catastrophic such as in a high rise building, a hospital, or on a ship far from port where a fire can threaten the lives of all aboard.

(7) However, even the best designed electrical system is not a total safeguard from an electrical fire caused by circuit overload, resistive heating at junctions or sockets, loose connectors, sparking, over voltage, or damaged electric lines and the like. For example, loose connections at a socket or wire connection in a junction box, will not cause an overload of current which will trip a circuit breaker. However, loose connections, along with over voltage situations, can generate resistive heating and in some cases sparking, which can easily ignite adjacent flammable materials in walls and ceilings and the like.

(8) Further, over time, by accident or design, circuit breakers can be replaced with replacement breakers having amperage ratings exceeding the circuit they supply. Such can easily occur during maintenance when a circuit breaker is replaced with one of higher amperage due to the installed

circuit breaker constantly tripping. While electricians would not make such a replacement, untrained personnel, owners and tenants, are well known for implementing such a fix.

(9) Installing circuit breakers which have current ratings which exceed that anticipated in the circuit, can easily result in resistive heating of wiring along the circuit in places hidden from discovery such as in within conduits or junction boxes. This is caused by the circuit feeding electricity to more equipment on the circuit with a sum amperage being used which exceeds that for which the circuit was designed.

(10) Further, loose connections along the circuit which cause resistive heating to occur during normal operation with the correct breaker engaged in the circuit, will emit heat which is significantly increased should the circuit draw more current than the maximum design. Such resistive heating and even sparking frequently occurs in junction boxes where multiple wires are engaged by wire nuts, terminal blocks, or in boxes housing electrical sockets and the like.

(11) Additionally, connectors such as sockets and switches can over time become damaged or loose from the wire supplying them, or engaged in a manner which causes heating within the conduits and junction boxes. Again such occurs out of sight by users and inspectors, but adjacent flammable wood or plastic or insulation materials in walls and floors which become pyrolyzed from continuous or instantaneous overheating will have a reduced ignition temperature.

(12) Such overheating of wiring in a junction box, or wall box holding an electrical socket or switch can thus easily become an ignition source and the cause of a fire. This is especially dangerous, since with the heat generated by loose connections or wires running electricity exceeding the wire capacity, continues for the duration of the ongoing communication of electrical current to the circuit. Thus, not only does the wiring become hot enough to ignite the insulation covering the wires, or the walls, ceilings, floors, and other adjacent flammable materials, this heat continues as long as the circuit is powered, and even after a fire has erupted in most cases leading to faster fire spread.

(13) Of course, such an ignition source and resulting fire is hidden and extremely hard to initially detect and just as hard to extinguish once discerned. Thus, the risk of fire ignition and passage through interior wall cavities from overheated electric circuits and the like, is not readily apparent to a layman, but is well known to those in the business of electrical fire safety.

(14) Often, as employees and firefighters do not have access to such relatively small spaces in order to view and discern flames, and to extinguish the flames, as typical water suppression systems are not supposed to be applied to electrically generated fires as that can pose additional fire safety risk for first responders or inhabitants trapped by the fire and the resultant fire spreads. Consequently, these fires can spread easily and quickly, even through structures constructed of fire-resistant material. Such a fire can ignite in the cable or wiring itself in a wall or ceiling if it becomes overheated or has been damaged by abrasion, rodents, lighting, or by other means where it can be exposed or slightly cut. Such fires can ignite in a junction box of a socket or where multiple conduits connect in a wall, to become a raging inferno and spread quickly from the ignition source by traveling through interior spaces of the ceiling or walls.

(15) Still further, in these modern and uncertain times, fires in wiring between circuit breakers and junction boxes can be ignited by an electromagnetic pulse caused by nuclear detonation of either a conventional or what is known as a “dirty” bomb. Such an electromagnetic pulse occurred in Hawaii, decades past when testing by the military detonated over the Pacific Ocean, and could easily occur again in this uncertain world. One such occasion, the copper conductors of all conventional cable wiring systems can instantly overheat which could/would lead to insulation degradation and fire. Such for example can occur as a result of directed energy weapons.

(16) While such potential from overheated circuits of all kinds is dangerous in homes, the risk of harm and loss of life is significantly higher in commercial establishments, high rises, and especially in airplanes, space ships, container ships or cruise ships, since a fire on the open sea in such metal ships spreads quickly and can cause massive loss of life.

(17) Accordingly, the ability to confine an electrically ignited fire to a single room or area, may depend upon the ability to preclude its travel through walls and electrical fixtures, or to accelerate to a larger fire subsequent to ignition. Although previously described conduit systems and fire-proof and fire-resistant junction boxes are formed of materials meant to resist the flames, conventional conduit style electric wiring systems provide no means to extinguish a fire, once ignited in the circuit or in wall or ceiling or other space adjacent thereto, or in a junction box where such cables engage other cables or sockets for appliances. While the noted, use of conduit for communication of electrical wiring through buildings and ships and aircraft provides a pathway to contain the wiring, the heat and smoke generated therein easily escapes to the surrounding area and initiates fires.

(18) However, conventional wiring and infrastructure systems provide no concurrent and jointly communicating pathway for the communication and activation of fire suppression chambers, and suppression devices and components. Instead, such fire suppression materials must be brought to the source of an electrical fire from a remote position such as a fire extinguisher. Such takes time by the time a wall-hidden or conduit-hidden fire is ongoing but first detected. This time wasted, in seeking out a fire suppressant supply and communicating it to the exact location of the previously hidden electrical fire, gives that fire time to spread even further or significantly intensify due to continued electrical heating, where the resulting flames travel through walls and conduits of the structure.

(19) As such there is an unmet need for a cabling system and method configured to route both wiring of electrical circuits in parallel adjacent pathways and through junction boxes and the like, which concurrently allows for positioning of a fire suppression chamber and supply system proximate to any potential fire generated in a conduit or wall or structure. Such a cabling device and method, in addition to providing suppression at or proximate to the point of any hidden or viewable electrical fire, should allow for concurrent positioning for a fire suppression pathway and suppression chambers along and adjacent each circuit of electrical wiring. Such a system should also provide site specific fire suppression components positionable in junction and access areas and adjacent electric wires in the conduit system, which will automatically deliver fire suppressant to an overheated circuit. Such a cabling system when employed for fire suppression should also, once activated at a position along the conduit system for electrical wiring, provides a means for cutting electrical power to the individual circuit which has overheated and for signaling and alerting employees and emergency personnel of an overheated circuit or fire caused by one, even where that fire is not yet viewable.

(20) The forgoing examples of related art and limitation related therewith are intended to be illustrative and not exclusive, and they do not imply any limitations on the invention described and claimed herein. Various limitations of the related art will become apparent to those skilled in the art upon a reading and understanding of the specification below and the accompanying drawings.

OBJECTS OF THE INVENTION

(21) It is an object of the present invention to provide a cabling system and method, which includes a concurrent installation of both electric circuits and a fluid conduit and suppression chambers, adapted for supply by centrally supplied fire suppressant circuits, which are communicable in concert with the electrical wiring pathway from a circuit breaker buss to and through each junction box and housing along the path of each electrical circuit.

(22) It is an additional object of the system herein to provide for suppressant-delivering components such as suppression chambers which are engageable with the fluid tubing along a fire suppressant pathway running adjacent or coaxial with the electrical conduit, which will self-activate to communicate fire suppressant to a circuit which has overheated due to resistive heating automatically.

(23) It is an additional object of the cabling system and method herein to provide means to alert the user of a fire or resistive heating or sparking in an electric circuit, even where hidden by walls or

conduits, along with the concurrent automatic release of fire retardant to the source of the resistive heating or sparking.

(24) It is yet another object of the present invention to provide a cable having a fluid conduit and wires which is thereby configured for concurrent routing of electrical wires and a fluid pathway for fluid delivery such as a flame retardant material.

(25) It is yet a further object of this invention to provide such a cable system which is configured to extinguish fires from sparking and resistive heating and the like in any electric circuit between junctions, as well as sense activation of such a fire suppression and concurrently cut electrical power to that circuit.

(26) These and other objects, features, and advantages of the present invention, as well as the advantages thereof, over existing prior art, which will become apparent from the description to follow, are accomplished by the improvements described in this specification and hereinafter described in the following detailed description which fully discloses the invention, but should not be considered as placing limitations thereon.

SUMMARY OF THE INVENTION

(27) In accordance with the purposes of the present invention, as embodied and broadly described herein, the present invention provides a system and method which includes a cabling system enabling the adjacent concurrent routing and proximal positioning, of both wires carrying electricity and a fluid conduit or tube. The tube or conduit for fluid flow, can be configured to automatically dispensed fire suppressant, within the conduits, junction boxes, and other components of an electric wiring system for communicating electrical power. The tubing or conduit providing fire suppressant circuits of the cabling system are configured to run along the same pathways through a structure as the wires and electrical junctions of an enclosed electrical system circuit. Employing the cabling and connectable components herein, both the electric wiring and fire suppressant system may be installed concurrently during construction of the structure or vehicle, where the electric system is installed.

(28) The system herein provides an electric cable surrounded by a sheath or cover which also includes a tubing or conduit pathway for communication of fluid or gas along the electric pathway of the cable. The cabling may be thus employed in one mode for delivery of a pressurized fire suppressant supply, which runs within or in combination with and parallel to the electric wiring in an electric conduit pathway for wiring. Some of the further components employable with the cabling system herein for fire suppression, include for example, suppressant chambers, junction box-housed fire suppressant dispensers, which are proximate to the positioning of electric wires joined in a circuit or which communicate in connections to sockets or connectors in a junction box which in turn connect to electricity-consuming devices.

(29) The system includes retardant dispensing components adapted for engagement to the fluid conduit of the cabling, which are configured for operative positioning in engagements within or to junction boxes, sub-panels, and socket or connection boxes, light fixture mounts, and the like. The dispensing components are configured to engage electric sockets and connectors as well as junctions between wires which enter or exit therefrom. The fluid conduit itself is formed of a material adapted to melt at a temperature indicative of a fire or overload from resistive heating and dispense suppressant at locations in between the circuit buss disconnect assemblies, and junction boxes.

(30) Connections between fluid conduit or tubing and dispensing components in one preferred mode of the system, employ circular junction points although alternative configurations can optionally include specific terminal male or female connectors for easy disassembly and access. The junction boxes having retardant dispensing components operatively mounted therein or thereto, may also include sub panel breakers and busses, and/or sockets engageable with appliances or lighting or other devices consuming electric power.

(31) To inhibit the spread of electrical fires, the junction box and other inter-connecting

components for connecting and routing of electric circuits, may additionally contain or have attached, a suppressant dispensing component such as a suppressant chamber, capable of holding a reservoir and releasing a specific volume of fire retardant material into the housing or junction box or the like. The tubing or fluid conduit of the cabling herein, can supply this fire retardant from a central source also, or in some systems charge each such suppressant dispensing component or chamber forming a local reservoir, and communicate additional suppressant from a central or remote source at a distal end of the fluid conduit.

(32) In the preferred mode of the device, the suppressant chamber, when operatively engaged with the fluid conduit, can be composed of a thin housing, which can be ruptured by impact, or which is configured of a thickness and of a material which will melt or open when exposed to a temperature level, indicative or generated by a fire or from overheating caused by resistive heating in wiring, prior to an ignition of a fire. The device should be configured for the fluid tubing or conduit of the cabling to engage and accommodate and dispense fire retardants which are either gas or liquid at room temperature such as Halon, and to provide a continuous or a specific volume communication of such to a locale until turned off.

(33) Additionally preferred, junction boxes for electrical wires and sockets and the like, may contain two or more suppressant ports, configured to engage with the fluid conduit of the cabling to draw retardant material from multiple sources, such as nearby junction boxes, for increased fire fighting capability.

(34) It is preferred in one mode, that a dispensing component such as a suppressant chamber or port include a visible viewable suppressant window, thus allowing for visual confirmation of the presence of a retardant supply therein. The suppressant ports or suppressant chambers can additionally contain one or a combination of fire and retardant activation sensors from a group including heat sensors, microphones, pressure sensors, dyes, color reactive films, accelerometers or contact switches.

(35) One or many flow sensors attached to the fire suppressant buss supplying the fire suppressant to fluid conduit of the cabling, or embedded within the suppressant ports or at locations on the fluid conduit, can also be used to detect a suppressant chamber rupture or a dispensing of retardant, and to send a signal to a central monitoring station, and/or to the circuit breaker supplying the individual electric circuit, to turn off electric power. Additionally, weight measurements can be monitored of fire suppressant tanks and should the weight of the tank drop, the electrical power can be disconnected.

(36) The sensor data can either be displayed proximal to individual suppressant component positions of the system, or through an external light or viewing screen, or viewing window. Such data might also be routed as an electric or preferably wireless signal to a central panel for efficient and simultaneous monitoring and diagnosis of all devices running along individual tubing pathways in the system. Remote display panels should contain means to uniquely identify the retardant tubing in relation to the circuit it supplied to each junction box by description or identification number.

(37) In another or second preferred mode of the device, a local supply of the retardant material may be stored within the suppressant chamber and as such, the suppressant chamber formed as part of or engaged with the junction box, may dispense retardant which may be supplied or replenished by a conduit connection to the suppressant tubing system. All or at least portions of the suppressant chamber should be formed of material, such as HDPE, pfa, nylon or similar polymeric material.

(38) The cabling herein, in all preferred modes, is configured to include and route one or more electric wires, and at least one adjacent fluid conduit, both of which are surrounded by an outer jacket or sheath. This configuration of both wiring and fluid conduits within an axial passage of a surrounding jacket or sheath, allows for easy concurrent installation of both a suppressant carrying conduit for gas or fluid, and electrical wires, in a manner similar to the conventional installation of wiring cables such as ROMEX or shielded cabling. When the fluid conduit is configured to carry

fire suppressant, all or portions of the fluid conduit may be formed of material adapted to melt or rupture upon reaching a temperature indicative of fire or overheating from resistive heating or sparking. Thus, the same cabling provides for communication of fluid or gas flame suppressant supplies to all points on the installed electric cable system, from the circuit breaker to all points along the circuit.

(39) In one preferred mode of the device, where suppressant is supplied from one end, the cabling includes a sheath or flexible jacket surrounding the electric cables and a fluid conduit which may include a series of perforations in the sheath. These perforations have been shown in experimentation, to allow for trimming during installation. Further, during testing unexpectedly it was found that the perforations or apertures also provided pathways for the dispensing of fire retardant material, to areas surrounding the cabling, should the tubing or fluid conduit carrying the retardant, be exposed to fire or heat within a wall which is of a temperature which will melt it. Additionally, one or a combination of currently available electrical protection devices can also be employed within the junction box for additional protection from a group including surge protectors, dedicated fuses, arc fault protective devices, and ground fault intercepts.

(40) When the cabling herein is employed in forming electric circuits, the junction boxes or gang boxes and the like, should be composed of one or a combination of durable fire resistant materials such as metal, aluminum, code-allowed plastic, fiberglass, glass or ceramics. The fluid conduit of the cabling should be made of one or a combination of polymeric materials, which are non-reactive from a group including polymeric material, plastic, nylon, PVC, polyethylene, or fiberglass or other material which is inert in the presence of the fire suppressant carried within.

(41) Particularly preferred is the employment of High-density polyethylene (HDPE) for the fluid conduit included in the cabling. HDPE has been shown in most indoor installations of the cabling herein to be superior as fluid conduit to supply retardant. This has been found to be due to HDPE's ability to maintain its structural integrity when exposed to heat below that of fire or potential fire over long periods of time. HDPE, pfa, nylon or other similar materials have a melting point of substantially 400 degrees Fahrenheit which enhances the ability of the fluid conduit to stay strong and resist melting when adjacent to electric circuits which can naturally heat daily during use.

(42) For example, a common electric wiring insulator material is PVC which melts at a first melting temperature which is substantially at 320 degrees Fahrenheit. As such, the material for the fluid conduit should preferably stay intact and not rupture or leak to a second temperature, beyond the first temperature of 320 degrees Fahrenheit, which the wires might reach, carrying a high current load. Thus, nylon with a melting point between 400 to 500 degrees Fahrenheit, or High Density polyethylene, with a melting point substantially at 400 degrees Fahrenheit would be good choices to maintain the fluid conduit intact, unless the circuit or area goes beyond a possible operating temperature where a fire or potential fire is present. In all modes of the device herein, the melting temperature of the fluid conduit, or the second melting temperature, should preferably be above a first melting temperature of the insulation on the electric wires.

(43) However, once the temperature threshold is reached due to overheating of the circuit such as from resistive heating, sparking, or fire, the fluid conduit will rupture and provide suppressant directly at the source of the fire anywhere along any circuit path allowing for purging of conduits systems, concealed wall spaces or within dedicated enclosure assemblies.

(44) Other non metal materials used for the fluid conduit during experimentation, showed signs of softening when exposed to heat over time at temperatures below that which might be considered dangerous in some instances and thus could cause leaking and fire alarms where none are present. Thus, system reliability in longer term installations, and where electric wiring carries current causing normal but ongoing heating, HDPE or nylon would be more preferable for use in the fluid conduit of the cabling when supplying fire suppressant and used with wiring carrying conventional PVC insulation. However, the material for the fluid conduit can be changed or adjusted such that it will fail and release the fire suppressant at a temperature higher than normal operating circuit

temperatures.

(45) The cabling system herein is described for the provision of cabling having both electric wires and a fluid conduit for supplying fire suppressant to allow for the easy installation of a combination wiring system and fire suppressing system during construction or retrofit of a building or structure. The cabling of the system herein would be especially useful to protect cruise ships, hospitals, nursing homes, airplanes, submarines, museums, data centers, banks, underground bunkers, as well as the noted use in buildings, businesses, restaurants, and residences, or in any situation where one skilled in the art would consider the ability to automatically sense potential or actual electrical fires and extinguish them.

(46) However, using the uniquely configured cable herein having both a fluid conduit and electrical wires in the same installed cabling component, the cabling can also be employed for other uses where electrical wires along with a fluid conduit would be beneficial. Such could include, but should not be limited to, outside power distribution circuiting, either over roof tops, or in desert (solar farm) style applications, for production plants, in areas of weather having high heat for carrying electricity, and other installations. In these modes, instead of fire retardant or suppressant being charged and delivered by the fluid conduit of the cabling, fluid conduit can be charged with a non conductive coolant, glycol for example, which when flowing through the system can help with heat dissipation.

(47) Additionally, the cabling herein would be helpful in very hot environments, where an engineer must de-rate (increase the size) of the conductors employed for carrying electric current to account for over heating due to ambient temperatures. Using the cabling herein with the unique combination fluid conduit and electrical wiring running adjacent, the user can employ the fluid conduit to flow the fluid to cool the circuits. This could eliminate the expensive de-rating of wiring due to outside or environmental ambient impacts.

(48) Still further, in another mode, components such as lamps could have small canisters of fire retardant mounted within the assembly and traverse the power circuit using the fluid gas line from strain relief up to light socket in combination with a simple locking switch, to either directly short the conductor to cause a breaker to trip or open should the canister release.

(49) As such, before explaining at least one preferred embodiment of the herein disclosed invention in detail, it is to be understood that the cabling invention is not limited in its application to the details of construction and to the arrangement of the components in the following description or illustrated in the drawings which primarily are directed to the use of the combination fluid and electrical conduit in buildings, structures and vehicle for fire suppression. The cabling system herein described and disclosed in the various modes and combinations is also capable of other embodiments and of being practiced and carried out in various ways which will be obvious to those skilled in the art. Any such alternative configuration as would occur to those skilled in the art is considered within the scope of this patent. Also, it is to be understood that the phraseology and terminology employed herein are for the purpose of description and should not be regarded as limiting.

(50) As can be discerned, those skilled in the art will appreciate that the conception upon which this disclosure is based may readily be utilized as a basis for designing of other systems of cabling with concurrent and adjacent positioning of electrical circuits and at least one fluid carrying conduit. It is important, therefore, that the claims be regarded as including such equivalent construction and methodology insofar as they do not depart from the spirit and scope of the present invention.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The accompanying drawings, which are incorporated herein and form a part of the

specification, illustrate some, but not the only, nor exclusive examples of embodiments and/or features of the disclosed system. It is intended that the embodiments and FIGS. disclosed herein are to be considered illustrative of the invention herein, rather than limiting in any fashion. In the drawings:

(2) FIG. 1 depicts a perspective view of a junction box employable with the cabling herein, depicted for example in FIGS. 8-17.

(3) FIG. 2 shows a front view of the junction box of FIG. 1 engaged in operative engagement with the cabling herein carrying both electric wires and one or more fluid conduit lines carrying fire suppressant.

(4) FIG. 3 displays a perspective view of one preferred mode of the cabling of the system herein which is formed with wires for electric communication in parallel adjacent positioning with at least one fluid conduit configured for fluid or gas flow therethrough, such as a fire suppressant fluid.

(5) FIG. 4 shows an electric junction box configured for engagement with the cabling herein, showing in exploded view, a suppressant chamber engaged as a cover.

(6) FIG. 4a depicts the junction box of FIG. 4, assembled.

(7) FIG. 5 depicts a gang box configured for positioning of electric switches, having a suppressant chamber with opposing openings, adapted for engagement with the electric wires and fluid conduit of the cabling herein.

(8) FIG. 6 shows an example of the cabling herein employed as a fire suppressant system having both electrical circuits and fluid conduits carrying fire suppressant, running from a central position or switch room.

(9) FIG. 7 depicts a mode of employment of the cabling herein in a fire suppressant system, showing the combination electrical buss for electric circuit breakers and the retardant supply buss having an optional dye and/or scent supply therefor, positioned to route retardant through the fluid conduit of the cabling, where both the fluid conduit and electric wires run in the cabling in a substantially parallel communication to different electric circuits.

(10) FIG. 8 shows the cabling herein having a fluid conduit with wiring positioned in the sidewall forming the fluid conduit and a surrounding flexible sheath.

(11) FIG. 9 shows the cabling herein formed with a fluid conduit and wiring running through the axial passage of the surround flexible sheath.

(12) FIG. 10 depicts the cabling herein in another mode with a plurality of electric wires and at least one fluid conduit running axially through the surrounding sheath which has perforations or sequential aligned apertures formed therein.

(13) FIG. 11 shows the cabling of the system herein wherein the plurality of wires carried in the sheath axial passage is four, and a single fluid conduit runs parallel thereto.

(14) FIG. 12 depicts a mode of the device wherein electric wires are positioned within the material forming the fluid conduit in a unitary structure of cables and fluid conduit.

(15) FIG. 13 is an end view of the mode of cabling of FIG. 12.

(16) FIG. 14 shows that the cabling can carry both a plurality of electric wires as well as one or more communications cables which run within the axial passage of the surrounding sheath along with the fluid conduit.

(17) FIG. 15 depicts the cabling of FIG. 14 showing perforations or sequentially aligned apertures formed in the sheath providing the axial passage for the fluid conduit and wires.

(18) FIG. 16 shows a mode of the cabling herein having an flexible but armored sheath surrounding the axial passage carrying at least one fluid conduit and one or the shown plurality of wires for electric current.

(19) FIG. 17 depicts the cabling herein, wherein the electric wires are carried in the sidewall forming the fluid conduit herein, where the wires may be extruded with the fluid conduit, or pressed into channels formed in the exterior of the fluid conduit.

(20) FIG. 18 shows differing connectors for engaging the fluid conduit of different cables for fluid

flow therebetween.

(21) FIG. **19** depicts a sliced view showing an interior passage of a fluid conduit in a sealed engagement with a fluid connector such as in FIG. **18**.

(22) FIG. **20** shows exemplars of a sub panel, in exploded view, which is adapted for engagement with both the wires, and the fluid conduit of the cabling herein, to provide electric power to the buss and fire suppressant to the fluid dispenser.

(23) FIG. **21** shows the sub panel of FIG. **20** assembled and ready for engagement with both the wires and fluid conduit of the cabling herein.

(24) FIG. **22** shows the cabling herein with the wires and fluid conduit of the cabling in operative engagement with a junction box, and fluid dispenser showing a fluid dispensing sprayer engageable with the fluid dispenser.

(25) FIG. **23** shows the cabling of the system herein, connected in a circuit for both the fluid conduit and wiring.

(26) FIG. **24** shows the cabling of the system herein providing both wiring and a fluid conduit operatively engaged to provide fire suppressive material for both socket connectors as well as overhead dispensers of fire suppressant, such as in a server room.

(27) FIG. **25** depicts a mode of the cable for the system herein having romex type wires running the axial passage of the surrounding sheath along with the fluid conduit.

(28) FIGS. **26A-26C** show views of a mode of the cable herein wherein the wire running within the axial passageway within the sheath of the cable is formed in a tubular fashion with wires within insulation which is configured to form a channel providing the fluid conduit.

(29) FIGS. **27A-27B** depict views of a mode of the cable for the system herein wherein the wires are in an encircling wind in engagements with the exterior of the polymeric material forming a fluid conduit which runs through the axial passageway of the sheath of the cable.

(30) FIG. **28** shows a junction box adapted for engagement of a socket therein and showing a chamber for holding retardant fluid therein which is slidably engageable into the junction box and has connectors **31** for provision of retardant fluid flow into and out of the chamber.

(31) FIG. **29** depicts a junction box of the system herein which has the fluid chamber formed as an upper portion of the junction box wherein electrical connections, such as to a socket, are positioned within the cavity of the junction box at a position underneath the fluid chamber.

(32) FIGS. **30-30A** show front and rear views of an especially preferred mode of a junction box of the system herein which is formed in a unitary structure of chamber and junction box wherein the formed chamber surrounds the internal cavity of the junction box which may be adapted for mounting or housing any electric connection such as the depicted socket engaged therein.

(33) FIG. **31** depicts a junction box of the system herein similar in function to that of FIG. **30** where hollow sidewalls, surrounding the interior cavity which is adapted for the appropriate electric connection and fluid conduits communicate fluid through the passages in the hollow sidewalls.

(34) FIG. **32** shows a mode of a junction box of the system herein wherein the internal cavity of the junction box is accessible through a first side opening by removal of a conventional cover and which has a fluid chamber engaged to the opposing side opening which is adapted with connectors for fluid flow therethrough.

(35) FIG. **33** depicts a junction box configured with one or a plurality of openings for passage of wires therethrough operatively into and out of the internal cavity and showing an insertable circuitous fluid tube holder for the tube which has connectors on both ends for operative connection to the fluid conduit.

(36) FIG. **34** shows the device as in FIG. **33**, assembled with the fluid tube holder and tube engaged thereon operatively positioned within an internal cavity of the junction box.

(37) FIG. **34A** depicts a junction box configured with one or a plurality of openings for passage of wires therethrough similar to FIG. **33**, and showing an insertable circuitous fluid tube holder

engageable to form a circuitous path for the tube through the junction box wherein it forms the reservoir.

(38) FIG. **34B** shows the device as in FIG. **34A** assembled with the fluid tube holder and tube wound thereon, operatively positioned within an internal cavity of the junction box.

(39) FIG. **35** depicts an extension cord configured with a fluid conduit for fire retardant of the system herein wherein retardant for the fluid conduit can be provided by an onboard pressurized supply or by a plug and receptacle adapted to sealably engage and communicate the retardant fluid from the fluid conduit communicating to the junction box.

(40) FIG. **36** depicts the extension cord similar to that of FIG. **35** wherein the cord housing engages with the wall socket.

(41) FIG. **37** shows a component of the system herein operating in a similar fashion to that of FIGS. **30-31** showing a housing formed to surround an electric inverter wherein the housing sidewall surrounding the internal cavities and components therein are hollow and form passages for fluid retardant therein.

(42) FIG. **38** depicts a junction box for the system herein, which has fluid nozzles formed to emit a directional flow of fire suppressant fluid therefrom.

(43) FIG. **39** shows exemplars of some of the nozzles which can be formed to emit a narrow, pointed, or wide flood of suppressant fluid therefrom.

(44) FIG. **40** shows a mode of the device herein, wherein the nozzles are formed in an engageable nozzle panel in a fluid-sealed engagement with the junction box where the nozzle panels can be from a kit of such including a variety of fluid directing nozzles formed in such nozzle panels.

DETAILED DESCRIPTION OF THE DRAWINGS

(45) Now referring to the drawings in FIGS. **1-40**, wherein similar components are identified by like reference numerals, there is seen in FIG. **1**, and other drawings where components are configured for operative engagement with the cabling **11** herein, to provide one or a plurality of wires and at least one fluid conduit, in the same cable **11** surrounded by a sheath **24** or cover. As noted, the cable **11** herein is employable with other systems where the parallel and concurrent positioning of both a fluid conduit **26** and electric wires **28** along the entire path of the same cable **11** would be beneficial.

(46) As shown in FIG. **1**, when the cable **11**, such as in FIG. **3** or FIGS. **8-17** herein, is employed to provide a combination electric wiring system and fluid passage for a fire suppressant system, the cable **11** is operatively engageable with other components in the system such as a junction box **12** or gang box or terminal box component, which is meant as any electrical box or the like used to join wires, engage sockets, lighting, sub circuits or for other purposes for such electrical boxes. The junction box **12** may be configured to house both electric connections therein such as to or between other wires **28**, and/or an electric socket **16**, and/or a fire suppressant component or chamber **18**, or other fire suppression fluid or gas emitter.

(47) The cable **11**, when employed in a fire suppressing electrical system **10**, is deployable in a variety of configurations, such as with one or more gang boxes or junction boxes **12**, shown in FIGS. **1** and **2** and **5**, for example. Such a junction box **12**, surrounds and secures the electrical connections between two or more of the wires **28** which enter or exit through one or more apertures defining openings **14**.

(48) Such junction boxes **12** are known by other names and surround connections mid circuit and are also used for sockets, light fixtures, and a wide variety of connections. However, this description should not be limiting as junction box **12** should be considered to be any housing where cables are joined, divided, connected to an electric device, or for other purposes. Although the openings **14** shown herein in the system **10** consist of circular apertures formed in the junction box **12**, alternative constructions can optionally include specific male or female connectors for easy disassembly and access.

(49) As an example, the junction boxes **12** may be configured to engage with conventional sockets

16 or switches **17** of electric fixtures, and/or wire **28** connections with wire nuts, terminal blocks, and other conventionally employed electrical components and junctions to configure the system for engagement of components to the electrical power within.

(50) To inhibit the spread of electrical fires, in the system herein, junctions between conduits and wiring in the electrical system such as at any type of junction box **12**, may also include a suppressant chamber **18**. The suppressant chamber **18** is configured to receive and hold a supply of fire suppressant or retardant such as Halon gas from the fluid conduit **26** which communicates with a central supply under pressure. The suppressant chamber **18** holds such fire suppressant or retardant within an internal cavity defined by the walls forming the suppressant chamber **18**. The suppressant chambers **18** may be configured to hold a local supply of retardant therein, should the fluid conduit **26** supplying the system fail, thus maintaining a local sealed supply of retardant or suppressant in each chamber **18** if the fluid conduit **26** is compromised. This can be done using valves on the inlet **29** and an outlet **29** of the suppressant chamber **18**. Or the suppressant chamber **18** may be provided a fluid supply from the fluid conduit **26** which is communicated from a reservoir of suppressant.

(51) The system **10** is configured such that any damage to the junction box **12** or its contents, through excess heat or fire, such as caused by electrical short or over-heated wiring **28**, will melt and cause a rupture of all or portions of the suppressant chamber **18**. Upon the formation of a heat induced rupture, the retardant or suppressant within or supplied to the suppressant chamber **18**, is communicated to the fire or overheating area. As shown, the fluid conduit **26**, can supply each suppressant chamber **18** and junction box **12**, with a continuous pressurized supply of retardant or fire suppressant which will continue to extinguish or prevent a fire from getting larger. As noted, all, or at least portions of the fluid conduit **26** itself, can be formed of material adapted to melt and rupture at a threshold temperature, and communicate the fire suppressant to adjacent areas anywhere the cable may be located in a wiring system, such as in-between junction boxes **12** and fixtures and a circuit breaker buss.

(52) In one preferred mode of the system **10**, all or portions of the suppressant chamber **18** can be composed of material, such as HDPE, pfa, nylon or similar polymeric material with a wall thickness which is calculated to melt and or otherwise open when exposed to a temperature over a determined safe level or when exposed to fire. This will cause a continuous dispensing of fire retardant or suppressant to extinguish the fire, or prevent one, by preventing oxygen from reaching the heat source. With regard to the wall thickness, it can calculate to fail, due to the internal pressure within the suppressant chamber **18**, when heated to a point the wall will distend and fail.

(53) Shown in FIGS. **2** and **4** and **5**, the junction box **12** is adapted to operatively engage with the fluid conduit **26** either through a conduit opening **20**, or by communication of the entire cable **11** through an opening **14**. Each suppressant chamber **18** is configured for a sealed engagement with the fluid conduit **26** running through the cable **11** herein, to provide the suppressant chamber **18** with a fluid or gas suppressant supply.

(54) For such engagement for example, the suppressant chamber **18** can be configured with one or a plurality of flanges **19** with axial passages into the interior cavity of the suppressant chamber **18**, which act as inputs or outputs for fluid to continue the communication of the suppressant through the chamber **18** to subsequent chambers **18** along a fluid circuit with connections therebetween by the fluid conduit **26** running through the axial passage **23** of the sheath **24** of the cable **11** along with the wires **28**.

(55) Preferably, the junction box **12** should include a suppressant window **22** for visual inspection to confirm a local supply of retardant or suppressant is present within the suppressant chamber **18** which is viewable through the window **22**.

(56) One or a plurality of flow and/or pressure sensors **31** may be placed in communication with suppressant axial passage **23** running through the fluid conduit **26** such as in FIG. **7**. For example, sensors **31** such as pressure supply meters, flow sensors, or pressure sensors, shown in FIG. **7**

and/or other electronic sensors which may discern a pressure drop in a fluid conduit **26** circuit, can be operatively engaged with each fluid circuit which parallels an electric circuit running through a cable **11**.

(57) The sensor data can either be displayed proximal to the system **10**, through an external light or screen, or routed to a central safety video display panel, for efficient and simultaneous monitoring and diagnosis of all systems **10**, or in a particularly preferred mode, such as shown in FIG. 7 for example, a signal from the sensors **31** will be communicated in a wired or wireless fashion to a circuit breaker **33** powering the same wire or wires **28** running through a cable **11** with a fluid conduit **26**. The signal will cause the circuit breaker **33** to open, and switch off electric power to the wires **28** in the cable **11** of the circuit where suppressant is being dispensed and which has caused the sensor **31** to generate a signal. Remote display panels, if displaying a sensor signal generation, should contain means to uniquely identify the location and circuit of the sensor **31** generating it. Such a signal could be generated by a weight sensor **31** to allow the system to monitor the weights of the fire suppressant tanks and should the weights fall below a certain threshold, it can shut that circuit down as well.

(58) Depicted in FIG. 3 is one example of the cable **11** herein, showing the sheath **24** forming an axial passageway **23** which provides a pathway for one or more wires **28**, and at least one adjacent running fluid conduits **26**, as shown, although a plurality of fluid conduits **26** can be included in a cable **11**.

(59) Formation of the cable **11** with wires **28** and a fluid conduit **26** running in an axial passageway **23** defined by the surrounding sheath **24**, allows for easy instillation of the cable **11** in a fashion much like conventional conduit routed electrical systems, thereby allowing concurrent positioning of both wires **28** and a fluid conduit **26** throughout the system.

(60) As shown in FIGS. 3, 10, and 15, the sheath **24** may include an array of aligned apertures **32** which allow for easier trimming during installation. Further, these apertures **32** provide vents to communicate fire suppressant from the fluid conduit **26** if a fire or heat melts the fluid conduit **26** to a rupture in between junction boxes **12**. The fluid conduit **26**, as noted, should be made of any non-reactive, durable material such as polymeric material, nylon, PVC or fiberglass, or most preferably HDPE or PFA, which has a melting point which will cause a rupture the fluid conduit **26** at an appropriate temperature above the operating temperature of the wires **28**, to extinguish or retard a fire if needed. The flexible sheath **24** would also preferably be formed of a similar material to that of the fluid conduit **26**, such that it will not melt or rupture in areas where the fluid conduit **26** is also adapted to operate which may be hot.

(61) Shown in FIGS. 4 and 4a is a mode of the junction box **12** which is depicted with the suppressant chamber **18**, configured to engage and provide a removable cover for the internal cavity of box **12**. Such would work well at junctions between main and sub circuits of the electrical system.

(62) In FIG. 5 there is shown a gang box or junction box **12** configured for engagement of electric switches **17**. This mode of the junction box **12** is engaged with a suppressant chamber **18** with connections **29** on both ends, for the fluid conduit **26** for a throughput of suppressant supplied by the fluid conduit **26** through the chamber **18** and on to a subsequent chamber **18**. Windows **22** in the faceplate allow for viewing of the contents of the suppressant chamber **18**.

(63) In FIG. 6 there is depicted an example of the system **10** herein using the cable **11** for positioning of both electrical circuits of the wire **28** and fire suppressant circuits of the fluid conduits **26** running to remote positions from a main electrical connection buss and retardant supply buss.

(64) Shown in FIG. 7, as noted above, shows the system where various circuits of the fluid conduit **26** of each cable **11** connect to a pressurized suppressant supply in a fluid buss. The fluid buss also allows for communication under pressure of one or both of a dye **61** or scent **63** to the fluid supply. The dye may be fluorescent or colorized otherwise easy to see and the scent should be one which is

easily sensed by humans. Such will allow for easier maintenance of the system wherein small leaks can be determined by dye **61** on surfaces adjacent leaks, and even hidden leaks which cannot be seen can be detected by the scent **63** which would permeate surrounding areas.

(65) The wires **28** for each respective cable **11** connect to one of the breakers **33** of an electric buss **35** portion as shown in the example of a combination electric and fluid buss shown in FIG. 7.

Gauges **39** and/or sensors **31** are engaged to suppressant circuits of each fluid conduit **26** and will sense the current pressurization level in each such circuit formed by a fluid conduit **26** in a cable **11**. The fluid conduit **26** and wires **28** of each cable **11** are routed through the axial passageway **23** of the sheath **24** with the wires **28** therein, thereby providing parallel and concurrent communication of electrical power and fluid such as fire suppression along the entire route of each individual circuit of the electrical system.

(66) As noted, FIG. 8 shows the cable **11** herein having a fluid conduit **26** and a plurality of wires **28**, both positioned in axial passage **23** of a surrounding flexible sheath **24** holding the components of the cable **11** adjacent. In the mode of FIG. 8, the material forming the sidewall of the fluid conduit **26**, is engaged with the plurality of wires **28** during extrusion of the fluid conduit **26**. Thus, the fluid conduit **26** and plurality of wires **28** running through the material forming it, are a unitary structure of wires **28** and fluid conduit **26**.

(67) In FIG. 9 is shown the cable **11** or cabling herein configured with a fluid conduit **26** and wires **28** running through the axial passage **23** of the surround flexible sheath **24**. The cable **11** so formed, can be wound into rolls or spools which can be unwound and installed in a conventional fashion thereby encouraging widespread use.

(68) FIG. 10 depicts the cable **11** herein in another mode with a plurality of three electric wires **28** and at least one fluid conduit **26** running axially through the surrounding sheath **24**. The wall of the sheath **24** includes aligned and sequentially positioned apertures **32** which as noted allow for easier cutting of the cable **11** as well as provide vents for passage of fire suppressant from the interior of the sheath **24**.

(69) FIG. 11 shows the cable **11** of the system herein wherein the plurality of wires carried in the sheath **24** axial passage is four, and a single fluid conduit **26** runs parallel thereto.

(70) FIGS. 12 and 13 show a mode of the cable **11** wherein electric wires **28** are positioned during extrusion within the material forming the fluid conduit **26**, and form the fluid conduit **26** and wires **28** in a unitary structure.

(71) FIG. 14 shows that the cable **11** or cabling with a plurality of electric wires **28** as well as one or more communications cables **28a** which run within the axial passage of the surrounding sheath **24** along with the fluid conduit **26**. As with all other modes of the formed cable **11**, it can be wound on large reels and dispensed during installation.

(72) FIG. 15 shows the cable **11** of FIG. 14 having the sequentially positioned apertures **32** formed in the sheath **24** providing the axial passage for the fluid conduit **26** and wires **28**.

(73) In FIG. 16 is shown the cable **11** or cabling herein having an armored sheath **24** surrounding the axial passage carrying at least one fluid conduit **26** and one or the shown plurality of wires **28** for electric current.

(74) FIG. 17 depicts the cable **11** or cabling herein, wherein the electric wires **28** are carried in the sidewall forming the fluid conduit **26** herein. As shown, the wires **28** may be pressed into channels formed in the exterior of the sheath **24** surrounding the fluid conduit **26**.

(75) FIG. 18 shows differing connectors **31** for sealed engagement between ends of the fluid conduits **26**, allowing a number thereof to be fluidly engaged.

(76) In FIG. 19 is depicted a sliced view showing an interior passage of a fluid conduit **26** in a sealed engagement with a fluid connector such as any of those in FIG. 18.

(77) In FIGS. 20-21 are depicted exemplars of a sub panel junction box **12** of an electric system, which is adapted for engagement with both the wires **28**, and the fluid conduit **26** of the cable **11** herein, to provide electric power to the buss and fire suppressant to the fluid dispenser. The

suppressant chamber **18** in the mode shown, has multiple inlet and outlet flanges **19** to allow the flow of suppressant to flow into and through the chamber **18** downline to the rest of the circuit. (78) FIG. **22** shows the cable **11** herein with the contained wires **28** and fluid conduit **26** of the cable **11**, in operative engagement with a junction box **12**, and fluid dispenser **18** engaged with a fluid dispensing sprayer **38** adapted to direct a downward flow of suppressant when activated by heat above a predetermined level. Such would be employed for example on a ceiling of a room to be protected.

(79) Shown in FIG. **23** is a depiction of the cable **11** herein, installed in a structure and providing both wiring **28** and a fluid conduit **26** which may be operatively engaged with a junction box **12** hosting a socket **16**, to provide fire suppressive material through the fluid conduit **26** to the depicted junction box **12** and a subsequent junction box **12** or other point serviced by the cable **11** extending therefrom.

(80) An example of an installation of the system is shown in FIG. **24** where the cable **11** provides the path for fire suppressive fluid for both socket connectors as well as overhead dispensers or sprayers **38** of fire suppressant, such as in a server room. The cable **11** may be any derivation of cable **11** shown and described herein as may the junction boxes **12** and other components.

(81) FIG. **25** depicts a mode of the cable **11** for the system herein configured with romex type wires **28** running the axial passageway **23** of the sheath **24** surrounding the components of the cable **11**. The fluid conduit **26** having an axial passage **25** for retardant communication therethrough is shown running adjacent the wires **11** formed into the romex with all running through the axial passageway **23** of the sheath **24** which is shown with apertures **32** therein.

(82) The cable **11** herein as noted may be configured to form the axial passage **25** therein or position the fluid conduit **26** having an axial passage **25** therein which runs axially through the cable **11**. This is shown in FIGS. **26A-26C** which depict versions of the cable **11** employable herein wherein the wires **28** running within the axial passageway **23** within the sheath **24** are extruded or molded into in polymeric insulation material extruded to define sidewalls surrounding an axial cavity **27**. This axial cavity **27** itself may be employed for the axial passage **25** in substitute of a fluid conduit **26**, or as shown in FIG. **26C** the fluid conduit **26** can run axially through the axial cavity **27**.

(83) Another mode of the cable **11** employable with the system herein is shown in FIGS. **27A-27B**. As shown, some or all of the electric wires **28** may be engaged in a spiral wound or encircling winding engagement with the exterior of the polymeric material forming a fluid conduit **26**. This spiral winding has been found in experimentation to provide excellent phase separation to cancel out flux and minimize electric noise generation. The fluid conduit **26** so formed is provides the axial passage **25** for retardant communication through the system as needed. The wires **28** in this spiral winding or encircling engagement with the sidewall of the polymeric material forming the fluid conduit **26** may be co-molded therein or as shown, may be frictionally or adhesively engaged within slots **42** formed to wind around the exterior circumference of the fluid conduit **26**. The sheath **24** with apertures therein would surround the wire-encircled fluid conduit **26** in same fashion as in other modes shown herein.

(84) Shown in FIG. **28** is a mode of the junction box **12** which is configured to surround an electric connection such as a switch or depicted socket **16** within the cavity **13** surrounded by sidewall of the junction box **12**. In this configuration, a chamber **18** for holding a local supply of retardant fluid therein, is slidably engageable into the cavity **13** formed in the junction box **12**. As shown the chamber **18** has at least one connection **29** as an inlet for retardant into the chamber **18** and preferably has two connections **29** to allow a pressurized flow of retardant into, through, and out of the chamber **18**. A window **22** formed into the socket or switch cover allows for both a viewing of the chamber **18** for visual confirmation of the presence of retardant therein, and for disbursement of fire retardant from the suppression chamber **18** and into non concealed areas such as interior room space areas surrounding the junction box **12**, should temperatures in that surrounding area, reach

the melting point of the material forming the chamber **18** within the area communicating through the window **22**.

(85) In FIG. **29** is shown a junction box **12** of the system herein which has the fluid chamber **18** engaged to form an upper portion and top sidewall of the junction box **12** wherein electrical connections such as to a socket **16** are positioned within the cavity **13** of the junction box **12** defined by the sidewalls of the junction box **12**. As noted above, by junction box **12** wherever used herein, is meant any housing employed in an eclectic wiring system wherein electric connections are made between wires **28** carrying electric current be those connects by wire nuts, crimping, electric receptacles such as a socket **16** or switch, or any other conventional electric connection positioned within the cavity **13** of the junction box **12**.

(86) As shown in FIG. **29**, in this mode of a junction box **12**, with the suppressant chamber **18** forming one sidewall of the cavity **13**, heat within the cavity **13** sufficient to melt the wall of the suppressant chamber **18**, formed as part of the junction box **12** and in communication with the cavity **13**, will cause fire retardant to flood the cavity **13**. Further, a projecting portion **37** of the suppression chamber **18** formed as part of the junction box, projects therefrom in a position to project into and through the window **22**. This positions the projecting portion **37** of the suppression chamber **18** within the window **22**. Thus the projecting portions **37** can be made to project through and forward of the window **22** in the cover and into surrounding open room spaces where electrified content items may connect to junction box.

(87) In FIGS. **30-30A** are depicted front and rear views of an especially preferred mode of a junction box **12** of the system herein. The junction box **12** is shown with transparent sidewalls **15**. As can be seen, the sidewalls **15** defining the cavity **13** of the junction box **12** have connected passages **21** within some or all of the sidewalls **15** which define the cavity **13** of the junction box **12**. Connections **29** for provision of fire retardant communicate with the passages **21** on one sidewall to communicate the fire retardant into the passage **21** of at least one sidewall, and preferably with passages **21** in other sidewalls **15** surrounding the cavity **13** such that fire retardant will flow into and through all of the passages **21** where positioned in sidewalls **15** of a junction box **12**.

(88) This mode of the system herein configures portions of the junction box **12** itself to form the suppression chamber **18** in a unitary structure. In operation, should the electric connection within a cavity **13** of a junction box **12** overheat, at least one of the surfaces of the sidewall **15** defining the suppressant chamber within the junction box **12** and facing the cavity **13**, will melt and cause a communication of fire retardant from a passage **21** in that sidewall **15** into the cavity **13**.

Alternatively, portions of common walls between the sidewall **15** and the cavity **13** may be fully or partially formed of material adapted to melt at the temperature slightly higher or lower than that of the insulation on the wires and melt when temperature inside the cavity **13** exceeds the melting temperature of the **26** conduit.

(89) Further shown in FIG. **30** is a projecting portion **37** of the suppression chamber formed by the junction box **12** itself. This projecting portion **37** in FIG. **30** is sized to project into or through the windows **22** in the cover plate which is shown covered by a hood **43**. Should the projecting portion encounter a temperature high enough to melt, fire retardant from the suppression chamber, formed within the junction box **12** walls and communicating to the projecting portion **37**, will be directed downward by the hood **43**.

(90) In FIG. **31** is shown a junction box **12** of the system herein similar in operation to that of FIG. **30**, where internal passages **21** at least one and preferably a plurality of the sidewalls **15** surrounding the interior cavity **13** of the junction box **12**, are in operative communication with the axial passage **25** of the operatively engaged fluid conduit **26**. In this fashion, fire retardant from the axial passage **25** communicates under pressure into one or more connected passages **25** formed within the sidewalls **15** surrounding the interior cavity **13** forming the suppression chamber **18** within the walls of the junction box **12** which surround the interior cavity **13** and any electric

connection therein. As in FIG. **30** the suppressant chamber **18**, is thus at least partly within the walls of the junction box **12** itself which are adapted to melt at the noted temperature levels herein. (91) Additionally shown in FIG. **31** are the series of pointed projections **49** formed into the surfaces of the sidewall **15**. Should resistive heat or fire develop within or adjacent the junction box **12** sufficient to melt the sidewall **15**, the pointed projections **49** will cause a directional flow of fire suppressant gas or fluid therethrough as they individually melt. These projections **49** can be positioned within the interior cavity **13** and/or on the exterior surfaces of the junction box **12** whereby fire retardant can be projected to areas adjacent the junction box **12**. These triangular projections **49** allow for the charged suppression space to be closer to connection points or energized components as so desired.

(92) In FIG. **32** is depicted a junction box **12** of the system herein wherein the internal cavity **13** of the junction box **12** is accessible through a first side opening **44** by removal of a conventional cover plate **46**. Covering the second side opening **50** opposite the first side opening **44** is a suppression chamber **18** adapted to engage with the second side opening **50** and enclose the electric connections within a closed internal cavity **13**.

(93) As depicted, a side surface **52** facing the internal cavity **13**, has fluid connections **29** adapted to engage the fluid conduits **26** in the circuit to communicate fire retardant through the chamber **18**. Also shown, formed into the side surface **52**, are recesses **54** adapted to hold electrical connections between two wires **28** such as wire nuts **56** secured over time. Further depicted are metal conduits **51** showing that the system herein can route the cable surrounded by the sheath **24** through metal conduits **51** in a commercial setting requiring such. Additionally depicted is a polymeric diaphragm **53** which fills an aperture in the cover plate **46**. This diaphragm **53** may be formed of a polymeric or other material adapted to melt at the appropriate temperature noted herein, to allow disbursement of fire retardant through the opening. The diaphragm also can be configured to have a burst pressure less than the enclosure to protect the enclosure structural integrity should over pressurization of the circuit occur thereby preventing the enclosure from structural failure from suppressant over-pressurization release.

(94) In FIG. **33**, is depicted a junction box **12** in a conventional fashion having sidewalls **15** which surround the internal cavity **13** and where punch-out portions of the sidewalls **15** are shown providing one or a plurality of openings for passage of wires into and out of the internal cavity **13**. Additionally depicted is an insertable track **41** routing windings of a fluid tube **58** which may be a continuation of, or be engaged at both ends to, the fluid conduit **26** to communicate fire retardant into and through the length of the fluid tube **58**. The fluid tube **58** may be pre-positioned or slid into a removable engagement with the junction box **12** and internal cavity through, an elongated slot **60** in one sidewall. Of course the track **41** may also engage a portion of the fluid conduit **26** from the cable **11** which would be engaged thereon in the circuitous route. The assembled mode of the junction box **12** of FIG. **33** is shown in FIG. **34** wherein the track **41** has been operatively engaged within the slot **60**.

(95) Shown in FIG. **34A** is a junction box **12** configured with one or a plurality of openings for passage of wires into the cavity **13** and through the junction box **12** similar to FIG. **33**. Also shown is the slot **60** configured for insertion of the track **41** to hold a fluid tube in a circuitous path thereby forming the suppression chamber from windings of the fluid conduit **26** in a similar fashion to that of FIG. **33**. Such might work well in retrofitting an older electrical system.

(96) The engagement of the track **41** within the slot **60** is shown in FIG. **34B**. As depicted, the suppression chamber is formed by a winding of fluid conduit **26** on the track **41** which has been inserted operatively into the slot **60**.

(97) Shown in FIGS. **35** and **36** depict a mode of the system herein which is a closed system. As shown, the cable herein defines an extension cord **62** adapted for connection to a first or wall socket **16** which is operatively engaged in the cavity **13** of a remotely positionable housing or junction box **12**. This mode of the system herein is self contained and has a fluid conduit **26**

communicating therethrough between a second socket **16** shown as plug receptacle **64** and an internally housed reservoir **66** of pressurized fire retardant within the housing. In this mode of the system, should the extension cord **62** overheat, the resulting communication of fire retardant to the overheating point on the extension cord **62** will extinguish any flame. While not shown, the apertures **32** can be formed in the flexible sheath of the cable forming the extension cord **62**.

(98) A similar self contained mode of the system herein is shown in FIG. **37**. As depicted a housing **68** is configured for positioning of larger electric components within the interior cavities **13** of the formed housing **68** which is defined by the surrounding sidewalls **15**. Shown in a transparent rendition the sidewalls **15** form an internal cavity having a reservoir **66** of fire retardant therein. The reservoir **66** connects through the fluid conduit **26** to the extension cord **62** to a remote plug receptacle **64**. This mode of the system would work well where the larger electronic component is for example used in a recreational vehicle or boat or other portable configuration, to guard against fire from resistive heating or sparking in wiring or overheating of the electronic component located proximate to the portable housing **68**.

(99) Shown in FIG. **38**, FIG. **38** depicts a junction box **12** which is operatively connected to a fluid conduit **26** which supplies suppressant fluid to passages **21**, such as in FIG. **30A**, to the junction box **12**. Shown, formed into the sidewall **15** of the junction box **12**, are differing configurations of nozzles **70**. These nozzles **70** are positioned on one or a plurality of the sidewalls **15** of the junction box **12** and can be configured for a targeted stream of suppressant in a directional flow **78** (FIG. **39**) therefrom.

(100) As shown, one projecting nozzle **70A** has a narrowing configuration wherein the distal end **72** thereof, forms to a point which is narrower than a base **74** of the projecting nozzle **70A**. The nozzle sidewall or sidewalls **84** thus angle from the base **74** toward the distal end **72**. The distal end **72** can be formed to melt or burst when heated and supplied with pressurized fluid, and to disburse suppressant fluid therefrom in a narrow spread thereof or a singular stream thereof. Where used herein, nozzle sidewall **84** is intended to mean a single nozzle sidewall **84** which, for example, may have a tube-like or a conical shape, or may have intersecting angled portions forming the sidewall **84** which define the shape and size of the nozzle **70**.

(101) A fluid opening **76**, as shown in FIG. **39**, would thus be formed at the distal end **72** of the projecting nozzle **70A**, by a melting of a plug positioned in the fluid opening **76**, or a melting of the distal end **72** of the projecting nozzle **70A**. Fluid would disburse during a fire, or overheating of the area surrounding the junction box **12**, and the directional flow **78** of suppressant fluid as in FIG. **39**, would flow therefrom.

(102) By directional flow **78**, as used herein, is meant a fluid flow focused by the configuration of the nozzle **70** to be emitted as a straight line, a fanned spread either in a single plane or radial pattern emission, or any other pattern of fluid emission which can be formed by nozzle **70** sidewalls **84**. Further, while nozzles **70** are shown as projecting nozzles **70A**, and recessed nozzles **70B**, or dome shaped nozzles **70C**, herein, such is for convenience and any nozzle **70** which can be positioned on or in a sidewall **15** of a junction box **12**, to emit a focused or shaped fluid stream therefrom, is considered within the scope of this invention.

(103) Also depicted in FIG. **38** nozzles **70** formed as recessed nozzles **70B** which have a nozzle opening **80** which is wider than a nozzle inlet **82** which recessed into the sidewall **15**. In this mode, the inlet **82** end of the recessed nozzle **70B** is formed to melt or burst first when heated and allow fluid suppressant to flow from the inlet **82** end, to the wider nozzle opening **80**. The fluid direction is focused to emit in a fanned or radial pattern or highly disbursed fluid by angled nozzle sidewalls **84**. Changing the number and angle of the angled sidewalls **84** allows for a changing of the pattern of fluid in the directional flow **78** of suppressant.

(104) Additionally shown in FIG. **38** are dome shaped or domed nozzles **70C**. The domed nozzles **70C** can be formed as depressions into the sidewall **15** or a projecting domes from the sidewall **15**. The dome wall **86** defining the domed nozzles **70C** can be formed of a material which melts before

the material forming the junction box **12** and sidewall **15** of the same material in a thinner layer such that it will melt before the junction box **12** and sidewall **13**. This mode of nozzle **70** can be employed to project a high volume of suppressant from the junction box **12** depending on the diameter or area forming the dome wall **86** of the domed nozzles **70C**.

(105) As noted, shown in FIG. **39** are exemplars of some of the nozzles **70** which can be formed to emit a narrow, pointed, or wide flood of suppressant fluid therefrom in the desired directional flow **78**. As also noted, the depictions in FIGS. **38-40** of the nozzles **70** should be in no way considered limiting.

(106) As shown in FIG. **40**, the nozzles **70** in all modes thereof, can be formed in nozzle panels **88**. While depicted with projecting nozzles **70A**, the nozzle panel **88** can be formed with any of the nozzle configurations herein, or which are shaped to emit the desired shape and volume of fluid in the directional flow **78** of choice. While shown as a single nozzle panel **88**, kits including a plurality of such nozzle panels **88** can be included in the system herein, wherein the user can choose the nozzle panel **88** having the desired configuration of nozzle **70** to emit a desired directional flow **78** of suppressant fluid therefrom in the desired pattern and volume determined by the shape or configuration of the nozzle **70**.

(107) As shown in FIG. **40**, the chosen nozzle panel **88** from the kit or plurality thereof, which has the desired nozzles **70** thereon, can be placed in a sealed engagement with the sidewall **15** of the junction box **12** which will have sidewall openings **90** in fluid communication with the suppressant communicated to the junction box **12** by the fluid conduit **26**.

(108) A panel seal **92** forms a sealed engagement of the junction box **12** sidewall **15** with the nozzle panel **88** chosen for such engagement. A panel connector is employed to hold the nozzle panel **88** in a sealed connection to the junction box **12**. Such may be any panel connector configured to hold the nozzle panel **88** in the sealed connection to the sidewall **15** of the junction box **12**, such as slots **94** into which opposing sides of the nozzle panel **88** engage. The depicted slots **94** should be considered in no way limiting as to the panel connector employed to hold a nozzle panel **88** chosen to the sealed engagement with the junction box **12**. Any panel connector, such as snaps, pins, adhesive, or mating connectors positioned on the junction box **12** and on the nozzle panel **88**, or other mating connectors as would occur to those skilled in the art, may be used.

(109) As noted, any of the different configurations and components can be employed with any other configuration or component shown and described herein. Additionally, while the present invention has been described herein with reference to particular embodiments thereof and steps in the method of production, a latitude of modifications, various changes and substitutions are intended in the foregoing disclosures, it will be appreciated that in some instance some features, or configurations, or steps in formation of the invention could be employed without a corresponding use of other features without departing from the scope of the invention as set forth in the following claims. All such changes, alternations and modifications as would occur to those skilled in the art are considered to be within the scope of this invention as broadly defined in the appended claims.

(110) Further, the purpose of any abstract of this specification is to enable the U.S. Patent and Trademark Office, the public generally, and especially the scientists, engineers, and practitioners in the art who are not familiar with patent or legal terms or phraseology, to determine quickly from a cursory inspection the nature and essence of the technical disclosure of the application. Any such abstract is neither intended to define the invention of the application, which is measured by the claims, nor is it intended to be limiting, as to the scope of the invention in any way.

Claims

1. A cable for an electrical power delivery station, the cable comprising: a sheath with an axial pathway running a length of the cable between a first end of the cable and a second end of the cable; a plurality of electrically conductive wires running through the axial pathway of the sheath

for the length of the cable, each of the electrically conductive wires configured to communicate electricity from the first end of the cable to the second end of the cable; and one or more fluid conduits immediately adjacent to the plurality of conductive wires within the sheath, each of the fluid conduits having a sidewall surrounding an axial passage thereof that provides a defined flow path for a fluid that is therein to flow between the first end of the cable and the second end of the cable and to cool an interior of the sheath, wherein one or more of the plurality of electrically conductive wires is embedded within the one or more fluid conduits.

2. The cable of claim 1, wherein the defined flow path of one or more of the fluid conduits directs a non-conductive coolant to flow along the length of the cable between the first end of the cable and the second end of the cable.

3. The cable of claim 1, wherein the defined flow path of one or more of the fluid conduits directs a fire suppressant to flow along the length of the cable between the first end of the cable and the second end of the cable.

4. The cable of claim 1, wherein each of the one or more fluid conduits extends along the length of the cable.

5. The cable of claim 1, wherein one or more of the conductive wires is disposed radially inward of the one or more fluid conduits.

6. The cable of claim 1, wherein one or more of the plurality of electrically conductive wires is encapsulated by one or more of the fluid conduits.

7. The cable of claim 1, wherein the plurality of electrically conductive wires are circumferentially arranged within the sheath.

8. The cable of claim 1, wherein the plurality of electrically conductive wires and the one or more fluid conduits are circumferentially arranged within the sheath.

9. The cable of claim 1, wherein each of the one or more fluid conduits is axially parallel to the plurality of electrically conductive wires along the length of the cable.

10. The cable of claim 1, wherein at least one of the plurality of electrically conductive wires directly contacts another one of the plurality of electrically conductive wires.

11. A cable for an electrical power delivery station, the cable comprising: a sheath with an axial pathway running a length of the cable between a first end of the cable and a second end of the cable; a plurality of electrically conductive wires running through the axial pathway of the sheath for the length of the cable, each of the electrically conductive wires configured to communicate electricity from the first end of the cable to the second end of the cable; and one or more fluid conduits immediately adjacent to the plurality of conductive wires within the sheath, each of the fluid conduits having a sidewall surrounding an axial passage thereof that provides a defined flow path for a fluid that is therein to flow between the first end of the cable and the second end of the cable and to cool an interior of the sheath, wherein one or more of the plurality of electrically conductive wires is immersed in a fluid conduit of the one or more fluid conduits.

12. The cable of claim 1, further comprising at least one sensor coupled to the fluid conduit configured to detect a change of state of the conduit, wherein the at least one sensor is configured to generate an electric signal in response to the detection of the change of state to the fluid conduit that causes the electrical power delivery station to shut off the flow of electricity.

13. The cable of claim 1, wherein the plurality of the electrically conductive wires are encapsulated by a fluid conduit of the one or more fluid conduits.

14. The cable of claim 1, wherein the plurality of the electrically conductive wires are embedded within a fluid conduit of the one or more fluid conduits.

15. The cable of claim 1, wherein each of the electrically conductive wires is insulated.

16. The cable of claim 1, wherein each of the electrically conductive wires is un-insulated.

17. The cable of claim 11, wherein the defined flow path of one or more of the fluid conduits directs a non-conductive coolant to flow along the length of the cable between the first end of the cable and the second end of the cable.

18. The cable of claim 11, wherein each of the one or more fluid conduits extends along the length of the cable.
19. The cable of claim 11, wherein one or more of the conductive wires is disposed radially inward of the one or more fluid conduits.
20. The cable of claim 11, wherein one or more of the plurality of electrically conductive wires is encapsulated by one or more of the fluid conduits.
21. The cable of claim 11, wherein the plurality of electrically conductive wires are circumferentially arranged within the sheath.
22. The cable of claim 11, wherein the plurality of electrically conductive wires and the one or more fluid conduits are circumferentially arranged within the sheath.
23. The cable of claim 11, wherein each of the one or more fluid conduits is axially parallel to the plurality of electrically conductive wires along the length of the cable.
24. The cable of claim 11, wherein at least one of the plurality of electrically conductive wires directly contacts another one of the plurality of electrically conductive wires.
25. The cable of claim 11, further comprising at least one sensor coupled to the fluid conduit configured to detect a change of state of the conduit, wherein the at least one sensor is configured to generate an electric signal in response to the detection of the change of state to the fluid conduit that causes the electrical power delivery station to shut off the flow of electricity.
26. The cable of claim 11, wherein the plurality of the electrically conductive wires are encapsulated by the fluid conduit of the one or more fluid conduits.
27. The cable of claim 11, wherein each of the electrically conductive wires is insulated.
28. The cable of claim 11, wherein each of the electrically conductive wires is un-insulated.
29. A cable for an electrical power delivery station, the cable comprising: a sheath with an axial pathway running a length of the cable between a first end of the cable and a second end of the cable; a plurality of electrically conductive wires running through the axial pathway of the sheath for the length of the cable, each of the electrically conductive wires configured to communicate electricity from the first end of the cable to the second end of the cable; and a plurality of fluid conduits immediately adjacent to the plurality of conductive wires within the sheath, each of the fluid conduits having a sidewall surrounding an axial passage thereof that provides a defined flow path for a fluid that is therein to flow between the first end of the cable and the second end of the cable and to cool an interior of the sheath.
30. The cable of claim 29, wherein a first set of electrically conductive wires of the plurality of electrically conductive wires is encapsulated by a first fluid conduit of the plurality of fluid conduits.
31. The cable of claim 29, wherein a first set of electrically conductive wires of the plurality of electrically conductive wires is embedded within a first fluid conduit of the plurality of fluid conduits.
32. A cable for an electrical power delivery station, the cable comprising: a sheath with an axial pathway running a length of the cable between a first end of the cable and a second end of the cable; a plurality of electrically conductive wires running through the axial pathway of the sheath for the length of the cable, each of the electrically conductive wires configured to communicate electricity from the first end of the cable to the second end of the cable; and a fluid conduit disposed within the sheath, the fluid conduit disposed radially outward of the plurality of electrically conductive wires and configured to provide a flow path for a fluid that is to flow therein between the first end of the cable and the second end of the cable and to cool an interior of the sheath.
33. The cable of claim 32, wherein the plurality of electrically conductive wires are immersed in the fluid conduit.
34. The cable of claim 32, wherein the sheath is a flexible armored sheath.
35. The cable of claim 32, wherein the fluid is to flow back from the second end of the cable to the

first end of the cable via an attached coupling.

36. The cable of claim 32, wherein the fluid is a non-conductive oil or glycol.

37. A cable for an electrical power delivery station, the cable comprising: a sheath with an axial pathway running a length of the cable between a first end of the cable and a second end of the cable; a plurality of electrically conductive wires running through the axial pathway of the sheath for the length of the cable, each of the electrically conductive wires configured to communicate electricity from the first end of the cable to the second end of the cable; one or more fluid conduits immediately adjacent to the plurality of conductive wires within the sheath, each of the fluid conduits having a sidewall surrounding an axial passage thereof that provides a defined flow path for a fluid that is therein to flow between the first end of the cable and the second end of the cable and to cool an interior of the sheath; and at least one sensor coupled to the fluid conduit configured to detect a change of state of the conduit, wherein the at least one sensor is configured to generate an electric signal in response to the detection of the change of state to the fluid conduit that causes the electrical power delivery station to shut off the flow of electricity.

38. The cable of claim 37, wherein the defined flow path of one or more of the fluid conduits directs a non-conductive coolant to flow along the length of the cable between the first end of the cable and the second end of the cable.

39. The cable of claim 37, wherein each of the one or more fluid conduits extends along the length of the cable.

40. The cable of claim 37, wherein one or more of the conductive wires is disposed radially inward of the one or more fluid conduits.

41. The cable of claim 37, wherein one or more of the plurality of electrically conductive wires is encapsulated by one or more of the fluid conduits.

42. The cable of claim 37, wherein the plurality of electrically conductive wires are circumferentially arranged within the sheath.

43. The cable of claim 37, wherein the plurality of electrically conductive wires and the one or more fluid conduits are circumferentially arranged within the sheath.

44. The cable of claim 37, wherein each of the one or more fluid conduits is axially parallel to the plurality of electrically conductive wires along the length of the cable.

45. The cable of claim 37, wherein at least one of the plurality of electrically conductive wires directly contacts another one of the plurality of electrically conductive wires.

46. The cable of claim 37, wherein the plurality of the electrically conductive wires are encapsulated by a fluid conduit of the one or more fluid conduits.

47. The cable of claim 37, wherein the plurality of the electrically conductive wires are embedded within a fluid conduit of the one or more fluid conduits.

48. The cable of claim 37, wherein each of the electrically conductive wires is insulated.

49. The cable of claim 37, wherein each of the electrically conductive wires is un-insulated.

50. The cable of claim 37, wherein the sheath is a flexible armored sheath.

51. A cable for an electrical power delivery station, the cable comprising: a sheath with an axial pathway running a length of the cable between a first end of the cable and a second end of the cable; a plurality of electrically conductive wires running through the axial pathway of the sheath for the length of the cable, each of the electrically conductive wires configured to communicate electricity from the first end of the cable to the second end of the cable; and one or more fluid conduits immediately adjacent to the plurality of conductive wires within the sheath, each of the fluid conduits having a sidewall surrounding an axial passage thereof that provides a defined flow path for a fluid that is therein to flow between the first end of the cable and the second end of the cable and to cool an interior of the sheath, wherein the plurality of the electrically conductive wires are encapsulated by a fluid conduit of the one or more fluid conduits.

52. The cable of claim 51, wherein the defined flow path of one or more of the fluid conduits directs a non-conductive coolant to flow along the length of the cable between the first end of the

cable and the second end of the cable.

53. The cable of claim 51, wherein each of the one or more fluid conduits extends along the length of the cable.

54. The cable of claim 51, wherein one or more of the conductive wires is disposed radially inward of the one or more fluid conduits.

55. The cable of claim 51, wherein the plurality of electrically conductive wires are circumferentially arranged within the sheath.

56. The cable of claim 51, wherein the plurality of electrically conductive wires and the one or more fluid conduits are circumferentially arranged within the sheath.

57. The cable of claim 51, wherein each of the one or more fluid conduits is axially parallel to the plurality of electrically conductive wires along the length of the cable.

58. The cable of claim 51, wherein at least one of the plurality of electrically conductive wires directly contacts another one of the plurality of electrically conductive wires.

59. The cable of claim 51, wherein the plurality of the electrically conductive wires are embedded within the fluid conduit.

60. The cable of claim 51, wherein each of the electrically conductive wires is insulated.

61. The cable of claim 51, wherein each of the electrically conductive wires is un-insulated.

62. The cable of claim 51, wherein the sheath is a flexible armored sheath.

63. A cable for an electrical power delivery station, the cable comprising: a sheath with an axial pathway running a length of the cable between a first end of the cable and a second end of the cable; a plurality of electrically conductive wires running through the axial pathway of the sheath for the length of the cable, each of the electrically conductive wires configured to communicate electricity from the first end of the cable to the second end of the cable; and one or more fluid conduits immediately adjacent to the plurality of conductive wires within the sheath, each of the fluid conduits having a sidewall surrounding an axial passage thereof that provides a defined flow path for a fluid that is therein to flow between the first end of the cable and the second end of the cable and to cool an interior of the sheath, wherein the plurality of the electrically conductive wires are embedded within a fluid conduit of the one or more fluid conduits.

64. The cable of claim 63, wherein the defined flow path of one or more of the fluid conduits directs a non-conductive coolant to flow along the length of the cable between the first end of the cable and the second end of the cable.

65. The cable of claim 63, wherein each of the one or more fluid conduits extends along the length of the cable.

66. The cable of claim 63, wherein one or more of the conductive wires is disposed radially inward of the one or more fluid conduits.

67. The cable of claim 63, wherein one or more of the plurality of electrically conductive wires is encapsulated by one or more of the fluid conduits.

68. The cable of claim 63, wherein the plurality of electrically conductive wires are circumferentially arranged within the sheath.

69. The cable of claim 63, wherein the plurality of electrically conductive wires and the one or more fluid conduits are circumferentially arranged within the sheath.

70. The cable of claim 63, wherein each of the one or more fluid conduits is axially parallel to the plurality of electrically conductive wires along the length of the cable.

71. The cable of claim 63, wherein at least one of the plurality of electrically conductive wires directly contacts another one of the plurality of electrically conductive wires.

72. The cable of claim 63, wherein the plurality of the electrically conductive wires are encapsulated by the fluid conduit of the one or more fluid conduits.

73. The cable of claim 63, wherein each of the electrically conductive wires is insulated.

74. The cable of claim 63, wherein each of the electrically conductive wires is un-insulated.
