

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414594
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Hetzel; Ryan

Running belt

Abstract

An example running belt that may include a panel at least partially forming an enclosed volume having a mouth to receive articles. The panel has a front face and a folded edge portion. The running belt may further include a waist support to extend about the waist of a person wearing the running belt. The waist support may include a band backing the folded edge portion, wherein the folded edge portion is secured to the front face and wherein the band is secured to the folded edge portion.

Inventors:	Hetzel; Ryan (Squamish, CA)
Applicant:	Amer Sports Canada Inc. (North Vancouver, CA)
Family ID:	1000008819971
Assignee:	Amer Sports Canada Inc. (North Vancouver, CA)
Appl. No.:	17/688321
Filed:	March 07, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230276882 A1	Sep. 07, 2023

Publication Classification

Int. Cl.: **A41F9/00** (20060101)

U.S. Cl.:

CPC **A41F9/002** (20130101); **A41D2600/10** (20130101)

Field of Classification Search

CPC: A41F (9/00); A41F (9/002); A41D (2600/10); A45C (1/104)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1418371	12/1921	Foster	224/587	A45C 1/04
1651921	12/1926	Felz	224/587	A45C 1/04
4461030	12/1983	Knudsen	2/22	A45C 1/04
4462116	12/1983	Sanzone	2/253	A41D 20/00
4501028	12/1984	Gottschall	2/338	A41F 9/002
4525879	12/1984	Kalomeris	2/338	A45C 1/04
4634031	12/1986	Frankhouse	224/602	A45C 1/04
5558440	12/1995	Miller	224/663	A45F 5/00
6311336	12/2000	Gootrad	224/257	A45C 11/22
8028345	12/2010	Waite	2/220	A41D 1/14
8321964	12/2011	Gernes	2/403	A41B 9/001
9021615	12/2014	Cockram	2/236	A41D 13/0015
9254010	12/2015	Hedrick	N/A	A41D 13/0017
9961947	12/2017	Cockram	N/A	A41D 31/18
10010158	12/2017	Do	N/A	A41D 27/205
10687604	12/2019	Do	N/A	N/A
10932529	12/2020	Mulfeld	N/A	A44B 11/006
11291257	12/2021	Epp Frenette	N/A	A41D 27/24
D1024545	12/2023	Lin	D3/226	N/A
2008/0190980	12/2007	Overton	224/660	A45F 3/14
2013/0048687	12/2012	Do	224/191	A41F 9/00
2013/0048695	12/2012	Do	224/676	A45F 3/005
2013/0276210	12/2012	Clarke	2/220	A41D 1/14
2014/0196194	12/2013	Clarke	2/237	A41D 1/002
2016/0051035	12/2015	Do	N/A	N/A
2016/0143424	12/2015	Stephens	224/676	A45F 3/005
2016/0331053	12/2015	Gordon	N/A	A41D 7/00
2017/0295870	12/2016	Harris et al.	N/A	N/A
2018/0220720	12/2017	Cockram	N/A	N/A
2018/0295972	12/2017	Do	N/A	A41F 9/00
2019/0269838	12/2018	Jablonski	N/A	A61M 60/857
2021/0235799	12/2020	Willows	N/A	A41D 27/20
2022/0160065	12/2021	Pagano	N/A	A41F 9/025
2023/0276882	12/2022	Hetzel	2/321	A41D 27/20
2023/0284757	12/2022	Gakovic	N/A	A45F 5/021
2023/0337809	12/2022	Wagner	N/A	A45F 5/021

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
4241599	12/2022	EP	N/A

Background/Summary

BACKGROUND

(1) Running belts are worn by persons running or jogging, and carry water, food and other articles such as smart phones, keys, cards and cash. Unfortunately, existing running belts may be bulky and unnecessarily heavy.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a top view of an example running belt while being worn.
- (2) FIG. 2 is a cross-section of the running belt of FIG. 1 taken along line 2-2.
- (3) FIG. 2A is an enlarged fragmentary view of a portion of the running belt of FIG. 2.
- (4) FIG. 3 is a sectional view of an example running belt taken along line 2-2 of FIG. 1.
- (5) FIG. 4 is a sectional view of an example running belt taken along line 2-2 of FIG. 1.
- (6) FIG. 5 is a sectional view taken along line 2-2 of FIG. 1.
- (7) FIG. 6 is a diagram of the example running belt of FIG. 5 containing an example article while being worn.
- (8) FIG. 7 large fragmentary sectional view illustrating portions of an example running belt.
- (9) FIG. 8 is a top view of an example running belt while being worn.
- (10) FIG. 8A is a cross-sectional view of the example running belt of FIG. 8 taken along line 8A-8A.
- (11) FIG. 9 is a top view of an example running belt while being worn.
- (12) FIG. 9A is a side example running belt of FIG. 9 taken along line 9A-9A.
- (13) FIG. 10 is a side view illustrating portions of an example running belt.
- (14) FIG. 10A is a sectional view of the running belt of FIG. 10 taken along line 10A-10A.
- (15) FIG. 11 is a perspective view of an example running belt while being worn.
- (16) FIG. 12 is a perspective view of the running belt of FIG. 11 with portions broken or omitted for purposes of illustration.
- (17) FIG. 13 is a perspective view of an example running belt.
- (18) FIG. 14 is a perspective view of the example running belt of FIG. 13.
- (19) Throughout the drawings, identical reference numbers designate similar, but not necessarily identical, elements. The figures are not necessarily to scale, and the size of some parts may be exaggerated to more clearly illustrate the example shown. Moreover, the drawings provide examples and/or implementations consistent with the description; however, the description is not limited to the examples and/or implementations provided in the drawings.

DETAILED DESCRIPTION OF EXAMPLES

- (20) Disclosed are example running belts that have a sleek and lightweight construction while still offering a large storage capacity. The example running belts eliminate excess material and weight while maintaining a smooth uninterrupted exterior having a reduced number of material edges or breaks.
- (21) The example running belts utilize a single panel that forms at least a portion of an enclosed storage volume. The single panel is inwardly folded to provide a smooth, rounded folded edge portion that is backed by a waist support. As a result, the waist support is covered and concealed, wherein in the running belt and the waist portion has a smooth rounded top edge without additional

coverings or material breaks. The upper regions of the running belt may be thinner in construction, reducing the weight of the belt and potentially increasing comfort for the person wearing the belt. (22) Disclosed is an example running belt that may comprise a panel at least partially forming an enclosed volume having a mouth to receive articles. The panel has a front face and a folded edge portion. The running belt may further comprise a waist support to extend about the waist of a person wearing the running belt. The waist support comprises a band backing the folded edge portion, wherein the folded edge portion is secured to the front face and wherein the band is secured to the folded edge portion.

(23) In some implementations, the panel has an outer portion forming a front of the enclosed volume, an inner portion forming a back of the enclosed volume and a lower folded portion connecting the outer portion to the inner portion. Such a construction reduces the amount of stitching and seams used to form the enclosed volume.

(24) In some implementations, the inner portion is recessed below the folded edge portion, below the top edge of the outer portion. As a result, the top of the enclosed volume is concealed behind the outer portion of the panel. In some implementations, a second band is secured to and backs the upper edge of the inner portion. The second band strengthens those regions of the belt around an upwardly facing mouth for the enclosed volume. The second band further provides upper portions of the running belt with a uniform thickness on opposite sides of the upwardly facing mouth in that the outer portion of the panel, the folded edge portion of the panel and the waist support may have a three ply thickness and the opposite side of the mouth also has a three ply thickness formed by the outer portion of the panel, the inner portion of the panel and the second band.

(25) In some implementations, the mouth faces in an upward direction. In other implementations, the mouth, providing access to the interior of the enclosed volume, faces in a frontwards or sideways direction.

(26) In some implementations, the lower folded portion comprises a W-shaped fold forming the floor of the enclosed volume and having a folded peak between the outer portion and the inner portion. In some implementations, the folded peak is secured to the inner portion. The W-shaped fold forming the floor of the enclosed volume or pocket provides the running belt with a distinct floor and flatter profile.

(27) In some implementations, front and inner portions of the panel are stitched or otherwise non-removably connected to one another to partition the larger enclosed volume at least partially formed by the panel into multiple distinct pockets or enclosed volumes. In some implementations, one or more pockets formed by the panel encircle the waist of the person wearing the running belt. In some implementations, one or more pockets formed by the panel extend along the portion of the running belt for positioning at the front or the rear of the runner, wherein portions of the waist support encircling the waist omit pockets or an enclosed volume.

(28) In some implementations, the waist support comprise a continuous loop, lacking separable ends that may be selectively disconnected. In some implementations, the waist support has first and second opposite ends or end portions which are releasably connectable and separable from one another by a releasable connection mechanism such as a quick release buckle, snaps, a hook and loop fastener or the like.

(29) For purposes of this disclosure, the term “coupled” shall mean the joining of two members directly or indirectly to one another. Such joining may be stationary in nature or movable in nature. Such joining may be achieved with the two members, or the two members and any number of additional intermediate members being integrally formed as a single unitary body with one another or with the two members or the two members and any additional intermediate member being attached to one another. Such joining may be permanent in nature or alternatively may be removable or releasable in nature. The term “operably coupled” shall mean that two members are directly or indirectly joined such that motion may be transmitted from one member to the other member directly or via intermediate members. The term “fluidly coupled” shall mean that two or

more fluid transmitting volumes are connected directly to one another or are connected to one another by intermediate volumes or spaces such that fluid may flow from one volume into the other volume.

(30) For purposes of this disclosure, the phrase “configured to” denotes an actual state of configuration that fundamentally ties the stated function/use to the physical characteristics of the feature proceeding the phrase “configured to.” For purposes of this disclosure, the term “releasably” or “removably” with respect to an attachment or coupling of two structures means that the two structures may be repeatedly connected and disconnected to and from one another without material damage to either of the two structures or their functioning.

(31) FIGS. 1 and 2 illustrate an example running belt 20. FIG. 1 is a top view of running belt 20 being worn about the waist 22 of a person. The belt is illustrated as being spaced from waist 22 merely for purposes of illustration. FIG. 2 is a sectional view of running belt 20 taken along line 2-2 of FIG. 1. Running belt 20 comprises panel 26 and waist support 30.

(32) Panel 26 comprises a flexible panel of material that at least partially forms an enclosed volume 32 which has a mouth 34 to receive articles and providing access to the interior of the enclosed volume 32. Panel 26 may be formed from a variety of materials. In some implementations, panel 26 is formed from a fabric. In some implementations, panel 26 is formed from a polymer, synthetic materials or natural materials. In some implementations, panel 26 is opaque. In some implementations, panel 26 is at least partially translucent, facilitating viewing of the contents of the enclosed volume. In some implementations, panel 26 is formed from an elastic or resiliently stretchable material.

(33) As shown by FIG. 2, the enclosed volume 32 is enclosed on a front side by an outer portion 38 of panel 26. The enclosed volume 32 is further bounded by floor 40 and a rear wall 42. In the example illustrated, enclosed volume 32 is accessible through a mouth 34 which faces in an upward direction in which receive articles in the direction indicated by the arrow 43. In some implementations, the floor 40 and the rear wall 42 are formed by panel 26. In some implementations, the floor 40 and the rear wall 42 may be formed by other panels joined to panel 26 by stitching, adhesives or the like.

(34) Waist support 30 comprise a structure that encircles waist 22 and supports the remainder of belt 20 at waist 22. In some implementations, waist support 30 comprise a continuous loop formed by a single band 49 of material having first and second waist support ends that are non-releasably or releasably connected to one another. In some implementations, waist support 30 be formed by a first band that backs portions of panel 26 and one or more additional bands that are secured to the first band, and which do not back panel 26. In some implementations, waist support 30 is inelastic. In some implementations, waist support 30 is resiliently flexible and elastic. In some implementations, waist support 30 has an adjustable length to accommodate differently sized waists.

(35) As shown by FIGS. 2 and 2A, panel 26 has a folded edge portion 52. Folded edge portion 52 integrally extends from outer portion 38 as a single unitary body with the remainder of panel 26. Folded edge portion 52 is inwardly folded, towards the interior of the loop formed by belt 20 when being worn, to form a rounded top edge 54. Folded edge portion 52 has an inner face 56 (facing waist 22 when belt 20 is worn) backed by band 49. In the example illustrated, folded edge portion 52 is vertically above and directly overlies both enclosed volume 32 and mouth 34.

(36) As schematically indicated by a broken lines 53, folded edge portion 52 is secured to outer portion 38 of panel 26 and the band 49. In some implementations, folded edge portion 52 is sandwiched between outer portion 38 and the band 49 by one or more stitches that pass through such layers. In some implementations, the band 49 is stitched to folded edge portion 52 by first stitch and folded edge portion 52 is stitched to the front face 50 of panel 26 by second stitch. In some implementations, a single stitching passing through each of the band, the folded edge portion 52 and the outer portion 38 of panel 26 to secure such layers together. In yet other implementations,

such layers may be held together by adhesives or welds. In some implementations, such layers may be individually held or secured to another by a combination of adhesives and stitches.

(37) Because band **49** is joined to folded edge portion **52** on the inside of the loop of running belt **20**, band **49** is concealed. Because folded edge portion **52** provides the front of belt **20** with a smooth rounded upper edge **54** without the use of an overlapping cover fabric, the front face **50** of panel **26** forms the entire front of belt **20**, providing a smooth uninterrupted sleek appearance less likely to inadvertently catch or snag. The front of belt **20** omits any breaks or transitions between different layers of material. In addition, the overall complexity and weight of belt **20** is reduced.

(38) FIG. **3** is a sectional view of running belt **120** taken along line 2-2 of FIG. **1**. Running belt **120** is similar to running belt **20** described above except that the enclosed volume **32** is additionally bound by a cover or cover **144** and that the enclosed volume **32** is accessed through a front opening or mouth **134**. Cover **144** may be formed by panel **26** or may be formed by additional panels of material stitched, welded, or bonded to panel **26** and/or those panels forming rear wall **42**.

(39) Mouth **134** provides access to the interior of enclosed volume **32** through front panel **26**. Those portions of panel **26** about mouth **134** may be flexed or moved to widen mouth **134** during the insertion of an article into enclosed volume **32**, where following such insertion, such portions resiliently flexed back to the original position and shape, capturing the article within the interior of the enclosed volume **32**. In one implementation, mouth **130** comprises an elongate slit extending longitudinally (horizontally when belt **20** is being worn) along a portion of the length of panel **26**. In some implementations, mouth **130** may comprise an elongate vertical slit through panel **26**. In yet other implementations, mouth **134** may have other shapes, sizes, locations and/or orientations. In some implementations, mouth **134** may additionally include a closing mechanism such as a zip, hook and loop fastener, snap, buckle, button or the like releasably retaining mouth **134** in a closed state.

(40) FIG. **4** is a sectional view illustrating running belt **220**. FIG. **4** illustrates an example of how panel **26** may be used to form at least three sides of the enclosed volume **32**. Running belt **220** is similar to running belt **20** described above except that the floor **40** and the rear wall **42**, bounding enclosed volume **32**, are also formed by panel **26**. Panel **26** has a lower folded portion **222** and an inner portion **224** which form floor **40** and rear wall **42**, respectively. Because the outer portion **38**, floor **40** and inner portion **224** are each formed by the integral, single, construction of running belt **20** is simplified and the number of edges is reduced.

(41) FIG. **5** is a sectional view of running belt **320**. Running belt **320** is similar to running belt **220** described above except that running belt **320** additionally comprises band **327**. The remaining components of running belt **320** which correspond to components of running belt **220** are numbered similarly.

(42) Band **327** comprise a strap or length of material extending along the inner or rear face of inner portion **224** of panel **26** adjacent to and below mouth **34**. Band **327** backs the upper edge of inner portion **224** along mouth **34**. Band **327** is vertically below band **49**. In the example illustrated, band **327** is an upper edge at a vertical height no greater than 1 cm and nominally no greater than 0.25 cm the lower edge of band **39**. As a result, the vertical spacing between bands **49** and **327** is sufficiently small such that the skin or other clothing of the person wearing running belt **320** is less likely to be pinched or caught between the lower edge of band **49** and the upper edge of band **327**, providing a more comfortable experience for the person wearing running belt **320**.

(43) In some implementations, band **327** comprises a band of elastic material such as a spandex, Lycra or elastane fiber alone or in combination with other material such as nylon. In other implementations, other elastic materials may be utilized to form band **327** as well as band **49**. In such implementations, band **49** may also be formed from an elastic material. In some implementations, band **49** is formed from the same elastic material that forms band **327**. Because both band **327** and **49** are formed from the same or different elastic materials, both band **327** and band **49** may be in a slightly stretched state when running belt **320** is being worn, gripping the

waist 22 of the person wearing running belt 320.

(44) FIG. 6 is a sectional view illustrating running belt 320 with enclosed volume 32 containing an article 329 and while running belt 320 is being worn about a waist 22 of a person. As shown by FIG. 6, because band 49 is elastic, band 49 resiliently closes about and against waist 22, closing mouth 34 overtop of enclosed volume 32. Because band 327 is elastic, band 327 resiliently closes about against waist 22 below band 49, further assisting in retaining mouth 34 in a closed state. Because both of such bands 327 and 49 are elastic, their inner faces both concurrently engage waist 22 in the same plane (as also shown by broken lines), reducing the likelihood of pinching of the skin are article between such bands. Because band 49 and band 327 are each part of a three-ply construction (three layers of material), the exterior running belt 320 remain flat smooth, omitting shoulders, edges or bumps. This consistent thickness that extends across both of bands 327 and 49 provides running belt 320 with a sleeker appearance when being worn.

(45) FIG. 7 is an enlarged fragmentary sectional view of running belt 420. FIG. 7 illustrates an example of how the lower folded portion of running belt 420 may be configured for an enhanced shape and appearance. Running belt 420 is similar to running belt 320 except that running belt 420 comprises a lower folded portion 446 in lieu of lower folded portion 46. Those remaining components of running belt for 20 which correspond to components of running belt 320 are numbered similarly and/or are shown in FIGS. 1, 5 and 6.

(46) Lower folded portion 446 joins outer portion 38 of panel 26 to inner portion 224 of panel 26. Lower folded portion 446 forms the floor 40 of enclosed volume 32. Lower folded portion 446 comprises a W-shaped fold having a folded peak 450 between outer portion 38 and inner portion 224. The folded peak assists in maintaining the shape and size of floor 40. In the example illustrated, the folded peak 450 is secured to inner portion 224 as schematically indicated by broken line 452. In some implementations, broken line 452 schematically represents stitching through and between a lower portion of inner portion 224 and peak 450. Some implementations, broken line 452 schematically represents a weld, fusion or adhesive bonding or joining lower portion of inner portion 224 to peak 450. In other implementations, peak 450 may be secured to a lower portion of outer portion 38 of panel 26. In some implementations, peak 450 may freely float between outer portion 38 and inner portion 224.

(47) FIG. 8 is a top view of running belt 520 being worn about the waist 22 of a person. FIG. 8A is a cross sectional view of belt 520 taken along line 8A-8A. The belt is illustrated as being spaced from waist 22 merely for purposes of illustration. FIG. 8 illustrates an example of how the enclosed volume at least partially formed by panel 26 may be partitioned into different pockets. FIG. 8 further illustrates an example of how end portions of waist support may be releasably joined to one another to facilitate donning of the running belt 520. Running belt 520 is similar to running belt 420 except that running belt 520 is illustrated with enclosed volume 32 extending from a first end portion 535 to a second end portion 537, where such end portions 535 and 537 are releasably connected to one another by a releasable connector 560.

(48) In the example illustrated, the enclosed volume 32 is partitioned into distinct pockets or pockets 532-1, 532-2, 532-3, 532-4 and 532-5 (collectively referred to as pockets 532). Each of pockets 532 directly underlies folded edge portion 52. Pocket 532-1 extends across the front of waist 22 while pockets 532-2 and 532-3 extend along the rear of waist 22. Pocket 532-2 extends between pocket 532-4 and connector 560. Pocket 532-3 extends between pocket 532-5 and connector 560. Pockets 532-4 and 532-5 form side pockets along the opposite sides of waist 22. Pocket 532-4 is formed between pocket 532-1 and 532-2. Pocket 532-5 is formed between pocket 532-1 and pocket 532-3. In some implementations, the relative positioning of such pockets 532 with respect to waist 22 may vary through the rotation of running belt 520 about waist 22. For example, running belt 520 may be rotated 180° such that connector 560 is positioned at the front center of waist 22 rather than at the rear center of waist 22.

(49) Enclosed volume 32 is partitioned into the various pockets by partitions 562 extending

between outer portion **38** of panel **26** and inner portion **224** of panel **26**. In some implementations, partitions **562** may comprise stitching passing through and connecting outer portion **38** to inner portion **224**. In some implementations, partitions **562** may comprise adhesives, welds or the like directly connecting opposite surfaces of outer portion **38** and inner portion **224**. In yet other implementations, partitions **562** may comprise additional flexible panels may be located between and secured to outer portion **38** and inner portion **224** to define sides of such internal volumes or pockets. In some implementations, partitions **562** may be omitted such that the enclosed volume **32** continuously extends about the waist **22** between end portions **535** and **537**. In some implementations, each or some of such pockets **532** may have covers **144** (shown in FIG. 3) formed by securing portions of outer portion **38** to inner portion **224** above the enclosed volume **32** by stitching, welds or adhesives, wherein panel **26** is provided with a mouth **134** (shown in FIG. 3) as described above.

(50) Releasable connector **560** releasably joins end portions **535** and **537**. In some implementations, releasable connector **560** comprises a quick release buckle. In some implementations, connector **560** comprises overlapping portions of a hook and loop (VELCRO) connector. In some implementations, connector **560** comprises a snap, a buckle, a button or other mechanisms for such releasable connection of end portions **535** and **537**. In some implementations, connector **560** may be omitted such as where end portions **535** and **537** are non-releasably connected to one another such as by stitching, welds, adhesives or the like.

(51) FIG. 9 is a top view of running belt **620** being worn about the waist **22** of a person. FIG. 9A is a side view of running belt **620** of FIG. 9 taken along line 9A-9A. The belt is illustrated as being spaced from waist **22** merely for purposes of illustration. FIG. 9 illustrates an example of how panel **26** may extend about a portion of the entirety of the person's waist **22** to provide pockets or other enclosed volumes about just a portion of a person's waist **22**. FIG. 9 illustrates an example of how the enclosed volume at least partially formed by panel **26** may be partitioned into different pockets or pockets. FIG. 9 further illustrates an example of how the waist support may extend beyond panel **26** and beyond portions of the enclosed volume **32**. Running belt **620** is similar to running belt **420** except that running belt **620** is specifically disclosed as having the construction shown in FIG. 9, wherein waist support **30** projects beyond ends of panel **26** and has end portions **635** and **637** releasably connected to one another by releasable connector **560** (described above). Those portions of running belt **620** extending along the front and sides of waist **22** that include panel **26** have a cross-sectional construction similar to that shown in FIG. 7.

(52) As shown by FIG. 9, panel **26** and enclosed volume **32** extend 240 degrees about waist **22**. Panel **26** and enclosed volume **32** are partitioned by partitions **562** to form pockets **632-1**, **632-2** and **632-3** (collectively referred to as pockets **632**). Pockets **632-1**, **632-2** and **632-3** are similar to pockets **532-1**, **532-4** and **532-5**, respectively. Waist support **30** extends beyond pocket **632-2** and **632-3** and includes end portions **635** and **637** releasably connected to one another by releasable connector **560**. Although running belts **520** and **620** are each described as having a cross-sectional construction similar to that shown in FIG. 7, in other implementations, running belts **520** and **620** may alternatively have panel **26** provided as part of a cross-sectional construction similar to that shown in and described with respect to any of FIGS. 2-6.

(53) FIG. 10 is a side view of an example running belt **720**, the side view as of FIG. 9A. FIG. 10A is a sectional view of running belt **720** of FIG. 10 taken along line 10A-10A. Running belt **720** is similar to running belt **620** except that front portion **38** and folded edge portion **52** of front panel **26** extend beyond pocket **632** and cover or overlap band **49** from the end of pocket **632-2** to connector **560** and from the end of pocket **632-2** to connector **560**. The outer portion **38** of panel **26** extending between pockets **632-2** and **632-3** to connector **560** terminate at or below the lower edge of band **49**. Such portions of panel **26** provide belt **720** with a continuous, uninterrupted transition between pockets **632** and the rearward portions of waist support **30** extending beyond such pockets **632**. As indicated by broken lines **561** in FIGS. 9A and 10, in some implementations, pockets **632-2** and

632-3 may have chamfered or rounded rear edge portions provide a smoother or more gradual transition to those portions of running belt **520** which do not include pockets.

(54) FIGS. **11** and **12** are perspective views illustrating portions of an example running belt **820**. Running belt **820** is similar to running belt **420** except that running belt **820** omits releasable connector **560**, non-releasably connecting the end portions of the panel and bands forming the running belt. Those remaining components of running belt **820** which correspond to components of running belt **520** are numbered similarly. Portions of running belt **822** are shown broken away or are removed to illustrate the various layers of material. In the example illustrated, partitions **562** comprise stitching through outer portion **38** and inner portion **224**. Bands **49** and **327** are further secured to portions of panel **26** by stitching. As shown by FIG. **11**, running belt **820** is extremely thin and lightweight while offering a sleek and smooth outer face.

(55) FIGS. **13** and **14** illustrate portions of an example running belt **920**. Running belt **920** is similar to running belt **820** described above except that running belt **920** comprises side pocket **932-5** and rear carrying straps **970** those remaining portions of running belt **920** are numbered similarly and/or are shown in and described with respect to FIGS. **6**, **7**, **8**, **11** and **12**.

(56) Side pocket **932-5** replaces pocket **532-5**. Although not illustrated, side pocket **532-4** may also be replaced with a side pocket similar to side pocket **932-5**. Side pocket **932-5** is similar to side pocket **532-5** except that side pocket **932-5** comprises a cover **144** (shown and described with respect to FIG. **3**) and a mouth **934** having a closure **974**. Cover **144** may be formed by securing portions of outer portion **38** to inner portion **224** above the enclosed volume **32** by stitching, welds or adhesives.

(57) Mouth **934** comprises an opening formed in outer portion **38** of panel **26**, providing access to the interior or enclosed volume **32** of pocket **932-5**. In the example illustrated, mouth **935** comprises a diagonal opening. In other implementations, mouth **935** may comprise a vertical or horizontal opening through outer portion **38** of panel **26**. Closure **974** comprises a mechanism to selectively open and close mouth **934**. In the example illustrated, closure **974** comprises a zipper. In other implementations, closure **974** may comprise a flap or other piece of material having a hooked portion of a hook and loop fastener one side of mouth **934** and the looped portion of the hook and loop fastener on the opposite side of mouth **934**. In other implementations, closure **934** may comprise a snap, buckle, button or other closing mechanism. In some implementations, pocket **932-5** may additionally omit cover **144**, providing two ways of accessing the interior of pocket **932-5**.

(58) Rear carrying straps **970** comprise bands of elastic material having opposite ends stitched, bonded or welded to the outer portion **38** of panel **26** proximate to a top edge and bottom edge of running belt **920**. Rear carrying straps **970** form at least two receiving and carrying articles, such as a water bottle, towel or the like adjacent the back the person wearing running belt **920**. Some implementations, running belt **920** may include more than two straps **970** in some implementations, the two or more carrying straps **970** may be located at the sides along other portions of running belt **920**. In some implementations, carrying straps **970** may be omitted.

(59) Although the present disclosure has been described with reference to example implementations, workers skilled in the art will recognize that changes may be made in form and detail without departing from the scope of the claimed subject matter. For example, although different example implementations may have been described as including features providing benefits, it is contemplated that the described features may be interchanged with one another or alternatively be combined with one another in the described example implementations or in other alternative implementations. Because the technology of the present disclosure is complex, not all changes in the technology are foreseeable. The present disclosure described with reference to the example implementations and set forth in the following claims is manifestly intended to be as broad as possible. For example, unless specifically otherwise noted, the claims reciting a single particular element also encompass a plurality of such particular elements. The terms “first,” “second,” “third” and so on in the claims merely distinguish different elements and, unless

otherwise stated, are not to be specifically associated with a particular order or particular numbering of elements in the disclosure.

Claims

1. A running belt comprising: a panel at least partially forming an enclosed volume having a mouth to receive articles, the enclosed volume bounded by a rear wall having an upper edge portion, a front wall and a floor extending between the rear wall and the front wall, the panel having an outer portion forming the front wall and a folded edge portion having a downwardly facing edge; a waist support to extend about a waist of a person wearing the running belt, the waist support comprising a band backing the folded edge portion, wherein the folded edge portion is secured to the outer portion and wherein the band is secured to the folded edge portion; and an access opening between the upper edge portion and the downwardly facing edge of the folded edge portion, the opening connected to the mouth between the upper edge portion and the downwardly facing edge of the folded edge portion.
2. The running belt of claim 1, wherein the panel further comprises an inner portion forming the rear wall of the enclosed volume and a lower folded portion connecting the outer portion and the inner portion and forming the floor of the enclosed volume.
3. The running belt of claim 2, wherein the lower folded portion comprises a W-shaped fold forming the floor and having a folded peak between the outer portion and the inner portion, wherein the folded peak is secured to the inner portion.
4. The running belt of claim 2 further comprising a second band secured to and backing the upper edge portion of the rear wall.
5. The running belt of claim 4, wherein the band and the second band are elastic.
6. The running belt of claim 5, wherein the band comprises first and second waist support ends that are connected to form a continuous loop to extend about a waist of a person wearing the running belt.
7. The running belt of claim 6, wherein the first and second waist support ends are non-releasably connected by bonding or stitching.
8. The running belt of claim 7, wherein the panel comprises first and second panel ends that are non-releasably connected to form a continuous panel loop to extend about the waist of the person wearing the running belt.
9. The running belt of claim 8, wherein the folded edge portion is secured to the outer portion by stitching and wherein the band is secured to the folded edge portion by stitching.
10. The running belt of claim 9, wherein portions of the outer portion of the panel and the inner portion of the panel are non-releasably connected to form a second enclosed volume having a second mouth to receive articles.
11. The running belt of claim 10, wherein second portions of the outer portion of the panel and the inner portion of the panel are non-releasably connected to form a third enclosed volume having a third mouth to receive articles, the second enclosed volume and the third enclosed volume extending on opposite sides of the enclosed volume.
12. The running belt of claim 11, wherein the panel forms a fourth enclosed volume having a fourth mouth to receive articles, the fourth enclosed volume extending between the second enclosed volume and the third enclosed volume, opposite the enclosed volume.
13. The running belt of claim 1, wherein the outer portion of the panel forms a frontmost surface of the running belt.
14. The running belt of claim 1, wherein the waist support comprises a second elastic band coupled to an end portion of the panel.
15. The running belt of claim 1, wherein the waist support comprises a connector to releasably connect end portions of the waist support to form a continuous loop.

16. The running belt of claim 1 further comprising a second band secured to and backing the upper edge portion of the rear wall, wherein the opening extends between the band and the second band.
17. The running belt of claim 16, where the second band is elastic.
18. A running belt comprising: a panel at least partially forming an enclosed volume having a mouth to receive articles, the panel having an outer portion and a folded edge portion; and a waist support to extend about a waist of a person wearing the running belt, the waist support comprising a band backing the folded edge portion, wherein the folded edge portion is secured to the outer portion and wherein the band is secured to the folded edge portion, wherein the outer portion forms a front of the enclosed volume, and wherein the panel further comprises an inner portion forming a back of the enclosed volume and a lower folded portion connecting the outer portion and the inner portion and forming a floor of the enclosed volume, and wherein the lower folded portion comprises a W-shaped fold forming the floor and having a folded peak between the outer portion and the inner portion, wherein the folded peak is secured to the inner portion.
19. The running belt of claim 18, wherein the outer portion has a first upper edge and wherein the inner portion has a second upper edge below the first upper edge.
20. The running belt of claim 19, where the mouth is formed between the second upper edge and the outer portion of the panel.
-