

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415021
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Epshteyn; Vitaliy Gennad'yevich et al.

Extracorporeal blood filtering machine and methods

Abstract

An extracorporeal blood filtering machine can include a blood circuit, an effluent circuit, and a source fluid circuit and can be controlled by a controller. The extracorporeal blood filtering machine can also include access ports for connecting the source fluid circuit to the blood circuit, as well as blood sensors to detect possible issues with the extracorporeal blood filtering machine. The extracorporeal blood filtering machine can include density sensors and flow sensors that enable it to be more accurate and to operate while being transported. The extracorporeal blood filtering machine can further include a user interface and can display fluid inflow/outflow information. A medical fluid container can automatically empty after being filled. An apparatus for supporting a medical fluid container can include a hanger and an attachment member with the apparatus able to adjust to ensure the medical fluid container remains properly oriented directly under a medical fluid container scale.

Inventors: Epshteyn; Vitaliy Gennad'yevich (Maple Grove, MN), Sandoval; Steven Daniel (Eden Prairie, MN), Berg; Kalley Francis (Lino Lakes, MN), Ulrich; Franz Willems (Minneapolis, MN)

Applicant: Nuwellis, Inc. (Eden Prairie, MN)

Family ID: 1000008820074

Assignee: NUWELLIS, INC. (Eden Prairie, MN)

Appl. No.: 18/298860

Filed: April 11, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240277931 A1	Aug. 22, 2024

Related U.S. Application Data

Publication Classification

Int. Cl.: **A61M1/16** (20060101); **A61M1/14** (20060101); **A61M1/36** (20060101); A61M1/10 (20060101); A61M1/34 (20060101); A61M5/14 (20060101); A61M5/165 (20060101); A61M5/172 (20060101); A61M60/109 (20210101); A61M60/268 (20210101)

U.S. Cl.:

CPC **A61M1/154** (20220501); **A61M1/1601** (20140204); **A61M1/36224** (20220501); A61M1/10 (20130101); A61M1/14 (20130101); A61M1/155 (20220501); A61M1/1562 (20220501); A61M1/15632 (20220501); A61M1/1566 (20220501); A61M1/16 (20130101); A61M1/1643 (20140204); A61M1/1694 (20130101); A61M1/34 (20130101); A61M1/3403 (20140204); A61M1/341 (20140204); A61M1/3413 (20130101); A61M1/342 (20130101); A61M1/3424 (20140204); A61M1/3427 (20140204); A61M1/3431 (20140204); A61M1/3434 (20140204); A61M1/3437 (20140204); A61M1/3441 (20130101); A61M1/3444 (20140204); A61M1/3451 (20140204); A61M1/3607 (20140204); A61M1/361 (20140204); A61M1/36225 (20220501); A61M1/362262 (20220501); A61M1/362264 (20220501); A61M1/362266 (20220501); A61M1/3624 (20130101); A61M1/3626 (20130101); A61M1/3627 (20130101); A61M1/3639 (20130101); A61M1/3644 (20140204); A61M1/3663 (20130101); A61M1/3672 (20130101); A61M5/1415 (20130101); A61M5/165 (20130101); A61M5/172 (20130101); A61M60/109 (20210101); A61M60/268 (20210101); A61M2202/0042 (20130101); A61M2205/3331 (20130101); A61M2205/3368 (20130101); A61M2205/3379 (20130101); A61M2205/3393 (20130101); A61M2205/50 (20130101); A61M2205/502 (20130101); A61M2205/505 (20130101); A61M2205/82 (20130101); A61M2205/8206 (20130101); A61M2205/8262 (20130101); A61M2230/005 (20130101)

Field of Classification Search

CPC: A61M (1/3413-3493); A61M (1/1601); A61M (1/3451); A61M (1/1643); A61M (1/14); A61M (1/154); A61M (1/155); A61M (1/1562); A61M (1/15632); A61M (1/1566); A61M (1/16); A61M (1/1694); A61M (1/34); A61M (1/3403); A61M (1/341); A61M (1/342); A61M (1/3424); A61M (1/3427); A61M (1/3431); A61M (1/3434); A61M (1/3437); A61M (1/3441); A61M (1/3444); A61M (1/3607); A61M (1/361); A61M (1/36224); A61M (1/36225); A61M (1/362262); A61M (1/362264); A61M (1/362266); A61M (1/3624); A61M (1/3626); A61M (1/3627); A61M (1/3639); A61M (1/3644); A61M (1/3663); A61M (1/3672); A61M (5/1415); A61M (5/165); A61M (5/172); A61M (60/109); A61M (60/268); A61M (2202/0042); A61M (2205/3331); A61M (2205/3379); A61M (2205/3393); A61M (2205/50); A61M (2205/502); A61M (2205/505); A61M (2205/82); A61M (2205/8206); A61M (2205/8262); A61M (2230/005); A61M (2205/3306); A61M (2205/3313); A61M (2205/3368); A61M (2209/082); A61M (1/1603); A61M (1/1692); A61M (2230/207); A61M (1/3455); A61M (1/3465); A61J (1/10)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4670007	12/1986	Wheeldon et al.	N/A	N/A
4728433	12/1987	Buck et al.	N/A	N/A
4850560	12/1988	Ross	N/A	N/A
5211849	12/1992	Kitaevich et al.	N/A	N/A
6200485	12/2000	Kitaevich et al.	N/A	N/A
6302864	12/2000	Nowosielski	N/A	N/A
6468241	12/2001	Gelfand et al.	N/A	N/A
6585675	12/2002	O'Mahony et al.	N/A	N/A
6685664	12/2003	Levin et al.	N/A	N/A
6695806	12/2003	Gelfand et al.	N/A	N/A
6773412	12/2003	O'Mahony et al.	N/A	N/A
6796955	12/2003	O'Mahony et al.	N/A	N/A
6887214	12/2004	Levin et al.	N/A	N/A
6890315	12/2004	Levin et al.	N/A	N/A
6923782	12/2004	O'Mahony et al.	N/A	N/A
6947131	12/2004	O'Mahony et al.	N/A	N/A
RE38869	12/2004	Polaschegg et al.	N/A	N/A
7018182	12/2005	O'Mahony et al.	N/A	N/A
7135008	12/2005	O'Mahony et al.	N/A	N/A
7199312	12/2006	O'Mahony et al.	N/A	N/A
7230687	12/2006	O'Mahony et al.	N/A	N/A
7232418	12/2006	Neri et al.	N/A	N/A
7297270	12/2006	Bernard et al.	N/A	N/A
7303540	12/2006	O'Mahony et al.	N/A	N/A
7311689	12/2006	Levin et al.	N/A	N/A
7314554	12/2007	Delnevo et al.	N/A	N/A
7410473	12/2007	Levin et al.	N/A	N/A
7410582	12/2007	Bernard et al.	N/A	N/A
7462786	12/2007	O'Mahony et al.	N/A	N/A
7547200	12/2008	O'Mahony et al.	N/A	N/A
7585286	12/2008	O'Mahony et al.	N/A	N/A
7647834	12/2009	O'Mahony et al.	N/A	N/A
7727391	12/2009	Delnevo et al.	N/A	N/A
7789850	12/2009	Roger	N/A	N/A
7867393	12/2010	Duchamp et al.	N/A	N/A
7886611	12/2010	O'Mahony et al.	N/A	N/A
7906737	12/2010	Freydank et al.	N/A	N/A
7935071	12/2010	Levin et al.	N/A	N/A
8197432	12/2011	O'Mahony et al.	N/A	N/A
8267308	12/2011	Devergne et al.	N/A	N/A
8267881	12/2011	O'Mahony et al.	N/A	N/A
8361023	12/2012	Bedingfield	N/A	N/A
8459543	12/2012	Devergne et al.	N/A	N/A
8562822	12/2012	Roger et al.	N/A	N/A
8562823	12/2012	Roger et al.	N/A	N/A
8603021	12/2012	Evin et al.	N/A	N/A
8608953	12/2012	Brotherton et al.	N/A	N/A

8702638	12/2013	O'Mahony et al.	N/A	N/A
9089639	12/2014	Breuel et al.	N/A	N/A
9138526	12/2014	Ware et al.	N/A	N/A
9999716	12/2017	Golarits et al.	N/A	N/A
10549023	12/2019	Updyke et al.	N/A	N/A
10603423	12/2019	Childers et al.	N/A	N/A
10695481	12/2019	Kelly et al.	N/A	N/A
10881347	12/2020	Barrett et al.	N/A	N/A
10987461	12/2020	Brugger et al.	N/A	N/A
11105669	12/2020	Evans et al.	N/A	N/A
11273246	12/2021	Plahey	N/A	N/A
11351291	12/2021	Kreymann et al.	N/A	N/A
11386994	12/2021	Handler	N/A	N/A
11524101	12/2021	Golarits et al.	N/A	N/A
2005/0251086	12/2004	Sternby	N/A	N/A
2005/0284815	12/2004	Sparks	604/4.01	G01F 1/8445
2007/0031976	12/2006	Trouilly et al.	N/A	N/A
2007/0265594	12/2006	Hagermark et al.	N/A	N/A
2008/0004594	12/2007	Pahlberg et al.	N/A	N/A
2008/0015487	12/2007	Szamosfalvi	210/323.1	A61M 1/3413
2010/0022934	12/2009	Hogard	N/A	N/A
2010/0038317	12/2009	Bissler et al.	N/A	N/A
2010/0089806	12/2009	Peters et al.	N/A	N/A
2010/0121246	12/2009	Peters et al.	N/A	N/A
2010/0264086	12/2009	Noack et al.	N/A	N/A
2011/0056897	12/2010	Kao	N/A	N/A
2011/0189048	12/2010	Curtis et al.	N/A	N/A
2013/0012861	12/2012	Zhang	N/A	N/A
2013/0199998	12/2012	Kelly et al.	N/A	N/A
2015/0238676	12/2014	Giordano et al.	N/A	N/A
2016/0287779	12/2015	Orczy-Timko et al.	N/A	N/A
2016/0354528	12/2015	Pouchoulin	N/A	N/A
2018/0361046	12/2017	Moretti et al.	N/A	N/A
2020/0353140	12/2019	Beden et al.	N/A	N/A
2021/0030937	12/2020	Kelly et al.	N/A	N/A
2021/0030938	12/2020	Kopperschmidt et al.	N/A	N/A
2021/0046235	12/2020	Klewinghaus	N/A	N/A
2021/0113753	12/2020	Moghaddam	N/A	N/A
2021/0128806	12/2020	Mitrovic et al.	N/A	N/A
2021/0128812	12/2020	Desouza et al.	N/A	N/A
2021/0170084	12/2020	Zacharia et al.	N/A	N/A
2021/0196880	12/2020	O'Mahony et al.	N/A	N/A
2022/0054724	12/2021	Askenazi et al.	N/A	N/A
2022/0080091	12/2021	Plahey	N/A	N/A
2022/0080093	12/2021	Kogan	N/A	N/A
2022/0211926	12/2021	Childers et al.	N/A	N/A
2022/0241477	12/2021	Gura	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
108325019	12/2017	CN	N/A
110152086	12/2018	CN	N/A
611227	12/1993	EP	N/A
2004069299	12/2003	WO	N/A
20090146913	12/2008	WO	N/A
2020132686	12/2019	WO	N/A
2021089689	12/2020	WO	N/A
2021089690	12/2020	WO	N/A
2021094294	12/2020	WO	N/A
2021094357	12/2020	WO	N/A
2021094446	12/2020	WO	N/A
2021219792	12/2020	WO	N/A
2022096389	12/2021	WO	N/A
2022167394	12/2021	WO	N/A
2022171728	12/2021	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion of the International Application No. PCT/US2023/071577, mailed Nov. 22, 2023, 22 pg. cited by applicant

Prismax Manual (Baxter) <https://usrenalacute.baxter.com/sites/g/files/ebysai3231/files/2020-12/Prismax%20Operator%627s%20Manual.pdf> Dated Jun. 2019. cited by applicant

Medtronic “Small Patients. Small Solutions. Big Results. Carpediem cardio-renal pediatric dialysis emergency machine” , Brochure dated Aug. 2021, 9 pgs. cited by applicant

Medtronic “Technical Data Sheet BL 250 complete kit for hemofiltration/hemodialysis 015 and 0258 with the CARPEDIEM cardio-renal pediatric dialysis emergency machine” , dated Jun. 2021, 4 pgs. cited by applicant

Primary Examiner: Su; Susan S

Attorney, Agent or Firm: Fredrikson & Byron, P.A.

Background/Summary

(1) The present application is a continuation of U.S. Non-Provisional patent application Ser. No. 18/171,612, filed Feb. 20, 2023, the entirety of which is incorporated herein by reference.

BACKGROUND

(1) People whose kidneys are not functioning properly (e.g., are failing) may be treated with renal replacement therapy. Renal replacement therapy replaces the normal blood-filtering function of the kidneys and can include multiple different therapies. Examples include dialysis and hemofiltration. Currently, there are many types of renal replacement therapy machines that can perform one of the therapies and some types of renal replacement therapy machines that can perform more than one of the therapies, albeit by making difficult adjustments. Generally, renal replacement therapy machines use a semi-permeable membrane (e.g., filter) when operating to filter a patient's blood. Renal replacement therapy can be continuous or intermittent, with both having advantages and disadvantages. Some example continuous renal replacement therapies include continuous renal

replacement therapy, continuous hemodialysis, continuous hemofiltration, and continuous hemodiafiltration. Some intermittent renal replacement therapies include intermittent renal replacement therapy, intermittent hemodialysis, intermittent hemofiltration, and intermittent hemodiafiltration.

(2) Current renal replacement machines may have issues with accuracy, ease of use, adaptability (e.g., ability to perform more than one therapy), safety, and transportability due to a variety of factors. For example, it can be difficult for a patient connected to a renal replacement machine to move around due to the continuous renal replacement machine receiving power from the wall, and the continuous renal replacement machine may lack accuracy while in transport. In another example, renal replacement machines may not be able to differentiate a blood leak from another condition (e.g., hemolysis) that can present safety concerns. It can also be difficult for a user to operate a renal replacement machine. For example, many current renal replacement machines require a user to remove and replace an effluent bag when it is full. Further, apparatuses that hang medical fluid bags used with renal replacement machines may cause accuracy issues. For example, the accuracy of determining a quantity of effluent removed from a patient's blood by a renal replacement machine may be decreased due to tilting of an effluent bag relative to the machine caused by the hanging apparatus.

SUMMARY

(3) The present disclosure generally relates to extracorporeal blood filtering machines and associated methods. Embodiments disclosed herein can relate to extracorporeal blood filtering machines that include various components, including components of a blood circuit, an effluent circuit, and a source fluid circuit. The embodiments can also include components such as sensors, access ports, user inputs, and controllers.

(4) The extracorporeal blood filtering machine, including its various components and its operation, can provide several advantages over existing renal replacement machines. For example, the extracorporeal blood filtering machine can increase safety using sensors, providing alerts, and ensuring an ability to end therapy if needed. In some examples, the extracorporeal blood filtering machine can increase accuracy using different sensors, enable multiple therapies to be used, and enable transportation of the extracorporeal blood filtering machine while still providing therapy.

(5) Embodiments disclosed herein can also include improvements to medical fluid containers, as well as improvements for supporting the medical fluid containers. For instance, a medical fluid container can be automatically emptied, while supports for medical fluid containers can increase accuracy by ensuring the medical fluid containers are correctly supported for related measurements.

(6) Examples provided herein include an apparatus with a bracket and a hanger configured to connect a medical fluid container to an extracorporeal blood filtering machine, a self-emptying medical fluid container, a method of operating an extracorporeal blood filtering machine in transport mode, techniques for calculating fluid flow quantities using determined (not assumed) fluid density values, selecting a single position for connecting a source fluid line to a blood circuit, displaying quantities of fluid flowing into and out of a patient, a method that enables selection of open-loop or closed-loop control, adjusting operation of a clamp based on temperature, and techniques for monitoring hemolysis. These examples can be combined in various ways to achieve synergistic advantages. For example, the apparatus with the bracket and hanger configured to connect the medical fluid container to the extracorporeal blood filtering machine may be combined with the self-emptying medical fluid container to enable further simplified handling of medical fluid containers. In another example, the method of operating the extracorporeal blood filtering machine in transport mode may be combined with the method that enables selection of open-loop or closed-loop control to facilitate open-loop control of the extracorporeal blood filtering machine while in transport mode and closed-loop control of the extracorporeal blood filtering machine while not in transport mode. In another example, selecting a single position for connecting the source

fluid line to the blood circuit may be combined with techniques for calculating fluid flow quantities using determined (not assumed) fluid density values in that priming a single source fluid line can prepare the extracorporeal blood filtering machine for operation and also provide a foundation for determining the source fluid density value. These examples are merely illustrative. Other combinations may be made to achieve additional synergistic advantages.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) The following drawings are illustrative of particular embodiments of the invention and therefore do not limit the scope of the invention. The drawings are not necessarily to scale (unless so stated) and are intended for use with the explanations in the following detailed description. Embodiments of the invention will hereinafter be described in conjunction with the appended drawings, wherein like numerals denote like elements.
- (2) FIG. 1 is a perspective view of an example extracorporeal blood filtering system including an extracorporeal blood filtering machine according to an aspect of the present disclosure.
- (3) FIG. 2 is a diagrammatic view of an example extracorporeal blood filtering machine according to an aspect of the present disclosure.
- (4) FIG. 3 is a diagrammatic view of the example extracorporeal blood filtering machine of FIG. 2 in one example configuration according to an aspect of the present disclosure.
- (5) FIG. 4 is a diagrammatic view of the example extracorporeal blood filtering machine of FIG. 2 in an alternate example configuration according to an aspect of the present disclosure.
- (6) FIG. 5 is a diagrammatic view of the example extracorporeal blood filtering machine of FIG. 2 in an alternate example configuration according to an aspect of the present disclosure.
- (7) FIG. 6 is a diagrammatic view of the example extracorporeal blood filtering machine of FIG. 2 in an alternate example configuration according to an aspect of the present disclosure.
- (8) FIG. 7 is a flow chart of an example method related to the illustrated embodiments of FIGS. 2-6, according to an aspect of the present disclosure.
- (9) FIG. 8 is a schematic view of an example extracorporeal blood filtering machine according to an aspect of the present disclosure.
- (10) FIG. 9 is an example method using the extracorporeal blood filtering machine of FIG. 8 according to an aspect of the present disclosure.
- (11) FIG. 10 is a diagrammatic view of an example extracorporeal blood filtering machine according to an aspect of the present disclosure.
- (12) FIG. 11 is a flowchart of an example operation of the example extracorporeal blood filtering machine of FIG. 10.
- (13) FIG. 12 is a diagrammatic view of an example extracorporeal blood filtering system according to an aspect of the present disclosure.
- (14) FIG. 13 is flowchart of an example operation of the extracorporeal blood filtering system of FIG. 12 according to an aspect of the present disclosure.
- (15) FIG. 14 is a perspective view of an example apparatus for hanging a medical fluid container and a perspective view of a portion of the medical fluid container according to an aspect of the present disclosure.
- (16) FIG. 15 is a perspective view of a rail assembly of the apparatus of FIG. 14 according to an aspect of the present disclosure.
- (17) FIG. 16 is a perspective view of a hanger of the apparatus of FIG. 14 according to an aspect of the present disclosure.
- (18) FIG. 17 is a front perspective view of the example apparatus of FIG. 14 with a hanger being slightly translated on the apparatus according to an aspect of the present disclosure.

(19) FIG. 18A and FIG. 18B are front perspective views of the example apparatus of FIG. 14 illustrating the example apparatus being rotated about an axis.

(20) FIG. 19A, FIG. 19B, and FIG. 19C are side perspective views of the example apparatus of FIG. 14 illustrating the example apparatus being rotated about another axis.

(21) FIG. 20 is a flowchart of an example operation of the apparatus of FIG. 14 according to an aspect of the present disclosure.

(22) FIG. 21 is a perspective view of an alternate example apparatus for hanging a medical fluid container according to an aspect of the present disclosure.

(23) FIG. 22A, 22B, 22C are side perspective views of the apparatus of FIG. 21 illustrating the example apparatus being rotated about an axis according to an aspect of the present disclosure.

(24) FIG. 23 is a front perspective view of the apparatus of FIG. 21 with a hanger being slightly translated on the apparatus according to an aspect of the present disclosure.

(25) FIG. 24 is a front sectional view of the apparatus of FIG. 21 according to an aspect of the present disclosure.

(26) FIG. 25 is a front view of an example medical fluid container according to an aspect of the present disclosure.

(27) FIG. 26 is a flowchart of an example method involving the medical fluid container of FIG. 25 according to an aspect of the present disclosure.

(28) FIG. 27 is a schematic view of an example extracorporeal blood filtering machine according to an aspect of the present disclosure.

(29) FIG. 28 is an example method of operating the extracorporeal blood filtering machine of FIG. 27 according to an aspect of the present disclosure.

(30) FIG. 29 is a schematic view of an example extracorporeal blood filtering system including an example extracorporeal blood filtering machine according to an aspect of the present disclosure.

(31) FIG. 30 is a flowchart of an example method of operating the extracorporeal blood filtering machine of FIG. 29 according to an aspect of the present disclosure.

(32) FIG. 31 is a flow chart of another example method of operating the example extracorporeal blood filtering machine of FIG. 29 according to an aspect of the present disclosure.

(33) FIG. 32 is a schematic view of an example extracorporeal blood filtering system including an example extracorporeal blood filtering machine according to an aspect of the present disclosure.

(34) FIG. 33 is a flowchart of an example method of operating the extracorporeal blood filtering machine of FIG. 32 according to an aspect of the present disclosure.

(35) FIG. 34 is a perspective view of an example display according to an aspect of the present disclosure.

DETAILED DESCRIPTION

(36) The following detailed description is exemplary in nature and is not intended to limit the scope, applicability, or configuration of the invention in any way. Rather, the following description provides some practical illustrations for implementing various embodiments of the present invention. Those skilled in the art will recognize that many of the noted examples have a variety of suitable alternatives.

(37) FIG. 1 is a perspective view of an example extracorporeal blood filtering machine **100** according to an aspect of the present disclosure. The extracorporeal blood filtering machine **100** is generally configured to receive blood from a connected patient, filter the blood, and return the filtered blood to the patient. The extracorporeal blood filtering machine **100** can include a variety of components to perform such an operation and can also include components that improve the overall therapeutic effectiveness.

(38) In some embodiments, the extracorporeal blood filtering machine **100** includes components that enable a source fluid line to be connected to different positions and that facilitate the extracorporeal blood filtering machine **100** to operate in different filtering modes. In some embodiments, the extracorporeal blood filtering machine **100** includes components that can help

alert a user that the extracorporeal blood filtering machine **100** has a fault, such as a blood leak. In some embodiments, the extracorporeal blood filtering machine **100** includes components that help prevent serious issues, such as a gas embolism, from affecting the patient. In some embodiments, the extracorporeal blood filtering machine **100** includes components that increase the accuracy of fluid removal/addition during blood filtering.

(39) As illustrated, the extracorporeal blood filtering machine can hold medical fluid containers, which can be part of the extracorporeal blood filtering machine. In some embodiments, the mechanism for holding the medical fluid containers is improved. In some embodiments, a medical fluid container has an improved design.

(40) In some embodiments, the extracorporeal blood filtering machine **100** includes components that enable the extracorporeal blood filtering machine **100** to operate under closed-loop control as well as operate under open-loop control. In some embodiments, the extracorporeal blood filtering machine **100** includes components that enable the extracorporeal blood filtering machine **100** to operate on wall power or battery power and easily switch between the power sources while maintaining accuracy. In some embodiments, the extracorporeal blood filtering machine **100** includes components that enable a user to accurately determine fluid inflow, fluid outflow, and a fluid balance of a patient connected to the extracorporeal blood filtering machine.

(41) The above embodiments and others are illustrated and described in detail throughout the entirety of this disclosure.

(42) Moving to FIG. 2, FIG. 2 is a diagrammatic of an example extracorporeal blood filtering machine **200** according to an aspect of the present disclosure. While the extracorporeal blood filtering machine **200** can be configured to perform various operations and incorporate various sensors, pumps, displays, and other devices, in general, the extracorporeal blood filtering machine **200** filters a patient's blood while it is outside of the patient.

(43) To filter a patient's blood, the extracorporeal blood filtering machine **200** includes a blood circuit. The blood circuit comprises a blood line including a blood inlet **204** configured to receive blood from a patient and a blood outlet **218** configured to return the blood to the patient. The blood circuit also includes a filter **216** fluidly connected to the blood line between the blood inlet **204** and the blood outlet **218** which is configured to remove waste from blood passing through it. For components that are fluidly connected to one another, fluid can pass from one of the components to the other (e.g., blood from the blood line passes through the filter **216**). The blood circuit further includes a blood pump **210** that is configured to pump the blood from the blood inlet **204** to the blood outlet **218** through the filter **216**. In operation of the blood circuit, the blood pump **210** pumps blood from the patient, through the filter **216**, and back into the patient.

(44) In filtering the patient's blood, waste products are generated in the form of effluent. Accordingly, the extracorporeal blood filtering machine **200** includes an effluent circuit to remove any effluent from the filter **216**. The effluent circuit includes an effluent line **220** fluidly connected to the filter **216** with the effluent line **220** configured to receive waste from the filter **216** in the form of effluent. The effluent circuit also includes an effluent pump **224** configured to pump the effluent from the filter **216**, through the effluent line **220**, and into an effluent receptacle **226**. The effluent receptacle **226** of FIG. 2 takes the form of an effluent fluid bag, though other receptacles can be used. In some examples, the effluent circuit or parts thereof (e.g., effluent pump **224**) are optional to the extracorporeal blood filtering machine **200** or are present but not used.

(45) In some examples, it can be advantageous to know how much effluent has been filtered from the blood of a patient, such as to determine the patient's fluid balance of fluid inflow vs. fluid outflow. In some such examples, the extracorporeal blood filtering machine **200** can include an effluent scale **246**. The effluent scale **246** is configured to dynamically weigh the effluent within the effluent receptacle **226**. In some examples, the effluent scale can take the form of one or more load cells, though other types of effluent scales can be used. In some embodiments, the effluent scale **246** is in communication with the effluent pump **224** and can affect the rate at which the

effluent pump **224** pumps effluent. Such configurations can help change or maintain a desired rate of effluent fluid that is removed from a patient's blood.

(46) In some configurations of the extracorporeal blood filtering machine **200**, external fluid is added to the patient's blood. For example, source fluid, such as dialysate replacement fluid or electrolyte fluid can be added into the patient's blood and can replace effluent that is filtered out from the blood to achieve fluid balance within the patient. Additionally or alternatively, the source fluid can include general nutritional injection fluid comprising nutrients for a patient. In the embodiment of FIG. 2, the extracorporeal blood filtering machine **200** includes a source fluid circuit which adds a source fluid to the patient's blood. The source fluid circuit includes a source fluid line **236** fluidly connected to a source fluid reservoir **234** which is configured to be connected to a single selected position in the blood circuit. The single selected position of the source fluid line can be selected from multiple potential positions, which is discussed further elsewhere herein. In FIG. 2, the source fluid line is fluidly connected at the filter **216**. The source fluid circuit also includes a source fluid pump **238**, which is configured to pump source fluid from the source fluid reservoir **234** through the source fluid line **236** and into the blood circuit.

(47) In similarity with the effluent circuit, in some examples, it can be advantageous to know how much source fluid has been added into the blood of a patient such as to determine the patient's fluid balance of fluid inflow vs. fluid outflow. In some such examples, the extracorporeal blood filtering machine **200** can include a source fluid scale **248**. The source fluid scale **248** is configured to dynamically weigh the source fluid within the source fluid reservoir **234**. In some examples, the source fluid scale can take the form of one or more load cells, though other types of source fluid scales can be used. In some embodiments, the source fluid scale **248** is in communication with the source fluid pump **238** and can affect the rate at which the source fluid pump **238** pumps source fluid. Such configurations can help change or maintain a desired amount of source fluid that is added to a patient's blood.

(48) In embodiments that include both a source fluid scale **248** and an effluent scale **246**, the source fluid scale **248** and the effluent scale **246**, along with the source fluid pump **238** and the effluent pump **224**, can be used together. For example, the source fluid scale **248** with the source fluid pump **238** can be configured to add an amount of source fluid to a patient's blood that is similar to, if not the same as, an amount of effluent being removed by the effluent pump **224** and stored in the effluent receptacle **226**. The fluid balance of a patient's blood can thus be maintained as the amount of effluent (e.g., fluid) removed from the patient's blood is compensated for by the addition of an approximately equal amount of source fluid. In some examples, a controller is connected to each of the source fluid scale **248**, the effluent scale **246**, the source fluid pump **238**, and the effluent pump **224** to ensure a desired fluid balance in the patient's blood. For instance, the controller can receive weights of the source fluid and the effluent via the source fluid scale **248** and the effluent scale **246** respectively while also receiving the pump speed of both the source fluid pump **238** and the effluent pump **224**. The controller can then adjust the source fluid pump **238** and/or the effluent pump **224** to maintain or change a fluid balance within the patient's blood. Additionally or alternatively, in some embodiments, the blood pump **210** can be adjusted based on any one of the source fluid scale **248**, the source fluid pump **238**, the effluent scale **246**, or the effluent pump **224**.

(49) Continuing with the embodiment of FIG. 2, the extracorporeal blood filtering machine **200** can include an anticoagulant source **240** fluidly connected to the blood line between the blood inlet **204** and the filter **216** via an anticoagulant line **242**. The anticoagulant source **240** is illustrated as a syringe, however other source types can be used. The anticoagulant source **240** can be used to introduce anticoagulant into the blood line before the filter **216** to ensure that blood does not clot within the filter and prevent blood from flowing therethrough. The anticoagulant source **240** can be used to introduce anticoagulant manually or automatically (e.g., via a motor pushing on the syringe plunger) into the blood line. In some examples, the anticoagulant source is connected to the filter directly.

(50) In addition to the fluid lines, pumps, and scales, the extracorporeal blood filtering machine **200** also includes various sensors. For example, between the blood inlet **204** and the blood pump **210**, the extracorporeal blood filtering machine **200** includes a hematocrit sensor **206** configured to sample the blood in the blood line to measure a proportion of red blood cells within the patient's blood. In some examples, the hematocrit sensor **206** is configured to output a hematocrit signal, which is indicative of the proportion of red blood cells within a patient's blood.

(51) The extracorporeal blood filtering machine **200** also includes a series of pressure sensors **208**, **212**, **222**, **227** configured to measure a pressure of the fluid within them. The series of pressure sensors **208**, **212**, **222**, **227** can be monitored to verify proper fluid flows within the extracorporeal blood filtering machine **200**. A first pressure sensor **208** is part of the blood circuit and is located between the blood inlet **204** and the blood pump **210**. A second pressure sensor **212** is also part of the blood circuit and is located between the blood pump **210** and the filter **216**. As shown, the anticoagulant line **242** connects to the blood circuit at the second pressure sensor **212**. A third pressure sensor **222** is part of the effluent circuit and is located on the effluent line **220** after the filter **216** and before the effluent receptacle **226**. Lastly, a fourth pressure sensor **227** is part of the blood circuit and is located after the filter **216** and before the blood outlet **218**. While the pressure sensors **208**, **212**, **222**, and **227** are illustrated in specific positions within their respective fluid circuits, the pressure sensors **208**, **212**, **222**, and **227** can be located in different positions. For example, the fourth pressure sensor **227** is illustrated as being before the bubble trap **228** but can be located after the bubble trap **228** in some examples. The pressure sensors **208**, **212**, **222**, and **227** can be any type of pressure sensor including an air pressure sensor.

(52) The extracorporeal blood filtering machine **200** further includes a blood leak detector **214**, which is located on the effluent line **220** after the filter **216**. The blood leak detector **214** can detect if some amount of a patient's blood has leaked through the filter **216** into the effluent line **220**. In some examples, the blood leak detector **214** can output a signal indicating if a threshold of blood is leaking into the effluent line.

(53) Additionally, in the embodiment of FIG. 2, the extracorporeal blood filtering machine **200** includes a bubble trap **228** located between the filter **216** and the blood outlet **218**. The bubble trap **228** is fluidly connected to the blood outlet **218** and removes air bubbles present in the blood line. After the bubble trap **228**, the extracorporeal blood filtering machine **200** includes a bubble sensor **230** (e.g., air bubble sensor) that detects/identifies if any gas bubbles (e.g., air bubbles) are present in the blood outlet **218** connected to the patient. If the bubble sensor **230** detects any gas bubbles are present in the blood outlet, the bubble sensor **230**, or a controller connected thereto, can activate a clamp **232** to clamp the blood outlet **218** and prevent any gas bubbles from flowing into the patient's body. The clamp **232** can stop all flow of blood to the patient to ensure no gas bubbles enter the patient's body. Additionally, if the bubble sensor **230** detects a gas bubble in the blood outlet **218**, the bubble sensor, or a controller connected thereto, can stop the blood pump **210**, the source fluid pump **238**, and/or the effluent pump **224** from pumping to prevent a pressure buildup within the fluid lines of the extracorporeal blood filtering machine **200**.

(54) In addition to the sensors and the fluid components, the extracorporeal blood filtering machine **200** can include a display **244**. The display **244** can be configured to display information about the extracorporeal blood filtering machine **200** including any data generated by the various sensors and pumps. The display **244** can also be configured to display information about a patient and information that is obtained from another machine (e.g., via electronic communication). In some examples, the display **244** comprises a user interface (e.g., via touch screen).

(55) The extracorporeal blood filtering machine **200** can also include a controller **249**. The controller can be in communication (e.g., electric communication) with one or more of the hematocrit sensor **206**, the pressure sensors **208**, **212**, **222**, **227** the blood pump **210**, the blood leak detector **214**, the effluent pump **224**, the bubble sensor **230**, the clamp **232**, the source fluid pump **238**, the display **244**, the effluent scale **246**, and/or the source fluid scale **248**. In some examples,

the controller **249** is also in communication with the anticoagulant source **240**. In general, the controller **249** can receive signals and/or send signals to any one or more of the above listed components and can perform functions related to received and/or sent signals. For example, the controller can receive signals from the various sensors, use those signals in a comparison, and output signals to one or more of the various pumps to adjust operation of one or more of the pumps based on received signals from the various sensors.

(56) Moving to an example operation of FIG. 2, the blood inlet **204** receives blood from a patient with the blood passing through the hematocrit sensor **206**. The hematocrit sensor **206** can measure a proportion of red blood cells within the patient's blood. Next, the blood passes through the first pressure sensor **208** which measures the blood pressure in the blood line before the blood is pumped through the blood pump **210**. Once pumped through the blood pump **210**, the blood passes into the second pressure sensor **212**, which measures the blood pressure in the blood line after the blood pump **210**. At this same point, anticoagulant can be added from the anticoagulant source **240**, through the anticoagulant line **242**, and into the blood line before the filter **216**. Next, the blood passes through the filter **216**, which removes waste from the blood in the form of effluent. The blood continues through the blood line to the fourth pressure sensor **227**, which measures the blood pressure in the blood line after the filter **216**. The blood further continues to the bubble trap **228**, which removes any air bubbles from the blood line. The blood then passes through the bubble sensor **230**, which determines if any gas bubbles are present in the blood line. The blood continues past the clamp **232**, which can clamp the blood line for reasons such as gas bubbles present within the blood line and finally returns back to the patient via the blood outlet **218**.

(57) While blood moves through the filter **216**, effluent removed from the blood by the filter **216** is pumped through the effluent line **220** through the blood leak detector **214** via the effluent pump **224**. The blood leak detector can detect if some amount of a patient's blood has leaked into the effluent line **220**. Next, the effluent continues to the third pressure sensor **222**, which can measure the pressure of the effluent within the effluent line **220**. The effluent is then pumped to the effluent receptacle **226**, which is attached to the effluent scale **246**. The effluent scale **246** can measure the weight of the effluent and can determine the amount of effluent within the effluent receptacle **226**.

(58) Further, while blood moves through the filter **216**, source fluid can be added to the blood line at the filter **216**. The source fluid can be pumped from the source fluid reservoir **234**, through the source fluid line **236**, to the filter **216** via the source fluid pump **238**. The source fluid reservoir **234** is connected to the source fluid scale **248**, which can measure the weight of the source fluid pumped into the blood line and can determine the amount of source fluid added to the blood line. Information about the source fluid added, effluent removed, the blood pump speed, and other information about the operation of the extracorporeal blood filtering machine **200** can be displayed in the display **244**.

(59) The illustrated embodiment of FIG. 2 is one configuration of an example extracorporeal blood filtering machine **200** that incorporates blood filtering, effluent removal, and source fluid replacement. Some configurations of an extracorporeal blood filtering machine are similar to FIG. 2; however, they incorporate the source fluid into the blood circuit at different locations. Alternatively, some configurations of an extracorporeal blood filtering machine may not include source fluid replacement.

(60) Moving to FIG. 3, FIG. 3 is a diagrammatic view of the example extracorporeal blood filtering machine **200** of FIG. 2 in one example configuration according to an aspect of the present disclosure. Specifically, the extracorporeal blood filtering machine **200** is in a configuration for performing continuous venovenous hemodialysis. In this configuration, the source fluid line **236** is connected to a first position **250** in the blood circuit, with the first position **250** being at the filter **216**. To connect the source fluid line **236** at the first position **250**, the extracorporeal blood filtering machine **200** includes an access port **252**, which can be referred to as a continuous venovenous hemodialysis access port **252**. The continuous venovenous hemodialysis access port **252** facilitates

connection of the source fluid line **236** to the filter **216**.

(61) In operation of the embodiment of FIG. 3, blood is pumped from the patient through the blood inlet **204** via the blood pump **210**. At the same time, source fluid is pumped from a source fluid reservoir (e.g., **234**) through the source fluid line **236** via the source fluid pump **238** to the first position **250**. At the filter **216**, the source fluid is pumped in the same direction to the flow of blood (e.g., co-axially) in the filter **216** with the filter **216** including a highly permeable membrane. The filter **216** filters out waste from the blood in the form of effluent, with the effluent then pumped into an effluent receptacle (e.g., **226**) via the effluent pump (e.g., **224**). The filtered blood continues through the blood circuit until it returns to the patient via the blood outlet **218**. In some examples, the source fluid is pumped in an opposite direction to the flow of blood (e.g., counter-axially) in the filter **216**, with the filter **216** including a highly permeable membrane.

(62) Moving to FIG. 4, FIG. 4 is a diagrammatic view of the example extracorporeal blood filtering machine **200** of FIG. 2 in an alternate example configuration according to an aspect of the present disclosure. Specifically, the extracorporeal blood filtering machine **200** is in a configuration for performing continuous venovenous hemofiltration, with source fluid being added pre-filter. In this configuration, the source fluid line **236** is connected to a second position **254** in the blood circuit, with the second position **254** being between the blood inlet **204** and the filter **216**. In some examples, the second position **254** is defined as being between a hematocrit sensor (e.g., **206**) and the filter **216**. To connect the source fluid line **236** at the second position **254**, the extracorporeal blood filtering machine **200** includes access ports **256**, **258**, which can each be referred to as a first continuous venovenous hemofiltration access port **256**, **258**. The access ports **256**, **258** facilitate connection of the source fluid line **236** to the blood line between the blood inlet **204** and the filter **216**.

(63) Both the access ports **256**, **258** are located at the second position **254**, however, the access port **258** is located before the blood pump **210** while the access port **256** is located after the blood pump **210**. The source fluid line **236** can connect to either of the access ports **256**, **258** to introduce source fluid to the blood line. In some examples, only one of access port **256** or access port **258** is incorporated into the extracorporeal blood filtering machine **200**. Alternatively, in some examples, more than one access port can be included between the blood inlet **204** and the filter **216** (e.g., in the second position **254**).

(64) In operation of the embodiment of FIG. 4, blood is pumped from the patient through the blood inlet **204** via the blood pump **210**. At the same time, source fluid is pumped from a source fluid reservoir (e.g., **234**) through the source fluid line **236** via the source fluid pump **238** to the second position **254**. At the second position **254**, between the blood inlet **204** and the filter **216**, the source fluid is introduced directly into the blood line and combines with the blood. The blood and source fluid combination then continues through the filter **216**, with the filter **216** filtering out waste from the blood and source fluid combination in the form of effluent. The effluent is then pumped into an effluent receptacle (e.g., **226**) via the effluent pump (e.g., **224**). The filtered blood and source fluid combination then continues through the blood circuit until it returns to the patient via the blood outlet **218**.

(65) Moving to FIG. 5, FIG. 5 is a diagrammatic view of the example extracorporeal blood filtering machine **200** of FIG. 2 in an alternate example configuration according to an aspect of the present disclosure. Specifically, the extracorporeal blood filtering machine **200** is in a configuration for performing continuous venovenous hemofiltration with source fluid being added post-filter. In this configuration, the source fluid line **236** is connected to a third position **260** in the blood circuit, with the third position **260** being between the filter **216** and the blood outlet **218**. In some examples, the third position **260** is defined as being between the filter **216** and an air bubble sensor (e.g., **230**). To connect the source fluid line **236** at the third position **260**, the extracorporeal blood filtering machine **200** includes access ports **262**, **264**, which can each be referred to as a second continuous venovenous hemofiltration access port. The access ports **262**, **264** facilitate connection

of the source fluid line **236** to the blood line between the filter **216** and the blood outlet **218**.

(66) Both the access ports **262**, **264** are located at the third position **260**, however, the access port **264** is located closer to the filter **216** in the blood line than the access port **262**. The source fluid line **236** can connect to either of the access ports **262**, **264** to introduce source fluid to the blood line. In some examples, only one of access port **262** or access port **264** is incorporated into the extracorporeal blood filtering machine **200**. Alternatively, in some examples, more than one access port can be included between the filter **216** and the blood outlet **218**.

(67) In operation of the embodiment of FIG. 5, blood is pumped from the patient through the blood inlet **204** via the blood pump **210** to the filter **216**. The blood is then filtered with the filter **216**, removing waste from the blood in the form of effluent. The effluent is then pumped into an effluent receptacle (e.g., **226**) via the effluent pump (e.g., **224**). At the same time, source fluid is pumped from a source fluid reservoir (e.g., **234**) through the source fluid line **236** via the source fluid pump **238** to the third position **260**. At the third position **260**, between the filter **216** and the blood outlet **218**, the source fluid is introduced directly into the blood line and combines with blood that has already been filtered by the filter **216**. The filtered blood and source fluid combination then continues through the blood circuit until it returns to the patient via the blood outlet **218**.

(68) Moving to FIG. 6, FIG. 6 is a perspective view of the example extracorporeal blood filtering machine **200** of FIG. 2 in an alternate example configuration according to an aspect of the present disclosure. Specifically, the extracorporeal blood filtering machine **200** is in a configuration for performing slow continuous ultrafiltration with no source fluid being added by the extracorporeal blood filtering machine **200**. In this configuration, a patient's blood is filtered to remove waste and excess fluid.

(69) In operation of the embodiment of FIG. 6, blood is pumped from the patient through the blood inlet **204** via the blood pump **210** to the filter **216**. The blood is then filtered with the filter **216**, removing waste from the blood in the form of effluent. The effluent is then pumped into an effluent receptacle (e.g., **226**) via the effluent pump (e.g., **224**). The filtered blood then continues through the blood circuit until it returns to the patient via the blood outlet **218**.

(70) Now referring to the illustrated embodiments of FIGS. 2-6, the extracorporeal blood filtering machine **200** of each of the illustrated embodiments include all the access ports including the continuous venovenous hemodialysis access port **252**, the first continuous venovenous hemofiltration access port **256**, **258**, and the second continuous venovenous hemofiltration access port **262**, **264**. The continuous venovenous hemodialysis access port **252** can facilitate connection of the source fluid line **236** to the first position **250**, which is at the filter **216**. The first continuous venovenous hemofiltration access port **256**, **258** can facilitate connection of the source fluid line **236** at the second position **254**, which is between the blood inlet **204** and the filter **216**. The second continuous venovenous hemofiltration access port **260**, **262** can facilitate connection of the source fluid line **236** to the third position **260**, which is between the filter **216** and the blood outlet **218**. Accordingly, the extracorporeal blood filtering machine **200** has a source fluid line **236** that can be connected to a single selected position in the blood circuit, with the single selected position being selected from among multiple potential positions, including the first position **250**, the second position **254**, the third position **260**, and no position (e.g., not connected as in FIG. 6). The ability to connect the source fluid line **236** to any of the selected positions is advantageous as a user can use the extracorporeal blood filtering machine **200** for different therapies that involve supplying source fluid at different points within the blood circuit.

(71) In the illustrated embodiments of FIGS. 2-6, each of the continuous venovenous hemodialysis access port **252**, the first continuous venovenous hemofiltration access port **256**, **258**, and the second continuous venovenous hemofiltration access port **262**, **264**, can comprise a self-sealing luer. In some examples, all the access ports of the extracorporeal blood filtering machine **200** comprise self-sealing luers. Using self-sealing luers for the access ports can be advantageous as a user can easily connect and disconnect a source fluid line from an access port without needing to

clamp the access port to prevent air from entering the line and prevent fluid from leaking.

(72) In some examples, the various access ports can enable a connected source fluid line **236** to be disconnected from a selected position (e.g., a second position **254**) and reconnected to a different position (e.g., a third position **260**) in the blood circuit while the blood pump **210** and the effluent pump **224** are operating. In some such examples, the access ports comprise self-scaling luers to prevent air from entering the line and prevent fluid leaks.

(73) As discussed with respect to FIG. **2**, the extracorporeal blood filtering machine **200** can include a controller **249**. In some examples, the controller **249** can be used to ensure that the source fluid line **236** is connected to the selected position rather than to an unselected position. For instance, the controller **249** can be configured to receive a measurement of pressure in the blood line, such as from the pressure sensors **208**, **212**, and/or **227**, during priming of the blood line. The controller **249** can further be configured to compare the received measurement with an expected value associated with a selected position (e.g., a first position **250**, at the filter **216**). The controller **249** may alert a user if the received pressure measurement is not within a threshold of the expected value as that would indicate an incorrect source fluid line connection to the blood line.

(74) Moving to FIG. **7**, FIG. **7** is a flow chart of an example method related to the illustrated embodiments of FIGS. **2-6**. The method starts at step **700** with providing an extracorporeal blood filtering machine. As discussed elsewhere herein, the extracorporeal blood filtering machine can comprise a blood circuit, an effluent circuit, and a source fluid circuit. The blood circuit can include a blood line with a blood inlet and blood outlet, a filter fluidly connected to the blood line between the blood inlet and the blood outlet, and a blood pump. The effluent circuit can include an effluent line fluidly connected to the filter and an effluent pump. The source fluid circuit can include a source fluid line fluidly connected to a source fluid reservoir and a source fluid pump. In some examples, the extracorporeal blood filtering machine also includes a hematocrit sensor in the blood line between the blood inlet and the filter. Also, in some examples, the extracorporeal blood filtering machine includes an air bubble sensor in the blood line between the filter and the blood outlet. The extracorporeal blood filtering machine can further include an anticoagulant source fluidly connected to the blood line between the blood inlet and the filter.

(75) The method continues with step **702** with determining whether to connect a source fluid line to the blood circuit. If a determination is made to not connect the source fluid line to the blood circuit, the method can end with the extracorporeal blood filtering machine performing slow continuous ultrafiltration (SCUF). One example of SCUF operation is illustrated in FIG. **6**. However, if a determination is made to connect the source fluid line to the blood circuit, the method continues to step **704**, selecting a connection position in the blood circuit from among: the filter, between the blood inlet and the filter, and between the filter and the blood outlet. Once selected, the method continues with connecting the source fluid line to the connection position in the blood circuit as in step **706**. In many examples, the source fluid line is connected to the connection position in the blood circuit and to no other positions in the blood circuit. In this way, only one source fluid line need be primed, and setup of the extracorporeal blood filtering machine can be significantly simplified.

(76) The method continues with operating the blood pump to pump blood in the blood circuit in step **708**. Specifically, the method includes operating the blood pump to pump blood from the blood inlet, through the blood line and the filter, and to the blood outlet, with the filter removing waste from the blood and providing the waste to the effluent line in the form of effluent. Next, the method continues in step **710** with operating the effluent pump to pump effluent in the effluent circuit. Specifically, the method includes operating the effluent pump to pump the effluent from the filter through the effluent line into an effluent receptacle. In some example methods, though, the effluent pump need not be operated. The method further continues with operating the source fluid pump to pump source fluid into the blood circuit in step **712**. Specifically, the method includes operating the source fluid pump to pump source fluid from the source fluid reservoir through the

source fluid line into the blood circuit. Depending upon which connection position is selected in step **704**, the extracorporeal blood filtering machine will operate in one of continuous venovenous hemodialysis (CVVHD), continuous venovenous hemofiltration pre-filter (CVVHF—Pre), or continuous venovenous hemofiltration post-filter (CVVHF—Post). An example of CVVHD connection is illustrated in FIG. **3**. An example of CVVHF—Pre is illustrated in FIG. **4**. An example of CVVHF—Post is illustrated in FIG. **5**.

(77) As discussed with respect to FIGS. **2-6**, the connection position can be chosen relative to other components of the extracorporeal blood filtering machine. For instance, in some embodiments, the connection position is between a hematocrit sensor and the filter. In some embodiments, the connection position is between the filter and an air bubble sensor.

(78) The method can optionally continue in step **714** with determining that the source fluid line should be disconnected from the connection position in the blood circuit, discontinuing operation of the source fluid pump, and disconnecting the source fluid line from the connection position in the blood circuit. Next, the method can optionally continue in step **716** with selecting a reconnection position in the blood circuit. For instance, the reconnection position can be selected from among the filter, between the blood inlet and the filter, and between the filter and the blood outlet. Further in step **716**, the method includes connecting the source fluid line to the reconnection position in the blood circuit and operating the source fluid pump to pump source fluid from the source fluid reservoir through the source fluid line into the blood circuit.

(79) In addition to or in lieu of the optional step **714**, the method can continue in optional step **718** with receiving a measurement of pressure in the blood line during priming of the blood line. The method further includes comparing the measurement with an expected value associated with the single selected connection position rather than to a different position. This method step can ensure the extracorporeal blood filtering machine is connected according to a selected connection position.

(80) While the steps of FIG. **7** may be illustrated and discussed in a particular order, it will be appreciated that the steps of FIG. **7** need not be performed in the illustrated or described order. For instance, in some examples, method steps illustrated as occurring after other methods steps can, in actuality, occur before the other method steps. Further, some steps can be performed substantially simultaneously as other steps, while some steps can be performed any amount of time after other steps. Moreover, while some steps are illustrated with dotted lines to indicate they are optional, in some examples, steps illustrated with solid lines can also be optional.

(81) The extracorporeal blood filtering machine described with respect to FIGS. **2-6** and the accompanying method described with respect to FIG. **7** has several advantages over existing systems. For example, the extracorporeal blood filtering machine can be configured to perform four different methods of filtration including SCUF, CVVHD, CVVHF—Pre, and CVVHF—Post. The flexibility in operation of the extracorporeal blood filtering machine can allow it to replace multiple machines that may each perform only one method of filtration. Additionally, it can be relatively easy to change the operation of the extracorporeal blood filtering machine from one method of filtration to another. For example, one can remove the source fluid line from one connection point that has a self-sealing luer and does not require extra clamping, and can move and connect the source fluid line to a different connection point that also has a self-sealing luer for a quick connection. In some examples, being able to select a connection position from among multiple potential positions simplifies a priming operation. In such examples, the priming operation can include priming the single source fluid line, which then can be connected to the single selected connection position, as opposed to having to prime multiple source fluid lines that are each connected to a different position. Priming and connecting multiple source fluid lines to multiple different positions on the extracorporeal blood filtering machine to preserve optionality can be unnecessarily complex.

(82) Moving to FIG. **8**, FIG. **8** is a schematic view of an example extracorporeal blood filtering machine **800** according to an aspect of the present disclosure. The extracorporeal blood filtering

machine **800** of FIG. **8** is similar to that of FIG. **2** in that it filters blood and can include some of the same components. However, the extracorporeal blood filtering machine **800** can include some additional components while not including other components of the extracorporeal blood filtering machine embodiment of FIG. **2**. Further, for case of readability, the extracorporeal blood filtering machine **800** in FIG. **8** does not illustrate some components that can be a part of the extracorporeal blood filtering machine **800**. Some of these components include: a hematocrit sensor (e.g., **206**), various pressure sensors (e.g., **208**, **212**, **222**, **227**), a source fluid reservoir (e.g., **234**), a source fluid scale (e.g., **248**), a source fluid line (e.g., **236**), a source fluid pump (e.g., **238**), an anticoagulant source (e.g., **240**), an anticoagulant line (e.g., **242**), and an effluent scale (e.g., **246**). One having ordinary skill in the art will appreciate that some or all of the listed components can be included in the extracorporeal blood filtering machine **800** of FIG. **8**.

(83) Continuing with FIG. **8**, the extracorporeal blood filtering machine **800** includes a blood circuit. The blood circuit comprises a blood line with a blood inlet **804** configured to receive blood from a patient and a blood outlet **818** configured to return the blood to the patient. The blood circuit also includes a filter **816** fluidly connected to the blood line between the blood inlet and the blood outlet and a blood pump **810**. The filter **816** is configured to remove waste from the blood, such as in the form of effluent. The blood pump **810** is configured to pump the blood from the blood inlet **804**, through the filter **816**, and to the blood outlet **818**. The extracorporeal blood filtering machine **800** also includes an effluent circuit. The effluent circuit comprises an effluent line **820** fluidly connected to the filter **816** with the effluent line configured to receive the waste from the filter **816** in the form of effluent. The effluent circuit also includes an effluent pump **824** configured to pump the effluent from the filter **816**, through the effluent line **820**, and into an effluent receptacle **826**. The effluent circuit can additionally include a blood leak detector **814**, which is configured to detect a presence of blood within the effluent line **820**. The extracorporeal blood filtering machine **800** further includes a controller **849** and a display **844** with the controller **849** in communication with various components of the extracorporeal blood filtering machine **800** including the display **844** and the blood leak detector **814**.

(84) Further in FIG. **8**, the extracorporeal blood filtering machine **800** includes one or more hemolysis sensors **870**, **872**, **874**, **876**, which are configured to sample fluid in a fluid line and output a hemolysis signal indicative of a detected degree of hemolysis in the fluid. A hemolysis sensor at a first location **870** can be used to sample the blood in the blood line between the blood inlet **804** and the blood pump **810**. A hemolysis sensor at a second location **872** can be used to sample blood in the blood line between the blood pump **810** and the filter **816**. A hemolysis sensor at a third location **874** can be used to sample effluent in the effluent line **820** between the filter **816** and the effluent pump **824**. A hemolysis sensor at a fourth location **876** can be used to sample blood in the blood line between the filter **816** and the blood outlet **818**. While four hemolysis sensors are illustrated, the extracorporeal blood filtering machine **800** can include one, two, three, four, or more hemolysis sensors. For example, the extracorporeal blood filtering machine **800** can include a single hemolysis sensor such as the hemolysis sensor at the third position **874**. In another example, the extracorporeal blood filtering machine **800** can include two hemolysis sensors such as the hemolysis sensor at the first position **870** and the hemolysis sensor at the fourth position **876**. Additionally, while each of the hemolysis sensors **870**, **872**, **874**, **876** are illustrated as being located at a specific point within the blood line or effluent line, the hemolysis sensors **870**, **872**, **874**, **876** can be located at different points within the blood line or effluent line.

(85) In some examples, the hemolysis sensors **870**, **872**, **874**, **876** are indirect sensors whereby they are not in direct contact with the fluid they are sampling. For example, the hemolysis sensors can be in optical communication with a fluid line. Alternatively, in some examples, the hemolysis sensors **870**, **872**, **874**, **876** are direct contact sensors whereby they are in fluid communication with the fluid they are sampling. In some examples, some of the hemolysis sensors are indirect sensors and some of the hemolysis sensors are direct contact sensors. The hemolysis sensors **870**, **872**, **874**,

876 can include optical-type sensors and use the electromagnetic spectrum to determine an amount of hemolysis present in the fluid.

(86) Continuing with FIG. **8**, the controller **849** is in electronic communication with each of the hemolysis sensor at the first position **870**, the hemolysis sensor at the second position **872**, the hemolysis sensor at the third position **874**, and the hemolysis sensor at the fourth position **876**. Each of the hemolysis sensors **870**, **872**, **874**, **876** can output a hemolysis signal to the controller **849**, with the hemolysis signal being indicative of a detected degree of hemolysis. The controller **849** is also in communication with the blood pump **810** and the effluent pump **824** and can receive signals indicative of the pump speed (e.g., rpm) of each and can output signals to control the blood pump **810** and the effluent pump **824**. The controller **849** is further in communication with the blood leak detector **814** and can receive a signal from the blood leak detector **814** indicative of a blood leak in the effluent line. Additionally, the controller is in communication with the display **844** and can send and/or receive signals from the display **844**.

(87) In one example operation of the extracorporeal blood filtering machine **800** involving the controller **849**, the blood leak detector **814** can detect a presence of blood within the effluent line **820** and can output a signal to the controller **849** indicative of the blood leak condition. The controller **849** can receive the signal from the blood leak detector **814** and can output a blood leak alarm signal. In some examples, the blood leak alarm signal is sent to the display **844** to alert a user of the blood leak condition. In some examples, the controller **849** can adjust operation of one or more of the blood pump **810** or the effluent pump **824** in response to receiving a signal from the blood leak detector indicative of a blood leak. For instance, the controller **849** can be configured to stop the effluent pump **824** if the blood leak detector **814** detects the presence of blood within the effluent line **820**.

(88) In some examples, the blood leak detector **814** can work together with the hemolysis sensor at the third position **874**. For example, blood may improperly pass through the filter **816** into the effluent line either because the filter **816** is improperly allowing blood to pass through the filter **816** or because the blood is hemolyzed and is thus small enough to pass through the filter **816**. The blood leak detector **814** can help determine if the filter **816** is improperly allowing blood to pass through the filter **816**. The hemolysis sensor at the third position **874** can help determine if the blood is hemolyzed and is thus small enough to pass through the filter **816**. In some examples, the controller **849** can receive a signal from the blood leak detector **814** and a hemolysis signal from the hemolysis sensor at the third position **874** and can identify a blood leak condition and/or a hemolysis condition.

(89) In another example operation of the controller **849**, the controller **849** can receive a hemolysis signal from one or more of the hemolysis sensors **870**, **872**, **874**, **876**. If, for instance, the received hemolysis signal indicates a detected degree of hemolysis exceeding a hemolysis threshold, the controller **849** can output a hemolysis alert signal to the display **844**. The display **844** can then display a hemolysis alert to alert a user of the hemolysis condition. In some examples, the controller **849** can adjust operation of one or more of the blood pump **810** or the effluent pump **824** in response to receiving a hemolysis signal from a hemolysis sensor (e.g., **870**, **872**, **874**, **876**) exceeding a hemolysis threshold. For example, the controller **849** can completely stop the blood pump **810** and/or the effluent pump **824** in response to receiving a hemolysis signal exceeding the hemolysis threshold.

(90) In some embodiments, multiple hemolysis thresholds can be used. For example, if the controller **1249** receives a hemolysis signal that exceeds a first hemolysis threshold, the controller **1249** can output a hemolysis alert signal. In this example, if the controller **1249** receives a hemolysis signal that exceeds a second hemolysis threshold, which is larger than the first hemolysis threshold, the controller **1249** can adjust (e.g., stop) operation of the blood pump **810** and/or the effluent pump **824**.

(91) In some examples, a hemolysis threshold comprises a slope threshold (e.g., function) of

hemolysis over time. For example, a slope threshold can include an increased degree of hemolysis over a specific period of time. Using a slope threshold can be advantageous as a patient's condition can be the cause of hemolysis detected by the one or more hemolysis sensors instead of the machine. Accordingly, using an absolute value threshold may only alert a user of the extracorporeal blood filtering machine of a patient's condition and not of the condition of the machine. Thus, in some examples, the controller **1249** can receive multiple hemolysis signals from a hemolysis sensor (e.g., **870**, **872**, **874**, **876**) over time and can compare the slope or function of the multiple hemolysis signals to a slope or function indicating an increasing amount of hemolysis over time. An increasing amount of hemolysis can indicate the extracorporeal blood filtering machine is contributing to the hemolysis that is already present due to a patient's condition.

(92) In general, it can be advantageous to include a hemolysis sensor (e.g., **872**, **874**, **876**) between the blood pump **810** and the blood outlet **818** to determine if hemolysis is present in the blood line and/or effluent line. However, in some examples, it is further advantageous to include multiple hemolysis sensors (e.g., **872**, **874**, **876**) located before and after one or more components (e.g., blood pump **810**, filter **816**) to determine if hemolysis is caused by the one or more components.

(93) In some such examples, the extracorporeal blood filtering machine **800** includes a hemolysis sensor at the first position **870**, which can be considered a reference hemolysis sensor **870**. The reference hemolysis sensor **870** can be in communication with the controller **849** and configured to sample the blood in the blood line between the blood inlet and the blood pump. The reference hemolysis sensor **870** can then output a reference hemolysis signal indicative of a reference degree of hemolysis to the controller **849**. The extracorporeal blood filtering machine **800** can further include a hemolysis sensor located anywhere between the blood pump **810** and the blood outlet **818**. For instance, the extracorporeal blood filtering machine **800** can include a hemolysis sensor at the fourth position **876**, which is configured to sample the blood in the blood line between the filter **816** and the blood outlet **818**. The hemolysis sensor at the fourth position **876** can also be configured to output a hemolysis signal indicative of a detected degree of hemolysis.

(94) As the controller **849** is in communication with both the reference hemolysis sensor **870** and the hemolysis sensor at the fourth position **876**, the controller **849** can receive and compare the reference hemolysis signal and the hemolysis signal from the hemolysis sensor at the fourth position **876**. The controller **849** can then output a hemolysis mismatch alert signal if the hemolysis signal from the hemolysis sensor at the fourth position **876** differs from the reference hemolysis signal by more than a threshold amount. In some such examples, the controller **849** can output the hemolysis mismatch signal to the display **844**, which can display the hemolysis mismatch signal. By comparing the reference hemolysis signal with the hemolysis signal from the hemolysis sensor at the fourth position **876**, the controller can determine if the blood pump **810**, the filter **816**, or other components in the blood line (e.g., pressure sensors **208**, **212** of FIG. 2) are causing hemolysis.

(95) While the above example uses the hemolysis sensor at the first position **870** as the reference hemolysis sensor along with the hemolysis sensor at the fourth position **876**, any two hemolysis sensors can be used. For example, the reference hemolysis sensor can be the hemolysis sensor at the first position **870** while a subsequent hemolysis sensor can be the hemolysis sensor at the second position **872**. This configuration would enable the controller **849** to determine if the blood pump is causing hemolysis. In another example, the reference hemolysis sensor can be the hemolysis sensor at the second position **872** while a subsequent hemolysis sensor can be the hemolysis sensor at the third position **874**. This configuration would enable the controller **849** to determine if the filter **816** is causing hemolysis. In many cases, it is advantageous to have the hemolysis sensor at the first location **870** be the reference hemolysis sensor as it can sample blood that has not yet traveled through any components of the extracorporeal blood filtering machine **800** such as the blood pump **810** or the filter **816**. Thus, the reference hemolysis sensor would only include hemolysis present in the patient, not hemolysis caused by any component of the

extracorporeal blood filtering machine **800**.

(96) Moving to FIG. **9**, FIG. **9** illustrates an example method using the extracorporeal blood filtering machine of FIG. **8** and one or more of the hemolysis sensors **870**, **872**, **874**, **876** according to an aspect of the present disclosure. The method starts at step **900** with providing an extracorporeal blood filtering machine. As discussed with respect to FIG. **8**, the extracorporeal blood filtering machine can include a blood circuit comprising a blood line with a blood inlet. The blood circuit can further include a filter fluidly connected to the blood line between the blood inlet and the blood outlet and a blood pump configured to pump blood from the blood inlet, through the filter, and to the blood outlet. The extracorporeal blood filtering machine can also include an effluent circuit with an effluent line fluidly connected to the filter and an effluent pump configured to pump effluent generated by the filter through the effluent line to an effluent receptacle. The extracorporeal blood filtering machine also includes a hemolysis sensor and a controller in communication with the blood pump, the effluent pump, and the hemolysis sensor.

(97) The method continues at step **902** with operating the extracorporeal blood filtering machine via the controller. Operating the extracorporeal blood filtering machine includes pumping blood with the blood pump from a patient into the blood inlet, through the blood line to the filter, and back to the patient through the blood line and out of the blood outlet. The filter can remove waste from the blood and provide the waste to the effluent line in the form of effluent. Operating the extracorporeal blood filtering machine also includes pumping the effluent with the effluent pump through the effluent line into an effluent receptacle. In some examples, the effluent pump and other components need not be operated when operating the extracorporeal blood filtering machine. Operating the extracorporeal blood filtering machine further includes sampling the effluent in the effluent line and/or blood in the blood line with the hemolysis sensor.

(98) The method then continues at step **904** with providing a hemolysis signal indicative of a detected degree of hemolysis from the hemolysis sensor to the controller. Next, in step **906**, a determination is made to whether the detected degree of hemolysis from the hemolysis sensor exceeds a hemolysis threshold. If the detected degree of hemolysis does exceed the hemolysis threshold, then the method continues with the controller outputting a hemolysis alert signal as in step **907**. If the detected degree of hemolysis does not exceed the hemolysis threshold, then the method can continue back with step **902**, operating the extracorporeal blood filtering machine. Optionally, in some examples, the controller can output a hemolysis alert signal to a display, which can then display the hemolysis alert signal as in step **918**.

(99) In some examples, the method can include providing a reference hemolysis sensor in addition to the hemolysis sensor sampling effluent from the effluent line and/or blood from the blood line. In such examples, the method can include steps **908-916**. The method can either go from step **904** directly to step **908**, or alternatively, can go to step **908** after a negative result of the hemolysis threshold determination of step **906**.

(100) In step **908**, the method continues with sampling the blood in the blood line between the blood inlet and the blood pump with the reference hemolysis sensor. The method further continues in step **910** with providing a reference hemolysis signal indicative of a reference degree of hemolysis from the reference hemolysis sensor to the controller. Next, in step **912**, the controller compares the reference hemolysis signal to the hemolysis signal. A determination is then made in step **914** of whether the hemolysis signal differs from the reference hemolysis signal by more than a threshold amount. If the hemolysis signal does differ from the reference hemolysis signal by more than the threshold amount, the controller can output a hemolysis mismatch alert signal as in step **916**. If the hemolysis signal does not differ from the reference hemolysis signal by more than the threshold amount, the method can continue with step **902**, operating the extracorporeal blood filtering machine. In some examples, the controller can output the hemolysis mismatch alert signal to the display which can display the hemolysis mismatch alert signal.

(101) While the steps of FIG. **9** may be illustrated and discussed in a particular order, it will be

appreciated that the steps of FIG. 9 need not be performed in the illustrated or described order. For instance, in some examples, method steps illustrated as occurring after other methods steps can, in actuality, occur before the other method steps. Further, some steps can be performed substantially simultaneously as other steps, while some steps can be performed any amount of time after other steps. Moreover, while some steps are illustrated with dotted lines to indicate they are optional, in some examples, steps illustrated with solid lines can also be optional.

(102) Moving to FIG. 10, FIG. 10 is a diagrammatic view of an example extracorporeal blood filtering machine **1000** according to an aspect of the present disclosure. The extracorporeal blood filtering machine **1000** of FIG. 10 is similar to that of the extracorporeal blood filtering machine of FIG. 2 and can include some or all of the components of FIG. 2. However, the extracorporeal blood filtering machine **1000** can include additional components not found in FIG. 2.

(103) In the illustrated embodiment of FIG. 10, the extracorporeal blood filtering machine **1000** includes a blood circuit with a blood line having a blood inlet **1004** configured to receive blood from a patient and a blood outlet **1018** configured to return the blood to the patient. The blood circuit also includes a filter **1016** fluidly connected to the blood line between the blood inlet **1004** and the blood outlet **1018**. The blood circuit further includes a blood pump **1010** configured to pump the blood from the blood inlet **1004** to the blood outlet **1018** through the filter **1016**, with the filter **1016** configured to remove waste from the blood.

(104) The extracorporeal blood filtering machine **1000** also includes a bubble trap **1028** configured to remove gas bubbles from the blood line before the blood outlet **1018**. After the bubble trap **1028**, the extracorporeal blood filtering machine **1000** includes a bubble sensor **1030** configured to identify gas bubbles within the blood line before the blood outlet **1018**. For instance, in some examples, the bubble sensor **1030** can be an air bubble sensor configured to identify an air bubble in the blood line and output an air bubble signal to a connected controller **1049**.

(105) The extracorporeal blood filtering machine **1000** additionally includes a clamp **1032** configured to engage the blood line and to move between a clamp-open position, in which the blood line is open for blood to return to the patient through the blood outlet **1018**, and a clamp-closed position, in which the blood line is closed off and blood is prevented from returning to the patient through the blood outlet **1018**. In some examples, the clamp **1032** is configured to impart a predetermined clamping force on the blood line when in the clamp-closed position. The clamp **1032** can be configured to prevent blood from returning to the patient for a variety of reasons, including preventing a detected air bubble from entering the patient's circulatory system. In some examples, the extracorporeal blood filtering machine **1000** can include thermal insulation

(106) **1081** around the blood line. The thermal insulation **1081** can be bonded to the blood line in any location and extend for any length of the blood line. However, in the example of FIG. 10, the thermal insulation **1081** is bonded to where the clamp **1032** engages the blood line before the blood outlet **1018**. The thermal insulation **1081** can reduce temperature-based fluctuations in the pliability of the blood line.

(107) Further in FIG. 10, the extracorporeal blood filtering machine **1000** includes a temperature sensor **1080** configured to measure an ambient air temperature and/or a temperature of the blood line. In FIG. 10, the temperature sensor **1080** is illustrated as being located on the exterior of the blood line proximate the clamp **1032**, or as being located proximate the clamp **1032**. In some examples, the extracorporeal blood filtering machine **1000** includes more than one temperature sensor. For instance, one temperature sensor can be located on the exterior of the blood line while another temperature sensor is located away from the blood line (e.g., not contacting the blood line). In some examples, a temperature sensor on the exterior of the blood line can measure the temperature of an exterior of the blood line while a temperature sensor away from the blood line can measure an ambient air temperature.

(108) The extracorporeal blood filtering machine **1000** can also include a controller **1049** and a display **1044**. The controller **1049** is in communication with the blood pump **1010** and the clamp

1032 and can be in further communication with the temperature sensor **1080** and the bubble sensor **1030**. The controller **1049** can also be in communication with the display **1044**. In some examples, the controller **1049** can be in communication with other components of the extracorporeal blood filtering machine **1000**, including components described in connection with FIG. 2 and FIG. 8. (109) In operation, the controller **1049** can be configured to receive the ambient air temperature and/or the blood line temperature from the temperature sensor **1080** and can adjust an operation of the clamp **1032** based on the received ambient air temperature and/or blood line temperature. This operation of the clamp **1032** can be advantageous as the tubing on which the clamp **1032** clamps down can become stiffer over time due to a change in its temperature. For instance, in some examples, the controller **1049** is configured to adjust the predetermined clamping force of the clamp **1032** based on the received ambient air temperature and/or blood line temperature. In some such examples, the controller **1049** can be configured to increase the predetermined clamping force when the ambient air temperature and/or the blood line temperature is below a first threshold. Similarly, the controller **1049** can be configured to decrease the predetermined clamping force when the ambient air temperature and/or the blood line temperature is above a second threshold. Decreasing the predetermined clamping force of the clamp **1032** can be advantageous as clamping too hard on the tubing may cause it to rupture.

(110) In another operation, the controller **1049** can adjust operation of the clamp **1032** by causing the clamp to move from the clamp-open position to the clamp-closed position and back to the clamp-open position if the ambient air temperature and/or the blood line temperature is below a threshold. Again, the tubing of the blood line on which the clamp **1032** clamps down can become stiffer over time, in part due to temperature changes (e.g., colder temperatures). By adjusting the operation of the clamp **1032** to move between a clamp-open position to the clamp-closed position and back again (e.g., to squeeze the tube one or two or several times), the tubing of the blood line can be kept soft enough to clamp with a predetermined clamping force. In some examples, the controller **1049** can be configured to pause the blood pump **1010** when the clamp **1032** is in the clamp-closed position. This operation can prevent a pressure buildup in the blood line. In some examples, the controller **1049** can repeat the process of clamping and unclamping the clamp **1032** periodically to maintain a desired stiffness of the tubing of the blood line.

(111) In some examples, the controller **1049** can be configured to initiate an alarm mode in which the controller controls the clamp **1032** to move from the clamp-open position to the clamp-closed position. In some such examples, the controller **1049** can initiate the alarm mode when the controller **1049** itself identifies an alarm condition. Additionally or alternatively, the controller **1049** can be configured to initiate an alarm mode when the controller **1049** receives an alarm signal. The alarm signal can comprise any number of signals including, for instance, an alarm signal from the bubble sensor **1030**. For example, if the bubble sensor **1030** identifies an air bubble in the blood line, it can send an air bubble signal to the controller **1049** which the controller **1049** receives and subsequently initiates the alarm mode. Thus, if the bubble sensor **1030** identifies an air bubble in the blood line, the controller **1049** can cause the clamp **1032** to move to the clamp-closed position and prevent the air bubble from entering a patient's bloodstream.

(112) Moving to FIG. 11, FIG. 11 is a flowchart of an example operation of the example extracorporeal blood filtering machine of FIG. 10. The method starts at step **1100** with providing an extracorporeal blood filtering machine. The extracorporeal blood filtering machine comprises a blood circuit. The blood circuit comprises a blood line including a blood inlet and a blood outlet, a filter fluidly connected to the blood line between the blood inlet and the blood outlet, and a blood pump. The extracorporeal blood filtering machine also includes a clamp engaged with the blood line, a temperature sensor, and a controller in communication with the blood pump and the clamp.

(113) Next, in step **1102**, the controller operates the extracorporeal blood filtering machine causing the blood pump to pump blood from a patient, through the blood inlet, into the filter, and out through the blood outlet back to the patient. The method also includes measuring the ambient air

temperature and/or temperature of the blood line with the temperature sensor and providing the ambient air temperature and/or the temperature of the blood line to the controller in step **1104**. The method continues with step **1106** with the controller adjusting an operation of the clamp based on the received ambient air temperature and/or blood line temperature.

(114) In some examples, the controller adjusting the operation of the clamp includes adjusting a predetermined clamping force the clamp imparts to the blood line to prevent blood from returning to the patient through the blood circuit as in **1108**. In some such examples, adjusting the predetermined clamping force includes increasing the predetermined clamping force via the controller when the ambient air temperature and/or the blood line temperature is below a first threshold (e.g., when tubing is stiffer) as in **1110**. Further, in some such examples, adjusting the predetermined clamping force includes decreasing the predetermined clamping force via the controller when the ambient air temperature and/or the blood line temperature is above a second threshold (e.g., when tubing is softer).

(115) In some examples, the controller adjusting operation of the clamp includes causing the clamp to impart an intermittent reconditioning force on the blood line by the controller as in step **1114**. The intermittent reconditioning force can include the clamp moving from a clamp-open position to a clamp-closed position and back to the clamp-open position (e.g., squeezing the blood line a few times). In some examples, the intermittent reconditioning force includes the clamp moving from the clamp-open position to a partially-closed position where some blood still flows through the blood line past the clamp.

(116) In some embodiments, only one of adjusting the predetermined clamping force or imparting an intermittent reconditioning force is performed. Alternatively, in some embodiments, both can be performed. For example, the controller can adjust the predetermined clamping force of the clamp based on a received ambient air temperature and/or blood line temperature and can further intermittently apply the adjusted, predetermined clamping force to the blood line.

(117) While the steps of FIG. **11** may be illustrated and discussed in a particular order, it will be appreciated that the steps of FIG. **11** need not be performed in the illustrated or described order. For instance, in some examples, method steps illustrated as occurring after other methods steps can, in actuality, occur before the other method steps. Further, some steps can be performed substantially simultaneously as other steps, while some steps can be performed any amount of time after other steps.

(118) The above embodiments are advantageous as they can help ensure that the clamp can maintain proper operation and prevent blood, which may contain gas bubbles, from being returned to the patient and causing the patient harm.

(119) Moving to FIG. **12**, FIG. **12** is a diagrammatic view of an example extracorporeal blood filtering system **1200** according to an aspect of the present disclosure. The extracorporeal blood filtering system **1200** can include some or all of the components described elsewhere herein such as in connection with FIG. **2** and FIG. **10**. However, the extracorporeal blood filtering system **1200** can also include additional components. For example, the extracorporeal blood filtering system **1200** includes one or more density sensors **1282**, **1284**, **1286**, **1288**. One of ordinary skill in the art will appreciate the extracorporeal blood filtering system **1200** is not limited to the illustrated components of FIG. **12** and that any additional components illustrated and described in FIG. **12** can be added to other extracorporeal blood filtering machines or systems described elsewhere herein. In examples like the one shown in FIG. **12**, extracorporeal blood filtering systems can determine the density of fluids (e.g., source fluid, effluent) flowing within the system and use the determined density values to ensure optimal fluid balance. Determining fluid densities in the ways described herein can provide significant benefits as compared to simply assuming that the density of such fluids matches the density of water.

(120) The extracorporeal blood filtering system **1200** includes a blood circuit. The blood circuit includes a blood line with a blood inlet **1204** configured to receive blood from a patient and a blood

outlet **1218** configured to return the blood to the patient. The blood circuit also includes a filter **1216** fluidly connected to the blood line between the blood inlet **1204** and the blood outlet **1218** and a blood pump **1210** configured to pump the blood from the blood inlet **1204** to the blood outlet **1218** through the filter **1216** with the filter **1216** configured to remove waste from the blood.

(121) The extracorporeal blood filtering system **1200** also includes an effluent circuit. The effluent circuit includes an effluent line **1220** fluidly connected to the filter, with the effluent line configured to receive the waste from the filter **1216** in the form of effluent. The effluent circuit also includes an effluent pump **1224** configured to pump the effluent from the filter **1216**, through the effluent line **1220**, to an effluent receptacle **1226**. In some examples, the effluent circuit can also include an effluent scale **1246** configured to measure an effluent weight value of the effluent receptacle **1226**.

(122) In some examples, the extracorporeal blood filtering system **1200** includes a source fluid circuit. The source fluid circuit includes a source fluid line **1236** fluidly connected to a source fluid reservoir **1234** and to the blood circuit. The source fluid circuit also includes a source fluid pump **1238** configured to pump source fluid from the source fluid reservoir **1234**, through the source fluid line **1236**, into the blood circuit. In some such examples, the source fluid circuit can also include a source fluid scale **1248** configured to measure a source fluid weight value of the source fluid reservoir **1234**.

(123) In some embodiments, the extracorporeal blood filtering system **1200** includes a display **1244**. The display **1244** can be used to display information and/or to act as a user input and receive user inputs. For example, the display **1244** can be used to display information about the extracorporeal blood filtering system **1200** and/or used as a touch display configured to receive a user input in the form of touch.

(124) In some examples, the extracorporeal blood filtering system **1200** includes a user input device **1268** which is configured to receive a user input. The user input device **1268** can be separate from the extracorporeal blood filtering system **1200** or can be integrated into the extracorporeal blood filtering system **1200**. Some examples of a user input device **1268** can include a computer mouse, a keyboard, or a touch interface.

(125) In some embodiments, the extracorporeal blood filtering system **1200** includes one or more density sensors **1282**, **1284**, **1286**, **1288** each configured to measure a fluid density of a connected fluid line. In FIG. **12**, a first source fluid density sensor **1282** can be used to sample source fluid in the source fluid line **1236** between the source fluid reservoir **1234** and the filter **1216**. The first source fluid density sensor **1282** can be considered inline with the source fluid line **1236** as it is within the extracorporeal blood filtering machine **1202**, and the source fluid line **1236** runs through it.

(126) A second source fluid density sensor **1284** can also be used to sample source fluid between the source fluid reservoir and filter **1216**. However, the second source fluid density sensor **1284** can be considered offline from the source fluid line **1236** as it is outside of the extracorporeal blood filtering machine **1202** and the source fluid line **1236** need not run through it. In some examples, the source fluid line **1236** can run from the source fluid reservoir **1234**, through the second source fluid density sensor **1284**, and back into the source fluid pump **1238**. Additionally or alternatively, a different fluid line is connected between the source fluid reservoir **1234** and the second source fluid density sensor **1284**. In some embodiments, the second source fluid density sensor **1284** is part of a separate machine than the extracorporeal blood filtering machine **1202** and is housed in a separate housing. In some such embodiments, though, the second source fluid density sensor can be considered part of the extracorporeal blood filtering system **1200**. While two source fluid density sensors **1282**, **1284** are illustrated, the extracorporeal blood filtering system **1200** can include only one of the first source fluid density sensor **1282** or the second source fluid density sensor **1284**. In some embodiments, no source fluid density sensor is included in the extracorporeal blood filtering system.

(127) Continuing with FIG. 12, the extracorporeal blood filtering system **1200** includes a first effluent density sensor **1286**, which can be used to sample effluent in the effluent line **1220** between the filter **1216** and the effluent receptacle **1226**. The first effluent density sensor **1286** can be considered inline with the effluent line **1220** as it is within the extracorporeal blood filtering machine **1202**, and the effluent line **1220** runs through it.

(128) A second effluent density sensor **1288** can also be used to sample effluent between the filter **1216** and the effluent receptacle **1226**. However, the second effluent density sensor **1288** can be considered offline from the effluent line **1220** as it is outside of the extracorporeal blood filtering machine **1202**, and the effluent line **1220** need not run through it. In some examples, the effluent line **1220** can run from the filter **1216**, through the second effluent density sensor **1288**, and to the effluent receptacle **1226**. Additionally or alternatively, a different fluid line can be connected between the filter **1216** and the second effluent density sensor **1288**. In some embodiments, the second effluent density sensor **1288** is part of a separate machine than the extracorporeal blood filtering machine **1202** and is housed in a separate housing. In some such embodiments, though, the second effluent density sensor can be considered part of the extracorporeal blood filtering system **1200**. While two effluent density sensors **1286**, **1288** are illustrated, the extracorporeal blood filtering system **1200** can include only one of the first effluent density sensor **1286** or the second effluent density sensor **1288**. In some embodiments, no effluent density sensor is included in the extracorporeal blood filtering system.

(129) The extracorporeal blood filtering system **1200** further includes a controller **1249**, which can be in communication with various components within the extracorporeal blood filtering system **1200**. In FIG. 12, the controller **1249** is in communication with the effluent pump **1224**, the effluent scale **1246**, the source fluid pump **1238**, the source fluid scale **1248**, the display **1244**, the one or more density sensors **1282**, **1284**, **1286**, **1288**, and the user input device **1268**. The controller **1249** can also be in communication with further components of the extracorporeal blood machine (e.g., the blood pump **1210**).

(130) In one example operation, the controller **1249** is configured to determine a quantity (e.g., a volume) of effluent pumped through the effluent line **1220** into the effluent receptacle **1226** based on a determined effluent density value. The controller **1249** can be configured to receive the determined effluent density value in multiple ways. For instance, in some examples, the controller **1249** can receive the determined effluent density value from one of the first effluent density sensor **1286** or the second effluent density sensor **1288**. Additionally or alternatively, in some examples, the controller **1249** can receive the determined effluent density value from a user input such as from the user input device **1268** or the display **1244**. In some such examples, the controller **1249** can receive a user input that is indicative of the determined effluent density value output by an effluent density sensor (e.g., the second effluent density sensor **1288**). Thus, the controller **1249** can receive a determined effluent density value from an effluent density sensor which is offline from the extracorporeal blood filtering machine **1202**.

(131) In some examples, to determine the quantity (e.g., the volume) of effluent pumped through the effluent line **1220** into the effluent receptacle **1226**, the controller **1249** can receive a determined effluent density value and receive an effluent weight value from the effluent scale **1246**. The controller **1249** can then take the effluent weight value from the effluent scale **1246** and divide it by the determined effluent density value to determine a quantity of effluent in the effluent receptacle **1226**.

(132) The controller **1249** can also be configured to output a system control signal based on the determined quantity of effluent. The system control signal can include a signal to control one or more aspects of the extracorporeal blood filtering system **1200** such as the effluent pump **1224**.

(133) In a similar example operation, the controller **1249** is configured to determine a quantity (e.g., a volume) of source fluid pumped through the source fluid line **1236** from the source fluid reservoir **1234** based on a determined source fluid density value. The controller **1249** can be

configured to receive the determined source fluid density value in multiple ways. For instance, in some examples, the controller **1249** can receive the determined source fluid density value from one of the first source fluid density sensor **1282** or the second source fluid density sensor **1284**. Additionally or alternatively, in some examples, the controller **1249** can receive the determined source fluid density value from a user input such as from the user input device **1268** or the display **1244**. In some such examples, the controller **1249** can receive a user input that is indicative of the determined source fluid density value output by a source fluid density sensor (e.g., the second source fluid density sensor **1284**). Thus, the controller **1249** can receive a determined source fluid density value from a source fluid density sensor that is offline from the extracorporeal blood filtering machine **1202**.

(134) In some examples, to determine the quantity of source fluid pumped through the source fluid line **1236** from the source fluid reservoir **1234**, the controller **1249** can receive a determined source fluid density value and receive a source fluid weight value from the source fluid scale **1248**. The controller **1249** can then take the source fluid weight value from the source fluid scale **1248** and divide it by the determined source fluid density value to determine a quantity of source fluid pumped from the source fluid reservoir **1234**.

(135) The controller **1249** can also be configured to output a system control signal based on the determined quantity of source fluid. The system control signal can include a signal to control one or more aspects of the extracorporeal blood filtering system **1200** such as the source fluid pump **1238**.

(136) In some examples, the controller **1249** is configured to determine both the quantity (e.g., volume) of effluent pumped through the effluent line **1220** and the quantity (e.g., volume) of source fluid pumped through the source fluid line **1236**. In some such examples, the controller **1249** can use an effluent density sensor **1286** that is inline with the effluent line **1220** and use a source fluid density sensor **1284** that is offline from the source fluid line **1236**. Alternatively, in some examples, the controller **1249** can use an effluent density sensor **1288** that is offline from the effluent line **1220** and a source fluid density sensor **1282** that is inline with the source fluid line **1236**. Other combinations of an effluent density sensor being inline/offline and a source fluid density sensor being offline/inline are also contemplated.

(137) The extracorporeal blood filtering system **1200** of FIG. **12** can be operated in a priming operation and a standard operation. A priming operation is used to flush air from the blood line by using a fluid (e.g., saline) within the blood line. The priming operation is usually performed once before a standard operation. During the priming operation, the source fluid pump **1238** is configured to pump priming fluid from a priming fluid reservoir through the source fluid line. Additionally, during the priming operation, the source fluid scale **1248** is configured to measure a priming fluid weight value of the priming fluid reservoir. In some examples, the priming fluid reservoir is the source fluid reservoir **1234**, however in some examples, the priming fluid reservoir is a separate reservoir. During the standard operation, the source fluid pump **1238** is configured to pump source fluid from the source fluid reservoir **1234** through the source line into the blood circuit. Additionally, during the standard operation, the source fluid scale **1248** is configured to measure a source fluid weight value of the source fluid reservoir **1234**.

(138) The controller **1249** can control aspects of the extracorporeal blood filtering system **1200** during both the priming operation and the standard operation. For example, the controller **1249** is configured to determine a source fluid pump rate during the priming operation based on the priming fluid weight value and known priming fluid density value. The priming fluid density value can be known beforehand as a user can input the priming fluid density into a user input, which the controller **1249** can then receive. The controller **1249** can also be configured to determine the determined source fluid density value during standard operation based on the source fluid weight value and the source fluid pump rate. Thus, the extracorporeal blood filtering system **1200** can be primed with a known density liquid, and the controller **1249** can determine a source fluid pump rate

and subsequently determine a source fluid density due to the known source fluid pump rate and the source fluid weight value.

(139) In some examples, the controller **1249** is further configured to determine an effluent pump rate, such as that of effluent pump **1224**, during the priming operation. In some such examples, the effluent pump rate can be based on an effluent weight value measured by the effluent scale **1246** and the known priming fluid density value. To obtain the effluent pump rate, a user can configure the extracorporeal blood filtering system **1200** such that the priming fluid is pumped through the effluent pump **1224** and is weighed by the effluent scale **1246**. The controller **1249** can be configured to determine the determined effluent density value during standard operation based on the effluent weight value and the effluent pump rate. Thus, the extracorporeal blood filtering system **1200** can be primed with a known density liquid, and the controller **1249** can determine an effluent pump rate and subsequently determine an effluent density due to the known effluent pump rate and the effluent weight value.

(140) Moving to FIG. **13**, FIG. **13** is flowchart of an example operation of the extracorporeal blood filtering system **1200** of FIG. **12** according to an aspect of the present disclosure. The method starts at step **1300** with providing an extracorporeal blood filtering system. As discussed in connection with FIG. **11**, the extracorporeal blood filtering machine includes a blood circuit. The blood circuit includes a blood line with a blood inlet configured to receive blood from a patient and a blood outlet configured to return the blood to the patient. The blood circuit also includes a filter fluidly connected to the blood line between the blood inlet and the blood outlet and a blood pump. The extracorporeal blood filtering system also includes an effluent circuit, which comprises an effluent line fluidly connected to the filter and an effluent pump. In some examples, the extracorporeal blood filtering system further includes a source fluid circuit, which comprises a source fluid line fluidly connected to a source fluid reservoir and to the blood circuit along with a source fluid pump. In some examples, the extracorporeal blood filtering system includes one or more density sensors such as an effluent density sensor and a source fluid density sensor. In some examples, the extracorporeal blood filtering machine includes an effluent scale and a source fluid scale.

(141) The method continues at step **1302** with operating the blood pump to pump blood received from a patient at the blood inlet through the filter and back to the patient at the blood outlet, with the filter removing waste from the blood and providing the waste to the effluent line in the form of effluent. Next, in step **1304**, the method continues with determining an effluent density value of the effluent and a source fluid density value of the source fluid. In some examples, the step of determining the effluent density value of the effluent and determining the source fluid density value of the source fluid comprises measuring the effluent density value with an effluent density sensor and measuring the source fluid density value with a source fluid density sensor as in step **1310**. In some such examples, the effluent density sensor and the source fluid density sensor can be inline with the effluent line and source fluid line respectively. Alternatively, in some such examples, the effluent density sensor and the source fluid density sensor can be offline from the effluent line and source fluid line respectively. In some examples, the effluent density sensor is inline, while the source fluid density sensor is offline. In some examples, the effluent density sensor is offline, while the source fluid density sensor is inline. In some embodiments where the effluent density sensor and/or the source fluid density sensor are offline, determining the effluent density value of the effluent and/or the source fluid density value of the source fluid can include receiving user input. For example, at step **1312**, the method includes receiving a first user input indicative of the effluent density value output by the effluent density sensor and receiving a second user input indicative of the source fluid density value output by the source fluid density sensor.

(142) Based on the determined effluent density value, the method can continue with determining a quantity (e.g., a volume) of effluent pumped through the effluent line into the effluent receptacle at step **1306**. In some examples, determining the quantity of effluent pumped can include measuring an effluent weight value of the effluent receptacle with the effluent scale as in step **1314**. Then,

determining the quantity of effluent pumped is based on the determined effluent density value and the effluent weight value.

(143) Additionally, based on the determined source fluid density value, the method can continue with determining a quantity (e.g., a volume) of source fluid pumped through the source fluid line from the source fluid reservoir at step **1308**. In some examples, determining the quantity of source fluid pumped can include measuring a source fluid weight value of the source fluid reservoir with the source fluid scale as in step **1316**. Then, determining the quantity of source fluid pumped is based on the determined source fluid density value and the source fluid weight value.

(144) After determining the quantity of effluent and source fluid pumped, the method continues at step **1310** with outputting a system control signal based on the determined quantity of effluent and source fluid pumped.

(145) Optionally, the method can further continue at step **1318** with operating the source fluid pump to pump a priming fluid from a priming fluid reservoir through the source fluid line during a priming operation. The method further continues with using the source fluid scale to measure a priming fluid weight value of the priming fluid reservoir during the priming operation at step **1320**. Next, in step **1322**, the method includes determining a source fluid pump rate during the priming operation based on the priming fluid weight value and a known priming fluid density value. Once the source fluid pump rate is determined, the method can continue with operating the source fluid pump in a standard operation and then using the source fluid scale to measure a source fluid weight value of the source fluid reservoir during the standard operation at step **1324**. Lastly, in step **1326**, the method includes determining the source fluid density value during standard operation based on the source fluid weight value and the source fluid pump rate. A similar method can be employed to determine an effluent pump rate during the priming operation and determining the effluent density value during standard operation based on an effluent weight value and the effluent pump rate.

(146) While the steps of FIG. **13** may be illustrated and discussed in a particular order, it will be appreciated that the steps of FIG. **13** need not be performed in the illustrated or described order. For instance, in some examples, method steps illustrated as occurring after other methods steps can, in actuality, occur before the other method steps. Further, some steps can be performed substantially simultaneously as other steps, while some steps can be performed any amount of time after other steps. Moreover, while some steps are illustrated with dotted lines to indicate they are optional, in some examples, steps illustrated with solid lines can also be optional.

(147) Now referencing FIGS. **14-19C**, FIGS. **14-19C** include various views of an apparatus **1400** for hanging a medical fluid container **1402**. FIG. **14** is a perspective view of an example apparatus **1400** for hanging the medical fluid container **1402** and a perspective view of a portion of the medical fluid container **1402**. FIG. **15** is a perspective view of just the rail assembly **1416** of FIG. **14**. FIG. **16** is a perspective view of just the hanger **1404** of FIG. **14**. FIG. **17** is a front perspective view of the example apparatus **1400** of FIG. **14** with a hanger **1404** being slightly translated on the apparatus **1400**. FIGS. **18A-18B** are front perspective views of the example hanger of FIG. **14** illustrating the example apparatus **1400** being rotated about an axis. FIGS. **19A-19C** are side perspective views of the example apparatus **1400** of FIG. **14** illustrating the example apparatus **1400** being rotated about another axis. In preferred embodiments, an apparatus for hanging a medical fluid container will enable the medical fluid container to self-align with a weight scale (e.g., by permitting the medical fluid container to pivot about one or more horizontal axes and by preventing rotation of the medical fluid container about a vertical axis, which can cause the medical fluid container to become tangled and prevent self-alignment).

(148) In the illustrated embodiments, the hanger **1404** of the apparatus **1400** is configured to hang the medical fluid container **1402**, which in some examples, can include a medical fluid bag (e.g., saline bag). To hold the medical fluid container **1402**, the hanger **1404** includes one or more hooks **1406a**, **1406b**, **1406c** configured to engage one or more holes **1408** of the medical fluid container **1402**. In some embodiments, the hanger **1404** includes three hooks, which comprise a first hook

1406a, a second hook **1406b**, and a third hook **1406c**. The first hook **1406a** can be spaced apart from the second hook **1406b** by approximately 3 inches, and the second hook **1406b** can be spaced apart from the third hook **1406c** by approximately 3 inches. As illustrated in FIG. 17, the first hook **1406a**, the second hook **1406b**, and the third hook **1406c** can be aligned along a horizontal axis **1409**. In some embodiments, such as in FIG. 14, the medical fluid container **1402** includes three or more holes **1408**. In some such embodiments, three of the three or more holes **1408** are secured to the three hooks **1406a**, **1406b**, **1406c**, while other holes remain unsecured and/or are doubled up on the same hooks.

(149) In addition to the hanger **1404**, the apparatus **1400** includes a bracket **1412** configured to attach to an extracorporeal blood filtering machine (e.g., extracorporeal blood filtering machine **1202**). The bracket **1412** can include a mount **1414**, which includes one or more fasteners (e.g., screws, clips) to secure the bracket **1412**, and the overall apparatus **1400**, to the extracorporeal blood filtering machine.

(150) The bracket **1412** is also configured to removably connect the hanger **1404** to the extracorporeal blood filtering machine. For example, the bracket **1412** comprises a rail assembly **1416** with a rail **1418** onto which the attachment member **1410** of the hanger **1404** secures. In general, the hanger **1404** can connect with the bracket **1412**. More specifically, the attachment member **1410** of the hanger **1404** is configured to fit into the rail **1418** and slide along the rail **1418** to connect with the rail **1418** of the bracket **1412**.

(151) As illustrated in FIG. 17, the rail **1418** of the rail assembly **1416** includes an inlet **1420** configured to receive the hanger **1404**. The attachment member **1410** of the hanger **1404** can insert into the inlet **1420** and slide along the rail **1418**. The bracket **1412** further includes a seat **1422**, with the seat **1422** being on one end of the bracket **1412** and the inlet **1420** being on an opposite end of the bracket **1412**. The seat **1422** extends lower on the bracket **1412** than the inlet **1420**, which can enable the attachment member **1410** of the hanger **1404** to slide along the rail **1418** to the seat **1422** and to be seated in the seat **1422**. In some examples, the rail **1418** can form a declined angle with the horizontal, which can aid in the attachment member **1410** sliding to the seat **1422**.

(152) Now referencing FIG. 15, the bracket **1412**, and specifically the rail assembly **1416**, can comprise two sides. Each of the two sides can be approximately the same shape and include many of the same features. In general, each side of the bracket **1412** is configured to enable the hanger **1404** to connect to the bracket **1412**. In some examples, the two sides are bonded together to produce the bracket **1412**.

(153) Starting with the seat **1422**, the seat **1422** can comprise a first seat **1423** (e.g., on a first side) and a second seat **1425** (e.g., on a second side) separated by a center wall **1428**. Continuing with the rail **1418**, the rail **1418** can include a first rail side **1424** and a second rail side **1426** that are separated by the center wall **1428**. The first rail side **1424** can extend between the inlet **1420** and the first seat **1423**, while the second rail side **1426** can extend between the inlet **1420** and the second seat **1425**. The first rail side **1424** can comprise a first lower wall **1430**, while the second rail side **1426** can comprise a second lower wall **1432**.

(154) Now referencing both FIG. 15 and FIG. 17, the inlet **1420** of the rail **1418** can include a lip **1434** extending from the first lower wall **1430** and the second lower wall **1432**. The lip **1434** can be angled upward from the first lower wall **1430** and the second lower wall **1432** and can be used to guide the attachment member **1410** to secure the attachment member **1410** to the rail **1418**. In some embodiments, the lip **1434** can include a tip **1436** and a base **1438** with the tip **1436** being narrower than the base **1438**. This can help in aligning the hanger **1404** with the lip **1434**.

(155) Referencing FIG. 16, the hanger **1404**, and specifically the attachment member **1410**, can also comprise two sides. Each of the two sides can be approximately the same shape and include many of the same features. The two sides can be used to enable the attachment member **1410** to connect to the bracket **1412**. The attachment member **1410** can comprise a first attachment member **1440** (e.g., on a first side) and a second attachment member **1442** (e.g., on a second side). The first

attachment member **1440** is configured to slide along the first rail side of the bracket **1412**, contact the first lower wall of the bracket **1412** while sliding, and settle (e.g., be seated) in the first seat. The second attachment member **1442** is configured to slide along the second rail side of the bracket **1412**, contact the second lower wall of the bracket **1412** while sliding, and settle (e.g., be seated) in the second seat.

(156) The attachment member **1410** includes a first side wall **1444** on one side and a second side wall **1446** on the other side. The first side wall **1444** can be positioned near the first rail side **1424** when the attachment member **1410** is sliding along the rail **1418**. Additionally, the second side wall **1446** can be positioned near the second rail side **1426** when the attachment member **1410** is sliding along the rail **1418**.

(157) The attachment member **1410** also includes a first protrusion **1448** extending from the first side wall **1444** toward the second side wall **1446** and a second protrusion **1450** extending from the second side wall **1446** toward the first side wall **1444**. The first protrusion **1448** can be configured to contact the first lower wall **1430** of the rail **1418** to enable the attachment member **1410** to slide along the first rail side **1424**. Additionally, the second protrusion **1450** can be configured to contact the second lower wall **1432** of the rail **1418** to enable the attachment member **1410** to slide along the second rail side **1426**. In some embodiments, the first protrusion **1448** includes a first bearing configured to roll along the first lower wall **1430** and the second protrusion **1450** includes a second bearing configured to roll along the second lower wall **1432**. The bearings can reduce the friction between the protrusions **1448**, **1450** and the lower walls **1430**, **1432** of the rail **1418**, enabling smoother movement.

(158) In some embodiments, the lip **1434** of the rail **1418** is configured to contact the first side wall **1444** and the second side wall **1446** of the attachment member **1410** to guide the first protrusion **1448** into contact with the first lower wall **1430** and to guide the second protrusion **1450** into contact with the second lower wall **1432**. In some examples, the tip **1436** of the lip **1434** is narrower than the base **1438** to align the first side wall **1444** and the second side wall **1446** of the attachment member **1410** as the attachment member **1410** is fitted into the inlet **1420** of the rail **1418**.

(159) Now referencing FIGS. **18A-18B** and FIGS. **19A-19C**, the hanger **1404** is configured to align the medical fluid container **1402** with a scale (e.g., **1248** of FIG. **12**) of the extracorporeal blood filtering machine when the attachment member **1410** is fit into the inlet **1420** of the rail **1418**. In some examples, the hanger **1404** is configured to align the medical fluid container **1402** with the scale by hanging the medical fluid container **1402** directly under, and vertically in line with, the scale. This can ensure the scale receives an accurate reading when it weighs the medical fluid container as the weight is pulling directly downward without tilting in a direction.

(160) In the illustrated embodiments, the hanger **1404** and the bracket **1412** are configured to permit the medical fluid container **1402** to pivot about a first horizontal axis **1452** and a second horizontal axis **1454** that differs from the first horizontal axis **1452**. This pivoting can enable the medical fluid container **1402** to hang directly under, and vertically in line with, the scale as the hanger **1404** and medical fluid container **1402** can pivot relative to the extracorporeal blood filtering device. In this way, the medical fluid container **1402** can self-align with the scale. While the hanger **1404** and the bracket **1412** are configured to permit the medical fluid container **1402** to pivot about the first horizontal axis **1452** and a second horizontal axis **1454**, the hanger **1404** and the bracket **1412** can prevent the medical fluid container **1402** from pivoting about a vertical axis **1456**. Pivoting about the vertical axis is illustrated by the arrow in FIG. **19C**. Pivoting about a vertical axis **1456** can be disadvantageous as such rotation can, for example, cause the medical fluid container to contact other devices, tubing, sensor contacts or the like, which can result in misalignment and/or erroneous weight scale measurements.

(161) In FIGS. **18A-18B**, even though the first horizontal axis **1452** is illustrated, the hanger **1404** pivots about the second horizontal axis **1454**, which is illustrated in FIGS. **19A-19C**. The second

horizontal axis **1454**, is illustrated in FIG. **18A/B**, would go into the page at the center point of the protrusions **1448**, **1450** of the hanger **1404**. The hanger **1404**, when the attachment member **1410** is seated in the seat **1422**, is configured to pivot relative to the rail assembly **1416** of the bracket **1412** about the second horizontal axis **1454**. This pivot of the hanger **1404** is illustrated in FIG. **18B** and by the arrow found in FIG. **19A**. While the hanger **1404** is only illustrated as pivoting such that a right side of the hanger is raised higher relative to the left side of the hanger, the hanger **1404** can pivot in the other direction. In some examples, though, pivoting the hanger **1404** such that the left side raises and the right side lowers, can result in the hanger **1404** sliding out of the seat **1422** and toward the inlet **1420**. However, in some such examples, the raised lip **1434** can prevent the hanger **1404** from completely sliding off of the bracket **1412**.

(162) In FIGS. **19A-19C**, even though the second horizontal axis **1454** is illustrated, the rail assembly **1416** pivots about the first horizontal axis **1452**, which is illustrated in FIGS. **18A-18B**. The first horizontal axis **1452**, if illustrated in FIGS. **19A-19C**, would go into the page at the center point of the rail assembly's **1416** connection to the mount **1414**. The rail assembly **1416** is configured to pivot relative to the mount **1414** about the first horizontal axis **1452**. This pivot is illustrated in FIGS. **19B-19C**, and by the arrow found in FIGS. **18A-18B**.

(163) The ability of the hanger **1404** to pivot relative to the rail assembly **1416**, along with ability of the rail assembly **1416** to pivot relative to the mount **1414**, enables the hanger **1404** and the attached medical fluid container **1402** to stay directly under the mount **1414**. Because the mount **1414** is attached to the extracorporeal blood filtering machine, and can be specifically attached to a scale, the hanger **1404** and the attached medical fluid container **1402** can be aligned (e.g., directly under and vertically in line) with the scale.

(164) Moving to FIG. **20**, FIG. **20** is a flowchart of an example operation of the apparatus **1400** of FIG. **14** according to an aspect of the present disclosure. The method starts at step **2000** with providing an extracorporeal blood filtering machine that includes a scale and a bracket having a rail and an inlet. The method also includes providing a hanger that includes one or more hooks and an attachment member as in step **2002**. The method further includes providing a medical fluid container having one or more holes as in step **2004**. Next, the method includes aligning the medical fluid container with the scale of the extracorporeal blood filtering as in step **2006**. The aligning step can itself include the steps of **2008** through **2012**. In step **2008**, the method includes engaging the one or more holes of the medical fluid container with the one or more hooks of the hanger to hang the medical fluid container onto the hanger. Next, in step **2010**, the method includes fitting the attachment member into the inlet of the rail. Further, in step **2012**, the method includes sliding the attachment member along the rail into alignment. In some embodiments, aligning the medical fluid container with the scale of the extracorporeal blood filtering machine comprises hanging the medical fluid container directly under and vertically in line with the scale.

(165) While the steps of FIG. **20** may be illustrated and discussed in a particular order, it will be appreciated that the steps of FIG. **20** need not be performed in the illustrated or described order. For instance, in some examples, method steps illustrated as occurring after other methods steps can, in actuality, occur before the other method steps. Further, some steps can be performed substantially simultaneously as other steps, while some steps can be performed any amount of time after other steps. Moreover, while some steps are illustrated with dotted lines to indicate they are optional, in some examples, steps illustrated with solid lines can also be optional.

(166) Now referencing FIGS. **21-24**, FIGS. **21-24** are views of an alternate apparatus **2100** for hanging a medical fluid container (e.g., **1402** of FIG. **14**) according to aspects of the present disclosure. FIG. **21** is a perspective view of the apparatus **2100** for hanging a medical fluid container. FIGS. **22A-22C** are side perspective views of the apparatus of FIG. **21** illustrating the example apparatus being rotated about an axis. FIG. **23** is a front perspective view of the apparatus of FIG. **21**, with a hanger being slightly translated on the apparatus **2100**. FIG. **24** is a front sectional view of the apparatus of FIG. **21**.

(167) The apparatus **2100** includes a hanger **2104** configured to hang a medical fluid container (e.g., **1402** of FIG. **14**). The hanger **2104** includes one or more hooks **2106a**, **2106b**, **2106c**, which are configured to engage one or more holes (e.g., **1408**) in the medical fluid container (e.g., **1402**). The hanger **2104** also includes an attachment member **2110**.

(168) The apparatus **2100** further includes a bracket **2112** configured to attach to an extracorporeal blood filtering machine. The bracket **2112** can include a mount **1414**, which is used to secure to the extracorporeal blood filtering machine. The bracket **2112** also includes a rail **2118** with an inlet **2120**, with the attachment member **2110** of the hanger **2104** configured to fit into the inlet **2120** of the rail **2118** and slide along the rail **2118**. In this configuration, the hanger **2104** is configured to align the medical fluid container with a scale of the extracorporeal blood filtering machine when the attachment member **2110** is fit into the inlet **2120** of the rail **2118**.

(169) The bracket **2112** can also define an attachment member opening **2158** with a bottom of the attachment member opening **2158** being defined by the rail **2118**. The attachment member **2110** can be inserted into the attachment member opening **2158** and slidable contact the rail **2118**. When the attachment member **2110** is inserted into the attachment member opening **2158**, the one or more hooks **2106a**, **2106b**, **2106c** of the hanger **2104** protrude downward through the attachment member opening **2158**. As illustrated in FIGS. **22A-22C**, the attachment member opening **2158** includes space on either side of the one or more hooks **2106a**, **2106b**, **2106c**. This configuration can enable the hanger **2104**, which includes the attachment member **2110**, to pivot relative to the bracket **2112** about a first axis. Further, the attachment member **2110** can be configured to slide along the rail on a second axis, as illustrated in FIG. **23**. The ability of the hanger to pivot relative to the bracket and to further slide along the rail can keep a medical fluid container hooked on the hanger to remain under a scale of an extracorporeal blood filtering machine. This can help maintain the accuracy of the scale despite the extracorporeal blood filtering machine being on an incline, for example.

(170) Now referencing FIG. **24**, the bracket **2112** can comprise a locking mechanism **2160** which is configured to prevent the attachment member **2110** from sliding relative to the bracket **2112** when the attachment member **2110** is in a first position. The first position is illustrated in FIG. **24** and comprises the attachment member **2110** being fully inserted into the attachment member opening **2158**. The locking mechanism **2160** includes a portion of the bracket **2112** and a portion of the attachment member **2110**. The bracket **2112** comprises a protruding member **2162** at an opposite end while the attachment member **2110** comprises a detent **2164** at an attachment member end. The protruding member **2162** is configured to insert into the detent **2164** and prevent the attachment member **2110** from sliding within the attachment member opening **2158**. However, because the protruding member **2162** can comprise a bearing, and because the detent **2164** can extend slightly around a circumference of the attachment member **2110**, the locking mechanism **2160** does not prevent the attachment member **2110** from pivoting relative to the bracket **2112** about a first axis.

(171) Moving to FIG. **25**, FIG. **25** is a front view of an example medical fluid container **2500** according to an aspect of the present disclosure. In operation, the medical fluid container **2500** is configured to receive a fluid and to subsequently empty the fluid automatically once the fluid reaches a specific level (e.g., full). In some examples, the received fluid is effluent, such as the effluent generated from filtering blood as described elsewhere herein.

(172) The medical fluid container **2500** has a top **2502**, a bottom **2504**, and two sides **2506**, **2508**. The medical fluid container **2500** includes a primary chamber **2510** configured to hold a fluid and a secondary chamber **2512**, in fluid communication with the primary chamber **2510**, which is also configured to hold the fluid. The secondary chamber **2512** is partially separated from the primary chamber **2510** by a first wall **2514** that extends from the top **2502** of the medical fluid container to an empty-level **2516** near the bottom **2504** of the medical fluid container. As illustrated, the primary chamber **2510** is larger than the secondary chamber **2512**. In some embodiments, the secondary chamber **2512** is the same size as or larger than the primary chamber **2510**.

(173) The medical fluid container **2500** further includes a discharge chamber **2518** in fluid communication with the secondary chamber **2512**. The discharge chamber **2518** is partially separated from the secondary chamber **2512** by a second wall **2520** that extends from the bottom **2504** of the medical fluid container **2500** to a full-level **2522** near the top **2502** of the medical fluid container **2500**. In the illustrated embodiment, the discharge chamber **2518** is formed by the second wall **2520** and the right side **2508** exterior wall of the medical fluid container **2500**. In some embodiments, the discharge chamber **2518** is formed by the second wall **2520** and another interior wall (e.g., a third wall), or an alternate exterior wall (e.g., left side **2506** wall).

(174) The medical fluid container **2500** can be made of one or more materials. In some examples, the medical fluid container **2500** is made from a single material. For instance, in some examples, the primary chamber **2510**, the secondary chamber **2512**, the discharge chamber **2518**, the first wall **2514**, and the second wall **2520** are all formed of the same material. However, in some examples, the medical fluid container **2500** is made from multiple materials.

(175) Continuing with FIG. **25**, the medical fluid container **2500** can define a series of holes **2524**, which can be used to hang the medical fluid container **2500**. For instance, in some examples, the apparatus described with respect to FIGS. **14-19C** can be used to hang the medical fluid container **2500** by using its one or more hooks to engage the series of holes **2524**. The medical fluid container **2500** can further define one or more corner holes **2526**, which can also be used to hang the medical fluid container **2500**.

(176) To fill/add fluid, the medical fluid container **2500** includes a fill port **2528**. The fill port **2528** is fluidly connected to the primary chamber **2510** and is configured to receive a fluid in order for the fluid to reach the primary chamber **2510**. In some examples, the fill port **2528** engages with tubing to receive fluid. In some embodiments, the medical fluid container includes integrated tubing that is in fluid communication with the fill port **2528** to receive fluid.

(177) To drain/remove fluid, the medical fluid container **2500** includes a first drain port **2530** and a second drain port **2532**. The first drain port **2530** is in fluid communication with the discharge chamber **2518** and leads to a first drain valve **2534**. Thus, the first drain valve **2534** is also in fluid communication with the discharge chamber **2518**. The first drain port **2530** and the first drain valve **2534** can be located proximate the bottom **2504** of the medical fluid container **2500**. The first drain valve **2534** is configured to control emptying/draining of any fluid within the discharge chamber **2518** and can be in an open or closed position.

(178) Similarly, the second drain port **2532** is in fluid communication with the primary chamber **2510** and leads to a second drain valve **2536**. Thus, the second drain valve **2536** is also in fluid communication with the primary chamber **2510**. The second drain port **2532** and the second drain valve **2536** can also be located proximate the bottom **2504** of the medical fluid container **2500**. The second drain valve **2536** is configured to control emptying of any fluid within the primary chamber **2510** and by extension, any fluid within the secondary chamber **2512** as the secondary chamber **2512** is in fluid communication with the primary chamber **2510**. The second drain valve **2536** can be in an open or closed position. While the illustrated embodiment of FIG. **25** includes a second drain port **2532** and second drain valve **2536**, in some embodiments, the medical fluid container only includes the first drain port **2530** and the first drain valve **2534**, and in some embodiments, the medical fluid container includes multiple drain ports and drain valves.

(179) In an example operation of the medical fluid container **2500**, fluid is received by the medical fluid container **2500** via the fill port **2528** and stored in the primary chamber **2510** and the secondary chamber **2512**. As more fluid is received and stored in the primary chamber **2510** and the secondary chamber **2512**, the fluid level (e.g., **2538**) within the primary chamber **2510** and the secondary chamber **2512** rises accordingly. However, once the fluid level rises above the full-level **2522** of the second wall **2520**, fluid within the primary chamber **2510** and the secondary chamber **2512** empties into the discharge chamber **2518**. As fluid continues to flow into the discharge chamber **2518**, a siphoning effect is created, which causes fluid in the primary chamber **2510** and

the secondary chamber **2512** to continue to empty until the fluid level drops to the empty-level **2516** of the first wall **2514**. With the first drain valve **2534** open, fluid empties from the discharge chamber **2518** out through the first drain valve **2534**. In some examples, in order to have fluid in the primary chamber **2510** and the secondary chamber **2512** empty until the fluid level drops to the empty-level **2516** of the first wall **2514**, the first drain valve **2534** must be open or the discharge chamber **2518** needs to be sufficiently large to hold such a volume of fluid. Additionally, fluid held by the primary chamber **2510** and the secondary chamber **2512**, but which has a fluid level at or below the empty-level **2516** of the first wall **2514**, can be emptied from the primary chamber **2510** and the secondary chamber **2512** via the second drain valve **2536**. In this way, the second drain valve **2536** can drain fluid that does not empty through the discharge chamber **2518**.

(180) Moving to FIG. **26**, FIG. **26** is a flowchart of an example method involving the medical fluid container of FIG. **25** according to an aspect of the present disclosure. The method starts at step **2600** with providing a medical fluid container that comprises a primary chamber, a secondary chamber, and a discharge chamber. The secondary chamber is in fluid communication with the primary chamber and is partially separated from the primary chamber by a first wall that extends from a top of the medical fluid container to an empty-level near a bottom of the medical container. The discharge chamber is in fluid communication with the secondary chamber and is partially separated from the secondary chamber by a second wall that extends from the bottom of the medical fluid container to a full-level near the top of the medical fluid container.

(181) The method continues with adding fluid (e.g., effluent) to the primary and secondary chambers in step **2602**. In some examples, adding fluid to the primary and secondary chambers comprises adding fluid via a fill port which is located in one of the primary or secondary chambers. Fluid can fill both the primary and secondary chambers simultaneously as they are in fluid communication with each other.

(182) Next, in step **2604**, the method includes automatically emptying the fluid within the primary chamber and the secondary chamber through the discharge chamber. Automatically emptying the fluid occurs when fluid in the primary chamber and the secondary chamber rises above the full-level of the second wall. The automatically emptying the fluid can continue until the fluid in the primary chamber and the secondary chamber drops to the empty-level of the first wall.

(183) In some embodiments, the method also includes the step **2606**, which comprises controlling the emptying of the fluid through the discharge chamber. In some such embodiments, the medical fluid container can include a drain valve in fluid communication with the discharge chamber that is used to control the emptying of the fluid through the discharge chamber. The drain valve in fluid communication with the discharge chamber can be considered a first drain valve. In many instances, the drain valve can be in an open position during operation so that fluid automatically drains from the discharge chamber.

(184) Additionally, in some embodiments, the method includes step **2608**. Step **2608** comprises draining the primary chamber and the secondary chamber. To drain the primary chamber and the secondary chamber, the medical fluid container can include a drain valve in fluid communication with the primary chamber. The drain valve in fluid communication with the primary chamber can be considered a second drain valve. In some embodiments, the second drain valve can be used to drain the fluid from the primary chamber and the secondary chamber that does not empty through the discharge chamber. In many instances, this second drain valve can be in a closed position during operation so that fluid does not drain automatically from the primary chamber or the secondary chamber.

(185) While the steps of FIG. **26** may be illustrated and discussed in a particular order, it will be appreciated that the steps of FIG. **26** need not be performed in the illustrated or described order. For instance, in some examples, method steps illustrated as occurring after other methods steps can, in actuality, occur before the other method steps. Further, some steps can be performed substantially simultaneously as other steps, while some steps can be performed any amount of time after other

steps. Moreover, while some steps are illustrated with dotted lines to indicate they are optional, in some examples, steps illustrated with solid lines can also be optional.

(186) In the medical fluid container illustrated in FIG. 25 and the related method of FIG. 26, fluid is effectively siphoned from the primary chamber 2510 and the secondary chamber 2512 into the discharge chamber 2518 once it reaches the full level 2522 of the second wall 2520. The medical fluid container 2500 and its operation can be advantageous over other medical fluid containers for a variety of reasons. For instance, the medical fluid container can be used to receive effluent generated by an extracorporeal blood filtering machine and can automatically empty the effluent instead of a user replacing the medical fluid container with another, empty medical fluid container. Further, instead of simply draining the effluent, the medical fluid container can hold an amount of effluent before it automatically empties. This can be advantageous as the medical fluid container can be connected to a scale (e.g., effluent scale 246 of FIG. 2). In such examples, the scale can weigh the effluent in the medical fluid container while a controller (e.g., 249) can use the weight to adjust operation of the extracorporeal blood filtering machine as is described elsewhere herein. In contrast, if effluent is drained only via a drain, the weight of the effluent cannot be used to adjust the operation of an extracorporeal blood filtering machine.

(187) Moving to FIG. 27, FIG. 27 is a schematic view of an example extracorporeal blood filtering machine 2700 according to an aspect of the present disclosure. The extracorporeal blood filtering machine 2700 can include some or all of the features of the extracorporeal blood filtering machines described elsewhere herein (e.g., FIG. 2-6, 8, 10, 12). The extracorporeal blood filtering machine 2700 can also include features not previously described. For example, the extracorporeal blood filtering machine 2700 can include an effluent flow sensor 2746 (e.g., a weight scale), secondary effluent flow sensors 2790, 2792, a source fluid flow sensor 2748 (e.g., a weight scale), secondary source fluid flow sensors 2794, 2796, and a drain 2798. One of ordinary skill in the art will appreciate that the extracorporeal blood filtering machine 2700 of FIG. 27 is not limited to the illustrated components alone, as some components may be omitted for case of illustration.

(188) In the illustrated example of the extracorporeal blood filtering machine 2700 of FIG. 27, the extracorporeal blood filtering machine 2700 includes a blood circuit, an effluent circuit, and a source fluid circuit. As described elsewhere herein, the blood circuit can include a blood line having a blood inlet 2704 and a blood outlet 2718 along with a filter 2716 and a blood pump 2710. The effluent circuit can include an effluent line 2720 and an effluent pump 2724, which pumps effluent through the effluent line 2720 to an effluent receptacle 2726. In some examples, the effluent circuit can include one or more effluent flow sensors. The source fluid circuit can include a source fluid line 2736 and a source fluid pump 2738, which pumps source fluid from a source fluid reservoir 2734 through the source fluid line 2736. In some examples, the source fluid circuit can include one or more source fluid flow sensors. The extracorporeal blood filtering machine 2700 also includes a controller 2749 in communication with the blood pump 2710, the effluent pump 2724, and the source fluid pump 2738. The controller 2749 can also be in communication with other sensors of the extracorporeal blood filtering machine 2700 as discussed elsewhere herein. The controller 2749 can control various aspects of the extracorporeal blood filtering machine 2700, including the blood pump 2710, the effluent pump 2724, and the source fluid pump 2738. In some embodiments, the controller 2749 can control various aspects of the extracorporeal blood filtering machine 2700 in response to inputs (e.g., from user inputs, sensors, and the like). Additionally, the extracorporeal blood filtering machine 2700 includes a user input device 2768 and a display 2744 that are both in communication with the controller 2749. The user input device 2768 and/or the display 2744 can be configured to receive user input and provide the user input to the controller 2749. Additionally or alternatively, the display 2744 can receive output from the controller 2749 and display the output.

(189) The extracorporeal blood filtering machine 2700 of FIG. 27 also includes the effluent flow sensor 2746, which is configured to measure an effluent flow quantity (e.g., weight, volume). In

many examples, the effluent flow sensor **2746** comprises an effluent scale, which is configured to measure a dynamic effluent weight value of the effluent receptacle **2726**. In some such examples, the dynamic effluent weight value of the effluent receptacle **2726** is used with an estimated or determined density value of the effluent to determine a volume of effluent in the effluent receptacle **2726**.

(190) In some embodiments, the extracorporeal blood filtering machine **2700** includes one or more secondary effluent flow sensors **2790**, **2792** that are each configured to measure a secondary effluent flow quantity in the effluent line **2720** at a location different from the effluent flow sensor **2746**. The secondary effluent flow sensors **2790**, **2792** of FIG. 27 are in fluid communication with the effluent line **2720** and are configured to measure an effluent volume by measuring the fluid flow therethrough. While the secondary effluent flow sensor **2790** is illustrated as being before the effluent pump **2724**, and the secondary effluent flow sensor **2792** is illustrated as being located after the effluent pump **2724**, the secondary effluent flow sensor can be located anywhere along the effluent line **2720**. Preferably, though, the secondary effluent flow sensor is located along the effluent line at a location different from the effluent flow sensor.

(191) The extracorporeal blood filtering machine **2700** of FIG. 27 further includes the source fluid flow sensor **2748**, which is configured to measure a source fluid flow quantity (e.g., weight, volume). In some examples, the source fluid flow sensor **2748** comprises a source fluid scale, which is configured to measure a dynamic source fluid weight value of the source fluid reservoir **2734**. In some such examples, the dynamic source fluid weight value of the source fluid reservoir **2734** is used with an estimated or determined density value of the source fluid to determine a volume of source fluid in the source fluid reservoir **2734**.

(192) In some embodiments, the extracorporeal blood filtering machine **2700** includes one or more secondary source fluid flow sensors **2794**, **2796** that are each configured to measure a secondary source fluid flow quantity in the source fluid line **2736** at a location different from the source fluid flow sensor **2748**. The secondary source fluid flow sensors **2794**, **2796** of FIG. 27 are in fluid communication with the source fluid line **2736** and are configured to measure a source fluid volume by measuring the fluid flow therethrough. While the secondary source fluid flow sensor **2794** is illustrated as being before the source fluid pump **2738**, and the secondary source fluid flow sensor **2796** is illustrated as being located after the source fluid pump **2738**, the secondary source fluid flow sensor can be located anywhere along the source fluid line **2736**. Preferably, though, the secondary source fluid flow sensor is located along the source fluid line **2736** at a location different from the source fluid flow sensor.

(193) Moving to example operations of the extracorporeal blood filtering machine **2700**, the controller **2749** can be in communication with the blood pump **2710**, the effluent pump **2724**, and the effluent flow sensor **2746**. The controller **2749** can then be configured to operate the extracorporeal blood filtering machine **2700** in an open-loop mode or a closed-loop mode. In the open-loop mode, the controller **2749** can set the blood pump speed and the effluent pump speed at respective fixed speeds. In the closed-loop mode, the controller **2749** can adjust the effluent pump speed based on the effluent flow quantity measured by the effluent flow sensor **2746**. In some embodiments, the effluent receptacle **2726** comprises a drain (e.g., a sink or a toilet) when the controller **2749** is operating the extracorporeal blood filtering machine **2700** in the open-loop mode. Further, in some embodiments, the effluent receptacle **2726** comprises a bag (e.g., like the medical fluid receptacles described herein) when the controller **2749** is operating the extracorporeal blood filtering machine **2700** in the closed-loop mode.

(194) In extracorporeal blood filtering machine embodiments that include a source fluid circuit, the controller **2749** can be in further communication with the source fluid pump **2738** and a source fluid flow sensor **2748**. In such embodiments, when operating in the open-loop mode, the controller **2749** can set the source fluid pump speed at a fixed speed. Further, when operating in the closed-loop mode, the controller **2749** can adjust the source fluid pump speed based on the source fluid

flow quantity measured by the source fluid flow sensor **2748**.

(195) As discussed elsewhere herein, the extracorporeal blood filtering machine **2700** can include one or more secondary source fluid flow sensors **2794**, **2796** configured to measure a secondary source fluid flow quantity. In such embodiments, the controller **2749** can be in communication with the source fluid flow sensor **2748** and the secondary source fluid flow sensors **2794**, **2796**. The controller **2749** can then be configured to compare the secondary source fluid flow quantity with the source fluid flow quantity measured by the source fluid flow sensor **2748**. If a difference between the secondary source fluid flow quantity and the source fluid flow quantity exceeds a threshold, the controller **2749** can output a source fluid flow mismatch alert. In some examples, the difference can be considered a “first difference” and the threshold can be considered a “first threshold.” In some examples, the source fluid flow mismatch alert can be output to the user input device **2768** and/or the display **2744**.

(196) As discussed elsewhere herein, the extracorporeal blood filtering machine **2700** can include one or more secondary effluent flow sensors **2790**, **2792** configured to measure a secondary effluent flow quantity. In such embodiments, the controller **2749** can be in communication with the effluent flow sensor **2746** and the secondary effluent flow sensors **2790**, **2792**. The controller **2749** can then be configured to compare the secondary effluent flow quantity with the effluent flow quantity measured by the effluent flow sensor **2746**. If a difference between the secondary effluent flow quantity and the effluent flow quantity exceeds a threshold, the controller **2749** can output a flow mismatch alert. In some examples, the difference can be considered a “second difference” and the threshold can be considered a “second threshold.” In some examples, the flow mismatch alert can be output to the user input device **2768** and/or the display **2744**.

(197) In some embodiments, the controller **2749** is configured to switch between operating in the open-loop mode and the closed-loop mode based on a user input (e.g., via user input device **2768** or display **2744**). In some embodiments, the controller **2749** is configured to switch between operating in the open-loop mode and the closed-loop mode automatically. For instance, in some embodiments, the controller **2749** can receive a signal from a sensor (e.g., a movement sensor) to switch between operating in the open-loop mode and the closed-loop mode.

(198) Moving to FIG. **28**, FIG. **28** is an example method of operating the extracorporeal blood filtering machine of FIG. **27** according to an aspect of the present disclosure. Starting at step **2800**, the method includes providing an extracorporeal blood filtering machine. As described elsewhere herein, the extracorporeal blood filtering machine can include a blood circuit, an effluent circuit, an effluent flow sensor, and a controller.

(199) Next, at step **2802**, the method includes operating the extracorporeal blood filtering machine via the controller. Operating the extracorporeal blood filtering machine via the controller can include pumping blood with the blood pump at a blood pump speed from a patient, into the blood line through the blood inlet, through the filter, and back to the patient through the blood outlet. During operation, the filter can remove waste from the blood in the form of effluent and provide the effluent to the effluent line. Additionally, operating the extracorporeal blood filtering machine via the controller can include pumping the effluent with the effluent pump at an effluent pump speed from the filter, through the effluent line, into an effluent receptacle. In some examples, operating the extracorporeal blood filtering machine via the controller does not include operating the effluent pump.

(200) The illustrated method continues with steps **2804** and **2806**, which include measuring an effluent flow quantity with the effluent flow sensor (e.g., a dynamic effluent weight value from an effluent scale) and receiving an input at the controller to operate the extracorporeal blood filtering machine in an open-loop mode or in a closed-loop mode. In some embodiments, the controller receives an input from a user input device and/or a display.

(201) Next the method includes the decision **2808**. If the input received at the controller is to operate the extracorporeal blood filtering machine in the open-loop mode, the method includes

setting the blood pump speed and the effluent pump speed by the controller at respective fixed speeds at step **2810**. However, if the input received at the controller is to operate the extracorporeal blood filtering machine in the closed-loop mode, the method includes dynamically adjusting the effluent pump speed by the controller based on the effluent flow quantity at **2812**.

(202) In some examples, the effluent flow sensor comprises an effluent scale, and the method step **2804** includes dynamically measuring a weight value of the effluent receptacle. In some embodiments, the effluent receptacle comprises a drain when the controller is operating the extracorporeal blood filtering machine in the open-loop mode. In some embodiments, the effluent receptacle comprises a bag when the controller is operating the extracorporeal blood filtering machine in the closed-loop mode.

(203) In some optional embodiments, the extracorporeal blood filtering machine includes a secondary effluent flow sensor on the effluent line. In such embodiments, the method can further include steps **2814** and **2816**. Step **2814** includes taking a secondary effluent flow quantity measurement with the secondary effluent flow sensor. Step **2816** includes comparing the secondary effluent flow quantity measurement with the effluent flow quantity and outputting an effluent flow mismatch alert if a difference between the secondary effluent flow quantity measurement and the effluent flow quantity exceeds a threshold. While steps **2814** and **2816** are illustrated as occurring before the open-loop or closed-loop determination of step **2808**, they can occur at any time. For example, steps **2814** and **2816** can occur during an open-loop mode operation.

(204) Additionally, in some optional embodiments, the extracorporeal blood filtering machine includes a source fluid circuit and a source fluid flow sensor. In such embodiments, the operating the extracorporeal blood filtering machine of step **2802** further includes pumping source fluid with the source fluid pump at a source fluid pump speed from the source fluid reservoir, through the source fluid line, into the blood circuit. The method can also include step **2818**. Step **2818** includes measuring a source fluid flow quantity with the source fluid flow sensor. Referring back to the decision step **2808**, if the input received at the controller is to operate the extracorporeal blood filtering machine in the open-loop mode, the method can include setting the source fluid pump speed by the controller at a respective fixed speed as in step **2820**. However, if the input received at the controller is to operate the extracorporeal blood filtering machine in the closed-loop mode, the method can include dynamically adjusting the source fluid pump speed by the controller based on the source fluid flow quantity as in step **2822**. In both the open-loop mode and the closed-loop mode, the method can return to operating the extracorporeal blood filtering machine as in step **2802**.

(205) In some examples, the source fluid flow sensor comprises a source fluid scale and the method step **2812** includes dynamically measuring a weight value of the source fluid reservoir.

(206) In some optional embodiments, the extracorporeal blood filtering machine includes a secondary source fluid flow sensor on the source fluid line. In such embodiments, the method can further include steps **2824** and **2826**. Step **2824** includes taking a secondary source fluid flow quantity measurement with the secondary source fluid flow sensor. Step **2826** includes comparing the secondary source fluid flow quantity measurement with the source fluid flow quantity and outputting a source fluid flow mismatch alert if a difference between the secondary source fluid flow quantity measurement and the source fluid flow quantity exceeds a threshold. While steps **2824** and **2826** are illustrated as occurring before the open-loop or closed-loop determination of step **2808**, they can occur at any time. For example, steps **2824** and **2826** can occur during an open-loop mode operation. Again, in both the open-loop mode and the closed-loop mode, the method can return to operating the extracorporeal blood filtering machine as in step **2802**.

(207) The method can optionally return to step **2806** after operating in the open-loop mode or the closed-loop mode. In step **2806** the method can comprise receiving a second input at the controller to switch operations. For instance, if the extracorporeal blood filtering machine is operating in the open-loop mode and receives a second input to operate in the closed-loop mode, the method

continues with step **2812**. In such an example, the extracorporeal blood filtering machine can switch from holding the effluent pump speed at the fixed speed, to dynamically adjusting the effluent pump speed by the controller based on the effluent flow quantity. Alternatively, if the extracorporeal blood filtering machine is operating in the closed-loop mode and receives a second input to operate in the open-loop mode, the method continues with step **2810**. In such an example, the extracorporeal blood filtering machine can switch from dynamically adjusting the effluent pump speed by the controller based on the effluent flow quantity to holding the effluent pump speed at a fixed speed. The source fluid pump speed can similarly be switched to/from a fixed speed from/to dynamically adjusting its speed based on source fluid flow quantity.

(208) While the steps of FIG. **28** may be illustrated and discussed in a particular order, it will be appreciated that the steps of FIG. **28** need not be performed in the illustrated or described order. For instance, in some examples, method steps illustrated as occurring after other methods steps can, in actuality, occur before the other method steps. Further, some steps can be performed substantially simultaneously as other steps, while some steps can be performed any amount of time after other steps. Moreover, while some steps are illustrated with dotted lines to indicate they are optional, in some examples, steps illustrated with solid lines can also be optional (e.g., pumping effluent).

(209) One advantage of the extracorporeal blood filtering machine being able to operate in an open-loop mode and/or a closed-loop mode is increased flexibility of the extracorporeal blood filtering machine. For example, as is explained further with respect of FIG. **29**, FIG. **30**, and FIG. **31**, being able to operate in an open-loop mode can enable the extracorporeal blood filtering machine to be transported more easily. Another advantage of the illustrated and described extracorporeal blood filtering machine is increased accuracy in both the open-loop mode and closed-loop mode which is achieved in part by using the flow sensors. Additionally, even if the extracorporeal blood filtering machine starts to become inaccurate, a user can be easily alerted to the inaccuracy issue. In some embodiments, the extracorporeal blood filtering machine can be operated in open-loop mode with respect to the source fluid circuit and source fluid pump and in a closed-loop mode with respect to the effluent circuit and effluent pump, or vice versa.

(210) Moving to FIG. **29**, FIG. **29** is a schematic view of an example extracorporeal blood filtering system **2900** including an example extracorporeal blood filtering machine **2902** according to an aspect of the present disclosure. The extracorporeal blood filtering system **2900** can include some or all of the features related to an extracorporeal blood filtering machine and/or system described elsewhere herein (e.g., FIGS. **2-6**, **8**, **10**, **12**, **27**). For example, the extracorporeal blood filtering system **2900** can include the various source line connection positions described in connection with FIGS. **3-6**. The extracorporeal blood filtering system **2900** can also include features not previously described. For example, extracorporeal blood filtering system **2900** can include a battery **2966** and an external power source **2978**. One of ordinary skill in the art will appreciate that the extracorporeal blood filtering system **2900** of FIG. **29** is not limited to the illustrated components alone as some components may be omitted for case of illustration.

(211) In the illustrated example of the extracorporeal blood filtering system **2900** of FIG. **29**, the extracorporeal blood filtering system **2900** includes all the features of the extracorporeal blood filtering machine of FIG. **27** including the blood circuit, the effluent circuit, and the source fluid circuit. The extracorporeal blood filtering system **2900** further includes the battery **2966** and the external power source **2978**. The battery **2966** is configured to provide power to the extracorporeal blood filtering machine **2902** for the extracorporeal blood filtering machine **2902** to operate. In some examples, the battery **2966** can have a large enough capacity to power the extracorporeal blood filtering machine **2902** for an extended period (e.g., 20 minutes or more). The battery **2966** can comprise any type of battery and can be configured to provide primary power and/or backup power to the extracorporeal blood filtering machine **2902**. The battery **2966** can be electrically connected to some or all the components of the extracorporeal blood filtering machine **2902** to power said components. For example, the battery **2966** can be connected to the blood pump **2910**,

the source fluid pump **2938**, the effluent pump **2924**, the controller **2949**, the display **2944**, and other components of the extracorporeal blood filtering machine **2902** including sensors and scales. The battery **2966** can be integrated into the extracorporeal blood filtering machine **2902** or can be provided as part of the extracorporeal blood filtering system **2900** such as being on a cart containing the extracorporeal blood filtering machine **2902** (e.g., as illustrated in FIG. 1). In some examples, the extracorporeal blood filtering system **2900** includes multiple batteries.

(212) Similarly, the external power source **2978** is configured to provide power to the extracorporeal blood filtering machine **2902** for the extracorporeal blood filtering machine **2902** to operate. The external power source **2978** can be connected to the extracorporeal blood filtering machine **2902** by a power connector **2979**, such as a standard power plug. The external power source **2978** can be configured to provide primary power and/or backup power to the extracorporeal blood filtering machine **2902**. In some examples, the battery **2966** provides backup power while the external power source **2978** provides primary power to the extracorporeal blood filtering machine **2902**. The external power source **2978** can be electrically connected to some or all the components of the extracorporeal blood filtering machine **2902** to power said components. For example, the extracorporeal blood filtering machine **2902** can be connected to the blood pump **2910**, the source fluid pump **2938**, the effluent pump **2924**, the controller **2949**, the display **2944**, and other components of the extracorporeal blood filtering machine **2902** including sensors and scales. In some examples, the extracorporeal blood filtering system **2900** includes multiple external power sources such as a primary external power source and a secondary, backup external power source.

(213) Now referencing the controller **2949**, the controller **2949** can be in communication with some or all components within the extracorporeal blood filtering system **2900** and can operate the extracorporeal blood filtering system **2900**, including some or all aspects of the extracorporeal blood filtering machine **2902**. For example, the controller **2949** is in communication with the extracorporeal blood filtering machine **2902** and is configured to operate the extracorporeal blood filtering machine **2902** in a stationary mode of operation and in a transport mode of operation. In both the stationary mode of operation and in the transport mode of operation, the blood pump **2910** is active and can pump blood.

(214) However, the effluent pump **2924** can be in an effluent pump stationary state when the extracorporeal blood filtering machine is in the stationary mode of operation and in an effluent pump transport state when the extracorporeal blood filtering machine is in the transport mode of operation. The effluent pump **2924** can be active (e.g., pumping effluent) in the effluent pump stationary state and inactive (e.g., not pumping effluent) in the effluent pump transport state. Additionally or alternatively, in some examples, the effluent pump is closed-loop controlled in the effluent pump stationary state and is open-loop controlled in the effluent pump transport state. Closed-loop control and open-loop control are further described in connection with FIGS. 27-28.

(215) In some examples, the controller **2949** can switch the extracorporeal blood filtering machine **2902** from the transport mode of operation to the stationary mode of operation. In some such examples, the controller **2949** can be configured to compare an estimated quantity of effluent that was collected in the effluent receptacle while the extracorporeal blood filtering machine was in the transport mode of operation with an actual quantity of effluent that was collected in the effluent receptacle while the extracorporeal blood filtering machine was in the transport mode of operation. The controller **2949** can further be configured to adjust the effluent pump **2924** to account for an effluent discrepancy between the estimated quantity of effluent and the actual quantity of effluent. For example, the controller **2949** could increase or decrease the effluent pump speed for a period of time to account for the discrepancy.

(216) In some embodiments, to obtain the estimated quantity of effluent that was collected in the effluent receptacle in the transport mode of operation, the controller **2949** can use measurements from the effluent flow sensors **2990**, **2992**. In many embodiments, to obtain the actual quantity of

effluent that was collected in the effluent receptacle in the transport mode of operation, the controller **2949** can use measurements from the effluent scale **2946**. For example, an effluent weight value measured by the effluent scale **2946** just before the extracorporeal blood filtering machine **2902** is switched into the transport mode of operation can be compared with an effluent weight value measured by the effluent scale **2946** just after the extracorporeal blood filtering machine **2902** is switched back to the stationary mode of operation. Additionally, in some examples, the controller **2949** can receive measurements from one or more effluent density sensors (e.g., **1282**, **1284** of FIG. **12**) to obtain one or both of the estimated quantity of effluent or the actual quantity of effluent.

(217) As illustrated in FIG. **29**, the extracorporeal blood filtering system includes a user interface device **2968** and the display **2944** that are in communication with the controller **2949**. Both the user interface device **2968** and the display **2944** can be used as user interfaces and can receive one or more parameters from a user. Further, the user interface device **2968** and the display **2944** can receive outputs from the controller **2949** and can, in some examples, display the output.

(218) In some embodiments, the controller **2949** can be configured to receive an effluent open-loop limit parameter from a user through the user interface. Additionally, the controller **2949** can be configured to output an effluent error notification via the user interface when the effluent open-loop limit parameter has been exceeded in the transport mode of operation. An effluent open-loop limit parameter can comprise one or more parameters including but not limited to time of operation in the transport mode, a quantity of effluent, source fluid, and/or blood pumped in the transport mode, and a flow mismatch between effluent and/or source fluid flow sensors. In some examples, the controller **2949** is further configured to switch the effluent pump transport state to inactive when the effluent open-loop limit parameter has been exceeded in the transport mode of operation. This can be advantageous as the quantity of effluent pumped may no longer be accurate once the effluent open-loop limit parameter has been exceeded. An inaccurate quantity of effluent pumped can lead to fluid imbalance and other compromised treatment of a patient. Instead, by switching the effluent pump transport state to inactive, the amount of effluent pumped can be approximately known within a degree of error.

(219) In some embodiments, the controller **2949** can be configured to receive a transport mode command from a user through the user interface. Additionally, the controller **2949** can be configured to switch from the stationary mode of operation to the transport mode of operation in response to the transport mode command.

(220) Continuing with the controller **2949** of FIG. **29**, the controller **2949** can be configured to operate the extracorporeal blood filtering machine **2902** in the stationary mode of operation when the extracorporeal blood filtering machine **2902** is receiving power from an external power source **2978** via a power connector **2979**. Additionally, the controller **2949** can be configured to operate the extracorporeal blood filtering machine **2902** in the transport mode of operation when the extracorporeal blood filtering machine **2902** is receiving power from a battery **2966**. In some embodiments, the controller **2949** is in communication with a user interface (e.g., user interface device **2968**, display **2944**) and is configured to detect when the controller is receiving power from the battery **2966**. In such embodiments, the controller **2949** can output a prompt to a user via the user interface to switch the extracorporeal blood filtering machine **2902** to the transport mode of operation.

(221) In some embodiments, the controller **2949** can be configured to detect that the extracorporeal blood filtering machine has begun to be transported (e.g., via a movement sensor such as an accelerometer). In some such embodiments, the controller **2949** can automatically switch the extracorporeal blood filtering machine **2902** into the transport mode of operation. Alternatively, in some such embodiments, the controller **2949** can output a prompt to a user via the user interface to switch the extracorporeal blood filtering machine **2902** to the transport mode of operation.

(222) The controller **2949** can also be configured to resume operating the extracorporeal blood

filtering machine **2902** in the stationary mode of operation after operating the extracorporeal blood filtering machine **2902** in the transport mode of operation. For example, the controller **2949** can resume operating in the stationary mode of operation when the extracorporeal blood filtering machine **2902** receives power from the external power source **2978** after receiving power from the battery **2966**.

(223) Embodiments of the extracorporeal blood filtering system **2900** can include a source fluid circuit with a source fluid pump **2938**. Further, as described elsewhere herein, the controller **2949** is in communication with the extracorporeal blood filtering machine **2902** and is configured to operate the extracorporeal blood filtering machine **2902** in a stationary mode of operation and in a transport mode of operation. Thus, in similarity with the effluent pump **2924** operation, the source fluid pump **2938** can be in a source fluid pump stationary state in the stationary mode of operation and in a source fluid pump transport state in the transport mode of operation. The source fluid pump **2938** can be active (e.g., pumping source fluid) in the source fluid pump stationary state and can be inactive (e.g., not pumping source fluid) in the source fluid pump transport state.

Additionally or alternatively, in some examples, the source fluid pump **2938** can be closed-loop controlled in the source fluid pump stationary state and can be open-loop controlled in the source fluid pump transport state. In some embodiments, the source fluid pump **2938** can be inactive in the source fluid pump transport state, and the effluent pump **2924** can be open-loop controlled in the effluent pump transport state. In some embodiments, the source fluid pump **2938** can be open-loop controlled in the source fluid pump transport state, and the effluent pump can be inactive in the effluent pump transport state. Closed-loop control and open-loop control are further described with respect to FIG. 27 and FIG. 28.

(224) In some examples, the controller **2949** can switch the extracorporeal blood filtering machine **2902** from the transport mode of operation to the stationary mode of operation. In some such examples, the controller **2949** can be configured to compare an estimated quantity of source fluid that was pumped from the source fluid reservoir into the blood circuit while the extracorporeal blood filtering machine was in the transport mode of operation with an actual quantity of source fluid that was pumped from the source fluid reservoir into the blood circuit while the extracorporeal blood filtering machine was in the transport mode of operation. For example, a source fluid weight value measured by the source fluid scale **2948** just before the extracorporeal blood filtering machine **2902** is switched into the transport mode of operation can be compared with a source fluid weight value measured by the source fluid scale **2948** just after the extracorporeal blood filtering machine **2902** is switched back to the stationary mode of operation. The controller **2949** can further be configured to adjust the source fluid pump **2938** to account for a source fluid discrepancy between the estimated quantity of source fluid and the actual quantity of source fluid. For example, the controller **2949** could increase or decrease the source fluid pump speed for a period of time to account for the discrepancy.

(225) Again, as described elsewhere herein, the controller **2949** can be in communication with a user interface. The controller **2949** can then be configured to receive a source fluid open-loop limit parameter from a user through the user interface. Additionally, the controller **2949** can be configured to output a source fluid error notification via the user interface when the source fluid open-loop limit parameter has been exceeded in the transport mode of operation. A source fluid open-loop limit parameter can comprise one or more parameters including but not limited to time of operation in the transport mode, a quantity of effluent, source fluid, and/or blood pumped in the transport mode, and a flow mismatch between effluent and/or source fluid flow sensors. In some examples, the controller **2949** is further configured to switch the source fluid pump transport state to inactive when the source fluid open-loop limit parameter has been exceeded in the transport mode of operation. This can be advantageous as the quantity of source fluid pumped may no longer be accurate once the source fluid open-loop limit parameter has been exceeded. An inaccurate quantity of source fluid pumped can lead to fluid imbalance and other compromised treatment of a

patient. Instead, by switching the source fluid pump transport state to inactive, the amount of source fluid pumped can be approximately known within a degree of error.

(226) Moving to FIG. 30, FIG. 30 is a flowchart of an example method of operating the extracorporeal blood filtering machine of FIG. 29 according to an aspect of the present disclosure. The method starts at step 3000 with providing an extracorporeal blood filtering machine. As described elsewhere herein, the extracorporeal blood filtering machine can include a blood circuit, an effluent circuit, and a source fluid circuit, along with their associated components. Next, while not an affirmative method step, the extracorporeal blood filtering machine can be operating in a stationary mode of operation. The stationary mode of operation can simply include operating the extracorporeal blood filtering machine. Operating the extracorporeal blood filtering machine generally includes pumping blood through the filter, pumping effluent generated by the filter into an effluent receptacle, and pumping source fluid into a blood line, as is described elsewhere herein.

(227) The method continues at step 3002 with switching the extracorporeal blood filtering machine from a stationary mode of operation to a transport mode of operation. As illustrated, in the stationary mode of operation, the blood pump is active while the effluent pump and the source fluid pump are each in a stationary state. In some examples, the effluent pump and the source fluid pump are each active in the stationary state. In some examples, the effluent pump and the source fluid pump are each closed-loop controlled in the stationary state. Alternatively, in the transport mode of operation, the blood pump is again active while the effluent pump and the source fluid pump are each in a transport state. In some examples, the effluent pump and the source fluid pump are each inactive in the transport state. In some examples, the effluent pump and the source fluid pump are each open-loop controlled in the transport state. In some examples, one of the effluent pump and the source fluid pump is inactive in the transport state and the other of the effluent pump and the source fluid pump is open-loop controlled in the transport state. The method can then continue with step 3004, 3018, and/or 3014.

(228) Starting with step 3004, the method can include switching the extracorporeal blood filtering machine from the transport mode of operation back to the stationary mode of operation. The method can further include comparing an estimated quantity of effluent that was collected in the effluent receptacle while the extracorporeal blood filtering machine was in the transport mode of operation with an actual quantity of effluent that was collected in the effluent receptacle while the extracorporeal blood filtering machine was in the transport mode of operation, as in step 3006. Additionally, the method can include comparing an estimated quantity of source fluid that was pumped from the source fluid reservoir into the blood circuit while the extracorporeal blood filtering machine was in the transport mode of operation with an actual quantity of source fluid that was pumped from the source fluid reservoir into the blood circuit while the extracorporeal blood filtering machine was in the transport mode of operation, as in step 3008.

(229) Next, in steps 3010 and 3012, the method can include adjusting the effluent pump and/or the source fluid pump. In step 3010, the method includes adjusting the effluent pump to account for an effluent discrepancy between the estimated quantity of effluent and the actual quantity of effluent. In step 3012, the method includes adjusting the source fluid pump to account for a source fluid discrepancy between the estimated quantity of source fluid and the actual quantity of source fluid. In some embodiments, the method can return to the extracorporeal blood filtering machine being operated in the stationary mode.

(230) Moving to step 3014, the method can include detecting when the extracorporeal blood filtering machine switches from receiving power from a battery to receiving power from an external power source via a power connector. If the switching of receiving power is detected, the method can further include automatically switching the extracorporeal blood filtering machine from the transport mode of operation to the stationary mode of operation as in step 3016. In some examples, the method can continue from step 3016 to step 3006 due to the transition from operating in the transport mode to operating in the stationary mode.

(231) Moving to step **3018**, the method can include receiving an open-loop limit parameter from a user (e.g., via a user interface). Next, in step **3020**, the method can include outputting an error notification when the open-loop limit parameter has been exceeded in the transport mode of operation. Further, if the open-loop limit parameter has been exceeded in the transport mode of operation, the method can include switching the stationary state for each of the effluent pump and the source fluid pump to inactive as in step **3022**.

(232) Moving to FIG. **31**, FIG. **31** is a flow chart of an example method of operating the example extracorporeal blood filtering machine of FIG. **29** according to an aspect of the present disclosure. Starting with step **3100**, the method can include providing an extracorporeal blood filtering machine (e.g., like those described elsewhere herein). Next, while not an affirmative step, the extracorporeal blood filtering machine can be operating in a stationary mode of operation. The stationary mode of operation can simply include operating the extracorporeal blood filtering machine. Operating the extracorporeal blood filtering machine generally includes pumping blood through the filter, pumping effluent generated by the filter into an effluent receptacle, and pumping source fluid into a blood line, as is described elsewhere herein. The method can then continue with step **3102**, **3106**, or **3108**.

(233) Starting with step **3102**, the method can include detecting when the extracorporeal blood filtering machine switches from receiving power from an external power source via a power connector to receiving power from a battery. If the switching of receiving power is detected, the method can continue with step **3104** or **3110**. Step **3104** includes automatically switching the extracorporeal blood filtering machine from the stationary mode of operation to the transport mode of operation. Alternatively, step **3110** includes prompting a user to input a transport mode command to switch the extracorporeal blood filtering machine from the stationary mode of operation to the transport mode of operation. From step **3110**, the method can continue with step **3108**.

(234) Moving to step **3108**, the method can include receiving a transport mode command from a user (e.g., via a user interface). Once received, the method continues with step **3112** which includes switching the extracorporeal blood filtering machine from a stationary mode of operation to a transport mode of operation in response to the transport mode command.

(235) Moving to step **3106**, the method can include detecting when the extracorporeal blood filtering machine has begun to be transported (e.g., via a movement sensor). From step **3106**, the method can continue with either step **3104** or step **3110**.

(236) As illustrated in the example method of operation illustrated in FIG. **31**, the extracorporeal blood filtering machine can change from operating in the stationary mode to operating in the transport mode manually from receiving a transport mode command, or automatically, as in step **3104**. In the manual method, the extracorporeal blood filtering machine can directly receive a transport command or receive a transport command after prompting a user. Further, to prompt the user, the extracorporeal blood filtering machine can detect a change in power source, as in step **3102**, or a transportation indication (e.g., being moved) as in step **3016**. Alternatively, the extracorporeal blood filtering machine can detect the change in the power source, as in step **3102**, or the transportation indication, as in step **3016**, to automatically switch operating modes.

(237) While the steps of FIG. **30** and FIG. **31** may be illustrated and discussed in a particular order, it will be appreciated that the steps of FIG. **30** and FIG. **31** need not be performed in the illustrated or described order. For instance, in some examples, method steps illustrated as occurring after other methods steps can, in actuality, occur before the other method steps. Further, some steps can be performed substantially simultaneously as other steps, while some steps can be performed any amount of time after other steps.

(238) There are several advantages of the extracorporeal blood filtering machine of FIG. **29** and the associated methods of FIG. **30** and FIG. **31**. For example, when a patient receiving extracorporeal blood filtering via the extracorporeal blood filtering machine moves from one place to another (e.g., to use the restroom), the effluent receptacle and/or the source fluid receptacle can move

around during transport. The moving around can impact the weight values measured by the respective scales, and using those weight values in closed-loop control of the effluent pump and/or the source fluid pump can lead to fluid imbalance. This imbalance can be especially pronounced for very small patients who have a small overall quantity of bodily fluids relative to larger patients. Switching the extracorporeal blood filtering machine into transport mode, and out of closed-loop control of the respective pumps, can aid in patient fluid balance.

(239) Moving to FIG. 32, FIG. 32 is a schematic view of an example extracorporeal blood filtering system **3200** including an example extracorporeal blood filtering machine **3202** according to an aspect of the present disclosure. The extracorporeal blood filtering system **3200** can include some or all of the features related to an extracorporeal blood filtering machine and/or system described elsewhere herein (e.g., FIGS. 2-6, 8, 10, 12, 27, 29). The extracorporeal blood filtering system **3200** can also include features not previously described. For example, extracorporeal blood filtering system **3200** can include an anticoagulant pump **3241** and can interact with an external device **3201**. One of ordinary skill in the art will appreciate that the extracorporeal blood filtering system **3200** of FIG. 32 is not limited to the illustrated components alone as some components may be omitted for case of illustration.

(240) In the illustrated example of the extracorporeal blood filtering system **3200** of FIG. 32, the extracorporeal blood filtering system **3200** includes all the features of the extracorporeal blood filtering machine of FIG. 2 including the blood circuit, the effluent circuit, and the source fluid circuit. As described elsewhere herein, source fluid pumped by the source fluid circuit into the blood line can include one or more of dialysate replacement fluid, electrolyte fluid, or general nutritional injection fluid. The extracorporeal blood filtering system **3200** also includes the anticoagulant circuit of FIG. 2. The effluent circuit comprises an anticoagulant line **3242** fluidly connected to an anticoagulant reservoir **3240** and configured to be connected to the blood circuit. In some embodiments, the anticoagulant reservoir **3240** can be its own anticoagulant pump as the anticoagulant reservoir **3240** comprises a syringe. In some such embodiments, the syringe can be manually used to introduce anticoagulant into the blood circuit and can be referred to as a “manual pump.” Alternatively, in some embodiments, the syringe can be pressed by a pump, piston, or other device that is automatic and can automatically introduce anticoagulant into the blood circuit. However, in some examples, the extracorporeal blood filtering system **3200** can include a separate anticoagulant pump **3241** configured to pump anticoagulant from the anticoagulant reservoir **3240** through the anticoagulant line **3242** into the blood circuit. As with the blood pump **3210**, the effluent pump **3224**, and the source fluid pump **3238**, the anticoagulant pump **3241** can be in communication with the controller **3249** and can be controlled by the controller **3249**.

(241) Additionally, the extracorporeal blood filtering system **3200** can interact with an external device **3201**. The external device **3201** can comprise a device that causes various kinds of fluid to flow into and/or out of the patient and can, in some examples, record an amount of fluid it causes to flow into or out of the patient. For example, the external device **3201** can include an infusion pump, a wound vacuum, and/or an extracorporeal membrane oxygenation machine. Fluids provided/received by external devices can include medications, electrolyte replacement fluid, nutritional fluid, albumin, anticoagulation fluid, and machines/receptacles that collect bodily fluids. The external device **3201** can also be in communication with the controller **3249** (e.g., wired or wireless communication) and can send external fluid inflow/outflow information to the controller **3249**. The external fluid inflow/outflow information can comprise the amount of fluid the external device **3201** causes to flow into and/or out of the patient. In some embodiments, the extracorporeal blood filtering system **3200** includes multiple external devices that are in communication with the controller **3249** and can send external fluid inflow/outflow information.

(242) Further, the extracorporeal blood filtering system **3200** can include a user interface which can be part of a user input device **3268** and/or a display **3244**. For example, both the user input device **3268** and the display **3244** can be used as user interfaces and can receive one or more inputs from a

user. Further, the user input device **3268** and the display **3244** can receive outputs from the controller **3249** and can, in some examples, display the output.

(243) The extracorporeal blood filtering system **3200** can further interact with a pulse oximetry sensor **3255** that is configured to measure a blood oxygen saturation of a patient. The pulse oximetry sensor **3255** can be separate from the extracorporeal blood filtering machine **3202** and can be put on a patient's finger, for example. However, in some instances, the pulse oximetry sensor **3255** can be part of the extracorporeal blood filtering system **3200** and is in communication with the controller **3249**. For example, the pulse oximetry sensor **3255** can provide the blood oxygen saturation it measures to the controller **3249**. In some embodiments, the controller **3249** is configured to provide the blood oxygen saturation to the user interface (e.g., display **3244**) for display. Additionally, in some embodiments, the controller **3249** can be configured to output an alarm signal to the user interface when the blood oxygen saturation measured by the pulse oximetry sensor is below an alarm threshold value (e.g., 88%).

(244) Now referencing the controller **3249**, the controller **3249** can be in communication with some or all components within the extracorporeal blood filtering system **3200** and can operate the extracorporeal blood filtering system **3200**, including some or all aspects of the extracorporeal blood filtering machine **3202**. For example, the controller **3249** is in communication with the extracorporeal blood filtering machine **3202** and is configured to operate the blood pump **3210**, the effluent pump **3224**, and the source fluid pump **3238** in order to filter a patient's blood.

(245) The controller **3249** is configured to collect internal fluid inflow/outflow information related to fluid flowing into and out of a patient via the extracorporeal blood filtering machine **3202**. The controller **3249** can collect the internal fluid inflow/outflow information through operation of the extracorporeal blood filtering machine **3202**. For example, the controller **3249** can collect internal fluid outflow information from the effluent scale **3246**, the effluent pump **3224**, and/or from another effluent sensing device (e.g., flow sensors **2990**, **2992** of FIG. 29) as the effluent is filtered out from a patient's blood. The fluid outflow information can thus comprise effluent flow information. Further, the controller **3249** can collect internal fluid inflow information from the source fluid scale **3248**, the source fluid pump **3238**, and/or from another source fluid sensing device (e.g., flow sensors **2994**, **2996** of FIG. 29). The fluid inflow information can thus comprise source fluid flow information. Additionally, in some embodiments, the controller **3249** can collect internal fluid inflow information from the anticoagulant pump and/or other anticoagulant sensing device as anticoagulant is added to the blood circuit. The internal fluid inflow information can thus include anticoagulant flow information. In some embodiments, the internal fluid inflow/outflow information comprises blood flow information, which the controller **3249** can collect from the blood pump **3210** and/or other blood sensing device.

(246) In some embodiments, the controller **3249** is also configured to receive external fluid inflow/outflow information related to fluid flowing into and out of a patient not via the extracorporeal blood filtering machine **3202**. For example, the controller **3249** can receive the external inflow/outflow information from the external device **3201**, which can produce the external fluid inflow/outflow information as it causes fluid to flow into and out of the patient. In some embodiments, the controller **3249** can receive the external inflow/outflow information by communicating directly with the external device **3201**. Additionally or alternatively, in some embodiments, the controller **3249** can receive the external inflow/outflow information indirectly, such as through another device.

(247) As described, the controller **3249** can collect the internal fluid inflow/outflow information and the external fluid inflow/outflow information automatically by communicating with various components. In some embodiments, the controller **3249** can receive the internal fluid inflow/outflow information and/or the external fluid inflow/outflow information via manual entry. For example, the controller **3249** can receive the external fluid inflow/outflow information by receiving manually entered external fluid inflow/outflow information. In some external inflow

examples, a user can manually inject fluids, such as medications or diagnostic fluids, into the blood line or the patient directly and/or can hook the patient up to an IV. The amount of manually injected fluids can then be entered. In some external outflow examples, a user can manually enter an amount of output from chest tubes, wound or drainage bags, or the like. The manually entered fluid inflow/outflow information can be entered via one or more of the user input device **3268**, the display **3244**, or the external device **3201** itself.

(248) The controller **3249** can be configured to determine a fluid inflow/outflow balance based on the internal fluid inflow/outflow information and the external fluid inflow/outflow information. The controller **3249** can further provide the fluid inflow/outflow balance information to the user interface (e.g., **3244**) for display. The fluid inflow/outflow balance can comprise the net fluid inflow vs. fluid outflow from both internal and external sources. The fluid inflow/outflow balance can be displayed as the net fluid inflow vs. fluid outflow (e.g., a single positive or negative number) and/or as the gross fluid inflow vs. the gross fluid outflow (e.g., total fluid inflow and total fluid outflow). In some embodiments, the controller **3249** is configured to determine the fluid inflow/outflow balance information based in part on the blood oxygen saturation measured by the pulse oximetry sensor **3255**. For example, a lower blood oxygen saturation may indicate an overload of fluid within a patient's body.

(249) In some embodiments, the controller **3249** can be configured to collect the internal fluid inflow/outflow information, receive the external fluid inflow/outflow information, determine the fluid inflow/outflow balance information, and provide the fluid inflow/outflow balance information to the user interface for display all dynamically in real time. This can be advantageous as a user can quickly determine multiple facets of fluid inflow and fluid outflow for a patient by viewing the user interface and can take steps to make appropriate adjustments as necessary.

(250) Moving to FIG. **33**, FIG. **33** is a flowchart of an example method of operating the extracorporeal blood filtering machine of FIG. **32** according to an aspect of the present disclosure. The method starts at step **3300**, which includes providing an extracorporeal blood filtering machine. In some embodiments, the extracorporeal blood filtering machine can simply comprise a user interface and a controller. However, in some embodiments, the extracorporeal blood filtering machine can comprise other elements such as a blood circuit, an effluent circuit, a source fluid circuit, and an anticoagulant circuit.

(251) The method continues at steps **3302** and **3304**. Step **3302** includes operating the extracorporeal blood filtering machine with the controller to cause fluid to flow into and out of a patient, while step **3304** includes collecting internal fluid inflow/outflow information by the controller. The internal fluid inflow/outflow information can be related to the fluid flowing into and out of the patient through operation of the extracorporeal blood filtering machine. For example, the internal fluid inflow/outflow information can comprise blood flow information, effluent flow information, source fluid flow information, and/or anticoagulant flow information.

(252) Next, in step **3306**, the method includes receiving external fluid inflow/outflow information by the controller. In similarity with the internal fluid inflow/outflow information, the external fluid inflow/outflow information can be related to fluid flowing into and out of the patient other than through operation of the extracorporeal blood filtering machine (e.g., via an external device). In some examples, the receiving external fluid inflow/outflow information by the controller includes receiving manually entered external fluid inflow/outflow information by the controller. Additionally or alternatively, in some examples, receiving external fluid inflow/outflow information by the controller includes communicating directly with an external device that causes fluid to flow into or out of the patient.

(253) The method further continues with step **3308** and step **3310**. In step **3308**, the method includes determining fluid inflow/outflow balance information by the controller based on the internal fluid inflow/outflow information and the external fluid inflow/outflow information. In step **3310**, the method includes providing the fluid inflow/outflow balance information by the controller

to the user interface for display.

(254) In some embodiments, providing the extracorporeal blood filtering machine in step **3300** includes providing a pulse oximetry sensor configured to measure a blood oxygen saturation of a patient. In some such embodiments, the step of determining fluid inflow/outflow balance information includes accounting for blood oxygen saturation measured by the pulse oximetry sensor as in step **3312**. Further, in some embodiments, the method can include outputting an alarm signal to the user interface when the blood oxygen saturation measured by the pulse oximetry sensor is below an alarm threshold value as in step **3314**.

(255) While the steps of FIG. **33** may be illustrated and discussed in a particular order, it will be appreciated that the steps of FIG. **33** need not be performed in the illustrated or described order. For instance, in some examples, method steps illustrated as occurring after other methods steps can, in actuality, occur before the other method steps. Further, some steps can be performed substantially simultaneously as other steps, while some steps can be performed any amount of time after other steps.

(256) There are several advantages of the extracorporeal blood filtering machine of FIG. **32** and the associated method of FIG. **33**. For example, although an extracorporeal blood filtering machine can ensure balance between the fluid it causes to flow into and out of a patient, it can be important to achieve overall fluid balance, accounting for fluid flowing into and out of the patient via various devices. Conventional methods of tracking such overall balance involve manually entering both internal and external fluid inflow/outflow information into a spreadsheet via a computer that is separate from the extracorporeal blood filtering machine. There are advantages to automatically capturing some or all of the fluid inflow/outflow information, and there are advantages to providing a user-friendly user interface for allowing manual entry of fluid inflow/outflow information and display of the overall fluid balance.

(257) Moving to FIG. **34**, FIG. **34** is a perspective view of an example display **3444** according to an aspect of the present disclosure. The display **3444** can be any type of display, but in some examples, includes a touch-enabled display. The display **3444** can also be considered a user interface or user input device and receive user inputs. As discussed elsewhere herein, the display **3444** can be in communication with a controller (e.g., **3249**) and can display outputs received from the controller.

(258) Various embodiments have been described. Such examples are non-limiting, and do not define or limit the scope of the invention in any way.

Claims

1. An extracorporeal blood filtering machine comprising: a blood circuit that includes: a blood line comprising a blood inlet configured to receive blood from a patient and a blood outlet configured to return the blood to the patient, a filter fluidly connected to the blood line between the blood inlet and the blood outlet, and a blood pump configured to pump the blood from the blood inlet to the blood outlet through the filter, the filter configured to remove waste from the blood; an effluent circuit that includes: an effluent line fluidly connected to the filter, the effluent line configured to receive the waste from the filter in the form of effluent, and an effluent pump configured to pump the effluent from the filter through the effluent line into an effluent receptacle; a hemolysis sensor configured to sample the effluent in the effluent line and/or the blood in the blood line and output a hemolysis signal indicative of a detected degree of hemolysis; and a controller in communication with the blood pump, the effluent pump, and the hemolysis sensor, the controller configured to receive the hemolysis signal and to output a hemolysis alert signal if the detected degree of hemolysis exceeds a hemolysis threshold.

2. The extracorporeal blood filtering machine of claim 1, wherein the hemolysis sensor is in optical communication with the effluent line and is configured to sample the effluent in the effluent line.

3. The extracorporeal blood filtering machine of claim 1, wherein the hemolysis sensor is fluidly connected to the blood line and configured to sample the blood in the blood line.
4. The extracorporeal blood filtering machine of claim 1, further comprising a display in communication with the controller, wherein the display is configured to receive the hemolysis alert signal from the controller and display a hemolysis alert.
5. The extracorporeal blood filtering machine of claim 1, further comprising a blood leak detector configured to detect a presence of blood within the effluent line, wherein the controller is in communication with the blood leak detector and is configured to output a blood leak alarm signal if the blood leak detector detects the presence of blood within the effluent line.
6. The extracorporeal blood filtering machine of claim 5, wherein the controller is further configured to stop the effluent pump if the blood leak detector detects the presence of blood within the effluent line.
7. The extracorporeal blood filtering machine of claim 1, wherein the hemolysis sensor is configured to sample the effluent in the effluent line and/or the blood in the blood line between the blood pump and the blood outlet.
8. The extracorporeal blood filtering machine of claim 7, further comprising a reference hemolysis sensor in communication with the controller and configured to sample the blood in the blood line between the blood inlet and the blood pump and to output a reference hemolysis signal indicative of a reference degree of hemolysis.
9. The extracorporeal blood filtering machine of claim 8, wherein the controller is configured to: receive the reference hemolysis signal, compare the reference hemolysis signal to the hemolysis signal, and output a hemolysis mismatch alert signal if the hemolysis signal differs from the reference hemolysis signal by more than a threshold amount.
10. The extracorporeal blood filtering machine of claim 9, further comprising a display in communication with the controller, wherein the display is configured to receive the hemolysis mismatch alert signal from the controller and display a blood pump hemolysis alert.
11. A method comprising: providing an extracorporeal blood filtering machine that includes: a blood circuit that includes: a blood line comprising a blood inlet and a blood outlet, a filter fluidly connected to the blood line between the blood inlet and the blood outlet, and a blood pump; an effluent circuit that includes: an effluent line fluidly connected to the filter, and an effluent pump; a hemolysis sensor; and a controller in communication with the blood pump, the effluent pump, and the hemolysis sensor; operating the extracorporeal blood filtering machine by the controller to: pump blood with the blood pump from a patient into the blood inlet through the blood line to the filter and back to the patient through the blood line out of the blood outlet, the filter removing waste from the blood and providing the waste to the effluent line in the form of effluent, and pump the effluent with the effluent pump through the effluent line into an effluent receptacle; sampling the effluent in the effluent line and/or the blood in the blood line with the hemolysis sensor; providing a hemolysis signal indicative of a detected degree of hemolysis from the hemolysis sensor to the controller; and outputting a hemolysis alert signal with the controller if the detected degree of hemolysis exceeds a hemolysis threshold.
12. The method of claim 11, wherein sampling the effluent in the effluent line and/or the blood in the blood line with the hemolysis sensor comprises sampling the effluent in the effluent line with the hemolysis sensor.
13. The method of claim 11, wherein sampling the effluent in the effluent line and/or the blood in the blood line with the hemolysis sensor comprises sampling the blood in the blood line with the hemolysis sensor.
14. The method of claim 11, wherein: the extracorporeal blood filtering machine further includes a display in communication with the controller, and the method further comprises the display receiving the hemolysis alert signal from the controller and displaying a hemolysis alert.
15. The method of claim 11, wherein sampling the effluent in the effluent line and/or the blood in

the blood line with the hemolysis sensor comprises sampling the effluent in the effluent line and/or the blood in the blood line between the blood pump and the blood outlet.

16. The method of claim 15, wherein: the extracorporeal blood filtering machine further includes a reference hemolysis sensor in communication with the controller, the method further comprises: sampling the blood in the blood line between the blood inlet and the blood pump with the reference hemolysis sensor, providing a reference hemolysis signal indicative of a reference degree of hemolysis from the reference hemolysis sensor to the controller, comparing the reference hemolysis signal to the hemolysis signal with the controller, and outputting a hemolysis mismatch alert signal with the controller if the hemolysis signal differs from the reference hemolysis signal by more than a threshold amount.

17. The method of claim 16, wherein: the extracorporeal blood filtering machine further includes a display in communication with the controller, the method further comprises: providing the hemolysis mismatch alert signal from the controller to the display, and displaying a blood pump hemolysis alert on the display.
