

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415406
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Maita; Hiroshi et al.

Air conditioner for rail vehicle

Abstract

An object of the present invention is to provide an air conditioner for a rail vehicle that is excellent in cleanliness and comfort by cleaning the air conditioner at an appropriate timing without causing discomfort to passengers. An air conditioner for a rail vehicle including a vehicle control system includes: a refrigeration cycle device **3** that can execute a cleaning operation; and an air conditioning control device **4** that controls the refrigeration cycle device, and the air conditioning control device **4** can communicate with the vehicle control system **2** and causes the refrigeration cycle device **3** to execute a cleaning operation on the basis of status information obtained from the vehicle control system **2**.

Inventors:	Maita; Hiroshi (Tokyo, JP), Toyoda; Hiroyuki (Tokyo, JP), Akimaru; Daisuke (Tokyo, JP), Kawasaki; Akinori (Tokyo, JP), Taguchi; Tomoaki (Tokyo, JP), Fujii; Fumio (Tokyo, JP)
Applicant:	HITACHI, LTD. (Tokyo, JP)
Family ID:	1000008820066
Assignee:	HITACHI, LTD. (Tokyo, JP)
Appl. No.:	17/921370
Filed (or PCT Filed):	June 24, 2021
PCT No.:	PCT/JP2021/023910
PCT Pub. No.:	WO2022/269849
PCT Pub. Date:	December 29, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240010051 A1	Jan. 11, 2024

Publication Classification

Int. Cl.: B60H3/00 (20060101); B61D27/00 (20060101)

U.S. Cl.:

CPC B60H3/0092 (20130101); B61D27/0072 (20130101);

Field of Classification Search

CPC: B60H (1/00371); B60H (1/00771); B60H (1/00778); B60H (3/0085); B60H (3/0092); B61D (27/00); B61D (27/0018); B61D (27/0072); Y02T (30/00); F24F (11/43); F24F (11/48)

USPC: 701/36

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2003/0168043	12/2002	Sakurai	123/647	F02M 35/10249
2006/0005738	12/2005	Kumar	105/35	B60L 50/30
2006/0005739	12/2005	Kumar	105/35	B60L 50/61
2012/0136555	12/2011	Okamoto	701/104	F02D 41/402
2014/0193761	12/2013	Donnelly	165/200	B61C 17/08
2018/0347844	12/2017	Zhao	N/A	F24F 11/32
2019/0001999	12/2018	Yamamoto	N/A	F25B 39/04
2019/0082240	12/2018	Li	N/A	F24F 11/30
2020/0041220	12/2019	Metropoulos	N/A	F28G 15/04
2020/0180399	12/2019	Tone	N/A	B60L 1/00
2020/0376927	12/2019	Rajaie	N/A	B60H 1/00764
2021/0086739	12/2020	Fischer	N/A	B61L 27/16
2021/0123623	12/2020	Notaro	N/A	F24F 11/58
2021/0370994	12/2020	Soule	N/A	B61C 17/06
2022/0118822	12/2021	Gutowski	N/A	B60H 1/00021
2022/0118951	12/2021	Gutowski	N/A	B60J 1/2016
2022/0118952	12/2021	Gutowski	N/A	B60W 10/30
2022/0281495	12/2021	Green	N/A	B61L 21/10

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2019226299	12/2019	AU	N/A
105216812	12/2015	CN	N/A
106274942	12/2016	CN	B61D 27/00
106347395	12/2016	CN	B61D 27/0018
109269014	12/2018	CN	F24F 11/64
111216751	12/2019	CN	B61D 17/02

111976767	12/2019	CN	B61D 27/0018
112172842	12/2020	CN	B61D 27/009
112727734	12/2020	CN	F04B 39/16
113085931	12/2020	CN	G06V 40/10
216655623	12/2021	CN	N/A
116642717	12/2022	CN	G01M 17/08
219511809	12/2022	CN	N/A
117485388	12/2023	CN	B61D 27/0018
117719546	12/2023	CN	N/A
118722746	12/2023	CN	B61D 27/0018
102010010867	12/2010	DE	N/A
202010018251	12/2014	DE	N/A
102022109471	12/2022	DE	B60W 10/04
102022109475	12/2022	DE	B60H 3/0085
102022109476	12/2022	DE	B60W 10/04
2368733	12/2010	EP	N/A
3369595	12/2017	EP	F24F 8/22
3470287	12/2018	EP	B61D 27/0018
3505840	12/2020	EP	B61D 27/0018
4477491	12/2023	EP	B60H 1/00907
2594340	12/2020	GB	B61L 27/10
2598486	12/2021	GB	B61D 27/0018
2598487	12/2021	GB	B61D 27/0018
10-59178	12/1997	JP	N/A
2013-107482	12/2012	JP	N/A
2018-103939	12/2017	JP	N/A
6400147	12/2017	JP	N/A
2019-215149	12/2018	JP	N/A
WO2019116801	12/2019	JP	B60L 1/02
2021112054	12/2020	JP	N/A
2022122743	12/2021	JP	N/A
2023173297	12/2022	JP	B61D 17/12
100831652	12/2007	KR	B01D 46/00
20100122995	12/2009	KR	B61D 27/0018
101524200	12/2014	KR	B61D 27/00
102120582	12/2019	KR	B61D 27/0018
102400317	12/2021	KR	B60H 1/0073
102400318	12/2021	KR	B60H 1/0073
102575051	12/2022	KR	B61L 15/0081

WO-2017212607	12/2016	WO	B61D 27/0018
WO-2022127140	12/2021	WO	B61C 17/04
WO-2022269849	12/2021	WO	B61D 27/00
WO-2023030831	12/2022	WO	B60H 1/00371

Primary Examiner: Trivedi; Atul

Attorney, Agent or Firm: Mattingly & Malur, PC

Background/Summary

TECHNICAL FIELD

(1) The present invention relates to an air conditioner for a rail vehicle.

BACKGROUND ART

(2) Most of dust or the like suspended in the inner air of a railroad vehicle is naturally discharged to the outside of the vehicle through openings such as ventilators and doors, but some of them adhere to the wall surfaces and floor surfaces of the vehicle and the inside of an air conditioning device. Even if dust or the like adheres to the wall surfaces and floor surfaces, it is removed by periodic cleaning work, and its sanitation is maintained. On the contrary, the cleaning work of the inside of the air conditioning device is often performed only when the maintenance work is performed. Due to an increase in cleanliness-consciousness in recent years, it is desirable to perform regular cleaning work even for the inside of the air conditioning device, but from the viewpoint of suppressing labor costs and the like, the demand for automation thereof is increasing.

(3) As a technique for automatically cleaning a heat exchanger configuring an air conditioning device, there is a technique described in, for example, Patent Literature 1. In this technique, the temperature of the heat exchanger is lowered to cover the surface of the heat exchanger with frost or ice, and then the temperature of the heat exchanger is raised to thaw the frost and the like and remove dust on the surface of the heat exchanger, and the operation thereof is referred to as freeze cleaning.

(4) However, since the air conditioning operation cannot be performed during the freeze cleaning operation, when this technology is applied to an air conditioner for a railroad vehicle, there is a possibility that the comfort of the inside of the vehicle is deteriorated to cause discomfort to passengers depending on the operation timing.

CITATION LIST

Patent Literature

(5) Patent Literature 1: Japanese Patent No. 6400147

SUMMARY OF INVENTION

Technical Problem

(6) An object of the present invention is to provide an air conditioner for a rail vehicle that is excellent in cleanliness and comfort by cleaning the air conditioner at an appropriate timing without causing discomfort to passengers.

Solution to Problem

(7) In order to solve the above problems, one of representative air conditioners for a rail vehicle of the present invention can be achieved by an air conditioner for a rail vehicle including a vehicle control system, the conditioner including: a refrigeration cycle device that can execute a cleaning operation; and an air conditioning control device that controls the refrigeration cycle device,

wherein the air conditioning control device can communicate with the vehicle control system and causes the refrigeration cycle device to execute a cleaning operation on the basis of status information obtained from the vehicle control system.

Advantageous Effects of Invention

(8) According to the present invention, it is possible to provide an air conditioner for a rail vehicle that is excellent in cleanliness and comfort by cleaning the air conditioner at an appropriate timing without causing discomfort to passengers.

(9) Problems, configurations, and effects other than those described above will be clarified by the following description of the embodiments.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a schematic diagram for showing a relationship between an air conditioner according to an embodiment of the present invention and a vehicle.

(2) FIG. 2 is a flowchart of control according to a first embodiment of the present invention.

(3) FIG. 3 is a flowchart of control according to a second embodiment of the present invention.

(4) FIG. 4 is a flowchart of control according to a third embodiment of the present invention.

(5) FIG. 5 is a flowchart of control according to a fourth embodiment of the present invention.

(6) FIG. 6 is a flowchart of control according to a fifth embodiment of the present invention.

DESCRIPTION OF EMBODIMENTS

(7) Hereinafter, embodiments of the present invention will be described by using the drawings. A rail vehicle is a general term for vehicles that run along laid tracks, and means a railroad vehicle, a streetcar, a new transportation system vehicle, and a monorail vehicle. Hereinafter, embodiments of the present invention will be described with reference to the drawings by exemplifying a railroad vehicle as a representative example of the rail vehicle. Accordingly, an air conditioning device for a railway vehicle of the embodiments configures an air conditioning device for a rail vehicle of the present invention.

(8) In the embodiments, status information of the vehicle includes, but is not limited to, information of an identification number (train number) for specifying the vehicle, information of whether or not the vehicle is activated, information of whether or not the vehicle is in a deadhead state, information of whether or not the current position of the vehicle is in a vehicle base, information of instructing an air conditioning control device 4 to perform cleaning control, information (time information) of whether or not the current time is within business operation hours, information (date information) of whether or not the current date is within a period during which cooling is used, and the like. However, the air conditioning control device 4 may store the business operation hours in advance to determine whether or not the current time is within the business operation hours from the built-in clock, or may store the period during which cooling is used in advance to determine whether or not the current date is within the period during which cooling is used from the built-in clock.

First Embodiment

(9) A first embodiment of the present invention relates to control for performing a cleaning operation during deadheading after the vehicle is activated. The first embodiment will be described by using FIG. 1 and FIG. 2. FIG. 1 is a schematic diagram for showing a relationship between an air conditioner according to the present invention and a vehicle. The air conditioner of the embodiment is configured using a refrigeration cycle device 3 and an air conditioning control device 4, both of which are connected to each other by at least a communication line 5.

(10) The air conditioning control device 4 is also connected to a vehicle control system 2 that controls various information of the vehicle by a communication line 6. The refrigeration cycle

device 3 is configured using a compressor, an outdoor heat exchanger, an indoor heat exchanger, a throttling device, an outdoor blower, an indoor blower, an outdoor temperature sensor, an in-vehicle temperature sensor, and the like, and the compressor, the blowers, the throttling device, and the like are driven on the basis of a command from the air conditioning control device 4. The air conditioning control device 4 controls the refrigeration cycle device 3 on the basis of an air conditioning command from the vehicle control system 2. The refrigeration cycle device 3 can clean the heat exchangers by a freeze cleaning operation. However, the cleaning of the heat exchangers is not limited to the freeze cleaning operation. In addition, the air conditioning control device 4 can obtain information on various current states of the train from the vehicle control system 2 in addition to the air conditioning command.

(11) Next, a flow of control performed by the air conditioning control device 4 will be described by using FIG. 2 that is a flowchart of control of the embodiment. The control starts when the vehicle is powered and activated. After activating the vehicle, the air conditioning control device 4 acquires status information of the vehicle from the vehicle control system 2 via the communication line 6 (Step S101). Thereafter, the activation state of the vehicle is determined on the basis of the status information (Step S102), and if it is determined that the vehicle is not activated, the air conditioning control device 4 terminates the control.

(12) On the other hand, in the case where it is determined in Step S102 that the vehicle is in the activation state, the air conditioning control device 4 determines whether or not the vehicle is in the deadhead state in Step S103. Whether or not the vehicle is in the deadhead state may be determined by using information of whether or not the vehicle is in the deadhead state among the status information of the vehicle acquired from the vehicle control system 2, or by using train number information in the case where whether or not the vehicle is in the deadhead state can be determined from the train number information. In addition, in the case where an operation schedule is set for each train, the air conditioning control device 4 can collate the train number information and the current time with the operation schedule to perform the cleaning operation when it is determined that the vehicle is not operated.

(13) Since the vehicle is in the normal operation state in the case where it is determined in Step S103 that the vehicle is not in the deadhead state, the air conditioning control device 4 performs an operation on the basis of the air conditioning command from the vehicle control system 2 (Step S107).

(14) On the other hand, in the case where it is determined in Step S103 that the vehicle is in the deadhead state, the air conditioning control device 4 then determines whether the cleaning of the heat exchangers has been completed (Step S104). In the case where it is determined that the cleaning has been completed, the flow proceeds to Step S107 in which the air conditioning control device 4 performs the operation on the basis of the air conditioning command from the vehicle control system 2. On the contrary, in the case where it is determined that the cleaning has not been completed, the air conditioning control device 4 performs the cleaning operation of the heat exchangers (Step S105), transmits heat exchanger cleaning completion information to the vehicle control system (Step S106), and performs the operation on the basis of the air conditioning command from the vehicle control system 2 (Step S107). Thereafter, the air conditioning control device 4 waits for a certain period of time (Step S108), returns to Step S101 to acquire the vehicle status again, and repeats the determination and control from Step S102. Since the heat exchanger cleaning completion information is transmitted to the vehicle control system in Step S106, the cleaning completion can also be grasped on the vehicle system side, and the information can be displayed to the crews or the cleaning history can be managed as a vehicle system.

(15) By performing the control in this manner, the cleaning operation can be performed during the deadhead operation in which no passengers are on board, so that the cleaning operation of the heat exchangers can be performed at a timing when no passengers feel discomfort. That is, it is possible to provide an air conditioner for a railroad vehicle that is excellent in cleanliness and comfort by

cleaning the heat exchangers in the air conditioner without causing discomfort to passengers.

Second Embodiment

(16) A second embodiment of the present invention relates to control for performing a cleaning operation when the vehicle is in a base after the vehicle is activated. The second embodiment will be described by using FIG. 3 while focusing on the difference from the first embodiment. The configuration of an air conditioner for a railroad vehicle according to the embodiment is the same as that of the first embodiment shown in FIG. 1.

(17) FIG. 3 is a flowchart of control of the air conditioning control device 4. The difference from the first embodiment is that the step (Step S103 in FIG. 2) in which the air conditioning control device 4 determines whether or not the vehicle is in the deadhead state in the first embodiment is replaced with a step (Step S203) of determining whether or not the vehicle is in a vehicle base. Since the other controls (Steps S201 to S202 and S204 to S209) are the same as those (Steps S101 to S102 and S104 to S108) of the first embodiment, the duplicated description is omitted.

(18) The determination of whether or not the vehicle is in the vehicle base in Step S203 can be made by the air conditioning control device 4 from information related to the current location such as kilometers (distance from a certain point) and point information among the status information of the vehicle acquired in Step S201.

(19) In general, in the case where the vehicle is in the vehicle base, it is considered that no passengers are on board, so that by performing the control in this manner, the cleaning operation of the heat exchangers can be performed at a timing when no passengers feel discomfort. That is, it is possible to provide an air conditioner for a railroad vehicle that is excellent in cleanliness and comfort by cleaning the heat exchangers in the air conditioner without causing discomfort to passengers.

Third Embodiment

(20) A third embodiment of the present invention relates to control for performing a cleaning operation in response to a command from the vehicle control system. The third embodiment will be described by using FIG. 4. The configuration of an air conditioner for a railroad vehicle according to the embodiment is the same as that of the first embodiment shown in FIG. 1.

(21) FIG. 4 is a flowchart of control of the air conditioning control device 4. The control starts when the vehicle is powered and activated. After the vehicle is activated, the air conditioning control device 4 acquires the status information of the vehicle from the vehicle control system 2 via the communication line 6 (Step S301). Thereafter, the activation state of the vehicle is determined on the basis of the status information (Step S302), and if it is determined that the vehicle is not activated, the air conditioning control device 4 terminates the control.

(22) On the other hand, in the case where it is determined in Step S302 that the vehicle is in the activation state, the air conditioning control device 4 determines in Step S303 whether or not a heat exchanger cleaning command is issued from the status information of the vehicle acquired in the previous step. Here, in the case where it is determined that there is no cleaning command, the air conditioning control device 4 performs an air conditioning operation on the basis of the air conditioning command (Step S306).

(23) In the case where it is determined that there is a cleaning command, the air conditioning control device 4 performs the heat exchanger cleaning operation (Step S304), and transmits the information to the vehicle control system after the completion of the cleaning (Step S305). Thereafter, the air conditioning control device 4 performs an operation on the basis of the air conditioning command from the vehicle control system 2 (Step S306). Further, the air conditioning control device 4 waits for a certain period of time (Step S307), returns to Step S301 again to acquire the vehicle status, and repeats the determination and control from Step S302.

(24) By performing the control in this manner, even in a situation where it is not easily determined whether there are passengers in the vehicle or whether the vehicle is in commercial operation, for example, in the case where the vehicle stops at a station platform and is standing by with the doors

closed, the cleaning of the heat exchangers can be performed in accordance with the determination on the vehicle system side. That is, it is possible to provide an air conditioner for a railroad vehicle that is excellent in cleanliness and comfort by cleaning the heat exchangers in the air conditioner without causing discomfort to passengers according to the determination on the vehicle system side.

Fourth Embodiment

(25) A fourth embodiment of the present invention relates to control in which a condition on the basis of a set time is added to the first embodiment. The fourth embodiment will be described by using FIG. 5 while focusing on the difference from the first embodiment. The configuration of an air conditioner for a railroad vehicle according to the embodiment is the same as that of the first embodiment shown in FIG. 1.

(26) FIG. 5 is a flowchart of control of the air conditioning control device 4. The difference from the first embodiment is that a step (Step S404 here) in which the air conditioning control device 4 determines whether the time is after the set time on the basis of the status information of the vehicle is added between a step (Step S403 here) of determining whether or not the vehicle is in the deadhead state in the first embodiment and a step (Step S405 here) of determining the completion of the cleaning of the heat exchangers. Since the other controls (Steps S401 to S403 and S405 to S409) are the same as those (Steps S101 to S103 and S104 to S108) of the first embodiment, the duplicated description is omitted.

(27) For example, if the set time included in the status information is set to 18:00, the air conditioning control device 4 can control the cleaning operation of the heat exchangers in Step S406 to be performed only after 18:00 (for example, during the deadheading of the vehicle). That is, if the set time is appropriately determined, the cleaning operation of the heat exchangers can be performed at the timing of deadheading after the completion of the commercial operation on the day.

(28) By performing the control in this manner, the cleaning operation can be performed after the commercial operation on the day, so that the heat exchangers contaminated with dust or the like during the air conditioning operation can be cleaned without carrying over the contamination to the next day. That is, it is possible to provide an air conditioner for a railroad vehicle that is more excellent in cleanliness and comfort by cleaning the heat exchangers in the air conditioner without causing discomfort to passengers.

Fifth Embodiment

(29) A fifth embodiment of the present invention relates to control for performing a cleaning operation during only a period in which air conditioning is used. The fifth embodiment will be described by using FIG. 6 while focusing on the difference from the first embodiment. The configuration of an air conditioner for a railroad vehicle according to the embodiment is the same as that of the first embodiment shown in FIG. 1.

(30) FIG. 6 is a flowchart of control of the air conditioning control device 4. The difference from the first embodiment is that a step (Step S504 here) in which the air conditioning control device 4 determines the current period on the basis of the status information is added between a step (Step S503 here) of determining whether or not the vehicle is in the deadhead state in the first embodiment and a step (Step S505 here) of determining the completion of the cleaning of the heat exchangers. Since the other controls (Steps S501 to S503 and S505 to S509) are the same as those (Steps S101 to S103 and S104 to S108) of the first embodiment, the duplicated description is omitted.

(31) For example, in the embodiment, the cleaning period is set to be between May and October during which cooling is used, and only in the case where the air conditioning control device 4 determines that the current time is the cleaning period, it is possible to control to perform the cleaning operation of the heat exchangers in Step S506. Accordingly, the cleaning operation of the heat exchangers is performed during only at least a period in which cooling is used.

(32) By performing the control in this manner, in the case where the air conditioning device is exclusively used for cooling, the cleaning operation can be performed during only a period in which cooling is used, so that the cleaning operation can be prevented from being inefficiently performed during a period such as in winter in which the air conditioning device is not contaminated. That is, it is possible to more efficiently provide an air conditioner for a railroad vehicle that is excellent in cleanliness and comfort by cleaning the heat exchangers in the air conditioner only in a period that is likely to cause discomfort to passengers.

(33) It should be noted that the cleaning of the air conditioner is not limited to the heat exchangers, and other parts may be cleaned under the control of the air conditioning control device 4.

LIST OF REFERENCE SIGNS

(34) 1 railroad vehicle 2 vehicle control system 3 refrigeration cycle device 4 air conditioning control device 5 communication line connecting control device and refrigeration cycle device 6 communication line connecting vehicle control system and air conditioning control system

Claims

1. An air conditioner for a rail vehicle including a vehicle control system, the air conditioner comprising: a refrigeration cycle device that can execute a cleaning operation; and an air conditioning control device that controls the refrigeration cycle device, wherein the air conditioning control device can communicate with the vehicle control system, has a built-in clock, and has access to at least one of stored vehicle operation time information or stored cooling period information, and wherein, based at least on the air conditioning control device determining from the built-in clock and the at least one of the stored vehicle operation time information or the stored cooling period information that a current time is at least one of (1) outside vehicle operating hours or (2) within a cooling period during which the refrigeration cycle device is operated, the air conditioning control device causes the refrigeration cycle device to execute the cleaning operation on a basis of status information obtained from the vehicle control system.
 2. The air conditioner for a rail vehicle according to claim 1, wherein the air conditioning control device causes the refrigeration cycle device to execute the cleaning operation on a basis of at least information of whether or not the rail vehicle is in a deadhead state obtained from the vehicle control system.
 3. The air conditioner for a rail vehicle according to claim 1, wherein the air conditioning control device causes the refrigeration cycle device to execute the cleaning operation on a basis of at least information of the current position of the rail vehicle obtained from the vehicle control system.
 4. The air conditioner for a rail vehicle according to claim 1, wherein the air conditioning control device causes the refrigeration cycle device to execute the cleaning operation on a basis of at least information for specifying the rail vehicle obtained from the vehicle control system.
 5. The air conditioner for a rail vehicle according to claim 1, wherein the air conditioning control device causes the refrigeration cycle device to execute the cleaning operation on a basis of at least command information obtained from the vehicle control system.
 6. The air conditioner for a rail vehicle according to claim 1, wherein the air conditioning control device causes the refrigeration cycle device to execute the cleaning operation on a basis of at least time information obtained from the vehicle control system.
 7. The air conditioner for a rail vehicle according to claim 1, wherein the air conditioning control device causes the refrigeration cycle device to execute the cleaning operation on a basis of at least date information obtained from the vehicle control system.
-