

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12415622

Kind Code

B2

Date of Patent

September 16, 2025

Inventor(s)

Nicholson; James Garret et al.

Spacecraft servicing devices and related assemblies, systems, and methods

Abstract

Spacecraft servicing devices or pods and related methods may include a body configured to be deployed from a host spacecraft at a location adjacent a target spacecraft and at least one spacecraft servicing component configured to perform at least one servicing operation on the target spacecraft. The spacecraft servicing device may include a thruster assembly coupled to a boom arm, where the boom arm is configured to alter an orientation of the thruster assembly as the boom arm is rotated about the spacecraft body and a docking device.

Inventors: Nicholson; James Garret (Broadlands, VA), Treachler; Daniel Carl (Leesburg, VA), Ortiz; Oliver Benjamin (Beltsville, MD), Reavill; James Dulin (Irving, TX), Hekman; Benjamin Michael (Percellville, VA), Sullivan; Robert Bryan (Chantilly, VA), Niederstrasser; Carlos Guillermo (Reston, VA), Lieberbaum; Mark (Arlington, VA), Glogowski; Michael Joseph (Leesburg, VA), Llorens; William A. (Herndon, VA), Chow; Kenneth Siu-Kin (Great Falls, VA), Cipollo; Peter Michael (Arlington, VA)

Applicant: Northrop Grumman Systems Corporation (Falls Church, VA)

Family ID: 1000008820017

Assignee: Northrop Grumman Systems Corporation (Falls Church, VA)

Appl. No.: 18/206592

Filed: June 06, 2023

Prior Publication Data

Document Identifier

Publication Date

US 20240158103 A1

May. 16, 2024

Related U.S. Application Data

Publication Classification

Int. Cl.: **B64G1/10** (20060101); **B64G1/24** (20060101); **B64G1/26** (20060101); **B64G1/40** (20060101); **B64G1/64** (20060101)

U.S. Cl.:

CPC **B64G1/1078** (20130101); **B64G1/2427** (20230801); **B64G1/26** (20130101); **B64G1/264** (20230801); **B64G1/40** (20130101); **B64G1/402** (20130101); **B64G1/4024** (20230801); **B64G1/643** (20230801); **B64G1/646** (20130101); **B64G1/6462** (20230801); **B64G1/6464** (20230801); B64G1/2429 (20230801)

Field of Classification Search

CPC: B64G (1/1078); B64G (1/26); B64G (1/264)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3268091	12/1965	Melton	N/A	N/A
3508723	12/1969	Warren	N/A	N/A
3662973	12/1971	Collins	N/A	N/A
4219171	12/1979	Rudmann	N/A	N/A
4298178	12/1980	Hujsak	N/A	N/A
4381092	12/1982	Barker	N/A	N/A
4391423	12/1982	Pruett	N/A	N/A
4431333	12/1983	Chandler	N/A	N/A
4449684	12/1983	Hinds	N/A	N/A
4588150	12/1985	Bock	N/A	N/A
4657211	12/1986	Fuldner	N/A	N/A
4664344	12/1986	Harwell	N/A	N/A
4750692	12/1987	Howard	N/A	N/A
4880187	12/1988	Rourke	N/A	N/A
4898348	12/1989	Kahn	N/A	N/A
4955559	12/1989	Kaminskas	N/A	N/A
5005786	12/1990	Okamoto	N/A	N/A
5040749	12/1990	Johnson	N/A	N/A
5094410	12/1991	Johnson	N/A	N/A
5104070	12/1991	Johnson	N/A	N/A
5125601	12/1991	Monford, Jr.	N/A	N/A
5169094	12/1991	Maute	N/A	N/A
5299764	12/1993	Scott	N/A	N/A
5349532	12/1993	Tilley	N/A	N/A

5364046	12/1993	Dobbs	N/A	N/A
5372340	12/1993	Ihara	N/A	N/A
5429328	12/1994	Dobbs	N/A	N/A
5449211	12/1994	Monford, Jr.	N/A	N/A
5490075	12/1995	Howard	N/A	N/A
5511748	12/1995	Scott	N/A	N/A
5735488	12/1997	Schneider	N/A	N/A
5803407	12/1997	Scott	N/A	N/A
5806802	12/1997	Scott	N/A	N/A
5813632	12/1997	Taylor	N/A	N/A
6017000	12/1999	Scott	N/A	N/A
6032904	12/1999	Hosick	N/A	N/A
6045094	12/1999	Rivera	N/A	N/A
6082678	12/1999	Maute	N/A	N/A
6264145	12/2000	Maute	N/A	N/A
6272751	12/2000	McMeekin	N/A	N/A
6275751	12/2000	Stallard	N/A	N/A
6296207	12/2000	Tilley	N/A	N/A
6299107	12/2000	Kong	N/A	N/A
6322023	12/2000	Soranno	N/A	N/A
6330987	12/2000	Scott	N/A	N/A
6354540	12/2001	Lewis	N/A	N/A
6378810	12/2001	Pham	N/A	N/A
6484973	12/2001	Scott	N/A	N/A
6523784	12/2002	Steinsiek	N/A	N/A
6565043	12/2002	Wittmann	N/A	N/A
6669148	12/2002	Anderman	N/A	N/A
6742745	12/2003	Tchoryk	N/A	N/A
6840481	12/2004	Gurevich	N/A	N/A
6843446	12/2004	Scott	N/A	N/A
6845303	12/2004	Byler	N/A	N/A
6866232	12/2004	Finney	N/A	N/A
6945500	12/2004	Wingo	N/A	N/A
6969030	12/2004	Jones	N/A	N/A
7070151	12/2005	D'Ausilio et al.	N/A	N/A
7104505	12/2005	Tchoryk	N/A	N/A
7114682	12/2005	Kistler	244/172.5	B64G 1/402
7118075	12/2005	Schubert	N/A	N/A
7163179	12/2006	Taylor	N/A	N/A
7207525	12/2006	Bischof	N/A	N/A
7216833	12/2006	D'Ausilio et al.	N/A	N/A
7216834	12/2006	D'Ausilio et al.	N/A	N/A
7240879	12/2006	Cepollina	N/A	N/A
7293743	12/2006	Cepollina	N/A	N/A
7370834	12/2007	Scott	N/A	N/A
7438264	12/2007	Cepollina	N/A	N/A
7461818	12/2007	D'Ausilio et al.	N/A	N/A
7484690	12/2008	D'Ausilio et al.	N/A	N/A
7513459	12/2008	Cepollina	N/A	N/A
7513460	12/2008	Cepollina	N/A	N/A

7559508	12/2008	Taylor	N/A	N/A
7575199	12/2008	D'Ausilio et al.	N/A	N/A
7575200	12/2008	Behrens	N/A	N/A
7588213	12/2008	D'Ausilio et al.	N/A	N/A
7611096	12/2008	D'Ausilio et al.	N/A	N/A
7611097	12/2008	D'Ausilio et al.	N/A	N/A
7624950	12/2008	D'Ausilio et al.	N/A	N/A
7815149	12/2009	Howard	N/A	N/A
7823837	12/2009	Behrens	N/A	N/A
7828249	12/2009	Ritter	N/A	N/A
7857261	12/2009	Tchoryk, Jr.	N/A	N/A
7861974	12/2010	Hays	N/A	N/A
7861975	12/2010	Behrens	N/A	N/A
7992824	12/2010	Tchoryk, Jr.	N/A	N/A
8006937	12/2010	Romano	N/A	N/A
8006938	12/2010	Behrens	N/A	N/A
8016242	12/2010	Baumann	N/A	N/A
8052092	12/2010	Atmur	N/A	N/A
8056864	12/2010	Hays	N/A	N/A
8074935	12/2010	Gryniewski	N/A	N/A
8181911	12/2011	Gryniewski	N/A	N/A
8196870	12/2011	Gryniewski	N/A	N/A
8205838	12/2011	Moorer, Jr.	N/A	N/A
8226046	12/2011	Poulos	N/A	N/A
8240613	12/2011	Ritter	N/A	N/A
8245370	12/2011	Ritter	N/A	N/A
8333347	12/2011	Ritter	N/A	N/A
8412391	12/2012	Paluszek	N/A	N/A
8448904	12/2012	Gryniewski	N/A	N/A
8628044	12/2013	Poulos	N/A	N/A
8899527	12/2013	Allen	N/A	N/A
9108747	12/2014	Roberts	N/A	N/A
9284073	12/2015	Bigelow	N/A	N/A
9302793	12/2015	Ghofranian	N/A	N/A
9321175	12/2015	Smith	N/A	N/A
9387942	12/2015	Celerier	N/A	N/A
9399295	12/2015	Roberts	N/A	N/A
9434485	12/2015	Lehocki	N/A	N/A
9463883	12/2015	Bigelow	N/A	N/A
9527607	12/2015	Celerier	N/A	N/A
9573703	12/2016	Celerier	N/A	N/A
9663250	12/2016	Gravseth	N/A	B64G 1/646
9663251	12/2016	Munir	N/A	N/A
9809327	12/2016	Rossettini	N/A	N/A
9878806	12/2017	Helmer	N/A	N/A
9914550	12/2017	Price	N/A	N/A
9926087	12/2017	Doubrere	N/A	N/A
9950424	12/2017	Roberts	N/A	N/A
10005180	12/2017	Roberts	N/A	N/A
10183765	12/2018	Bibighaus	N/A	N/A

10232959	12/2018	Moro	N/A	N/A
10407184	12/2018	Mori	N/A	N/A
10464694	12/2018	Schwarz	N/A	N/A
10569909	12/2019	Ho	N/A	N/A
10577130	12/2019	Parish	N/A	N/A
10850869	12/2019	Nicholson	N/A	N/A
10994867	12/2020	Nicholson	N/A	B64G 1/643
11124318	12/2020	Nicholson	N/A	N/A
11358739	12/2021	Faber	N/A	N/A
11492148	12/2021	Nicholson	N/A	B64G 1/244
11685554	12/2022	Nicholson	244/172.5	B64G 1/40
11718420	12/2022	Nicholson	244/172.5	B64G 1/26
11724826	12/2022	Nicholson	244/172.5	B64G 1/6462
12240630	12/2024	Nicholson	N/A	B64G 1/4024
2001/0017337	12/2000	Holemans	N/A	N/A
2002/0063188	12/2001	Steinsiek	N/A	N/A
2003/0029969	12/2002	Turner	N/A	N/A
2003/0192995	12/2002	Tchoryk	N/A	N/A
2004/0026571	12/2003	Scott	N/A	N/A
2004/0245404	12/2003	Kerstein	N/A	N/A
2004/0245407	12/2003	D'Ausilio et al.	N/A	N/A
2005/0001102	12/2004	Schubert	N/A	N/A
2005/0040282	12/2004	Wingo	N/A	N/A
2005/0103940	12/2004	Bischof	N/A	N/A
2005/0258311	12/2004	Scott	N/A	N/A
2006/0145023	12/2005	Babb	N/A	N/A
2006/0145024	12/2005	Kosmas	N/A	N/A
2006/0151671	12/2005	Kosmas	N/A	N/A
2007/0051854	12/2006	Behrens	N/A	N/A
2007/0114334	12/2006	D'Ausilio et al.	N/A	N/A
2007/0125910	12/2006	Cepollina	N/A	N/A
2007/0164164	12/2006	Cepollina	N/A	N/A
2007/0228219	12/2006	Behrens	N/A	N/A
2007/0228220	12/2006	Behrens	N/A	N/A
2008/0060460	12/2007	Smith	N/A	N/A
2008/0078886	12/2007	Foster	N/A	N/A
2008/0121759	12/2007	Behrens	N/A	N/A
2008/0237400	12/2007	Gryniewski	N/A	N/A
2008/0265098	12/2007	Connelly	N/A	N/A
2009/0001221	12/2008	Collyer	N/A	N/A
2009/0166476	12/2008	Termini	N/A	N/A
2010/0038491	12/2009	Cepollina	244/172.5	B64G 1/4024
2011/0121139	12/2010	Poulos	N/A	N/A
2011/0147532	12/2010	Chaix	N/A	N/A
2011/0180670	12/2010	D'Ausilio et al.	N/A	N/A
2011/0192936	12/2010	Knirsch	N/A	N/A
2012/0112009	12/2011	Gryniewski	N/A	N/A
2012/0286098	12/2011	Poulos	N/A	N/A
2012/0292449	12/2011	Levin	N/A	N/A
2012/0325972	12/2011	Gryniewski	N/A	N/A

2013/0103193	12/2012	Roberts	N/A	N/A
2013/0292516	12/2012	Celerier	N/A	N/A
2013/0313369	12/2012	Celerier	N/A	N/A
2014/0027577	12/2013	Darooka	N/A	N/A
2014/0107865	12/2013	Griffith, Sr.	N/A	N/A
2014/0239125	12/2013	Aston	244/172.3	B64G 1/402
2014/0361123	12/2013	Celerier	N/A	N/A
2014/0361124	12/2013	Celerier	N/A	N/A
2015/0008288	12/2014	Bigelow	N/A	N/A
2015/0008290	12/2014	Bigelow	N/A	N/A
2015/0053823	12/2014	Bigelow	N/A	N/A
2015/0097084	12/2014	Szabo	N/A	N/A
2015/0314893	12/2014	Rembala	N/A	N/A
2016/0039543	12/2015	Roberts	N/A	N/A
2016/0039544	12/2015	Roberts	N/A	N/A
2016/0176545	12/2015	Munir	N/A	N/A
2016/0185471	12/2015	Blincow	N/A	N/A
2016/0207641	12/2015	Myers	N/A	B64G 1/4021
2016/0257435	12/2015	Coraboeuf	N/A	N/A
2017/0081048	12/2016	Glogowski	N/A	N/A
2017/0113818	12/2016	Mori	N/A	N/A
2017/0129627	12/2016	Moro	N/A	N/A
2017/0283096	12/2016	Kawahara	N/A	B64G 1/4022
2017/0342943	12/2016	Watts	N/A	N/A
2017/0349302	12/2016	Bibighaus	N/A	N/A
2018/0029727	12/2017	Doubrere	N/A	N/A
2018/0072436	12/2017	Ishikawa	N/A	N/A
2018/0087683	12/2017	Raven	N/A	N/A
2018/0118377	12/2017	Garber	N/A	N/A
2018/0148197	12/2017	Halsband	N/A	N/A
2018/0186476	12/2017	Poncet	N/A	N/A
2018/0251240	12/2017	Reitman	N/A	N/A
2018/0251242	12/2017	Gorakavi	N/A	N/A
2018/0297722	12/2017	Agathon-Burton	N/A	N/A
2018/0297723	12/2017	Sorensen	N/A	N/A
2019/0023420	12/2018	Nicholson	N/A	N/A
2019/0023421	12/2018	Nicholson	N/A	N/A
2019/0023422	12/2018	Nicholson	N/A	N/A
2019/0135456	12/2018	Wingo	N/A	N/A
2019/0300207	12/2018	Izumisawa	N/A	N/A
2020/0223568	12/2019	Nicholson	N/A	N/A
2021/0237909	12/2020	Nicholson	N/A	B64G 1/26
2021/0253277	12/2020	Nicholson	N/A	N/A
2022/0002004	12/2021	Nicholson	N/A	N/A
2023/0058379	12/2022	Nicholson	N/A	B64G 1/646
2023/0271725	12/2022	Nicholson	N/A	B64G 1/1078
2023/0365275	12/2022	Nicholson	N/A	B64G 1/643

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
------------	------------------	---------	-----

103587726	12/2013	CN	N/A
104071357	12/2013	CN	N/A
0541052	12/1992	EP	N/A
0741655	12/1995	EP	N/A
0937644	12/1998	EP	N/A
1654159	12/2005	EP	N/A
2134606	12/2008	EP	N/A
2522577	12/2011	EP	N/A
3083406	12/2015	EP	N/A
3156335	12/2016	EP	N/A
3186151	12/2016	EP	N/A
3248737	12/2016	EP	N/A
H01282098	12/1988	JP	N/A
H02182599	12/1989	JP	N/A
H05201395	12/1992	JP	N/A
H08216999	12/1995	JP	N/A
2015174647	12/2014	JP	N/A
22013121126	12/2014	JP	N/A
101808553	12/2016	KR	N/A
2586437	12/2015	RU	N/A
2601522	12/2015	RU	N/A
1987004992	12/1986	WO	N/A
1994029927	12/1993	WO	N/A
2005110847	12/2004	WO	N/A
2005118394	12/2004	WO	N/A
2007117373	12/2006	WO	N/A
2008109993	12/2007	WO	N/A
2008134321	12/2007	WO	N/A
2013071438	12/2012	WO	N/A
2014024199	12/2013	WO	N/A
2015190527	12/2014	WO	N/A
2016030890	12/2015	WO	N/A
2016181079	12/2015	WO	N/A

OTHER PUBLICATIONS

Written Opinion of the International Search Authority for International Application No. PCT/US2018/043188 dated Oct. 17, 2018, 8 pages. cited by applicant

Written Opinion of the International Search Authority for International Application No. PCT/US2018/043182 dated Sep. 24, 2018, 7 Pages. cited by applicant

Written Opinion of the International Search Authority for International Application No. PCT/US2018/043180 dated Oct. 12, 2018, 8 pages. cited by applicant

International Search Report for International Application No. PCT/US2018/043188 dated Oct. 17, 2018, 5 pages. cited by applicant

International Search Report for International Application No. PCT/US2018/043182 dated Sep. 24, 2018, 5 pages. cited by applicant

International Search Report for International Application No. PCT/US2018/043180 dated Oct. 12, 2018, 5 pages. cited by applicant

Weise et al., “An Intelligent Building Blocks Concept for On-Orbit-Satellite Servicing”, Turin, Italy, Sep. 4-6, 2012. cited by applicant

Sellmaier et al., “On-Orbit Servicing Missions: Challenges and Solutions for Spacecraft

Operations”, SpaceOps 2010 Conference, AIAA 2010-2169, 2010. cited by applicant
Reintsema et al., “DEOS—The In-Flight Technology Demonstration of German Robotics Approach to Dispose Malfunctioned Satellites”, 2010, 8 pages. cited by applicant
Mukherjee, “Robotic Assembly-of-Space Assets; Architectures and Technologies” Future In-Space Operations (FISO) Teleconference, Jun. 27, 2018, 2018 NASA Jet Propulsion Laboratory California Institute of Technology, 41 pages. cited by applicant
Medina et al., “Towards a standardized grasping and refuelling on-orbit servicing for geo spacecraft”, Acta Astronautica, vol. 134, 2017, pp. 1-10. cited by applicant
IBOSS13 a modular approach towards enhanced future space systems and flexibility, <http://www.iboss-satellites.com/iboss/>, http://exchange.ciros-engineering.com/download/public/iBOSS_IAC-2017.wmv. cited by applicant
FEHSE “Automated Rendezvous and Docking of Spacecraft”, 15 pages, Cambridge University Press 2003. cited by applicant
DLR, iBOSS-intelligent Building-Blocks for On-Orbit Satellite Servicing and Assembly; German Aerospace Center (DLR) Space Administration, 2017, 2 pages. cited by applicant

Primary Examiner: Sanderson; Joseph W

Attorney, Agent or Firm: BK RIP LLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation of U.S. patent application Ser. No. 17/107,095, filed Nov. 30, 2020, which application is a continuation of U.S. patent application Ser. No. 16/041,709, filed Jul. 20, 2018, which application claims the benefit under 35 U.S.C. § 119(e) of U.S. Provisional Patent Application Ser. No. 62/535,747, filed Jul. 21, 2017, the disclosure of each of which is hereby incorporated herein in its entirety by this reference.

TECHNICAL FIELD

(1) Embodiments of the present disclosure generally relate to servicing devices for spacecraft (e.g., satellites). In particular, embodiments of the present disclosure relate to servicing devices including one or more detachable servicing devices (e.g., pods or modules) and related devices, systems, assemblies, and methods.

BACKGROUND

(2) Thousands of spacecraft orbit the Earth for performing various functions including, for example, telecommunication, GPS navigation, weather forecasting, and mapping. Like all machines, spacecraft periodically require servicing to extend their functioning life span. Servicing may include, for example, component repair, refueling, orbit raising, station-keeping, momentum balancing, or other maintenance. To accomplish this, a servicing spacecraft may be sent into orbit to dock with a client spacecraft requiring maintenance, and subsequent to docking, perform life extending maintenance on the client spacecraft. Without life extension maintenance, these spacecraft may fall out of service, and replacement is generally extraordinarily expensive and can have a lead time of years.

(3) Various patents and publications have considered such spacecraft servicing and related features and issues, including U.S. Pat. Nos. 3,508,723, 4,219,171, 4,391,423, 4,588,150, 4,664,344, 4,898,348, 5,005,786, 5,040,749, 5,094,410, 5,299,764, 5,364,046, 5,372,340, 5,490,075, 5,511,748, 5,735,488, 5,803,407, 5,806,802, 6,017,000, 6,299,107, 6,330,987, 6,484,973, 6,523,784, 6,742,745, 6,843,446, 6,945,500, 6,969,030, 7,070,151, 7,104,505, 7,207,525,

7,216,833, 7,216,834, 7,240,879, 7,293,743, 7,370,834, 7,438,264, 7,461,818, 7,484,690, 7,513,459, 7,513,460, 7,575,199, 7,588,213, 7,611,096, 7,611,097, 7,624,950, 7,815,149, 7,823,837, 7,828,249, 7,857,261, 7,861,974, 7,861,975, 7,992,824, 8,006,937, 8,006,938, 8,016,242, 8,056,864, 8,074,935, 8,181,911, 8,196,870, 8,205,838, 8,240,613, 8,245,370, 8,333,347, 8,412,391, 8,448,904, 8,899,527, 9,108,747, 9,302,793, 9,321,175, and 9,399,295; U.S. Patent Pub. Nos. 2004/0026571, 2006/0145024, 2006/0151671, 2007/0228220, 2009/0001221, 2012/0112009, 2012/0325972, 2013/0103193, 2015/0008290, 2015/0314893, 2016/0039543, and 2016/0039544; European Patent Nos. EP 0541052, 0741655 B1, 0741655 B2, and 1654159; PCT Pub. Nos. 2005/110847, 2005/118394, 2014/024199, and 2016/030890; Japan Patent No. JPH01282098; *Automated Rendezvous and Docking of Spacecraft*, Fehse, Wigbert, Cambridge University Press (2003); *On-Orbit Servicing Missions: Challenges and Solutions for Spacecraft Operations*, Sellmaier, F., et al., SpaceOps 2010 Conference, AIAA 2010-2159 (2010); and *Towards a Standardized Grasping and Refueling On—Orbit Servicing for Geo Spacecraft*, Medina, Alberto, et al., Acta Astronautica 134 1-10 (2017); *DEOS—The In-Flight Technology Demonstration of German's Robotics Approach to Dispose Malfunctioned Satellites*, Reintsema, D., et al., the disclosure of each of which is hereby incorporated herein in its entirety by this reference.

(4) However, reliable and robust servicing spacecraft that provide a variety of servicing options for spacecraft may be cost prohibitive. On the other hand, lower cost options may not be able to provide a variety of servicing options and reliable and robust servicing features necessary for many applications.

BRIEF SUMMARY

(5) Embodiments of the present disclosure include a spacecraft servicing device including a body configured to be deployed from a host spacecraft at a location adjacent a target spacecraft, where the host spacecraft houses a plurality of spacecraft servicing devices, and at least one spacecraft servicing component configured to perform at least one servicing operation on the target spacecraft while being coupled to the target spacecraft. The at least one spacecraft servicing component comprises a thruster assembly configured to alter at least one of an orbit, a velocity, or a momentum of the target spacecraft. The thruster assembly comprises at least one thruster. The spacecraft servicing device further includes a communication device configured to receive data relating to the at least one of an orbit, a velocity, or a momentum of the target spacecraft from a location remote from the spacecraft servicing device.

(6) Embodiments of the present disclosure further include a spacecraft servicing pod having a body configured to be deployed from a host spacecraft, a thruster assembly coupled to the body, the thruster assembly configured to alter at least one of an orbit, a velocity, or a momentum of the target spacecraft after being coupled to the target spacecraft, and a communication device configured to receive data relating to the at least one of an orbit, a velocity, or a momentum of the target spacecraft from a location remote from the spacecraft servicing device.

(7) Embodiments of the present disclosure further include a spacecraft servicing pod having a body configured to be deployed from a host spacecraft housing a plurality of spacecraft servicing pods at a location adjacent a target spacecraft, a coupling mechanism coupled to the body and configured to couple the pod to the target spacecraft at the location adjacent the target spacecraft, and at least one spacecraft servicing component configured to perform at least one servicing operation on the target spacecraft. The coupling mechanism comprises at least one movable coupling configured to rotate the body relative to the target spacecraft when the spacecraft servicing pod is coupled to the target spacecraft.

(8) Embodiments of the present disclosure further include a spacecraft servicing system comprising a body configured to be deployed from a host spacecraft, a coupling mechanism attached to the body and configured to couple the pod to a target spacecraft, and a thruster assembly positioned on a single boom arm extending away from the body configured to alter at least one of an orbit, a

velocity, or a momentum of the target spacecraft.

(9) Embodiments of the present disclosure further include a spacecraft servicing device including a body configured to be deployed from a host spacecraft at a location adjacent a target spacecraft, where the host spacecraft houses a plurality of spacecraft servicing devices, and a thruster assembly coupled to the body. The thruster assembly is configured to alter at least one of an orbit, a velocity, or a momentum of the target spacecraft when coupled to the target spacecraft.

(10) Embodiments of the present disclosure further include a spacecraft servicing pod having a body configured to be deployed from a host spacecraft housing a plurality of spacecraft servicing pods at a location adjacent a target spacecraft, a coupling mechanism coupled to the body and configured to couple the pod to the target spacecraft at the location adjacent the target spacecraft, and at least one spacecraft servicing component configured to perform at least one servicing operation on the target spacecraft. A total mass of the spacecraft servicing pod is less than 500 kg.

(11) Embodiments of the present disclosure further include a method of servicing a spacecraft. The method includes transferring a pod of a spacecraft servicing device to the spacecraft with the spacecraft servicing device, coupling the pod to the spacecraft while the pod is in contact with the spacecraft servicing device, after being coupled to the spacecraft, altering at least one of an orbit or a velocity of the spacecraft with a thruster assembly of the spacecraft servicing device, and receiving data relating to the at least one of an orbit, a velocity, or a momentum of the spacecraft from a location remote from the pod with a communications device.

(12) The above summary is not intended to describe each illustrated embodiment or every implementation of the present disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The drawings included in the present application are incorporated into, and form part of, the specification. They illustrate embodiments of the present disclosure and, along with the description, serve to explain the principles of the disclosure. The drawings are only illustrative of certain embodiments and do not limit the disclosure.

(2) FIG. 1A is a simplified schematic view of a spacecraft servicing system and a target spacecraft to be serviced according to one or more embodiments of the present disclosure.

(3) FIG. 1B depicts an embodiment of a fuel tank supply device that may be implemented on one or more devices of the spacecraft servicing system of FIG. 1A.

(4) FIG. 2A is a simplified schematic view of a spacecraft servicing device according to one or more embodiments of the present disclosure.

(5) FIG. 2B is a simplified schematic view of a spacecraft servicing device according to one or more embodiments of the present disclosure.

(6) FIGS. 2C through 2K depict various embodiments of coupling mechanisms according to one or more embodiments of the present disclosure.

(7) FIG. 2L is a perspective view of a spacecraft servicing device according to one or more embodiments of the present disclosure.

(8) FIG. 3 is a simplified schematic view of a mission extension pod according to one or more embodiments of the present disclosure.

(9) FIG. 4 is a simplified schematic view of a mission extension pod attached to a spacecraft in two thrust vector orientations according to one or more embodiments of the present disclosure.

(10) FIG. 5 is another simplified schematic view of a mission extension pod attached to a spacecraft in two thrust vector orientations according to one or more embodiments of the present disclosure.

(11) FIG. 6 is a simplified schematic view of a resupply device of a spacecraft servicing system

according to one or more embodiments of the present disclosure.

(12) FIGS. 7 through 10 depict various embodiments of spacecraft servicing devices including a number of pods coupled to the spacecraft servicing devices according to one or more embodiments of the present disclosure.

DETAILED DESCRIPTION

(13) The illustrations presented herein are not meant to be actual views of any particular device. The illustrations presented herein are not meant to be actual views of any particular device, assembly, system, or component thereof, but are merely idealized representations employed to describe illustrative embodiments. The drawings are not necessarily to scale.

(14) As used herein, the term “substantially” in reference to a given parameter means and includes to a degree that one skilled in the art would understand that the given parameter, property, or condition is met with a small degree of variance, such as within acceptable manufacturing tolerances. For example, a parameter that is substantially met may be at least about 90% met, at least about 95% met, or even at least about 99% met.

(15) Embodiments of the disclosure relate generally to spacecraft (e.g., satellite or other vehicle) servicing devices for providing life extending service to spacecraft (otherwise referred to as “clients”). The spacecraft servicing systems, assemblies, or devices (e.g., spacecraft, vehicles) may include one or more deployable spacecraft servicing devices, pods, or modules (e.g., a mission extension pod (MEP)) that are initially attached to the spacecraft servicing device (e.g., a MEP mother ship (MEPM) or mission robotic vehicle (MRV)). The spacecraft servicing device may then transfer the pods to/from the client spacecraft. A spacecraft servicing resupply device may provide additional pods for the spacecraft servicing device.

(16) The pods (e.g., five pods, six pods, ten pods, fifteen pods, or more provided by the mother ship) may be provided to the target spacecraft (e.g., may be individually deployed and/or attached to the spacecraft) in order to supply life extending service to spacecraft including, for example, component repair, refueling, orbit raising or other modifications (e.g., deorbit), relocation, inclination pull-down, station-keeping, momentum balancing, momentum adjustment, replenishment of supplies, providing new supplies or componentry, and/or other maintenance. In some embodiments, the pods may be utilized to adjust the velocity, positioning, and/or orbit of a spacecraft including station-keeping, inclination pull-down, orbit relocation, and disposal. In some embodiments the pods may be used to manage the momentum and provide attitude control of a spacecraft. In some embodiments, the pods may supply replacement or additional components. For example, the pods may be equipped with components (e.g., flight control components, avionic components, such as a reaction wheel, motor components, communication components, power system components, sensor components, optic components, thermal control components, telemetry components, combinations thereof, etc.) that may be utilized to replace failing componentry, supplement existing componentry, and/or add componentry and selected functioning and features to the spacecraft. By way of further example, the pods may include telemetric features, such as, for example, an optical device that measures the position of stars using photocells or a camera (e.g., a star tracker). Such a device or devices may be supplied on the pod to monitor and/or modify characteristics of travel of the spacecraft (e.g., attitude).

(17) In some embodiments, the spacecraft servicing device may deploy and attach one or more of the pods to the spacecraft in need of service using robotic spacecraft servicing devices (e.g., one or more robotic arms capable of one or more degrees of freedom with one or more end effectors for various tasks) for in-orbit satellite servicing. For example, the spacecraft servicing device may deploy and attach one or more of the pods to a portion of the spacecraft (e.g., a separation ring, an engine, external appendage, or any other suitable mechanical attachment or coupling structure, or any other suitable mechanical attachment or coupling structure). In some embodiments, the spacecraft servicing device itself may perform some servicing tasks before, during, and/or after deployment of the pod to the spacecraft.

(18) The spacecraft servicing device travels in space to and between spacecraft and may install a mission extension pod onto spacecraft in need of servicing. In some embodiments, the spacecraft servicing device may attach the pod to the spacecraft and leave the pod attached for servicing. For example, the pod may be permanently attached to the spacecraft and essentially become another component of the spacecraft, which may or may not be in communication with the existing system of the spacecraft. In such embodiments, the pod may be configured to provide service over a selected amount of time (e.g., for short-term servicing and/or long-term servicing, such as, over minutes, weeks, months, years, or combinations thereof)). In some embodiments, the spacecraft servicing device or another similar device, may remove, replenish (e.g., refuel), and/or replace the pod after a selected amount of servicing. For example, a portion of the servicing systems (e.g., the spacecraft servicing device or another portion, such as the resupply device discussed below) may revisit the pod to resupply (e.g., refill, replenish, supplement, etc.) the pod with one or more consumables (e.g., fuel, gas, componentry, etc.). In some embodiments, the spacecraft servicing device may attach an additional device (e.g., tank) with such consumables to the pod. In some embodiments, the spacecraft servicing device may detach the pod from a spacecraft, replenish and/or refurbish the pod and reinstall it (e.g., reuse it) on the same or another spacecraft.

(19) Once attached to the spacecraft, the pod may be activated and provide, for example, orbit maintenance by altering the velocity (e.g., by providing a ΔV) including, for example, altering direction of the spacecraft (e.g., by altering the orbit, position, or another orientation of the spacecraft). By providing a change in velocity to the combined mass of the spacecraft and the mission extension pod, in the correct time and direction, the mission extension pod may extend the spacecraft's in-orbit life, for example, by replacing (e.g., completely replacing the propulsive functions of the spacecraft or by reducing the rate of spacecraft fuel consumption needed to maintain the desired velocity, position, and orbit. The mission extension pod may provide such a change in velocity to the spacecraft according to a schedule that is provided from data relating to the spacecraft. In some embodiments, data needed for the maneuver schedule may be pre-programmed into the mission extension pod. In some embodiments, such schedule and other data may be transmitted to the mission extension pod after the pod has been launched and/or coupled to the spacecraft. In some embodiments, the pod may be configured to only provide a thrust force (e.g., a relatively low-magnitude thrust force) to the spacecraft without otherwise interacting with other systems or attributes of the spacecraft. In some embodiments, the pod may be configured to provide a torque about the spacecraft so that the spacecraft is able to adjust its momentum. In other embodiments, the pod may provide other services (e.g., as discussed herein) and/or may be in at least partial communication with one or more systems or subsystems of the spacecraft.

(20) In some embodiments, a satellite servicing system may be configured to supply or resupply the spacecraft servicing device with pods, for example, once the number of pods on the spacecraft servicing device have been decreased or depleted with a mission extension pod supply or resupply device (MEPR). For example, once the supply of mission extension pods is decreased or depleted, the spacecraft servicing device may acquire a new supply of pods (e.g., five pods, six pods, ten pods, fifteen pods, or more) to continue offering life extension services to potential spacecraft.

(21) The mission extension pod resupply device (e.g., a spacecraft) may carry a number (e.g., 2, 3, 4, 5, or more pods) in order to rendezvous with the spacecraft servicing device and to supply the pods to the device. For example, the pod resupply device with the mission extension pods may be placed in a geosynchronous orbit (GEO) or other orbits while the spacecraft servicing device rendezvous to its location. Once the spacecraft servicing device approaches the mission extension pod resupply device, one or more devices on the spacecraft servicing device and/or the pod resupply device (e.g., robotic arms of the spacecraft servicing device) may relocate the mission extension pods from the mission extension pod resupply device to the spacecraft servicing device. In other embodiments, the pod resupply device may be configured to travel to the spacecraft servicing device. In other embodiments, one or more devices on the pod resupply device may be

configured to supply the pods to the spacecraft servicing device or the pod resupply device and the spacecraft servicing device may be configured to couple together or otherwise be placed in physical communication in order to transfer one or more of the pods.

(22) In some embodiments, the mission extension pod resupply device may provide additional supplies to or servicing of the spacecraft servicing device. For example, the pod resupply device may provide additional propellant for the spacecraft servicing device maneuvering as needed. In some embodiments, the pod resupply device may transfer propellant to the spacecraft servicing device by a refueling operation and/or by transferring tanks loaded with propellant from the resupply device to the servicing device (e.g., with one or more robotic arms on one or more of the spacecraft servicing device and the resupply device).

(23) In some embodiments, one or more of the spacecraft servicing device and the spacecraft for mission extension pod deliveries may be conducted with and/or comprise an Evolved Expendable Launch Vehicle (EELV) Secondary Payload Adaptor (ESPA or ESPA ring) class spacecraft, for example, such as those developed by Northrup Grumman, of Falls Church, VA, known as ESPASTMStar, or any other suitable type device, spacecraft, or launch vehicle that may be possible in an appropriate geosynchronous orbit or another orbits.

(24) In some embodiments, one or more devices or components of the satellite servicing system may be disposed of, for example, by transporting them from a select geosynchronous orbit to a geosynchronous graveyard orbit (e.g., for the spacecraft servicing device and/or mission extension pod resupply device) or by abandoning in place on the spacecraft (e.g., for the mission extension pods).

(25) FIG. 1A depicts a simplified schematic view of a spacecraft servicing system **10** where at least a portion of the spacecraft servicing system **10** may be operated to approach, capture, dock to, and/or service a device (e.g., another vehicle or spacecraft **20**). However, in some embodiments, a spacecraft servicing device **100** may be configured to approach the spacecraft **20** and to transfer one or more modules or pods **102** (e.g., mission extension pods **102**) to the spacecraft **20**, as discussed below in greater detail.

(26) Such a spacecraft **20** may be in low earth orbit, medium earth orbit, geosynchronous orbit, beyond geosynchronous orbit, or in another orbit around a body such as Earth. Spacecraft **20** may include components, such as, for example, an engine, a separation ring, and any other type of feature known and/or implemented in spacecraft fields (e.g., a propulsion device or system **22**, a fuel tank **24**, etc.), which can be used to provide for mechanical coupling of the pod **102** to the spacecraft **20**. For example, the engine may be a liquid apogee engine, solid fuel motor, thruster, or other type of engine or motor. The engine may be positioned on the zenith deck of the spacecraft **20**, which, in the case of a spacecraft orbiting the Earth, is a deck of the spacecraft substantially positioned opposite the Earth.

(27) As shown in FIG. 1A, the spacecraft servicing device **100** may be a separate spacecraft designed to approach and service the spacecraft **20**. Spacecraft servicing device **100** may facilitate providing services to the spacecraft **20** including station-keeping, orbital raising, momentum adjustment (e.g., unloading momentum about one or more axes), attitude control, relocation, deorbit, refueling, repair, inclination pull-down, or other services that may be provided on-orbit. The spacecraft servicing device **100** includes one or more deployable pods or modules **102** that are initially attached to the spacecraft servicing device **100**. The pods **102** may be provided to spacecraft **20** (e.g., may be deployed and/or attached to the spacecraft) and may include servicing componentry **103** (e.g., only shown in one instant of the pods **102** for clarity) in order to service (e.g., to supply life extending service to spacecraft **20**) including, for example, component repair, replacement, and/or addition, refueling, orbit raising, station-keeping, momentum balancing, replenishment of supplies, providing new supplies, and/or other maintenance.

(28) As depicted in FIG. 1A, at least one pod may be provided from the spacecraft servicing device **100** and coupled to the spacecraft **20** (e.g., proximate or along an axis extending through the center

of mass of the spacecraft) in order to supply such servicing.

(29) In some embodiments, the spacecraft servicing system **10** may include a mission extension pod supply or resupply device **30** configured to supply or resupply the spacecraft servicing device **100** with pods **102**, for example, once the number of pods **102** on the spacecraft servicing device **100** have been decreased or depleted. For example, once the supply of mission extension pods **102** is decreased or depleted, the spacecraft servicing device **100** may acquire a new supply of pods **102** (e.g., five pods, ten pods, fifteen pods, or more) to continue offering life extension services to potential spacecraft **20**. In some embodiments, the pod resupply device **30** with the mission extension pods **102** may be placed in a geosynchronous orbit (GEO) while spacecraft servicing device **100** rendezvous to its location. Once the spacecraft servicing device **100** approaches mission extension pod resupply device **30**, one or more devices on one or both of the spacecraft servicing device **100** and the pod resupply device **30** (e.g., robotic arms on the spacecraft servicing device **100** discussed below) may relocate one or more of the mission extension pods **102** from the mission extension pod resupply device **30** to the spacecraft servicing device **100**. In some embodiments, one of the pod resupply device **30** and the spacecraft servicing device **100** may be configured to retain the other in order to relocate the mission extension pods **102**. For example, the spacecraft servicing device **100** may approach the pod resupply device **30** and dock or otherwise engage with the resupply device **30**. Once docked, the spacecraft servicing device **100** may transfer one or more of pods **102** (e.g., using the robotic arms) from the resupply device **30** to the spacecraft servicing device **100**. The spacecraft servicing device **100** may then undock and deploy more pods to other devices. In other embodiments, the pod resupply device **30** may be configured to travel to the spacecraft servicing device **100**. In other embodiments, one or more devices on the pod resupply device **30** (e.g., robotic arms) may be configured to supply the pods **102** to the spacecraft servicing device **100**.

(30) In order to position the pods **102** on the target spacecraft **20**, the spacecraft servicing device **100** may position and store the pods **102** within reach of one or more mechanisms **122** (FIG. 2A) configured to the position, move, and/or install the pods. As discussed below, the mechanism may comprise one or more robotic arms **122** and/or another type of deployment device (e.g., coupling mechanism), such as an extendable and/or expandable boom, similar to deployment device **160** discussed below, that is configured to secure the spacecraft servicing device **100** to the pods **102** as discussed below. In some embodiments, the one or more robotic arms **122** may comprise one or more degrees of freedom enabling movement of the arm **122** along one or more axes of movement. For example, the arm **122** may comprise an extendable boom in some embodiments (e.g., similar to the deployment device **160** discussed below) that is translatable along one axis of movement or a device being capable of rotating and/or translating along one or more axes of movement. If reach is insufficient with a first single mechanism (e.g., an arm), optionally, a second mechanism (e.g., a second arm or some other device capable of moving or reorienting the pods **102**) may be implemented to move the pods **102** within reach of the first mechanism used to install pod **102** onto the target spacecraft **20**.

(31) For example, the pods **102** may be positioned on or in structure of the spacecraft servicing device **100** within reach of the robotic arm(s). If reach is insufficient with a single arm, an optional second arm or other device is used to move pod **102** within reach of the other robotic arm used to install pod **102** onto the target spacecraft **20**.

(32) In some embodiments, the pods **102** may be positioned on one or more separable structures within reach of the robotic arm(s). Once the pods **102** are depleted (e.g., entirely depleted) the separable structures may be detached from the spacecraft servicing device **100**. In such an embodiment, the fuel consumption of the spacecraft servicing device **100** may be reduced for later rendezvous and servicing activities.

(33) In some embodiments, the pods **102** may be carried on another device (e.g., a pod resupply device **30** that launches with the spacecraft servicing device **100**) and then the pods **102** may be

transferred to the spacecraft servicing device **100** after launch. For example, the spacecraft servicing device **100** may be used to tug the pod resupply device **30** to a geosynchronous orbit or other orbits and then the vehicles may separate. The spacecraft servicing device **100** may dock with the pod resupply device **30** using a docking mechanism on the spacecraft servicing device **100** and complementary structure or devices on the pod resupply device **30**. Once docked, robotic arm(s) on the spacecraft servicing device **100** may transfer one or more pods **102** from the pod resupply device **30** to stow locations on the spacecraft servicing device **100**. In this manner, the total mass of the spacecraft servicing device **100** is minimized for its recurring transits and rendezvous with target spacecraft **20** resulting in minimized fuel use over the life cycle of the mission. The pod resupply device **30** may be cooperatively controlled to place it in desired orbit locations for the spacecraft servicing device **100** to return and resupply the pods **102**.

(34) As discussed above, a portion of the system **10** (e.g., the pods **102**, the spacecraft servicing device **100**, and/or the resupply device **30**) may couple with another portion of the system **10** or to an external device (e.g., the pods **102**, the spacecraft servicing device **100**, and/or the spacecraft **20**) to supply (e.g., refill, replenish, supplement, etc.) the device with one or more consumables (e.g., fuel, gas, componentry, etc.). In some embodiments, such supplies may be supplied in an additional external tank attached to the device and/or may be supplied through a replacement (e.g., refueling) proceeding using existing components.

(35) Spacecraft will generally use a propellant (e.g., xenon, hydrazine) to maintain positioning and pointing during mission life. Depletion of this propellant generally results in end of mission life. In some embodiments, the spacecraft servicing device **100**, the pods **102**, and/or the resupply device **30** (a “fuel supply device”) may provide additional propellant to another portion of the system **10** or to an external device (e.g., the pods **102**, the spacecraft servicing device **100**, and/or the spacecraft **20** (a “target device”). In other embodiments, the fuel supply device may act to supply other fuels or fluids, such as, for example, a tank of high pressure xenon, hydrazine, helium, nitrogen tetroxide (NTO), a green propellant, combinations thereof, or any other suitable fuel. In some embodiments, the selection of propellant or fuel may be based on the application of the pod **102** (e.g., based on the configuration of the spacecraft **20**).

(36) FIG. 1B depicts an embodiment of such a fuel tank supply device **140** of the fuel supply device that may be implemented on one or more devices of the system **10** (FIG. 1A). As shown in FIG. 1B, in some embodiments, tubing **142** on the fuel tank supply device **140** may supply the fuel (e.g., high pressure xenon) in a tank **141** to a regulator **143** (e.g., a mechanical and/or electrical regulator). The regulator **143** may control (e.g., reduce) the pressure to a level that can be used by the system of the target device. Additional tubing **144** may be positioned downstream of the regulator **143** and may be connected to a mating adapter **145**. The mating adapter **145** may connect to a coupling (e.g., a service port valve) of the target device that is in communication with the fuel of the target device. In some embodiments, such mating adapters **145** of the fuel supply device may include connection fittings (e.g., quick disconnect fittings, cooperative service valves, and/or a simple mechanical service valve) for coupling with a tank of the target device. For example, such a mating adapter **145** may comprise a valve (e.g., a rotating valve or nut) that opens and closes the flow path. The mating adapter **145** may include a coupling member (e.g., a female coupling member) that may be attached to a coupling (e.g., valve port) of the target device (e.g., a complementary male coupling member).

(37) In some embodiments, the mating adapter **145** may be prepared by removing a cap or plug and the target device may be prepared by removing any structure (e.g., blankets and/or a cap or plug) over the coupling of the target device. Once prepared, the mating adapter **145** is mechanically attached to the service valve of the target device and one or more valves (e.g., on the target device and the fuel tank supply device **140**) may be opened and the pressure monitored (e.g., the pressure detecting in the systems of the target device). Decrease in this pressure may indicate that there is an incorrect mating between the adapter of the fuel tank supply device **140** and the mating adapter **145**.

of the fuel tank supply device **140**. Once the connection has been verified, the valve upstream of the mating adapter **145** may be moved to the open position and the tank **141** will supply fuel to the tank of the target device. In embodiments where the tank **141** of the fuel tank supply device **140** lacks pressure telemetry, systems of the target device may be utilized to monitor fuel use to determine if the tank **141** of the fuel tank supply device **140** is reaching depletion. As the tank **141** of the fuel tank supply device **140** nears depletion, the tank **141** of the fuel tank supply device **140** may be removed from communication by closing the valve upstream of the mating adapter **145** and the target device and a new tank may be connected to the target device (e.g., on the same fuel tank supply device **140** by replacing a previous tank or on a different fuel tank supply device, which may enable a previous tank to remain connected). Such a fuel tank supply device **140** may include a service valve **146** to initially pressurize the system, mechanical supports for equipment and attachment to the target device, grappling appendages, and/or passive thermal control.

(38) FIG. 2A depicts a simplified schematic view of an embodiment of a spacecraft servicing device **100** (e.g., the spacecraft servicing device **100** of FIG. 1A). As shown in FIG. 2A, the spacecraft servicing device **100** includes the one or more deployable pods or modules **102** that are initially attached to the spacecraft servicing device **100**. The spacecraft servicing device **100** may be a satellite or other spacecraft situated in orbit around a body.

(39) In order to deliver, attach, and/or retrieve the pods **102** to another spacecraft, the spacecraft servicing device **100** may include a chemical or another type of reaction engine and/or may include an electrically powered propulsion system. For example, the spacecraft servicing device **100** may include one or more thrusters **104**, a power system including chemical and/or electric propulsion sources (e.g., fuel tanks **106** housing a xenon propellant for an ion thruster and/or a hydrazine propellant), and power processing units **108**. The propulsion system of the spacecraft servicing device **100** (e.g., including the thrusters **104**) may enable the spacecraft servicing device **100** to move in one or more axes of movement (e.g., three axis of translation and three axes of rotation for a total of six axes of movement). The spacecraft servicing device **100** may include solar arrays **110** (e.g., directable solar arrays), batteries **112**, power regulation electronics, such as, a power distribution assembly **114**), control subsystems **116** (e.g., command and data handling, thermal controls, guidance, navigation, and control), communication subsystems **118** (e.g., radio frequency (RF) communications with associated antenna **120**), and accessory tools **121** (e.g., service componentry and/or end effector for the robotic arm(s) discussed below). Such components may enable the spacecraft servicing device **100** to maneuver to a location proximate another spacecraft to be serviced.

(40) In order to deploy, attach, and/or retrieve the pods **102** onto another spacecraft, the spacecraft servicing device **100** may include deployment and/or removal devices (e.g., one or more movable arms, for example, robotic arms **122** having one, two, three, four, five, or six degrees of freedom, a lance and/or extendable deployment device, as discussed below, that may be coupled to a portion of the pods **102**, such as an internal portion of the engine) with an associated imaging system (e.g., camera **124**) and control and power systems (e.g., robotic avionics **126** and power supply **128**). Such devices and components may be utilized to engage with (e.g., to attach to) the pods **102** on the spacecraft servicing device **100**. For example, one or more of the robotic arms **122** may be used to couple to one pod **102** (e.g., with an end effector) and to move that pod **102** into proximity of the target spacecraft, to attach the pod **102** to the spacecraft, and to release the pod **102** after attachment.

(41) In some embodiments, other devices and methods may be utilized to deliver and/or attach the pods **102** to the spacecraft. For example, the spacecraft servicing device **100** itself may be oriented relative to the spacecraft to place a selected pod **102** in contact with the spacecraft, the spacecraft servicing device **100** itself may capture or otherwise retain the spacecraft while applying the pod **102**, the pods **102** may include one or more onboard systems for controlling and attaching the pods **102**, the spacecraft servicing device **100** may include a reusable and separately controllable unit

with a propulsion unit control configured to deliver the pods **102**, or combinations thereof.

(42) In some embodiments, the spacecraft servicing device **100** may deliver, attach, and/or retrieve the pods **102** to the spacecraft without the use of a robotic arm. For example, with one or more pods **102** attached, the spacecraft servicing device **100** may rendezvous with the target spacecraft (e.g., utilizing sensors to detect the position and/or orientation of the target spacecraft, such as those discussed below). While the pod **102** is attached to the spacecraft servicing device **100**, a coupling mechanism of the pod **102**, as also discussed below, may be deployed and engaged with the target spacecraft. The pod **102** may be released from the spacecraft servicing device **100** and, before, during, and/or after the release, any remaining docking procedures may be completed in order to secure the pod **102** to the target spacecraft.

(43) Regardless of the particular mechanism or feature utilized to deploy, attach, and/or retrieve the pods **102**, the spacecraft servicing device **100** may be configured to directly deliver (e.g., via mechanism and/or features) the pods **102** to a location at the target spacecraft using one or more portions of the spacecraft servicing device **100**. For example, the spacecraft servicing device **100** may deploy, attach, and/or retrieve the pods **102** using only the deployment mechanism and/or features (e.g., robotic arm(s) **122**, an extendable and/or expandable docking mechanism, etc.) that are resident on (e.g., part of) the spacecraft servicing device **100**. In some embodiments, only the deployment mechanism and/or features that are resident on the spacecraft servicing device **100** are utilized while any maneuvering (e.g., propulsion) devices on the pods **102** are not utilized. For example, the pods **102** may be directly manipulated by the spacecraft servicing device **100** while not independently maneuvering and/or manipulating the pods **102** under their own power or propulsion to a location adjacent the target spacecraft. After being moved into position, a mechanism and/or feature of the spacecraft servicing device **100** (e.g., robotic arm(s) **122**, an extendable and/or expandable docking mechanism) and/or a feature of the pods **102** (e.g., a coupling mechanism, such as deployment device **160**) may be utilized to secure the pod **102** to the target spacecraft. In some embodiments, the pod **102** may be secured to the target spacecraft while the pod **102** remains in at least partial contact with the spacecraft servicing device **100**. For example, once the pod **102** is at least partially in contact with (e.g., secured to) the target spacecraft, the pod **102** may be released from the spacecraft servicing device **100**.

(44) In some embodiments, the spacecraft servicing device **100** includes sensor assemblies such as rendezvous and proximity operations **130** (e.g., light detection and ranging **132**, infrared sensors **134**, and/or visible light sensors **136**). Such components may enable the spacecraft servicing device **100** to monitor and/or detect other objects (e.g., the pods **102**, other spacecraft when servicing related functions are performed). For example, one or more of the sensors (e.g., light detection and ranging **132**, infrared sensors **134**, and/or visible light sensors **136**) may enable the spacecraft servicing device **100** to facilitate rendezvous and proximity operations relative to the target spacecraft **20** (FIG. 1A) in order to deploy, install, and/or remove the pod **102** (FIG. 1A).

(45) In some embodiments, the one or more of the sensors (e.g., light detection and ranging **132**, infrared sensors **134**, and/or visible light sensors **136**) may enable the spacecraft servicing device **100** to detect one or more features of the target spacecraft **20** (FIG. 1A). For example, the one or more of the sensors of the spacecraft servicing device **100** may detect a docking feature (e.g., a docking, berthing, or coupling mechanism) of the target spacecraft **20** or other features (e.g., structural characteristics) of the target spacecraft **20** in order to determine the manner through which the pod **102** should be attached to the target spacecraft **20**.

(46) In some embodiments, the spacecraft servicing device **100** may be at least partially reconfigurable to facilitate operations performed by the spacecraft servicing device **100**. For example, during coupling (e.g., docking) with a spacecraft **20** (FIG. 1A), device **100** may relocate (e.g., stow, unstow) various structures and/or components (e.g., stanchions used for docking with the spacecraft **20**). Such structures and/or components may be detached by one or more tools (e.g., the robotic arm **122**) and placed in a temporary storage location. The structures and/or components

may be attached when the spacecraft servicing device **100** is docking (e.g., and servicing) the target spacecraft **20**.

(47) In some embodiments, features on the spacecraft servicing device **100** may be used to reconfigure other device (e.g., spacecraft). For example, one or more tools (e.g., the robotic arm **122**) of the spacecraft servicing device **100** may be used to remove structures that facilitate the stacking of secondary payloads above the spacecraft servicing device **100** after launch. In some embodiments, the spacecraft servicing device **100** (e.g., and the attached pods **102** (FIG. 1A)) may be attached to an ESPA ring or some another suitable structure. After launch (e.g., in orbit), the robotic arm **122** may detach and relocate pods **102** to storage locations and then detach accessory structure used during the launch disposal or temporary storage.

(48) FIG. 2B depicts a simplified schematic view of an embodiment of a spacecraft servicing device **150**, which may be substantially similar to the spacecraft servicing device **100** of FIG. 2A and, as depicted, may include some, a majority of, or all of the components of the spacecraft servicing device **100**. As shown in FIG. 2B, the spacecraft servicing device **150** includes a coupling mechanism **152** (e.g., a docking, berthing, retaining, or otherwise attaching mechanism) for coupling to other devices (e.g., other spacecraft, such as spacecraft **20**, the pods **102**, the resupply device **30**, etc.).

(49) As discussed above, once on orbit with its initial supply of pods **102**, the spacecraft servicing device **100** travels from target spacecraft **20** (FIG. 1A) to target spacecraft **20** to install pods **102**. In some embodiments, the spacecraft servicing device **100** may employ additional control techniques to hold at an optimal position relative to the spacecraft **20** to permit installation (e.g., robotic installation) of the pods **102**. This optimal position may be centered or not centered on the spacecraft **20** and may stand back from the spacecraft **20** a select distance so that there is room for the pods **102** and the robotic arm **122** to be moved onto the spacecraft. Data from the rendezvous sensors may be sent to the robotics control computers on spacecraft servicing device **100** so that machine vision and robotic motion control algorithms may have a prior knowledge of the relative positions and motions of the two spacecraft.

(50) FIGS. 2C through 2K depict various embodiments of coupling mechanisms according to one or more embodiments of the present disclosure. As shown in FIGS. 2C and 2D, the coupling mechanism **152** may comprise an expandable docking mechanism **160** (e.g., having a spear shape) configured to be received in a receiving portion (e.g., engine **156**) of at least one of the spacecraft **20** (e.g., a portion of an engine or any other portion to which a mechanical coupling may be made). The expandable docking mechanism **160** is guided into position either entirely by the spacecraft servicing device **100** (FIG. 2A) or by having a robotic arm guide the final docking while the spacecraft servicing device **100** holds the position relative to the spacecraft **20**. Once in place, one or more expandable portions may deploy and contact the receiving portion **156** in order to secure the expandable docking mechanism **160** to the spacecraft **20**.

(51) Such an expandable docking mechanism **160** is disclosed in, for example, U.S. Pat. No. 15,829,807, filed Dec. 1, 2017, titled "SYSTEMS FOR CAPTURING A CLIENT VEHICLE," the disclosure of which is hereby incorporated herein in its entirety by this reference. For example, the expandable docking mechanism **160** may be inserted within the engine **156** of the spacecraft **20** as shown in FIG. 2C. Once inserted in the engine **156**, one or more portions of the expandable docking mechanism **160** may be moved (e.g., expanded, extended) in order to contact the engine **156** and secure the expandable docking mechanism **160** to the engine **156**, thereby, securing the pod **102** (FIG. 1A) to the spacecraft **20**. Before, after, and/or during the securing, the expandable docking mechanism **160** may include an extension arm that is retracted to place the pod **102** (FIG. 1A) into closer proximity to the spacecraft **20**.

(52) As shown in FIGS. 2E and 2F, the coupling mechanism **152** may comprise an expandable and/or retractable docking mechanism **162** (e.g., having the shape of a chuck) configured to engage with the receiving portion **156** of the spacecraft **20**. The docking mechanism **162** may be guided

into position in a manner similar to that described above. Once in place, docking mechanism **162** may either retract or expand in order to secure the expandable docking mechanism **162** to the spacecraft **20**.

(53) As shown in FIGS. **2G** and **2H**, the coupling mechanism **152** may comprise a snare docking mechanism **164** (e.g., including a plurality of wires, for example, braided metal wires, positioned at an opening of a cavity). The snare docking mechanism **164** may be guided into position in a manner similar to that described above. The snare docking mechanism **164** is configured to engage with the receiving portion **156** of the spacecraft **20** by enabling the receiving portion **156** to enter through an opening in the wires. Once in place, the snare docking mechanism **164** may move (e.g., rotate) such that the wires at least partially restrict the opening defined by the wires to secure the snare docking mechanism **164** to the spacecraft **20**.

(54) As shown in FIGS. **2I** and **2J**, the coupling mechanism **152** may comprise a clamping docking mechanism **166** (e.g., a three-point clamping mechanism including a movable member and two stationary members) configured to engage with the receiving portion **156** of the spacecraft **20**. The docking mechanism **166** may be guided into position in a manner similar to that described above. Once in place, the movable member or members of the docking mechanism **166** may move toward the stationary member or members in order to secure the expandable docking mechanism **166** to the spacecraft **20**.

(55) As shown in FIG. **2K**, the coupling mechanism **152** may comprise an inflatable clamping docking mechanism **168** (e.g., one or more inflatable bags configured to be received on an exterior portion and/or an interior portion of the receiving portion **156**) configured to engage with the receiving portion **156** of the spacecraft **20**. The docking mechanism **168** may be guided into position in a manner similar to that described above. Once in place, the inflatable bag (e.g., an annular bag) or bags (e.g., two opposing bags) may be inflated in order to secure the expandable docking mechanism **168** to the spacecraft **20**. In some embodiments, the bag may be filled with a fluid (e.g., liquid) that will at least partially solidify to form an at least partially rigid connection between the structures.

(56) FIG. **2L** is a perspective view of a spacecraft servicing device **180** that may be similar to those discussed above. As depicted, the spacecraft servicing device **180** may include a body **182** comprising an ESPA ring with pods **102** coupled about the body **182**. Each pod **102** may include a coupling mechanism **184** for coupling with a target spacecraft **20** (FIG. **1A**) and an optional solar array **186**. As above, the coupling mechanism **184** may comprise a spear-shaped extendable device configured to engage with the engine of the target spacecraft **20**.

(57) Referring to FIG. **1A**, in yet additional embodiments, a structural portion of the pods **102** (e.g., a stanchion or other frame member) may be utilized to dock with the spacecraft **20**. For example, a robotic arm or other feature (e.g., a non-robotic method) would first position the pod **102** at a predetermined location depending on the geometry and features of the spacecraft **20** and components (e.g., separation rings) of the spacecraft **20**. The spacecraft servicing device **100** may then dock to the spacecraft **20** using the structural portion of the pod **102**. Once the docking is complete, the structural portion of the pod **102** may be secured to the spacecraft **20** (e.g., by actuating a clamp or otherwise rigidizing the coupling via an electronic command through the robotic interface or via electromechanical drive power from the robotic interface). A portion of the spacecraft servicing device **100** (e.g., the robotic arm) may then release the pod **102** and the spacecraft servicing device **100** may undock from the spacecraft **20** leaving behind the pod **102** installed on the spacecraft **20** (e.g., on a separation ring).

(58) In yet additional embodiments, a portion of the spacecraft servicing device **100** (e.g., a robotic arm) may reach out and place the pods **102** on a portion of the spacecraft (e.g., a separation ring or other compatible mechanical feature of the spacecraft **20**). An electronic command to the pod **102** or spacecraft **20** to actuate a coupling mechanism or electromechanical drive on either device may then be used to secure the pod **102** in place on the spacecraft **20**.

(59) Referring to FIG. 2A, in instances where the robotic arm is used to place the pods **102**, the robotic arm **122**, an end effector, and/or other tools may employ techniques related to docking mechanism **166** that minimize zero gravity contact dynamics between the two vehicles. Such techniques include, but are not limited to, minimizing friction at contact interfaces, minimizing the time between first contact and rigidization (e.g., completion of docking or other coupling), and providing compliance in the path. In some embodiments, passive and active first contact electrostatic discharge (ESD) mitigation techniques may be employed in the design of the pods **102**, the robotic arm **122**, the spacecraft servicing device **100**, and the resupply device **30** to ensure that first contact ESD is minimized or eliminated. Such ESD mitigation is disclosed in, for example, U.S. patent application Ser. No. 15/829,758, filed Dec. 1, 2017, titled “ELECTROSTATIC DISCHARGE MITIGATION FOR A FIRST SPACECRAFT OPERATING IN PROXIMITY TO A SECOND SPACECRAFT,” the disclosure of which is hereby incorporated herein in its entirety by this reference.

(60) Referring to FIG. 1A, it may be desirable, when installing the pods **102** on a spacecraft **20**, to have as brief a connection as possible between the spacecraft servicing device **100** and the spacecraft **20**. In some embodiments, during installation of the pod **102**, both the spacecraft **20** and the spacecraft servicing device **100** may be in free drift together for only a brief period of time (e.g., seconds to minutes) in which the installation of the pod **102** is established and the spacecraft servicing device **100** releases the pod **102** to break the mechanical connection between the two vehicles. The spacecraft servicing device **100** propulsion system may then be reactivated and the spacecraft servicing device **100** may retreat to a safe location. The spacecraft **20** attitude control system may be reactivated shortly thereafter so that the target spacecraft **20** can reacquire its positioning.

(61) Referring to both FIGS. 1A and 2A, in some embodiments, after installation, the pods **102** may be activated via, for example: a ground command to a transceiver in the pod **102**, an electrical command from the robotic arm **122**, e.g., with a timer, sensor (e.g., a break-wire timer or similar sensor) that enables the pod **102** to sense that it is no longer connected to any of the spacecraft servicing device **100**, the resupply device **30**, or the robotic arm **122**. In some embodiments, such sensors may include one or more mechanical limit switches activated by the completion of the docking or installation mechanical activity.

(62) In yet additional embodiments, the pods **102** may be activated via a feature incorporated into the interface between the spacecraft servicing device **100** and the pod **102**. For example, a portion of the deployment device of the spacecraft servicing device **100** (e.g., the tool drive mechanism or end effector on the robotic arm **122**) may assist in the activation and/or initial deployment of appendages on the pods **102**. Such a technique would potentially simplify the pod **102** mechanisms by taking advantage of the functionality of the robotic arm **122** of the spacecraft servicing device **100** (e.g., an end effector of the arm **122**) to perform deployment and initiation of the pods **102** (e.g., one-time actuations on the pods **102**). The robotic arm **122** and/or components and tools thereof may perform at least partial in-orbit assembly of the pods **102**. For example, use of the robotic arm **122** for final assembly of appendages onto the pods **102** may allow for simplified, lighter, and/or lower cost packaging of the pods **102** components for launch.

(63) FIG. 3 depicts a simplified schematic view of an embodiment of a pod (e.g., mission extension pod **102** of FIG. 1A) of the spacecraft servicing device **100**. As shown in FIG. 3, the mission extension pod **102** includes one or more devices for controlling (e.g., orienting and moving) the pod **102** and any other structure attached to a main body **201** of the pod **102**. For example, the pod **102** may include a chemical or another type of reaction engine and/or may include an electrically powered propulsion system. As depicted, one or more thruster assemblies **200** may include one or more thrusters **202** (e.g., electric propulsion (EP) thrusters) attached (e.g., movably attached) to the pod **102** with a movable (e.g., rotatable) coupling (e.g., gimbal **204** and a boom **206**). In some embodiments, the positioning of the thrusters **202** relative to the main body **201** may be selected

based on one or more characteristics (e.g., size, dimensions, mass, center of mass, combinations thereof, etc.) of the spacecraft to which the pod is to be attached. In some embodiments, the thrusters **202** may provide relatively low acceleration to minimize or avoid disturbances due to the propellant moving around in a propellant tank.

(64) While the embodiment of FIG. 3 illustrates one thruster assembly **200** on a single boom **206**, in other embodiments, the pod **102** may include multiple thruster assemblies on multiple booms (e.g., two, three, or more thruster assemblies and accompanying booms). For example, two thruster assemblies may be provided on two booms where one thruster assembly substantially mirrors the other thruster assembly. Further, in some embodiments, multiple thruster assemblies may be provided on a single boom. In such an embodiment, multiple thrusters may be implemented to ensure that the lifetime throughput capability of the system is adequately realized or the desired thrust levels are reached. In some embodiments, one or more thruster assemblies **200** may not be provided on a boom, but installed directly on the pod **102**. In some embodiments, one thruster assembly **200** may be used for life extension services, including spacecraft relocation, station keeping, inclination pull-down, momentum adjustments, and/or end of life (EOL) disposal. In some embodiments, multiple thruster assemblies **200** may each be used for all life extension services or may be divided for different life extension services. For example, one or more thruster assemblies **200** may be provided on one or more booms for station keeping services, while one or more thruster assemblies **200** may be installed on the pod for orbit relocation, inclination pull-down, and EOL disposal.

(65) In some embodiments, antenna **208** may be positioned on the thruster assembly **200**. In some embodiments, antenna **208** may be positioned on a separate deployable boom. In some embodiments, additional solar cells to generate power may be placed on the thruster boom assembly **200**.

(66) The pod **102** may include a power and propulsion system **210** including one or more power sources and associated componentry (e.g., where at least a portion of the power system may be an electric propulsion power system). For example, the power system and propulsion system **210** may include one or more propellant tanks (e.g., housing a xenon propellant or any other suitable propellant for electric or chemical propulsion systems), thrusters (e.g., electronic thrusters) and associated power processing units. The pod **102** may include a solar array **212** and one or more batteries **214**. In some embodiments, the solar array **212** may be rigidly coupled to the main body **201** or attached with a movable (e.g., rotatable) coupling with one or more axes of motion (e.g., one or more gimbals **216** or other movable joints and a boom **218** providing movement about one, two, or more axes) to direct the solar array **212** toward the sun.

(67) In some embodiments, the gimbaled solar array **212** may provide many advantages over a similar rigid array. For example, the gimbaled solar array **212** enables the solar array **212** to be removed from/spaced from thrusters of the target spacecraft **20** so that the target spacecraft **20** may perform orbit maintenance while minimizing concerns of the thrusters of the target spacecraft **20** pluming onto the solar arrays of the pod **102**. The gimbaled solar array **212** may further decouple the pod **102** thermally from the target spacecraft **20** and increase the effectiveness of the solar array **212** by enabling it to track the Sun. An increase in effectiveness of the gimbaled solar array **212** enables the thrusters of the pod **102** to fire longer and it also enables the use of smaller, lighter, and more inexpensive batteries. A longer firing propulsion system may facilitate the servicing of heavier target spacecraft **20**. In some embodiments, the gimbaled solar array **212** may be articulated in a way to conserve momentum (e.g., where no net momentum is imparted) upon the target spacecraft **20** over an orbit.

(68) In some embodiments, the solar array **212** may track the sun utilizing stored logic on the pod **102** during the sunlit portions of the satellite servicing in order to maximize solar array **212** power generation, thereby minimizing the solar array **212** and battery size. In some embodiments, the movement of the solar array **212** may be limited, for example, to simplify the mechanical design

and to eliminate or minimize the shadowing of the spacecraft arrays, impingement from thruster plumes on the pod **102** and/or spacecraft **20**, interference with sensors or antennae on the pod **102** and/or spacecraft **20**, or other system constraints. In some embodiments, the solar array **212** may include two separate wings with one or two axes of motion. In some embodiments, the gimbaled solar array **212** may include one axis of movement configured to counteract the rotation of the pod **102**.

(69) Embodiments of the pod **102** may provide spacecraft servicing in a relatively physically small package and light footprint on the spacecraft vehicle **20** (FIG. **1A**) by using low power (e.g., electric) propulsion systems, such as gridded ion thrusters, Hall effect thrusters, colloidal/field effect thrusters, arcjets, and resistojets. Such an electric propulsion system may produce the required amount of thrust over a selected time period for one or more burns to adjust positioning of the spacecraft **20** (e.g., burning twice in a twenty-four hour period) where each thrust lasts a select period of time. In some embodiments, the pod **102** may be positioned on the zenith (e.g., anti-earth) facing side of the spacecraft and the solar array **212** of the pod **102** in order to experience unobscured sunlight for at least twelve hours per day. In some embodiments, one thruster burn may occur while the solar array **212** of the pod **102** is fully illuminated, while a second thruster burn occurs with the solar array **212** of the pod **102** completely obscured by the spacecraft body.

(70) In some embodiments, each thruster burn during a twenty-four hour period may occur while the solar array **212** of the pod **102** is obscured by the spacecraft **20** body. In some embodiments, each thruster burn during a twenty-four hour period may occur while the solar array **202** of the pod **102** is fully illuminated. A battery (e.g., battery **214**, such as a lithium-ion battery) may be used to store energy during the period of pod **102** solar illumination, and the battery **214** may be sized to support the pod **102** bus power draw as well as a thruster burn power during the periods of no sunlight. In some embodiments, the thruster burns are performed with chemical thrusters.

(71) In some embodiments, the propellant of the power and propulsion system **210** of the pod **102** may include an amount of propellant (e.g., around 25 kg, 50 kg, 100 kg, 150 kg or more) to support station keeping (e.g., maneuvering and momentum adjustment requirements) of the spacecraft **20** (FIG. **1A**) for a selected period of time (e.g., at least a number of years). The pod **102** may be loaded with the propellant prior to launch so that no propellant transfer is required once in orbit. As the spacecraft **20** requires relocation to a different orbital location for continuation of its operational life or reaches the end of its operational life, the pod **102** thrust schedule and position can be adjusted to deliver change in velocity in the orbit velocity direction of the spacecraft **20** to move the spacecraft **20** to a different orbit, orbit location, or combination thereof, for purpose of operational life extension or end-of-life disposal.

(72) In some embodiments, the fuel or propellant of the pod **102** may be utilized to service the spacecraft **20** without relying on one or more systems of the spacecraft **20**. For example, only the propellant of the pod **102** may be utilized to service the spacecraft **20** (e.g., maneuvering and/or adjusting at least one momentum, including attitude, of the spacecraft **20**).

(73) Referring to FIGS. **1A** and **3**, in some embodiments, the fuel tank **24** of the spacecraft **20** may be bypassed (e.g., not be utilized) to service the spacecraft **20**. For example, the propellant of the pod **102** (e.g., supplied from tank **141** in a configuration similar to that shown in FIG. **1B**, supplied from a tank of the propulsion system **210** of the pod **102**) may be supplied (e.g., directly supplied) to a portion of a propellant system **22** of the target spacecraft **20** (e.g., while bypassing the fuel tank **24** of the spacecraft **20**). In such an embodiment, the propellant of the pod **102** may be utilized to service the spacecraft **20** without transferring (e.g., refueling) the propellant to the tank **24** of the spacecraft **20** (e.g., through a refueling procedure). For example, the propellant of the pod **102** may be coupled (e.g., fluidly coupled via coupling mechanism **152**, mating adapter **145** (FIG. **1B**), etc.) to a portion of the fuel system of the spacecraft **20**. In some embodiments, such an existing connection may exist on the spacecraft **20**. In some embodiments, one or more of the spacecraft servicing device **100** and the pod **102** may install at least a portion of the connection on the

spacecraft **20**.

(74) Propellant from the pod **102** may be transferred into the propellant system **22** of the target spacecraft **20** and be utilized to service the spacecraft **20** (e.g., maneuvering and/or adjusting at least one of an orbit, a velocity, or a momentum of the spacecraft **20**) using, for example, one or more thrusters of the propellant system **22**.

(75) In some embodiments, the pod **102** may lack propulsion devices for independently moving the pod **102**.

(76) In some embodiments, the pod **102** may have a relatively low overall mass, such as, for example, less than 700 kilograms (kg) (e.g., less than 600 kg, 500 kg, 400 kg, 350 kg, 300 kg, 200 kg, 100 kg, or less).

(77) In some embodiments, the pods **102** are configured to remain permanently on the spacecraft **20** and are not recovered or replaced. In some embodiments, the pods **102** may be detached from the spacecraft **20** and used on a different client spacecraft. In some embodiments, the pods **102** may be detached from the spacecraft **20**, refueled by the spacecraft servicing device **100** or resupply device **30**, and reattached to the spacecraft **20**.

(78) The pod **102** may include power controls (e.g., a single circuit board of power controls **220**) and flight controls (e.g., a single circuit board of avionic controls **222**) provided on any suitable type and number of electronic devices.

(79) The pod **102** may include a communication subsystem **224** (e.g., radio frequency (RF) communications in communication with the antenna **208** and a transceiver (XCVR). The communication subsystem **224** of the pod **102** may be designed to operate with commercially available communications services with a periodic contact rather than continuous contact requirement.

(80) In some embodiments, a communication device of the pod **102** (e.g., communication subsystem **224**) may receive data relating to the at least one of an orbit or a velocity of the target spacecraft **20** (FIG. 1A) (e.g., relating to a momentum of the spacecraft **20**). Such data may be transmitted or otherwise transferred to the pod **102** from a location remote from the pod **102** (e.g., directly or indirectly through the ground station, a satellite relay, direct transmission, and/or an electrical connection, such as, directly from the target spacecraft **20**). Such data may include calculations for a related burn and/or systems of the pod **102** may preform calculations for the burn based on the data. In some embodiments, the telemetry data may be provided from the target spacecraft **20** to the pod **102** (e.g., through a radio frequency link), either directly or indirectly through a ground station. In some embodiments, the telemetry data may be provided from one or more of the target spacecraft **20**, the spacecraft servicing device **100**, or from a ground station to the pod **102**, either directly or indirectly.

(81) In some embodiments, the telemetry data may be updated at selected intervals in a closed loop system and subsequent burns may be calculated based on the updated data.

(82) In some embodiments, the predetermined burn schedule may be provided to the pod **102** or another portion of the system **10**.

(83) In some embodiments, the pod **102** may lack any independent systems for determining the telemetry data (e.g., velocity, attitude, momentum, position, orbit, etc.) of the pod **102** and/or the target spacecraft **20** and may need to rely on an exterior source (e.g., the target spacecraft **20**, a ground station, the servicing mother ship device **100**) for such information.

(84) Pod **102** may store telemetry data over a time period (e.g., eight to twelve hour period) and return this data to the communications network when polled on a selected schedule (e.g., two or three times daily). The total data set may be relatively small, resulting in a relatively short contact time, which provides a relatively low cost footprint for operating numerous pods **102** over a period of multiple years. In some embodiments, the pod **102** may be positioned on the non-earth-facing side of the target spacecraft **20** (FIG. 1A). In order to provide a line of sight to ground station antennas and/or orbiting communications services, the transceiver antenna **208** may be positioned

on the same boom carrying the thruster assembly **200** to provide a clear line of sight. Given the geosynchronous orbit range and the low power nature of the components of the pod **102**, along with a relative modest gain antenna **208**, pod **102** may forward and return data at relatively low data rates (e.g., less than one kb/s, less than a few kb/s). Thus, the pod **102** is capable of receiving a limited set of commands to adjust its thrust schedule and boom pointing in accordance with adjustments specified by the spacecraft **20** spacecraft operators from Earth.

(85) In some embodiments, one or more portions of the system **10** (FIG. **1A**) (e.g., the pod **102**) may utilize a flexible frequency transceiver, which may enable the pod **102** to be in communication with a ground station associated with the spacecraft **20**. By using a flexible frequency transceiver and using an existing ground system for the spacecraft **20**, the pod **102** may not require any additional regulatory agency licensing or third party services to establish command and telemetry connectivity between the pod **102** and the ground station for the spacecraft **20**. This may enable an operator of the spacecraft **20** to establish control (e.g., full control) over the pod **102** at relatively minimized additional investment with little to no regulatory disclosures or licensing necessary. Given that the market base for target spacecraft **20** includes a relatively large amount of spacecraft **20** utilizing C-band and Ku-band RF frequencies for communication, the launched pods **102** may be configured with either C-band or Ku-band transceivers. Prelaunch coordination may establish the ratio of pods **102** with either C-band or Ku-band based communication systems that would be launched on either the initial capability or in the resupply spacecraft. If a target spacecraft **20** does not utilize C-band or Ku-band communications, the pods **102** may be configured to implement the type of communication system to substantially match that of the target spacecraft **20** or a C-band or Ku-band pod **102** may still be utilized with the target spacecraft **20** having a differing type of communication system. In some embodiments, a pod **102** may store its telemetry data over a select time period (e.g., eight to twelve hours) and may return this data to the communications network when polled (e.g., two or three times daily).

(86) In some embodiments, the flexible frequency transceiver may enable the pod **102** to mate with a variety of target spacecraft **20** as frequencies of the flexible frequency transceiver may be modified based on the target spacecraft **20** in orbit (e.g., to utilize an unused portion of one or more bands of frequencies utilized by the target spacecraft **20**).

(87) In some embodiments, a space-to-space command and telemetry link between the pods **102** and spacecraft servicing device **100** may be implemented to utilize the relatively larger gain and power of the spacecraft servicing device **100** to connect the pods **102** to the ground system of the spacecraft **20**. In some embodiments, this technique may be employed while the spacecraft servicing device **100** is in fairly close proximity with pods **102** and/or may be implanted for long-term operations where the pods **102** thruster burn schedule may only require occasional adjustments (e.g., adjustments performed weekly, monthly, or a longer intervals).

(88) In some embodiments, a communication system of the pods **102** may use a transceiver that is designed to take advantage of the close proximity of the antenna of the pods **102** to the uplink antenna of the spacecraft **20** to feed a spread spectrum telemetry signal from the pods **102** into the uplink of the spacecraft **20**. That signal then receives a high gain boost by the communications system of the spacecraft **20** to send telemetry from the pod **102** to the ground.

(89) The various communication systems in the pods **102** disclosed herein may enable monitoring of the functions of and results achieved from the pod **102** in near real time, with time lag only due to speed of light from geosynchronous orbit to ground. Such configurations may enable the pod **102** to perform a number of functions (e.g., such as those described above) where those functions can return performance data to the ground station. Software in the ground station as well as in the target spacecraft **20** or the pod **102** may also be utilized to “close the loop” with speed of light lag such that data from pod **102** or the target spacecraft **20** may be delivered into the software associated with the target spacecraft **20** or the pod **102** to control the target spacecraft **20**. In some embodiments, the pod **102** may not be required to directly communicate with the spacecraft **20** that

hosts the pod **102** and may communicate with the spacecraft **20** via the speed of light round trip time lag through the ground station. In such an embodiment, it is possible to “close the loop” for complex functionality that may be provided in the form of the pod **102** spacecraft servicing. For example, this complex functionality may include the ability to manage three axes of momentum of the spacecraft **20** with the thruster assemblies **200** of the pod **102** by means of a gimbal control logic resident in ground software or pod software using telemetered data from the spacecraft **20**.

(90) In order to deploy and attach the pod **102** onto another spacecraft **20** (FIG. 1A), the pod **102** may include an attachment feature (e.g., a coupling mechanism **226** configured for one or more of docking with, berthing to, attaching to, retaining, or combinations thereof, a target spacecraft **20**) configured to attach to the spacecraft **20** and/or one or more coupling features (e.g., grapple mechanism **228**) that may be engaged by a feature of the spacecraft servicing device **100** (FIG. 2A) (e.g., a robotic arm **122**). The coupling mechanism **226** may be movably mounted to the main body **201** (e.g., with gimbal **230**).

(91) In some embodiments, the thruster assembly **200** of the pod **102** may be positioned on a multi-axis actuator system (e.g., defined by a number of gimbals and/or other translation or rotation devices). For example, gimbal **204** may be configured to move the thruster assembly **200** in a first axis of direction and gimbal **205** may be configured to move the thruster assembly **200** in a second axis of direction that is transverse to the first axis of direction. In some embodiments, the gimbals **204**, **205** may be collocated at the thruster assembly **200**. In some embodiments, the gimbals **204**, **205** may be separated by a boom. The pod **102** may include a third gimbal **230** (e.g., for rotating the main body **201** relative to the spacecraft **20** (FIG. 1A)) for positioning gimbals **204**, **205** relative to the spacecraft body. In some embodiments, the pod **102** may include a third gimbal **230** proximate gimbal **204** (e.g., between the main body **201** and the boom **206**). Such a third gimbal **230** may act in cooperation with gimbals **204**, **205** to create three degrees of freedom (e.g., three rotational degrees of freedom).

(92) In some embodiments, the grapple mechanism **228** may be spaced from the main body **201** with one or more structures **232** to facilitate coupling with the robotic arms **122** of the of the spacecraft servicing device **100** (FIG. 2A).

(93) The pod **102** may include a mechanism utilized to secure the pod **102** to the spacecraft servicing device **100** (FIG. 2A). For example, the pod **102** may include stow mechanism **234** (e.g., which may be spaced from the main body **201** with the structure **232**) that couples with a portion of the spacecraft servicing device **100**. In other embodiments, one or more of the above existing features (e.g., the coupling mechanism **226** and/or the grapple mechanism **228**) or another feature may be used to secure the pod **102** to the spacecraft servicing device **100**.

(94) As discussed above, the pod **102** may be configured to deliver a change in orbital velocity (e.g., station keeping, relocation, EOL disposal) to the spacecraft **20** (FIG. 1A), for example, while being separated from (e.g., not in communication with) the control systems of the spacecraft **20**. In other words, the pod **102** alone may alter the trajectory (e.g., orbit) of the spacecraft **20** while being attached to the spacecraft **20**, but not being in communication with the control systems of the spacecraft **20**. The change in velocity may be supplied from the thrusters **202** (e.g., ion thruster, Hall current thruster, gridded ion thruster, Hall effect thruster, or any other suitable type of electric or chemical thruster that generates any suitable level of thrust).

(95) In some embodiments, as discussed above, the pod **102** may function, at least partially, as an auxiliary fuel tank (e.g., a tank of high pressure xenon, hydrazine, helium, nitrogen tetroxide (NTO), a green propellant, combinations thereof, or any other suitable fuel) that is coupled to spacecraft **20** (e.g., FIG. 1A) (e.g., to an exterior of the spacecraft **20**). For example, the pod **102** may include one or more of such tanks in the power and propulsion system **210**. In other embodiments, as discussed below, the pod **102** may comprise only the fuel tank along with associated componentry configured to attach to and place the tank in communication with the spacecraft **20**.

(96) In some embodiments, the pod **102** may essentially only comprise an auxiliary tank system and may not include a majority or any of the above-described components. Such an auxiliary tank system pod **102** may include a service valve to initially pressurize the system, mechanical supports for equipment and attachment to the spacecraft, grappling appendages, and/or passive thermal control. In some embodiments, a deployment device (e.g., a robotic arm) may be used to place the auxiliary tank system pod **102** at its destination, which destination may be cooperatively designed to or to not to host the tank. The target spacecraft **20** for this transfer tank system pod **102** may either have cooperatively designed interfaces for gas and fluid transfer or, when the spacecraft **20** lacks such interfaces, the auxiliary tank pod **102** may include an interface configured to adapt to varying sizes and configurations of fittings on such spacecraft **20**.

(97) FIG. **4** is a simplified schematic view of a pod **102** attached to a spacecraft **20** in a first configuration **300** with a first thrust vector orientation **301** and in a second configuration **302** with a second thrust vector orientation **303**. Referring to FIGS. **3** and **4**, the gimbals **204**, **205**, **230** may provide a select number of degrees of freedom (e.g., two degrees of freedom, three degrees of freedom) for pointing the thrust force vector through the center of mass of the spacecraft **20**. Thrust may be generated on command (e.g., from a remote ground station) and/or on a schedule (e.g., a predetermined schedule and/or a schedule actively transmitted to the pod **102**) based on the initial position of the spacecraft **20** in orbit and may reduce or even remove the burden of station keeping and momentum unloading from the propulsion subsystem of the spacecraft **20**. In some embodiments, the amount of thrust and/or thrust force vectors may be transmitted to the pod **102** via a communications link to the pod **102** on any desirable schedule.

(98) As shown in the first configuration **300** of the gimbals **204**, **205**, **230** (e.g., three rotational degrees of freedom) that provide the first thrust vector orientation **301**, the thrust force may be applied in a predominately southern direction, or anti-normal to the spacecraft orbital direction. Similarly, as shown in the second configuration **302** of the gimbals **204**, **205**, **230** that provide the second thrust vector orientation **303**, the thrust force may be applied in a predominately northern direction, or normal to the spacecraft orbital direction. As shown in FIG. **4**, each configuration may include a component of the thrust vector in the positive or negative direction of the orbital velocity. As shown in FIG. **5**, the thrust vector in each configuration (e.g., southward and northward) also has a sizeable component in the orbit radial direction of the spacecraft. Slight variations in the thruster vector and burn duration on command (e.g., from a remote ground station) and/or on a schedule (e.g., a predetermined schedule and/or a schedule actively transmitted to the pod **102**) are used to perform station keeping of the spacecraft **20** as well as momentum adjustments, as discussed below. In some embodiments, the thrust vector may be applied at different locations around the spacecraft and at different times in the orbit to optimize the control of the spacecraft orbital elements and management of the spacecraft momentum.

(99) This additional thrust from the pod **102** may reduce the rate of propellant consumption from the spacecraft **20** by, for example, 90% or higher, up to 100% and, thereby, acts to extend the mission life of the spacecraft **20**.

(100) Given that thrust cannot generally be provided to entirely eliminate drift of the orbital elements of the spacecraft **20** during a single activation period (i.e., burn), the pod **102** may induce a small directional velocity on the spacecraft **20** in one or more orbital directions (e.g., orbit radial, normal, anti-normal, in-plane) with each thruster activation period and through the combination of multiple activation periods achieve control of all orbital elements of the spacecraft **20**. For example, the pod **102** thrust schedule may be planned for selected intervals over a single orbital revolution (e.g., two twelve hour time periods over a day) and for different orbital revolutions over the period of a week, two weeks, three weeks, one month, or longer. Such a schedule may provide pairing thruster burns and associated gimbal angles that create velocity changes that control some or all orbit elements and adjust spacecraft momentum concurrent with the velocity changes or separate from the velocity changes.

(101) FIG. 5 provides another simplified schematic view of the pod **102** (e.g., rotated 90 degrees from the view in FIG. 4) attached to the spacecraft **20** in a first configuration **304** with first thrust vector orientation **305** and in a second configuration **306** with second thrust vector orientation **307**. Referring to FIGS. 3 and 5, the gimbals **204**, **205** may provide the two degrees of freedom for pointing the thrust force vectors **305**, **307** through the center of mass **158** of the spacecraft **20**. As depicted, the pod **102** thrust schedule may be planned for two time periods on twelve hour intervals over a day (or any interval that provides the desired result for the target spacecraft **20**). Such a schedule may provide pairing thruster burns **305**, **307** that create velocity changes that may cancel each other out or be used to control the eccentricity of the spacecraft orbit.

(102) In some embodiments, a thrusting command and/or schedule may be developed and communicated to the pod **102** in order to provide the desired orbit, position, and/or velocity of the spacecraft **20** based, at least in part, on the characteristics of the spacecraft **20**.

(103) In some embodiments, a coupling portion **310** of the pod **102** (e.g., including a docking mechanism, such as the expandable docking mechanism **160** discussed above) may include a movable (e.g., rotatable) joint. For example, the rotatable coupling portion **310** may secure the pod **102** to the target spacecraft **20** (e.g., by wedging against a portion of an engine **314** of the target spacecraft) while enabling the pod **102** to rotate relative to the target spacecraft **20**. Such a configuration may enable a degree of freedom of a thruster boom arm **312** (e.g., eliminating the need for a separate movable joint, such as, the third gimbal **230** (FIG. 3)), and eliminating the need for two or more thruster gimbal assemblies.

(104) FIG. 6 is a simplified schematic view of a resupply device of a spacecraft servicing system (e.g., the resupply device **30** of the spacecraft servicing system **10** (FIG. 1A)). As shown in FIG. 6, the resupply device **30** may include a number of pods **102** attached to and/or contained within a structure **400** (e.g., an ESPA ring). In some embodiments, each pod **102** may include a respective attachment mechanism **401** for coupling to the structure **400**. The structure **400** may include a number of couplings. For example, a first and second coupling **402**, **404** for connecting to one of a payload of a launch vehicle and/or the launch vehicle itself. The structure **400** may include a bus **406** comprising one or more spacecraft systems for controlling, monitoring, powering, etc., the resupply device **30**. The structure **400** may include a grappling feature **408** configured for coupling with another portion of the system **10** (FIG. 1A) (e.g., the spacecraft servicing device **100** (FIG. 2A)). For example, the grappling feature **408** may comprise a structure to which the robotic arm **122** of the spacecraft servicing device **100** may couple (see FIG. 2A). In some embodiments, the structure of the resupply device **30** may include simulated features (e.g., similarly shaped and/or configured structures) of a separation ring and/or a spacecraft engine so the spacecraft servicing device **100** may dock to it.

(105) FIGS. 7 through 10 depict various embodiments of spacecraft servicing devices including a number of pods coupled to the spacecraft servicing device according to one or more embodiments of the present disclosure. As shown in FIG. 7, a spacecraft servicing device **500** may be defined by one or more annular structures **502** (e.g., two ESPA rings axially stacked on each other). The pods **102** may be coupled about (e.g., around in a stack of at least two pods **102**) the annular structures **502**. For example, a pod **102** may be coupled to each port defined around the annular structures **502**. A tool (e.g., robotic arm **506**) may be coupled to one of the annular structures **502** (e.g., a radially extending surface on one side of the annular structure **502**).

(106) As shown in FIG. 8, the spacecraft servicing device **500** may have a differing configuration of pods **102** coupled about the annular structures **502**. For example, pods **102** may be coupled to each port defined around the annular structures **502**. A second row of pods **102** may be coupled to a respective pod **102** that is positioned next to (e.g., adjacent and/or coupled to) the annular structure **502**. Another set of pods **102** may be positioned (e.g., coupled) in between the sets of two pods **102** extending from the annular structure **502**. In some embodiments, a select amount of clearance (e.g., including no clearance) may be provided between the pods **102**. In some embodiments, outermost

pods **102** may be configured to be positioned within, extend to, or extend beyond, a diameter of a portion of a launch vehicle (e.g., a payload fairing).

(107) As shown in FIG. **9**, the spacecraft servicing device **500** may have a differing configuration of pods **102** coupled about the annular structures **502**. For example, pods **102** may be coupled to, but spaced from, each port defined around the annular structures **502**. A second row of pods **102** may be positioned adjacent (e.g., coupled to) a respective pod **102** that is positioned next to the annular structure **502**. Another set of pods **102** may be positioned (e.g., coupled) in between the sets of two pods **102** extending from the annular structure **502**.

(108) As shown in FIG. **10**, the spacecraft servicing device **500** may have a differing configuration of pods **102** coupled about the annular structures **502**. For example, a select amount of pods **102** (e.g., three pods **102**) may be coupled to each port defined around the annular structures **502**. A second row of pods **102** may be positioned adjacent (e.g., coupled to) a respective pod **102** that is positioned next to the annular structure **502**. Another set of pods **102** may be positioned (e.g., coupled) on either side of the each respective pod **102** that is positioned next to the annular structure **502**.

(109) The embodiments of the disclosure described above and illustrated in the accompanying drawing figures do not limit the scope of the disclosure, since these embodiments are merely examples of embodiments of the disclosure, which is defined by the appended claims and their legal equivalents. Any equivalent embodiments are intended to be within the scope of this disclosure. Indeed, various modifications of the present disclosure, in addition to those shown and described herein, such as alternative useful combinations of the elements described, may become apparent to those skilled in the art from the description. Such modifications and embodiments are also intended to fall within the scope of the appended claims and their legal equivalents.

Claims

1. A spacecraft servicing device, comprising: a spacecraft body; a docking device coupled to the spacecraft body, the docking device for coupling the spacecraft servicing device to a target spacecraft; a boom arm coupled to the spacecraft body; and a thruster assembly coupled to a distal portion of the boom arm, the thruster assembly configured to maneuver at least one of the target spacecraft or the spacecraft body, the boom arm configured to alter an orientation of the thruster assembly relative to the spacecraft body as the boom arm is rotated about the spacecraft body and the docking device, wherein the boom arm is coupled to the spacecraft body at a rotatable coupling on the spacecraft body.
2. The spacecraft servicing device of claim 1, wherein the boom arm is coupled to the spacecraft body at a location adjacent to the docking device.
3. The spacecraft servicing device of claim 2, wherein the boom arm is configured to rotate about the rotatable coupling and at least partially about the docking device.
4. The spacecraft servicing device of claim 1, wherein the docking device comprises an expandable docking mechanism coupled to the spacecraft body.
5. The spacecraft servicing device of claim 4, where the expandable docking mechanism exhibits a spear shape with a distal end configured to be received in an engine of the target spacecraft.
6. The spacecraft servicing device of claim 4, wherein the spacecraft servicing device is configured to engage the expandable docking mechanism with the target spacecraft after being positioned by a host spacecraft.
7. The spacecraft servicing device of claim 4, wherein the expandable docking mechanism comprises one or more expandable portions configured to secure the expandable docking mechanism to the target spacecraft.
8. The spacecraft servicing device of claim 1, further comprising two solar arrays extending from either side of the spacecraft body.

9. The spacecraft servicing device of claim 1, further comprising one or more transceiver antennas positioned on the boom arm.
 10. A spacecraft servicing device, comprising: a spacecraft body; a docking mechanism coupled to the spacecraft body, the docking mechanism for coupling the spacecraft servicing device to a target spacecraft; a boom arm rotatably coupled to the spacecraft body; and a thruster assembly coupled to a distal portion of the boom arm, the thruster assembly configured to maneuver at least one of the target spacecraft or the spacecraft body, the thruster assembly comprising at least one thruster, the boom arm configured to alter the thruster assembly relative to the spacecraft body as the boom arm is rotated about the spacecraft body and at least partially about the docking mechanism.
 11. A method of servicing a spacecraft, the method comprising: engaging a target spacecraft with a servicing device at a coupling mechanism of the servicing device; rotating a thruster assembly coupled to a distal portion of a boom arm of the servicing device at least partially about the coupling mechanism of the servicing device; and maneuvering at least one of the target spacecraft or the servicing device with the thruster assembly of the servicing device.
 12. The method of claim 11, further comprising extending the coupling mechanism of the servicing device comprising an extendable lance to the target spacecraft to engage the target spacecraft.
 13. The method of claim 11, further comprising positioning the servicing device proximate to the target spacecraft with a host spacecraft.
 14. The method of claim 13, further comprising releasing the servicing device from the host spacecraft after the servicing device is coupled to the target spacecraft.
 15. The method of claim 11, further comprising engaging the target spacecraft with one or more expandable portions of the coupling mechanism of the servicing device.
 16. The method of claim 11, further comprising extending solar arrays from one or more sides of the servicing device.
 17. The method of claim 11, further comprising latching the thruster assembly and the boom arm in a retracted position with a latching mechanism.
 18. The method of claim 11, further comprising positioning the coupling mechanism and the boom arm on the same side of the servicing device.
 19. The method of claim 11, further comprising receiving one or more signals with one or more transceiver antennas positioned on the boom arm.
 20. The method of claim 11, further comprising configuring the servicing device to only comprise the thruster assembly on the boom arm while lacking any additional thruster assemblies.
-