

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12416212
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Atkins; Paul

Milling tool

Abstract

A milling tool for cutting an outer casing string of a wellbore, the milling tool comprising a tool body, an extendable cutting member located in the tool body configured to cut the outer casing string, and an extendable reaming block located in the tool body configured to clean a window formed in an inner casing string of the wellbore, wherein the reaming block is configured to extend from the tool body independently from the cutting member, and wherein the cutting member and the reaming block are configured to extend from the tool body by circulating drilling fluid through the milling tool.

Inventors:	Atkins; Paul (Phuket, TH)
Applicant:	Atkins; Paul (Phuket, TH)
Family ID:	1000008819998
Appl. No.:	17/766354
Filed (or PCT Filed):	October 20, 2020
PCT No.:	PCT/AU2020/051130
PCT Pub. No.:	WO2021/077160
PCT Pub. Date:	April 29, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230265727 A1	Aug. 24, 2023

Foreign Application Priority Data

SG	10201909833S	Oct. 21, 2019
----	--------------	---------------

Publication Classification

Int. Cl.: E21B29/00 (20060101)

U.S. Cl.:

CPC E21B29/005 (20130101);

Field of Classification Search

CPC: E21B (29/005); E21B (29/00); E21B (29/002); E21B (10/322); E21B (10/345)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2548931	12/1950	Baker	175/269	E21B 10/322
2654575	12/1952	Kammerer	175/391	E21B 10/345
2690897	12/1953	Clark, Jr.	175/266	E21B 29/005
3050122	12/1961	Huitt	175/269	E21B 47/095
4431065	12/1983	Andrews	175/269	E21B 10/567
4893675	12/1989	Skipper	N/A	N/A
5070952	12/1990	Neff	175/426	E21B 10/46
5810079	12/1997	Lynde	166/55.6	E21B 29/002
2011/0220357	12/2010	Segura	166/55.3	E21B 29/005
2013/0199785	12/2012	Hekelaar	166/55.7	E21B 29/005
2015/0275605	12/2014	Bennett et al.	N/A	N/A
2015/0354306	12/2014	Fuller	166/55.7	E21B 17/1078

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2011/115941	12/2010	WO	N/A
2012/087712	12/2011	WO	N/A
2012/087712	12/2011	WO	N/A
2015/054227	12/2014	WO	N/A
2015/054227	12/2014	WO	N/A
2015/191572	12/2014	WO	N/A

OTHER PUBLICATIONS

International Search Report Issued—Nov. 24, 2020 For Corresponding PCT Application No. PCT/AU2020/051130. cited by applicant

Supplemental Partial European Search Report Issued on Nov. 2, 2023 For Corresponding European Patent Application No. 20879434.7. cited by applicant

Primary Examiner: Gray; George S

Attorney, Agent or Firm: Michelle L. Gross, P.C.

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application is a National Stage Application, filed under 35 U.S.C. 371, of International Patent Application No. PCT/AU2020/051130, filed on Oct. 20, 2020, which claims priority to Singapore patent application Ser. No. 10/201,909833S filed on Oct. 21, 2019, contents of both of which are incorporated herein by reference in their entireties.

FIELD OF THE INVENTION

(2) The invention relates to a milling tool. In particular, the invention relates, but is not limited, to a milling tool in the form of a dual string section mill for cutting/milling a window in an outer casing string of a wellbore and an expandable under-reamer.

BACKGROUND TO THE INVENTION

(3) Reference to background art herein is not to be construed as an admission that such art constitutes common general knowledge in Singapore or elsewhere.

(4) Oil and gas wells are ordinarily completed by first cementing metallic casing strings in the borehole. Depending on the properties of the formation (e.g., formation porosity), dual casing strings may be employed, for example, including a smaller diameter casing string (inner string) deployed internal to a larger diameter casing string (outer casing string). In such dual or multiple casing string wellbores, the internal string is commonly cemented to the larger diameter string (i.e., the annular region between the first and second strings is filled or partially filled with cement).

(5) When oil and gas wells are no longer commercial viable, they must be abandoned in accordance with local government regulations. In certain jurisdictions, well abandonment requires a length of the wellbore casing to be removed prior to filling the wellbore with a cement plug. The inner casing string is commonly removed via a milling operation that employs a single inner string section milling tool. However, milling a dual outer casing string typically requires a dual string section mill with larger knife extension sweep/arc than the single inner string section milling tool used for milling the inner casing string. A separate inner string window clean out operation may also be required to remove the cement layer or other debris located between the inner and outer casing strings. These multiple operations are both time consuming and expensive and therefore are undesirable. Milling blades are prone to failure as they can bend or break during use. The use of larger diameter milling blades can also be problematic in that the larger blades are subject to increased shear and torsional loads. Larger diameter blades are also difficult to fully collapse into a tool body.

OBJECT OF THE INVENTION

(6) It is an aim of this invention to provide a milling tool which overcomes or ameliorates one or more of the disadvantages or problems described above, or which at least provides a useful alternative.

(7) Other preferred objects of the present invention will become apparent from the following description.

SUMMARY OF INVENTION

(8) In one form, although not necessarily the only or broadest form, the invention resides in a milling tool for cutting an outer casing string of a wellbore, the milling tool comprising: a tool body; an extendable cutting member located in the tool body configured to cut the outer casing string; and an extendable reaming block located in the tool body configured to clean a window formed in an inner casing string of the wellbore, wherein the reaming block is configured to extend from the tool body independently from the cutting member, and wherein the cutting member and the reaming block are configured to extend from the tool body by circulating drilling fluid through the milling tool.

- (9) Preferably, the milling tool is a dual string section mill. Preferably, the milling tool has a first end and a second end. Preferably, the first and second ends can be coupled with a drill string.
- (10) Preferably, the tool body has an inner assembly and an outer assembly. Preferably, the inner assembly has an inner housing and an inner mandrel connected to the inner housing. Preferably, the cutting member is connected to the inner housing.
- (11) Preferably, the inner housing has a central bore that provides a fluid pathway for the drilling fluid. Preferably, the inner mandrel is aligned with the central bore of the inner housing.
- (12) Preferably, the inner housing comprises a J-slot portion that engages with the outer housing. Preferably, engagement of the J-slot portion with the outer housing allows for rotational torque to be transmitted to the outer assembly from the inner assembly.
- (13) Preferably, the cutting member comprises a knife arm. Preferably, a distal portion of the knife arm includes a plurality of cutting elements. Preferably, the milling tool includes at least three cutting members.
- (14) Preferably, the cutting member engages with the reaming block. Preferably, an engaging portion of the cutting member engages with an engaging portion of the reaming block. Preferably, the engaging portion of the cutting member includes a linear projection. Preferably, the engaging portion of the reaming block includes a linear recess.
- (15) Preferably, the outer assembly is slidable relative to the inner assembly. Preferably, the outer assembly includes an outer housing. Preferably, the outer housing includes a knife portion, a middle portion, a nozzle portion and a bottom portion.
- (16) Preferably, the knife portion of the outer housing includes a cut-out for the cutting member to extend through and a cut-out for the reaming block to extend through.
- (17) Preferably, the outer assembly further includes a piston assembly for extending the reaming block. Preferably, the piston assembly is located in the outer housing.
- (18) Preferably, the piston assembly includes a knife ramp support block. Preferably, the reaming block is connected to the knife ramp support block. Preferably, the knife ramp support block includes a recess that engages with the engaging portion of the cutting member. Preferably, engagement of the knife ramp support block with the cutting member extends the cutting member from the tool body.
- (19) Preferably, the piston assembly further includes a wedge rod that extends through the knife ramp support block. Preferably, the wedge rod includes a projection that extends through a cut-out in the knife ramp support block. Preferably, the wedge rod is movable with respect to the knife ramp support block.
- (20) Preferably, the inner mandrel extends through the wedge rod.
- (21) Preferably, the piston assembly further includes a piston head and a spring located between the piston head and the knife ramp support block. Preferably, movement of the piston head moves the wedge rod relative to the knife ramp support block. Preferably, movement of the wedge rod causes the projection of the wedge rod to engage with the reaming block. Preferably, engagement of the projection of the wedge rod with the reaming block extends the reaming block from the tool body.
- (22) Preferably, pressure of the drilling fluid in the bottom portion moves the piston head.
- (23) Preferably, the milling tool has a plurality of reaming blocks. Preferably, the milling tool has a first extendable reaming block and a second extendable reaming block located in the tool body. Preferably, the second reaming block is spaced from the first reaming block along a longitudinal axis of the milling tool. Preferably, the second projection extends through the cut-out in the knife ramp support block.
- (24) Preferably, the wedge rod includes a plurality of projections. Preferably, the wedge rod includes a first projection and a second projection spaced from the first projection along a longitudinal axis of the milling tool. Preferably, movement of the wedge rod causes the first projection of the wedge rod to engage with the first reaming block and the second projection of the wedge rod to engage with the second reaming block. Preferably, engagement of the first projection

of the wedge rod with the first reaming block extends the first reaming block from the tool body. Preferably, engagement of the second projection of the wedge rod with the second reaming block extends the first reaming block from the tool body.

(25) Preferably, the first reaming block and the second reaming block extend simultaneously from the tool body. Preferably, the first and second reaming blocks are pivotally connected to knife ramp support block.

(26) Preferably, the first and second reaming blocks extend in the same direction. Preferably, the first and second reaming blocks are identical in shape.

(27) Preferably, the first and second reaming blocks extend in the opposite directions. Preferably, the first reaming block extends towards the first end and the second reaming block extends towards the second end. Preferably, the second reaming block is larger than the first reaming block.

(28) Preferably, a nozzle is located on the tool body. Preferably, the nozzle is located in the nozzle portion of the outer housing. Preferably, the nozzle is an aperture formed in the nozzle portion. Preferably, when the first reaming block is extended, the drilling fluid can flow through the nozzle.

(29) Preferably, the milling tool further comprises a shear assembly.

(30) Preferably, the shear assembly includes a shear sleeve and a shear member releasably connected to the shear sleeve. Preferably, the shear assembly further includes a shear pin engaged with the shear sleeve and the shear member. Preferably, the shear pin prevents disengagement of the shear member from the shear sleeve.

(31) Preferably, the shear assembly includes: a shear sleeve; an outer disconnect member operatively connected to the shear sleeve; an inner disconnect member releasably engaged with the outer disconnect member; and a disconnect sleeve releasably engaged with the inner disconnect member.

(32) Preferably, a locking member is located between the outer disconnect member and the disconnect sleeve. Preferably, the locking member engages with the outer disconnect member. Preferably, a projection of the locking member engages with a recess of the outer disconnect member. Preferably, the locking member engages with the inner disconnect member. Preferably, a base of the locking member engages with the inner disconnect member. Preferably, the base of the locking member has an arcuate cross-sectional shape.

(33) Preferably, the shear assembly further includes a shear pin engaged with the inner disconnect member and the disconnect sleeve. Preferably, the shear pin prevents disengagement of the disconnect sleeve from the inner disconnect member.

(34) Preferably, the disconnect sleeve is located inside the inner disconnect member. Preferably, the locking member prevents disengagement of the disconnect sleeve from the inner disconnect member.

(35) Preferably, an O-ring is located between the disconnect sleeve and the inner disconnect member. Preferably, the O-ring prevents disengagement of the disconnect sleeve from the inner disconnect member.

(36) Preferably, the inner mandrel extends through the shear sleeve. Preferably, the shear sleeve is connected to the outer housing.

(37) Preferably, the milling tool can move between (i) a closed position where the cutting member and the reaming block are not extended, (ii) a first open position where the reaming block is extended and the cutting member is not extended, and (iii) a second open position where the cutting member and the reaming block are extended from the tool body.

(38) Preferably, disengagement of the shear member from the shear sleeve moves the milling tool to the second open position.

(39) In another form the invention resides in a method for cutting an outer casing string of a wellbore, the method comprising: inserting a milling tool in the wellbore; extending a reaming block located in a tool body of the milling tool; cleaning a window formed in an inner casing string of the wellbore by the reaming block; extending a cutting member located in the tool body; and

cutting the outer casing string by the cutting member, wherein the cutting member and the reaming block are extended from the tool body by circulating drilling fluid through the milling tool.

(40) Preferably, extending the reaming block includes moving a piston head located in the tool body by the drilling fluid. Preferably, moving the piston head includes applying force on the piston head by the drilling fluid.

(41) Preferably, extending the reaming block includes engaging a projection of a wedge rod with the reaming block.

(42) Preferably, cleaning the window formed in the inner casing string includes rotating the milling tool when the reaming block is extended into the window.

(43) Preferably, extending the cutting member includes disengaging a shear member connected to the tool body from a shear sleeve. Preferably, disengaging the shear member from the shear sleeve includes dropping a ball on to the shear member and circulating the drilling fluid through the milling tool.

(44) Preferably, extending the cutting member includes disengaging a disconnect sleeve from an inner disconnect housing. Preferably, extending the cutting member further includes disengaging the inner disconnect housing from an outer disconnect housing operatively connected to a shear sleeve. Preferably, the shear sleeve is connected to the tool body.

(45) Preferably, disengaging the disconnect sleeve from the inner disconnect housing includes shearing a shear pin engaged with the disconnect sleeve and the inner disconnect housing. Preferably, shearing the shear pin includes dropping a ball on to the disconnect sleeve and circulating the drilling fluid through the milling tool.

(46) Preferably, extending the cutting member further includes moving a knife ramp support block located in the tool body by the drilling fluid. Preferably, moving the knife ramp support block includes applying force on the shear sleeve by the drilling fluid.

(47) Preferably, cutting the outer casing string includes rotating the milling tool when the cutting member is extended into the window.

(48) Preferably, the milling tool is herein as described.

(49) Further features and advantages of the present invention will become apparent from the following detailed description.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) By way of example only, preferred embodiments of the invention will be described more fully hereinafter with reference to the accompanying figures, wherein:
- (2) FIG. 1 illustrates a cross-sectional view of a milling tool, according to an embodiment of the invention;
- (3) FIG. 2 illustrates a cross-sectional view of the milling tool shown in FIG. 1 with the reaming blocks extended;
- (4) FIG. 3 illustrates a cross-sectional view of the milling tool shown in FIG. 1 with the knife arm and reaming blocks extended;
- (5) FIG. 4 illustrates an alternative cross-sectional view of the milling tool shown in FIG. 1;
- (6) FIG. 5 illustrates a cross-sectional view of the milling tool shown in FIG. 4 with the reaming blocks extended;
- (7) FIG. 6 illustrates a cross-sectional view of the milling tool shown in FIG. 4 with the knife arms and reaming blocks extended;
- (8) FIGS. 7A and 7B illustrate partial cross-sectional views of a piston assembly of a milling tool according to a further embodiment of the invention;
- (9) FIG. 8 illustrates a cross-sectional view of a shear assembly of a milling tool according to a

further embodiment of the invention;

(10) FIGS. **9A-F** illustrate a cross-sectional view and multiple transverse cross-sectional views of a milling tool according to a further embodiment of the invention;

(11) FIGS. **10A-C** illustrate a cross-sectional view and multiple transverse cross-sectional views of the milling tool shown in FIG. **9** with the knife arm and reaming blocks extended;

(12) FIGS. **11A-F** illustrate cross-sectional view and multiple transverse cross-sectional views of a milling tool according to a further embodiment of the invention;

(13) FIGS. **12A-E** illustrate a cross-sectional view and multiple transverse cross-sectional views of the milling tool shown in FIG. **11** with the knife arm and reaming blocks extended;

(14) FIG. **13** illustrates a knife arm that can be installed in the milling tool shown in FIG. **1**, **7A**, **8**, **9A-F** or **11A-F**;

(15) FIG. **14** illustrates an alternative knife arm that can be installed in the milling tool shown in FIG. **1**, **7A**, **9A-F** or **11A-F**;

(16) FIG. **15** illustrates a reaming block that can be installed in the tool shown in FIG. **1**, **7A**, **8**, **9A-F** or **11A-F**; and

(17) FIG. **16** illustrates an alternative reaming block that can be installed in the milling tool shown in FIG. **1**, **7A**, **8**, **9A-F** or **11A-F**.

DETAILED DESCRIPTION OF THE DRAWINGS

(18) FIGS. **1-6** illustrate a milling tool in the form of a dual string section mill ('DSSM') **10** according to an embodiment of the invention. The DSSM **10** has a tool body including an inner assembly **100** and an outer assembly **200** that is connected and slidable relative to the inner assembly **100**. The DSSM **10** has a first end **11** (which is a distal end of the inner assembly **100**) and a second end **12** (which is a distal end of the outer assembly **200**) which can be coupled with a drill string (or other tool string).

(19) The inner assembly **100** comprises a cylindrical inner housing **110** with a central bore that provides a fluid pathway for drilling fluid and an inner mandrel **120** which also has a central bore that is aligned with the central bore of the inner housing **100**.

(20) A proximal end of the inner housing **110** includes a J-slot portion **130** that has a diameter that is slightly greater than that of the remaining inner housing **100**. The J-slot portion **130** includes two recesses (in the form of J-slots) that are equally spaced from each other and located on opposite sides of the J-slot portion **130**, and a plurality of cutting members in the form of knife arms **140** connected to the J-slot portion **130**. Although only one knife arm **140** is shown in FIGS. **1-3**, the DSSM **10** includes three knife arms **140** that are equally radially spaced from each other, with the knife arms **140** being pivotally connected to the J-slot portion **130** at points that lie in a common plane that is perpendicular to a longitudinal axis **15** of the DSSM **10**. However, in further embodiments, the J-slot portion **130** may include only one or three or more recesses and/or the recesses may be shaped differently. Moreover, in further embodiments, the DSSM **10** may include only one, two or four or more knife arms, or the cutting members may be under-reaming arms instead of knife arms **140**.

(21) The distal portions of each knife arm **140** includes a plurality of cutting elements. Any cutting elements suitable for milling/removing cement and drilling formation may be utilized including, but not limited to, polycrystalline diamond cutter (PDC) inserts, thermally stabilized polycrystalline (TSP) inserts, diamond inserts, glyphaloy carbide inserts, boron nitride inserts, abrasive materials, and other cutting elements known to those skilled in the art. However, in further embodiments, the cutting elements may be located elsewhere on the knife arms **140**, for example, along the entire length of each knife arm **140**.

(22) Each knife arm **140** also includes a narrow engaging portion on its underside in the form of an elongate linear projection to engage with a respective reaming block **240a** and a respective recess of the knife ramp support block **221**. The engaging portion extends centrally from the distal portion of the knife arm **140** to about the centre of the knife arm **140**, along its length. However, in further

embodiments, the engaging portion may be differently shaped depending on the shape of the corresponding engaging portion of the reaming blocks **240a**.

(23) The inner mandrel **120** is connected to and extends from an end of the J-slot portion **130**, through the outer assembly **200** and terminates in a pressure chamber **217** of the outer assembly **200**. Drilling fluid is pumped into the inner mandrel **120** from the first end **11** of the DSSM **10** (through the central bore of the inner housing **110**) and flows out through the other end of the inner mandrel **120** into the pressure chamber **217**, exiting the DSSM **10** at its second end **12**.

(24) The outer assembly **200** includes a cylindrical outer housing **210**, a piston assembly **220** for extending reaming blocks **240a**, **240b**, and a shear assembly **230** to prevent premature movement of the outer assembly **200** with respect to the inner assembly **100**. The outer assembly **200** extends from the second end **12** of the DSSM **10** and terminates at a distance from the first end **11** of the DSSM **10**, i.e. there is a substantial overlap between the inner and outer assemblies **100**, **200**, with a substantial portion of inner assembly **100** located in the outer assembly **200**.

(25) The outer housing **210** of the outer assembly **200** is hollow and comprises a knife portion **211**, a middle portion **212**, a nozzle portion **213** and a bottom portion **214**. An end of the knife portion **211** that is proximate to the first end **11** of the DSSM **10** is connected to a debris cap **215**, with the other end of the knife portion **211** being connected to an end of the middle portion **212**. The other end of the middle portion **212** (that is not connected to the knife portion **211**) is connected to an end of the nozzle portion **213** and the other end of the nozzle portion **213** (that is not connected to the middle portion **212**) is connected to an end of the bottom portion **214**. The other end of the bottom portion **214** (that is not connected to the nozzle portion **213**) forms the second end **12** of the DSSM **10**. However, in further embodiments, the outer housing **210** may comprise only two or five or more portions connected to each other or the outer housing **210** may be integrally formed.

(26) The knife portion **211** of the outer housing **210** includes several cut-outs for the knife arms **140** and reaming blocks **240a**, **240b** to extend radially outwards from the knife portion **211** of the outer housing **210** of the DSSM **10**. Each cut-out is located adjacent to one of the knife arms **140** or reaming blocks **240a**, **240b** and is sized such that a portion of the knife arm **140** or reaming block **240a**, **240b** can extend outwardly through the cut-out.

(27) The knife portion **211** of the outer housing **210** encases the J-slot portion **130** of the inner housing **110** and includes internal lugs extending radially inwards from the inner wall of the knife portion **211**, with each lug engaging with one of the recesses (J-slots) of the J-slot portion **130**. The mating of the internal lugs of the knife portion **211** of the outer housing **210** with the recesses of the J-slot portion **130** of the inner housing **110** allows for rotational torque to be transmitted to the outer assembly **200** from the inner assembly **100**, i.e. the outer assembly **200** can be rotated by rotating the inner assembly **100**.

(28) The piston assembly **220** extends through the knife portion **211**, the middle portion **212** and the nozzle portion **213** of the outer housing **210** and includes a knife ramp support block **221** to which the reaming blocks **240a**, **240b** are connected, a wedge rod **222** extending partially through the knife ramp support block **221**, a piston head **223** and a compression spring **224** located between the wedge rod **222** and the piston head **223**. Both, the knife ramp support block **221** and the wedge rod **222**, have a hollow central tubular portion, with the inner mandrel **120** extending through the hollow portion of the wedge rod **222** and the wedge rod **222** extending through the hollow portion of the knife ramp support block **221**.

(29) An end of the knife ramp support block **221** that is proximal to the first end **11** of the DSSM **10** has a frustoconical portion with three recesses, each recess providing a path for a knife arm **140** to slide along. The recesses are equally spaced from each other and run substantially along the entire length of the frustoconical portion. However, in further embodiments, the frustoconical portion of the knife ramp support block **221** may be differently shaped and/or include only one, two or four or more recesses depending on the number of knife arms **140**.

(30) The main body of the knife ramp support block **221** (without the frustoconical portion) is

tubular in shape with three elongate cut-outs formed in the wall of the knife ramp support block **221**. The cut-outs of the main body of the knife ramp support block **221** are equally radially spaced from each other and extend completely through the wall of the knife ramp support block **221**.

(31) Each cut-out of the main body of the knife ramp support block **221** has two reaming blocks **240a**, **240b** located therein, with the reaming blocks **240a** longitudinally spaced from the reaming blocks **240b** along the cut-out, i.e. three reaming blocks **240a** are pivotally connected to the knife ramp support block **221** proximate to the end with the frustoconical portion and the other three reaming blocks **240b** are pivotally connected to the knife ramp support block **221** proximate to the other end of the knife ramp support block **221** that is distal to the frustoconical portion. When the reaming blocks **240a**, **240b** are in the retracted configuration and located completely inside the outer housing **210**, each of the reaming blocks **240a**, **240b** extends towards the second end **12** of the DSSM **10**. When extended, each of the reaming blocks **240a**, **240b** pivots radially outwards towards the first end **11** of the DSSM **10**.

(32) The reaming blocks **240a** are equally radially spaced from each other and are also equally longitudinally spaced from their respective reaming blocks **240b** (that are located in the same cut-out). Similar to the reaming blocks **240a**, the reaming blocks **240b** are also equally radially spaced from each other.

(33) Similar to the knife arms **140**, the distal portion of each reaming block **240a**, **240b** includes a plurality of cutting elements. Any cutting elements suitable for milling/removing cement may be utilized including, but not limited to, polycrystalline diamond cutter (PDC) inserts, thermally stabilized polycrystal line (TSP) inserts, diamond inserts, glyphaloy carbide inserts, boron nitride inserts, abrasive materials, and other cutting elements known to those skilled in the art. However, in further embodiments, the cutting elements may be located elsewhere on the reaming blocks **240a**, **240b**, for example, along the entire length of each reaming block **240a**, **240b**.

(34) Each of the reaming blocks **240a** also includes an engaging portion in the form of an elongate linear recess to engage with the engaging portion of each respective knife arm **140**. The engaging portion of each reaming block **240a**, **240b** extends centrally along the length of the reaming block **240a**, **240b**. Although, in use, only the engaging portions of reaming blocks **240a** engage with engaging portions of respective knife arms **140**, the reaming blocks **240a** and reaming blocks **240b** are identical in shape to allow for interchangeability and ease of manufacture.

(35) The wedge rod **222** is in the shape of a hollow cylinder with two sets of projections extending radially outwards from the wall of the wedge rod **222**. Each set of the projections includes three equally radially spaced projections, with each projection having a trapezoidal shape and the two sets of projections being longitudinally spaced from each other. The projections of the wedge rod **222** align with and extend through the cut-outs of the main body of the knife ramp support block **221** such that movement of the wedge rod **222** relative to the knife ramp support block **221** results in the projections of the wedge rod **222** sliding longitudinally in the cut-outs of the main body of the knife ramp support block **221**.

(36) The portion of the wedge rod **222** with the projections extends through the knife ramp support block **221** while the remaining body of the wedge rod **222** extends through the middle portion **212** of the outer housing **210** and is connected to the piston head **223** at an end of the wedge rod **222** such that movement of the piston head **223** relative to the outer housing **210** results in the movement of the wedge rod **222** relative to the knife ramp support block **221**. The spring **224** is also located in the middle portion **212** of the outer housing **210** and extends around the wedge rod **222**, between the knife ramp support block **221** and the piston head **223**, i.e. the wedge rod **222** extends through the central cavity of the spring **224** along its longitudinal axis.

(37) The piston head **223** has a hollow cylindrical body with a first end facing the first end **11** of the DSSM **10** and a second end facing the second **12** of the DSSM **10**, with the inner mandrel **120** extending through the piston head **223** from the first to second end. The opening at the first end of the piston head **223** is sized such that no fluid can flow through the opening while the inner

mandrel **120** extends through it (except the fluid flowing through the inner mandrel **120** itself). The opening at the second end of the piston head **223** is larger than the opening at the first end of the piston head **223** and allows for fluid to enter the hollow body of the piston head **223**.

(38) The nozzle portion **213** of the outer housing **210** includes a plurality of nozzles **216** in the form of apertures (not shown in FIGS. **4-6**) located in the cylindrical wall of the nozzle portion **213**. The nozzles **216** extend substantially through the wall of the nozzle portion **213** such that fluid can flow from inside the hollow body of the nozzle portion **213**, through the nozzles **216** and to the exterior of the outer housing **210**. The internal openings of the nozzles **216** are normally restricted by the piston head **223** and become unrestricted only when the piston head **223** moves towards the first end **11** of the DSSM **10**.

(39) The bottom portion **214** has a first section, a second section (at the second end **12** of the DSSM **10**) and an intermediate section located between the first and second sections. The internal diameter of the first section is greater than the internal diameter of the second section, with the internal diameter of the intermediate section tapering from the internal diameter of the first section to the internal diameter of the second section. The first section of the bottom portion **214** forms the pressure chamber **217** into which the drilling fluid flows as it exits the inner mandrel **120**.

(40) A plate **218** is located at the junction of the first and intermediate sections of the bottom portion **214**. The plate **218** is disc-shaped with a plurality of apertures formed through the plate **218** such that the drilling fluid can flow through the apertures from first section to the second section of the bottom portion **214**.

(41) The shear assembly **230** comprises a shear sleeve **231**, a shear member **232** releasably connected to the shear sleeve **231** and a plurality of shear pins **233** (not shown in FIGS. **4-6**) located in the region where the shear sleeve **231** and shear member **232** are connected to each other. The shear sleeve **231** is connected to the end of the nozzle portion **213** that is connected to the bottom portion **214** and extends towards the second end **12** of the DSSM, through the bottom portion **214**. The shear sleeve **231** has a hollow cylindrical body with the inner mandrel **120** extending therethrough and includes a plurality of apertures in the portion that engages with the nozzle portion **213** such that fluid can flow from the bottom portion **214**, through the apertures and into the nozzle portion **213**.

(42) The shear member **232** also has a hollow cylindrical body with a portion of the shear member **232** extending through the inner mandrel **120**. The other portion of the shear member **232** which does not extend through the inner mandrel **120** has a comparatively smaller diameter that tapers towards the second end **12** of the DSSM **10**.

(43) The shear pins **233** prevent disengagement of the shear member **232** from the shear sleeve **231**, with a portion of each shear pin **233** being engaged with the shear sleeve **231** and another portion of each shear pin **233** being engaged with the shear member **232**. The shear member **232** disengages from the shear sleeve **231** only when the shear pins **233** have been sheared due to application of force.

(44) The milling tool (DSSM **10**) is used to mill a window (a circumferential cut along a length of the string) in an outer casing string of a dull-string wellbore, as well as to remove cement or other debris located in the window of the inner casing string and/or between the inner and outer casing strings. To mill a window in the outer casing string, the inner casing string is first milled by a separate milling tool to create a window in the inner casing string. The separate milling tool is retracted from the wellbore and the DSSM **10** is inserted (with the second end **12** as the leading end) into the wellbore in its place, with the DSSM **10** being in a closed position in which the knife arms **140** and the reaming blocks **240a**, **240b** are located entirely inside the outer housing **210** (as shown in FIGS. **1** and **4**).

(45) The DSSM **10** is first located at a point in the wellbore that is approximately 2 metres above the window of the inner casing string. The drilling fluid is then pumped into the DSSM **10** through the first end **11** and into the pressure chamber **217** (via the inner mandrel **120**). The flow of the

fluid out of bottom portion **214** is restricted due to the apertures provided in the plate **218** which leads to build-up of hydraulic pressure inside the pressure chamber **217**. The pressure exerts a force on the first end of the piston head **223** causing it to move towards the first end **11** of the DSSM **10**. The movement of the piston head **223** also causes the wedge rod **222** to move relative to the knife ramp support block **221** (towards the first end **11** of the DSSM **10**), thereby resulting in the projections of the wedge rod **222** moving along the cut-outs of the knife ramp support block **221** and causing the reaming blocks **240a**, **240b** to extend and pivot radially outwards through the cut-outs in the knife portion **211**.

(46) However, the extension of the reaming blocks **240a**, **240b** is greatly limited by the restricted space (clearance) between the DSSM **10** and the wall of the inner casing string, i.e. only a small portion of each of the reaming blocks **240a**, **240b** extends out of the outer housing **210** and is in contact with the wall of the inner casing string. With the pressure of the fluid being maintained, the DSSM **10** is further lowered into the wellbore until a reduction in the pressure of the fluid is observed. The reduction in the fluid pressure occurs when the DSSM **10** is lowered to a point where the reaming blocks **240a**, **240b** can extend completely (i.e. they extend into the window formed in the inner casing string) and the piston head **223** has moved sufficiently towards the first end **11** of the DSSM **10** so as to allow flow of fluid through the nozzles **216**. The reaming blocks **240a**, **240b** are able to extend to a maximum predetermined position, with the extension of the reaming blocks **240a**, **240b** being limited by a respective extension stop plate located on each reaming block **240a**, **240b**. With the reaming blocks **240a**, **240b** fully extended, the DSSM **10** is considered to have moved from a closed position to a first open position (as shown in FIGS. 2 and 5).

(47) The depth at which the reduction in the pressure of the fluid is observed provides a depth of the top end of the window formed in the inner casing string. The DSSM **10** is then lowered further such that the reaming blocks **240a** are located about 0.5 metres below the top end of the window formed in the inner casing string. Rotation of the DSSM **10** is then commenced (while the fluid pressure is maintained) by applying rotational torque to the inner housing **110** which causes the outer assembly **200** (including the reaming blocks **240a**, **240b**) to rotate. The rotation of the reaming blocks **240a**, **240b** in the window formed in the inner casing string cleans the window of cement and other debris. Notably, even when the reaming blocks **240a**, **240b** are full extended to the maximum predetermined position, no portion of the outer casing string is milled or cut as the extension of the reaming blocks **240a**, **240b** is appropriately configured. The entire length of the window formed in the inner casing string is cleaned by the reaming blocks **240a**, **240b** by lowering the DSSM **10** until set-down weight is observed on the reaming blocks **240b** (due to contact with the bottom end of the window formed in the inner casing string). The depth at which the set-down weight is observed confirms the depth/length of the window formed in the inner casing string.

(48) Next, rotation of the DSSM **10** is stopped and the DSSM **10** is raised/retracted slowly so as to allow the extended reaming blocks **240a**, **240b** to travel along the full length of the window formed in the inner casing string. If no overpull or set-down weight is observed, the window formed in the inner casing string is deemed to have been scrubbed clean by the reaming blocks **240a**, **240b**. However, if any overpull or set-down weight is observed when the reaming blocks **240a**, **240b** are travelling along the length of the window formed in the inner casing string, the rotation of the DSSM **10** is recommenced and the reaming blocks **240a**, **240b** are used to continue cleaning the window until no overpull or set-down weight is observed upon moving the reaming blocks **240a**, **240b** along the length of the window when the DSSM **10** is not rotating.

(49) Once it has been determined that the window formed in the inner casing string has been cleaned by the reaming blocks **240a**, **240b**, the circulation of drilling fluid and rotation of the DSSM **10** is stopped. As the pressure of the fluid in the pressure chamber **217** drops, the spring **224** forces the piston head **223** to move towards the second end **12** of the DSSM **10**, resulting in the reaming blocks **240a**, **240b** retracting back completely into the outer housing **210** until the DSSM

10 has moved back to the closed position.

(50) A shear ball is then dropped into the inner mandrel **120** from the first end **11** of the DSSM **10** and the DSSM **10** is moved to a position in the wellbore where the cut-outs for the knife arms **140** in the knife portion **211** are located approximately 0.5 metres below the top end of the window formed in the inner casing string. The shear ball travels along the inner mandrel **120** until it reaches the shear member **232**. The inner diameter of the shear member **232** is chosen such that further movement of the shear ball towards the second end **12** of the DSSM **10** is prevented. With the shear ball located in the shear member **232**, the drilling fluid is recirculated through the inner mandrel **120** causing the shear pins **233** to shear due to build-up of pressure in the inner mandrel **120**.

(51) The shearing of the shear pins **233** results in a pressure drop of the fluid (which is observed to provide indication of shearing of the shear pins **233**) as the shear member **232** is disengaged from the shear sleeve **231** and the fluid flows into the pressure chamber **217**. The circulation of the fluid is stopped when the pressure drop is observed. The shear member **232** and the shear pins **233** drop into the pressure chamber **217** onto the plate **218**.

(52) Next, rotation of the DSSM **10** is commenced and torque is measured. The measured torque provides a reference for expected torque when the DSSM **10** can rotate freely without any resistance ('free torque'). The circulation of drilling fluid through the DSSM **10** is then restarted and, as the pressure of the fluid in the pressure chamber **217** increases, the piston head **223** moves towards the first end **11** of the DSSM **10** and the reaming blocks **240a**, **240b** are extended to their maximum extendable length. Further, with the shear member **232** disengaged from the shear sleeve **231**, the shear sleeve **231** is now free to move along the inner mandrel **120**. Accordingly, due to the pressure of the fluid in the pressure chamber **217**, the entire outer assembly **200** moves relative to the inner assembly **100** towards the first end **11** of the DSSM **10**.

(53) As the knife ramp support block **221** of the outer assembly **200** moves towards the first end **11** of the DSSM **10**, the engaging portions of the knife arms **140** slide along the respective recesses of the frustoconical portion of the knife ramp support block **221** to extend the knife arms **140** radially outwards from the respective cut-outs in the knife portion **211** until the distal tips of the knife arms **140** come into contact with the outer casing string. However, the knife arms **140** are only partially extended (about half of the maximum possible extendable length) when they first come into contact with the outer casing string. Further, as the knife arms **140** extend outwards from the cut-outs of the knife portion **211**, the engaging portion on the underside of each knife arm **140** engages and slides along the engaging portion of its respective reaming block **240a**. Thus, each reaming block **240a** provides additional support to the respective knife arm **140**.

(54) As the DSSM **10** continues to rotate with the distal tips of the knife arms **140** in contact with the outer casing string, the knife arms **140** begin to cut the outer casing string. The torsional stresses acting on the knife arms **140** are distributed to the J-slot portion **130** of the inner housing **110** by the pivot pins which connect the knife arms **140** to the J-slot portion **130** and by the engagement of the engaging portions of the knife arms **140** and the reaming blocks **240a**.

(55) The knife arms **140** are able to extend to a maximum predetermined position, with the extension of the knife arms **140** being limited by a respective extension stop plate located on each knife arm **140**. When the entire thickness of the wall of the outer casing string has been milled by the knife arms, the knife arms **140** (and the reaming blocks **240a**, **240b**) are fully extended and the DSSM **10** is considered to have moved to a second open position (as shown in FIGS. 3 and 6).

(56) The torque is continually measured as the DSSM **10** rotates and the knife arms **140** mill the outer casing string. Reduction of the torque to the value previously measured as the 'free torque' indicates that the particular section of the outer casing string has been completely cut/milled by the knife arms **140**. The DSSM **10** is lowered in the wellbore, while rotating, to allow the knife arms **140** to cut the outer casing string along the window formed in the inner casing string until the reaming blocks **240b** are approximately 0.5 metres above the bottom end of the window formed in the inner casing string. This results in the formation of a window in the outer casing string with a

total length/depth of approximately 2 metres less than the total length/depth of the window formed in the inner casing string.

(57) Next, rotation of the DSSM **10** is stopped and the DSSM **10** is raised/retracted slowly so as to allow the extended knife arms **140** to travel along the full length of the window formed in the outer casing string. If no overpull or set-down weight is observed, the window formed in the outer casing string is deemed to have been milled clean by the knife arms **140**. However, if any overpull or set-down weight is observed when the knife arms **140** are travelling along the length of the window formed in the outer casing string, the rotation of the DSSM **10** is recommenced and the knife arms **140** are used to continue cleaning the window until no overpull or set-down weight is observed upon moving the knife arms **140** along the length of the window when the DSSM **10** is not rotating.

(58) Once it has been determined that the window formed in the outer casing string has been cleaned by the knife arms **140**, the circulation of drilling fluid and rotation of the DSSM **10** is stopped. As the fluid pressure in the pressure chamber **217** drops, the piston head **223** and remaining the outer assembly **200** move downwards towards the second end **12** of the DSSM **10** resulting in the knife arms **140** and the reaming blocks **240a**, **240b** being retracted completely into the outer housing **210** and the DSSM **10** moving back to the closed position.

(59) The milling tool (DSSM **10**) provides several advantages over similar known milling tools. The DSSM **10** is capable of cleaning the window formed in the inner casing string, as well as cutting a window in the outer casing string, without requiring the DSSM **10** to be retracted from the wellbore. Further, engagement of the knife arms **140** with the reaming blocks **240a** provides additional support for the knife arms **140** against failure of the knife arms **140** due to excessive torsional stresses, while having two sets of reaming blocks **240a**, **240b** provides stability to the milling tool when in use. The DSSM **10** can also be used as an under-reaming tool by replacing the knife arms **140** with suitable under-reaming arms. The DSSM **10**, when used as an under-reaming tool, can under-ream single string casing window to expose new formation for cement barrier placement, enlarge wellbores for greater cement coverage and zone isolation, and/or enlarge wellbores for gas injection storage.

(60) FIGS. 7A and 7B illustrate a portion of a piston assembly of a milling tool according to a further embodiment of the invention. The milling tool is in the form of a dual string section mill (DSSM) **20** and is substantially similar to the DSSM **10** with differences therebetween noted below.

(61) Like the DSSM **10**, the DSSM **20** includes a piston assembly **1220** having a knife ramp support block **1221** (partially shown), a wedge rod **1222** (partially shown), a piston head **1223** (not shown) and a compression spring **1224** (partially shown). The piston assembly **1220** also includes reaming blocks **1240a**, **1240b** pivotally connected to the knife ramp support block **1221**. However, unlike the reaming blocks **240a**, **240b** of the DSSM **10**, the reaming blocks **1240a** and reaming blocks **1240b** are not identical to each other and extend/pivot in opposite directions. Although, in their retracted configuration, the reaming blocks **1240a** extend towards the second end **22** (not shown) of the DSSM **20** (which is located beyond the spring **1223**), the reaming blocks **1240b** extend towards the first end (not shown) of the DSSM **20** (which is located beyond the reaming blocks **1240a**), i.e. the reaming blocks **240a**, **240b** extend in opposite directions relative to each other. Accordingly, when the wedge rod **1222** moves towards the first end relative to the knife ramp support block **1221**, the first set of projections of the wedge rod **1222** cause the reaming blocks **1240a** to pivot radially outwards towards the first end while the second set of projections of the wedge rod **1222** cause the reaming blocks **1240b** to pivot radially outwards towards the second end **22** of the DSSM **20**.

(62) Further, although the reaming blocks **1240a** are similar in shape to the reaming blocks **240a**, **240b**, the reaming blocks **1240b** are differently shaped and are larger than the reaming blocks **1240a**. The larger reaming blocks **1240b** allow for greater surface contact for reaming/cutting cement to clean the window formed in the inner casing string and also provide greater stability.

(63) FIG. 8 illustrates a shear assembly **2230** of a milling tool according to a further embodiment of the invention. The milling tool is in the form of a dual string section mill (DSSM) **30** and is substantially similar to the DSSM **20** with differences therebetween noted below.

(64) Like the DSSM **20**, the DSSM **30** includes a shear assembly **2230**. However, the shear assembly **2230** of the DSSM **30** is differently shaped and operates in a different manner. The shear assembly **2230** comprises a shear sleeve **2231** (in the form of an outer disconnect anchor member), a shoulder member **2232**, an adjustment collar **2233**, an outer disconnect member **2234**, an inner disconnect member **2235** and a disconnect sleeve **2236**. The shear sleeve **2231** is connected to the end of the nozzle portion **2213** that is connected to the bottom portion **2214** and extends towards the second end **212** (not shown) of the DSSM, through the bottom portion **2214**. The shear sleeve **2231** has a hollow cylindrical body with the inner mandrel **2120** extending therethrough and includes a plurality of apertures in the end that engages with the nozzle portion **2213** such that fluid can flow from the pressure chamber **2217** (partially shown) of the bottom portion **2214**, through the apertures and into the nozzle portion **2213**.

(65) The other end of the shear sleeve **2231** (that is not connected to the nozzle portion **2213**) is threadingly connected to an end of the shoulder member **2232**. The shoulder member **2232** has a hollow cylindrical body with the inner mandrel **2120** extending therethrough and an internal diameter that is greater than the internal diameter of the shear sleeve **2231**. The other end of the shoulder member **2232** (that is not connected to the shear sleeve **2231**) has a radial flange extending radially outwards that engages with and supports a corresponding radial flange (that extends radially inwards) located at an end of the adjustment collar **2233**. The shoulder member **2232** also has an intermediate threaded portion that threadingly engages with a locking ring **2237**. The locking ring **2237** can be used to tighten the engagement of the flanges of the shoulder member **2232** and the adjustment collar **2233** with each other.

(66) The adjustment collar **2233** has a hollow cylindrical body with an internal diameter that is greater than the internal diameter of the shoulder member **2232**. The other end of the adjustment collar **2233** (this is not engaged with the shoulder member **2232**) is threadingly connected to an end of the outer disconnect member **2234**.

(67) The outer disconnect member **2234** also has a hollow cylindrical body with an external diameter that is less than the internal diameter of the adjustment collar **2233**, and an internal diameter that is greater than the internal diameter of the shoulder member **2232**. The other end of the outer disconnect member **2234** (that is not connected to the adjustment collar **2233**) includes two circumferential recesses located on the inner wall of the outer disconnect member **2234**, with the recesses being shaped to engage with radially outwardly extending projections of three locking members **2238** located between the outer disconnect member **2234** and the disconnect sleeve **2236**.

(68) The inner disconnect member **2235** has a hollow cylindrical body with an external diameter that is less than the internal diameter of the outer disconnect member **2234**. The inner disconnect member **2235** is located inside the outer disconnect member **2234** with an end of the inner disconnect member **2235** being threadingly connected to the terminal end of the inner mandrel **2120**. A radial flange extending radially inwards is formed at a point on the inner wall of the inner disconnect member **2235** immediately below the terminal end of the inner mandrel **2120**. The inner disconnect member **2235** also includes three cut-outs formed on the body for the projections of the locking members **2238** to extend through.

(69) The other end of the inner disconnect member **2235** (that is not connected to the inner mandrel **2120**) includes four apertures for a portion of shearing pins **2239** to extend through. A portion of the shearing pins **2239** also extends through an external circumferential recess provided at an end of the disconnect sleeve **2236**. However, in further embodiments, any number of shear pins **2239** (and corresponding number of apertures in the inner disconnect member **2235**) and/or locking members **2238** (and corresponding number of cut-outs in the inner disconnect member **2235**) may be used.

(70) Each locking member **2238** has a base with an arcuate cross-sectional shape and two projections extending radially outwards from the base. The projections of each locking member **2238** extend through their respective cut-out in the inner disconnect member **2235** to engage with the recesses formed in the outer disconnect member **2234**. Further, a portion of the base of each locking member **2238** extends beyond the respective cut-out in the inner disconnect member **2235** to engage with the inner disconnect member **2235**. The base of each locking member **2238** is also in contact with the outer surface of the disconnect sleeve **2236**.

(71) The disconnect sleeve **2236** has a hollow cylindrical body with an internal diameter that is slightly less than the internal diameter of the inner mandrel **2120**. The disconnect sleeve **2236** is located inside the inner disconnect member **2235** and is held in place by an O-ring (not shown) located between the disconnect sleeve **2236** and the inner disconnect member **2235**, and the locking members **2238** (by compressive force exerted onto the disconnect sleeve **2236** by the locking members **2238**). Movement of the disconnect sleeve **2236** relative to the inner disconnect member **2235** is further restricted by the shear pins **2239**. The disconnect sleeve **2236** disengages from the inner disconnect member **2235** only when the shear pins **2239** have been sheared due to application of force.

(72) In use, to move the DSSM **30** to the second open position (with the knife arms and the reaming blocks extended), a shear ball is first dropped into the inner mandrel **2120** from the first end **211** (not shown) of the DSSM **30**. The shear ball travels along the inner mandrel **2120** until it reaches the inner disconnect member **2235**. The inner diameter of the inner disconnect member **2235** is chosen such that further movement of the shear ball towards the second end **212** of the DSSM **30** is prevented. The drilling fluid is then circulated through the inner mandrel **120** causing the shear pins **2239** to shear due to build-up of pressure in the inner mandrel **2120**. The inner disconnect member **2235**, the shear pins **2239** and the locking members **2238** drop into the pressure chamber **2217** onto the plate **2218** (not shown). With the locking members **2238** disengaged from the outer disconnect member **2234** and the inner disconnect member **2235**, the inner disconnect member **2235** is free to move relative to the outer disconnect member **2234**, which allows the outer assembly to move relative to the inner assembly to move the DSSM **30** to the second open position.

(73) The shear assembly **2230** can be used with the DSSM **10** in place of the shear assembly **230**, or with any other tool where a hydraulic disconnect/shear assembly is required. Further, the shear assembly **2230** may be used in other milling tools configured to cut an outer casing string and/or an inner casing string of a wellbore.

(74) The configuration and design of the shear assembly **2230** prevents premature shearing of the shearing pins **2239** (due to shock loads or rotational stress experienced during drilling operation) by transferring and applying the loads to the locking member **2238** instead of the shearing pins **2239**, thereby isolating the shearing pins from any loads or stresses.

(75) FIGS. **9A-F** and **10A-C** illustrate a milling tool according to a further embodiment of the invention. The milling tool is in the form of a dual string section mill (DSSM) **40** and is substantially similar to the DSSM **10** with differences therebetween noted below.

(76) Like the DSSM **10**, the DSSM **40** includes a piston assembly **3220** having a knife ramp support block **3221**, a wedge rod **3222**, a piston head **3223** and a compression spring **3224**. The piston assembly **3220** also includes reaming blocks **3240a**, **3240b** pivotally connected to the knife ramp support block **3221**. However, unlike the reaming blocks **240a**, **240b** of the DSSM **10**, the reaming blocks **3240a** and reaming blocks **3240b** are not identical to each other and extend/pivot in opposite directions, similar to the reaming blocks **1240a**, **1240b** of the DSSM **20**. Accordingly, when the wedge rod **3222** moves towards the first end **41** relative to the knife ramp support block **3221**, the first set of projections of the wedge rod **3222** cause the reaming blocks **3240a** to pivot radially outwards towards the first end **41** while the second set of projections of the wedge rod **3222** cause the reaming blocks **3240b** to pivot radially outwards towards the second end **42** of the DSSM **40**.

(77) Further, like the DSSM **10**, the DSSM **40** includes a shear assembly **3230**. However, the shear assembly **3230** of the DSSM **40** is different from the shear assembly **230** of the DSSM **10**, and is instead identical to the shear assembly **2230** of the DSSM **30**.

(78) Transverse cross-section A (FIG. **9B**) taken along 'A-A' of FIG. **9A** shows the knife arms **3140** located entirely within the knife portion **3211** of the outer housing **3210**. Transverse cross-section B (FIG. **9C**) taken along 'B-B' of FIG. **9A** shows the distal tips of the knife arms **3140** and the knife ramp support block **3221**. Transverse cross-section C (FIG. **9D**) taken along 'C-C' of FIG. **9A** shows reaming blocks **3240b** located entirely within the knife portion **3211** of the outer housing **3210** and the knife ramp support block **3221**. Transverse cross-section D (FIG. **9E**) taken along 'D-D' of FIG. **9A** shows the shear sleeve **3231** and the nozzle portion **3213** of the outer housing **3210**. Transverse cross-section E (FIG. **9F**) taken along 'E-E' of FIG. **9A** shows some of the components of the shear assembly **3230** (outer disconnect member **3234**, an inner disconnect member **3235**, disconnect sleeve **3236** and locking members **3238**) located within the bottom portion **3214** of the outer housing **3210**.

(79) Transverse cross-section F (FIG. **10B**) taken along 'F-F' of FIG. **10A** shows the knife arms **3140** and reaming blocks **3240a** extending outwardly from the knife portion **3211** of the outer housing **3210**, and transverse cross-section G (FIG. **10C**) taken along 'G-G' of FIG. **10A** shows reaming blocks **3240b** extending outwardly from the knife portion **3211** of the outer housing **3210**.

(80) FIGS. **11A-F** and **12A-E** illustrate a milling tool according to a further embodiment of the invention. The milling tool is in the form of a dual string section mill (DSSM) **50** and is substantially similar to the DSSM **40** with differences therebetween noted below.

(81) Like the DSSM **40**, the DSSM **50** includes a piston assembly **4220** having a knife ramp support block **4221**, a wedge rod **4222**, a piston head **4223** and a compression spring **4224**. The piston assembly **4220** also includes reaming blocks **4240a**, **4240b** pivotally connected to the knife ramp support block **4221**. However, unlike the reaming blocks **3240a**, **3240b** of the DSSM **40**, the reaming blocks **4240a** and reaming blocks **4240b** extend/pivot in the same direction, towards the second end **52**. Accordingly, when the wedge rod **4222** moves towards the first end **51** relative to the knife ramp support block **4221**, the first and second set of projections of the wedge rod **4222** cause the reaming blocks **4240a** and reaming blocks **4240b** to pivot radially outwards towards the second end **52** of the DSSM **50**.

(82) FIGS. **11B-F** and **12B-E** also include transverse cross-sections A, B, C, D, E, F, G, H and I taken along 'A-A', 'B-B', 'C-C', 'D-D', 'E-E', 'F-F', 'G-G', 'H-H' and 'I-I' of FIGS. **11A** and **12A**, respectively.

(83) FIGS. **13** and **14** illustrate two types of knife arms that can be used as the knife arms in DSSM **10**, DSSM **20**, DSSM **30** and/or DSSM **40**.

(84) FIGS. **15** and **16** illustrate two types of reaming blocks that can be used as the reaming blocks in DSSM **10**, DSSM **20**, DSSM **30** and/or DSSM **40**.

(85) In this specification, adjectives such as first and second, forward and backward, upward and downward, top and bottom, proximal and distal, and the like may be used solely to distinguish one element or action from another element or action without necessarily requiring or implying any actual such relationship or order. Where the context permits, reference to an integer or a component or step (or the like) is not to be interpreted as being limited to only one of that integer, component, or step, but rather could be one or more of that integer, component, or step etc.

(86) The above description of various embodiments of the present invention is provided for purposes of description to one of ordinary skill in the related art. It is not intended to be exhaustive or to limit the invention to a single disclosed embodiment. As mentioned above, numerous alternatives and variations to the present invention will be apparent to those skilled in the art of the above teaching. Accordingly, while some alternative embodiments have been discussed specifically, other embodiments will be apparent or relatively easily developed by those of ordinary skill in the art. The invention is intended to embrace all alternatives, modifications, and variations

of the present invention that have been discussed herein, and other embodiments that fall within the spirit and scope of the above described invention.

(87) In this specification, the terms ‘comprises’, ‘comprising’, ‘includes’, ‘including’, or similar terms are intended to mean a non-exclusive inclusion, such that a method, system or apparatus that comprises a list of elements does not include those elements solely, but may well include other elements not listed.

Claims

1. A milling tool for cutting an outer casing string of a wellbore, the milling tool comprising: a tool body; an extendable cutting member located in the tool body configured to cut the outer casing string; and an extendable reaming block located in the tool body configured to clean a window formed in an inner casing string of the wellbore, wherein the reaming block is configured to extend from the tool body independently from the cutting member, wherein the cutting member and the reaming block are configured to extend from the tool body by circulating drilling fluid through the milling tool, wherein an engaging portion of the cutting member engages with and abuts an engaging portion of the reaming block, wherein the tool body has an outer assembly that includes a piston assembly for extending the reaming block, the piston assembly including a knife ramp support block, wherein an end of the knife ramp support block has a recess, the recess providing a path for the cutting member to slide along a being configured to engage with the cutting member.
2. The milling tool of claim 1, wherein a distal end of the cutting member is configured to extend beyond a distal end of the reaming block.
3. The milling tool of claim 1, wherein the engaging portion of the cutting member is an elongate projection located on an underside of the cutting member.
4. The milling tool of claim 1, wherein the engaging portion of the reaming block is an elongate recess.
5. The milling tool of claim 1, wherein the tool body has an inner assembly, the outer assembly being slidable relative to the inner assembly, wherein the inner assembly has an inner housing and an inner mandrel connected to the inner housing, the inner housing having a central bore that provides a fluid pathway for the drilling fluid, and wherein the cutting member is connected to the inner housing.
6. The milling tool of claim 5, wherein sliding engagement of the outer assembly with the inner assembly extends the cutting member from the tool body.
7. The milling tool of claim 1, wherein the reaming block is connected to the knife ramp support block.
8. The milling tool of claim 7, wherein engagement of the knife ramp support block with the cutting member extends the cutting member from the tool body.
9. The milling tool of claim 7, wherein the piston assembly includes a wedge rod that extends through the knife ramp support block, and wherein engagement of a projection of the wedge rod with the reaming block extends the reaming block from the tool body.
10. The milling tool of claim 1, wherein the milling tool has a first extendable reaming block and a second extendable reaming block that is spaced from the first reaming block along a longitudinal axis of the milling tool.
11. The milling tool of claim 10, wherein the first and second reaming blocks extend in the same direction relative to the longitudinal axis of the milling tool and towards a first end of the milling tool.
12. The milling tool of claim 10, wherein the first and second reaming blocks extend in opposite directions.
13. The milling tool of claim 1, wherein the milling tool is configured to move between (i) a closed position where the cutting member and the reaming block are not extended, (ii) a first open position

where the reaming block is extended and the cutting member is not extended, and (iii) a second open position where the cutting member and the reaming block are extended from the tool body.

14. The milling tool of claim 1, wherein the milling tool comprises a shear assembly, the shear assembly comprising: a shear sleeve; an outer disconnect member operatively connected to the shear sleeve; an inner disconnect member releasably engaged with the outer disconnect member; and a disconnect sleeve releasably engaged with the inner disconnect member.

15. A method for cutting an outer casing string of a wellbore, the method comprising: inserting a milling tool in the wellbore; extending a reaming block located in a tool body of the milling tool; cleaning, by the reaming block, a window formed in an inner casing string of the wellbore; extending a cutting member located in the tool body; and cutting the outer casing string by the cutting member, wherein the cutting member and the reaming block are extended from the tool body by circulating drilling fluid through the milling tool, And wherein an engaging portion of the cutting member engages with and abuts an engaging portion of the reaming block, wherein extending the cutting member includes engaging the cutting member with a knife ramp support block of an outer assembly of the tool body, wherein an end of the knife ramp support block has a recess, the recess providing a path for the cutting member to slide along and being configured to engage with the cutting member.

16. The method of claim 15, wherein extending the reaming block includes moving a piston head located in the tool body by applying force on the piston head by the drilling fluid, and/or wherein extending the reaming block includes engaging a projection of a wedge rod with the reaming block.

17. The method of claim 15, wherein extending the cutting member includes extending a distal end of the cutting member beyond a distal end of the reaming block.
