

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12416836
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Nomura; Morikazu

Liquid crystal display device

Abstract

Liquid crystal display device is provided and includes first substrate having a first surface; second substrate having second surface opposed to and spaced from first surface; liquid crystal layer disposed between first and second surfaces, signal lines extending in parallel including first signal line; and spacers protruding from second surface to first surface, spacers including first spacer and second spacer adjacent to first spacer, wherein spacers overlap signal lines, first and second spacers overlap first signal line, and arrangement of spacers on one signal line is staggered, such that: center of first spacer shifts to right side of first signal line; and center of second spacer shifts to left side of first signal line.

Inventors:	Nomura; Morikazu (Aichi, JP)
Applicant:	Magnolia White Corporation (Tokyo, JP)
Family ID:	1000008820046
Assignee:	Magnolia White Corporation (Tokyo, JP)
Appl. No.:	18/375765
Filed:	October 02, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240027842 A1	Jan. 25, 2024

Foreign Application Priority Data

JP	2012-048708	Mar. 06, 2012
----	-------------	---------------

Related U.S. Application Data

continuation parent-doc US 17869357 20220720 US 11774806 child-doc US 18375765
continuation parent-doc US 17215908 20210329 US 11397355 20220726 child-doc US 17869357
continuation parent-doc US 16538169 20190812 US 10962842 20210330 child-doc US 17215908
continuation parent-doc US 15459834 20170315 US 10379404 20190813 child-doc US 16538169
continuation parent-doc US 13740915 20130114 US 9638961 20170502 child-doc US 15459834

Publication Classification

Int. Cl.: **G02F1/1339** (20060101); **G02F1/1335** (20060101); **G02F1/1362** (20060101)

U.S. Cl.:

CPC **G02F1/1339** (20130101); **G02F1/13394** (20130101); G02F1/133512 (20130101);
G02F1/13396 (20210101); G02F1/136295 (20210101); G02F2201/503 (20130101)

Field of Classification Search

CPC: G02F (1/1339); G02F (1/13394); G02F (1/13396); G02F (1/136295); G02F (1/133512)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6774975	12/2003	Ahn	N/A	N/A
6788372	12/2003	Kaise et al.	N/A	N/A
8120252	12/2011	Cho	N/A	N/A
2007/0165179	12/2006	Jang	N/A	N/A
2008/0198317	12/2007	Tseng	N/A	N/A
2009/0122241	12/2008	Satoh	N/A	N/A
2009/0160748	12/2008	Kimura	N/A	N/A
2009/0168167	12/2008	Hiroya et al.	N/A	N/A
2010/0045906	12/2009	Tokuda et al.	N/A	N/A
2010/0118254	12/2009	Hashimoto	349/155	G02F 1/13394
2010/0201933	12/2009	Sonoda	349/141	G02F 1/133305
2010/0231842	12/2009	Ishitani	349/156	G02F 1/13394
2010/0302492	12/2009	Kubota et al.	N/A	N/A
2012/0268699	12/2011	Min et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101900913	12/2009	CN	N/A
09-105945	12/1996	JP	N/A
11-174487	12/1998	JP	N/A
2000-206541	12/1999	JP	N/A
2003-186023	12/2002	JP	N/A
2010-054622	12/2009	JP	N/A
2010-224097	12/2009	JP	N/A
2010-237660	12/2009	JP	N/A
201106069	12/2010	TW	N/A

OTHER PUBLICATIONS

Chinese Office Action issued Jul. 22, 2016 in corresponding Chinese Application No.

201310038708.1. cited by applicant

Japanese Office Action issued Mar. 3, 2015 in corresponding Japanese Application No. 2012-048708. cited by applicant

Taiwan Office Action issued Feb. 4, 2015 in corresponding Taiwanese Application No. 101142105. cited by applicant

Definition of word “at”, Merriam-Webster Online Dictionary; definition downloaded on Sep. 9, 2015. cited by applicant

Japanese Office Action issued Jan. 9, 2018 in corresponding Japanese Application No. 2017-047603. cited by applicant

Chinese Office Action issued Aug. 5, 2020 in corresponding Chinese Application No. 201810324948.0. cited by applicant

Primary Examiner: Medich; Angela M.

Attorney, Agent or Firm: K&L Gates LLP

Background/Summary

CROSS REFERENCES TO RELATED APPLICATIONS (1) The present application is a continuation of U.S. patent application Ser. No. 17/869,357, filed on Jul. 20, 2022, which application is a continuation of U.S. patent application Ser. No. 17/215,908, filed on Mar. 29, 2021, and issued as U.S. Pat. No. 11,397,355 on Jul. 26, 2022, which application is a continuation of U.S. patent application Ser. No. 16/538,169, filed on Aug. 12, 2019, and issued as U.S. Pat. No. 10,962,842 on Mar. 30, 2021, which application is a continuation of U.S. patent application Ser. No. 15/459,834, filed on Mar. 15, 2017, and issued as U.S. Pat. No. 10,379,404 on Aug. 13, 2019, which application is a continuation application of U.S. patent application Ser. No. 13/740,915, filed on Jan. 14, 2013, and issued as U.S. Pat. No. 9,638,961 on May 2, 2017, which application claims priority to Japanese Priority Patent Application JP 2012-048708 filed in the Japan Patent Office on Mar. 6, 2012, the entire content of which is hereby incorporated by reference.

BACKGROUND

(1) The present disclosure relates to a liquid crystal display device adapted to display an image, manufacturing method of the same and electronic equipment having the same.

(2) There is a type of liquid crystal display device that includes an array substrate, opposed substrate and liquid layer. The array substrate has a transistor formed in each of a plurality of pixel regions that are arranged in a matrix form. The opposed substrate is arranged to be opposed to the array substrate. The liquid crystal layer is formed between the array and opposed substrates. Each of the pixel regions includes an opening region adapted to pass light and light-shielding region surrounding the opening region.

(3) In such a liquid crystal display device, for example, an electric field based on image data is supplied to the liquid crystal layer from a pixel electrode and common electrode for each of the pixel regions, thus displaying a given image in each of the pixel region. This allows an image to be displayed, for example, on the outside of the opposed substrate.

(4) In such a liquid crystal display device, a spacer is formed between the array and opposed substrates to create a space in which to form the liquid crystal layer. The spacer is fixed in position,

for example, on the opposed substrate. Further, the spacer is arranged to coincide with the light-shielding region.

(5) Here, if the array or opposed substrate bends due to an external force, the two substrates may be misaligned with each other horizontally (in the direction parallel to the substrate surface). In this case, the spacer may squeeze out into the opening region of the array substrate, possibly damaging, for example, the orientation film or other film and the element arranged in the opening region. This may result in leakage of light.

(6) In contrast, a method is available to minimize the spacer from squeezing out of the light-shielding region in which the spacer is arranged by expanding the same region.

(7) Japanese Patent Laid-Open No. 2000-206541 is referred.

SUMMARY

(8) However, expanding the light-shielding region in which the spacer is arranged leads to a smaller opening region, thus making it difficult to use a liquid crystal display device adapted to display a high-definition image.

(9) In light of the foregoing, it is desirable to provide a liquid crystal display device, manufacturing method of the same and electronic equipment having the same that provide reduced likelihood of the spacer damaging the film and element arranged in the opening region while at the same time securing an area for the opening region.

(10) According to an embodiment of the present disclosure, there are provided a liquid crystal display device, manufacturing method of the same and electronic equipment having the same which will be described below.

(11) The liquid crystal display device includes a first substrate, a second substrate, a liquid crystal layer, a first spacer section, and a second spacer section. The first substrate has a first surface. The first surface includes a light-shielding region in a lattice form and a plurality of opening regions surrounded by the light-shielding region. The light-shielding region includes a plurality of first extended portions extending in a first direction and a plurality of second extended portions extending in a second direction that intersects the first direction. The first substrate has a plurality of transistors formed thereon. The second substrate has a second surface that is opposed to and spaced from the first surface. The liquid crystal layer is arranged between the first and second surfaces. The first spacer section has long sides oriented in the second direction and is formed on one of the first or second surfaces, arranged at one of a plurality of intersections obtained as a result of each of the plurality of first extended portions intersecting one of the plurality of second extended portions, and protrudes into the liquid crystal layer. The second spacer section has long sides oriented in the first direction, is formed on the other of the first or second surfaces, arranged at the intersection where the first spacer section is arranged in such a manner as to intersect the first spacer section, and protrudes into the liquid crystal layer.

(12) Further, the manufacturing method of the liquid crystal display device includes forming, on a first surface of a first substrate, a first spacer section having long sides in such a manner as to be located at one of a plurality of intersections obtained as a result of each of a plurality of first extended portions intersecting one of a plurality of second extended portions and have the long sides oriented in a second direction, the first substrate having the first surface, the first surface including a light-shielding region in a lattice form and a plurality of opening regions surrounded by the light-shielding region, the light-shielding region including the plurality of first extended portions extending in a first direction and the plurality of second extended portions extending in the second direction that intersects the first direction, the first substrate having a plurality of transistors formed thereon. The method further includes forming a second spacer section having long sides on a second surface of a second substrate, arranging the first and second substrates in such a manner that the first and second surfaces are opposed to and spaced from each other, that the second spacer section is arranged at the intersection where the first spacer section is arranged, that the second spacer section has long sides oriented in the first direction, and that the second spacer section

intersects the first spacer section, and forming a liquid crystal layer between the first and second surfaces.

(13) Still further, the electronic equipment includes a liquid crystal display device configured to display an image. The liquid crystal display device has a first substrate, a second substrate, a liquid crystal layer, a first spacer section, and a second spacer section. The first substrate has a first surface. The first surface includes a light-shielding region in a lattice form and a plurality of opening regions surrounded by the light-shielding region. The light-shielding region includes a plurality of first extended portions extending in a first direction and a plurality of second extended portions extending in a second direction that intersects the first direction. The first substrate has a plurality of transistors formed thereon. The second substrate has a second surface that is opposed to and spaced from the first surface. The liquid crystal layer is arranged between the first and second surfaces. The first spacer section has long sides oriented in the second direction and is formed on one of the first or second surfaces, arranged at one of a plurality of intersections obtained as a result of each of the plurality of first extended portions intersecting one of the plurality of second extended portions, and protrudes into the liquid crystal layer. The second spacer section has long sides oriented in the first direction, is formed on the other of the first or second surfaces, arranged at the intersection where the first spacer section is arranged in such a manner as to intersect the first spacer section, and protrudes into the liquid crystal layer.

(14) The liquid crystal display device, manufacturing method of the same and electronic equipment provide reduced likelihood of the spacer damaging the film and element arranged in the opening region while at the same time securing an area for the opening region.

(15) Additional features and advantages are described herein, and will be apparent from the following Detailed Description and the figures.

Description

BRIEF DESCRIPTION OF THE FIGURES

(1) FIGS. 1A and 1B are diagrams illustrating an example of a liquid crystal display device according to a first embodiment;

(2) FIG. 2 is a top view illustrating an array substrate and opposed substrate that are out of alignment with each other in the liquid crystal display device according to the first embodiment;

(3) FIG. 3 is a top view illustrating a liquid crystal display device according to a second embodiment;

(4) FIG. 4 is a partially enlarged view of spacer sections and their surrounding areas;

(5) FIG. 5 is a cross-sectional view along line B-B' in FIG. 3;

(6) FIGS. 6A to 6D are diagrams illustrating an example of a manufacturing method of the liquid crystal display device according to the second embodiment;

(7) FIG. 7 is a top view illustrating the array substrate and opposed substrate that are out of alignment with each other in the liquid crystal display device according to the second embodiment;

(8) FIG. 8 is a cross-sectional view illustrating modification example 1;

(9) FIG. 9 is a cross-sectional view illustrating an example of a liquid crystal display device according to a third embodiment;

(10) FIG. 10 is a cross-sectional view illustrating modification example 2;

(11) FIG. 11 is a cross-sectional view illustrating an example of a liquid crystal display device according to a fourth embodiment;

(12) FIG. 12 is a cross-sectional view illustrating modification example 3;

(13) FIG. 13 is a top view illustrating an example of a liquid crystal display device according to a fifth embodiment;

(14) FIG. 14 is a top view illustrating an example of a liquid crystal display device according to a

sixth embodiment;

(15) FIG. 15 is a diagram illustrating an example of appearance of a television set to which the liquid crystal display device is applied;

(16) FIGS. 16A and 16B are diagrams illustrating an example of appearance of a digital camera to which the liquid crystal display device is applied;

(17) FIG. 17 is a diagram illustrating an example of appearance of a laptop personal computer to which the liquid crystal display device is applied;

(18) FIG. 18 is a diagram illustrating an example of appearance of a video camcorder to which the liquid crystal display device is applied; and

(19) FIGS. 19A to 19G are diagrams illustrating an example of appearance of a mobile phone to which the liquid crystal display device is applied.

DETAILED DESCRIPTION

(20) A description will be given below of the preferred embodiments with reference to the accompanying drawings.

First Embodiment

(21) FIGS. 1A and 1B are diagrams illustrating an example of a liquid crystal display device according to a first embodiment. FIG. 1A illustrates a top view of a liquid crystal display device 10, and FIG. 1B a cross-sectional view along line A-A' in FIG. 1A. It should be noted that the top view of FIG. 1A does not show an opposed substrate 2 and liquid crystal layer 3.

(22) The liquid crystal display device 10 includes an array substrate 1, opposed substrate 2, liquid crystal layer 3, spacer sections 4 and 5 and orientation films 8 and 9.

(23) The array substrate 1 has, for example, a plurality of pixel regions that are arranged in a matrix form. TFTs (Thin Film Transistors) and pixel electrodes are formed in each of the pixel regions. A transparent glass substrate, for example, is used as the array substrate 1.

(24) Further, the array substrate 1 has a surface 1a and a surface 1b on the opposite side of the surface 1a. The surface 1a includes a light-shielding region 7 in a lattice form. The light-shielding region 7 includes a plurality of extended portions 11 extending in the X direction and a plurality of extended portions 12 extending in the Y direction. The X and Y directions are, for example, orthogonal to each other.

(25) Here, the light-shielding region 7 overlaps a light-shielding film (e.g., black matrix) or a light-shielding interconnect pattern such as gate and source lines formed on the array substrate 1 or opposed substrate 2. It should be noted that the light-shielding film is not shown.

(26) Further, the surface 1a has a plurality of opening regions 13 each of which is surrounded by the light-shielding region 7. That is, each of the opening regions 13 is exposed from the light-shielding interconnect pattern such as a light-shielding film, gate lines or source lines formed on the array substrate 1 or opposed substrate 2. Here, each of the opening regions 13 is associated with one of the pixel regions.

(27) A color filter and common electrode are, for example, formed on the opposed substrate 2. A transparent glass substrate, for example, is used as the opposed substrate 2. Further, the opposed substrate 2 has a surface 2a and a surface 2b on the opposite side of the surface 2a. The opposed substrate 2 is arranged in such a manner that the surface 2a is opposed to and spaced from the surface 1a of the array substrate 1.

(28) The liquid crystal layer 3 is arranged between the surface 1a of the array substrate 1 and the surface 2a of the opposed substrate 2. Here, an electric field based on image data is supplied to the liquid crystal layer 3 from a pixel electrode and common electrode for each of the pixel regions in the liquid crystal display device 10. This changes the orientation of liquid crystal molecules based on the supplied electric field for each of the pixel regions.

(29) In this condition, light from a backlight arranged on the side of the surface 1b of the array substrate 1 enters the liquid crystal display device 10 via a polarizing plate, passes through the liquid crystal layer 3 and leaves the liquid crystal display device 10 from the surface 2b of the

opposed substrate 2 via a polarizing plate, thus allowing a given image to be displayed on the surface 2b.

(30) The spacer section 4 is in a shape having long sides such as elliptical or rectangular shape. Also, the spacer section 4 is formed on the surface 1a of the array substrate 1 or the surface 2a of the opposed substrate 2 in such a manner as to protrude into the liquid crystal layer 3. In FIGS. 1A and 1B, the spacer section 4 is formed on the surface 1a of the array substrate 1. Further, the spacer section 4 has its long sides oriented in the Y direction and is arranged at one of a plurality of intersections obtained as a result of each of the plurality of extended portions 11 intersecting one of the plurality of extended portions 12. It should be noted that an orientation film 8 is formed on the surface 1a of the array substrate 1 to cover the spacer section 4.

(31) The spacer section 5 is in a shape having long sides such as elliptical or rectangular shape. Also, the spacer section 5 is formed on the surface 1a of the array substrate 1 or the surface 2a of the opposed substrate 2 in such a manner as to protrude into the liquid crystal layer 3. In FIGS. 1A and 1B, the spacer section 5 is formed on the surface 2a of the opposed substrate 2.

(32) Further, the spacer section 5 has its long sides oriented in the X direction and is arranged at the intersection where the spacer section 4 is arranged in such a manner as to intersect the spacer section 4. That is, the spacer sections 4 and 5 intersect as seen in the vertical direction (direction perpendicular to the surfaces 1a and 2a). It should be noted that the orientation film 9 is formed on the surface 2a of the opposed substrate 2 to cover the spacer section 5.

(33) This ensures that the gap between the surface 1a of the array substrate 1 and the surface 2a of the opposed substrate 2 is maintained constant by the spacer sections 4 and 5.

(34) As described above, the spacer sections 4 and 5 are formed respectively on the array substrate 1 and opposed substrate 2 of the liquid crystal display device 10. Further, the spacer section 4 has its long sides oriented in the Y direction and is arranged at one of the plurality of intersections obtained as a result of each of the plurality of extended portions 11 intersecting one of the plurality of extended portions 12. The spacer section 5 has its long sides oriented in the X direction and is arranged at the intersection where the spacer section 4 is arranged in such a manner as to intersect the spacer section 4.

(35) This configuration ensures overlapping of the spacer sections 4 and 5 even if the array substrate 1 and opposed substrate 2 are horizontally (that is, in a direction parallel to the surfaces 1a and 2a) misaligned due to bending of either of the substrates by an external force. As a result, it is possible to provide reduced likelihood of the spacer section formed on the opposed substrate 2 touching and damaging the film such as orientation film and the element arranged in the opening region 13.

(36) Further, this configuration contributes to reduced likelihood of the spacer formed on the opposed substrate 2 damaging the film and element arranged in the opening region 13 without widening the width (length along the Y direction) of the extended portions 11 of the light-shielding region 7 and the width (length along the X direction) of the extended portions 12 of the light-shielding region 7. That is, it is possible to provide reduced likelihood of the spacer damaging the film and element arranged in the opening region 13 while at the same time securing an area for the opening region 13.

(37) FIG. 2 is a top view illustrating the array substrate and opposed substrate that are out of alignment with each other in the liquid crystal display device according to the first embodiment.

(38) If, for example, the spacer section 5 is displaced in a diagonal direction D1 due to horizontal misalignment between the array substrate 1 and opposed substrate 2, the spacer section 5 partially overlaps an opening region 13a. However, an edge portion 5a of the spacer section 5 overlaps an edge portion 4a of the spacer section 4. That is, the spacer section 5 is supported by the spacer section 4 and does not touch the film or element arranged in the opening region 13a.

(39) Further, if, for example, the spacer section 5 is displaced in a diagonal direction D2, the spacer section 5 partially overlaps an opening region 13b. However, an edge portion 5b of the spacer

section 5 overlaps an edge portion 4b of the spacer section 4. That is, the spacer section 5 is supported by the spacer section 4 and does not touch the film or element arranged in the opening region 13a.

Second Embodiment

(40) A description will be given next of a second embodiment.

(41) FIG. 3 is a top view illustrating a liquid crystal display device according to the second embodiment. FIG. 4 is a partially enlarged view of the spacer sections and their surrounding areas. FIG. 5 is a cross-sectional view along line B-B' in FIG. 3. It should be noted that not only the components of an opposed substrate 30 other than a spacer section 74 but also a pixel electrode 68 are not shown in FIG. 3.

(42) A liquid crystal display device 100 includes an array substrate 20, opposed substrate 30 and liquid crystal layer 40. A pixel electrode 68 is formed on the array substrate 20, and a common electrode 73 on the opposed substrate 30 in the liquid crystal display device 100. Among such liquid crystal display devices are TN (Twisted Nematic) mode, VA (Vertical Alignment) mode and ECB (Electrically Controlled Birefringence) mode liquid crystal display devices.

(43) A description will be given first of the array substrate 20.

(44) The array substrate 20 includes a transparent substrate 21 having a surface 21a and a surface 21b on the opposite side of the surface 21a. A glass substrate, for example, is used as the transparent substrate 21. The surface 21a includes a light-shielding region 50 in a lattice form. The light-shielding region 50 includes a plurality of extended portions 51 extending in the X direction and a plurality of extended portions 52 extending in the Y direction. It should be noted that the X and Y directions are orthogonal to each other.

(45) Here, the light-shielding region 50 overlaps a light-shielding film (e.g., black matrix) or a light-shielding interconnect pattern such as gate lines 61 and source lines 63 formed on the array substrate 20 or opposed substrate 30. It should be noted that the light-shielding film is not shown. Further, the width (length in the Y direction) of the extended portions 51 of the light-shielding region 50 is greater than that (length in the X direction) of the extended portions 52 of the light-shielding region 50. It should be noted that a polarizing plate and backlight are arranged on the side of the surface 21b.

(46) Still further, the surface 21a has a plurality of opening regions 53 each of which is surrounded by the light-shielding region 50. That is, each of the opening regions 53 is exposed from the light-shielding interconnect pattern such as a light-shielding film, the gate lines 61 or source lines 63 formed on the array substrate 20 or opposed substrate 30.

(47) The plurality of gate lines 61 are formed on the surface 21a of the transparent substrate 21, each in such a manner as to extend in the X direction and overlap one of the extended portions 51 of the light-shielding region 50. A metal film, for example, is used as each of the gate lines 61. Further, an interlayer insulating film 62 is formed above the surface 21a to cover the gate lines 61. Still further, the plurality of source lines 63 are formed on the interlayer insulating film 62, each in such a manner as to extend in the Y direction and overlap one of the extended portions 52 of the light-shielding region 50. A metal film, for example, is used as each of the source lines 63.

(48) It should be noted that each of the regions surrounded by the two adjacent gate lines 61 and two adjacent source lines 63 on the surface 21a corresponds to a pixel region. A transistor including a gate electrode 61a, semiconductor layer 64 and drain electrode 65 is formed in each of the pixel regions.

(49) The semiconductor layer 64 has its one end connected to the drain electrode 65 and its other end connected to the source line 63. Further, the gate electrode 61a is arranged in such a manner as to overlap the semiconductor layer 64 with a gate insulating film provided therebetween. The same electrode 61a is connected to the gate line 61. That is, this transistor controls the passage of current between the source line 63 and drain electrode 65 based on the voltage supplied to the gate line 61.

(50) Further, an organic insulating film 66 is formed on the interlayer insulating film 62 to cover

the source lines **63**. Here, part of the organic insulating film **66** protrudes in the direction away from the surface **21a** of the transparent substrate **21**. This protruding portion forms a spacer section **67**. The spacer section **67** protrudes 0.2 μm or more into the opening regions **53**.

(51) The spacer section **67** is in a shape having long sides. Further, the spacer section **67** is arranged at one of the plurality of intersections obtained as a result of each of the plurality of extended portions **51** intersecting one of the plurality of extended portions **52** in such a manner as to have its long sides oriented in the Y direction. It should be noted that the plurality of spacer sections **67** may be formed. In this case, the spacer sections **67** are arranged at some of the plurality of intersections rather than all thereof.

(52) Further, the spacer section **67** has edge portions **67a** and **67b** and an intermediate portion **67c** provided between the edge portions **67a** and **67b**. The edge portions **67a** and **67b** are arranged to overlap one of the extended portions **52** of the light-shielding region **50**. The intermediate portion **67c** is arranged to overlap one of the extended portions **51**. Here, a width **W1** of the intermediate portion **67c** is greater than a width **W2** of the edge portions **67a** and **67b**.

(53) Still further, a plurality of pixel electrodes **68** are formed on the organic insulating film **66** to expose a top surface **67d** of the spacer section **67**. Each of the pixel electrodes **68** is connected to one of the drain electrodes **65**. A transparent electrode made, for example, of ITO (Indium Tin Oxide) or IZO (Indium Zinc Oxide) is used as the pixel electrode **68**. Further, an orientation film **69** is formed on the organic insulating film **66** to cover the top surface **67d** of the spacer section **67** and the pixel electrodes **68**.

(54) A description will be given next of the opposed substrate **30**.

(55) The opposed substrate **30** includes a transparent substrate **31** having a surface **31a** and a surface **31b** on the opposite side of the surface **31a**. A glass substrate, for example, is used as the transparent substrate **31**. The transparent substrate **31** is arranged in such a manner that the surface **31a** is opposed to the surface **21a** of the transparent substrate **21**. It should be noted that a polarizing plate is arranged on the side of the surface **31b**.

(56) Color filters **71a**, **71b** and **71c** are formed on the surface **31a** of the transparent substrate **31**. For example, the color filters **71a**, **71b** and **71c** are red, blue and green color filters, respectively. The color filters **71a**, **71b** and **71c** are provided for each of the pixel regions.

(57) Further, an overcoat layer **72** is formed on the color filters **71a**, **71b** and **71c**. Still further, the common electrode **73** is formed on the overcoat layer **72**. A transparent electrode made, for example, of ITO or IZO is used as the common electrode **73**.

(58) Still further, the spacer section **74** is formed on the common electrode **73**. The same section **74** is made, for example, of an acrylic resin. On the other hand, the spacer section **74** is in an elliptical shape. It should be noted that the spacer section **74** may be in a rectangular shape rather than an elliptical shape.

(59) Then, the spacer section **74** has its long sides oriented in the X direction and is arranged at the intersection of the light-shielding region **50** where the spacer section **67** of the array substrate **20** is arranged in such a manner as to intersect the spacer section **67**. That is, the spacer sections **67** and **74** intersect as seen in the vertical direction (direction perpendicular to the surface **21a** of the transparent substrate **21** and the surface **31a** of the transparent substrate **31**). Further, the spacer section **74** is arranged to overlap one of the extended portions **51** of the light-shielding region **50**. This ensures that the gap between the array substrate **20** and opposed substrate **30** is maintained constant by the spacer sections **67** and **74**.

(60) Further, an orientation film **75** is formed above the overcoat layer **72** to cover the common electrode **73** and spacer section **74**. Here, the orientation film **75** covering a top surface **74a** of the spacer section **74** and the orientation film **69** covering the top surface **67d** of the spacer section **67** of the array substrate **20** are in contact with each other.

(61) A description will be given next of the liquid crystal layer **40**.

(62) The liquid crystal layer **40** is formed between the orientation film **69** of the array substrate **20**

and the orientation film **75** of the opposed substrate **30**. Here, the spacer section **67** of the array substrate **20** and the spacer section **74** of the opposed substrate **30** are formed to protrude into the liquid crystal layer **40**.

(63) A description will be given next of the operation of the liquid crystal display device **100** adapted to display an image.

(64) In the liquid crystal display device **100**, for example, a control signal is supplied to the gate lines **61**, and a data signal to the source lines **63**, thus allowing an electric field based on image data to be supplied to the liquid crystal layer **40** from the pixel electrode **68** and common electrode **73** for each of the pixel regions. This changes the orientation of liquid crystal molecules based on the supplied electric field for each of the pixel regions.

(65) In this condition, light from a backlight arranged on the side of the surface **21b** of the transparent substrate **21** enters the liquid crystal display device **100** via a polarizing plate, passes through the liquid crystal layer **40** and leaves the liquid crystal display device **100** from the surface **31b** of the transparent substrate **31** via a polarizing plate, thus allowing a given color image to be displayed on the surface **31b**.

(66) A description will be given next of the manufacturing method of the liquid crystal display device **100**.

(67) FIGS. **6A** to **6D** are diagrams illustrating an example of the manufacturing method of the liquid crystal display device according to the second embodiment.

(68) First, as illustrated in FIG. **6A**, the gate lines **61**, gate electrodes **61a**, semiconductor layer **64** and interlayer insulating film **62** are formed on the surface **21a** of the transparent substrate **21**, followed by the formation of the source lines **63** and drain electrodes **65** on the interlayer insulating film **62**. Here, each of the drain electrodes **65** is connected to the semiconductor layer **64** via a contact hole **62a** provided in the interlayer insulating film **62**.

(69) The gate lines **61**, source lines **63** and drain electrodes **65** are formed, for example, by forming a metal film on the underlying layer by sputtering technique and then etching the metal film using a resist mask formed by photolithography technique.

(70) Next, as illustrated in FIG. **6B**, the organic insulating film **66** is formed on the interlayer insulating film **62** to cover the source lines **63** and drain electrodes **65**. The organic insulating film **66** is formed, for example, by applying an organic material to the interlayer insulating film **62**.

(71) Next, as illustrated in FIG. **6C**, the organic insulating film **66** is half-etched with a given region left unetched. More specifically, the organic insulating film **66** is half-exposed and developed with a given region left unexposed. The region left unetched serves as the spacer section **67**. It should be noted that a contact hole **66a** is provided at this time in the organic insulating film **66**.

(72) Next, as illustrated in FIG. **6D**, the pixel electrodes **68** are formed. Here, each of the pixel electrodes **68** is connected to the drain electrode **65** via a contact hole **66a**. The pixel electrodes **68** are formed, for example, by forming an ITO film on the organic insulating film **66** by sputtering technique, then etching the ITO film using a resist mask formed by photolithography technique, and finally thermally treating the etched film.

(73) Then, the orientation film **69** is formed on the organic insulating film **66** in such a manner as to cover the pixel electrodes **68**, thus forming the array substrate **20**. Next, the opposed substrate **30** is arranged above the array substrate **20** in such a manner that the surface **21a** of the transparent substrate **21** is opposed to the surface **31a** of the transparent substrate **31** with a predetermined distance kept therebetween. Then, the liquid crystal layer **40** is formed between the array substrate **20** and opposed substrate **30**, thus forming the liquid crystal display device **100**.

(74) As described above, the spacer sections **67** and **74** are formed respectively on the array substrate **20** and opposed substrate **30** in the liquid crystal display device **100**. Further, the spacer section **67** has its long sides oriented in the Y direction and is arranged at one of the plurality of intersections obtained as a result of each of the plurality of extended portions **51** of the light-

shielding region **50** intersecting one of the plurality of extended portions **52** of the light-shielding region **50**. Still further, the spacer section **74** has its long sides oriented in the X direction and is arranged at the intersection of the light-shielding region **50** where the spacer section **67** is arranged in such a manner as to intersect the spacer section **67**.

(75) This configuration ensures overlapping of the spacer sections **67** and **74** even if the array substrate **20** and opposed substrate **30** are horizontally (in the direction parallel to the surfaces **21a** and **31a**) misaligned due to bending of either of the substrates by an external force. As a result, it is possible to provide reduced likelihood of the spacer section **74** touching and damaging the film such as orientation film **69** and the element arranged in the opening region **53**.

(76) Further, this configuration contributes to reduced likelihood of the spacer section **74** touching and damaging the film and element arranged in the opening region **53** without widening the width (length along the Y direction) of the extended portions **51** of the light-shielding region **50** and the width (length along the X direction) of the extended portions **52** of the light-shielding region **50**. That is, it is possible to provide reduced likelihood of the spacer section **74** damaging the film and element arranged in the opening region **53** while at the same time securing an area for the opening region **53**.

(77) FIG. **7** is a top view illustrating the array substrate and opposed substrate that are out of alignment with each other in the liquid crystal display device according to the second embodiment. (78) If, for example, the spacer section **74** is displaced in a diagonal direction **D11** due to horizontal misalignment between the array substrate **20** and opposed substrate **30**, the spacer section **74** partially overlaps an opening region **53a**. However, an edge portion **74b** of the spacer section **74** overlaps an edge portion **67a** of the spacer section **67**. That is, the spacer section **74** is supported by the spacer section **67** and does not touch the orientation film **69** arranged in the opening region **53a**.

(79) Further, if, for example, the spacer section **74** is displaced in a diagonal direction **D12**, the spacer section **74** partially overlaps an opening region **53b**. However, an edge portion **74c** of the spacer section **74** overlaps an edge portion **67b** of the spacer section **67**. That is, the spacer section **74** is supported by the spacer section **67** and does not touch the orientation film **69** arranged in the opening region **53b**.

(80) Still further, in the liquid crystal display device **100**, the spacer section **67** having its long sides oriented in the Y direction extends in such a manner as to overlap the extended portion **52** that is narrower than the extended portion **51**. As a result, it is necessary for the spacer section **67** to be more accurate in size and position than the spacer section **74** having its long sides oriented in the X direction.

(81) In the liquid crystal display device **100**, the spacer section **67** having its long sides oriented in the Y direction is formed on the side of the array substrate **20**. The reduced projection and reset-and-repeat (stepper) photolithography process is used for the array substrate **20**, thus allowing for micropatterning of the array substrate **20**. This makes it possible to form the spacer section **67** with high accuracy in size and position without significantly changing the manufacturing steps.

(82) It should be noted that the one-to-one projection and proximity exposure (one-shot exposure or mirror projection aligner) lithography process is used for the opposed substrate **30**. For example, the line width and positional accuracy for the opposed substrate **30** is on the order of microns. In contrast, that for the array substrate **20** is on the order of submicrons.

(83) In the liquid crystal display device **100**, on the other hand, the spacer section **67** has the edge portions **67a** and **67b** and the intermediate portion **67c** provided between the edge portions **67a** and **67b**. Further, the width **W1** of the intermediate portion **67c** is greater than the width **W2** of the edge portions **67a** and **67b**. This configuration provides, for example, the spacer section **67** with more resistance to the pressure caused by the spacer section **67** being pressed by the spacer section **74** when a vertical force is applied to the opposed substrate **30**.

(84) Further, in the liquid crystal display device **100**, the spacer section **67** includes part of the organic insulating film **66**. That is, the spacer section **67** is made of the same material as the organic

insulating film **66**. This configuration makes it possible to form the spacer section **67** without using any new material, thus contributing to reduced cost of the liquid crystal display device **100**.

(85) Still further, in the liquid crystal display device **100**, the spacer section **67** is formed by half-etching the organic insulating film **66** with a given region left unetched. This configuration makes it possible to form the spacer section **67** without significantly increasing the number of steps.

Modification Example 1

(86) A description will be given next of a modification example of the second embodiment as modification example 1.

(87) FIG. **8** is a cross-sectional view illustrating modification example 1.

(88) A liquid crystal display device **110** differs from the liquid crystal display device **100** in that a spacer section **81** is formed rather than the spacer section **67**. The liquid crystal display device **110** is the same as the liquid crystal display device **100** in all the other respects. The spacer section **81** is made, for example, of an acrylic resin. It should be noted that the spacer section **81** is the same in shape and arrangement as the spacer section **67**.

(89) That is, the spacer section **67** is formed with part of the organic insulating film **66** in the liquid crystal display device **100**. In contrast, the spacer section **81** is formed separately from the organic insulating film **66** in the liquid crystal display device **110**. This configuration makes it possible, for example, to select a material more resistant to force as the spacer section **81**.

(90) Further, the liquid crystal display device **110** also provides reduced likelihood of the spacer section **74** damaging the film and element arranged in the opening region **53** while at the same time securing an area for the same region **53**.

Third Embodiment

(91) A description will be given next of a third embodiment.

(92) FIG. **9** is a cross-sectional view illustrating an example of a liquid crystal display device according to the third embodiment.

(93) A liquid crystal display device **120** differs from the liquid crystal display device **100** according to the second embodiment in that a common electrode **73a** is formed on the side of the array substrate **20** rather than the opposed substrate **30**. In the liquid crystal display device **120**, the common electrode **73a** is formed on the organic insulating film **66** to cover the top surface **67d** of the spacer section **67**. It should be noted that among liquid crystal display devices having its common electrode formed on the side of the array substrate are FFS (Fringe Field Switching) mode liquid crystal display devices.

(94) Further, an insulating film **82** is formed above the organic insulating film **66** to cover the common electrode **73a**. An inorganic insulating film is used as the insulating film **82**. Among inorganic insulating films are silicon oxide film (SiO₂) and silicon nitride films (SiN). Then, the pixel electrodes **68** are formed on the insulating film **82**. Further, the orientation film **69** is formed to cover the pixel electrodes **68**. It should be noted that the liquid crystal display device **120** is the same as the liquid crystal display device **100** in all the other respects.

(95) The liquid crystal display device **120** also provides reduced likelihood of the spacer section **74** damaging the film and element arranged in the opening region **53** while at the same time securing an area for the opening region **53** as does the liquid crystal display device **100**.

Modification Example 2

(96) A description will be given next of a modification example of the third embodiment as modification example 2.

(97) FIG. **10** is a cross-sectional view illustrating modification example 2.

(98) A liquid crystal display device **130** differs from the liquid crystal display device **120** in that the common electrode **73a** and insulating film **82** are formed by exposing the top surface **67d** of the spacer section **67**. The liquid crystal display device **130** is the same as the liquid crystal display device **120** in all the other respects.

(99) That is, in the liquid crystal display device **130**, the common electrode **73a** and insulating film

82 are not sandwiched by the spacer sections **67** and **74**. This minimizes cracking of the insulating film **82** and damage to the common electrode **73a** in the case that the spacer section **67** is pressed by the spacer section **74**.

(100) Further, the liquid crystal display device **130** also provides reduced likelihood of the spacer section **74** damaging the film and element arranged in the opening region **53** while at the same time securing an area for the opening region **53**.

Fourth Embodiment

(101) A description will be given next of a fourth embodiment.

(102) FIG. **11** is a cross-sectional view illustrating an example of a liquid crystal display device according to the fourth embodiment.

(103) A liquid crystal display device **140** includes two sections, i.e., a section **140a** that has the same structure as the liquid crystal display device **120** according to the third embodiment and a section **140b** that has the same structure as the liquid crystal display device **120** except that the spacer section **67** is not formed.

(104) That is, the liquid crystal display device **140** includes the two sections, i.e., the section **140a** in which the spacer sections **67** and **74** are formed as a pair, and the section **140b** in which only one of the spacer sections **67** and **74**, namely, the spacer section **74**, is formed. It should be noted that the section **140b** may have only the spacer section **67** formed therein rather than the spacer section **74**.

(105) In other words, in the section **140a** of the liquid crystal display device **140**, the spacer section **74** rests on (is supported by) the spacer section **67**. In the section **140b** thereof, on the other hand, the spacer section **74** is left floating.

(106) Here, when the liquid crystal display device **140** vibrates due to a sudden large force caused, for example, by a shock resulting from a fall, the following problem may arise if the space (gap) between the array substrate **20** and opposed substrate **30** is difficult to deform. That is, the gap is put under vacuum pressure, thus causing part of the liquid crystal layer **40** or the gases dissolved therein to evaporate and keeping air bubbles trapped therein.

(107) In contrast, the section **140b** of the liquid crystal display device **140** has the spacer section **74** floating. Therefore, if an external vertical force is suddenly applied, this force is concentrated on the spacer section **67** of the section **140a**. This causes the spacer section **67** of the section **140a** to elastically deform, thus causing the gap to deform with ease. As a result, it is possible to minimize air bubbles in the gap.

(108) On the other hand, when a vertical force is statically applied to the liquid crystal display device **140** as when the surface **31b** of the transparent substrate **31** is pressed with a finger, the spacer section **74** of the section **140b** rests on the array substrate **20**. This allows the vertical force to be distributed over the spacer section **67** of the section **140a** and the spacer section **74** of the section **140b**, thus minimizing the elastic deformation and crushing of the spacer section **67**. As a result, it is possible to minimize inconsistent image display caused by crushing of the spacer section **67**.

(109) Further, the liquid crystal display device **140** also provides reduced likelihood of the spacer section **74** touching and damaging the film and element arranged in the opening region **53** while at the same time securing an area for the opening region **53**.

Modification Example 3

(110) A description will be given next of a modification example of the fourth embodiment as modification example 3.

(111) FIG. **12** is a cross-sectional view illustrating modification example 3.

(112) A liquid crystal display device **150** includes a section **150a** that is configured in the same manner as the counterpart of the liquid crystal display device **120** of the third embodiment. Further, the liquid crystal display device **150** includes a section **150b** that has the same structure as the liquid crystal display device **130** according to modification example 2 except that the gap between

the array substrate **20** and opposed substrate **30** is larger so as to keep a distance between the orientation films **69** and **75**.

(113) That is, in the section **150a** of the liquid crystal display device **150**, the spacer section **74** rests on the spacer section **67**. In the section **150b** thereof, on the other hand, the spacer section **74** is left floating. Therefore, the liquid crystal display device **150** minimizes air bubbles in the gap and non-uniformity on image display as does the liquid crystal display device **140**.

(114) Further, the liquid crystal display device **150** also provides reduced likelihood of the spacer section **74** touching and damaging the film and element arranged in the opening region **53** while at the same time securing an area for the opening region **53**.

Fifth Embodiment

(115) A description will be given next of a fifth embodiment.

(116) FIG. **13** is a top view illustrating an example of a liquid crystal display device according to the fifth embodiment.

(117) A liquid crystal display device **160** has the same structure as the liquid crystal display device **100** of the second embodiment except that the plurality of pairs of spacer sections **67** and **74** are formed. Further, each of the spacer sections **67** is connected to the other spacer section **67** adjacent thereto in the Y direction via a connection section **83**. The connection sections **83** are, for example, formed integrally with the spacer sections **67**.

(118) Still further, each of the spacer sections **74** is connected to the other spacer section **74** adjacent thereto in the X direction via a connection section **84**. The connection sections **84** are, for example, formed integrally with the spacer sections **74**. The liquid crystal display device **160** is the same as the liquid crystal display device **100** in all the other respects.

(119) This configuration provides reduced likelihood of the spacer section **74** touching and damaging the film and element arranged in the opening region **53** while at the same time securing an area for the opening region **53**. Further, this configuration ensures, for example, that the connection sections **84** are supported by the connection sections **83** even if the array substrate **20** and opposed substrate **30** become significantly misaligned horizontally with each other, thus providing reduced likelihood of the spacer section **74** touching the film and element arranged in the opening region **53**.

Sixth Embodiment

(120) A description will be given next of a sixth embodiment.

(121) FIG. **14** is a top view illustrating an example of a liquid crystal display device according to the sixth embodiment.

(122) A liquid crystal display device **170** has the same structure as the liquid crystal display device **100** of the second embodiment except that the plurality of pairs of spacer sections **67** and **74** are formed. Further, the spacer sections **74** that are adjacent to each other in the Y direction are arranged to be misaligned with each other in the opposite directions along the X direction.

(123) For example, the spacer sections **74** in the second row from the top and adjacent to each other in the X direction are shifted in such a manner as to be closer to each other. On the other hand, those in the first and third rows from the top and adjacent to each other in the X direction are shifted in such a manner as to be farther away from each other. It should be noted that the spacer sections **74** adjacent to each other in the X direction may be arranged to be misaligned with each other in the opposite directions along the Y direction. The liquid crystal display device **170** is the same as the liquid crystal display device **100** in all the other respects.

(124) This configuration provides reduced likelihood of the spacer section **74** touching and damaging the film and element arranged in the opening region **53** while at the same time securing an area for the opening region **53**.

Module and Application Examples

(125) A description will be given next of application examples of the liquid crystal display devices described in the above embodiments with reference to FIGS. **15** to **19G**. The liquid crystal display

devices according to the above embodiments are applicable to electronic equipment across all disciplines adapted to display a video signal externally fed thereto or generated therein as an image or picture. Among examples of electronic equipment are a television set, digital camera, laptop personal computer, personal digital assistance such as mobile phone and video camcorder.

Application Example 1

(126) FIG. **15** illustrates an example of appearance of a television set to which the liquid crystal display device is applied. This television set has, for example, a video display screen section **510** including a front panel **511** and filter glass **512**. The video display screen section **510** includes the liquid crystal display device according to one of the above embodiments.

Application Example 2

(127) FIGS. **16A** and **16B** illustrate an example of appearance of a digital camera to which the liquid crystal display device is applied. FIG. **16A** is a perspective view as seen from the front, and FIG. **16B** a perspective view as seen from the rear. This digital camera has, for example, a flash-emitting section **521**, display section **522**, menu switch **523** and shutter button **524**. The display section **522** includes the liquid crystal display device according to one of the above embodiments.

Application Example 3

(128) FIG. **17** illustrates an example of appearance of a laptop personal computer to which the liquid crystal display device is applied. This laptop personal computer has, for example, a main body **531**, keyboard **532** adapted to be manipulated for entry of text or other information and a display section **533** adapted to display an image. The display section **533** includes the liquid crystal display device according to one of the above embodiments.

Application Example 4

(129) FIG. **18** illustrates an example of appearance of a video camcorder to which the liquid crystal display device is applied. This video camcorder has, for example, a main body section **541**, lens **542** provided on the front-facing side surface of the main body section **541** to capture the image of the subject, imaging start/stop switch **543** and display section **544**. The display section **544** includes the liquid crystal display device according to one of the above embodiments.

Application Example 5

(130) FIGS. **19A** to **19G** illustrate an example of appearance of a mobile phone to which the liquid crystal display device is applied. FIG. **19A** is a front view of the mobile phone in an open position, FIG. **19B** a side view thereof in FIG. **19A**, FIG. **19C** a front view thereof in a closed position, FIG. **19D** a left side view thereof in FIG. **19C**, FIG. **19E** a right side view thereof in FIG. **19C**, FIG. **19F** a top side view thereof in FIG. **19C**, and FIG. **19G** a bottom side view thereof in FIG. **19C**.

(131) This mobile phone is made up, for example, of an upper enclosure **710** and lower enclosure **720** that are connected together with a connecting section (hinge section) **730** and has a display **740**, subdisplay **750**, picture light **760** and camera **770**. Each of the display **740** and subdisplay **750** includes the liquid crystal display device according to one of the above embodiments.

(132) It should be noted that the present application may have the following configurations. (1) A liquid crystal display device including: a first substrate having a first surface, the first surface including a light-shielding region in a lattice form and a plurality of opening regions surrounded by the light-shielding region, the light-shielding region including a plurality of first extended portions extending in a first direction and a plurality of second extended portions extending in a second direction that intersects the first direction, the first substrate having a plurality of transistors formed thereon; a second substrate having a second surface that is opposed to and spaced from the first surface; a liquid crystal layer arranged between the first and second surfaces; a first spacer section having long sides oriented in the second direction and formed on one of the first or second surfaces, arranged at one of a plurality of intersections obtained as a result of each of the plurality of first extended portions intersecting one of the plurality of second extended portions and protruding into the liquid crystal layer; and a second spacer section having long sides oriented in the first direction, formed on the other of the first or second surfaces, arranged at the intersection where the first

spacer section is arranged in such a manner as to intersect the first spacer section and protruding into the liquid crystal layer. (2) The liquid crystal display device according to the paragraph (1), in which a gate line is formed on each of the plurality of first extended portions, a source line is formed on each of the plurality of second extended portions, an insulating film is formed above the first surface to cover the plurality of gate lines and the plurality of source lines, the first spacer section is formed on the insulating film, and the second spacer section is formed above the second surface. (3) The liquid crystal display device according to the paragraph (2), in which the first spacer section has two edge portions oriented in the longitudinal direction and an intermediate portion between the two edge portions, and the width of the intermediate portion is greater than that of either or both of the edge portions. (4) The liquid crystal display device according to the paragraph (2) or (3), in which the first spacer section is made of the same material as the insulating film. (5) The liquid crystal display device according to any one of the paragraphs (2) to (4), in which a plurality of pixel electrodes and a common electrode are formed on the insulating film, and the common electrode is formed to cover the first spacer section. (6) The liquid crystal display device according to any one of the paragraphs (2) to (4), in which a plurality of pixel electrodes and a common electrode are formed on the insulating film, and the common electrode is formed to expose the first spacer section. (7) The liquid crystal display device according to any one of the paragraphs (1) to (6), in which the plurality of first spacer sections and the plurality of second spacer sections are formed, and each of the plurality of first spacer sections and the plurality of second spacer sections is arranged at one of the plurality of intersections. (8) The liquid crystal display device according to the paragraph (7), in which the plurality of first spacer sections are arranged at some of the plurality of intersections rather than all thereof. (9) The liquid crystal display device according to the paragraph (7) or (8), in which each of the plurality of first spacer sections includes a third spacer section and a fourth spacer section lower in height than the third spacer section. (10) The liquid crystal display device according to any one of the paragraphs (7) to (9), in which the plurality of first or second spacer sections are connected to each other. (11) The liquid crystal display device according to any one of the paragraphs (7) to (9), in which of the plurality of first or second spacer sections, those adjacent to each other in one of the first or second directions are arranged to be misaligned with each other in the opposite directions along the other of the first or second directions. (12) A manufacturing method of a liquid crystal display device including: forming, on a first surface of a first substrate, a first spacer section having long sides in such a manner as to be located at one of a plurality of intersections obtained as a result of each of a plurality of first extended portions intersecting one of a plurality of second extended portions and have the long sides oriented in a second direction, the first substrate having the first surface, the first surface including a light-shielding region in a lattice form and a plurality of opening regions surrounded by the light-shielding region, the light-shielding region including the plurality of first extended portions extending in a first direction and the plurality of second extended portions extending in the second direction that intersects the first direction, the first substrate having a plurality of transistors formed thereon; forming a second spacer section having long sides on a second surface of a second substrate; arranging the first and second substrates in such a manner that the first and second surfaces are opposed to and spaced from each other, that the second spacer section is arranged at the intersection where the first spacer section is arranged, that the second spacer section has long sides oriented in the first direction, and that the second spacer section intersects the first spacer section; and forming a liquid crystal layer between the first and second surfaces. (13) The manufacturing method of a liquid crystal display device according to the paragraph (12), in which a gate line is formed on each of the plurality of first extended portions, and a source line is formed on each of the plurality of second extended portions, and the process of forming the first spacer section includes forming, on the first surface, an insulating film in such a manner as to cover the plurality of gate lines and the plurality of source lines, and half-etching the formed insulating film with part of the insulating film left unetched. (14) Electronic equipment

including: a liquid crystal display device configured to display an image, the liquid crystal display device having a first substrate having a first surface, the first surface including a light-shielding region in a lattice form and a plurality of opening regions surrounded by the light-shielding region, the light-shielding region including a plurality of first extended portions extending in a first direction and a plurality of second extended portions extending in a second direction that intersects the first direction, the first substrate having a plurality of transistors formed thereon, a second substrate having a second surface that is opposed to and spaced from the first surface; a liquid crystal layer arranged between the first and second surfaces, a first spacer section having long sides oriented in the second direction and formed on one of the first or second surfaces, arranged at one of a plurality of intersections obtained as a result of each of the plurality of first extended portions intersecting one of the plurality of second extended portions and protruding into the liquid crystal layer, and a second spacer section having long sides oriented in the first direction, formed on the other of the first or second surfaces, arranged at the intersection where the first spacer section is arranged in such a manner as to intersect the first spacer section and protruding into the liquid crystal layer.

(133) It should be understood that various changes and modifications to the presently preferred embodiments described herein will be apparent to those skilled in the art. Such changes and modifications can be made without departing from the spirit and scope of the present subject matter and without diminishing its intended advantages. It is therefore intended that such changes and modifications be covered by the appended claims.

Claims

1. A display device comprising: a first substrate having a first surface; a second substrate having a second surface that is opposed to and spaced from the first surface; a first wiring line on the first substrate; a second wiring line intersecting the first wiring line; and spacers protruding from the second surface toward the first surface and formed with an organic insulating film, the spacers including a first spacer and a second spacer that is adjacent to the first spacer, wherein the first spacer and the second spacer overlap the first wiring line, the first spacer and the second spacer are arranged such that: a center of the first spacer shifts to a first side of the first wiring line; and a center of the second spacer shifts to a second side of the first wiring line, the second side being an opposite side of the first side, and the first spacer and the second spacer overlap the second wiring line.
2. The display device according to claim 1, wherein the first substrate has a first protruding part and a second protruding part protruding toward the second surface, the first protruding part is in contact with the first spacer, and the second protruding part is in contact with the second spacer.
3. The display device according to claim 2, wherein the first protruding part has a first region overlapping the first spacer and a second region not overlapping the first spacer.
4. The display device according to claim 3, wherein the second protruding part has a third region overlapping the second spacer and a fourth region not overlapping the second spacer.
5. The display device according to claim 3, wherein the first spacer has a first area overlapping the first protruding part and a second area not overlapping the first protruding part.
6. The display device according to claim 1, wherein the first substrate has a first protruding part and a second protruding part protruding the first toward the second surface, a film is located on a first top surface of the first spacer and a second top surface of the second spacer, and is thinner than the first spacer and the second spacer, the first protruding part is in contact with the film and overlaps the first top surface via the film, and the second protruding part is in contact with the film and overlaps the second top surface via the film.
7. The display device according to claim 1, further comprising a liquid crystal layer between the first substrate and the second substrate, wherein the film is an orientation film that orients liquid

crystal molecules in the liquid crystal layer.

8. A display device comprising: a first substrate having a first surface; a second substrate having a second surface that is opposed to and spaced from the first surface; a first wiring line on the first substrate; a second wiring line intersecting the first wiring line; and spacers protruding from the second surface toward the first surface, formed with an organic insulating film, overlapping the first wiring line, and including first spacers and second spacers, wherein a center of each of the first spacers shifts to a first side of the first wiring line, a center of each the second spacers shifts to a second side of the first wiring line, the second side being an opposite side of the first side, and the first spacers and the second spacers are arranged along and above the first wiring line alternately one by one, and the first spacers and the second spacers overlap the second wiring line.

9. The display device according to claim 8, wherein the first substrate has a first protruding part and a second protruding part protruding toward the second substrate, the first protruding part is in contact with one of the first spacers, and the second protruding part is in contact with one of the second spacers.

10. The display device according to claim 9, wherein the first protruding part has a first region overlapping the one of the first spacers and a second region not overlapping the one of the first spacers.

11. The display device according to claim 10, wherein the second protruding part has a third region overlapping the one of the second spacers and a fourth region not overlapping the one of the second spacers.

12. The display device according to claim 10, wherein the one of the first spacers has a first area overlapping the first protruding part and a second area not overlapping the first protruding part.
