

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12418426
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Yoon; Woongah et al.

Electronic device having partial ledger in blockchain network and operating method thereof

Abstract

An electronic device constituting a first blockchain node included in a blockchain network may generate an encryption key corresponding to a transaction based on obtaining a transaction generation request, transmit information of the encryption key to at least one blockchain node related to the transaction, encrypt first data stored in the partial ledger among input data required to execute a first smart contract of the transaction based on the encryption key, upload the first data to a data server included in the blockchain network, download second data encrypted based on the encryption key from the data server, the second data being data not stored in the partial ledger among the input data, decrypt the second data based on the encryption key, and execute the first smart contract based on the first data and the decrypted second data.

Inventors: Yoon; Woongah (Suwon-si, KR), Kwon; Wooup (Suwon-si, KR), Kim; Hun (Suwon-si, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 1000008819937

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Appl. No.: 18/139551

Filed: April 26, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230261887 A1	Aug. 17, 2023

Foreign Application Priority Data

KR	10-2021-0135099	Oct. 12, 2021
KR	10-2021-0169754	Dec. 01, 2021

Related U.S. Application Data

continuation parent-doc WO PCT/KR2022/015327 20221012 PENDING child-doc US 18139551

Publication Classification

Int. Cl.: H04L9/00 (20220101); H04L9/08 (20060101)

U.S. Cl.:

CPC H04L9/50 (20220501); H04L9/0819 (20130101); H04L9/0861 (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10540652	12/2019	Saur et al.	N/A	N/A
10834095	12/2019	Irazabal et al.	N/A	N/A
11023968	12/2020	Arnold et al.	N/A	N/A
12170694	12/2023	Hu	N/A	H04L 63/10
2019/0379754	12/2018	Krishnaswamy	N/A	N/A
2020/0065763	12/2019	Rosinzonsky et al.	N/A	N/A
2020/0084037	12/2019	Zhang	N/A	H04L 9/3226
2020/0143337	12/2019	Conroy et al.	N/A	N/A
2020/0177390	12/2019	Yang et al.	N/A	N/A
2020/0267002	12/2019	Yuan et al.	N/A	N/A
2020/0410461	12/2019	Moir et al.	N/A	N/A
2021/0091924	12/2020	Holmberg et al.	N/A	N/A
2021/0224805	12/2020	Pennington et al.	N/A	N/A
2021/0288788	12/2020	Sardesai et al.	N/A	N/A
2021/0295303	12/2020	Phan et al.	N/A	N/A
2023/0252461	12/2022	Oh	705/75	H04L 65/40

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
6909452	12/2020	JP	N/A
10-1870113	12/2017	KR	N/A
10-2484453	12/2022	KR	N/A

OTHER PUBLICATIONS

International Search Report (PCT/ISA/210) issued by the International Searching Authority on Jan. 30, 2023 in corresponding International Application No. PCT/KR2022/015327. cited by applicant
Written Opinion (PCT/ISA/237) issued by the International Searching Authority on Jan. 30, 2023 in corresponding International Application No. PCT/KR2022/015327. cited by applicant

Primary Examiner: Etienne; Ario

Assistant Examiner: Mian; Mohammad Yousuf A.

Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) (1) This application is a bypass continuation of PCT International Application No. PCT/KR2022/015327, which was filed on Oct. 12, 2022, and claims priority to Korean Patent Application No. 10-2021-0135099, filed on Oct. 12, 2021, and to Korean Patent Application No. 10-2021-0169754, filed on Dec. 1, 2021, in the Korean Intellectual Property Office, the disclosures of which are incorporated herein by reference in their entireties.

BACKGROUND

1. Field

(1) The disclosure relates to an electronic device for controlling function execution using a blockchain network and an operating method thereof, and more specifically, to an electronic device for agreeing on a transaction between blockchain nodes in the blockchain network that have a partial ledger, and an operating method thereof.

2. Description of Related Art

(2) A blockchain network is expressed as a decentralized network, and is distinguished from a centralized network in which decision-making is performed by a central server. The blockchain network may refer to a network in which decision-making is performed according to a consensus algorithm for nodes participating in the blockchain network.

(3) A distributed ledger in the blockchain network may include at least one or more blocks generated based on a transaction executed in the blockchain network and a database (e.g., a state database) that stores data (e.g., state data) related to the transaction. A distributed ledger can be stored in each of nodes participating in the blockchain network. The distributed ledger may include one or more blocks linked to each other. The linking of these blocks may be expressed as a blockchain. At least one block stored in the distributed ledger may be expressed as a blockchain.

(4) To maintain security and integrity, the distributed ledger of the blockchain network may be updated based on a consensus algorithm employed by the blockchain nodes participating in the blockchain network. Specifically, the blockchain nodes participating in the blockchain network may perform an endorsement operation, an ordering operation, and a validation operation, to generate a block based on the transaction.

(5) A blockchain network may include blockchain nodes that validate transactions in the blockchain system. For example, an electronic device that is used to participate in the blockchain network may be configured as a blockchain node of the blockchain network.

(6) Nodes participating in the blockchain network must store and maintain data about a full blockchain in devices thereof for the integrity of a block. When the data about the full blockchain is not large, there is no problem. However, as the number of blocks increases, data about the full blockchain gradually increases. Therefore, there is a problem in that the nodes participating in the blockchain must store, maintain, and manage a large amount of data. In addition, when a node participating in the blockchain is a personal mobile device, the node may be unable to meet the required level of performance.

(7) Additionally, the nodes participating in the blockchain network participate in consensus operations for transactions in the blockchain system, including transactions that may be unrelated

to the node. Hence, the blockchain nodes, which need to maintain central processing unit (CPU) processing and blockchain network communication, continuously consume power. Further, random communications with other blockchain nodes included the blockchain network may cause a security problem.

SUMMARY

(8) According to various embodiments an electronic device constituting a first blockchain node included in a blockchain network, includes a communication circuit configured to communicate with at least one other device in the blockchain network, a memory storing a partial ledger including a part of a full ledger of the blockchain network, and at least one processor configured to: generate an encryption key corresponding to a transaction based on obtaining a transaction generation request, transmit information of the encryption key to at least one blockchain node related to the transaction, encrypt first data stored in the partial ledger among input data required to execute a first smart contract of the transaction based on the encryption key, upload the encrypted first data to a data server included in the blockchain network, download encrypted second data that is encrypted based on the encryption key, from the data server, wherein the second data is not stored in the partial ledger among the input data, decrypt the encrypted second data based on the encryption key, and execute the first smart contract based on the first data and the second data.

(9) According to various embodiments a method for operating an electronic device constituting a first blockchain node included in a blockchain network, includes: generating an encryption key corresponding to a transaction based on obtaining a transaction generation request; transmitting information of the encryption key to at least one blockchain node related to the transaction; encrypting first data based on the encryption key, wherein the first data is stored in a partial ledger including part of a full ledger of the blockchain network, among input data required to execute a first smart contract of the transaction; uploading the encrypted first data to a data server included in the blockchain network; downloading encrypted second data that is encrypted based on the encryption key, from the data server, wherein the second data is not stored in the partial ledger among the input data; decrypting the encrypted second data based on the encryption key; and executing the first smart contract based on the first data and the second data.

(10) According to various embodiments an electronic device constituting a first blockchain node included in a blockchain network, includes a communication circuit configured to communicate with at least one other device in the blockchain network, a memory storing a partial ledger including a part of a full ledger of the blockchain network, and at least one processor configured to: generate an encryption key corresponding to a transaction based on obtaining a transaction generation request, transmit information of the encryption key to at least one blockchain node related to the transaction, encrypt, based on the encryption key, first data stored in the partial ledger among input data required to execute a smart contract of the transaction, upload the encrypted first data to a data server of the blockchain network, the data server including a shared ledger, transmit an endorsement request of the transaction to the at least one blockchain node, obtain at least one endorsement data, based on the endorsement request, wherein the at least one endorsement data includes data generated by executing a smart contract of the transaction stored in the at least one blockchain node, wherein the smart contract is executed based on at least part of the shared ledger, and endorse the transaction based on the output data generated by the at least one blockchain node and output data generated by executing a first smart contract of the transaction stored in the memory.

(11) The systems and methods described herein provide a number of technical effects and benefits. Various embodiments in the disclosure provide for an electronic device that may efficiently use its memory by storing a partial ledger including at least a part of a distributed ledger when forming a blockchain network with external electronic devices.

(12) According to various embodiments, the electronic device may store a partial ledger and maintain the same consensus authentication level as a general blockchain consensus authentication

level through a data server included in the blockchain network having a full ledger.

(13) According to various embodiments, the electronic device may reduce unnecessary power consumption by participating only in transaction processing related to the electronic device.

(14) According to various embodiments, the electronic device may obtain necessary data for transaction execution using a data server included in the blockchain network and thus reduce an amount of random communications with other devices.

(15) Effects obtainable from the disclosure are not limited to the above-mentioned effects, and other effects which have not been mentioned, will be clearly understood by those skilled in the art to which the present disclosure belongs from the description below.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The above and other aspects, features, and advantages of certain embodiments of the present disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

(2) FIG. 1 is a block diagram of an electronic device, according to an embodiment;

(3) FIG. 2 is a block diagram illustrating a blockchain platform of an electronic device, according to an embodiment;

(4) FIG. 3 is a block diagram illustrating a blockchain network, according to an embodiment.

(5) FIG. 4 is a flow diagram illustrating a method of generating an encryption key by an electronic device according to an embodiment;

(6) FIG. 5 is a flow diagram illustrating a method of executing a smart contract by an electronic device according to an embodiment;

(7) FIG. 6 is a flow diagram illustrating a method of endorsing a transaction of a blockchain network, according to an embodiment;

(8) FIG. 7 is a flowchart illustrating a method of executing a smart contract, according to an embodiment;

(9) FIG. 8 is a flowchart illustrating a method of endorsing a transaction, according to an embodiment; and

(10) FIG. 9 is a block diagram illustrating an electronic device in a network environment, according to various embodiments.

DETAILED DESCRIPTION

(11) Hereinafter, various embodiments of the present disclosure will be described with reference to the accompanying drawings. However, it should be understood that it is not intended to limit the present disclosure to a specific embodiment, and various modifications, equivalents, and/or alternatives of the embodiments of the present disclosure are embraced. In regard to descriptions of the drawings, the same or similar reference numbers may be used for the same or corresponding components.

(12) FIG. 1 is a block diagram of an electronic device, according to an embodiment.

(13) Referring to FIG. 1, an electronic device **100** may include a memory **110**, a communication circuit **120**, a processor **130** and a display **140** or a combination thereof. In various embodiments, the electronic device **100** may include an additional component in addition to the components shown in FIG. 1, or may omit at least one of the components shown in FIG. 1.

(14) According to an embodiment, the memory **110** may store instructions, when executed, for the processor **130** to process data or control the component of the electronic device **100** to perform an operation of the electronic device **100**. In addition, the memory **110** may include a secure area or a separate secure storage medium (e.g., a secure memory area (e.g., a trust zone) accessible only through a secure operating system (OS)). According to an embodiment, the memory **110** may

include at least one blockchain application for performing a blockchain related operation. For example, it may include a blockchain platform corresponding to a blockchain application or a blockchain module for performing the blockchain related operation.

(15) According to an embodiment, the memory **110** may store a distributed ledger of a blockchain network. If the electronic device **100** corresponds to a mobile node included in the blockchain network, the memory **110** may store a partial ledger including part of the distributed ledger of the blockchain network. The part of the distributed ledger distinguished from the full ledger may be referred to as the partial ledger.

(16) According to an embodiment, the distributed ledger may include a blockchain connecting at least one block. At least one block may include at least one transaction of the blockchain network. Also, the distributed ledger may include a state data-base including state data related to transactions executed in the blockchain network.

(17) According to an embodiment, the partial ledger stored in the memory **110** may include at least one block corresponding to at least one transaction in which the electronic device **100** participates. In addition, the state data-base stored in the memory **110** may include data of at least one transaction in which the electronic device **100** participates. Hence, the electronic device **100** may store in the memory **110** only the block related to the transaction in which the electronic device **100** participates, and thus efficiently manage the memory **110**.

(18) According to an embodiment, the communication circuit **120** may be configured to transmit and receive data by connecting to an external device. According to an embodiment, the electronic device **100** may build a blockchain network with at least one external device through the communication circuit **120**. The blockchain network may include at least one external device and the electronic device **100** as blockchain nodes. Accordingly, the electronic device **100** and/or the at least one external device may serve as the blockchain node and a client. In an embodiment, the electronic device **100** may transmit and receive data to and from at least one external devices included in the blockchain network through the communication circuit **120**, and perform transaction consensus of the blockchain network.

(19) According to an embodiment, the blockchain network may include a data server accessible by the blockchain nodes. According to an embodiment, the data server may include a data base for storing a shared ledger generated based on at least some of the blockchain nodes.

(20) According to various embodiments, the data server may indicate various devices for sharing data. For example, the data server may be a mobile device, a server, a tablet personal computer (PC), a computer, and/or a blockchain node included in the blockchain network. The data server is not limited to the above examples, and a device for communicating with the electronic device **100** may correspond to the data server.

(21) According to various embodiments, the blockchain network may include a peer node and/or an ordering node as the blockchain node. According to an embodiment, the blockchain node is the electronic device **100** and/or the external electronic device, and may indicate a portable electronic device. For example, the electronic device **100** and/or the external electronic device may correspond to a mobile device, a tablet PC and/or a notebook. Descriptions on the blockchain network according to various embodiments shall be described by referring to FIG. 3.

(22) According to an embodiment, the processor **130** may be electrically or operatively connected with the memory **110**, the communication circuit **120** and the display **140**. According to an embodiment, the processor **130** may execute an operation or data processing related to control and/or communication of at least one other component of the electronic device **100** using the instructions stored in the memory **110**. According to an embodiment, the processor **130** may include at least one of a central processing unit (CPU), a graphic processing unit (GPU), a micro controller unit (MCU), a sensor hub, a supplementary processor, a communication processor, an application processor, an application specific integrated circuit (ASIC), and field programmable gate arrays (FPGA), and may have a plurality of cores.

- (23) According to an embodiment, the processor **130** may perform an operation related to the blockchain through the blockchain platform stored in the memory **110**. According to an embodiment, the processor **130** may obtain a request for a transaction. For example, the processor **130** may obtain a transaction generation request, from a user of the electronic device **100** and/or other application stored in the memory **110**.
- (24) According to an embodiment, the processor **130** may generate an encryption key corresponding to the transaction in response to obtaining the transaction generation request. According to an embodiment, the encryption key, which is based on the transaction, may indicate a unique encryption key for the transaction executed in the blockchain network. According to an embodiment, the processor **130** may generate the encryption key based on various encryption key generation algorithms. For example, the processor **130** may generate an encryption key corresponding to a symmetric encryption algorithm (e.g., advanced encryption standard (AES)) or an asymmetric encryption algorithm (e.g., Rivest Shamir Adleman (RSA)). According to an embodiment, the processor **130** may share the generated encryption key to other blockchain nodes included in the blockchain network.
- (25) According to an embodiment, the symmetric encryption algorithm may indicate an encryption scheme in which data encryption key and decryption key are the same. In an embodiment, if the processor **130** uses the symmetric encryption algorithm, the processor **130** may generate the encryption key for the transaction, and share the generated encryption key to other blockchain nodes included in the blockchain network. In another example, the processor **130** may share a seed value used to generate the encryption key to other blockchain nodes. The other blockchain nodes sharing the seed value (e.g., a root seed) may generate the same encryption key as the encryption key generated by the processor **130** using the seed value. The processor **130** may use the generated encryption key in encrypting data. Also, the other blockchain nodes sharing the encryption key and/or the seed value of the encryption key may decrypt data based on information of the obtained encryption key. According to various embodiments, the processor **130** may use various encryption schemes, for encrypting or decrypting data. For example, the processor **130** may use a stream cipher scheme (e.g., Rivest cipher 4 (RC4), A5) or a block cipher system (e.g., data encryption standard, AES).
- (26) According to an embodiment, the asymmetric encryption algorithm may indicate an encryption algorithm where data encryption key and decryption key are different. In the asymmetric encryption, the processor **130** may encrypt or decrypt data using both a public key and a private key. According to an embodiment, the processor **130** may generate the public key and the private key for the transaction based on the seed value. For example, the processor **130** may generate a master private key and a master chain code from a hash value generated through a hash-based message authentication code (HMAC)-secure hash algorithm (SHA) **512** function. In a 512-bit hashed value, left 256 bits may be used as the private key, and right 256 bits may be used as the chain code. The processor **130** may acquire the public key using the private key and an elliptic curve function.
- (27) According to an embodiment, the processor **130** may generate a public key and a private key which are the encryption key for the transaction, and share the generated public key and private key to other blockchain nodes included in the blockchain network. In another example, the processor **130** may share a seed value used to generate the encryption key to other blockchain nodes. The other blockchain nodes sharing the seed value may generate the public key and the private key which are the same encryption key as the encryption key generated by the processor **130** using the seed value. Next, the processor **130** may use the generated public key and/or encryption key in encrypting data. Also, the other blockchain nodes sharing the encryption key and/or the seed value of the encryption key may decrypt data based on information of the obtained encryption key. In an embodiment, if sharing the private key, the processor **130** may transmit a data packet including the generated private key in a secure field not accessible by an external device to the other blockchain

nodes. According to various embodiments, for the data encryption or decryption, the processor **130** may use one of various encryption schemes including elliptic curve cryptosystem (ECC), RSA, and elgammal. The encryption key disclosed in this document may indicate a symmetric key or an asymmetric key (a public key and a private key) according to the encryption algorithm used by the processor **130**.

(28) According to an embodiment, the seed value may indicate a default value for generating a plurality of keys. The seed value may indicate a value randomly generated in an available condition range in the blockchain network. For example, the seed value may be generated based on a dynamic characteristic (e.g., a unique value of a hardware chip) occurring in the operation of the electronic device **100**.

(29) According to an embodiment, the processor **130** may determine input data required to execute a first smart contract for the requested transaction. According to an embodiment, the input data may indicate data (e.g., read-set) to refer to in the state data-base stored in the memory **110**, according to executing the smart contract. Hereafter, the input data may indicate the same meaning. In addition, the processor **130** may determine whether data required to execute the first smart contract is stored in the memory **110**. For example, the processor **130** may determine whether the input data (e.g., read-set) required to execute the first smart contract is included in the memory **110**. For example, the processor **130** may determine whether data to read from the state data-base to execute the first smart contract is stored in the memory **110**.

(30) According to an embodiment, the processor **130** may encrypt first data stored in the memory **110** among the input data based on the encryption key. According to an embodiment, the first data may be data stored in the memory **110** among the input data required to execute the smart contract for the transaction. According to an embodiment, the processor **130** may encrypt the first data stored in the partial ledger included in the memory **110** among the input data required to execute the smart contract for the transaction, using the encryption key based on the transaction. According to various embodiments, the processor **130** may encrypt the first data using the encryption key based on various encryption algorithms.

(31) According to an embodiment, the processor **130** may encrypt the first data based on the symmetric encryption algorithm. For example, the processor **130** may encrypt the first data through the encryption key based on the AES algorithm. The processor **130** may encrypt the first data by modifying a state array of a 4×4 byte array type through multiple rounds according to a size of the generated encryption key. The processor **130** may encrypt the first data by repeating a set operation of four operations addroundkey, subbytes, shiftrows, and mixcolumns. The above-described example may be applied if the processor **130** encrypts data in the symmetric encryption manner according to the AES algorithm. The processor **130** is not limited to the described example and may encrypt the first data based on the symmetric encryption scheme based on the encryption key generated based on various algorithms.

(32) According to an embodiment, the processor **130** may encrypt the first data based on the asymmetric encryption algorithm. For example, the processor **130** may encrypt the first data using the public key of the generated encryption key.

(33) According to an embodiment, the processor **130** may encrypt the first data based on the asymmetric encryption algorithm. For example, the processor **130** may encrypt the first data through the public key based on the RSA algorithm. In an embodiment, the processor **130** may encrypt the first data using the public key and the encryption function. It is not limited to the described example, and the processor **130** may encrypt the first data based on the asymmetric encryption scheme using the encryption key generated based on various algorithms.

(34) The data encryption scheme disclosed in this document may be similar to the encryption scheme of the first data. According to an embodiment, the processor **130** may upload the encrypted first data to the data server included in the blockchain network. For example, the processor **130** may transmit the first data to the blockchain network which includes the electronic device **100** as

the blockchain node through the communication circuit **120**. For example, the processor **130** may upload the first data encrypted with the encryption key to the data server included in the blockchain network. According to an embodiment, the processor **130** may upload the first data encrypted using the encryption key to the shared ledger of the transaction included in the data server.

(35) According to an embodiment, the other blockchain nodes included in the blockchain network may download the uploaded first data. In an embodiment, the other blockchain nodes may decrypt the encrypted first data based on encryption key information shared through the electronic device **100**.

(36) For example, if the processor **130** encrypts the first data based on the symmetric encryption algorithm, the other blockchain nodes may decrypt the first data using a symmetric key which is the shared encryption key. Alternatively, the other blockchain nodes may generate a symmetric key using the shared seed value, and decrypt the first data using the generated symmetric key. The generated symmetric key may indicate the same key as the symmetric key owned by the electronic device **100**.

(37) As another example, if the processor **130** encrypts the first data based on the asymmetric encryption algorithm, that is, if the processor **130** encrypts the first data with the public key, the other blockchain nodes may decrypt the first data using the shared private key. For example, the other blockchain nodes may acquire the first data by applying the first data encrypted using the private key shared from the electronic device **100** to the encryption function. As another example, if the processor **130** shares the seed value for generating the private key, the other blockchain nodes may generate the private key using the seed value. The generated private key may indicate the same key as the private key owned by the electronic device **100**. The other blockchain nodes may generate the private key using the seed value, and decrypt the first data using the generated private key.

(38) According to an embodiment, the processor **130** may download second data encrypted based on the encryption key from the data server. According to an embodiment, the second data may be data not stored in the memory **110** among the input data required to execute the smart contract for the transaction. According to an embodiment, the processor **130** may obtain the second data not stored in the memory **110** among the input data required to execute the smart contract for the transaction through the data server. According to an embodiment, the second data obtained from the data server may indicate data encrypted through an external device sharing the encryption key from the electronic device **100**.

(39) According to an embodiment, the processor **130** may decrypt the second data based on the encryption key, and execute a first smart contract for the requested transaction based on the first data and the second data. For example, the processor **130** may execute the first smart contract using the first data stored in the partial ledger and the decrypted second data as the input data.

(40) According to an embodiment, if every input data required to execute the first smart contract is stored in the state data-base, the processor **130** may execute the first smart contract based on the stored data.

(41) According to another example, if some of the data required to execute the first smart contract is not stored in the state data-base, the processor **130** may obtain the not-stored data from the data server included in the blockchain network. According to an embodiment, the data server may store data uploaded by the blockchain nodes included in the blockchain network. For example, the data server may include the shared ledger corresponding to the transaction running in the blockchain network, and store state data of the transaction in the shared ledger. According to an embodiment, the data uploaded to the shared ledger may be data encrypted based on the encryption key.

According to an embodiment, the processor **130** may execute the first smart contract using the obtained data.

(42) According to various embodiments, the electronic device **100** may share various data with the other blockchain nodes included in the blockchain network. For example, the electronic device **100**

may share various data to share with the other blockchain nodes using the data server. For example, the processor **130** may share data (e.g., smart contract version information) related to the smart contract and/or data (e.g., blockchain node configuration information) related to the blockchain node included in the blockchain network with the other blockchain nodes via the data server. According to an embodiment, the processor **130** may encrypt various data to share with the other blockchain nodes through the encryption key, and share the encrypted data with the other blockchain nodes via the data server. For example, the processor **130** may encrypt various data to share with the other blockchain nodes using the encryption key, and upload the encrypted data to the data server. The other blockchain nodes included in the blockchain network may download the data uploaded to the data server. Also, the processor **130** may download the various data uploaded to the data server. The various data uploaded to the data server may be data encrypted using the encryption key. Hence, the processor **130** may download the encrypted data, and decrypt using the encryption key.

(43) According to an embodiment, the processor **130** may endorse the transaction using at least part of data returned according to executing the first smart contract.

(44) According to an embodiment, as the endorsement of the transaction is finished in the blockchain network, an operation for generating a block including transaction data of the transaction may be performed. For example, the processor **130** may perform the operation for generating a block including a hash field and block data. The hash field may include previous block information of the distributed ledger. The block data may include data related to the transaction. For example, the processor **130** may request the ordering node (e.g., a block generation node) included in the blockchain network to generate the block including the transaction data. The block may be finalized through consensus with the blockchain nodes included in the blockchain network through the communication circuit **120**. In an embodiment, the processor **130** may store the block in the memory **110**. For example, the processor **130** may obtain an update request of the block finalized through the consensus from the ordering node, and store the block in the memory **110** based on the update request. In so doing, the processor **130** may store the block as a block after a terminal block of the blockchain of the partial ledger.

(45) According to an embodiment, the display **140** may display various contents (e.g., text, image, video, icon, and/or symbol). According to an embodiment, the display **140** may include a liquid crystal display (LCD), a light emitting diode (LED) display or an organic light emitting diode (OLED) display.

(46) According to an embodiment, the processor **130** may display various contents related to the blockchain application on the display **140**. For example, the processor **130** may display contents indicating success or failure notification of the transaction requested to execute through the display **140**. For example, if the endorsement operation, the validation operation and/or the ordering operation for the transaction consensus fails, the processor **130** may abort the transaction consensus operation and display the notification of the block generation failure on the display **140**. According to various embodiments, the processor **130** is not limited to the display **140** and may output the failure notification using various configurations included in the electronic device **100**.

(47) FIG. 2 is a block diagram illustrating a blockchain platform of an electronic device, according to an embodiment.

(48) Referring to FIG. 2, an electronic device **100** may include the blockchain platform **200**. According to an embodiment, the blockchain platform **200** may correspond to the blockchain application for performing the blockchain related operation stored in the memory **110** or the blockchain module for performing the blockchain related operation stored in the processor **130**.

(49) According to an embodiment, the blockchain platform **200** may include a smart contract **210**, a partial ledger **220** and/or a blockchain processor **230**. According to various embodiments, the blockchain platform **200** may further include various configurations to perform an operation related to the blockchain or may omit some configuration.

(50) According to an embodiment, the blockchain processor **230** may be included in the processor **130**. The blockchain processor **230** may control operations of components included in the blockchain platform **200**. For example, the blockchain processor **230** may execute a transaction including ledger synchronization, transaction signing and/or transaction recording on the blockchain network.

(51) According to an embodiment, the blockchain platform **200** may include the smart contract **210**. The smart contract indicates script or software code used to process the transaction in the blockchain based system. More specifically, the smart contract is code which programs various conditions used to process the transaction, states, and actions according to the conditions, and may include, for example, smart contract of Ethereum, chain code of hyper ledge fabric and so on. In the blockchain based system, the blockchain node may share the uploaded smart contract.

(52) In executing the smart contract **210** for the transaction, the blockchain processor **230** may provide a necessary value (e.g., read-set) to the smart contract **210**. For example, the blockchain processor **230** may provide the input data explained by referring to FIG. **1** to the smart contract **210**. Also, the blockchain processor **230** may store an outputted value, by executing the smart contract **210**. For example, the blockchain processor **230** may provide data and factors required to execute the smart contract **210**.

(53) According to an embodiment, as the smart contract **210** is executed, a data (required data) set (e.g., read-set) to read from a state database **222** to execute the smart contract **210**, data (e.g., write-set) changed in data stored in the state database according to the execution of the smart contract **210** and/or data (e.g., delete-set) deleted from the state database according to the execution of the smart contract **210** may be returned. Hereafter, the data returned according to executing the smart contract **210** may be referred to as output data.

(54) In an embodiment, the blockchain platform **200** may store a part of the distributed ledge of the blockchain network where the electronic device **100** is configured as the blockchain node. The distributed ledger may include a blockchain **221** which is a linked-list of blocks including data of transactions executed in the blockchain network and the state database **222** which stores world state data.

(55) In an embodiment, the partial ledge **220** may include the blockchain **221** and the state database **222**. In an embodiment, the partial ledger may include the part of the distributed ledger of the blockchain network. According to an embodiment, the partial ledger **220** may store the transaction data related to the electronic device **100** in the blockchain network. For example, it may store blocks and data based on the transaction participated by the electronic device **100** in consensus. According to an embodiment, the partial ledger **220** may be a partial ledger including at least a part of a full ledger of the blockchain network. For example, the partial ledger may be the partial ledger which stores blocks and data of transactions related to the electronic device **100** in the full ledger which stores blocks and data of every transaction of the blockchain network.

(56) According to an embodiment, the blockchain **221** may include at least one block generated through the blockchain network. The block may include a block header and transaction data. According to an embodiment, the block header may include at least one of a hash value of a header and a data region, a hash value of a previous block, a height value of a block, a hash value of state data after executing the transaction included in the block, a public key of a block generator, a value obtained by signing a hash value based on a private key of the block generator, or a value obtained by signing a hash value based on an attestation key certificate chain or an attestation key.

(57) The block data may include at least one of hash values of at least part of transaction data, smart contract version information, smart contract ID, smart contract function ID, smart contract data which is a factor value (e.g., read-set) required for the smart contract function, a nonce value which is a transaction generation number of the transaction generator, a public key of the transaction generator, a value obtained by signing the hash value based on the private key of the transaction generator, a value obtained by signing the attestation key certificate chain or the hash

value based on the attestation key. In addition, the block data may include at least one of transaction type, transaction version, timestamp, blockchain network channel ID value, epoch, payload visibility, chain code path, chain code name, chain code version, chain code type, timeout, transaction endorser ID and endorser signature, response status, namespace, read-set, write-set, read list, and Merkle tree query summary.

(58) In an embodiment, the block data may include block metadata. The block metadata may include at least one of block generator ID value, related signature, last configuration block number, and flag of each transaction included in the block.

(59) In an embodiment, the transaction may include the smart contract (or chain code). At a transaction request, the smart contract may be executed, and thus the world state may be updated.

(60) In an embodiment, the blocks of the partial ledger **220** are chained (e.g., linked-list) and the block data may be stored in the partial ledger **220**. For example, at least one block included in the blockchain **221** may include a hash field and block data. According to an embodiment, the hash field may include previous block information of the full ledger of the blockchain network and previous block information of the partial ledger of the blockchain network. In an embodiment, the block data may include transaction data of the corresponding block.

(61) According to an embodiment, at least one block included in the blockchain **221** may be connected based on the previous block information included in the hash field.

(62) In an embodiment, the state database **222** may store values changed by the transaction execution of the blockchain network in a key-value form. According to an embodiment, the key-value form may include data key, data value, data hash, information of a block node owning data in the blockchain network and block number. In an embodiment, the data stored in the state database **222** may be expressed as state data. The state data may indicate, for example, data stored in the world state which is a database used in the Hyperledger fabric. However, it is not limited thereto and the state database **222** may use a level database or a couch database.

(63) The state database **222** may store final values changed by executing transactions in the key-value form. Hence, the electronic device **100** may identify the state database **222** to identify the final values by the transaction execution of the blockchain network.

(64) According to an embodiment, the state database **222** may store data of transactions participated by the user of the electronic device **100**. For example, it may store values changed by the transaction execution related to the electronic device **100** in the blockchain network.

(65) According to an embodiment, the blockchain processor **230** may control the electronic device **100** to process the blockchain consensus in the blockchain network. For example, the blockchain processor **230** may process the blockchain consensus based on the consensus algorithm used in the blockchain network. The blockchain processor **230** may support various consensus algorithms which are typically used in the blockchain. For example, the blockchain processor **230** may perform the transaction consensus with the blockchain nodes included in the blockchain network based on proof of work (POW), proof of stake (POS), practical Byzantine fault-tolerance (PBFT), and reversible addition—fragmentation chain-transfer (RAFT).

(66) According to an embodiment, the blockchain processor **230** may endorse the transaction requested to generate. For example, the blockchain processor **230** may generate first output data by executing the smart contract for the transaction. According to an embodiment, the first output data may indicate a data set returned according to executing the smart contract. For example, the first output data may include data (e.g., write-set) changed in the state database **222** according to the smart contract execution, data (e.g., the input data described in FIG. 1) referred to in the state database **222** according to the smart contract execution, and data (e.g., delete-set) deleted from the state database **222** according to the smart contract execution.

(67) According to an embodiment, the blockchain processor **230** may transmit an endorsement request including the transaction to a blockchain node related to the transaction among at least one blockchain node (e.g., a peer node) included in the blockchain network.

(68) According to an embodiment, the blockchain processor **230** may obtain endorsement data including second output data of the transaction from the blockchain node related to the transaction based on the endorsement request. For example, the blockchain processor **230** may obtain the second output data including a smart contract execution result of the transaction from a second blockchain node related to the transaction.

(69) According to an embodiment, the blockchain processor **230** may endorse the transaction based on the first output data and the second output data obtained from the second blockchain node. For example, if the first output data which is the execution result of the first smart contract included in the electronic device **100** and the second output data which is the execution result of the second smart contract included in the second blockchain node are the same, the blockchain processor **230** may determine that the endorsement of the transaction is successful. As another example, if the first output data and the second output data are different, the blockchain processor **120** may determine that the transaction endorsement fails. According to various embodiments, the blockchain processor **230** may endorse the transaction using one of various endorsement methods. For example, the blockchain processor **230** may determine the endorsement success even if the first output data and the second output data are identical in part. For example, the blockchain processor **230** may perform the endorsement based on the data changed in the state database **222** according to executing the smart contract **210** in data included in the first output data and the second output data. As another example, the blockchain processor **230** may perform the endorsement based on data changed in the state database and data deleted from the state database according to executing the smart contract **210** in data included in the first output data and the second output data.

(70) According to an embodiment, the blockchain processor **230** may perform an operation related to the blockchain network which the electronic device **100** participates in as the blockchain node. According to an embodiment, the blockchain processor **230** may build the blockchain network, and perform an operation related to other nodes (external devices) included in the blockchain network.

(71) FIG. **3** is a block diagram illustrating a blockchain network, according to an embodiment.

(72) Referring to FIG. **3**, a plurality of blockchain nodes **310**, **320**, **330**, and **340** and a data server **350** may build a blockchain network **300**. The plurality of the blockchain nodes **310**, **320**, **330**, and **340** building the blockchain network **300** may include a portable electronic device. For example, the plurality of the blockchain nodes **310**, **320**, **330**, and **340** may correspond to a mobile, a tablet PC and/or a notebook. According to an embodiment, a first blockchain node **310**, a second blockchain node **320** and a second blockchain node **330** may indicate endorser nodes which are portable mobile nodes. According to an embodiment, a fourth blockchain node **340** may indicate an ordering node.

(73) According to an embodiment, the first through third blockchain nodes **310**, **320** and **330** may simulate transaction execution and generate read-write sets. The read-set may simulate a task to read data of the partial ledger in the transaction. The write-set may indicate a data set to be updated to the ledger if the transaction is executed and committed to the partial ledger. However, it is not limited thereto, and the first through third blockchain nodes **310**, **320** and **330** may generate various data sets. For example, the first through third blockchain nodes **310**, **320** and **330** may generate a delete-set which is a data set to be deleted from the ledger, if the transaction is executed and committed to the partial ledger.

(74) According to an embodiment, the endorser node may execute and endorse the transaction. Also, the endorser node may be a committer node. For example, the first through third blockchain nodes **310**, **320** and **330** may update the partial ledger stored in their nodes based on an update request of the endorsed transaction.

(75) According to an embodiment, the first blockchain node **310** may be a leader node which requests to generate a transaction. According to various embodiments, the leader node may change in each transaction generated in the blockchain network **300**.

(76) According to an embodiment, the first blockchain node **310** (e.g., the electronic device **100**),

the second blockchain node **320** and/or the third blockchain node **330** may include a similar configuration to the electronic device **100** explained in FIG. **1** and FIG. **2**. For example, the plurality of the blockchain nodes **310**, **320**, **330**, and **340** may include similar configurations to the blockchain platform **200** as configurations for performing necessary operations in the blockchain network. For example, the first through third blockchain nodes **310**, **320** and **330** may store a smart contract (e.g., the smart contract **210**) and the partial ledger (e.g., the partial ledger **220**) in a memory (e.g., the memory **110**) of the electronic device (e.g., the electronic device **100**). For example, the first blockchain node **310** may include a first partial ledger **311** including a third block and state data of the third block in the distributed ledger of the blockchain network.

(77) According to an embodiment, the fourth blockchain node **340** may correspond to the ordering node. For example, the fourth blockchain node **340** may receive transaction data including the transaction and the read-write sets and the block generation request from the endorser node (e.g., at least one of the first through third blockchain nodes **310**, **320** and **330**). The fourth blockchain node **340** may sequence at least one transaction data obtained from the endorser node in the blockchain network and then generate blocks in order. Alternatively, the fourth blockchain node **340** may perform the consensus to sequence the transaction data and then generate blocks in order, and request the committer node to update the blocks. For example, the fourth blockchain node **340** may receive transaction data including the transaction and the read-write sets and the block generation request from the first blockchain node **310**. In addition, the fourth blockchain node **340** may identify whether input data (e.g., read-set) and output data have no problems between transactions. For example, the fourth blockchain node **340** may identify whether the input data (e.g., read-set) and the output data conflict between the transactions. In an embodiment, the fourth blockchain node **340** may identify no conflicts, and finalize the block by performing the consensus.

(78) According to the present disclosure, the four blockchain nodes build the blockchain network to ease the explanations, but it is not limited thereto.

(79) According to an embodiment, the data server **350** may indicate a storage space inside the blockchain network accessible by the plurality of the blockchain nodes **310**, **320**, **330**, and **340** included in the blockchain network **300**. According to another example, the data server **350** may be an external storage space of the blockchain network **300**.

(80) According to an embodiment, the data server **350** may indicate a space allowing the first through third blockchain nodes **310**, **320** and **330** to store and retrieve data to share necessary data for the transaction consensus. According to an embodiment, the data server **350** may generate the shared ledger by receiving a request from the leader node which obtains the transaction generation request. For example, the data server **350** may generate a shared ledger **351** of the transaction based on a request of the first blockchain node **310** obtaining the transaction generation request. The shared ledger **351** may be deleted as the transaction generation is finished.

(81) According to an embodiment, the first through third blockchain nodes **310**, **320** and **330** may encrypt the necessary data for the transaction consensus with a transaction encryption key and upload it to the shared ledger **351**.

(82) According to an embodiment, the first blockchain node **310** may generate the encryption key for the transaction. In addition, it may share the generated encryption key to nodes (e.g., the second blockchain node **320** and the third blockchain node **330**) to participate in the transaction consensus among at least one blockchain node included in the blockchain network **300**. The data server **350** may obtain the encrypted data from the first through third blockchain nodes **310**, **320** and **330**, and upload it to the shared ledger **351**.

(83) According to an embodiment, the first blockchain node **310** may use various methods to share the generated encryption key. For example, the processor **130** may share the encryption key generated in a plaintext form to the nodes (e.g., the second blockchain node **320** and the third blockchain node **330**) to participate in the consensus.

(84) As another example, in sharing the generated encryption key, the first blockchain node **310**

may share through the asymmetric encryption scheme. For example, the processor **130** may encrypt the generated encryption key with a public key of the second blockchain node **320** and share to the second blockchain node **320**. In addition, the processor **130** may encrypt the generated encryption key with a public key of the third blockchain node **330** and share to the third blockchain node **320**. In an embodiment, the second blockchain node **320** and the third blockchain node **330** sharing the encryption key encrypted with their public key may decrypt and use the encryption key with their private key. Yet, the method for the first blockchain node **310** to share the encryption key is not limited thereto.

(85) In an embodiment, the first through third blockchain nodes **310**, **320** and **330** may perform transaction generation and block recording related to the devices in all the transactions in the blockchain network **300**. For example, the first through third blockchain nodes **310**, **320** and **330** may participate in the transaction consensus related to the devices, and store only a block and state data of the transaction related to the devices in their memory. For example, the first blockchain node **310** may participate in the transaction consensus related to the electronic device **100** and/or the user of the electronic device **100**, and store only the block and the state data of the transaction in the memory **110**. Hence, the first through third blockchain nodes **310**, **320** and **330** may store a partial ledger storing only the block and the state data of their participating transaction of the full ledger of the blockchain network **300** in their memory. For example, the first blockchain node **310** may store the first partial ledger **311** including third block data. In addition, the second blockchain node **320** may store a second partial ledger **321** including second block data. In addition, the third blockchain node **330** may store a third partial ledger **331** including first and fourth block data.

(86) According to an embodiment, the first through third blockchain nodes **310**, **320** and **330** each may independently execute a smart contract for the transaction execution. In an embodiment, the smart contract may execute the same program logic for processing the transaction. The nodes included in the blockchain network **300** according to an embodiment may be configured to participate in only the transaction executed related to the devices.

(87) In an embodiment, to execute the smart contract, the first through third blockchain nodes **310**, **320** and **330** may refer to the state data stored in the state database included in at least one of the first through third blockchain nodes **310**, **320** and **330**. For example, the first through third blockchain nodes **310**, **320** and **330** each may refer to the state data uploaded to the data server **350** through at least a part of the first through third blockchain nodes **310**, **320** and **330** to execute the smart contract.

(88) According to an embodiment, the first through third blockchain nodes **310**, **320** and **330** each may execute the smart contract based on the state data, and determine whether to execute the transaction based on a result of the endorsement process performed between them. For example, the transaction endorsement success may be determined if result values (e.g., output data) generated by executing the smart contract by the first through third blockchain nodes **310**, **320** and **330** match. The block of the transaction may be generated through the endorsement performed between the devices related to the transaction execution among the first through third blockchain nodes **310**, **320** and **330**. According to an embodiment, the generated block may be added to the blockchain of the distributed ledger stored in the devices related to the transaction execution. For example, the added block may be connected as a block after a terminal block of the blockchain of the distributed ledger.

(89) According to an embodiment, key values stored in the state database of the devices related to the transaction execution among the first through third blockchain nodes **310**, **320** and **330** may be updated by the transaction execution. For example, as finishing the transaction generation and execution, the first through third blockchain nodes **310**, **320** and **330** may obtain a transaction update request from the fourth blockchain node **340**. Based on the update request, the first through third blockchain nodes **310**, **320** and **330** may update their partial ledgers (the first partial ledger **311**, the second partial ledger **321** and the third partial ledger **330**).

(90) The nodes of the blockchain network **300** according to an embodiment, which participate only in the transaction execution related to their device, may store the state data of the transaction related to the devices. Accordingly, the nodes of the blockchain network **300** may update the state database if the transaction related to the devices is executed, without having to update the state database according to the execution of every transaction.

(91) FIG. 4 through FIG. 6 are flow diagrams illustrating methods of transaction generation of an electronic device according to an embodiment. According to various embodiments, some of operations of FIG. 4 through FIG. 6 may be omitted, and the order of some operations may be changed.

(92) FIG. 4 is a flow diagram **400** illustrating an electronic device generating an encryption key, according to an embodiment.

(93) Referring to FIG. 4, a first blockchain node **410** (e.g., the first blockchain node **310** of FIG. 3), a second blockchain node **420** (e.g., the second blockchain node **320** of FIG. 3) and a third blockchain node **430** (e.g., the third blockchain node **330** of FIG. 3) are shown. According to an embodiment, the first blockchain node **410** may indicate the leader node which generates a transaction and requests endorsement, and the second blockchain node **420** and the third blockchain node **430** may indicate the endorser nodes which participate in the transaction endorsement.

(94) According to an embodiment, the first blockchain node **410** may obtain a transaction generation request **451** according to a request of the user and/or other application stored in the electronic device **100** which is the first blockchain node **410**.

(95) In an embodiment, the first blockchain node **410** may identify at least one blockchain node **452** related to the transaction based on the transaction generation request **451**. For example, the first blockchain node **410** may identify at least one blockchain node for endorsing the transaction.

(96) According to an embodiment, the first blockchain node **410** may design to define nodes participating in the transaction with an input value before executing a first smart contract for the transaction, and identify at least one blockchain node for endorsing the transaction based on the design.

(97) According to an embodiment, the first blockchain node **410** may identify at least one blockchain node for endorsing the transaction in runtime for which the smart contract is executed logically.

(98) According to an embodiment, the first blockchain node **410** may identify at least one blockchain node for endorsing the transaction based on node information of blockchain nodes included in a blockchain network (e.g., the blockchain network **300** of FIG. 3) stored in a memory (e.g., the memory **110** of FIG. 1) or node information obtained from a separate blockchain node which manages the node information.

(99) According to an embodiment, the first blockchain node **410** may generate an encryption key **453** corresponding to the transaction. For example, the first blockchain node **410** may generate a unique encryption key for the transaction requested to generate. The generated encryption key may indicate a temporary encryption key (e.g., temporary transaction encryption key (TTEK)) for the transaction.

(100) According to an embodiment, the first blockchain node **410** may request a data server (e.g., the data server **350** of FIG. 3) included in the blockchain network to generate a shared ledger (e.g., the shared ledger **451** of FIG. 3) of the transaction in response to the transaction generation request **451**. According to an embodiment, the shared ledger generated through the first blockchain node **410** may be deleted as the endorsement of the corresponding transaction is finished.

(101) According to an embodiment, the first blockchain node **410** may share the encryption key generated for the transaction with the blockchain node participating in the transaction endorsement. For example, the first blockchain node **410** may transmit the encryption key **454** to the second blockchain node **420**, and transmit the encryption key **455** to the third blockchain node **430**.

(102) FIG. 5 is a flow diagram illustrating an electronic device executing a smart contract,

according to an embodiment.

(103) Referring to FIG. 5, a first blockchain node **410**, a second blockchain node **420**, a third blockchain node **430** and a data server **510** (e.g., the data server **350** of FIG. 3) are shown.

(104) According to an embodiment, the first blockchain node **410** may determine first data **551** stored in a memory (e.g., the memory **110**) among input data (e.g., the read-set explained in FIG. 2) required to execute a first smart contract of a transaction requested to generate. For example, the first blockchain node **410** may determine data stored in a state database (e.g., the state database **222** of FIG. 2) among the input data.

(105) According to an embodiment, the input data may include data not stored in the memory of the first blockchain node **410** among the input data required to execute the smart contract. Hereafter, the data stored in the first blockchain node among the input data may be expressed as first data. In addition, the data not stored in the first blockchain node among the input data may be expressed as second data.

(106) According to an embodiment, the first blockchain node **410** may encrypt the first data **552** with an encryption key of the transaction. For example, the first blockchain node **410** may encrypt the first data with the encryption key based on the symmetric encryption algorithm (e.g., the AES).

(107) According to an embodiment, the first blockchain node **410** may upload the encrypted first data **553** to the data sever **510**. For example, the first blockchain node **410** may upload the encrypted first data to a shared ledger of the transaction generated at the data server **510**. According to an embodiment, the data server **510** may store the encrypted first data in the shared ledger, based on the upload **553**.

(108) According to an embodiment, the data server **510** may notify the upload to other blockchain nodes included in the blockchain network according to the data upload in the shared ledger. For example, based on the first data upload, the data server **510** may transmit a first data upload notification **554** to the second blockchain node **420**, and transmit a first data upload notification **555** to the third blockchain node **430**.

(109) According to an embodiment, the second blockchain node **420** and the third blockchain node **430** may receive a transaction endorsement request from the first blockchain node **410**. In an embodiment, the second blockchain node **420** may upload the second data stored in the second blockchain node **420** to the data server **510** among the input data required to execute the smart contract of the transaction requested to generate based on the transaction endorsement request. For example, the second blockchain node **420** may encrypt the second data based on the encryption key obtained from the first blockchain node **410**, and upload the encrypted second data **556** to the data server **510**. According to an embodiment, based on the upload **556**, the data server **510** may store the second data in the shard ledger. It has been described that the second blockchain node **420** uploads the second data not stored in the first blockchain node **410** to ease the description, but the second data may be uploaded through various blockchain nodes included in the blockchain network according to various embodiments.

(110) According to an embodiment, the second blockchain node **420** may encrypt the second data based on various encryption algorithms. For example, if obtaining the encryption key from the first blockchain node **410**, the second blockchain node **420** may encrypt the second data with the obtained encryption key. Alternatively, if the second blockchain node **420** obtains encryption key information from the first blockchain node **410**, the second blockchain node **420** may generate an encryption key based on the encryption key information, and encrypt the second data with the generated encryption key. For example, if the second blockchain node **420** obtains a seed value used to generate the encryption key from the first blockchain node **410**, the second blockchain node **420** may generate an encryption key using the obtained seed value, and encrypt the second data with the generated encryption key. In an embodiment, the encryption key generated by the second blockchain node **420** using the encryption key information may indicate the same encryption key as the encryption key owned by the first blockchain node **410**.

(111) According to an embodiment, the data server **510** may notify the upload to other blockchain nodes included in the blockchain network according to the data upload in the shared ledger. For example, based on the second data upload, the data server **510** may transmit a second data upload notification **557** to the first blockchain node **420**.

(112) According to an embodiment, in response to the notification **557**, the first blockchain node **410** may request the second data **558** from the data server **510**. For example, in response to the second data upload to the data server **510**, the first blockchain node **410** may request the second data from the data server **510**, among the first data and the second data required to execute the first smart contract.

(113) According to an embodiment, the first blockchain node **410** may obtain from the data server **510** a notification indicating that at least part of the second data is uploaded, and download at least part of the second data uploaded to the data server **510** in response to the notification.

(114) According to an embodiment, the first blockchain node **410** may identify the second data not stored in the partial ledger among the input data required to execute the first smart contract of the transaction, and request the second data from the data server **510**. In an embodiment, the first blockchain node **410** may request the second data from the data server **510** before receiving the second data upload notification from the data server **510**. In this case, the first blockchain node **410** may hold the second data upload.

(115) According to an embodiment, the data server **510** may transmit the encrypted second data **559** in response to the request **558**.

(116) According to an embodiment, the first blockchain node **410** may decrypt the encrypted second data **560** with the encryption key. For example, the first blockchain node **410** may acquire the second data by decrypting the encrypted second data based on the encryption key information.

(117) According to an embodiment, the data uploaded to the data server **510** may be encrypted with the encryption key of the transaction and decrypted, and thus the blockchain nodes may exchange state data required to execute the smart contract of the transaction without security problems.

(118) According to an embodiment, the first blockchain node **410** may execute a first smart contract **561** based on the first data and the second data. For example, the first blockchain node **410** may execute the first smart contract using the first data stored in the memory and the second data obtained from the data server as the input data. The first blockchain node **410** may obtain first output data by executing the first smart contract. For example, the first blockchain node **410** may acquire the first output data including the input data, data (e.g., write-set) to be updated to the state database based on the first smart contract execution, and/or data (e.g., delete-set) to be deleted from the state database based on the first smart contract execution.

(119) Generating the encryption key and encrypting and/or decrypting the first data or the second data using the encryption key explained in FIG. 4 and FIG. 5 may indicate similar operations to generating the encryption key and encrypting and/or decrypting the first data using the encryption key explained in FIG. 1 and FIG. 2.

(120) FIG. 6 is a flow diagram illustrating an electronic device endorsing a transaction of a blockchain network, according to an embodiment.

(121) Referring to FIG. 6, a first blockchain node **410**, a second blockchain node **420**, a third blockchain node **430**, a data server **510** and a fourth blockchain node **610** (e.g., the fourth blockchain node **340** of FIG. 3) are shown.

(122) According to an embodiment, the first blockchain node **410** may indicate the leader node which generates a transaction and requests endorsement, and the second blockchain node **420** and the third blockchain node **430** may indicate the endorser nodes which participate in the transaction endorsement. In addition, the fourth blockchain node **610** may indicate the ordering node.

(123) According to an embodiment, the first blockchain node **410** may identify at least one blockchain node related to the transaction in response to the transaction generation request, and transmit a transaction endorsement request to the identified blockchain node. For example, the first

blockchain node **410** may transmit a transaction endorsement request **651** to the second blockchain node **420**. In addition, the first blockchain node **410** may transmit a transaction endorsement request **652** to the third blockchain node **430**.

(124) According to an embodiment, the second blockchain node **420** obtaining the endorsement request **651** may execute a second smart contract **653** for the transaction requested to endorse. In an embodiment, the second blockchain node **420** may perform a similar operation to the smart contract execution of the first blockchain node **410** explained in FIG. 5. For example, the second blockchain node **420** may encrypt data stored in the memory of the second blockchain node **420** with an encryption key among data required to execute the second smart contract and upload it to the data server **510**. Also, for example, second blockchain node **420** may download from the data server **510** data not stored in the memory of the second blockchain node **420** among the data required to execute the second smart contract, and decrypt and use it with the encryption key. According to an embodiment, the second blockchain node **420** may generate second output data according to executing the second smart contract.

(125) According to an embodiment, the second blockchain node **420** may transmit endorsement data **654** including the second output data to the first blockchain node **410**. For example, the endorsement data may include the second output data and/or the input data for the second smart contract.

(126) According to an embodiment, the second blockchain node **420** may delete the encryption key **655** after the transmission operation **654**. For example, the second blockchain node **420** may shred the encryption key after transmitting the endorsement data for the transaction endorsement operation.

(127) According to an embodiment, the third blockchain node **430** obtaining the endorsement request **652** may execute a third smart contract **656** of the transaction requested for the endorsement. In an embodiment, the third blockchain node **430** may execute the third smart contract in the similar manner to the second blockchain node **420**. Hence, the third blockchain node **430** may generate third output data by executing the third smart contract.

(128) According to an embodiment, the third blockchain node **430** may transmit endorsement data **657** including the third output data to the first blockchain node **410**. For example, the endorsement data may include the third output data and/or the input data for the third smart contract.

(129) According to various embodiments, the endorsement data transmitted to the first blockchain node **410** in response to the endorsement request of the first blockchain node **410** may include various data. For example, according to an endorsement policy, the second blockchain node **420** may transmit the endorsement data including some of the second output data to the first blockchain node **410**. In addition, according to the endorsement policy, the third blockchain node **430** may transmit the endorsement data including some of the third output data to the first blockchain node **410**. The endorsement policy may indicate a transaction endorsement method predetermined among various transaction endorsement methods.

(130) According to an embodiment, the third blockchain node **430** may delete the encryption key **658** after the transmission operation **657**. For example, the third blockchain node **430** may shred the encryption key after transmitting the endorsement data for the transaction endorsement operation.

(131) According to an embodiment, the first through third blockchain nodes **410**, **420** and **430** participating in the transaction endorsement operation each may execute a smart contract of the transaction. In an embodiment, the first through third blockchain nodes **410**, **420** and **430** each may execute the smart contract using the state data stored in the shared ledger of the data server **510**. In so doing, the first through third blockchain nodes **410**, **420** and **430** may upload to the data server **510** or download from the data server **510** the encrypted state data using the pre-shared encryption key, thus maintaining security of the state data.

(132) In addition, at least one blockchain node including the partial ledger included in the

blockchain network may obtain from the data server **510** data not stored in the partial ledger among the data required to execute the smart contract, thus reducing unnecessary communications.

(133) According to an embodiment, the first blockchain node **410** may endorse the transaction **659** based on the first output data and the endorsement data. For example, the first blockchain node **410** may compare at least part of the first output data with at least part of the second output data included in the endorsement data obtained from the second blockchain node **420**. The compared data may be determined according to the endorsement policy. As a result of the comparison, if the first output data and the second output data match, transaction endorsement success may be determined. Also, for example, the first blockchain node **410** may compare at least part of the first output data with at least part of the third output data included in the endorsement data obtained from the third blockchain node **430**. As a result of the comparison, if the first output data and the third output data match, transaction endorsement success may be determined.

(134) As another example, as a result of the comparison, if the first output data and the second output data do not match, the first blockchain node **410** may determine transaction endorsement failure. Also, as another example, if the first output data and the third output data do not match, the first blockchain node **410** may determine transaction endorsement failure.

(135) According to an embodiment, the first blockchain node **410** may determine transaction endorsement complete if every endorsement obtained from other blockchain nodes included in the blockchain network is successful.

(136) According to an embodiment, the first blockchain node **410** may finish the transaction endorsement by performing operation **651** through operation **659** with the blockchain nodes related to the transaction.

(137) According to various embodiments, the transaction endorsement operation may be carried out through various methods. According to another example, the second blockchain node **420** may obtain an endorsement request **651** from the first blockchain node **410**. In so doing, the endorsement request **651** may include the first output data. The second blockchain node **420** may execute a second smart contract **653** of the transaction, in response to the endorsement request **651**. In addition, the second blockchain node **420** may compare at least part of the first output data obtained from the first blockchain node **410** with at least part of the second output data. As a result of the comparison, the second blockchain node **420** may determine endorsement success if the first output data and the second output data are the same, and may determine endorsement failure if they are different. In an embodiment, the second blockchain node **420** may transmit endorsement data **654** including the determination result to the first blockchain node **410**.

(138) Also, the third blockchain node **430** may obtain an endorsement request **652** from the first blockchain node **410**. In so doing, the endorsement request **652** may include the first output data. The third blockchain node **430** may execute a third smart contract **656** of the transaction, in response to the endorsement request **652**. In addition, the third blockchain node **430** may compare at least part of the first output data obtained from the first blockchain node **410** with at least part of the third output data. As a result of the comparison, the third blockchain node **430** may determine endorsement success if the first output data and the third output data are the same, and may determine endorsement failure if they are different. In an embodiment, the third blockchain node **430** may transmit endorsement data **657** including the determination result to the first blockchain node **410**.

(139) In an embodiment, if omitting operation **659** and determining the endorsement success based on the endorsement data received from the second blockchain node **420** and the endorsement data received from the third blockchain node **430**, the first blockchain node **410** may request the fourth blockchain node **610** to generate a block **660** including transaction data.

(140) According to an embodiment, the first blockchain node **410** may display information of the endorsement operation result on a display (e.g., the display **140** of FIG. 1) included in the first blockchain node **410**. For example, if the endorsement operation fails, the first blockchain node

410 may abort the transaction and provide a failure notification. As another example, if the endorsement operation is successful, the first blockchain node **410** may provide a transaction success notification.

(141) According to an embodiment, the first blockchain node **410** may request the fourth blockchain node **610** to generate a block **660** including transaction data. For example, the first blockchain node **410** may request to generate the transaction block as the transaction consensus is finished. The first blockchain node **410** may transmit the transaction data including various data (e.g., the input data, the first output data) required to generate the transaction block to the fourth blockchain node **610**.

(142) According to an embodiment, the first blockchain node **410** may request the data server **510** to delete the shared ledger **661** as the transaction endorsement is finished. For example, the first blockchain node **410** may request to delete the shared ledger generated in the data base of the data server **510** as the transaction endorsement is finished. The data server **610** may delete the shared ledger **662** in response to the request **661**. Hence, the shared ledger of the transaction may be temporarily generated and deleted based on the transaction generation in the blockchain network.

(143) According to an embodiment, the fourth blockchain node **610** may store the transaction data in a block confirmation queue in response to the request **660**. According to an embodiment, the fourth blockchain node **610** is not limited to the queue and may store the transaction data using one of various data structures. According to an embodiment, the fourth blockchain node **610** may generate a block **663** in order of storing in the block confirmation queue in a first in first out manner. The block generation operation may be expressed as ordering. According to an embodiment, the fourth blockchain node **610** may verify the block requested to generate based on the storage order of the block confirmation queue. For example, the fourth blockchain node **610** may generate a block based on the transaction data in the block confirmation queue storage order, and perform the block consensus operation. According to an embodiment, the block consensus operation may be performed based on various consensus algorithms. For example, the block consensus operation may be performed with the ordering nodes included in the blockchain network based on the POW, the POS, the PBFT, and the RAFT.

(144) According to an embodiment, as the block is generated, the fourth blockchain node **610** may confirm the generated block as the verified block, and connect as a terminal node to the blockchain of the full ledger included in the blockchain network. Also, the fourth blockchain node **610** may request to update the partial ledger based on the confirmed block. According to an embodiment, the fourth blockchain node **610** may request the blockchain nodes participating in the transaction consensus of the block to update the block. For example, the fourth blockchain node **610** may request the third blockchain node **430** to update the partial ledger **664**. Likewise, the fourth blockchain node **610** may request the second blockchain node **420** to update the partial ledger **665**, and request the first blockchain node **420** to update the partial ledger **666**.

(145) According to an embodiment, the first through third blockchain nodes **410**, **420** and **430** may update their partial ledger based on the partial ledger update requests **664**, **665** and **666**. For example, the first blockchain node **410** may update the partial ledger **667**. For example, the first blockchain node **410** may store first output data generated based on the transaction in a state database (e.g., the state database **222** of FIG. 2), and connect the generated block as a terminal block of the blockchain (e.g., the blockchain **221** of FIG. 2). According to an embodiment, the first blockchain node **410** may shred the encryption key based on finishing the transaction generation.

(146) FIG. 7 is a flowchart illustrating a method **700** of executing a smart contract, according to an embodiment.

(147) Hereafter, redundant descriptions on similar operations to the operations explained in FIG. 3 through FIG. 6 shall be omitted.

(148) Referring to FIG. 7, the electronic device **100** (e.g., the first blockchain node **410**) may generate an encryption key corresponding to a transaction in response to obtaining a transaction

generation request in operation **701**. According to an embodiment, the processor **130** (e.g., the blockchain processor **230**) of the electronic device **100** may obtain the transaction generation request from the user of the electronic device **100** and/or other application stored in the memory **110**, and accordingly generate the encryption key corresponding to the transaction. In an embodiment, the encryption key may indicate a unique encryption key of the transaction. Hence, if a plurality of transactions is generated, their corresponding encryption keys may be different from each other.

(149) According to an embodiment, the electronic device **100** may transmit encryption key information to at least one blockchain node related to the transaction in operation **703**. For example, the electronic device **100** may transmit the encryption key information to at least one blockchain node (e.g., the second blockchain node **420** and/or the third blockchain node **430**) related to the transaction requested to generate among blockchain nodes included in a blockchain network (e.g., the blockchain network **300** of FIG. 3). In an embodiment, the encryption key information may include a seed value (root-seed) for deriving the encryption key or at least part of the encryption key.

(150) According to an embodiment, the electronic device **100** may encrypt first data stored in the partial ledger **220** based on the encryption key among input data (e.g., read-set) required to execute a first smart contract of the transaction in operation **705**. For example, the electronic device **100** may identify the first data stored in the state database **222** among the input data, and encrypt the first data with the encryption key based on the asymmetric encryption algorithm.

(151) According to an embodiment, the electronic device **100** may encrypt and upload the first data to a data server (e.g., the data server **350** of FIG. 3) included in the blockchain network in operation **707**. According to an embodiment, the electronic device **100** may upload the first data to the shared ledger of the transaction stored in the data server.

(152) According to an embodiment, the electronic device **100** may download second data encrypted based on the encryption key from the data server in operation **709**. According to an embodiment, the electronic device **100** may obtain from the data server the second data not stored in the partial ledger **220** among the input data (e.g., read-set) required to execute the first smart contract of the transaction. According to an embodiment, the second data encrypted with the encryption key may include data uploaded through at least one other blockchain nodes included in the blockchain network.

(153) According to an embodiment, the electronic device **100** may decrypt the second data based on the encryption key in operation **711**. For example, the electronic device **100** may decrypt the second data encrypted with the encryption key of the transaction.

(154) According to an embodiment, the electronic device **100** may execute the first smart contract based on the first data and the decrypted second data in operation **713**. For example, the electronic device **100** may execute the first smart contract based on the first data which is data stored in the partial ledger **220** among the input data and the second data not stored in the partial ledger **220** and obtained from the data server. The electronic device **100** according to an embodiment, which stores the partial ledger **220** rather than the full ledger of the blockchain network, may not store part of state data required to execute a smart contract. Hence, the electronic device **100** may execute a smart contract using the input data uploaded to the data server.

(155) According to an embodiment, the electronic device **100** may finish a transaction endorsement operation based on the first output data generated as executing the first smart contract and endorsement data obtained from the blockchain nodes related to the transaction.

(156) FIG. 8 is a flowchart illustrating a method **800** of endorsing a transaction, according to an embodiment.

(157) Hereafter, redundant descriptions on similar operations to the operations explained in FIG. 3 through FIG. 7 shall be omitted.

(158) Referring to FIG. 8, the electronic device **100** (e.g., the first blockchain node **410**) may

generate an encryption key corresponding to a transaction in response to obtaining a transaction generation request in operation **801**.

(159) According to an embodiment, the electronic device **100** may transmit encryption key information to at least one blockchain node related to the transaction in operation **803**.

(160) According to an embodiment, the electronic device **100** may encrypt first data stored in the partial ledger **220** based on the encryption key among input data required to execute a first smart contract of the transaction in operation **805**.

(161) According to an embodiment, the electronic device **100** may store the encrypted first data, in a shared ledger of a blockchain network (e.g., the blockchain network **300** of FIG. 3) and upload to a data server (e.g., the data server **510** of FIG. 6) accessible by at least one blockchain nodes in operation **807**.

(162) According to an embodiment, the electronic device **100** may transmit a transaction endorsement request to at least one blockchain node in operation **809**. For example, the electronic device **100** may identify a blockchain node participating in consensus of the transaction requested to generate, and transmit the endorsement request to the at least one blockchain node identified (e.g., the second blockchain node **420** and/or the third blockchain node **430** of FIG. 6).

(163) According to an embodiment, in operation **811**, the electronic device **100** may obtain endorsement data from at least one blockchain node. For example, the electronic device **100** may obtain the endorsement data including at least part of output data which is an execution result of a smart contract executed at each of at least one blockchain node based on the endorsement request. According to an embodiment, to execute the smart contract, the at least one blockchain node may use data uploaded to the data server.

(164) According to an embodiment, the electronic device **100** may endorse the transaction in operation **813**. For example, the electronic device **100** may endorse the transaction based on the endorsement data and first output data generated according to executing a first smart contract. For example, the electronic device **100** may endorse the transaction, by performing a similar operation to operation **659** explained in FIG. 6.

(165) According to an embodiment, the electronic device **100** may obtain second data not stored in the partial ledger **220** among the data required to execute the first smart contract from the data server, and execute the first smart contract based on the first data and the second data. For example, the electronic device **100** may download the second data encrypted based on the encryption key from the data server, and decrypt the second data based on the encryption key. In addition, the electronic device **100** may execute the first smart contract based on the first data and the decrypted second data. The electronic device **100** may endorse the transaction based on first output data generated according to executing the first smart contract.

(166) According to an embodiment, as the endorsement is finished, the electronic device **100** may request a block generation node (e.g., the fourth blockchain node **610**) to generate a block including transaction data, and receive an update request including the generated block in response to a block generation request.

(167) According to an embodiment, the electronic device **100** may update the partial ledger **220** based on the generated block and the transaction data in response to the update request including the block.

(168) As stated above, according to an embodiment, an electronic device (e.g., the electronic device **100** of FIG. 1) constituting a first blockchain node included in a blockchain network may include a communication circuit (e.g., the communication circuit **120** of FIG. 1) for communicating with the blockchain network, a memory (e.g., the memory **110** of FIG. 1) for storing a partial ledger (e.g., the partial ledger **220** of FIG. 2) including a part of a full ledger of the blockchain network and at least one processor (e.g., the processor **130** of FIG. 1) electrically connected with the communication circuit and the memory, and the at least one processor may generate an encryption key corresponding to a transaction in response to obtaining a transaction generation request,

transmit information of the encryption key to at least one blockchain node related to the transaction, encrypt first data stored in the partial ledger among input data required to execute a first smart contract of the transaction based on the encryption key, upload the first data to a data server included in the blockchain network, download second data encrypted based on the encryption key from the data server, the second data being data not stored in the partial ledger among the input data, decrypt the second data based on the encryption key, and execute the first smart contract based on the first data and the decrypted second data.

(169) According to an embodiment, the at least one processor may generate first output data by executing the first smart contract, transmit an endorsement request including the transaction to a second blockchain node related to the transaction, obtain endorsement data including second output data generated from the second blockchain node based on the endorsement request from the second blockchain node, and endorse the transaction based on the first output data and the second output data.

(170) According to an embodiment, the second output data may be generated at the second blockchain node by executing a second smart contract of the transaction stored in the second blockchain node.

(171) According to an embodiment, the encrypted second data may include data stored in the second blockchain node among the input data and encrypted by the second blockchain node based on information of the encryption key.

(172) According to an embodiment, the at least one processor may generate transaction data based on the input data and the first output data as the endorsement of the transaction is finished, request a third blockchain node included in the blockchain network to generate a block including the transaction data, receive an update request including the generated block based on the request from the third blockchain node, and store the partial ledger based on the block and the first output data in response to the update request.

(173) According to an embodiment, the at least one processor may request the data server to generate a partial ledger of the transaction in response to the transaction generation request, and request the data server to delete the shared ledger included in the data server as the endorsement of the transaction is finished, and the shared ledger may include a database which stores the first data and the second data encrypted based on the encryption key.

(174) According to an embodiment, the at least one processor may shred the encryption key in response to finishing the transaction endorsement.

(175) According to an embodiment, the partial ledger may include at least one block corresponding to at least one transaction of which consensus is participated by the electronic device and state data related to the at least one transaction.

(176) According to an embodiment, the at least one processor may obtain from the data server a notification indicating that at least part of the second data is uploaded, and download at least part of the second data uploaded to the data server in response to the notification.

(177) According to an embodiment, the at least one processor may identify the second data not stored in the partial ledger among the input data in response to generating the encryption key, and request the second data not stored in the partial ledger among the input data from the data server.

(178) According to an embodiment, the at least one processor may identify the at least one blockchain node based on node information of blockchain nodes included in the blockchain network stored in the memory or node information obtained from a fourth blockchain node which manages the node information included in the blockchain network.

(179) As set forth above, an operating method of an electronic device (e.g., the electronic device **100** of FIG. 1) constituting a first blockchain node included in a blockchain network may include generating an encryption key corresponding to a transaction in response to obtaining a transaction generation request, transmitting information of the encryption key to at least one blockchain node related to the transaction, encrypting first data which is data stored in a partial ledger including part

of a full ledger of the blockchain network among input data required to execute a first smart contract of the transaction based on the encryption key, uploading the encrypted first data to a data server included in the blockchain network, downloading second data encrypted based on the encryption key from the data server, the second data being data not stored in the partial ledger among the input data, decrypting the second data based on the encryption key, and executing the first smart contract based on the first data and the decrypted second data.

(180) According to an embodiment, the operating method of the electronic device may further include generating first output data by executing the first smart contract, transmitting an endorsement request including the transaction to a second blockchain node related to the transaction, obtaining endorsement data including second output data generated from the second blockchain node based on the endorsement request from the second blockchain node, and endorsing the transaction based on the first output data and the second output data.

(181) According to an embodiment, the operating method may further include requesting the data server to generate a shared ledger of the transaction in response to the transaction generation request, and requesting the data server to delete the shared ledger included in the data server as the endorsement of the transaction is finished, and the shared ledger may store the first data and the second data encrypted based on the encryption key.

(182) According to an embodiment, endorsing may include shredding the encryption key.

(183) According to an embodiment, downloading the second data may include obtaining from the data server a notification indicating that at least part of the second data is uploaded and downloading at least part of the second data uploaded to the data server in response to the notification.

(184) According to an embodiment, transmitting the information of the encryption key may include identifying the at least one blockchain node based on node information of blockchain nodes included in the blockchain network stored in the electronic device or node information obtained from a blockchain node which manages the node information included in the blockchain network, and transmitting the encryption key information to the at least one blockchain node identified, and the encryption key information may include at least one of a seed value for deriving the encryption key or the encryption key.

(185) As set forth above, an electronic device (e.g., the electronic device **100** of FIG. **1**) constituting a first blockchain node included in a blockchain network may include a communication circuit (e.g., the communication circuit **120** of FIG. **1**) for communicating with the blockchain network, a memory (e.g., the memory **110** of FIG. **1**) for storing a partial ledger (e.g., the partial ledger **220** of FIG. **2**) including a part of a full ledger of the blockchain network and at least one processor (e.g., the processor **130** of FIG. **1**) electrically connected with the communication circuit and the memory, and the at least one processor may generate an encryption key corresponding to a transaction in response to obtaining a transaction generation request and transmitting information of the encryption key to at least one blockchain node related to the transaction, encrypt first data which is data stored in the partial ledger among input data required to execute a smart contract of the transaction based on the encryption key, upload the encrypted first data to a data server of the blockchain network, the data server storing the shared ledger, transmit an endorsement request of the transaction to the at least one blockchain node, in response to the endorsement request, obtain at least one endorsement data including output data generated by executing a smart contract of the transaction stored in the at least one blockchain node based on at least a part of the shared ledger stored in the data server, and endorse the transaction based on the output data generated from the at least one blockchain node and output data generated by executing a first smart contract of the transaction stored in the memory.

(186) According to an embodiment, the at least one processor may download second data encrypted based on the encryption key from the data server, the second data being data not stored in the partial ledger among the input data, decrypt the second data based on the encryption key, and

execute the first smart contract based on the first data and the decrypted second data.

(187) According to an embodiment, the at least one processor may generate transaction data based on the input data and the output data generated by executing the first smart contract as the endorsement of the transaction is finished, request a block generation node included in the blockchain network to generate a block including the transaction data, receive an update request including the block generated in response to the request from the block generation node, and in response to the update request, update the partial ledger based on the block and the transaction data.

(188) FIG. 9 is a block diagram illustrating an electronic device **901** in a network environment **900**, according to various embodiments. Referring to FIG. 9, the electronic device **901** in the network environment **900** may communicate with an electronic device **902** via a first network **998** (e.g., a short-range wireless communication network), or at least one of an electronic device **904** or a server **908** via a second network **999** (e.g., a long-range wireless communication network).

According to an embodiment, the electronic device **901** may communicate with the electronic device **904** via the server **908**. According to an embodiment, the electronic device **901** may include a processor **920**, memory **930**, an input module **950**, a sound output module **955**, a display module **960**, an audio module **970**, a sensor module **976**, an interface **977**, a connecting terminal **978**, a haptic module **979**, a camera module **980**, a power management module **988**, a battery **989**, a communication module **990**, a subscriber identification module (SIM) **996**, or an antenna module **997**. In some embodiments, at least one of the components (e.g., the connecting terminal **978**) may be omitted from the electronic device **901**, or one or more other components may be added in the electronic device **901**. In some embodiments, some of the components (e.g., the sensor module **976**, the camera module **980**, or the antenna module **997**) may be implemented as a single component (e.g., the display module **960**).

(189) The processor **920** may execute, for example, software (e.g., a program **940**) to control at least one other component (e.g., a hardware or software component) of the electronic device **901** coupled with the processor **920**, and may perform various data processing or computation.

According to one embodiment, as at least part of the data processing or computation, the processor **920** may store a command or data received from another component (e.g., the sensor module **976** or the communication module **990**) in volatile memory **932**, process the command or the data stored in the volatile memory **932**, and store resulting data in non-volatile memory **934**. According to an embodiment, the processor **920** may include a main processor **921** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **923** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **921**. For example, when the electronic device **901** includes the main processor **921** and the auxiliary processor **923**, the auxiliary processor **923** may be adapted to consume less power than the main processor **921**, or to be specific to a specified function. The auxiliary processor **923** may be implemented as separate from, or as part of the main processor **921**.

(190) The auxiliary processor **923** may control at least some of functions or states related to at least one component (e.g., the display module **960**, the sensor module **976**, or the communication module **990**) among the components of the electronic device **901**, instead of the main processor **921** while the main processor **921** is in an inactive (e.g., sleep) state, or together with the main processor **921** while the main processor **921** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **923** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **980** or the communication module **990**) functionally related to the auxiliary processor **923**. According to an embodiment, the auxiliary processor **923** (e.g., the neural processing unit) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g.,

by the electronic device **901** where the artificial intelligence is performed or via a separate server (e.g., the server **908**). Learning algorithms may include, but are not limited to, e.g., supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

(191) The memory **930** may store various data used by at least one component (e.g., the processor **920** or the sensor module **976**) of the electronic device **901**. The various data may include, for example, software (e.g., the program **940**) and input data or output data for a command related thereto. The memory **930** may include the volatile memory **932** or the non-volatile memory **934**.

(192) The program **940** may be stored in the memory **930** as software, and may include, for example, an operating system (OS) **942**, middleware **944**, or an application **946**.

(193) The input module **950** may receive a command or data to be used by another component (e.g., the processor **920**) of the electronic device **901**, from the outside (e.g., a user) of the electronic device **901**. The input module **950** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

(194) The sound output module **955** may output sound signals to the outside of the electronic device **901**. The sound output module **955** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.

(195) The display module **960** may visually provide information to the outside (e.g., a user) of the electronic device **901**. The display module **960** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display module **960** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.

(196) The audio module **970** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **970** may obtain the sound via the input module **950**, or output the sound via the sound output module **955** or a headphone of an external electronic device (e.g., an electronic device **902**) directly (e.g., wired) or wirelessly coupled with the electronic device **901**.

(197) The sensor module **976** may detect an operational state (e.g., power or temperature) of the electronic device **901** or an environmental state (e.g., a state of a user) external to the electronic device **901**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **976** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(198) The interface **977** may support one or more specified protocols to be used for the electronic device **901** to be coupled with the external electronic device (e.g., the electronic device **902**) directly (e.g., wired) or wirelessly. According to an embodiment, the interface **977** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(199) A connecting terminal **978** may include a connector via which the electronic device **901** may be physically connected with the external electronic device (e.g., the electronic device **902**). According to an embodiment, the connecting terminal **978** may include, for example, a HDMI

connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone connector).

(200) The haptic module **979** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **979** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(201) The camera module **980** may capture a still image or moving images. According to an embodiment, the camera module **980** may include one or more lenses, image sensors, image signal processors, or flashes.

(202) The power management module **988** may manage power supplied to the electronic device **901**. According to one embodiment, the power management module **988** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

(203) The battery **989** may supply power to at least one component of the electronic device **901**. According to an embodiment, the battery **989** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(204) The communication module **990** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **901** and the external electronic device (e.g., the electronic device **902**, the electronic device **904**, or the server **908**) and performing communication via the established communication channel. The communication module **990** may include one or more communication processors that are operable independently from the processor **920** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **990** may include a wireless communication module **992** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **994** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **998** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **999** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **992** may identify and authenticate the electronic device **901** in a communication network, such as the first network **998** or the second network **999**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **996**.

(205) The wireless communication module **992** may support a 5G network, after a 4G network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **992** may support a high-frequency band (e.g., the mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **992** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **992** may support various requirements specified in the electronic device **901**, an external electronic device (e.g., the electronic device **904**), or a network system (e.g., the second network **999**). According to an embodiment, the wireless communication module **992** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164

dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1 ms or less) for implementing URLLC.

(206) The antenna module **997** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **901**. According to an embodiment, the antenna module **997** may include an antenna including a radiating element composed of a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment, the antenna module **997** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **998** or the second network **999**, may be selected, for example, by the communication module **990** (e.g., the wireless communication module **992**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **990** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **997**.

(207) According to various embodiments, the antenna module **997** may form a mmWave antenna module. According to an embodiment, the mmWave antenna module may include a printed circuit board, a RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(208) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(209) According to an embodiment, commands or data may be transmitted or received between the electronic device **901** and the external electronic device **904** via the server **908** coupled with the second network **999**. Each of the electronic devices **902** or **904** may be a device of a same type as, or a different type, from the electronic device **901**. According to an embodiment, all or some of operations to be executed at the electronic device **901** may be executed at one or more of the external electronic devices **902**, **904**, or **908**. For example, if the electronic device **901** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **901**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **901**. The electronic device **901** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **901** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In another embodiment, the external electronic device **904** may include an internet-of-things (IoT) device. The server **908** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **904** or the server **908** may be included in the second network **999**. The electronic device **901** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(210) The electronic device according to various embodiments may be one of various types of electronic devices. The electronic devices may include, for example, a portable communication

device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance. According to an embodiment of the disclosure, the electronic devices are not limited to those described above.

(211) It should be appreciated that various embodiments of the present disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., wired), wirelessly, or via a third element.

(212) As used in connection with various embodiments of the disclosure, the term “module” may include a unit implemented in hardware, software, or firmware, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(213) Various embodiments as set forth herein may be implemented as software (e.g., the program **940**) including one or more instructions that are stored in a storage medium (e.g., internal memory **936** or external memory **938**) that is readable by a machine (e.g., the electronic device **901**). For example, a processor (e.g., the processor **920**) of the machine (e.g., the electronic device **901**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it, with or without using one or more other components under the control of the processor. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Wherein, the term “non-transitory” simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(214) According to an embodiment, a method according to various embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., compact disc read only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of the application store, or a relay server.

(215) According to various embodiments, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the multiple entities may be separately disposed in different components. According to various

embodiments, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to various embodiments, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to various embodiments, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

Claims

1. An electronic device constituting a first blockchain node included in a blockchain network, the electronic device comprising: a communication circuit configured to communicate with at least one other device in the blockchain network; at least one processor; and a memory storing a partial ledger including a part of a full ledger of the blockchain network, and instructions that, when executed by the at least one processor individually or collectively, cause the electronic device to: generate an encryption key corresponding to a transaction based on obtaining a transaction generation request, transmit information of the encryption key to at least one blockchain node related to the transaction, encrypt first data stored in the partial ledger among input data required to execute a first smart contract of the transaction based on the encryption key, upload the encrypted first data to a data server included in the blockchain network, download encrypted second data that is encrypted based on the encryption key, from the data server, wherein the second data is not stored in the partial ledger among the input data, decrypt the encrypted second data based on the encryption key, and execute the first smart contract based on the first data and the second data.
2. The electronic device of claim 1, wherein the instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to: generate first output data by executing the first smart contract, transmit an endorsement request including the transaction to a second blockchain node related to the transaction, obtain endorsement data from the second blockchain node, the endorsement data including second output data generated by the second blockchain node based on the endorsement request, and endorse the transaction based on the first output data and the second output data.
3. The electronic device of claim 2, wherein the second output data includes data that the second blockchain node generates by executing a second smart contract of the transaction stored in the second blockchain node.
4. The electronic device of claim 2, wherein the second data includes data stored in the second blockchain node among the input data, and the second data is encrypted by the second blockchain node based on information of the encryption key.
5. The electronic device of claim 2, wherein the instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to: generate transaction data based on the input data and the first output data, request a third blockchain node included in the blockchain network to generate a block including the transaction data, receive an update request including the generated block, from the third blockchain node, and store the partial ledger based on the block, and the first output data, based on the update request.
6. The electronic device of claim 2, wherein the instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to: request the data server to generate a partial ledger of the transaction based on the transaction generation request, and request the data server to delete a shared ledger included in the data server based on completing the endorsement of the transaction, wherein the shared ledger includes the encrypted first data and the encrypted second data, that are encrypted based on the encryption key.

7. The electronic device of claim 2, wherein the instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to: shred the encryption key based on finishing the transaction endorsement.

8. The electronic device of claim 1, wherein the partial ledger includes at least one block corresponding to at least one transaction and state data related to the at least one transaction, and wherein the electronic device participates in a consensus operation for the at least one transaction.

9. The electronic device of claim 1, wherein the instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to: obtain a notification from the data server, the notification indicating that at least part of the second data is uploaded to the data server; and download at least part of the second data from the data server, based on the notification.

10. The electronic device of claim 1, wherein the instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to: identify the second data not stored in the partial ledger among the input data based on generating the encryption key, and request the second data not stored in the partial ledger among the input data from the data server.

11. The electronic device of claim 1, wherein the instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to: identify the at least one blockchain node based on node information of blockchain nodes included in the blockchain network stored in the memory, or node information obtained from a fourth blockchain node that manages the node information included in the blockchain network.

12. A method for operating an electronic device constituting a first blockchain node included in a blockchain network, the method comprising: generating an encryption key corresponding to a transaction based on obtaining a transaction generation request; transmitting information of the encryption key to at least one blockchain node related to the transaction; encrypting first data based on the encryption key, wherein the first data is stored in a partial ledger including part of a full ledger of the blockchain network, among input data required to execute a first smart contract of the transaction; uploading the encrypted first data to a data server included in the blockchain network; downloading encrypted second data that is encrypted based on the encryption key, from the data server, wherein the second data is not stored in the partial ledger among the input data; decrypting the encrypted second data based on the encryption key; and executing the first smart contract based on the first data and the second data.

13. The method of claim 12, further comprising: generating first output data by executing the first smart contract; transmitting an endorsement request including the transaction to a second blockchain node related to the transaction; obtaining endorsement data, from the second blockchain node, the endorsement data including second output data generated by the second blockchain node based on the endorsement request; and endorsing the transaction based on the first output data and the second output data.

14. The method of claim 13, further comprising: requesting the data server to generate a shared ledger of the transaction based on the transaction generation request; and requesting the data server to delete the shared ledger based on completing the endorsement of the transaction, wherein the shared ledger stores the encrypted first data and the encrypted second data, that are encrypted based on the encryption key.

15. The method of claim 13, wherein endorsing the transaction comprises: shredding the encryption key.

16. The method of claim 12, wherein downloading the second data comprises: obtaining a notification, from the data server, the notification indicating that at least part of the second data is uploaded to the data server; and downloading at least part of the second data based on the notification.

17. The method of claim 12, wherein transmitting the information of the encryption key comprises:

identifying the at least one blockchain node based on node information of blockchain nodes included in the blockchain network stored in the electronic device, or node information obtained from a blockchain node that manages the node information included in the blockchain network; and transmitting the encryption key information to the identified at least one blockchain node, wherein the encryption key information includes at least one of a seed value for deriving the encryption key, or the encryption key.

18. An electronic device constituting a first blockchain node included in a blockchain network, comprising: a communication circuit configured to communicate with at least one other device in the blockchain network; at least one processor; and a memory storing a partial ledger including a part of a full ledger of the blockchain network, and instructions that, when executed by the at least one processor individually or collectively, cause the electronic device to: generate an encryption key corresponding to a transaction based on obtaining a transaction generation request, transmit information of the encryption key to at least one blockchain node related to the transaction, encrypt, based on the encryption key, first data stored in the partial ledger among input data required to execute a first smart contract of the transaction, upload the encrypted first data to a data server of the blockchain network, the data server including a shared ledger, transmit an endorsement request of the transaction to the at least one blockchain node, obtain at least one endorsement data, based on the endorsement request, wherein the at least one endorsement data includes data generated by executing a smart contract of the transaction stored in the at least one blockchain node, wherein the smart contract is executed based on at least part of the shared ledger, and endorse the transaction based on the at least one endorsement data and output data generated by executing the first smart contract of the transaction stored in the memory.

19. The electronic device of claim 18, wherein the instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to: download encrypted second data that is encrypted based on the encryption key, from the data server, wherein the second data is not stored in the partial ledger among the input data; decrypt the encrypted second data based on the encryption key, and execute the first smart contract based on the first data and the second data.

20. The electronic device of claim 18, wherein the instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to: generate transaction data based on the input data and the output data generated by executing the first smart contract, request a block generation node included in the blockchain network to generate a block including the transaction data, receive an update request including the generated block from the block generation node, and update the partial ledger based on the generated block and the transaction data.
