

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12418730
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Mitsuma; Nobutaka

Image capture and desired timing image reconstruction device, system, method, and non-transitory computer readable medium

Abstract

An information processing device (10) includes an acquisition unit (121), a recognition unit (122), and an output unit (125). The acquisition unit (121) acquires information in which event data and detection time of the event data are associated with each other, the event data being data output from a first sensor (220) including a pixel array unit (300), which has a plurality of pixels arranged in a two-dimensional lattice pattern, each of the pixels configured to detect a luminance change in incident light and output event data. The recognition unit (122) recognizes the object detected by the first sensor (220) by using a trained model using information related to the detection time and the event data as an input. The output unit (125) outputs an image related to the recognized object.

Inventors:	Mitsuma; Nobutaka (Kanagawa, JP)
Applicant:	Sony Semiconductor Solutions Corporation (Kanagawa, JP)
Family ID:	1000008820044
Assignee:	Sony Semiconductor Solutions Corporation (Kanagawa, JP)
Appl. No.:	18/256142
Filed (or PCT Filed):	December 27, 2021
PCT No.:	PCT/JP2021/048479
PCT Pub. No.:	WO2022/153854
PCT Pub. Date:	July 21, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240040271 A1	Feb. 01, 2024

Foreign Application Priority Data

JP 2021-003238 Jan. 13, 2021

Publication Classification

Int. Cl.: H04N23/951 (20230101); H04N23/61 (20230101); H04N23/63 (20230101); H04N25/47 (20230101)

U.S. Cl.:

CPC H04N23/951 (20230101); H04N23/61 (20230101); H04N23/633 (20230101); H04N25/47 (20230101);

Field of Classification Search

CPC: H04N (23/951); H04N (23/61); H04N (23/633); H04N (25/47); A63B (71/06); G03B (15/00)

USPC: 348/222.1

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2004/0199064	12/2003	Van Liere	600/407	G06T 11/005
2010/0077421	12/2009	Cohen	348/370	G07C 9/37
2022/0161654	12/2021	Nakagawa	N/A	A61B 5/1128
2022/0270216	12/2021	Wang	N/A	G06T 5/80

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2017530467	12/2016	JP	N/A
2020162000	12/2019	JP	N/A
2020162016	12/2019	JP	N/A

OTHER PUBLICATIONS

International Search Report (PCT/ISA/210), International Application No. PCT/JP2021/048479, dated Feb. 1, 2022. cited by applicant

Primary Examiner: Khan; Usman A

Attorney, Agent or Firm: Michael Best & Friedrich LLP

Background/Summary

FIELD

(1) The present disclosure relates to an information processing device, an information processing

system, an information processing method, and a program.

BACKGROUND

(2) There has been proposed an asynchronous solid-state imaging element that performs real-time detection of a luminance change for each pixel as an event in a solid-state imaging device using a complementary metal oxide semiconductor (CMOS) or the like. The solid-state imaging element that detects an event for each pixel like this is also referred to as an event-based vision sensor (EVS).

(3) Furthermore, for example, Patent Literature 1 discloses a technique of generating a frame image based on an event detected by the EVS.

CITATION LIST

Patent Literature

(4) Patent Literature 1: JP 2017-530467 A

SUMMARY

Technical Problem

(5) There is a demand for a technology of clipping and presenting a specific moment from an image obtained by capturing an object moving at a high speed. For example, in sports such as tennis, a system of judging whether a ball landed inside or outside a line is required to capture an image at the moment when a ball moving at a high speed touches the ground.

(6) However, in the case of a frame image created at regular intervals, the frame image does not necessarily include a desired moment. Therefore, it is desirable to present an image of the object at a desired timing to the user.

(7) In view of this, the present disclosure provides a mechanism capable of presenting an image of an object at a desired timing to a user.

(8) Note that the above problem or target is merely one of a plurality of problems or targets that can be solved or achieved by a plurality of embodiments disclosed in the present specification.

Solution to Problem

(9) According to the present disclosure, an information processing apparatus is provided. The information processing device includes an acquisition unit, a recognition unit, and an output unit. The acquisition unit acquires information in which event data and detection time of the event data are associated with each other, the event data being data output from a first sensor including a pixel array unit, which has a plurality of pixels arranged in a two-dimensional lattice pattern, each of the pixels configured to detect a luminance change in incident light and output event data. The recognition unit recognizes the object detected by the first sensor by using a trained model using information related to the detection time and the event data as an input. The output unit outputs an image related to the recognized object.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a diagram illustrating an overview of information processing according to an embodiment of the present disclosure.

(2) FIG. 2 is a block diagram illustrating a configuration example of an information processing system according to the embodiment of the present disclosure.

(3) FIG. 3 is a diagram illustrating an arrangement example of a detection device according to the embodiment of the present disclosure.

(4) FIG. 4 is a block diagram illustrating a configuration example of the detection device according to the embodiment of the present disclosure.

(5) FIG. 5 is a block diagram illustrating a functional configuration example of the EVS according to the embodiment of the present disclosure.

- (6) FIG. 6 is a circuit diagram illustrating a schematic configuration example of a unit pixel according to the embodiment of the present disclosure.
- (7) FIG. 7 is a block diagram illustrating a schematic configuration example of an address event detection unit according to the embodiment of the present disclosure.
- (8) FIG. 8 is a circuit diagram illustrating another example of a current-voltage conversion unit according to the embodiment of the present disclosure.
- (9) FIG. 9 is a circuit diagram illustrating a schematic configuration example of a subtractor and a quantizer according to the embodiment of the present disclosure.
- (10) FIG. 10 is a block diagram illustrating a configuration example of a control device according to the embodiment of the present disclosure.
- (11) FIG. 11 is a diagram illustrating an example of event detection data acquired by an acquisition unit according to the embodiment of the present disclosure.
- (12) FIG. 12 is a diagram illustrating an example of image data acquired by an acquisition unit according to the embodiment of the present disclosure.
- (13) FIG. 13 is a diagram illustrating an example of image data generated by a recognition unit according to the embodiment of the present disclosure.
- (14) FIG. 14 is a diagram illustrating a recognition result obtained by the recognition unit according to the embodiment of the present disclosure.
- (15) FIG. 15 is a diagram illustrating detection of a generation timing performed by a detection unit according to the embodiment of the present disclosure.
- (16) FIG. 16 is a flowchart illustrating an example of a flow of setting processing executed by the information processing system according to the embodiment of the present disclosure.
- (17) FIG. 17 is a flowchart illustrating an example of a flow of imaging processing executed by the information processing system according to the embodiment of the present disclosure.
- (18) FIG. 18 is a flowchart illustrating an example of a flow of generation processing executed by the information processing system according to the embodiment of the present disclosure.
- (19) FIG. 19 is a diagram for describing another application example of the information processing system according to the embodiment of the present disclosure.
- (20) FIG. 20 is a hardware configuration diagram illustrating an example of a computer that implements functions of a control device.

DESCRIPTION OF EMBODIMENTS

- (21) Hereinafter, embodiments of the present disclosure will be described in detail with reference to the accompanying drawings. Note that redundant descriptions will be omitted from the present specification and the drawings by assigning the same reference signs to components having substantially the same functional configuration.
- (22) Furthermore, in the present specification and the drawings, similar components in the embodiments may be distinguished by adding different alphabets after the same reference numerals. However, when there is no need to particularly distinguish similar components from each other, only the same reference numeral is assigned.
- (23) One or more embodiments (examples and modifications) described below can each be implemented independently. On the other hand, at least some of the plurality of embodiments described below may be appropriately combined with at least some of other embodiments. The plurality of embodiments may include novel features different from each other. Accordingly, the plurality of embodiments can contribute to achieving or solving different objects or problems, and can exhibit different effects.
- (24) Note that the description will be provided in the following order. 1. Introduction 1.1. Background 1.2. Proposed Technology 2. Information processing system 2.1. Configuration example of detection device 2.1.1. Configuration example of EVS 2.1.2. Configuration example of unit pixel 2.1.3. Configuration example of address event detection unit 2.1.4. Configuration example of current-voltage conversion unit 2.1.5. Configuration example of subtractor and

quantizer 2.2. Configuration example of control device 3. Information processing 3.1. Setting processing 3.2. Imaging processing 3.3. Generation processing 4. Other embodiments 5. Hardware configuration 6. Summary

1. Introduction

(25) <1.1. Background>

(26) Conventionally, a high-speed camera has been used to capture a video at a desired imaging timing (hereinafter, also referred to as a decisive moment) such as a hitting moment of a high-speed object. The high-speed camera can capture a video (frame) at a rate of one several hundredth to several thousandth of a second, for example. For example, by analyzing an image captured by the high-speed camera, the information processing device presents the image at the decisive moment to the user.

(27) Here is a case to be considered in which the above-described high-speed camera captures a video at a decisive moment such as a moment when the ball touches the ground in a sport in which the ball moves at a high speed, such as tennis.

(28) For example, in the case of tennis, the initial speed of a serve can exceed 240 km/h. In addition, the speed of the ball is close to 140 km/h (47.2 m/sec) even at a point where the ball touches the court. For example, when a ball is captured by a camera that performs imaging at 350 fps, the ball moves 135 mm between the frames. Even when the camera images the ball at 2500 fps, the ball moves 18.9 mm between the frames.

(29) Therefore, when an object (for example, a ball) moving at a high speed is imaged by a camera with a low frame rate, there is a high possibility that a decisive moment (for example, a moment when the ball touches the ground) occurs between the frames. In this case, there is a high possibility that the camera with a low frame rate cannot capture an image at the decisive moment.

(30) On the other hand, increasing the frame rate increases the possibility that the camera captures an image at the decisive moment. However, increasing the frame rate would increase the number of captured images, leading to a dramatically increase in data volume. This would cause problems such as an increase in cost of a storage that stores captured images and an increase in processing load of analyzing the captured images.

(31) In a system used for video judgment in a tennis challenge system, ten or more 350 fps cameras are combined to track the trajectory of a ball, reconstructs a moment at which the ball touches the ground by computer graphics (CG) and presents the reconstructed image to a user. Alternatively, a system that presents an actual captured image to a user by using 40 or more 2500 fps cameras is also known. In such a system, the actual captured image is presented to the user to make the video judgment more convincing.

(32) Meanwhile, an EVS is known to perform real-time detection of a luminance change for each pixel as an event. The EVS captures a change in luminance in units of 1 μ Sec at maximum. The EVS is an asynchronous solid-state imaging element, and has no concept of a frame used in a synchronous solid-state imaging element. However, even in a case where the rate is converted into a frame, the EVS can detect an object with time resolution higher than that of a general high-speed camera. In addition, since the EVS detects the luminance change, the data volume of the event data can be suppressed. Moreover, it is possible to suppress an increase in the cost of storage that stores event data and an increase in the processing load for analyzing the event data.

(33) However, the event data output from the EVS is data indicating a luminance change, and thus, needs to be converted into an image that can be recognized by the user.

(34) To handle this, the proposed technology of the present disclosure provides a mechanism of presenting a video of a decisive moment to the user using event data output from the EVS.

(35) <1.2. Proposed Technology>

(36) FIG. 1 is a diagram illustrating an overview of information processing according to an embodiment of the present disclosure. Information processing according to the technology of the present disclosure is executed by an information processing system 1. The information processing

system **1** includes a control device **10** and a detection device **20**.

(37) Although the following will describe a case where the information processing system **1** is a system that presents the timing at which a tennis ball touched the ground to the user, the video to be presented by the information processing system **1** is not limited thereto.

(38) The detection device **20** includes an EVS (an example of a first sensor) that performs real-time detection of a luminance change for each pixel as an event, and outputs the detected event data and the detection time to the control device **10** in association with each other.

(39) The control device **10** is an information processing device that controls the detection device **20** and presents a video at a desired timing to the user based on the event data acquired from the detection device **20**.

(40) The control device **10** acquires event data from the detection device **20** (Step S1). As illustrated in FIG. **1**, the event data includes data indicating that the luminance change exceeds a predetermined threshold (positive event) and data indicating that the luminance change falls below the predetermined threshold (negative event).

(41) In this manner, the event data output by the detection device **20** is data indicating the luminance change of each pixel, and is displayed as a simple point group when displayed as an image, making it difficult for the user to recognize the object in some cases.

(42) To handle this, the control device **10** according to the embodiment of the present disclosure recognizes an object (subject) detected by the detection device **20** using machine learning using event data and a detection time as an input (Step S2). In an example of FIG. **1**, the control device **10** recognizes that the subject is a ball and detects the position of the ball on the screen. For example, the control device **10** may detect a motion vector of the ball together with the position of the ball.

(43) Next, based on the recognition result, the control device **10** detects a generation timing of an image to be presented to the user (Step S3). Here, the control device **10** detects, as the generation timing, a timing at which a ball being a subject touched the ground. Details of detection of the generation timing will be described below.

(44) The control device **10** generates an image at the detected generation timing (Step S4). The control device **10** generates, for example, an output image including a ball that touched the ground and a line drawn on the ground. The control device **10** can generate an output image by combining a ball image with a background image captured by an image sensor (not illustrated). Furthermore, the control device **10** may generate a moving image of a constant period including the generation timing, as the output image.

(45) The control device **10** outputs the generated image to a display device (not illustrated) (Step S5). With this operation, the control device **10** presents the video at a desired timing to the user.

(46) As described above, the information processing system **1** according to the embodiment of the present disclosure detects information related to the subject based on the data output by the EVS. The information processing system **1** generates and outputs a video at a desired timing based on information regarding the detected subject.

(47) Since the EVS has no concept of frames, the information processing system **1** can generate an image based on event data at any timing. This makes it possible for the information processing system **1** to present a video at a desired timing to the user.

(48) In addition, the small data volume generated by the EVS leads to saving of the storage, making it possible to suppress an increase in the processing load of data analysis performed by the control device **10**. This makes it possible for the control device **10** to generate an image in a shorter time and present the generated image to the user.

(49) Furthermore, the control device **10** generates the output image based on the output data of the EVS, making it possible for the information processing system **1** to present an image having a higher visibility for the user.

2. Information Processing System

(50) FIG. 2 is a block diagram illustrating a configuration example of the information processing system **1** according to the embodiment of the present disclosure. The information processing system **1** illustrated in FIG. 2 includes a control device **10** and a plurality of detection devices **20A**, **20B**, The control device **10** and the plurality of detection devices **20** are connected to each other via a network **30**.

(51) <2.1. Configuration Example of Detection Device>

(52) The detection device **20** includes a plurality of sensors that detect a subject. The detection device **20** is disposed on a tennis court in order to capture a timing at which a tennis ball touches the ground, for example.

(53) FIG. 3 is a diagram illustrating an arrangement example of the detection device **20** according to the embodiment of the present disclosure. As illustrated in FIG. 3, the plurality of detection devices **20** is arranged along lines of a tennis court so as to image the lines. At this time, the plurality of (two in FIG. 3) detection devices **20** having different imaging directions are arranged for one line. With this arrangement, even when the ball is hidden by a player or the like from one detection device **20**, for example, the ball can be imaged by the other detection device **20**. By arranging the plurality of detection devices **20** for one line in this manner, the detection device **20** can detect the ball with higher reliability.

(54) FIG. 4 is a block diagram illustrating a configuration example of the detection device **20** according to the embodiment of the present disclosure. As illustrated in FIG. 4, the detection device **20** includes an imaging lens **210**, an EVS **220**, an imaging lens **230**, an image sensor **240**, a control unit **250**, a storage unit **260**, and an I/F unit **270**, for example.

(55) (Imaging Lens **210**)

(56) The imaging lens **210** is an example of an optical system that collects incident light and forms an optical image based on the light on a light receiving surface of the EVS **220**. The light receiving surface may be a surface on which photoelectric conversion elements are arranged in the EVS **220**.

(57) (EVS **220**)

(58) The EVS **220** is the first sensor that detects an object (subject) present in a detection range of the detection device **20**. The EVS **220** is an asynchronous image sensor in which a detection circuit is provided for each pixel. The detection circuit is configured to performs real-time detection of an event that the light reception amount exceeds a threshold as an address event.

(59) A typical EVS adopts a driving system referred to as event-driven driving system. In this system, the presence or absence of occurrence of an address event is detected for each unit pixel, and when the occurrence of the address event has been detected, a pixel signal is read from the unit pixel in which the address event has occurred.

(60) Furthermore, a typical EVS executes a read operation for the unit pixel in which the occurrence of the address event is detected. Accordingly, the EVS is characterized by the capability of performing reading at a much higher speed than that in a synchronous image sensor in which the read operation is executed for all the unit pixels, and characterized by the small volume of data to be read.

(61) Note that a unit pixel in the present description is a minimum unit of a pixel including one photoelectric conversion element (also referred to as a light receiving element), and corresponds to each dot in image data read from an image sensor, for example. Furthermore, an address event is an event that occurs for each address assigned to each of the plurality of unit pixels arranged in a two-dimensional lattice pattern, and corresponds to an event that a value of a current (hereinafter, referred to as photocurrent) based on a charge generated in the photoelectric conversion element or a change amount thereof exceeds a certain threshold.

(62) In the present embodiment, the EVS **220** detects an occurrence of an address event based on the amount of incident light, and generates, as event data, address information for specifying the unit pixel in which the occurrence of the address event has been detected. The event data is output in association with time information such as a time stamp indicating the timing at which the

occurrence of the address event is detected. The combination of the event data and the time information is also referred to as event detection data. The generated event detection data is input to the control unit **250**.

(63) (Imaging Lens **230**)

(64) Similarly to the imaging lens **210**, the imaging lens **230** is an example of an optical system that collects incident light and forms an image of the condensed light on a light receiving surface of the image sensor **240**. The light receiving surface may be a surface on which the photoelectric conversion elements in the image sensor **240** are arranged.

(65) (Image Sensor **240**)

(66) The image sensor **240** may be, for example, various image sensors capable of acquiring image data, such as a charge coupled device (CCD) image sensor or a complementary metal-oxide-semiconductor (CMOS) image sensor. The image data acquired by the image sensor **240** is individually input to the control unit **250**.

(67) Note that the EVS **220** and the image sensor **240** may be arranged close to each other in the same direction so as to capture substantially the same angle of view, for example.

(68) (Control Unit **250**)

(69) The control unit **250** controls individual portions of the detection device **20**. The control unit **250** controls the EVS **220** to acquire event data. The control unit **250** stores the acquired event data in the storage unit **260**.

(70) The control unit **250** controls the image sensor **240** to acquire image data. The control unit **250** stores the acquired image data in the storage unit **260**.

(71) (Storage Unit **260**)

(72) The storage unit **260** is storage that stores event data output from the EVS **220** and image data output from the image sensor **240**. The storage unit **260** may be an external device of the detection device **20**.

(73) (I/F Unit **270**)

(74) The I/F unit **270** is, for example, an interface for transmitting and receiving data to and from an external device via the network **30** (refer to FIG. 2).

(75) <2.1.1. Configuration Example of EVS>

(76) Next, a configuration example of the EVS **220** will be described in detail with reference to the drawings. FIG. 5 is a block diagram illustrating a functional configuration example of the EVS **220** according to the embodiment of the present disclosure. As illustrated in FIG. 5, the EVS **220** includes a drive circuit **211**, a signal processing unit **212**, an arbiter **213**, and a pixel array unit **300**.

(77) The pixel array unit **300** includes a plurality of unit pixels arranged in a two-dimensional lattice pattern. As will be described in detail below, the unit pixel includes, for example: a photoelectric conversion element such as a photodiode; and a pixel circuit (in the present embodiment, the pixel circuit corresponds to an address event detection unit **400** described below) that detects the presence or absence of occurrence of an address event based on whether a current value of a photocurrent due to a charge generated in the photoelectric conversion element or a change amount thereof exceeds a predetermined threshold. Here, the pixel circuit can be shared by a plurality of photoelectric conversion elements. In that case, each unit pixel includes one photoelectric conversion element and a shared pixel circuit.

(78) The plurality of unit pixels of the pixel array unit **300** may be grouped into a plurality of pixel blocks each including a predetermined number of unit pixels. Hereinafter, a set of unit pixels or pixel blocks arranged in the horizontal direction is referred to as a “row”, and a set of unit pixels or pixel blocks arranged in a direction perpendicular to the row is referred to as a “column”.

(79) When occurrence of an address event is detected in the pixel circuit, each unit pixel outputs, to the arbiter **213**, a request for reading a signal from the unit pixel.

(80) The arbiter **213** arbitrates a request from one or more unit pixels, and transmits a predetermined response to the unit pixel that has issued the request based on a result of the

arbitration. The unit pixel that has received this response outputs a detection signal indicating occurrence of an address event to the drive circuit **211** and the signal processing unit **212**.

(81) The drive circuit **211** sequentially drives the unit pixel that has output the detection signal, thereby allowing a signal corresponding to the amount of received light to be output from the unit pixel in which the occurrence of the address event has been detected to the signal processing unit **212**. The EVS **220** may have, for example, an analog-to-digital converter for converting a signal read from a photoelectric conversion element **333** to be described below into a signal of a digital value according to the charge amount, provided for each of one or a plurality of unit pixels or columns.

(82) The signal processing unit **212** performs predetermined signal processing on the signal input from the unit pixel, and supplies a result of the signal processing to the control unit **250** via the signal line **209** as event detection data. The event detection data can include the address information of the unit pixel in which the occurrence of the address event has been detected as described above, and time information (detection time information) such as a time stamp indicating an address event occurrence timing.

(83) <2.1.2. Configuration Example of Unit Pixel>

(84) Next, a configuration example of an unit pixel **310** will be described. FIG. **6** is a circuit diagram illustrating a schematic configuration example of the unit pixel **310** according to the embodiment of the present disclosure. As illustrated in FIG. **6**, the unit pixel **310** includes, for example, a light receiving unit **330** and an address event detection unit **400**. Note that a logic circuit **221** in FIG. **6** may be, for example, a logic circuit constituting the control unit **250** in FIG. **4**.

(85) The light receiving unit **330** includes, for example, a photoelectric conversion element **333** such as a photodiode, and has its output connected to the address event detection unit **400**.

(86) The address event detection unit **400** includes, for example, a current-voltage conversion unit **410** and a subtractor **430**. However, the address event detection unit **400** further includes a buffer, a quantizer, and a transfer unit. Details of the address event detection unit **400** will be described below with reference to FIG. **7** and the like.

(87) In such a configuration, the photoelectric conversion element **333** of the light receiving unit **330** performs photoelectric conversion on the incident light to generate a charge. The charge generated in the photoelectric conversion element **333** is input to the address event detection unit **400** as a photocurrent of a current value corresponding to the charge amount.

(88) <2.1.3. Configuration Example of Address Event Detection Unit>

(89) FIG. **7** is a block diagram illustrating a schematic configuration example of the address event detection unit **400** according to the embodiment of the present disclosure. As illustrated in FIG. **7**, the address event detection unit **400** includes a buffer **420** and a transfer unit **450** in addition to the current-voltage conversion unit **410**, the subtractor **430**, and a quantizer **440** illustrated in FIG. **6** as well.

(90) The current-voltage conversion unit **410** converts the photocurrent from the light receiving unit **330** into a logarithmic voltage signal, and outputs the voltage signal generated by the conversion to the buffer **420**.

(91) The buffer **420** corrects the voltage signal from the current-voltage conversion unit **410** and outputs the corrected voltage signal to the subtractor **430**.

(92) The subtractor **430** lowers the voltage level of the voltage signal from the buffer **420** according to the row drive signal from the drive circuit **211**, and outputs the lowered voltage signal to the quantizer **440**.

(93) The quantizer **440** quantizes the voltage signal from the subtractor **430** into a digital signal, and outputs the digital signal generated by the quantization to the transfer unit **450** as a detection signal.

(94) The transfer unit **450** transfers the detection signal from the quantizer **440** to the signal processing unit **212** and the like. For example, when occurrence of an address event is detected, the

transfer unit **450** outputs, to the arbiter **213**, a request for transmission of a detection signal of the address event from the transfer unit **450** to the drive circuit **211** and the signal processing unit **212**. Having received a response to the request from the arbiter **213**, the transfer unit **450** outputs a detection signal to the drive circuit **211** and the signal processing unit **212**.

(95) <2.1.4. Configuration Example of Current-Voltage Conversion Unit>

(96) The current-voltage conversion unit **410** in the configuration illustrated in FIG. 7 may be, for example, a converter referred to as a source-follower current-voltage conversion unit including an LG transistor **411**, an amplification transistor **412**, and a constant current circuit **415** as illustrated in FIG. 6. However, the converter is not limited thereto, and for example, as illustrated in FIG. 8, it is also allowable to use a converter referred to as a gain boost current-voltage converter including two LG transistors **411** and **413**, two amplification transistors **412** and **414**, and a constant current circuit **415**. FIG. 8 is a circuit diagram illustrating another example of the current-voltage conversion unit **410** according to the embodiment of the present disclosure.

(97) As illustrated in FIG. 6, the source of the LG transistor **411** and the gate of the amplification transistor **412** are connected to the cathode of the photoelectric conversion element **333** of the light receiving unit **330**, for example. The drain of the LG transistor **411** is connected to a power supply terminal VDD, for example.

(98) Furthermore, for example, the amplification transistor **412** has its source grounded and has its drain connected to the power supply terminal VDD via the constant current circuit **415**. The constant current circuit **415** may include, for example, a load metal-oxide-semiconductor (MOS) transistor such as a P-type MOS transistor.

(99) In contrast, when using a gain boost type unit, as illustrated in FIG. 8, the source of the LG transistor **411** and the gate of the amplification transistor **412** are connected to the cathode of the photoelectric conversion element **333** of the light receiving unit **330**, for example. Furthermore, the drain of the LG transistor **411** is connected to the source of the LG transistor **413** and the gate of the amplification transistor **412**, for example. The drain of the LG transistor **413** is connected to the power supply terminal VDD, for example.

(100) Furthermore, for example, the source of the amplification transistor **414** is connected to the gate of the LG transistor **411** and the drain of the amplification transistor **412**. The drain of the amplification transistor **414** is connected to the power supply terminal VDD via the constant current circuit **415**, for example.

(101) The use of the connection relationship illustrated in FIG. 6 or 8 leads to a configuration of a loop-shaped source follower circuit. With this configuration, the photocurrent from the light receiving unit **330** is converted into a logarithmic voltage signal corresponding to the charge amount. Note that each of the LG transistors **411** and **413** and the amplification transistors **412** and **414** may include an NMOS transistor, for example.

(102) <2.1.5. Configuration Example of Subtractor and Quantizer>

(103) FIG. 9 is a circuit diagram illustrating a schematic configuration example of the subtractor **430** and the quantizer **440** according to the embodiment of the present disclosure. As illustrated in FIG. 9, the subtractor **430** includes capacitors **431** and **433**, an inverter **432**, and a switch **434**. Furthermore, the quantizer **440** includes a comparator **441**.

(104) The capacitor **431** has one end connected to an output terminal of the buffer **420** and the other end connected to an input terminal of the inverter **432**. The capacitor **433** is connected in parallel to the inverter **432**. The switch **434** opens and closes a path connecting both ends of the capacitor **433** according to the row drive signal.

(105) The inverter **432** inverts the voltage signal input through the capacitor **431**. The inverter **432** outputs the inverted signal to a non-inverting input terminal (+) of the comparator **441**.

(106) When the switch **434** is turned on, a voltage signal Vinit is input to the buffer **420** side of the capacitor **431**. The opposite side works as a virtual ground terminal. The potential of the virtual ground terminal is assumed to be zero for convenience. At this time, when the capacitance of the

capacitor **431** is C1, a potential Qinit accumulated in the capacitor **431** is expressed by the following Formula (1). On the other hand, since both ends of the capacitor **433** are short-circuited, the accumulated charge is 0.

$$Q_{init}=C1 \times V_{init} \quad (1)$$

(107) Next, in an assumed case where the switch **434** is turned off and the voltage on the buffer **420** side of the capacitor **431** has changed to a voltage Vafter, charge Qafter accumulated in the capacitor **431** is expressed by the following Formula (2).

$$Q_{after}=C1 \times V_{after} \quad (2)$$

(108) On the other hand, when the output voltage is Vout, the charge Q2 accumulated in the capacitor **433** is expressed by the following Formula (3).

$$Q2=C2 \times V_{out} \quad (3)$$

(109) At this time, since the total charge amounts of the capacitors **431** and **433** do not change, the following Formula (4) holds.

$$Q_{init}=Q_{after}+Q2 \quad (4)$$

(110) When Formulas (1) to (3) are substituted into Formula (4), then the result can be transformed into the following Formula (5).

$$V_{out}=-(C1/C2) \times (V_{after}-V_{init}) \quad (5)$$

(111) Formula (5) represents a subtraction operation of the voltage signals, in which the gain for the subtraction result is C1/C2. Since maximized gain is desirable in usual cases, it is preferable to design C1 to be large and C2 to be small. On the other hand, excessively small C2 would increase kTC noise and cause deterioration in noise characteristics. Therefore, capacity reduction of C2 is limited to a noise tolerable range. In addition, since the address event detection unit **400** including the subtractor **430** is mounted in each unit pixel, the capacitances C1 and C2 have area restrictions. In consideration of these, the values of the capacitances C1 and C2 are determined.

(112) The comparator **441** compares the voltage signal from the subtractor **430** with a predetermined threshold voltage Vth applied to the inverting input terminal (-). The comparator **441** outputs a signal indicating the comparison result to the transfer unit **450** as a detection signal.

(113) Furthermore, when the conversion gain of the current-voltage conversion unit **410** is CG.sub.log and the gain of the buffer **420** is '1', gain A of the entire address event detection unit **400** is expressed by the following Formula (6).

$$(114) \quad A = \frac{CG_{\log} \cdot \text{Math. } C1}{C2} \cdot \text{Math. } i_{\text{photo_n}} \quad (6)$$

(115) In Formula (6), i.sub.photo_n is the photocurrent of the nth unit pixel, having a unit of ampere (A), for example. N is the number of unit pixels **310** in the pixel block, and is '1' in the present embodiment.

(116) <2.2. Configuration Example of Control Device>

(117) Returning to FIG. 2. As described above, the information processing system **1** includes the control device **10**. The control device **10** is an information processing device that controls the detection device **20** and generates an image to be presented to the user.

(118) FIG. 10 is a block diagram illustrating a configuration example of the control device **10** according to the embodiment of the present disclosure. As illustrated in FIG. 10, the control device **10** includes an I/F unit **110**, a control unit **120**, and a storage unit **130**.

(119) (I/F Unit **110**)

(120) The I/F unit **110** is, for example, an interface for transmitting and receiving data to and from the detection device **20** via the network **30** (refer to FIG. 2).

(121) (Storage Unit **130**)

(122) The storage unit **130** is a storage device that stores various programs and data necessary for information processing performed by the control unit **120**.

(123) (Control Unit **120**)

(124) The control unit **120** is implemented by execution of programs stored inside the control

device **10** by a central processing unit (CPU), a micro processing unit (MPU), or the like, using random access memory (RAM) or the like, as a working area. Furthermore, the control unit **120** is actualized by, for example, an integrated circuit such as an application specific integrated circuit (ASIC) or a field programmable gate array (FPGA).

(125) As illustrated in FIG. **10**, the control unit **120** includes an acquisition unit **121**, a recognition unit **122**, a detection unit **123**, a generation unit **124**, and an output control unit **125**, and implements or executes a function and an action of information processing described below. The internal configuration of the control unit **120** is not limited to the configuration illustrated in FIG. **10**, and may be any other configuration as long as it is a configuration that performs information processing described below. Furthermore, each configuration included in the control unit **120** may be implemented as a separate device.

(126) (Acquisition Unit **121**)

(127) The acquisition unit **121** acquires data from the detection device **20** based on an instruction from the user. The instruction from the user can be acquired from an input device (not illustrated) connected via the I/F unit **110**. As described above, in a case where the information processing system **1** according to the embodiment of the present disclosure is used for video judgment in tennis, the user designates the detection device **20** to be subjected to the video judgment and a period in which the judgment is to be performed. The user may designate a period in which judgment is performed, and may designate at least one of a start time and an end time of the period.

(128) The acquisition unit **121** acquires data of a period designated by the user from the detection device **20** designated by the user. In a case where the user designates one of the start time and the end time, the acquisition unit **121** acquires data of a certain period from the designated time. The data acquired from the detection device **20** can include event detection data and image data of the predetermined period.

(129) FIG. **11** is a diagram illustrating an example of event detection data acquired by the acquisition unit **121** according to the embodiment of the present disclosure. FIG. **12** is a diagram illustrating an example of image data acquired by the acquisition unit **121** according to the embodiment of the present disclosure.

(130) As described above, the event detection data includes address information for specifying the unit pixel in which the occurrence of the address event is detected. Therefore, as illustrated in FIG. **11**, the event detection data in the predetermined period is represented as a point group representing a continuous change in luminance. In addition, when data at time t_{10} , being a certain time, is acquired, the acquired data is represented as a group of points representing the luminance change.

(131) On the other hand, the image data is image data captured at a predetermined frame rate (fps). Accordingly, as illustrated in FIG. **12**, the acquisition unit **121** acquires a plurality of pieces of image data captured at a constant cycle (1/fps) in a predetermined period. The image data acquired by the acquisition unit **121** as the image data at time t_{20} is general image data, including an image that enables the user to easily recognize an object which is a subject. In addition, since the image data is acquired at a predetermined frame rate, the acquisition unit **230** acquires the image data at a timing of a certain cycle, but does not acquire the image data between the cycle (between the frames). Therefore, in a case where the timing at which the ball touched the ground is between the frames, the acquisition unit **230** cannot acquire the image data in which the ball is landing on the ground.

(132) In accordance with an instruction from the detection unit **123** to be described below, the acquisition unit **121** outputs, from among the acquired event detection data, event detection data for a constant period having a time designated by the detection unit **123** as an end time to the recognition unit **122**. In addition, the acquisition unit **121** outputs the acquired image data to the generation unit **124**.

(133) (Recognition Unit **122**)

(134) The recognition unit **122** recognizes the subject detected by the detection device **20** based on

the event detection data input from the acquisition unit **121**. For example, the recognition unit **122** recognizes the subject using a trained model generated based on machine learning, such as deep neural network (DNN).

(135) The recognition unit **122** recognizes the subject using the trained model using information regarding the event detection data as an input. As described above, the event detection data includes the address information for specifying the unit pixel in which the occurrence of the address event is detected, and the time information indicating the detection timing. In addition, the event detection data includes event type information indicating whether the detected event is a positive event or a negative event.

(136) The recognition unit **122** uses the trained model using the address information, the time information, and the event type information as an input to acquire information to be used for generation of an output image to be described below, such as a position, contour, a shape, a state, a speed, and a motion vector of the subject. Furthermore, the recognition unit **122** recognizes whether the subject is an object as a detection target (here, a ball).

(137) The recognition unit **122** may use the address information, the time information, and the event type information as input variables of the trained model, but for example, may generate image data (an example of an input image) based on the address information, the time information, and the event type information, and use the generated image data as an input to the trained model.

(138) FIG. **13** is a diagram illustrating an example of image data generated by the recognition unit **122** according to the embodiment of the present disclosure. FIG. **14** is a diagram illustrating a recognition result obtained by the recognition unit **122** according to the embodiment of the present disclosure.

(139) As described above, the recognition unit **122** acquires the event detection data for a constant period. The recognition unit **122** replaces the event type information included in the acquired event detection data with color information. For example, the recognition unit **122** replaces the pixel in which the positive event has been detected with a green pixel (indicated by oblique lines from the upper right to the lower left in FIG. **13**), and replaces the pixel in which the negative event has been detected with a red pixel (indicated by oblique lines from the upper left to the lower right in FIG. **13**). In addition, pixels for which no event has been detected are replaced with blue pixels (indicated in white in FIG. **13**). The color indicating the event is not limited to green, red, or blue. Other colors may be used as long as detection/non-detection of an event and positive/negative of an event can be distinguished.

(140) In addition, the recognition unit **122** replaces the time information included in the event detection data with the luminance information. The recognition unit **122** replaces the luminance value of each pixel so as to allow the pixel in which the event is detected at the end timing of the constant period to have a lowest luminance and allow the pixel in which the event is detected at the start timing to have a highest luminance. Note that the luminance of the pixel in which the event has not been detected can be a constant value.

(141) In this manner, the recognition unit **122** represents each pixel with the luminance value according to the time difference of the event detection timing, making it possible to include the information regarding the time in the input to the trained model.

(142) For example, in a case where the detection device **20** has detected a moving ball, an image used as an input to the trained model by the recognition unit **122** includes a red point group having a shape close to a semicircle and a green point group having a shape close to a semicircle as illustrated in FIG. **13**. In each point group, the color becomes thicker in the traveling direction of the ball (the left side in FIG. **13**), and the color becomes thinner in the direction opposite to the traveling direction.

(143) For example, the recognition unit **122** recognizes the position, shape, motion vector, and the like of the ball as illustrated in FIG. **14** by using the image illustrated in FIG. **13** as an input to the trained model.

(144) The recognition unit **122** outputs the recognition result to the detection unit **123** and the generation unit **124**.

(145) Here, the recognition unit **122** performs recognition by using the trained model using the event detection data for a constant period as an input, but the input is not limited thereto. For example, the recognition unit **122** may use a constant number of pieces of event detection data instead of a constant period, as the input. In this case, the acquisition unit **121** goes back from the time (hereinafter, also referred to as designated time) designated by the detection unit **123**, and outputs a constant number of pieces of event detection data to the recognition unit **122**.

(146) In addition, the learning accuracy and efficiency change according to the speed range and the complexity of the shape of the object as a detection target, the surrounding environment, and the like. Therefore, the period (constant period) and the number (constant number) of the event detection data received by the recognition unit **122** from the acquisition unit **121** can be appropriately adjusted according to the speed range and the complexity of shape of the object as a detection target (here, a tennis ball), the surrounding environment, and the like.

(147) In this case, for example, the recognition unit **122** may generate a group of pixels close to each other based on the event detection data sequentially input so as to go back from the designated time, and may perform the recognition processing by the learning in a case where the number of pixels included in the group becomes a predetermined value or more. In this manner, the event detection data output from the acquisition unit **121** to the recognition unit **122** is not limited to a constant period or a constant number of pieces of data.

(148) Furthermore, for example, the recognition unit **122** may perform pre-processing before recognition by machine learning, such as not performing recognition processing in a case where the object included in the generated image is clearly different from the detection target. For example, in a case where it is clear that the detection target is not included in the generated image, for example, in a case where the generated image includes a vertically long object such as a player while the detection target is a tennis ball, the recognition unit **122** can omit the recognition processing.

(149) In the above example, the recognition unit **122** recognizes the speed and the motion vector by machine learning, but the operation is not limited thereto. The recognition unit **122** need not recognize the speed and the motion vector by machine learning. In this case, for example, the recognition unit **122** can estimate the speed and the motion vector from the position change of the recognized object based on the event detection data in different periods.

(150) (Detection Unit **123**)

(151) The detection unit **123** detects a generation timing of an image to be presented to the user based on a recognition result obtained by the recognition unit **122**. For example, in the case of video judgment in tennis, the detection unit **123** detects the timing at which the ball touches the ground as the generation timing of the image to be presented to the user. In other words, the detection unit **123** detects the timing at which the object (ball) is positioned at (touches) a predetermined place (ground). In this case, the detection unit **123** detects the timing at which the direction of the motion vector of the recognized object is reversed as the generation timing.

(152) FIG. **15** is a diagram illustrating detection of a generation timing performed by the detection unit **123** according to the embodiment of the present disclosure.

(153) First, by instructing the acquisition unit **121** that time t_1 , being a certain time, is defined as the designated time, the detection unit **123** acquires, from the recognition unit **122**, information related to the position and the motion vector of the object (here, the ball) at time t_1 . In the example of FIG. **15**, the detection unit **123** detects a downward motion vector V_1 .

(154) Next, with time t_2 later than time t_1 defined as the designated time, the detection unit **123** acquires the position and a motion vector V_2 of the object at time t_2 . Here, it is assumed that the motion vector V_2 acquired by the detection unit **123** is a vector having the same direction as the motion vector V_1 at time t_1 and having a smaller size than the motion vector V_1 .

(155) Next, with time t_8 later than time t_2 defined as the designated time, the detection unit **123**

acquires the position and a motion vector V3 of the object at time t8. Here, it is assumed that the motion vector V3 acquired by the detection unit **123** is upward, which is a direction opposite to the motion vector V2 at time t2.

(156) In this case, the ball is considered to have touched the ground and bounded between time t2 and time t8. Therefore, with time t5, which is a time before time t8 and between time t2 and time t8, defined as the designated time, the detection unit **123** acquires the position of the object and a motion vector V4 at time t5.

(157) Moreover, with time t3 between time t2 and time t5 defined as the designated time, the detection unit **123** acquires the position of the object and a motion vector V5 at time t3. With time t7 between time t5 and time t8 defined as the designated time, the detection unit **123** acquires the position of the object and a motion vector V6 at time t7.

(158) The detection unit **123** compares the positions of the objects at times t3, t5, and t7, and detects the time of the lowest position. For example, in FIG. 15, the position of the object at time t5 is the lowest.

(159) In this case, with time t4 between time t3 and time t5 as the designated time, the detection unit **123** acquires the position and a motion vector V7 of the object at time t4. With time t6 between time t5 and time t7 defined as the designated time, the detection unit **123** acquires the position of the object and a motion vector V8 at time t6.

(160) The detection unit **123** compares the positions of the objects at times t4, t5, and t6, and detects the time of the lowest position. For example, in FIG. 15, the position of the object at time t5 is the lowest. Similarly, the detection unit **123** compares the positions of the objects while narrowing the time interval, and detects the time at the lowest position. The detection unit **123** determines the detected time as the generation timing. In the example of FIG. 15, the detection unit **123** determines time t5 indicated by a dotted line as the generation timing.

(161) (Generation Unit **124**)

(162) The generation unit **124** generates an output image at the generation timing detected by the detection unit **123**. For example, by combining an image related to an object (here, a ball) with image data (background) at a time closest to the generation timing, the generation unit **124** generates an output image. Alternatively, the generation unit **124** can generate an output image by combining an image related to an object with a background image acquired in advance. The combining position and the size of the image related to the object are determined based on the recognition result obtained by the recognition unit **122**.

(163) Here, the image related to the object is a contour image of the object or an image generated from three-dimensional CG. The generation unit **124** may combine the image by using an image of the object acquired in advance, or using an object image clipped from the image data acquired from the detection device **20**. Alternatively, the image related to the object may be an image generated by the recognition unit **122** based on the event detection data. Furthermore, the generation unit **124** may use a plurality of images for combining an image. For example, the generation unit **124** may combine both the image generated by the recognition unit **122** based on the event detection data and the contour image of the object to generate the output image.

(164) In this manner, the generation unit **124** combines the image generated based on the event detection data to obtain the output image, making it possible for the control device **10** to present a more convincing output image to the user.

(165) Further, the generation unit **124** may generate an output video including the output image at the generation timing. The output video is a moving image in a predetermined period including a generation timing.

(166) The generation unit **124** generates a plurality of output images in a predetermined period, and joins the plurality of output images to generate the output video. Alternatively, the generation unit **124** interpolates images between frames of image data acquired from the detection device **20** to generate an output image.

(167) At this time, for example, a generation unit **124** may generate the output video such that the time interval becomes narrowest before and after the generation timing in the predetermined period, and the time interval becomes widest near the start and end of the predetermined period. That is, a generation unit **124** generates the output video such that the output video is reproduced in slow motion before and after the generation timing, for example.

(168) In this manner, the frame rate of the output video generated by a generation unit **124** may be set to be variable in the output video. Note that such a frame rate may be a value designated by the user, or may be a value set in advance according to the operating environment of the system or the like.

(169) (Output Control Unit **125**)

(170) The output control unit **125** presents the output image or the output video to the user by outputting the output image or the output video generated by the generation unit **124** to a display device (not illustrated) via the I/F unit **110**.

3. Information Processing

(171) Next, an example of information processing by the information processing system **1** according to the embodiment of the present disclosure will be described.

(172) <3.1. Setting Processing>

(173) First, setting processing by the information processing system **1** according to the embodiment of the present disclosure will be described with reference to FIG. **16**. FIG. **16** is a flowchart illustrating an example of a flow of setting processing executed by the information processing system **1** according to the embodiment of the present disclosure. The information processing system **1** executes setting processing at the start of system operation. The setting processing is mainly executed by the control unit **120** of the control device **10** of the information processing system **1**.

(174) As illustrated in FIG. **16**, the control device **10** acquires an installation position of the detection device **20** (Step **S101**). The control device **10** acquires the installation position from an administrator who operates the system. Alternatively, control device **10** may acquire the installation position from a positioning sensor such as a global positioning system (GPS) sensor (not illustrated) grounded to the detection device **20**.

(175) The control device **10** controls the detection device **20** to adjust the focus and angle of view of the EVS **220** and the image sensor **240** (Step **S102**). For example, the control device **10** adjusts the focus and the angle of view to be the same in the EVS **220** and the image sensor **240**. The focus and the angle of view may be adjusted manually.

(176) Next, the control device **10** acquires various setting values such as the line position on the ground, the size of the ball as a detection target, and the distance to the ground (Step **S103**). The various setting values are values that vary depending on an object to be detected, a timing to be detected, an environment, and the like. The control device **10** uses the setting values to adjust the trained model, for example.

(177) The control device **10** acquires a background image as a background of the output image (Step **S104**). For example, the control device **10** acquires a still image acquired by the image sensor **240** of the detection device **20** as a background image. Alternatively, the control device **10** may acquire, as the background image, a captured image captured in advance, such as an image captured by another device, or an image generated by CG or the like. For example, in a case where a background image other than the image data captured by the image sensor **240** is acquired, the control device **10** may calibrate the acquired background image and the angle of view of the EVS **220** with each other.

(178) The control device **10** acquires object information to be used for generating an image related to an object (Step **S105**). An example of the object information is information indicating a three-dimensional shape of the object (here, a ball) or image information of the object. The control device **10** generates an output image by combining a two-dimensional object image generated

based on the object information in image generation processing to be described below with a background image.

(179) In a case where the control device **10** uses image data captured by the image sensor **240** as the background image, the acquisition of the background image in Step **S104** may be omitted. Furthermore, in a case where the control device **10** combines the object image included in the image data captured by the image sensor **240** or the image generated by the recognition unit **122** with the background image to generate the output image, the acquisition of the object information in Step **S105** may be omitted.

(180) <3.2. Imaging Processing>

(181) Next, imaging processing performed by the information processing system **1** according to the embodiment of the present disclosure will be described with reference to FIG. **17**. FIG. **17** is a flowchart illustrating an example of a flow of imaging processing executed by the information processing system **1** according to the embodiment of the present disclosure. The imaging processing is executed by the detection device **20** in accordance with an instruction from the control device **10** of the information processing system **1**. When having received an operation start instruction from the control device **10**, the detection device **20** executes imaging processing illustrated in FIG. **17**.

(182) The detection device **20** acquires sensor data (Step **S201**). The sensor data includes event detection data output by the EVS **220** and image data output by the image sensor **240**. The detection device **20** stores the acquired sensor data in the storage unit **260** (Step **S202**).

(183) The detection device **20** judges whether there is an imaging stop request from the control device **10** (Step **S203**). When there is no stop request (Step **S203**; No), the detection device **20** returns to Step **S201**.

(184) In contrast, when there is a stop request (Step **S203**; Yes), the detection device **20** judges whether there is a data transfer request (Step **S204**). When there is no transfer request (Step **S204**; No), the detection device **20** ends the imaging processing.

(185) In contrast, when there is a transfer request (Step **S204**; Yes), the detection device **20** outputs requested data which is sensor data for a period requested by the control device **10** (Step **S205**).

(186) <3.3. Generation Processing>

(187) An output image generation processing performed by the information processing system **1** according to the embodiment of the present disclosure will be described with reference to FIG. **18**. FIG. **18** is a flowchart illustrating an example of a flow of generation processing executed by the information processing system **1** according to the embodiment of the present disclosure. The generation processing is executed by the control device **10** of the information processing system **1**. The control device **10** executes the generation processing until there is an end instruction from the user.

(188) The control device **10** instructs the detection device **20** to start an operation (Step **S301**). With this instruction, the detection device **20** executes imaging processing and acquires sensor data.

(189) Next, the control device **10** judges whether a judgment request has been made by the user (Step **S302**). The judgment request here is a request for video judgment from the user, and is a request for outputting an output image at a desired timing.

(190) In a case where there is no judgment request from the user (Step **S302**; No), the control device **10** returns to Step **S302** and waits for a judgment request. In contrast, in a case where there is a judgment request from the user (Step **S302**; Yes), the detection device **20** to be the target in generating the output image is selected according to the instruction from the user (Step **S303**). Alternatively, based on the image data captured by the image sensors **240** of the plurality of detection devices **20**, the control device **10** may select the detection device **20** by specifying the detection device **20** that has captured the object as a detection target near the time instructed by the user.

(191) The control device **10** acquires sensor data from the selected detection device **20** (Step **S304**).

The control device **10** analyzes the acquired data (Step S305). More specifically, the control device **10** recognizes a ball, which is a detection target, from the event detection data, and detects the timing of generating the output image. The control device **10** generates an output video of a judgment point including the detected timing and outputs the output video to a display device (not illustrated), thereby reproducing the judgment point (Step S306).

(192) After reproducing the judgment point, the control device **10** judges whether to end the processing (Step S307). When having received an instruction to end the processing from the user, the control device **10** judges to end the generation processing (Step S307; Yes) and ends the generation processing. In contrast, when having no instruction to end the processing from the user, or having received an instruction to continue the processing from the user, the control device **10** judges not to end the generation processing (Step S307; No), and returns to Step S301.

4. Other Embodiments

(193) The above-described embodiment is an example, and various modifications and applications are possible.

(194) In the above-described embodiment, the information processing system **1** is used for video judgment of tennis, but application is not limited thereto. The information processing system **1** according to the embodiment of the present disclosure can be applied to video judgment in sports other than tennis such as volleyball, a collision experiment of a moving body such as a car, for example.

(195) Alternatively, the information processing system **1** may be applied to goal judgment of athletics or horse racing. In this case, the control device **10** detects the generation timing according to whether the object has crossed a predetermined position (for example, a goal line) instead of detecting the timing of generating the output image from the motion vector of the object.

(196) Hereinafter, a case where the information processing system **1** is applied to goal judgment of a horse race will be described as an example. FIG. **19** is a diagram for describing another application example of the information processing system **1** according to the embodiment of the present disclosure.

(197) For example, at the time of calibration in the setting processing, the control device **10** sets the position to be the goal on the angle of view in units of pixels. In the generation processing, the control device **10** generates an output video with the timing at which the contour of the recognized object touched the set goal line as a judgment point.

(198) In the goal judgment in horse racing and athletics, the object as a detection target is a horse or a person. Therefore, due to a complicated shape of the object, there may be a case where a part of the shape is detected without the entire object entering the angle of view. Even in a case where a part of the object is detected as described above, the control device **10** is supposed to pre-adjust the trained model so as to more accurately recognize the contour of the moving object.

(199) Note that the method of searching for the timing at which the contour of the object touched the goal line can be similar to the case of searching for the timing at which the ball touched the ground described above. That is, the control device **10** can detect the timing at which the contour of the object touched the goal line by recognizing the position of the object while shifting the time.

(200) Alternatively, by predicting the time of crossing the goal from the size of the recognized motion vector and the speed of the object, and comparing the position of the object before and after the prediction time with the goal line, the control device **10** can further reduce the convergence time, that is, the search time.

(201) Furthermore, the application example of the information processing system **1** according to the above-described embodiment is not limited to the video judgment and the goal judgment. For example, the information processing system **1** can be applied to an analysis system of a Pachinko game machine. For example, the information processing system **1** analyzes a contact point between pins and a ball of a Pachinko game table and a track of the ball. At this time, the information processing system **1** can detect both the change timing of the motion vector of the ball and the

contact timing between the ball and the pin as the generation timing.

(202) The information processing system **1** performs track analysis of the balls in the pachinko game machine by performing super slow reproduction centered on the contact timing between the pin and the ball or plotting the trajectory of the ball.

(203) Since the information processing system **1** detects an object using the EVS **220**, it is possible to store data for a longer time and to reduce the analysis time as compared with a high-speed camera (high frame rate camera).

(204) Although the above embodiment has described that the detection device **20** includes the image sensor **240**, but application is not limited thereto. In a case where the control device **10** generates the output image without using the captured image of the image sensor **240**, such as a case where a background image captured in advance is used or a case where a CG image is used as the background image, the detection device **20** does not have to be equipped with the image sensor **240**.

(205) This enables further downsizing of the detection device **20**, leading to an improved degree of freedom in arrangement of the detection device **20**. In addition, the image data of the image sensor **240** need not be stored, making it possible to further reduce the volume of data to be stored in the storage unit **260**.

5. Hardware Configuration

(206) An information processing device **100** according to the above-described embodiment is implemented by a computer **1000** having a configuration as illustrated in FIG. **20**, for example. FIG. **20** is a hardware configuration diagram illustrating an example of the computer **1000** that implements functions of the control device **10**. The computer **1000** includes a CPU **1100**, RAM **1200**, ROM **1300**, storage **1400**, a communication interface **1500**, and an input/output interface **1600**. Individual components of the computer **1000** are interconnected by a bus **1050**.

(207) The CPU **1100** operates on the basis of a program stored in the ROM **1300** or the storage **1400** so as to control each component. For example, the CPU **1100** develops a program stored in the ROM **1300** or the storage **1400** in the RAM **1200**, and executes processing corresponding to various programs.

(208) The ROM **1300** stores a boot program such as a basic input output system (BIOS) executed by the CPU **1100** when the computer **1000** starts up, a program dependent on hardware of the computer **1000**, or the like.

(209) The storage **1400** is a non-transitory computer-readable recording medium that records a program executed by the CPU **1100**, data used by the program, or the like. Specifically, the storage **1400** is a recording medium that records a program according to the present disclosure which is an example of a program data **1450**.

(210) The communication interface **1500** is an interface for connecting the computer **1000** to an external network **1550**. For example, the CPU **1100** receives data from other devices or transmits data generated by the CPU **1100** to other devices via the communication interface **1500**.

(211) The input/output interface **1600** is an interface for connecting an input/output device **1650** with the computer **1000**. For example, the CPU **1100** can receive data from an input device such as a keyboard, a mouse, and an acceleration sensor **13** via the input/output interface **1600**. In addition, the CPU **1100** transmits data to an output device such as a display, a speaker, or a printer via the input/output interface **1600**. Furthermore, the input/output interface **1600** may function as a media interface for reading a program or the like recorded on a predetermined recording medium.

Examples of the media include optical recording media such as a digital versatile disc (DVD) or a phase change rewritable disk (PD), a magneto-optical recording medium such as a magneto-optical disk (MO), a tape medium, a magnetic recording medium, and semiconductor memory.

(212) For example, when the computer **1000** functions as the control device **10** according to the embodiment, the CPU **1100** of the computer **1000** executes the information processing program loaded on the RAM **1200** so as to implement the functions of the control unit **120** or the like. In

addition, the storage **1400** stores a program according to the present disclosure and data in the storage unit **130**. While the CPU **1100** executes program data **1450** read from the storage **1400**, the CPU **1100** may acquire these programs from another device via the external network **1550**, as another example.

6. Summary

(213) The preferred embodiments of the present disclosure have been described in detail above with reference to the accompanying drawings. However, the technical scope of the present disclosure is not limited to such examples. It will be apparent to those skilled in the art of the present disclosure that various modifications and alterations can be conceived within the scope of the technical idea described in the claims and naturally fall within the technical scope of the present disclosure.

(214) Among the processing described in the above embodiments, all or a part of the processing described as being performed automatically may be manually performed, or the processing described as being performed manually can be performed automatically by known methods. In addition, the processing procedures, specific names, and information including various data and parameters illustrated in the above Literatures or drawings can be arbitrarily altered unless otherwise specified. For example, a variety of information illustrated in each of the drawings are not limited to the information illustrated.

(215) In addition, each of components of each device is provided as a functional and conceptional illustration and thus does not necessarily need to be physically configured as illustrated. That is, the specific form of distribution/integration of each of the devices is not limited to those illustrated in the drawings, and all or a part thereof may be functionally or physically distributed or integrated into arbitrary units according to various loads and use situations.

(216) Furthermore, the above-described embodiments can be appropriately combined within a range implementable without contradiction of processes.

(217) Furthermore, the effects described in the present specification are merely illustrative or exemplary and are not limited. That is, the technology according to the present disclosure can exhibit other effects that are apparent to those skilled in the art from the description of the present specification in addition to or instead of the above effects.

(218) Note that the following configurations also belong to the technical scope of the present disclosure.

(219) (1)

(220) An information processing device comprising: an acquisition unit that acquires information including event data and a detection time of the event data associated with each other, the event data being data output from a first sensor including a pixel array unit, the pixel array unit having a plurality of pixels arranged in a two-dimensional lattice pattern, each of the pixels configured to detect a luminance change in incident light and output event data; a recognition unit that recognizes an object detected by the first sensor by using a trained model using information related to the detection time and the event data as an input; and an output unit that outputs an image related to the recognized object.

(221) (2)

(222) The information processing device according to (1), wherein the recognition unit sets, as the input to the trained model, an input image in which information indicating whether luminance included in the event data has changed to positive or negative with respect to a threshold is set as color information, and in which difference information between a reference time and the detection time is set as luminance information.

(223) (3)

(224) The information processing device according to (1) or (2), wherein the acquisition unit acquires frame image data from a second sensor that captures a frame image, and the output unit outputs a combined image obtained by combining an object image related to the object with the

frame image data.

(225) (4)

(226) The information processing device according to (3), wherein the object image is an illustrative image of the object.

(227) (5)

(228) The information processing device according to (3), wherein the object image is an image in which information indicating whether luminance included in the event data has changed to positive or negative with respect to a threshold is set as color information and in which difference information between a reference time and the detection time is set as luminance information.

(229) (6)

(230) The information processing device according to any one of (1) to (5), further comprising a detection unit that detects a timing at which the object is positioned at a predetermined location based on movement information of the object, wherein the output unit outputs the image related to the object at the timing.

(231) (7)

(232) The information processing device according to (6), wherein the output unit outputs a plurality of frame images in a period including the timing, the plurality of frame images including the image related to the object.

(233) (8)

(234) The information processing device according to (7), wherein the output unit outputs the plurality of frame images having different frame rates.

(235) (9)

(236) An information processing system comprising: a first sensor including a pixel array unit, the pixel array unit having a plurality of pixels arranged in a two-dimensional lattice pattern, each of the pixels configured to detect a luminance change in incident light and output event data; and an information processing device, wherein the information processing device includes: an acquisition unit that acquires information including the event data output from the first sensor and a detection time of the event data associated with each other; a recognition unit that recognizes an object detected by the first sensor by using a trained model using information related to the detection time and the event data as an input; and an output unit that outputs an image related to the recognized object.

(237) (10)

(238) An information processing method comprising: acquiring information including event data and a detection time of the event data associated with each other, the event data being data output from a first sensor including a pixel array unit, the pixel array unit having a plurality of pixels arranged in a two-dimensional lattice pattern, each of the pixels configured to detect a luminance change in incident light and output event data; recognizing an object detected by the first sensor by using a trained model using information related to the detection time and the event data as an input; and outputting an image related to the recognized object.

(239) (11)

(240) A program for causing a computer to function as: an acquisition unit that acquires information including event data and a detection time of the event data associated with each other, the event data being data output from a first sensor including a pixel array unit, the pixel array unit having a plurality of pixels arranged in a two-dimensional lattice pattern, each of the pixels configured to detect a luminance change in incident light and output event data; a recognition unit that recognizes an object detected by the first sensor by using a trained model using information related to the detection time and the event data as an input; and an output unit that outputs an image related to the recognized object.

REFERENCE SIGNS LIST

(241) **1** INFORMATION PROCESSING SYSTEM **10** CONTROL DEVICE **20** DETECTION

Claims

1. An information processing device comprising: a memory storing a program, and at least one processor configured to execute the program to perform operations comprising: acquiring information including event data and a detection time of the event data associated with each other, the event data being data output from a first sensor including a pixel array unit, the pixel array unit having a plurality of pixels arranged in a two-dimensional lattice pattern, each of the pixels configured to detect a luminance change in incident light and output event data; recognizing an object detected by the first sensor by using a trained model using information related to the detection time and the event data as an input; and outputting an image related to the recognized object, acquiring frame image data from a second sensor that captures a frame image; and generating a reconstructed image of a desired timing obtained by combining an illustrative image of the object with the frame image data.
2. The information processing device according to claim 1, wherein the operations further comprise: setting, as the input to the trained model, an input image in which information indicating whether luminance included in the event data has changed to positive or negative with respect to a threshold is set as color information, and setting, as luminance information, difference information between a reference time and the detection time.
3. The information processing device according to claim 1, wherein the object image is an image in which information indicating whether luminance included in the event data has changed to positive or negative with respect to a threshold is set as color information and in which difference information between a reference time and the detection time is set as luminance information.
4. The information processing device according to claim 1, wherein the operations further comprise: detecting a timing at which the object is positioned at a predetermined location based on movement information of the object, and outputting the image related to the object at the timing.
5. The information processing device according to claim 4, wherein the operations further comprise: outputting a plurality of frame images in a period including the timing, the plurality of frame images including the image related to the object.
6. The information processing device according to claim 5, wherein the operations further comprise: outputting the plurality of frame images having different frame rates.
7. An information processing system comprising: a first sensor including a pixel array unit, the pixel array unit having a plurality of pixels arranged in a two-dimensional lattice pattern, each of the pixels configured to detect a luminance change in incident light and output event data; and an information processing device, wherein the information processing device includes: a memory storing a program, and at least one processor configured to execute the program to perform operations comprising: acquiring information including the event data output from the first sensor and a detection time of the event data associated with each other; recognizing an object detected by the first sensor by using a trained model using information related to the detection time and the event data as an input; and outputting an image related to the recognized object, wherein acquiring information including the event data output from the first sensor and a detection time of the event data associated with each other includes acquiring frame image data from a second sensor that captures a frame image, and outputting an image related to the recognized object comprises generating a reconstructed image of a desired timing obtained by combining an illustrative image of the object with the frame image data.
8. An information processing method comprising: acquiring information including event data and a detection time of the event data associated with each other, the event data being data output from a first sensor including a pixel array unit, the pixel array unit having a plurality of pixels arranged in

a two-dimensional lattice pattern, each of the pixels configured to detect a luminance change in incident light and output event data; acquiring frame image data from a second sensor that captures a frame image, recognizing an object detected by the first sensor by using a trained model using information related to the detection time and the event data as an input; and outputting an image related to the recognized object, wherein the image related to the recognized object is a reconstructed image of a desired timing obtained by combining an illustrative image of the object with the frame image data.

9. The method of claim 8, wherein the method further comprises: setting, as the input to the trained model, an input image in which information indicating whether luminance included in the event data has changed to positive or negative with respect to a threshold is set as color information, and setting, as luminance information, difference information between a reference time and the detection time.

10. The method of claim 8, wherein the method further comprises: detecting a timing at which the object is positioned at a predetermined location based on movement information of the object, and outputting the image related to the object at the timing.

11. The method of claim 10, wherein the method further comprises: outputting a plurality of frame images in a period including the timing, the plurality of frame images including the image related to the object.

12. The method of claim 11, wherein the method further comprises: outputting the plurality of frame images having different frame rates.

13. A non-transitory computer readable medium storing a program for causing an information processing device to perform a set of operations comprising: acquiring information including event data and a detection time of the event data associated with each other, the event data being data output from a first sensor including a pixel array unit, the pixel array unit having a plurality of pixels arranged in a two-dimensional lattice pattern, each of the pixels configured to detect a luminance change in incident light and output event data; recognizing an object detected by the first sensor by using a trained model using information related to the detection time and the event data as an input; and outputting an image related to the recognized object, wherein acquiring information including event data and a detection time of the event data associated with each other comprises acquiring frame image data from a second sensor that captures a frame image, and wherein outputting an image related to the recognized object comprises generating a reconstructed image of a desired timing obtained by combining an illustrative image of the object with the frame image data.

14. The non-transitory computer readable medium of claim 13, wherein the operations further comprise: setting, as the input to the trained model, an input image in which information indicating whether luminance included in the event data has changed to positive or negative with respect to a threshold is set as color information, and setting, as luminance information, difference information between a reference time and the detection time.

15. The non-transitory computer readable medium of claim 13, wherein the operations further comprise: detecting a timing at which the object is positioned at a predetermined location based on movement information of the object, and outputting the image related to the object at the timing.

16. The non-transitory computer readable medium of claim 15, wherein the operations further comprise: outputting a plurality of frame images in a period including the timing, the plurality of frame images including the image related to the object.

17. The non-transitory computer readable medium of claim 16, wherein the operations further comprise: outputting the plurality of frame images having different frame rates.
