

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402908
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Zeng; Junhua et al.

Transperineal puncture guiding bracket

Abstract

A transperineal puncture guiding bracket is provided, comprising a probe fixing assembly and a guiding assembly, wherein a mounting plate is set on top of the probe fixing assembly, the guiding assembly comprises a needle grooved plate and a cover plate, and the needle grooved plate is detachably combined to a first side surface of the mounting plate by a first vertical insertion structure, a first hanging structure and a first buckling structure, the cover plate is detachably combined with the needle grooved plate by a second vertical insertion structure, a second hanging structure and a second buckling structure, thereby the cover plate is detachably attached to the needle grooved plate to form a plurality of needle guiding holes. In the bracket, needled grooved plates of different specifications can be replaced according to the puncture needles, and the puncture needle can be easily separated from the bracket.

Inventors:	Zeng; Junhua (Guangdong, CN), Han; Yi (Guangdong, CN)
Applicant:	JingFang Precision Medical Device (Shenzhen) Co., Ltd. (Guangdong, CN)
Family ID:	84168436
Assignee:	JingFang Precision Medical Device (Shenzhen) Co., Ltd. (Shenzhen, CN)
Appl. No.:	18/836353
Filed (or PCT Filed):	May 12, 2023
PCT No.:	PCT/CN2023/093911
PCT Pub. No.:	WO2024/066379
PCT Pub. Date:	April 04, 2024

Prior Publication Data

Foreign Application Priority Data

CN202211187742.0Sep. 27, 2022

Publication Classification

Int. Cl.: A61B17/34 (20060101); A61B8/00 (20060101); A61B8/12 (20060101)

U.S. Cl.:

CPC A61B17/3403 (20130101); A61B8/12 (20130101); A61B8/4455 (20130101); A61B2017/3411 (20130101); A61B2017/3413 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5871448	12/1998	Ellard	600/459	A61B 8/0841
2016/0022309	12/2015	Allaway	600/464	A61B 10/0241
2018/0199851	12/2017	Krieger	N/A	G01R 33/287
2022/0160339	12/2021	Whitmore et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
219126587	12/2022	CN	N/A
2006075386	12/2005	JP	N/A

OTHER PUBLICATIONS

International Search Report of PCT Patent Application No. PCT/CN2023/093911 issued on Jul. 28, 2023. cited by applicant

Primary Examiner: Farag; Amal Aly

Background/Summary

FIELD

(1) The present application generally relates to ultrasound intervention medical auxiliary devices, more particularly to a transperineal puncture guiding bracket.

BACKGROUND

(2) With changes of people's lifestyle in recent years, an incidence rate of prostate cancer in China

has increased year by year, and it has ranked first in malignant tumors of the urinary system (male). Early detection and timely treatment can save lives of patients. Real time ultrasound guided prostate biopsy is a best choice for diagnosing prostate cancers due to its small trauma and high accuracy. There are two ways to perform prostate biopsy surgery: one is through the perineum, and the other is through the rectum. During transrectal puncture biopsy surgery, a biopsy needle is inserted into the prostate site through an entrance of the anus and intestines, and the rectal mucosa is prone to bleeding and infection after surgery. During transperineal puncture biopsy surgery, a biopsy needle is inserted into the prostate site through the external perineum, thus the surgery can be aseptic, has a low risk of infection, comprehensive sampling, and higher safety. Transperineal puncture biopsy is more conducive to detecting early tumors and reducing postoperative adverse reactions, and is currently a mainstream prostate biopsy method.

(3) In the process of transperineal prostate biopsy surgery, an intracavitary ultrasound probe is equipped with a puncture guiding bracket for use. A front end of the puncture guiding bracket needs to be close to a patient's perineum, and a biopsy needle needs to pass through a guide hole on the puncture guiding bracket to puncture into the prostate gland. Commonly used puncture guiding brackets currently have the following limitations: 1. Due to use of a closed needle hole structure for guiding a biopsy needle, the puncture guiding bracket cannot be separated from the biopsy needle, which limits the flexible operation of doctors. 2. A needle grooved plate and a bracket body are integrated to form a whole structure, thus different puncture guiding brackets are required when using biopsy needles of different specifications, which brings inconvenience to doctors during surgical operations.

SUMMARY

(4) The technical problem to be solved by the present application is to provide a transperineal puncture guiding bracket that can replace needle grooved plates of different specification according to puncture needles of different specifications and facilitate separation of puncture needles in view of the above-mentioned drawbacks of the prior art.

(5) The technical solution adopted by the present application to solve the technical problem thereof is to provide a transperineal puncture guiding bracket, comprising a probe fixing assembly and a guiding assembly, wherein the probe fixing assembly is fixedly installed with an intracavitary ultrasound probe, the guiding assembly provides a plurality of vertically distributed and parallel needle guiding holes along a puncture direction, wherein, an mounting plate is set on top of the probe fixing assembly, and the guiding assembly further comprises a needle grooved plate and a cover plate, the needle grooved plate has a first side surface and a second side surface opposite to the first side surface, with the first side surface of the needle grooved plate being provided with a plurality of vertically distributed and parallel needle guiding grooves; and a lower portion of the needle grooved plate is detachably combined with the top of the probe fixing assembly adjacent to the mounting plate by a first vertical insertion structure, an upper portion of the needle grooved plate is detachably hung with an upper portion of the mounting plate by a first hanging structure, and the second side surface of the needle grooved plate is detachably buckled with a first side surface of the mounting plate by a first buckling structure, thereby the second side surface of the needle grooved plate is detachably attached to the first side surface of the mounting plate; and a lower portion of the cover plate is detachably combined with the lower portion of the needle grooved plate or the top of the probe fixing assembly by a second vertical insertion structure, an upper portion of the cover plate is detachably hung with the upper portion of the needle grooved plate by a second hanging structure, and the cover plate is further detachably buckled with the upper portion of the mounting plate, the upper portion of the needle grooved plate or the top of the probe fixing assembly through a second buckling structure, thereby a second side surface of the cover plate is detachably attached to the first side surface of the needle grooved plate to close the plurality of needle guiding grooves to form the plurality of needle guiding holes.

(6) In the transperineal puncture guiding bracket according to an embodiment of the present

application, the first vertical insertion structure comprises first limiting feet provided at the lower portion of the needle grooved plate which extend out from the first side surface of the needle grooved plate and limiting grooves formed at the top of the probe fixing assembly for insertion of the first limiting feet; and the second vertical insertion structure comprises second limiting feet set at the lower portion of the cover plate and limiting holes on the first limiting feet of the needle grooved plate for insertion of the second limiting feet.

(7) In the transperineal puncture guiding bracket according to an embodiment of the present application, the first vertical insertion structure comprises first limiting feet provided at the lower portion of the needle grooved plate and first limiting grooves set at the top of the probe fixing assembly for insertion of the first limiting feet; and the second vertical insertion structure comprises second limiting feet set at the lower portion of the cover plate and second limiting grooves formed at the top of the probe fixing assembly for insertion of the second limiting feet.

(8) In the transperineal puncture guiding bracket according to an embodiment of the present application, the first hanging structure comprises first hanging holes at the upper portion of the needle grooved plate and first hooks at the upper portion of the mounting plate which extend out from the first side surface of the mounting plate to hang into the first hanging holes; and the second hanging structure comprises second hanging holes at the upper portion of the cover plate and second hooks at the upper portion which extend out from the first side surface of the needle grooved plate to hang into the second hanging holes.

(9) In the transperineal puncture guiding bracket according to an embodiment of the present application, the first buckling structure comprises a first limiting buckle set in the middle of the second side surface of the needle grooved plate and a first elastic buckle set in the middle of the mounting plate, wherein a through-hole is set in the middle of the mounting plate that connects the first side surface and a second side surface of the mounting plate, and the first elastic buckle is set inside the through-hole, the first elastic buckle has a first buckling position that is engaged with the first limiting buckle and a first operating part that extends out of the second side surface of the mounting plate for releasing engagement between the first buckling position and the first limiting buckle.

(10) In the transperineal puncture guiding bracket according to an embodiment of the present application, the second buckling structure comprises a second elastic buckle set at the upper portion of the needle grooved plate, wherein the second elastic buckle has a second buckling position for pressing a top surface of the cover plate and a second operating part for releasing the second buckling position from pressing the top surface of the cover plate.

(11) In the transperineal puncture guiding bracket according to an embodiment of the present application, the second buckling structure comprises a second elastic buckle set at the upper portion of the mounting plate, wherein the second elastic buckle has a second buckling position for pressing a top surface of the cover plate and a second operating part for releasing the second buckling position from pressing the top surface of the cover plate.

(12) In the transperineal puncture guiding bracket according to an embodiment of the present application, the second buckling structure comprises a second limiting buckle set at the upper portion of the first side surface of the needle grooved plate and a second elastic buckle at the corresponding upper portion of the cover plate, wherein a through-hole is set at the upper portion of the cover plate that connects a first side surface and the second side surface of the cover plate, and the second elastic buckle is set inside the through-hole, the second elastic buckle has a second buckling position that is engaged with the second limiting buckle and a second operating part that extends out of the first side surface of the cover plate for releasing engagement between the second buckling position and the second limiting buckle.

(13) In the transperineal puncture guiding bracket according to an embodiment of the present application, the probe fixing assembly comprises an upper fixing member and a lower fixing member, wherein the upper fixing member and the lower fixing member work together to hold

outer surface of the intracavitary ultrasound probe, and the mounting plate is set on top of the upper fixing member.

(14) In the transperineal puncture guiding bracket according to an embodiment of the present application, upper wrapping surfaces are formed on a lower surface of the upper fixing member for fitting upper surface of the intracavitary ultrasound probe, and lower wrapping surfaces are formed on an upper surface of the lower fixing member for fitting lower surface of the intracavitary ultrasound probe, and the upper fixing member and the lower fixing member are rotationally connected on one side and buckled on the opposite side to tightly hold the intracavitary ultrasound probe through the upper wrapping surfaces and the lower wrapping surfaces.

(15) Implementing the transperineal puncture guiding bracket of the present application has the following beneficial effects: The transperineal puncture guiding bracket according to the embodiments of the present application can guide puncture needles of different specifications by replacing the guiding assembly with needle holes of different specifications, without a need of replacing the entire transperineal puncture guiding bracket, which facilitates surgical operations of doctors. With the transperineal puncture guiding bracket according to the embodiments of the present application, the puncture needle can be easily separated from the transperineal puncture guiding bracket during surgery by separating the cover plate from the needle grooved plate of the guiding assembly, making the doctor's operation more flexible.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The present application will be further described with reference to the accompanying drawings and embodiments, in which:
- (2) FIG. 1 is a schematic structural diagram of a transperineal puncture guiding bracket according to a first embodiment of the present application;
- (3) FIG. 2 is an exploded structural diagram of the transperineal puncture guiding bracket shown in FIG. 1;
- (4) FIG. 3 is an exploded structural diagram of a probe fixing assembly shown in FIG. 2;
- (5) FIG. 4 is an exploded structural diagram of the probe fixing assembly shown in FIG. 2 from another perspective;
- (6) FIG. 5 is an exploded structural diagram of a guiding assembly shown in FIG. 2;
- (7) FIG. 6 is an exploded structural diagram of the guiding assembly shown in FIG. 2 from another perspective;
- (8) FIG. 7 is a planar structural diagram of a needle inlet end of a needle guiding hole according to the first embodiment of the present application;
- (9) FIG. 8 is a schematic structural diagram of a guiding assembly according to a second embodiment of the present application;
- (10) FIG. 9 is an exploded structural diagram of a transperineal puncture guiding bracket according to a third embodiment of the present application;
- (11) FIG. 10 is an exploded structural diagram of the transperineal puncture guiding bracket shown in FIG. 9 from another perspective;
- (12) FIG. 11 is schematic structural diagram of a transperineal puncture guiding bracket according to a fourth embodiment of the present application.

DETAILED DESCRIPTION

(13) To explain objects, technical solutions and advantages of the present application more clearly, the present application will be further described with reference to the accompanying drawings and embodiments in the following. It should be understood that, the specific embodiments described here are only for explanation, but not for limitation to the present application. And, the

embodiments and features in the embodiments of the present application can be combined with each other without conflict.

(14) FIG. 1 shows a schematic structural diagram of a transperineal puncture guiding bracket **100** guiding a puncture needle **200** according to a first embodiment of the present application, and FIG. 2 shows an exploded structural diagram of the transperineal puncture guiding bracket **100**. As shown in FIG. 1 and FIG. 2, the transperineal puncture guiding bracket **100** comprises a probe fixing assembly **10** and a guiding assembly **20**. The probe fixing assembly **10** is used for fixed installation with an intracavitary ultrasound probe. The guiding assembly **20** is detachably installed on the probe fixing assembly **10**. The guiding assembly **20** provides a plurality of needle guiding holes **23** along a puncture direction, which are vertically equidistant and parallel to each other, used to guide the puncture needle **200** to pass through a needle guiding hole **23** for biopsy puncture. The probe fixing assembly **10** further comprises an upper fixing member **11**, a lower fixing member **12**, and a mounting plate **13**. The upper fixing member **11** and the lower fixing member **12** work together to hold outer surface of the intracavitary ultrasound probe for fixation. The mounting plate **13** is set on the upper fixing member **11** for detachable installation of the guiding assembly **20**. The guiding assembly **20** further comprises a needle grooved plate **21** and a cover plate **22**, which are also detachably combined to form the plurality of vertically equidistant and parallel needle guiding holes **23**. The transperineal puncture guiding bracket **100** according to the above embodiment of the present application can guide puncture needles **200** of different specifications by replacing the guiding assembly **20** with needle holes **23** of different specifications, without a need of replacing the entire transperineal puncture guiding bracket **100**, which facilitates surgical operations of doctors. With the transperineal puncture guiding bracket **100** according to the above embodiment of the present application, the puncture needle **200** can be easily separated from the transperineal puncture guiding bracket **100** during surgery by separating the cover plate **22** from the needle grooved plate **21** of the guiding assembly **20**, making the doctor's operation more flexible.

(15) FIG. 3 and FIG. 4 respectively show exploded structural diagrams of the probe fixing assembly **10** from different perspectives. As shown in FIG. 3 and FIG. 4, the probe fixing assembly **10** comprises the upper fixing member **11**, the lower fixing member **12**, and the mounting plate **13**. The upper fixing member **11** has a roughly arc shaped outer contour that matches the outer surface of the intracavitary ultrasound probe. The mounting plate **13** is fixedly set on one side along the puncture direction on top of the upper fixing member **11**, and can be integrated molded with the upper fixing member **11**. A positioning groove **115** that matches a positioning convex bar on the intracavitary ultrasound probe is formed on a lower surface of the upper fixing member **11**.

Rotation of the upper fixing member **11** can be restricted by aligning and inserting the positioning groove **115** with the positioning convex bar on the intracavitary ultrasound probe. Upper wrapping surfaces **113a** and **113b** are formed on front and rear ends along the puncture direction of the lower surface of the upper fixing member **11** respectively, which are used for fitting the upper surface of the intracavitary ultrasound probe. In addition, there are shaft sleeves **111a** and **111b** at the front and rear ends on one side of the upper fixing member **11**, and a notch **1111** is formed at an inlet end of one shaft sleeve **111a**. On the other side opposite to the two shaft sleeves **111a** and **111b** of the upper fixing member **11**, there are also equipped with two limiting buckles **112a** and **112b** that are spaced forward and backward. Correspondingly, the lower fixing member **12** also has a roughly arc shaped outer contour that matches the outer surface of the intracavitary ultrasound probe. Two lower wrapping surfaces **125a** and **125b** are formed at front and rear ends of the upper surface of the lower fixing member **12** respectively, which are fitted with the outer surface of the intracavitary ultrasound probe. In addition, a connecting rod **121** is formed on the lower fixing member **12** on one side corresponding to the two shaft sleeves **111a** and **111b** of the upper fixing member **11**, and two rotating shafts **122a** and **122b** that rotationally fit with the two shaft sleeves **111a** and **111b** extend coaxially from both ends of the connecting rod **121**. A semi-cylindrical protrusion **1221** is provided at the end of the rotating shaft **122a** corresponding to the shaft sleeve **111a** having a notch

1111. After the rotating shaft **122b** of the lower fixing member **12** is aligned with and inserted into the shaft sleeve **111b** of the upper fixing member **11**, the lower fixing member **12** is rotated so as to align and insert the semi-cylindrical protrusion **1221** on the rotating shaft **122a** into the notch **1111** on the shaft sleeve **111a** of the upper fixing member **11**, then the lower fixing member **12** is further rotated around the rotating shafts **122a** and **122b** till an indicator protrusion **1211** on the connecting rod **121** turns to the outside, thus the upper fixing member **11** and the lower fixing member **12** are rotationally connected on the one side (see FIG. 2). On the other side of the lower fixing member **12**, a handheld unit **124** extends upwards from the lower fixing member **12**, and two retaining rings **123a** and **123b** are formed on the handheld unit **124**, to match the two limiting buckles **112a** and **112b** on the corresponding other side of the upper fixing member **11**. After the upper wrapping surfaces **113a** and **113b** of the upper fixing member **11** are tightly attached to the upper surface of the intracavitary ultrasound probe with the positioning convex bar on the upper surface of the intracavitary ultrasound probe being aligned and embedded into the positioning groove **115**, the lower fixing member **12** is rotated by the handheld unit **124** around axis of the rotating shafts **122a** and **122b** relative to the upper fixing member **11**, till the lower wrapping surfaces **125a** and **125b** of the lower fixing member **12** are tightly attached to the lower surface of the intracavitary ultrasound probe. Then, the two retaining rings **123a** and **123b** are interlocked with the two limiting buckles **112a** and **112b** by force acting on the handheld unit **124** to make the handheld unit **124** generating elastic deformation adapting to the shape of the intracavitary ultrasound probe, thus the upper fixing member **11** and the lower fixing member are clasped on the corresponding other side to tightly hold the intracavitary ultrasound probe. By reverse force acting on the handheld unit **124**, the two retaining rings **123a** and **123b** on the handheld unit **124** can be released from the two limiting buckles **112a** and **112b**, and then the intracavitary ultrasound probe can be separated by reversibly rotating the lower fixing member **12**. Due to a certain deformation curvature of the handheld unit **124**, it can withstand clamping forces of different deformation amounts, and therefore the probe fixing assembly **10** can be compatible with intracavitary ultrasound probes with different diameters within a certain range. Moreover, there is avoidance design that does not contact with the intracavitary ultrasound probe between the respective upper wrapping surfaces **113a** and **113b** of the upper fixing member **11** and the respective lower wrapping surfaces **125a** and **125b** of the lower fixing member **12**. Thus warping of the probe fixing assembly can be avoided after installation on the intracavitary ultrasound probe.

(16) Again as shown in FIG. 3 and FIG. 4, the mounting plate **13** is fixedly set on one side along the puncture direction on top of the upper fixing member **11**, having a first side surface **131** and a second side surface **132** opposite to the first side surface **131**. There is a through-hole **133** in the middle of the mounting plate **13** that connects the first side surface **131** and the second side surface **132**, and a first elastic buckle **134** is set in the through-hole **133** for clamping the needle grooved plate **21** of the guiding assembly **20**. The first elastic buckle **134** has a first buckling position **1341** extending out from the first side surface **131** and a first operating part **1342** extending out from the second side surface **132**. A second elastic buckle **136** is set in the middle on top of the mounting plate **13**, which is used for clamping the cover plate **22** of the guiding assembly **20**. According to different embodiments of the present application, the second elastic buckle **136** can also be set at other positions on upper portion of the mounting plate **13**, not limited to the top of the mounting plate **13** in the illustrated embodiment. The second elastic buckle **136** also has a second buckling position **1361** extending out from the first side surface **131** and a second operating part **1362** extending out from the second side surface **132**. The mounting plate **13** is also equipped with two first hooks **135a** and **135b** on its first side surface **131**, which extend out from the first side surface **131** at front and rear ends on the top of the first side surface **131** respectively, for hanging the needle grooved plate **21** of the guiding assembly **20**. Similarly, according to different embodiments of the present application, the first hooks **135a** and **135b** may also be provided at other positions on the upper portion of the mounting plate **13**, not limited to the top of the mounting plate **13** in the

illustrated embodiment. There are also two limiting grooves **114a** and **114b** on the top of the upper fixing member **11** adjacent to the mounting plate **13**, which are used to install and position the needle grooved plate **21** of the guiding assembly **20** in cooperation with the mounting plate **13**. Regarding specific implementation of the detachable combination structure between the mounting plate **13** and the guiding assembly **20**, a more detailed description will be provided in conjunction with the description of the guiding assembly **20** in the below.

(17) FIG. 5 and FIG. 6 show exploded structural diagrams of the guiding assembly **20** from different perspectives respectively. As shown in FIG. 5 and FIG. 6, the guiding assembly **20** is composed of a needle grooved plate **21** and a cover plate **22** that are detachably combined with each other. The needle grooved plate **21** has a first side surface **211** and a second side surface **212** opposite to the first side surface **211**. On the first side surface **211** of the needle grooved plate **21**, there are a plurality of needle guiding grooves **213** which are vertically equidistant and parallel to each other. The needle guiding grooves **213** pass through the front and rear ends of the needle grooved plate **21** along the puncture direction, and an insertion guiding surface **2131** is formed at least at the needle inlet end (as shown in FIG. 7) to facilitate needle insertion. The insertion guiding surface **2131** is preferably a guiding slope. The cover plate **22** has a first side surface **221** and a second side surface **222** opposite to the first side surface **221**. After the cover plate **22** is combined with the needle grooved plate **21**, the second side surface **222** of the cover plate **22** is tightly adhered to the first side surface **211** of the needle grooved plate **21**, closing open sides of the plurality of needle guiding grooves **213** to form the plurality of needle guiding holes **23**. As shown in FIG. 7, each of the needle guiding grooves **213** is preferably a U-shaped groove, which has a half-circle right limiting cambered surface **2132**, an upper limiting plat surface **2133**, and a lower limiting plat surface **2134** when viewed from the puncture direction, plus the second side surface **222** of the cover plate **22** serving as a left limiting plat surface to form a D-shaped needle guiding hole **23**, which limits position of the puncture needle **200** up, down, left, and right, so that the puncture needle **200** can only move axially.

(18) As shown in FIG. 5 and FIG. 6 again, two first limiting feet **214a** and **214b** are provided at a lower portion (preferably at the bottom) of the needle grooved plate **21**, which extend out from the first side surface **211** at front and rear ends of the needle grooved plate **21** respectively, for insertion into the limiting grooves **114a** and **114b** on top of the upper fixing member **11**. There are further limiting holes **215a** and **215b** on the two first limiting feet **214a** and **214b** respectively, for insertion and installation of two second limiting feet **223a** and **223b** provided at a corresponding lower portion (preferably at the bottom) of the cover plate **22**. Two second hooks **217a** and **217b** are provided at an upper portion of the needle grooved plate **21**, which extend out from the first side surface **211** at the front and rear ends of the needle grooved plate **21** respectively. Corresponding to the second hooks **217a** and **217b**, two second hanging holes **224a** and **224b** are formed at the front and rear ends of the cover plate **22**, which are used for hanging the second hooks **217a** and **217b**. After the second hanging holes **224a** and **224b** of the cover plate **22** are aligned and hung with the second hooks **217a** and **217b** of the needle grooved plate **21**, the second limiting feet **223a** and **223b** at the bottom of the cover plate **22** are inserted into the limiting holes **215a** and **215b** on the first limiting feet **214a** and **214b** at the bottom of the needle grooved plate **21** by moving downwards the cover plate **22** with its second side surface **222** closely contacting the first side surface **211** of the needle grooved plate **21**, thus the cover plate **22** is combined with the needle grooved plate **21**. Reverse operation can also separate the cover plate **22** from the needle grooved plate **21**. In addition, two first hanging holes **216a** and **216b** spaced back and forth are formed at the upper portion of the needle grooved plate **21**, which pass through the first side surface **211** to the second side surface **212** of the needle grooved plate **21**. These two first hanging holes **216a** and **216b** are matched with the two first hooks **135a** and **135b** at the top of the mounting plate **13**, for the two first hooks **135a** and **135b** to be hung in. A first limiting buckle **218** is also formed in the middle of the second side surface **212** of the needle grooved plate **21**, which is used to engage with

the first elastic buckle **134** of the mounting plate **13**. On the first side surface **221** of the cover plate **22**, there are also two handheld members **226a** and **226b** extending out from the first side surface **221** at the front and rear ends of the cover plate **22**, which are convenient for operation. A process of installing the guiding assembly **20** composed of the combined needle grooved plate **21** and the cover plate **22** onto the probe fixing assembly **10** is as follows: pressing the second operating part **1362** of the second elastic buckle **136** at the top of the mounting plate **13** to lift the second buckling position **1361** of the second elastic buckle **136**; then, aligning and hanging the first hanging holes **216a** and **216b** on the upper portion of the needle grooved plate **21** with the first hooks **135a** and **135b** on the top of the mounting plate **13**, and moving downwards the needle grooved plate **21** with the second side surface **212** of the needle grooved plate **21** being closely attached to the first side surface **131** of the mounting plate **13**, and inserting the first limiting feet **214a** and **214b** on the lower portion of the needle grooved plate **21** into the limiting grooves **114a** and **114b** on top of the upper fixing member **11**, and engaging the first limiting buckle **218** in the middle of the second side surface **212** of the needle grooved plate **21** with the first elastic buckle **1341** in the middle of the mounting plate **13**; and then, release the pressing on the second operating part **1362** of the second elastic buckle **136** at the top of the mounting plate **13** to make the second buckling position **1361** of the second elastic buckle **136** press against a top surface **225** of the cover plate **22**. Thus the guiding assembly **20** is installed and positioned on the probe fixing assembly **10**. Except that the needle grooved plate **21** is firstly combined with the cover plate **22** and then is installed onto the probe fixing assembly **10** as described above, the transperineal puncture guiding bracket **100** according to the embodiments of the present application may also be configured with the needle grooved plate **21** being firstly assembled with the mounting plate **13** of the probe fixing assembly **10** and then being combined with the cover plate **22**.

(19) According to the above embodiment of the present application, the lower portion of the needle grooved plate **21** is detachably combined with the upper fixing member **11** by a first vertical insertion structure composed of the first limiting feet **214a** and **214b** and the limiting grooves **114a** and **114b**, the upper portion of the needle grooved plate **21** is detachably hung with the upper portion of the mounting plate **13** by a first hanging structure composed of the first hanging hole **216a** and **216b** and the first hooks **135a** and **135b**, and the middle portion of the second side surface **212** of the needle grooved plate **21** is detachably buckled with the middle portion of the first side surface **131** of the mounting plate **13** by a first buckling structure composed of the first limiting buckle **218** and the first elastic buckle **134**, thereby the second side surface **212** of the needle grooved plate **21** is detachably attached to the first side surface **131** of the mounting plate **13**. Wherein, the first vertical insertion structure and the first hanging structure are used in combination to limit a vertical downward and left and right lateral movement of the needle grooved plate **21** relative to the mounting plate **13**, ensuring that the second side surface **212** of the needle grooved plate **21** is tightly adhered to the first side surface **131** of the mounting plate **13**, and the first buckling structure is used to limit a vertical upward movement of the needle grooved plate **21** relative to the mounting plate **13**. According to the above embodiment of the present application, the lower portion of the cover plate **22** is detachably combined with the lower portion of the needle grooved plate **21** by a second vertical insertion structure composed of the second limiting feet **223a** and **223b** and the limiting holes **215a** and **215b** on the first limiting feet **214a** and **214b**, the upper portion of the cover plate **22** is detachably hung with the upper portion of the needle grooved plate **21** by a second hanging structure composed of the second hanging holes **224a** and **224b** and the second hooks **217a** and **217b**, and the cover plate **22** is further detachably buckled with the mounting plate **13** by a second buckling structure composed of the top surface **225** of the cover plate **21** and the second elastic buckle **136** on the mounting plate **13**, thereby the cover plate **22** is detachably combined with the needle grooved plate **21**, with the second side surface **222** of the cover plate **22** being in contact with the first side surface **211** of the needle grooved plate **21** to close the plurality of needle guiding grooves **213** to form the plurality of needle guiding holes **23**.

Wherein, the second vertical insertion structure and the second hanging structure are used in combination to limit a vertical downward and left and right lateral movement of the cover plate **22** relative to the needle grooved plate **21**, ensuring that the second side surface **222** of the cover plate **22** is tightly adhered to the first side surface **211** of the needle grooved plate **21**, and the second buckling structure is used to limit a vertical upward movement of the cover plate **22** relative to the needle grooved plate **21**. In this way, in the transperineal puncture guiding bracket **100** according to the above embodiment of the present application, not only the guiding assembly **20** and the probe fixing assembly **10** can be detachable and separated, but also the cover plate **22** and the needle grooved plate **21** of the guiding assembly **20** can be detachable and separated, and after being assembled, they can also provide a stable structure to guide the puncture needle **200** to perform precise biopsy.

(20) According to the above embodiment of the present application, the puncture needle **200** can be separated from the transperineal puncture guiding bracket **100**. During a puncture surgery, the puncture needle **200** can be easily separated from the transperineal puncture guiding bracket **100** by operations of pressing the second operating part **1362** of the second elastic buckle **136** at the top of the mounting plate **13** to lift the second buckle position **1361** of the second elastic buckle **136** and releasing pressure to the cover plate **22**, and then pulling up the cover plate **22** through the handheld members **226a** and **226b** till the second limiting feet **223a** and **223b** at the lower portion of the cover plate **22** is removed from the limiting holes **215a** and **215b** at the lower portion of the needle grooved plate **21**, and then detaching the second hanging holes **224a** and **224b** at the upper portion of the cover plate **22** from the second hooks **217a** and **217b** of the needle grooved plate **21**, and then removing the cover plate **22** laterally.

(21) According to the above embodiment of the present application, the transperineal puncture guiding bracket **100** can be replaced with different needle grooved plates **21** according to puncture needles **200** of different specifications. Firstly, the cover plate **22** can be removed referring to the separation operations as described above. Then the needle grooved plate **21** can be removed by operations of pressing the first operating part **1342** of the first elastic buckle **134** in the middle of the mounting plate **13** to release engagement of the first buckling position **1341** of the first elastic buckle **134** with the limiting buckle **218** of the needle grooved plate **21**, and then pulling up the needle grooved plate **21** till the first limiting feet **214a** and **214b** at the lower portion of the needle grooved plate **21** being removed from the limiting grooves **114a** and **114b** on top of the upper fixing member **11**, and then detaching the first hanging holes **216a** and **216b** at the upper portion of the needle grooved plate **21** from the first hooks **135a** and **135b** of the mounting plate **13**, and then removing the needle grooved plate **21** laterally. Finally, a new needle grooved plate can be installed to replace the needle grooved plate **21** referring to the installation process of the needle grooved plate **21** mentioned earlier.

(22) In the transperineal puncture guiding bracket **100** according to the above embodiment of the present application, the needle grooved plate **21** and the cover plate **22** that constitute the guiding assembly **20** are both made of plastic materials with low cost. According to a second embodiment of the present application, as shown in FIG. 8, a guiding assembly **20'** can be made of metal materials, comprising a metal needle grooved plate **21'** and a metal cover plate **22'**. Both of them can be combined with detachable structures that are basically the same as the needle grooved plate **21** and the cover plate **22** of the aforementioned embodiment to form a plurality of parallel and equidistant metal needle guiding holes **23'**. A biggest advantage of the metal guiding assembly **20'** is that it can prevent the puncture needle from scratching wall of the needle guiding holes **23'** and generating debris.

(23) FIG. 9 and FIG. 10 illustrate exploded structural diagrams of a transperineal puncture guiding bracket **300** according to a third embodiment of the present application respectively. As shown in FIG. 9 and FIG. 10, the transperineal puncture guiding bracket **300** has a similar structure to that of the transperineal puncture guiding bracket **100** in the first embodiment mentioned above, and also

comprises a probe fixing assembly **310** and a guiding assembly **320**. Similarly, the probe fixing assembly **310** further comprises an upper fixing member **311**, a lower fixing member **312**, and a mounting plate **313**. The upper fixing member **311** and the lower fixing member **312** work together to hold outer surface of the intracavitary ultrasound probe for fixation, and the mounting plate **313** is provided on the upper fixing member **311** for detachable installation of the guiding assembly **320**. The guiding assembly **320** further comprises a needle grooved plate **321** and a cover plate **322**. The needle grooved plate **321** has a first side surface **3211** and a second side surface **3212** opposite to the first side surface **3211**, and the first side surface **3211** of the needle grooved plate **321** is provided with a plurality of vertically equidistant and parallel needle guiding grooves **3213**. The cover plate **322** has a first side surface **3221** and a second side surface **3222** opposite to the first side surface **3221**. The cover plate **322** is also detachably combined with the needle grooved plate **321** to tightly adhere the second side surface **3222** of the cover plate **322** to the first side surface **3211** of the needle grooved plate **3211**, thereby closing open sides of the plurality of needle guiding grooves **3213** to form a plurality of needle guiding holes for guiding the puncture needle to perform biopsy puncture.

(24) As shown in FIG. 9 and FIG. 10, there is a through-hole **3133** in the middle of the mounting plate **313** that connects a first side surface **3131** and a second side surface **3132** of the mounting plate **313**, and a first elastic buckle **3134** is set in the through-hole **3133** for clamping the first limiting buckle **3218** in the middle of the second side surface **3212** of the needle grooved plate **21**. The first elastic buckle **3134** has a first buckling position **3135** that extends out of the first side surface **3131** and engages with the first limiting buckle **3218**, and a first operating part **3136** that extends out of the second side surface **3132** for users to operate and release the engagement between the first buckling position **3135** and the first limiting buckle **3218**. The mounting plate **313** is equipped with two first hooks **3137a** and **3137b** on its first side surface **3131**, which extend out from the first side surface **3131** at front and rear ends at an upper portion (preferably at the top) of the first side surface **3131** respectively, for installation with two first hanging holes **3216a** and **3216b** at a corresponding upper portion of the needle grooved plate **321**. There are two limiting grooves **3111a** and **3111b** on top of the upper fixing member **311** adjacent to the mounting plate **313**, which are used for vertical insertion of two first limiting feet **3214a** and **3214b** extending out of the first side surface **3211** at the front and rear ends of the needle grooved plate **321** respectively. Furthermore, there are limiting holes **3215a** and **3215b** on the two first limiting feet **3214a** and **3214b** of the needle grooved plate **321** respectively, for insertion and installation of two second limiting feet **3223a** and **3223b** provided at a corresponding lower portion (preferably at the bottom) of the cover plate **322**. Two second hooks **3217a** and **3217b** are provided at an upper portion of the needle grooved plate **321**, which extend out from the first side surface **3211** at the front and rear ends of the needle grooved plate **321** respectively, for hanging with corresponding second hanging holes **3224a** and **3224b** at the front and rear ends of the cover plate **322**. A difference between the transperineal puncture guiding bracket **300** shown in FIG. 9 and FIG. 10 and the transperineal puncture guiding bracket **100** in the aforementioned first embodiment of the present application is that, a second limiting buckle **3219** is set in the middle of the upper portion of the first side surface **3211** of the needle grooved plate **321**, and a through-hole **3225** is opened in the middle of the upper portion of the cover plate **322**, which passes through the first side surface **3221** and the second side surface **3222** of the cover plate **322**, and a second elastic buckle **3226** is set in the through-hole **3225**, which is used to engage with the second limiting buckle **3219** on the first side surface **3211** of the needle grooved plate **321**. The second elastic buckle **3226** has a second buckling position **3227** that extends out of the second side surface **3222** and engages with the second limiting buckle **3219**, and a second operating part **3228** that extends out of the first side surface **3221** for users to operate and release the engagement between the second buckling position **3227** and the second limiting buckle **3219**. In the transperineal puncture guiding bracket **300** according to the third embodiment of the present application, the lower portion of the needle grooved plate **321** is

detachably combined with the upper fixing member **311** by a first vertical insertion structure composed of the first limiting feet **3214a** and **3214b** and the limiting grooves **3111a** and **3111b**, the upper portion of the needle grooved plate **321** is detachably hung with the upper portion of the mounting plate **313** by a first hanging structure composed of the first hanging hole **3216a** and **3216b** and the first hooks **3137a** and **3137b**, and the middle portion of the second side surface **3212** of the needle grooved plate **321** is detachably buckled with the middle portion of the first side surface **3131** of the mounting plate **313** by a first buckling structure composed of the first limiting buckle **3218** and the first elastic buckle **3134**, thereby the second side surface **3212** of the needle grooved plate **321** is detachably attached to the first side surface **3131** of the mounting plate **313**. The lower portion of the cover plate **322** is detachably combined with the lower portion of the needle grooved plate **321** by a second vertical insertion structure composed of the second limiting feet **3223a** and **3223b** and the limiting holes **3215a** and **3215b** on the first limiting feet **3214a** and **3214b**, the upper portion of the cover plate **322** is detachably hung with the upper portion of the needle grooved plate **321** by a second hanging structure composed of the second hanging holes **3224a** and **3224b** and the second hooks **3217a** and **3217b**, and the cover plate **322** is further detachably buckled with the first side surface **3211** of the needle grooved plate **321** by a second buckling structure composed of the second elastic buckle **3226** and the second limiting buckle **3219**, thereby the cover plate **322** is detachably combined with the needle grooved plate **321**, with the second side surface **3222** of the cover plate **322** being in contact with the first side surface **3211** of the needle grooved plate **321** to close the plurality of needle guiding grooves **3213** to form the plurality of needle guiding holes. In this way, in the transperineal puncture guiding bracket **300** according to the third embodiment of the present application, not only the guiding assembly **320** and the probe fixing assembly **310** can be detachable and separated, but also the cover plate **322** and the needle grooved plate **321** of the guiding assembly **320** can be detachable and separated, and after being assembled, they can also provide a stable structure to guide the puncture needle to perform precise biopsy.

(25) FIG. **11** shows an exploded structural diagram of a transperineal puncture guiding bracket **400** according to a fourth embodiment of the present application. As shown in FIG. **11**, the transperineal puncture guiding bracket **400** has structure that is basically the same as the transperineal puncture guiding bracket **100** in the first embodiment mentioned above, and also comprises a probe fixing assembly **410** and a guiding assembly **420**. Similarly, the probe fixing assembly **410** further comprises an upper fixing member **411**, a lower fixing member **412**, and a mounting plate **413**. The upper fixing member **411** and the lower fixing member **412** work together to hold outer surface of the intracavitary ultrasound probe for fixation. The mounting plate **413** is provided on the upper fixing member **411** for detachable installation of the guiding assembly **420**. The guiding assembly **420** further comprises a needle grooved plate **421** and a cover plate **422**. The needle grooved plate **421** has a first side surface **4211** and a second side surface **4212** opposite to the first side surface **4211**, and the first side surface **4211** of the needle grooved plate **421** is provided with a plurality of vertically equidistant and parallel needle guiding grooves **4213**. The cover plate **422** has a first side surface **4221** and a second side surface **4222** opposite to the first side surface **4221**. The cover plate **422** is also detachably combined with the needle grooved plate **421** to tightly adhere the second side surface **4222** of the cover plate **422** to the first side surface **4211** of the needle grooved plate **421**, thereby closing open sides of the plurality of needle guiding grooves **4213** to form a plurality of needle guiding holes for guiding the puncture needle to perform biopsy puncture.

(26) Further as shown in FIG. **11**, a through-hole **4133** is formed in the middle of the mounting plate **413** that connects the first side surface **4131** and the second side surface **4132**, and a first elastic buckle **4134** is set in the through-hole **4133** for clamping the first limiting buckle (not visible in the figure) in the middle of the second side surface **4212** of the needle grooved plate **421**. The first elastic buckle **4134** has a first buckling position **4135** that extends out of the first side surface **4131** and engages with the first limiting buckle, and a first operating part that extends out

of the second side surface **4132** (not visible in the figure) for users to operate and release the engagement between the first buckling position **4135** and the first limiting buckle. The mounting plate **413** is equipped with two first hooks **4136a** and **4136b** on its first side surface **4131**, which extend out from the first side surface **4131** at front and rear ends at an upper portion (preferably at the top) of the first side surface **4131** respectively, for installation with two first hanging holes **4216a** and **4216b** at a corresponding upper portion of the needle grooved plate **421**. There are two first limiting grooves **4111a** and **4111b** on top of the upper fixing member **411** adjacent to the mounting plate **413**, which are used for vertical insertion of two first limiting feet **4214a** and **4214b** provided at the front and rear ends of the lower portion (preferably at the bottom) of the needle grooved plate **321** respectively. Furthermore, two second hooks **4217a** and **4217b** are provided at an upper portion of the needle grooved plate **421**, which extend out from the first side surface **4211** at the front and rear ends of the needle grooved plate **421** respectively, for hanging with corresponding second hanging holes **4224a** and **4224b** at the front and rear ends of the cover plate **422**. A difference between the transperineal puncture guiding bracket **400** shown in FIG. **11** and the transperineal puncture guiding bracket **100** in the aforementioned first embodiment of the present application is that, there are two second limiting grooves **4112a** and **4112b** on top of the upper fixing member **411** adjacent the two first limiting grooves **4111a** and **4111b** respectively, for vertical insertion of two second limiting feet (not visible in the figure) at the front and rear ends of the lower portion (preferably at the bottom) of the cover plate **422**. The other difference between the transperineal puncture guiding bracket **400** shown in FIG. **11** and the transperineal puncture guiding bracket **100** in the aforementioned first embodiment of the present application is that, a second elastic buckle **4215** is provided in the middle of the upper portion (preferably the top) of the needle grooved plate **421**. The second elastic buckle **4215** has a second buckling position **4218** extending out of the first side surface **4211** and a second operating part **4219** extending out of the second side surface **4212**. The second buckling position **4216** of the second elastic buckle **4215** presses against the top surface **4225** of the cover plate **422** to form a detachable buckling installation. By operating the second operating part **4219**, buckling by the second buckling position **4216** to the top surface **4225** of the cover plate **322** can be released.

(27) In the transperineal puncture guiding bracket **400** according to the fourth embodiment of the present application, the lower portion of the needle grooved plate **421** is detachably combined with the upper fixing member **411** by a first vertical insertion structure composed of the first limiting feet **4214a** and **4214b** and the first limiting grooves **4111a** and **4111b**, the upper portion of the needle grooved plate **421** is detachably hung with the upper portion of the mounting plate **413** by a first hanging structure composed of the first hanging hole **4216a** and **4216b** and the first hooks **4136a** and **4136b**, and the middle portion of the second side surface **4212** of the needle grooved plate **421** is detachably buckled with the middle portion of the first side surface **4131** of the mounting plate **413** by a first buckling structure composed of the first limiting buckle (not visible in the figure) and the first elastic buckle **4134**, thereby the second side surface **4212** of the needle grooved plate **421** is detachably attached to the first side surface **4131** of the mounting plate **413**. The lower portion of the cover plate **422** is detachably combined with the lower portion of the needle grooved plate **421** by a second vertical insertion structure composed of the second limiting feet (not visible in the figure) and the second limiting grooves **4112a** and **4112b**, the upper portion of the cover plate **422** is detachably hung with the upper portion of the needle grooved plate **421** by a second hanging structure composed of the second hanging holes **4224a** and **4224b** and the second hooks **4217a** and **4217b**, and the upper portion of the cover plate **422** is further detachably buckled with the needle grooved plate **421** by a second buckling structure composed of the top surface **4225** of the cover plate **422** and the second elastic buckle **4215** of the needle grooved plate **421**, thereby the cover plate **422** is detachably combined with the needle grooved plate **421**, with the second side surface **4222** of the cover plate **422** being in contact with the first side surface **4211** of the needle grooved plate **421** to close the plurality of needle guiding grooves **4213** to form the plurality of

needle guiding holes. In this way, in the transperineal puncture guiding bracket **400** according to the fourth embodiment of the present application, not only the guiding assembly **420** and the probe fixing assembly **410** can be detachable and separated, but also the cover plate **422** and the needle grooved plate **421** of the guiding assembly **420** can be detachable and separated, and after being assembled, they can also provide a stable structure to guide the puncture needle to perform precise biopsy.

(28) The above is only the preferred embodiments of the present application, and is not intended to limit the present application. Any modifications, equivalent substitutions and improvements made within the spirit and principles of the present application should be included within the protection scope of the present application.

Claims

1. A transperineal puncture guiding bracket, comprising a probe fixing assembly and a guiding assembly, wherein the probe fixing assembly is fixedly installed with an intracavitary ultrasound probe, the guiding assembly provides a plurality of vertically distributed and parallel needle guiding holes along a puncture direction, characterized in that, a mounting plate is set on top of the probe fixing assembly, and the guiding assembly further comprises a needle grooved plate and a cover plate, the needle grooved plate has a first side surface and a second side surface opposite to the first side surface, with the first side surface of the needle grooved plate being provided with a plurality of vertically distributed and parallel needle guiding grooves; and a lower portion of the needle grooved plate is detachably combined with the top of the probe fixing assembly adjacent to the mounting plate by a first vertical insertion structure, an upper portion of the needle grooved plate is detachably hung with an upper portion of the mounting plate by a first hanging structure, and the second side surface of the needle grooved plate is detachably buckled with a first side surface of the mounting plate by a first buckling structure, thereby the second side surface of the needle grooved plate is detachably attached to the first side surface of the mounting plate; and a lower portion of the cover plate is detachably combined with the lower portion of the needle grooved plate or the top of the probe fixing assembly by a second vertical insertion structure, an upper portion of the cover plate is detachably hung with the upper portion of the needle grooved plate by a second hanging structure, and the cover plate is further detachably buckled with the upper portion of the mounting plate, the upper portion of the needle grooved plate or the top of the probe fixing assembly through a second buckling structure, thereby a second side surface of the cover plate is detachably attached to the first side surface of the needle grooved plate to close the plurality of needle guiding grooves to form the plurality of needle guiding holes.
2. The transperineal puncture guiding bracket of claim 1, characterized in that the first vertical insertion structure comprises first limiting feet provided at the lower portion of the needle grooved plate which extend out from the first side surface of the needle grooved plate and limiting grooves formed at the top of the probe fixing assembly for insertion of the first limiting feet; and the second vertical insertion structure comprises second limiting feet set at the lower portion of the cover plate and limiting holes on the first limiting feet of the needle grooved plate for insertion of the second limiting feet.
3. The transperineal puncture guiding bracket of claim 1, characterized in that the first vertical insertion structure comprises first limiting feet provided at the lower portion of the needle grooved plate and first limiting grooves set at the top of the probe fixing assembly for insertion of the first limiting feet; and the second vertical insertion structure comprises second limiting feet set at the lower portion of the cover plate and second limiting grooves formed at the top of the probe fixing assembly for insertion of the second limiting feet.
4. The transperineal puncture guiding bracket of claim 1, characterized in that the first hanging structure comprises first hanging holes at the upper portion of the needle grooved plate and first

hooks at the upper portion of the mounting plate which extend out from the first side surface of the mounting plate to hang into the first hanging holes; and the second hanging structure comprises second hanging holes at the upper portion of the cover plate and second hooks at the upper portion which extend out from the first side surface of the needle grooved plate to hang into the second hanging holes.

5. The transperineal puncture guiding bracket of claim 1, characterized in that the first buckling structure comprises a first limiting buckle set in the middle of the second side surface of the needle grooved plate and a first elastic buckle set in the middle of the mounting plate, wherein a through-hole is set in the middle of the mounting plate that connects the first side surface and a second side surface of the mounting plate, and the first elastic buckle is set inside the through-hole, the first elastic buckle has a first buckling position that is engaged with the first limiting buckle and a first operating part that extends out of the second side surface of the mounting plate for releasing engagement between the first buckling position and the first limiting buckle.

6. The transperineal puncture guiding bracket of claim 1, characterized in that the second buckling structure comprises a second elastic buckle set at the upper portion of the needle grooved plate, wherein the second elastic buckle has a second buckling position for pressing a top surface of the cover plate and a second operating part for releasing the second buckling position from pressing the top surface of the cover plate.

7. The transperineal puncture guiding bracket of claim 1, characterized in that the second buckling structure comprises a second elastic buckle set at the upper portion of the mounting plate, wherein the second elastic buckle has a second buckling position for pressing a top surface of the cover plate and a second operating part for releasing the second buckling position from pressing the top surface of the cover plate.

8. The transperineal puncture guiding bracket of claim 1, characterized in that the second buckling structure comprises a second limiting buckle set at the upper portion of the first side surface of the needle grooved plate and a second elastic buckle at the corresponding upper portion of the cover plate, wherein a through-hole is set at the upper portion of the cover plate that connects a first side surface and the second side surface of the cover plate, and the second elastic buckle is set inside the through-hole, the second elastic buckle has a second buckling position that is engaged with the second limiting buckle and a second operating part that extends out of the first side surface of the cover plate for releasing engagement between the second buckling position and the second limiting buckle.

9. The transperineal puncture guiding bracket of claim 1, characterized in that the probe fixing assembly comprises an upper fixing member and a lower fixing member, wherein the upper fixing member and the lower fixing member work together to hold outer surface of the intracavitary ultrasound probe, and the mounting plate is set on top of the upper fixing member.

10. The transperineal puncture guiding bracket of claim 9, characterized in that upper wrapping surfaces are formed on a lower surface of the upper fixing member for fitting upper surface of the intracavitary ultrasound probe, and lower wrapping surfaces are formed on an upper surface of the lower fixing member for fitting lower surface of the intracavitary ultrasound probe, and the upper fixing member and the lower fixing member are rotationally connected on one side and buckled on the opposite side to tightly hold the intracavitary ultrasound probe through the upper wrapping surfaces and the lower wrapping surfaces.
