

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403509
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Zhou; Yu Xin et al.

In-situ state of fluid sensor

Abstract

The invention provides a sensor, which includes a sensing surface; a housing including a recess, the sensing surface is located at the bottom of the recess, and the recess includes at least one side wall and an opening circumferentially surrounding the sensing surface. A compressed fluid nozzle is provided in the at least one side wall to nozzle compressed fluid from the compressed fluid nozzle to force the substance on the sensing surface to leave from the opening. This design makes it possible to refresh in situ with good efficiency without involving additional mechanical parts, thus reducing the risk of sensing surface damage, such as scratch wear, in the presence of wear particles.

Inventors: Zhou; Yu Xin (Shanghai, CN), Pan; Yunfei (Shanghai, CN), Yi; Xing (Shanghai, CN), Han; Bo (Shanghai, CN), Lang; Defeng (Delft, NL)

Applicant: Aktiebolaget SKF (Gothenburg, SE)

Family ID: 84359132

Assignee: Aktiebolaget SKF (Gothenburg, SE)

Appl. No.: 17/960431

Filed: October 05, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230128092 A1	Apr. 27, 2023

Foreign Application Priority Data

CN	202111239599.0	Oct. 25, 2021
----	----------------	---------------

Publication Classification

Int. Cl.: G01N11/16 (20060101); B08B3/02 (20060101)

U.S. Cl.:

CPC B08B3/024 (20130101); G01N11/16 (20130101); B08B2240/00 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10293794	12/2018	McAndrew	N/A	B60S 1/56
2018/0178259	12/2017	Gillies	N/A	H04N 23/51
2019/0375378	12/2018	Nezu	N/A	B08B 5/02

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2506165	12/2004	CA	N/A
3214424	12/2016	EP	N/A
3481683	12/2018	EP	B08B 3/02
3686068	12/2019	EP	N/A
3481683	12/2019	EP	N/A
H09329594	12/1996	JP	N/A
2008241289	12/2007	JP	N/A
WO-2021089241	12/2020	WO	B08B 3/02

Primary Examiner: Breene; John E

Assistant Examiner: Plumb; Nigel H

Attorney, Agent or Firm: GARCIA-ZAMOR INTELLECTUAL PROPERTY LAW, LLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application claims priority to Chinese Patent Application no. 202111239599.0, filed Oct. 25, 2021, the contents of which is fully incorporated herein by reference.

TECHNICAL FIELD

(2) The invention relates to a sensor, and in particular relates to a sensor which can refresh the material on the sensing surface.

BACKGROUND

(3) Currently, sensors are needed to monitor the state of fluid in many occasions. When monitoring the state of viscoelastic substances/semi-fluid and semi-solid substances (e.g. grease, gel, paste, emulsion, etc.), it is essential that the sensor can successfully capture fresh samples inside the fluid system. Compared with conventional fluid, this kind of material lacks flowability due to its viscoelasticity, and it requires a specific driving force such as shear force or pressure etc., to refresh

the sensing surface or remove the old sample from the sensing surface.

(4) According to the current technology, the sensor for this kind of fluid is set at a specific position in a system involving use of the fluid, such as in the grease flow path in the bearing, where it is expected that the sample on the sensing surface can be refreshed by the inherent grease flow field in the system.

(5) However, due to the yield and adhesive properties of viscoelastic materials, this self-flow-refreshing is not effective enough, and it is very difficult to clean when the sensing surface is covered by the accumulation of this material, which hinders the refreshing of new samples and data acquisition. One sensing surface cleaning technology is to use a mechanical rotary scraper (made of PTFE or silicone rubber, for example) to clean the sensing surface, but this requires mechanical driving parts. Once there are hard particle pollutants on the sensing surface, it will increase the design complexity and the risk of mechanical damage, such as abrasion or scratch.

SUMMARY

(6) In view of this, the present invention provides a sensor comprising: a sensing surface; a housing, including a recess, the sensing surface being disposed at the bottom of the recess, and the recess including at least one side wall and an opening surrounding the sensing surface in the circumferential direction; wherein a compressed fluid nozzle is provided in the at least one side wall, to eject a compressed fluid from the compressed fluid nozzle, to force a substance on the sensing surface to leave from the opening.

(7) The forced refreshing mechanism for the sensing surface of the present invention uses compressed fluid to blow away the substance on the sensing surface. Through the existing flow in the system, the new sample to be sensed can reach the sensing surface again and gather at the top of the sensing surface, reaching the side wall on the sensor housing, to be blocked and gathered.

(8) The sensor based on the invention can realize the feeding and refreshing of fluid substances on the sensing surface, so as to better capture the updated substance sample signal. This will realize the sample renewal on the sensing surface, and can effectively collect the in-situ material conditions inside the system.

(9) This design makes it possible to refresh in situ with good efficiency without involving additional mechanical parts, thus reducing the risk of sensing surface damage in the presence of wear particles (such as scratching).

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) At least one of the embodiments of the present invention is accurately represented by this application's drawings which are relied on to illustrate such embodiment(s) to scale and the drawings are relied on to illustrate the relative size, proportions, and positioning of the individual components of the present invention accurately relative to each other and relative to the overall embodiment(s). Those of ordinary skill in the art will appreciate from this disclosure that the present invention is not limited to the scaled drawings and that the illustrated proportions, scale, and relative positioning can be varied without departing from the scope of the present invention as set forth in the broadest descriptions set forth in any portion of the originally filed specification and/or drawings. Through the following drawings, those skilled in the art will have a better understanding of this disclosure, and the advantages of this disclosure can be more clearly reflected. FIGS. 1 and 2 are schematic diagrams of a sensor according to an embodiment of the present invention;

(2) FIGS. 3A and 3B show the arrangement of sensing surfaces and related side walls according to different embodiments of the present invention.

DETAILED EMBODIMENTS OF THE INVENTION

(3) Those of ordinary skill in the art will appreciate from this disclosure that when a range is provided such as (for example) an angle/distance/number/weight/volume/spacing being between one (1 of the appropriate unit) and ten (10 of the appropriate units) that specific support is provided by the specification to identify any number within the range as being disclosed for use with a preferred embodiment. For example, the recitation of a percentage of copper between one percent (1%) and twenty percent (20%) provides specific support for a preferred embodiment having two point three percent (2.3%) copper even if not separately listed herein and thus provides support for claiming a preferred embodiment having two point three percent (2.3%) copper. By way of an additional example, a recitation in the claims and/or in portions of an element moving along an arcuate path by at least twenty) (20° degrees, provides specific literal support for any angle greater than twenty) (20° degrees, such as twenty-three) (23° degrees, thirty) (30° degrees, thirty-three-point five) (33.5° degrees, forty-five) (45° degrees, fifty-two) (52° degrees, or the like and thus provides support for claiming a preferred embodiment with the element moving along the arcuate path thirty-three-point five) (33.5° degrees. Referring to FIGS. 1 and 2, according to an embodiment of the present invention, a sensor **1** is provided, which comprises: a sensing surface **10** and a housing **20**, the housing including a recess **21**, the sensing surface **10** being disposed at the bottom of the recess **21** (or to say, being part of the bottom of the recess **21**), and the recess **21** including a sidewall **211** and an opening **212** surrounding the sensing surface **10** in the circumferential direction (see FIG. 2). is provided with a compressed fluid nozzle **213** is provided in one of the side walls **211** (the side wall **211a** shown in FIG. 2), so as to eject the compressed fluid from the compressed fluid nozzle **213**, to force the substance on the sensing surface to leave from the opening.

(4) As mentioned above, the substance on the sensing surface may be viscoelastic/semi-solid and semi-fluid substance such as grease and gel, which forms shear flow or pressure flow, and the flow direction is shown by arrow A in FIG. 1, for example. This shear flow or pressure flow, for example, is approximately parallel to the sensing surface.

(5) Furthermore, there wide choices for the compressed fluid according to different substances targeted by the sensor, such as compressed air, compressed nitrogen, high-pressure liquid, etc., as long as it is suitable for removing the substances on the sensing surface and basically does not affect the substance and the working performance of the system. According to the embodiment shown in FIGS. 1 and 2, the compressed fluid is preferably implemented as compressed air.

(6) The sensing surface is preferably a flat surface and can have various geometric shapes. Therefore, the compressed fluid nozzle can be arranged at the position opposite to the opening according to the geometry of the sensing surface. With this arrangement, the compressed fluid can make the substance on the sensing surface leave the opening smoothly.

(7) For example, according to the preferred embodiment shown in FIGS. 1 and 2, the sensing surface **10** is formed as a rectangular sensing surface, the recess **21** includes three side walls **211a**, **211b** and **211c** and one opening **212** surrounding the rectangular sensing surface in the circumferential direction, and the compressed fluid nozzle **213** is disposed at the side wall **211a** opposite to the opening **212**, for example. FIG. 2 shows the flow direction of the compressed fluid, which enters from the compressed fluid inlet **22** located at the bottom of the housing **20** (for example, connected, as shown by arrow B, to the compressed fluid source via a hose (not shown)), and is ejected from the compressed fluid nozzle **213** (as shown by the dotted arrow C), so as to blow the substance on the sensing surface **10** away from the opening **212**.

(8) For example, in an embodiment not shown, the sensing surface may be formed as a circular sensing surface, and the recess may include one arc-shaped side wall and one arc-shaped opening surrounding the circular sensing surface in the circumferential direction, and the compressed fluid nozzle is disposed in the one arc-shaped side wall at a position opposite to the one arc-shaped opening. For example, the one arc-shaped side wall can take the form of a superior arc, an inferior arc or a semi-circular arc around the circular sensing surface in the circumferential direction, and

the missing arc-shaped part correspondingly forms the one arc-shaped opening. In the direction perpendicular to the sensing surface, the arc-shaped sidewall and the arc-shaped notch, for example, form a roughly C-shaped shape. Furthermore, the compressed fluid nozzle can be formed at a certain position of the arc-shaped side wall, as long as it ejects the compressed fluid toward the opening to blow off the substance on the sensing surface.

(9) Although the rectangular sensing surface is adopted in the embodiment of FIGS. 1 and 2 and the recess is provided with three side walls, it is conceivable to provide one side wall or two side walls on the sensing surface. As shown in the top view of FIG. 3A, in this embodiment, only one side wall **211** (as shown by the black solid part in FIG. 3A) is formed along one side of the sensing surface **10**, while the other three sides have no side walls, forming an open part used as the opening. Accordingly, a compressed fluid nozzle (not shown) can be provided in this one side wall **211**. As shown in the top view of FIG. 3B, in this embodiment, two side walls **211a** and **211b** (as shown by the black solid part in FIG. 3B) are provided along both sides of the sensing surface **10**. And accordingly, a compressed fluid nozzle (not shown) can be provided in any of the two side walls **211a** and **211b**. Therefore, according to the present invention, there may be at least one side wall circumferentially surrounding the sensing surface.

(10) Furthermore, according to other embodiments not shown, the sensing surface may be formed as a polygonal sensing surface, the recess includes at least one side wall and one opening surrounding the polygonal sensing surface in the circumferential direction, and the compressed fluid nozzle is disposed at the side wall opposite to the one opening.

(11) As mentioned above, the substance on the sensing surface comprises, for example, a viscoelastic substance which flows through the sensing surface in a manner of shear flow or pressure flow, so that the compressed fluid nozzle is disposed to eject compressed fluid in a direction opposite to (or to say, contrary to) the direction of the shear flow or the pressure flow. For example, in the embodiment shown in FIGS. 1 and 2, the fluid ejected from the compressed fluid nozzle **213** (dotted arrow C in FIG. 2) is opposite to the direction of shear flow or pressure flow (arrow A in FIG. 1). By such a preferred design, the substance just removed by the compressed fluid will not be pushed back to the sensing surface **10** immediately, so as to facilitate the sufficient refreshing of the sensed sample.

(12) Of course, according to the specific situation of the sensor and the structure it is applied, it is also possible to set the compressed fluid nozzle to eject the compressed fluid in a direction perpendicular or inclined to the direction of the shear flow or pressure flow, so that the sensor and its surface substance cleaning/refreshing mechanism can be designed more flexibly to meet different needs.

(13) According to the embodiment described in FIGS. 1 and 2, the compressed fluid nozzle **213** may have a narrow and long rectangular shape in a cross section perpendicular to the compressed fluid ejection direction (the direction indicated by the dotted arrow C in FIG. 2), for example. Of course, it is also conceivable to adopt other compressed fluid nozzles with cross-sectional shapes, and the number of the compressed fluid nozzles can be one or more.

(14) According to different embodiments, the compressed fluid nozzle can eject compressed fluid in a direction parallel or inclined to the sensing surface. In the embodiment shown in FIGS. 1 and 2, the compressed fluid nozzle **213** ejects compressed fluid in a direction generally parallel to the sensing surface **10**, but according to different situations, it is also possible to eject compressed fluid obliquely toward the sensing surface (for example, aligning with the sensing surface or offset from the sensing surface) by setting the internal flow guiding structure of the compressed fluid nozzle.

(15) In addition, since the sensor according to the present invention can be applied to a variety of different viscous and viscoelastic fluids, the compressed fluid can be ejected at a prescribed frequency for a certain time according to the characteristics of the substance on the sensing surface and the status of the system flow field (for example, once an hour for grease and lasting for 60 seconds or more, etc.), so that the substance on the sensing surface can be more sufficiently

removed, to refresh the sample to be sensed. Moreover, the pressure of the compressed fluid can also be appropriately selected according to different applications, as long as it can sufficiently remove the substances on the sensing surface without affecting the refreshing of the sample to be sensed.

(16) Furthermore, according to a further preferred embodiment, the sensing surface can be surface treated to have a property of being repel the substance on the sensing surface, such as setting an oleophobic coating for grease or lubricant. This can help to remove the accumulated substances on the sensing surface smoothly.

(17) The exemplary implementation of the scheme proposed in this disclosure has been described in detail above with reference to the preferable embodiments. However, it can be understood by those skilled in the art that without departing from the concept of this disclosure, various changes and modifications can be made to the above specific embodiments, and various technical features and structures proposed in this disclosure can be combined in various ways without exceeding the scope of protection of this disclosure, which is determined by the appended claims.

Claims

1. A sensor, comprising: a flat rectangular sensing surface; a housing, including a recess, the sensing surface being disposed at the bottom of the recess, and the recess including at least one side wall and an opening surrounding the sensing surface in the circumferential direction; wherein a compressed fluid nozzle is provided in the at least one side wall, to eject a compressed fluid from the compressed fluid nozzle, to force a substance on the sensing surface to leave from the opening; and wherein the sensing surface and the opening of the compressed fluid nozzle are the same width.
2. The sensor according to claim 1, wherein the compressed fluid nozzle is disposed at a position opposite to the opening according to the geometry of the sensing surface.
3. The sensor according to claim 2, wherein the sensing surface is formed as a polygonal sensing surface, the recess includes at least one side wall and one opening surrounding the polygonal sensing surface in the circumferential direction, and the compressed fluid nozzle is disposed at the side wall opposite to the one opening.
4. The sensor according to claim 2, wherein the sensing surface is formed as a circular sensing surface, the recess includes one arc-shaped side wall and one arc-shaped opening surrounding the circular sensing surface in the circumferential direction, and the compressed fluid nozzle is disposed in the one arc-shaped side wall at a position opposite to the one arc-shaped opening.
5. The sensor according to claim 1, wherein the substance on the sensing surface comprises a viscoelastic substance which flows through the sensing surface in a manner of shear flow or pressure flow, and the compressed fluid nozzle is disposed to eject compressed fluid in a direction opposite to the direction of the shear flow or the pressure flow.
6. The sensor according to claim 1, wherein the substance on the sensing surface comprises a viscoelastic substance which flows through the sensing surface in a manner of shear flow or pressure flow, and the compressed fluid nozzle is disposed to eject compressed fluid in a direction perpendicular or inclined to the direction of the shear flow or the pressure flow.
7. The sensor according to claim 1, wherein the compressed fluid nozzle ejects compressed fluid in a direction parallel or inclined to the sensing surface.
8. The sensor according to claim 1, wherein the compressed fluid comprises any one of compressed air, compressed nitrogen and high-pressure liquid.
9. The sensor according to claim 1, wherein the compressed fluid is sprayed at a prescribed frequency for a certain time according to the properties of substances on the surface of the sensor.

10. The sensor according to claim 1, wherein the sensing surface is surface-treated to have a property of being alienated from the substance on the sensing surface.
