

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403736
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Xu; Yuanjun et al.

Axle structure and vehicle

Abstract

The present application relates to an axle structure and a vehicle. The vehicle includes a chassis, and the axle structure is arranged on the chassis. The axle structure includes a pedestal, a pivot shaft, an axle and limiting structures. The pivot shaft is fixed to the pedestal. The middle of the axle is rotatably connected to the pivot shaft, so that two ends of the axle can rotate vertically relative to the pedestal. In the axle structure provided in the present disclosure, the pivot shaft is provided on the pedestal, and the axle is rotatably connected to the pivot shaft.

Inventors: Xu; Yuanjun (Guangdong, CN), Chen; Shaojie (Guangdong, CN), Wang; Ben (Guangdong, CN)

Applicant: SHENZHEN MAMMOTION INNOVATION CO., LIMITED (Guangdong, CN)

Family ID: 84225677

Assignee: SHENZHEN MAMMOTION INNOVATION CO., LIMITED (Shenzhen, CN)

Appl. No.: 19/033203

Filed: January 21, 2025

Prior Publication Data

Document Identifier	Publication Date
US 20250162366 A1	May. 22, 2025

Foreign Application Priority Data

CN	202222015265.1	Aug. 01, 2022
----	----------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/CN2023/079054 20230301 PENDING child-doc US 19033203

Publication Classification

Int. Cl.: B60G9/02 (20060101)

U.S. Cl.:

CPC B60G9/02 (20130101);

Field of Classification Search

CPC: B60G (9/02); B60G (9/022); B60G (9/025)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4750751	12/1987	Schafer	180/41	A01D 75/285
5946893	12/1998	Gordon	56/15.8	A01D 34/74
6695328	12/2003	Cope	280/124.111	B62D 53/026
7309081	12/2006	Zuhlsdorf	280/6.154	B62K 5/01
7866671	12/2010	Madler	180/41	A01D 34/66
8205899	12/2011	Mackin	180/209	A01D 41/12
10836227	12/2019	Dyna	N/A	B62D 7/04
11470773	12/2021	Wenzel	N/A	A01D 34/74
2004/0262070	12/2003	Uemura	180/378	B60B 35/003
2009/0103842	12/2008	Vannorsdel	384/151	F16C 11/04
2020/0262266	12/2019	Weiss	N/A	B60G 9/02

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2787486	12/2005	CN	N/A
202945032	12/2012	CN	N/A
217936537	12/2021	CN	N/A
2004243912	12/2003	JP	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion in International Application No. PCT/CN2023/079054, issued on Jun. 13, 2023 with English translation provided by WIPO. cited by applicant

Primary Examiner: To; Toan C

Attorney, Agent or Firm: Ladas & Parry, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) The present application is a continuation of International Application No. PCT/CN2023/079054, filed on Mar. 1, 2023, which claims priority to Chinese Patent Application No. CN202222015265.1, filed with the China National Intellectual Property Administration on Mar. 1, 2022 and entitled “Axle structure and vehicle”, the disclosures of which are incorporated herein by reference in their entireties.

TECHNICAL FIELD

(1) The present disclosure relates to the technical field of vehicles, and in particular to an axle structure and a vehicle.

BACKGROUND ART

(2) When driving over uneven ground, existing vehicles tend to experience jolting vibrations, resulting in poor driving stability of the vehicles.

SUMMARY OF THE INVENTION

(3) The present disclosure provides an axle structure and a vehicle to solve the problem of poor driving stability in existing vehicle.

(4) In a first aspect, the present disclosure provides an axle structure. The axle structure includes a pedestal, a pivot shaft, an axle and limiting structures. The pivot shaft is fixed to the pedestal. The middle of the axle is rotatably connected to the pivot shaft, so that two ends of the axle can rotate vertically relative to the pedestal. The pivot shaft includes an intermediate section and connecting sections connected to two ends of the intermediate section, a diameter of the intermediate section is greater than that of the connecting section, and the middle of the axle is rotatably connected to the intermediate section.

(5) In a second aspect, the present disclosure provides a vehicle. The vehicle includes a chassis and the axle structure, and the axle structure is arranged on the chassis.

(6) In the axle structure provided in the present disclosure, the pivot shaft is provided on the pedestal, and the axle is rotatably connected to the pivot shaft, so that when the vehicle drives over uneven ground, the axle can rotate vertically relative to the pedestal, so as to counteract the impact of the uneven ground on the pedestal, thereby improving the driving stability of the vehicle.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) To describe the technical solutions in the embodiments of the present disclosure more clearly, the drawings required for illustration of the embodiments of the present disclosure will be briefly introduced below. Obviously, the drawings in the following description are only for some of the embodiments of the present disclosure, and for those of ordinary skill in the art, other drawings can also be obtained from these drawings without any creative effort.

(2) FIG. 1 is a partial schematic structural diagram of a vehicle according to an embodiment of the present disclosure.

(3) FIG. 2 is an exploded view of an axle structure on the vehicle in FIG. 1.

(4) FIG. 3 is a schematic diagram of a vehicle in a first driving state according to an embodiment of the present disclosure.

(5) FIG. 4 is a schematic diagram of a vehicle in a second driving state according to an embodiment of the present disclosure.

(6) FIG. 5 is a schematic diagram of a vehicle in a third driving state according to an embodiment of the present disclosure.

(7) FIG. 6 is a cross-sectional view of an axle structure on the vehicle in FIG. 1 from a first perspective.

(8) FIG. 7 is a cross-sectional view of a pivot shaft on the axle structure in FIG. 6.

(9) FIG. 8 is a cross-sectional view of an axle structure on the vehicle in FIG. 1 from a second perspective.

(10) FIG. 9 is a schematic diagram of a vehicle in a fourth driving state according to an embodiment of the present disclosure.

(11) Description of reference signs of main elements: Vehicle **1**; Chassis **10**; Axle structure **20**; Pedestal **100**; Bottom plate **110**; Side plate **120**; Limiting structure **130**; Chamfer structure **111**; Stopper **121**; Mounting groove **122**; Pivot shaft **200**; Intermediate section **210**; Connecting section **220**; Stop plate **230**; Fastener **240**; Axle **300**; Abutment surface **301**; First subsection **310**; Reinforcing structure **311**; Connection hole **312**; Second subsection **320**; Flat section **321**; Bent section **322**; Accommodating cavity **330**; Base **400**; Guide post **410**; Buffer member **420**; Cable **500**.

(12) The following specific implementations will further illustrate the present disclosure in conjunction with the aforementioned accompanying drawings.

DETAILED DESCRIPTION OF EMBODIMENTS

(13) The technical solutions in the embodiments of the present disclosure will be clearly and completely described below in conjunction with the accompanying drawings in the embodiments of the present disclosure. The drawings are used for exemplary illustration only, are merely schematic diagrams, and should not be construed as limitations to this disclosure. Obviously, the described embodiments are only a part rather than all of the embodiments of the present disclosure. All other embodiments obtained by a person of ordinary skill in the art based on the embodiments of the present disclosure without creative efforts shall fall within the protection scope of the present disclosure.

(14) The phrase “embodiment” or “embodiments” mentioned herein means that the specific features, structures or characteristics described with reference to the embodiment or embodiments may be included in at least one embodiment of the present disclosure. This phrase in various places in the specification does not necessarily refer to the same embodiment or an independent or alternative embodiment exclusive of other embodiments. It should be appreciated explicitly or implicitly by those skilled in the art that the embodiments described herein can be combined with other embodiments.

(15) It should be noted that the terms “first”, “second” and so on in the specification, the claims and the drawings of the present disclosure are intended to distinguish different objects, rather than to describe a specific order. In addition, the terms “comprise” and “have” and any variations thereof are intended to cover a non-exclusive inclusion.

(16) Referring to FIGS. 1 and 2, an embodiment of the present disclosure provides a schematic structural diagram of a vehicle **1**. The vehicle **1** includes a chassis **10** and an axle structure **20** arranged on the chassis **10**. Wheels are respectively connected to two ends of the axle structure **20**. The axle structure **20** includes a pedestal **100**, a pivot shaft **200** and an axle **300**. The pedestal **100** is connected to the chassis **10**. The pivot shaft **200** is fixed to the pedestal **100**. The middle of the axle **300** is rotatably connected to the pivot shaft **200**, so that two ends of the axle **300** can rotate vertically relative to the pedestal **100**. The vertical rotation refers to the relative movement of the two ends of the axle **300** close to or away from the ground when the vehicle **1** is normally placed on the ground. Alternatively, it refers to the axle **300** rotating in a plane perpendicular to both the ground and a central axis of the pivot shaft **200**, with the central axis of the pivot shaft **200** as a rotation center.

(17) It can be understood that the ground is not entirely a flat plane and typically has depressions or protrusions, and the vehicle **1** cannot completely avoid the depressions or the protrusions on the ground while driving. In an existing vehicle, an axle is relatively fixedly connected to a chassis, and the axle cannot rotate relative to the chassis; therefore, when the vehicle drives over a depression or a protrusion, the axle will drive the chassis to tilt from side to side along with the fluctuation of the ground, leading to jolting vibrations of a vehicle body of the vehicle, thereby

resulting in poor driving stability of the vehicle. In this embodiment, when the vehicle **1** drives over uneven ground, the axle **300** can rotate relative to the pedestal **100** adaptively according to the fluctuation of the ground, so that the chassis **10** of the vehicle **1** is always maintained in a state parallel to the ground, thereby greatly reducing jolting vibrations of the vehicle **1** during driving, and further improving the driving stability of the vehicle.

(18) Referring to FIG. 3, in FIG. 3, the reference sign G represents the ground, the reference sign T represents a top surface of a protrusion on the ground, and the reference sign B represents a bottom surface of the chassis **10**. The top surface of the protrusion may be a surface of the protrusion away from the ground, and the bottom surface B of the chassis **10** refers to a surface of the chassis **10** facing the ground. In FIG. 3, a right wheel of the vehicle **1** is located on the ground, and a left wheel is located on a protrusion. When the vehicle **1** drives over the protrusion, the axle **300** rotates relative to the pivot shaft **200**, allowing the chassis **10** to remain approximately parallel to the ground. In this way, when the vehicle **1** drives over the protrusion, the vehicle body of the vehicle **1** does not vibrate greatly, and thus the vehicle **1** can smoothly drive over the protrusion.

(19) In FIG. 3, when the height of the protrusion on the ground is relatively low, a ground clearance of the bottom surface B of the chassis **10** is greater than that of the top surface T of the protrusion when the vehicle **1** drives over the protrusion, and at this time, the chassis **10** will not collide with the protrusion. Referring to FIG. 4, when the height of the protrusion on the ground is relatively high, the ground clearance of the bottom surface B of the chassis **10** is less than that of the top surface T of the protrusion when the vehicle **1** drives over the protrusion, and at this time, the chassis **10** will collide with the protrusion (as indicated by a dashed line in FIG. 4). Therefore, when an angle at which the axle **300** can rotate relative to the pivot shaft **200** is too large, the chassis **10** is likely to collide with a higher protrusion on the ground when the vehicle **1** drives over the high protrusion.

(20) In this embodiment, limiting structures **130** are provided on the pedestal **100**, and the limiting structures **130** are configured to limit a rotating angle of the axle **300** relative to the pivot shaft **200**, so that the rotating angle of the axle **300** relative to the pivot shaft **200** is limited within a preset angle, thereby preventing the chassis **10** from colliding with obstacles when the vehicle **1** traverses the obstacles. Referring to FIG. 5, when the vehicle **1** crosses a higher protrusion on the ground, after the axle **300** rotates by the preset angle relative to the chassis **10**, if the axle **300** continues to rotate relative to the ground, the axle **300** will drive the chassis **10** to rotate, so that the chassis **10** tilts relative to the ground. At this time, the side of the chassis **10** close to the protrusion will be lifted, and a ground clearance of a left side of the bottom surface B will be greater than that of the top surface T of the protrusion, so that the vehicle **1** can smoothly drive over the protrusion. In this way, in this embodiment, by providing the limiting structures **130** on the pedestal **100**, the obstacle-traversing ability of the vehicle **1** can be improved, and when the height of the obstacles is less than a preset value, the vehicle **1** has good driving stability. The preset angle is related to the ground clearance of the bottom surface B and the height of the protrusion that the vehicle **1** requires to drive over, and a specific range of the preset angle may be specifically set according to actual needs of the vehicle **1**, which is not specifically limited in the present disclosure.

(21) Referring to FIGS. 2 and 6, the pedestal **100** includes a bottom plate **110** and side plates **120** connected to the bottom plate **110**. Two side plates **120** are provided, and the two side plates **120** are arranged opposite each other. In this embodiment, the limiting structures **130** are configured as chamfer structures **111** arranged on the pedestal **100**. The axle **300** is provided with abutment surfaces **301** mating with the chamfer structures **111**. Specifically, the chamfer structures **111** are provided on the bottom plate **110** and positioned between the two side plates **120**. The bottom plate **110** is substantially of a rectangular structure, the two side plates **120** are disposed on two opposite sides of the bottom plate **110**, and the chamfer structures **111** are disposed on the other two opposite sides of the bottom plate **110**. When the axle **300** rotates relative to the chassis **10** by the preset angle, the abutment surfaces **301** abut against the chamfer structures **111**, and the axle **300** cannot

continue to rotate relative to the pivot shaft **200**. If the axle **300** continues to rotate relative to the ground, the axle **300** will drive the chassis **10** to rotate relative to the ground, and at this moment, the bottom surface B of the chassis **10** will tilt relative to the ground.

(22) In some embodiments, a stopper **121** is arranged at one end of the side plate **120** away from the bottom plate **110**, and the limiting structure **130** is configured as the stopper **121**. The pivot shaft **200** is provided between the stoppers **121** and the bottom plate **110**. A limiting space is formed between the stoppers **121** and the bottom plate **110**, and the axle **300** can rotate in the limiting space. When the axle **300** rotates relative to the chassis **10** by the preset angle, the axle **300** abuts against the stoppers **121**. As the axle **300** continues to rotate, the axle **300** will drive the chassis **10** to tilt relative to the ground.

(23) In this embodiment, two ends of the pivot shaft **200** are fixedly connected to the two side plates **120** respectively, and the pivot shaft **200** is positioned between the two side plates **120**. The bottom plate **110** and the two side plates **120** jointly enclose an accommodating space, and the pivot shaft **200** is provided in the accommodating space. The pivot shaft **200** is spaced from the bottom plate **110** to provide a space for the axle **300** to move. The pivot shaft **200** and the side plates **120** may be fixedly connected by screwing, clamping, welding, bonding, etc. In this embodiment, ends of the two side plates **120** facing away from the bottom plate **110** are respectively provided with mounting grooves **122**, and the two ends of the pivot shaft **200** are respectively disposed in the mounting grooves **122** of the two side plates **120**. Specifically, the mounting grooves **122** are provided on opposite sides of the two side plates **120** and do not penetrate opposing sides of the two side plates **120**. When the pivot shaft **200** is mounted in the mounting grooves **122**, the two ends of the pivot shaft **200** do not extend out of the side plates **120** to prevent structural interference between the ends of the pivot shaft **200** and other elements on the vehicle **1**. The pivot shaft **200** is connected to the side plates **120** via fasteners **240**. The fasteners **240** may be configured as pins, bolts, rivets, etc. In this embodiment, the fasteners **240** are configured as bolts, the number of which is set to two. A threaded hole is formed in a groove wall of a side of the mounting groove **122** close to the bottom plate **110**, through holes are respectively formed at the two ends of the pivot shaft **200**, and the two bolts are respectively threaded through the through holes on the two ends of the pivot shaft **200** and are then connected to the threaded holes on the groove walls, thereby fixing the pivot shaft **200** in the mounting grooves **122** on the two side plates **120**. Thus, the two ends of the pivot shaft **200** are fixed by the fasteners **240**, and if a fastener **240** at one end of the pivot shaft **200** is loosened, the fastener **240** at the other end can still fix the pivot shaft **200** on the side plates **120**, thereby preventing the pivot shaft **200** from loosening.

(24) It can be understood that, after the vehicle **1** has been used for a long time, due to continuous friction between the axle **300** and the pivot shaft **200**, a position on the pivot shaft **200** corresponding to the axle **300** will be worn, resulting in a decrease in the structural strength of the pivot shaft **200** at that position, thereby making the pivot shaft prone to breakage at that position. Referring to FIGS. **6** and **7**, in this embodiment, the pivot shaft **200** includes an intermediate section **210** and connecting sections **220** connected to two ends of the intermediate section **210**, a diameter of the intermediate section **210** being greater than that of the connecting section **220**. The middle of the axle **300** is rotatably connected to the intermediate section **210**. In this embodiment, by increasing the diameter of the intermediate section **210**, the intermediate section **210** still maintains sufficient structural strength after prolonged wear, thereby prolonging the service life of the pivot shaft **200**. A difference between the diameter of the intermediate section **210** and the diameter of the connecting section **220** may be a preset value, and the preset value may be specifically set according to the selection of materials of the pivot shaft **200** and the axle **300** and the service life of the pivot shaft **200**. For example, the diameter of the intermediate section **210** can be set larger when a longer service life is required for the pivot shaft **200**. The diameter of the connecting section **220** being less than that of the intermediate section **210** can also reduce the

difficulty in installing the axle **300** and the pivot shaft **200**. When installing the axle **300**, since the diameter of the connecting section **220** is relatively small, technicians can easily sleeve the axle **300** onto the connecting sections **220** and pre-position the axle **300** through the connecting sections **220**, thereby facilitating the technicians to sleeve the axle **300** onto the intermediate section **210** in a next step.

(25) In some embodiments, the pivot shaft **200** may be configured as an eccentric shaft, where the intermediate section **210** is eccentrically disposed from the connecting sections **220**. After the pivot shaft **200** is fixed to the pedestal **100**, a central axis of the intermediate section **210** is located on a side of a central axis of the connecting section **220** away from the bottom plate **110**, so that the distance between the middle of the axle **300** and the bottom plate **110** is increased, thereby allowing the axle **300** to have a larger rotation space in the accommodating space. In some embodiments, the pivot shaft **200** may be rotatably connected to the pedestal **100**, that is, the pivot shaft **200** is rotatably connected to the side plates **120**, thereby reducing the rotation resistance of the axle **300** when rotating relative to the pedestal **100**, and further improving the driving stability of the vehicle **1**.

(26) Optionally, baffle **230** are provided on the pivot shaft **200**, and the baffles **230** are positioned between the axle **300** and the pedestal **100** to prevent friction between the axle **300** and the pedestal **100** when the axle rotates with respect to the pivot shaft **200**. Specifically, two baffles **230** are provided, and the axle **300** is sandwiched between the two baffles **230**, so that the axle **300** is spaced apart from the two side plates **120**. The baffles **230** can also restrict the axial movement of the axle **300** on the pivot shaft **200**, so that the axle **300** does not slide on the pivot shaft **200**, thereby improving the stability of the connection between the axle **300** and the pivot shaft **200**. In this embodiment, the baffles **230** may be configured as retaining rings, the retaining rings being sleeved onto the pivot shaft **200**. In some embodiments, the baffles **230** may also be configured as snap rings, the pivot shaft **200** is provided with snap ring grooves, and the snap rings are snap-fitted in the snap ring grooves, so that the axle **300** is limited between the two snap rings. Preferably, the snap rings are in clearance fit with the axle **300** so that the axle **300** can rotate relative to the pivot shaft **200**.

(27) Referring to FIGS. 2 and 8, in this embodiment, the axle **300** is configured as a crankshaft structure, and the axle **300** is bent outward at a position thereon corresponding to the pedestal **100** to form an arched structure. A middle of the axle **300** is bent in a direction away from the ground to form the arched structure. A middle raised section of the arched structure is arranged away from the ground with respect to the two ends of the axle **300**. When the vehicle **1** is normally placed on the ground, the axle **300** is substantially in a shape like the Chinese character “𠂇”. In this embodiment, the axle **300** is configured as an arched structure, such that the middle of the axle **300** has a larger ground clearance relative to the two ends of the axle **300**, and thus the chassis **10** has a larger ground clearance, i.e., the height of the chassis of the vehicle **1** is higher, thereby improving the off-road capability of the vehicle **1** and the driving ability under complex road conditions. Of course, in some embodiments, the axle **300** may also be configured as a straight shaft.

(28) Specifically, the axle **300** includes a first subsection **310** and two second subsections **320** connected to two ends of the first subsection **310**. The first subsection **310** is rotatably connected to the pivot shaft **200**. One end of the second subsection **320** away from the first subsection **310** is connected to a wheel. Each second subsection **320** is bent relative to the first subsection **310**. In this embodiment, the axle **300** is arranged on a side of the chassis **10** facing away from the ground. The second subsection **320** includes a flat section **321** and a bent section **322** connected between the flat section **321** and the first subsection **310**. The flat section **321** is located on a side of the first subsection **310** that faces the ground. An extension direction of the flat section **321** and an extension direction of the first subsection **310** are parallel to the chassis **10**. The bent section **322** is bent toward a side facing away from the ground relative to the flat section **321** and is connected to

the first subsection **310**. A bending angle of the bent section **322** relative to the flat section **321** may be specifically set according to actual needs of the vehicle **1**. The bending angle refers to an acute angle formed between the extension direction of the flat section **321** and an extension direction of the bent section **322**. When the length of the bent section **322** is a constant value, the larger the bending angle is, the farther the distance between the flat section **321** and the first subsection **310** in a direction perpendicular to the ground is, the greater the ground clearance of the chassis **10** is. A surface of a side of the bent section **322** facing the bottom plate **110** may be configured as an abutment surface **301**.

(29) When the vehicle **1** is normally placed on the ground, the extension direction of the first subsection **310** and the extension direction of the flat section **321** are substantially parallel to the ground, and the extension direction of the bent section **322** is angled relative to the ground. The first subsection **310** is located on a side of the flat section **321** facing away from the ground. As such, the bent section **322** may increase the ground clearance of the chassis **10**. In some embodiments, the axle **300** may also be configured in a circular arc structure, a curved structure, or other forms of arched structures such that the middle of the axle **300** may be away from the ground with respect to the two ends of the axle **300**.

(30) Referring to FIG. 9, a dashed line C in FIG. 9 represents a central axis of the wheel. The obstacle-traversing ability of the vehicle **1** is related to a diameter of the wheel and the ground clearance of the chassis **10**. The higher the ground clearance of the chassis **10**, the greater the height of obstacles that the vehicle **1** can traverse, and the better the off-road capability of the vehicle **1**. In this embodiment, when the vehicle **1** is normally placed on the ground, a central axis C of the wheel is located on a side of the bottom surface B facing away from the ground. The ground clearance of the chassis **10** is related to the diameter of the wheel and the distance between the bottom surface B and the central axis C. The greater the diameter of the wheel, the smaller the distance between the bottom surface B and the central axis C, the greater the ground clearance of the chassis **10**. The larger the diameter of the wheel, the larger the overall size of the vehicle **1**. Therefore, an increase in the ground clearance of the chassis **10** by increasing the diameter of the wheel will impede the miniaturization design of the vehicle **1**. In this embodiment, by configuring the axle **300** as an arched structure, the distance between the bottom surface B and the central axis C can be reduced, so that the ground clearance of the chassis **10** is increased, thereby improving the off-road capability of the vehicle **1**. It should be noted that, in some embodiments, when the vehicle **1** is normally placed on the ground, the central axis C of the wheel is located on a side of the bottom surface B close to the ground. At this time, the greater the distance between the bottom surface B and the central axis C, the greater the ground clearance of the chassis **10**.

(31) A connection hole **312** for connecting to the pivot shaft **200** is formed in the first subsection **310**, and the pivot shaft **200** penetrates through the connection hole **312**. It should be understood that, after the first subsection **310** is provided with the connection hole **312**, the structural strength of the first subsection **310** around the connection hole **312** may be significantly reduced, and when the axle **300** is subjected to vibration or impact, breakage is likely to occur in the proximity of the connection hole **312**. Optionally, in this embodiment, a reinforcing structure **311** for reinforcing the structural strength of a connection between the axle **300** and the pivot shaft **200** is provided in the middle of the axle **300**, and the thickness of the reinforcing structure **311** in the middle is greater than the thickness thereof at the two ends.

(32) Specifically, in this embodiment, the reinforcing structure **311** is configured as a cylindrical structure, and an axial direction of the cylindrical structure is perpendicular to an extension direction of the axle **300**. The shape of a cross section of the cylindrical structure is substantially circular, and a center hole of the cylindrical structure is configured as the connection hole **312**. In a view angle as shown in FIG. 8, the cylindrical structure has a first thickness in a first direction X, and the first subsection **310** has a second thickness in the first direction X other than at the location of the cylindrical structure, the first thickness being greater than the second thickness. In a second

direction Y, the thickness of the cylindrical structure in the middle is greater than the thickness thereof at the two ends. The first direction X refers to a direction perpendicular to the chassis **10**, and the second direction Y refers to a direction parallel to the chassis **10**. In a circumferential direction of the cylindrical structure, wall thicknesses at various positions of the cylindrical structure are substantially equal, so that the first subsection **310** has sufficient structural strength at the connection hole **312**, thereby solving the problem that breakage easily occurs in the proximity of the connection hole **312**.

(33) In some embodiments, a cross section of the reinforcing structure **311** may be configured as a spindle shape, a minor axis of the spindle-shaped structure is parallel to the first direction X, a major axis thereof is parallel to the second direction Y, and the connection hole **312** is formed in a middle position of the spindle-shaped structure. In some embodiments, the reinforcing structure **311** may also be configured as a reinforcing rib provided near the connection hole **312** on the first subsection **310**, and the reinforcing rib may be provided along the extension direction of the axle **300**.

(34) In this embodiment, the vehicle **1** further includes a base **400** and guide posts **410** arranged on the base **400**. Preferably, a plurality of guide posts **410** are provided. The pedestal **100** is slidably connected to the guide posts **410**, and the pedestal **100** can slide along the guide posts **410** to be away from or close to the base **400**. The pedestal **100** has a first position and a second position with respect to the base **400**. In the first position, the pedestal **100** is relatively close to the base **400**, and in the second position, the pedestal **100** is relatively far away from the base **400**. When the vehicle **1** is normally placed on the ground, the vehicle body will move close to the ground with respect to the axle **300** under the action of gravity, and at this time, the pedestal **100** slides to the second position along the guide posts **410**. When the vehicle **1** is lifted and separated from the ground, the axle **300** may move with respect to the vehicle body in a direction close to the ground under the action of gravity, and at this time, the pedestal **100** slides to the first position along the guide posts **410**. Preferably, a buffer member **420** is provided between the pedestal **100** and the base **400**. The buffer member **420** is configured to provide a damping force for the pedestal **100** when the pedestal **100** slides along the guide posts **410**, slowing down a sliding speed of the pedestal **100** to avoid a large impact with the base **400** when the pedestal **100** moves to the first position or the second position. At the same time, the buffer member **420** may also be configured to absorb a part of impact force of the ground on the vehicle **1** when the vehicle **1** drives over uneven ground, thereby improving the smoothness of the vehicle **1** during the driving process.

(35) In this embodiment, an accommodating cavity **330** is provided in the axle **300**, and cables **500** for connecting drive motors on the vehicle **1** are routed through the accommodating cavity **330**. The accommodating cavity **330** is formed along the extension direction of the axle **300**. The first subsection **310** is provided with holes through which the cables **500** pass, and the cables **500** enter through the holes and exit from the ends of the axle **300**. Preferably, the drive motors are configured as hub motors, and the hub motors are mounted on the wheels. The cables **500** are configured to connect the hub motors to components such as a power supply and a controller on the vehicle body. In this embodiment, by accommodating the cables **500** in the accommodating cavity **330**, the cables **500** can be neatly stored, and the axle **300** can also protect for the cables **500** to prevent the cables **500** from being worn.

(36) The foregoing descriptions are merely some of the embodiments of the present disclosure, but are not intended to limit the scope of protection of the present disclosure. Any variation or replacement readily figured out by a person skilled in the art within the technical scope disclosed in the present disclosure shall fall within the scope of protection of the present disclosure. Therefore, the scope of protection of the present disclosure shall be subject to the scope of protection of the claims.

Claims

1. An axle structure, comprising: a pedestal; a pivot shaft, disposed on the pedestal; and an axle, wherein a middle of the axle is rotatably connected to the pivot shaft, allowing two ends of the axle to rotate vertically relative to the pedestal; wherein the pivot shaft comprises an intermediate section and connecting sections connected to two ends of the intermediate section, a diameter of the intermediate section is greater than a diameter of the connecting section, and the middle of the axle is rotatably connected to the intermediate section.
2. The axle structure according to claim 1, wherein the limiting structures are provided on the pedestal, and the limiting structures are configured to limit a rotating angle of the axle.
3. The axle structure according to claim 2, wherein the limiting structures are configured as a chamfer structures disposed on the pedestal, and the axle comprises abutment surfaces mating with the chamfer structures.
4. The axle structure according to claim 1, wherein the pedestal comprises a bottom plate and two side plates connected to the bottom plate, the two side plates are disposed opposite each other, and the pivot shaft is located between the two side plates; and mounting grooves are formed on sides of the side plates facing away from the bottom plate, the pivot shaft is positioned in the mounting grooves, and the pivot shaft is connected to the side plates via fasteners.
5. The axle structure according to claim 1, wherein the axle is bent outward at a position thereon corresponding to the pedestal to form an arched structure.
6. The axle structure according to claim 1, wherein the axle comprises a first subsection and two second subsections connected to two ends of the first subsection; the first subsection is rotatably connected to the pivot shaft; and each of the second subsections is bent relative to the first subsection.
7. The axle structure according to claim 1, wherein a reinforcing structure is provided in the middle of the axle, the thickness of the middle of the reinforcing structure is greater than that at two ends thereof, and a connection hole for connecting to the pivot shaft is formed in the reinforcing structure.
8. The axle structure according to claim 1, wherein baffle are provided on the pivot shaft, and the baffle are located between the axle and the pedestal.
9. The axle structure according to claim 1, further comprising a base, wherein guide posts are provided on the base, the pedestal is slidably connected to the guide posts, and a buffer member is provided between the base and the pedestal.
10. The axle structure according to claim 1, wherein an accommodating cavity is provided in the axle, and cables for connecting to drive motors of a vehicle are routed through the accommodating cavity.
11. A vehicle, comprising an axle structure, a chassis, the axle structure is arranged on the chassis comprising an axle structure, the axle structure comprises a pedestal; a pivot shaft, disposed on the pedestal; and an axle, wherein a middle of the axle is rotatably connected to the pivot shaft, allowing two ends of the axle to rotate vertically relative to the pedestal; wherein the pivot shaft comprises an intermediate section and connecting sections connected to two ends of the intermediate section, a diameter of the intermediate section is greater than a diameter of the connecting section, and the middle of the axle is rotatably connected to the intermediate section.
12. The vehicle according to claim 11, wherein the limiting structures are provided on the pedestal, and the limiting structures are configured to limit a rotating angle of the axle.
13. The vehicle according to claim 12, wherein the limiting structures are configured as a chamfer structures disposed on the pedestal, and the axle comprises abutment surfaces mating with the chamfer structures.
14. The vehicle according to claim 11, wherein the pedestal comprises a bottom plate and two side

plates connected to the bottom plate, the two side plates are disposed opposite each other, and the pivot shaft is located between the two side plates; and mounting grooves are formed on sides of the side plates facing away from the bottom plate, the pivot shaft is positioned in the mounting grooves, and the pivot shaft is connected to the side plates via fasteners.

15. The vehicle according to claim 11, wherein the axle is bent outward at a position thereon corresponding to the pedestal to form an arched structure.

16. The vehicle according to claim 11, wherein the axle comprises a first subsection and two second subsections connected to two ends of the first subsection; the first subsection is rotatably connected to the pivot shaft; and each of the second subsections is bent relative to the first subsection.

17. The vehicle according to claim 11, wherein a reinforcing structure is provided in the middle of the axle, the thickness of the middle of the reinforcing structure is greater than that at two ends thereof, and a connection hole for connecting to the pivot shaft is formed in the reinforcing structure.

18. The vehicle according to claim 11, wherein baffle are provided on the pivot shaft, and the baffle are located between the axle and the pedestal.

19. The vehicle according to claim 11, further comprising a base, wherein guide posts are provided on the base, the pedestal is slidably connected to the guide posts, and a buffer member is provided between the base and the pedestal.

20. The vehicle according to claim 11, wherein an accommodating cavity is provided in the axle, and cables for connecting to drive motors of a vehicle are routed through the accommodating cavity.
