

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403801
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Shibata; Yuji et al.

Nursery equipment

Abstract

An adjustment mechanism of nursery equipment includes a string connecting a fixed portion and a movable portion, a reel that is rotatable in both forward and reverse directions and that changes the position or shape of the movable portion by winding up and feeding out the string, a rotation operation member that controls rotation of the reel, a motion transmission portion that transmits a rotational motion of the rotation operation member to the reel, and a motion separation portion that does not transmit the rotational motion of the rotation operation member to the reel.

Inventors:	Shibata; Yuji (Tokyo, JP), Nishikawa; Tadashi (Tokyo, JP)
Applicant:	GRACO CHILDREN'S PRODUCTS, INC. (Atlanta, GA)
Family ID:	83901948
Assignee:	GRACO CHILDREN'S PRODUCTS, INC. (Atlanta, GA)
Appl. No.:	17/660604
Filed:	April 25, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220354272 A1	Nov. 10, 2022

Foreign Application Priority Data

JP	2021-079141	May. 07, 2021
----	-------------	---------------

Publication Classification

Int. Cl.: B60N2/28 (20060101); B65H54/28 (20060101)

U.S. Cl.:

CPC **B60N2/2816** (20230801); **B60N2/2812** (20130101); **B65H54/2857** (20130101);
B60N2/2887 (20130101)

Field of Classification Search

CPC: B60N (2/2806); B60N (2/2816); B60N (2/2887); B60N (2/2812); B65H (54/2857)

USPC: 297/253

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5383708	12/1994	Nagasaka et al.	N/A	N/A
5490685	12/1995	Kitayama et al.	N/A	N/A
5681094	12/1996	Brown et al.	N/A	N/A
7004362	12/2005	Boone	N/A	N/A
7726737	12/2009	Jane Santamaria	N/A	N/A
8038214	12/2010	Brandl et al.	N/A	N/A
8328275	12/2011	Vogt et al.	N/A	N/A
8444222	12/2012	Buckingham et al.	N/A	N/A
8967715	12/2014	Carpenter et al.	N/A	N/A
9643765	12/2016	Pivonka	N/A	N/A
9688167	12/2016	Hutchinson et al.	N/A	N/A
10829011	12/2019	Campbell et al.	N/A	N/A
2003/0071511	12/2002	Stafford et al.	N/A	N/A
2013/0001992	12/2012	Hartenstine et al.	N/A	N/A
2013/0127218	12/2012	Carpenter et al.	N/A	N/A
2018/0361888	12/2017	Campbell et al.	N/A	N/A
2022/0354272	12/2021	Shibata et al.	N/A	N/A
2022/0354273	12/2021	Shibata et al.	N/A	N/A
2022/0354274	12/2021	Shibata et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
208017262	12/2017	CN	N/A
109017472	12/2017	CN	N/A
112278056	12/2020	CN	N/A
0295838	12/1987	EP	N/A
H07-323816	12/1994	JP	N/A
2749478	12/1997	JP	N/A
H10-119612	12/1997	JP	N/A
2004-130996	12/2003	JP	N/A
2008290587	12/2007	JP	N/A
2013-014320	12/2012	JP	N/A
2013162974	12/2012	JP	N/A
2015-131024	12/2014	JP	N/A
2020-192875	12/2019	JP	N/A
2020/071585	12/2019	WO	N/A

OTHER PUBLICATIONS

USPTO Office Action issued in U.S. Appl. No. 17/660,600, mailed Oct. 3, 2023. cited by applicant
USPTO Office Action issued in U.S. Appl. No. 17/660,610, mailed Oct. 20, 2023. cited by applicant

Primary Examiner: Nelson, Jr.; Milton

Attorney, Agent or Firm: Eversheds Sutherland (US) LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application claims priority to JP Patent Application No. 2021-079141, filed May 7, 2021, the entire contents of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

Field of the Invention

(2) The present invention relates to nursery equipment, and more particularly to nursery equipment including a fixed portion, a movable portion that is movable relative to the fixed portion, and an adjustment mechanism for adjusting the position or shape of the movable portion.

Background Art

(3) Nursery equipment such as car seat, stroller, bassinet, and baby carrier typically has a movable portion that can be changed in position with respect to a fixed portion.

(4) For example, Japanese Unexamined Patent Publication No. 2008-290587 (Patent Literature 1) discloses a car seat whose shoulder straps can be adjusted in length according to the body of a child. In this car seat, the length of each shoulder strap can be adjusted by merely pulling the tip end of the shoulder strap located on the back side of a seat portion.

(5) For example, Japanese Unexamined Utility Model Publication No. H07-4248 (Patent Literature 2) discloses a stroller whose reclining angle can be adjusted by connecting belts to a handlebar and adjusting the length of the belts by a buckle attached to the back of a backrest portion.

(6) For example, Japanese Unexamined Patent Publication No. 2013-162974 (Patent Literature 3) discloses a baby carrier that can be used to carry a baby in either an upright position or a reclined position. This baby carrier has shoulder straps to be placed around parent's shoulders, a waist strap to be placed around a parent's waist, and connection straps connecting a baby and a parent, and each of these straps can be adjusted in length.

CITATION LIST

Patent Literatures

(7) Patent Literature 1: Japanese Unexamined Patent Publication No. 2008-290587 Patent

Literature 2: Japanese Unexamined Utility Model Publication No. 1107-4248 Patent Literature 3: Japanese Unexamined Patent Publication No. 2013-162974

SUMMARY OF INVENTION

(8) In the nursery equipment disclosed in Japanese Unexamined Patent Publication No. 2008-290587, Japanese Unexamined Utility Model Publication No. H07-4248, and Japanese Unexamined Patent Publication No. 2013-162974, the length of the body restraint straps such as shoulder straps and the reclining angle need to be adjusted with both hands, and the structure is complicated.

(9) The present invention was made to solve the above problems, and it is an object of the present invention to provide nursery equipment whose movable portion can be adjusted in position or

shape by a simple structure.

(10) Nursery equipment according to one aspect of the present invention includes: a fixed portion; a movable portion that is movable relative to the fixed portion; and an adjustment mechanism that adjusts a position or shape of the movable portion. The adjustment mechanism includes a string connecting the fixed portion and the movable portion, a reel that is rotatable in both forward and reverse directions and that changes the position or shape of the movable portion by winding up and feeding out the string, a one-way clutch mechanism that allows rotation of the reel in a winding direction of the string and prohibits rotation of the reel in a feeding direction of the string, and an unlock member that unlocks the reel from a rotation prohibited state caused by the one-way clutch mechanism and thus allows the reel to rotate freely.

(11) Preferably, the adjustment mechanism further includes a rotation operation member that controls rotation of the reel.

(12) Preferably, the adjustment mechanism further includes a biasing member that biases the reel in the winding direction of the string.

(13) Preferably, the adjustment mechanism further includes a holder that rotatably supports the reel, the one-way clutch mechanism includes an engagement tooth located on one of the reel and the holder, and an engagement pawl attached to the other of the reel and the holder, the engagement pawl being movable between an engaged position in which the engagement pawl engages with the one of the reel and the holder and a disengaged position in which the engagement pawl does not engage with the one of the reel and the holder, and the unlock member includes an operation portion that is operated to move the engagement pawl to the disengaged position.

(14) Preferably, the engagement tooth is located on an outer peripheral surface of the reel that extends parallel to a rotation axis of the reel, the engagement pawl is located on the holder and moves in a direction perpendicular to the engagement tooth, and the unlock member unlocks the reel from the rotation prohibited state by moving in a direction perpendicular to the rotation axis of the reel.

(15) Preferably, the engagement tooth is located on the holder and extends in a circumferential direction of the reel, the engagement pawl is located on the reel and moves in a horizontal direction with respect to the engagement tooth, and the unlock member unlocks the reel from the rotation prohibited state by moving in the circumferential direction of the reel.

(16) Preferably, the engagement tooth is located on an upper or lower surface of the reel that extends in a direction perpendicular to a rotation axis of the reel, the engagement pawl is located on the holder and moves in a direction perpendicular to the engagement tooth, and the unlock member unlocks the reel from the rotation prohibited state by moving in a direction parallel to the rotation axis of the reel.

(17) Preferably, the nursery equipment is a car seat, the fixed portion is a seat, and the movable portion is a body restraint strap attached to the seat.

(18) Preferably, the nursery equipment is a car seat, the fixed portion is a car seat body, and the movable portion is an ISOFIX attached to the car seat body.

(19) Nursery equipment according to another aspect includes: a body; an extended portion extended from the body; and an adjustment mechanism that adjusts a position or shape of the extended portion. The adjustment mechanism includes a string having one end connected to the body and the other end held by the extended portion, a reel that is rotatable in both forward and reverse directions and that changes the position or shape of the extended portion by winding up and feeding out the string, and a rotation lock mechanism that prohibits rotation of the reel.

(20) Preferably, the nursery equipment is nursery equipment with a seat, the body is the seat that receives a child, the extended portion is a pair of shoulder straps that is extended from the seat and restrains shoulders of the child, the adjustment mechanism includes a pair of the strings, and the pair of strings is held by ends of the pair of shoulder straps.

(21) Preferably, the nursery equipment is nursery equipment with a seat, the body is the seat that

receives a child, the extended portion is a crotch strap that is extended from the seat and restrains a crotch of the child, and the string is held by an end of the crotch strap.

(22) Preferably, the nursery equipment is a car seat, the body is a car seat body, and the extended portion is an ISOFIX extended rearward from the car seat body.

(23) Preferably, the nursery equipment is a baby carrier, the body is a baby carrier body, and the extended portion is a movable portion extended from the baby carrier body.

(24) Preferably, the baby carrier body includes a parent shoulder strap to be worn around a shoulder of a parent, and a parent waist strap to be worn around a waist of the parent, and the extended portion is a portion extended from the parent shoulder portion or the parent waist portion.

(25) Preferably, the baby carrier body includes a child support portion that supports a body of a child, and the extended portion is a portion extended from the child support portion.

(26) Preferably, the adjustment mechanism further includes an unlock member that unlocks the reel from a rotation prohibited state caused by the rotation lock mechanism and thus allows the reel to rotate freely.

(27) Nursery equipment according to still another aspect includes: a fixed portion; a movable portion that is movable relative to the fixed portion; and an adjustment mechanism that adjusts a position or shape of the movable portion. The adjustment mechanism includes a string connecting the fixed portion and the movable portion, a reel that is rotatable in both forward and reverse directions and that changes the position or shape of the movable portion by winding up and feeding out the string, a rotation operation member that controls rotation of the reel, a motion transmission portion that transmits a rotational motion of the rotation operation member to the reel, and a motion separation portion that does not transmit the rotational motion of the rotation operation member to the reel.

(28) Preferably, the motion transmission portion normally transmits the rotational motion of the rotation operation member to the reel, and the rotation separation portion does not transmit the rotational motion of the rotation operation member to the reel under more than a certain load.

(29) Preferably, when the rotation operation member rotates in one direction, the motion transmission portion transmits the rotational motion of the rotation operation member to the reel, and when the rotation operation member rotates in the other direction, the rotation separation portion does not transmit the rotational motion of the rotation operation member to the reel.

(30) Preferably, the reel includes a reel body that winds up and feeds out the string, and a moving member that is located between the reel body and the rotation operation member, and the motion transmission portion or the motion separation portion includes a drive gear portion located on the rotation operation member and a driven gear portion located on the moving member.

(31) Preferably, the moving member is biased in a direction toward the rotation operation member.

(32) Preferably, the drive gear portion includes a first tilted portion tilted in a winding direction of the string from the reel toward the rotation operation member, and a second tilted portion tilted in a feeding direction of the string from the reel toward the rotation operation member, and an angle of the first tilted portion with respect to the winding direction is smaller than an angle of the second tilted portion with respect to the feeding direction.

(33) Nursery equipment according to yet another aspect includes: a fixed portion; a movable portion that is movable relative to the fixed portion and that is movable downward in a vertical direction; and an adjustment mechanism that adjusts a position or shape of the movable portion. The adjustment mechanism includes a string connecting the fixed portion and the movable portion, a reel that is rotatable in both forward and reverse directions and that changes the position or shape of the movable portion by winding up and feeding out the string, a biasing member that biases the reel in such a way that the reel rotates in a winding direction of the string, and a lock member that prohibits rotation of the reel. A biasing force of the biasing member is selected to be smaller than a biasing force with which the movable portion tends to move downward in the vertical direction.

(34) Preferably, the adjustment member further includes a one-way clutch mechanism that allows

rotation of the reel in the winding direction of the string and prohibits rotation of the reel in a feeding direction of the string.

(35) Preferably, the lock member includes a reel lock pawl that is movable between a first position and a second position, the first position being a position in which the reel lock pawl engages with a portion that rotates with the reel and prohibits rotation of the reel, and the second position being a position in which the reel lock pawl is disengaged from the portion that rotates with the reel and allows rotation of the reel.

(36) Preferably, the adjustment mechanism further includes an unlock member that moves the lock member to the second position to allow the reel to rotate freely.

(37) Preferably, the biasing member is a mainspring, one end of the mainspring is fixed to the reel, and the other end of the mainspring is fixed to a housing of the adjustment mechanism.

(38) Preferably, the nursery equipment is a car seat, the fixed portion is a seat, and the movable portion is a body restraint strap attached to the seat.

(39) The present invention provides nursery equipment whose movable portion can be adjusted in position or shape by a simple structure.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1A is a perspective view of a car seat according to an embodiment of the present invention, FIG. 1B is a perspective view of an adjustment mechanism and ISOFIX latches, FIG. 1C is a sectional view of the ISOFIX latch with an ISOFIX latch body pulled out of a storage portion, and FIG. 1D is a sectional view of the ISOFIX latch with the ISOFIX latch body pushed into the storage portion.

(2) FIG. 2A is a perspective view of a car seat according to another embodiment, FIG. 2B is a perspective view of an adjustment mechanism, shoulder straps, and waist straps with the shoulder straps pulled out, and FIG. 2C is a perspective view of the adjustment mechanism, the shoulder straps, and the waist straps with the shoulder straps wound from the state shown in FIG. 2B.

(3) FIG. 3A is a perspective view of a car seat according to still another embodiment, FIG. 3B is a schematic sectional view of the car seat with its straps in a restricting state, and FIG. 3C is a schematic sectional view of the car seat with the straps in a releasing state.

(4) FIGS. 4A to 4C shows an adjustment mechanism according to a first embodiment of the present invention, where FIG. 4A is a perspective view, FIG. 4B is a plan view, and FIG. 4C is a sectional view as viewed from line IVc-IVc in FIG. 4B.

(5) FIG. 5 is an exploded perspective view of the adjustment mechanism according to the first embodiment of the present invention.

(6) FIGS. 6A to 6B shows plan views of an unlock member, a lock member, a reel, and a partition, where FIG. 6A shows the state in which the unlock member is not operated, and FIG. 6B shows the state in which the unlock member is operated.

(7) FIG. 7 is a sectional view as viewed from line VII-VII in FIG. 4C.

(8) FIG. 8A is a perspective view of a rotation operation member and a moving member, FIG. 8B is a schematic view of a drive gear of the rotation operation member and a driven gear of the moving member, FIG. 8C is a perspective view of the rotation operation member as viewed from the back, and FIG. 8D is an enlarged view of the drive gear portion in FIG. 8C.

(9) FIGS. 9A to 9B shows sectional views of the rotation operation member, the moving member, and a link member, where FIG. 9A shows the state in which a motion transmission portion is functioning, and FIG. 9B shows the state in which a motion separation portion is functioning.

(10) FIG. 10 is a sectional view of a modification of the adjustment mechanism.

(11) FIGS. 11A to 11B shows schematic views of another modification of the adjustment

mechanism, where FIG. 11A shows the state in which an unlock member is not operated, and FIG. 11B shows the state in which the unlock member is operated.

(12) FIGS. 12A to 12C shows an adjustment mechanism in a second embodiment of the present invention, where FIG. 12A is a perspective view, FIG. 12B is a plan view, and FIG. 12C is a sectional view as viewed from line XIIc-XIIc in FIG. 4B.

(13) FIG. 13 is an exploded perspective view of the adjustment mechanism in the second embodiment of the present invention.

(14) FIGS. 14A to 14B shows sectional views of the adjustment mechanism in the second embodiment of the present invention, where FIG. 14A indicates the state in which an unlock member is not operated, and FIG. 14B shows the state in which the unlock member is operated.

(15) FIG. 15A is a perspective view of a reel and a lock member, and FIG. 15B is a schematic view of a one-way lock mechanism, and FIG. 15C is a perspective view of the reel as viewed from the back.

(16) FIG. 16 is a sectional view as viewed from line XVI-XVI in FIG. 12C.

(17) FIG. 17A is a perspective view of a rotation operation member and a moving member, FIG. 17B is a schematic view of a drive gear of the rotation operation member and a driven gear of the moving member, FIG. 17C is a perspective view of the rotation operation member as viewed from the back, and FIG. 17D is an enlarged view of the drive gear portion in FIG. 17C.

(18) FIGS. 18A to 18B shows sectional views of the rotation operation member, the moving member, and a link member, where FIG. 18A shows the state in which a motion transmission portion is functioning, and FIG. 18B shows the state in which a motion separation portion is functioning.

(19) FIG. 19 is a sectional view of a modification of the adjustment mechanism.

(20) FIG. 20 is a sectional view of another modification of the adjustment mechanism.

(21) FIGS. 21A to 21C shows an adjustment mechanism in a third embodiment of the present invention, where FIG. 21A is a perspective view, FIG. 21B is a plan view, and FIG. 21C is a sectional view as viewed from line XXIc-XXIc in FIG. 21B.

(22) FIG. 22 is an exploded perspective view of the adjustment mechanism in the third embodiment of the present invention.

(23) FIG. 23 is a plan view of an upper holder.

(24) FIG. 24A is a perspective view of a rotation operation member, a moving member, and a link member, FIG. 24B is a schematic view of a drive gear of the rotation operation member and a driven gear of the moving member, and FIG. 24C is a perspective view of the rotation operation member as viewed from the back.

(25) FIG. 25A is a perspective view of the link member and a lock member and FIGS. 25B to 25D are partial sectional views as viewed line XXV-XXV in FIG. 21C, showing the state in which the link member is rotated.

(26) FIGS. 26A to 26D are partial sectional views as viewed from line XXVI-XXVI in FIG. 21C, showing the state in which the link member is rotated.

(27) FIGS. 27A to 27B shows a lower holder of the adjustment mechanism, where FIG. 27A is a bottom perspective view, and FIG. 27B is a plan view.

(28) FIG. 28A is a perspective view of the rotation operation member, the moving member, a biasing portion, and the link member, FIG. 28B is a schematic view of a drive gear of the rotation operation member and a driven gear of the moving member, and FIG. 28C is a perspective view of the rotation operation member as viewed from the back.

(29) FIGS. 29A to 29B shows sectional views of the rotation operation member, the moving member, the biasing portion, and the link member, where FIG. 29A shows the state in which a motion transmission portion is functioning, and FIG. 29B shows the state in which the motion separation portion is functioning.

(30) FIG. 30 is a plan view of the lock member.

(31) FIG. 31A shows the state in which the unlock member is not operated, and FIG. 31B shows the state in which the unlock member is operated.

(32) FIGS. 32A to 32D shows a modification of the adjustment mechanism, where FIG. 32A is a perspective view, FIG. 32B is a schematic view of a drive gear of a rotation operation member and a driven gear of a moving member, FIG. 32C shows the state in which a motion transmission portion is functioning, and FIG. 32D indicates the state in which a motion separation portion is functioning.

(33) FIG. 33 is an exploded perspective view of an adjustment mechanism according to a fourth embodiment of the present invention.

(34) FIGS. 34A to 34D are schematic views illustrating the operation of a car seat according to the fourth embodiment of the present invention.

DESCRIPTION OF EMBODIMENTS

(35) Embodiments of the present invention will be described in detail with reference to the drawings. The same or corresponding portions are denoted by the same reference characters throughout the drawings, and description thereof will not be repeated.

(36) First, an example of nursery equipment with an adjustment mechanism 3 will be described. Examples of the nursery equipment with the adjustment mechanism 3 include a stroller, a car seat, a baby carrier, a bassinet, and a high chair. An example in which the present invention is applied to a car seat, a stroller, and a baby carrier will be described.

(37) Overview of Nursery Equipment

(38) An example of nursery equipment 1 according to an embodiment will be described with reference to FIGS. 1A to 3C.

(39) Car Seat

(40) First, an example in which the nursery equipment 1 is a car seat will be described. In the description of the car seat 1, the longitudinal direction corresponds to the longitudinal direction of the car seat 1, the lateral direction (width direction) corresponds to the lateral direction of the car seat 1 as viewed from the front of the car seat 1, and the vertical direction corresponds to the vertical direction of the car seat 1.

(41) Referring to FIG. 1A, a basic structure of the car seat 1 may be similar to the structure of a typical car seat. The car seat 1 is a device that is installed on a seat of an automobile so that a child such as infant or toddler can safely ride in the automobile. The car seat 1 includes a base body 10 and a seat 20. The base body 10 and the seat 20 are a car seat body. The car seat body is a “fixed portion” of the present embodiment, and is also a “body” of the present embodiment.

(42) The base body 10 is placed on a seat of a passenger car and supports the seat 20 from below. The base body 10 has at its front end a load leg (not shown) extending toward the floor of the passenger car. The base body 10 has, at its rear end, ISOFIX latches 11 to be connected to anchors of the seat of the passenger car. The ISOFIX latches 11 are portions protruding rearward from the car seat body (base body 10). The ISOFIX latches 11 are a “movable portion” of the present embodiment and are also an “extended portion” of the present embodiment.

(43) The seat 20 is attached to the upper side of the base body 10, and is supported so as to be rotatable with respect to the base body 10. FIG. 1A shows the seat 20 with a soft cloth member such as a covering member like a cushioning material thereon.

(44) The seat 20 includes a seat portion 21 and a backrest portion 22 standing from the rear part of the seat portion 21. Since a child is seated on the seat 20, the seat portion 21 supports the buttocks of the child, and the backrest portion 22 supports the back of the child. A cushioning structure is detachably provided in a corner portion where the seat portion 21 and the backrest portion 22 meet.

(45) The backrest portion 22 is provided with a pair of shoulder straps 23. The shoulder straps 23 restrain both shoulders of the child seated on the seat 20. The seat portion 21 is provided with a crotch strap 24 and a pair of waist straps 25. The crotch strap 24 extends between the legs (both thighs) of the child seated on the seat 20, and the waist straps 25 restrain the waist of the child

seated on the seat **20**. A buckle **26** is provided at the tip end of the crotch strap **24**, and the straps **23**, **24**, and **25** are connected near the belly of the child by the buckle **26**. These straps **23**, **24**, and **25** are so-called 5-point harness straps. These straps **23**, **24**, and **25** are body restraint straps that restrain the body of the child, and are portions protruding forward from the car seat body (seat **20**). These straps **23**, **24**, and **25** are a “movable portion” of the present embodiment and are also an “extended portion” of the present embodiment. The body restraint straps are also similarly applied to other nursery equipment.

(46) Such a car seat **1** uses the adjustment mechanism **3**. The adjustment mechanism **3** generally includes a string **4** and an adjustment mechanism body **5** that winds up and pulls out (feeds out) the string **4**. Application of the adjustment mechanism **3** to the car seat **3** will be described first.

(47) ISOFIX Latches

(48) As shown in FIGS. **1A** to **1D**, the adjustment mechanism **3** of the car seat **1** of the present embodiment is used to adjust the positions of the ISOFIX latches **11**. As shown in FIG. **1A**, the adjustment mechanism **3** is located at a front position of the car seat body (base body **10**).

(49) As shown in FIGS. **1B** and **1C**, each ISOFIX latch **11** includes an ISOFIX latch body **12**, a storage portion **13** capable of storing the ISOFIX latch body **12**, and a spring portion **14** that biases the ISOFIX latch body **12** outward. The ISOFIX latch bodies **12** are connected to the anchors of the seat of the passenger car and are fixed with an appropriate length.

(50) A method for adjusting the positions of the ISOFIX latches **11** by the adjustment mechanism **3** will be described with reference to FIGS. **1C** and **1D**. First, as shown in FIG. **1C**, the ISOFIX latch body **12** of each ISOFIX latch **11** is pulled out of the storage portion **13**. The ISOFIX latch body **12** of each ISOFIX latch **11** is then connected to the anchor of the seat of the passenger car, and the car seat **1** is pushed against the seat of the passenger car. The adjustment mechanism body **5** is operated to wind up the string **4**. The car seat **1** and the seat of the passenger car can thus be connected with no gap therebetween, and the distance between the car seat **1** and the seat of the passenger car can be finely adjusted.

(51) The following methods are possible to increase the length of the ISOFIX latch bodies **12**. One method is to unlock the ISOFIX latches **11**, operate the adjustment mechanism body **5**, and pull the car seat body away from the seat of the passenger car. Another method is to operate the adjustment mechanism body **5** to automatically increase the length of the ISOFIX latch bodies **12** by the spring portions **14**. Still another method is to operate the adjustment mechanism body **5** and pull the ISOFIX bodies **12** with a hand of a user. The length of the ISOFIX latches **11** can thus be adjusted by a simple method.

(52) Adjustment of Length of Shoulder Straps

(53) As shown in FIGS. **2A** to **2C**, the adjustment mechanism **3** of a car seat **1A** of another embodiment is used to adjust the length of the shoulder straps **23**. As shown in FIG. **2A**, the adjustment mechanism **3** is fixed at a front position of the seat portion **21** of the car seat body (seat **20**). FIGS. **2B** and **2C** show only the shoulder straps **23** and adjustment mechanism **3** of the car seat **1** in FIG. **2A**.

(54) There is a pair of shoulder straps **23**, and the string **4** is fixed to one end of each shoulder strap **23**. Namely, there is a pair of strings **4**, and the pair of strings **4** is held by the one ends of the pair of shoulder straps **23**.

(55) The adjustment mechanism **3** is operated in order to adjust the length of the shoulder straps **23**. Specifically, in order to reduce the length of the shoulder straps **23**, the shoulder straps **23** are changed from the state shown in FIG. **2B** to the state shown in FIG. **2C** by operating the adjustment mechanism body **5** to wind up the strings **4**. In order to increase the length of the shoulder straps **23**, the adjustment mechanism body **5** is operated from the state shown in FIG. **2C** and the shoulder straps **23** are pulled out by hand. The shoulder straps **23** can thus be adjusted by a simple method.

(56) The adjustment mechanism body **5** winds up the pair of strings **4** held by the one ends of the pair of shoulder straps **23**. However, the adjustment mechanism body **5** may directly wind up the

shoulder straps **23**.

(57) Flip-Up Mechanisms for Shoulder Straps

(58) As shown in FIGS. **3A** to **3C**, the adjustment mechanism **3** of a car seat **1B** of still another embodiment is used for flip-up mechanisms **27** for the shoulder straps **23**. The flip-up mechanisms **27** for the shoulder straps **23** are a structure that flips up the shoulder strap **23** from a restraining position (FIG. **3B**) to a releasing position (FIG. **3C**) so that the shoulder belt **23** does not interfere when the child is seated on the car seat **1B**.

(59) As shown in FIG. **3B**, the flip-up mechanism **27** of the shoulder strap **23** includes a rotating portion **28** and a flip-up portion **29** that is rotatable about the rotating portion **28**. As shown in FIG. **3C**, when the flip-up portion **29** flips up, the shoulder strap **23** flips up with the flip-up portion **29**. As shown in FIG. **3A**, the adjustment mechanism **3** is fixed at a front position of the seat portion **21** of the car seat body (seat **20**). As shown in FIG. **3B**, one end of the string **4** is connected to the rotating portion **28** of the flip-up mechanism **27**.

(60) A method for operating the flip-up mechanisms **27** of the shoulder straps **23** by the adjustment mechanism **3** will be described. In order to move the shoulder strap **23** from the restraining position to the releasing position, the shoulder strap **23** is changed from the state shown in FIG. **3B** to the state shown in FIG. **3C** by operating the adjustment mechanism body **5** to wind up the string **4**. In order to move the shoulder strap **23** from the releasing position to the restraining position, the adjustment mechanism body **5** is operated from the state shown in FIG. **3C** to press down the shoulder strap **23** and feeds out the string **4**. The flip-up mechanism **27** of the shoulder belt **23** can thus be operated by a simple method.

(61) Examples in which the adjustment mechanism **3** is used in the car seats **1**, **1A**, and **1B** are described above. However, the present invention is not limited to the above embodiments. Although the adjustment mechanism **3** of a first embodiment that will be described below is shown in FIGS. **1A** to **3C**, an adjustment mechanism of any embodiment may be used.

(62) The adjustment mechanism may be used to adjust the length of the crotch strap **24** that restrains the crotch of a child. In this case, one end of the string **4** of the adjustment mechanism is held by one end of the crotch strap **24**.

(63) In the case where a headrest **22a** that protects the head of a child is an extended portion extending from the body, the adjustment mechanism body **5** may be used to adjust the shape of the headrest **22a**. Specifically, adjustment of the shape of the headrest **22a** is to adjust the height of the headrest **22a**, to adjust the width of a standing wall **22b**, or to adjust the distance between a pair of sidewalls **22c**. In this case, one end of the string **4** may be connected to a movable portion of the headrest **22a**, and the adjustment mechanism body **5** may be fixed to the back of the backrest portion **22** that is a fixed portion.

(64) The adjustment mechanism **3** may be used to adjust the length of the load leg located at the front end of the base body **10**. In this case, the string **4** may be connected to one end of the load leg, and the adjustment mechanism body **5** may be fixed to the base body **10** that is a fixed portion.

(65) Baby Carrier

(66) An example in which the nursery equipment is a baby carrier will be described. A basic structure of the baby carrier may be similar to the structure of a typical baby carrier. The baby carrier is a device that allows a user to carry a child on front or back.

(67) The baby carrier includes a baby carrier body, parent shoulder straps to be worn around both shoulders of a user (e.g., parent), and parent waist straps to be worn around the waist of the parent. The baby carrier body is a portion that holds the back or belly of a child and that occupies a large area of the baby carrier. The baby carrier body is a “fixed portion” of the present embodiment, and is also a “body” of the present embodiment. The parent shoulder straps and the parent waist straps are movable portions that extend from the baby carrier body. The parent shoulder straps and the parent waist straps are an “movable portion” of the present embodiment and are also an “extended portion” of the present embodiment. The adjustment mechanism body **5** is provided in order to

adjust the length or shape of such shoulder straps or waist straps. In this case, one end of the string **4** may be connected to one end of the shoulder strap or the parent waist strap, and the adjustment mechanism body **5** may be fixed to the back of the baby carrier body that is a fixed portion.

(68) In the case where a headrest that protects the head of a child is an extended portion extending from the baby carrier body (body), the adjustment mechanism body **5** may be used to adjust the height of the headrest according to the child's growth. In this case, one end of the string **4** may be connected to a movable portion of the headrest, and the adjustment mechanism body **5** may be fixed to the back of the baby carrier body that is a fixed portion.

(69) Other Nursery Equipment

(70) The car seat, the stroller, and the baby carrier are described above as examples of the nursery equipment using the adjustment mechanism **3**. Other examples of the nursery equipment using the adjustment mechanism **3** include devices in which a child sits or sleeps, such as bassinet and high chair. The above embodiments are merely illustrative, and the present invention is not limited to the above nursery equipment as long as the nursery equipment includes a body and an extended portion extending from the body and the adjustment mechanism serves to adjust the position or shape of the extended portion.

(71) The adjustment mechanism **3** that is used in such nursery equipment will be described in detail.

First Embodiment

(72) The adjustment mechanism **3** according to a first embodiment will be described with reference to FIGS. **4A** to **9B**. The adjustment mechanism **3** can be attached at various positions on the nursery equipment. In the following description of the first embodiment, the vertical direction in FIGS. **4C**, **5**, **9A** and **9B** is the vertical direction of the adjustment mechanism **3**, and the lateral direction in FIGS. **4C**, **5**, **9A** and **9B** is the lateral direction of the adjustment mechanism **3**.

(73) As described above, the adjustment mechanism **3** generally includes the string **4** and the adjustment mechanism body **5**. Referring particularly to FIGS. **4A-4C** and **5**, the adjustment mechanism body **5** includes a holder **30**, a rotation operation member **40**, a moving member **50**, an unlock member **60**, a lock member **70**, and a reel **80**. The adjustment mechanism **3** is configured to wind up the string **4** by the rotation operation member **40** and pull out (feed out) the string **4** by operating the unlock member **60**.

(74) For example, the string **4** connects a fixed portion such as car seat body or baby carrier body to a movable portion such as shoulder belts. The string **4** is wound on the reel **80**, and is fixed to the fixed portion via the reel **80**. There may be one string **4** or a plurality of strings **4**. When there are two movable portions, both ends of one string **4** may be connected to the movable portions, and an intermediate portion of the string **4** may be wound on the reel **80**. Alternatively, one ends of two strings **4** may be connected to the movable portions, and the other ends of the two strings **4** may be connected to the fixed portion. The reel **80** may be fixed to the movable portion instead of to the fixed portion. In that case, both ends of the string **4** may be connected to the fixed portion, and the distance between the movable portion and the fixed portion may be reduced by winding the string **4** on the reel **80**.

(75) The string **4** is a long member. The string **4** means a member produced by braiding, knitting, or sewing up a yarn, thread, chemical fiber, metal, paper, etc., and also includes, for example, a wire and a belt.

(76) Referring to FIGS. **4A-4C** and **5**, the holder **30** rotatably supports the reel **80**. The holder **30** includes an upper holder **31**, a lower holder **34**, and a partition **37** interposed between the upper holder **31** and the lower holder **34**. The upper holder **31** includes an upper surface and a side surface protruding downward from the outer peripheral edge of the upper surface. The upper holder **31** has a through hole **32** substantially in the center of its upper surface. The upper end of the reel **80** extends through the through hole **32**. The upper holder **31** further has an operation hole **33** in the side surface. An operation portion **61** of the unlock member **60** extends through the operation hole

33.

(77) The lower holder **34** includes a lower surface and a side surface protruding upward from the outer peripheral edge of the lower surface. The lower holder **34** has a recess **35** in a region surrounded by the lower and side surfaces. The recess **35** holds the reel **80**. The lower holder **34** further has string holes **36** in a pair of side surfaces. The string **4** extends through the string holes **36**.

(78) The partition **37** has a flat rectangular shape, and has a through hole **38** substantially in its center. The through hole **38** is aligned with the through hole **32** of the upper holder **31** in the vertical direction. The upper end of the reel **80** extend through the through hole **38**. The partition **37** further has a plurality of rails in its upper surface. The rails guide the unlock member **60**. A protruding portion **39** protruding upward is attached to a part of the outer peripheral edge of the partition **37**.

(79) The rotation operation member **40** is a member that operates rotation of the reel **80**. The rotation operation member **40** serves as a handle the user can grip and turn. As shown in FIGS. **8A** to **8D**, the rotation operation member **40** of the present embodiment is in the shape of a knob, and includes an upper surface **41** and a side surface **42** protruding downward from the outer peripheral edge of the upper surface **41**. A drive gear portion **43** protruding downward is provided on a back surface **41a** of the rotation operation member **40** (the opposite surface **41a** of the rotation operation member **40** from the upper surface **41**). The rotation operation member **40** may have slits at regular intervals in the side surface **42** in order to make it easier for an operator to use the rotation operation member **40**.

(80) A foldable handle may be attached to the rotation operation member **40**. The handle is, for example, a rod member and is preferably in such a shape that the handle protrudes upward when in use and is folded to extend along the upper surface **41** or the side surface **42** when not in use.

(81) The moving member **50** is located under the rotation operation member **40**. The moving member **50** is a cylindrical shape that opens downward. The moving member **50** includes an upper surface **51** and an outer peripheral edge **52** protruding downward from the outer peripheral edge of the upper surface **51**. A driven gear portion **53** protruding upward is provided on the upper surface **51**. The driven gear portion **53** engages with the drive gear portion **43** provided on the rotation operation member **40**. The outer peripheral edge **52** has a plurality of vertical slits that engages with a link member **57**.

(82) As shown in FIG. **4C**, the link member **57** has a cylindrical overall shape, and includes a large diameter portion **57a**, a small diameter portion **57b** located under the large diameter portion **57a**, and a step **57c** located between the large diameter portion **57a** and the small diameter portion **57b**. The small diameter portion **57b** is smaller than the through hole **32** of the upper holder **31**. The link member **57** is therefore held in the through hole **32** of the upper holder **31** by the step **57c**. A ring **58** may be provided between the link member **57** and the upper holder **31**. A biasing member **56** is interposed between the moving member **50** and the link member **57**. The biasing member **56** is, for example, a spring and biases the moving member **50** in the direction toward the rotation operation member **40**.

(83) The reel **80** is rotatable in both forward and reverse directions (one direction and the other direction). Referring to FIGS. **4C** and **5**, the reel **80** includes a string holding portion **81**, a flange **84**, a first connection portion **85**, and a second connection portion **86** from bottom to top.

(84) The string holding portion **81** is a portion with the string **4** fixed thereto, and is a portion that winds up and feeds out the string **4**. How the string **4** is placed in the string holding portion **81** will be described with reference to FIG. **7**. In the following description, T represents the direction in which the string **4** is wound up (hereinafter also referred to as “winding direction”), and S represents the direction in which the string **4** is fed out (hereinafter also referred to as “feeding direction”).

(85) The string holding portion **81** includes a fixing portion **81a** to which the string **4** is fixed,

string extending portions **81b** along which the string **4** extends, and rounded portions **81c** located between the fixing portion **81a** and the string extending portions **81b**. The fixing portion **81a** is located substantially in the center of the string holding portion **81**, and the string **4** is fixed at its middle in the longitudinal direction to the fixing portion **81a**. The string **4** fixed to the fixing portion **81a** is wound back along the rounded portions **81c** and extends along the string extending portions **81b** to the outside of the adjustment mechanism body **5** though the string holes **36** of the lower holder **34**.

(86) The string extending portions **81b** and the rounded portions **81c** are located point symmetrically with respect to the fixing portion **81a**. The string **4** is thus held in an inverted S shape by the string holding portion **81** as viewed in plan. Since the rounded portions **81c** are located at the positions where the string **4** is wound back, the string **4** is smoothly wound around the arc shape of the rounded portions **81c**. This configuration prevents the string **4** from being worn by the corners even when the string **4** is pulled and subjected to an excessive load.

(87) As shown in FIG. 4C, the flange **84** is located above the string holding portion **81**, and is in contact with the lower part of the partition **37**. The first connection portion **85** has, for example, a cylindrical shape. The first connection portion **85** has a diameter smaller than that of the through hole **38** of the partition **37**, and extends through the through hole **38**. As shown in FIGS. 6A and 6B, the first connection portion **85** has engagement teeth **87** on its outer peripheral surface extending parallel to the rotation axis of the reel **80**. The second connection portion **86** extends through a through hole **65** of the unlock member **60**. The upper end of the second connection portion **86** connects to the small diameter portion **57b** of the link member **57**. The reel **80** is thus fixed to the link member **57**, so that the link member **57** rotates with the reel **80** when the reel **80** rotates. The reel **80** and the link member **57** may be a single-piece member.

(88) As shown in FIGS. 5, 6A, and 6B, the lock member **70** includes a pair of lock bodies **71**, engagement pawls **72**, first pins **73**, second pins **74**, and biasing portions **75**. The engagement pawls **72** are provided on the lock bodies **71**. The first and second pins **73**, **74** extend through holes of the rock bodies **71**. The biasing portions **75** bias the rock bodies **71**.

(89) Each rock body **71** is movable between a lock position (FIG. 6A) where the engagement pawls **72** engage with the engagement teeth **87** and an unlock position (FIG. 6B) where the engagement pawls **72** do not engage with the engagement teeth **87**. Each engagement pawl **72** is formed at the end of the corresponding lock body **71** that faces the reel **80**. As shown in FIG. 5, each lock body **71** has two pin holes through which the first and second pins **73**, **74** extend. This motion of the rock bodies **71** is performed by the unlock member **60** sliding up and down.

(90) As shown in FIGS. 6A and 6B, the engagement pawls **72** move in a direction perpendicular to the engagement teeth **87** of the reel **80** and engage with the engagement teeth **87** of the reel **80**. The angle of the engagement pawls **72** is preferably a right angle, but may be an acute angle. The engagement pawls **72** are movable between a first position and a second position. At the first position, the engagement pawls **72** engage with the engagement teeth **87** that rotate with the reel **80**, and prohibit rotation of the reel **80**. At the second position, the engagement pawls **72** disengage from the portion that rotates with the reel **80**, and allows rotation of the reel **80**. The first pins **73** fix the biasing portions **75**, and extend through first holes **63** of the unlock member **60**. The first pins **73** serve as guides for the unlock member **60** and as pivot points about which the rock bodies **71** rotate. The second pins **74** extend through second holes **64** of the unlock member **60**. The biasing portions **75** are, for example, torsion springs, and bias the lock bodies **71** in such a direction that the engagement pawls **72** of the lock body **71** engage with the engagement teeth **87** of the reel **80** (toward the lock position). The engagement pawls **72** of the lock member **70** and the engagement teeth **87** of the reel **80** are a "rotation lock mechanism" that prohibits rotation of the reel **80**.

(91) The unlock member **60** unlocks the reel **80** from the rotation prohibited state to allow the reel **80** to rotate freely. That is, the string **4** wound on the reel **80** can be pulled out by operating the unlock member **60**. FIG. 6A shows the state in which the unlock member **60** is not operated. In this

state, the string **4** can be wound on the reel **80** but cannot be fed out of the reel **80**. FIG. 6B shows the state in which the unlock member **60** is operated. In this state, the string **4** can be fed out of the reel **80**. By moving the unlock member **60** in a direction perpendicular to the rotation axis of the reel **80**, the unlock member **60** unlocks the reel **80** from the rotation prohibited state.

(92) As shown in FIGS. 6A and 6B, the unlock member **60** includes the operation portion **61**, an unlock body **62**, the first and second holes **63**, **64**, the through hole **65**, a recess **66**, and a biasing portion **67**. The unlock body **62** slides as the operation portion **61** is operated. The first and second holes **63**, **64**, the through hole **65**, and the recess **66** are formed in the unlock body **62**. Since the unlock member **60** is provided separately from other members, the unlock member **60** can have various shapes, and the position of the unlock member **60** is not limited. Therefore, the unlock member **60** can be designed with flexibility.

(93) The operation portion **61** is operated so as to move the engagement pawls **72** of the lock member **70** to the disengaged position. As shown in FIG. 5, the operation portion **61** protrudes outward from the operation hole **33** of the upper holder **31** so that the operation portion **61** can be pressed inward. The unlock member **60** is in the shape of a plate, and the first and second holes **63**, **64** are holes extending through the unlock member **61** in the vertical direction. Specifically, the first holes **63** are long holes extending in the direction in which the operation portion **61** is operated. The second holes **64** are substantially in an inverted L shape. The first and second holes **63**, **64** are located point symmetrically. That is, the first and second holes **63**, **64** are located in the upper right and lower left portions of the unlock member **60** in FIG. 6A.

(94) The through hole **65** is located substantially in the center of the unlock member **60**, and the upper end of the reel **80** extends through the through hole **65**. The recess **66** holds the biasing portion **67**. The biasing portion **67** is, for example, a coil spring. The biasing portion **67** is located between the protruding portion **39** of the partition **37** and the recess **66**. The unlock member **60** is thus biased to the state of FIG. 6A by the biasing portion **67**. The biasing portion **67** is a separate member from the unlock member **60**. However, the biasing portion **67** may be integral with the unlock body **62**, or may be provided on the side surface of the upper holder **31**.

(95) One-Way Clutch Mechanism

(96) A one-way clutch mechanism will be described with reference to FIGS. 6A and 6B. The one-way clutch mechanism is a mechanism that allows rotation of the reel **80** in the direction in which the string **4** is wound, and prohibits rotation of the reel **80** in the direction in which the string **4** is fed out. The one-way clutch mechanism is a mechanism that rotates easily in one direction but does not rotate in the other direction or does not rotate unless a certain load is applied. In the present embodiment, in FIG. 6A, the reel **80** rotates in the direction T in which the reel **80** winds up the string **4** (clockwise), but does not rotate in the direction S in which the reel **80** feeds out the string **4** (counterclockwise).

(97) The one-way clutch mechanism of the present embodiment includes the engagement teeth **87** provided on the reel **80** and the engagement teeth **72** that are attached to the partition **37** and that are movable between the engaged position (FIG. 6A) where the engagement teeth **72** engage with the reel **80** and the disengaged position (FIG. 6B) where the engagement teeth **72** do not engage with the reel **80**.

(98) Each engagement tooth **87** of the reel **80** includes a first tilted portion **87a** and a second tilted portion **87b**. The angle between the first tilted portion **87a** and the second tilted portion **87b** is preferably a right angle so as to conform to the shape of the engagement pawls **72** of the lock member **70**. The engagement teeth **87** of the reel **80** and the engagement pawls **72** of the lock member **70** are not limited to the illustrated shape, and may have any shape like the shape of a typical one-way clutch as long as the engagement teeth **87** and the engagement pawls **72** mesh with each other.

(99) Since the one-way clutch mechanism of the present embodiment is provided, the reel **80** rotates only in the winding direction T, and does not rotate in the feeding direction S. Accordingly,

the string **4** is wound to the reel **80** by rotating the rotation operation member **40** and is fed out of the reel **80** by operating the unlock member **70** and pulling the string **4**. This configuration prevents or reduces erroneous operations. Since the string **4** cannot be fed out of the reel **80** by rotating the rotation operation member **40**, the string **4** will not be fed out of the reel **80** even if the rotation operation member **40** is operated by mistake. This configuration improves safety.

(100) The one-way clutch mechanism of the present embodiment completely prohibits rotation in the direction in which the string **4** is fed out. However, the one-way clutch mechanism may prohibit a certain amount of rotation. The one-way clutch mechanism of the present embodiment may have a motion transmission portion and a motion separation portion like the drive gear portion **43** and the driven gear portion **53** that will be described below. From a safety point of view, such a one-way clutch mechanism is preferably used to adjust the position or shape of a portion that is not subjected to a load.

(101) Motion Transmission Portion and Motion Separation Portion

(102) The motion transmission portion and the motion separation portion that are provided on the rotation operation member **40** and the moving member **50** will be described with reference to FIGS. **8A** to **9B**.

(103) As shown in FIGS. **8C** and **8D**, the drive gear portion **43** is provided on the back surface **41a** of the rotation operation member **40**. As shown in FIG. **8B**, the drive gear portion **43** includes a first tilted portion **44** and a second tilted portion **45**. The first tilted portion **44** is tilted in the feeding direction **S** from the moving member **50** side toward the back surface **41a** of the rotation operation member **40**. The second tilted portion **45** is tilted in the winding direction **T** from the moving member **50** side toward the back surface **41a** of the rotation operation member **40**. Both the angle $\theta_{\text{sub.44}}$ between the back surface **41a** and the first tilted portion **44** and the angle $\theta_{\text{sub.45}}$ between the back surface **41a** and the second tilted portion **45** are acute angles, but the angle $\theta_{\text{sub.45}}$ is larger than the angle $\theta_{\text{sub.44}}$ ($\theta_{\text{sub.45}} > \theta_{\text{sub.44}}$).

(104) As shown in FIG. **8A**, the driven gear portion **53** is provided on the upper surface **51** of the moving member **50**. As shown in FIG. **8B**, the driven gear portion **53** includes a first tilted portion **54** and a second tilted portions **55**. The first tilted portion **54** is tilted in the winding direction **T** from the rotation operation member **40** side toward the upper surface **51** of the moving member **50**. The second tilted portion **55** is tilted in the feeding direction **S** from the upper surface **51** of the moving member **50** toward the back surface **41a** of the rotation operation member **40**. Both the angle $\theta_{\text{sub.54}}$ between the upper surface **51** and the first tilted portion **54** and the angle $\theta_{\text{sub.45}}$ between the upper surface **51** and the second tilted portion **55** are acute angles, but the angle $\theta_{\text{sub.55}}$ is larger than the angle $\theta_{\text{sub.54}}$ ($\theta_{\text{sub.55}} > \theta_{\text{sub.54}}$). In the present embodiment, $\theta_{\text{sub.44}} \approx \theta_{\text{sub.54}}$ and $\theta_{\text{sub.45}} \approx \theta_{\text{sub.55}}$, so that the drive gear portion **43** and the driven gear portion **53** securely mesh with each other.

(105) When the rotation operation member **40** is rotated in the winding direction **T**, the second tilted portion **45** of the drive gear portion **43** and the second tilted portion **55** of the moving member **50** that have a large tilt angle mesh with each other, and the moving member **50** (reel **80**) rotates with the rotation operation member **40**. The moving member **50** (reel **80**) rotating with the rotation operation member **40** is shown in FIG. **9A**.

(106) When the string **4** finishes being wound, the moving member (reel **80**) cannot rotate any more, and therefore a certain load or more (high torque) is applied to the meshing portion between the second tilted portion **45** of the drive gear portion **43** and the second tilted portion **55** of the moving member **50**. When the rotation operation member **40** is rotated in this state, the drive gear portion **43** gets over the driven gear portion **53**, and only the rotation operation member **40** rotates. That is, when a certain load or more is applied to the rotation operation member **40**, the rotational motion of the rotation operation member **40** will not be transmitted to the reel **80**. This state is shown in FIG. **9B**. As shown in FIG. **9B**, the drive gear portion **43** gets over the driven gear portion **53**, and the moving member **50** moves downward by a dimension **L**. When a certain load or more is

applied to the rotation operation member **40**, the moving member **50** repeatedly moves up and down while the rotation operation member **40** rotates without engagement.

(107) That is, the second tilted portion **45** of the drive gear portion **43** and the second tilted portion **55** of the moving member **50** normally serve as the “motion transmission portion” that transmits the rotational motion of the rotation operation member **40** to the reel **80**. When a certain load or more is applied to the rotation operation member **40**, the second tilted portion **45** of the drive gear portion **43** and the second tilted portion **55** of the moving member **50** serve as the “motion separation portion” that does not transmit the rotational motion of the rotation operation member **40** to the reel **80**.

(108) For improved operability, the rotation operation member **40** has a one-way clutch structure that does not allow the string **4** to be pulled out. When the rotation operation member **40** is rotated in the feeding direction S, the first tilted portion **44** of the drive gear portion **43** and the first tilted portion **54** of the moving member **50** mesh with each other. However, due to the one-way clutch mechanism that does not allow the reel **80** to rotate in the feeding direction S (FIG. 6A), the drive gear portion **43** of the rotation operation member **40** gets over the driven gear portion **53** of the moving member **50** and the rotation operation member **40** rotates without engagement. That is, when a certain load or more is applied to the rotation operation member **40**, the rotational motion of the rotation operation member **40** will not be transmitted to the reel **80**.

(109) The adjustment mechanism **3** of the present embodiment includes the motion transmission portion and the motion separation portion, and the rotation operation member **40** is configured to rotate without engagement when the rotation operation member **40** is rotated in the feeding direction S. Operability is thus improved. The rotation operation member **40** is also configured to rotate without engagement when the rotation operation member **40** is further rotated in the winding direction T after the string **4** finishes being wound. This configuration prevents the string **4** from being pulled hard, and can also be used as an indication of the winding condition of the string **4**.

(110) In the above embodiment, the drive gear portion **43** is provided on the back surface **41a** of the rotation operation member **40** (the opposite surface **41a** of the rotation operation member **40** from the upper surface **41**), and the driven gear portion **53** is provided on the upper surface **51** of the moving member **50**. However, the driven gear portion **53** may be provided in a direction perpendicular to the rotation axis of the reel **80** (lateral direction). A specific example of such a configuration includes a configuration in which the drive gear portion **43** is provided on the inner side surface of the rotation operation member **40** (the opposite surface of the rotation operation member **40** from the side surface **42**) and the driven gear portion **53** is provided on the moving member **50**. With this configuration, when the rotation operation member **40** is rotated and a certain load or more is applied to the rotation operation member **40**, the moving member **50** repeatedly moves in the horizontal direction (lateral direction) while the rotation operation member **40** rotates without engagement.

(111) The biasing member **56** for biasing the moving member **50** in the direction toward the rotation operation member **40** is provided in the embodiment. However, for example, a resin spring may be formed integrally with a member with the driven gear portion **53**.

(112) Operation

(113) The operation of the adjustment mechanism **3** of the first embodiment will be described. The rotation operation member **40** is rotated when winding up the string **4**, and the operation portion **61** of the unlock member **60** is pressed and the string **4** is pulled when feeding out the string **4**.

(114) Specifically, when winding up the string **4**, the rotation operation member **40** is rotated in the winding direction T (clockwise) as shown in FIG. 6A. Due to the one-way clutch mechanism, the engagement pawls **72** of the lock member **70** repeats the motion of getting over the first tilted portion **87a** of one engagement tooth **87** of the reel **80** and engaging with the next engagement tooth **87** of the reel **80**, so that the reel **80** also rotates clockwise and winds up the string **4**.

(115) When feeding out the string **4**, the operation portion **61** of the unlock member **60** is pressed

toward the holder **30** as shown in FIG. **6B**. The unlock body **62** thus slides upward in FIG. **6B**. As a result, the second pins **74** extending through the second holes **64** of the unlock body **62** move and the lock member **70** move accordingly, so that the engagement pawls **72** of the lock member **70** are disengaged from the engagement teeth **87** of the reel **80**. The reel **80** thus becomes rotatable, and the string **4** can be fed out by pulling the string **4**.

First Modification

(116) An adjustment mechanism **3A** in a first modification will be described with reference to FIG. **10**. A reel **80A** of the adjustment mechanism **3A** in the first modification is a member in which the rotation operation member **40**, the moving member **50**, the link member **57**, and the reel **80** of the above embodiment are formed integrally. Since the rotation operation member **40**, the moving member **50**, and the link member **57** are not required for the adjustment mechanism **3A** in the first modification, the number of parts is reduced and the configuration is simplified. In the first modification, the motion transmission portion and the motion separation portion are not provided because the rotation operation member **40** and the moving member **50** are formed integrally.

Second Modification

(117) An adjustment mechanism **3B** in a second modification will be described with reference to FIGS. **11A** and **11B**. FIG. **11A** shows the state in which the unlock member **60** is not operated, and FIG. **11B** shows the state in which the unlock member **60** is operated.

(118) The engagement pawl **72** of the adjustment mechanism **3B** in the second modification may be provided on the unlock member **60** of the above embodiment. Specifically, an engagement pawl **72** may be provided on the outer peripheral edge of a through hole **65B** of an unlock member **60B** so as to protrude inward in the through hole **65B**. By pressing the operation portion **61** of the unlock member **60B**, the engagement tooth **87** of the reel **80** is disengaged from the engagement pawl **72**, and the reel **80** is unlocked from the rotation prohibited state. Since the lock member **70** is not required for the adjustment mechanism **3B** in the third modification, the number of parts is reduced and the configuration is simplified.

Second Embodiment

(119) An adjustment mechanism **3C** in a second embodiment will be described with reference to FIGS. **12A** to **18B**. Only the differences from the adjustment mechanism **3** in the first embodiment will be described in detail. The second embodiment is generally different from the first embodiment in an unlock member **60C** and the one-way lock mechanism. The adjustment mechanism **3** can be attached at various positions on the nursery equipment. In the following description, the upward direction in FIGS. **12C** and **13** is the upward direction of the adjustment mechanism **3C**, and the downward direction in FIGS. **12C** and **13** is the downward direction of the adjustment mechanism **3C**.

(120) The adjustment mechanism **3C** generally includes the string **4** and an adjustment mechanism body **5C**. Referring particularly to FIGS. **12A-12C** and **13**, the adjustment mechanism body **5C** includes a holder **30C**, a rotation operation member **40C**, a moving member **50C**, an unlock member **60C**, a lock member **70C**, and a reel **80C**. The adjustment mechanism **3C** is configured to wind up the string **4** by the rotation operation member **40C** and pull out (feed out) the string **4** by operating the unlock member **60C**.

(121) The holder **30C** includes an upper holder **31C** and a lower holder **34C**. The upper holder **31C** has a through hole **32C** substantially in the center of its upper surface. The rotation operation member **40C** extends through the through hole **32C**. The upper holder **31** has holes **33C** in its side surfaces. The string **4** extends through the holes **33C**. The lower holder **34C** has a recess **35** substantially in its center. The recess **35** holds the lock member **70C**.

(122) The rotation operation member **40C** is a member for controlling rotation of the reel **80C**. The rotation operation member **40C** has cuts at regular intervals along the corner between an upper surface **41C** and a side surface **42C** so that an operator can easily use the rotation operation member **40C**. The rotation operation member **40C** further has a through hole **46C** substantially in

the center of its upper surface **41C**. The unlock member **60C** extends through the through hole **46C**. As shown in FIGS. **17C** and **17D**, the drive gear portion **43** protruding downward is provided on the back surface of the rotation operation member **40C** (the opposite surface of the rotation operation member **40C** from the upper surface **41C**).

(123) As shown in FIG. **13**, the moving member **50C** is located below the rotation operation member **40C**. The moving member **50C** has a hole in its upper surface **51C**. An unlock body **62C** of the unlock member **60C** extends through the hole. The driven gear portion **53** standing upward is provided along the outer peripheral edge **52** of the moving member **50C**. The driven gear portion **43** engages with the drive gear portion **43** of the rotation operation member **40C**.

(124) As shown in FIG. **12C**, a link member **57C** includes a bottom portion **57aC** and a side portion **57bC** standing upward from the bottom portion **57aC**. The biasing member **56** is interposed between the moving member **50C** and the link member **57C**. The biasing member **56** is, for example, a spring, and biases the moving member **50C** in the direction toward the rotation operation member **40C**.

(125) The reel **80C** includes a string holding portion **81C** and a flange **84C**. The string holding portion **81C** is located on the upper side of the flange **84C**. How the string **4** is placed in the string holding portion **81C** will be described with reference to FIG. **16**. The string holding portion **81C** of the present embodiment is different from the string holding portion **81** of the first embodiment in where the string **4** is held. The string **4** of the first embodiment was fixed at one position, namely by the fixing portion **81a** located substantially at the center of the string holding portion **81** as viewed in plan. However, the string **4** of the present embodiment is fixed at two positions, namely by two fixing portions **81aC** located above and below substantially the center of the string holding portion **81C** as viewed in plan in FIG. **16**. The fixed portions **81aC** are cuts and have such a shape that the fixed portions **81aC** can hold the ends of the string **4**. In the present embodiment, two strings **4** are provided instead of one string.

(126) As shown in FIG. **12C**, the flange **84C** extends in a direction perpendicular to the rotation axis and is in contact with the top of the lower holder **34C**. As shown in FIG. **15C**, engagement teeth **87C** are provided on the back surface of the flange **84C**.

(127) As shown in FIGS. **12C** and **15A**, the lock member **70C** includes a lock body **71C**, engagement pawls **72C** provided on the upper surface of the lock body **71C**, and a biasing member **75C** for biasing the lock body **71C**. The lock body **71C** is movable between an engaged position where the engagement pawls **72C** engage with the engagement teeth **87C** (FIG. **14A**) and a disengaged position where the engagement pawls **72C** engage with the engagement teeth **87C** (FIG. **14B**). The engagement teeth **87C** are provided on the lower surface of the reel **80C** that extends in a direction perpendicular to the rotation axis of the reel **80C**. The engagement pawls **72C** of the lock member **70C** and the engagement teeth **87C** of the reel **80C** are a “rotation lock mechanism” that prohibits rotation of the reel **80C**.

(128) The unlock member **60C** unlocks the reel **80C** from the rotation prohibited state to allow the reel **80C** to rotate freely. That is, by operating the unlock member **60C**, the string **4** wound on the reel **80C** can be pulled out. FIG. **14A** shows the state in which the unlock member **60C** is not operated. In this state, the string **4** can be wound on the reel **80C** but cannot be fed out of the reel **80C**. FIG. **14B** shows the state in which the unlock member **60C** is operated. In this state, the string **4** can be fed out from the reel **80C**. The unlock member **60C** moves in a direction parallel to the rotation axis of the reel **80C** to unlock the reel **80C** from the rotation prohibited state.

(129) Referring to FIGS. **14A** and **14B**, the unlock member **60C** includes an operation portion **61C** to be operated by the user, and an unlock body **62C** in a rod shape extending in the vertical direction. The unlock member **60C** is in contact with the top of the moving member **50C**. The unlock member **60C** is thus always biased toward an unlock position (upward) by the biasing member **75C**.

(130) One-Way Clutch Mechanism

(131) The one-way clutch mechanism will be described with reference to FIGS. 15A to 15C. In the above embodiment, the one-way clutch mechanism is implemented by the lock member 70C moving in a direction perpendicular to the rotation axis. In the present embodiment, however, the one-way clutch mechanism is implemented by the lock member 70C moving in a direction parallel to the rotation axis.

(132) In the present embodiment, the one-way clutch mechanism is implemented by engagement between the engagement teeth 87C on the reel 80C and the engagement pawls 72C on the lock member 70C. The engagement pawls 72C are movable between a first position and a second position. At the first position, the engagement pawls 72C engage with the engagement teeth 87C that rotate with the reel 80C, and prohibit rotation of the reel 80C. At the second position, the engagement pawls 72C disengage from the portion that rotates with the reel 80C, and allows rotation of the reel 80C. Each engagement tooth 87C of the reel 80C includes a first tilted portion 87aC and a second tilted portion 87bC. The angle between the first tilted portion 87aC and the second tilted portion 87bC is preferably, for example, a right angle. The angle of the engagement pawls 72C of the lock member 70C is preferably a right angle so as to conform to the shape of the engagement teeth 87. The engagement pawls 72C move in a direction perpendicular to the engagement teeth 87C.

(133) Motion Transmission Portion and Motion Separation Portion

(134) A motion transmission portion and a motion separation portion that are provided on the rotation operation member 40C and the moving member 50C will be described with reference to FIGS. 17A to 18B. The motion transmission portion and the motion separation portion will be briefly described with reference to the figures since they are substantially the same as those in the first embodiment.

(135) As shown in FIGS. 17C and 17D, the drive gear portion 43 is provided on a back surface 41aC of the rotation operation member 40C (the opposite surface of the rotation operation member 40C from an upper surface 41C). As shown in FIG. 17A, the driven gear portion 53 standing upward is provided along the outer peripheral edge 52 of the moving member 50C.

(136) As shown in FIG. 17B, when the rotation operation member 40C is rotated in the winding direction T with the drive gear portion 43 and the driven gear portion 53 meshing with each other, the moving member 50C (reel 80C) also rotate with the rotation operation member 40C. The moving member 50C (reel 80C) rotating with the rotation operation member 40C is shown in FIG. 18A.

(137) When the rotation operation member 40C continues to be rotated in the winding direction T and the string 4 finishes being wound, the moving member 50C (reel 80C) cannot rotate any more. If the rotation operation member 40C is further rotated in the winding direction T, a certain load or more is applied to the meshing portion between the drive gear portion 43 and the driven gear portion 53. As a result, as shown in FIG. 18B, the drive gear portion 43 gets over the driven gear portion 53, and only the rotation operation member 40C rotates. That is, when a certain load or more is applied to the rotation operation member 40C, the rotational motion of the rotation operation member 40C will not be transmitted to the reel 80C. This state is shown in FIG. 18B. As shown in FIG. 18B, the drive gear portion 43 gets over the driven gear portion 53, and the moving member 50 moves downward by a dimension L. When a certain load or more is applied to the rotation operation member 40C, the moving member 50C repeatedly moves up and down while the rotation operation member 40C rotates without engagement.

(138) For improved operability, the rotation operation member 40C has a one-way clutch structure that does not allow the string 4 to be pulled out. When the rotation operation member 40C is rotated in the feeding direction S, the drive gear portion 43 gets over the driven gear portion 53 and the rotation operation member 40C rotates without engagement. That is, when a certain load or more is applied to the rotation operation member 40C, the rotational motion of the rotation operation member 40C will not be transmitted to the reel 80C.

(139) Operation

(140) The operation of the adjustment mechanism 3C of the second embodiment will be described. The rotation operation member 40C is rotated when winding up the string 4, and the unlock member 60C is pressed and the string 4 is pulled when feeding out the string 4.

(141) Specifically, when winding up the string 4, the rotation operation member 40C is rotated in the winding direction T. As shown in FIGS. 14A and 15B, the engagement teeth 87C of the reel 80C are engaged with the engagement pawls 72C of the lock member 70C, but due to the one-way clutch mechanism, the engagement teeth 87C of the reel 80C repeats the motion of getting over one engagement pawl 72C and engaging with the next engagement pawl 72C of the lock member 70C, so that the reel 80C rotates clockwise and winds up the string 4.

(142) When feeding out the string 4, the operation portion 61C of the unlock member 60C is pressed down as shown in FIG. 14B. The unlock body 62C thus moves the moving member 50C downward, so that the engagement pawls 72C of the lock member 70C are disengaged with the engagement teeth 87C of the reel 80C. The reel 80C thus becomes rotatable, and the string 4 can be fed out by pulling the string 4.

(143) In the present embodiment, the rotation operation member 40C and the unlock member 60C are located at the same position. However, since the unlock member 60C makes a rotational motion, and the operation portion 61C makes a vertical moving motion, the direction in which the unlock member 60C is operated is different from the direction in which the operation portion 60C is operated. This configuration improves operability and prevents or reduces erroneous operations.

First Modification

(144) An adjustment mechanism 3D in a first modification will be described with reference to FIG. 19. The adjustment mechanism 3D may be a member in which the unlock member 60C and the lock member 70C of the above embodiment are formed integrally. That is, an unlock member 60D has a function to lock or unlock rotation of the reel 80C. By operating the unlock member 60D, the unlock member 60D moves downward, and the reel 80C becomes rotatable. In the adjustment mechanism 3D in the first modification, the unlock member 60C and the lock member 70C of the above embodiment are molded integrally. Therefore, the number of parts is reduced, and the configuration is simplified.

Second Modification

(145) An adjustment mechanism 3E in a second modification will be described with reference to FIG. 20. The adjustment mechanism 3E may be a member in which the rotation operating member 40C and the reel 80C of the above embodiment are formed integrally. That is, a reel 80E may be rotated to wind up the string 4. In the adjustment mechanism 3E in the second modification, the rotation operation member 40C and the lock member 70C are molded integrally. Therefore, the number of parts is reduced, and the configuration is simplified. In this modification, a motion transmission portion and a motion separation portion are not provided because the rotation operation member 40C and the moving member 50C of the second embodiment are formed integrally.

Third Embodiment

(146) An adjustment mechanism 3F in a third embodiment will be described with reference to FIGS. 21A to 31B. Only the differences from the adjustment mechanisms 3, 3C of the first and second embodiments will be described in detail. Although there are various differences between the first embodiment and the third embodiment, the third embodiment is generally different from the first embodiment in an unlock member 60F and a lock member 70F. The adjustment mechanism 3F can be attached at various positions on the nursery equipment. In the following description, the vertical direction in FIGS. 21C and 22 is the vertical direction of the adjustment mechanism 3F, and the lateral direction in FIGS. 21C and 22 is the lateral direction of the adjustment mechanism 3F.

(147) The adjustment mechanism 3F generally includes the string 4 and an adjustment mechanism

body 5F. Referring particularly to FIGS. 21A-21C and 22, the adjustment mechanism body 5F includes a holder 30F, a rotation operation member 40F, a moving member 50F, an unlock member 60F, a lock member 70F, and a reel 80F. As in the above embodiments, the adjustment mechanism 3F is also configured to wind up the string 4 by the rotation operation member 40F and pull out (feed out) the string 4 by operating the unlock member 60F.

(148) The holder 30F includes an upper holder 31F and a lower holder 34F. As shown in FIGS. 22 and 23, the upper holder 31F has in its upper surface a through hole 32F and a pair of long holes 32fF. The through hole 32F is offset to the left, and the long holes 32fF face each other in an oblique vertical direction in FIGS. 22 and 23 with the through hole 32F interposed therebetween.

(149) A pair of leg portions 57cF of a link member 57F extends through the through hole 32F of the upper holder 31F from above, and engagement pawls 73F, 93F of the lock member 70F extend through the through hole 32F of the upper holder 31F from below. Referring to FIG. 23, the upper holder 31F has ribs 32aF along the outer peripheral edge of the through hole 32F. The ribs 32aF protrude inward in the through hole 32F. The ribs 32aF include arc portions 32bF and engagement teeth 32cF located at regular intervals along the arc portions 32bF. The engagement teeth 32cF are provided on the inner peripheral surface of the through hole 32F of the upper holder 31F along the circumferential direction of the reel 80F. Each engagement tooth 32cF includes a first tilted portion 32dF and a second tilted portion 32eF. The first tilted portion 32dF forms substantially a right angle with respect to the arc portion 32bF, and the second tilted portion 32eF forms an obtuse angle with respect to the arc portion 32bF. The engagement pawls 73F, 93F of the lock member 70F and the engagement teeth 32cF of the upper holder 31F are a “rotation lock mechanism” that prohibit rotation of the reel 80F.

(150) As shown in FIGS. 21A and 22, the upper holder 31F has string holes 33F in a pair of side surfaces thereof. The string 4 extends through the string holes 33F. The long holes 32fF have an arc shape conforming to the circular shape of the through hole 32F. Screw holes 68dF of a second release member 64F that will be described later extend through the long holes 32fF.

(151) As shown in FIG. 22, the lower holder 34F serves as a lower lid, and is, for example, a rectangular plate member. Legs may be provided at the four corners of the lower holder 34F.

(152) The rotation operation member 40F is a member for controlling rotation of the reel 80F. As shown in FIGS. 28A and 29A, the rotation operation member 40F has a through hole 46F substantially in the center of its upper surface 41. A screw 47F extends through the through hole 46F and supports the moving member 50F such that the moving member 50F can move in the vertical direction. As shown in FIG. 28C, the drive gear portion 43 protruding downward is provided on the back surface 41a of the rotation operation member 40F (the opposite surface of the rotation operation member 40F from the upper surface 41).

(153) As shown particularly in FIGS. 28A and 28B, the moving member 50F is located below the rotation operation member 40F. A driven gear portion 53F is provided on the moving member 50F. The driven gear portion 53F is recessed downward from an upper surface 51aF of the moving member 50F. The driven gear portion 53F engages with the driven gear portion 43 on the rotation operation member 40F.

(154) As shown in FIG. 29A, the link member 57F includes an upper portion 57aF and a lower portion 57bF. The upper portion 57aF has a cylindrical shape that is open upward. The upper portion 57aF holds the moving member 50F and the biasing member 56 therein. The lower portion 57bF includes the pair of leg portions 57cF protruding downward. The leg portions 57cF are connected to the reel 80F. The link member 57F is thus fixed to the reel 80F, so that rotation of the link member 57F is directly coupled to rotation of the reel 80.

(155) As shown in FIGS. 22 and 27A-27B, the reel 80F includes a string holding portion 81F and a flange 84F that rotatably holds the string holding portion 81F. In FIG. 27B, the winding direction T and the feeding direction S of the string 4 are shown by arrows. The string 4 is placed in the string holding portion 81F in substantially the same manner as in the string holding portion 81 of the first

embodiment. In the present embodiment, there is no fixing portion that fixes the string **4** to the reel **80F**. However, as in the first embodiment, the string **4** may be fixed at its middle in the longitudinal direction as viewed in plan. In the first embodiment, the rounded portions **81c** are provided only where the string **4** is wound back, and the string holding portion **81** does not have a symmetrical shape. In the present embodiment, however, the string holding portion **81F** may be a symmetrical shape, and rounded portions **81cF** may be provided even where the string **4** is not wound back. (156) As shown in FIG. **22**, the flange **84F** of the reel **80F** extends in a direction perpendicular to the rotation axis of the reel **80F**. The flange **84F** is located above the string holding portion **81F**, and is connected to the leg portions **57cF** of the link member **57F**. That is, the reel **80F** is connected to the link member **57F**. When the link member **57F** rotates, the reel **80F** rotates with the link member **57F**.

(157) The lock member **70F** will be described with reference to FIGS. **22** to **26D**. Referring particularly to FIG. **24A**, the lock member **70F** of the present embodiment includes an upper slide member **71F**, a lower slide member **91F** located under the upper slide member **71F**, and a spring **90F** located between the upper slide member **71F** and the lower slide member **91F**.

(158) The upper slide member **71F** includes a slide body **72F**, an engagement pawl **73F**, a support portion **74F**, a first cut **77F**, a first hole **75F**, and a second hole **76F**. The engagement pawl **73F** protrudes upward from the slide body **72F**. The support portion **74F** protrudes downward from the slide body **72F**. The first cut **77F** is formed in the slide body **72F**. The first hole **75F** and the second hole **76F** branch from the first cut **77F**.

(159) The lower slide member **91F** is provided substantially symmetrically with the upper slide member **71F**. The lower slide member **91F** includes a slide body **92F**, an engagement pawl **93F**, a support portion **94F**, a first cut **97F**, a first hole **95F**, and a second hole **96F**. The engagement pawl **93F** protrudes upward from the slide body **92F**. The support portion **94F** protrudes downward from the slide body **92F**. The first cut **97F** is formed in the slide body **92F**. The first hole **95F** and the second hole **96F** branch from the first cut **97F**. The engagement pawls **73F**, **93F** extend through the through hole **32F** of the upper holder **31**. The engagement pawls **73F**, **93F** move in the horizontal direction with respect to the engagement teeth **32cF**. A guide portion **98F** extending in the lateral direction is provided on the upper portion in the figures of the lower slide member **91F** in order to guide the lateral sliding motion of the upper slide member **71F**.

(160) Since the upper slide member **71F** and the lower slide member **91F** are placed on top of each other in the vertical direction, the first holes **75F**, **95F** vertically communicate with each other, and the second holes **76F**, **96F** vertically communicate with each other. As shown in FIGS. **24B** and **24C**, as the upper slide member **71F** slides to the right and the lower slide member **91F** slides to the left, the first holes **75F**, **95F** and the second holes **76F**, **96F** change in shape and become smaller.

(161) The spring **90F** is placed between the support portion **74F** of the upper slide member **71F** and the support portion **94F** of the lower slide member **91F**. The upper slide member **71F** and the lower slide member **91F** are thus always biased in the directions away from each other.

(162) Next, the operation of the lock member **70F** will be described. As shown in FIGS. **22** and **25A-25D**, the leg portions **57cF** of the link member **57F** extend through the first holes **75F**, **95F** and the second holes **76F**, **96F** of the lock member **70F**. The leg portions **57cF** of the link member **57F** are connected to the reel **80F** with screws. The lock member **70F** is sandwiched between the link member **57F** and the reel **80F**. Therefore, when the link member **57F** is rotated in the winding direction **T** in FIG. **25A**, one leg portion **57cF** of the link member **57F** pushes the first hole **75F** of the upper slide member **71F** to the right, and the other leg portion **57cF** of the link member **57F** pushes the second hole **96F** of the lower slide member **91F** to the left, as shown in FIG. **25C**. As a result, the upper slide member **71F** moves to the right, the lower slide member **91F** moves to the left, and the engagement pawls **73F**, **93F** of the lock member **70F** move inward.

(163) FIGS. **26A** to **26D** are sectional views as viewed from line XXVI-XXVI in FIG. **21C**, showing the upper holder **31F** placed on the structure shown in FIGS. **25B** to **25D**. When the link

member 57F is rotated, the engagement pawls 73F, 93F of the lock member 70F rotate with the link member 57 with the distance between the engagement pawls 73F, 93F increased and decreased. Specifically, when the link member 57 is rotated in the winding direction T in the state shown in FIG. 26A, the engagement pawls 73F, 93F of the lock member 70F approach each other as shown in FIG. 29B. When the link member 57F is further rotated, the engagement pawls 73F, 93F of the lock member 70F engage with the next engagement tooth 32cF. The engagement pawls 73F, 93F of the lock member 70F thus wind up the string 4 while rotating, for example, by increments of 45 degrees. The lock member 70 does not rotate in the feeding direction S of the string 4 due to the one-way clutch mechanism.

(164) The unlock member 60F will be described with reference to FIGS. 22, 30, and 31A-3B. FIG. 31A shows the state in which the unlock member 60 is not operated, and FIG. 31B shows the state in which the unlock member 60 is operated. The figures on the left side of in FIGS. 31A and 31B are plan views showing only the upper holder 31F and the second release member 64F, and the figures on the right side of FIGS. 31A and 31B shows the upper holder 31F, the second release member 64F, and a first release member 61F placed on the upper holder 31F with the portion of FIG. 26A seen through. The unlock member 60 unlocks the reel 80F from the rotation prohibited state when the unlock member 60 moves in a direction perpendicular to the rotation axis of the reel 80F. For better understanding, the first release member 64F is shown shaded in FIGS. 30 and 31A-31B.

(165) Referring particularly to FIG. 22, the unlock member 60F includes the first release member 61F, the second release member 64F, and a biasing portion 69F. The first release member 61F is operated by the user. The second release member 64F slides in the vertical direction when the first release member 61F is operated. The biasing portion 69F biases the second release member 64F in the opposite direction to the unlock direction. The first release member 61F and the second release member 64F are configured to move together. The biasing portion 69F is, for example, a coil spring, and biases the first release member 61F and the second release member 64F in the directions away from each other. The first release member 61F, the second release member 64F, and the biasing portion 69F may not be separate members, but may be a single-piece member.

(166) The first release member 61F includes an unlock body 62F and a through hole 63F located substantially in the center of the unlock body 62F. The unlock body 62F further has a pair of screw holes 62aF. Although the unlock body 62F has a substantially circular shape as viewed in plan, a part of the unlock body 62F protrudes and serves as an operation portion. The leg portions 57cF of the link member 57F extend through the through hole 63F.

(167) Referring to FIGS. 22 and 30, the second release member 64F includes a release body 65F and a protrusion 66F protruding from the release body 65F. The release body 65F has a through hole 67F substantially in its center, and has a pair of screw holes 68dF around the through hole 67F. The leg portions 57cF of the link member 57F extend through the through hole 67F. Screws extending through the screw holes 62aF of the first release member 61F extend through the screw holes 68dF. The protrusion 66F has a hole 66aF. A pin member 69aF located at an end of the biasing member 69F extends through the hole 66aF. The unlock member 62F is thus biased in the opposite direction to the unlock direction.

(168) Next, the operation of the unlock member 60F will be described. As shown in FIG. 31A, when the first release member 61F of the unlock member 60F is rotated counterclockwise (by about 45 degrees), the second release member 64F is also rotated counterclockwise. As shown in FIG. 31B, the engagement teeth 32cF of the ribs 32aF of the upper holder 31F are covered by arc portions 67aF of the second release member 64F, and the engagement pawls 73F, 93F of the lock member 70F move inward, so that the reel 80F connected to the lock member 70F becomes rotatable. The lock member 70F can thus be disengaged from the upper holder 30F by moving the unlock member 60F in a direction perpendicular to the rotation axis of the reel 80F.

(169) One-Way Clutch Mechanism

(170) The one-way clutch mechanism will be described with reference to FIGS. 26A to 26D. As in the first embodiment, the one-way clutch mechanism of the present embodiment is implemented by the lock member 70F moving in a direction perpendicular to the rotation axis.

(171) The one-way clutch mechanism of the present embodiment is implemented by engagement between the engagement teeth 32cF on the upper holder 31F and the engagement pawls 73F, 93F on the lock member 70F. The engagement pawls 73F, 93F move in a direction perpendicular to the engagement teeth 32cF. Each engagement tooth 32cF of the upper holder 31F includes the first tilted portion 32dF and the second tilted portion 32eF. The angle between the first tilted portion 32dF and the arc portion 32bF is preferably, for example, a right angle. The angle between the second tilted portion 32eF and the arc portion 32bF is preferably, for example, an obtuse angle. This structure allows the reel 80F to rotate in the winding direction T, but does not allow the reel 80F to rotate in the feeding direction S.

(172) Motion Transmission Portion and Motion Separation Portion

(173) A motion transmission portion and a motion separation portion that are provided between the rotation operation member 40F and the moving member 50F will be described with reference to FIGS. 25A to 26D. The motion transmission portion and the motion separation portion will be briefly described with reference to the figures since they are substantially the same as those in the first embodiment.

(174) As shown in FIG. 28C, the drive gear portion 43 is provided on the back surface of the rotation operation member 40F. As shown in FIG. 28A, the driven gear portion 53F is provided on the upper surface of the moving member 50F.

(175) As shown in FIG. 28A, when the rotation operation member 40F is rotated with the drive gear portion 43 meshing with the driven gear portion 53F, the moving member 50F (reel 80F) also rotates with the rotation operation member 40F. When the rotation operation member 40F continues to be rotated in the winding direction T and the string 4 finishes being wound, the moving member 50F (reel 80F) cannot rotate any more, and a certain load or more is applied to the meshing portion between the drive gear portion 43 and the driven gear portion 53F. If the rotation operation member 40F is further rotated in this state, the drive gear portion 43 gets over the driven gear portion 53F, and only the rotation operation member 40F rotates, as shown in FIG. 28B. That is, when a certain load or more is applied to the rotation operation member 40F, the rotational motion of the rotation operation member 40F will not be transmitted to the reel 80F.

(176) For improved operability, the rotation operation member 40F has a one-way clutch structure that does not allow the string 4 to be pulled out. When the rotation operation member 40F is rotated in the feeding direction S, the drive gear portion 43 gets over the driven gear portion 53F and the rotation operation member 40F rotates without engagement. That is, when a certain load or more is applied to the rotation operation member 40F, the rotational motion of the rotation operation member 40F will not be transmitted to the reel 80F.

(177) Operation

(178) The operation of the adjustment mechanism 3F of the third embodiment will be described. The rotation operation member 40F is rotated when winding up the string 4, and the unlock member 60F is rotated and the string 4 is pulled when feeding out the string 4.

(179) Specifically, when winding up the string 4, the rotation operation member 40F (reel 80F) is rotated clockwise as shown in FIG. 25A. Due to the one-way clutch mechanism, each of the engagement pawls 73F, 93F of the lock member 70 repeats the motion of disengaging from one engagement tooth 32cF of the upper holder 31F and engaging with the next engagement tooth 32cF of the upper holder 31F, so that the reel 80F also rotates clockwise and winds up the string 4, as shown in FIGS. 26A to 26D.

(180) When feeding out the string 4, the first release member 61F of the unlock member 60F is rotated counterclockwise (in the direction shown by arrow S in FIG. 26A) as shown in FIGS. 31A and 31B. The second release member 64F thus rotates, and the arc portions 67aF of the second

release member **62F** cover the engagement teeth **32cF** of the upper holder **31F**. Therefore, the engagement pawls **73F**, **93F** of the lock member **70F** will not engage with the engagement teeth **32cF** of the upper holder **31F**. The reel **80F** thus becomes rotatable, and the string **4** can be fed out by pulling the string **4**.

(181) In the present embodiment, the unlock member **60F** and the unlock member **70F** are separate members. However, the unlock member **60F** and the unlock member **70F** may be a single-piece member, as in the above embodiments.

First Modification

(182) An adjustment mechanism **3G** in a first modification will be described with reference to FIGS. **32A** to **32D**. The adjustment mechanism **3G** is different from the third embodiment in the configuration of the motion transmission portion and the motion separation portion. In the third embodiment, the biasing member **56** is provided under the moving member **50F**, and the moving member **50F** is biased toward the rotation operation member **40F**. In the present modification, however, a rotation operation member **40G** is biased toward a moving member **50G**.

(183) Specifically, the adjustment mechanism **3G** further includes a lid **48G** that is fitted in a recess **46G** in the upper surface of a rotation operation member **40G**. A biasing member **56G** that biases the rotation operation member **40G** downward is provided between the recess **46G** of the rotation operation member **40G** and the lid **48G**. Accordingly, when the rotation operation member **40G** is rotated under more than a certain load, the drive gear portion **43** on the rotation operation member **40G** gets over the driven gear portion **53** on the moving member **50G**, and the rotation operation member **40G** rotates without engagement. In the present modification, the rotation operation member **40G** moves up and down when the rotation operation member **40G** rotates without engagement.

Fourth Embodiment

(184) An adjustment mechanism **311** in a fourth embodiment will be described with reference to FIGS. **33** and **34A-34D**. Only the differences from the adjustment mechanism **3C** in the second embodiment will be described in detail. The present embodiment is different from the second embodiment in that the rotation operation member is not provided and a biasing member **11011** for biasing the reel **80C** in the winding direction is provided. The adjustment mechanism **311** can be attached at various positions on the nursery equipment. In the following description, the upward direction in FIG. **33** is the upward direction of the adjustment mechanism **311**, and the downward direction in FIG. **33** is the downward direction of the adjustment mechanism **311**.

(185) The adjustment mechanism **311** of the present embodiment includes the string **4**, the holder **30C**, the unlock member **60C**, the lock member **70C**, the reel **80C**, and the biasing member **11011**. The adjustment mechanism **311** can automatically wind up the loose string **4**.

(186) The biasing force of the biasing member **11011** is set to be smaller than the biasing force with which a movable portion tends to move downward in the vertical direction. The biasing force will be described in detail in the description of the operation. The biasing member **11011** is, for example, a mainspring wound in a helical shape. One end of the biasing member **11011**, namely a radially inner end of the biasing member **11011**, is fixed to the reel **80C**, and the other end of the biasing member **11011**, namely a radially outer end of the biasing member **11011**, is fixed to the upper holder **31C**. The reel **80C** is thus always biased in the winding direction of the spring **4**.

(187) In the present embodiment, the mainspring is used as the biasing member **11011**. However, the biasing member **11011** may be any member that biases the reel **80C** so that the reel **80C** rotates in the winding direction of the string **4**. For example, the biasing member **11011** may be other spring, or may be other biasing member that applies an elastic biasing force.

(188) As described above, the lock member **70C** is a one-way clutch mechanism that allows rotation of the reel **80C** in the winding direction of the string **4** and prohibits rotation of the reel **80C** in the feeding direction of the string **4**. The one-way clutch mechanism may have a configuration in which a motion transmission portion and a motion separation portion are provided

like the drive gear portion **43** and the driven gear portion **53**, or may be a configuration similar to that described in the second embodiment.

(189) The engagement pawls **72C** of the lock member **70C** are reel lock pawls that lock rotation of the reel **80C**. The reel lock pawls are movable between a first position and a second position. At the first position, the reel lock pawls engage with a portion that rotates with the reel **80C**, and prohibit rotation of the reel **80C**. At the second position, the reel lock pawls disengage from the portion that rotates with the reel **80C**, and allows rotation of the reel **80C**. This motion of the engagement pawls **72C** is performed by the lock member **70C** sliding up and down, and is shown in FIGS. **14A** and **14B**.

(190) The lock member **70C** is caused to slide up and down by the unlock member **60C**. The unlock member **60C** is a member that moves the lock member **70C** to the second position so that the reel **80C** can rotate freely.

(191) The operation of a car seat **1C** will be described with reference to FIGS. **34A** to **34D**. The car seat **1C** is nursery equipment that uses the adjustment mechanism **311** in the fourth embodiment. The basic configuration of the car seat **1C** used in the present embodiment is substantially the same as that of the car seat **1B** in FIGS. **3A-3C**.

(192) As shown in FIGS. **34A-34D**, an adjustment mechanism body **511** is provided at the upper end of the backrest portion **22** of the car seat **1C**. The string **4** is attached to the rotating portion **28** of the flip-up mechanism **27** for the shoulder strap **23**. The flip-up mechanism **27** for the shoulder strap **23** is a mechanism that fixes the shoulder strap **23** so as to open the seat **20** so that the shoulder belt **23** does not interfere when a child is seated on the car seat **1C**.

(193) When the buckle **26** is disconnected from the state shown in FIG. **34A** and the shoulder strap **23** is moved upward as shown in FIG. **34B**, the string **4** connected to the rotating portion **28** becomes loose. The adjustment mechanism **311** includes the biasing member **11011** (FIG. **33**) that biases the reel **80C** so that the reel **80C** rotates in the winding direction of the string **4**. The biasing force of the biasing member **11011** is set to be smaller than the biasing force with which the shoulder strap **23** and the flip-up mechanism **27** move downward in the vertical direction due to their own weight. In other words, the biasing member **11011** rotates the reel **80C** to wind up the string **4** when the biasing force with which the shoulder strap **23** and the flip-up mechanism **27** move downward in the vertical direction is no longer applied.

(194) Since the reel **80C** is biased to rotate in the winding direction of the string **4**, the loose string **4** is wound on the reel **80C** as shown in FIG. **34C**. Since the loose string **4** can be wound up without requiring the user to do anything, the user can smoothly get a child into and out of the car seat **1C**.

(195) After getting a child into the car seat **1C**, the user operates the operation portion **61C** of the unlock member **60C** to unlock the lock member **70C** and the reel **80C**, as shown in FIG. **34D**. Since the biasing force of the biasing member **11011** is smaller than the biasing force with which the shoulder strap **23** and the flip-up mechanism **27** tend to move downward in the vertical direction, the string **4** is automatically pulled out due to the weight of the shoulder strap **23** and the flip-up mechanism **27**. Lastly, the user connects the shoulder straps **23** by the buckle **26**.

(196) In the present embodiment, the movable portion is the flip-up mechanism **27** for the shoulder strap **23** and the shoulder strap **23**. However, the movable portion may be any member that tends to move downward in the vertical direction due to its own weight. For example, in a reclining mechanism of a stroller, the backrest portion may be a movable portion. Alternatively, regarding headrest height adjustment of a baby carrier, the headrest portion may be a movable portion.

(197) Although the movable portion moves downward in the vertical direction in the above description, the movable portion need not necessarily move downward perpendicularly to a horizontal plane, but may move downward at an angle with respect to the vertical direction. The force with which the movable portion tends to move downward in the vertical direction is not limited to the weight of the movable portion itself, and may include the biasing force of a spring

etc. that moves the movable portion downward in the vertical direction.

(198) In the present embodiment, the unlock member **60C** and the lock member **70C** are separate members. However, the unlock member **60C** and the lock member **70C** may be a single-piece member.

(199) Although the embodiments of the present invention are described above with reference to the drawings, the present invention is not limited to the illustrated embodiments. Various modifications and alterations can be made to the illustrated embodiments within the scope that is the same as or equivalent to that of the present invention.

Claims

1. A nursery equipment, comprising: a fixed portion; a movable portion that is movable relative to the fixed portion; and an adjustment mechanism that adjusts a position or shape of the movable portion, wherein the adjustment mechanism includes: a string connecting the fixed portion and the movable portion, a reel that is rotatable in both forward and reverse directions and that changes the position or shape of the movable portion by winding up and feeding out the string, a rotation operation member that controls rotation of the reel, a motion transmission portion that transmits a rotational motion of the rotation operation member to the reel, and a motion separation portion that does not transmit the rotational motion of the rotation operation member to the reel, wherein the motion transmission portion or the motion separation portion includes a drive gear portion and a driven gear portion meshed with the drive gear.
2. The nursery equipment according to claim 1, wherein the motion transmission portion normally transmits the rotational motion of the rotation operation member to the reel, and the rotation separation portion does not transmit the rotational motion of the rotation operation member to the reel under more than a certain load.
3. The nursery equipment according to claim 1, wherein: when the rotation operation member rotates in one direction, the motion transmission portion transmits the rotational motion of the rotation operation member to the reel, and when the rotation operation member rotates in the other direction, the rotation separation portion does not transmit the rotational motion of the rotation operation member to the reel.
4. The nursery equipment according to claim 1, wherein: the reel includes a reel body that winds up and feeds out the string, and a moving member that is located between the reel body and the rotation operation member, and the drive gear portion is located on the rotation operation member and the driven gear portion is located on the moving member.
5. The nursery equipment according to claim 4, wherein the moving member is biased in a direction toward the rotation operation member.
6. The nursery equipment according to claim 4, wherein: the drive gear portion includes a first tilted portion tilted in a winding direction of the string from the reel toward the rotation operation member, and a second tilted portion tilted in a feeding direction of the string from the reel toward the rotation operation member, and an angle of the first tilted portion with respect to the winding direction is smaller than an angle of the second tilted portion with respect to the feeding direction.
7. A nursery equipment, comprising: a fixed portion; a movable portion configured to be movable relative to the fixed portion; and an adjustment mechanism configured to adjust a position or shape of the movable portion, the adjustment mechanism comprising: a string connecting the fixed portion and the movable portion; a reel configured to be rotatable in both forward and reverse directions and to change the position or shape of the movable portion by winding up and feeding out the string; a rotation operation member configured to control rotation of the reel; a motion transmission portion configured to transmit a rotational motion of the rotation operation member to the reel; and a motion separation portion that does not transmit the rotational motion of the rotation operation member to the reel, wherein the motion transmission portion or the motion separation

portion comprises a drive gear portion and a driven gear portion meshed with the drive gear.

8. The nursery equipment according to claim 7, wherein the motion transmission portion normally transmits the rotational motion of the rotation operation member to the reel, and the rotation separation portion does not transmit the rotational motion of the rotation operation member to the reel under more than a certain load.

9. The nursery equipment according to claim 7, wherein, when the rotation operation member rotates in one direction, the motion transmission portion transmits the rotational motion of the rotation operation member to the reel, and, when the rotation operation member rotates in the other direction, the rotation separation portion does not transmit the rotational motion of the rotation operation member to the reel.

10. The nursery equipment according to claim 7, wherein the reel comprises: a reel body configured to wind up and feed out the string; and a moving member that is located between the reel body and the rotation operation member.

11. The nursery equipment according to claim 10, wherein the moving member is biased in a direction toward the rotation operation member.

12. The nursery equipment according to claim 10, wherein the drive gear portion is located on the rotation operation member and the driven gear portion is located on the moving member.

13. The nursery equipment according to claim 12, wherein the drive gear portion comprises: a first tilted portion tilted in a winding direction of the string from the reel toward the rotation operation member; and a second tilted portion tilted in a feeding direction of the string from the reel toward the rotation operation member.

14. The nursery equipment according to claim 13, wherein an angle of the first tilted portion with respect to the winding direction is smaller than an angle of the second tilted portion with respect to the feeding direction.

15. A method for using a nursery equipment, the method comprising: controlling a rotation operation member to cause a motion transmission portion of an adjustment mechanism of the nursery equipment to transmit a rotational motion of the rotation operation member to rotate a reel of the nursery equipment in a forward direction or a reverse direction to change a position or shape of a movable portion of the nursery equipment connected to a fixed portion of the nursery equipment via a string by winding up and feeding out the string, wherein a motion separation portion of the adjustment mechanism of the nursery equipment does not transmit the rotational motion of the rotation operation member to the reel, and wherein the motion transmission portion or the motion separation portion comprises a drive gear portion and a driven gear portion meshed with the drive gear.

16. The method according to claim 15, wherein the motion transmission portion normally transmits the rotational motion of the rotation operation member to the reel, and the rotation separation portion does not transmit the rotational motion of the rotation operation member to the reel under more than a certain load.

17. The method according to claim 15, wherein rotating the rotation operation member in one direction causes the motion transmission portion to transmit the rotational motion of the rotation operation member to the reel, and wherein, when rotating the rotation operation member in the other direction, the rotation separation portion does not transmit the rotational motion of the rotation operation member to the reel.

18. The method according to claim 15, wherein the reel comprises: a reel body configured to wind up and feed out the string; and a moving member that is located between the reel body and the rotation operation member, wherein the moving member is biased in a direction toward the rotation operation member.

19. The method according to claim 18, wherein the drive gear portion is located on the rotation operation member and the driven gear portion is located on the moving member.

20. The method according to claim 19, wherein the drive gear portion comprises: a first tilted

portion tilted in a winding direction of the string from the reel toward the rotation operation member; and a second tilted portion tilted in a feeding direction of the string from the reel toward the rotation operation member, wherein an angle of the first tilted portion with respect to the winding direction is smaller than an angle of the second tilted portion with respect to the feeding direction.
