

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404778
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Johnson; Steven Douglas et al.

Turbine engine with a rotor seal assembly

Abstract

A turbine engine having a stator, a rotor, and a seal assembly. The rotor being rotatable about a rotational axis. The seal assembly having a carriage assembly, a seal body and a biasing element. The carriage assembly being carried by the stator. The carriage assembly defining a seal cavity. The seal body being provided within the seal cavity.

Inventors: Johnson; Steven Douglas (Milford, OH), McManus; Kevin Randall (Cincinnati, OH), Bidkar; Rahul Anil (Niskayuna, NY)

Applicant: GENERAL ELECTRIC COMPANY (Schenectady, NY)

Family ID: 84241522

Assignee: General Electric Company (Evendale, OH)

Appl. No.: 18/483173

Filed: October 09, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240035390 A1	Feb. 01, 2024

Related U.S. Application Data

continuation parent-doc US 17338807 20210604 US 11821320 child-doc US 18483173

Publication Classification

Int. Cl.: F01D11/22 (20060101); F01D11/00 (20060101); F01D11/02 (20060101)

U.S. Cl.:

CPC **F01D11/001** (20130101); **F01D11/025** (20130101); **F01D11/22** (20130101);
F05D2220/323 (20130101); F05D2240/11 (20130101); F05D2240/80 (20130101);
F05D2260/38 (20130101)

Field of Classification Search

CPC: F01D (11/001); F01D (11/025); F01D (11/22); F05D (2220/323); F05D (2240/11); F05D
(2240/80); F05D (2260/38)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5100158	12/1991	Gardner	N/A	N/A
5143384	12/1991	Lipschitz	N/A	N/A
5301957	12/1993	Hwang	N/A	N/A
5509664	12/1995	Borkiewicz	N/A	N/A
6145843	12/1999	Hwang	N/A	N/A
6505837	12/2002	Heshmat	N/A	N/A
6572115	12/2002	Sarshar et al.	N/A	N/A
6655696	12/2002	Fang et al.	N/A	N/A
6692006	12/2003	Holder	N/A	N/A
6811154	12/2003	Proctor et al.	N/A	N/A
7726660	12/2009	Datta	N/A	N/A
7914007	12/2010	Berard	N/A	N/A
8002285	12/2010	Justak	N/A	N/A
8056902	12/2010	Roddis	N/A	N/A
8641045	12/2013	Justak	N/A	N/A
9045994	12/2014	Bidkar et al.	N/A	N/A
9115810	12/2014	Bidkar et al.	N/A	N/A
9145785	12/2014	Bidkar et al.	N/A	N/A
9255642	12/2015	Bidkar et al.	N/A	N/A
9359908	12/2015	Bidkar et al.	N/A	N/A
9587746	12/2016	Bidkar et al.	N/A	N/A
10060280	12/2017	Crawley, Jr. et al.	N/A	N/A
10161259	12/2017	Gibson et al.	N/A	N/A
10190431	12/2018	Bidkar et al.	N/A	N/A
10352455	12/2018	Berard	N/A	N/A
10443424	12/2018	McCaffrey	N/A	N/A
10539034	12/2019	Miller	N/A	N/A
10633997	12/2019	Scimeca	N/A	N/A
10781709	12/2019	Sen	N/A	N/A
2007/0053772	12/2006	Couture, Jr. et al.	N/A	N/A
2007/0274829	12/2006	Chevette	415/231	F16J 15/442
2008/0056895	12/2007	Senoo	N/A	N/A
2012/0223483	12/2011	Bidkar et al.	N/A	N/A
2014/0008871	12/2013	Bidkar et al.	N/A	N/A
2014/0062024	12/2013	Bidkar et al.	N/A	N/A
2015/0159498	12/2014	Mukhopadhyay et al.	N/A	N/A

2016/0010480	12/2015	Bidkar et al.	N/A	N/A
2016/0097291	12/2015	Hayford et al.	N/A	N/A
2016/0130963	12/2015	Wilson et al.	N/A	N/A
2016/0138412	12/2015	Rioux	N/A	N/A
2016/0281531	12/2015	Dube	N/A	F01D 11/001
2016/0376907	12/2015	O'Leary et al.	N/A	N/A
2017/0051621	12/2016	Ackermann et al.	N/A	N/A
2017/0370474	12/2016	Berard	N/A	N/A
2018/0372229	12/2017	Bidkar et al.	N/A	N/A
2019/0072186	12/2018	Bidkar et al.	N/A	N/A
2019/0085712	12/2018	Wesling et al.	N/A	N/A
2019/0203842	12/2018	Bidkar et al.	N/A	N/A
2019/0218927	12/2018	Difrancesco	N/A	N/A
2020/0040735	12/2019	Millier et al.	N/A	N/A
2020/0063588	12/2019	Morliere et al.	N/A	N/A
2020/0318489	12/2019	Webb	N/A	N/A
2021/0148244	12/2020	Freeman	N/A	N/A
2022/0235667	12/2021	Mizumi et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103237960	12/2012	CN	N/A
110017211	12/2018	CN	N/A
1707751	12/2014	EP	N/A
3234419	12/2016	EP	N/A
3263842	12/2017	EP	N/A
2019/224463	12/2018	WO	N/A

OTHER PUBLICATIONS

Grondahl et al., "Film Riding Leaf Seals for Improved Shaft Sealing", Proceeding of ASME Turbo Expo 2010: Power for Land, Sea and Air, Jun. 14-18, 2010, 8 pages, Glasgow, UK. cited by applicant

Munson et al., "Development of Film Riding Face Seals for a Gas Turbine Engine", Tribology Transactions, 35:1. 65-70, DOI: 10.1080/10402009208982090, Published Mar. 25, 2008, 7 pages, vol. 35 (1992). cited by applicant

Steinetz et al., "Advanced Seal Technology Role in Meeting Next Generation Turbine Engine Goals", RTO AVT Symposium on "Design Principles and Methods for Aircraft Gas Turbine Engines", 14 pages, May 11-15, 1998, Toulouse France. cited by applicant

Primary Examiner: Wong; Elton K

Assistant Examiner: Ribadeneyra; Theodore C

Attorney, Agent or Firm: Dority & Manning, P.A.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S)

(1) This application claims priority to U.S. patent application Ser. No. 17/338,807, filed Jun. 4, 2021, now U.S. Pat. No. 11,821,320, which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

(2) The disclosure generally relates to a turbine engine, and more specifically to a rotor seal assembly for a gas turbine engine.

BACKGROUND

(3) Turbine engines, and particularly gas turbine engines, are rotary engines that extract energy from a flow of working air passing serially through a compressor section, where the working air is compressed, a combustor section, where fuel is added to the working air and ignited, and a turbine section, where the combusted working air is expanded and work taken from the working air to drive the compressor section along with other systems, and provide thrust in an aircraft implementation. The compressor and turbine stages comprise axially arranged pairs of rotating blades and stationary vanes. The gas turbine engine can be arranged as an engine core comprising at least a compressor section, a combustor section, and a turbine section in axial flow arrangement and defining at least one rotating element or rotor and at least one stationary component or stator. A seal assembly, specifically a labyrinth seal assembly, can be located between the stator and the rotor and be used to reduce leakage fluids between the rotor and stator. In a bypass turbofan implementation, an annular bypass air flow passage is formed about the core, with a fan section located axially upstream of the compressor section.

BRIEF DESCRIPTION

(4) In one aspect, the disclosure relates to a turbine engine comprising an engine core comprising at least a compressor section, a combustor section, and a turbine section in axial flow arrangement defining an axial direction and an engine centerline, and defining a rotor and a stator, a carriage assembly carried by the stator and having a seal seat defining a seal cavity, and a seal assembly having a floating seal body, at least partially located within the seal cavity and having a first seal face confronting the rotor, and a biasing element located within the seal cavity and biasing the floating seal body such that the seal face is biased toward the rotor.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) A full and enabling disclosure of the present description, including the best mode thereof, directed to one of ordinary skill in the art, is set forth in the specification, which refers to the appended FIGS., in which:

(2) FIG. 1 is a schematic cross-sectional view of a gas turbine engine for an aircraft.

(3) FIG. 2 is a schematic cross-sectional view of the gas turbine engine of FIG. 1, further including a rotor and a stator with a rotor seal assembly disposed therebetween.

(4) FIG. 3A is an enlarged schematic cross-sectional view of the rotor seal assembly of FIG. 2, further including a carriage assembly, a seal assembly, and a biasing element in a first position with respect to the rotor.

(5) FIG. 3B is an enlarged schematic cross-sectional view of the rotor seal assembly of FIG. 2, further including the carriage assembly, the seal assembly, and the biasing element in a second position with respect to the rotor.

(6) FIG. 4 is a schematic cross-sectional illustration of an exemplary rotor seal assembly of FIG. 2, further including a radial fastener coupling the biasing element to the carriage assembly.

(7) FIG. 5 is a schematic cross-sectional illustration of an exemplary rotor seal assembly of FIG. 2, further including a circumferential pin coupling the biasing element to the carriage assembly.

(8) FIG. 6 is a schematic cross-sectional illustration of an exemplary rotor seal assembly of FIG. 2,

- further including a pin extending axially and coupling the biasing element to the carriage assembly.
- (9) FIG. 7 is a schematic cross-sectional illustration of an exemplary rotor seal assembly of FIG. 2, further including an exemplary pin extending axially and coupling the biasing element to the carriage assembly.
- (10) FIG. 8 is a schematic cross-sectional illustration of an exemplary rotor seal assembly of FIG. 2, further an exemplary pin extending axially coupling the biasing element to the carriage assembly.
- (11) FIG. 9 is a schematic cross-sectional illustration of an exemplary rotor seal assembly of FIG. 2, further including a biasing element integrally formed with the carriage assembly.
- (12) FIG. 10 is a schematic cross-sectional illustration of an exemplary rotor seal assembly of FIG. 2, further including an exemplary pin axially extending and coupling the biasing element to the carriage assembly, and further including a fastener securing the biasing element to the seal assembly.
- (13) FIG. 11 is a schematic cross-sectional illustration of an exemplary rotor seal assembly of FIG. 2, further including a carriage assembly including an internal passage fluidly coupled to the interior of the biasing element.
- (14) FIG. 12 is a schematic cross-sectional illustration of an exemplary rotor seal assembly of FIG. 2, further including a protrusion extending from the carriage assembly.

DETAILED DESCRIPTION

- (15) Aspects of the disclosure described herein are broadly directed to a rotor seal assembly having a seal with a floating portion confronting a rotor of the gas turbine engine and a static portion carried by a stator of the gas turbine engine. Specifically, the rotor seal assembly includes a carriage assembly carried by the gas turbine engine and having a seal seat defining a seal cavity, and a seal assembly having a floating seal body including a first seal face opposing the rotor. In some instances, a biasing element can be positioned between the carriage assembly and the floating seal body such that the floating seal body can move between a first position and a second position with the first position being displaced radially inward with respect to the rotor when compared to the second position. The floating seal body can further include an internal passage fluidly coupling an inlet on a second seal face defined as an upstream or axially forward face of the floating seal body to an outlet provided on a third seal face radially opposite the first seal face. The outlet can be fluidly coupled to an interior of the biasing element.
- (16) The rotor seal assembly can provide for a dynamic sealing environment through the use of the biasing element moveable between the first position and the second position. For the purposes of illustration, one exemplary environment within which the rotor seal assembly can be utilized will be described in the form of a turbine engine. Such a turbine engine can be in the form of a gas turbine engine, a turboprop, turboshaft or a turbofan engine having a power gearbox, in non-limiting examples. It will be understood, however, that aspects of the disclosure described herein are not so limited and can have general applicability within other sealing systems. For example, the disclosure can have applicability for a rotor seal assembly in other engines or vehicles, and can be used to provide benefits in industrial, commercial, and residential applications.
- (17) As used herein, the term “upstream” refers to a direction that is opposite the fluid flow direction, and the term “downstream” refers to a direction that is in the same direction as the fluid flow. The term “fore” or “forward” means in front of something and “aft” or “rearward” means behind something. For example, when used in terms of fluid flow, fore/forward can mean upstream and aft/rearward can mean downstream.
- (18) Additionally, as used herein, the terms “radial” or “radially” refer to a direction away from a common center. For example, in the overall context of a turbine engine, radial refers to a direction along a ray extending between a center longitudinal axis of the engine and an outer engine circumference. Furthermore, as used herein, the term “set” or a “set” of elements can be any number of elements, including only one.

(19) Further yet, as used herein, the term “fluid” or iterations thereof can refer to any suitable fluid within the gas turbine engine at least a portion of the gas turbine engine is exposed to such as, but not limited to, combustion gases, ambient air, pressurized airflow, working airflow, or any combination thereof. It is yet further contemplated that the gas turbine engine can be other suitable turbine engine such as, but not limited to, a steam turbine engine or a supercritical carbon dioxide turbine engine. As a non-limiting example, the term “fluid” can refer to steam in a steam turbine engine, or to carbon dioxide in a supercritical carbon dioxide turbine engine.

(20) All directional references (e.g., radial, axial, proximal, distal, upper, lower, upward, downward, left, right, lateral, front, back, top, bottom, above, below, vertical, horizontal, clockwise, counterclockwise, upstream, downstream, forward, aft, etc.) are only used for identification purposes to aid the reader's understanding of the present disclosure, and do not create limitations, particularly as to the position, orientation, or use of aspects of the disclosure described herein. Connection references (e.g., attached, coupled, secured, fastened, connected, and joined) are to be construed broadly and can include intermediate members between a collection of elements and relative movement between elements unless otherwise indicated. As such, connection references do not necessarily infer that two elements are directly connected and in fixed relation to one another. The exemplary drawings are for purposes of illustration only and the dimensions, positions, order and relative sizes reflected in the drawings attached hereto can vary.

(21) FIG. 1 is a schematic cross-sectional diagram of a turbine engine, specifically a gas turbine engine **10** for an aircraft. The gas turbine engine **10** has a generally longitudinally extending axis or engine centerline **12** extending forward **14** to aft **16**. The gas turbine engine includes, in downstream serial flow relationship, a fan section **18** including a fan **20**, a compressor section **22** including a booster or low pressure (LP) compressor **24** and a high pressure (HP) compressor **26**, a combustion section **28** including a combustor **30**, a turbine section **32** including a HP turbine **34**, and a LP turbine **36**, and an exhaust section **38**. The gas turbine engine **10** as described herein is meant as a non-limiting example, and other architectures are possible, such as, but not limited to, the steam turbine engine, the supercritical carbon dioxide turbine engine, or any other suitable turbine engine

(22) The fan section **18** includes a fan casing **40** surrounding the fan **20**. The fan **20** includes a set of fan blades **42** disposed radially about the engine centerline **12**. The HP compressor **26**, the combustor **30**, and the HP turbine **34** form an engine core **44** of the gas turbine engine **10**, which generates combustion gases. The engine core **44** is surrounded by core casing **46**, which can be coupled with the fan casing **40**.

(23) A HP shaft or spool **48** disposed coaxially about the engine centerline **12** of the gas turbine engine **10** drivingly connects the HP turbine **34** to the HP compressor **26**. A LP shaft or spool **50**, which is disposed coaxially about the engine centerline **12** of the gas turbine engine **10** within the larger diameter annular HP spool **48**, drivingly connects the LP turbine **36** to the LP compressor **24** and fan **20**. The spools **48**, **50** are rotatable about the engine centerline **12** and couple to a set of rotatable elements, which can collectively define a rotor **51**.

(24) The LP compressor **24** and the HP compressor **26** respectively include a set of compressor stages **52**, **54**, in which a set of compressor blades **56**, **58** rotate relative to a corresponding set of static compressor vanes **60**, **62** (also called a nozzle) to compress or pressurize the stream of fluid passing through the stage. In a single compressor stage **52**, **54**, multiple compressor blades **56**, **58** can be provided in a ring and can extend radially outwardly relative to the engine centerline **12**, from a blade platform to a blade tip, while the corresponding static compressor vanes **60**, **62** are positioned upstream of and adjacent to the rotating blades **56**, **58**. It is noted that the number of blades, vanes, and compressor stages shown in FIG. 1 were selected for illustrative purposes only, and that other numbers are possible.

(25) The blades **56**, **58** for a stage of the compressor can be mounted to a disk **61**, which is mounted to the corresponding one of the HP and LP spools **48**, **50**, with each stage having its own disk **61**.

The vanes **60, 62** for a stage of the compressor can be mounted to the core casing **46** in a circumferential arrangement.

(26) The HP turbine **34** and the LP turbine **36** respectively include a set of turbine stages **64, 66**, in which a set of turbine blades **68, 70** are rotated relative to a corresponding set of static turbine vanes **72, 74** (also called a nozzle) to extract energy from the stream of fluid passing through the stage. In a single turbine stage **64, 66**, multiple turbine blades **68, 70** can be provided in a ring and can extend radially outwardly relative to the engine centerline **12**, from a blade platform to a blade tip, while the corresponding static turbine vanes **72, 74** are positioned upstream of and adjacent to the rotating blades **68, 70**. It is noted that the number of blades, vanes, and turbine stages shown in FIG. **1** were selected for illustrative purposes only, and that other numbers are possible.

(27) The blades **68, 70** for a stage of the turbine can be mounted to a disk **71**, which is mounted to the corresponding one of the HP and LP spools **48, 50**, with each stage having a dedicated disk **71**. The vanes **72, 74** for a stage of the compressor can be mounted to the core casing **46** in a circumferential arrangement.

(28) Complementary to the rotor portion, the stationary portions of the gas turbine engine **10**, such as the static vanes **60, 62, 72, 74** among the compressor and turbine sections **22, 32** are also referred to individually or collectively as a stator **63**. As such, the stator **63** can refer to the combination of non-rotating elements throughout the gas turbine engine **10**.

(29) In operation, the airflow exiting the fan section **18** is split such that a portion of the airflow is channeled into the LP compressor **24**, which then supplies pressurized airflow **76** to the HP compressor **26**, which further pressurizes the air. The pressurized airflow **76** from the HP compressor **26** is mixed with fuel in the combustor **30** and ignited, thereby generating combustion gases. Some work is extracted from these gases by the HP turbine **34**, which drives the HP compressor **26**. The combustion gases are discharged into the LP turbine **36**, which extracts additional work to drive the LP compressor **24**, and the exhaust gas is ultimately discharged from the gas turbine engine **10** via the exhaust section **38**. The driving of the LP turbine **36** drives the LP spool **50** to rotate the fan **20** and the LP compressor **24**. The pressurized airflow **76** and the combustion gases can together define a working airflow that flows through the fan section **18**, compressor section **22**, combustor section **28**, and turbine section **32** of the gas turbine engine **10**.

(30) A portion of the pressurized airflow **76** can be drawn from the compressor section **22** as bleed air **77**. The bleed air **77** can be drawn from the pressurized airflow **76** and provided to engine components requiring cooling. The temperature of pressurized airflow **76** entering the combustor **30** is significantly increased. As such, cooling provided by the bleed air **77** is necessary for operating of such engine components in the heightened temperature environments.

(31) A remaining portion of the airflow **78** bypasses the LP compressor **24** and engine core **44** and exits the gas turbine engine **10** through a stationary vane row, and more particularly an outlet guide vane assembly **80**, comprising a set of airfoil guide vanes **82**, at the fan exhaust side **84**. More specifically, a circumferential row of radially extending airfoil guide vanes **82** are utilized adjacent the fan section **18** to exert some directional control of the airflow **78**.

(32) Some of the air supplied by the fan **20** can bypass the engine core **44** and be used for cooling of portions, especially hot portions, of the gas turbine engine **10**, and/or used to cool or power other aspects of the aircraft. In the context of a turbine engine, the hot portions of the engine are normally downstream of the combustor **30**, especially the turbine section **32**, with the HP turbine **34** being the hottest portion as it is directly downstream of the combustion section **28**. Other sources of cooling fluid can be, but are not limited to, fluid discharged from the LP compressor **24** or the HP compressor **26**.

(33) FIG. **2** further illustrates the rotor **51**, the stator **63**, and a rotor seal assembly **100** for the gas turbine engine **10** as seen from section II of FIG. **1**. In the example shown, at least a portion of the rotor seal assembly **100** can be provided in the HP turbine **32** and depend from a portion of the stator **63**, specifically from the turbine vanes **72** that extend from the outer portions of the stator **63**

and located between two adjacent turbine blades **68**. It will be appreciated, however, that the rotor seal assembly **100** can be positioned between any suitable rotating and stationary component of the gas turbine engine **10** within any portion of the gas turbine engine **10** such as, for example, in the fan section **18**, the compressor section **22**, or the turbine section **32**. As such, the rotor seal assembly **100** can depend from any suitable stationary component such as, but not limited to, the compressor vanes **60**, **62**, or the turbine vanes **72**, **74**. For purposes of this disclosure, the turbine vane **72**, or any other vane (e.g., the static vanes **60**, **62**, **72**, **74**), which depends from the stator **63** can be collectively referred to as the stator **63**.

(34) The rotor seal assembly **100** can include a carriage assembly **102** carried by the stator **63** and having a seal seat **106** defining a seal cavity **108**, and a seal assembly **104** at least partially located within the seal cavity **108** and having a segmented floating seal body **110**. A biasing element **112** be located within the seal cavity **108** between the floating seal body **110** and the carriage assembly **102**.

(35) During operation of the gas turbine engine **10**, a working fluid **88** can flow over the turbine blades **68** and turbine vanes **72**. In the specific example, the working fluid **88** can be defined by the pressurized airflow **76**, however, it will be appreciated that the working fluid **88** can be any suitable working fluid or airflow such as, but not limited to, the pressurized airflow **76**, combustion gases, an ambient airflow, any combination thereof, or any other suitable fluid as described herein. The majority of the working fluid **88** can flow over the turbine vanes **72** and the turbine blades **68** to define a working fluid path. A leakage fluid **90** diverges from the working fluid **88** and enters the space between the compressor blade **58** and the compressor vane **62**, and flows between a radially inner portion of the stator **63** (e.g., the radially inner portions of the turbine vanes **72**) and the rotor **51** defining. The rotor seal assembly **100** can reduce or otherwise eliminate the amount of leakage fluid **90** that flows from an upstream portion of the turbine vane **68** to a downstream portion of the turbine vane **68** by establishing a labyrinth between the stator **63** and the rotor **51**. In other words, the rotor seal assembly **100** can create a torturous path for the leakage fluid **90**, thus either reducing or eliminating the amount of leakage fluid **90** that is able to flow around the radially inner portion of the stator **63**.

(36) FIGS. 3A-3B are schematic cross-sectional illustrations of the rotor seal assembly **100** in a first position (FIG. 3A) and a second position (FIG. 3B) as seen from enlarged area III of FIG. 2. As illustrated, the difference between the first position and the second position of the rotor seal assembly is that the seal assembly **104** is radially closer to the rotor **51** while in the first position than when in the second position. Further yet, the biasing element **112** in the first position can be expanded in the radial direction when compared to the biasing element **112** in the second position. As such, FIGS. 3A-3B illustrate a comparison of the rotor seal assembly **100** between the first position and the second position, respectively.

(37) At least one of the carriage assembly **102** or the seal assembly **104** can extend about the entire periphery of the rotor **51** or otherwise be circumferentially continuous about the engine centerline **12**. Additionally, or alternatively, at least one of the seal assembly **104** or the carriage assembly **102** can be segmented about the engine centerline **12**. For example, the seal assembly **104** can be a segmented seal assembly **104** split into two or more segments about the engine centerline **12**. The number of segments of the carriage assembly **102** can correspond to the number of segments of the seal assembly **104**.

(38) The biasing element **112** can extend within the seal cavity **108** between the carriage assembly **102** and the seal assembly **104** and be operably coupled to at least one of the floating seal body **110** or the carriage assembly **102** through any suitable method such as, but not limited to, adhesion, fastening, welding, or the like. The biasing element **112** can include a head **115**, defined as a radially outer portion of the biasing element **112**, that confronts at least a portion of the carriage assembly **102**.

(39) As illustrated, the biasing element **112** is a pneumatic bellows defining an interior **113**,

specifically a hollow interior. As such, a fluid can be introduced into the interior of the biasing element **112** to move the biasing element **112** from a contracted position (FIG. 3B) to an extended position (FIG. 3A), which results in a corresponding movement of the floating seal body **110**. It is contemplated that the biasing element **112** can be biased to the contracted position. The biasing element **112** can be sized based on the location of the rotor seal assembly **100** within the gas turbine engine **10**. For example, in the case of the pneumatic bellows, a number of folds or layers and the thickness of the pneumatic bellows can be increased or decreased based on the desired length of extension or contraction of the biasing element **112**. Although illustrated as the pneumatic bellows, it will be appreciated that the biasing element can be any other suitable biasing element such as, but not limited to, a leaf spring, a garter spring, flexures, or the like.

(40) The carriage assembly **102** of the rotor seal assembly **100** can define the seal seat **106** defining the seal cavity **108**. The seal seat **106** can take on many forms, but, as illustrated, the seal seat **106** includes a first wall **114**, a second wall **116**, and a third wall **118**. Both the first wall **114** and the second wall **116** can extend radially inwardly from the stator **63**, specifically the turbine vane **72**, with the second wall **116** being upstream or axially forward the first wall **114**. The third wall **118** can extend in the axial direction and interconnect the first wall **114** and the second wall **116**.

Together, the first wall **114**, the second wall **116**, and the third wall **118** can define the seal seat **106** and hence the seal cavity **108**. It will be appreciated that the first wall **114**, the second wall **116**, and the third wall **118**, and hence the seal seat **106**, can be sized such that the seal assembly **104**, and more specifically the floating seal body **110**, can be at least partially received within the seal cavity **108**. The first wall **114** and the second wall **116** together define a radial seal guide for the floating seal body **110**. In other words, the floating seal body **110** can be free to move in the radial direction within the seal cavity **108** demarcated by the first wall **114** and the second wall **116**.

(41) The second wall **116** can include a tooth **120** confronting at least a portion of the floating seal body **110**. The tooth **120** can be used to limit, restrict, or stop the leakage fluid from passing between the second wall **116** and the floating seal body **110** and into the seal cavity **108**. It is contemplated that the tooth **120** can be designed to provide a minimal radial frictional load on the seal assembly **104**, while still ensuring that the leakage fluid **90** is limited or otherwise stopped from flowing around the seal assembly **104** and into the seal cavity **108**.

(42) The seal seat **106** can further include a flange **122** that extends from a portion of the seal seat **106** and into the seal cavity **108**. As a non-limiting example, the flange **122** can extend from a radially inner portion of the third wall **118** and into the seal cavity **108**. In other words, the flange **122** can extend radially inwardly from a portion of the carriage assembly **102** and into the seal cavity **108**. It will be appreciated, however, that the flange **122** can extend from any other suitable portion of the carriage assembly **102** and into the seal cavity **108**. For example, the flange **122** can extend axially inwardly from the second wall **116** and axially into the seal cavity **108**. A distal end of the flange **122** can confront the floating seal body **110**. As a non-limiting example, the floating seal body **110** can include a seat **124** that the distal end of the flange **122** confronts, physical contacts, or is coupled to. As a non-limiting example, the flange **122** can be coupled to the seat **124** through any suitable coupling method such as, but not limited to, welding, adhesion, fastening, magnetism, friction, or any combination thereof. As the carriage assembly **102** is static and the flange **122** is coupled to or otherwise a portion of the carriage assembly **102**, the flange **122** can be further defined as a static portion of the rotor seal assembly **100**. As such, the flange **122** and the seat **124** can limit at least one of an axial, circumferential, or radial movement of the floating seal body **110**.

(43) The carriage assembly **102** can further include a tab **128** extending from the seal seat **106**, specifically between the third wall **118** and the stator **63**. The tab **128** can be used to physically couple the carriage assembly **102** to the stator **63**. As illustrated, the tab **128** extends from an upstream or axially forward portion of the third wall **118** to the turbine vane **72** or the stator **63**, however, it will be appreciated that the tab **128** can extend from any portion of the carriage

assembly **102** and couple to any portion of the stator **63**. The coupling between the tab **128** and the stator **63** can be done through any suitable method such as, but not limited to, welding, adhesion, fastening, frictional contact (e.g., confronting one another without a physical coupling), or the like. As illustrated, the carriage assembly **102** is a separate, discrete component coupled to the stator through the tab **128**, however, it will be appreciated that the carriage assembly **102** can be integrally formed with the stator **63**. Specifically, the carriage assembly can be integrally formed with the turbine vane **72**, or any other suitable component of the stator **63**, through additive manufacturing, casting, or the like such that the carriage assembly **102** and at least a portion of the stator **63** form a monolithic structure.

(44) A retainer groove **130** can be formed within a portion of the seal seat **106**, specifically the third wall **118**, with a retainer **132** corresponding to the retainer groove **130**. As illustrated, the retainer groove **130** can be formed on an axially downward or downstream portion of the third wall **118**. It is contemplated that the retainer groove **130** and the retainer **132** can be located along a radially outer portion of the third wall that is on axially opposite from where the tab **128** extends from. The retainer **132** can be any suitable retainer such as, but not limited to, a snap ring, a cover plate, cover plate with bolts, a bayonet-retained cover plate, or the like.

(45) It is contemplated that the seal seat **106** can include any number of one or more walls including any of the components described herein (e.g., the flange **122**). At least one of the first wall **114**, the second wall **116**, or the third wall **118** can be excluded from the carriage assembly **102**. As a non-limiting example, the rotor seal assembly **100** can be defined as a Compressor Discharge Pressure (CDP) seal assembly. In such a case, the second wall **116** can be excluded such that the seal seat **106** is defined at least by the first wall **114** extending radially inward toward the rotor **51** at a downstream portion of the seal assembly **104**, and the third wall **118** extending upstream or forward the second wall **116**.

(46) A set of tertiary seals **134** can be located between the carriage assembly **102** and the stator **63**. Specifically, the set of tertiary seals **134** can be located between a radially inner portion of the stator **63** and a radially outer portion of the third wall **118**. As illustrated, there can be two tertiary seals **134** arranged in series. The set of tertiary seals **134** can include any suitable seal such as, but not limited to, a piston ring, an E-seal, a W-seal, a C-seal, a leaf seal, a bellows, a braid/rope seal, a contact seal, or any combination thereof. It will be appreciated that the tertiary seals can be 360-degree seals (e.g., they can extend circumferentially about the entirety of the rotor **51**), two segments 180-degree each, or more than two segments.

(47) The seal assembly **104** can include the floating seal body **110** defined by a first seal face **136** confronting the rotor **51**, a second seal face **138** confronting the second wall **116** of the carriage assembly **102**, a third seal face **140** opposite the first seal face **136** and confronting at least a portion of the seal cavity **108** and/or the biasing element **112**, and a fourth seal face **142** opposite the second seal face **138** and confronting the first wall **114**. In other words, the first seal face **136** can define a radially inner face of the floating seal body **110**, the second seal face **138** can define an axially forward or upstream face of the floating seal body **110** (e.g., the face confronting at least a portion of the leakage fluid **90**), the third seal face **140** can define a radially outer face of the floating seal body, and the fourth seal face **142** can define an axially downward or downstream face of the floating seal body **110**.

(48) An internal passage **144** can fluidly couple the leakage fluid **90** upstream of the rotor seal assembly **100** to various interfaces between portions of the seal assembly **104**. The internal passage **144** can be formed within the floating seal body **110** and fluidly couple an inlet **146** on the second seal face **138** to a set of outlets **148** located on a portion of the third seal face **140** and confronting at least one of the seal cavity **108** or the interior **113** of the biasing element **112**. It is contemplated that at least one outlet **148** of the set of outlets **148** can be fluidly coupled to the interior **113** of the biasing element **112** and be radially opposite or otherwise oppose the head **115** of the biasing element **112**.

(49) During operation of the gas turbine engine **10**, at least a portion of the leakage fluid can flow into the internal passage **144** through the inlet **146**. The leakage fluid **90** can subsequently flow through the internal passage and ultimately out at least one outlet **148** of the set of outlet **148**. Upon start-up of the turbine engine **10**, the biasing element **112** can be in the contracted, second position (FIG. 3B). Once the working fluid **88** is generated, at least a portion of the leakage fluid **90** exiting the set of outlets **148** can be exhausted into the interior **113** of the biasing element **112** or otherwise into the interior of the seal cavity **108**. This, in turn, can move the biasing element **112** from the contracted position (FIG. 3B) to the extended position (FIG. 3A). As the floating seal body **110** is coupled to the biasing element **112**, the floating seal body **110**, and hence the seal assembly **104**, can move with the biasing element **112** between the first position (FIG. 3A) and the second position (FIG. 3B). In other words, the contraction or extension of the biasing element **112** can move the rotor seal assembly **100** between the first position, and the second position. The movement of the biasing element **112** can be dependent on the operational state of the gas turbine engine **10**. For example, the leakage fluid **90** will only be present in the gas turbine engine **10** when there is a working fluid **88** or airflow (e.g., the pressurized airflow **76** or combustion gases) flowing through the gas turbine engine **10**. In other words, the leakage fluid **90** will only be present when the gas turbine engine **10** is being operated. As such, at least a portion of the leakage fluid **90** will enter the interior **113** of the biasing element **112** and cause the biasing element **112** to expand or go into its expanded position. This will result in the rotor seal assembly **100** being in the first position. When the gas turbine engine **10** is not being operated, however, the pressurized working fluid and the leakage fluid **90** will not actively flow through the gas turbine engine **10**. As such, there will be no leakage fluid **90** flowing into the interior **113** of the biasing element **112**. This will result in the biasing element **112** going back to its biased position (e.g., the contracted position) and the rotor seal assembly **100** being in the second position. The axial, circumferential, or radial position of the floating seal body **110** can further be defined by the flange **122**. For example, during operation of the gas turbine engine **10**, the rotor **51** can exert an axial, a radial, or a circumferential force on the floating seal body **110** such that floating seal body **110** will want to move in the direction of the force. As the flange **122** is static and confronts, is received within, or is otherwise coupled to the seat **124**, the flange **122** and the seat **124** can limit at least a portion of the circumferential, axial, or radial movement of the floating seal body **110**. In other words, the flange **122** can circumferentially, axially or radially position the floating seal body **110** within the seal cavity **108** and limit or otherwise stop the floating seal body **110** from moving in at least one of the axial, radial or circumferential directions.

(50) The leakage fluid **90** that flows into the interior **113** of the biasing element **112** can expand the biasing element **112** such that the biasing element exerts a closing force on the seal assembly **104**. As used herein, the term “closing force” can refer to the radial force exerted on the seal assembly **104**, specifically the floating seal body **110**, by the biasing element **112** that pushes the seal assembly **104** toward the rotor **51**. The closing force can be based on the location of the rotor seal assembly **100** within the gas turbine engine **10** and be based on one or more operational characteristics of the gas turbine engine **10**. As used herein, the term “operational characteristics” can refer to the operational state of the gas turbine engine **10** (e.g., the gas turbine engine **10** is operational, or the gas turbine engine **10** is non-operational), or to other characteristics of the gas turbine engine **10** such as, but not limited to, a pressure differential between an upstream side and a downstream side of the portion of the stator **63** that the rotor seal assembly **100** depends from. If the pressure differential is larger (e.g., the upstream side has a higher pressure than the downstream side), then the leakage fluid **90** will be at a higher pressure within the interior **113** of the biasing element **112** than if the pressure differential were smaller. The larger the pressure within the interior **113** of the biasing element **112**, or the larger the amount of leakage fluid **90** within the biasing element **112**, then the greater the closing force. This, in turn, results in a closing force that scales with the differential pressure across the rotor seal assembly **100**. As such, the closing force will be

dependent on the pressure differential or the operational state of the gas turbine engine **10**. During operation of the gas turbine engine **10**, the rotor **51** can translate radially. The closing force allows for the rotor seal assembly **100** to accurately and faithfully follow the radial movement of the rotor **51** without radially, axially, or circumferentially displacing the rotor seal assembly **100** in an undesired fashion.

(51) FIG. **4** is a schematic illustration of cross-sectional view of an exemplary rotor seal assembly **200** of FIG. **2**. The exemplary rotor seal assembly **200** is similar to the rotor seal assembly **100**; therefore, like parts will be identified with like numerals in the **200** series, with it being understood that the description of the like parts of the rotor seal assembly **100** applies to the exemplary rotor seal assembly **200** unless otherwise noted.

(52) The rotor seal assembly **200** can include a biasing element **212** which can include a first bore **260** extending radially through a portion of the biasing element **212**. Specifically, the first bore **260** can extend through a radially distal portion of the biasing element **212** (e.g., the head **215** of the biasing element **212**).

(53) The rotor seal assembly can further include a carriage assembly **202** carried by at least a portion of the stator **63**. The carriage assembly **202** can include the first wall **114**, the second wall **116**, and a third wall **218** interconnecting the first wall **114** and the second wall **116**. The third wall **218** can include a second bore **254** extending radially through a portion of the third wall **218**. Specifically, the second bore **254** can extend from a radially distal portion of the third wall **218** and through at least a portion of the third wall **218**. As illustrated, the second bore **254** can include a radially upper portion and a radially inner portion with the radially upper portion having a larger diameter than the radially inner portion. As such, the second bore **254** can be defined by a step such that the bore decreases in cross sectional area from the radially outer portion of the bore to a radially inner portion of the bore. Alternatively, the second bore **254** can be defined by a constant cross-sectional area.

(54) The third wall **218** can further include a protrusion **256** extending radially inwardly from a radially inner portion of the third wall **218** confronting the seal cavity **108**. The protrusion **256**, as illustrated, can include a seat **258** corresponding to the head **215** of the biasing element **212**.

(55) The biasing element **212** can be axially located such that the head **215** of the biasing element **212** corresponds to the seat **258** of the third wall **218**. As such, the first bore **260** can correspond to the second bore **254**, specifically the radially inner portion of the second bore **254**. A fastener **262** can extend through the second bore **254** and at least a portion of the first bore **260** to operatively couple the biasing element **212** to the carriage assembly **202**. It is contemplated that the fastener **262** and the seat **258** can limit at least one of an axial movement, a circumferential movement, or a radial movement of the biasing element **212**. The fastener **262** can be any suitable fastener such as, but not limited to, a screw, a tab, a pin, a weld, a bolt and nut with the bolt being integrally formed with the top of the biasing element **212**, a retaining snap ring, or any combination thereof.

(56) FIG. **5** is a schematic illustration of a cross-sectional view of an exemplary rotor seal assembly **300** of FIG. **2**. The exemplary rotor seal assembly **300** is similar to the rotor seal assembly **100**, **200**; therefore, like parts will be identified with like numerals in the **300** series, with it being understood that the description of the like parts of the rotor seal assembly **100**, **200** applies to the exemplary rotor seal assembly **300** unless otherwise noted.

(57) The rotor seal assembly **300** can include a carriage assembly **302** carried by at least a portion of the stator **63**. The carriage assembly **302** can include the first wall **114**, the second wall **116**, and a third wall **318** interconnecting the first wall **114** and the second wall **116**. The third wall **318** can include a protrusion **356** extending radially inwardly from a radially inner portion of the third wall **318** confronting the seal cavity **108**. The protrusion **356**, as illustrated, can include a seat **358** extending radially through at least a portion of the protrusion **356** and into at least a portion of the third wall **318**.

(58) A biasing element **312** can include a head **315** that corresponds to and fits within the seat **358**.

The biasing element **312** can further include a first bore **360** extending in circumferentially. A pin **366**, corresponding to the first bore **360**, can extend circumferentially through at least a portion of the biasing element **312**, specifically the head **315** of the biasing element **312**. The pin **366** and the seat **358** can limit at least one of a circumferential movement, an axial movement, or a radial movement of the biasing element **312**.

(59) FIG. **6** is a schematic illustration of a cross-sectional view of an exemplary rotor seal assembly **400** of FIG. **2**. The exemplary rotor seal assembly **400** is similar to the rotor seal assembly **100**, **200**, **300**; therefore, like parts will be identified with like numerals in the **400** series, with it being understood that the description of the like parts of the rotor seal assembly **100**, **200**, **300** applies to the exemplary rotor seal assembly **400** unless otherwise noted.

(60) The rotor seal assembly **400** can include a biasing element **412**, which can include a head **415**. The biasing element **412**, specifically the head **415**, can include a first bore **260** extending axially through the head **415** of the biasing element **412**.

(61) The rotor seal assembly **400** can include a carriage assembly **402** carried by at least a portion of the stator **63**. The carriage assembly **402** can include the first wall **114**, the second wall **116**, and a third wall **418** interconnecting the first wall **114** and the second wall **116**. The third wall **418** can include a protrusion **456** extending radially inwardly from a radially inner portion of the third wall **418** confronting the seal cavity **108**. The protrusion **456**, as illustrated, can include a seat **358** extending radially through at least a portion of the protrusion **456** and into at least a portion of the third wall **418**. The protrusion **456** can extend along an entire downstream half and at least a portion of an upstream half of the third wall **418** and include a second bore **254** extending axially within at least a portion of the protrusion **456** or the third wall **418**. As illustrated, the second bore **254** can have a constant cross-sectional area and be non-continuous in the axial direction.

(62) The head **415** can fit within the seat **458** such that the first bore **460** corresponds to the second bore **454** such that a pin **466** can extend axially through the first bore **260** and at least a portion of the second bore **254** so as to couple the biasing element **412** to the carriage assembly **402**. The pin **466** and the seat **458** can couple the biasing element **412** to the carriage assembly **402** and limit at least one of an axial movement, a radial movement, or circumferential movement or an axial movement of the biasing element **412**.

(63) FIG. **7** is a schematic illustration of a cross-sectional view of an exemplary rotor seal assembly **500** of FIG. **2**. The exemplary rotor seal assembly **500** is similar to the rotor seal assembly **100**, **200**, **300**, **400**; therefore, like parts will be identified with like numerals in the **500** series, with it being understood that the description of the like parts of the rotor seal assembly **100**, **200**, **300**, **400** applies to the exemplary rotor seal assembly **500** unless otherwise noted.

(64) The rotor seal assembly **500** can including a biasing element **512** can include a head **515** including a first bore **460** extending axially through the head **515**. The rotor seal assembly **500** can further include a carriage assembly **502** carried by at least a portion of the stator **63**. The carriage assembly **502** can include the first wall **114**, the second wall **116**, and a third wall **520** interconnecting the first wall **114** and the second wall **116**. The third wall **520** can include a second bore **554** extending radially through a portion of the third wall **518**, specifically a radially outer portion of the third wall **518**. The third wall **520** can further include a protrusion **556** extending radially inwardly from a radially inner portion of the third wall **520** confronting the seal cavity **108**. The protrusion **556** can include a seat **558** extending radially through at least a portion of the protrusion **556** and corresponding to the second bore **554** of the third wall **520**.

(65) As illustrated, the head **515** can be sized with varying diameters to fit through both the seat **558** and the second bore **554**. The head **515** can extend radially past the third wall **520**. A pin **566** can extend axially through the first bore **560** of the biasing element **512**. The seat **558**, the second bore **554**, and the pin **566** can couple the biasing element **512** to the carriage assembly **502** and limit at least one of an axial movement, a radial movement, or a circumneutral movement of the biasing element **512**.

(66) FIG. 8 is a schematic illustration of a cross-sectional view of an exemplary rotor seal assembly **600** of FIG. 2. The exemplary rotor seal assembly **600** is similar to the rotor seal assembly **100**, **200**, **300**, **400**, **500**; therefore, like parts will be identified with like numerals in the **600** series, with it being understood that the description of the like parts of the rotor seal assembly **100**, **200**, **300**, **400**, **500** applies to the exemplary rotor seal assembly **600** unless otherwise noted.

(67) The rotor seal assembly **600** can include biasing element **612**, which can include a head **615** confronting the carriage assembly **602**. The head **615** can include a first bore **660** extending axially through the head **615**.

(68) The rotor seal assembly **600** can further include a carriage assembly **602** carried by at least a portion of the stator **63**. The carriage assembly **602** can include the first wall **114**, the second wall **116**, and a third wall **618** interconnecting the first wall **114** and the second wall **116**. The third wall **618** can include a set of protrusions **656** extending radially inwardly from radially inner portions of the third wall **618** confronting the seal cavity **108**. Specifically, two protrusions **656** can extend from separate radially inner portions of the third wall **618**. The set of protrusions **656**, as illustrated, can each include a second bore **654** extending radially through at least a portion of the corresponding protrusions **656**.

(69) The biasing element **612** can be positioned such that the head **615** is positioned axially between the set of protrusions **656**. Specifically, the biasing element **612** can be positioned such that the first bore **660** of the head **615** corresponds to the second bore **654** of the protrusions **656**. A pin **666** can extend axially through the first bore **660** and the second bore **654** such that the pin **666** can couple the biasing element **612** to the carriage assembly **602** and limit at least one of an axial movement, a radial movement, or a circumneutral movement of the biasing element **612**.

(70) FIG. 9 is a schematic illustration of a cross-sectional view of an exemplary rotor seal assembly **700** of FIG. 2. The exemplary rotor seal assembly **700** is similar to the rotor seal assembly **100**, **200**, **300**, **400**, **500**, **600**; therefore, like parts will be identified with like numerals in the **700** series, with it being understood that the description of the like parts of the rotor seal assembly **100**, **200**, **300**, **400**, **500**, **600** applies to the exemplary rotor seal assembly **700** unless otherwise noted.

(71) The rotor seal assembly **700** can include a carriage assembly **702** carried by at least a portion of the stator **63**. The carriage assembly **702** can include the first wall **114**, the second wall **116**, and a third wall **718** interconnecting the first wall **114** and the second wall **116**. The third wall **718** can include a protrusion **756** extending radially inwardly from radially inner portions of the third wall **718** confronting the seal cavity **108**.

(72) A biasing element **712** can include a head **715** confronting the carriage assembly **702**, with the head **715** being integrally formed with at least a portion of the carriage assembly **702**. Specifically, the head **715** can be integrally formed within a portion of the protrusion **756** in order to couple the biasing element **712** to the carriage assembly **702**. It is contemplated that biasing element **712**, or the head **715** of the biasing element **712**, can be integrally formed with the protrusion **756** through any suitable method such as, but not limited to, additive manufacturing or casting, or otherwise be coupled to the protrusion **756** through any suitable method such as, but not limited to, welding, adhesion or the like. The protrusion **756** can couple the biasing element **712** to the carriage assembly **602** and limit at least one of an axial movement, a radial movement, or a circumneutral movement of the biasing element **612**.

(73) FIG. 10 is a schematic illustration of a cross-sectional view of an exemplary rotor seal assembly **800** of FIG. 2. The exemplary rotor seal assembly **800** is similar to the rotor seal assembly **100**, **200**, **300**, **400**, **500**, **600**, **700**; therefore, like parts will be identified with like numerals in the **800** series, with it being understood that the description of the like parts of the rotor seal assembly **100**, **200**, **300**, **400**, **500**, **600**, **700** applies to the exemplary rotor seal assembly **800** unless otherwise noted.

(74) The rotor seal assembly **800** can include a carriage assembly **802**, a rotor seal assembly **804**, and a biasing element **812** provided therebetween. The biasing element **812** can include a head **815**

confronting the carriage assembly **802**. The head **815** can include a first bore **860** extending axially through the head **815**.

(75) The carriage assembly **802** can be carried by at least a portion of the stator **63**, and include the first wall **114**, the second wall **116**, and a third wall **818** interconnecting the first wall **114** and the second wall **116**. The third wall **818** can include a protrusion **856** extending radially inwardly from radially inner portions of the third wall **818** confronting the seal cavity **108**. The protrusion **856**, as illustrated, can include a second bore **854** extending radially through at least a portion of the protrusion **856** and into at least a portion of the third wall **818**. The protrusion **856** can further include a seat **858** extending radially through at least a portion of the protrusion **856** or the third wall **818**.

(76) The seal assembly **804** can be at least partially located within the seal cavity **108**, and include a floating seal body **810** defined by a first seal face **836**, the second seal face **138**, the third seal face **140**, and a fourth seal face **842**. A third bore **870** can extend radially through at least a portion of the seal body **810** from the first seal face **836** to the fourth seal face **842**.

(77) The biasing element **812** can be axially positioned to overlay the third bore **870** and have the head **815** correspond to and fit within the seat **858** such that the first bore **860** corresponds to the second bore **854**. A pin **866** can extend axially through at least a portion of the first bore **860** and the second bore **854** so as to couple the biasing element **812** to the carriage assembly **402**. A fastener **876** can extend radially through the third bore **870** of the seal assembly **804** and couple the biasing element **812** to the floating seal body **810**. As illustrated, the fastener **876** can be a screw and nut assembly, however, can be any other suitable fastener such as, but not limited to, a screw, a tab, a pin, a weld, a dovetail, or the like. The pin **866** and the seat **858** can couple the biasing element **812** to the carriage assembly **802**, while the fastener **876** can couple to the biasing element **812** to the seal assembly **804**. The pin **866**, the seat **858**, and the fastener **876** and limit at least one of an axial movement, a radial movement, or circumferential movement or an axial movement of the biasing element **812**.

(78) An internal passage **844** can be formed within at least a portion of the floating seal body **810** and the fastener **876**. The internal passage **844** can fluidly couple the inlet **146** on the third seal face **140** to at least an outlet **848** provided along a portion of the fastener **876** exposed to the interior **113** of the biasing element **812**. As such, the internal passage **844** can be formed within the floating seal body **810** and the fastener **876** and fluidly couple the interior **113** to the inlet **146**.

(79) FIG. **11** is a schematic illustration of a cross-sectional view of an exemplary rotor seal assembly **900** of FIG. **2**. The exemplary rotor seal assembly **900** is similar to the rotor seal assembly **100**, **200**, **300**, **400**, **500**, **600**, **700**, **800**; therefore, like parts will be identified with like numerals in the **900** series, with it being understood that the description of the like parts of the rotor seal assembly **100**, **200**, **300**, **400**, **500**, **600**, **700**, **800** applies to the exemplary rotor seal assembly **900** unless otherwise noted.

(80) The rotor seal assembly **900** can include a carriage assembly **902** carried by at least a portion of the stator **63**. The carriage assembly **902** can include the first wall **114**, the second wall **116**, and a third wall **918** interconnecting the first wall **114** and the second wall **116**. An internal passage **978** can be formed within the third wall **918** of the carriage assembly **902** and fluidly couple an inlet **980** formed on an upstream face **982** of the third wall **918** to an outlet **984** located on a radially inner face **986**, confronting the seal cavity **108**, of the third wall **918**.

(81) The rotor seal assembly **900** can further include a seal assembly **904** at least partially located within the seal cavity **108**, and including a floating seal body **910** defined by the first seal face **136**, a second seal face **938** similar to the first seal face **136** but without the inlet **146**, the third seal face **140**, and a fourth seal face **942**. A biasing element **912** can include a head **915** confronting the seal assembly **804**, specifically the fourth seal face **942**. The interior **113** of the biasing element **912** can correspond to the outlet **984** such that the interior **113** is fluidly coupled to the inlet **980** through the internal passage **978**. The biasing element can be coupled to at least one of the carriage

assembly **902** or the seal assembly **904** through any suitable coupling method such as, but not limited to, welding, adhesion, fastening, or the like.

(82) Additional biasing elements **912**, illustrated as a set of garter springs **990**, can extend circumferentially about or otherwise coil around the entirety of a floating seal body **910**, or alternatively across one or more segments of a set of floating seal bodies **910**. The set of garter springs **990** can urge the floating seal body **910** toward the rotor **51** similar to how the biasing element **912** urges the floating seal body **910** toward the rotor **51**. Thus, the set of garter springs **990** and the biasing element **912** can together be used or otherwise be defined as the biasing element configured to provide the closing force. The set of garter springs **990** can interface with the floating seal body **910** by a corresponding groove or channel **992**. The channel **992** can be formed within a protrusion extending from the fourth seal face **942** as illustrated. Additionally, or alternatively, the channel **992** can be extend into the third seal face **940** such that at least a portion of the set of garter springs **990** extend into the floating seal body **910**.

(83) The set of garter springs **990** can be used in cases where the rotor seal assembly **900** is provided within a portion of the gas turbine engine **10** with a high-pressure differential. As such, the set of garter springs **990** can provide an additional closing force to the closing force generated by the biasing element **912** to ensure that the overall closing force is sufficient based on the pressure differential.

(84) FIG. **12** is a schematic illustration of a cross-sectional view of an exemplary rotor seal assembly **1000** of FIG. **2**. The exemplary rotor seal assembly **1000** is similar to the rotor seal assembly **100**, **200**, **300**, **400**, **500**, **600**, **700**, **800**, **900**; therefore, like parts will be identified with like numerals in the **1000** series, with it being understood that the description of the like parts of the rotor seal assembly **100**, **200**, **300**, **400**, **500**, **600**, **700**, **800**, **900** applies to the exemplary rotor seal assembly **1000** unless otherwise noted. The rotor seal assembly **1000** is similar to the rotor seal assembly **100**, **200**, **300**, **400**, **500**, **600**, **700**, **800**, **900**, except that the rotor seal assembly **1000** does not include a biasing element like the rotor seal assembly **100**, **200**, **300**, **400**, **500**, **600**, **700**, **800**, **900** does.

(85) The rotor seal assembly **1000** can include a carriage assembly **1002** carried by at least a portion of the stator **63**. The carriage assembly **1002** can include the first wall **114**, the second wall **116**, and a third wall **1018** interconnecting the first wall **114** and the second wall **116**. The third wall **1018** can include a protrusion **1056** extending radially inwardly from a radially inner portion of the third wall **1018** and confronting the seal cavity **108**. A pin **1066** can extend circumferentially through the protrusion **1056**. It is contemplated that the pin **1066** can be used in cases where the rotor seal assembly **1000** is defined as a segmented rotor seal assembly **100** (e.g., at least a portion of the rotor seal assembly **1000** is circumferentially non-continuous about the rotor **51**). The pin **1066** can act as a method to physically couple one segment of the carriage assembly **1002** (or any other portion of the rotor seal assembly **1000**) to a corresponding adjacent carriage assembly **1002**. It will be appreciated that the pin **1066** extending through the protrusion **1056** can be any suitable component to couple one segment to another such as, but not limited, a bolt, a pin, a fastener, or the like.

(86) The rotor seal assembly **1000** can further include a seal assembly **1004** at least partially located within the seal cavity **108**, and including a floating seal body **1010** defined by the first seal face **136**, a second seal face **1038** similar to the first seal face **136** but without the inlet **146**, a third seal face **1040**, and the fourth seal face **142**. A pair of biasing elements illustrated as a set of garter springs **1090**, can be received within a set of circumferential channels **1092** formed within a portion of the seal assembly **1004**. As a non-limiting example, the set of garter springs **1090** can be received within the set of circumferential channels **1092** formed within a portion of the third seal face **1040**. As illustrated, the floating seal body **1010** does not include an internal passage.

(87) Benefits of the present disclosure include the rotor seal assembly with an increased sealing capability, without an increased manufacturing burden, when compared to conventional rotor seal

assemblies. For example, conventional rotor seal assemblies can rely on creating a labyrinth between the stator and the rotor by extending components from the rotor (e.g., teeth that extend from the rotor). The space between the components from the rotor and the stator ultimately determine the effectiveness of the rotor seal assembly from limiting or preventing the leakage fluid from passing through the rotor-stator gap. This space is only scalable by locating the stationary components of the rotor seal assembly closer to the components extending from the rotor. This ultimately results in an increased manufacturing burden as each rotor seal assembly needs to be tuned, designed, or otherwise separately manufactured depending on its location within the turbine engine. Conventional labyrinth seals also have limited capability for leakage control based on seal diameter, vibratory response, and other factors. A labyrinth seal tooth to stator (usually honeycomb abradable) sealing gap or clearance can only be held so tight in a gas turbine engines operation, generally to a physical gap of 4 to 100 mils, depending on the seal size and location. The rotor seal assembly as described herein, however, specifically the floating seal body, that can be radially translated, through the biasing element, with respect to the rotor based on the operational characteristics of the turbine engine. Specifically, the biasing element can move between the contracted and expanded position based on the operational state of the turbine engine, thus radially moving the seal assembly with respect to the rotor based on the operational state of the turbine engine. For example, when the turbine engine is operational, the leakage fluid will enter the interior of the biasing element and move from the contracted to expanded position, resulting in the biasing element exerting the closing force on the seal assembly, and vice-versa for when the turbine engine is non-operational. As the sealing assembly is not in contact with the rotor when the turbine engine starts up, shuts down, or is non-operational the total time that the sealing assembly is in contact with the rotor is reduced when compared to conventional rotor seal assemblies, which decreases the total wear on the rotor seal assembly, which ultimately increases the total lifespan of the rotor seal assembly. Further, as discussed herein, the closing force scaled based on the location of the rotor seal assembly within the turbine engine as the closing force is based on the pressure differential between the upstream side and the downstream side of the portion of the stator that the carriage assembly of the rotor seal assembly depends from. As the rotor seal assembly is scalable based on its location throughout the turbine engine, there is less of a manufacturing burden as a rotor seal assembly does not need to be tuned, designed, or otherwise separately manufactured based on its location within the turbine engine. The rotor seal assembly can be used throughout the entirety of the turbine engine.

(88) Yet another benefit of the present disclosure includes a rotor seal assembly that is dynamic based on the operational state of the turbine engine when compared to traditional turbine engines including traditional rotor seal assemblies. For example, during operation of traditional turbine engines, a film of fluid can be formed between a portion of the rotor seal assembly and the rotor. A radial opening force, dependent on the pressure differential of where the traditional rotor seal assembly is located, can be formed by the film of fluid that pushes or otherwise displaces the rotor seal assembly radially away or outward from the rotor. Further, during operation of the turbine engine, the rotor can translate radially and it is important the rotor seal assembly accurately follow the radial translation of the rotor (e.g., the rotor seal assembly should not become axially or circumferentially displaced based on the radial movement of the rotor). The film of fluid generated by the traditional rotor seal assemblies can cause the traditional rotor seal assembly to translate axially, circumferentially, or radially in an undesired fashion, ultimately reducing the sealing effectiveness of the traditional rotor seal assembly. The rotor seal assembly as described herein, however, counteracts the radial opening force with the closing force, specifically a radially closing force, generated through the biasing element. As discussed herein, the closing force, similar to the radial opening force, is dependent on the pressure-differential. As the biasing element allows for the closing force to scale to the pressure differential, that means the closing force can be scaled to counteract the radial opening force. This, in turn, ensures that the seal assembly does not get

displaced too far radially from the rotor, thus ensuring a reduced film stiffness when compared to the traditional rotor seal assembly and that the floating seal body can faithfully or accurately track the radial motion of the rotor. Additionally, the pressurized biasing element allows for a method for increasing the closing force. This allows for a dynamic force/moment balance of the floating seal body. This ensures that the rotor seal assembly as described herein allows for an increase sealing effectiveness, when compared to traditional rotor seal assemblies, which ultimately increases the overall efficiency of the turbine engine.

(89) To the extent not already described, the different features and structures of the various aspects can be used in combination with each other as desired. That one feature cannot be illustrated in all of the aspects is not meant to be construed that it cannot be, but is done for brevity of description. Thus, the various features of the different aspects can be mixed and matched as desired to form new aspects, whether or not the new aspects are expressly described. Combinations or permutations of features described herein are covered by this disclosure.

(90) This written description uses examples to describe aspects of the disclosure described herein, including the best mode, and also to enable any person skilled in the art to practice aspects of the disclosure, including making and using any devices or systems and performing any incorporated methods. The patentable scope of aspects of the disclosure is defined by the claims, and can include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if they have structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal languages of the claims.

(91) Further aspects of the invention are provided by the subject matter of the following clauses:

(92) A turbine engine comprising an engine core comprising at least a compressor section, a combustor section, and a turbine section in axial flow arrangement defining an axial direction and an engine centerline, and defining a rotor and a stator, a carriage assembly carried by the stator and having a seal seat defining a seal cavity, and a seal assembly having a floating seal body, at least partially located within the seal cavity and having a first seal face confronting the rotor, and a biasing element located within the seal cavity and biasing the floating seal body such that the first seal face is biased toward the rotor.

(93) The turbine engine of any preceding clause, further comprising an internal passage located within the floating seal body coupling an inlet located on a second seal face of the floating seal body to an outlet located on a third seal face of the floating seal body, with the second seal face being upstream the third seal face, and the third seal face being opposite the first seal face.

(94) The turbine engine of any preceding clause, wherein the biasing element includes a hollow interior, and the outlet are fluidly coupled to the hollow interior.

(95) The turbine engine of any preceding clause, wherein the biasing element is a pneumatic bellows.

(96) The turbine engine of any preceding clause, wherein the seal seat further comprises a first wall extending radially inwardly from the stator, a second wall extending radially inwardly from the stator and upstream of the first wall, and a third wall interconnecting the first wall and the second wall wherein the first wall, the second wall, and the third wall at least partially define the seal cavity and envelope the floating seal body.

(97) The turbine engine of any preceding clause, further comprising a protrusion extending radially inwardly from the third wall with respect to the engine centerline, and a pin extending circumferentially through at least a portion of the protrusion.

(98) The turbine engine of any preceding clause, further comprising a flange extending at least one of axially or radially inwardly from the second wall or the third wall, respectively, and into the seal cavity, and a seat extending from the floating seal body and into the seal cavity wherein the flange confronts the seat to limit at least one of an axial or circumferential movement of the floating seal body with respect to the engine centerline.

- (99) The turbine engine of any preceding clause, further comprising an internal passage formed in one of either the carriage assembly or the floating seal body, and fluidly coupling an inlet provided on an upstream face of the carriage assembly or the floating seal body with an outlet fluidly coupled to an interior of the biasing element.
- (100) The turbine engine of any preceding clause, wherein the biasing element further comprises a head located on a radially opposite end of the biasing element with respect to the outlet.
- (101) The turbine engine of any preceding clause, wherein the head is integrally formed with at least a portion of the carriage assembly.
- (102) The turbine engine of any preceding clause, wherein the head includes a first bore extending either axially, radially, or circumferentially through the head.
- (103) The turbine engine of any preceding clause, wherein a pin extends through the first bore.
- (104) The turbine engine of any preceding clause, further comprising a second bore, corresponding to the first bore, extending through at least a portion of the carriage assembly, and wherein the pin extends through at least a portion of the second bore.
- (105) The turbine engine of any preceding clause, further comprising a third bore extending radially through at least a portion of the floating seal body, a fastener extending through the third bore and coupled to a portion of the biasing element radially opposite the head, and an internal passage formed within a portion of the floating seal body and the fastener and fluidly coupling an inlet located on an upstream face of the floating seal body to at least one outlet located along a portion of the fastener confronting the biasing element, with the outlet being fluidly coupled to an interior of the biasing element.
- (106) The turbine engine of any preceding clause, further comprising a second bore, corresponding to the first bore, extending through at least a portion of the carriage assembly, wherein the first bore and the second bore each extend radially and a fastener extends through at least a portion of the first bore and the second bore.
- (107) The turbine engine of any preceding clause, wherein the carriage assembly further comprises a retainer guide extending into a portion of the seal seat and shaped to receive a retainer, a tab extending from the seal seat, and coupled to at least a portion of the stator, a flange extending from the seal seat, and confronting a corresponding portion of the floating seal body, and a set of tertiary seals provided between a radially outer portion of the carriage assembly and a radially inner portion of the stator, wherein the tab, the retainer, and the flange limit at least one of an axial or a circumferential movement of the carriage assembly.
- (108) The turbine engine of any preceding clause, wherein the seal assembly further comprises a set of additional biasing elements extending circumferentially along a portion of the floating seal body.
- (109) The turbine engine of any preceding clause, wherein the carriage assembly is integrally formed with the stator.
- (110) The turbine engine of any preceding clause, wherein the carriage assembly and the seal assembly are located within the turbine section.

Claims

1. A turbine engine comprising: a core casing; a stator extending from the core casing; a rotor rotatable about a rotational axis; and a seal assembly comprising: a carriage assembly carried by the stator and being radially spaced from the core casing, with respect to the rotational axis, the carriage assembly having a seal seat defining a seal cavity; a plurality of segments coupled to one another, the carriage assembly having a tab extending between the stator and the carriage assembly, the tab coupling the carriage assembly to the stator; a seal body provided within the seal cavity and having a first seal face confronting the rotor and a second seal face, opposite the first seal face, confronting the seal cavity; and a biasing element provided within the seal cavity and biasing the

seal body radially against the rotor.

2. The turbine engine of claim 1, wherein the plurality of segments are circumferentially spaced about the rotational axis.

3. The turbine engine of claim 1, wherein the seal assembly further comprises a pin extending through a respective portion of the carriage assembly.

4. The turbine engine of claim 3, wherein the pin operably couples adjacent segments of the plurality of segments to one another.

5. The turbine engine of claim 3, wherein the pin extends circumferentially about an entirety of the rotational axis.

6. The turbine engine of claim 1, wherein the carriage assembly extends circumferentially about an entirety of the rotational axis.

7. The turbine engine of claim 1, wherein the seal assembly is provided entirely axially within the seal cavity.

8. The turbine engine of claim 1, further comprising an internal passage provided within one of either the carriage assembly or the seal body.

9. The turbine engine of claim 8, wherein the internal passage is fluidly coupled to the biasing element.

10. The turbine engine of claim 1, wherein the biasing element is a garter spring.

11. The turbine engine of claim 1, wherein the seal body includes a circumferential channel, with the biasing element being provided within the circumferential channel.

12. The turbine engine of claim 1, further comprising a turbine section with the seal assembly being provided within the turbine section.

13. The turbine engine of claim 1, wherein the carriage assembly includes a protrusion extending radially into the seal seat, and the seal assembly includes a pin extending through the protrusion and coupling at least two adjacent segments of the plurality of segments to one another.

14. The turbine engine of claim 1, wherein the stator comprises a static vane mounted to the core casing, the carriage assembly carried by the static vane.

15. The turbine engine of claim 1, wherein the core casing at least partially defines a working fluid path of the turbine engine; the stator extends through the working fluid path; and a working fluid flows through the working fluid path during operation of the turbine engine, a leakage fluid of the working fluid within an area of the working fluid path local to the seal assembly configured to flow into the seal assembly, and the seal body being radially moveable with respect to the rotor through introduction of the leakage fluid into the seal assembly.

16. A turbine engine comprising: a stator; a rotor rotatable about a rotational axis; and a seal assembly comprising: a carriage assembly carried by the stator and having a seal seat defining a seal cavity, the carriage assembly including a flange extending into the seal cavity; a seal body within the seal cavity and having a first seal face confronting the rotor and a second seal face, opposite the first seal face, confronting the seal cavity, the seal body having a seat sized to receive a respective portion of the flange, the seat extending radially inward into the seal body and forming an opening along the second seal face; and a biasing element provided within the seal cavity and biasing the seal body radially against the rotor.

17. The turbine engine of claim 16, wherein the carriage assembly includes a carriage body and the flange extends radially inward from the carriage body.

18. A turbine engine comprising: a core casing; a stator extending from the core casing; a rotor rotatable about a rotational axis; and a seal assembly comprising: a carriage assembly carried by the stator and being radially spaced from the core casing; with respect to the rotational axis, the carriage assembly having a carriage body defining a seal seat and a seal cavity, the carriage body including a protrusion extending radially into the seal cavity; a seal body within the seal cavity and having a first seal face confronting the rotor and a second seal face, opposite the first seal face, confronting the seal cavity, and a biasing element provided within the seal cavity and biasing the

seal body radially against the rotor; wherein the biasing element extends into a respective portion of the protrusion and is coupled to the carriage assembly through a pin extending through a respective portion of the biasing element.
