

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12404975

Kind Code

B2

Date of Patent

September 02, 2025

Inventor(s)

Cho; Seong Cheol et al.

Low profile flat bombe for LPG storage and method for manufacturing the same

Abstract

A low profile flat bombe for Liquefied Petroleum Gas (LPG) storage and method for manufacturing the same, may include a flat bombe body including an upper plate having a plurality of first piercing holes and a pump installation hole formed therethrough, a lower plate having a plurality of second piercing holes formed therethrough at positions vertically coinciding with the plurality of first piercing holes, and side plates integrally connecting first and second side end portions of the upper and lower plates, end plates mounted at front and rear openings in the flat bombe body, and support pipes, wherein upper end portions of the support pipes are welded to internal circumferential portions of the plurality of first piercing holes and lower end portions thereof are welded to internal circumferential portions of the plurality of second piercing holes to maintain a vertical distance between the upper and lower plates.

Inventors: Cho; Seong Cheol (Seoul, KR), Lee; Sung Won (Hwaseong-si, KR), Song; Ju Tae (Hwaseong-si, KR), Yeo; Seung Hyun (Gimcheon-si, KR), Park; Duk Hee (Pyeongtaek-si, KR)

Applicant: HYUNDAI MOTOR COMPANY (Seoul, KR); KIA CORPORATION (Seoul, KR); DAE HUNG PRECISION IND'L CO., LTD. (Seosan-si, KR)

Family ID: 83997373

Assignee: Hyundai Motor Company (Seoul, KR); Kia Corporation (Seoul, KR); Dae Hung Precision Ind'l Co., Ltd. (Seosan-si, KR)

Appl. No.: 18/531177

Filed: December 06, 2023

Prior Publication Data

Document Identifier

US 20240102611 A1

Publication Date

Mar. 28, 2024

Foreign Application Priority Data

KR

10-2021-0068155

May. 27, 2021

Related U.S. Application Data

division parent-doc US 17533683 20211123 US 11885464 child-doc US 18531177

Publication Classification

Int. Cl.: F17C3/00 (20060101)

U.S. Cl.:

CPC F17C3/00 (20130101); F17C2201/0171 (20130101); F17C2203/013 (20130101); F17C2205/0103 (20130101); F17C2205/0305 (20130101); F17C2209/2181 (20130101); F17C2209/221 (20130101); F17C2209/232 (20130101); F17C2221/033 (20130101); F17C2227/0135 (20130101); F17C2270/0168 (20130101)

Field of Classification Search

CPC: F17C (1/14); F17C (13/084); F17C (2201/0157); F17C (2201/0171); F17C (2201/054); F17C (2201/056); F17C (2203/013); F17C (2203/0617); F17C (2203/0636); F17C (2205/0103); F17C (2205/0192); F17C (2205/0305); F17C (2209/2181); F17C (2209/221); F17C (2209/232); F17C (2221/033); F17C (2221/035); F17C (2223/0153); F17C (2223/033); F17C (2227/0135); F17C (2227/0178); F17C (2270/0168); F17C (2270/0171); F17C (3/00)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4558695	12/1984	Kumazawa	228/159	B23K 1/008
4724293	12/1987	Bertels	219/78.12	B23K 11/002
5102005	12/1991	Trussler	220/4.12	B29D 22/003
5697511	12/1996	Bampton	228/180.1	B23K 20/1265
6138859	12/1999	Aulph	N/A	N/A
6364197	12/2001	Oelgoetz	228/2.1	B23K 20/122
9963997	12/2017	Cornet	N/A	B21D 51/18
2005/0011891	12/2004	Austerhoff	220/4.12	B60K 15/03006
2006/0214416	12/2005	Watanabe	N/A	N/A
2014/0166664	12/2013	Lin	220/562	F17C 1/14
2015/0184803	12/2014	Jarzyunski	N/A	N/A
2015/0343899	12/2014	Furusawa	N/A	N/A
2016/0185210	12/2015	Lee	180/69.5	B60K 15/063
2020/0378555	12/2019	Boecker	N/A	B29C 49/42
2022/0260207	12/2021	Ojeda Monge	N/A	B60R 16/08

2022/0348074	12/2021	Vaishnav	N/A	N/A
2024/0117931	12/2023	Baverel	N/A	F17C 1/08
2024/0117932	12/2023	Baverel	N/A	F17C 1/00
2024/0123777	12/2023	Thompson	N/A	F17C 1/00

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
110385981	12/2018	CN	N/A
2065245	12/2008	EP	N/A
3667040	12/2020	EP	N/A
2020/251001	12/2019	WO	N/A

OTHER PUBLICATIONS

U.S. Notice of Allowance dated Sep. 20, 2023 issued in U.S. Appl. No. 17/533,683. cited by applicant

U.S. Non-Final Office dated Jun. 9, 2023 issued in U.S. Appl. No. 17/533,683. cited by applicant

Primary Examiner: Walker; Keith

Assistant Examiner: Gamino; Carlos J

Attorney, Agent or Firm: Morgan Lewis & Bockius LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) The present application is a divisional patent application of U.S. patent application Ser. No. 17/533,683, filed on Nov. 23, 2021, which claims priority to Korean Patent Application No. 10-2021-0068155 filed on May 27, 2021, the entire contents of which are incorporated herein for all purposes by this reference.

BACKGROUND OF THE INVENTION

Field of the Invention

(1) The present invention relates to a low profile flat bombe for Liquefied Petroleum Gas (LPG) storage and a method for manufacturing the same. More particularly, it relates to a low profile flat bombe for LPG storage which may be easily mounted on an underbody of a vehicle to secure the indoor space of the vehicle and the load space thereof, and a method for manufacturing the same.

Description of Related Art

(2) In a vehicle provided with an LPI engine, a bombe which is a fuel tank configured to supply LPG fuel to an engine is manufactured as a cylinder-type or a donut-type structure, and is provided on the bottom of a trunk or a luggage compartment of the vehicle or on the underbody of the vehicle.

(3) However, because vehicles are manufactured in a structure in which the overall height of a vehicle body is reduced and the center of gravity of the vehicle body is adjusted downwards depending on a vehicle design trend, and the height of the underbody tends to be reduced to secure passenger comfort in the interior of the vehicle (for example, to adjust the hip point of a seat downwards), it is difficult to secure a space for mounting the cylinder-type or donut-type bombe therein.

(4) For example, the cylinder-type bombe has a cylindrical structure with a long length and a large volume and occupies a part of the inner space of a trunk or a luggage compartment, thus substantially reducing the available space in the trunk or the luggage compartment.

(5) Furthermore, in a vehicle body in which the overall height of the vehicle body is reduced, the center of gravity of the vehicle body is adjusted downwards and the height of an underbody is reduced, there is a spatial limitation in installation of the cylinder-type or donut-type bombe on the underbody.

(6) The information disclosed in this Background of the Invention section is only for enhancement of understanding of the general background of the invention and may not be taken as an acknowledgement or any form of suggestion that this information forms the prior art already known to a person skilled in the art.

BRIEF SUMMARY

(7) Various aspects of the present invention are directed to providing a low profile flat bombe for LPG storage which has a flat structure having a rectangular shape and may thus be easily mounted on the underbody of a vehicle to secure the internal space of the vehicle and the load space thereof, and a method for manufacturing the same.

(8) Various aspects of the present invention are directed to providing a low profile flat bombe for LPG storage including a flat bombe body including an upper plate having a plurality of first piercing holes and a pump installation hole formed therethrough, a lower plate having a plurality of second piercing holes formed therethrough at positions vertically coinciding with the plurality of first piercing holes, and side plates integrally connecting first and second side end portions of the upper plate and the lower plate, end plates mounted at front and rear openings in the flat bombe body, and support pipes, wherein upper end portions of the support pipes are welded to internal circumferential portions of the plurality of first piercing holes and lower end portions thereof are welded to internal circumferential portions of the plurality of second piercing holes to maintain a vertical distance between the upper plate and the lower plate.

(9) In various exemplary embodiments of the present invention, the upper plate and the lower plate may be provided as plate structures configured to have the same area with a greater longitudinal length than a lateral length, and the side plates and the end plates may be provided as curved surface structures configured to be convex outwards and to have a height equal to the vertical distance between the upper plate and the lower plate.

(10) In various exemplary embodiments of the present invention, the longitudinal length or the lateral length of the upper plate and the lower plate may be set to be greater than the height of the side plates and the end plates.

(11) In various exemplary embodiments of the present invention, a flange portion bent towards inside of the flat bombe body to be welded to each of the support pipes may be formed in an internal circumferential portion of each of the plurality of first piercing holes and the plurality of second piercing holes.

(12) In various exemplary embodiments of the present invention, a plurality of baffles having fluid passing holes formed therethrough may be disposed in a predetermined arrangement between support pipes in the flat bombe body, and an upper and a lower end portion of each of the plurality of baffles may be respectively welded to the upper plate and the lower plate.

(13) In various exemplary embodiments of the present invention, each of the plurality of baffles may have a plate structure bent at a designated angle to relieve and distribute stress concentrated on spaces between the neighboring support pipes in the flat bombe body, and may be configured such that lengths and areas of portions of each of the plurality of baffles welded to the upper plate and the lower plate are maximally increased.

(14) In various exemplary embodiments of the present invention, a bead portion configured to have a designated shape convex towards inside of the flat bombe body may be formed on the lower plate at a position vertically coinciding with the pump installation hole of the upper plate.

(15) In various exemplary embodiments of the present invention, a boss portion configured to secure a space for installation of a pump may be welded to the pump installation hole of the upper plate, and at least two reinforcing blades configured to support and protect the pump may be

connected to a lower end portion of the boss portion welded to the pump installation hole of the upper plate and to the bead portion of the lower plate by welding.

(16) In various exemplary embodiments of the present invention, a reinforcing rib may be connected to the at least two reinforcing blades by welding.

(17) In various exemplary embodiments of the present invention various exemplary embodiments of the present invention, a reinforcing steel pipe to relieve local stress may be located at a central region between the upper plate and the lower plate, and may be welded to the upper plate and the bead portion of the lower plate.

(18) In various exemplary embodiments of the present invention various exemplary embodiments of the present invention, a plurality of mounting brackets configured to be fixedly assembled with a vehicle body may be mounted on the flat bombe body and the end plates.

(19) Various aspects of the present invention are directed to providing a method for manufacturing a low profile flat bombe for LPG storage, the method including preparing a plate body having a designated area, forming a plurality of first piercing holes and a pump installation hole through one side region of the plate body used as an upper plate, and simultaneously, forming a plurality of second piercing holes through a remaining side region of the plate body used as a lower plate, using piercing and drawing, bending both side end portions of the plate body to form side plates, preparing a flat bombe body including the upper plate configured to have the plurality of first piercing holes and the pump installation hole formed therethrough, the lower plate configured to have the plurality of second piercing holes formed therethrough at positions vertically coinciding with the plurality of first piercing holes, and the side plates integrally connecting first and second side end portions of the upper plate and the lower plate by welding the bent side end portions of the bent plate body, welding end plates to front and rear openings of the flat bombe body, and welding upper end portions of support pipes, configured to connect the upper plate and the lower plate to each other and to maintain a vertical distance between the upper plate and the lower plate, to internal circumferential portions of the plurality of first piercing holes, and simultaneously, welding lower end portions of the support pipes to internal circumferential portions of the plurality of second piercing holes.

(20) In various exemplary embodiments of the present invention, the method may further include, before the welding the end plates to the front and rear openings, welding upper end portions and lower end portions of baffles, configured to have fluid passing holes, to the upper plate and the lower plate in spaces between neighboring support pipes among an internal space of the flat bombe body.

(21) In various exemplary embodiments of the present invention, the method may further include, before welding the end plates to the front and rear openings, welding a boss portion configured to secure a space for installation of a pump to the pump installation hole of the upper plate, and welding at least two reinforcing blades configured to support and protect the pump to the boss portion and the lower plate.

(22) In various exemplary embodiments of the present invention, the method may further include assembling a pump assembly into the boss portion and the reinforcing blades.

(23) Other aspects and exemplary inventions of the present invention are discussed infra.

(24) The above and other features of the present invention are discussed infra.

(25) The methods and apparatuses of the present invention have other features and advantages which will be apparent from or are set forth in more detail in the accompanying drawings, which are incorporated herein, and the following Detailed Description, which together serve to explain certain principles of the present invention.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is an exploded perspective view exemplarily illustrating a low profile flat bombe for LPG storage according to various exemplary embodiments of the present invention;
- (2) FIG. 2 is an assembled perspective view exemplarily illustrating the low profile flat bombe for LPG storage according to various exemplary embodiments of the present invention;
- (3) FIG. 3 is a cross-sectional view exemplarily illustrating the low profile flat bombe for LPG storage according to various exemplary embodiments of the present invention;
- (4) FIG. 4 is a cross-sectional view exemplarily illustrating a support pipe in a welded state among elements of the low profile flat bombe for LPG storage according to various exemplary embodiments of the present invention;
- (5) FIG. 5 is a perspective cross-sectional view exemplarily illustrating a baffle in a welded state among the elements of the low profile flat bombe for LPG storage according to various exemplary embodiments of the present invention;
- (6) FIG. 6 is a perspective cross-sectional view exemplarily illustrating a boss portion and a reinforcing blade in a welded state among the elements of the low profile flat bombe for LPG storage according to various exemplary embodiments of the present invention;
- (7) FIG. 7 is a perspective cross-sectional view exemplarily illustrating a reinforcing steel pipe in a welded state among the elements of the low profile flat bombe for LPG storage according to various exemplary embodiments of the present invention;
- (8) FIG. 8, FIG. 9, FIG. 10, FIG. 11 and FIG. 12 are perspective views exemplarily illustrating a process for manufacturing the low profile flat bombe for LPG storage according to various exemplary embodiments of the present invention in order; and
- (9) FIG. 13 is a schematic view exemplarily illustrating the provided position and state of the low profile flat bombe for LPG storage according to various exemplary embodiments of the present invention.
- (10) It should be understood that the appended drawings are not necessarily to scale, presenting a somewhat simplified representation of various preferred features illustrative of the basic principles of the present invention. The specific design features of the present invention as disclosed herein, including, for example, specific dimensions, orientations, locations, and shapes, will be determined in part by the particular intended application and use environment.
- (11) In the figures, reference numbers refer to the same or equivalent parts of the present invention throughout the several figures of the drawing.

DETAILED DESCRIPTION

- (12) Reference will now be made in detail to various embodiments of the present invention(s), examples of which are illustrated in the accompanying drawings and described below. While the present invention(s) will be described in conjunction with exemplary embodiments of the present invention, it will be understood that the present description is not intended to limit the present invention(s) to those exemplary embodiments. On the other hand, the present invention(s) is/are intended to cover not only the exemplary embodiments of the present invention, but also various alternatives, modifications, equivalents and other embodiments, which may be included within the spirit and scope of the present invention as defined by the appended claims.
- (13) Hereinafter reference will be made in detail to various embodiments of the present invention, examples of which are illustrated in the accompanying drawings and described below. While the present invention will be described in conjunction with exemplary embodiments of the present invention, it will be understood that the present description is not intended to limit the present invention to the exemplary embodiments. On the other hand, the present invention is intended to cover not only the exemplary embodiments of the present invention, but also various alternatives, modifications, equivalents and other embodiments, which may be included within the spirit and scope of the present invention as defined by the appended claims.

(14) FIG. 1, FIG. 2, and FIG. 3 illustrate a low profile flat bombe for LPG storage according to various exemplary embodiments of the present invention and in these figures, reference numeral **100** indicates a flat bombe body.

(15) As shown in FIG. 1, FIG. 2, and FIG. 3, the flat bombe body **100** includes an upper plate **110** configured to have a plurality of first piercing holes **111** and a pump installation hole **112** formed therethrough, a lower plate **120** configured to have a plurality of second piercing holes **121** formed therethrough at positions vertically coinciding with the first piercing holes **111**, and side plates **130** configured to integrally connect both side end portions of the upper plate **110** and the lower plate **120**.

(16) Furthermore, end plates **140**, which provide a closed space configured to charge the flat bombe with LPG and are configured to prevent backward flow or overflow of LPG, are welded to front and rear openings of the flat bombe body **100**.

(17) The flat bombe body **100** must be easily mounted on the underbody of a vehicle, which has a reduced overall height and the center of gravity adjusted downwards and has the reduced height of the underbody, without a spatial limitation.

(18) For the present purpose, the upper plate **110** and the lower plate **120** are provided as plate structures having the same area which have a greater longitudinal length than a lateral length, and the side plates **130** and the end plates **140** are provided as curved surface structures which have the same height as a vertical distance between the upper plate **110** and the lower plate **120** and are convex outwards.

(19) Furthermore, because the longitudinal length or the lateral length of the upper plate **110** and the lower plate **120** is set to be greater than the height of the side plates **130** and the end plates **140** so that the flat bombe body **100** is manufactured in a flat rectangular shape, the flat bombe body **100** may be easily mounted on the underbody of the vehicle without a spatial limitation, and thus, a large internal space of the vehicle and a large load space thereof may be secured.

(20) In the flat bombe body **100**, the upper plate **110** and the lower plate **120** must not be deformed to easily endure the internal pressure of the flat bombe charged with LPG, and the constant vertical distance between the upper plate **110** and the lower plate **120** must be maintained.

(21) For the present purpose, a plurality of support pipes **150** is provided between the upper plate **110** and the lower plate **120**.

(22) More concretely, as shown in FIG. 4, the external diameter portion of the upper end portion of the support pipe **150** is attached and welded to the internal circumferential portion of the first piercing hole **111** of the upper plate **110**, and the external diameter portion of the lower end portion of the support pipe **150** is attached and welded to the internal circumferential portion of the second piercing hole **121** of the lower plate **120**.

(23) Here, flange portions **113** and **123**, which are bent toward the inside of the flat bombe body **100** to be welded to the support pipes **150**, are formed in the internal circumferential portions of the first piercing holes **111** and the second piercing holes **121** by drawing.

(24) Therefore, as shown in FIG. 4, concave valleys **114** and **124** externally exposed are formed as spaces, in which welding is easily performed, at a contact region between the external diameter portion of the upper end portion of the support pipe **150** and the flange portion **113** in the internal circumferential portion of the first piercing hole **111** and a contact region between the external diameter portion of the lower end portion of the support pipe **150** and the flange portion **123** in the internal circumferential portion of the second piercing hole **121**.

(25) Therefore, equipment, such as a welding gun, may easily approach the valleys **114** and **124**, being capable of easily performing welding.

(26) Accordingly, the support pipes **150** are integrally connected to the upper plate **110** and the lower plate **120** by welding and thus serve to securely fix the upper plate **110** and the lower plate **120** and to maintain the constant vertical distance between the upper plate **110** and the lower plate **120**, and consequently, the upper plate **110** and the lower plate **120** are not deformed by the internal

pressure of the flat bombe charged with LPG.

(27) A plurality of baffles **160**, each of which includes a plate body bent at a designated angle and fluid passing holes **162** formed therethrough, is disposed in a designated arrangement in spaces between the neighboring support pipes **150** among the internal space of the flat bombe body **100**, and the upper end portion and the lower end portion of each of the baffles **160** are attached and welded to the lower surface of the upper plate **110** and the upper surface of the lower plate **120**.

(28) Therefore, the respective baffles **160** are configured to reduce the velocity of fluid, such as LPG, and noise caused thereby while allowing the flow of the fluid through the fluid passing holes **162**, and are also configured to distribute stress applied to the upper plate **110** and the lower plate **120** because the baffles **160** are connected to the upper plate **110** and the lower plate **120** by welding.

(29) Furthermore, when the upper end portion and the lower end portion of each of the baffles **160** are attached and welded to the lower surface of the upper plate **110** and the upper surface of the lower plate **120**, the welding sections of each of the baffles **160** may be formed to have a length as long as possible to relieve stress applied to the flat bombe.

(30) More concretely, each of the baffles **160** may have a plate structure bent at a designated angle to relieve and distribute stress concentrated on the spaces between the neighboring support pipes **150** among the internal space of the flat bombe body **100**, and be configured such that the lengths and areas of portions of the baffle **160** welded to the upper plate **110** and the lower plate **120** are maximally increased.

(31) A pump assembly **200** configured to supply LPG to an engine of the vehicle is provided inside and outside the flat bombe body **100**.

(32) For the present purpose, the pump installation hole **112** is formed through the upper plate **110**, and a bead portion **125** having a designated shape, which is convex toward the inside of the flat bombe body **100**, is formed on the lower plate **120** at a position vertically coinciding with the pump installation hole **112**.

(33) Here, the bead portion **125**, which is a kind of reinforcing structure against the load of the pump assembly **200**, is formed to be convex using a press used to manufacture the upper plate **110** and the lower plate **120**, and in the instant housing, the bead portion **125** is formed as having a loop-type profile to surround the circumference of the lower end portion of the pump assembly **200**.

(34) Furthermore, as shown in FIG. 6, a cylindrical boss portion **170** configured to secure a space for installation of the pump assembly **200** is welded to the inlet of the pump installation hole **112** of the upper plate **110**, and two or more curved-type reinforcing blades **172** configured to support and protect a pump are connected to the lower end portion of the boss portion **170** welded to the pump installation hole **112** of the upper plate **110** and to the bead portion **125** of the lower plate **120** by welding.

(35) A reinforcing rib **174** is further connected to the two or more reinforcing blades **172** by welding.

(36) Therefore, when the pump assembly **200** enters the inside of the flat bombe body **100** through the pump installation hole **112** and is mounted in the bead portion **125** of the lower plate **120**, the circumference of the pump assembly **200** may be supported by the boss portion **170** and the reinforcing blades **172**, deformation of the reinforcing blades **172** may be prevented by the reinforcing rib **174** even though the load of the pump and stress are transmitted to the reinforcing blades **172**, and deformation of the lower plate **120** on which the load of the pump assembly **200** and the stress are concentrated may be prevented by the bead portion **125** provided as a reinforcing structure formed on the lower plate **120**.

(37) The flat bombe body **100** has a rectangular shape as seen from above, local stress may be concentrated on a central region between the upper plate **110** and the lower plate **120**, and to solve the present concentration, a separate reinforcing steel pipe **176** may be located between the upper

plate **110** and the lower plate **120** and connected to the lower surface of the upper plate **110** and the bead portion **125** of the lower plate **120** by welding, as shown in FIG. 7.

(38) A plurality of mounting brackets **180** configured to be fixedly assembled with a vehicle body is mounted on the external surfaces of both sides of the flat bombe body **100** and the external surfaces of the end plates **140** in a designated arrangement by welding.

(39) Accordingly, the low profile flat bombe according to various exemplary embodiments of the present invention is manufactured to have a structure having a low height and a large area, compared to the conventional cylinder-type or donut-type bombe, and may thus be easily mounted on an underbody **300** of a vehicle, as shown in FIG. 13, and thereby, a large internal space of the vehicle and a large load space thereof may be secured.

(40) Furthermore, in a vehicle body having a reduced overall height and the center of gravity which is adjusted downwards, and including the underbody **300** having a reduced height, the low profile flat bombe for LPG storage according to various exemplary embodiments of the present invention may be easily mounted on the underbody **300** without a spatial limitation.

(41) Hereinafter, a method for manufacturing the flat bombe having the above-described configuration according to various exemplary embodiments of the present invention will be described.

(42) FIG. 8, FIG. 9, FIG. 10, FIG. 11 and FIG. 12 are perspective views exemplarily illustrating a process for the manufacturing low profile flat bombe for LPG storage according to various exemplary embodiments of the present invention in order.

(43) First, a metal plate body having a designated area is prepared.

(44) Thereafter, using piercing and drawing, a plurality of first piercing holes **111** and the pump installation hole **112** are formed through one side region (first side region) **11** of the metal plate body **10** which will be used as the upper plate **110**, and simultaneously a plurality of second piercing holes **121** is formed through the other side region of the metal plate body **10** which will be used as the lower plate **120**, and then both side end portions (first and second side end portions) **13**, **14** of the metal plate body **10** are bent to form side plates **130**.

(45) Therefore, to prepare the flat bombe body **100**, the first piercing holes **111** and the pump installation hole **112** may be formed through one side region **11** of the metal plate **10** body which will be used as the upper plate **110** and the second piercing holes **121** may be formed through the other side region (remaining side region) **12** of the metal plate body which will be used as the lower plate **120** simultaneously, and both side end portions (first and second side end portions) **13**, **14** of the metal plate body **10** are bent into a curved type to form the side plates **130**, by performing piecing and drawing on the metal plate body **10** having the designated area, as shown in FIG. 8.

(46) Thereafter, preparation of the flat bombe body **100** including the upper plate **110** having the first piercing holes **111** and the pump installation hole **112** formed therethrough, the lower plate **120** having the second piercing holes **121** formed therethrough at positions vertically coinciding with the first piercing holes **111**, and the side plates **130** integrally connecting both side end portions of the upper plate **110** and the lower plate **120** may be completed by welding the bent side end portions of the metal plate body, as shown in FIG. 9.

(47) Here, the baffles **160**, the boss portion **170**, etc. may be easily placed into the flat bombe body **100** through the front and rear openings of the flat bombe body **100**.

(48) Thereafter, the upper end portions and the lower end portions of the baffles **160** having the fluid passing holes **162** are welded to the lower surface of the upper plate **110** and the upper surface of the lower plate **120** in spaces between the neighboring support pipes **150**, which will be mounted in a subsequent operation, among the internal space of the flat bombe body **100**, as shown in FIG. 10.

(49) Furthermore, the boss portion **170** configured to secure a space for installation of the pump assembly **200** is welded to the pump installation hole **112** of the upper plate **110**, and two or more reinforcing blades **172** configured to support and protect the pump are welded to the lower end

portion of the boss portion **170** and the bead portion **125** of the lower plate **120**.

(50) Here, the reinforcing rib **174** may be further welded to the two or more reinforcing blades **172**, and the reinforcing steel pipe **176** may be welded to the tower surface of the upper plate **110** and the bead portion **125** of the lower plate **120**.

(51) Thereafter, the end plates **140** are welded to the front and rear openings of the flat bombe body **100**, as shown in FIG. **11**.

(52) Thereafter, the support pipes **150** configured to connect the upper plate **110** and the lower plate **120** to each other and to maintain the vertical distance between the upper plate **110** and the lower plate **120** are inserted into and then welded to the first piercing holes **111** of the upper plate **110** and the second piercing holes **121** of the lower plate **120**, as shown in FIG. **12**.

(53) That is, the external diameter portions of the upper end portions of the support pipes **150** are attached and welded to the internal circumferential portions of the first piercing holes **111**, and the external diameter portions of the lower end portions of the support pipes **150** are attached and welded to the internal circumferential portions of the second piercing holes **121**, securely supporting the upper plate **110** and the lower plate **120** and maintaining the constant vertical distance between the upper plate **110** and the lower plate **120**.

(54) Finally, the pump assembly **200** is assembled into the boss portion **170** and the reinforcing blades **172**.

(55) That is, when the pump assembly **200** is inserted into the flat bombe body **100** through the pump installation hole **112** and is mounted in the bead portion **125** of the lower plate **120**, the circumference of the pump assembly **200** may be supported by the boss portion **170** and the reinforcing blades **172**.

(56) Accordingly, the low profile flat bombe according to various exemplary embodiments of the present invention having a structure which has a low height and a large area, compared to the conventional cylinder-type or donut-type bombe, may be easily manufactured.

(57) As is apparent from the above description, a low profile flat bombe for LPG storage and a method for manufacturing the same according to various exemplary embodiments of the present invention are directed to providing the following effects.

(58) First, the low profile flat bombe for LPG storage according to various exemplary embodiments of the present invention has a flat structure having a rectangular shape and may thus be easily mounted on the underbody of a vehicle, being configured for securing a large internal space of the vehicle and a large load space thereof.

(59) Second, in a vehicle body having a reduced overall height and the center of gravity which is adjusted downwards, and including an underbody having a reduced height, the low profile flat bombe for LPG storage according to various exemplary embodiments of the present invention may be easily mounted on the underbody without a spatial limitation.

(60) For convenience in explanation and accurate definition in the appended claims, the terms “upper”, “lower”, “inner”, “outer”, “up”, “down”, “upwards”, “downwards”, “front”, “rear”, “back”, “inside”, “outside”, “inwardly”, “outwardly”, “interior”, “exterior”, “internal”, “external”, “forwards”, and “backwards” are used to describe features of the exemplary embodiments with reference to the positions of such features as displayed in the figures. It will be further understood that the term “connect” or its derivatives refer both to direct and indirect connection.

(61) The foregoing descriptions of specific exemplary embodiments of the present invention have been presented for purposes of illustration and description. They are not intended to be exhaustive or to limit the present invention to the precise forms disclosed, and obviously many modifications and variations are possible in light of the above teachings. The exemplary embodiments were chosen and described to explain certain principles of the present invention and their practical application, to enable others skilled in the art to make and utilize various exemplary embodiments of the present invention, as well as various alternatives and modifications thereof. It is intended that the scope of the present invention be defined by the Claims appended hereto and their equivalents.

Claims

1. A method for manufacturing a low profile flat bombe for Liquefied Petroleum Gas (LPG) storage, the method comprising: preparing a plate body having a designated area; forming a plurality of first piercing holes and a pump installation hole through a first side region of the plate body used as an upper plate, and simultaneously, forming a plurality of second piercing holes through a remaining side region of the plate body used as a lower plate, using piercing and drawing; bending first and second side end portions of the plate body to form side plates; preparing a flat bombe body including the upper plate having the plurality of first piercing holes and the pump installation hole formed therethrough, the lower plate having the plurality of second piercing holes formed therethrough at positions vertically corresponding to the plurality of first piercing holes, and the side plates integrally connecting first and second side end portions of the upper plate and the lower plate by welding the bent first and second side end portions of the bent side plates of the plate body; welding end plates to front and rear openings of the flat bombe body; and welding upper end portions of support pipes, configured to connect the upper plate and the lower plate to each other and to maintain a vertical distance between the upper plate and the lower plate, to flange portions of the plurality of first piercing holes, and simultaneously, welding lower end portions of the support pipes to flange portions of the plurality of second piercing holes.
 2. The method of claim 1, further including, before the welding of the end plates to the front opening and the rear opening: welding upper end portions and lower end portions of baffles, configured to have fluid passing holes, to the upper plate and the lower plate in spaces between neighboring support pipes in the flat bombe body.
 3. The method of claim 1, further including, before the welding of the end plates to the front opening and the rear opening: welding a boss portion configured to secure a space for installation of a pump to the pump installation hole of the upper plate, and welding at least two reinforcing blades configured to support and protect the pump to the boss portion and the lower plate.
 4. The method of claim 3, further including: assembling a pump assembly into the boss portion and the at least two reinforcing blades.
-