

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405637
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Zhang; Jianji

Foldable device and display device

Abstract

The present disclosure provides a foldable device and a display device, wherein at least one secondary folding axis intersects a primary folding axis and divides the frame plate into a plurality of sub-frame plates, and a folding hinge is configured to enable the foldable device to be folded on the plurality of folding axes, thereby improving a user's experience.

Inventors:	Zhang; Jianji (Hubei, CN)
Applicant:	WUHAN CHINA STAR OPTOELECTRONICS SEMICONDUCTOR DISPLAY TECHNOLOGY CO., LTD. (Hubei, CN)
Family ID:	84243373
Assignee:	WUHAN CHINA STAR OPTOELECTRONICS SEMICONDUCTOR DISPLAY TECHNOLOGY CO., LTD. (Hubei, CN)
Appl. No.:	18/247587
Filed (or PCT Filed):	February 13, 2023
PCT No.:	PCT/CN2023/075682
PCT Pub. No.:	WO2024/031948
PCT Pub. Date:	February 15, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240361811 A1	Oct. 31, 2024

Foreign Application Priority Data

CN	202210959483.2	Aug. 10, 2022
----	----------------	---------------

Publication Classification

Int. Cl.: G06F1/16 (20060101); H05K5/02 (20060101)

U.S. Cl.:

CPC G06F1/1681 (20130101); H05K5/0226 (20130101);

Field of Classification Search

CPC: G06F (1/1681); G06F (1/16); G06F (1/1616); G06F (1/1652); G06F (1/1618); H05K (5/0226); H04M (1/0222); H04M (1/0249)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2007/0279315	12/2006	Laves	345/1.1	H04M 1/0268
2010/0041439	12/2009	Bullister	455/566	G06F 1/165
2014/0375530	12/2013	Delaporte	345/1.3	G06F 1/1652
2018/0039467	12/2017	Feng	N/A	G09G 3/3208
2021/0151697	12/2020	Cao	N/A	H10K 71/00
2021/0355988	12/2020	Cheng	N/A	G06F 1/1681
2022/0043480	12/2021	Seo	N/A	G09F 9/301
2022/0238049	12/2021	Min	N/A	G09F 9/301
2022/0283608	12/2021	Xianyu	N/A	H04M 1/0247
2022/0303371	12/2021	Liao	N/A	H04M 1/0268
2023/0021638	12/2022	Yun	N/A	G06F 1/1681
2023/0054249	12/2022	Wu	N/A	G06F 1/1681
2023/0320006	12/2022	Gong	361/807	H04M 1/0268
2024/0044360	12/2023	Zhang	N/A	H04M 1/022

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
107508932	12/2016	CN	N/A
110232869	12/2018	CN	N/A
111637147	12/2019	CN	F16C 11/04
113299195	12/2020	CN	N/A
114754065	12/2021	CN	N/A
115442459	12/2021	CN	N/A
2015109013	12/2014	JP	N/A

OTHER PUBLICATIONS

International Search Report in International application No. PCT/CN2023/075682, mailed on May 29, 2023. cited by applicant

Primary Examiner: Shrestha; Sagar

Attorney, Agent or Firm: PV IP PC

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates to a technical field of electronic apparatuses, and more particularly, to a foldable device and a display device.

BACKGROUND

(2) Recently, OLED display technology has been widely used, and folding mobile phones are more and more popular owe to the OLED display technology. The folding mobile phones are future development trend of mobile phone industry, and thus becoming a research hotspot to mobile phones and panel manufacturers. Meanwhile, foldable tablets and notebook computers also appear. However, conventional folding display devices have only a single folding axis or two folding axes parallel to each other. As such, the conventional folding display device has less folding configuration. With the development of science and technology, more and more user pay attention to user's experience, and therefore display devices having more folding configuration are needed to satisfy the user experience.

Technical Problem

(3) The present disclosure provides a foldable device and a display panel to improve a user' experience.

SUMMARY

(4) The present disclosure provides a foldable device including: a frame plate; one primary folding axis; at least one secondary folding axis, wherein the at least one secondary folding axis does not intersect each other, the at least one secondary folding axis intersects the primary folding axis to divide the frame plate into a plurality of sub-frame plates; and a folding mechanism including a first folding hinge and a second folding hinge; wherein at least one pair of adjacent sub-frame plates located on the primary folding axis are connected by the first folding hinge, at least one pair of adjacent sub-frame plates located on the at least one secondary folding axis are connected by the second folding hinge, and any one of the sub-frame plates is connected to at least one of the first folding hinge or the second folding hinge.

(5) In some embodiments of the present disclosure, the first folding hinge and the second folding hinge include: a first rotating member; a second rotating member; and a first base, wherein an end of the first rotating member is rotatably connected to the first base, and an end of the second rotating member is rotatably connected to the first base; wherein a side of another end of the first rotating member of the first folding hinge is connected to one of the at least one pair of adjacent sub-frame plates located on the primary folding axis, and a side of another end of the second rotating member of the first folding hinge is connected to another of the at least one pair of adjacent sub-frame plates located on the primary folding axis; wherein a side of another end of the first rotating member of the second folding hinge is connected to one of the at least one pair of adjacent sub-frame plates located on the at least one secondary folding axis, and a side of another end of the second rotating member of the second folding hinge is connected to another of the at least one pair

of adjacent sub-frame plates located on the at least one secondary folding axis.

(6) In some embodiments of the present disclosure, the first folding hinge and the second folding hinge further include: a first damping mechanism connected to the first base and the first rotating member; and a second damping mechanism connected to the first base and the second rotating member; when the first rotating member is rotated relative to the first base from a first position to a second position by an external force, the first damping mechanism generates a damping force that prevents the first rotating member from rotating, and when the external force is removed, the first damping mechanism holds the first rotating member in the second position; when the second rotating member is rotated relative to the first base from a third position to a fourth position by the external force, the second damping mechanism generates the damping force that prevents the second rotating member from rotating, and when the external force is removed, the second damping mechanism holds the second rotating member in the fourth position.

(7) In some embodiments of the present disclosure, the first damping mechanism includes: a first rotating shaft provided on the first base; a first movable portion, wherein an end of the first movable portion is rotatably connected to the first rotating shaft, and another end of the first movable portion is rotatably connected to the first rotating member; and a first damping portion provided on the first rotating shaft; when the first rotating member is rotated relative to the first base from the first position to the second position by the external force, the first movable portion and the first damping portion are relatively rotated, and a frictional damping force is generated.

(8) In some embodiments of the present disclosure, when the first rotating member is rotated relative to the first base from the first position to the second position by an external force, the first movable portion and the first damping portion are relatively rotated to a set position, and the frictional damping force is generated between the first movable portion and the first damping portion; when the external force is removed, the first movable portion holds the first rotating member in the second position.

(9) In some embodiments of the present disclosure, the first damping portion includes: a first slider slidably disposed on the first rotating shaft; and a first elastic member provided between the first slider and the first base; when the first rotating member is rotated relative to the first base from the first position to the second position by the external force, the first movable portion and the first slider are relatively rotated and press the first elastic member, and the frictional damping force is generated between the first movable portion and the first slider by the first elastic member.

(10) In some embodiments of the present disclosure, the second damping mechanism includes: a second rotating shaft provided on the first base; a second movable portion, wherein an end of the second movable portion is rotatably connected to the second rotating shaft, and another end of the second movable portion is connected to the second rotating member; and a second damping portion provided on the second rotating shaft; when the second rotating member is rotated relative to the first base from the third position to the fourth position by the external force, the second movable portion and the second damping portion are relatively rotated, and a frictional damping force is generated.

(11) In some embodiments of the present disclosure, when the second rotating member is rotated relative to the first base from the third position to the fourth position by the external force, the second movable portion and the second damping portion are relatively rotated to a set position, and the frictional damping force is generated between the second movable portion and the second damping portion; when the external force is removed, the frictional damping force holds the second rotating member in the fourth position.

(12) In some embodiments of the present disclosure, the second damping portion includes: a second slider slidably disposed on the second rotating shaft; and a second elastic member provided between the second slider and the first base; when the second rotating member is rotated relative to the first base from the third position to the fourth position by the external force, the second movable portion and the second slider are relatively rotated and press the second elastic member,

and the frictional damping force is generated between the second movable portion and the second slider by the second elastic member.

(13) In some embodiments of the present disclosure, at least one pair of adjacent sub-frame plates located on the primary folding axis are connected by two first folding hinges; wherein the two first folding hinges are connected through a first base plate.

(14) In some embodiments of the present disclosure, the folding mechanism further includes: a hinge structure including a third rotating member, a fourth rotating member, and a second base, wherein an end of the third rotating member is rotatably connected to the second base, and an end of the fourth rotating member is rotatably connected to the second base; wherein the at least one pair of adjacent sub-frame plates located on the primary folding axis are connected by a first hinge structure, wherein a side of another end of the third rotating member of the first hinge structure is connected to one of the at least one pair of adjacent sub-frame plates located on the primary folding axis, and a side of another end of the fourth rotating member of the first hinge structure is connected to another of the at least one pair of adjacent sub-frame plates located on the primary folding axis.

(15) In some embodiments of the present disclosure, the at least one pair of adjacent sub-frame plates located on the at least one secondary folding axis are connected by a second hinge structure; wherein a side of another end of the third rotating member of the second hinge structure is connected to one of the at least one pair of adjacent sub-frame plates located on the secondary folding axis, and a side of another end of the fourth rotating member of the second hinge structure is connected to another of the at least one pair of adjacent sub-frame plates located on the secondary folding axis.

(16) In some embodiments of the present disclosure, the at least one pair of adjacent sub-frame plates located on the at least one secondary folding axis are connected to the second folding hinge by the second hinge structure, and the first base of the second folding hinge is connected to the second base of the second hinge structure by a connecting plate.

(17) In some embodiments of the present disclosure, the secondary folding axis is divided into a first folding section and a second folding section by the primary folding axis, a pair of adjacent sub-frame plates located on the first folding section are connected by the second hinge structure and the second folding hinge, and a pair of adjacent sub-frame plates located on the second folding section are connected by the second hinge structure and the second folding hinge; wherein the first base of the second folding hinge located on the first folding section is connected to the second base of the second hinge structure located on the second folding section by a first connecting plate; and the first base of the second folding hinge located on the second folding section is connected to the second base of the second hinge structure located on the second folding section by a second connecting plate.

(18) In some embodiments of the present disclosure, the first connecting plate and the second connecting plate are connected by a third hinge structure, wherein a side of another end of the third rotating member of the third hinge structure is connected to the first connecting plate, and a side of another end of the fourth rotating member of the third hinge structure is connected to the second connecting plate.

(19) In some embodiments of the present disclosure, the foldable device further includes: a first folding housing provided at a bending region of the first folding section of the secondary folding axis, wherein the first folding housing is provided at a side of the first connecting plate close to the frame plate and is connected to a side of another end of the third rotating member of the third hinge structure, and the first connecting plate; a second folding housing provided at a bending region of the second folding section of the secondary folding axis, wherein the second folding housing is provided at a side of the second connecting plate close to the frame plate and is connected to a side of another end of the fourth rotating member of the third hinge structure, and the second connecting plate; and a third folding housing provided on a side of the third hinge structure close to the frame

plate and connected to the second base of the third hinge structure.

(20) In some embodiments of the present disclosure, the hinge structure further includes a second synchronizing mechanism connected between the third rotating member and the fourth rotating member, wherein the second synchronizing mechanism leads the third rotating member and the fourth rotating member to rotate synchronically towards each other or away from each other.

(21) In some embodiments of the present disclosure, the second synchronization mechanism includes: a third link, wherein an end of the third link is hinged to the third rotating member, and another end of the third link is hinged to the fourth rotating member.

(22) In some embodiments of the present disclosure, the second synchronizing mechanism further includes: a third eccentric shaft provided on the third rotating member and paralleled axially to a rotating center of the third rotating member rotating about the second base; and a fourth eccentric shaft provided on the fourth rotating member and paralleled axially to a rotating center of the fourth rotating member rotating about the second base; wherein an end of the third link is hinged to the third eccentric shaft, and another end of the third link is hinged to the fourth eccentric shaft.

(23) In some embodiments of the present disclosure, a display device is provided, wherein the display device includes a foldable device and a display panel. The foldable device includes a frame plate, one primary folding axis, at least one secondary folding axis, wherein the at least one secondary folding axis does not intersect each other, the at least one secondary folding axis intersects the primary folding axis to divide the frame plate into a plurality of sub-frame plates; and a folding mechanism including a first folding hinge and a second folding hinge; wherein at least one pair of adjacent sub-frame plates located on the primary folding axis are connected by the first folding hinge, at least one pair of adjacent sub-frame plates located on the at least one secondary folding axis are connected by the second folding hinge, and any one of the sub-frame plates is connected to at least one of the first folding hinge or the second folding hinge. The display panel is disposed on a side of the frame plate of the foldable device.

Beneficial Effects

(24) A foldable device and a display device are provided in the present disclosure. The foldable device includes a frame plate; one primary folding axis; at least one secondary folding axis, wherein the at least one secondary folding axis does not intersect each other, the at least one secondary folding axis intersects the primary folding axis to divide the frame plate into a plurality of sub-frame plates; and a folding mechanism including a first folding hinge and a second folding hinge; wherein at least one pair of adjacent sub-frame plates located on the primary folding axis are connected by the first folding hinge, at least one pair of adjacent sub-frame plates located on the at least one secondary folding axis are connected by the second folding hinge, and any one of the sub-frame plates is connected to at least one of the first folding hinge or the second folding hinge. According to the foldable device, the at least one secondary folding axis intersects the primary folding axis to divide the frame plate into a plurality of sub-frame plates. The user can use the folding hinges to fold the foldable device along the folding axes, as such, the user' experience is improved.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In order that the technical solution in the embodiments of the present disclosure may be explained more clearly, references will now be made briefly to the accompanying drawings required for the description of the embodiments. It will be apparent that the accompanying drawings in the following description are merely some of the embodiments of the present disclosure, and other drawings may be made to those skilled in the art without involving any inventive effort.

- (2) FIG. 1 is a schematic diagram of a folding hinge from a first view according to the present disclosure;
- (3) FIG. 2 is an exploded schematic diagram of FIG. 1;
- (4) FIG. 3 is a schematic diagram of a folding hinge from a second view according to the present disclosure;
- (5) FIG. 4 is an exploded schematic diagram of FIG. 3;
- (6) FIG. 5 is a schematic diagram of a first rotating member of a folding hinge according to the present disclosure;
- (7) FIG. 6 is a schematic diagram of a second rotating member of a folding hinge according to the present disclosure;
- (8) FIG. 7 is a schematic assembled diagram of a first rotating member and a second rotating member of a folding hinge according to the present disclosure;
- (9) FIG. 8 is a schematic diagram of a first base of a folding hinge from a first view according to the present disclosure;
- (10) FIG. 9 is a schematic diagram of a first base of a folding hinge from a second view according to the present disclosure;
- (11) FIG. 10 is a schematic diagram of a first damping mechanism and a second damping mechanism of a folding hinge according to the present disclosure;
- (12) FIG. 11 is a schematic diagram of a first movable portion of a first damping mechanism of a folding hinge according to the present disclosure;
- (13) FIG. 12 is a schematic diagram of a second movable portion of a second damping mechanism of a folding hinge according to the present disclosure;
- (14) FIG. 13 is a schematic diagram of a first damping portion and a second damping portion of a folding hinge according to the present disclosure;
- (15) FIG. 14 is a schematic diagram of a first synchronizing mechanism of a folding hinge according to the present disclosure;
- (16) FIG. 15 is a schematic diagram of a foldable device according to the present disclosure;
- (17) FIG. 16 is an exploded schematic diagram of FIG. 15;
- (18) FIG. 17 is a schematic diagram of a frame plate of a foldable device according to the present disclosure;
- (19) FIG. 18 is a schematic diagram of a folding mechanism of a foldable device according to the present disclosure;
- (20) FIG. 19 is a schematic diagram of a folded housing of a foldable device according to the present disclosure;
- (21) FIG. 20 is a schematic diagram of a hinge structure of a foldable device from a first view according to the present disclosure.
- (22) FIG. 21 is an exploded schematic diagram of FIG. 20;
- (23) FIG. 22 is a schematic diagram of a hinge structure of a foldable device from a second view according to the present disclosure;
- (24) FIG. 23 is an exploded schematic diagram of FIG. 22;
- (25) FIG. 24 is a schematic diagram of a third rotating member of a hinge structure of a foldable device according to the present disclosure;
- (26) FIG. 25 is a schematic diagram of a fourth rotating member of a hinge structure of a foldable device according to the present disclosure;
- (27) FIG. 26 is a schematic assembled diagram of a third rotating member and a fourth rotating member of a hinge structure of a foldable device according to the present disclosure;
- (28) FIG. 27 is a schematic diagram of a second base of a hinge structure of a foldable device from a first view according to the present disclosure;
- (29) FIG. 28 is a schematic diagram of a second base of a hinge structure of a foldable device from a second view according to the present disclosure;

(30) FIG. 29 is a schematic diagram of a second synchronizing mechanism of a hinge structure of a foldable device according to the present disclosure; and

(31) FIG. 30 is a schematic diagram of a display panel of a display device according to the present disclosure.

DETAILED DESCRIPTION OF THE EMBODIMENTS

(32) The technical solutions in the embodiments of the present disclosure will be clearly and completely described in connection with the accompanying drawings in the embodiments of the present disclosure. It will be apparent that the described embodiments are merely a part of the embodiments of the present disclosure, rather than all the embodiments. Based on the embodiments in the present disclosure, all other embodiments obtained by a person skilled in the art without any inventive effort are within the scope of the present disclosure.

(33) In the description of this disclosure, it should be understood that the azimuth or positional relationship indicated by the terms “center”, “length”, “width”, “up”, “down”, “front”, “back”, “left”, “right”, “inside”, “outside”, and the like, is based on the azimuth or positional relationship shown in the drawings, merely to facilitate and simplify the description of this disclosure, and not to indicate or imply that the indicated device or element must have a particular azimuth, be constructed and operated in a particular azimuth, and therefore is not to be construed as limiting the disclosure. Furthermore, the terms “first” and “second” are used for descriptive purposes only and are not to be construed as indicating or implying relative importance or implying the number of indicated technical features. Thus, features defined as “first”, “second” may expressly or implicitly include one or more of said features. In the description of this application, “plurality” means two or more, unless otherwise expressly and specifically defined.

(34) In the description of the present disclosure, unless expressly defined and defined otherwise, terms such as “connected with”, “connected to”, “mounted”, “fixed” and the like are to be understood in a broad sense, for example, may be fixedly connected, detachably connected, or as a whole; may be mechanically connected or electrically connected; may be directly connected, indirectly connected through an intermediate medium, connected inside the two elements or interacted between the two elements. It will be appreciated by those of ordinary skill in the art that the foregoing may be understood as a specific meaning within the present invention, depending on the specific circumstances.

(35) The present disclosure provides a folding hinge, a foldable device, and a display device, which are described in detail below. It should be noted that the order in which the following examples are described is not intended to limit the preferred order of the embodiments of the present disclosure.

(36) Referring to FIGS. 1-4, FIG. 1 is a schematic diagram of a folding hinge 100 from a first view according to the present disclosure, FIG. 2 is an exploded schematic diagram of FIG. 1, FIG. 3 is a schematic diagram of the folding hinge 100 from a second view according to the present disclosure, and FIG. 4 is an exploded schematic diagram of FIG. 3. A folding hinge 100 is provided, wherein the folding hinge 100 includes a first rotating member 10, a second rotating member 20, a first base 30, a first damping mechanism 40, and a second damping mechanism 50.

(37) An end of the first rotating member 10 is rotatably connected to the first base 30, and an end of the second rotating member 20 is rotatably connected to the first base 30. The first damping mechanism 40 is connected to the first base 30 and the first rotating member 10. The second damping mechanism 50 is connected to the first base 30 and the second rotating member 20. When the first rotating member 10 is rotated from a first position to a second position with respect to the first base 30 by an external force, the first damping mechanism 40 generates a damping force to prevent the first rotating member 10 from rotating, and when the external force is removed, the first damping mechanism 40 holds the first rotating member 10 in the second position. When the second rotating member 20 is rotated from a third position to a fourth position with respect to the first base 30 by an external force, the second damping mechanism 50 generates a damping force to prevent the second rotating member 20 from rotating, and when the external force is removed, the second

damping mechanism **50** holds the second rotating member **20** in the fourth position.

(38) In the present disclosure, the first rotating member **10** is hovered by the first damping mechanism **40**, the second rotating member **20** is hovered by the second damping mechanism **50**. A certain damping sense can be fed back to the user by the damping mechanism, thereby improving the user experience.

(39) It should be noted that, when the first rotating member **10** is in the first position, the damping mechanism may maintain a damping force of a certain magnitude or 0. For example, when the first rotating member **10** is in the first position and the second rotating member **20** is in the third position, and an angle between the first rotating member **10** and the second rotating member **20** is 180° , the damping force of the damping mechanism is 0. When the first rotating member **10** is in the first position, and the angle between the first rotating member **10** and the second rotating member **20** is other than 180° , the damping mechanism maintains the damping force of a certain magnitude.

(40) Referring to FIGS. 5 to 9, FIG. 5 is a schematic diagram of a first rotating member **10** of a folding hinge **100** according to the present disclosure, FIG. 6 is a schematic diagram of a second rotating member **20** of a folding hinge **100** according to the present disclosure, FIG. 7 is a schematic assembled diagram of the first rotating member **10** and the second rotating member **20** of the folding hinge **100** according to the present disclosure, FIG. 8 is a schematic diagram of a first base **30** of the folding hinge **100** from a first view according to the present disclosure, and FIG. 9 is a schematic diagram of the first base **30** of the folding hinge **100** from a second view according to the present disclosure. In some embodiments, the first base **30** is provided with a first arcuate rail **31** or a first arcuate chute **11**, and the first rotating member **10** is provided with a first arcuate chute **11** or a first arcuate rail **31**, wherein the first arcuate rail **31** or the first arcuate chute **11** provided on the first base **30** is cooperated with the first arcuate chute **11** or the first arcuate rail **31** provided on the first rotating member **10**. Specifically, the first arcuate rail **31** is provided on the first base **30** and the first arcuate chute **11** is provided on the first rotating member **10**, and the first arcuate rail **31** is cooperated with the first arcuate chute **11**. An end of the first rotating member **10** is rotatably connected to the first base **30** by the engagement of the first arcuate rail **31** with the first arcuate chute **11**. It is contemplated that the first rotating member **10** may be rotatably connected to the first base **30** by a rotating shaft so that the end of the first rotating member **10** is rotatably connected to the first base **30**.

(41) Further, a first recess **33** is provided on a side of the first base **30**, and the first arcuate rail **31** is respectively provided on two opposite side walls of the first recess **33**. Specifically, the first rotating member **10** includes a first rotating block **13** and a first rotating plate **12**, and the first rotating block **13** is fixed at an end of the first rotating plate **12**. The first rotating block **13** is located in the first recess **33**, both sides of the first rotating block **13** are respectively provided with the first arcuate chute **11** which cooperates with the first arcuate rail **31**. An arcuate surface **15** is provided on a surface of the first rotating block **13** close to a bottom of the first recess **33**, so that friction between the first rotating block **13** and the first recess **33** can be reduced. A first through hole **35** is provided at the bottom of the first recess **33**, so that the contact between the first rotating block **13** and the first recess **33** can be reduced, thereby further reducing friction between the first rotating block **13** and the first recess **33**.

(42) In some embodiments, the first base **30** is provided with a second arcuate rail **32** or a second arcuate chute **21**, and the second rotating member **20** is provided with a second arcuate chute **21** or a second arcuate rail **32**, wherein the second arcuate rail **32** or the second arcuate chute **21** provided on the first base **30** is cooperated with the second arcuate chute **21** or the second arcuate rail **32** provided on the second rotating member **20**. Specifically, the second arcuate rail **32** is provided on the first base **30** and the second arcuate chute **21** is provided on the second rotating member **20**, and the second arcuate rail **32** is cooperated with the second arcuate chute **21**. The second arcuate chute **21** is engaged by the second arcuate rail **32** so that an end of the second rotating member **20** is

rotatably connected to the first base **30**. It is contemplated that the second rotating member **20** may be rotatably connected to the first base **30** by a rotating shaft so that the end of the second rotating member **20** is rotatably connected to the first base **30**.

(43) Further, in some embodiments of the present disclosure, a second recess **34** is provided on a side of the first base **30**, and the second arcuate rail **32** or the second arcuate chute **21** is provided on two opposite side walls of the second recess **34**, respectively. Specifically, the second rotating member **20** includes a second rotating block **23** and a second rotating plate **22**, the second rotating block **23** is fixed at an end of the second rotating plate **22**, and the second rotating block **23** is located in the second recess **34**. Both sides of the second rotating block **23** are respectively provided with the second arcuate chute **21** which cooperates with the second arcuate rail **32**. An arcuate surface **25** is provided on a surface of the second rotating block **23** close to a bottom of the second recess **34**, so that friction between the second rotating block **23** and the second recess **34** can be reduced. A second through hole **36** is provided at the bottom of the second recess **34**, so that contact between the second rotating block **23** and the second recess **34** can be reduced, thereby further reducing friction between the second rotating block **23** and the second recess **34**.

(44) In some embodiments, when an included angle between the first rotating member **10** and the second rotating member **20** is 180° , an end of the first rotating member **10** abuts against an end of the second rotating member **20**. The included angle between the first rotating member **10** and the second rotating member **20** can be defined to range from 0° to 180° , thereby avoiding an excessive rotation. Specifically, the first recess **33** communicates with the second recess **34**, and when the included angle between the first rotating member **10** and the second rotating member **20** is 180° , an end of the first rotating block **13** abuts against an end of the second rotating block **23**, a first notch **16** is provided on a surface of the first rotating block **13** contacting with the second rotating block **23**, and a first clamping block **26** which is cooperated with the first notch **16** is provided on the second rotating block **23**. The first rotating block **13** and the second rotating block **23** are engaged by the first notch **16** and the first clamping block **26**, and define an angle of 0° to 180° between the first rotating member **10** and the second rotating member **20**. Further, a second notch **27** is provided on a surface of the second rotating block **23** contacting with the first rotating block **13**, and the first rotating block **13** is provided with a second clamping block **17** which cooperates with the second notch **27**.

(45) Further, the folding hinge further includes a first end cover **60** provided on a side of the first base **30**, the first damping mechanism **40** is provided on a side of the first base **30** opposite to the first end cover **60**, and the first end cover **60** is connected to the first rotating member **10**. Specifically, a first connecting hole **37** communicating with the first recess **33** is provided on the first base **30** and at a side of the first base **30** provided with the first end cover **60**, and the first end cover **60** is connected to the first rotating member **10** through the first connecting hole **37**. The first end cover **60** is provided to prevent dust or impurities from entering the first recess **33**.

(46) In addition, the folding hinge further includes a second end cover **70** provided on a side of the first base **30**, the second damping mechanism **50** is provided on a side of the first base **30** opposite to the second end cover **70**, and the second end cover **70** is connected to the second rotating member **20**. Specifically, a second connecting hole **38** communicating with the second recess **34** is provided on the first base **30** and at a side of the first base **30** provided with the second end cover **70**, and the second end cover **70** is connected to the second rotating member **20** through the second connecting hole **38**. The second end cover **70** is provided to prevent dust or impurities from entering the second recess **34**.

(47) Referring to FIGS. **10** to **13**, FIG. **10** is a schematic diagram of a first damping mechanism **40** and a second damping mechanism **50** of a folding hinge **100** according to the present disclosure, FIG. **11** is a schematic diagram of a first movable portion **42** of the first damping mechanism **40** of the folding hinge **100** according to the present disclosure, FIG. **12** is a schematic diagram of a second movable portion **52** of the second damping mechanism **50** of the folding hinge **100**.

according to the present disclosure, and FIG. 13 is a schematic diagram of a first damping portion 43 and a second damping portion 53 of the folding hinge 100 according to the present disclosure. (48) In some embodiments, the first damping mechanism 40 includes: a first rotating shaft 41 provided on the first base 30; a first movable portion 42, wherein an end of the first movable portion 42 is rotatably connected to the first rotating shaft 41, and another end of the first movable portion 42 is connected to the first rotating member 10; a first damping portion 43 provided on the first rotating shaft 41; wherein, when the first rotating member 10 is rotated from a first position to a second position with respect to the first base 30 by an external force, the first movable portion 42 and the first damping portion 43 are relatively rotated to generate a frictional damping force. (49) According to the present disclosure, another end of the first movable portion 42 is connected to the first rotating member 10, the first rotating member 10 rotates the first movable portion 42 around the first rotating shaft 41 during its rotation. When the first rotating member 10 rotates relative to the first base 30 from the first position to the second position by the external force, the first movable portion 42 rotates relative to the first damping portion 43 and generates a frictional damping force. When the external force is removed, the frictional damping force causes the first rotating member 10 to remain in the second position.

(50) Specifically, the first movable portion 42 includes a first wing plate 423 and a first sleeve 422, and the first wing plate 423 and the first sleeve 422 are connected. The first sleeve 422 is rotatably connected to the first rotating shaft 41, an end of the first wing plate 423 is connected to the first sleeve 422, and the other end of the first wing plate 423 is connected to the first rotating plate 12. Further, a side of the first rotating plate 12 is provided with a first chute 14 along a rotating radial, and the other end of the first wing plate 423 is provided with a first sliding shaft 4231 cooperated with the first chute 14. The first rotating plate 12 and the first wing plate 423 are slidably connected to each other, thereby avoiding jamming.

(51) In some embodiments, the first damping portion 43 includes: a first slider 431 slidably disposed on the first rotating shaft 41; a first elastic member 432 disposed between the first slider 431 and the first base 30; wherein, when the first rotating member 10 is rotated from the first position to the second position with respect to the first base 30 by an external force, the first movable portion 42 and the first slider 431 are relatively rotated to press the first elastic member 432, and the first elastic member 432 generates a frictional damping between the first movable portion 42 and the first slider 431.

(52) That is, when the first rotating member 10 is rotated from the first position to the second position with respect to the first base 30 by an external force, the first movable portion 42 and the first slider 431 are relatively rotated to press the first elastic member 432, and the first elastic member 432 imparts a reverse force to the first slider 431, so that a frictional damping force is generated on the first movable portion 42 and the first slider 431.

(53) In some embodiments, a first projection 421 is provided on a surface of the first movable portion 42 contacting with the first slider 431, a first recess portion 4311 is provided on a surface of the first slider 431 contacting with the first movable portion 42, and the first recess portion 4311 is cooperated with the first projection 421. A first friction portion 4312 is provided on the surface of the first slider 431 contacting with the first movable portion 42, and the first friction portion 4312 is provided adjacent to the first recess portion 4311. Specifically, the first sleeve 422 is provided with a first projection 421 on a surface of the first sleeve 422 contacting with the first slider 431, and the first recess portion 4311 and the first friction portion 4312 are located in a same circumferential direction.

(54) That is, when the first projection 421 of the first movable portion 42 is aligned and engaged with the first recess portion 4311 of the first slider 431, no frictional damping force is generated between the first movable portion 42 and the first slider 431. When the first movable portion 42 and the first slider 431 are relatively rotated, the first projection 421 of the first movable portion 42 is aligned and engaged with the first frictional portion 4312 of the first slider 431. At this time, the

first movable portion **42** presses the first slider **431** and the first elastic member **432**, and the first elastic member **432** exerts a reverse force on the first slider **431**, so that the first movable portion **42** and the first slider **431** generate frictional damping force.

(55) When the number of the first recess portion **4311** is one, that is, one first recess portion **4311** is provided on the surface of the first slider **431** contacting with the first rotating member **10**. The first friction portion **4312** is provided on other portion except for the portion provided with the first recess portion **4311**. When the first projection **421** of the first movable portion **42** is aligned and engaged with the first recess portion **4311** of the first slider **431**, the first rotating member **10** is in a horizontal state, and the first rotating member **10** has not yet been rotated. When the first rotating member **10** is rotated, the first projection **421** of the first movable portion **42** is aligned and engaged with the first friction portion **4312** of the first slider **431**. Since the first friction portion **4312** is provided on other portion of the surface of the first slider **431** contacting with the first moveable portion **42** except for the portion provided with the first recess portion **4311**, the first friction portion **4312** can provide damping force to the first rotating member **10** for its continuous hovering. The first rotating member **10** can continue to rotate, as long as the external force overcomes the frictional damping force between the first movable portion **42** and the first slider **431**. When the external force is removed, the frictional damping force between the first movable portion **42** and the first slider **431** causes the first rotating member **10** to hover.

(56) Further, the first elastic member **432** comprises a spring sleeved on the first rotating shaft **41**, wherein the spring is located between the first slider **431** and the first base **30**. When the first projection **421** of the first movable portion **42** is aligned and engaged with the first frictional portion **4312** of the first slider **431**, the first movable portion **42** presses the first slider **431** and the spring, and the spring imparts a reverse force to the first slider **431** so that a frictional damping force is generated between the first movable portion **42** and the first slider **431**. In other embodiments of the present disclosure, the first elastic member **432** includes a spring washer sleeved on the first rotating shaft **41** and is located between the first slider **431** and the first base **30**.

(57) In some embodiments, the first recess portion **4311** includes an arcuate groove. Further, a side wall of the arcuate groove is an arcuate curved surface, and a bottom surface of the arcuate groove is a plane surface. The first recess portion **4311** is provided as an arcuate groove, so that the first projection **421** and the first recess portion **4311** can rotate relatively smoothly, thereby avoiding the occurrence of jamming. The first friction portion **4312** includes a first contact surface on the same circumference as the first recess portion **4311**. The first contact surface includes a non-smooth surface provided with a particle projection to increase the friction force, thereby increasing the friction damping force between the first friction portion **4312** and the first projection **421**.

(58) Further, the first projection **421** includes a second contact surface **4211**, a first arcuate curved surface **4212** and a second arcuate curved surface **4213**, wherein the second contact surface **4211** protrudes toward the first slider **431**, the first arcuate curved surface **4212** is connected between an end of the second contact surface **4211** and the first movable portion **42**, and the second arcuate curved surface **4213** is connected between the other end of the second contact surface **4211** and the first movable portion **42**. The first projection **421** has two arcuate curved surfaces, and the first arcuate curved surface **4212** and the second arcuate curved surface **4213** correspond to the side walls of the arcuate grooves, respectively, so that the friction force between the first projection **421** and the first recess portion **4311** is further reduced, and the first projection **421** and the first recess portion **4311** are more smoothly rotated relative to each other. Further, the second contact surface **4211** includes a non-smooth surface provided with a particle projection to increase the friction force, thereby increasing the friction damping force between the first friction portion **4312** and the first projection **421**.

(59) In some embodiments, when the first rotating member **10** is rotated relative to the first base **30** from the first position to the second position by an external force, the first movable portion **42** and the first damping portion **43** are relatively rotated to a set position, and a frictional damping force is

generated between the first movable portion **42** and the first damping portion **43**. When the external force is removed, the first movable portion **42** holds the first rotating member **10** in the second position.

(60) That is, the first movable portion **42** and the first damping portion **43** are relatively rotated to the set position, and a frictional damping force is generated between the first movable portion **42** and the first damping portion **43** so that the first rotating member **10** can be hovered at the set position.

(61) Further, a surface of the first slider **431** contacting with the first movable portion **42** is provided with a plurality of first recess portions **4311** in a same circumferential, and a first friction portion **4312** is provided between adjacent first recess portions **4311**. By providing a plurality of first recess portions **4311**, and providing a first friction portion **4312** between adjacent first recess portions **4311**, the first projection portions **421** can cooperate with the plurality of first recess portions **4311** or the plurality of first friction portions **4312**. When the first movable portion **42** and the first damping portion **43** are relatively rotated to a position in which the first projection **421** is aligned and engaged with the first friction portion **4312**, a frictional damping force is generated between the first movable portion **42** and the first damping portion **43**, so that the first rotating member **10** can be hovered at a set position. Since the first projection **421** cooperates with the plurality of first recess portions **4311** or the plurality of first friction portions **4312**, a plurality of hovering positions is provided, thereby hovering the first rotating member **10** at a plurality of rotation angles.

(62) Referring to FIGS. **10** to **13**, FIG. **10** is a schematic diagram of a first damping mechanism **40** and a second damping mechanism **50** of a folding hinge **100** according to the present disclosure, FIG. **11** is a schematic diagram of a first movable portion **42** of the first damping mechanism **40** of the folding hinge **100** according to the present disclosure, FIG. **12** is a schematic diagram of a second movable portion **52** of the second damping mechanism **50** of the folding hinge **100** according to the present disclosure, and FIG. **13** is a schematic diagram of a first damping portion **43** and a second damping portion **53** of the folding hinge **100** according to the present disclosure.

(63) In some embodiments, the second damping mechanism **50** includes: a second rotating shaft **51** provided on the first base **30**; a second movable portion **52**, wherein an end of the second movable portion **52** is rotatably connected to the second rotating shaft **51**, and another end of the second movable portion **52** is connected to the second rotating member **20**; a second damping portion **53** provided on the second rotating shaft **51**; wherein, when the second rotating member **20** is rotated from a third position to a fourth position with respect to the first base **30** by an external force, the second movable portion **52** and the second damping portion **53** are relatively rotated to generate a frictional damping force.

(64) According to the present disclosure, another end of the second movable portion **52** is connected to the second rotating member **20**, the second rotating member **20** rotates the second movable portion **52** around the second rotating shaft **51** during its rotation. When the second rotating member **20** rotates relative to the first base **3** from the third position to the fourth position **0** by the external force, the second movable portion **52** rotates relative to the second damping portion **53** and generates a frictional damping force. When the external force is removed, the frictional damping force causes the second rotating member **20** to remain in the fourth position.

(65) Specifically, the second movable portion **52** includes a second wing plate **523** and a second sleeve **522**, and the second wing plate **523** and the second sleeve **522** are connected. The second sleeve **522** is rotatably connected to the second rotating shaft **51**, an end of the second wing plate **523** is connected to the second sleeve **522**, and the other end of the second wing plate **523** is connected to the second rotating plate **22**. Further, a side of the second rotating plate **22** is provided with a second chute **24** along a rotating radial, and the other end of the second wing plate **523** is provided with a second sliding shaft **5231** cooperated with the second chute **24**. The second rotating plate **22** and the second wing plate **523** are slidably connected to each other, thereby

avoiding jamming.

(66) In some embodiments, the second damping portion **53** includes: a second slider **531** slidably disposed on the second rotating shaft **51**; a second elastic member **532** disposed between the second slider **531** and the first base **30**; wherein, when the second rotating member **20** is rotated from the third position to the fourth position with respect to the first base **30** by an external force, the second movable portion **52** and the second slider **531** are relatively rotated to press the second elastic member **532**, and the second elastic member **532** generates a frictional damping between the second movable portion **52** and the second slider **531**.

(67) That is, when the second rotating member **20** is rotated from the third position to the fourth position with respect to the first base **30** by an external force, the second movable portion **52** and the second slider **531** are relatively rotated to press the second elastic member **532**, and the second elastic member **532** imparts a reverse force to the second slider **531**, so that a frictional damping force is generated on the second movable portion **52** and the second slider **531**.

(68) In some embodiments, a second projection **521** is provided on a surface of the second movable portion **52** contacting with the second slider **531**, a second recess portion **5311** is provided on a surface of the second slider **531** contacting with the second movable portion **52**, and the second recess portion **5311** is cooperated with the second projection **521**. A second friction portion **5312** is provided on the surface of the second slider **531** contacting with the second movable portion **52**. and the second friction portion **5312** is provided adjacent to the second recess portion **5311**. Specifically, the second recess portion **5311** and the second friction portion **5312** are located in a same circumferential direction.

(69) That is, when the second projection **521** of the second movable portion **52** is aligned and engaged with the second recess portion **5311** of the second slider **531**, no frictional damping force is generated between the second movable portion **52** and the second slider **531**. When the second movable portion **52** and the second slider **531** are relatively rotated, the second projection **521** of the second movable portion **52** is aligned and engaged with the second frictional portion **5312** of the second slider **531**. At this time, the second movable portion **52** presses the second slider **531** and the second elastic member **532**, and the second elastic member **532** exerts a reverse force on the second slider **531**, so that the second movable portion **52** and the second slider **531** generate frictional damping force.

(70) When the number of the second recess portion **5311** is 1, that is, one second recess portion **5311** is provided on the surface of the second slider **531** contacting with the second rotating member **20**. The second friction portion **5312** is provided on other portion except for the portion provided with the second recess portion **5311**. When the second projection **521** of the second movable portion **52** is aligned and engaged with the second recess portion **5311** of the second slider **531**, the second rotating member **20** is in a horizontal state, and the second rotating member **20** has not yet been rotated. When the second rotating member **20** is rotated, the second projection **521** of the second movable portion **52** is aligned and engaged with the second friction portion **5312** of the second slider **531**. Since the second friction portion **5312** is provided on other portion of the surface of the second slider **531** contacting with the second moveable portion **52** except for the portion provided with the second recess portion **5311**, the second friction portion **5312** can provide damping force to the second rotating member **20** for its continuous hovering. The second rotating member **20** can continue to rotate, as long as the external force overcomes the frictional damping force between the second movable portion **52** and the second slider **531**. When the external force is removed, the frictional damping force between the second movable portion **52** and the second slider **531** causes the second rotating member **20** to hover.

(71) Further, the second elastic member **532** comprises a spring sleeved on the second rotating shaft **51**, wherein the spring is located between the second slider **531** and the first base **30**. When the second projection **521** of the second movable portion **52** is aligned and engaged with the second frictional portion **5312** of the second slider **531**, the second movable portion **52** presses the second

slider **531** and the spring, and the spring imparts a reverse force to the second slider **531** so that a frictional damping force is generated between the second movable portion **52** and the second slider **531**. In other embodiments of the present disclosure, the second elastic member **532** includes a spring washer sleeved on the second rotating shaft **51** and is located between the second slider **531** and the first base **30**.

(72) In some embodiments, the second recess portion **5311** includes an arcuate groove. Further, a side wall of the arcuate groove is an arcuate curved surface, and a bottom surface of the arcuate groove is a plane surface. The second recess portion **5311** is provided as an arcuate groove, so that the second projection **521** and the second recess portion **5311** can rotate relatively smoothly, thereby avoiding the occurrence of jamming. The second friction portion **5312** includes a second contact surface on the same circumference as the second recess portion **5311**. The second contact surface includes a non-smooth surface provided with a particle projection to increase the friction force, thereby increasing the friction damping force between the second friction portion **5312** and the second projection **521**.

(73) Further, the second projection **521** includes a fourth contact surface **5211**, a third arcuate curved surface **5212** and a fourth arcuate curved surface **5213**, wherein the fourth contact surface **5211** protrudes toward the second slider **531**, the third arcuate curved surface **5212** is connected between an end of the fourth contact surface **5211** and the second movable portion **52**. and the fourth arcuate curved surface **5213** is connected between the other end of the fourth contact surface **5211** and the second movable portion **52**. The second projection **521** has two arcuate curved surfaces, and the third arcuate curved surface **5212** and the fourth arcuate curved surface **5213** correspond to the side walls of the arcuate grooves, respectively, so that the friction force between the second projection **521** and the second recess portion **5311** is further reduced, and the second projection **521** and the second recess portion **5311** are more smoothly rotated relative to each other. Further, the fourth contact surface **5211** includes a non-smooth surface provided with a particle projection to increase the friction force, thereby increasing the friction damping force between the second friction portion **5312** and the second projection **521**.

(74) In some embodiments, when the second rotating member **20** is rotated relative to the first base **30** from the third position to the fourth position by an external force, the second movable portion **52** and the second damping portion **53** are relatively rotated to a set position, and a frictional damping force is generated between the second movable portion **52** and the second damping portion **53**. When the external force is removed, the frictional damping force holds the second rotating member **20** in the second position.

(75) That is, the second movable portion **52** and the second damping portion **53** are relatively rotated to the set position, and a frictional damping force is generated between the second movable portion **52** and the second damping portion **53** so that the second rotating member **20** can be hovered at the set position.

(76) Further, a surface of the second slider **531** contacting with the second movable portion **52** is provided with a plurality of second recess portions **5311** in a same circumferential, and a first second portion **5312** is provided between adjacent second recess portions **5311**. By providing a plurality of second recess portions **5311**, and providing a second friction portion **5312** between adjacent second recess portions **5311**, the second projection portions **521** can cooperate with the plurality of second recess portions **5311** or the plurality of second friction portions **5312**. When the second movable portion **52** and the second damping portion **53** are relatively rotated to a position in which the second projection **521** is aligned and engaged with the second friction portion **5312**, a frictional damping force is generated between the second movable portion **52** and the second damping portion **53**, so that the second rotating member **20** can be hovered at a set position. Since the second projection **521** cooperates with the plurality of second recess portions **5311** or the plurality of second friction portions **5312**, a plurality of hovering positions is provided, thereby hovering the second rotating member **20** at a plurality of rotation angles.

(77) In some embodiments, the first slider **431** is connected to the second slider **531** by a second link **44**. By connecting the first slider **431** to the second slider **531** by the second link **44**, the first slider **431** and the second slider **531** can be kept sliding synchronously, thereby ensuring that the first damping mechanism **40** and the second damping mechanism **50** generate the same frictional damping force, while preventing the first slider **431** and the second slider **531** from rotating.

(78) Referring to FIGS. 1-14, FIG. 14 is a schematic diagram of a first synchronizing mechanism **80** of a folding hinge **100** according to the present disclosure. In some embodiments, the folding hinge **100** further includes a first synchronizing mechanism **80** connected between the first damping mechanism **40** and the second damping mechanism **50**. The first synchronizing mechanism **80** leads the first rotating member **10** and the second rotating member **20** to rotate synchronically towards or away from each other.

(79) The first synchronizing mechanism **80** is provided to rotate synchronically the first rotating member **10** and the second rotating member **20** towards or away from each other, such that the first rotating member **10** and the second rotating member **20** remains a same rotating angle.

(80) Further, the first synchronizing mechanism **80** includes a first link **81**, wherein an end of the first link **81** is hinged to the first movable portion **42** of the first damping mechanism **40**, and the other end of first link **81** is hinged to the second movable portion **52** of the second damping mechanism **50**. The first movable part **42** of the first damping mechanism **40** and the second movable part **52** of the second damping mechanism **50** are driven by the first link **81** to rotate synchronically towards or away from each other. Specifically, the end of the first link **81** is hinged to the first sleeve **422** of the first movable portion **42**, and the other end of the first link **81** is hinged to the second sleeve **522** of the second movable portion **52**.

(81) Further, the first synchronizing mechanism **80** further includes a first eccentric shaft **82** and a second eccentric shaft **83**. The first eccentric shaft **82** is provided on the first movable portion **42** in parallel with the first rotating shaft **41**. The second eccentric shaft **83** is provided on the second movable portion **52** in parallel with the second rotating shaft **51**. The end of the first link **81** is hinged to the first eccentric shaft **82**, and the other end of the first link **81** is hinged to the second eccentric shaft **83**. Specifically, the first eccentric shaft **82** is provided on the first sleeve **422** in parallel with the first rotating shaft **41**, and the second eccentric shaft **83** is provided on the second sleeve **522** in parallel with the second rotating shaft **51**. In addition, a first mounting notch **4221** provided on a wall of the first sleeve **422** towards the second sleeve **522**, and the first eccentric shaft **82** is provided in the first mounting notch **4221**. A second mounting notch **5221** is provided on a wall of the second sleeve **522** towards the first sleeve **422**, and the second eccentric shaft **83** is provided in the second mounting notch **5221**. As such, the compactness of the first synchronizing mechanism **80** can be improved and the occupied area can be reduced. The radian of the first mounting notch **4221** is greater than or equal to 180° , and the radian of the second mounting notch **5221** is greater than or equal to 180° .

(82) Referring to FIGS. 15 to 18, FIG. 15 is a schematic diagram of a foldable device **1000** according to the present disclosure, FIG. 16 is an exploded schematic diagram of FIG. 15, FIG. 17 is a schematic diagram of a frame plate **101** of the foldable device **1000** according to the present disclosure, and FIG. 18 is a schematic diagram of a folding mechanism **102** of the foldable device **1000** according to the present disclosure. Accordingly, an embodiment of the present disclosure also provides a foldable device **1000** including a frame plate **101**, one primary folding axis **1011**. at least one secondary folding axis **1012**, and a folding mechanism **102**.

(83) The at least one secondary folding axis **1012** does not intersect each other, and the at least one secondary folding axis **1012** intersects the primary folding axis **1011** to divide the frame plate **101** into a plurality of sub-frame plates **1013**.

(84) The primary folding axis **1011** and the secondary folding axis **1012** are folding axes of the foldable device **1000**, that is, the foldable device **1000** can be folded along the primary folding axis **1011** or the secondary folding axis **1012**. The at least one secondary folding axis **1012** intersects the

primary folding axis **1011** to divide the frame plate **101** into a plurality of sub-frame plates **1013**, that is, the primary folding axis **1011** divides the frame plate **101** into two parts, and the at least one secondary folding axis **1012** divides the two parts into a plurality of sub-frame plates **1013**. For example, if only one secondary folding axis **1012** is provided, the frame plate **101** is divided into four sub-frame plates **1013**; and if two secondary folding axes **1012** are provided, the frame plate **101** is divided into six sub-frame plates **1013**.

(85) The folding mechanism **102** includes a first folding hinge **1021** and a second folding hinge **1022**. At least one pair of adjacent sub-frame plates **1013** located on the primary folding axis **1011** are connected by the first folding hinge **1021**, at least one pair of adjacent sub-frame plates **1013** located on the at least one secondary folding axis **1012** are connected by the second folding hinge **1022**, and any one of the sub-frame plates **1013** is connected to at least one first folding hinge **1021** or second folding hinge **1022**. Take providing only one secondary folding axis for example, the frame plate **101** is divided into four sub-frame plates **1013**, two pairs of adjacent sub-frame plates **1013** are provided on the primary folding axis **1011**, and the adjacent sub-frame plates **1013** are provided on two sides of the primary folding axis **1011**, respectively. There are two pairs of adjacent sub-frame plates **1013** located on the secondary folding axis **1012**, and the adjacent sub-frame plates **1013** are located on two sides of the secondary folding axis **1012**, respectively. Any one of the sub-frame plates **1013** is connected to at least one first folding hinge **1021** or second folding hinge **1022**, that is, it is ensured that at least one folding hinge and any one of the sub-frame plates **1013** are provided on the primary folding axis **1011** and the sub-folding axis **1012**.

(86) Specifically, a side of the other end of the first rotating member **10** of the first folding hinge **1021** is connected to one sub-frame plate **1013** of at least one pair of adjacent sub-frame plates **1013** located on the primary folding axis **1011**, and a side of the other end of the second rotating member **20** of the first folding hinge **1021** is connected to the other sub-frame plate **1013** of at least one pair of adjacent sub-frame plates **1013** located on the primary folding axis **1011**. A side of the other end of the first rotating member **10** of the second folding hinge **1022** is connected to one sub-frame plate **1013** of at least one pair of adjacent sub-frame plates **1013** located on the at least one secondary folding axis **1012**, and a side of the other end of the second rotating member **20** of the second folding hinge **1022** is connected to the other sub-frame plate **1013** of at least one pair of adjacent sub-frame plates **1013** located on the at least one secondary folding axis **1012**.

(87) It should be noted that the primary folding axis **1011** and the secondary folding axis **1012** are virtual axes generated by the foldable device **1000** of the present disclosure during the folding process. The foldable device **1000** of the present disclosure places the frame plate **101** on one side of the first folding hinge **1021** and the second folding hinge **1022**, so that the sub-frame plate **1013** can be folded along the primary folding axis **1011** and the secondary folding axis **1012**.

Furthermore, the foldable device **1000** of the present disclosure has not only a folding direction along the primary folding axis **1011** but also a folding direction along the secondary folding axis **1012**, and the primary folding axis **1011** and the secondary folding axis **1012** are intersected, so that the foldable device **1000** of the present disclosure can have at least two folding configurations, thereby improving a user experience.

(88) In some embodiments, at least one pair of adjacent sub-frame plates **1013** located on the primary folding axis **1011** are connected by two first folding hinges **1021**. The two first folding hinges **1021** are connected by a first base plate **1026**.

(89) The connection by the two first folding hinges **1021** enhances the frictional damping force. The two first folding hinges **1021** are connected by the first base plate **1026**, thereby improving the stability of the foldable device **1000** of the present disclosure.

(90) Referring to FIGS. **18** and **20** to **28**, FIG. **20** is a schematic diagram of a hinge structure of a foldable device **1000** from a first view according to the present disclosure, FIG. **21** is an exploded schematic diagram of FIG. **20**, FIG. **22** is a schematic diagram of a hinge structure of a foldable device **1000** from a second view according to the present disclosure, FIG. **23** is an exploded

schematic diagram of FIG. 22, FIG. 24 is a schematic diagram of a third rotating member 201 of a hinge structure of a foldable device 1000 according to the present disclosure, FIG. 25 is a schematic diagram of a fourth rotating member 202 of a hinge structure of a foldable device 1000 according to the present disclosure, FIG. 26 is a schematic assembled diagram of the third rotating member 201 and the fourth rotating member 202 of a hinge structure of a foldable device 1000 according to the present disclosure, FIG. 27 is a schematic diagram of a second base 203 of a hinge structure of a foldable device 1000 from a first view according to the present disclosure, and FIG. 28 is a schematic diagram of a second base 203 of a hinge structure of a foldable device 1000 from a second view according to the present disclosure.

(91) Further, the folding mechanism 102 further includes: a hinge structure including a third rotating member 201, a fourth rotating member 202, and a second base 203, wherein an end of the third rotating member 201 is rotatably connected to the second base 203, and an end of the fourth rotating member 202 is rotatably connected to the second base 203; wherein at least one pair of adjacent sub-frame plates 1013 located on the primary folding axis 1011 are connected by a first hinge structure 1024, wherein a side of the other end of the third rotating member 201 of the first hinge structure 1024 is connected to one sub-frame plate 1013 of at least one pair of adjacent sub-frame plates 1013 located on the primary folding axis 1011, and a side of the other end of the fourth rotating member 202 of the first hinge structure 1024 is connected to the other sub-frame plate 1013 of at least one pair of adjacent sub-frame plates 1013 located on the primary folding axis 1011.

(92) Specifically, take providing one secondary folding axis 1012 for example, the frame plate 101 is divided into four sub-frame plates 1013, the primary folding axis 1011 has two pairs of adjacent sub-frame plates 1013, the pair of adjacent sub-frame plates 1013 located on the primary folding axis 1011 is connected by two first folding hinges 1021, and the other pair of adjacent sub-frame plates 1013 located on the primary folding axis 1011 is connected by the first hinge structure 1024. The first hinge structure 1024 only functions as a hinge, and no damping mechanism is provided to the first folding hinge 1021. Thus, the first hinge structure 1024 is additionally provided on the primary folding axis 1011, in case of the primary folding axis 1011 providing with a first folding hinge 1021. As such, the foldable device 1000 can be hovered by the first folding hinge 1021, and the stability of folding of the foldable terminal in the primary folding axis 1011 can be improved by the first hinge structure 1024. Therefore, the number of the first folding hinges 1021 can be reduced, and the weight of the foldable terminal in the present disclosure can be reduced.

(93) In some embodiments, the at least one pair of adjacent sub-frame plates 1013 located on the at least one secondary folding axis 1012 are connected by a second hinge structure 1023. A side of the other end of the third rotating member 201 of the second hinge structure 1023 is connected to one sub-frame plate 1013 of at least one pair of adjacent sub-frame plates 1013 located on the secondary folding axis 1012, and a side of the other end of the fourth rotating member 202 of the second hinge structure 1023 is connected to the other sub-frame plate 1013 of at least one pair of adjacent sub-frame plates 1013 located on the secondary folding axis 1012. Any one of the secondary axis 1012 has two pairs of the sub-frame plates 1013. The second hinge structure 1023 only functions as a hinge, and no damping mechanism is provided to the second folding hinge 1022. Thus, the first hinge structure 1023 is additionally provided, in case of the second folding hinge 1022 providing with a secondary folding axis 1012. As such, the foldable device 1000 can be hovered by the second folding hinge 1022, and the stability of folding of the foldable terminal in the secondary folding axis 1012 can be improved by the second hinge structure 1023. Therefore, the number of the second folding hinges 1022 can be reduced, and the weight of the foldable terminal in the present disclosure can be reduced.

(94) Further, the at least one pair of adjacent sub-frame plates 1013 located on the at least one secondary folding axis 1012 are connected by the second hinge structure 1023 and the second folding hinge 1022, and the first base 30 of the second folding hinge 1022 is connected to the

second base **203** of the second hinge structure **1023** by a connecting plate. The secondary folding axis **1012** has two pairs of adjacent sub-frame plates **1013**, two pairs of adjacent sub-frame plates **1013** or one pair of adjacent sub-frame plates **1013** on the secondary folding axis **1012** are connected by the second hinge structure **1023** and the second folding hinge **1022**, and the first base **30** of the second folding hinge **1022** is connected by to the second base **203** of the second hinge structure **1023** the connecting plate, thereby improving the stability of folding of the foldable terminal in the direction of the secondary folding axis **1012**.

(95) Specifically, the secondary folding axis **1012** is divided into a first folding section and a second folding section by the primary folding axis **1011**, a pair of adjacent sub-frame plates **1013** located on the first folding section are connected by the second hinge structure **1023** and the second folding hinge **1022**, and a pair of adjacent sub-frame plates **1013** located on the second folding section are connected by the second hinge structure **1023** and the second folding hinge **1022**. A first base **30** of the second folding hinge **1022** located on the first folding section is connected to a second base **203** of the second hinge structure **1023** located on the second folding section by a first connecting plate **1027**. A first base **30** of the second folding hinge **1022** located on the second folding section is connected to a second base **203** of the second hinge structure **1023** located on the second folding section by a second connecting plate **1028**. That is, the secondary folding axis **1012** has two pairs of adjacent sub-frame plates **1013**, and the two pairs of adjacent sub-frame plates **1013** on the secondary folding axis **1012** are connected through the second hinge structure **1023** and the second folding hinge **1022**.

(96) In some embodiments, the first connecting plate **1027** and the second connecting plate **1028** are connected by a third hinge structure **1025**. A side of the other end of the third rotating member **201** of the third hinge structure **1025** is connected to the first connecting plate **1027**, and a side of the other end of the fourth rotating member **202** of the third hinge structure **1025** is connected to the second connecting plate **1028**.

(97) The first connecting plate **1027** and the second connecting plate **1028** are connected by the third hinge structure **1025**, thereby improving the consistency of the two pairs of adjacent sub-frame plates **1013** located on the secondary folding axis **1012** when folded, thereby improving the user experience.

(98) Referring to FIGS. **16-19**, FIG. **19** is a schematic diagram of a folding housing of a foldable device **1000** provided herein. Further, in some embodiments, the foldable device **1000** further includes: a first folding housing **106** provided at a bending region **1015** of the first folding section of the secondary folding axis **1012**, wherein the first folding housing **106** is provided at a side of the first connecting plate **1027** close to the frame plate **101**, and the first folding housing **106** is connected to a side of the other end of the third rotating member **201** of the third hinge structure **1025** and the first connecting plate **1027**; a second folding housing **107** provided at a bending region **1015** of the second folding section of the secondary folding axis **1012**, wherein the second folding housing **107** is provided at a side of the second connecting plate **1028** close to the frame plate **101**, and the second folding housing **107** is connected to a side of the other end of the fourth rotating member **202** of the third hinge structure **1025** and the second connecting plate **1028**; a third folding housing **108** provided on a side of the third hinge structure **1025** adjacent to the frame plate **101** and connected to the second base **203** of the third hinge structure **1025**.

(99) In the present disclosure, the first folding housing **106**, the second folding housing **107**, and the third folding housing **108** are provided to protect the bending region **1015** and the third hinge structure **1025** located on the secondary folding axis **1012**. In addition, the first folding housing **106** is connected to the first connecting plate **1027**, the second folding housing **107** is connected to the second connecting plate **1028**, and the third hinge structure **1025** is connected to the first folding housing **106** and the second folding housing **107**, so that the third hinge structure **1025** connects the first connecting plate **1027** and the second connecting plate **1028**.

(100) Further, the plurality of the sub-frame plates **1013** are provided with a first accommodating

recess **1016** at a position corresponding to the first folding housing **106**, the second folding housing **107** and the third folding housing **108** on the secondary folding axis **1012**, and the first accommodating recess **1016** is provided for accommodating the first folding housing **106**, the second folding housing **107** and the third folding housing **108**, thereby reducing the overall thickness.

(101) Referring to FIGS. **16-19**, further, in some embodiments, the primary folding axis **1011** is divided into a plurality of primary folding segments by the secondary folding axis **1012**, the bending region **1014** of each folding segment of the primary folding axis **1011** is provided with a primary folding housing **109** connected to a first base **30** of the first folding hinge **1021** or a second base **203** of the first hinge structure **1024**. The bending region **1014** located on the primary folding axis **1011** is protected by a primary folding housing **109**.

(102) Further, the plurality of the sub-frame plates **1013** are provided with a second accommodating cavity **1017** at a position corresponding to the primary folding housing **109** on the primary folding axis **1011**, and the second accommodating cavity **1017** is provided for accommodating the primary folding housing **109**, thereby reducing the overall thickness.

(103) Referring to FIGS. **15-17**, further in some embodiments, the foldable device **1000** further includes a protective housing **103**, each of the sub-frame plates **1013** is provided with the protective housing **103**, the protective housing **103** is connected to the sub-frame plate **1013**, and the protective housing **103** is provided on a side of the sub-frame plate away from the folding mechanism **102**. The sub-frame plate **1013** can be protected by the protective housing **103**, and the protective housing **103** and the sub-frame plate **1013** are in one-to-one correspondence.

(104) Referring to FIGS. **20 to 29**, in some embodiments, the second base **203** is provided with a third arcuate rail **2031** or a third arcuate chute **2011**, and the third rotating member **201** is provided with a third arcuate chute **2011** or a third arcuate rail **2031**, wherein the third arcuate rail **2031** or the third arcuate chute **2011** cooperates with the third arcuate chute **2011** or the third arcuate rail **2031**. Specifically, the second base **203** is provided with a third arcuate rail **2031**, and the third rotating member **201** is provided with the third arcuate chute **2011** that cooperates with the third arcuate rail **2031**. The third arcuate rail **2031** is engaged with the third arcuate chute **2011** so that an end of the third rotating member **201** is rotatably connected to the second base **203**. It is contemplated that the third rotating member **201** may be rotatably connected to the second base **203** by a rotating shaft, so that the end of the third rotating member **201** is rotatably connected to the second base **203**.

(105) Further, a third recess **2033** is provided on a side of the second base **203**, and the third arcuate rail **2031** is respectively provided on two opposite side walls of the third recess **2033**. Specifically, the third rotating member **201** includes a third rotating block **2012** and a third rotating plate **2013**, and the third rotating block **2012** is fixed at an end of the third rotating plate **2013**. The third rotating block **2012** is located in the third recess **2033**, both sides of the third rotating block **2012** are respectively provided with the third arcuate chute **2031** which cooperates with the third arcuate rail **2011**. An arcuate surface **2014** is provided on a surface of the third rotating block **2012** close to a bottom of the third recess **2033**, so that friction between the third rotating block **2012** and the third recess **2033** can be reduced. A third through hole **2035** is provided at the bottom of the third recess **2033**, so that the contact between the third rotating block **2012** and the third recess **2033** can be reduced, thereby further reducing friction between the third rotating block **2012** and the third recess **2033**.

(106) In some embodiments, the second base **203** is provided with a fourth arcuate rail **2032** or a fourth arcuate chute **2021**, and the fourth rotating member **202** is provided with a fourth arcuate chute **2021** or a fourth arcuate rail **2032**, wherein the fourth arcuate rail **2032** or the fourth arcuate chute **2021** provided on the second base **203** is cooperated with the fourth arcuate chute **2021** or the fourth arcuate rail **2032** provided on the fourth rotating member **202**. Specifically, the fourth arcuate rail **2032** is provided on the second base **203** and the fourth arcuate chute **2021** is provided

on the fourth rotating member **202**, and the fourth arcuate rail **2032** is cooperated with the fourth arcuate chute **2021**. The fourth arcuate chute **2021** is engaged by the fourth arcuate rail **2032** so that an end of the fourth rotating member **202** is rotatably connected to the second base **203**. It is contemplated that the fourth rotating member **202** may be rotatably connected to the second base **203** by a rotating shaft so that the end of the fourth rotating member **202** is rotatably connected to the second base **203**.

(107) Further, a fourth recess **2034** is provided on a side of the second base **203**, and the fourth arcuate rail **2032** or the fourth arcuate chute **2021** is provided on two opposite side walls of the fourth recess **2034**, respectively. Specifically, the fourth rotating member **202** includes a fourth rotating block **2022** and a fourth rotating plate **2023**, the fourth rotating block **2022** is fixed at an end of the fourth rotating plate **2023**, and the fourth rotating block **2022** is located in the fourth recess **2034**. Both sides of the fourth rotating block **2022** are respectively provided with the fourth arcuate chute **2021** which cooperates with the fourth arcuate rail **2032**. An arcuate surface **2024** is provided on a surface of the fourth rotating block **2022** close to a bottom of the fourth recess **2034**, so that friction between the fourth rotating block **2022** and the fourth recess **2034** can be reduced. A fourth through hole **2036** is provided at the bottom of the fourth recess **2034**, so that contact between the fourth rotating block **2022** and the fourth recess **2034** can be reduced, thereby further reducing friction between the fourth rotating block **2022** and the fourth recess **2034**.

(108) In some embodiments, when an included angle between the third rotating member **201** and the fourth rotating member **202** is 180° , an end of the third rotating member **201** abuts against an end of the fourth rotating member **202**. The included angle between the third rotating member **201** and the fourth rotating member **202** can be defined to range from 0° to 180° , thereby avoiding an excessive rotation. Specifically, the third recess **2033** communicates with the fourth recess **2034**, and when the included angle between the third rotating member **201** and the fourth rotating member **202** is 180° , an end of the third rotating block **2012** abuts against an end of the fourth rotating block **2022**, a third notch **2015** is provided on a surface of the third rotating block **2012** contacting with the fourth rotating block **2022**, and a third clamping block **2025** which is cooperated with the third notch **2015** is provided on the fourth rotating block **2022**. The third rotating block **2012** and the fourth rotating block **2022** are engaged by the third notch **2015** and the third clamping block **2025**, and define an angle of 0° to 180° between the third rotating member **201** and the fourth rotating member **202**. Further, a fourth notch **2026** is provided on a surface of the fourth rotating block **2022** contacting with the third rotating block **2012**, and the third rotating block **2012** is provided with a fourth clamping block **2016** which cooperates with the fourth notch **2026**.

(109) Further, the folding hinge further includes a third end cover **204** provided on a side of the second base **203**, and the third end cover **204** is connected to the third rotating member **201**. Specifically, a third connecting hole **2037** communicating with the third recess **2033** is provided on the second base **203** and at a side of the second base **203** provided with the third end cover **204**, and the third end cover **204** is connected to the third rotating member **201** through the third connecting hole **37**. The third end cover **204** is provided to prevent dust or impurities from entering the third recess **2033**.

(110) In addition, the folding hinge further includes a fourth end cover **205** provided on a side of the second base **203**, and the fourth end cover **205** is connected to the fourth rotating member **202**. Specifically, a fourth connecting hole **2038** communicating with the fourth recess **2034** is provided on the second base **203** and at a side of the second base **203** provided with the fourth end cover **205**, and the fourth end cover **205** is connected to the fourth rotating member **202** through the fourth connecting hole **2038**. The fourth end cover **205** is provided to prevent dust or impurities from entering the fourth recess **2034**.

(111) Referring to FIGS. **20-29**, FIG. **29** is a schematic diagram of a second synchronizing mechanism **206** of a hinge structure of a foldable device **1000** according to the present disclosure.

In some embodiments, the hinge structure further includes a second synchronizing mechanism **206** connected between the third rotating member **201** and the fourth rotating member **202**, the third synchronizing mechanism **206** lead the third rotating member **201** and the fourth rotating member **202** to rotate synchronically towards or away from each other.

(112) The second synchronizing mechanism **206** is provided to rotate synchronically the third rotating member **201** and the fourth rotating member **202** towards or away from each other, such that the third rotating member **201** and the fourth rotating member **202** remains a same rotating angle.

(113) Further, the second synchronizing mechanism **206** includes a third link **2061**, wherein an end of the third link **2061** is hinged to the third rotating member **201**, and the other end of the third link **2061** is hinged to the fourth rotating member **202**. The third rotating member **201** and the fourth rotating member **202** are driven by the third link **2061** to rotate synchronically towards or away from each other. Specifically, the end of the third link **2061** is hinged to the third rotating plate **2013** of the third rotating member **201**, and the other end of the third link **2061** is hinged to the fourth rotating plate **2023** of the fourth rotating member **202**.

(114) Further, the second synchronizing mechanism **206** further includes a third eccentric shaft **2062** and a fourth eccentric shaft **2063**. The third eccentric shaft **2062** and a rotating center of the third rotating member **201** rotating about the second base **203** are axially paralleled to the third rotating member **201**. The fourth eccentric shaft **2063** and a rotating center of the fourth rotating member **202** rotating about the second base **203** are axially paralleled to the fourth rotating member **202**. An end of the third link **2061** is hinged to the third eccentric shaft **2062**, and the other end of the third link **2061** is hinged to the fourth eccentric shaft **2063**.

(115) Referring to FIGS. **16** and **30**, FIG. **30** is a schematic diagram of a display panel **104** of a display device according to the present disclosure.

(116) Accordingly, an embodiment of the present disclosure further provides a display device, wherein the display device further includes: the foldable device **1000** as described above; a display panel **104** provided on a side of the frame plate **101** of the foldable device **1000**. Specifically, the display panel **104** is provided on a side of the frame plate **101** close to the folding mechanism **102**.

(117) The display panel **104** includes a steel sheet layer **1041**, a support film layer **1042**, an OLED light-emitting layer **1043**, a polarizing plate **1044**, a second optical transparent adhesive layer **1045**, an ultra-thin glass **1046**, a first optical transparent adhesive layer **1047**, and a protective film layer **1048**, which are stacked in sequence. The ultra-thin glass layer **1046** is provided with a first thinning region **10461** at the bending region of the primary folding axis **1011** and the secondary folding axis **1012**.

(118) The first thinning region **10461** is located on a side of the ultra-thin glass layer **1046** close to the first optical transparent adhesive layer **1047**. A thickness compensation coating **1049** is provided between the ultra-thin glass layer **1046** and the first optical transparent adhesive layer **1047**. The thickness compensation coating **1049** fills the first thinning region **10461**, and a material of the thickness compensation coating **1049** includes any one of polyimide, polyurethane, polymethyl methacrylate, and resin. The refractive index of the material of the thickness compensation coating **1049** is close to the refractive index of the ultra-thin glass, so that the optical abnormality of the first thinning region **10461** can be avoided by providing the thickness compensation coating **1049**.

(119) In the present disclosure, the ultra-thin glass layer is locally thinned, and the first thinning region **10461** is provided corresponding to the bending region. The first thinning region **10461** forms a cross thinning region at the position where the primary folding axis **1011** and the auxiliary folding axis **1012** intersect, thereby improving the bending performance of the ultra-thin glass **1046** in the bending region and ensuring the overall mechanical performance.

(120) Further, the steel sheet layer **1041** is provided with a second thinning region **10411** in the bending region of the primary folding axis **1011** and the secondary folding axis **1012**. In the present

disclosure, the steel sheet layer is locally thinned, and the second thinning region **10411** corresponds to the bending region, and the second thinning region **10411** forms a cross thinning region at the position where the primary folding axis **1011** and the auxiliary folding axis **1012** intersect, thereby improving the bending performance of the steel sheet layer **1041** in the bending region and ensuring the overall mechanical performance.

(121) The advantageous effects of the display device provided in the embodiment of the present invention are the same as those of the foldable device **1000** provided in the above-mentioned technical solution, and details are not described herein.

(122) In some embodiments, the display device further includes: a pressing strip **105** provided on the display panel **104** and adhesively connected to the frame plate **101**. The display panel **104** is fixed to the frame plate **101** by the pressing strip **105**.

(123) The present disclosure has been described in detail with reference to a foldable device and a display device according to the embodiments, in which specific examples are used to illustrate the principles and applications of the present disclosure. The description of the above embodiments is merely provided to assist in understanding the method of the present disclosure and the core concepts thereof. At the same time, variations will occur to those skilled in the art in both the detailed description and the scope of disclosure in accordance with the teachings of the present disclosure. In summary, the present description should not be construed as limiting the disclosure.

Claims

1. A foldable device, comprising: a frame plate; one primary folding axis; at least one secondary folding axis, wherein the at least one secondary folding axis intersects the primary folding axis to divide the frame plate into a plurality of sub-frame plates; and a folding mechanism including a first folding hinge and a second folding hinge; wherein at least one pair of adjacent sub-frame plates located on the primary folding axis are connected by the first folding hinge, at least one pair of adjacent sub-frame plates located on the at least one secondary folding axis are connected by the second folding hinge, and any one of the sub-frame plates is connected to at least one of the first folding hinge or the second folding hinge; wherein each of the first folding hinge and the second folding hinge comprises: a first rotating member; a second rotating member; and a first base, wherein an end of the first rotating member is rotatably connected to the first base, and an end of the second rotating member is rotatably connected to the first base; wherein a side of another end of the first rotating member of the first folding hinge is connected to one of the at least one pair of adjacent sub-frame plates located on the primary folding axis, and a side of another end of the second rotating member of the first folding hinge is connected to another of the at least one pair of adjacent sub-frame plates located on the primary folding axis; wherein a side of another end of the first rotating member of the second folding hinge is connected to one of the at least one pair of adjacent sub-frame plates located on the at least one secondary folding axis, and a side of another end of the second rotating member of the second folding hinge is connected to another of the at least one pair of adjacent sub-frame plates located on the at least one secondary folding axis; and wherein each of the first folding hinge and the second folding hinge further comprises: a first damping mechanism connected to the first base and the first rotating member; and a second damping mechanism connected to the first base and the second rotating member; when the first rotating member is rotated relative to the first base from a first position to a second position by an external force, the first damping mechanism generates a damping force that prevents the first rotating member from rotating, and when the external force is removed, the first damping mechanism holds the first rotating member in the second position; when the second rotating member is rotated relative to the first base from a third position to a fourth position by the external force, the second damping mechanism generates the damping force that prevents the second rotating member from rotating, and when the external force is removed, the second damping

mechanism holds the second rotating member in the fourth position.

2. The foldable device of claim 1, wherein the first damping mechanism comprises: a first rotating shaft provided on the first base; a first movable portion, wherein an end of the first movable portion is rotatably connected to the first rotating shaft, and another end of the first movable portion is rotatably connected to the first rotating member; and a first damping portion provided on the first rotating shaft; when the first rotating member is rotated relative to the first base from the first position to the second position by the external force, the first movable portion and the first damping portion are relatively rotated, and a frictional damping force is generated.

3. The foldable device of claim 2, wherein, when the first rotating member is rotated relative to the first base from the first position to the second position by an external force, the first movable portion and the first damping portion are relatively rotated to a set position, and the frictional damping force is generated between the first movable portion and the first damping portion; when the external force is removed, the first movable portion holds the first rotating member in the second position.

4. The foldable device of claim 2, wherein the first damping portion comprises: a first slider slidably disposed on the first rotating shaft; and a first elastic member provided between the first slider and the first base; when the first rotating member is rotated relative to the first base from the first position to the second position by the external force, the first movable portion and the first slider are relatively rotated and press the first elastic member, and the frictional damping force is generated between the first movable portion and the first slider by the first elastic member.

5. The foldable device of claim 1, wherein the second damping mechanism comprises: a second rotating shaft provided on the first base; a second movable portion, wherein an end of the second movable portion is rotatably connected to the second rotating shaft, and another end of the second movable portion is connected to the second rotating member; and a second damping portion provided on the second rotating shaft; when the second rotating member is rotated relative to the first base from the third position to the fourth position by the external force, the second movable portion and the second damping portion are relatively rotated, and a frictional damping force is generated.

6. The foldable device according to claim 5, wherein, when the second rotating member is rotated relative to the first base from the third position to the fourth position by the external force, the second movable portion and the second damping portion are relatively rotated to a set position, and the frictional damping force is generated between the second movable portion and the second damping portion; when the external force is removed, the frictional damping force holds the second rotating member in the fourth position.

7. The foldable device of claim 5, wherein the second damping portion comprises: a second slider slidably disposed on the second rotating shaft; and a second elastic member provided between the second slider and the first base; when the second rotating member is rotated relative to the first base from the third position to the fourth position by the external force, the second movable portion and the second slider are relatively rotated and press the second elastic member, and the frictional damping force is generated between the second movable portion and the second slider by the second elastic member.

8. The foldable device of claim 1, wherein at least one pair of adjacent sub-frame plates located on the primary folding axis are connected by two first folding hinges; wherein the two first folding hinges are connected through a first base plate.

9. The foldable device of claim 1, wherein the folding mechanism further comprises: a hinge structure including a third rotating member, a fourth rotating member, and a second base, wherein an end of the third rotating member is rotatably connected to the second base, and an end of the fourth rotating member is rotatably connected to the second base; wherein the at least one pair of adjacent sub-frame plates located on the primary folding axis are connected by a first hinge structure, wherein a side of another end of the third rotating member of the first hinge structure is

connected to one of the at least one pair of adjacent sub-frame plates located on the primary folding axis, and a side of another end of the fourth rotating member of the first hinge structure is connected to another of the at least one pair of adjacent sub-frame plates located on the primary folding axis.

10. The foldable device of claim 9, wherein the at least one pair of adjacent sub-frame plates located on the at least one secondary folding axis are connected by a second hinge structure, wherein a side of another end of the third rotating member of the second hinge structure is connected to one of the at least one pair of adjacent sub-frame plates located on the secondary folding axis, and a side of another end of the fourth rotating member of the second hinge structure is connected to another of the at least one pair of adjacent sub-frame plates located on the secondary folding axis.

11. The foldable device of claim 10, wherein the at least one pair of adjacent sub-frame plates located on the at least one secondary folding axis are connected to the second folding hinge by the second hinge structure.

12. The foldable device of claim 11, wherein the secondary folding axis is divided into a first folding section and a second folding section by the primary folding axis, a pair of adjacent sub-frame plates located on the first folding section are connected by the second hinge structure and the second folding hinge, and a pair of adjacent sub-frame plates located on the second folding section are connected by the second hinge structure and the second folding hinge; wherein the first base of the second folding hinge located on the first folding section is connected to the second base of the second hinge structure located on the second folding section by a first connecting plate; and the first base of the second folding hinge located on the second folding section is connected to the second base of the second hinge structure located on the second folding section by a second connecting plate.

13. The foldable device of claim 12, wherein the first connecting plate and the second connecting plate are connected by a third hinge structure, wherein a side of another end of the third rotating member of the third hinge structure is connected to the first connecting plate, and a side of another end of the fourth rotating member of the third hinge structure is connected to the second connecting plate.

14. The foldable device of claim 13, further comprising: a first folding housing provided at a bending region of the first folding section of the secondary folding axis, wherein the first folding housing is provided at a side of the first connecting plate close to the frame plate and is connected to a side of another end of the third rotating member of the third hinge structure, and the first connecting plate; a second folding housing provided at a bending region of the second folding section of the secondary folding axis, wherein the second folding housing is provided at a side of the second connecting plate close to the frame plate and is connected to a side of another end of the fourth rotating member of the third hinge structure, and the second connecting plate; and a third folding housing provided on a side of the third hinge structure close to the frame plate and connected to the second base of the third hinge structure.

15. The foldable device of claim 9, wherein the hinge structure further comprises: a second synchronizing mechanism connected between the third rotating member and the fourth rotating member, wherein the second synchronizing mechanism leads the third rotating member and the fourth rotating member to rotate synchronically towards each other or away from each other.

16. The foldable device of claim 15, wherein the second synchronization mechanism comprises: a third link, wherein an end of the third link is hinged to the third rotating member, and another end of the third link is hinged to the fourth rotating member.

17. The foldable device of claim 16, wherein the second synchronizing mechanism further comprises: a third eccentric shaft provided on the third rotating member and paralleled axially to a rotating center of the third rotating member rotating about the second base; and a fourth eccentric shaft provided on the fourth rotating member and paralleled axially to a rotating center of the fourth

rotating member rotating about the second base; wherein an end of the third link is hinged to the third eccentric shaft, and another end of the third link is hinged to the fourth eccentric shaft.

18. A display device, comprising: a foldable device; and a display panel; wherein the foldable device comprises: a frame plate; one primary folding axis; at least one secondary folding axis, wherein the at least one secondary folding axis intersects the primary folding axis to divide the frame plate into a plurality of sub-frame plates; and a folding mechanism including a first folding hinge and a second folding hinge; wherein at least one pair of adjacent sub-frame plates located on the primary folding axis are connected by the first folding hinge, at least one pair of adjacent sub-frame plates located on the at least one secondary folding axis are connected by the second folding hinge, and any one of the sub-frame plates is connected to at least one of the first folding hinge or the second folding hinge; wherein the display panel is disposed on a side of the frame plate of the foldable device; wherein each of the first folding hinge and the second folding hinge comprises: a first rotating member; a second rotating member; and a first base, wherein an end of the first rotating member is rotatably connected to the first base, and an end of the second rotating member is rotatably connected to the first base; wherein a side of another end of the first rotating member of the first folding hinge is connected to one of the at least one pair of adjacent sub-frame plates located on the primary folding axis, and a side of another end of the second rotating member of the first folding hinge is connected to another of the at least one pair of adjacent sub-frame plates located on the primary folding axis; wherein a side of another end of the first rotating member of the second folding hinge is connected to one of the at least one pair of adjacent sub-frame plates located on the at least one secondary folding axis, and a side of another end of the second rotating member of the second folding hinge is connected to another of the at least one pair of adjacent sub-frame plates located on the at least one secondary folding axis; wherein the folding mechanism further comprises: a hinge structure including a third rotating member, a fourth rotating member, and a second base, wherein an end of the third rotating member is rotatably connected to the second base, and an end of the fourth rotating member is rotatably connected to the second base; wherein the at least one pair of adjacent sub-frame plates located on the primary folding axis are connected by a first hinge structure, wherein a side of another end of the third rotating member of the first hinge structure is connected to one of the at least one pair of adjacent sub-frame plates located on the primary folding axis, and a side of another end of the fourth rotating member of the first hinge structure is connected to another of the at least one pair of adjacent sub-frame plates located on the primary folding axis.

19. The display device of claim 18, wherein the at least one pair of adjacent sub-frame plates located on the at least one secondary folding axis are connected by a second hinge structure, wherein a side of another end of the third rotating member of the second hinge structure is connected to one of the at least one pair of adjacent sub-frame plates located on the secondary folding axis, and a side of another end of the fourth rotating member of the second hinge structure is connected to another of the at least one pair of adjacent sub-frame plates located on the secondary folding axis.

20. The display device of claim 19, wherein the at least one pair of adjacent sub-frame plates located on the at least one secondary folding axis are connected to the second folding hinge by the second hinge structure.
