

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12407894
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Duffy; Gavin K. et al.

Digital assistant for providing graphical overlays of video events

Abstract

An example process includes while displaying, on a display, a video event: receiving, by a digital assistant, a natural language speech input corresponding to a participant of the video event; in accordance with receiving the natural language speech input, identifying, by the digital assistant, based on context information associated with the video event, a first location of the participant; and in accordance with identifying the first location of the participant, augmenting, by the digital assistant, the display of the video event with a graphical overlay displayed at a first display location corresponding to the first location of the participant.

Inventors: Duffy; Gavin K. (Los Gatos, CA), Macharia; Raymond M. (San Francisco, CA), Peck Brown; Jessica J. (Morgan Hill, CA), Schulman; Robert M. (Los Gatos, CA)

Applicant: Apple Inc. (Cupertino, CA)

Family ID: 83598700

Assignee: Apple Inc. (Cupertino, CA)

Appl. No.: 18/587689

Filed: February 26, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240205489 A1	Jun. 20, 2024

Related U.S. Application Data

continuation parent-doc WO PCT/US2022/041912 20220829 PENDING child-doc US 18587689
us-provisional-application US 63239290 20210831

Publication Classification

Int. Cl.: H04N21/431 (20110101); G06F3/01 (20060101); G06F3/14 (20060101); G06F3/16 (20060101); G10L15/18 (20130101)

U.S. Cl.:

CPC H04N21/4312 (20130101); G06F3/013 (20130101); G06F3/017 (20130101); G06F3/1431 (20130101); G06F3/167 (20130101); G10L15/1822 (20130101);

Field of Classification Search

CPC: H04N (21/4312); G06F (3/013); G06F (3/017); G06F (3/1431); G06F (3/167); G10L (15/1822); G06V (20/20); G06V (20/42); G06V (20/63); G06V (40/18)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8056099	12/2010	Shanks et al.	N/A	N/A
8358907	12/2012	Inagaki et al.	N/A	N/A
8606090	12/2012	Eyer	N/A	N/A
9250703	12/2015	Hernandez-Abrego et al.	N/A	N/A
9298986	12/2015	Ferlatte et al.	N/A	N/A
9338493	12/2015	Van Os et al.	N/A	N/A
9858925	12/2017	Gruber et al.	N/A	N/A
10317992	12/2018	Prokofieva et al.	N/A	N/A
10331312	12/2018	Napolitano et al.	N/A	N/A
10475446	12/2018	Gruber et al.	N/A	N/A
10659851	12/2019	Lister et al.	N/A	N/A
10726631	12/2019	Ha	N/A	N/A
10732708	12/2019	Roche et al.	N/A	N/A
10832031	12/2019	Kienzle et al.	N/A	N/A
11507183	12/2021	Manjunath et al.	N/A	N/A
11755275	12/2022	Lovitt	N/A	N/A
12045288	12/2023	Barut	N/A	G06F 16/532
2002/0166123	12/2001	Schrader et al.	N/A	N/A
2010/0318357	12/2009	Istvan et al.	N/A	N/A
2011/0289530	12/2010	Dureau et al.	N/A	N/A
2012/0162540	12/2011	Ouchi et al.	N/A	N/A
2012/0265528	12/2011	Gruber et al.	N/A	N/A
2013/0339991	12/2012	Ricci	N/A	N/A
2014/0053198	12/2013	Sirpal et al.	N/A	N/A
2014/0081633	12/2013	Badaskar	N/A	N/A
2014/0181865	12/2013	Koganei	N/A	N/A
2014/0237366	12/2013	Poulos et al.	N/A	N/A
2015/0382047	12/2014	Van Os et al.	N/A	N/A

2016/0212488	12/2015	Van Os et al.	N/A	N/A
2016/0378861	12/2015	Eledath	707/766	G06V 20/52
2017/0068423	12/2016	Napolitano et al.	N/A	N/A
2017/0068670	12/2016	Orr et al.	N/A	N/A
2017/0230709	12/2016	Van Os et al.	N/A	N/A
2017/0235361	12/2016	Rigazio et al.	N/A	N/A
2017/0285915	12/2016	Napolitano et al.	N/A	N/A
2019/0259386	12/2018	Kudurshian et al.	N/A	N/A
2019/0310765	12/2018	Napolitano et al.	N/A	N/A
2019/0362557	12/2018	Lacey et al.	N/A	N/A
2019/0371327	12/2018	Quinn	N/A	G10L 15/16
2019/0391726	12/2018	Iskandar et al.	N/A	N/A
2020/0105260	12/2019	Piernot et al.	N/A	N/A
2020/0218074	12/2019	Hoover et al.	N/A	N/A
2020/0226823	12/2019	Stachniak et al.	N/A	N/A
2021/0105528	12/2020	Van Os et al.	N/A	N/A
2021/0191603	12/2020	Napolitano et al.	N/A	N/A
2021/0191968	12/2020	Orr et al.	N/A	N/A
2023/0066552	12/2022	Van Os et al.	N/A	N/A
2024/0192917	12/2023	Duffy et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102857808	12/2012	CN	N/A
104584010	12/2014	CN	N/A
106462617	12/2016	CN	N/A
2014-126600	12/2013	JP	N/A
2015-527683	12/2014	JP	N/A
10-2015-0038375	12/2014	KR	N/A
10-2017-0036805	12/2016	KR	N/A
2014/047047	12/2013	WO	N/A
2016/049439	12/2015	WO	N/A
2017/044257	12/2016	WO	N/A

OTHER PUBLICATIONS

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2022/041927, mailed on Mar. 14, 2024, 11 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2022/041927, mailed on Dec. 22, 2022, 16 pages. cited by applicant

“Second Spectrum”, Available online at: <https://www.secondspectrum.com/video.html>, Retrieved on Nov. 4, 2024, 5 pages. cited by applicant

Lu et al., “Learning to Track and Identify Players from Broadcast Sports Videos”, Available online at: <https://www.cs.ubc.ca/~murphyk/Papers/weilwun-pami12.pdf>, Retrieved on Nov. 4, 2024, pp. 1-13. cited by applicant

102857808, CN, A, Cited by the Chinese Patent Office in an Office Action for related Patent Application No. 202110024848.8 on Feb. 29, 2024. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2022/041912, mailed on Mar. 14, 2024, 7 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2022/041912, mailed on Dec. 22, 2022, 10 pages. cited by applicant

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of PCT Application No. PCT/US2022/041912, entitled “DIGITAL ASSISTANT FOR PROVIDING GRAPHICAL OVERLAYS OF VIDEO EVENTS,” filed on Aug. 29, 2022, which claims priority to U.S. Patent Application No. 63/239,290, entitled “DIGITAL ASSISTANT FOR PROVIDING GRAPHICAL OVERLAYS OF VIDEO EVENTS,” filed on Aug. 31, 2021. The entire contents of each of these applications are hereby incorporated by reference in their entireties.

FIELD

(1) This relates to using digital assistants to augment the display of video events with graphical overlays.

BACKGROUND

(2) Digital assistants allow users to interact with electronic devices via natural language input. For example, after a user provides a spoken request to a digital assistant implemented on an electronic device, the digital assistant can determine a user intent corresponding to the spoken request. The digital assistant can then cause the electronic device to perform one or more task(s) to satisfy the user intent and to provide output(s) indicative of the performed task(s).

SUMMARY

(3) Example methods are disclosed herein. An example method includes at an electronic device having one or more processors, memory, and a display: while displaying, on the display, a video event: receiving, by a digital assistant operating on the electronic device, a natural language speech input corresponding to a participant of the video event; in accordance with receiving the natural language speech input, identifying, by the digital assistant, based on context information associated with the video event, a first location of the participant; and in accordance with identifying the first location of the participant, augmenting, by the digital assistant, the display of the video event with a graphical overlay displayed at a first display location corresponding to the first location of the participant.

(4) Example non-transitory computer-readable media are disclosed herein. An example non-transitory computer-readable storage medium stores one or more programs. The one or more programs comprise instructions, which when executed by one or more processors of an electronic device having a display, cause the electronic device to: while displaying, on the display, a video event: receive, by a digital assistant operating on the electronic device, a natural language speech input corresponding to a participant of the video event; in accordance with receiving the natural language speech input, identify, by the digital assistant, based on context information associated with the video event, a first location of the participant; and in accordance with identifying the first location of the participant, augment, by the digital assistant, the display of the video event with a graphical overlay displayed at a first display location corresponding to the first location of the participant.

(5) Example electronic devices are disclosed herein. An example electronic device comprises a display; one or more processors; a memory; and one or more programs, where the one or more programs are stored in the memory and configured to be executed by the one or more processors, the one or more programs including instructions for: while displaying, on the display, a video event: receiving, by a digital assistant operating on the electronic device, a natural language speech input corresponding to a participant of the video event; in accordance with receiving the natural

language speech input, identifying, by the digital assistant, based on context information associated with the video event, a first location of the participant; and in accordance with identifying the first location of the participant, augmenting, by the digital assistant, the display of the video event with a graphical overlay displayed at a first display location corresponding to the first location of the participant.

(6) Augmenting the displays of video events with graphical overlays according to the techniques discussed herein allows digital assistants to efficiently and intelligently provide relevant graphical responses to user requests about the video event. For example, responsive to a natural language request received during display of a live sports game, the digital assistant can augment the display of the live sports game with one or more graphical overlays including information relevant to the user request. Automatically augmenting the display of video events without requiring further user input (e.g., after receiving the natural language input) makes the user-device interface more efficient (e.g., by reducing user inputs otherwise required to satisfy user requests about the video event, by helping users to understand information in the context of the displayed video event), which additionally, reduces power usage and improves device battery life by enabling quicker and more efficient device usage.

Description

BRIEF DESCRIPTION OF FIGURES

- (1) FIGS. 1A-1B depict exemplary systems for use in various extended reality technologies.
- (2) FIG. 2 illustrates a block diagram of a digital assistant, according to various examples.
- (3) FIGS. 3A-3H illustrate various manners of augmenting the display of video events with graphical overlays, according to various examples.
- (4) FIG. 4 illustrates a process for augmenting the display of a video event with a graphical overlay, according to various examples.

DESCRIPTION

- (5) Examples of systems and techniques for implementing extended reality (XR) based technologies are described herein.
- (6) FIG. 1A and FIG. 1B depict exemplary system **150** used to implement various extended reality technologies.
- (7) In the example of FIG. 1A, system **150** includes device **150a**. Device **150a** includes at least some of: processor(s) **101**, memory(ies) **102**, RF circuitry(ies) **103**, display(s) **104**, image sensor(s) **105**, touch-sensitive surface(s) **106**, location sensor(s) **107**, microphone(s) **108**, speaker(s) **109**, and orientation sensor(s) **110**. Communication bus(es) **111** of device **150a** optionally enable communication between the various components of device **150a**.
- (8) In some examples, some components of system **150** are implemented in a base station device (e.g., a computing device such as a laptop, remote server, or mobile device) and other components of system **150** are implemented in a second device (e.g., a head-mounted device). In some examples, the base station device or the second device implements device **150a**.
- (9) In the example of FIG. 1B, system **150** includes at least two devices in communication, e.g., via a wired connection or a wireless connection. First device **150c** (e.g., a head-mounted device) includes at least some of: processor(s) **101**, memory(ies) **102**, RF circuitry(ies) **103**, display(s) **104**, image sensor(s) **105**, touch-sensitive surface(s) **106**, location sensor(s) **107**, microphone(s) **108**, speaker(s) **109**, and orientation sensor(s) **110**. Communication bus(es) **111** of first device **150c** optionally enable communication between the components of first device **150c**. Second device **150b**, such as a base station device, includes processor(s) **101**, memory(ies) **102**, and RF circuitry(ies) **103**. Communication bus(es) **111** of second device **150b** optionally enable communication between the components of second device **150b**.

(10) Processor(s) **101** include, for instance, graphics processor(s), general processor(s), and/or digital signal processor(s).

(11) Memory(ies) **102** are one or more non-transitory computer-readable storage mediums (e.g., flash memory, random access memory) storing computer-readable instructions. The computer-readable instructions, when executed by processor(s) **101**, cause system **150** to perform various techniques discussed below.

(12) RF circuitry(ies) **103** include, for instance, circuitry to enable communication with other electronic devices and/or with networks (e.g., intranets, the Internet, wireless networks (e.g., local area networks and cellular networks)). In some examples, RF circuitry(ies) **103** include circuitry enabling short-range and/or near-field communication.

(13) In some examples, display(s) **104** implement a transparent or semi-transparent display. Accordingly, a user can view a physical setting directly through the display and system **150** can superimpose virtual content over the physical setting to augment the user's field of view. In some examples, display(s) **104** implement an opaque display. In some examples, display(s) **104** transition between a transparent or semi-transparent state and an opaque state.

(14) In some examples, display(s) **104** implement technologies such as liquid crystal on silicon, a digital light projector, LEDs, OLEDs, and/or a laser scanning light source. In some examples, display(s) **104** include substrates (e.g., light waveguides, optical reflectors and combiners, holographic substrates, or combinations thereof) through which light is transmitted. Alternative example implementations of display(s) **104** include display-capable automotive windshields, display-capable windows, display-capable lenses, heads up displays, smartphones, desktop computers, or laptop computers. As another example implementation, system **150** is configured to interface with an external display (e.g., smartphone display). In some examples, system **150** is a projection-based system. For example, system **150** projects images onto the eyes (e.g., retina) of a user or projects virtual elements onto a physical setting, e.g., by projecting a holograph onto a physical setting or by projecting imagery onto a physical surface.

(15) In some examples, image sensor(s) **105** include depth sensor(s) for determining the distance between physical elements and system **150**. In some examples, image sensor(s) **105** include visible light image sensor(s) (e.g., charged coupled device (CCD) sensors and/or complementary metal-oxide-semiconductor (CMOS) sensors) for obtaining imagery of physical elements from a physical setting. In some examples, image sensor(s) **105** include event camera(s) for capturing movement of physical elements in the physical setting. In some examples, system **150** uses depth sensor(s), visible light image sensor(s), and event camera(s) in conjunction to detect the physical setting around system **150**. In some examples, image sensor(s) **105** also include infrared (IR) sensor(s) (e.g., passive or active IR sensors) to detect infrared light from the physical setting. An active IR sensor implements an IR emitter (e.g., an IR dot emitter) configured to emit infrared light into the physical setting.

(16) In some examples, image sensor(s) **105** are used to receive user inputs, e.g., hand gesture inputs. In some examples, image sensor(s) **105** are used to determine the position and orientation of system **150** and/or display(s) **104** in the physical setting. For instance, image sensor(s) **105** are used to track the position and orientation of system **150** relative to stationary element(s) of the physical setting. In some examples, image sensor(s) **105** include two different image sensor(s). A first image sensor is configured to capture imagery of the physical setting from a first perspective and a second image sensor is configured to capture imagery of the physical setting from a second perspective different from the first perspective.

(17) Touch-sensitive surface(s) **106** are configured to receive user inputs, e.g., tap and/or swipe inputs. In some examples, display(s) **104** and touch-sensitive surface(s) **106** are combined to form touch-sensitive display(s).

(18) In some examples, microphone(s) **108** are used to detect sound emanating from the user and/or from the physical setting. In some examples, microphone(s) **108** include a microphone array (e.g., a

plurality of microphones) operating in conjunction, e.g., for localizing the source of sound in the physical setting or for identifying ambient noise.

(19) Orientation sensor(s) **110** are configured to detect orientation and/or movement of system **150** and/or display(s) **104**. For example, system **150** uses orientation sensor(s) **110** to track the change in the position and/or orientation of system **150** and/or display(s) **104**, e.g., relative to physical elements in the physical setting. In some examples, orientation sensor(s) **110** include gyroscope(s) and/or accelerometer(s).

(20) FIG. 2 illustrates a block diagram of digital assistant (DA) **200**, according to various examples.

(21) The example of FIG. 2 shows that DA **200** is implemented, at least partially, within system **150**, e.g., within device **150a**, **150b**, or **150c**. For example, DA **200** is at least partially implemented as computer-executable instructions stored in memory(ies) **102**. In some examples, DA **200** is implemented in a distributed manner, e.g., distributed across multiple computing systems. For example, the components and functions of DA **200** are divided into a client portion and a server portion. The client portion is implemented on one or more user devices (e.g., devices **150a**, **150b**, **150c**) and may communicate with a computing server via one or more networks. The components and functions of DA **200** are implemented in hardware, software instructions for execution by one or more processors, firmware (e.g., one or more signal processing and/or application specific integrated circuits), or a combination or sub-combination thereof. It will be appreciated that DA **200** is exemplary, and thus DA **200** can have more or fewer components than shown, can combine two or more components, or can have a different configuration or arrangement of the components.

(22) As described below, DA **200** performs at least some of: automatic speech recognition (e.g., using speech to text (STT) module **202**); determining a user intent corresponding to received natural language input; determining a task flow to satisfy the determined intent; and executing the task flow to satisfy the determined intent.

(23) In some examples, DA **200** includes natural language processing (NLP) module **204** configured to determine the user intent. NLP module **204** receives candidate text representation(s) generated by STT module **202** and maps each of the candidate text representations to a “user intent” recognized by the DA. A “user intent” corresponds to a DA performable task and has an associated task flow implemented in task module **206**. The associated task flow includes a series of programmed actions (e.g., executable instructions) the DA takes to perform the task. The scope of DA **200**'s capabilities can thus depend on the types of task flows implemented in task module **206**, e.g., depend on the types of user intents the DA recognizes.

(24) In some examples, upon identifying a user intent based on the natural language input, NLP module **204** causes task module **206** to perform the actions for satisfying the user request. For example, task module **206** executes the task flow corresponding to the determined intent to perform a task satisfying the user request. In some examples, executing a task flow includes employing the services of identification module **208** and display augmentation module **210**, discussed below, to perform the task. In some examples, performing the task includes causing system **150** to provide graphical, audio, and/or haptic output indicating the performed task.

(25) In some examples, DA **200** includes identification module **208**. Identification module **208** is configured to perform various identification actions based on instructions from task module **206**, e.g., based on instructions generated by executing a task flow. For example, identification module **208** is configured to identify participants (e.g., players or persons) in video events, identify the participants' displayed locations, and track the participants' movements. Example video events include broadcasts/videos of sports games/competitions, videos of performances (e.g., concerts and shows), television broadcasts, movies, and the like.

(26) In some examples, as discussed below with respect to FIGS. 3A-3H, identification module **208** implements computer vision techniques (e.g., image recognition, facial and/or body recognition, image tracking) to perform the identification actions. For example, identification module **208** is

configured to identify a participant referred to by the natural language input “who is that?” and track the identified participant's movement in a video event. In some examples, identification module **208** implements probabilistic techniques (e.g., machine-learning techniques) to identify participants. For example, identification module **208** determines and/or adjusts likelihood scores of candidate participants and identifies the candidate participant having the highest likelihood score and/or having a likelihood score above a threshold. The likelihood scores of candidate participants are based on various context information, detailed below, associated with the video event (e.g., whether an audio stream of the video event names a candidate participant, the frequency with which the user gazes at a candidate participant, the degree of match between a candidate participant's identified visual features and known information about participants in the video event (e.g., jersey numbers, jersey design, facial and/or bodily features), a confidence associated with facial and/or body recognition of the candidate participant).

(27) In some examples, as discussed below with respect to FIGS. **3A-3H**, identification module **208** implements gaze tracking techniques (e.g., on user gaze data detected by image sensor(s) **105**) to identify the locations of participants. For example, identification module **208** identifies a current (or previous) user gaze location and identifies a participant displayed at or near the current (or previous) user gaze location. In some examples, identification module **208** identifies the locations of participants based on user gesture inputs (e.g., tap gestures or pointing gestures detected by image sensor(s) **105**, display(s) **104**, and/or touch-sensitive surfaces(s) **106**). For example, identification module **208** identifies a display location corresponding to user gesture input (e.g., where the user points at) and identifies a participant displayed at or near the display location.

(28) In some examples, DA **200** includes display augmentation module **210**. In conjunction with task module **206** and identification module **208**, display augmentation module **210** is configured to cause system **150** (e.g., device **150a** or **150c**) to augment the display of video events. For example, display augmentation module **210** generates a graphical overlay and causes system **150** to augment the display of a video event with the graphical overlay. As one example, responsive to a user asking DA **200** “who is that?” during display of a live sports game, identification module **208** identifies the intended participant. Display augmentation module **210** then causes system **150** to augment the display of the live sports game with a graphical overlay identifying the participant, e.g., where the graphical overlay would not otherwise be displayed in the live sports game.

(29) In some examples, display augmentation module **208** generates different types of graphical overlays and augments the display of video events in different manners based on instructions from task module **206**. For example, by executing a particular task flow corresponding to a particular user intent, task module **206** causes display augmentation module **208** to generate a type of graphical overlay corresponding to the particular user intent. Various types of graphical overlays and the various manners in which DA **200** can augment the display of video events with the graphical overlays are now discussed with respect to FIGS. **3A-3H**.

(30) FIGS. **3A-3H** illustrate various manners of augmenting the display of video events with graphical overlays, according to various examples. FIGS. **3A-3H** show display **302** of device **300**, e.g., a head mounted device. Device **300** is implemented as device **150a** or device **150c**. Display **302** displays a video event, e.g., a live soccer game.

(31) In some examples, the video event is displayed via video pass-through depicting a display of an external electronic device. Accordingly, display **302** and the display of the external electronic device concurrently display the video event. For example, in FIG. **3A**, while the external device (e.g., a television, a computer, or a tablet) displays the soccer game, display **302** concurrently displays the soccer game via video pass-through of the external device. In other examples, the video event is not displayed via video-pass through. For example, device **300** streams the video event via an internet connection or displays the video event that is stored in local memory of device **300**.

(32) In some examples, while display **302** displays the video event, device **300** receives input to

invoke DA 200. Example input to invoke DA 200 includes speech input including a predetermined spoken trigger (e.g., “hey assistant,” “turn on,” and the like), predetermined types of gesture input (e.g., hand motions) detected by device 300, and selection of a physical or virtual button of device 300. In some examples, input to invoke DA 200 includes user gaze input, e.g., indicating that user gaze is directed to a particular displayed user interface element for a predetermined duration. In some examples, device 300 determines that user gaze input is input to invoke DA 200 based on the timing of received natural language input relative to the user gaze input. For example, user gaze input invokes DA 200 if device 300 determines that user gaze is directed to the user interface element at a start time of the natural language input and/or at an end time of the natural language input. In the example of FIG. 3A, a user provides the spoken trigger “hey assistant” to invoke DA 200.

(33) In FIG. 3A, DA 200 invokes. For example, device 300 displays DA indicator 304 to indicate invoked DA 200 and begins to execute certain processes corresponding to DA 200. In some examples, once DA 200 invokes, DA 200 processes received natural language input to augment the display of the video event with various types of graphical overlays, discussed below. For simplicity, the description of FIGS. 3C-3H below does not explicitly describe receiving input to invoke DA 200. However, it will be appreciated that, in some examples, DA 200 processes the natural language inputs described with respect to FIGS. 3C-3H in accordance with receiving input to invoke DA 200.

(34) In some examples, a user provides a natural language input to DA 200 (and causes DA 200 to process the natural language input) without providing input to invoke DA 200. For example, DA 200 determines, based on various conditions associated with the natural language input, that the natural language input is intended for DA 200 and thus processes the natural language input. For example, a condition includes that a user gesture corresponds to (e.g., the user points or gestures at) a location on display 302 when receiving the natural language input. Thus, if DA 200 determines that a user gesture corresponds to a location on display 302 when receiving the natural language input, DA 200 processes the natural language input without requiring input to invoke DA 200. As another example, a condition includes that the natural language input corresponds to a user intent associated with the video event. For example, DA 200 processes received natural language inputs to determine whether they correspond to predetermined types of user intents (e.g., an intent to identify a participant in the video event, an intent to pause, rewind, and/or fast-forward the video event, an intent to request further information about the video event, an intent to locate a participant in the video event). If DA 200 determines that a natural language input corresponds to a user intent associated with the video event, DA 200 processes the natural language input to display a graphical overlay without requiring input to invoke DA 200.

(35) In FIG. 3A, while display 302 displays the video event, DA 200 receives a natural language input corresponding to participant 306 of the video event. Participants of video events includes players and other entities involved in the video event, e.g., coaches, referees, linesmen, spectators, actors, actresses, animated characters, and the like. In some examples, the natural language input does not explicitly specify participant 306 but includes a deictic reference to participant 306, e.g., “that,” “he,” “she,” “they,” and the like. For example, after being invoked, DA 200 receives the natural language input “who is that?”. The natural language input includes a request to identify participant 306, e.g., a player in the soccer game. As discussed below, responsive to the natural language input, DA 200 identifies location 308 of participant 306, uses identified location 308 to resolve the deictic reference (e.g., identify the player corresponding to “that”), and displays graphical overlay 310 indicating identified participant 306.

(36) In accordance with receiving the natural language input, DA 200 identifies location 308 (e.g., a displayed location) of participant 306. DA 200 identifies location 308 based on context information associated with the video event, discussed below. In some examples, DA 200 further determines that a user intent corresponding to the natural language input is to identify participant

306 and identifies participant **306** in accordance with determining the user intent.

(37) In some examples, device **300** detects user gaze data and the context information includes the detected user gaze data. The user gaze data includes, for instance, data captured by image sensor(s) **105**, e.g., data captured by camera(s) of device **300** configured to track a user's gaze. In some examples, the user gaze data includes data captured by orientation sensor(s) **110** (e.g., data indicating a user's head pose) that DA **200** can use to determine a user's gaze location. In some examples, the gaze data indicates where (e.g., on display **302**) the user gazes over time, e.g., indicates that the user gazes at a particular location at a particular time.

(38) In some examples, identifying location **308** of participant **306** includes determining, based on the user gaze data, that a user gaze is directed to location **308** of participant **306**. In some examples, the timing of the user gaze data used to identify location **308** depends on the tense of the natural language input. For example, if a natural language input refers to participant **306** in the present tense (e.g., “who is that?”) user gaze is currently directed to participant **306**'s location, e.g., directed to participant **306**'s location while DA **200** receives at least a portion of the natural language input. In contrast, if a natural language input refers to participant **306** in the past tense (e.g., “who was that?”), the user's previous gaze (e.g., gaze before receiving the natural language input) may have been directed to a previous displayed location of participant **306**. FIGS. 3C-3D below describe techniques for handling natural language inputs that refer to participants in the past tense.

(39) In the example of FIG. 3A, DA **200** determines that the natural language input “who is that?” refers to participant **306** in the present tense. For example, NLP module **204** performs a grammatical and/or syntactic analysis of the natural language input to determine the tense. In some examples, in accordance with a determination that the natural language input refers to participant **306** in the present tense, DA **200** identifies location **308** of participant **306** as the location at which user gaze is directed at a current time. In some examples, the current time (e.g., of the video event) corresponds to a start time of the language natural input, to when DA **200** is invoked, or to a current timestamp of the displayed video event. For example, in FIG. 3A, DA **200** identifies location **308** of participant **306** by determining that user gaze is directed to location **308** when the user starts to speak “who is that?”.

(40) Sometimes, the time when a user gazes at participant **306** does not exactly match the current time. For example, the user may gaze at participant **306** slightly before and/or slightly after speaking “who is that?”. Accordingly, in some examples, in accordance with a determination that the natural language input refers to participant **306** in the present tense, DA **200** analyzes user gaze data within a predetermined time window around the current time to identify location **308**. The analyzed user gaze data includes, for instance, buffered gaze data (e.g., detected before the current time), gaze data detected while receiving the natural language input, and/or gaze data detected after an end time of the natural language input. In some examples, DA **200** analyzes the user gaze data using a prediction model (e.g., a machine-learned model implemented in identification module **208**) to identify location **308**. For example, the prediction model analyzes the user gaze data concurrently with the corresponding display of the video event to identify the time(s) when user gaze is directed to a displayed entity (e.g., a human participant) and the corresponding gazed-at location(s) (e.g., location **308**) of the entity. In some examples, the training data for the prediction model includes user gaze data and a corresponding display of a video event. In some examples, the training data is annotated to indicate when a user gazes at an entity and the corresponding displayed location of the entity.

(41) In some examples, device **300** detects user gesture input and the context information includes the detected user gesture input. Accordingly, in some examples, identifying location **308** of participant **306** includes determining that the user gesture input (e.g., representing a tap or pointing gesture) corresponds to location **308**. For example, DA **200** determines that the gesture input corresponds to location **308** at a particular time, e.g., the current time, while receiving any portion of the natural language input, within a predetermined duration before receiving the natural

language input, and/or within a predetermined duration after receiving the natural language input. In some examples, DA **200** determines that the gesture input corresponds to location **308** at the particular time in accordance with determining that the natural language input refers to participant **306** in the present tense. In this manner, DA **200** can identify location **308** by determining that the user points at location **308** when starting to speak “who is that?”.

(42) In some examples, DA **200** further analyzes the display of the video event at identified location **308** using context information to identify participant **306**. The context information includes, for instance, information corresponding to opposing parties (e.g., opposing teams, opposing participants) of the video event. The information corresponding to opposing parties includes, for instance, respective jersey numbers of the participants of the opposing parties, respective identities corresponding to the jersey numbers, and/or respective jersey designs (e.g., colors, patterns, other visual characteristics) of the opposing parties. For example, for the currently displayed soccer game, DA **200** accesses the jersey colors of the opposing teams and rosters of both teams indicating the player identities and corresponding jersey numbers. In some examples, the context information includes information corresponding to any participant of the video event, e.g., information indicating the participant's costume, outfit, and/or jersey number. For example, for a doubles tennis or doubles volleyball match, the context information indicates the respective outfits (e.g., outfit color, outfit style) of each participant. As another example, for a concert, the context information indicates the respective costumes of each musician in the concert, e.g., if each musician has a signature performance costume.

(43) In some examples, the context information includes an audio stream of the video event. For example, the audio stream includes commentary of the video event. In some examples, the context information includes an annotated event stream of the video event. For example, the annotated event stream represents a timeline of the video event indicating the times of notable moments (e.g., start time, fouls, goals, substitutions, touchdowns, steals, time outs, a new play, records, kickoff, half time, overtime, a notable athlete appearing, a decided winner, dribbles (in soccer), ball interceptions, and the like) in the video event and optionally, the participant(s) corresponding to the notable moments. In some examples, DA **200** receives the annotated event stream from an external service, e.g., from a service that analyzes live events in real-time to generate the annotated event stream. In some examples, the context information includes data representing facial and/or bodily features of participants in the video event, e.g., data enabling DA **200** to identify the participants using facial and/or body recognition.

(44) In some examples, the context information further indicates respective role(s) of participant(s) in the video event. For example, for a soccer game, the context information indicates whether each player is a goalie, a midfielder, a forward, or a defender. As another example, for a baseball game, the context information indicates the participant who is the pitcher, the catcher, or the like. As another example, for a concert, the context information indicates the participant (e.g., of a band) who is the lead singer, the drummer, the keyboard player, the guitarist, or the like. In some examples, the context information indicates the popularity (e.g., as determined from social media data) of at least some of the participants of the video event. For example, the context information indicates the player who is most popular on their soccer team, e.g., based on having the largest social media following. In some examples, the popularity is represented by a ranking (e.g., relative to the participant's team or to all participants in the video event) and/or a numerical score, e.g., based on the participant's number of social media followers.

(45) In FIG. **3A**, DA **200** analyzes the display of the video event at location **308**, and at the current time (or when user gaze at location **308** is otherwise detected), to identify participant **306**. For example, DA **200** performs image recognition of the video event (e.g., a still frame of the video event) at the current time and around location **308** to identify an entity (e.g., person) at or near location **308**. For example, the image recognition process implements a search process to identify the pixels in the vicinity of location **308** that form an entity. The image recognition thus identifies

that an entity is at or near location **308** and further identifies visual features (e.g., jersey number, jersey design, facial and/or bodily features) of the entity. DA **200** matches the visual features to the above described context information to identify the entity as participant **306**. For example, DA **200** determines that the entity has jersey number **10** and the team roster indicates Lionel Messi has jersey number **10**, and thus identifies participant **306** as Lionel Messi.

(46) In some examples, the visual features identified by the image recognition indicate a role of the entity. For example, the image recognition can determine, based on the entity's visual characteristics and/or relative location in the video event, whether the entity is a goalie, a pitcher, a drummer, a guitarist, or the like. DA **200** can thus match the determined role of the entity to the context information (indicating the roles of the participants) to identify the entity as a particular participant. For example, if DA **200** determines that the entity is a drummer, DA **200** increases a likelihood score of the participant(s) of the video event who are drummers.

(47) In some examples, DA **200** additionally or alternatively identifies participant **306** using other techniques based on the context information. For example, DA **200** identifies participant **306** based on the audio stream of the video event. For example, DA **200** determines whether the audio stream of the video event, within a predetermined time window around the current time, includes the name of a participant. If so, DA **200** identifies participant **306** as the named participant or increases a likelihood of participant **306** being the named participant. In some examples, DA **200** identifies participant **306** based on an annotated event stream of the video event. For example, DA **200** analyzes the annotated event stream within a predetermined time window around the current time to determine whether the event stream indicates a participant. If so, DA **200** identifies participant **306** as the indicated participant or increases likelihood of participant **306** being the indicated participant. For example, users may more likely ask DA **200** to identify a participant if the participant is involved in a notable moment of the video event. If the participant is involved in the notable moment (e.g., scored a goal), the audio stream of the soccer game likely identifies the participant around the current time (e.g., "Goal for Lionel Messi!") and/or the event stream likely identifies the participant, e.g., by indicating a goal for Lionel Messi at a particular time.

(48) As another example, DA **200** identifies participant **306** based on the popularity of participant **306**, e.g., as indicated by the context data. For example, if two participants' respective likelihood scores are otherwise equal, DA **200** determines a higher likelihood score for the more popular participant. As another example, DA **200** assumes by default that participant **306** is the most popular participant, e.g., by increasing the most popular participant's likelihood score by a predetermined amount.

(49) In some examples, in accordance with identifying participant **306** (e.g., based on the audio stream and/or annotated event stream), DA **200** identifies current location **308** of participant **306**. For example, DA **200** performs image recognition on the video event at the current time to determine current location **308** based on participant **306**'s known features indicated by the context information (e.g., jersey design, jersey number, facial and/or bodily features).

(50) In accordance with identifying current location **308**, DA **200** augments the display of the video event with graphical overlay **310**. Graphical overlay **310** is displayed at a display location corresponding to current location **308**. For example, DA **200** selects a display location near (e.g., within a predetermined distance of) current location **308** that does not obscure the display of participant **306** with graphical overlay **310**.

(51) In some examples, DA **200** generates graphical overlays having different types and/or contents depending on the user intent corresponding to natural language input. For example, in FIG. 3A, because the natural language input "who is that?" includes a request to identify participant **306**, DA **200** generates graphical overlay **310** including information corresponding to participant **306**. The information indicates, for example, an identity of participant **306**, one or more predetermined highlights (e.g., notable moments) corresponding to participant **306** (e.g., text or video describing notable moments of participant **306** in the video event), and/or statistics (e.g., distance ran, goals

scored, passes completed, dribbles completed, tackles made, shots taken, and the like) corresponding to participant **306**. In some examples, graphical overlay **310** indicates additional information about participant **306**, such as a representation (e.g., picture or video) of participant **306**, a position (e.g., forward, defender, goalie, quarterback) of participant **306**, and/or general knowledge (e.g., an encyclopedia entry) about participant **306**. In some examples, graphical overlay **310** indicates information about the video event, e.g., statistics and scores of the displayed game, knowledge (e.g., encyclopedia entries) about the teams of the video event, text and/or video description of notable moments in the video event, user-selectable links to view respective videos of the notable moments, and/or rosters of the opposing teams. In some examples, graphical overlay **310** indicates current location **308** of participant **306**, e.g., includes a circle or other shape displayed under participant **306**.

(52) In some examples, device **300** receives a user input corresponding to a selection of graphical overlay **310**. Example user input includes gesture input (e.g., a tap gesture) and/or speech input (e.g., “show me more about Lionel Messi”). In response to receiving the user input, display **302** displays a user interface including more detailed information about participant **306**. For example, if the user selects graphical overlay **310** shown in FIG. 3A, display **302** displays a user interface providing more detail about Lionel Messi, e.g., Lionel Messi's statistics in the soccer game and/or text and/or video description of Lionel Messi's highlights in the soccer game.

(53) In some examples, DA **200** further generates and provides output (e.g., audio output) corresponding to graphical overlay **310**. The audio output indicates the identified participant. For example, DA **200** additionally outputs “that's Lionel Messi” while display **302** displays graphical overlay **310**. In some examples, if DA **200** cannot determine location **308** (e.g., did not detect user gaze data or was unable to identify a user gaze location) and/or cannot identify participant **306** (e.g., image recognition cannot confidently identify participant **306**), DA **200** provides an output indicating an error, e.g., “sorry, I don't know who that is.”

(54) While the above describes an example of augmenting the display of a sports game with a graphical overlay, DA **200** can augment the display of other types of video events with graphical overlays in a similar manner. As one example, the video event is a concert and the user may request DA **200** to identify a participant (e.g., a lead singer, a guitarist, a drummer) of the concert. DA **200** can identify the participant as discussed herein and display a graphical overlay at or near the identified participant's location. The graphical overlay includes, for example, general knowledge about the participant and/or a list of the participant's music albums or songs. As another example, the video event is a personal video (e.g., a home video recorded by a user's personal device) and the user can request DA **200** to identify a participant shown in the personal video. DA **200** can identify the participant as discussed herein (e.g., using facial and/or body recognition) and display a graphical overlay indicating the identity of the participant. As yet another example, the video event is a movie or news broadcast and the user can request DA **200** to identify a participant (e.g., news anchor, reporter, politician, actor, actress) of the movie or news broadcast. Further, the techniques discussed herein can apply to identifying participants depicted in a user's personal photos. For example, while viewing a photo, the user can ask DA **200** “who is that?”. If DA **200** can confidently identify the referred-to participant (e.g., based on facial recognition and the user's gaze), DA **200** displays a graphical overlay indicating the participant's identity.

(55) As discussed, DA **200** may augment the display of video events with other types of graphical overlays depending on the user intent corresponding to the natural language input. As a further example, suppose the video event is a concert and the user intent is to obtain further information about the concert, e.g., via natural language inputs such as “tell me about this show,” “tell me about this tour,” or “show me the song list.” DA **200** can retrieve the requested information and augment the display of the concert with a graphical overlay indicating the requested information, e.g., general information about the concert, a list of stops on the tour, the song list for the concert. As another example, the user intent is to visualize the audio of the concert, e.g., via natural language

inputs such as “visualize this song,” “show me the chords,” or “show me the lyrics.” DA 200 can analyze the audio stream of the concert (e.g., to determine a corresponding waveform, to determine the chords being played, to recognize the current lyrics) and display a graphical overlay corresponding to the user intent, e.g., a live updated graphical overlay showing the waveform, showing the currently played chords, or showing the currently recognized lyrics.

(56) Turning to FIG. 3B, in some examples, graphical overlay 310 follows a location of participant 306. For example, DA 200 detects a change from location 308 of participant 306 to location 312 of participant 306, e.g., as Lionel Messi runs forward with the ball in the live soccer game. In some examples, DA 200 detects the change by analyzing the video event using image tracking technologies, e.g., by tracking the movement of participant 306 using participant 306's previously identified visual features. In response to detecting the change from location 308 to location 312, DA 200 displays, on display 302, graphical overlay 310 at an updated display location corresponding to location 312. In this manner, displays of graphical overlays can follow the displayed locations of the participants. In some examples, graphical overlay 310 follows the location for a predetermined time (e.g., 5 seconds or 10 seconds after initially displaying the graphical element) and then ceases to be displayed. In other examples, a user setting of device 300 defines the length for which to display graphical overlay 310. In other examples, display 302 displays graphical overlay 310 until ceasing to display the video event, or until device 300 receives user input instructing to cease display of graphical overlay 310.

(57) FIGS. 3C-3D illustrate techniques for handling natural language inputs in the past tense that include requests to identify participant 314. In FIG. 3C, DA 200 receives the natural language input “who was that?”. For example, participant 314 has just scored a goal in the soccer game and the user wants to know who scored the goal.

(58) In some examples, in accordance with receiving the natural language input, DA 200 determines that a user intent corresponding to the natural language input is to identify participant 314. In some examples, in accordance with such determination, DA 200 identifies, based on the context information, a location of participant 314. For example, DA 200 identifies the currently displayed location of participant 314 to determine where to display graphical overlay 318 identifying participant 314. As discussed below, identifying the currently displayed location of participant 314 may include first identifying participant 314, and then identifying the currently displayed location of participant 314.

(59) In some examples, DA 200 determines that the natural language input (e.g., “who was that?”) refers to participant 314 in the past tense. In accordance with a determination that the natural language speech input refers to participant 314 in the past tense, DA 200 determines previously displayed location(s) at which the user was previously gazing. For example, DA 200 determines based on previous user gaze data (e.g., detected before the current time) that a previous user gaze was directed to one or more previously displayed locations. In some examples, the previous user gaze data analyzed by DA 200 is within a predetermined duration (e.g., 5 seconds, 10 seconds, 20 seconds, 30 seconds) before the current time. For example, responsive to receiving “who was that?”, DA 200 analyzes user gaze data detected within 20 seconds beforehand to determine previously displayed location(s) at which the user gazed during the previous 20 seconds.

(60) In some examples, DA 200 analyzes the previous display of the video event at the previously displayed location(s) using the context information to identify participant 314. For example, if device 300 detected user gaze once every second in the previous 20 seconds, DA 200 analyzes 20 different previously displayed locations the user gazed at, e.g., in 20 respective previous still frames of the video event. For example, consistent with the techniques discussed with respect to FIG. 3A, DA 200 performs image recognition on each still frame around each of the previously displayed location(s) to identify a displayed entity corresponding to each previously displayed location, e.g., by implementing a search process to detect an entity in the vicinity of each previously displayed location. In one example, the image recognition indicates that within the

previous 20 seconds, the display location(s) most frequently correspond to the same entity (meaning in most of the previous 20 still frames, the user gazed at the same entity). DA **200** then matches identified visual features (e.g., jersey number and jersey color) of the most frequent entity to the context information to identify participant **314**. For example, if the identified visual features match the context information, DA **200** increases a likelihood score of identifying participant **314** corresponding to the matching context information.

(61) In some examples, DA **200** performs the above described process for each other detected entity (if any), e.g., entity(ies) the user less frequently gazed at in some of the previous still frames. For example, DA **200** matches identified visual features of the other entity(ies) to the context information to determine other participant(s) corresponding to the entity(ies), but assigns the other participant(s) lower likelihood scores because they were less frequently gazed at. As a specific example, if DA **200** determines that a user gazes at a first participant in 15 of the previous still frames and gazes at a second participant in 5 of the previous still frames, DA **200** assigns the first participant a higher likelihood score than the second participant.

(62) To illustrate the above process, FIG. 3D shows a previous display (e.g., previous still frame) of the video event, such as display of the video event before participant **314** scores the goal in FIG. 3C. In FIG. 3D, DA **200** determines that the user previously gazed at previously displayed location **316** of participant **314**. Accordingly, DA **200** identifies visual features (e.g., jersey color and number) of participant **314** and matches the visual features to the context information (e.g., team roster information) to identify participant **314**.

(63) In some examples, DA **200** alternatively or additionally uses other techniques based on the context information to identify participant **314**, e.g., in accordance with a determination that the natural language input refers to the participant in the past tense. For example, DA **200** identifies participant **314** by performing facial and/or bodily recognition, e.g., of respective face(s) and/or body(ies) detected closest to the previously displayed location(s). For example, DA assigns a participant having their face and/or body more frequently recognized (e.g., in the previous still frames) a higher likelihood score than a participant having their face and/or body less frequently recognized. As another example, DA **200** identifies participant **314** based on the audio stream of the video event. For example, DA **200** determines whether the audio stream of the video event, at and/or within a predetermined duration before the current time, includes name(s) of participant(s). If so, DA **200** increases a likelihood score of identifying the named participant(s). As another example, DA **200** identifies participant **314** based on an annotated event stream of the video event. For example, DA **200** analyzes the event stream, at and/or within a predetermined duration before the current time, to determine whether the event stream indicates participant(s). If so, DA **200** increases the likelihood score of identifying the indicated participant(s). In some examples, consistent with that discussed with respect to FIG. 3A, DA **200** identifies participant **314** based on the user's gaze at the current time. For example, if DA **200** identifies a candidate participant based on the user's current gaze location, DA **200** increases a likelihood score of identifying the candidate participant as the correct participant **314**.

(64) In some examples, DA **200** identifies participant **314** based on participant **314**'s popularity, e.g., in a manner similar to that discussed above. For example, DA **200** increases the likelihood scores of participants to bias towards identifying more popular participants. In this manner, DA **200** can determine that natural language inputs such as “who was that?” more likely refer to more popular participants.

(65) In the present example, according to the above discussed techniques, DA **200** identifies participant **314** as Megan Rapinoe. For example, DA **200** determines that within 20 seconds before receiving the natural language input “who was that?”, the user was most frequently gazing at Megan Rapinoe, the audio stream of the video event includes Megan Rapinoe's name (e.g., “Megan Rapinoe has the ball”), and/or an event stream of the video event indicates that Megan Rapinoe was passed the ball or scored a goal.

(66) In some examples, in accordance with identifying participant **314**, DA **200** identifies participant **314**'s currently displayed location. For example, after identifying participant **314**, DA **200** performs image recognition on the current display of the video event in FIG. 3C, using context information corresponding to participant **314** (e.g., Megan Rapinoe's jersey number, jersey design, facial and/or bodily features), to identify participant **314**'s currently displayed location. In accordance with identifying participant **314**'s currently displayed location, DA **200** augments the display of the video event with graphical overlay **318** displayed at a display location corresponding to participant **314**'s currently displayed location.

(67) In some examples, DA **200** further optionally provides other output (e.g., audio output) identifying participant **314**, e.g., "that was Megan Rapinoe." In some examples, if DA **200** cannot identify the current location of participant **314** (e.g., if display **302** does not currently display Megan Rapinoe), DA **200** provides the output without displaying graphical overlay **318**. In some examples, if DA **200** cannot identify participant **314** (e.g., if no participant has a sufficiently high likelihood score), DA **200** provides an output indicative of an error, e.g., "sorry, I don't know who that was."

(68) FIG. 3E shows an example where the natural language input specifies participant **320** and includes a request to locate participant **320**. For example, while display **302** displays a video event, a user asks DA **200** "where is Alex Morgan?"

(69) In accordance with receiving the natural language input, DA **200** identifies, based on the context information, a location of participant **320**. For example, DA **200** determines a user intent to locate participant **320** and then performs image recognition to locate participant **320**. For example, DA **200** retrieves context information corresponding to specified participant **320** (e.g., jersey number, jersey design, facial and/or bodily features) and analyzes the display of the video event at the current time to detect participant **320** matching the context information.

(70) In accordance with identifying the location of participant **320**, DA **200** augments the display of the video event with graphical overlay **322** displayed at a display location corresponding to the identified location. For example, graphical overlay **322** in FIG. 3E indicates the location of participant **320** Alex Morgan. In some examples, DA **200** further provides output indicating the located participant. For example, DA **200** speaks "there she is" while display **302** displays graphical overlay **322**. In some examples, if DA **200** is unable to locate participant **320** (e.g., if Alex Morgan is not currently displayed and/or image recognition fails to identify Alex Morgan), DA provides an output indicating that participant **320** cannot be located (e.g., "I can't find Alex Morgan") and forgoes displaying graphical overlay **322**.

(71) FIG. 3F shows an example where a natural language input includes a request to visually distinguish between a first party (e.g., team or individual participant) of the video event and an opposing second party (e.g., opposing team or opposing individual participant) of the video event. For example, while display **302** displays a live soccer game, a user asks DA **200** to "show me the teams." Other example natural language inputs including requests to visually distinguish between parties include "highlight the teams," "distinguish the teams," "highlight the players," and the like.

(72) In accordance with receiving the natural language input, DA **200** determines that the natural language input includes a request to visually distinguish between the first party and the opposing second party, e.g., by determining a user intent to visually distinguish between the parties. In accordance with such determination, DA **200** identifies, based on context information, the location(s) of first participant(s) corresponding to the first party (first location(s)) and the location(s) of second participant(s) corresponding to the opposing second party (second location(s)). For example, DA **200** performs image recognition on the currently displayed video event to identify the first location(s) (e.g., based on the jersey design of the first party) and to identify the second location(s) (e.g., based on the jersey design of the second party). In accordance with identifying the first location(s), DA **200** augments the display of the video event with first graphical overlay **324** displayed at first display location(s) respectively corresponding to the first

location(s). Similarly, in accordance with identifying the second location(s), DA 200 augments the display of the video event with second graphical overlay 326 displayed at second display location(s) respectively corresponding to the second location(s).

(73) In some examples, display 302 concurrently displays first graphical overlay 324 and second graphical overlay 326 and displays first graphical overlay 324 in a different manner than second graphical overlay 326 (e.g., different color, shape, brightness, size, shading). In this manner, as shown in FIG. 3F, DA 200 may visually distinguish between opposing parties of the video event based on, e.g., identifying the different jersey designs of the opposing parties.

(74) In some examples, DA 200 further provides output (e.g., audio output) indicating the visually distinguished parties. For example, while display 302 displays graphical overlays 324 and 326, DA 200 outputs “here are the teams.”

(75) In some examples, consistent with that discussed with respect to FIG. 3B, graphical overlays 324 and 326 follow the location(s) of the respective participants. For example, DA 200 continues to track the first and second location(s) (e.g., by using image recognition to track the movements of the opposing jersey designs) as the video event progresses and updates the displayed locations of graphical overlays 324 and 326 accordingly. In some examples, graphical overlays 324 and 326 remain displayed for a predetermined duration and cease to be displayed after the predetermined duration. In other examples, graphical overlays 324 and 326 are displayed until display 302 ceases displaying the video event or until device 300 receives input instructing to cease display of graphical overlays 324 and 326.

(76) FIG. 3G illustrates an example where the natural language input includes a request to analyze an occurrence (e.g., play, goal, scoring event, new record, foul, and the like) of the video event. For example, while display 302 displays a video event, DA 200 receives the natural language input “break down that play.” Other example natural language inputs including requests to analyze occurrences of video events include “analyze that play,” “show me that again,” “what happened?”, “show me a replay,” “explain what just happened,” and the like.

(77) In some examples, DA 200 determines that the natural language input includes a request to analyze an occurrence of the video event, e.g., by determining a corresponding intent. In accordance with such determination, DA 200 causes display 302 to display a replay of the occurrence. In some examples, the time of the video event at which the replay starts (reply start time) is a predetermined duration before a current time of the video event. In some examples, DA 200 uses the annotated event stream of the video event to determine the replay start time. For example, DA 200 determines, based on the annotated event stream, when a most recent notable moment (e.g., goal) occurred and determines the replay start time as a predetermined duration before the most recent notable moment occurring. As another example, if the annotated event stream indicates a start time of each new play (e.g., in American football), DA 200 determines the replay start time as the start time of the most recent play.

(78) FIG. 3H shows a displayed replay of an occurrence of a video event. For example, participant 328 has just scored a goal in FIG. 3G and FIG. 3H shows a replay of the events before the goal. The replay of the video event can include various types of graphical overlays generated by DA 200, as discussed below.

(79) In some examples, in accordance with receiving the natural language input, DA 200 identifies, based on the context information, a location of participant 328 corresponding to the natural language input. Participant 328 may be the person of interest primarily involved in the occurrence, e.g., goal scorer, person who broke a record, person who committed a foul, person who ran with the ball, and the like. In the present example, the identified location of participant 328 is a location (e.g., displayed location) in the replay of the occurrence. For example, in FIG. 3H, DA 200 identifies the displayed location of participant 328 (e.g., the goal scorer) in the replay so DA 200 can augment the replay with graphical overlay 330 to emphasize participant 328 of interest.

(80) In some examples, identifying the location of participant 328 includes identifying participant

328 based on context information associated with the video event. Accordingly, responsive to a user request to analyze an occurrence of the video event, **DA 200** may automatically identify participant **328** of interest in the occurrence and emphasize participant **328** via graphical overlay **330**. **DA 200** identifies participant **328** according to the techniques discussed above with respect to FIGS. 3A-3D. For example, **DA 200** analyzes the user's previous gaze data (e.g., between the replay start time and the current time) to identify participant **328**, e.g., as previous user gaze was likely directed to participant **328** of interest. As another example, **DA 200** analyzes the event stream of the video event at and/or within a predetermined duration before the current time to identify participant **328**, e.g., as the event stream likely indicates participant **328** involved in the occurrence. As yet another example, **DA 200** identifies participant **328** based on their popularity, e.g., by determining a high likelihood score of participant **328** because they are the most popular player in the game. In the example of FIG. 3H, **DA 200** identifies participant **328** as Lionel Messi.

(81) In some examples, in accordance with a determination that the natural language input includes a request to analyze the occurrence of the video event, **DA 200** identifies, based on the context information, other participant(s) corresponding to the occurrence. The other participant(s) may be people involved in the occurrence other than the primary person of interest, e.g., participant **328**. For example, the other participant(s) may be the players who participant **328** dribbled past to score the goal, the player who had a pass intercepted, a defensive player who tackled the quarterback (in football), the goalie who was scored against, and the like. **DA 200** identifies the other participant(s) according to the same techniques used to identify participant **328**. For example, **DA 200** determines likelihood scores of the participants in the replay based on the context information (e.g., by determining higher likelihood scores for participants the user more frequently gazed at in previous still frames, by determining likelihood scores based on whether the event stream and/or audio stream of the video event name the participant(s), by determining higher likelihood scores for more popular participants). **DA 200** then identifies the participant(s) having the highest likelihood scores, e.g., the ones having likelihood scores above a threshold. In FIG. 3H, for instance, **DA** additionally identifies participant **342** (the goalie A. Bob) and participant **344** (the defender B. Fred). Participant **328**'s likelihood score may be higher than each of participant **342** and **344**'s respective likelihood scores, e.g., as participant **328** is the primary person of interest.

(82) In some examples, in accordance with identifying participant(s) (e.g., participants **328**, **342**, and **344**), **DA 200** identifies the respective location(s) (e.g., location(s) in the displayed replay) of the participant(s) based on the context information. For example, **DA 200** performs image recognition on the replay using visual features of identified participant **328** (e.g., jersey color, jersey number, facial and/or bodily features) to identify the location of participant **328** and performs a similar process to identify the respective locations of participants **342** and **344**. In some examples, **DA 200** further tracks the respective location(s) of the identified participant(s) in the replay, e.g., using image recognition to track the identified participant(s)' visual features.

(83) In some examples, in accordance with identifying the respective location(s) of the participant(s), **DA 200** augments the display of the video event with graphical overlay(s) displayed at respective display location(s) (e.g., in the replay) corresponding to the respective identified location(s) of the participant(s). In some examples, the graphical overlay(s) indicate respective trajectory(ies) (e.g., path(s) taken) of the identified participant(s). For example, in FIG. 3H, the graphical overlays **330**, **346**, and **348** indicate respective trajectories of participants **328**, **342**, and **344**. **DA 200** generates the trajectories by tracking the movement of the participants **328**, **342**, and **344** in the replay, e.g., based on their identified visual features. In some examples, in accordance with identifying the respective location(s) of the participant(s), **DA 200** further provides output indicating an analysis of the occurrence, e.g., "here's what happened."

(84) In some examples, consistently with the techniques discussed above, **DA 200** augments the display of the replay with various other types of graphical overlays. For example, graphical overlay **332**, displayed at a location corresponding to the location of participant **328**, indicates an identity of

participant **328**. Graphical overlays **334** and **336** visually distinguish between participants of opposing parties involved in the occurrence. In some examples, graphical overlays **334** and **336** follow the locations of the corresponding participants during the replay, e.g., based on DA **200** tracking the movements of the corresponding participants. Graphical overlays **338** indicate the respective identity(ies) of any other participant(s) different from primary participant **328**, e.g., who DA **200** identifies by performing image recognition on the replay. Graphical overlay **340** indicates a ball trajectory, e.g., based on DA **200** performing image tracking on the ball. In some examples, a user setting of device **300** defines the various types of graphical overlays displayed in the replay. For example, a user setting specifies whether to display graphical overlays **334** and **336** distinguishing between opposing parties and another user setting specifies whether to display graphical overlay **340** indicating a ball trajectory.

(85) The above examples describe augmenting the display of the video event with graphical overlays displayed during the replay. For example, graphical overlays **330**, **346**, and **348** can change (e.g., grow longer) during the replay to indicate the respective trajectory(ies) of participants **328**, **342**, and **344**. In some examples, display **302** displays some graphical overlays at a start of the replay. For example, display **302** displays graphical overlay(s) indicating the trajectory(ies) of identified participant(s) during the replay (e.g., graphical overlays **330**, **346**, and **348**) and/or a graphical overlay indicating the ball trajectory during the replay (e.g., graphical overlay **340**) at a start of the replay, and optionally, during the entirety of the replay. In this manner, the replay shows the identified participant(s) moving according to respective pre-indicated trajectory(ies) (e.g., shows participants **328**, **342**, and **344** running over respective graphical overlays **330**, **346**, and **348**). Accordingly, during the replay, a user can determine where a participant and/or a ball will move next, thereby providing a more informative user experience.

(86) FIG. 4 illustrates process **400** for augmenting the display of a video event with a graphical overlay, according to various examples. Process **400** is performed, for example, at a device (e.g., device **300**) and using DA **200** and system **150**. In process **400**, some operations are, optionally, combined, the orders of some operations are, optionally, changed, and some operations are, optionally, omitted. In some examples, additional operations are performed in combination with process **400**.

(87) At block **402**, while displaying, on a display (e.g., display **302**) of an electronic device (e.g., device **300**), a video event, a natural language speech input corresponding to a participant of the video event (e.g., “who is that?”, “who was that?”, “where is Alex Morgan?”, “show me the teams,” and “break down that play” in FIGS. 3A, 3C, 3E, 3F, and 3G, respectively) is received by a digital assistant (e.g., DA **200**) operating on the electronic device. In some examples, the video event is displayed via video pass-through depicting a second display of an external electronic device and the display and the second display concurrently display the video event. In some examples the natural language speech input (e.g., “who is that?”, “who was that?”) includes a request to identify the participant.

(88) At block **404**, while displaying the video event and in accordance with receiving the natural language speech input, a first location of the participant is identified by the digital assistant (e.g., using identification module **208**) based on context information associated with the video event. In some examples, a user gesture input is detected, where the context information includes the detected user gesture input. In some examples, identifying the first location of the participant includes determining that the user gesture input corresponds to the first location at a start time of the natural language speech input and analyzing the display of the video event at the first location (e.g., using identification module **208**) using the context information associated with the video event to identify the first participant. In some examples, the respective locations of participants of video events are continuously identified, e.g., whenever a video event is displayed. For example, during display of a video event, the digital assistant continuously tracks the displayed locations of the participants, e.g., by using image recognition track the movement of human bodies. When the

digital assistant receives the natural language speech input, the digital assistant determines the location relevant to the user request (e.g., the location of the participant corresponding to the speech input) according to the techniques discussed herein.

(89) In some examples, user gaze data is detected, where the context information includes the detected user gaze data. In some examples, identifying the first location of the participant includes determining, based on the user gaze data, that a user gaze is directed to the first location and analyzing the display of the video event at the first location (e.g., using identification module **208**) using the context information associated with the video event to identify the first participant. In some examples, the context information further includes information corresponding to opposing parties of the video event.

(90) In some examples, it is determined (e.g., by NLP module **204**) that the natural language speech input refers to the participant in the present tense. In some examples, determining that the user gaze is directed to the first location includes determining, in accordance with a determination that the natural language speech input refers to the participant in the present tense, that the user gaze is directed to the first location (e.g., location **308** in FIG. 3A) at a start time of the natural language speech input.

(91) In some examples, it is determined (e.g., by NLP module **204**) that the natural language speech input refers to the participant in the past tense. In some examples, in accordance with a determination that the natural language speech input refers to the participant in the past tense, it is determined (e.g., by identification module **208**), based on previous user gaze data detected before a start time of the natural language speech input, that a previous user gaze was directed to a previously displayed location (e.g., location **316** in FIG. 3D). In some examples, in accordance with a determination that the natural language speech input refers to the participant in the past tense, the display of the video event at the previously displayed location is analyzed using the context information associated with the video event (e.g., by identification module **208**) to identify the participant. In some examples, the first location of the participant is a currently displayed location of the participant (e.g., the location of participant **314** in FIG. 3C) and identifying the currently displayed location of the participant is performed in accordance with identifying the participant. In some examples, the context information associated with the video event includes at least one of: information corresponding to opposing parties of the video event, an audio stream of the video event, and an annotated event stream of the video event.

(92) At block **406**, while displaying the video event and in accordance with identifying the first location of the participant, the display of the video event is augmented by the digital assistant (e.g., using display augmentation module **210**) with a graphical overlay displayed at a first display location corresponding to the first location of the participant. In some examples, the graphical overlay (e.g., graphical overlays **310**, **318**, **332**, and **338**) includes information corresponding to the participant. In some examples, the information corresponding to the participant indicates at least one of an identity of the participant, a predetermined highlight corresponding to the participant, and statistics corresponding to the participant.

(93) In some examples, the natural language speech input specifies the participant and includes a request to locate the participant (e.g., “where is Alex Morgan?”). In some examples, the graphical overlay (e.g., graphical overlay **322**) indicates a location of the participant.

(94) In some examples, the natural language speech input includes a request to visually distinguish between a first party of the video event and an opposing second party of the video event (e.g., “show me the teams”), where the participant corresponds to the first party. In some examples, in accordance with receiving the natural language speech input and a determination that the natural language speech input includes a request to visually distinguish between the first party and the opposing second party, a second location of a second participant of the video event is identified by the digital assistant (e.g. using identification module **208**) based on the context information, where the second participant corresponds to the opposing second party. In some examples, in accordance

with identifying the second location of the second participant, the display of the video event is augmented by the digital assistant (e.g., using display augmentation module **210**) with a second graphical overlay (e.g., graphical overlay **326**) displayed at a second display location corresponding to the second location of the second participant. In some examples, the graphical overlay (e.g., graphical overlay **324**) and the second graphical overlay (graphical overlay **326**) are concurrently displayed, and the graphical overlay is displayed in a different manner than the second graphical overlay when the graphical overlay and the second graphical overlay are concurrently displayed. (95) In some examples, the natural language speech input includes a request to analyze an occurrence of the video event (e.g., “break down that play”). In some examples, the graphical overlay (e.g., graphical overlay **330**) indicates a trajectory of the participant (e.g., participant **328**), the trajectory corresponding to the occurrence.

(96) In some examples, in accordance with a determination that the natural language speech input includes a request to analyze the occurrence of the video event, a replay of the occurrence (e.g., in FIG. 3H) is displayed on the display. In some examples, the first location of the participant (e.g., participant **328**) is a location in the replay of the occurrence and the first display location corresponds to the replay of the occurrence. In some examples, identifying the first location of the participant includes identifying (e.g., by identification module **208**), based on the context information associated with the video event, the participant and in accordance with identifying the participant, identifying (e.g., by identification module **208**), based on the context information associated with the video event, the first location.

(97) In some examples, in accordance with a determination that the natural language speech input includes a request to analyze the occurrence of the video event, a second participant (e.g., participants **342** and **344**) corresponding to the occurrence is identified (e.g., by identification module **208**) based on the context information associated with the video event. In some examples, in accordance with identifying the second participant, a third location of the second participant in the replay is identified based on the context information. In some examples, the display of the replay of the occurrence is augmented (e.g., using display augmentation module **210**) with a second graphical overlay (e.g., graphical overlays **346** and **348**) displayed at a third display location corresponding to the third location of the second participant, the second graphical overlay indicating a second trajectory of the second participant.

(98) In some examples, the context information includes at least one: of second information corresponding to opposing parties of the video event, a second audio stream of the video event, and a second annotated event stream of the video event. In some examples, the second information corresponding to the opposing parties of the video event indicates respective jersey numbers of the participants of the opposing parties, respective identities of the participants of the opposing parties, and respective jersey designs of the opposing parties.

(99) In some examples, process **400** further includes detecting a change from the first location of the participant (e.g., location **308**) to a second location of the participant (e.g., location **312**) and in response to detecting the change, displaying (e.g., using display augmentation module **210**), on the display, the graphical overlay (e.g., graphical overlay **310**) at a second display location corresponding to the second location of the participant.

(100) The operations discussed above with respect to FIG. 4 are optionally implemented by the components depicted in FIG. 2, e.g., by system **150** and DA **200**.

(101) In some examples, a computer-readable storage medium (e.g., a non-transitory computer readable storage medium) is provided, the computer-readable storage medium storing one or more programs for execution by one or more processors of an electronic device, the one or more programs including instructions for performing any of the methods or processes described herein.

(102) In some examples, an electronic device is provided that comprises means for performing any of the methods or processes described herein.

(103) In some examples, an electronic device is provided that comprises a processing unit

configured to perform any of the methods or processes described herein.

(104) In some examples, an electronic device is provided that comprises one or more processors and memory storing one or more programs for execution by the one or more processors, the one or more programs including instructions for performing any of the methods or processes described herein.

(105) Various techniques described in the present disclosure involve gathering and using personal information of a user. For example, the personal information (e.g., user gaze data) may be used to augment the displays of video events with graphical overlays. However, when the personal information is gathered, the information should be gathered with the user's informed consent. In other words, users of the XR systems described herein should have knowledge of and control over how their personal information is used.

(106) Only appropriate parties should use the personal information, and the appropriate parties should only use the personal information for reasonable and legitimate purposes. For example, the parties using the personal information will comply with privacy policies and practices that, at a minimum, obey appropriate laws and regulations. Further, such policies should be well-established, user-accessible, and recognized as in compliance with, or to exceed, governmental/industrial standards. Additionally, these parties will not distribute, sell, or otherwise share such information for unreasonable or illegitimate purposes.

(107) Users may also limit the extent to which their personal information is accessible (or otherwise obtainable) by such parties. For example, the user can adjust XR system settings or preferences that control whether their personal information can be accessed by various entities. Additionally, while some examples described herein use personal information, various other examples within the scope of the present disclosure can be implemented without needing to use such information. For example, if personal information (e.g., gaze data) is gathered, the systems can obscure or otherwise generalize the information so the information does not identify the particular user.

Claims

1. A non-transitory computer-readable storage medium storing one or more programs, the one or more programs comprising instructions, which when executed by one or more processors of an electronic device having a display, cause the electronic device to: while displaying, on the display, a video event: receive, by a digital assistant operating on the electronic device, a first natural language speech input corresponding to a first participant of the video event; detecting a user gesture input; in accordance with receiving the first natural language speech input, identify, by the digital assistant, based on context information associated with the video event, a first location of the first participant, including: in accordance with a determination that the first natural language speech input refers to the first participant in the present tense, identifying the first location of the first participant as a location corresponding to the user gesture input when a portion of the first natural language speech input is received; and in accordance with identifying the first location of the first participant, augment, by the digital assistant, the display of the video event with a first graphical overlay displayed at a first display location corresponding to the first location of the first participant.

2. The non-transitory computer-readable storage medium of claim 1, wherein the one or more programs further comprise instructions, which when executed by the one or more processors, cause the electronic device to: detect a change from the first location of the first participant to a second location of the first participant; and in response to detecting the change, display, on the display, the first graphical overlay at a second display location corresponding to the second location of the first participant.

3. The non-transitory computer-readable storage medium of claim 1, wherein: the video event is

displayed via video pass-through depicting a second display of an external electronic device; and the display and the second display concurrently display the video event.

4. The non-transitory computer-readable storage medium of claim 1, wherein: the first natural language speech input includes a request to identify the first participant; and the first graphical overlay includes information corresponding to the first participant.

5. The non-transitory computer-readable storage medium of claim 4, wherein the information corresponding to the first participant indicates at least one of: an identity of the first participant; a predetermined highlight corresponding to the first participant; and statistics corresponding to the first participant.

6. The non-transitory computer-readable storage medium of claim 4, wherein identifying the first location of the first participant includes: analyzing the display of the video event at the first location of the first participant using the context information associated with the video event to identify the first participant.

7. The non-transitory computer-readable storage medium of claim 4, wherein the one or more programs further comprise instructions, which when executed by the one or more processors, cause the electronic device to: detect user gaze data, wherein the context information includes the detected user gaze data, and wherein identifying the first location of the first participant includes: determining, based on the user gaze data, that a user gaze is directed to the first location of the first participant; and analyzing the display of the video event at the first location of the first participant using the context information associated with the video event to identify the first participant.

8. The non-transitory computer-readable storage medium of claim 6, wherein the context information further includes information corresponding to opposing parties of the video event.

9. The non-transitory computer-readable storage medium of claim 4, wherein the one or more programs further comprise instructions, which when executed by the one or more processors, cause the electronic device to: determine that the first natural language speech input refers to the first participant in the past tense; and in accordance with a determination that the first natural language speech input refers to the first participant in the past tense: determine, based on previous user gaze data detected before a start time of the first natural language speech input, that a previous user gaze was directed to a previously displayed location; analyze the display of the video event at the previously displayed location using the context information associated with the video event to identify the first participant, wherein: the first location of the first participant is identified as a currently displayed location of the first participant; and identifying the currently displayed location of the first participant is performed in accordance with identifying the first participant.

10. The non-transitory computer-readable storage medium of claim 9, wherein the context information associated with the video event includes at least one of: information corresponding to opposing parties of the video event; an audio stream of the video event; and an annotated event stream of the video event.

11. The non-transitory computer-readable storage medium of claim 1, wherein the one or more programs further comprise instructions, which when executed by the one or more processors, cause the electronic device to: while displaying, on the display, the video event: receive, by the digital assistant operating on the electronic device, a second natural language speech input corresponding to a second participant of the video event, wherein the second natural language speech input specifies the second participant and includes a request to locate the second participant; in accordance with receiving the second natural language speech input, identify, by the digital assistant, based on the context information associated with the video event, a first location of the second participant; and in accordance with identifying the first location of the second participant, augment, by the digital assistant, the display of the video event with a second graphical overlay displayed at a second display location corresponding to the first location of the second participant, wherein the second graphical overlay indicates the first location of the second participant.

12. The non-transitory computer-readable storage medium of claim 1, wherein the one or more

programs further comprise instructions, which when executed by the one or more processors, cause the electronic device to: while displaying, on the display, the video event: receive, by the digital assistant operating on the electronic device, a second natural language speech input that the natural language speech input includes a request to visually distinguish between a first party of the video event and an opposing second party of the video event; and in accordance with receiving the second natural language speech input and a determination that the second natural language speech input includes the request to visually distinguish between the first party and the opposing second party: identify, by the digital assistant, based on the context information associated with the video event: a first location of a second participant of the video event, wherein the second participant corresponds to the first party; and a first location of a third participant of the video event, the third participant corresponding to the opposing second party; in accordance with identifying the first location of the second participant, augment, by the digital assistant, the display of the video event with a second graphical overlay displayed at a second display location corresponding to the first location of the second participant; and in accordance with identifying the first location of the third participant, augment, by the digital assistant, the display of the video event with a third graphical overlay displayed at a third display location corresponding to the first location of the third participant.

13. The non-transitory computer-readable storage medium of claim 12, wherein the second graphical overlay and the third graphical overlay are concurrently displayed, and wherein the second graphical overlay is displayed in a different manner than the third graphical overlay when the second graphical overlay and the third graphical overlay are concurrently displayed.

14. The non-transitory computer-readable storage medium of claim 1, wherein the one or more programs further comprise instructions, which when executed by the one or more processors, cause the electronic device to: while displaying, on the display, the video event: receive, by the digital assistant operating on the electronic device, a second natural language speech input that includes a request to analyze an occurrence of the video event, wherein the occurrence corresponds to a second participant of the video event; in accordance with receiving the second natural language speech input, identify, by the digital assistant, based on the context information associated with the video event, a first location of the second participant; and in accordance with identifying the first location of the second participant, augment, by the digital assistant, the display of the video event with a second graphical overlay displayed at a second display location corresponding to the first location of the second participant, wherein the second graphical overlay indicates a trajectory of the second participant, the trajectory corresponding to the occurrence.

15. The non-transitory computer-readable storage medium of claim 14, wherein the one or more programs further comprise instructions, which when executed by the one or more processors, cause the electronic device to: in accordance with a determination that the second natural language speech input includes the request to analyze the occurrence of the video event, display, on the display, a replay of the occurrence, wherein: the first location of the second participant is a location in the replay of the occurrence; and the second display location corresponds to the replay of the occurrence.

16. The non-transitory computer-readable storage medium of claim 15, wherein identifying the first location of the second participant includes: identifying, based on the context information associated with the video event, the second participant; and in accordance with identifying the second participant, identifying, based on the context information associated with the video event, the first location of the second participant.

17. The non-transitory computer-readable storage medium of claim 15, wherein the one or more programs further comprise instructions, which when executed by the one or more processors, cause the electronic device to: in accordance with a determination that the second natural language speech input includes the request to analyze the occurrence of the video event: identify, based on the context information associated with the video event, a third participant corresponding to the

occurrence; in accordance with identifying the third participant, identify, based on the context information associated with the video event, a first location of the third participant in the replay; and augment the display of the replay of the occurrence with a third graphical overlay displayed at a third display location corresponding to the first location of the third participant, the third graphical overlay indicating a second trajectory of the third second participant.

18. The non-transitory computer-readable storage medium of claim 1, wherein the context information includes at least one of: second information corresponding to opposing parties of the video event; a second audio stream of the video event; and a second annotated event stream of the video event.

19. The non-transitory computer-readable storage medium of claim 18, wherein the second information corresponding to the opposing parties of the video event indicates: respective jersey numbers of participants of the opposing parties; respective identities of the participants of the opposing parties; and respective jersey designs of the opposing parties.

20. An electronic device comprising: a display; one or more processors; a memory; and one or more programs, wherein the one or more programs are stored in the memory and configured to be executed by the one or more processors, the one or more programs including instructions for: while displaying, on the display, a video event: receiving, by a digital assistant operating on the electronic device, a first natural language speech input corresponding to a first participant of the video event; detecting a user gesture input; in accordance with receiving the first natural language speech input, identifying, by the digital assistant, based on context information associated with the video event, a first location of the first participant, including: in accordance with a determination that the first natural language speech input refers to the first participant in the present tense, identifying the first location of the first participant as a location corresponding to the user gesture input when a portion of the first natural language speech input is received; and in accordance with identifying the first location of the first participant, augmenting, by the digital assistant, the display of the video event with a first graphical overlay displayed at a first display location corresponding to the first location of the first participant.

21. The electronic device of claim 20, wherein the one or more programs further include instructions for: detecting a change from the first location of the first participant to a second location of the first participant; and in response to detecting the change, displaying, on the display, the first graphical overlay at a second display location corresponding to the second location of the first participant.

22. The electronic device of claim 20, wherein: the video event is displayed via video pass-through depicting a second display of an external electronic device; and the display and the second display concurrently display the video event.

23. The electronic device of claim 20, wherein: the first natural language speech input includes a request to identify the first participant; and the first graphical overlay includes information corresponding to the first participant.

24. The electronic device of claim 23, wherein identifying the first location of the first participant includes analyzing the display of the video event at the first location of the first participant using the context information associated with the video event to identify the first participant.

25. The electronic device of claim 23, wherein the one or more programs further include instructions for: detecting user gaze data, wherein the context information includes the detected user gaze data, and wherein identifying the first location of the first participant includes: determining, based on the user gaze data, that a user gaze is directed to the first location of the first participant; and analyzing the display of the video event at the first location of the first participant using the context information associated with the video event to identify the first participant.

26. The electronic device of claim 23, wherein the one or more programs further include instructions for: determining that the first natural language speech input refers to the first participant in the past tense; and in accordance with a determination that the first natural language

speech input refers to the first participant in the past tense: determining, based on previous user gaze data detected before a start time of the first natural language speech input, that a previous user gaze was directed to a previously displayed location; analyzing the display of the video event at the previously displayed location using the context information associated with the video event to identify the first participant, wherein: the first location of the first participant is identified as a currently displayed location of the first participant; and identifying the currently displayed location of the first participant is performed in accordance with identifying the first participant.

27. The electronic device of claim 20, wherein the one or more programs further include instructions for: while displaying, on the display, the video event: receiving, by the digital assistant operating on the electronic device, a second natural language speech input corresponding to a second participant of the video event, wherein the second natural language speech input specifies the second participant and includes a request to locate the second participant; in accordance with receiving the second natural language speech input, identifying, by the digital assistant, based on the context information associated with the video event, a first location of the second participant; and in accordance with identifying the first location of the second participant, augmenting, by the digital assistant, the display of the video event with a second graphical overlay displayed at a second display location corresponding to the first location of the second participant, wherein the second graphical overlay indicates the first location of the second participant.

28. The electronic device of claim 20, wherein the one or more programs further include instructions for: while displaying, on the display, the video event: receiving, by the digital assistant operating on the electronic device, a second natural language speech input that includes a request to visually distinguish between a first party of the video event and an opposing second party of the video event; and in accordance with receiving the second natural language speech input and a determination that the second natural language speech input includes the request to visually distinguish between the first party and the opposing second party: identifying, by the digital assistant, based on the context information associated with the video event: a first location of a second participant of the video event, wherein the second participant corresponds to the first party; and a first location of a third participant of the video event, the third participant corresponding to the opposing second party; in accordance with identifying the first location of the second participant, augmenting, by the digital assistant, the display of the video event with a second graphical overlay displayed at a second display location corresponding to the first location of the second participant; and in accordance with identifying the first location of the third participant, augmenting, by the digital assistant, the display of the video event with a third graphical overlay displayed at a third display location corresponding to the first location of the third participant.

29. The electronic device of claim 20, wherein the one or more programs further include instructions for: while displaying, on the display, the video event: receiving, by the digital assistant operating on the electronic device, a second natural language speech input that includes a request to analyze an occurrence of the video event, wherein the occurrence corresponds to a second participant of the video event; in accordance with receiving the second natural language speech input, identifying, by the digital assistant, based on the context information associated with the video event, a first location of the second participant; and in accordance with identifying the first location of the second participant, augmenting, by the digital assistant, the display of the video event with a second graphical overlay displayed at a second display location corresponding to the first location of the second participant, wherein the second graphical overlay indicates a trajectory of the second participant, the trajectory corresponding to the occurrence.

30. The electronic device of claim 29, wherein the one or more programs further include instructions for: in accordance with a determination that the second natural language speech input includes the request to analyze the occurrence of the video event, displaying, on the display, a replay of the occurrence, wherein: the first location of the second participant is a location in the replay of the occurrence; and the second display location corresponds to the replay of the

occurrence.

31. The electronic device of claim 20, wherein the context information includes at least one of: second information corresponding to opposing parties of the video event; a second audio stream of the video event; and a second annotated event stream of the video event.

32. A method, comprising: at an electronic device having one or more processors, memory, and a display: while displaying, on the display, a video event: receiving, by a digital assistant operating on the electronic device, a first natural language speech input corresponding to a first participant of the video event; detecting a user gesture input; in accordance with receiving the first natural language speech input, identifying, by the digital assistant, based on context information associated with the video event, a first location of the first participant, including: in accordance with a determination that the first natural language speech input refers to the first participant in the present tense, identifying the first location of the first participant as a location corresponding to the user gesture input when a portion of the first natural language speech input is received; and in accordance with identifying the first location of the first participant, augmenting, by the digital assistant, the display of the video event with a first graphical overlay displayed at a first display location corresponding to the first location of the first participant.

33. The method of claim 32, further comprising: detecting a change from the first location of the first participant to a second location of the first participant; and in response to detecting the change, displaying, on the display, the first graphical overlay at a second display location corresponding to the second location of the first participant.

34. The method of claim 32, wherein: the video event is displayed via video pass-through depicting a second display of an external electronic device; and the display and the second display concurrently display the video event.

35. The method of claim 32, wherein: the first natural language speech input includes a request to identify the first participant; and the first graphical overlay includes information corresponding to the first participant.

36. The method of claim 35, wherein identifying the first location of the first participant includes analyzing the display of the video event at the first location of the first participant using the context information associated with the video event to identify the first participant.

37. The method of claim 35, further comprising: detecting user gaze data, wherein the context information includes the detected user gaze data, and wherein identifying the first location of the first participant includes: determining, based on the user gaze data, that a user gaze is directed to the first location of the first participant; and analyzing the display of the video event at the first location of the first participant using the context information associated with the video event to identify the first participant.

38. The method of claim 35, further comprising: determining that the first natural language speech input refers to the first participant in the past tense; and in accordance with a determination that the first natural language speech input refers to the first participant in the past tense: determining, based on previous user gaze data detected before a start time of the first natural language speech input, that a previous user gaze was directed to a previously displayed location; analyzing the display of the video event at the previously displayed location using the context information associated with the video event to identify the first participant, wherein: the first location of the first participant is identified as a currently displayed location of the first participant; and identifying the currently displayed location of the first participant is performed in accordance with identifying the first participant.

39. The method of claim 32, further comprising: while displaying, on the display, the video event: receiving, by the digital assistant operating on the electronic device, a second natural language speech input corresponding to a second participant of the video event, wherein the second natural language speech input specifies the second participant and includes a request to locate the second participant; in accordance with receiving the second natural language speech input, identifying, by

the digital assistant, based on the context information associated with the video event, a first location of the second participant; and in accordance with identifying the first location of the second participant, augmenting, by the digital assistant, the display of the video event with a second graphical overlay displayed at a second display location corresponding to the first location of the second participant, wherein the second graphical overlay indicates the first location of the second participant.

40. The method of claim 32, further comprising: while displaying, on the display, the video event: receiving, by the digital assistant operating on the electronic device, a second natural language speech input that includes a request to visually distinguish between a first party of the video event and an opposing second party of the video event; and in accordance with receiving the second natural language speech input and a determination that the second natural language speech input includes the request to visually distinguish between the first party and the opposing second party: identifying, by the digital assistant, based on the context information associated with the video event: a first location of a second participant of the video event, wherein the second participant corresponds to the first party; and a first location of a third participant of the video event, the third participant corresponding to the opposing second party; in accordance with identifying the first location of the second participant, augmenting, by the digital assistant, the display of the video event with a second graphical overlay displayed at a second display location corresponding to the first location of the second participant; and in accordance with identifying the first location of the third participant, augmenting, by the digital assistant, the display of the video event with a third graphical overlay displayed at a third display location corresponding to the first location of the third participant.

41. The method of claim 32, further comprising: while displaying, on the display, the video event: receiving, by the digital assistant operating on the electronic device, a second natural language speech input that includes a request to analyze an occurrence of the video event, wherein the occurrence corresponds to a second participant of the video event; in accordance with receiving the second natural language speech input, identifying, by the digital assistant, based on the context information associated with the video event, a first location of the second participant; and in accordance with identifying the first location of the second participant, augmenting, by the digital assistant, the display of the video event with a second graphical overlay displayed at a second display location corresponding to the first location of the second participant, wherein the second graphical overlay indicates a trajectory of the second participant, the trajectory corresponding to the occurrence.

42. The method of claim 41, further comprising: in accordance with a determination that the second natural language speech input includes the request to analyze the occurrence of the video event, displaying, on the display, a replay of the occurrence, wherein: the first location of the second participant is a location in the replay of the occurrence; and the second display location corresponds to the replay of the occurrence.

43. The method of claim 32, wherein the context information includes at least one of: second information corresponding to opposing parties of the video event; a second audio stream of the video event; and a second annotated event stream of the video event.
