

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12407924
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Son; Youngbae et al.

Electronic device including camera for obtaining different image data from a plurality of image sensors using an optical splitter

Abstract

An electronic device according to an embodiment includes a camera module, a memory, and a processor. The camera module includes a lens part, a first image sensor, a second image sensor, and an optical splitter. The optical splitter provides a first portion of light introduced through the lens part to the first image sensor and provides a second portion of the light introduced through the lens part to the second image sensor. The processor combines first image data obtained based on the first image sensor and second image data obtained based on the second image sensor to generate third image data and performs a specified function.

Inventors: Son; Youngbae (Suwon-si, KR), Heu; Min (Suwon-si, KR), Byon; Kwangseok (Suwon-si, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 84102963

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Appl. No.: 17/747719

Filed: May 18, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220377246 A1	Nov. 24, 2022

Foreign Application Priority Data

KR	10-2021-0064330	May. 18, 2021
----	-----------------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: **H04N5/335** (20110101); **H04N23/54** (20230101); **H04N23/55** (20230101); **H04N23/67** (20230101); **H04N23/80** (20230101)

U.S. Cl.:

CPC **H04N23/672** (20230101); **H04N23/54** (20230101); **H04N23/55** (20230101); **H04N23/80** (20230101);

Field of Classification Search

CPC: H04N (23/672)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4876591	12/1988	Muramatsu	348/E9.01	H04N 23/843
8134618	12/2011	Ajito	348/222.1	H04N 25/134
10404952	12/2018	Yoon et al.	N/A	N/A
10616536	12/2019	Kane	N/A	H04N 23/16
10874293	12/2019	Kato	N/A	N/A
10921552	12/2020	Park et al.	N/A	N/A
11009830	12/2020	Lee et al.	N/A	N/A
2002/0140822	12/2001	Kahn	348/207.99	H04N 5/33
2008/0030611	12/2007	Jenkins	348/336	H04N 23/84
2010/0073499	12/2009	Gere	348/222.1	H04N 23/15
2016/0198141	12/2015	Fettig	348/46	H04N 25/709
2017/0026622	12/2016	Yoon et al.	N/A	N/A
2017/0251912	12/2016	Kato	N/A	N/A
2017/0272642	12/2016	Zhang	N/A	H04N 25/702
2018/0307181	12/2017	Lee et al.	N/A	N/A
2019/0222813	12/2018	Kane et al.	N/A	N/A
2021/0137369	12/2020	Meester	N/A	A61B 1/0646
2021/0368080	12/2020	Bachar	N/A	G02B 13/0045
2022/0407998	12/2021	Bachar et al.	N/A	N/A
2023/0336848	12/2022	Bachar et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
105049698	12/2014	CN	N/A
6-261328	12/1993	JP	N/A
2003-295044	12/2002	JP	N/A
WO2016/117049	12/2015	JP	N/A
1020160104236	12/2015	KR	N/A
10-2017-0011818	12/2016	KR	N/A
1020180119428	12/2017	KR	N/A
102090625	12/2019	KR	N/A
102252088	12/2020	KR	N/A
2020030989	12/2019	WO	N/A

OTHER PUBLICATIONS

International Search Report (PCT/ISA/210) dated Aug. 23, 2022 issued by the International Searching Authority in International Application No. PCT/KR2022/007034. cited by applicant
Communication issued Apr. 29, 2025 by the Korean Intellectual Property Office in Korean Patent Application No. 10-2021-0064330. cited by applicant

Primary Examiner: Vieaux; Gary C

Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) (1) This application is a by-pass continuation application of International Application No. PCT/KR2022/007034, filed on May 17, 2022, which claims priority from Korean Patent Application No. 10-2021-0064330, filed on May 18, 2021, in the Korean Intellectual Property Office, the disclosures of which are herein incorporated by reference in their entireties.

BACKGROUND

1. Technical Field

(1) Various embodiments disclosed in the disclosure relate to an electronic device including a camera.

2. Description of the Related Art

(2) An electronic device may include a camera module (or a camera or a camera device) and may capture a photo or a moving image using the camera module. Recently, an electronic device including a folded camera module has been introduced to reduce a thickness of the camera module.

(3) The folded camera module may include a prism which operates as a reflection mirror for changing a progress direction of light therein. Light incident from the outside may be changed in direction through the prism and may be delivered to an image sensor.

(4) An electronic device may include a camera module including an image sensor. In this case, restrictions on a size or a resolution of the image sensor may occur according to optical specifications (e.g., an aperture value and an angle of view). Recently, an electronic device may include an image sensor in which two photo diodes (hereinafter, 2PD) are arranged in one pixel (hereinafter, a 2PD image sensor) to perform precise auto focus (AF). The electronic device may perform phase detection auto focus (PDAF) using the 2PD image sensor. A single pixel of the 2PD image sensor may be larger in size than a single pixel of an image sensor which does not have a

2PD scheme. Due to this, there is a problem that it is difficult to implement a higher pixel density in the same area than a general image sensor.

(5) Various embodiments may provide an electronic device for obtaining different image data from a plurality of image sensors using an optical splitter.

SUMMARY

(6) In accordance with an aspect of the disclosure, an electronic device is provided. The electronic device may include a camera module, a memory, and a processor electrically connected with the camera module and the memory. The camera module may include a lens part, a first image sensor including a plurality of pixels corresponding to a first color and a second color, each pixel of the plurality of pixels including two photo diodes; a second image sensor having a pixel of a third color; and an optical splitter. The optical splitter may provide a first portion of a light introduced through the lens part to the first image sensor; and provide a second portion of the light introduced through the lens part to the second image sensor. The processor may combine first image data obtained based on the first image sensor and second image data obtained based on the second image sensor to generate third image data and may perform a specified function using at least one of the first image data, the second image data, or the generated third image data.

(7) The electronic device according to various embodiments of the disclosure may separate an image signal of a single color (e.g., green) from an image signal of a plurality of colors (e.g., red and blue), using an optical splitter (e.g., a beam splitter), and may synthesize them in various manners. As a result, the electronic device may perform precise auto focus (AF) without deterioration in resolution.

(8) The electronic device according to various embodiments of the disclosure may separate an image signal of a single color (e.g., green) from an image signal of a plurality of colors (e.g., red and blue), thus increasing sensitivity of a single color sensor (a green channel) and enhancing low illumination performance.

Description

DESCRIPTION OF THE DRAWINGS

(1) The above and/or other aspects will become apparent and more readily appreciated from the following description of example embodiments, taken in conjunction with the accompanying drawings in which.

(2) FIG. 1 is a block diagram illustrating an electronic device in a network environment according to various embodiments;

(3) FIG. 2 is a block diagram illustrating a camera module according to various embodiments;

(4) FIGS. 3A and 3B illustrate an electronic device including a camera module according to various embodiments;

(5) FIG. 4 illustrates a structure of a folded camera module according to various embodiments;

(6) FIGS. 5A, 5B, and 5C illustrate a pixel structure in a first image sensor and a second image sensor according to various embodiments;

(7) FIG. 6 illustrates synthesis of first image data and second image data according to various embodiments.

DETAILED DESCRIPTION

(8) Hereinafter, various embodiments of the disclosure are described with reference to the accompanying drawings. Accordingly, those of ordinary skill in the art will recognize that modification, equivalent, and/or alternative on the various embodiments described herein can be variously made without departing from the scope and spirit of the disclosure. With regard to description of drawings, similar denotations may be used for similar components.

(9) FIG. 1 is a block diagram illustrating an electronic device **101** in a network environment **100**

according to various embodiments. Referring to FIG. 1, the electronic device **101** in the network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or at least one of an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network). According to an embodiment, the electronic device **101** may communicate with the electronic device **104** via the server **108**. According to an embodiment, the electronic device **101** may include a processor **120**, memory **130**, an input module **150**, a sound output module **155**, a display module **160**, an audio module **170**, a sensor module **176**, an interface **177**, a connecting terminal **178**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In some embodiments, at least one of the components (e.g., the connecting terminal **178**) may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In some embodiments, some of the components (e.g., the sensor module **176**, the camera module **180**, or the antenna module **197**) may be implemented as a single component (e.g., the display module **160**).

(10) The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation. According to one embodiment, as at least part of the data processing or computation, the processor **120** may store a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in non-volatile memory **134**. According to an embodiment, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **123** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**. For example, when the electronic device **101** includes the main processor **121** and the auxiliary processor **123**, the auxiliary processor **123** may be adapted to consume less power than the main processor **121**, or to be specific to a specified function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**.

(11) The auxiliary processor **123** may control at least some of functions or states related to at least one component (e.g., the display module **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **123** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**. According to an embodiment, the auxiliary processor **123** (e.g., the neural processing unit) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g., by the electronic device **101** where the artificial intelligence is performed or via a separate server (e.g., the server **108**). Learning algorithms may include, but are not limited to, e.g., supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof but is not limited thereto. The artificial intelligence model may, additionally or

alternatively, include a software structure other than the hardware structure.

(12) The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**.

(13) The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

(14) The input module **150** may receive a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input module **150** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

(15) The sound output module **155** may output sound signals to the outside of the electronic device **101**. The sound output module **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.

(16) The display module **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display module **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display module **160** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.

(17) The audio module **170** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **170** may obtain the sound via the input module **150**, or output the sound via the sound output module **155** or a headphone of an external electronic device (e.g., an electronic device **102**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **101**.

(18) The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(19) The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **177** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(20) A connecting terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**). According to an embodiment, the connecting terminal **178** may include, for example, a HDMI connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone connector).

(21) The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(22) The camera module **180** may capture a still image or moving images. According to an embodiment, the camera module **180** may include one or more lenses, image sensors, image signal processors, or flashes.

(23) The power management module **188** may manage power supplied to the electronic device **101**. According to one embodiment, the power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

(24) The battery **189** may supply power to at least one component of the electronic device **101**. According to an embodiment, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(25) The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently from the processor **120** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **196**.

(26) The wireless communication module **192** may support a 5G network, after a 4G network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **192** may support a high-frequency band (e.g., the mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the electronic device **104**), or a network system (e.g., the second network **199**). According to an embodiment, the wireless communication module **192** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1 ms or less) for implementing URLLC.

(27) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to an embodiment, the antenna module **197** may include an antenna including a radiating element composed of a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment, the antenna module **197** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may

be selected, for example, by the communication module **190** (e.g., the wireless communication module **192**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **197**.

(28) According to various embodiments, the antenna module **197** may form a mmWave antenna module. According to an embodiment, the mmWave antenna module may include a printed circuit board, a RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(29) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(30) According to an embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the electronic devices **102** or **104** may be a device of a same type as, or a different type, from the electronic device **101**. According to an embodiment, all or some of operations to be executed at the electronic device **101** may be executed at one or more of the external electronic devices **102**, **104**, or **108**. For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **101**. The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **101** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In another embodiment, the external electronic device **104** may include an internet-of-things (IoT) device. The server **108** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(31) FIG. 2 is a block diagram **200** illustrating the camera module **180** according to various embodiments.

(32) Referring to FIG. 2, the camera module **180** may include a lens assembly **210**, a flash **220**, an image sensor **230**, an image stabilizer **240**, memory **250** (e.g., buffer memory), or an image signal processor **260**. The lens assembly **210** may collect light emitted or reflected from an object whose image is to be taken. The lens assembly **210** may include one or more lenses. According to an embodiment, the camera module **180** may include a plurality of lens assemblies **210**. In such a case, the camera module **180** may form, for example, a dual camera, a 360-degree camera, or a spherical camera. Some of the plurality of lens assemblies **210** may have the same lens attribute (e.g., view angle, focal length, auto-focusing, f number, or optical zoom), or at least one lens assembly may have one or more lens attributes different from those of another lens assembly. The

lens assembly **210** may include, for example, a wide-angle lens or a telephoto lens.

(33) The flash **220** may emit light that is used to reinforce light reflected from an object. According to an embodiment, the flash **220** may include one or more light emitting diodes (LEDs) (e.g., a red-green-blue (RGB) LED, a white LED, an infrared (IR) LED, or an ultraviolet (UV) LED) or a xenon lamp. The image sensor **230** may obtain an image corresponding to an object by converting light emitted or reflected from the object and transmitted via the lens assembly **210** into an electrical signal. According to an embodiment, the image sensor **230** may include one selected from image sensors having different attributes, such as a RGB sensor, a black-and-white (BW) sensor, an IR sensor, or a UV sensor, a plurality of image sensors having the same attribute, or a plurality of image sensors having different attributes. Each image sensor included in the image sensor **230** may be implemented using, for example, a charged coupled device (CCD) sensor or a complementary metal oxide semiconductor (CMOS) sensor.

(34) The image stabilizer **240** may move the image sensor **230** or at least one lens included in the lens assembly **210** in a particular direction, or control an operational attribute (e.g., adjust the read-out timing) of the image sensor **230** in response to the movement of the camera module **180** or the electronic device **101** including the camera module **180**. This allows compensating for at least part of a negative effect (e.g., image blurring) by the movement on an image being captured. According to an embodiment, the image stabilizer **240** may sense such a movement by the camera module **180** or the electronic device **101** using a gyro sensor (not shown) or an acceleration sensor (not shown) disposed inside or outside the camera module **180**. According to an embodiment, the image stabilizer **240** may be implemented, for example, as an optical image stabilizer.

(35) The memory **250** may store, at least temporarily, at least part of an image obtained via the image sensor **230** for a subsequent image processing task. For example, if image capturing is delayed due to shutter lag or multiple images are quickly captured, a raw image obtained (e.g., a Bayer-patterned image, a high-resolution image) may be stored in the memory **250**, and its corresponding copy image (e.g., a low-resolution image) may be previewed via the display device **160**. Thereafter, if a specified condition is met (e.g., by a user's input or system command), at least part of the raw image stored in the memory **250** may be obtained and processed, for example, by the image signal processor **260**. According to an embodiment, the memory **250** may be configured as at least part of the memory **130** or as a separate memory that is operated independently from the memory **130**.

(36) The image signal processor **260** may perform one or more image processing with respect to an image obtained via the image sensor **230** or an image stored in the memory **250**. The one or more image processing may include, for example, depth map generation, three-dimensional (3D) modeling, panorama generation, feature point extraction, image synthesizing, or image compensation (e.g., noise reduction, resolution adjustment, brightness adjustment, blurring, sharpening, or softening). Additionally or alternatively, the image signal processor **260** may perform control (e.g., exposure time control or read-out timing control) with respect to at least one (e.g., the image sensor **230**) of the components included in the camera module **180**. An image processed by the image signal processor **260** may be stored back in the memory **250** for further processing, or may be provided to an external component (e.g., the memory **130**, the display device **160**, the electronic device **102**, the electronic device **104**, or the server **108**) outside the camera module **180**. According to an embodiment, the image signal processor **260** may be configured as at least part of the processor **120**, or as a separate processor that is operated independently from the processor **120**. If the image signal processor **260** is configured as a separate processor from the processor **120**, at least one image processed by the image signal processor **260** may be displayed, by the processor **120**, via the display device **160** as it is or after being further processed.

(37) According to an embodiment, the electronic device **101** may include a plurality of camera modules **180** having different attributes or functions. In such a case, at least one of the plurality of camera modules **180** may form, for example, a wide-angle camera and at least another of the

plurality of camera modules **180** may form a telephoto camera. Similarly, at least one of the plurality of camera modules **180** may form, for example, a front camera and at least another of the plurality of camera modules **180** may form a rear camera.

(38) FIGS. **3A** and **3B** illustrate an electronic device including a camera module according to various embodiments. It is illustratively shown in FIG. **3B** that an electronic device **301** includes a folded camera module **350**, but not limited thereto.

(39) Referring to FIGS. **3A** and **3B**, an electronic device **301** (e.g., an electronic device **101** of FIG. **1**) may include a body part (or a housing) **305**, a display **310** (e.g., a display device **160** of FIG. **1**), and the folded camera module **350** (e.g., a camera module **180** of FIG. **1** or **2**).

(40) The body part (or the housing) **305** may mount the display **310** and the folded camera module **350**. The body part **305** may include various components, for example, a processor (e.g., a processor **120** of FIG. **1**), a memory (e.g., a memory **130** of FIG. **1**), communication circuitry (e.g., a communication module **190** of FIG. **1**), a printed circuit board, or a battery (e.g., a battery **189** of FIG. **1**), for driving the electronic device **301** therein.

(41) The display **310** may display various pieces of content, such as text or an image, on a first surface (e.g., a front surface) of the body part **305**. The display **310** may include a plurality of layers. For example, the display **310** may include a glass panel, a touch panel, or a display panel.

(42) At least a part of the folded camera module (or a folded camera structure) **350** may be exposed towards a second surface of the body part **305** (e.g., a rear surface, a surface where the display **310** does not output content, or a surface where a back cover is mounted). For example, a flash or a sensor unit of the folded camera module **350** may be exposed to the outside of the body part **305**. It is illustratively shown in FIG. **3B** that the camera module **350** is a rear camera, but not limited thereto. For example, the folded camera module **350** may be a front camera which is disposed in the same direction as the display **310**.

(43) According to various embodiments, the folded camera module **350** may include a prism (or a reflection mirror) **410** therein. The prism **410** may change a path of light introduced into the folded camera module **350**.

(44) According to various embodiments, the folded camera module **350** may include an optical splitter (not shown) (refer to FIG. **4**) and a plurality of image sensors (not shown) (refer to FIG. **4**) therein. Light reflected from the prism **410** may be split by the optical splitter to be introduced into the plurality of image sensors.

(45) FIG. **4** illustrates a structure of a folded camera module according to various embodiments.

(46) Referring to FIG. **4**, the folded camera module **350** may include a prism **410**, a driving part **420**, a magnetic body **430**, a lens part **440**, an optical splitter (or a beam splitter) **460**, a first image sensor **480**, and a second image sensor **490**. For example, when the folded camera module **350** is a telephoto camera, it is possible to ensure distances between the lens part **440** and the image sensors **480** and **490** and it may be easy to insert the optical splitter **460**. When the lens part **440** is a high magnification telephoto zoom lens, an FBL (a distance from the last lens to the image sensor) may be relatively long and an arrangement space of the optical splitter **460** may be ensured.

(47) The prism **410** may operate as a reflection mirror which changes a path of light introduced into the folded camera module **350**. Light reflected from the prism **410** may pass through the lens part **440** to be introduced into the optical splitter **460**.

(48) The driving part **420** may rotate the prism **410** in a first direction (e.g., a yaw direction) or a second direction (e.g., a pitch direction). The driving part **420** may operate according to a control signal of a processor (e.g., a processor **120** of FIG. **1**) or an image signal processor (e.g., an image signal processor **260** of FIG. **2**) included in the folded camera module **350**.

(49) The magnetic body **430** may move together depending on rotation of the prism **410**. Magnetic flux around the prism **410** may change according to movement of the magnetic body **430**.

(50) The lens part **440** may be disposed between the prism **410** and the optical splitter **460**. The lens part **440** may deliver light reflected from the prism **410** to the optical splitter **460**. For example,

when the lens part **440** is a high magnification telephoto zoom lens, an FBL (a distance from the last lens to the image sensor) may be relatively long and an arrangement space of the optical splitter **460** may be ensured.

(51) The optical splitter **460** may split light delivered from the lens part **440** to deliver the light to the first image sensor **480** or the second image sensor **490**. For example, the optical splitter **460** may be a prism, an inclined plane of which faces the lens part **440** and transmits a portion of light delivered from the lens part **440**. Visible light incident to the optical splitter **460** may be split into two by the inclined plane of the prism. For example, light transmitted through the optical splitter **460** may be incident to the first image sensor **480** implemented in a two-photo diode (hereinafter, 2PD) manner (that is, two photo diodes are arranged in one pixel in the first image sensor **480**), and light reflected from the optical splitter **460** may be incident to a single PD-type second image sensor **490** (that is, one photo diode is arranged in one pixel in the second image sensor **490**). For another example, the optical splitter **460** may be in the form of a plate including an inclined plane. Light transmitted through the optical splitter **460** in the form of the plate of the inclined plane may be incident to the first image sensor **480** implemented in the 2PD manner, and light reflected from the optical splitter **460** may be incident to the single PD-type second image sensor **490**.

(52) The first image sensor **480** may include a plurality of pixels implemented in the 2PD manner. The first image sensor **480** may convert light passing through the optical splitter **460** into an electronic image signal. The first image sensor **480** may read out electronic image data according to the photoelectric conversion effect, which is recorded in each pixel.

(53) According to various embodiments, a sensing surface of the first image sensor **480** may be disposed in a direction facing the lens part **440** (or a direction facing a side surface of an electronic device (an electronic device **101** of FIG. **1** or an electronic device **301** of FIGS. **3A** and **3B**)). When the thickness of the electronic device **101** or **301** is limited (when the electronic device **101** or **301** has a relatively thin thickness), the first image sensor **480** having a relatively large pixel in the 2PD manner may have limited resolution (the limited number of pixels). For example, when the first image sensor **480** and the second image sensor **490** have the same size, resolution of the 2PD-type first image sensor **480** may be lower than resolution of the single PD-type second image sensor **490**. For example, when the first image sensor **480** and the second image sensor **490** have the same size, the resolution of the first image sensor **480** may be 12 Mpx (4000*3000) and the resolution of the second image sensor **490** may be 48 Mpx (8000*6000).

(54) The second image sensor **490** may include a plurality of pixels implemented in the single PD manner. The second image sensor **490** may convert light reflected from the optical splitter **460** into an electronic image signal. The second image sensor **490** may read out electronic image data according to the photoelectric conversion effect, which is recorded in each pixel.

(55) According to various embodiments, a sensing surface of the second image sensor **490** may be disposed in a direction perpendicular to an optical axis of the lens part **440** (or a direction facing a front surface or a rear surface of the electronic device **101** or **301**).

(56) A pixel of the second image sensor **490** may be smaller in size than a pixel of the first image sensor **480**. Thus, the single PD-type second image sensor **490** may be higher in resolution than the 2PD-type first image sensor **480**. For example, when the first image sensor **480** and the second image sensor **490** have the same size, the resolution of the first image sensor **480** may be 12 Mpx (4000*3000) and the resolution of the second image sensor **490** may be 48 Mpx (8000*6000).

(57) According to various embodiments, the processor (e.g., the processor **120** of FIG. **1**) or the image signal processor (e.g., the image signal processor **260** of FIG. **2**) included in the folded camera module **350** may synthesize first image data obtained by the first image sensor **480** and second image data obtained by the second image sensor **490** in various manners (refer to FIG. **6**). The processor **120** or the image signal processor **260** may perform a specified function such as auto focus (AF) or may correct an image displayed to a user, using at least one of the first image data, the second image data, or the combined image data.

(58) According to various embodiments, the arrangement of the 2PD-type first image sensor **480** and the arrangement of the single PD-type second image sensor **490** may be exchanged with each other. For example, the 2PD-type first image sensor **480** may be disposed in a direction perpendicular to an optical axis of the lens part **440** to image light reflected from the optical splitter **460**. The single PD-type second image sensor **490** may be disposed in a direction facing the lens part **440** to image light passing through the optical splitter **460**.

(59) FIGS. 5A, 5B, and 5C illustrate a pixel structure in a first image sensor and a second image sensor according to various embodiments.

(60) Referring to FIG. 5A, a first image sensor **480** may include a plurality of pixels implemented in a 2PD manner. One pixel **510** among the plurality of pixels may include a microlens **505**, a color filter **506**, a first PD (or a first sub-pixel) (PD1) **511**, and a second PD (or a second sub-pixel) (PD2) **512**. The pixel **510** included in the first image sensor **480** may be larger in size than a pixel **550** included in the second image sensor **490** (e.g., two times larger). When the first image sensor **480** and the second image sensor **490** are the same in size, the first image sensor **480** may be lower in resolution than the second image sensor **490**. For example, when the first image sensor **480** and the second image sensor **490** have the same size, the resolution of the first image sensor **480** may be 12 Mpx (4000*3000) and the resolution of the second image sensor **490** may be 48 Mpx (8000*6000).

(61) The microlens **505** may cover the first PD **511** and the second PD **512**. The microlens **505** may adjust a path of an incident light such that light incident from the outside may arrive at the first PD **511** and the second PD **512**.

(62) The color filter **506** may be disposed between the microlens **505** and PDs (the first PD **511** and the second PD **512**) to pass light of a wavelength range corresponding to one of a first color (e.g., red) and a second color (e.g., blue). For example, the color filter **506** may allow the light of the wavelength range corresponding to one of a red color or a blue color in light passing through the microlens **505** to arrive at the first PD **511** and the second PD **512** and may block light of a wavelength range of a green color.

(63) Each of the first PD **511** and the second PD **512** may convert light passing through the microlens **505** and the color filter **506** into an electrical signal. As light introduced from the outside (e.g., light reflected from an object) may be refracted by the microlens **505**, a progress path thereof may be changed. Light passing through the microlens **505** may be directly introduced into PDs, or may be reflected from a pixel wall W between the PDs to be introduced into the PDs.

(64) According to various embodiments, when light reflected from the same point (or an adjacent point) of an external object is incident to the first PD **511** and the second PD **512**, an optical path difference may be generated by the microlens **505** or the pixel wall W. Thus, a phase difference may occur between data of the first PD **511** and data of the second PD **512**. The processor **120** or the image signal processor **260** may perform precise AF using the phase difference.

(65) According to various embodiments, the first image sensor **480** may obtain first image data where a first color (e.g., red) and a second color (e.g., blue) intersect each other to be arranged. The processor **120** or the image signal processor **260** may perform a specified function (e.g., AF) based on the first image data.

(66) Referring to FIG. 5C, the second image sensor **490** may include a plurality of single PD-type pixels. One pixel **550** among the plurality of pixels may include a microlens **555**, a color filter **556**, and a PD **561**. The pixel **550** may include one PD **561**. The pixel **550** included in the second image sensor **490** may be smaller in size than the pixel **510** included in the first image sensor **480** (e.g., $\frac{1}{2}$ times). When the first image sensor **480** and the second image sensor **490** are the same in size, the second image sensor **490** may be higher in resolution than the first image sensor **480** (e.g., four times higher).

(67) The microlens **555** may cover the PD **561**. The microlens **555** may adjust a path of an incident light such that light incident from the outside may arrive at the PD **561**.

(68) The color filter **556** may be disposed between the microlens **555** and the PD **561** and may pass

light of a wavelength range corresponding to a third color (e.g., green). The color filter **556** may allow light of a wavelength range corresponding to a green color in light passing through the microlens **555** to arrive at the PD **561** and may block light of a wavelength range corresponding to a red color or a blue color.

(69) The PD **561** may convert light passing through the microlens **555** and the color filter **556** into an electrical signal. As light introduced from the outside (e.g., light reflected from an object) may be refracted by the microlens **555**, a progress path thereof may be changed.

(70) According to various embodiments, the first image sensor **480** may obtain first image data where a first color (e.g., red) and a second color (e.g., blue) intersect each other to be arranged. The second image sensor **490** may obtain second image data configured with only the third color (e.g., green). The processor **120** or the image signal processor **260** may synthesize the first image data and second image data in various manners (refer to FIG. **6**).

(71) FIG. **6** illustrates synthesis of first image data and second image data according to various embodiments. FIG. **6** is illustrative, but not limited thereto. A scheme of synthesizing first image data **610** and second image data **620** may be variously applied.

(72) Referring to FIG. **6**, a first image sensor **480** may convert light passing through an optical splitter **460** into an electronic image signal to obtain the first image data **610**. First color (e.g., red) data and second color (e.g., blue) data may intersect each other to be arranged in the first image data **610**.

(73) A second image sensor **490** may convert light reflected from the optical splitter **460** into an electronic image signal to obtain the second image data **620**. Third color (e.g., green) data may be disposed in the entire region of the second image data **620**.

(74) For example, when the first image sensor **480** and the second image sensor **490** have the same size, the first image data **610** obtained by the 2PD-type first image sensor **480** may be lower in resolution than the second image data **620** obtained by the single PD-type second image sensor **490**. For example, when a pixel size of the first image sensor **480** is $1.4\ \mu\text{m}$ and when a pixel size of the second image sensor **490** is $0.7\ \mu\text{m}$, the first image data **610** may have resolution of 12 Mpx (4000×3000) and the second image data **620** may have resolution of 48 Mpx (8000×6000).

(75) According to various embodiments, a processor (e.g., a processor **120** of FIG. **1**) or an image signal processor (e.g., an image signal processor **260** of FIG. **2**) included in the folded camera module **350** may synthesize the first image data **610** and the second image data **620** to generate combination image data **630**. For example, the combination image data **630** may be an RGBG Bayer-patterned image.

(76) According to an embodiment, the combination image data **630** may have the same resolution as the second image data **620**.

(77) For example, a green color pixel (e.g., P11, P13, P22, or P24) in the combination image data **630** may have the same value as a corresponding pixel (e.g., G11, G13, G22, or G24) of the second image data **620**.

(78) For example, some (e.g., P12) of red color pixels of the combination image data **630** may have the same value as corresponding pixels (e.g., R11) of the first image data **610**. Some (e.g., P14) of red color pixels of the combination image data **630** may have the same value as a pixel (e.g., R11 or R22) adjacent to corresponding pixels of the first image data **610**.

(79) For example, some (e.g., P23) of blue color pixels of the combination image data **630** may have the same value as corresponding pixels (e.g., B12) of the first image data **610**. Some (e.g., P21) of blue color pixels of the combination image data **630** may have the same value as a pixel (e.g., B12 or B21) adjacent to corresponding pixels of the first image data **610**. The combination image data **630** may be displayed as a preview image or may be displayed as an image by means of a gallery app.

(80) According to various embodiments, the processor (e.g., the processor **120** of FIG. **1**) or the image signal processor (e.g., the image signal processor **260** of FIG. **2**) may reflect a pixel (e.g.,

G12, G14, G21, or G23) corresponding to a red color pixel or a blue color pixel of the combination image data **630** in the second image data **620** in a green color pixel (e.g., P11, P13, P22, or P24) of the combination image data **630**. For example, the processor or the image signal processor may replace data with much noise among green color pixels (e.g., P11, P13, P22, and P24) with adjacent pixels (e.g., G12, G14, G21, and G23) or may partially reflect the data with much noise in the adjacent pixels (e.g., G12, G14, G21, and G23).

(81) According to various embodiments, the second image data **620** may have twice the sensitivity of a composite image **630**. The processor (e.g., the processor **120** of FIG. **1**) or the image signal processor (e.g., the image signal processor **260** of FIG. **2**) included in the folded camera module **350** may improve low illumination performance of the combination image data **630** based on an analysis characteristic of the single color second image data **620**.

(82) An electronic device (e.g., an electronic device **101** of FIG. **1** or an electronic device **301** of FIGS. **3A** and **3B**) according to various embodiments may include a camera module (e.g., a camera module **180** of FIG. **1** or the folded camera module **350** of FIG. **3B**), a memory (e.g., a memory **130** of FIG. **1**), and a processor (e.g., a processor **120** of FIG. **1**) electrically connected with the camera module and the memory. The camera module (e.g., the camera module **180** of FIG. **1** or the folded camera module **350** of FIG. **3B**) may include a lens part, a first image sensor (e.g., a first image sensor **480** of FIG. **4**) having a two-photo diode (PD) pixel of a first color and a second color, a second image sensor (e.g., a second image sensor **490** of FIG. **4**) having a pixel of a third color, and an optical splitter (e.g., an optical splitter **460** of FIG. **4**) for splitting light introduced through the lens part. The optical splitter (e.g., the optical splitter **460** of FIG. **4**) may pass and input a first portion of the light introduced through the lens part to the first image sensor. The optical splitter (e.g., the optical splitter **460** of FIG. **4**) may reflect and input a second portion of the light introduced through the lens part to the second image sensor. The processor (e.g., the processor **120** of FIG. **1**) may combine first image data obtained by means of the first image sensor (e.g., the first image sensor **480** of FIG. **4**) and second image data obtained by means of the second image sensor (e.g., the second image sensor **490** of FIG. **4**) to generate third image data and may perform a specified function using at least one of the first image data, the second image data, or the generated third image data.

(83) According to various embodiments, a sensing surface of the first image sensor (e.g., the first image sensor **480** of FIG. **4**) may face a first direction, and a sensing surface of the second image sensor (e.g., the second image sensor **490** of FIG. **4**) may face a second direction perpendicular to the first direction.

(84) According to various embodiments, the first direction may be a direction facing a side surface of the electronic device (e.g., the electronic device **101** of FIG. **1** or an electronic device **301** of FIGS. **3A** and **3B**), and the second direction may be a direction facing a display (e.g., a display device **160** of FIG. **1** or a display **310** of FIG. **3A**) or a back cover of the electronic device (e.g., the electronic device **101** of FIG. **1** or an electronic device **301** of FIGS. **3A** and **3B**).

(85) According to an embodiment, the first direction may be a direction facing the lens part.

(86) According to various embodiments, the first direction may be a direction facing a display (e.g., a display device **160** of FIG. **1** or a display **310** of FIG. **3A**) or a back cover of the electronic device (e.g., the electronic device **101** of FIG. **1** or an electronic device **301** of FIGS. **3A** and **3B**), and the second direction may be a direction facing a side surface of the electronic device (e.g., the electronic device **101** of FIG. **1** or an electronic device **301** of FIGS. **3A** and **3B**).

(87) According to various embodiments, the first image data may have lower resolution than the second image data.

(88) According to various embodiments, the third image data may have the same resolution as the second image data.

(89) According to various embodiments, the processor (e.g., the processor **120** of FIG. **1**) may correct the third image data based on an analysis characteristic of the second image data.

(90) According to various embodiments, the processor (e.g., the processor **120** of FIG. **1**) may determine a value of a first type pixel (or a first pixel) of the first color in the third image data based on a value of a pixel of a position corresponding to the first type pixel or a pixel adjacent to the position in the first image data.

(91) According to various embodiments, the processor (e.g., the processor **120** of FIG. **1**) may determine a value of a second type pixel (or a second pixel) of the second color in the third image data based on a value of a pixel of a position corresponding to the second type pixel or a pixel adjacent to the position in the first image data.

(92) According to various embodiments, the processor (e.g., the processor **120** of FIG. **1**) may determine a value of a third type pixel (or a third pixel) of the third color in the third image data based on a value of a pixel of a position corresponding to the third type pixel in the second image data.

(93) According to various embodiments, the first image sensor (e.g., the first image sensor **480** of FIG. **4**) may be larger in pixel size than the second image sensor (e.g., the second image sensor **490** of FIG. **4**).

(94) According to various embodiments, the camera module (e.g., the camera module **180** of FIG. **1** or the folded camera module **350** of FIG. **3B**) may further include a first prism (e.g., a prism **410** of FIG. **4**) and may input light reflected from the first prism (e.g., the prism **410** of FIG. **4**) to the lens part.

(95) According to various embodiments, the optical splitter (e.g., the optical splitter **460** of FIG. **4**) may be a second prism, an inclined plane of which faces the lens part or the second image sensor (e.g., the second image sensor **490** of FIG. **4**).

(96) According to various embodiments, the optical splitter (e.g., the optical splitter **460** of FIG. **4**) may be in the form of a plate including an inclined plane.

(97) According to various embodiments, the lens part may be disposed between the first prism and the optical splitter (e.g., the optical splitter **460** of FIG. **4**).

(98) According to various embodiments, the camera module (e.g., the camera module **180** of FIG. **1** or the folded camera module **350** of FIG. **3B**) may be a telephoto camera, and the lens part may have a zoom magnification above a specified magnification.

(99) According to various embodiments, the function may be auto focus (AF). The processor (e.g., the processor **120** of FIG. **1**) may perform the auto focus (AF) based on a phase difference in data obtained from the 2PD pixel of the first image sensor (e.g., the first image sensor **480** of FIG. **4**).

(100) According to various embodiments, the electronic device (e.g., the electronic device **101** of FIG. **1** or the electronic device **301** of FIGS. **3A** and **3B**) may further include a display (e.g., a display device **160** of FIG. **1** or a display **310** of FIG. **3A**). The processor (e.g., the processor **120** of FIG. **1**) may display an image on the display (e.g., the display device **160** of FIG. **1** or the display **310** of FIG. **3A**) based on the third image data.

(101) According to various embodiments, the third image data may be an RGBG Bayer-patterned image.

(102) The electronic device according to various embodiments may be one of various types of electronic devices. The electronic devices may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance. According to an embodiment of the disclosure, the electronic devices are not limited to those described above.

(103) It should be appreciated that various embodiments of the disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly

indicates otherwise. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(104) As used in connection with various embodiments of the disclosure, the term “module” may include a unit implemented in hardware, software, or firmware, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(105) Various embodiments as set forth herein may be implemented as software (e.g., the program **140**) including one or more instructions that are stored in a storage medium (e.g., internal memory **136** or external memory **138**) that is readable by a machine (e.g., the electronic device **101**). For example, a processor (e.g., the processor **120**) of the machine (e.g., the electronic device **101**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it, with or without using one or more other components under the control of the processor. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Wherein, the term “non-transitory” simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(106) According to an embodiment, a method according to various embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., compact disc read only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of the application store, or a relay server.

(107) According to various embodiments, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the multiple entities may be separately disposed in different components. According to various embodiments, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to various embodiments, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to various embodiments, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

Claims

1. An electronic device, comprising: a camera module; a memory; and a processor electrically connected with the camera module and the memory, wherein the camera module includes: a lens part; a first image sensor including a first pixel of a first color and a second pixel of a second color, wherein the second pixel is at a position adjacent to the first pixel; a second image sensor including a third pixel of a third color, wherein four pixels including the third pixel corresponds to the first pixel; and an optical splitter configured to: provide a first portion of a light introduced through the lens part to the first image sensor; and provide a second portion of the light introduced through the lens part to the second image sensor, and wherein the processor is configured to: obtain first image data including a first value of the first pixel and a second value of the second pixel from the first image sensor; obtain second image data including a third value of the third pixel from the second image sensor; and generate combined image data including four pixels using at least one of the first value, the second value and the third value, and wherein a value of the second color among the four pixels of the combined image data is generated using the second value of the second pixel at a position adjacent to the first pixel.
 2. The electronic device of claim 1, wherein a sensing surface of the first image sensor faces a first direction, and wherein a sensing surface of the second image sensor faces a second direction perpendicular to the first direction.
 3. The electronic device of claim 2, further comprising a display and a back cover, wherein the second direction is a direction facing the display or the back cover of the electronic device.
 4. The electronic device of claim 2, wherein the first direction is a direction facing the lens part.
 5. The electronic device of claim 2, further comprising a display and a back cover, wherein the first direction is a direction facing the display or the back cover of the electronic device.
 6. The electronic device of claim 1, wherein the first image data has a lower resolution than the second image data.
 7. The electronic device of claim 1, wherein the combined image data has the same resolution as the second image data.
 8. The electronic device of claim 1, wherein the processor is further configured to correct the combined image data based on an analysis characteristic of the second image data.
 9. The electronic device of claim 1, wherein the first image sensor is a larger pixel size than the second image sensor.
 10. The electronic device of claim 1, wherein the camera module further includes a first prism and is configured to provide a light reflected from the first prism to the lens part.
 11. The electronic device of claim 10, wherein the optical splitter includes a second prism, and wherein an inclined plane of the second prism faces the lens part or the second image sensor.
 12. The electronic device of claim 10, wherein the optical splitter is in a form of a plate including an inclined plane.
 13. The electronic device of claim 10, wherein the lens part is provided between the first prism and the optical splitter.
 14. The electronic device of claim 1, wherein the camera module is a telephoto camera, and wherein the lens part has a zoom magnification above a specified magnification.
 15. The electronic device of claim 1, wherein the processor performs auto focus (AF) using at least one of the first image data, the second image data, or the combined image data.
 16. The electronic device of claim 1, further comprising: a display, wherein the processor is further configured to control the display to display an image based on the combined image data.
 17. The electronic device of claim 1, wherein the combined image data is an RGBG Bayer-patterned image.
-

