

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408292
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Zeng; Miaomiao et al.

Wireless charger

Abstract

A wireless charger includes an upper housing assembly, a lower housing assembly, a magnetic sheet coil, and a heat dissipation ring. A concave structure is provided on an upper surface of the lower housing assembly, and the concave structure is coupled to the upper housing assembly to form a cavity structure. The cavity structure accommodates the magnetic sheet coil and the heat dissipation ring. The heat dissipation ring is embedded in the magnetic sheet coil and is in contact with the magnetic sheet coil. An upper surface of the heat dissipation ring is coupled to the upper housing assembly. A lower surface of the heat dissipation ring is coupled to a bottom of the concave structure of the lower housing assembly. The heat dissipation ring may transfer heat in the upper housing assembly to the bottom of the lower housing assembly.

Inventors: Zeng; Miaomiao (Dongguan, CN), Yang; Chao (Dongguan, CN), Guan; Zhipeng (Shenzhen, CN), Wang; Yong (Dongguan, CN), Wang; Zhao (Dongguan, CN), Gong; Yanan (Dongguan, CN), He; Li (Dongguan, CN), Zhu; Guli (Shenzhen, CN), Gu; Tong (Chengdu, CN), Li; Xiaozhen (Dongguan, CN)

Applicant: Huawei Digital Power Technologies Co., Ltd. (Shenzhen, CN)

Family ID: 83580130

Assignee: Huawei Digital Power Technologies Co., Ltd. (Shenzhen, CN)

Appl. No.: 18/347831

Filed: July 06, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240015923 A1	Jan. 11, 2024

Foreign Application Priority Data

CN	202210795078.1	Jul. 07, 2022
----	----------------	---------------

Publication Classification

Int. Cl.: H05K7/20 (20060101); H02J50/00 (20160101)

U.S. Cl.:

CPC H05K7/20154 (20130101); H02J50/005 (20200101);

Field of Classification Search

CPC: H05K (7/20154); H02J (50/005)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11317544	12/2021	Zeng	N/A	H02K 1/20

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
207234482	12/2017	CN	H02J 7/00
209217759	12/2018	CN	N/A
209497287	12/2018	CN	N/A
112311048	12/2020	CN	N/A
112383153	12/2020	CN	F25B 21/02

OTHER PUBLICATIONS

CN 112383153 A Eng translation (Year: 2021). cited by examiner
CN 207234482 U Eng translation (Year: 2018). cited by examiner
CN 209497287 U, Eng translation (Year: 2019). cited by examiner

Primary Examiner: Patel; Mukundbhai G

Attorney, Agent or Firm: Maier & Maier, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims priority to Chinese Patent Application No. 202210795078.1, filed on Jul. 7, 2022, which is hereby incorporated by reference in its entirety.

TECHNICAL FIELD

(2) The embodiments relate to the field of wireless charging technologies and a wireless charger.

BACKGROUND

(3) With development of wireless charging technologies, an electronic device may be charged by using a wireless charger. The wireless charger converts electrical energy into a wireless charging signal and transmits the wireless charging signal to the to-be-charged electronic device, so as to implement a wireless charging function. The existing wireless charger has disadvantages such as

being unsteady in structure, poor in internal heat dissipation, and slow in charging speed, which are not conducive to product promotion and use.

SUMMARY

(4) To resolve the foregoing problem, the embodiments may provide a wireless charger, including an upper housing assembly, a lower housing assembly, a magnetic sheet coil, and a heat dissipation ring. A concave structure is provided on an upper surface of the lower housing assembly, and the concave structure is coupled to the upper housing assembly to form a cavity structure. The cavity structure accommodates the magnetic sheet coil and the heat dissipation ring. The heat dissipation ring is embedded in the magnetic sheet coil and is in contact with the magnetic sheet coil. An upper surface of the heat dissipation ring is coupled to the upper housing assembly. A lower surface of the heat dissipation ring is coupled to a bottom of the concave structure of the lower housing assembly. When heat in an electronic device is transferred to the upper housing assembly, the heat dissipation ring may transfer heat in the upper housing assembly to the bottom of the lower housing assembly, so that a heat dissipation area of the electronic device is increased, and heat dissipation capabilities of the wireless charger and the electronic device are improved.

(5) The embodiments may provide a wireless charger, including an upper housing assembly, a lower housing assembly, a magnetic sheet coil, and a heat dissipation ring, where a concave structure is provided on an upper surface of the lower housing assembly, the concave structure is coupled to the upper housing assembly to form a cavity structure, the magnetic sheet coil is sleeved outside the heat dissipation ring, and a gap among the upper housing assembly, the concave structure, the magnetic sheet coil, and the heat dissipation ring is filled with a thermally conductive adhesive. An upper surface of the heat dissipation ring is coupled to a lower surface of the upper housing assembly, a lower surface of the heat dissipation ring is coupled to a bottom of the concave structure of the lower housing assembly, and an outer side surface of the heat dissipation ring is coupled to the magnetic sheet coil. The upper surface of the heat dissipation ring is a surface that is of the heat dissipation ring and that is close to the upper housing assembly, the lower surface of the heat dissipation ring is a surface that is of the heat dissipation ring and that is close to the bottom of the concave structure of the lower housing assembly, and the lower surface of the upper housing assembly is a surface that is of the upper housing assembly and that constitutes the cavity structure. The heat dissipation ring is configured to conduct heat of the upper housing assembly and the magnetic sheet coil to the bottom of the concave structure of the lower housing assembly.

(6) In an implementation, a limiting magnet is further included, where the limiting magnet is disposed inside the heat dissipation ring, an upper surface of the limiting magnet is coupled to the lower surface of the upper housing assembly, and a lower surface of the limiting magnet is coupled to the bottom of the concave structure of the lower housing assembly. The upper surface of the limiting magnet is a surface that is of the limiting magnet and that is close to the upper housing assembly, and the lower surface of the limiting magnet is a surface that is of the limiting magnet and that is close to the bottom of the concave structure of the lower housing assembly. The limiting magnet is configured to transfer heat of the upper housing assembly to the bottom of the concave structure of the lower housing assembly.

(7) In an implementation, a thermally conductive adhesive is provided between the upper surface of the limiting magnet and the lower surface of the upper housing assembly, and a thermally conductive adhesive is provided between the lower surface of the limiting magnet and the bottom of the concave structure of the lower housing assembly.

(8) In an implementation, a thermally conductive adhesive is provided between the heat dissipation ring and the limiting magnet.

(9) In an implementation, a thermally conductive adhesive is provided between the upper surface of the heat dissipation ring and the upper housing assembly, and a thermally conductive adhesive is provided between the lower surface of the heat dissipation ring and the bottom of the concave structure of the lower housing assembly.

- (10) In an implementation, the magnetic sheet coil is coupled to the lower surface of the upper housing assembly, and a thermally conductive adhesive is provided between the magnetic sheet coil and the lower surface of the upper housing assembly.
- (11) In an implementation, the magnetic sheet coil includes a magnetic sheet assembly and a coil assembly, a circular groove is provided in the magnetic sheet assembly to accommodate the coil assembly, and a thermally conductive adhesive is provided in the circular groove of the magnetic sheet assembly.
- (12) In an implementation, the heat dissipation ring is made of a high thermally conductive material.
- (13) In an implementation, the upper housing assembly is made of a high thermally conductive material. When the wireless charger wirelessly charges an electronic device, the upper housing assembly conducts heat of the electronic device to the lower housing assembly by using the heat dissipation ring.
- (14) In an implementation, the upper housing assembly conducts the heat of the electronic device to the lower housing assembly.
- (15) In an implementation, the upper housing assembly conducts the heat of the electronic device to the lower housing assembly by using the thermally conductive adhesive.
- (16) In an implementation, the heat dissipation ring conducts heat of the magnetic sheet coil to the lower housing assembly.
- (17) In an implementation, the limiting magnet conducts the heat of the magnetic sheet coil to the lower housing assembly.
- (18) In an implementation, the thermally conductive adhesive conducts the heat of the magnetic sheet coil to the lower housing assembly and the upper housing assembly.
- (19) In an implementation, the concave structure includes a coil supporting plane, the magnetic sheet coil is disposed on the coil supporting plane, and the coil supporting plane conducts the heat of the magnetic sheet coil to the lower housing assembly.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The following briefly describes the accompanying drawings that need to be used in the descriptions of the embodiments or a conventional technology.
- (2) FIG. 1 is a schematic diagram of a scenario in which a wireless charger charges an electronic device according to an embodiment;
- (3) FIG. 2 is a schematic diagram of a top-view structure of a wireless charger according to an embodiment;
- (4) FIG. 3 is an exploded diagram of a structure of a wireless charger according to an embodiment;
- (5) FIG. 4 is a schematic diagram of a cross-sectional structure of a wireless charger according to an embodiment;
- (6) FIG. 5 is a schematic diagram of a concave structure of a lower housing assembly of a wireless charger according to an embodiment;
- (7) FIG. 6 is a schematic diagram of a top-view structure of a lower housing assembly of a wireless charger according to an embodiment;
- (8) FIG. 7 is a schematic diagram of a structure of an upper housing assembly of a wireless charger according to an embodiment;
- (9) FIG. 8 is a schematic diagram of a structure of a magnetic sheet coil of a wireless charger according to an embodiment;
- (10) FIG. 9 is a schematic diagram of a cross-sectional structure of a magnetic sheet coil of a wireless charger according to an embodiment;

- (11) FIG. **10** is a schematic diagram of a structure of an electronic device and a wireless charger thereof according to an embodiment;
- (12) FIG. **11** is a schematic diagram of a structure of a limiting magnet of a wireless charger according to an embodiment;
- (13) FIG. **12** is a schematic diagram of a structure of another limiting magnet of a wireless charger according to an embodiment;
- (14) FIG. **13** is a schematic diagram of a structure of another limiting magnet of a wireless charger according to an embodiment;
- (15) FIG. **14** is a schematic diagram of a position relationship among a magnetic sheet coil, a limiting magnet, and a heat dissipation ring of a wireless charger according to an embodiment;
- (16) FIG. **15** is a schematic diagram of a position relationship among a magnetic sheet coil, a limiting magnet, and a heat dissipation ring of another wireless charger according to an embodiment;
- (17) FIG. **16** is a schematic diagram of a position relationship among a magnetic sheet coil, a limiting magnet, and a heat dissipation ring of another wireless charger according to an embodiment;
- (18) FIG. **17** is a schematic diagram of a limiting magnet and a shielding assembly of a wireless charger according to an embodiment;
- (19) FIG. **18** is a schematic diagram of 18 combinations of a limiting magnet **230**, a shielding assembly **280**, and a thermally conductive adhesive according to an embodiment;
- (20) FIG. **19** is a schematic diagram of heat transfer among heat-emitting components such as a magnetic sheet coil and a limiting magnet of a wireless charger according to an embodiment; and
- (21) FIG. **20** is a schematic diagram of heat transfer when an electronic device is disposed on a wireless charger according to an embodiment.

DETAILED DESCRIPTION OF THE EMBODIMENTS

- (22) The following describes the embodiments with reference to the accompanying drawings.
- (23) In the descriptions, locations or position relationships indicated by terms “center”, “up”, “down”, “in front of”, “behind”, “left”, “right”, “vertical”, “horizontal”, “top”, “bottom”, “inside”, “outside”, and the like are based on locations or position relationships shown in the accompanying drawings, and may be intended for ease of describing the embodiments and simplifying descriptions, instead of indicating or implying that a mentioned apparatus or component needs to be provided on a location or constructed and operated on a location, and therefore shall not be understood as limitations.
- (24) In the descriptions, it should be noted that, unless otherwise clearly specified and limited, terms “mount”, “link”, and “connect” should be understood in a broad sense, for example, may mean a fixed connection, may be a detachable connection, or may be a butt joint connection or an integrated connection. Persons of ordinary skill in the art can understand meanings of the foregoing terms. In the embodiments, “contact” or “coupling” may mean direct contact between components or may mean contact between components by using a bonding agent or a thermally conductive adhesive.
- (25) In the descriptions, the described features, structures, materials, or characteristics may be combined in a proper manner in any one or more of embodiments or examples.
- (26) FIG. **1** is a schematic diagram of a scenario in which a charger charges an electronic device according to an embodiment. An electronic device **100** may be an electronic watch, a smartphone, a wireless headset, a tablet computer, a notebook computer, or the like. A wireless charger **200** may be a portable wireless charger, an in-vehicle wireless charger, or the like. During wireless charging, the electronic device **100** may be disposed on an upper surface of the wireless charger **200**, or a distance between the electronic device **100** and the wireless charger **200** is less than or equal to a charging distance. The wireless charger **200** converts electrical energy into a wireless charging signal. After receiving the wireless charging signal, the electronic device **100** converts the wireless

charging signal into electrical energy, to supply power to the electronic device **100**.

(27) In this embodiment, when the wireless charger **200** is disposed on a desktop, the “upper surface” is a surface that is of the wireless charger **200** and that is away from the desktop. The upper surface of the wireless charger **200** may be a substrate configured to carry the electronic device **100** or may be a housing of the wireless charger **200** or another structural part. In this embodiment, the surface may be a plane or a curved surface. By analogy, an upper surface of each component in the wireless charger **200** is a surface that is of the component and that is away from the desktop. A “lower surface” is a surface opposite to the “upper surface”. In this embodiment, “facing upward” means a direction pointing from the wireless charger **200** to the electronic device **100** during wireless charging. “Facing downward” is an opposite direction of “facing upward”.

(28) FIG. 2 to FIG. 4 are schematic diagrams of a wireless charger according to an embodiment. As shown in FIG. 2 to FIG. 4, a wireless charger **200** is in a shape of a cylinder. In another embodiment, the wireless charger **200** may alternatively be in another shape such as an elliptic cylinder or a polygonal column.

(29) As shown in FIG. 3, the wireless charger **200** includes an upper housing assembly **210**, a magnetic sheet coil **220**, a limiting magnet **230**, a heat dissipation ring **240**, a lower housing assembly **250**, a circuit board **260**, and a cable **270**. The upper housing assembly **210** is coupled to the lower housing assembly **250** to form a housing of the wireless charger **200**. A concave structure is provided on an upper surface of the lower housing assembly **250**. After the upper housing assembly **210** is coupled to the concave structure of the lower housing assembly **250**, a cavity structure is formed between the upper housing assembly **210** and the lower housing assembly **250**. The cavity structure is used to accommodate the magnetic sheet coil **220**, the limiting magnet **230**, the heat dissipation ring **240**, and the circuit board **260**. The lower housing assembly **250** is provided with a through hole, which enables the cable **270** to enter the cavity structure. The cable **270** is electrically connected to the circuit board **260**.

(30) As shown in FIG. 3, top-view shapes of the upper housing assembly **210**, the limiting magnet **230**, and the lower housing assembly **250** are round shapes, and top-view shapes of the magnetic sheet coil **220** and the heat dissipation ring **240** are circular ring shapes. In this embodiment, the top-view shape of the lower housing assembly **250** is related to a shape of the wireless charger **200**. The overall shape of the wireless charger **200** is a cylinder, and the lower housing assembly **250** is in a shape of a cylinder. The upper housing assembly **210**, the magnetic sheet coil **220**, the limiting magnet **230**, the heat dissipation ring **240**, and the lower housing assembly **250** may be in other shapes.

(31) The concave structure is provided on the upper surface of the lower housing assembly **250**. The upper housing assembly **210** is coupled at an outlet of the concave structure of the lower housing assembly **250**, and the cavity structure is formed between the upper housing assembly **210** and the lower housing assembly **250**. The cavity structure is used to accommodate components such as the magnetic sheet coil **220**, the limiting magnet **230**, the heat dissipation ring **240**, and the circuit board **260**.

(32) As shown in FIG. 3, a top-view shape of the concave structure of the lower housing assembly **250** is a round shape. In another embodiment, the top-view shape of the concave structure of the lower housing assembly **250** may alternatively be another shape such as a rectangle, an ellipse, or a polygon. A radius of the concave structure of the lower housing assembly **250** is equal to or slightly greater than a radius of the upper housing assembly **210**. The upper housing assembly **210** is disposed at the outlet of the concave structure of the lower housing assembly **250**, the upper housing assembly **210** is embedded into the concave structure of the lower housing assembly **250**, and an upper surface of the upper housing assembly **210** and the upper surface of the lower housing assembly **250** are on a same plane.

(33) In an embodiment, the lower housing assembly **250** includes a side plate and a bottom plate. In this embodiment, the wireless charger **200** is in a shape of a cylinder, the side plate of the lower

housing assembly **250** is in a shape of a toroidal column, and the bottom plate of the lower housing assembly **250** is in a shape of a round plate. In another embodiment, the bottom plate of the lower housing assembly **250** is in a shape the same as that of the upper housing assembly **210**.

(34) In an assembly process, the bottom plate of the lower housing assembly **250** is fastened to an opening on one side of the side plate of the lower housing assembly **250**, to form the lower housing assembly **250** with the concave structure. The upper housing assembly **210** is fastened to an opening on the other side of the side plate of the lower housing assembly **250**. The upper housing assembly **210**, the side plate of the lower housing assembly **250**, and the bottom plate of the lower housing assembly **250** constitute the cavity structure. In this embodiment, the lower housing assembly **250** is split into two parts: the bottom plate and the side plate, and may be divided into two components for manufacturing, so that a manufacturing difficulty of the lower housing assembly **250** is reduced.

(35) FIG. 5 and FIG. 6 are schematic diagrams of a lower housing assembly of a wireless charger according to an embodiment. A plurality of supporting planes may be provided in the concave structure of the lower housing assembly **250** of the wireless charger **200** provided in this embodiment, and are respectively used to support a plurality of components of the upper housing assembly **210**, the magnetic sheet coil **220**, the limiting magnet **230**, the heat dissipation ring **240**, or the circuit board **260**.

(36) The upper housing assembly **210**, the magnetic sheet coil **220**, the limiting magnet **230**, the heat dissipation ring **240**, or the circuit board **260** is in contact with the plurality of supporting planes of the lower housing assembly **250** respectively, and the lower housing assembly **250** transfers heat to gas outside of the wireless charger **200**, so that a heat dissipation capability of the wireless charger **200** is improved.

(37) As shown in FIG. 5, an upper housing supporting plane **251** is provided on an inner side wall of the concave structure of the lower housing assembly **250**. The upper housing supporting plane **251** is close to the upper surface of the lower housing assembly **250** and is close to an opening of the concave structure of the lower housing assembly **250**. The upper housing supporting plane **251** is used to support the upper housing assembly **210**.

(38) In this embodiment, a depth of the upper housing supporting plane **251** is a distance between the upper housing supporting plane **251** and the upper surface of the lower housing assembly **250**.

(39) In an embodiment, the depth of the upper housing supporting plane **251** is equal to a thickness of the upper housing assembly **210**. The upper housing supporting plane **251** supports the upper housing assembly **210**, and the upper surface of the upper housing assembly **210** and the upper surface of the lower housing assembly **250** are on a same plane.

(40) In another embodiment, the depth of the upper housing supporting plane **251** may be slightly greater than the thickness of the upper housing assembly **210**. Correspondingly, a bonding agent may be added between the upper housing assembly **210** and the upper housing supporting plane **251**, and the upper surface of the upper housing assembly **210** and the upper surface of the lower housing assembly **250** are on a same plane. The upper surface of the upper housing assembly **210** and the upper surface of the lower housing assembly **250** are on a same plane, so that the upper surface of the wireless charger **200** is flat, which helps the upper surface of the wireless charger **200** support an electronic device.

(41) In this embodiment, a width of the upper housing supporting plane **251** is a difference between an inner radius and an outer radius of the upper housing supporting plane **251**. In an embodiment, the inner radius of the upper housing supporting plane **251** is less than the radius of the upper housing assembly **210**. The upper housing assembly **210** is disposed in the concave structure of the lower housing assembly **250**, and the upper housing supporting plane **251** supports the upper housing assembly **210**. In an embodiment, the inner radius of the upper housing supporting plane **251** is greater than an outer radius of the magnetic sheet coil **220**. The magnetic sheet coil **220** is disposed in the concave structure of the lower housing assembly **250**, and the magnetic sheet coil

220 may pass through the upper housing supporting plane **251**.

(42) As shown in FIG. 5, a coil supporting plane **252** may be further provided in the concave structure of the lower housing assembly **250**. The coil supporting plane **252** is used to support the magnetic sheet coil **220**. The coil supporting plane **252** is located between the upper housing supporting plane **251** and the bottom of the concave structure of the lower housing assembly **250**. The coil supporting plane **252** supports the magnetic sheet coil **220**, and a gap between the bottom of the concave structure of the lower housing assembly **250** and the magnetic sheet coil **220** is used to accommodate the circuit board **260**.

(43) In this embodiment, a depth of the coil supporting plane **252** is a distance between the coil supporting plane **252** and the upper surface of the lower housing assembly **250**. The depth of the coil supporting plane **252** is greater than or equal to a sum of a thickness of the magnetic sheet coil **220** and the thickness of the upper housing assembly **210**.

(44) In an embodiment, a distance between the coil supporting plane **252** and the upper housing supporting plane **251** is slightly greater than the thickness of the magnetic sheet coil **220**. The upper housing assembly **210** and the magnetic sheet coil **220** are disposed in the concave structure of the lower housing assembly **250**, and there is a gap between the upper housing assembly **210** and the magnetic sheet coil **220**. The gap between the upper housing assembly **210** and the magnetic sheet coil **220** may be filled with a thermally conductive adhesive. The upper housing assembly **210**, the magnetic sheet coil **220** and the coil supporting plane **252** may constitute a longitudinal limiting structure. In addition, the upper surface of the upper housing assembly **210** is deformed due to an external force, and deformation of the upper housing assembly **210** does not squeeze the magnetic sheet coil **220**, so as to avoid damage to the magnetic sheet coil **220**.

(45) In an embodiment, the distance between the coil supporting plane **252** and the upper housing supporting plane **251** is equal to the thickness of the magnetic sheet coil **220**. Correspondingly, the upper housing assembly **210**, the magnetic sheet coil **220** and the coil supporting plane **252** may constitute a longitudinal limiting structure.

(46) As shown in FIG. 6, a top-view shape of the coil supporting plane **252** is a partially annular shape. In an embodiment, a circular sector angle corresponding to the coil supporting plane **252** is greater than or equal to 180 degrees.

(47) In this embodiment, a width of the coil supporting plane **252** is a difference between an inner radius and an outer radius of the coil supporting plane **252**. The outer radius of the magnetic sheet coil **220** is greater than or equal to the inner radius of the coil supporting plane **252**. In an embodiment, the outer radius of the coil supporting plane **252** is equal to the inner radius of the upper housing supporting plane **251**. In an embodiment, the inner radius of the coil supporting plane **252** is greater than an outer radius of the heat dissipation ring **240**, the outer radius of the heat dissipation ring **240** is not greater than an inner radius of the magnetic sheet coil **220**, and the heat dissipation ring **240** may pass through the magnetic sheet coil **220** and the coil supporting plane **252**. The magnetic sheet coil **220** is sleeved on the heat dissipation ring **240**.

(48) As shown in FIG. 6, the coil supporting plane **252** is formed by using a fence-shaped support body. The fence-shaped support body is provided on the bottom of the concave structure of the lower housing assembly **250**, and an upper surface of the fence-shaped support body is the coil supporting plane **252**. The fence-shaped support body is fixedly connected to the bottom and the inner side wall of the concave structure of the lower housing assembly **250**. In an embodiment, the lower housing assembly **250** includes a fence-shaped support body, and the fence-shaped support body includes one arc-shaped fence and a plurality of column-shaped fences. The arc-shaped fence is fastened on the bottom of the concave structure of the lower housing assembly **250**, and the arc-shaped fence is parallel to the inner side wall of the concave structure of the lower housing assembly **250**. The plurality of column-shaped fences may be fastened on the bottom of the concave structure of the lower housing assembly **250**. Each column-shaped fence is connected between the inner side wall of the concave structure of the lower housing assembly **250** and the

arc-shaped fence. The plurality of column-shaped fences may provide radial support for the arc-shaped fence. The heat dissipation ring **240** is mounted in the concave structure of the lower housing assembly **250**. Under the action of a radial support force provided by the plurality of column-shaped fences, a position of the coil supporting plane **252** does not change due to extrusion of the heat dissipation ring **240**.

(49) In an embodiment, the arc-shaped fence and the column-shaped fences of the fence-shaped support body are of a same height, so that a supporting plane of the coil supporting plane **252** is flat. The magnetic sheet coil **220** is disposed on the coil supporting plane **252**, so that damage caused by an uneven force on the magnetic sheet coil **220** can be avoided.

(50) In an embodiment, the plurality of column-shaped fences may be provided between the inner side wall of the concave structure of the lower housing assembly **250** and the arc-shaped fence at an equal spacing. In another embodiment, the plurality of column-shaped fences may be provided between the inner side wall of the concave structure of the lower housing assembly **250** and the arc-shaped fence in another arrangement manner.

(51) In an embodiment, the plurality of column-shaped fences may be separated, and a gap is formed among the column-shaped fences, the arc-shaped fence, and the inner side wall of the concave structure of the lower housing assembly **250f** and is used to be filled with a thermally conductive adhesive. Correspondingly, heat generated by the magnetic sheet coil **220** may not only be transferred to the lower housing assembly **250** by using the fence-shaped support body of the coil supporting plane **252**, but also be transferred to the lower housing assembly **250** by using the thermally conductive adhesive, so that a heat dissipation capability of the wireless charger **200** is improved.

(52) The coil supporting plane **252** of the wireless charger **200** provided in this embodiment is formed by using the fence-shaped support body, so that a material for manufacturing the lower housing assembly **250** can be reduced, thereby reducing costs and a weight of the wireless charger **200**. In addition, the coil supporting plane **252** is formed by using the fence-shaped support body, so that a watermark can be prevented from being formed on a lower surface of the lower housing assembly **250**, thereby avoiding affecting an appearance of the wireless charger **200**.

(53) In this embodiment, the wireless charger **200** may further include the limiting magnet **230** and/or the heat dissipation ring **240**. As shown in FIG. 5, a magnet supporting plane **253** may be further provided in the concave structure of the lower housing assembly **250**. In this embodiment, a middle area of the bottom of the concave structure of the lower housing assembly **250** may be used as a supporting plane of the limiting magnet **230** and/or the heat dissipation ring **240**, and the supporting plane is subsequently referred to as the magnet supporting plane **253**.

(54) In this embodiment, a depth of the magnet supporting plane **253** is a depth of the concave structure of the lower housing assembly **250**. In an embodiment, a lower surface of the upper housing assembly **210** is flat, and the depth of the magnet supporting plane **253** is greater than a sum of a height of the limiting magnet **230** and the thickness of the upper housing assembly **210**. In an embodiment, there is a protrusion structure on the lower surface of the upper housing assembly **210**, and the depth of the magnet supporting plane **253** is greater than a sum of the height of the limiting magnet **230**, the thickness of the upper housing assembly **210**, and a height of the protrusion structure on the lower surface of the upper housing assembly **210**.

(55) In an embodiment, the lower surface of the upper housing assembly **210** is flat, and the depth of the magnet supporting plane **253** is greater than a sum of a height of the heat dissipation ring **240** and the thickness of the upper housing assembly **210**.

(56) In an embodiment, there is a protrusion structure on the lower surface of the upper housing assembly **210**, and the depth of the magnet supporting plane **253** is greater than a sum of the height of the heat dissipation ring **240**, the thickness of the upper housing assembly **210**, and the height of the protrusion structure on the lower surface of the upper housing assembly **210**.

(57) In another embodiment, the height of the limiting magnet **230** is different from that of the heat

dissipation ring **240**, and a depth of a part supporting the limiting magnet **230** in the magnet supporting plane **253** may be different from a depth of a part supporting the heat dissipation ring **240**.

(58) In this embodiment, the limiting magnet **230** is of a columnar structure, and the magnetic sheet coil **240** is of an annular structure. The magnetic sheet coil **240** is disposed on the coil supporting plane **252**. The limiting magnet **230** is disposed on the magnet supporting plane **253**. At least a part of the limiting magnet **230** passes through the annular structure of the magnetic sheet coil **240**.

(59) In an embodiment, the limiting magnet **230** and the heat dissipation ring **240** are mounted in the concave structure of the lower housing assembly **250**, there is a gap between the upper housing assembly **210** and the limiting magnet **230**, and there is a gap between the upper housing assembly **210** and the heat dissipation ring **240**. The upper surface of the upper housing assembly **210** is deformed due to an external force, and deformation of the upper housing assembly **210** does not squeeze the limiting magnet **230** and the heat dissipation ring **240**, so as to avoid damage to the limiting magnet **230** and the heat dissipation ring **240**. In an embodiment, the gap between the upper housing assembly **210** and the limiting magnet **230** and the gap between the upper housing assembly **210** and the heat dissipation ring **240** may be filled with a thermally conductive adhesive, to improve heat dissipation efficiency of the wireless charger **200**.

(60) As shown in FIG. 7, an isolation plate **254** is provided on the magnet supporting plane **253** and is used to limit positions of the limiting magnet **230** and the heat dissipation ring **240**. In an embodiment, the limiting magnet **230** is disposed on the magnet supporting plane **253**, and the limiting magnet **230** is located on an inner side of the isolation plate **254**. In an embodiment, the heat dissipation ring **240** is disposed between a side face of the fence-shaped support body of the coil supporting plane **252** and the isolation plate **254**. The isolation plate **254** is provided between the limiting magnet **230** and the heat dissipation ring **240**, so as to avoid a case in which a volume of the heat dissipation ring **240** becomes larger after the heat dissipation ring **240** absorbs heat, and an extrusion pressure generated by the heat dissipation ring **240** damages the limiting magnet **230**.

(61) In this embodiment, a shape of the isolation plate **254** is related to space reserved between the limiting magnet **230** and the heat dissipation ring **240** and may be another shape such as an ellipse or a polygon. This is not limited. In an embodiment, a top-view shape of the limiting magnet **230** is a round shape, a top-view shape of the heat dissipation ring **240** is a circular ring shape, and a top-view shape of the isolation plate **254** is a circular ring shape. An inner radius of the isolation plate **254** is greater than or equal to a radius of the limiting magnet **230**, and an outer radius of the isolation plate **254** is less than or equal to an inner radius of the heat dissipation ring **240**. In an embodiment, the magnet supporting plane **253** is provided with an annular protrusion **254**, which is used to isolate the limiting magnet **230** from the heat dissipation ring **240**. In an embodiment, the magnet supporting plane **253** is provided with an annular isolation plate **254**, which is used to isolate the limiting magnet **230** from the heat dissipation ring **240**.

(62) As shown in FIG. 4, a receiving cavity is formed among the magnetic sheet coil **220**, the bottom of the concave structure of the lower housing assembly **250**, the inner side wall of the concave structure of the lower housing assembly **250**, and the heat dissipation ring **240**, and is used to accommodate the circuit board **260** and the cable **270**. A top-view shape of the receiving cavity and the top-view shape of the coil supporting plane **252** constitute a circular ring shape.

(63) A part that is of the bottom of the concave structure of the lower housing assembly **250** and that constitutes the receiving cavity is a circuit board supporting plane **256**. The circuit board supporting plane **256** is located on the bottom of the concave structure of the lower housing assembly **250** and is located at an edge of the bottom of the concave structure of the lower housing assembly **250**. The circuit board supporting plane **256** is used to support the circuit board **260**. As shown in FIG. 6, the circuit board supporting plane **256** is located on the bottom of the concave structure of the lower housing assembly **250** and is located at an edge of the magnet supporting plane **253**. A top-view shape of the circuit board supporting plane **256** and the top-view shape of

the coil supporting plane **252** constitute a circular ring shape.

(64) A through hole **255** is provided on the inner side wall that is of the concave structure of the lower housing assembly **250** and that corresponds to the receiving cavity. A wiring trough **257** is provided on the bottom that is of the concave structure of the lower housing assembly **250** and that corresponds to the receiving cavity. The wiring trough **257** is communicated with the through hole **255**. A wire of the circuit board **260** is connected to an external circuit by using the wiring trough **257** and the through hole **255**.

(65) In this embodiment, a depth of the circuit board supporting plane **256** is a distance between a plane on which the circuit board supporting plane **256** is located and the upper surface of the lower housing assembly **250**. In an embodiment, the lower surface of the upper housing assembly **210** is flat, and the depth of the circuit board supporting plane **256** is greater than a sum of the thickness of the upper housing assembly **210**, the thickness of the magnetic sheet coil **220**, and a thickness of the circuit board **260**.

(66) In an embodiment, there is a protrusion structure on the lower surface of the upper housing assembly **210**, and the depth of the circuit board supporting plane **256** is greater than a sum of the thickness of the upper housing assembly **210**, a height of the protrusion structure on the lower surface of the upper housing assembly **210**, the thickness of the magnetic sheet coil **220**, and the thickness of the circuit board **260**.

(67) In an embodiment, the depth of the circuit board supporting plane **256** may be different from that of the magnet supporting plane **253**.

(68) In an embodiment, a height difference between the circuit board supporting plane **256** and the coil supporting plane **252** is equal to or slightly greater than the thickness of the circuit board **260**. After the circuit board **260** and the magnetic sheet coil **220** are respectively disposed on the circuit board supporting plane **256** and the coil supporting plane **252**, there is a gap between the circuit board **260** and the magnetic sheet coil **220**, so as to prevent the circuit board **260** from being damaged by an extrusion pressure generated by the magnetic sheet coil **220**.

(69) As shown in FIG. **6**, the lower housing assembly **250** is provided with the through hole **255**. The cable **270** may pass through the through hole **255** and enter the concave structure of the lower housing assembly **250**. The cable **270** may be electrically connected to the circuit board **260**, so that the circuit board **260** provides electrical energy for the wireless charger **200**. The through hole **255** is located on the inner side wall of the concave structure of the lower housing assembly **250** and is located on a part that is of the inner side wall of the concave structure of the lower housing assembly **250** and that constitutes the receiving cavity. In another embodiment, a shape of the through hole **255** may be a round shape, an ellipse, or another shape. This is not limited.

(70) As shown in FIG. **6**, the circuit board supporting plane **256** is provided with the wiring trough **257**. The through hole **255** is located on the bottom of the concave structure of the lower housing assembly **250** and is located at a part that is of the concave structure of the lower housing assembly **250** and that constitutes the receiving cavity. The wiring trough **257** is communicated with the through hole **255**, and a wire of the circuit board **260** is connected to an external circuit by using the wiring trough **257** and the through hole **255**. the circuit board **260** may be an independent component. The circuit board **260** is electrically connected to the cable **270**, and the cable **270** is welded to an endpoint on a surface of the circuit board **260**, which causes a protrusion on the surface of the circuit board **260**. The circuit board **260** is disposed on the circuit board supporting plane **256**, and the protrusion of the circuit board **260** and the cable **270** are trapped in the wiring trough **257**, so that the circuit board **260** is better disposed on the circuit board supporting plane **256**.

(71) In an embodiment, a central axis of the through hole **255** and a central axis of the wiring trough **257** are in a straight line. In an embodiment, the central axis of the through hole **255** and the central axis of the wiring trough **257** are not in a straight line, and the cable **270** needs to be bent, so as to dispose the circuit board **260** on the circuit board supporting plane **256**. The cable **270** is

easy to break after being bent, which reduces reliability of the wireless charger **200**. Further, if the central axis of the through hole **255** and the central axis of the wiring trough **257** are not in a straight line, a distance between an extension line of the central axis of the through hole **255** and an extension line of the central axis of the wiring trough **257** may be less than a specified threshold. The specified threshold is a maximum range in which the cable **270** is not easy to break.

(72) In this embodiment, the lower housing assembly **250** is provided with the upper housing supporting plane **251**, the coil supporting plane **252**, the magnet supporting plane **253**, the circuit board supporting plane **256**, and the like. The upper housing supporting plane **251** supports the upper housing assembly **210**. The coil supporting plane **252** supports the magnetic sheet coil **220**. The magnet supporting plane **253** supports the limiting magnet **230** and the heat dissipation ring **240**. The circuit board supporting plane **256** supports the circuit board **260**. A plurality of supporting planes of the wireless charger **200** may support the components at different positions, to avoid overlapping of the components. If the wireless charger **200** is affected by an external force, all the components that are overlapped together may be damaged. As a result, reliability of the wireless charger **200** is reduced.

(73) In addition, top-view shapes of the magnetic sheet coil **220** and the heat dissipation ring **240** are circular ring shapes, and a top-view shape of the limiting magnet **230** is a round shape. With the limitation of the coil supporting plane **252** and the magnet supporting plane **253**, the magnetic sheet coil **220**, the limiting magnet **230**, and the heat dissipation ring **240** may be sleeved together. This improves integration of the components and facilitates miniaturization of the wireless charger **200**. Correspondingly, the inner side wall of the concave structure of the lower housing assembly **250** and the heat dissipation ring **240** constitute a transverse limiting structure of the magnetic sheet coil **220**, so that structural stability of the wireless charger **200** can be improved.

(74) FIG. 7 is a schematic diagram of a structure of an upper housing assembly of a wireless charger according to an embodiment. The upper housing assembly **210** is a part of the housing of the wireless charger **200**. In a wireless charging process, the upper surface of the upper housing assembly **210** is in contact with a lower surface of the electronic device **100**. In this embodiment, a top-view shape of the upper housing assembly **210** is related to the shape of the wireless charger **200**. In an embodiment, the shape of the wireless charger **200** is a cylinder, and the top-view shape of the upper housing assembly **210** is a round shape.

(75) As shown in FIG. 7, a periphery of the upper surface of the upper housing assembly **210** is flat, and the concave structure **211** is provided in a middle of the upper surface of the upper housing assembly **210**. The concave structure **211** of the upper housing assembly **210** is used to support the electronic device **100** and limit a position of the electronic device **100**. A bottom of the concave structure **211** of the upper housing assembly **210** is flat.

(76) The electronic device **100** is disposed on the wireless charger **200**, and a protrusion structure on the lower surface of the electronic device **100** is embedded into the concave structure on the upper surface of the upper housing assembly **210**. The lower surface of the electronic device **100** is in contact with the upper surface of the upper housing assembly **210**, so that a distance between a wireless charging coil of the electronic device **100** and a coil assembly **222** of the wireless charger **200** can be reduced, thereby reducing an electrical energy loss of the wireless charger. In another embodiment, the upper surface of the upper housing assembly **210** may be flat.

(77) As shown in FIG. 7, the concave structure **211** of the upper housing assembly **210** is truncated cone shaped. In an embodiment, the concave structure of the upper housing assembly **210** is in a shape of a truncated cone-shaped column. A radius of a bottom of the concave structure **211** of the upper housing assembly **210** is less than a radius of an opening of the concave structure **211** of the upper housing assembly **210**. In another embodiment, the concave structure **211** of the upper housing assembly **210** may alternatively be in another shape such as a cylinder or a cuboid. This is not limited.

(78) The concave structure **211** is provided on the upper surface of the upper housing assembly **210**

of the wireless charger **200** provided in this embodiment. The concave structure **211** on the upper surface of the upper housing assembly **210** may be coupled to a protrusion structure of the electronic device **100**, so that a distance between the electronic device **100** and the wireless charger **200** can be shortened, and an electrical energy loss of wireless charging can be reduced. In addition, the concave structure **211** is provided on the upper surface of the upper housing assembly **210**, so that a surface area of the upper surface of the wireless charger **200** can be increased, and a contact area between the wireless charger **200** and the electronic device **100** can be increased, thereby improving heat dissipation efficiency of the wireless charger **200**.

(79) In addition, in a wireless charging process, the electronic device **100** is disposed on the upper surface of the upper housing assembly **210** of the wireless charger **200**. The protrusion structure of the electronic device **100** is embedded into the concave structure **211** of the upper housing assembly **210**, and the protrusion structure of the electronic device **100** may be in contact with the concave structure **211** of the upper housing assembly **210**. The periphery of the upper surface of the upper housing assembly **210** is in contact with the lower surface of the electronic device **100**. Heat of the electronic device **100** is transferred to the housing of the wireless charger **200**, so that a heat dissipation area of the electronic device **100** is increased, and reduction of a temperature of the electronic device **100** is accelerated.

(80) As shown in FIG. 7, a truncated cone-shaped protrusion structure **212** may be further disposed on the lower surface of the upper housing assembly **210**. The lower surface of the upper housing assembly **210** is a surface that is of the upper housing assembly **210** and that constitutes the cavity structure. In another embodiment, the protrusion structure **212** of the upper housing assembly **210** may alternatively be in another shape, such as a cylinder or a cuboid. This is not limited herein.

(81) In an embodiment, the protrusion structure **212** is disposed at a middle position of the lower surface of the upper housing assembly **210**. The upper housing assembly **210** and the lower housing assembly **250** constitute the cavity structure, and a top of the protrusion structure **212** of the upper housing assembly **210** is coupled to at least one of the limiting magnet **230** or the heat dissipation ring **240**.

(82) In an embodiment, the upper housing assembly is made of a high thermally conductive material. The top of the protrusion structure **212** of the upper housing assembly **210** is coupled to at least one of the limiting magnet **230** and the heat dissipation ring **240**, and the upper housing assembly **210** conducts heat of the electronic device **100** to the lower housing assembly **250** by using the heat dissipation ring **240** and the limiting magnet **230**.

(83) In an embodiment, the protrusion structure **212** of the upper housing assembly **210** is in a shape of a truncated cone-shaped column. A radius of a bottom of the protrusion structure **212** of the upper housing assembly **210** is greater than a radius of the top of the protrusion structure **212** of the upper housing assembly **210**.

(84) In an embodiment, a top-view shape of the top of the protrusion structure **212** of the upper housing assembly **210** is a round shape. A top-view shape of the heat dissipation ring **240** is a circular ring shape. A radius of the top of the protrusion structure **212** of the upper housing assembly **210** is greater than or equal to the outer radius of the heat dissipation ring **240**.

(85) In an embodiment, a top-view shape of the bottom of the protrusion structure **212** of the upper housing assembly **210** is a round shape. A top-view shape of the magnetic sheet coil **220** is a circular ring shape. A radius of the bottom of the protrusion structure **212** of the upper housing assembly **210** is less than the inner radius of the magnetic sheet coil **220**.

(86) In an embodiment, the thickness of the upper housing assembly **210** is less than a difference between the depth of the concave structure of the lower housing assembly **250** and the height of the limiting magnet **230**. Alternatively, a thickness of the upper housing assembly **210** is less than a difference between the depth of the concave structure of the lower housing assembly **250** and the height of the heat dissipation ring **240**.

(87) As shown in FIG. 7, a circular notch **213** is further disposed on the lower surface of the upper

housing assembly **210**. The circular notch **213** is located around the protrusion structure **212** of the upper housing assembly **210** and is used to sleeve on the magnetic sheet coil **220**. A lower surface of the circular notch of the upper housing assembly **210** is coupled to an upper surface of the magnetic sheet coil **220**. The upper surface of the magnetic sheet coil **220** is a surface that is of the magnetic sheet coil **220** and that is close to the upper housing assembly **210**.

(88) In an embodiment, a top-view shape of the circular notch **213** of the upper housing assembly **210** is a circular ring shape. A top-view shape of the magnetic sheet coil **220** is a circular ring shape. An outer radius of the circular notch **213** of the upper housing assembly **210** is greater than the outer radius of the magnetic sheet coil **220**. An inner radius of the circular notch **213** of the upper housing assembly **210** is less than the inner radius of the magnetic sheet coil **220**.

(89) In an embodiment, an inner side of the circular notch **213** of the upper housing assembly **210** is higher than an outer side of the circular notch **213** of the upper housing assembly **210**.

(90) The magnetic sheet coil **220** is configured to convert electrical energy into a wireless charging signal. The magnetic sheet coil **220** is mounted on the coil supporting plane **252** of the lower housing assembly **250**. In a wireless charging process, after converting electrical energy into a wireless charging signal, the magnetic sheet coil **220** enables the wireless charging signal to radiate in a specified direction.

(91) FIG. **8** is a schematic diagram of a structure of a magnetic sheet coil of a wireless charger according to an embodiment. As shown in FIG. **8**, the magnetic sheet coil **220** includes a magnetic sheet assembly **221** and a coil assembly **222**. In this embodiment, the magnetic sheet assembly **221** is in a shape of a toroidal column. A circular groove is provided on an upper surface of the magnetic sheet assembly **221** and is used to accommodate the coil assembly **222**. An opening direction of the circular groove points to the upper housing assembly **210**.

(92) As shown in FIG. **8**, a top-view shape of the circular groove of the magnetic sheet assembly **221** is a circular ring shape. The coil assembly **222** is disposed in the circular groove of the magnetic sheet assembly **221**. A top-view shape of the coil assembly **222** is a circular ring shape. In this embodiment, top-view shapes of the magnetic sheet assembly **221**, the circular groove, and the coil assembly **222** are circular ring shapes with a shared center.

(93) In a process of assembling the magnetic sheet coil **220**, the coil assembly **222** is bent into a shape of the circular groove of the magnetic sheet assembly **221**. Then, an assembler disposes the coil assembly **222** in the circular groove of the magnetic sheet assembly **221**. Finally, the assembler adds a bonding agent or a thermally conductive adhesive to the circular groove of the magnetic sheet assembly **221**, to fasten the coil assembly **222** into the circular groove of the magnetic sheet assembly **221**. In this embodiment, the coil assembly **222** is fastened in the circular groove of the magnetic sheet assembly **221**, so as to avoid a change in a shape and a position of the coil assembly **222**, which causes a change in a position and charging power of the wireless charger **200** and reduces stability of the wireless charger **200**.

(94) In this embodiment, the magnetic sheet assembly **221** is made of a magnetic material with a low conductivity. The coil assembly **222** is disposed in the circular groove of the magnetic sheet assembly **221**. The magnetic sheet assembly **221** may shield a wireless charging signal radiated by the coil assembly **222** to a central area, so as to avoid an eddy current generated by the limiting magnet **240** disposed in a middle of an annular structure of the magnetic sheet coil **220**. This not only can improve an electrical energy conversion rate of the wireless charger **200**, but also can decelerate a temperature rise inside the wireless charger **200**.

(95) In an embodiment, an inner radius of the magnetic sheet assembly **221** is greater than or equal to the outer radius of the heat dissipation ring **240**, so that the heat dissipation ring **240** may be mounted on the magnet supporting plane **253** by passing through the magnetic sheet assembly **221**.

(96) In an embodiment, the inner radius of the magnetic sheet assembly **221** is greater than or equal to a radius of the protrusion structure **213** of the upper housing assembly **210**, so that the protrusion structure **213** of the upper housing assembly **210** may be in contact with the limiting magnet **230**.

and the heat dissipation ring **240**.

(97) In an embodiment, an outer radius of the magnetic sheet assembly **221** is less than or equal to the outer radius of the coil supporting plane **252** of the lower housing assembly **250**, so that the magnetic sheet assembly **221** may be disposed on the coil supporting plane **252** of the lower housing assembly **250**.

(98) In an embodiment, a thickness of the magnetic sheet assembly **221** is less than or equal to a distance between the upper housing supporting plane **251** and the coil supporting plane **252** of the lower housing assembly **250**, so that the magnetic sheet assembly **221** is disposed on the coil supporting plane **252** of the lower housing assembly **250**, to avoid affecting fastening of the upper housing assembly **210** to the upper housing supporting plane **251** of the lower housing assembly **250**.

(99) In this embodiment, a top-view cross-sectional area of an opening of the circular groove of the magnetic sheet assembly **221** is less than a top-view cross-sectional area of a bottom of the circular groove of the magnetic sheet assembly **221**. Alternatively, a top-view cross-sectional area of an opening of the circular groove of the magnetic sheet assembly **221** is less than a top-view cross-sectional area of any position between the opening of the circular groove of the magnetic sheet assembly **221** and a bottom of the circular groove of the magnetic sheet assembly **221**.

(100) As shown in FIG. 9, an outer side wall surface and an inner side wall surface of the circular groove of the magnetic sheet assembly **221** are oblique surfaces, so that the circular groove of the magnetic sheet assembly **221** is in a shape of a toroidal truncated cone-shaped column with the opening smaller than the bottom. The coil assembly **222** is disposed in the circular groove of the magnetic sheet assembly **221**, and a magnetic conductive material wraps the coil assembly **222** as much as possible. The magnetic sheet coil **220** is mounted in the wireless charger **200**, and the opening of the circular groove of the magnetic sheet assembly **221** faces the upper housing assembly **210**. When the wireless charger **200** performs wireless charging, a wireless charging signal generated by the coil assembly **222** radiates only to a direction of the electronic device **100**, so that an electrical energy conversion rate of the wireless charger **200** is improved.

(101) In another embodiment, the circular groove of the magnetic sheet assembly **221** may be in a shape of a toroidal column or in another shape. When the shape of the circular groove of the magnetic sheet assembly **221** is a toroidal column, the outer side wall surface of the circular groove of the magnetic sheet assembly **221** is parallel to an outer side wall surface of the magnetic sheet assembly **221**, and the inner side wall surface of the circular groove of the magnetic sheet assembly **221** is parallel to an inner side wall surface of the magnetic sheet assembly **221**.

(102) For example, the electronic device **100** is an electronic watch. Components such as a heart rate detection module and a temperature detection module may be mounted in a middle area of a charging coil of the electronic device **100**. When wireless charging is performed on the electronic device **100**, the components such as the heart rate detection module and the temperature detection module are located in a middle area of the coil assembly **222** of the wireless charger **200**. The circular groove of the magnetic sheet coil **220** in the wireless charger **200** provided in this embodiment may wrap the coil assembly **222**, to limit a direction in which the coil assembly **222** radiates a wireless charging signal, so that a vortex generated by the coil assembly **222** does not affect the components such as the heart rate detection module and the temperature detection module of the electronic device **100**.

(103) As shown in FIG. 8, a top-view shape of the magnetic sheet assembly **221** and the circular groove of the magnetic sheet assembly **221** is a circular ring shape. In an embodiment, a ratio of an outer radius to an inner radius of the circular groove of the magnetic sheet assembly **221** is greater than 1.9. In an embodiment, the ratio of the outer radius to the inner radius of the circular groove of the magnetic sheet assembly **221** is greater than 1.7. A smaller ratio between the inner radius and the outer radius of the circular groove of the magnetic sheet assembly **221** in the wireless charger **200** provided in this embodiment indicates a larger width of the top-view shape of the circular

groove of the magnetic sheet assembly **221**, and a larger area of the top-view shape of the coil assembly **222** that is accommodated by the circular groove of the magnetic sheet assembly **221**, so that a wireless charging area of the wireless charger **200** can be increased. After the width of the circular groove of the magnetic sheet assembly **221** is increased, a larger quantity of turns of the coil assembly **222** are accommodated by the circular groove of the magnetic sheet assembly **221**, so that wireless charging power of the wireless charger **200** can be increased. A larger depth of the circular groove of the magnetic sheet assembly **221** indicates a larger quantity of turns of the coil assembly **222** that can be accommodated by the circular groove of the magnetic sheet assembly **221**, and higher charging power of the wireless charger **200**.

(104) In an embodiment, the lower surface of the upper housing assembly **210** is flat, and heights of the magnetic sheet assembly **221** on two sides of the circular groove of the magnetic sheet assembly **221** may be the same. A direction of a wireless charging signal radiated by the magnetic sheet coil **220** is an upward direction perpendicular to the upper surface of the magnetic sheet coil **220**.

(105) In an embodiment, there is a protrusion structure **212** on the lower surface of the upper housing assembly **210**, and heights of the magnetic sheet assembly **221** on two sides of the circular groove of the magnetic sheet assembly **221** may be different. A height of the magnetic sheet assembly **221** on an inner side of the circular groove of the magnetic sheet assembly **221** is less than a height of the magnetic sheet assembly **221** on an outer side of the circular groove of the magnetic sheet assembly **221**. In another embodiment, the circular notch **213** is provided on the lower surface of the upper housing assembly **210**. The circular notch **213** on the lower surface of the upper housing assembly **210** is located around the protrusion structure **212**. In an assembly process, when the upper housing assembly **210** is mounted on the upper housing supporting plane **251**, the magnetic sheet assembly **221** is embedded in the circular notch **213** on the lower surface of the upper housing assembly **210**. In this embodiment, the circular notch **213** is provided on the lower surface of the upper housing assembly **210**, so that a depth of the circular groove of the magnetic sheet assembly **221** can be increased, thereby improving charging power of the wireless charger **200**.

(106) As shown in FIG. 8, the magnetic sheet assembly **221** is provided with a plurality of breaches. For example, the magnetic sheet assembly **221** is provided with a breach **2211** and a breach **2212**. The breach **2211** is used to limit an orientation of the magnetic sheet coil **220** mounted on the coil supporting plane **252**. In this embodiment, the magnetic sheet assembly **221** is in a shape of a toroidal column, and the breach **2211** is located on the outer side of the circular groove of the magnetic sheet assembly **221**. Correspondingly, a protrusion is provided on an outer edge of the coil supporting plane **252**. A shape of the protrusion of the coil supporting plane **252** matches a shape of the breach **2211** of the magnetic sheet assembly **221**. The magnetic sheet coil **220** is mounted on the coil supporting plane **252**, and the breach **2211** of the magnetic sheet assembly **221** is coupled to the protrusion of the coil supporting plane **252**. The breach **2211** of the magnetic sheet assembly **221** may limit an orientation in which the magnetic sheet coil **220** is mounted on the coil supporting plane **252**, so as to prevent the magnetic sheet coil **220** from rotating in the wireless charger **2000**. In another embodiment, a positioning part **2211** provided on the magnetic sheet assembly **221** may also be of another structure, such as a protrusion structure or a buckle.

(107) The breach **2212** is located on the outer side of the circular groove of magnetic sheet assembly **221**. The circuit board **260** may be located on a bottom of the magnetic sheet assembly **221**, so as to prevent the coil assembly **222** from generating a vortex on the circuit board **260**. Both ends of the coil assembly **222** pass through the wiring trough **2212** and are welded to an endpoint of the circuit board **260** by using solder. In another embodiment, the breach **2212** is located on the inner side of the circular groove of the magnetic sheet assembly **221**. The breach **2211** and the breach **2212** may be a same breach.

(108) In this embodiment, the magnetic sheet assembly **221** of the magnetic sheet coil **220** may replace the limiting magnet **230**. In an embodiment, the N pole of the limiting magnet of the electronic device **100** faces upward, and the S pole faces downward. After the magnetic sheet assembly **221** is magnetized, the N pole of the magnetic sheet assembly **221** faces upward, and the S pole faces downward. In an embodiment, the S pole of the limiting magnet of the electronic device **100** faces upward, and the N pole faces downward. After the magnetic sheet assembly **221** is magnetized, the S pole of the magnetic sheet assembly **221** faces upward, and the N pole faces downward. The electronic device **100** is disposed on the upper housing assembly **210** of the wireless charger **200**, and the electronic device **100** fits a specified position of the upper housing assembly **210** of the wireless charger **200** through limitation of the limiting magnets of the electronic device **100** and the wireless charger **200**.

(109) FIG. **10** is a schematic diagram of a structure of an electronic device **100** and a wireless charger **200** thereof according to an embodiment. The electronic device **100** may be a watch, a mobile phone, a headset, a tablet, a computer, or the like. The charger **200** may be a portable wireless charger, an in-vehicle wireless charger, or the like. For ease of describing a charging coil and a limiting magnet of an electronic device **100** or a charger **200**, other circuits or structures of the electronic device **100** and the wireless charger **200** are omitted in FIG. **10**.

(110) As shown in FIG. **10**, the electronic device **100** includes a wireless charging coil **110** and a limiting magnet **120**. The wireless charger **200** includes a magnetic sheet coil **220**. The magnetic sheet coil **220** includes a magnetic sheet assembly **221** and a coil assembly **222**. The coil assembly **222** is disposed in a circular groove of the magnetic sheet assembly **221**. An opening of the circular groove of the magnetic sheet assembly **221** faces upward.

(111) As shown in FIG. **10**, the wireless charger **200** is horizontally disposed on a desktop, and the electronic device **100** is stacked on the wireless charger **200**. The limiting magnet **120** of the electronic device **100** matches the magnetic sheet assembly **221** of the wireless charger **200** and limits the electronic device **100** to a specified position on an upper surface of the wireless charger **200**. Wireless charging may be performed after the charging coil **110** of the electronic device **100** matches the coil assembly **222** of the wireless charger **200**.

(112) FIG. **11** is a schematic diagram of a structure of a limiting magnet of a wireless charger according to an embodiment. A limiting magnet **230** of the wireless charger provided in this embodiment may include one independent magnet, for example, a cylindrical magnet or a magnet of a toroidal column. The limiting magnet **230** may include a plurality of magnets. For example, the limiting magnet **230** may be a cylindrical magnet formed by splicing a cylindrical magnet and a plurality of magnets of toroidal columns.

(113) As shown in FIG. **11**, a limiting magnet **230** includes a first magnet **231** and a second magnet **232**. The first magnet **231** and the second magnet **232** are adjacently disposed on a same surface. The first magnet **231** is of a cylindrical structure, and a top-view cross-sectional shape of the first magnet **231** is a round shape. The second magnet **232** is of an annular cylindrical structure, and a top-view cross-sectional shape of the second magnet **232** is a circular ring shape. An inner radial size of the second magnet **232** is greater than or equal to a radial size of the first magnet **231**. The first magnet **231** is disposed on an inner side of the second magnet **232**.

(114) In this embodiment, if the N pole of the first magnet **231** faces upward, the S pole faces downward, the N pole of the second magnet **232** faces an inner side of the circular ring, and the S pole faces an outer side of the circular ring, magnetic fields of the first magnet **231** and the second magnet **232** enhance each other on an upper side of the limiting magnet **230**, and magnetic adsorption between an upper side of a wireless charger **200** and a lower side of an electronic device **100** is enhanced, so that a contact position between the electronic device **100** and the wireless charger **200** can be better limited, and a charging coil of the electronic device **100** easily matches a charging coil of the wireless charger **200**, thereby improving convenience of wireless charging. The magnetic fields of the first magnet **231** and the second magnet **232** weaken each other on a lower

side of the limiting magnet **230**, and magnetic field strength on the lower side of the limiting magnet **230** weakens. This not only can reduce impact of the limiting magnet **230** in the wireless charger **200** on another magnetic sensitive device, but also can omit or reduce a soft magnetic material, so that heat dissipation and miniaturization of the wireless charger **200** are facilitated.

(115) As shown in FIG. **12**, the second magnet **232** includes a plurality of permanent magnet modules and the plurality of permanent magnet modules may be spliced to form an annular cylindrical structure. In this embodiment, a top-view cross-sectional shape of the plurality of permanent magnet modules in the second magnet **232** is an arc. The permanent magnet module may be a sector magnet with an angle of $360/M$ degrees. M is a quantity of permanent magnet modules that are spliced to form one circular ring-shaped permanent magnet and is greater than or equal to 2. In some embodiments, a top-view cross-sectional shape of the permanent magnet module may alternatively be a polygon such as a triangle or a quadrilateral. According to internal space of the charger **200**, permanent magnet modules of various shapes may be selected for the limiting magnet **230**, to improve applicability of the limiting magnet **230**.

(116) In some embodiments, the first magnet **231** of the limiting magnet **230** may include a plurality of permanent magnet modules and the plurality of permanent magnet modules may be spliced to form a cylindrical structure. In some embodiments, the second magnet **232** of the limiting magnet **230** may include only one permanent magnet module in a shape of an annular cylinder. In some embodiments, the first magnet **231** and the second magnet **232** of the limiting magnet **230** each include a plurality of permanent magnet modules. In other words, the plurality of permanent magnets in the limiting magnet **230** may each include one or more permanent magnet modules.

(117) In an embodiment, a magnetic field direction inside the first magnet **231** is perpendicular to a surface, and a magnetic field direction inside the second magnet **232** is parallel to the surface. The magnetic field direction inside the first magnet **231** is perpendicular to the magnetic field direction inside the second magnet **232**.

(118) In an embodiment, a magnetic field direction inside the first magnet **231** is parallel to a surface, and a magnetic field direction inside the second magnet **232** is perpendicular to the surface. The magnetic field direction inside the first magnet **231** is perpendicular to the magnetic field direction inside the second magnet **232**.

(119) In an embodiment, a top-view cross-sectional shape of the first magnet **231** is one of a round shape or a polygon, and a top-view cross-sectional shape of the second magnet **232** is an annular shape. The annular shape may be a circular ring shape or a polygonal ring shape.

(120) In an embodiment, the first magnet **231** and the second magnet **232** are fixedly connected to each other.

(121) In an embodiment, the first magnet **231** and the second magnet **232** are separately fastened on a surface of the concave structure of the lower housing assembly **250**.

(122) FIG. **13** is a schematic diagram of a structure of a limiting magnet according to an embodiment. As shown in FIG. **13**, a limiting magnet **230** includes a first assembly **231** and a second assembly **232**. The first assembly **231** and the second assembly **232** are disposed on a same surface along a first direction. The first assembly **231** and the second assembly **232** may be disposed on a same surface in a horizontal direction. A top-view cross-sectional shape of the first assembly **231** is in a circular ring shape, and the second assembly **232** is of a cylindrical structure. An inner radial size of the first assembly **231** is greater than or equal to a radial size of the second assembly **232**. The second assembly **232** is disposed on an inner side of the first assembly **231**. In an embodiment, the first assembly **231** and the second assembly **232** may be fixedly connected, to form an overall structure. In another embodiment, the first assembly **231** and the second assembly **232** may be separately fastened on a same surface, and there may be a gap or a filling material between the first assembly **231** and the second assembly **232**.

(123) The first assembly **231** includes a first magnet **231-1** and a second magnet **231-2**. The second

assembly **232** includes a second assembly **232**. The first magnet **231-1** and the second magnet **231-2** are disposed in a stacked manner along a second direction. The first magnet **231-1** and the second magnet **231-2** may be disposed vertically on the surface in a stacked manner. Top-view cross-sectional shapes of both the first magnet **231-1** and the second magnet **231-2** are circular ring shapes. In an embodiment, the first magnet **231-1** and the second magnet **231-2** may be fixedly connected to form an overall structure. In another embodiment, the first magnet **231-1** and the second magnet **231-2** may be separately fastened on a side face of the second assembly **232**, and there may be a gap or a filling material between the first magnet **231-1** and the second magnet **231-2**.

(124) In this embodiment, the S pole of the first magnet **231-1** faces an inner side of the circular ring, and the N pole faces an outer side of the circular ring. The N pole of the second magnet **231-2** faces the inner side of the circular ring, and the S pole faces the outer side of the circular ring. The S pole of the second assembly **232** faces upward, and the N pole faces downward. The S pole of the first magnet **231-1** and the S pole of the second assembly **232** enhance each other on an upper side of a magnetic suction apparatus **500**, so that magnetic field strength on the upper side of the magnetic suction apparatus **500** is enhanced.

(125) In an embodiment, there may be two or more magnets in the first assembly **231**. There may be two or more magnets in the second assembly **232**.

(126) In an embodiment, a magnetic field direction inside the magnets of the first assembly **231** is perpendicular to a surface, and a magnetic field direction inside the magnets of the second assembly **232** is parallel to the surface. The magnetic field direction inside the magnets of the first assembly **231** is perpendicular to the magnetic field direction inside the magnets of the second assembly **232**.

(127) In an embodiment, a magnetic field direction inside the magnets of the first assembly **231** is parallel to a surface, and a magnetic field direction inside the magnets of the second assembly **232** is perpendicular to the surface. The magnetic field direction inside the magnets of the first assembly **231** is perpendicular to the magnetic field direction inside the magnets of the second assembly **232**.

(128) In an embodiment, a top-view cross-sectional shape of the magnets of the first assembly **231** is one of a round shape or a polygon, and a top-view cross-sectional shape of the magnets of the second assembly **232** is an annular shape. The annular shape may be a circular ring shape or a polygonal ring shape.

(129) In an embodiment, the magnets in the first assembly **231** and the magnets in the second assembly **232** are fixedly connected.

(130) In an embodiment, the magnets in the first assembly **231** and the magnets in the second assembly **232** are separately fastened on a surface of the concave structure of the lower housing assembly **250**.

(131) In an embodiment, the magnet in the first assembly **231** is formed by splicing one or more sub-magnet modules. The magnet in the second assembly **232** is formed by splicing one or more sub-magnet modules.

(132) A position relationship among the magnetic sheet coil **220**, the limiting magnet **230**, and the heat dissipation ring **240** in the wireless charger **200** provided in this embodiment is not limited to the position relationship shown in FIG. **3**, and there may be another position relationship. For example, FIG. **14** to FIG. **16** are schematic diagrams of a position relationship among a magnetic sheet coil, a limiting magnet, and a heat dissipation ring of a wireless charger according to embodiments.

(133) As shown in FIG. **14**, a wireless charger **200** includes a magnetic sheet coil **220**, a limiting magnet **230**, and a heat dissipation ring **240**. A top-view shape of the magnetic sheet coil **220** is a circular ring shape. A top-view shape of the limiting magnet **230** is a circular ring shape. A top-view shape of the heat dissipation ring **240** is a round shape or a circular ring shape. In this case, an

outer radius of the magnetic sheet coil **220** is less than or equal to an inner radius of a coil supporting plane **252** of a lower housing assembly **250**. An outer radius of the limiting magnet **230** is less than or equal to an inner radius of the magnetic sheet coil **220**. An inner radius of the limiting magnet **230** is greater than or equal to an outer radius of the magnetic sheet coil **220**. A height of the limiting magnet **230** is the same as a height of the heat dissipation ring **240**, or a height of the limiting magnet **230** is different from a height of the heat dissipation ring **240**.

(134) The magnetic sheet coil **220** is disposed on the coil supporting plane **252** of the lower housing assembly **250**. The heat dissipation ring **240** is embedded in an annular structure of the magnetic sheet coil **220** and is fastened to a magnet supporting plane **253** of the lower housing assembly **250**. The limiting magnet **230** is embedded in the heat dissipation ring **240** and is fastened to the magnet supporting plane **253** of the lower housing assembly **250**. Correspondingly, the heat dissipation ring **240** is embedded between the limiting magnet **230** and the magnetic sheet coil **220**. In an embodiment, a gap among the heat dissipation ring **240**, the limiting magnet **230**, and the magnetic sheet coil **220** may be filled with a thermally conductive adhesive, so as to improve heat dissipation efficiency of the wireless charger **200**.

(135) As shown in FIG. **15**, a wireless charger **200** includes a magnetic sheet coil **220**, a limiting magnet **230**, and a heat dissipation ring **240**. A top-view shape of the magnetic sheet coil **220** is a circular ring shape. A top-view shape of the limiting magnet **230** is a circular ring shape. A top-view shape of the heat dissipation ring **240** is a round shape or a circular ring shape. In this case, an outer radius of the magnetic sheet coil **220** is less than or equal to an inner radius of a coil supporting plane **252** of a lower housing assembly **250**. An outer radius of the limiting magnet **230** is less than or equal to an inner radius of the magnetic sheet coil **220**. An inner radius of the limiting magnet **230** is greater than or equal to an outer radius of the heat dissipation ring **240**. A height of the magnetic sheet coil **220** is the same as a height of the limiting magnet **230**.

(136) In a process of assembling the wireless charger **200**, the magnetic sheet coil **220** is disposed on the coil supporting plane **252** of the lower housing assembly **250**. The limiting magnet **230** is embedded in the magnetic sheet coil **220** and is fastened to the coil supporting plane **252** of the lower housing assembly **250**. The heat dissipation ring **240** is embedded in the limiting magnet **230** and is fastened to a magnet supporting plane **253** of the lower housing assembly **250**.

(137) As shown in FIG. **16**, a wireless charger **200** includes a magnetic sheet coil **220**, a limiting magnet **230**, and a heat dissipation ring **240**. A top-view shape of the magnetic sheet coil **220** is a circular ring shape. A top-view shape of the limiting magnet **230** is a circular ring shape. A top-view shape of the heat dissipation ring **240** is a round shape or a circular ring shape. In this case, an outer radius of the limiting magnet **230** is less than or equal to an inner radius of a coil supporting plane **252** of a lower housing assembly **250**. An outer radius of the magnetic sheet coil **220** is less than or equal to an inner radius of the limiting magnet **230**. An inner radius of the magnetic sheet coil **220** is greater than or equal to an outer radius of the heat dissipation ring **240**. A height of the magnetic sheet coil **220** is the same as a height of the limiting magnet **230**.

(138) In a process of assembling the wireless charger **200**, the limiting magnet **230** is fastened to the coil supporting plane **252** of the lower housing assembly **250**. The magnetic sheet coil **220** is embedded in the limiting magnet **230** and is fastened to the coil supporting plane **252** of the lower housing assembly **250**. The heat dissipation ring **240** is embedded in the magnetic sheet coil **220** and is fastened to a magnet supporting plane **253** of the lower housing assembly **250**.

(139) The circuit board **260** of the wireless charger **200** provided in this embodiment may include a circuit such as an alternating current/direct current converter and a protective circuit. The alternating current/direct current converter converts an alternating current into a direct current or converts a direct current into an alternating current. The protective circuit enables the wireless charger **200** to be in an open circuit state when a short circuit occurs in the wireless charger **200**. In this embodiment, an input end of the circuit board **260** is electrically connected to the cable **270**, and an output end of the circuit board **260** is electrically connected to the coil assembly **222** of the

magnetic sheet coil **220**. In this embodiment, the circuit board **260** may also be referred to as a printed circuit board assembly (PCBA).

(140) As shown in FIG. **4**, the circuit board **260** is disposed in the receiving cavity of the lower housing assembly **250**. In this embodiment, a distance between a plane on which the circuit board supporting plane **256** is located and a plane on which the coil supporting plane **253** is located is greater than the thickness of the circuit board **260**.

(141) In an embodiment, the magnetic sheet coil **220** is disposed on the coil supporting plane **252** of the lower housing assembly **250**, the circuit board **260** is disposed on the circuit board supporting plane **256** of the lower housing assembly **250**, and there is a gap between an upper surface of the circuit board **260** and a lower surface of the magnetic sheet coil **220**. The upper surface of the magnetic sheet coil **220** deforms due to an external force, and the deformation of the magnetic sheet coil **220** does not squeeze the circuit board **260**, so as to avoid damage to the circuit board **260**.

(142) In an embodiment, the magnetic sheet coil **220** is disposed on the coil supporting plane **252** of the lower housing assembly **250**, and the circuit board **260** is fastened on the lower surface of the magnetic sheet coil **220** by using a bonding agent, so as to improve stability of the circuit board **260**.

(143) FIG. **17** is a schematic diagram of a limiting magnet and a shielding assembly of a wireless charger according to an embodiment. In this embodiment, the wireless charger **200** further includes a shielding assembly **280**. The shielding assembly **280** is made of a high electrical conductivity material, such as copper or aluminum. A thickness of the shielding assembly **280** is greater than a skin depth. The skin depth is a thickness of most charges when charges are transmitted in a conductor. If the thickness of the shielding assembly **280** is less than the skin depth, the shielding assembly **280** cannot effectively isolate a wireless charging signal.

(144) A shape of the shielding assembly **280** is related to a shape of the limiting magnet **230**. In an embodiment, the limiting magnet **230** is in a shape of a cylinder, and the shielding assembly **280** is in a shape of a hollow cylinder, a toroidal column, or the like. In an embodiment, the limiting magnet **230** is in a shape of a truncated cone-shaped column, and the shielding assembly **280** is in a shape of a hollow truncated cone-shaped column, a truncated cone-shaped annular column, or the like. The shielding assembly **280** may also be in another shape.

(145) The shape of the shielding assembly **280** is related to a shielding manner. The limiting magnet **230** is used as an example, and the limiting magnet **230** is in a shape of a cylinder. The shielding assembly **280** shields an entire surface of the limiting magnet **230**, and the shielding assembly **280** is in a shape of a hollow cylinder. The shielding assembly **280** shields a side face of the limiting magnet **230**, and the shielding assembly **280** is in a shape of a toroidal column. The shielding assembly **280** may also be in another shape.

(146) In this embodiment, the limiting magnet **230** is of a columnar structure, the heat dissipation ring **240** is of an annular structure, and the shielding assembly **280** disposed on an outer surface on a periphery of the limiting magnet **230** is in contact with an inner side surface of the heat dissipation ring **240**. In an embodiment, the limiting magnet **230** is of a cylindrical structure, the heat dissipation ring **240** is of a circular ring-shaped structure, and the shielding assembly **280** disposed on a side face of the limiting magnet **230** is in contact with an inner side surface of the heat dissipation ring **240**.

(147) In an embodiment, the shielding assembly **280** is disposed in a middle of the heat dissipation ring **240**, and the shielding assembly **280** is fastened to the heat dissipation ring **240** by using a bonding agent, so as to improve stability of the wireless charger **200**. In an embodiment, the shielding assembly **280** is disposed in the middle of the heat dissipation ring **240**, and a gap between the heat dissipation ring **240** and the shielding assembly **280** is filled with a thermally conductive adhesive, so as to improve heat transfer efficiency between components of the wireless charger **200**.

(148) As shown in FIG. 17, the shielding assembly 280 of the wireless charger 200 is disposed on the outer surface on the periphery of the limiting magnet 230. In this embodiment, the limiting magnet 230 is in a cylindrical shape, and the shielding assembly 280 is disposed on a side face of the limiting magnet 230. The shielding assembly 280 may prevent a wireless charging signal from being reflected to the limiting magnet 230 and prevent the wireless charging signal generated by the coil assembly 222 from forming a vortex on the limiting magnet 230, so as to avoid a temperature rise inside the wireless charger 200.

(149) In an embodiment, the shielding assembly 280 is further disposed on at least a part of an upper surface of the limiting magnet 230. In an embodiment, the shielding assembly 280 is further disposed on at least a part of a lower surface of the limiting magnet 230. In an embodiment, the shielding assembly 280 is further disposed on at least a part of the upper surface and at least a part of the lower surface of the limiting magnet 230. The upper surface of the limiting magnet 230 is a surface that is of the limiting magnet 230 and that is close to the upper housing assembly 210. The lower surface of the limiting magnet 230 is a surface that is of the limiting magnet 230 and that is close to the bottom of the concave structure of the lower housing assembly 250.

(150) In an embodiment, the shielding assembly 280 is further disposed on at least a part of an upper surface of the heat dissipation ring 240. In an embodiment, the shielding assembly 280 is further disposed on at least a part of a lower surface of the heat dissipation ring 240. In an embodiment, the shielding assembly 280 is further disposed on at least a part of the upper surface and at least a part of the lower surface of the heat dissipation ring 240. The upper surface of the heat dissipation ring 240 is a surface that is of the heat dissipation ring 240 and that is close to the upper housing assembly 210. The lower surface of the heat dissipation ring 240 is a surface of the heat dissipation ring 240 that is close to the bottom of the concave structure of the lower housing assembly 250.

(151) In an embodiment, the shielding assembly 280 disposed on the upper surface of the limiting magnet 230 is in contact with the lower surface of the upper housing assembly 210. In an embodiment, the shielding assembly 280 disposed on the upper surface of the heat dissipation ring 240 is in contact with the lower surface of the upper housing assembly 210.

(152) In an embodiment, the shielding assembly 280 disposed on the lower surface of the limiting magnet 230 is in contact with the bottom of the concave structure of the lower housing assembly 250. In an embodiment, the shielding assembly 280 disposed on the lower surface of the heat dissipation ring 240 is in contact with the bottom of the concave structure of the lower housing assembly 250.

(153) In an embodiment, the shielding assembly 280 disposed on the upper surface of the limiting magnet 230 and the shielding assembly 280 disposed on the upper surface of the heat dissipation ring 240 are on a same plane. In an embodiment, the shielding assembly 280 disposed on the lower surface of the limiting magnet 230 and the shielding assembly 280 disposed on the lower surface of the heat dissipation ring 240 are on a same plane.

(154) As shown in FIG. 18 (a), the shielding assembly 280 is mounted between the heat dissipation ring 240 and the limiting magnet 230. The shielding assembly 280 is in a shape of a toroidal column, and a top-view shape of an epitaxial edge is a circular ring shape. An opening at an upper end of the shielding assembly 280 is provided with the epitaxial edge, and an outer radius of the epitaxial edge is less than or equal to an inner radius of the magnetic sheet coil 220. The epitaxial edge of the shielding assembly 280 is disposed on the upper surface of the heat dissipation ring 240, so as to facilitate the assembler to mount the shielding assembly 280. The epitaxial edge of the shielding assembly 280 may be in contact with the magnetic sheet coil 220, so that a heat conduction loop is formed between the magnetic sheet coil 220 and the limiting magnet 230, thereby improving heat transfer efficiency between components of the wireless charger 200. A gap between the heat dissipation ring 240 and the shielding assembly 280 may be filled with a thermally conductive adhesive, so as to improve heat transfer efficiency between the components

of the wireless charger **200**.

(155) A part in FIG. **18 (b)** that is the same as that in FIG. **18 (a)** is not described again. As shown in FIG. **18 (b)**, a gap between the limiting magnet **230** and the magnet supporting plane **253** of the lower housing assembly **250** may be further filled with a thermally conductive adhesive, so as to improve heat transfer efficiency among the limiting magnet **230**, the heat dissipation ring **240**, and the lower housing assembly **250** in the wireless charger **200**.

(156) A part in FIG. **18 (c)** that is the same as that in FIG. **18 (a)** is not described again. As shown in FIG. **18 (c)**, the shielding assembly **280** is further disposed on a part of the upper surface of the limiting magnet **230**, so as to facilitate the assembler to mount the shielding assembly **280**.

(157) A part in FIG. **18 (d)** that is the same as that in FIG. **18 (c)** is not described again. As shown in FIG. **18 (d)**, a gap between the limiting magnet **230** and the magnet supporting plane **253** of the lower housing assembly **250** may be further filled with a thermally conductive adhesive, so as to improve heat transfer efficiency among the limiting magnet **230**, the heat dissipation ring **240**, and the lower housing assembly **250** in the wireless charger **200**.

(158) A part in FIG. **18 (e)** that is the same as that in FIG. **18 (c)** is not described again. As shown in FIG. **18 (e)**, the epitaxial edge of the shielding assembly **280** may be further disposed on the entire upper surface of the heat dissipation ring **240**. Correspondingly, a side face of the shielding assembly **280** may be in a shape of a toroidal column, and a top-view shape of the upper surface is a round shape.

(159) A part in FIG. **18 (f)** that is the same as that in FIG. **18 (e)** is not described again. As shown in FIG. **18 (f)**, a gap between the limiting magnet **230** and the magnet supporting plane **253** of the lower housing assembly **250** may be further filled with a thermally conductive adhesive, so as to improve heat transfer efficiency among the limiting magnet **230**, the heat dissipation ring **240**, and the lower housing assembly **250** in the wireless charger **200**.

(160) A part in FIG. **18 (g)** that is the same as that in FIG. **18 (a)** is not described again. As shown in FIG. **18 (g)**, the shielding assembly **280** is further disposed on a part of the lower surface of the limiting magnet **230**. The shielding assembly **280** does not completely cover the lower surface of the limiting magnet **230**, so as to prevent the shielding assembly **280** from preventing the limiting magnet **230** from transferring heat downwards.

(161) A part in FIG. **18 (h)** that is the same as that in FIG. **18 (g)** is not described again. As shown in FIG. **18 (h)**, a gap among the shielding assembly **280** disposed on the lower surface of the limiting magnet **230**, the limiting magnet **230**, and the magnet supporting plane **253** of the lower housing assembly **250** may be further filled with a thermally conductive adhesive, so as to improve heat transfer efficiency among the limiting magnet **230**, the shielding assembly **280**, and the lower housing assembly **250** in the wireless charger **200**.

(162) A part in FIG. **18 (i)** that is the same as that in FIG. **18 (g)** is not described again. As shown in FIG. **18 (i)**, the shielding assembly **280** is further disposed on a part of the upper surface of the limiting magnet **230**, so as to facilitate the assembler to mount the shielding assembly **280**.

(163) A part in FIG. **18 (j)** that is the same as that in FIG. **18 (i)** is not described again. As shown in FIG. **18 (j)**, a gap among the shielding assembly **280** disposed on the lower surface of the limiting magnet **230**, the limiting magnet **230**, and the magnet supporting plane **253** of the lower housing assembly **250** may be further filled with a thermally conductive adhesive, so as to improve heat transfer efficiency among the limiting magnet **230**, the shielding assembly **280**, and the lower housing assembly **250** in the wireless charger **200**.

(164) A part in FIG. **18 (k)** that is the same as that in FIG. **18 (i)** is not described again. As shown in FIG. **18 (k)**, the shielding assembly **280** is further disposed on the entire upper surface of the limiting magnet **230**, so as to prevent a wireless charging signal radiated by the coil assembly **222** from being reflected to the upper surface of the limiting magnet **230**.

(165) A part in FIG. **18 (l)** that is the same as that in FIG. **18 (k)** is not described again. As shown in FIG. **18 (l)**, a gap among the shielding assembly **280** disposed on the lower surface of the limiting

magnet **230**, the limiting magnet **230**, and the magnet supporting plane **253** of the lower housing assembly **250** may be further filled with a thermally conductive adhesive, so as to improve heat transfer efficiency among the limiting magnet **230**, the shielding assembly **280**, and the lower housing assembly **250** in the wireless charger **200**.

(166) A part in FIG. **18 (m)** that is the same as that in FIG. **18 (a)** is not described again. As shown in FIG. **18 (m)**, the shielding assembly **280** is further disposed on the entire lower surface of the limiting magnet **230**, so as to prevent a wireless charging signal radiated by the coil assembly **222** from being reflected to the lower surface of the limiting magnet **230**. In an embodiment, a gap between the shielding assembly **280** disposed on the lower surface of the limiting magnet **230** and the limiting magnet **230** may be further filled with a thermally conductive adhesive, so as to improve heat transfer efficiency between the limiting magnet **230** and the shielding assembly **280** in the wireless charger **200**.

(167) A part in FIG. **18 (n)** that is the same as that in FIG. **18 (m)** is not described again. As shown in FIG. **18 (n)**, a gap between the shielding assembly **280** disposed on the lower surface of the limiting magnet **230** and the magnet supporting plane **253** of the lower housing assembly **250** may be further filled with a thermally conductive adhesive, so as to improve heat transfer efficiency among the limiting magnet **230**, the shielding assembly **280**, and the lower housing assembly **250** in the wireless charger **200**.

(168) A part in FIG. **18 (o)** that is the same as that in FIG. **18 (m)** is not described again. As shown in FIG. **18 (o)**, the shielding assembly **280** is further disposed on a part of the upper surface of the limiting magnet **230**, so as to prevent a wireless charging signal radiated by the coil assembly **222** from being reflected to the upper surface of the limiting magnet **230**.

(169) A part in FIG. **18 (p)** that is the same as that in FIG. **18 (o)** is not described again. As shown in FIG. **18 (p)**, a gap between the shielding assembly **280** disposed on the lower surface of the limiting magnet **230** and the magnet supporting plane **253** of the lower housing assembly **250** may be further filled with a thermally conductive adhesive, so as to improve heat transfer efficiency among the limiting magnet **230**, the shielding assembly **280**, and the lower housing assembly **250** in the wireless charger **200**.

(170) A part in FIG. **18 (q)** that is the same as that in FIG. **18 (m)** is not described again. As shown in FIG. **18 (q)**, the shielding assembly **280** is further disposed on the entire upper surface of the limiting magnet **230**, so as to prevent the wireless charging signal radiated by the coil assembly **222** from being reflected to the upper surface of the limiting magnet **230**.

(171) A part in FIG. **18 (r)** that is the same as that in FIG. **18 (q)** is not described again. As shown in FIG. **18 (r)**, a gap between the shielding assembly **280** disposed on the lower surface of the limiting magnet **230** and the magnet supporting plane **253** of the lower housing assembly **250** may be further filled with a thermally conductive adhesive, so as to improve heat transfer efficiency among the limiting magnet **230**, the shielding assembly **280**, and the lower housing assembly **250** in the wireless charger **200**.

(172) The heat dissipation ring **240** in the wireless charger **200** provided in this embodiment is made of a material with a high thermal conductivity and a low electrical conductivity. The heat dissipation ring **240** is disposed on the magnet supporting plane **253**. The heat dissipation ring **240** is in contact with one or more of components such as the upper housing assembly **210**, the magnetic sheet coil **220**, the limiting magnet **230** and the circuit board **260**, and may transfer heat of the components such as the upper housing assembly **210**, the magnetic sheet coil **220**, the limiting magnet **230** and the circuit board **260** to the lower housing assembly **250**, so that a heat dissipation area of the wireless charger **200** is increased, and a heat dissipation capability of the wireless charger **200** is improved.

(173) In an embodiment, the heat dissipation ring **240** may be a part of the lower housing assembly **250**. The heat dissipation ring **240** and the lower housing assembly **250** are manufactured in an integrated molding manner. The heat dissipation ring **240** is located on the magnet supporting plane

253 of the lower housing assembly 250. The heat dissipation ring 240 and the lower housing assembly 250 are of an overall structure, so that a quantity of components of the wireless charger 200 can be reduced, and an assembly difficulty of the wireless charger 200 can be reduced.

(174) In an embodiment, the heat dissipation ring 240 and the lower housing assembly 250 are of an overall structure, and the magnet supporting plane 253 of the lower housing assembly 250 may be unnecessarily provided with the isolation plate 254. In a process of manufacturing the heat dissipation ring 240 and the lower housing assembly 250, an inner radius of the heat dissipation ring 240 is made to be greater than an outer radius of the limiting magnet 230. In an embodiment, there is no isolation plate 254 in the concave structure of the lower housing assembly 250, so that a manufacturing difficulty of the lower housing assembly 250 can be greatly reduced.

(175) In an embodiment, each of the heat dissipation ring 240 and the lower housing assembly 250 of the wireless charger 220 provided in this embodiment may be an independent component. A process of assembling the wireless charger 200 is as follows. Step 1: Dispose the heat dissipation ring 240 on the magnet supporting plane 253 of the lower housing assembly 250. The heat dissipation ring 240 may be in contact with and fastened to the magnet supporting plane 253 of the lower housing assembly 250 and the heat dissipation ring 240 may be in contact with and fastened to the inner side wall that is in a shape of a toroidal column and that is of the coil supporting plane 252 of the lower housing assembly 250. Step 2: Dispose the limiting magnet 230 on an inner side of the heat dissipation ring 240. The limiting magnet 230 may be in contact with and fastened to the magnet supporting plane 253 of the lower housing assembly 250 and the limiting magnet 230 may be in contact with and fastened to the inner side surface of the heat dissipation ring 240. Step 3: Pass the cable 270 through the through hole 255 of the lower housing assembly 250 and enable the cable 270 to be electrically connected to the circuit board 260. The cable 270 may be fastened to an endpoint on an outer side surface of the circuit board 260 in a manner such as welding. Step 4: Dispose the circuit board 260 on the circuit board supporting plane 256 of the lower housing assembly 250. A surface of a side of the circuit board 260 connected to the cable 270 may be in contact with and fastened to the circuit board supporting plane 256 and the cable 270 and a protrusion of the circuit board 260 may be trapped in the wiring trough 257 of the circuit board supporting plane 256. Step 5: Dispose the magnetic sheet coil 220 on the coil supporting plane 252 of the lower housing assembly 250. The magnetic sheet coil 220 may be in contact with and fastened to the coil supporting plane 252 of the lower housing assembly 250 and a coil endpoint of the magnetic sheet coil 220 may be electrically connected to an endpoint of the circuit board 260. The magnetic sheet coil 220 is embedded between an outer side surface of the heat dissipation ring 240 and an inner side wall of the concave structure of the lower housing assembly 250. The limiting magnet 230, the heat dissipation ring 240, the magnetic sheet coil 220, and the inner side wall of the concave structure of the lower housing assembly 250 constitute a transverse limiting structure. Step 6: Dispose the upper housing assembly 210 on the upper housing supporting plane 251 of the lower housing assembly 250. The upper housing assembly 210 may be in contact with and fastened to the upper housing supporting plane 251 of the lower housing assembly 250 and an upper surface of the upper housing assembly 210 and an upper surface of the lower housing assembly 250 may be on a same plane. A lower surface of the upper housing assembly 210 is in contact with an upper surface of the magnetic sheet coil 220. The upper housing assembly 210, the magnetic sheet coil 220 and the coil supporting plane 252 constitute a longitudinal limiting structure.

(176) In a process of assembling the wireless charger 200 in this embodiment, the heat dissipation ring 240, the limiting magnet 230, the circuit board 260, the magnetic sheet coil 220, and the upper housing assembly 210 are sequentially fastened to the magnet supporting plane 253, the circuit board supporting plane 256, the coil supporting plane 252, and the upper housing supporting plane 251 of the lower housing assembly 250 in a bottom-up order, so as to implement assembly of the wireless charger 200.

(177) In an embodiment, the heat dissipation ring **240** is a part of the lower housing assembly **250**. In a process of assembling the wireless charger **200**, the foregoing “step 1” may be omitted. The heat dissipation ring **240** and the lower housing assembly **250** are of an overall structure, so that a quantity of components of the wireless charger **200** can be reduced, so that the wireless charger **200** is assembled more easily, and assembly efficiency is improved.

(178) In an embodiment, each of the heat dissipation ring **240** and the lower housing assembly **250** is an independent component. The lower housing assembly **250** includes a bottom plate and side plates. A process of assembling the wireless charger **200** is as follows. Step 1: Dispose the heat dissipation ring **240** on the bottom plate of the lower housing assembly **250**. The heat dissipation ring **240** may be in contact with and fastened to the bottom plate of the lower housing assembly **250**. In this case, the bottom plate of the lower housing assembly **250** is the magnet supporting plane **253** of the lower housing assembly **250**. Step 2: Dispose the limiting magnet **230** on an inner side of the heat dissipation ring **240**. The limiting magnet **230** may be in contact with and fastened to the bottom plate of the lower housing assembly **250** and the limiting magnet **230** may be in contact with and fastened to the inner side surface of the heat dissipation ring **240**. Step 3: Pass the cable **270** through the through hole **255** of the side plate of the lower housing assembly **250** and enable the cable **270** to be electrically connected to the circuit board **260**. The cable **270** may be fastened to an endpoint on an outer surface of the circuit board **260** in a manner such as welding. Step 4: Dispose the circuit board **260** on the circuit board supporting plane **256** of the lower housing assembly **250**. A surface of a side of the circuit board **260** connected to the cable **270** may be in contact with and fastened to the circuit board supporting plane **256** and the cable **270** and a protrusion of the circuit board **260** may be trapped in the wiring trough **257** of the circuit board supporting plane **256**. Step 5: Dispose the magnetic sheet coil **220** on the coil supporting plane **252** of the side plate of the lower housing assembly **250**. The magnetic sheet coil **220** may be in contact with and fastened to the coil supporting plane **252** of the side plate of the lower housing assembly **250** and a coil endpoint of the magnetic sheet coil **220** may be electrically connected to an endpoint of the circuit board **260**.

(179) It should be noted that, in the process of assembling the wireless charger **200**, in “step 1” and “step 2”, the bottom plate of the lower housing assembly **250** is assembled as an assembly line, and in “step 3”, “step 4”, and “step 5”, the side plate of the lower housing assembly **250** is assembled as an assembly line. In the assembly process, the assembly line of the bottom plate of the lower housing assembly **250** and the assembly line of the side plate of the lower housing assembly **250** are not in a particular order. The two assembly lines may be performed simultaneously or may be performed one after the other. This is not limited herein. Step 6: Dispose the side plate of the lower housing assembly **250** on the bottom plate of the lower housing assembly **250**. The side plate of the lower housing assembly **250** may be embedded on the bottom plate of the lower housing assembly **250**, so that the heat dissipation ring **240** is in contact with and fastened to the inner side wall that is in a shape of a toroidal column and that is of the coil supporting plane **252** of the side plate of the lower housing assembly **250**, and the side plate of the lower housing assembly **250** may be in contact with and fastened to the bottom plate of the lower housing assembly **250**. Step 7: Dispose the upper housing assembly **210** on the upper housing supporting plane **251** of the side plate of the lower housing assembly **250**. The upper housing assembly **210** may be in contact with and fastened to the upper housing supporting plane **251** of the side plate of the lower housing assembly **250**, and the upper surface of the upper housing assembly **210** and the upper surface of the lower housing assembly **250** may be on a same plane.

(180) In this embodiment, in a process of assembling the wireless charger, the lower housing assembly **250** is split into a bottom plate and a side plate, so that structure complexity of the lower housing assembly **250** is reduced, the wireless charger **200** is assembled more easily, and assembly efficiency is improved. The lower housing assembly **250** is split into the bottom plate and the side plate, the heat dissipation ring **240** and the limiting magnet **230** are fastened to the bottom plate of

the lower housing assembly **250**, and the circuit board **260** and the magnetic sheet coil **220** are fastened to the coil supporting plane **252** of the side plate of the lower housing assembly **250**. In the assembly process, assembly is performed by using two assembly lines: the bottom plate of the housing assembly **250** and the side plate of the lower housing assembly **250**, and then overall assembly is performed, so that a time for assembling the wireless charger **200** can be reduced, and a manufacturing capacity can be improved.

(181) In addition, a heat conduction component of the wireless charger **200** is split into the upper housing assembly **210**, the side plate of the lower housing assembly **250**, the bottom plate of the lower housing assembly **250**, and the heat dissipation ring **240**. According to an actual requirement, the components are manufactured by using different materials, so that the wireless charger **200** can improve heat dissipation performance in a targeted manner and optimize costs.

(182) In the wireless charger **200** provided in this embodiment, the upper housing assembly **210**, the magnetic sheet coil **220**, the limiting magnet **230**, the heat dissipation ring **240**, the lower housing assembly **250**, and the circuit board **260** may be fastened to a pre-specified position by using a bonding agent, so that structural strength of the wireless charger **200** is enhanced, and product durability is improved. A gap among the upper housing assembly **210**, the magnetic sheet coil **220**, the limiting magnet **230**, the heat dissipation ring **240**, the lower housing assembly **250**, and the circuit board **260** in the wireless charger **200** may be further filled with a thermally conductive adhesive, to improve structural strength and heat dissipation performance of the wireless charger **200**.

(183) In this embodiment, a concave structure is provided on an upper surface of the lower housing assembly **250** of the wireless charger **200**, and the concave structure is coupled to the upper housing assembly **210** by using a bonding agent to form a cavity structure. The heat dissipation ring **240** is sleeved on the limiting magnet **230**, and the magnetic sheet coil **220** is sleeved on the heat dissipation ring **240**.

(184) In an embodiment, the upper housing assembly **210** is fastened to the upper housing supporting plane **251** of the lower housing assembly **250** by using a bonding agent. A bonding agent may be provided on the upper housing supporting plane **251** or the lower surface of the upper housing assembly **210**, the upper housing assembly **210** may be disposed on the upper housing supporting plane **251**, and the lower surface of the upper housing assembly **210** may be fixedly connected to the upper housing supporting plane **251** by using the bonding agent. In this embodiment, the upper housing assembly **210** and the lower housing assembly **250** of the wireless charger **200** are fastened together by using the bonding agent. Compared with an existing screw fastening manner, the housing of the wireless charger **200** is more beautiful.

(185) In this embodiment, the bonding agent may alternatively be an AB adhesive, a double-sided adhesive, or the like. This is not limited. The AB adhesive may be made of a material such as propylene acid, epoxy, or polyurethane.

(186) In an embodiment, at least one of the limiting magnet **230** or the heat dissipation ring **240** is fastened to the bottom of the concave structure of the lower housing assembly **250** by using a bonding agent. In an embodiment, at least one of the limiting magnet **230** or the heat dissipation ring **240** is fastened to the lower surface of the upper housing assembly **210** by using a bonding agent.

(187) In an embodiment, the heat dissipation ring **240** is fastened to the magnet supporting plane **253** of the lower housing assembly **250** by using a bonding agent. A bonding agent may be provided on the bottom of the heat dissipation ring **240**, the heat dissipation ring **240** may be disposed at a specified position of the magnet supporting plane **253** of the lower housing assembly **250**, and the bonding agent may fasten the heat dissipation ring **240** to the magnet supporting plane **253** of the lower housing assembly **250**, so as to prevent the heat dissipation ring **240** from shaking inside the wireless charger **200** to generate an abnormal sound.

(188) The heat dissipation ring **240** may be fastened to the magnet supporting plane **253** of the

lower housing assembly **250**, and there may be a gap between a side face of the heat dissipation ring **240** and the inner side wall of the concave structure of the lower housing assembly **250**. The gap between the side face of the heat dissipation ring **240** and the inner side wall of the concave structure of the lower housing assembly **250** may be filled with a thermally conductive adhesive, so that a heat dissipation capability of the wireless charger **200** is improved. Correspondingly, the inner side wall of the concave structure of the lower housing assembly **250**, the magnetic sheet coil **220**, and the heat dissipation ring **240** constitute a transverse limiting structure, so as to prevent the magnetic sheet coil **220** and the heat dissipation ring **240** from shaking horizontally inside the wireless charger **200** to generate an abnormal sound, thereby improving structural reliability of the wireless charger **200**.

(189) In an embodiment, the limiting magnet **230** is fastened to the magnet supporting plane **253** of the lower housing assembly **250** by using a bonding agent. A bonding agent may be provided on a bottom of the limiting magnet **230**, the limiting magnet **230** may be embedded in the heat dissipation ring **240**, and the limiting magnet **230** may be in contact with the magnet supporting plane **253** of the lower housing assembly **250**. The bonding agent fastens the limiting magnet **230** to the magnet supporting plane **253** of the lower housing assembly **250**, so as to prevent the limiting magnet **230** from shaking inside the wireless charger **200** to generate an abnormal sound.

(190) In an embodiment, the limiting magnet **230** is embedded in the heat dissipation ring **240**, and there is a gap between an outer side surface of the limiting magnet **230** and an inner side face of the heat dissipation ring **240**. The gap between the outer side surface of the limiting magnet **230** and the inner side face of the heat dissipation ring **240** may be filled with a thermally conductive adhesive. Correspondingly, the inner side wall of the concave structure of the lower housing assembly **250**, the magnetic sheet coil **220**, the heat dissipation ring **240** and the limiting magnet **230** constitute a transverse limiting structure, so as to prevent the magnetic sheet coil **220**, the limiting magnet **230** and the heat dissipation ring **240** from shaking inside the wireless charger **200** to generate an abnormal sound, thereby improving structural reliability of the wireless charger **200**. In addition, the thermally conductive adhesive may be filled in the gap between the outer side surface of the limiting magnet **230** and the inner side face of the heat dissipation ring **240**, so as to improve a heat dissipation capability of the wireless charger **200**.

(191) In an embodiment, the circuit board **260** is fastened to the receiving cavity by using a thermally conductive adhesive. The magnetic sheet coil **220** may be disposed on the coil supporting plane **252**, and the circuit board **260** may be disposed between the magnetic sheet coil **220** and the bottom of the concave structure of the lower housing assembly **250**. The magnetic sheet coil **220** and the bottom of the concave structure of the lower housing assembly **250** constitute the receiving cavity. A gap among the magnetic sheet coil **220**, the bottom of the concave structure of the lower housing assembly **250**, and the circuit board **260** is filled with a thermally conductive adhesive. The thermally conductive adhesive fastens the circuit board **260** in the receiving cavity, so as to prevent the circuit board **260** from shaking inside the wireless charger **200** to generate an abnormal sound, and further avoid an open circuit problem caused by movement of the circuit board **260** in the receiving cavity, thereby improving reliability of the wireless charger **200**.

(192) In an embodiment, the circuit board **260** is fastened to the lower surface of the magnetic sheet coil **220** by using a bonding agent. A bonding agent may be provided on a surface of the circuit board **260** or a lower surface of the magnetic sheet coil **220**, and the bonding agent may fasten the circuit board **260** on the lower surface of the magnetic sheet coil **220**, so as to prevent the circuit board **260** from shaking inside the wireless charger **200** to generate an abnormal sound, and further avoid an open circuit problem caused by movement of the circuit board **260** in the receiving cavity, thereby improving reliability of the wireless charger **200**.

(193) In this embodiment, the coil supporting plane **252** is provided in the concave structure of the lower housing assembly **250**. The coil supporting plane **252** is used to support the magnetic sheet coil **220**. The coil supporting plane **252** is close to the upper surface of the lower housing assembly

250.

(194) In an embodiment, the magnetic sheet coil **220** is fastened to the coil supporting plane **252** of the lower housing assembly **250** by using a bonding agent. A bonding agent may be provided on the coil supporting plane **252** and the magnetic sheet coil **220** may be disposed on the coil supporting plane **252**. The bonding agent fastens the magnetic sheet coil **220** to the coil supporting plane **252** of the lower housing assembly **250**, so as to prevent the magnetic sheet coil **220** from shaking inside the wireless charger **200** to generate an abnormal sound.

(195) In an embodiment, an upper surface of the magnetic sheet coil **220** is in contact with the lower surface of the upper housing assembly **210**. The upper surface of the magnetic sheet coil **220** is a surface that is of the magnetic sheet coil **220** and that is close to the upper housing assembly **210**, and the lower surface of the upper housing assembly **210** is a surface that is of the upper housing assembly **210** and that constitutes the cavity structure. The coil supporting plane **252** supports the magnetic sheet coil **220**, and the upper housing assembly **210**, the magnetic sheet coil **220** and the coil supporting plane **252** constitute a longitudinal limiting structure, so as to prevent the magnetic sheet coil **220** from shaking inside the wireless charger **200** to generate an abnormal sound.

(196) In an embodiment, a gap among the lower surface of the upper housing assembly **210**, the concave structure of the lower housing assembly **250**, and the magnetic sheet coil **220** is filled with a thermally conductive adhesive, and the upper housing assembly **210**, the magnetic sheet coil **220** and the coil supporting plane **252** constitute a longitudinal limiting structure, so as to prevent the magnetic sheet coil **220** from shaking inside the wireless charger **200** and improve heat dissipation efficiency of the wireless charger **200**.

(197) In an embodiment, the coil supporting plane **252** is of a fence-shaped structure, and a thermally conductive adhesive is filled among a plurality of fences of the fence-shaped structure. The coil supporting plane **252** may include a fence-shaped support body. The fence-shaped support body includes one arc-shaped fence and a plurality of column-shaped fences. A gap among the column-shaped fences, the arc-shaped fence, and the inner side wall of the concave structure of the lower housing assembly **250** is filled with a thermally conductive adhesive, so that a heat dissipation capability of the wireless charger **200** is improved.

(198) In an embodiment, the lower housing assembly **250** includes two parts: a bottom plate and a side plate. The side plate of the lower housing assembly **250** is fastened to the bottom plate of the lower housing assembly **250** by using a bonding agent. The bonding agent used between the bottom plate of the lower housing assembly **250** and the side plate of the lower housing assembly **250** may be an AB adhesive. The heat dissipation ring **240** and the limiting magnet **230** are fastened to the bottom plate of the lower housing assembly **250** by using a double-sided adhesive.

(199) A plurality of components in the wireless charger **200** provided in this embodiment may be fastened by using a bonding agent, so as to enhance structural strength of the wireless charger **200** and improve product durability. In addition, a gap among the plurality of components of the wireless charger **200** is filled with a thermally conductive adhesive, so as to improve a heat dissipation capability of the wireless charger **200**.

(200) In this embodiment, powder of a ceramic material is used as a bonding agent in the wireless charger **200**, and another type of bonding agent such as a white adhesive or a double-sided adhesive is not needed, so that types of bonding agents can be reduced, and manufacturing costs of the wireless charger **200** can be reduced. In addition, the powder of the ceramic material has a good heat conductivity, which further improves a heat dissipation capability of the wireless charger **200**.

(201) In this embodiment, when the wireless charger **200** performs wireless charging, the magnetic sheet coil **220** generates a large amount of heat. A wireless charging signal generated by the wireless charger **200** generates a vortex on the limiting magnet **230**, and a large amount of heat is generated in the limiting magnet **230**. The circuit board **260** works for a long time, and various components of the circuit board **260** generate heat.

(202) In this embodiment, components that generate heat in the wireless charger **200** may be the magnetic sheet coil **220** and the circuit board **260**. In a process of converting electrical energy into a wireless charging signal, the magnetic sheet coil **220** generates a large amount of heat. Heat generated by the circuit board **260** is far less than that of the magnetic sheet coil **220** and the limiting magnet **230**. Therefore, a problem to be resolved may be to reduce heat generated by the magnetic sheet coil **220** and the limiting magnet **230**.

(203) In order to improve a heat dissipation capability of the wireless charger **200**, the upper housing assembly **210** and the lower housing assembly **250** of the wireless charger **200** may be made of materials with a high thermal conductivity. In the embodiments, the material with a high thermal conductivity may include ceramic, thermally conductive plastic, and the like.

(204) In an embodiment, the upper housing assembly **210** and the lower housing assembly **250** may be made of a material with a low electrical conductivity. In a process in which the magnetic sheet coil **220** converts electrical energy into a wireless charging signal, the housing of the wireless charger **200** cannot transmit electrical energy, and no electric leakage occurs.

(205) FIG. **19** is a schematic diagram of heat transfer among heat-emitting components such as a magnetic sheet coil and a limiting magnet of a wireless charger according to an embodiment. In this embodiment, a wireless charger **200** may include an upper housing assembly **210**, a magnetic sheet coil **230**, a heat dissipation ring **240**, and a lower housing assembly **250**. A concave structure is provided on an upper surface of the lower housing assembly **250**, and the concave structure of the lower housing assembly **250** is coupled to the upper housing assembly **210** form a cavity structure. The magnetic sheet coil **230** is sleeved outside the heat dissipation ring **240**. A gap among the upper housing assembly **210**, the concave structure of the lower housing assembly **250**, the magnetic sheet coil **230**, and the heat dissipation ring **240** is filled with a thermally conductive adhesive.

(206) As shown in FIG. **19**, the magnetic sheet coil **220** and the heat dissipation ring **240** are disposed in the concave structure of the lower housing assembly **250** of the wireless charger **200**. The heat dissipation ring **240** is disposed in an annular structure of the magnetic sheet coil **220**, and the magnetic sheet coil **220** is sleeved outside the heat dissipation ring. An outer side surface of the heat dissipation ring **240** is coupled to the magnetic sheet coil **220**, and the outer side surface of the heat dissipation ring **240** is in contact with an inner side surface of the magnetic sheet coil **220**. An upper surface of the heat dissipation ring **240** is coupled to a lower surface of the upper housing assembly **210**, and a lower surface of the heat dissipation ring **240** is coupled to a bottom of the concave structure of the lower housing assembly **250**. The upper surface of the heat dissipation ring **240** is a surface that is of the heat dissipation ring **240** and that is close to the upper housing assembly **210**, the lower surface of the heat dissipation ring **240** is a surface that is of the heat dissipation ring **240** and that is close to the bottom of the concave structure of the lower housing assembly **250**, and the lower surface of the upper housing assembly **210** is a surface that is of the upper housing assembly **10** and that constitutes the cavity structure.

(207) In an embodiment, the heat dissipation ring **240** is fastened between the lower surface of the upper housing assembly **210** and the bottom of the concave structure of the lower housing assembly **250**. In an embodiment, a thermally conductive adhesive is provided between the upper surface of the heat dissipation ring **240** and the upper housing assembly **210**, and a thermally conductive adhesive is provided between the lower surface of the heat dissipation ring **240** and the bottom of the concave structure of the lower housing assembly **250**. The heat dissipation ring **210** is configured to conduct heat of the upper housing assembly **210** and the magnetic sheet coil **220** to the bottom of the concave structure of the lower housing assembly **250**.

(208) In an embodiment, the heat dissipation ring **240** and the lower housing assembly **250** are made of a high thermally conductive material. Heat generated on the inner side surface of the magnetic sheet coil **220** may be transferred to the heat dissipation ring **240** by using the thermally conductive adhesive. The heat of the heat dissipation ring **240** is transferred to the lower housing

assembly **250** by using the thermally conductive adhesive. The lower housing assembly **250** performs heat exchange with external gas, and transfers heat of the magnetic sheet coil **220** to the external gas, so as to reduce a temperature of the wireless charger **200**.

(209) As shown in FIG. **19**, a coil supporting plane **252** is provided in the concave structure of the lower housing assembly **250**. The magnetic sheet coil **220** is disposed on the coil supporting plane **252**. In an embodiment, an outer side surface of the magnetic sheet coil **220** is in contact with an inner side wall of the concave structure of the lower housing assembly **250**, and a lower surface of the magnetic sheet coil **220** is in contact with the coil supporting plane **252** of the lower housing assembly **250**. Heat generated by the magnetic sheet coil **220** may be quickly transferred to the lower housing assembly **250**.

(210) In an embodiment, the lower housing assembly **250** is made of a high thermally conductive material. Heat generated on the outer side surface and the lower surface of the magnetic sheet coil **220** may be transferred to the lower housing assembly **250** by using the thermally conductive adhesive. The lower housing assembly **250** performs heat exchange with external gas, and transfers heat of the magnetic sheet coil **220** to the external gas, so as to reduce a temperature of the wireless charger **200**.

(211) In an embodiment, the magnetic sheet coil **220** is coupled to the lower surface of the upper housing assembly **210**, and a thermally conductive adhesive is provided between the magnetic sheet coil **220** and the lower surface of the upper housing assembly **210**. In an embodiment, the lower surface of the upper housing assembly **210** of the wireless charger **200** is in contact with an upper surface of the magnetic sheet coil **220**. Heat generated on the upper surface of the magnetic sheet coil **220** may be transferred to the upper housing assembly **210** by using the thermally conductive adhesive. The upper housing assembly **210** performs heat exchange with external gas, and transfers heat of the magnetic sheet coil **220** to the external gas, so as to reduce a temperature of the wireless charger **200**.

(212) As shown in FIG. **19**, the wireless charger **200** is further provided with a limiting magnet **230**. The limiting magnet **230** is disposed inside the heat dissipation ring **240**, an upper surface of the limiting magnet **230** is coupled to the lower surface of the upper housing assembly **210**, and a lower surface of the limiting magnet **230** is coupled to the bottom of the concave structure of the lower housing assembly **250**. The upper surface of the limiting magnet **230** is a surface that is of the limiting magnet **230** and that is close to the upper housing assembly **210**, and the lower surface of the limiting magnet **230** is a surface that is of the limiting magnet **230** and that is close to the bottom of the concave structure of the lower housing assembly **250**.

(213) In an embodiment, the limiting magnet **230** is fastened between the lower surface of the upper housing assembly **210** and the bottom of the concave structure of the lower housing assembly **250**. In an embodiment, a thermally conductive adhesive is provided between the upper surface of the limiting magnet **230** and the lower surface of the upper housing assembly **210**, and a thermally conductive adhesive is provided between the lower surface of the limiting magnet **230** and the bottom of the concave structure of the lower housing assembly **250**. A thermally conductive adhesive is provided between the heat dissipation ring **240** and the limiting magnet **230**. The limiting magnet **230** is configured to transfer heat of the upper housing assembly **210** to the bottom of the concave structure of the lower housing assembly **250**, so as to greatly improve a heat dissipation capability of the wireless charger **200** and reduce a temperature of the wireless charger **200**.

(214) In an embodiment, a side face of the limiting magnet **230** is in contact with an inner side surface of the heat dissipation ring **240**, and heat generated by the limiting magnet **230** may be quickly transferred to the heat dissipation ring **240**.

(215) As shown in FIG. **6**, a plurality of heat dissipation holes **258** may be provided on the magnet supporting plane **253** of the lower housing assembly **250**. The heat dissipation holes **258** are located at a position at which the limiting magnet **230** is fastened in the magnet supporting plane **253**. Heat

of the limiting magnet **230** may be exchanged with external gas by using the heat dissipation holes **258**, and the heat of the limiting magnet **230** is transferred to the external gas, so as to reduce a temperature of the wireless charger **200**. In another embodiment, there may be any quantity of heat dissipation holes **258**. The heat dissipation hole **258** may be in a shape of an ellipse or a polygon, or in another shape.

(216) In an embodiment, a radius of a protrusion structure on the lower surface of the upper housing assembly **210** is not greater than a radius of an inner side of the magnetic sheet assembly **221** of the magnetic sheet coil **220**, and the radius of the protrusion structure on the lower surface of the upper housing assembly **210** is not less than a radius of the limiting magnet **230**. The upper housing assembly **210** is disposed on the upper housing supporting plane **251** of the lower housing assembly **250**. The upper housing assembly **210** is not only in contact with the upper surface of the magnetic sheet coil **220**, but also in contact with the upper surface of the limiting magnet **230** at a bottom of the protrusion structure of the upper housing assembly **210**. Heat of the limiting magnet **230** is transferred to the upper housing assembly **210**. The upper housing assembly **210** performs heat exchange with external gas, so as to reduce a temperature of the wireless charger **200**.

(217) In an embodiment, the radius of the protrusion structure on the lower surface of the upper housing assembly **210** is not less than a radius of the heat dissipation ring **240**. The upper housing assembly **210** is disposed on the upper housing supporting plane **251** of the lower housing assembly **250**. The upper housing assembly **210** is not only in contact with the upper surface of the magnetic sheet coil **220**, but also in contact with the limiting magnet **230** and the heat dissipation ring **240**. Heat of the limiting magnet **230** and the heat dissipation ring **240** is transferred to the upper housing assembly **210**. The upper housing assembly **210** performs heat exchange with external gas, so as to reduce a temperature of the wireless charger **200**.

(218) In this embodiment, the upper surface of the limiting magnet **230** and the upper surface of the heat dissipation ring **240** may be in contact with the upper housing assembly **210**. The lower surface of the limiting magnet **230** and the lower surface of the heat dissipation ring **240** are in contact with the bottom of the concave structure of the lower housing assembly **250**. Heat generated by the limiting magnet **230** may be transferred to the upper housing assembly **210** and the lower housing assembly **250**, so that a heat dissipation capability of the wireless charger **200** can be further improved.

(219) As shown in FIG. **19**, a lower surface of the circuit board **260** is in contact with the magnet supporting plane **253** of the lower housing assembly **250**, or an upper surface of the circuit board **260** is in contact with the magnetic sheet coil **220**. Heat generated by the circuit board **260** is transferred to the magnetic sheet coil **220**, the heat dissipation ring **240**, and the lower housing assembly **250**. In an embodiment, a temperature of the magnetic sheet coil **220** is higher than that of the circuit board **260**, and the circuit board **260** does not transfer heat to the magnetic sheet coil **220**, and instead absorbs the heat of the magnetic sheet coil **220**. In this case, heat generated by the circuit board **260** is transferred to the lower housing assembly **250**. In an embodiment, the temperature of the circuit board **260** is higher than that of the magnetic sheet coil **220**, and heat generated by the circuit board **260** is transferred to the magnetic sheet coil **220** and the lower housing assembly **250**. Heat generated by the circuit board **260** and heat generated by the magnetic sheet coil **220** are exchanged together by using the housing of the wireless charger **200**, so as to reduce a temperature of the wireless charger **200**.

(220) In this embodiment, the upper surface of the magnetic sheet coil **220** of the wireless charger **200** may be in contact with the upper housing assembly **210**, the outer side surface of the magnetic sheet coil **220** and the lower surface of the magnetic sheet coil **220** may be in contact with the lower housing assembly **250**, and an inner side surface of the magnetic sheet coil **220** may be in indirect contact with the upper housing assembly **210** and the lower housing assembly **250** by using the limiting magnet **230** and the heat dissipation ring **240**. Heat generated by the magnetic sheet coil **220** may be transferred from all sides to the housing of the wireless charger **200**, so that a heat

dissipation capability of the wireless charger **200** is greatly improved. The housing of the wireless charger **200** performs heat exchange with external gas, so as to reduce a temperature of the wireless charger **200**.

(221) FIG. **20** is a schematic diagram of heat transfer when an electronic device is disposed on a wireless charger according to an embodiment. As shown in FIG. **20**, when a wireless charger **200** wirelessly charges an electronic device **100**, the electronic device **100** generates heat. The electronic device **100** has a relatively large quantity of components and a complex structure, and an excessively high temperature of the electronic device **100** needs to be prevented. Therefore, the electronic device **100** is overheated, causing an excessively high temperature, and wireless charging power needs to be reduced or wireless charging needs to be stopped. Consequently, a wireless charging speed of the electronic device **100** is affected.

(222) As shown in FIG. **20**, in a wireless charging process, the electronic device **100** is disposed on an upper surface of an upper housing assembly **210** of the wireless charger **200**. A protrusion structure of the electronic device **100** is embedded into a concave structure **211** of the upper housing assembly **210**, and the protrusion structure of the electronic device **100** may be in contact with the concave structure **211** of the upper housing assembly **210**. A periphery of an upper surface of the upper housing assembly **210** is in contact with a lower surface of the electronic device **100**. Heat of the electronic device **100** is transferred to a housing of the wireless charger **200**, so that a heat dissipation area of the electronic device **100** is increased, and reduction of a temperature of the electronic device **100** is accelerated.

(223) After heat exchange is performed between the upper housing assembly **210** and the electronic device **100**, some heat of the upper housing assembly **210** is directly exchanged with surrounding gas, and heat of the electronic device **100** is transferred to the surrounding gas of the upper housing assembly **210**, so that a temperature of the electronic device **100** is reduced. The upper housing assembly **210** may also transfer the heat to a lower housing assembly **250**. An outer surface area of the lower housing assembly **250** is relatively large, and the heat of the electronic device **100** can be quickly transferred to surrounding gas, so as to quickly reduce a temperature of the electronic device **100**.

(224) In an embodiment, the upper housing assembly **210** and the lower housing assembly **250** are made of a high thermally conductive material. A thermally conductive coefficient of the upper housing assembly **210** and the lower housing assembly **250** is higher than that of the electronic device **100**, and thermal resistance of the upper housing assembly **210** and the lower housing assembly **250** is lower than that of the electronic device **100**. The upper housing assembly **210** can quickly absorb heat of the electronic device **100** and transfer the heat to surrounding gas and the lower housing assembly **250**, so that a heat dissipation capability of the electronic device **100** can be improved. The heat of the electronic device **100** is dissipated through a heat dissipation channel of “the electronic device **100**.fwdarw.the upper housing assembly **210** of the wireless charger **200**.fwdarw.the lower housing assembly **250** of the wireless charger **200**”, so as to quickly reduce a temperature of the electronic device **100**, thereby improving a wireless charging speed of the electronic device **100**.

(225) In an embodiment, a gap among the upper housing assembly **250**, a limiting magnet **230**, a heat dissipation ring **240**, and the lower housing assembly **250** of the wireless charger **200** is filled with a thermally conductive adhesive. The upper housing assembly **210** absorbs heat of the electronic device **100**, and heat of the upper housing assembly **210** may be transferred to a side face of the lower housing assembly **250** and a bottom plate of the lower housing assembly **250** by using the thermally conductive adhesive. In this embodiment, heat of the electronic device **100** is dissipated through a heat dissipation channel of “the electronic device **100**.fwdarw.the upper housing assembly **210** of the wireless charger **200**.fwdarw.the thermally conductive adhesive.fwdarw.the lower housing assembly **250** of the wireless charger **200**”, so as to quickly reduce a temperature of the electronic device **100**, thereby improving a wireless charging speed of

the electronic device **100**.

(226) In an embodiment, a protrusion structure **212** of the upper housing assembly **210** is in contact with an upper surface of the limiting magnet **230** and an upper surface of the heat dissipation ring **240** by using a thermally conductive adhesive or in a direct manner, a lower surface of the limiting magnet **230** is in contact with a bottom of a concave structure of the lower housing assembly **250**, and a lower surface of the heat dissipation ring **240** is in contact with the bottom of the concave structure of the lower housing assembly **250**.

(227) After the upper housing assembly **210** absorbs heat of the electronic device **100**, heat of the upper housing assembly **210** is transferred to the limiting magnet **230** and the heat dissipation ring **240**. Heat of the limiting magnet **230** and the heat dissipation ring **240** is transferred to the bottom of the concave structure of the lower housing assembly **250**. In another embodiment, the upper housing assembly **210** may transfer heat to the bottom of the concave structure of the lower housing assembly **250** by using one of the limiting magnet **230** and the heat dissipation ring **240**.

(228) In this embodiment, heat of the electronic device **100** is dissipated through a heat dissipation channel of “the electronic device **100**.fwdarw.the upper housing assembly **210** of the wireless charger **200**.fwdarw.the limiting magnet **230** and/or the heat dissipation ring **240**.fwdarw.the lower housing assembly **250** of the wireless charger **200**”, so as to quickly reduce a temperature of the electronic device **100**, thereby improving a wireless charging speed of the electronic device **100**.

(229) When wirelessly charging the electronic device **100**, the wireless charger **200** provided in this embodiment may further dissipate heat for the electronic device **100**, to improve a heat dissipation capability of the electronic device **100**, thereby improving a wireless charging speed of the electronic device **100**. During experimental simulation, when the wireless charger **200** provided in this embodiment wirelessly charges the electronic device **100**, a time for charging the electronic device **100** from an electric quantity of 0 to 100% may be reduced by 25 minutes, and a charging speed is obviously improved.

(230) The wireless charger provided in this embodiment may include an upper housing assembly and a lower housing assembly. A plurality of supporting planes, such as an upper housing supporting plane, a coil supporting plane, a magnet supporting plane, and a circuit board supporting plane, may be disposed in the lower housing assembly. The upper housing supporting plane supports the upper housing assembly. The coil supporting plane supports the magnetic sheet coil. The magnet supporting plane supports the limiting magnet and the heat dissipation ring. The circuit board supporting plane supports a circuit board **260**. The plurality of supporting planes of the wireless charger may support the components at different positions, so as to avoid overlapping of the components. If the wireless charger is affected by an external force, all the components that are overlapped together may be damaged. As a result, reliability of the wireless charger **200** is reduced.

(231) The wireless charger provided in this embodiment may include an upper housing assembly, a lower housing assembly, and a magnetic sheet coil. A concave structure is provided on an upper surface of the lower housing assembly, and the concave structure is coupled to the upper housing assembly to form a cavity structure. The cavity structure accommodates the magnetic sheet coil. The magnetic sheet coil includes a magnetic sheet assembly and a coil assembly. A circular groove is provided on an upper surface of the magnetic sheet assembly and is used to accommodate the coil assembly. The coil assembly converts electrical energy into a wireless charging signal and radiates the wireless charging signal to the surroundings. The wireless charging signal is radiated in a specified direction under the limitation of the magnetic sheet assembly. The magnetic sheet assembly limits a radiation direction of the wireless charging signal, to avoid a temperature rise of the wireless charger due to a fact that the wireless charging signal generated by the coil assembly forms a vortex on another component of the wireless charger.

(232) The wireless charger provided in this embodiment may include an upper housing assembly, a lower housing assembly, a magnetic sheet coil, a limiting magnet, and a shielding assembly. A concave structure is provided on an upper surface of the lower housing assembly, and the concave

structure is coupled to the upper housing assembly to form a cavity structure. The cavity structure accommodates the magnetic sheet coil, the limiting magnet, and the shielding assembly. The shielding assembly is disposed between the magnetic sheet coil and the limiting magnet. The shielding assembly may prevent a wireless charging signal generated by the coil assembly from forming a vortex on the limiting magnet, and avoid a temperature rise of the wireless charger.

(233) The wireless charger provided in this embodiment may include an upper housing assembly, a lower housing assembly, and a heat dissipation ring. A concave structure is provided on an upper surface of the lower housing assembly, and the concave structure is coupled to the upper housing assembly to form a cavity structure. The cavity structure accommodates the heat dissipation ring. An upper surface of the heat dissipation ring is coupled to the upper housing assembly. A lower surface of the heat dissipation ring is coupled to a bottom of the concave structure of the lower housing assembly. The heat dissipation ring may transfer heat of the wireless charger by using the upper housing assembly and the lower housing assembly, so as to improve a heat dissipation capability of the wireless charger.

(234) The wireless charger provided in this embodiment may include an upper housing assembly, a lower housing assembly, and a heat dissipation ring. A concave structure is provided on an upper surface of the lower housing assembly, and the concave structure is coupled to the upper housing assembly to form a cavity structure. The cavity structure accommodates the heat dissipation ring. An upper surface of the heat dissipation ring is coupled to the upper housing assembly. A lower surface of the heat dissipation ring is coupled to a bottom of the concave structure of the lower housing assembly. Heat of the electronic device is transferred to the upper housing assembly, and the heat dissipation ring may transfer the heat of the upper housing assembly to the bottom of the lower housing assembly, so that a heat dissipation area of the electronic device is increased, and a heat dissipation capability of the electronic device is improved.

(235) The wireless charger provided in this embodiment may include an upper housing assembly, a lower housing assembly, a magnetic sheet coil, and a heat dissipation ring. A concave structure is provided on an upper surface of the lower housing assembly, and the concave structure is coupled to the upper housing assembly to form a cavity structure. The cavity structure accommodates the magnetic sheet coil and the heat dissipation ring. The heat dissipation ring is embedded in the magnetic sheet coil and is in contact with the magnetic sheet coil. An upper surface of the heat dissipation ring is coupled to the upper housing assembly. A lower surface of the heat dissipation ring is coupled to a bottom of the concave structure of the lower housing assembly. Heat of the electronic device is transferred to the upper housing assembly, and the heat dissipation ring may transfer the heat of the upper housing assembly to the bottom of the lower housing assembly, so that a heat dissipation area of the electronic device is increased, and heat dissipation capabilities of the wireless charger and the electronic device are improved.

(236) The wireless charger provided in this embodiment may include an upper housing assembly, a lower housing assembly, a magnetic sheet coil, and a limiting magnet. A concave structure is provided on an upper surface of the lower housing assembly, and the concave structure is coupled to the upper housing assembly to form a cavity structure. The cavity structure accommodates the magnetic sheet coil and the limiting magnet. The magnetic sheet coil and the limiting magnet are fastened on the upper housing assembly and the lower housing assembly, to prevent each component from shaking inside the wireless charger to generate an abnormal sound. In addition, components such as the magnetic sheet coil and the limiting magnet of the wireless charger are fastened together by using a bonding agent, so as to enhance structural strength of the wireless charger and improve durability of the product. In addition, a gap between the components of the wireless charger is filled with a thermally conductive adhesive, so as to improve a heat dissipation capability of the wireless charger.

(237) The wireless charger provided in this embodiment may include an upper housing assembly, a lower housing assembly, a magnetic sheet coil, a limiting magnet, and a heat dissipation ring. A

concave structure is provided on an upper surface of the upper housing assembly. A protrusion structure is provided on a lower surface of the upper housing assembly. A circular notch is further provided on a lower surface of the upper housing assembly.

(238) In this embodiment, the concave structure may be provided on the upper surface of the upper housing assembly, so that the concave structure on the upper surface of the upper housing assembly may be coupled to a protrusion structure of the electronic device. This can reduce a distance between the electronic device and the wireless charger and reduce an electrical energy loss during wireless charging. The protrusion structure is provided on the lower surface of the upper housing assembly, so that the upper housing assembly is in contact with the heat dissipation ring and the limiting magnet, thereby improving a heat dissipation capability of the wireless charger. A circular notch is further provided on the lower surface of the upper housing assembly, so that the magnetic sheet coil is embedded in the circular notch, thereby increasing a height of the magnetic sheet coil. In this case, a quantity of coil turns that can be accommodated in the magnetic sheet coil is increased, and power of the wireless charger is increased.

(239) The wireless charger provided in this embodiment may include an upper housing assembly, a lower housing assembly, a magnetic sheet coil, and a limiting magnet. The lower housing assembly includes a side plate and a bottom plate, and the bottom plate of the lower housing assembly is fastened to one opening of the side plate of the lower housing assembly, to form a concave structure. The upper housing assembly is fastened to the other opening of the side plate of the lower housing assembly, to form a cavity structure. The cavity structure accommodates the magnetic sheet coil and the limiting magnet. The lower housing assembly may be split into two parts: a bottom plate and a side plate, and may be divided into two components for manufacturing, so that a manufacturing difficulty of the lower housing assembly is reduced.

(240) Types, quantities, shapes, installation manners, structures, and the like of components of the wireless charger provided in embodiments may not be limited to the foregoing embodiments. All solutions may fall within the scope of the embodiments. Any one or more embodiments or figures combined in a proper manner shall fall within the scope of the embodiments.

(241) Finally, it is noted that the foregoing embodiments are merely used to describe some solutions. A person of ordinary skill in the art should understand that, although described in detail with reference to the foregoing embodiments, the solutions described in the foregoing embodiments may still be modified, or some features thereof may be equivalently replaced. Such modifications or replacements do not make the essence of the corresponding solutions depart from the scope of the embodiments.

Claims

1. A wireless charger, comprising: an upper housing assembly; a lower housing assembly; a magnetic sheet coil; and a heat dissipation ring, wherein a concave structure is provided on an upper surface of the lower housing assembly, the concave structure is coupled to the upper housing assembly to form a cavity structure, the magnetic sheet coil is sleeved outside the heat dissipation ring, and a gap among the upper housing assembly, the concave structure, the magnetic sheet coil, and the heat dissipation ring is filled with a thermally conductive adhesive; an upper surface of the heat dissipation ring is coupled to a lower surface of the upper housing assembly, a lower surface of the heat dissipation ring is coupled to a bottom of the concave structure of the lower housing assembly, and an outer side surface of the heat dissipation ring is coupled to the magnetic sheet coil, wherein the upper surface of the heat dissipation ring is a surface that is of the heat dissipation ring and that is close to the upper housing assembly, the lower surface of the heat dissipation ring is a surface that is of the heat dissipation ring and that is close to the bottom of the concave structure of the lower housing assembly, and the lower surface of the upper housing assembly is a surface that is of the upper housing assembly and that constitutes the cavity structure; and the heat

dissipation ring is configured to conduct heat of the upper housing assembly and the magnetic sheet coil to the bottom of the concave structure of the lower housing assembly.

2. The wireless charger according to claim 1, further comprising: a limiting magnet, wherein the limiting magnet is disposed inside the heat dissipation ring, an upper surface of the limiting magnet is coupled to the lower surface of the upper housing assembly, and a lower surface of the limiting magnet is coupled to the bottom of the concave structure of the lower housing assembly, wherein the upper surface of the limiting magnet is a surface that is of the limiting magnet and that is close to the upper housing assembly, and the lower surface of the limiting magnet is a surface that is of the limiting magnet and that is close to the bottom of the concave structure of the lower housing assembly; and the limiting magnet is configured to transfer heat of the upper housing assembly to the bottom of the concave structure of the lower housing assembly.

3. The wireless charger according to claim 2, wherein a thermally conductive adhesive is provided between the upper surface of the limiting magnet and the lower surface of the upper housing assembly, and a thermally conductive adhesive is provided between the lower surface of the limiting magnet and the bottom of the concave structure of the lower housing assembly.

4. The wireless charger according to claim 2, wherein a thermally conductive adhesive is provided between the heat dissipation ring and the limiting magnet.

5. The wireless charger according to claim 1, wherein a thermally conductive adhesive is provided between the upper surface of the heat dissipation ring and the upper housing assembly, and a thermally conductive adhesive is provided between the lower surface of the heat dissipation ring and the bottom of the concave structure of the lower housing assembly.

6. The wireless charger according to claim 1, wherein the magnetic sheet coil is coupled to the lower surface of the upper housing assembly, and a thermally conductive adhesive is provided between the magnetic sheet coil and the lower surface of the upper housing assembly.

7. The wireless charger according to claim 6, wherein the magnetic sheet coil further comprises: a magnetic sheet assembly; and a coil assembly, a circular groove is provided in the magnetic sheet assembly to accommodate the coil assembly, and a thermally conductive adhesive is provided in the circular groove of the magnetic sheet assembly.

8. The wireless charger according to claim 1, wherein the heat dissipation ring is made of a high thermally conductive material.

9. The wireless charger according to claim 1, wherein the upper housing assembly is made of a high thermally conductive material, and when the wireless charger is configured to wirelessly charges an electronic device, the upper housing assembly is configured to conducts heat of the electronic device to the lower housing assembly by using the heat dissipation ring.

10. The wireless charger according to claim 9, wherein the upper housing assembly is configured to conducts the heat of the electronic device to the lower housing assembly.

11. The wireless charger according to claim 9, wherein the upper housing assembly is configured to conducts the heat of the electronic device to the lower housing assembly by using the thermally conductive adhesive.

12. The wireless charger according to claim 1, wherein the heat dissipation ring is configured to conduct heat of the magnetic sheet coil to the lower housing assembly.

13. The wireless charger according to claim 1, wherein the limiting magnet is configured to conduct the heat of the magnetic sheet coil to the lower housing assembly.

14. The wireless charger according to claim 1, wherein the thermally conductive adhesive is configured to conduct the heat of the magnetic sheet coil to the lower housing assembly.

15. The wireless charger according to claim 1, wherein the concave structure further comprises: a coil supporting plane, the magnetic sheet coil is disposed on the coil supporting plane, and the coil supporting plane conducts the heat of the magnetic sheet coil to the lower housing assembly.
