

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250275497

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

MONTENGUISE; Justin L. et al.

CONTROLLING SEED PLACEMENT BASED ON PRIOR MATERIAL PLACEMENT

Abstract

An indication of previously-applied material is obtained. A planting machine is controlled to plant seeds based on the indication of the previously-applied material.

Inventors: MONTENGUISE; Justin L. (Bettendorf, IA), HUBNER; Cary S. (Geneseo, IL), WONDERLICH; Grant J. (Milan, IL)

Applicant: Deere & Company (Moline, IL)

Family ID: 85251754

Appl. No.: 19/057457

Filed: February 19, 2025

Related U.S. Application Data

parent US continuation 17677521 20220222 parent-grant-document US 12256658 child US 19057457

Publication Classification

Int. Cl.: A01B79/02 (20060101); A01C7/06 (20060101); A01C7/10 (20060101)

U.S. Cl.:

CPC A01B79/02 (20130101); A01C7/06 (20130101); A01C7/102 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] The present application is a continuation of and claims priority of U.S. patent application Ser. No. 17/677,521, filed Feb. 22, 2022, the content of which is hereby incorporated by reference in its entirety.

FIELD OF THE DESCRIPTION

[0002] The present description generally relates to planting equipment. More specifically, but not by limitation, the present description relates to a processing and control system for an agricultural planting machine that is configured to sense and track seed movement to control seed release from a seeding system to a target location based on the location of material previously applied to the field.

BACKGROUND

[0003] There are a wide variety of different types of agricultural seeding or planting machines. They can include row crop planters, or the like. These machines place seeds at a desired depth within a plurality of parallel seed trenches that are formed in the soil. As one example, a row unit is often mounted to a planter with a plurality of other row units. The planter is often towed by a tractor over soil where seed is planted in the soil, using the row units. The row units on the planter follow the ground profile by using a combination of a down force assembly that imparts a down force to the row unit to push disk openers into the ground and gauge wheels to set the depth of penetration of the disk openers. The mechanisms that are used for moving the seed from the seed hopper to the ground often include a seed metering system and a seed delivery system.

[0004] The seed metering system receives the seeds in a bulk manner, and divides the seeds into smaller quantities (such as a single seed, or a small number of seeds depending on the seed size and seed type) and delivers the metered seeds to the seed delivery system. In one example, the seed metering system uses a rotating mechanism (which is normally a disc or a concave or bowl-shaped mechanism) that has seed receiving apertures, that receive the seeds from a seed pool and move the seeds from the seed pool to the seed delivery system which delivers the seeds to the ground (or to a location below the surface of the ground, such as in a trench). The seeds can be biased into the seed apertures in the seed metering system using air pressure (such as a vacuum or a positive air pressure differential).

[0005] There are also different types of seed delivery systems that move the seed from the seed metering system to the ground. One seed delivery system is a gravity drop system that includes a seed tube that has an inlet position below the seed metering system. Metered seeds from the seed metering system are dropped into the seed tube and fall (via gravitational force) through the seed tube into the seed trench. Other types of seed delivery systems are assistive systems, in that they do not simply rely on gravity to move the seed from the metering mechanism into the ground. Instead, such systems actively capture the seeds from the seed meter and physically move the seeds from the meter to a lower opening, where the seeds exit into the ground or trench.

[0006] Row units can also be used to apply material to the field (e.g., fertilizer, herbicide, insecticide, or pesticide etc.) over which they are traveling. In some scenarios, each row unit has a valve that is coupled between a source of material to be applied, and an application assembly. As the valve is actuated, the material passes through the valve, from the source to the application assembly, and is applied to the field. In other scenarios, each row unit has a commodity tank and a commodity delivery system that delivers a commodity (such as fertilizer, herbicide, insecticide, pesticide, etc.) to the soil.

[0007] Many current systems apply the material in a substantially continuous way. For instance, where the application machine is applying a liquid fertilizer, the machine actuates the valve to apply a substantially continuous strip of the liquid fertilizer. The same is true of machines that apply other liquid substances, as examples.

[0008] The discussion above is merely provided for general background information and is not intended to be used as an aid in determining the scope of the claimed subject matter.

SUMMARY

[0009] An indication of previously-applied material is obtained. A planting machine is controlled to plant seeds based on the indication of the previously-applied material.

[0010] Example 1 is a computer implemented method of controlling a planter, comprising: [0011] identifying a material characteristic indicative of previously applied material applied to a field; [0012] controlling the planter to plant seed based on the material characteristic.

[0013] Example 2 is the computer implemented method of any or all previous examples wherein identifying a material characteristic comprises: [0014] identifying a material location indicative of a location where the previously applied material was applied to the field.

[0015] Example 3 is the computer implemented method of any or all previous examples wherein the planter is configured to move through a field in a direction of travel and wherein controlling the planter comprises: [0016] controlling the planter to eject seeds from a seed ejection endpoint at seed locations in a furrow opened by the planter based on the material location.

[0017] Example 4 is the computer implemented method of any or all previous examples and further comprising: [0018] applying the material to the field with a material application system coupled to the planter to apply the material ahead of the seed ejection endpoint in the direction of travel.

[0019] Example 5 is the computer implemented method of any or all previous examples wherein identifying the location of the material comprises: [0020] identifying, during operation of the planter, the location of the previously applied material relative to the seed ejection endpoint.

[0021] Example 6 is the computer implemented method of any or all previous examples wherein controlling the planter to eject seeds comprises: [0022] controlling the planter to eject a seed based on the location of the previously applied material relative to the seed ejection endpoint.

[0023] Example 7 is the computer implemented method of any or all previous examples wherein identifying the location of the material comprises: [0024] identifying a geographic location of the previously applied material.

[0025] Example 8 is the computer implemented method of any or all previous examples wherein controlling the planter to eject seeds comprises: [0026] identifying a geographic location of the planter; and [0027] controlling the planter to eject a seed based on the geographic location of the previously applied material and the geographic location of the planter.

[0028] Example 9 is the computer implemented method of any or all previous examples wherein controlling the planter comprises: [0029] controlling the planter, based on the location of the material, to eject the seed from the seed ejection endpoint at a point that conforms to a predefined spatial relation to the location of the material.

[0030] Example 10 is the computer implemented method of any or all previous examples wherein identifying a material location comprises: [0031] identifying a timing of material placement by the material application system to a location in the field.

[0032] Example 11 is the computer implemented method of any or all previous examples wherein controlling the planter comprises: [0033] controlling the planter, based on the timing of material placement, to eject the seed from the seed ejection endpoint at a time so the seed is ejected at a location in a predefined spatial relation to the location of the material in the field.

[0034] Example 12 is the computer implemented method of any or all previous examples wherein identifying a material location comprises: [0035] receiving a material map that maps locations in the field where the previously applied material was applied; and [0036] identifying a geographic location of the material based on the material map.

[0037] Example 13 is the computer implemented method of any or all previous examples wherein controlling the planter to eject seeds comprises: [0038] controlling the planter to eject seeds from a seed ejection endpoint at seed locations in a furrow opened by the planter based on the geographic location of the material.

[0039] Example 14 is an agricultural system, comprising: [0040] an agricultural machine including a seeding system that delivers seed to a field; [0041] a target determination component that

identifies a target parameter indicative of previously applied material applied to a field; and [0042] a seed ejection system generating a control signal to control the seeding system to plant the seed based on the target parameter.

[0043] Example 15 is the agricultural system of any or all previous examples and further comprising: [0044] a seed tracking system configured to track a position of seeds in the seeding system and generate a seed position signal, the seed ejection system being configured to generate the control signal based on the seed tracking signal.

[0045] Example 16 is the agricultural system of any or all previous examples wherein the agricultural machine is configured to move through the field in a direction of travel and wherein the target determination component is configured to control the seeding system to eject seeds from a seed ejection endpoint at seed locations in a furrow opened by the agricultural machine based on the target parameter.

[0046] Example 17 is the agricultural system of any or all previous examples wherein the agricultural machine further comprises: [0047] a material application control system; and [0048] a material application system controlled by the material application control system to apply the material to locations in the field ahead of the seed ejection endpoint in the direction of travel.

[0049] Example 18 is the agricultural system of any or all previous examples wherein the target determination component is configured to identify, during operation of the seeding system, a location of the previously applied material relative to the seed ejection endpoint, the seed ejection system being configured to control the seeding system to eject a seed based on the locations of the previously applied material relative to the seed ejection endpoint.

[0050] Example 19 is a computer system for controlling a planter that is configured to move through a field in a direction of travel, the computer system comprising: [0051] at least one processor; and [0052] memory storing computer executable instructions which, when executed by the at least one processor, cause the at least one processor to perform steps, comprising: [0053] identifying a material location characteristic indicative of a location of previously applied material applied to a field; and [0054] controlling the planter to eject seeds from a seed ejection endpoint at seed locations in a furrow opened by the planter based on the material location characteristic.

[0055] Example 20 is the computer system of any or all previous examples and further comprising: [0056] a material application system; and [0057] a material application control system configured to control the material application system to apply the material to the field ahead of the seed ejection endpoint in the direction of travel.

[0058] This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter. The claimed subject matter is not limited to implementations that solve any or all disadvantages noted in the background.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0059] FIG. 1 shows one example of a top view of an agricultural machine.

[0060] FIG. 2 shows one example of a side view of a row unit of the agricultural machine shown in FIG. 1.

[0061] FIG. 3 shows an example of a side view of a row unit of the agricultural machine shown in FIG. 1.

[0062] FIG. 4 is a perspective view of a portion of a seed metering system.

[0063] FIGS. 5 and 6 show two examples of different seed delivery systems that can be used with a seed metering system.

[0064] FIG. **7** is a simplified block diagram of one example of an agricultural machine architecture (or agricultural system).

[0065] FIG. **8** is a flow diagram of one example operation of an agricultural machine.

[0066] FIG. **9** is a flow diagram of one example operation of a seed tracking system.

[0067] FIG. **10** is a flow diagram of one example operation of controlling a seeding system based on tracked seed movements.

[0068] FIG. **11** is a block diagram showing one example of the architecture illustrated in FIG. **7**, deployed in a remote server architecture.

[0069] FIGS. **12-14** show examples of mobile devices that can be used in the architectures shown in the previous figures.

[0070] FIG. **15** is a block diagram showing one example of a computing environment that can be used in the architectures shown in the previous figures.

DETAILED DESCRIPTION

[0071] As discussed above, many current systems apply material to a field in a relatively continuous way. This can result in wasted material. For instance, some material that is applied at certain locations between seeds or plants in a field may be unnecessary. Similarly, it may be desirable to apply some material only at locations other than seeds. Thus, continuous application can result in lower productivity and lower efficiency. This problem can be exacerbated in instances where the material is applied at a relatively high rate, such as in the case of high rate fertilizer application.

[0072] The present description thus proceeds with respect to a system that controllably applies fertilizer (or other material) as desired (such as intermittently or otherwise), identifies an indication of where the fertilizer or other material is applied (such as the specific location or timing of fertilizer application), and controllably dispenses a seed based upon the indication of where the fertilizer or other material was applied. It will be appreciated that the present discussion will proceed with respect to placing or applying fertilizer and then seeding based on the fertilizer location. However, the same discussion can be made with respect to placing or applying other material (such as herbicide, pesticide, etc.), and fertilizer is just one example of material that can be applied.

[0073] FIG. **1** is a partial pictorial, partial schematic top view of one example of an architecture **90** that includes agricultural planting machine **100**, towing vehicle **94**, that is operated by operator **92**, and material application control system **113**, which can be on one or more individual parts of machine **100** (such as on each row unit, or set of row units), centrally located on machine **100**, distributed about the architecture **90**, or on towing vehicle **94**. Operator **92** can illustratively interact with operator interface mechanisms **96** to manipulate and control vehicle **94**, system **113**, and some or all portions of machine **100**.

[0074] Machine **100** is a row crop planting machine that illustratively includes a toolbar **102** that is part of a frame **104**. FIG. **1** also shows that a plurality of planting row units **106** are mounted to the toolbar **102**. Machine **100** can be towed behind towing vehicle **94**, such as a tractor. FIG. **1** shows that material can be stored in a tank **107** and pumped through a supply line **111** so the material can be dispensed in or near the rows being planted. In one example, a set of devices (e.g., actuators) **109** is provided to perform this operation. For instance, actuators **109** can be individual pumps that service individual row units **106** and that pump material from tank **107** through supply line **111** so the material can be dispensed on the field. In such an example, material application control system **113** controls the pumps **109**. In another example, actuators **109** are valves and one or more pumps **115** pump the material from tank **107** to valves **109** through supply line **111**. In such an example, material application control system **113** controls valves **109** by generating valve or actuator control signals. The control signal for each valve or actuator can, in one example, be a pulse width modulated control signal. The flow rate through the corresponding valve **109** can be based on the duty cycle of the control signal (which controls the amount of time the valve is open and closed).

The flow rate can be based on multiple duty cycles of multiple valves or based on other criteria. Further, the material can be applied in varying rates. For example, fertilizer may be applied at one rate when it is being applied at a location where it will be spaced from a seed location and at a second, higher, rate when it is being applied at a location closer to the seed location. These are examples only.

[0075] In addition, each row unit **106** can have a commodity tank **110** that stores material to be applied. A commodity delivery system **98** (as is discussed in greater detail below) can have a motor that drives a commodity meter that dispenses an amount of the material. The motor can be controlled by material application control system **113** to dispense the material at desired locations or in another desired way.

[0076] FIG. **2** is a side view showing one example of a row unit **106** in more detail. FIG. **2** shows that each row unit **106** illustratively has a frame **108**. Frame **108** is illustratively connected to toolbar **102** by a linkage shown generally at **110**. Linkage **110** is illustratively mounted to toolbar **102** so that linkage **110** can move upwardly and downwardly (relative to toolbar **102**).

[0077] Row unit **106** also illustratively has a seed hopper **112** that stores seed. The seed is provided from hopper **112** to a seed metering system **114** that meters the seed and provides the metered seed to a seed delivery system **116** that delivers the seed from the seed metering system **114** to the furrow or trench **182** generated by furrow opener **120** on the row unit **106**. In one example, seed metering system **114** uses a rotatable member, such as a disc or concave-shaped rotating member, and an air pressure differential to retain seed on the disc and move it from a seed pool of seeds (provided from hopper **112**) to the seed delivery system **116**. Other types of meters can be used as well.

[0078] Row unit **106** can also include a row cleaner **118**, ahead of furrow opener **120**, a set of gauge wheels **122**, and a set of closing wheels **124**. Row unit **106** can also include an additional hopper that can be used to provide additional material, such as a fertilizer or another chemical.

[0079] Row unit **106** also has a fertilizer furrow opener **129** and a depth setting gauge wheel **131**. A fertilizer conduit or supply line **125** carries fertilizer (or other material) to a valve **109**. Valve **109** is actuated by material application control system **113**. System **113** can control the valve **109** to dispense the material. Opener **129** can open a furrow **181** that is offset from furrow **182** opened by furrow opener **120** in a direction transverse to the direction of travel **128** to apply fertilizer at a location to the side of seeds. Opener **129** can also open a furrow **181** aligned with the furrow **182** opened by opener **120** so fertilizer (or other material) can be placed in furrow **182** prior to placing the seeds so the fertilizer (or other material) is below seeds or between seeds in the furrow **182**.

[0080] In operation, as row unit **106** moves in the direction generally indicated by arrow **128**, opener **129** opens a furrow **181** at a depth by gauge wheel **131**. Material application control system **113** generates a control signal to actuate valve **109** to apply material (such as fertilizer) to the furrow at desired locations, or intervals in furrow **181**. Row cleaner **118** generally cleans the row ahead of the opener **120** to remove plant debris from the previous growing season and the opener **120** opens a furrow **182** in the soil. Gauge wheels **122** control a depth of the furrow **182**, and seed is metered by seed metering system **114** and delivered to the furrow by seed delivery system **116**. The position of each seed (and/or when the seed is placed in the furrow) is controlled based on the position of fertilizer, or the timing of application of fertilizer, as is described below. Closing wheels **124** close the furrow **182** over the seed. A downforce generator **131** can also be provided to controllably exert downforce to keep the row unit **106** in desired engagement with the soil.

[0081] FIG. **3** is a side view of another example of a row unit **106**, with actuator **109**, and system **113** shown as well. Actuator **109** is shown in three possible locations labeled as **109**, **109A**, and **109B**. Row unit **106** illustratively includes a chemical tank (also referred to herein as a commodity tank) **150**, a seed storage tank **152**, and commodity delivery system **98** (which, itself, can include a motor **156**, a commodity meter **158** and it can include other items **160**). Row unit **106** also illustratively includes one or more disc openers **164**, a set of gauge wheels **166**, and a set of closing

wheels **168**. Seeds from tank **152** are fed into a seed meter **174** (e.g., by gravity or from a centralized commodity distribution system that uses pneumatic commodity distribution to each row unit). The seed meter **174** controls the rate at which seeds are dropped into a seed tube **170** or other seed delivery system, such as a brush belt or flighted belt from seed storage tank **152**. The seeds can be sensed by a seed sensor **172**.

[0082] In the example shown in FIG. **3**, liquid material is passed, e.g., pumped or otherwise forced, through supply line **111** to an inlet end of actuator **109**. Actuator **109** is controlled by control system **113** to allow the liquid to pass from the inlet end of actuator **109** to an outlet end.

[0083] As liquid passes through actuator **109**, the liquid travels through an application assembly **117** from a proximal end (which is attached to an outlet end of actuator **109**) to a distal tip (or application tip) **119**, where the liquid is discharged into a trench **182**, or proximate a trench or furrow **182**, opened by disc opener **164**.

[0084] Material application control system **113** can generate control signals to control motor **156** to drive commodity meter **158**. Meter **158**, when driven by motor **156**, meters out a desired amount of commodity from tank **150**.

[0085] Some parts of row unit **106** shown in FIGS. **2** and **3** will now be discussed in more detail. First, it will be noted that there are different types of seed meters **114**, **174**, and the one that is shown is shown for the sake of example only and is described in greater detail below. However, in one example, each row unit **106** need not have its own seed meter. Instead, metering or other singulation or seed dividing techniques can be performed at a central location, for groups of row units **106**. The metering systems can include finger pick-up discs and/or vacuum meters (e.g., having rotatable discs, rotatable concave or bowl-shaped devices), among others. The seed delivery system can be a gravity drop system (such as seed tube **170** shown in FIG. **3**) in which seeds are dropped through the seed tube **170** and fall (via gravitational force) through the seed tube and out the outlet end **171** into the seed trench **182**. Other types of seed delivery systems may be or may include assistive systems (e.g., system **116** shown in FIG. **2**), in that the assistive systems do not simply rely on gravity to move the seed from the metering system into the ground. Instead, such assistive systems actively assist the seeds in moving from the meter to a lower opening, where they exit or are deposited into the ground or trench. These can be systems that physically capture the seed and move it from the meter to the outlet end of the seed delivery system or they can be pneumatic systems that pump air through the seed tube to assist movement of the seed. The air velocity can be controlled to control the speed at which the seed moves through the delivery system. Some examples of assistive systems are described in greater detail below with respect to FIGS. **5** and **6**.

[0086] A downforce actuator or generator **131**, **126** is mounted on a coupling assembly **110**, **128** that couples row unit **106** to toolbar **102**. Actuator **131**, **126** can be a hydraulic actuator, a pneumatic actuator, a spring-based mechanical actuator or a wide variety of other actuators. In the example shown in FIGS. **2** and **3**, a rod **130** is coupled to a parallel linkage **132** and is used to exert an additional downforce (in the direction indicated by arrow **134**) on row unit **106**. The total downforce (which includes the force indicated by arrow **134** exerted by actuator **136**, **126**, plus the force due to gravity acting on row unit **106**, and indicated by arrow **136**) is offset by upwardly directed forces acting on closing wheels **124**, **168** (from ground and indicated by arrow **140**) and disc opener **120**, **164** (again from ground and indicated by arrow **142**). In FIG. **3** the offsetting force may also include upwardly directed forces on row cleaner **118**. The remaining force (the sum of the force vectors indicated by arrows **134** and **136**, minus the force indicated by arrows **140** and **142**—and in the example shown in FIG. **2**, the force on cleaner **118**) and the force on any other ground engaging component on the row unit, is the differential force indicated by arrow **146**. The differential force may also be referred to herein as the downforce margin. The force indicated by arrow **146** acts on the gauge wheels **122**, **166**. This load can be sensed by a gauge wheel load sensor, which may be located anywhere on row unit **106** where it can sense that load. The gauge

wheel load sensor can also be placed where it may not sense the load directly, but a characteristic indicative of that load. For example, the load sensor can be disposed near a set of gauge wheel control arms (or gauge wheel arm), such as arms **148** in FIG. **2** that movably mount gauge wheels **166** to shank **152** and control an offset between gauge wheels **166** and the discs in double disc opener **164**, to control planting depth.

[0087] Some items regarding planting depth and seed delivery are now shown and described with respect to FIG. **3** for the sake of example, but they could also be shown and described in a similar way with respect to FIG. **2**. Arms (or gauge wheel arms) **148** illustratively abut against a mechanical stop (or arm contact member—or wedge) **151**. The position of mechanical stop **151** relative to shank **153** can be set by a planting depth actuator assembly **155**. Control arms **148** illustratively pivot around pivot point **157** so that, as planting depth actuator assembly **155** actuates to change the position of mechanical stop **151**, the relative position of gauge wheels **166**, relative to the double disc opener **164**, changes, to change the depth at which seeds are planted.

[0088] In operation, row unit **106** travels generally in the direction indicated by arrow **160**. The double disc opener **164** opens the furrow **182** in the soil **138**, and the depth of the furrow **182** is set by planting depth actuator assembly **155**, which, itself, controls the offset between the lowest parts of gauge wheels **166** and disc opener **164**. Seeds are dropped through seed tube **170**, into the furrow **182** and closing wheels **168** close the furrow **182**, e.g., push soil back into the furrow **182**.

[0089] As the seeds are dropped through seed tube **170**, they can be sensed by seed sensor **172**. Some examples of seed sensor **172** may include an optical or reflective sensor, which includes a radiation transmitter component and a receiver component. The transmitter component emits electro-magnetic radiation and the receiver component then detects the radiation and generates a signal indicative of the presence or absence of a seed adjacent the sensors. In another example, row unit **106** may be provided with a seed firmer that is positioned to travel through the furrow **182**, after seeds are placed in furrow **182**, and before the furrow **182** is closed to firm the seeds in place. A seed sensor can be placed on the seed firmer and generate a sensor signal indicative of a seed. Some examples of other seed sensors are described in greater detail below.

[0090] In order to determine where a seed is to be placed, in one example, a target determination component described below with respect to FIG. **7** first determines where the fertilizer or other material has been placed. The location of the fertilizer or other material may be determined by material application control system **113**. Material application control system **113** illustratively is programmed with, or detects a distance, e.g., a longitudinal distance, that the distal tip **119** is from the exit end **171** of seed tube **170**. System **113** also illustratively senses, or is provided (e.g., by another component, such as a GPS unit or a tractor, etc.), the ground speed of row unit **106**. As the row units **106** on an implement being towed by a prime mover (e.g., a tractor) may move faster or slower than the tractor during turns, particularly as the width of the implement increases, the material application control system **113** may sense or be provided the ground speed of each row unit **106** of the implement. By way of example, the material application control system **113** may sense or be provided information when the implement is turning right indicating that the rightmost row unit **106** is travelling slower, i.e., has a lower ground speed, than the leftmost row unit **106**. Further, the material application control system **113** detects, is provided, or is programmed with, system data indicating the responsiveness of actuator **109** and/or motor **156** and commodity meter **158**, under certain conditions (such as under certain temperature conditions, certain humidity conditions, certain elevations, when spraying a certain type of fluid, etc.) and system **113** also detects, is provided, or programmed with one or more properties of the material being applied through actuator **109** and commodity delivery system **98** (as this may affect the speed at which actuator **109** and/or system **154** responds, the time it takes for the material to travel through application assembly **117** to the distal tip **119** or delivered by system **98** and be applied to furrow **182**, etc.). Further, material application control system **113** illustratively detects (or is provided with a sensor signal indicative of) the forward speed of row unit **106** in the direction generally indicated

by arrow **160**.

[0091] With this type of information, once system **113** receives a signal indicating that fertilizer or other material is dispensed, system **113** It then determines where tip **119** (or an outlet end of commodity delivery system **98**) was when the valve **109** was actuated or commodity motor **156** was actuated to determine the location where the material was applied in the furrow. By way of example, it may be that some material is to be applied in discontinuous strips in the furrow, of a given (the strips having a pre-set, default, or selected) length. In that case, system **113** times the actuation of actuator **109** so that the applied material will be applied as strips of the given length. Further, actuator **109** can be actuated to dispense material at a varying rate. System can control actuator **109** to dispense more material at a first set of locations and less at other locations spaced from the first set of locations or according to other patterns. The seeds can then be placed at desired locations relative to such patterns of material placement.

[0092] It will be noted that a wide variety of different configurations are contemplated herein. For instance, in one example, FIG. **3** shows that actuator **109** may be placed closer to the distal tip **119** (such as indicated by actuator locations **109A** and **109B**). In this way, there is less uncertainty as to how long it will take the material to travel from the actuator **109A** and **109B** to the distal tip **119**. In yet another example, the valve or actuator **109** is disposed at a different location. All of these and other configurations are contemplated herein.

[0093] FIG. **4** shows one example of a rotatable mechanism that can be used as part of the seed metering system **114**, **174**. The rotatable mechanism includes a rotatable element **200**, such as a disc or concave element. Rotatable element **200** has a cover (not shown) and is rotatably mounted relative to the frame of the row unit **106**. Rotatable element **200** is driven by a motor and has a plurality of projections or tabs **202** that are closely proximate corresponding apertures **204**. A seed pool **206** is disposed generally in a lower portion of an enclosure formed by rotatable element **200** and its corresponding cover. Rotatable element **200** is rotatably driven by a motor (such as an electric motor, a pneumatic motor, a hydraulic motor, etc.) for rotation generally in the direction indicated by arrow **208**, about a hub. A pressure differential is introduced into the interior of the metering system so that the pressure differential influences seeds from seed pool **206** to be drawn to apertures **204**. For instance, a vacuum can be applied to draw the seeds from seed pool **206** so that they come to rest in apertures **204**, where the vacuum holds them in place. Alternatively, a positive pressure can be introduced into the interior of the metering system to create a pressure differential across apertures **204** to perform the same function.

[0094] Once a seed comes to rest in (or proximate) an aperture **204**, the vacuum or positive pressure differential acts to hold the seed within the aperture **204** such that the seed is carried upwardly generally in the direction indicated by arrow **208**, from seed pool **206**, to a seed discharge area **210**. It may happen that multiple seeds are residing in an individual seed cell. In that case, a set of brushes or other members **212** that are located closely adjacent the rotating seed cells tend to remove the multiple seeds so that only a single seed is carried by each individual cell. Additionally, a sensor **214** is also illustratively mounted adjacent to rotatable element **200**.

[0095] Once the seeds reach the seed discharge area **210**, the vacuum or other pressure differential is illustratively removed, and a positive seed removal wheel or knock-out wheel **216**, can act to remove the seed from the seed cell. Wheel **216** illustratively has a set of projections **218** that protrude at least partially into apertures **204** to actively dislodge the seed from those apertures. When the seed is dislodged, it is illustratively moved by the seed delivery system **116** (one example of which is seed tube **170** and two other examples of which are shown below in FIGS. **5** and **6**) to the furrow in the ground. FIG. **4** shows seeds **173** and **175** approaching knock-out wheel **216** and seed **230** after being removed from aperture **204** by one of the projections **218** on knock-out wheel **216**.

[0096] It will be noted that the motor that drives rotation of meter rotatable element **200** or rotatable element **200**, itself, can be arranged relative to a seed meter sensor that generates a sensor

signal indicative of the angular position of the motor, or the rotatable element **200**, or another item from which the angular position of rotatable element **200**, can be derived. As described below, the angular position of rotatable element **200**, along with the signal from seed sensor **214** and the speed of rotation of meter **114**, **174**, can be used to determine the position of the seed as it moves through the seeding system and into the ground. This can be used to control the dispensing of seeds at precise field locations.

[0097] In one example, the seed meter sensor comprises a rotary or angle encoder that senses an angular position of a portion of seed metering system **114**, **174**, or of the motor driving seed metering system **114**, **174**. For instance, a rotary encoder can be mounted inside the motor driving the meter shaft, or can be external to the motor and configured to sense the meter shaft. A locating feature (such as a keyed interface) can be utilized in mounting the seed meter disc to the shaft, such that the position of the seed cells relative to the motor shaft position is pre-defined or known. Examples of the seed meter sensor include tooth encoders, Hall Effect sensors, and the like.

[0098] In another example, an optical sensor is utilized. For instance, one or more optical sensors can be positioned relative to slot(s) formed in the seed meter. As the disc rotates, the **16** optical sensors detect the slots (e.g., an optical sensor detects light passing through a slot) as they pass by the optical sensor.

[0099] In another example, the seed meter sensor can be a proximity sensor configured to measure seed cells directly, or other features of rotatable element **200**.

[0100] FIG. **5** shows an example where the rotating element **200** is positioned so that its seed discharge area **210** is above, and closely proximate, seed delivery system **116** which includes an assistive seed delivery or transport mechanism. In the example shown in FIG. **5**, the seed transport mechanism includes a belt **220** with a brush that is formed of distally extending bristles **222** attached to belt **220**. Belt **220** is mounted about pulleys **224** and **226**. One of pulleys **224** and **226** is illustratively a drive pulley while the other is an idler pulley. The drive pulley is illustratively rotatably driven by a conveyance motor which can be an electric motor, a pneumatic motor, a hydraulic motor, etc. Belt **220** is driven generally in the direction indicated by arrow **228**.

[0101] Therefore, when seeds **230** are moved by rotating element **200** to the seed discharge area **210**, where they are discharged from the seed cells in rotating element **200**, they are illustratively positioned within the bristles (e.g., in a receiver) **222** by the projections **202** following each aperture **204** and the projections **218** on knock-out wheel **216** that pushes the seed into the bristles **222**. Seed delivery system **116** illustratively includes walls that form an enclosure around the bristles **222**, so that, as the bristles **222** move in the direction indicated by arrow **228**, the seeds **230** are carried along with the bristles **222** from the seed discharge area **210** of the metering mechanism, to a discharge area **232** where the seeds are discharged either at **6** ground level, or below ground level within a trench or furrow **182** that is generated by the furrow opener **120**, **164** on the row unit **106**. Seed **161** is shown after being discharged from discharge area **232**, and seeds **167** are shown after coming to rest in furrow **182**.

[0102] Additionally, a sensor **234** is also illustratively coupled to seed delivery system **116**. As the seeds are moved within bristles **222**, sensor **234** can detect the presence or absence of a seed. It should also be noted that while the present description will proceed as having sensors **214** and **234**, it is expressly contemplated that, in another example, only one sensor is used. Additional sensors can also be used.

[0103] FIG. **6** is similar to FIG. **5**, except that seed delivery system **116** is not formed by a belt **220** with distally extending bristles **222**. Instead, the transport mechanism includes a flighted belt in which a set of paddles **236** form individual chambers (or receivers) **238**, into which the seeds **230** are dropped from the seed discharge area **210** of the metering mechanism. The flighted belt moves the seeds **230** from the seed discharge area **210** to the discharge area **232** within the trench or furrow **182**.

[0104] There are a wide variety of other types of delivery systems as well, that include a transport

mechanism and a receiver that receives a seed. For instance, the delivery system can include dual belt delivery systems in which opposing belts receive, hold and move seeds to the furrow **182**, a rotatable wheel that has sprockets which catch seeds from the metering system and move them to the furrow **182**, multiple transport wheels that operate to transport the seed to the furrow **182**, an auger, among others. The present description will proceed with respect to a brush belt, but many other delivery systems are contemplated herein as well.

[0105] As mentioned above, for a variety of reasons, significant deviations in the seed placement location or spacing (from a desired or optimal location or spacing) can occur. This can adversely affect yield, decreased field area utilization, and/or results in wasted seeds. The deviations can be caused by, for example, irregularities in the operation of seed metering system **114** (e.g., irregularities in the pressure differentials), variations in seed size and/or shape, foreign material in the seed system, etc. Even if seed delivery system **116** is matched or otherwise correlated to operation of seed metering system **114**, the seeds may be placed at incorrect locations and spacings. Further, it may be desirable to place the seeds at a specific location relative to where the fertilizer or other material has already been placed. This can be very difficult without being able to place the seeds accurately.

[0106] The present description provides a processing and control system for an agricultural machine that is configured to control seed release to a target location relative to the location of fertilizer or other previously-placed material. In one example, the processing and control system does this by tracking individual seed movement through portions of the seeding system or planter.

[0107] FIG. 7 shows a block diagram of one example of an agricultural machine architecture (or agricultural system) including an agricultural machine **201** having a processing and control system that includes seeding system **203**. One example of machine **201** includes machine **100** illustrated above with respect to FIG. 1. In the example shown in FIG. 7, each row unit **106** includes a seeding system **203** having a seed metering system **205** and a seed delivery system **207** disposed thereon or otherwise associated with the row unit **106**. Agricultural machine **201** can also include processing system **241**, control system **244**, one or more processors **276**, data store **274**, operator interface mechanisms **256**, position sensor(s) **266**, speed sensor(s) **268**, communication system **248**, seed ejection system **242**, crop care material application system **265**, and other items **278**. FIG. 7 also shows an operator **258** (which may be operator **92** in FIG. 1) interacting with operator interface mechanisms **256**. FIG. 7 further shows machine **201** coupled to remote system(s) **250**, which has remote user **254**, through network **252**.

[0108] Remote system **250** can be a wide variety of different types of systems. For example, remote system **250** can be a remote server environment, remote computing system that may be used, for example, by a remote user **254**. Further, it can be a remote computing system, such as a mobile device, remote network, or a wide variety of other remote systems. Remote system **250** can include one or more processors or servers, a data store, and it can include other items as well.

[0109] Network **252** can be any of a wide variety of different types of networks, such as the Internet, a cellular network, a local area network, a near field communication network, or any of a wide variety of other networks or combinations of networks or communication systems.

[0110] Communication system **248** can include wireless communication logic, which can be substantially any wireless communication system that can be used by the systems and components of machine **201** to communicate information to other items, such as between seeding system **203**, processing system **241**, and/or control system **244**. In one example, communication system **248** communicates over a CAN bus (or another network, such as an Ethernet network, etc.) to communicate information between systems **203**, **241**, and/or **244** or other items. This information can include the various sensor signals and output signals generated based on the sensor variables and/or sensed variables.

[0111] Position sensor(s) **266** are configured to determine a geographic position, heading, and/or route of machine **201**. Position sensor **266** can include, but is not limited to, a Global Navigation

Satellite System (GNSS) receiver **270** that receives signals from a GNSS satellite transmitter. Position sensor **266** can also include a Real-Time Kinematic (RTK) component that is configured to enhance the precision of position data derived from the GNSS signal from receiver **270**. Illustratively, an RTK component uses measurements of the phase of the signal's carrier wave in addition to the information content of the signal to provide real-time corrections, which can provide up to centimeter-level accuracy of the position determination. Position sensor(s) **266** can include other items **272** as well.

[0112] Speed sensor(s) **268** are configured to determine a speed at which machine **201** is traversing a worksite (e.g., field or other terrain) during the planting operation. This can include sensors that sense the movement of ground engaging elements (e.g., wheels or tracks), sensors that sense axle speed, and/or can utilize signals received from other sources, such as position sensor(s) **266**.

[0113] Machine **201** also includes a data store **274**, one or more processors **276**, and can include other items **278**. Data store **274** can store any of a wide variety of different types of information. Illustratively, data store **274** stores target seed planting data (e.g., planting maps or other models) **280**, actual seed planting data (e.g., planting maps) **282**, and can store other data items as well.

[0114] Seed metering system **205** includes a seed meter **209** that is driven by a motor **211** to meter or otherwise singulate seeds from a seed source (such as a seed container or tank). One example of seed meter **209** is illustrated above with respect to FIG. 4.

[0115] Seed metering system **205** can include a seed meter sensor **213** configured to sense characteristics of seed metering system **205** and to generate a sensor signal indicative of a position of seed meter **209**. For example, sensor **213** can directly sense seed meter **209** and/or it can sense motor **211** (or other component that drives seed meter **209**), such as a speed and/or position of motor **211** (e.g., an angular position of a motor output shaft). Some examples of seed meter sensor **213** are discussed above. For instance, sensor **213** can include, but is not limited to, an angle encoder, a Hall Effect sensor, an optical sensor, or any of a wide variety of other sensors that generate a signal indicative of angular position. A seed presence sensor **215** (also **11** referred to as seed sensor **215**) can also be provided that senses the presence of seeds in seed meter **209**, and can include other items **217** as well. One example of seed sensor **215** can be seed sensor **214** shown in FIG. 4.

[0116] Seed delivery system **207** includes an assistive seed transport mechanism **219** driven by a motor **221**. Examples of seed transport mechanism **219** can be the brush belt and flighted belt illustrated above with respect to FIGS. 5 and 6, respectively.

[0117] Seed delivery system **207** can include a mechanism position sensor **223** configured to sense characteristics of seed delivery system **207** and to generate a sensor signal indicative of a position of an assistive seed transport mechanism **219**. For example, sensor **223** can directly sense mechanism **219** and/or it can sense a motor **221** that drives mechanism **219**.

[0118] For instance, sensor **223** can be integrated into motor **221**, or provided separately (e.g., external to motor **221**), and configured to sense operational characteristics of motor **221**. For example, sensor **223** can be mounted, to a shaft of a gearbox, a pulley, and/or motor **221**.

[0119] In one example, sensor **223** senses an angular position of an output shaft of motor **221**, that is rotatably coupled to drive seed transport mechanism **219** to transport seeds, received from seed metering system **208**, to a second or release position in which the seeds are released from the seed transport mechanism **219**. Some examples of sensor **223** are discussed above. For instance, sensor **223** can include, but is not limited to, an angle encoder, a Hall Effect sensor, an optical sensor, or any of a wide variety of other sensors that generate a signal indicative of angular position.

[0120] It is noted that while separate motors **211** and **221** are illustrated in FIG. 7, in another example only one motor is used to drive both seed metering system **205** and seed delivery system **207**. Further, seed delivery system **207** may also be seed tube **170** described above with respect to FIG. 3, in which case motor **221**, motor sensor **223**, and seed transport mechanisms **219** are not needed.

[0121] A seed presence sensor **225** (also referred to as seed sensor **225**) is positioned along the transport route to detect the presence of seeds at the sensor location. Examples of seed sensor **225** include seed sensor **172** shown above in FIG. 3, and sensor **234** illustrated above in FIGS. 5 and 6. Seed sensor **225** is configured to generate and send a sensor signal indicative of the sensed seed presence. As used herein, a sensor signal includes both an analog signal and a digital signal, such as communications using a controller area network (CAN) bus.

[0122] In addition to sending an indication (e.g., a sensor signal) indicative of the presence of a seed in the seed transport mechanism **219**, seed sensor **225** (or another sensor) can be configured to sense a characteristic of the seed, such as, but not limited to, a size, shape, color or other characteristic (such as an indication that the seed is cracked or otherwise irregular). Seed delivery system **207** can include other items **227** as well.

[0123] It is noted that while FIG. 7 illustrates seed sensors **215** and **225** in each of seed metering system **205** and seed delivery system **207**, in one example only seed metering system **205** includes a seed sensor (or system **207** does not include a seed sensor) configured to sense the presence of seed as the seed passes the sensor location. In another example, only seed delivery system **207** includes a seed sensor (or system **205** does not include a seed sensor) configured to sense the presence of seed as the seed passes the sensor location.

[0124] In one example, seed sensor **215** (and/or seed sensor **225**) includes an optical or reflective sensor and thus includes a transmitter component and a receiver component. In another example seed sensor **215** (and/or seed sensor **225**) includes a mechanical sensor that senses the seed presence, or it can be another type of sensor that senses the presence of the seed.

[0125] The transmitter component emits electromagnetic radiation, into seed delivery system **207** in the case of a reflective sensor. The receiver component then detects the reflected radiation and generates a signal indicative of the presence or absence of a seed adjacent to the sensor based on the reflected radiation. With other sensors, radiation such as light, is transmitted through the seed delivery system **207**. When the light beam is interrupted by seed, the sensor signal varies to indicate a seed. Thus, the sensor generates a seed sensor signal that pulses or otherwise varies, and the pulses or variations are indicative of the presence of a seed passing the sensor location proximate the sensor.

[0126] In the example of a rotating brush belt, such as the example shown above with respect to FIG. 5, bristles (e.g., bristles **222**) absorb a majority of the radiation emitted from the transmitter component. As a result, absent a seed, reflected radiation received by the receiver is relatively low. Alternatively, when a seed passes the sensor location, more of the emitted light is reflected off the seed and back to the receiver component, indicating the presence of a seed. The differences in the reflected radiation allow for a determination to be made as to whether a seed is, in fact, present. Additionally, in other examples, a seed sensor can include a camera and image processing logic that provides visual detection as to whether a seed is present within seed delivery system **207**, at the sensor location proximate the sensor.

[0127] Seeding system **203** (e.g., on a particular row unit **106**) can also include a furrow opener **229** (such as furrow openers **120**, **164**) configured to form a furrow or trench in the ground, a delivery endpoint component **231** configured to deliver the seed into the furrow, and a controller **233**. In one example, controller **233** provides a closed loop control system and can include a processor **235** and a timer **237**, which can be used to time the performance of operations within seeding system **203**. Of course, seeding system **203** can include other items **239** as well.

[0128] Agricultural machine **201** includes a processing system **241** having a seed tracking system **240** configured to track seed movement within seeding system **203** and a seed ejection system **242** configured to control, or to generate control signals that are used by a control system **244** to control, ejection of the seeds from component **231**. It is noted that while processing system **241** is broken out separately in FIG. 7, some or all of the tracking and ejection control functions can be performed by seeding system **203**. The illustration in FIG. 7 is for sake of example only.

[0129] As discussed in further detail below, processing system **241** is configured to control one (or both) of seed metering system **205** and seed delivery system **207** to place seeds at desired locations relative to previously-placed fertilizer or other material based on the speed of agricultural machine **201** and the position and/or speed of the respective system being controlled (i.e., **114** and/or **116**), when seed is detected and when the seed is to be released from the respective system.

[0130] For sake of illustration, processing system **241** is configured to receive a sensor signal that represents the angular position of system **205** (e.g., seed meter **209** itself or motor **211** driving it) when seed sensor **215** senses a seed in seed meter **209**. This angular position is correlated to the position of the sensed seed. Therefore, processing system **241** determines or tracks the location of the sensed seed along a conveyance path through seed metering system **205**. System **241** can then calculate the angular distance (and/or time) it will take for system **205** (or seed meter **209**) to rotate to a position where the seed exits seed metering system **205** (e.g., at seed discharge area **210**), and is provided to seed delivery system **207**. This position corresponds to the interface, or hand-off point, between systems **205** and **207**.

[0131] By sensing the angular position of system **205**, processing system **241** can determine the point in time at which a particular seed is released by seed metering system **205** and received by seed delivery system **207**. Processing system **241** can then correlate the position of the particular seed to the angular position of system **207** (e.g., to the angular position of mechanism **219** itself or motor **221** driving it).

[0132] Before discussing processing system **241** in further detail, other components of machine **201** will be described.

[0133] In the example illustrated in FIG. 7, control system **244** is configured to control other components and systems of machine **201**. For instance, control system **244** generates control signals to control communication system **248** to communicate between components of machine **201** and/or with other systems, such as remote system **250** over a network **252**. Control system **244** includes row unit controller (RUC or controller) **246**, display device controller **260**, material application control system **113**, and other items **264**. Display device controller **260** can control interfaces, such as operator interface mechanisms **256** that include input mechanisms configured to receive input from an operator **258** and output mechanisms that render outputs to operator **258**. The operator input mechanisms can include mechanisms such as hardware buttons, switches, joysticks, keyboards, etc., as well as virtual mechanisms or actuators such as a virtual keyboard or actuators displayed on a touch sensitive screen. The output mechanisms can include display screens, speakers, other audio, visual, or haptic items, etc.

[0134] Control system **244** also is illustrated as including material application control system **113**. Material application control system **113** is configured to control a crop care material application system **265** to control the application of chemicals, such as fertilizers, herbicides, pesticides, and the like. Thus, crop care material application system **265** can include actuator(s) **109**, pump(s) **115**, etc. that are discussed above and controlled by material application control system **113**. System **113** can generate an output indicative of where and/or when material is applied to the field by system **265**.

[0135] In the illustrated example, row unit controller **246** controls seeding system **203** based on processing performed by processing system **241** and based on where material is applied to the field as controlled by material application control system **113**. This can include sending messages or other signals over any suitable communication mechanism, such as a CAN bus. Controller **246** can thus control, either directly or with controller **233**, the seeding system on each row unit.

[0136] It is noted that in one example seeding system **203** (e.g., on a particular row unit) includes some (or all) of the components and related functionality described with respect to processing system **241**. This is represented by the dashed block in FIG. 7.

[0137] Processing system **241** includes one or more processors **243**, and seed tracking system **240**. In one example, processor **243** implements a timer **245** utilized in conjunction with timer **237** of

seed delivery system **207**, to coordinate the sending and receiving of signals and messages between processing system **241** and seeding system **203**. Also, the timers **237** and **245** can be utilized for the generation and application of control signals by control system **244** to seeding system **203**, to control operation of seed delivery system **207** in transporting seeds to endpoint component **231**. In one example, communication system **248** includes a timestamp generator **249**. Timestamp generator **249** is configured to generate timestamps, using timers **237** and **245**, on messages and signals sent by systems **207** and **241**. The timestamps can be utilized by the receiving system to determine a latency in the communication channel.

[0138] Seed tracking system **240** illustratively includes a signal conditioner **284**, seed presence detector **286**, seed characteristic determination component **288**, seed position calculation component **290** (which includes motor position detection and correlation component **292**, motor speed detection component **294**, seed tracking queue **296**, time correlation and offset compensation component **298**, and other items **299**). Signal conditioner **284** receives signals generated by sensor **225** (and/or sensor **215**), and to condition those signals for subsequent processing. Conditioning can include amplifying the generated sensor signal, performing filtering, linearization, normalization, and/or any other conditioning which can improve the quality of the sensor signal. The conditioned signal is then provided to other components of seed tracking system **240** such as, but not limited to, seed presence detector **286**, seed characteristic determination component **288**, and seed position calculation component **290**.

[0139] Seed presence detector **286** receives the sensor signal, which may be conditioned, and determines whether a seed is present in the transport route of seed transport mechanism **219**, **8** at the location corresponding to seed sensor **225**. Seed presence detector **286** can distinguish **9** between seed sensor signals which indicate background noise (indicating an absence of seed) and a pulse (indicating the presence of a seed).

[0140] Seed characteristic determination component **288** is configured to detect a characteristic of the seed. For instance, component **288** can generate an output indicative of a size, shape, color, or other characteristic of the seed. This can be utilized to determine whether the detected seed is, instead, foreign material (and thus not an actual seed), or whether the seed may have an irregularity, such as being cracked, etc., that may affect its germination and subsequent growth.

[0141] Seed position calculation component **290** calculates the position of the seed in seed transport mechanism **219**, thus facilitating tracking of movement of the seed through seed delivery system **207** as seed transport mechanism **219** (e.g., brush belt) is rotated by motor **221**. Component **290** includes motor position detection and correlation component **292** which detects the angular position of the output shaft of motor **221**, which can be coupled directly, through a transmission component, or otherwise, to seed transport mechanism **219**. In either case, component **292** correlates the position of the detected seed to the angular position of the output shaft of motor **221**.

[0142] A motor speed detection component **294** detects the speed of motor **221**, as it rotates to move seed transport mechanism **219** and convey the seed along the transport route. Seed tracking queue **296** stores tracking information for each seed whose presence is detected by detector **286**. In one example, seed tracking queue **296** stores a plurality of data records or other data items that identify each seed individually, along with information that correlates the position of the seed to the position of mechanism **219** for position tracking of the individual seed. For instance, a two-dimensional array of values can be stored representing seed and mechanism (e.g., belt) position. The information in seed tracking queue **296** can be utilized to identify a number of seeds that are presently in seed transport mechanism **219**, as well as the spacings between each seed and a magnitude of rotation of the output shaft of motor **221** needed to move that seed to the release point, to release the seed toward endpoint component **231**.

[0143] Depending on the type of communication channel utilized by communication system **248**, latencies may be introduced in the communications. For example, a typical CAN message-based communication has latency delays on the order of 5 milliseconds. The time correlation and offset

compensation component **298** correlates each message or other communication sent between processing system **241** and seeding system **203** using timestamps generated by the timestamp generator **249**. Component **298** thus accounts for these latencies, by compensating for timing offsets.

[0144] Seed ejection system **242** includes a target determination component **302**, machine position and speed detector **304**, seed ejection control component **306**, geo-referenced seed placement component **316** and other items **318**. Seed ejection control component **306** includes target motor speed **312**, target motor position **310**, target ejection time **308** and end point compensation component **314**. Target determination component **302** identifies a target or target parameter for ejecting each seed from seed delivery system **207**. The target or target parameter can represent any of a variety of different types of parameters. In the illustrated example, but not by limitation, the target is a target geographic location on the terrain (field) and may be identified relative to the location of previously-placed fertilizer or other material). In one example, the target geographic location is referenced to an absolute location in the field, such as using global coordinates in a global coordinate system (e.g., World Geodetic System (WGS)). In one example, the target geographic location is referenced to local coordinates in the field.

[0145] Further, target locations for seed placement can be pre-defined (e.g., a target planting map) based on fertilizer or other material locations. Alternatively, or in addition, the target or target parameter for seed placement is determined in situ or “on-the-fly” based on the application of fertilizer or other material. In one example, target location for placement of a next seed is determined based on a location and/or characteristic of a prior seed ejected by seed system **202** and the location and/or characteristic of fertilizer or other already-applied material.

[0146] The location or timing of previous fertilizer application or other material application can be identified based on an output from material application control system **113** or in other ways. That location or timing can then be used by target determination component **302** to identify the target parameter indication how the seed metering system **205** and/or seed delivery system **207** should be controlled to deliver seed to the furrow **182**.

[0147] Machine position and speed detector **304** detects the geographic position of machine **201** using signals from position sensor(s) **266** and determines the speed of machine **201** based on signals from speed sensor(s) **268**.

[0148] Seed ejection control component **306** generates a motor operating parameter to control motor **221** to eject each seed based on the target parameters determined by target determination component **302**. In the illustrated example, component **306** identifies, for each individual seed in mechanism **219**, a target ejection time (or timing) **308** for releasing the seed from component **231**, a target motor position **310** corresponding to target ejection time **308**, and a target motor speed **312** corresponding to target ejection time **308**.

[0149] Target ejection time (or timing) **308** is determined based on the target location or other target parameter for the seed placement and the current machine position and machine speed. That is, the target ejection time (or timing) **308** represents the time (or time offset from a known time) at which the next seed in mechanism **219** is to be released so that it is placed in the furrow at the target location or according to another target parameter which is, itself, determined based on a location or timing and/or other characteristic of previously-placed fertilizer or other material.

[0150] In one example, determination of target ejection time (or timing) **308** is compensated for a time delay between when the seed is released from seed transport mechanism **219** and the seed is deposited in the furrow by delivery endpoint component **231**. Accordingly, an endpoint compensation component **314** generates an estimation of an amount of time that it will take the seed to pass from seed transport mechanism **219** (after release) through delivery endpoint component **231** and reach the furrow. This time delay can vary based on the distance to, and geometry of, component **231**.

[0151] For sake of illustration, but not by limitation, assume that component **314** determines that it

will take approximately one-half second for the seed to reach the furrow, once released from mechanism **219**. Here, target ejection time **308** is calculated so that the seed is released approximately one-half second before component **231** (e.g., seed boot) is at the target location (taking into account the current machine position and the machine speed).

[0152] Component **306** identifies target motor position **310** for releasing the seed at the target ejection time **308**. Illustratively, the target motor position **310** represents an angular rotational position of the output shaft of motor **221** at which mechanism **219** will be at a position in which the given seed will be released from mechanism **219** toward component **231**. In one example, target motor position **310** is calculated based on a predefined rotational range over which the output shaft of motor **221** must rotate to move the portion of mechanism **219** containing the seed from the sensor location to the release location.

[0153] Component **306** identifies target motor speed **312** based on an offset instantaneous speed of mechanism **219** when the seed is released. This offset speed determines the velocity of the seed (relative to the row unit) when the seed is released. In one example, the target motor speed **312** is determined based on the machine speed. For instance, target motor speed **312** is selected so that the speed of transport mechanism **219** (and thus the speed of the seed when it is released) matches and thus offsets the speed of machine **201** so the seed is ejected rearwardly relative to the direction of travel of machine **201** at the same speed that machine **201** is traveling. The offset speed thus discourages, if not prevents, the seed from rolling in the furrow.

[0154] A geo-referencing seed placement component **316** is configured to generate a geo-referenced placement indicator that indicates the actual placement location of each seed. For example, when each seed is released from seed delivery system **207**, component **316** determines the actual planting location of that seed by correlating it to GPS coordinates (or otherwise). This information can be stored as actual seed planting location data **282**. Of course, system **242** can include other items **318** as well.

[0155] FIG. **8** is a flow diagram **400** illustrating an example operation of an agricultural machine. For sake of illustration, but not by limitation, FIG. **8** will be described in the context of agricultural machine **201** illustrated in FIG. **7**.

[0156] At block **402**, the systems of machine **201** are calibrated or otherwise configured for operation. This can be done manually (represented by block **404**), automatically (represented by block **406**), or a combination of manual or automatic processes (block **408**).

[0157] In one example, block **402** includes synchronizing timers **237** and **245**, which are utilized for sending and receiving control signals and messages between processing system **241** and seeding system **203**. Synchronizing timers is represented by block **410**. In one example, timers **237** and **245** comprise parallel independent clocks running on corresponding processing units that are synchronized in time on the order of ten to one hundred microseconds. Timers **237** and **245** can be synchronized in any of a variety of ways. A message or other signal is sent between systems **203** and **241** using any suitable communication protocol. In one example, a separate physical hardware bus provides a signal line between the systems for timer synchronization. Of course, this is only one example. After timer synchronization, a message sent by a sending one of the systems includes a timestamp generated (using timestamp generator **249**) based on a time of the timer (**237** or **245**) of the sending system. The timer (**237** or **245**) of the receiving system can then be utilized to determine latency in the communication of the message through the communication channel. The receiving system can then account for a latency delay, in particular when using communication protocols such as CAN message-based communication. Further, the timestamps and corresponding timer(s) can be used to extrapolate values to use between the sending and receiving of the messages.

[0158] For the sake of illustration, as noted above CAN bus messages are often limited by sampling rate. Timestamps can be bundled with the data broadcast in the CAN messages to enable the receivers of the data to extrapolate higher accuracy data, such as position or time estimates. For

instance, assume a scenario in which motor sensor **223** sends periodic messages indicating the angular position of the output shaft of motor **221**. If each of these messages is timestamped based on the current value of timer **237**, then using the value of timer **245** processing system **241** can extrapolate the position at intervening times between those messages. Thus, if a seed is detected by seed sensor **225** at a time between the messages sent by sensor **223**, then processing system **241** can accurately determine the position of the seed relative to the motor output shaft by extrapolating the position of the output shaft from the timestamped messages sent by sensor **223**.

[0159] Likewise, a corresponding extrapolation process can be utilized to determine seed spacing between adjacent seeds in seed transport mechanism **219** by using the detected velocity of seed transport mechanism **219** (based on signals from sensor **223**) and timestamps of the corresponding seed presence signals generated by seed sensor **225**, for those adjacent seeds.

[0160] It is worth noting that, in some implementations, motor **221** can be directly coupled to seed transport mechanism **219**. In other examples, the output shaft of motor **221** can be coupled to seed transport mechanism **219** through a transmission, such as a set of gears at a particular gear ratio. The gear ratio of the transmission can be utilized to determine the position of the seed transport mechanism **219**, and thus seeds carried along the transport route, relative to the position of the output shaft of motor **221**.

[0161] At block **412**, a position offset of each delivery endpoint component (i.e., the delivery endpoint component **231** on each row unit) is determined. The position offset represents a difference between the position sensed by the position sensor (i.e., position sensor **266** in FIG. 7) associated with machine **201** and the particular location of the endpoint component **231**. The position sensor may be located on a central frame of machine **201**, on a support vehicle such as a towing tractor, or otherwise. The position offset represents a multi-dimensional coordinate displacement from that sensor location. Using the position offset, the precise location of each endpoint component **231** can be determined based on the sensor signal generated by the position sensor **266**.

[0162] At block **414**, an ejection time offset or delay is determined based on the characteristics of seed delivery system **266**. As mentioned above, an ejection time offset or delay represents an estimated time that it will take a seed that is released from seed transport mechanism **219** to reach the furrow. This offset or delay is based, at least in part, on the size, shape, and/or geometry of the delivery endpoint component **231**, and any intermediate components that connect component **231** to the release position of mechanism **219**. Of course, the systems can be calibrated in other ways as well, as represented by block **416**.

[0163] At block **418**, a seeding operation is initiated. The operation can be initiated manually based on inputs from operator **258**, automatically, or otherwise. Material application control system **113** can control crop care material application system **265** to apply material to a location on the field, as indicated by block **417**. The material can be fertilizer or other material applied to the surface of the field, or to a furrow opened, ahead of the seed delivery end of the delivery end point component **231** of the seed delivery system **207**. The material may be applied during a prior operation as well.

[0164] The target parameter is then identified by target determination component **302**, as indicated by block **419**. The target parameter may be a globally referenced or locally referenced geographic location where the seed is to be placed based on the location of the applied material. The target parameter may be a timing for seed delivery, based on when the material was applied and based on a delay between when the material is applied and when the delivery end of the delivery end point component **231** of the seed delivery system **207** will be in position to eject the seed at the desired location relative to where the material is placed. Once the seeding operation is initiated, seed meter **209** is operated to meter seed from a seed source, such as a seed tank or container to an interface between seed metering system **205** and seed delivery system **207**, where the seed is handed off to seed transport mechanism **219**, as represented by block **420**.

[0165] At block **422**, motor **221** of seed delivery system **207** is operated to move seed transport

mechanism **219** to transport the metered seed, received from seed meter **207**, along a transport route to a second, release position in which the seed is released. Movement of the seeds along the transport route is tracked at block **424**. The seeds can be tracked based on a seed presence signal (indicative of seed presence at the sensor location) received from seed sensor **225** and detected by seed presence detector **286**, as is represented by block **426**. The movement of the seeds can also be tracked based on detected movement of transport mechanism **219**. In one example, this tracking is based on a signal from sensor **223**, which indicates the change in angular position of the output shaft of motor **221**, which in turn indicates the amount of movement of seed transport mechanism **219** (e.g., the bristles in the case of a brush belt) along the transport route for a given time period. Tracking this movement is represented by block **428**.

[0166] As noted above, in the case where a transmission couples motor **221** to seed transport mechanism **219**, movement of the transport mechanism can be detected based on the angular change in position of the output shaft of motor **221**, taking into account a gear ratio between the output shaft and mechanism **219**.

[0167] At block **430**, a motor operating parameter is generated based on the tracked position of the seed and the target parameter for releasing the seed onto the terrain (e.g., into the furrow created by furrow opener **229**). In one example, a target parameter includes, or is otherwise indicative of, a target geographic location or timing for ejecting the seed. The target parameter can be a global or absolute geographic location, such as latitude and longitudinal coordinates, or can be relative to a particular location on the terrain (such as a location relative to the location of a fertilizer or other material placement), or a timing parameter based on when the fertilizer or other material was placed. The motor operating parameter can be generated in other ways as well, as represented by block **434**. At block **436**, motor **221** is operated to drive movement of seed transport mechanism **219** based on the motor operating parameter.

[0168] At block **438**, seed placement locations for the seeds are stored. In one example, this information is stored as planting maps **282** in data store **274**. A planting map **282** represents the actual seed planting locations as, for example, a dot matrix or other suitable representation. A planting map **282** can also store the fertilizer or other material locations and can be utilized during a subsequent spraying operation, a subsequent harvesting operation, and/or a planting operation in a subsequent year. For example, it may be that the harvesting operation utilizes the **8** information as estimated yield data for specific areas of the field. In another example, planting operations in a subsequent year may use the planting maps from the prior year so that crop rows are placed in an area of the field that resides between the crop rows from the prior year.

[0169] At block **440**, a control signal is generated based on the seed placement locations. In one example, the control signal can control a display on, or associated with, machine **201** to display the seed placement locations, as is represented by block **442**. Alternatively, or in addition, the seed placement location information can be sent to remote system **250**, as represented by block **444**. In another example, subsystems of machine **201** can be controlled, as represented by block **446**. Control systems can be generated in other ways as well, as is represented by block **448**.

[0170] FIG. **9** is a flow diagram **450** illustrating one example of operation of a seed tracking system. For sake of illustration, but not by limitation, FIG. **9** will be discussed in the context of seed tracking system **240** illustrated in FIG. **7**.

[0171] At step **452**, presence of a seed in seed transport mechanism **219** is detected at a first (sensor) location (e.g., at the location of sensor **234** in FIG. **5**). In the illustrated example, detecting seed presence is based on a signal generated by seed sensor **225**, which is indicated by block **454**. In one example, a time-stamped message is received from controller **233** through communication system **248**, where the time stamp may be generated using timestamp generator **249**. The timestamp is indicative of a time of timer **237** when the seed presence was detected, as represented by block **456**. Presence of the seed can be detected in other ways as well, as represented by block **458**.

[0172] In one example, a characteristic of the seed can be detected, as represented by block **460**. For example, seed sensor **225** (and/or another sensor) can generate a signal indicative of a color (block **462**), a size (block **464**), a shape (block **466**), and/or irregularities (block **468**) of the seed. Other characteristics can be detected as well, as represented by block **470**.

[0173] Based on the characteristics detected at block **460**, seed characteristic determination component **288** can determine that the seed detected a block **452** is a typical seed, is an atypical seed (it has irregularities, such as being cracked) and/or is likely not a seed (e.g., foreign material, such as a different type of seed).

[0174] At block **472**, a position of the seed transport mechanism is detected or estimated. The position can be detected or estimated based on detecting the angular position of the motor output shaft, which is indicated by block **474**. Alternatively, or in addition, the angular position of the output shaft can be extrapolated based on other detected angular positions, as is represented by block **476**. For example, if the position of the motor output shaft is sampled every 10 milliseconds, then the position of the output shaft between those samples can be extrapolated based on the sampled positions and corresponding rotational speed.

[0175] At block **478**, the position information is received from controller **233** in a time-stamped message, that is timestamped by timestamp generator **249** based on timer **237**. As discussed above, the timestamps can be utilized to account for latency in the communications through communication system **248**.

[0176] At block **480**, based on a valid seed detection, the position of the seed is correlated to the position of the seed transport mechanism. For example, block **480** associates the angular position of the motor output shaft, at the time the seed is detected by seed sensor **225**, with the location of the seed at the sensor location. In one example, this association includes component **298** performing time correlation and offset compensation, examples of which are discussed above, as is represented by block **482**.

[0177] At block **484**, the seed position information is stored, for example in seed tracking queue **296**. In this example, at a given moment in time, seed tracking queue **296** stores representations of each seed currently in seed transport mechanism **219**, and corresponding position information, correlated to the angular rotation position of the motor output shaft.

[0178] At block **486**, seed tracking system **240** tracks movements of the seeds along the transport route, as seed transport mechanism **219** is moved by motor **221**. In this example, the movement is tracked based on a detected change in the angular position of the motor output shaft, which is represented by block **488**. Also, the movement can be tracked, taking into account any gear ratio or other transmission change between motor **221** and seed transport mechanism **219**, as is represented by block **490**.

[0179] At block **492**, the seed position information in seed tracking queue **296** is updated to reflect the new position information based on the movement tracked at block **486**. At block **494**, operation is continued for any subsequent seeds that are detected by the seed sensor.

[0180] FIG. **10** is a flow diagram **500** illustrating one example of controlling a seeding system based on tracked seed movements. For sake of illustration, but not by limitation, FIG. **10** will be discussed in the context of seed ejection system **242** illustrated in FIG. **7**.

[0181] At block **502**, a seed tracking queue is accessed for a particular seeding system. In one example, as noted above, seeding system **203** corresponds to a particular row unit, of a plurality of row units, on machine **201**. Thus, the operation shown in FIG. **10** can be performed for each row unit, on a separate row unit-by-row unit basis.

[0182] Based on the seed tracking queue for seeding system **203**, a target parameter is identified for a next seed in seed transport mechanism **219**, as represented by block **504**.

[0183] The target parameter is based on prior placement of material such as fertilizer or other material and can be identified in any of a number of ways. In one example, the target parameter is based on prior data, such as a map of prior material placement that can be used to generate a pre-

defined seed target map. A seed target map can take a variety of different forms. In one example, the seed target includes a dot matrix or other model that identifies specific geographic locations of individual seeds, as represented by block **506**. Alternatively, or in addition, the target parameter can be identified based in situ data, such as the sensed timing of the material applied to the field by the row unit, itself, and how that timing affects the timing or location for the seed placement, as represented by block **508**. Sensors on or otherwise associated with machine **201** can obtain this data as the planting operation occurs.

[0184] The target parameter identifies, in one example, a geographic target location for the seed, as represented by block **510**. As noted above, the target location can be a global geographic position, such as a position represented by longitude and latitude coordinates on a global coordinate system. In another example, the target location can represent a spacing (or offset) from the location of a previously-applied material.

[0185] For sake of illustration, material application control system **113** can generate control signals to control actuation of valve **109** and generate an output indicative of that actuation based on the sensed speed of the machine **201** and the known or sensed delay between actuation of valve **109** and when the material hits the ground. The timing of when the next seed should be ejected can be calculated and used by seed ejection system **242** to eject the next seed at a location that is in a desired relationship with (e.g., spaced from or the same as) the location of the applied material. In another using the information indicative of the speed of machine **201**, the actuation of valve **109**, and the delay between valve actuation and the material hitting the ground, along with the geographic location and heading of machine **201**, target determination component **302** may identify a geographic location of the material and/or the target geographic location for the seed and seed ejection system **242** can then eject the seed based on that target location.

[0186] The target parameter can be identified in other ways as well, as represented by block **512**.

[0187] Based on the target parameter identified at block **504**, the location of delivery endpoint component **231** determined based on the position offset, and the machine speed, a target ejection or release time/location is determined at block **524**. As noted above, this can be based on endpoint timing compensation so the target ejection time/location can take into account an estimated amount of time (or change in location) it will take the seed to travel into the furrow after it is released from seed transport mechanism **219**. The target ejection time/location can be determined in other ways as well.

[0188] At block **530**, the target motor speed at the time of seed release is determined. In one example, the target motor speed is set so that the speed of the seed, as it is released from seed transport mechanism **219**, conforms to (e.g., closely matches, but is in the opposite direction of) the speed of machine **201** to mitigate the effects of the seed rolling along the furrow, which may cause the seed to deviate from the target geographic location, as represented by block **532**. The target motor speed can be determined in other ways as well, as represented by block **534**.

[0189] At block **536**, a target motor position is determined for the release of the seed. The target motor position is illustratively the angular position of the motor output shaft when the seed is at the release position of the seed transport mechanism **219**, such that it is ejected from seed transport mechanism **219**.

[0190] At block **538**, motor operating parameters are generated based on the determinations at blocks **524-536**. The motor operating parameters can include a motor speed for driving seed transport mechanism **219**, as represented by block **540**. Also, the motor operating parameter can include a duration for operating the motor at the particular speed, as represented by block **542**. Of course, other motor operating parameters can be generated as well, as represented by block **544**.

[0191] In one example, the motor operating parameters generated at block **538** indicate a series of motor adjustments, so that the motor increases speed so the seed approaches the release location relatively quickly, in accordance with the target release time, and then slows to more closely match the machine speed to mitigate the effects of rolling. In other words, the speed at block **540** can be

greater than the target motor speed determined at block **530**, and then, prior to the seed release, the motor is slowed to the target motor speed. This is just one example.

[0192] At block **546**, the motor is operated based on the operating parameters. In one example, this includes controller **246** sending the motor operating parameters to controller **233**, which controls motor **221** in accordance therewith.

[0193] If the operation is continued at block **548**, the operation returns to block **502** where a next seed in the queue is identified and the seed transport mechanism **219** is operated to release the next seed at the next target geographic location.

[0194] It can thus be seen that locations where fertilizer or other material has been placed are identified and seeds are then accurately placed relative to the locations where the fertilizer or other material has been placed. This provides significant advantages, especially when the seeds are to be placed on top of the fertilizer or other material during planting. Also, in some systems, seed placement may be more accurate than fertilizer or other material placement. Therefore, by controlling seed placement based on locations where fertilizer or other material has been placed, the placement of the seed relative to the fertilizer or other material can be performed more accurately. In one example, but not by limitation, individual seeds are detected and tracked within the transport mechanism (e.g., seed tube or brush belt). By tracking the seed individually, the transport mechanism can be controlled in a manner that facilitates precision location planting.

[0195] It will be noted that the above discussion has described a variety of different systems, components and/or logic. It will be appreciated that such systems, components and/or logic can be comprised of hardware items (such as processors and associated memory, or other processing components, some of which are described below) that perform the functions associated with those systems, components and/or logic. In addition, the systems, components and/or logic can be comprised of software that is loaded into a memory and is subsequently executed by a processor or server, or other computing component, as described below. The systems, components and/or logic can also be comprised of different combinations of hardware, software, firmware, etc., some examples of which are described below. These are only some examples of different structures that can be used to form the systems, components and/or logic described above. Other structures can be used as well.

[0196] The present discussion has mentioned processors, processing systems, controllers and/or servers. In one example, these can include computer processors with associated memory and timing circuitry, not separately shown. The processors, processing systems, controllers, and/or servers are functional parts of the systems or devices to which they belong and are activated by, and facilitate the functionality of the other components or items in those systems.

[0197] Also, a number of user interface displays (UIs) have been discussed. The UIs can take a wide variety of different forms and can have a wide variety of different user actuatable input mechanisms disposed thereon. For instance, the user actuatable input mechanisms can be text boxes, check boxes, icons, links, drop-down menus, search boxes, etc. The mechanisms can also be actuated in a wide variety of different ways. For instance, the mechanisms can be actuated using a point and click device (such as a track ball or mouse). The mechanisms can be actuated using hardware buttons, switches, a joystick or keyboard, thumb switches or thumb pads, etc. The mechanisms can also be actuated using a virtual keyboard or other virtual actuators. In addition, where the screen on which they are displayed is a touch sensitive screen, the mechanisms can be actuated using touch gestures. Also, where the device that displays them has speech recognition components, the mechanisms can be actuated using speech commands.

[0198] A number of data stores have also been discussed. It will be noted they can each be broken into multiple data stores. All can be local to the systems accessing them, all can be remote, or some can be local while others are remote. All of these configurations are contemplated herein.

[0199] Also, the figures show a number of blocks with functionality ascribed to each block. It will be noted that fewer blocks can be used so the functionality is performed by fewer components.

Also, more blocks can be used with the functionality distributed among more components.

[0200] FIG. 11 is a block diagram of one example of the agricultural machine architecture, shown in FIG. 7, where agricultural machine 201 communicates with elements in a remote server architecture 2. In an example, remote server architecture 2 can provide computation, software, data access, and storage services that do not require end-user knowledge of the physical location or configuration of the system that delivers the services. In various examples, remote servers can deliver the services over a wide area network, such as the internet, using appropriate protocols. For instance, remote servers can deliver applications over a wide area network and they can be accessed through a web browser or any other computing component. Software or components shown in FIG. 7 as well as the corresponding data, can be stored on servers at a remote location. The computing resources in a remote server environment can be consolidated at a remote data center location or they can be dispersed. Remote server infrastructures can deliver services through shared data centers, even though they appear as a single point of access for the user. Thus, the components and functions described herein can be provided from a remote server at a remote location using a remote server architecture. Alternatively, they can be provided from a conventional server, or they can be installed on client devices directly, or in other ways.

[0201] In the example shown in FIG. 11, some items are similar to those shown in FIG. 7 and they are similarly numbered. FIG. 11 specifically shows that system 241 and data store 274 can be located at a remote server location 4. Therefore, agricultural machine 201 accesses those systems through remote server location 4.

[0202] FIG. 11 also depicts another example of a remote server architecture. FIG. 16 shows that it is also contemplated that some elements of FIG. 7 are disposed at remote server location 4 while others are not. By way of example, data store 274 can be disposed at a location separate from location 4, and accessed through the remote server at location 4. Alternatively, or in addition, system 241 can be disposed at location(s) separate from location 4, and accessed through the remote server at location 4.

[0203] Regardless of where the items in FIG. 11 are located, they can be accessed directly by agricultural machine 201, through a network (either a wide area network or a local area network), the items can be hosted at a remote site by a service, or the items can be provided as a service, or accessed by a connection service that resides in a remote location. Also, the data can be stored in substantially any location and intermittently accessed by, or forwarded to, interested parties. For instance, physical carriers can be used instead of, or in addition to, electromagnetic wave carriers. In such an example, where cell coverage is poor or nonexistent, another mobile machine (such as a fuel truck) can have an automated information collection system. As the agricultural machine comes close to the fuel truck for fueling, the system automatically collects the information from the machine or transfers information to the machine using any type of ad-hoc wireless connection. The collected information can then be forwarded to the main network as the fuel truck reaches a location where there is cellular coverage (or other wireless coverage). For instance, the fuel truck may enter a covered location when traveling to fuel other machines or when at a main fuel storage location. All of these architectures are contemplated herein. Further, the information can be stored on the agricultural machine until the agricultural machine enters a covered location. The agricultural machine, itself, can then send and receive the information to/from the main network.

[0204] It will also be noted that the elements of FIG. 7, or portions of them, can be disposed on a wide variety of different devices. Some of those devices include servers, desktop computers, laptop computers, tablet computers, or other mobile devices, such as palm top computers, cell phones, smart phones, multimedia players, personal digital assistants, etc.

[0205] FIG. 12 is a simplified block diagram of one example of a handheld or mobile computing device that can be used as a user's or client's hand held device 16, in which the present system (or parts of it) can be deployed. For instance, a mobile device can be deployed in the operator compartment of agricultural machine 201 (e.g., in the operator compartment of towing vehicle 94)

or as remote system **250**. FIGS. **13-14** are examples of handheld or mobile devices.

[0206] FIG. **12** provides a general block diagram of the components of a client device **16** that can run some components shown in FIG. **7**, that interacts with them, or both. In the device **16**, a communications link **13** is provided that allows the handheld device to communicate with other computing devices and in some examples provides a channel for receiving information automatically, such as by scanning. Examples of communications link **13** include allowing communication through one or more communication protocols, such as wireless services used to provide cellular access to a network, as well as protocols that provide local wireless connections to networks.

[0207] In other examples, applications can be received on a removable Secure Digital (SD) card that is connected to an interface **15**. Interface **15** and communication links **13** communicate with a processor **17** (which can also embody processors or servers from previous FIGS.) along a bus **19** that is also connected to memory **21** and input/output (I/O) components **23**, as well as clock **25** and location system **27**.

[0208] I/O components **23**, in one example, are provided to facilitate input and output operations. I/O components **23** for various embodiments of the device **16** can include input components such as buttons, touch sensors, optical sensors, microphones, touch screens, proximity sensors, accelerometers, orientation sensors and output components such as a display device, a speaker, and or a printer port. Other I/O components **23** can be used as well.

[0209] Clock **25** illustratively comprises a real time clock component that outputs a time and date. It can also, illustratively, provide timing functions for processor **17**.

[0210] Location system **27** illustratively includes a component that outputs a current geographical location of device **16**. This can include, for instance, a global positioning system (GPS) receiver, a LORAN system, a dead reckoning system, a cellular triangulation system, or other positioning system. It can also include, for example, mapping software or navigation software that generates desired maps, navigation routes and other geographic functions.

[0211] Memory **21** stores operating system **29**, network settings **31**, applications **33**, application configuration settings **35**, data store **37**, communication drivers **39**, and communication configuration settings **41**. Memory **21** can include all types of tangible volatile and non-volatile computer-readable memory devices. It can also include computer storage media (described below). Memory **21** stores computer readable instructions that, when executed by processor **17**, cause the processor to perform computer-implemented steps or functions according to the instructions. Processor **17** can be activated by other components to facilitate their functionality as well.

[0212] FIG. **13** shows one example in which device **16** is a tablet computer **50**. In FIG. **13**, computer **50** is shown with user interface display screen **52**. Screen **52** can be a touch screen or a pen-enabled interface that receives inputs from a pen or stylus. It can also use an on-screen virtual keyboard. Of course, it might also be attached to a keyboard or other user input device through a suitable attachment mechanism, such as a wireless link or USB port, for instance. Computer **50** can also illustratively receive voice inputs as well.

[0213] FIG. **14** shows that the device can be a smart phone **71**. Smart phone **71** has a touch sensitive display **73** that displays icons or tiles or other user input mechanisms **75**. Mechanisms **75** can be used by a user to run applications, make calls, perform data transfer operations, etc. In general, smart phone **71** is built on a mobile operating system and offers more advanced computing capability and connectivity than a feature phone.

[0214] Note that other forms of the devices **16** are possible.

[0215] FIG. **15** is one example of a computing environment in which elements of FIG. **7**, or parts of it, (for example) can be deployed. With reference to FIG. **15**, an example system for implementing some embodiments includes a computing device in the form of a computer **1010** programmed to operate as described above. Components of computer **1010** may include, but are not limited to, a processing unit **1020** (which can comprise processors or servers from previous

FIGS.), a system memory **1030**, and a system bus **1021** that couples various system components including the system memory to the processing unit **1020**. The system bus **1021** may be any of several types of bus structures including a memory bus or memory controller, a peripheral bus, and a local bus using any of a variety of bus architectures. Memory and programs described with respect to FIG. 7 can be deployed in corresponding portions of FIG. 15.

[0216] Computer **1010** typically includes a variety of computer readable media. Computer readable media can be any available media that can be accessed by computer **1010** and includes both volatile and nonvolatile media, removable and non-removable media. By way of example, and not limitation, computer readable media may comprise computer storage media and communication media. Computer storage media is different from, and does not include, a modulated data signal or carrier wave. It includes hardware storage media including both volatile and nonvolatile, removable and non-removable media implemented in any method or technology for storage of information such as computer readable instructions, data structures, program modules or other data. Computer storage media includes, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other optical disk storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by computer **1010**. Communication media may embody computer readable instructions, data structures, program modules or other data in a transport mechanism and includes any information delivery media. The term “modulated data signal” means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal.

[0217] The system memory **1030** includes computer storage media in the form of volatile and/or nonvolatile memory such as read only memory (ROM) **1031** and random access memory (RAM) **1032**. A basic input/output system **1033** (BIOS), containing the basic routines that help to transfer information between elements within computer **1010**, such as during start-up, is typically stored in ROM **1031**. RAM **1032** typically contains data and/or program modules that are immediately accessible to and/or presently being operated on by processing unit **1020**. By way of example, and not limitation, FIG. 15 illustrates operating system **1034**, application programs **1035**, other program modules **1036**, and program data **1037**.

[0218] The computer **1010** may also include other removable/non-removable volatile/nonvolatile computer storage media. By way of example only, FIG. 15 illustrates a hard disk drive **1041** that reads from or writes to non-removable, nonvolatile magnetic media, an optical disk drive **1055**, and nonvolatile optical disk **1056**. The hard disk drive **1041** is typically connected to the system bus **1021** through a non-removable memory interface such as interface **1040**, and optical disk drive **1055** is typically connected to the system bus **1021** by a removable memory interface, such as interface **1050**.

[0219] Alternatively, or in addition, the functionality described herein can be performed, at least in part, by one or more hardware logic components. For example, and without limitation, illustrative types of hardware logic components that can be used include Field-programmable Gate Arrays (FPGAs), Application-specific Integrated Circuits (e.g., ASICs), Application-specific Standard Products (e.g., ASSPs), System-on-a-chip systems (SOCs), Complex Programmable Logic Devices (CPLDs), etc.

[0220] The drives and their associated computer storage media discussed above and illustrated in FIG. 15, provide storage of computer readable instructions, data structures, program modules and other data for the computer **1010**. In FIG. 15, for example, hard disk drive **1041** is illustrated as storing operating system **1044**, application programs **1045**, other program modules **1046**, and program data **1047**. Note that these components can either be the same as or different from operating system **1034**, application programs **1035**, other program modules **1036**, and program data **1037**.

[0221] A user may enter commands and information into the computer **1010** through input devices

such as a keyboard **1062**, a microphone **1063**, and a pointing device **1061**, such as a mouse, trackball or touch pad. Other input devices (not shown) may include a joystick, game pad, satellite dish, scanner, or the like. These and other input devices are often connected to the processing unit **1020** through a user input interface **1060** that is coupled to the system bus, but may be connected by other interface and bus structures. A visual display **1091** or other type of display device is also connected to the system bus **1021** via an interface, such as a video interface **1090**. In addition to the monitor, computers may also include other peripheral output devices such as speakers **1097** and printer **1096**, which may be connected through an output peripheral interface **1095**.

[0222] The computer **1010** is operated in a networked environment using logical connections (such as a local area network—LAN, or wide area network—WAN, or a controller area network-CAN) to one or more remote computers, such as a remote computer **1080**.

[0223] When used in a LAN networking environment, the computer **1010** is connected to the LAN **1071** through a network interface or adapter **1070**. When used in a WAN networking environment, the computer **1010** typically includes a modem **1072** or other means for establishing communications over the WAN **1073**, such as the Internet. In a networked **17** environment, program modules may be stored in a remote memory storage device. FIG. **20** illustrates, for example, that remote application programs **1085** can reside on remote computer **1080**.

[0224] It should also be noted that the different examples described herein can be combined in different ways. That is, parts of one or more examples can be combined with parts of one or more other examples. All of this is contemplated herein.

[0225] Although the subject matter has been described in language specific to structural features and/or methodological acts, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described above. Rather, the specific features and acts described above are disclosed as example forms of implementing the claims.

Claims

1-20. (canceled)

21. A method of controlling an agricultural machine, the method comprising: identifying a material location in a field of an agricultural material previously applied to the field; identifying a target seed location based on a target spatial relation for a seed relative to the material location of the agricultural material previously applied to the field; and controlling the agricultural machine to apply the seed at a location that is spaced apart from the material location based on the target seed location.

22. The method of claim 21, wherein the agricultural machine comprises a planter having a seed ejection endpoint.

23. The method of claim 22, wherein the material location, of the agricultural material previously applied to the field, resides in a path of the seed ejection endpoint.

24. The method of claim 23, wherein the planter is configured to move through a field in a direction of travel and wherein controlling the planter comprises: controlling the planter to eject seeds from the seed ejection endpoint at seed locations in a furrow opened by the planter based on the material location.

25. The method of claim 24, and further comprising: applying the agricultural material to the field with a material application system coupled to the planter to apply the agricultural material ahead of the seed ejection endpoint in the direction of travel.

26. The method of claim 21, wherein controlling the agricultural machine to apply the seed comprises: identifying a geographic location of the agricultural machine; and controlling the agricultural machine to apply the seed based on the geographic location of the agricultural material and the geographic location of the agricultural machine.

27. The method of claim 21, wherein identifying the material location comprises identifying a

timing of material placement to a location in the field, and controlling the agricultural machine comprises controlling the agricultural machine, based on the timing of material placement, to eject the seed at a time so the seed is ejected at a location in a predefined spatial relation to the location of the agricultural material in the field.

28. The method of claim 21, wherein identifying the location of the agricultural material comprises: identifying the location of the agricultural material during operation of the agricultural machine.

29. The method of claim 21, wherein identifying the material location comprises: receiving a material map that maps locations in the field where the agricultural material was applied; identifying a geographic location of the agricultural material based on the material map; and identifying the target seed location based on the geographic location of the agricultural material.

30. The method of claim 21, wherein the target seed location comprises a location above the material location of the agricultural material previously applied to the field.

31. The method of claim 21, wherein the target seed location comprises a location that is offset, relative to the material location, in a transverse direction relative to a direction of travel of the agricultural machine.

32. An agricultural system comprising: an agricultural machine including a seeding system configured to deliver seed to a field; a target determination component configured to: identify a material location in a field of an agricultural material previously applied to the field; and identify a target seed location based on a target spatial relation for a seed relative to the material location of the agricultural material previously applied to the field; and a seed ejection system having a seed ejection endpoint configured to apply the seed at a location that is spaced apart from the material location based on the target seed location.

33. The agricultural system of claim 32, and further comprising: a seed tracking system configured to track a position of seeds in the seeding system and generate a seed position signal, the seed ejection system being configured to apply the seeds based on the seed tracking signal.

34. The agricultural system of claim 32, and further comprising: a material application control system; and a material application system controlled by the material application control system to apply the agricultural material to locations in the field ahead of the seed ejection endpoint in a direction of travel.

35. The agricultural system of claim 32, wherein the target determination component is configured to identify the material location in the field of an agricultural material previously applied to the field during operation of the seeding system.

36. The agricultural system of claim 32, wherein the target determination component is configured to: receive a material map that maps locations in the field where the agricultural material was applied; identify a geographic location of the agricultural material based on the material map; and identify the target seed location based on the geographic location of the agricultural material.

37. The agricultural system of claim 32, wherein the target seed location comprises one of: a location above the material location of the agricultural material previously applied to the field, or a location that is offset, relative to the material location, in a transverse direction relative to a direction of travel of the agricultural machine.

38. A computer system for controlling an agricultural machine that is configured to move through a field in a direction of travel, the computer system comprising: at least one processor; and memory storing computer executable instructions which, when executed by the at least one processor, cause the computer system to: identify a material location in a field of an agricultural material previously applied to the field; identify a target seed location based on a target spatial relation for a seed relative to the material location of the agricultural material previously applied to the field; and control the agricultural machine to apply the seed at a location that is spaced apart from the material location based on the target seed location.

39. The computer system of claim 38, wherein the agricultural machine comprises a planter having a seed ejection endpoint, and the material location, of the agricultural material previously applied to

the field, resides in a path of the seed ejection endpoint.

40. The computer system of claim 38, wherein the target seed location comprises one of: a location above the material location of the agricultural material previously applied to the field, or a location that is offset, relative to the material location, in a transverse direction relative to a direction of travel of the agricultural machine.
