

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250278062

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Bailey; Matthew et al.

WEARABLE DEVICES AND ASSOCIATED BAND STRUCTURES FOR SENSING NEUROMUSCULAR SIGNALS AND IDENTIFYING HAND GESTURES AND METHODS OF USE THEREOF

Abstract

A wearable apparatus for gesture control is disclosed. The wearable apparatus includes one or more first sensors configured to contact skin on a wrist of a user when the wearable apparatus is worn by the user. The one or more first sensors are configured to generate first signals associated with muscle activity of the user. The wearable apparatus further includes an inertial sensor configured to generate second signals associated with a motion of the user. The wearable apparatus further includes one or more processors configured to receive the first signals generated by the one or more first sensors and receive the second signals generated by the inertial sensor. The one or more processors are further configured to determine a gesture of the user based at least in part on an analysis of the first signals and the second signals, and perform an action associated with the gesture.

Inventors: Bailey; Matthew (Kitchener, CA), Lake; Stephen (Kitchener, CA), Grant; Aaron Williams (Seattle, WA), Morun; Cezar (Kitchener, CA)

Applicant: Meta Platforms Technologies, LLC (Menlo Park, CA)

Family ID: 85227671

Appl. No.: 19/211105

Filed: May 16, 2025

Related U.S. Application Data

parent US continuation 18908662 20241007 PENDING child US 19211105

parent US continuation 18887033 20240916 PENDING child US 18908662

parent US continuation 17899580 20220830 PENDING child US 18887033

parent US continuation 14505836 20141003 ABANDONED child US 15882858

parent US continuation 14465194 20140821 ABANDONED child US 16899843

parent US continuation 16137960 20180921 parent-grant-document US 10429928 child US 16550905
parent US continuation 15799621 20171031 parent-grant-document US 10101809 child US 16137960
parent US continuation 16292609 20190305 parent-grant-document US 10898101 child US 17141646
parent US continuation 15799628 20171031 parent-grant-document US 10251577 child US 16292609
parent US continuation-in-part 14461044 20140815 parent-grant-document US 11426123 child US 17899580
parent US continuation-in-part 15882858 20180129 parent-grant-document US 11644799 child US 17899580
parent US continuation-in-part 16899843 20200612 ABANDONED child US 17899580
parent US continuation-in-part 16550905 20190826 ABANDONED child US 17899580
parent US continuation-in-part 17141646 20210105 parent-grant-document US 11666264 child US 17899580
parent US division 14539773 20141112 parent-grant-document US 10042422 child US 15799621
parent US division 14553657 20141125 parent-grant-document US 10188309 child US 15799628
us-provisional-application US 61866960 20130816
us-provisional-application US 61887193 20131004
us-provisional-application US 61887812 20131007
us-provisional-application US 61891694 20131016
us-provisional-application US 61897097 20131029
us-provisional-application US 61903238 20131112
us-provisional-application US 61909786 20131127
us-provisional-application US 61869526 20130823

Publication Classification

Int. Cl.: **G04G21/08** (20100101); **G04G17/08** (20060101); **G06F3/01** (20060101); **G06F3/044** (20060101)

U.S. Cl.:

CPC **G04G21/08** (20130101); **G06F3/011** (20130101); **G06F3/014** (20130101); **G06F3/015** (20130101); **G06F3/017** (20130101); **G04G17/08** (20130101); **G06F3/044** (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/908,662, filed on Oct. 7, 2024, entitled “Wearable Devices and Associated Band Structures For Sensing Neuromuscular Signals and Identifying Hand Gestures and Methods of Use Thereof”, which is a continuation of U.S. patent application Ser. No. 18/887,033, filed on Sep. 16, 2024, entitled “Wearable Devices And Associated Band Structures For Sensing Neuromuscular Signals Using Sensor Pairs With A Communicative Pathway To A Processor,” which is a continuation of U.S. patent application Ser. No. 17/899,580, filed on Aug. 30, 2022, entitled “Wearable Devices For Sensing Neuromuscular Signals Using A Small Number Of Sensor Pairs, And Methods Of Manufacturing The Wearable Devices,” which is a continuation-in-part of U.S. patent application Ser. No. 14/461,044, filed on Aug. 15, 2014 (now U.S. Pat. No.

11,426,123), entitled "Systems, Articles And Methods For Signal Routing In Wearable Electronic Devices That Detect Muscle Activity Of A User Using A Set Of Discrete And Separately Enclosed Pod Structures," which claims the benefit of U.S. Provisional Patent Application Ser. No. 61/866,960, filed Aug. 16, 2013, entitled "Systems, Articles And Methods For Signal Routing In Wearable Electronic Devices." Each of these related applications is hereby fully incorporated by reference in its respective entirety. [0002] U.S. patent application Ser. No. 17/899,580 is also a continuation-in part of U.S. patent application Ser. No. 15/882,858, filed on Jan. 29, 2018 (now U.S. Pat. No. 11,644,799), entitled "Systems, Articles And Methods For Wearable Electronic Devices Employing Contact Sensors," which is a continuation of U.S. patent application Ser. No. 14/505,836, filed Oct. 3, 2014, entitled "Systems, Articles And Methods For Wearable Electronic Devices Employing Contact Sensors," which claims the benefit of U.S. Provisional Patent Application Ser. No. 61/887,193, filed Oct. 4, 2013, entitled "Systems, Articles And Methods For Smart Watches"; U.S. Provisional Patent Application Ser. No. 61/887,812, filed Oct. 7, 2013, entitled "Systems, Articles And Methods For Wristwatches With Sensing Capability"; U.S. Provisional Patent Application Ser. No. 61/891,694, filed Oct. 16, 2013, entitled "Systems, Articles And Methods For Wristwatches With Sensing Capability"; and U.S. Provisional Patent Application Ser. No. 61/897,097, filed Oct. 29, 2013, entitled "Systems, Articles And Methods For Wearable Electronic Devices Employing Capacitive Sensors." Each of these related applications is hereby fully incorporated by reference in its respective entirety. [0003] U.S. patent application Ser. No. 17/899,580 is additionally a continuation-in part of U.S. patent application Ser. No. 16/899,843, filed on Jun. 12, 2020, entitled "Systems, Articles, And Methods For Human-Electronics Interfaces," which is a continuation of and claims the benefit of U.S. patent application Ser. No. 14/465,194, filed Aug. 21, 2014, entitled "Systems, Articles, And Methods For Human-Electronics Interfaces," which claims the benefit of U.S. Provisional Patent Application Ser. No. 61/869,526, filed Aug. 23, 2013, entitled "Systems, Articles, And Methods For Human-Electronics Interfaces." Each of these related applications is hereby fully incorporated by reference in its respective entirety. [0004] U.S. patent application Ser. No. 17/899,580 is further a continuation-in part of U.S. patent application Ser. No. 16/550,905, filed on Aug. 26, 2019, entitled "Systems, Articles, And Methods For Capacitive Electromyography Sensors," which is a continuation of U.S. patent application Ser. No. 16/137,960, filed Sep. 21, 2018 (now U.S. Pat. No. 10,429,928), entitled "Systems, Articles, And Methods For Capacitive Electromyography Sensors," which is a continuation of U.S. patent application Ser. No. 15/799,621, filed Oct. 31, 2017 (now U.S. Pat. No. 10,101,809), entitled "Systems, Articles, And Methods For Capacitive Electromyography Sensors," which is a divisional of U.S. patent application Ser. No. 14/539,773, filed Nov. 12, 2014 (now U.S. Pat. No. 10,042,422), entitled "Systems, Articles, And Methods For Capacitive Electromyography Sensors," which claims the benefit of U.S. Provisional Patent Application Ser. No. 61/903,238, filed Nov. 12, 2013, entitled "Systems, Articles, And Methods For Capacitive Electromyography Sensors." Each of these related applications is hereby fully incorporated by reference in its respective entirety. [0005] U.S. patent application Ser. No. 17/899,580 is as well a continuation-in part of U.S. patent application Ser. No. 17/141,646, filed on Jan. 5, 2021 (now U.S. Pat. No. 11,666,264), entitled "Systems, Articles, And Methods For Electromyography Sensors," which is a continuation of U.S. patent application Ser. No. 16/292,609, filed Mar. 5, 2019 (now U.S. Pat. No. 10,898,101), entitled "Systems, Articles, And Methods For Electromyography Sensors," which is a continuation of U.S. patent application Ser. No. 15/799,628, filed Oct. 31, 2017 (now U.S. Pat. No. 10,251,577), entitled "Systems, Articles, And Methods For Capacitive Electromyography Sensors," which is a divisional of U.S. patent application Ser. No. 14/553,657, filed Nov. 25, 2014 (now U.S. Pat. No. 10,188,309), entitled "Systems, Articles, And Methods For Capacitive Electromyography Sensors," which claims the benefit of U.S. Provisional Patent Application Ser. No. 61/909,786, filed Nov. 27, 2013, entitled "Systems, Articles, And Methods For Capacitive Electromyography Sensors." Each of these related applications is hereby fully incorporated by reference in its

respective entirety. [0006] This application and/or U.S. patent application Ser. No. 18/908,662 are related to U.S. patent application Ser. No. 16/696,760, filed on Nov. 26, 2019 (now U.S. Pat. No. 11,009,951), entitled “Wearable Muscle Interface Systems, Devices And Methods That Interact With Content Displayed On An Electronic Display,” which is a continuation of U.S. patent application Ser. No. 14/155,107, filed Jan. 14, 2014 (now U.S. Pat. No. 10,528,135), entitled “Wearable Muscle Interface Systems, Devices And Methods That Interact With Content Displayed On An Electronic Display,” which claims the benefit of U.S. Provisional Patent Application Ser. No. 61/752,226, filed Jan. 14, 2013, entitled “Muscle Interface Device And Method For Interacting With Content Displayed On Wearable Head Mounted Displays.” Each of these related applications is hereby fully incorporated by reference in its respective entirety.

TECHNICAL FIELD

[0007] The present systems, articles and methods generally relate to wearable electronic devices and particularly relate to systems, articles and methods identifying hand gestures via wearable electronic devices.

BACKGROUND

[0008] Electronic devices are commonplace throughout most of the world today. Advancements in integrated circuit technology have enabled the development of electronic devices that are sufficiently small and lightweight to be carried by the user. Such “portable” electronic devices may include on-board power supplies (such as batteries or other power storage systems) and may be designed to operate without any wire-connections to other electronic systems (except, in some cases, during charging); however, a small and lightweight electronic device may still be considered portable even if it includes a wire-connection to another electronic system. For example, a microphone may be considered a portable electronic device whether it is operated wirelessly or through a wire-connection.

[0009] The convenience afforded by the portability of electronic devices has fostered a huge industry. Smartphones, audio players, laptop computers, tablet computers, and ebook readers are all examples of portable electronic devices. However, the convenience of being able to carry a portable electronic device has also introduced the inconvenience of having one's hand(s) encumbered by the device itself. This problem is addressed by making an electronic device not only portable, but wearable.

[0010] A wearable electronic device is any portable electronic device that a user can carry without physically grasping, clutching, or otherwise holding onto the device with their hand(s). For example, a wearable electronic device may be attached or coupled to the user by a strap or straps, a band or bands, a clip or clips, an adhesive, a pin and clasp, an article of clothing, tension or elastic support, an interference fit, an ergonomic form, etc. Examples of wearable electronic devices include digital wristwatches, electronic armbands, electronic rings, electronic ankle-bracelets or “anklets,” head-mounted electronic display units, hearing aids, and so on.

[0011] Two exemplary design factors for wearable electronic devices that may be of importance to users are: functionality and affordability. The functionality of a wearable electronic device is, of course, dependent on the electric circuitry (i.e., the electrical/electronic components and the electrical wiring therebetween) that the device employs. Users of wearable electronic devices may desire more sophisticated functionality, but more sophisticated functionality may adversely affect affordability. Affordability is directly tied to manufacturability, and more sophisticated functionality may necessitate more expensive electric circuitry or manufacturing processes that drive up manufacturing costs. There is a need in the art for wearable electronic device designs that provide desired functionality without compromising affordability.

[0012] A wearable electronic device may provide direct functionality for a user (such as audio playback, data display, computing functions, etc.) or it may provide electronics to interact with, receive information from, or control another electronic device. For example, a wearable electronic

device may include sensors that are responsive to (i.e., detect and provide one or more signal(s) in response to detecting) inputs effected by a user and transmit signals to another electronic device based on those inputs. Sensor-types and input-types may each take on a variety of forms, including but not limited to: tactile sensors (e.g., buttons, switches, touchpads, or keys) providing manual control, acoustic sensors providing voice-control, electromyography sensors providing gesture control, and/or accelerometers providing gesture control.

[0013] A human-computer interface (“HCI”) is an example of a human-electronics interface. The present systems, articles, and methods may be applied to wearable HCIs, but may also be applied to any other form of wearable human-electronics interface.

[0014] Human-electronics interfaces that employ EMG, a process for detecting and processing the electrical signals generated by muscle activity, have been proposed in the art. For example, U.S. Pat. Nos. 6,244,873 and 8,170,656 describe such systems. Characteristics that are common to these known proposals will now be described. Typically, such systems (e.g., the two examples listed above) employ a wearable EMG device that exclusively controls specific, pre-defined functions of a specific, pre-defined “receiving” electronic device. The term “pre-defined” here refers to information that is programmed into the wearable EMG device (or with which the wearable EMG device is programmed) in advance of a following interaction with a receiving device. The wearable EMG device typically includes built-in EMG sensors that detect muscle activity of a user and an on-board processor that determines when the detected muscle activity corresponds to a pre-defined gesture. The on-board processor maps each pre-defined gesture to a particular pre-defined function of the pre-defined receiving device. In other words, the wearable EMG device stores and executes pre-defined mappings between detected gestures and receiving device functions. The receiving device function(s) is/are then controlled by one or more “command(s)” that is/are output by the wearable EMG device. Each command that is output by the wearable EMG device has already been formulated to control (and is therefore limited to exclusively controlling) a specific function of a specific receiving device prior to being transmitted by the wearable EMG device.

[0015] Additionally, U.S. Pat. Nos. 6,244,873 and 8,170,656 both describe proposals in which a user dons a wearable EMG device and performs physical gestures to control functions of a separate electronic device. In both cases, the separate electronic device is not itself a wearable electronic device, so true hands-free operation of and/or access to the separate electronic device is not achieved. For example, both cases describe using EMG signals to control mobile phones, smart phones, computers, laptop computers, and so on, all of which still typically require the user to use their hand(s) to carry the device and/or to orient the device in such a way that the user may see, access, receive feedback from, and/or generally interact with a display screen on the device.

[0016] The wearable EMG devices proposed in the art are hard-coded to map pre-defined gestures to specific, pre-defined commands controlling specific, pre-defined functions of a specific, pre-defined receiving device. The wearable EMG devices proposed in the art are programmed with information about the specific receiving device (and/or about a specific application within the specific receiving device) under their control such that the wearable EMG devices proposed in the art output commands that include instructions that are specifically formulated for the specific receiving device (and/or the specific application within the specific receiving device). Thus, existing proposals for human-electronics interfaces that employ EMG are limited in their versatility because they employ a wearable EMG device that is hard-coded to control a specific electronic device (and/or a specific application within a specific electronic device). For such systems, the wearable EMG device needs to be modified/adapted for each distinct use (e.g., the wearable EMG device needs to be programmed with command signals that are specific to the receiving device and/or specific to the application within the receiving device). Because the outputs (i.e., commands) provided by such wearable EMG devices are hard-coded with information about the function(s) of the receiving device(s), a user cannot use such a wearable EMG device to control any generic electronic device (or any generic application within an electronic device) without

reprogramming/reconfiguring the wearable EMG device itself. A user who wishes to control multiple electronic devices (or multiple applications within a single electronic device, either simultaneously or in sequence) must use multiple such wearable EMG devices with each wearable EMG device separately controlling a different electronic device, or the user must re-program a single such wearable EMG device in between uses. There is a need in the art for a human-electronics interface employing EMG that overcomes these limitations.

[0017] The concept of a wristwatch with on-board computation capabilities and functionality beyond timekeeping (i.e., a “smart watch”) has been around for decades. Seiko and Casio were building digital wristwatches with user-programmable memory and computing capability as far back as in the 1980s. However, at least as a consequence of their limited functionality, the initial designs for smart watches never took off in consumer markets.

[0018] Motivated by the availability of more advanced integrated circuit, display, and battery technologies, there has recently been a resurgence in the smart watch industry. Exemplary smart watches that are currently known to be under development include: the Apple Watch, the Samsung Galaxy Gear™, the Sony SmartWatch™, the Qualcomm Toq™, and the Pebble™ by Pebble Technology. Each of these examples provides (or is expected to provide) various functions and capabilities and employs a unique design and geometry. However, all of these designs are fundamentally similar in that they essentially emulate the design of a traditional wristwatch. That is, each design comprises a housing that is physically coupled to a strap or band that fits around the user's wrist, the housing having a display on one side and a back-plate proximate the user's wrist on the side opposite the display. Conforming to this generic arrangement is a design constraint for virtually any smart watch, as most smart watches are designed to resemble the traditional wristwatch as much as possible.

[0019] The back-plate that is common to all known wristwatch designs (both traditional and smart watches alike) provides structural support and protects the internal components (circuitry or gears, etc.) of the wristwatch from its environment. Otherwise, the back-plate that is common to all known wristwatch designs does not typically provide or enable other functions and/or capabilities of the wristwatch. Similarly, the strap or band (or similar, hereafter “watchstrap”) that is common to virtually all known wristwatch designs (both traditional and smart watches alike) typically serves one purpose: holding the watch in position on the user's wrist. Beyond this, the watchstrap that is common to virtually all known wristwatch designs does not typically impart or enable any functionality or capability in the watch itself.

[0020] Solutions to the above-described drawbacks are provided below.

SUMMARY

[0021] A wearable electronic device may be summarized as including a set of pod structures that form physically coupled links of the wearable electronic device, wherein each pod structure in the set of pod structures is positioned adjacent and physically coupled to at least one other pod structure in the set of pod structures, and wherein the set of pod structures comprises at least two sensor pods and a processor pod, each of the at least two sensor pods comprising a respective sensor to in use detect inputs effected by a user and provide signals in response to the detected inputs, and the processor pod comprising a processor to in use process signals provided by each of the at least two sensor pods; and a plurality of communicative pathways to in use route signals provided by the at least two sensor pods to the processor pod, wherein each of the at least two sensor pods is communicatively coupled to the processor pod by at least one respective communicative pathway from the plurality of communicative pathways. Each of the at least two sensor pods may include a respective amplification circuit to in use amplify signals provided by the respective sensor.

[0022] The processor pod may include at least one analog-to-digital conversion (“ADC”) circuit to in use convert analog signals provided by the at least two sensor pods into digital signals. The at least two sensor pods may include a first sensor pod and a second sensor pod, the first sensor pod

communicatively coupled to the processor pod by a first communicative pathway from the plurality of communicative pathways and the second sensor pod communicatively coupled to the processor pod by a second communicative pathway from the plurality of communicative pathways, and: the first communicative pathway may include: a first portion to in use route analog signals output by the first sensor pod to the processor pod, and the second communicative pathway may include: a first portion to in use route analog signals output by the second sensor pod to the first sensor pod, and a second portion to in use route analog signals output by the second sensor pod from the first sensor pod to the processor pod. The at least two sensor pods may further include a third sensor pod, the third sensor pod communicatively coupled to the processor pod by a third communicative pathway from the plurality of communicative pathways, and the third communicative pathway may include: a first portion to in use route analog signals output by the third sensor pod to the second sensor pod; a second portion to in use route analog signals output by the third sensor pod from the second sensor pod to the first sensor pod; and a third portion to in use route analog signals output by the third sensor pod from the first sensor pod to the processor pod. The at least two sensor pods may further include a fourth sensor pod, the fourth sensor pod communicatively coupled to the processor pod by a fourth communicative pathway from the plurality of communicative pathways, and the fourth communicative pathway may include: a first portion to in use route analog signals output by the fourth sensor pod to the third sensor pod; a second portion to in use route analog signals output by the fourth sensor pod from the third sensor pod to the second sensor pod; a third portion to in use route analog signals output by the fourth sensor pod from the second sensor pod to the first sensor pod; and a fourth portion to in use route analog signals output by the fourth sensor pod from the first sensor pod to the processor pod.

[0023] Each of the at least two sensor pods may include a respective analog-to-digital conversion (“ADC”) circuit to in use convert analog signals provided by the respective sensor into digital signals. The wearable electronic device may further include a clock signal line communicatively coupled to each pod structure in the set of pod structures and wherein the plurality of communicative pathways includes a digital signal bus that is communicatively coupled to the processor pod, wherein the at least two sensor pods include a first sensor pod and a second sensor pod, the first sensor pod communicatively coupled to the digital signal bus by a first communicative pathway from the plurality of communicative pathways and the second sensor pod communicatively coupled to the digital signal bus by a second communicative pathway from the plurality of communicative pathways. The at least two sensor pods may further include a third sensor pod, the third sensor pod communicatively coupled to the digital signal bus by a third communicative pathway from the plurality of communicative pathways. The at least two sensor pods may further include a fourth sensor pod, the fourth sensor pod communicatively coupled to the digital signal bus by a fourth communicative pathway from the plurality of communicative pathways.

[0024] The plurality of communicative pathways may include at least one power line and at least one ground line.

[0025] The wearable electronic device may further include at least one adaptive coupler, wherein each respective pod structure in the set of pod structures is adaptively physically coupled to at least one adjacent pod structure in the set of pod structures by at least one adaptive coupler. For each of the at least two sensor pods, the sensor may include an electromyography sensor to in use detect muscle activity by the user and provide signals in response to the detected muscle activity.

[0026] The processor pod may further include: a sensor to in use detect inputs effected by the user and provide analog signals in response to the detected inputs; an amplification circuit to in use amplify analog signals provided by the sensor; and an analog-to-digital conversion (“ADC”) circuit to in use convert analog signals into digital signals. Each pod structure in the set of pod structures may include a respective housing formed of a substantially rigid material and having a respective inner volume, and, for each of the at least two sensor pods, the sensor may be positioned on or

proximate a surface of the housing, while for the processor pod, the processor may be positioned in the inner volume of the housing, and each communicative pathway in the plurality of communicative pathways may include a respective first portion in the inner volume of the housing of a respective first pod structure in the set of pod structures, a respective second portion in the inner volume of the housing of a respective second pod structure in the set of pod structures, and a respective third portion that extends between the housing of the respective first pod structure in the set of pod structures and the housing of the respective second pod structure in the set of pod structures.

[0027] At least one communicative pathway in the plurality of communicative pathways may be selected from the group consisting of: an electrically conductive pathway and an optical pathway. At least one communicative pathway in the plurality of communicative pathways may comprise or be a component of a flexible printed circuit board. Each pod structure in the set of pod structures may be positioned adjacent and in between two other pod structures in the set of pod structures and physically coupled to the two other pod structures in the set of pod structures, and the set of pod structures may form a perimeter of an annular configuration.

[0028] A wearable electronic device may be summarized as including: a set of pod structures that form physically coupled links of the wearable electronic device, the set of pod structures comprising a plurality of sensor pods and a processor pod, each sensor pod comprising a respective sensor to in use detect inputs effected by a user and provide signals in response to the detected inputs, and the processor pod comprising a processor to in use process signals provided by the plurality of sensor pods, wherein each pod structure in the set of pod structures is positioned adjacent and physically coupled to at least one other pod structure in the set of pod structures; and a plurality of communicative pathways to in use route signals provided by the plurality of sensor pods to the processor pod, wherein each pod structure in the set of pod structures is communicatively coupled to at least one adjacent pod structure in the set of pod structures by a respective communicative pathway from the plurality of communicative pathways to in use serially route signals provided by each sensor pod to the processor pod via successive ones of adjacent pod structures in the set of pod structures by respective communicative pathways in the plurality of communicative pathways.

[0029] The plurality of sensor pods may include: a first sensor pod positioned adjacent and physically coupled to the processor pod; a second sensor pod positioned adjacent and physically coupled to the processor pod; a third sensor pod positioned adjacent and physically coupled to the first sensor pod; and a fourth sensor pod positioned adjacent and physically coupled to the second sensor pod. The first sensor pod may be communicatively coupled to the processor pod by a first communicative pathway in the plurality of communicative pathways to in use route signals provided by the first sensor pod to the processor pod. The second sensor pod may be communicatively coupled to the processor pod by a second communicative pathway in the plurality of communicative pathways to in use route signals provided by the second sensor pod to the processor pod. The third sensor pod may be communicatively coupled to the processor pod by a third communicative pathway in the plurality of communicative pathways to in use route signals output by the third sensor pod from the third sensor pod via the first sensor pod to the processor pod. The fourth sensor pod may be communicatively coupled to the processor pod by a fourth communicative pathway in the plurality of communicative pathways to in use route signals output by the fourth sensor pod from the fourth sensor pod via the second sensor pod to the processor pod. The third communicative pathway may include at least a portion of the first communicative pathway and the fourth communicative pathway may include at least a portion of the second communicative pathway.

[0030] The processor pod may further include an analog-to-digital conversion (“ADC”) circuit to in use convert analog signals into digital signals. Each sensor pod in the plurality of sensor pods may include a respective analog-to-digital conversion (“ADC”) circuit to in use convert analog

signals into digital signals. The plurality of communicative pathways may include at least one power line and at least one ground line.

[0031] The wearable electronic device may further include: at least one adaptive coupler, wherein each respective pod structure in the set of pod structures is adaptively physically coupled to at least one adjacent pod structure in the set of pod structures by at least one adaptive coupler. For each sensor pod in the plurality of sensor pods: the sensor may include an electromyography sensor to in use detect muscle activity by the user and provide signals in response to the detected muscle activity. The processor pod may include a sensor to in use detect inputs effected by the user and provide signals in response to the detected inputs.

[0032] Each pod structure in the set of pod structures may include a respective housing formed of a substantially rigid material and having a respective inner volume, and, for each sensor pod in the plurality of sensor pods, the sensor may be positioned on or proximate a surface of the housing, while for the processor pod, the processor may be positioned in the inner volume of the housing, and each communicative pathway in the plurality of communicative pathways may include a respective first portion in the inner volume of the housing of a respective first pod structure in the set of pod structures, a respective second portion in the inner volume of the housing of a respective second pod structure in the set of pod structures, and a respective third portion that extends between the housing of the respective first pod structure in the set of pod structures and the housing of the respective second pod structure in the set of pod structures.

[0033] At least one communicative pathway in the plurality of communicative pathways may be selected from the group consisting of: an electrically conductive pathway and an optical pathway. At least one communicative pathway in the plurality of communicative pathways may include or be a component of a flexible printed circuit board. Each pod structure in the set of pod structures may be positioned adjacent and in between two other pod structures in the set of pod structures and physically coupled to the two other pod structures in the set of pod structures, and the set of pod structures may form a perimeter of an annular configuration.

[0034] A method of operating a wearable electronic device that comprises a set of pod structures and a plurality of communicative pathways, the set of pod structures including a plurality of sensor pods and a processor pod, wherein each sensor pod in the plurality of sensor pods comprises a respective sensor and the processor pod comprises a processor, and wherein each pod structure in the set of pod structures is positioned adjacent and physically coupled to at least one other pod structure in the set of pod structures, may be summarized as including: detecting inputs effected by a user by the sensor in at least one sensor pod in the plurality of sensor pods; providing signals in response to the detected inputs by the sensor in the at least one sensor pod in the plurality of sensor pods; serially routing the signals via successive ones of adjacent pod structures in the set of pod structures by respective communicative pathways in the plurality of communicative pathways until the signals are routed to the processor pod; and processing the signals by the processor in the processor pod.

[0035] Providing signals in response to the detected inputs by the sensor in the at least one sensor pod in the plurality of sensor pods may include providing analog signals in response to the detected inputs by the sensor in the at least one sensor pod in the plurality of sensor pods. Serially routing the signals via successive ones of adjacent pod structures in the set of pod structures by respective communicative pathways in the plurality of communicative pathways until the signals are routed to the processor pod may include serially routing the analog signals via successive ones of adjacent pod structures in the set of pod structures by respective communicative pathways in the plurality of communicative pathways until the analog signals are routed to the processor pod. The processor pod may include an analog-to-digital conversion (“ADC”) circuit, and the method further include converting the analog signals into digital signals by the ADC circuit in the processor pod, wherein processing the signals by the processor in the processor pod includes processing the digital signals by the processor in the processor pod.

[0036] Providing signals in response to the detected inputs by the sensor in the at least one sensor pod in the plurality of sensor pods may include providing analog signals in response to the detected inputs by the sensor in the at least one sensor pod in the plurality of sensor pods, and each sensor pod in the plurality of sensor pods may include a respective analog-to-digital conversion (“ADC”) circuit, with the method further including: converting the analog signals provided by the sensor in the at least one sensor pod in the plurality of sensor pods into digital signals by the ADC circuit in the at least one sensor pod in the plurality of sensor pods, wherein: serially routing the signals via successive ones of adjacent pod structures in the set of pod structures by respective communicative pathways in the plurality of communicative pathways until the signals are routed to the processor pod includes serially routing the digital signals via successive ones of adjacent pod structures in the set of pod structures by respective communicative pathways in the plurality of communicative pathways until the digital signals are routed to the processor pod, and processing the signals by the processor in the processor pod includes processing the digital signals by the processor in the processor pod.

[0037] The respective sensor in each sensor pod in the plurality of sensor pods may include an electromyography sensor, and detecting inputs effected by a user by the sensor in at least one sensor pod in the plurality of sensor pods may include detecting muscle activity of the user by the electromyography sensor in at least one sensor pod in the plurality of sensor pods and providing signals in response to the detected inputs by the sensor in the at least one sensor pod in the plurality of sensor pods may include providing signals in response to muscle activity of the user by the sensor in the at least one sensor pod in the plurality of sensor pods.

[0038] In some embodiments, the present systems, articles and methods generally relate to wearable electronic devices having on-board sensors, and particularly relate to wearable electronic devices that incorporate one or more contact sensor(s) of any one or more of a variety of different types.

[0039] The human body generates electrical signals that may be non-invasively sensed by sensors that physically contact the user's skin (either directly or through an electrically insulative medium such as a dielectric layer). Such “contact sensors” may couple to these electrical signals through, for example, capacitive coupling or via non-capacitive coupling for instance resistive coupling and/or galvanic coupling. This property is exploited in, for example, electromyography (“EMG”) sensors that detect the electrical signals produced by a user's muscles when the user performs a physical gesture. The human body also has a capacitance of its own (i.e., the “body capacitance”) that enables it to store charge and act as a capacitor. This property is exploited in some capacitive touch sensing technologies, such as in the capacitive touchscreens of many portable electronic devices today. Capacitive touchscreens employ a conductive screen that is excited by an electrical signal at a single, fixed frequency. When a user touches the screen, the body capacitance of the user causes changes in this signal that are detected by a sensing circuit. Throughout the remainder of this specification and the appended claims, capacitive touch sensors that employ a single electrical frequency are referred to as “single-frequency capacitive touch sensors.”

[0040] Recently, a new type of touch sensing technology that employs a range of electrical signal frequencies has been developed by Disney Research. Dubbed “Touché,” this new type of touch sensing technology takes advantage of the fact that different types of touch events may have different effects at different signal frequencies. The electrical signal that is used to excite the conductive screen is swept over a continuous range of electrical signal frequencies and the sensing circuit monitors changes in the corresponding return signal at various frequencies over the sweep. In this way, a frequency profile of the touch event is established, where each detectably-different type of touch event (e.g., one finger, two finger, pinch, swipe, etc.) produces a unique frequency profile that may be identified using, for example, machine intelligence algorithms, pattern recognition algorithms, and the like. Throughout the remainder of this specification and the appended claims, capacitive touch sensors that sweep over a continuous range of electrical

frequencies in this manner are referred to as “swept frequency capacitive touch sensors.” Swept frequency capacitive touch sensors are described in, for example, Sato et al., “Touché: Enhancing Touch Interaction on Humans, Screens, Liquids, and Everyday Objects,” presented at CHI '12, May 5-10, 2012 and available online: <http://www.disneyresearch.com/project/touche-touch-and-gesture-sensing-for-the-real-world/> (last accessed Sep. 29, 2014), which is incorporated by reference herein in its entirety.

[0041] Each different type of capacitive sensor described above may be implemented by substantially similar hardware. Essentially, at least one electrically conductive element (such as a plate of electrically conductive material or a conductive screen) is provided as a contact sensor or electrode and is electrically coupled to circuitry (e.g., electrical or electronic circuitry) by at least one electrically communicative pathway. Depending on the implementation, the electrically conductive material of an electrode may be bare and physically contact the skin of the user directly, or the electrically conductive material may be coated with an insulative layer (such as a dielectric layer) that physically couples to the skin of the user. At least one aspect that is unique to each of the different sensor types described above is the nature and function of the circuitry to which the at least one electrically conductive element is coupled.

[0042] In general, sensors that are responsive to and detect signals produced, generated, or otherwise effected by the human body are referred to herein as “biometric sensors.” Contact sensors are examples of biometric sensors that couple to the user's skin, and capacitive sensors (e.g., capacitive biometric sensors) are examples of contact sensors; however, other forms of contact sensors may couple to the user's skin through other means, such as through resistive coupling.

[0043] A wristwatch may be summarized as including: a housing having a top surface that includes a display and an inner cavity that includes a timekeeping device; and a watchstrap that is flexible and carries a set of components and a set of communication pathways, the watchstrap physically coupled to the housing, wherein the set of components includes at least one contact sensor (e.g., at least one biometric contact sensor) and at least one communication terminal, and wherein the at least one communication terminal is communicatively coupled to the at least one contact sensor by at least one communication pathway in the set of communication pathways. The set of components carried by the watchstrap may further include at least one component selected from the group consisting of: a battery, an inductive charging element, an inertial sensor, a pedometer, a compass, a Global Position System unit, an altimeter, a digital processor, and a non-transitory processor-readable storage medium. The set of components carried by the watchstrap may include a digital processor communicatively coupled to the at least one contact sensor and a non-transitory processor-readable storage medium communicatively coupled to the digital processor, and the non-transitory processor-readable storage medium may store processor-executable contact sensing instructions that, when executed by the digital processor, cause the digital processor to process signals received from the at least one contact sensor.

[0044] The at least one contact sensor may be carried on a first surface of the watchstrap, the first surface in physical contact with a user when the watchstrap is worn around a wrist of the user. The set of components carried by the watchstrap may include at least one component that is carried on a second surface of the watchstrap, the second surface opposite the first surface. The set of components carried by the watchstrap may include at least one component that is carried within the watchstrap.

[0045] The at least one contact sensor may include at least one capacitive biometric sensor selected from the group consisting of: an electromyography sensor, a single-frequency capacitive touch sensor, and a multi-frequency capacitive touch sensor. The display may include at least one of: a window, a digital display screen, and/or a touchscreen. The at least one communication terminal may include a wireless communication terminal.

[0046] The at least one communication terminal may include a wired communication terminal. The

housing may include circuitry and at least one component in the set of components carried by the watchstrap may be communicatively coupled to the circuitry of the housing through the wired communication terminal.

[0047] A composition of the watchstrap may be selected from the group consisting of: a single piece of flexible material, multiple layers of flexible material, a single piece of elastic material, multiple layers of elastic material, and a set of substantially rigid links physically coupled together by at least one adaptive coupler. Communicative coupling between the at least one contact sensor and the at least one communication terminal may be mediated by at least one additional component in the set of components carried by the watchstrap.

[0048] A watchstrap for integration into a wristwatch may be summarized as including: a flexible strap; a set of communication pathways carried by the strap; and a set of components carried by the strap, the set of components including at least one contact sensor (e.g., at least one biometric contact sensor) and at least one communication terminal, wherein the at least one communication terminal is communicatively coupled to the at least one contact sensor by at least one communication pathway in the set of communication pathways. The set of components carried by the strap may further include any or all of: a battery communicatively coupled to the at least one contact sensor by at least one communication pathway in the set of communication pathways; an inductive charging element communicatively coupled to the at least one contact sensor by at least one communication pathway in the set of communication pathways; an inertial sensor communicatively coupled to the at least one communication terminal by at least one communication pathway in the set of communication pathways; and/or a pedometer communicatively coupled to the at least one communication terminal by at least one communication pathway in the set of communication pathways.

[0049] The set of components carried by the strap may include: a digital processor communicatively coupled to the at least one contact sensor; and a non-transitory processor-readable storage medium communicatively coupled to the digital processor, wherein the non-transitory processor-readable storage medium stores processor-executable contact sensing instructions that, when executed by the digital processor, cause the digital processor to process signals received from the at least one contact sensor.

[0050] The at least one contact sensor may include at least one capacitive biometric sensor selected from the group consisting of: an electromyography sensor, a single-frequency capacitive touch sensor, and a multi-frequency capacitive touch sensor. The strap may be sized and dimensioned to mate with a wristwatch housing. The at least one contact sensor may include multiple contact sensors. The at least one communication terminal may include at least one of a wireless communication terminal and/or a wired communication terminal. Communicative coupling between the at least one contact sensor and the at least one communication terminal may be mediated by at least one additional component in the set of components carried by the strap.

[0051] The strap may include a first surface and a second surface, and at least one component in the set of components carried by the strap may be carried on the first surface of the strap and at least one component in the set of components carried by the strap may be carried on the second surface of the strap. At least one component in the set of components carried by the strap may be carried within the strap.

[0052] A wristwatch may be summarized as including: a wristband; a housing physically coupled to the wristband, the housing comprising: a top surface that includes a display; and a back-plate formed of a substantially rigid material and positioned underneath the top surface, wherein the back-plate and the top surface together define a cavity therebetween, and wherein the back-plate includes a first surface that carries at least one contact sensor (e.g., at least one biometric contact sensor) and a second surface that carries circuitry, the second surface opposite the first surface and the circuitry contained within the cavity and communicatively coupled to the at least one contact sensor; and a digital processor contained within the cavity, the digital processor communicatively

coupled to the circuitry. The housing may further comprise at least one sidewall formed of a substantially rigid material, the at least one sidewall providing physical coupling between the top surface and the back-plate, wherein the top surface, the back-plate, and the at least one sidewall form a hollow volume that encompasses the cavity.

[0053] The housing may have a geometry with a two-dimensional projection that is selected from the group consisting of: substantially square, substantially rectangular, substantially circular, and substantially polygonal. The housing may be substantially planar.

[0054] The housing may further comprise at least one component selected from the group consisting of: a battery contained within the cavity, a wireless transmitter, an inductive charging element contained within the cavity, an inertial sensor contained within the cavity, a pedometer contained within the cavity, and a non-transitory processor-readable storage medium contained within the cavity. The housing may include a non-transitory processor-readable storage medium contained within the cavity, and the non-transitory processor-readable storage medium may store processor-executable contact sensing instructions that, when executed by the digital processor, cause the digital processor to process signals received from the at least one contact sensor. The at least one component may be carried by the second surface of the back-plate.

[0055] The at least one contact sensor may include at least one capacitive biometric sensor selected from the group consisting of: an electromyography sensor, a single-frequency capacitive touch sensor, and a multi-frequency capacitive touch sensor. The display may include at least one of: a window, a digital display screen, and/or a touchscreen. The circuitry carried by the second surface of the back-plate may be communicatively isolated from the display, and the circuitry carried by the second surface of the back-plate may include the digital processor and a wireless transmitter communicatively coupled to the digital processor.

[0056] A back-plate for integration into a wristwatch may be summarized as including: a plate of substantially rigid material; at least one contact sensor (e.g., at least one biometric contact sensor) carried on a first side of the plate; circuitry carried on a second side of the plate, the second side opposite the first side, wherein the at least one contact sensor is communicatively coupled to the circuitry; and at least one component selected from the group consisting of: a tethered connector port communicatively coupled to the circuitry, the tethered connector port to in use communicatively couple to at least one electrical or electronic component of a wristwatch; and a wireless transmitter communicatively coupled to the circuitry, the wireless transmitter to in use wirelessly transmit data provided by the at least one contact sensor. The back-plate may further include any or all of: a battery carried on the second side of the plate and communicatively coupled to the circuitry; an inductive charging element carried on the second side of the plate and communicatively coupled to the circuitry; an inertial sensor carried on the second side of the plate and communicatively coupled to the circuitry; and/or a pedometer carried on the second side of the plate and communicatively coupled to the circuitry.

[0057] The back-plate may include a non-transitory processor-readable storage medium carried on the second side of the plate, wherein the non-transitory processor-readable storage medium stores processor-executable contact sensing instructions that, when executed by a processor, cause the processor to process signals received from the at least one contact sensor. The back-plate may further include a digital processor carried on the second side of the plate and communicatively coupled to both the circuitry and the non-transitory processor-readable storage medium.

[0058] The at least one contact sensor may include at least one capacitive biometric sensor selected from the group consisting of: an electromyography sensor, a single-frequency capacitive touch sensor, and a multi-frequency capacitive touch sensor. The plate may be sized and dimensioned to mate with a wristwatch housing and to provide an underside thereof. The at least one contact sensor may include multiple contact sensors. The plate may be substantially planar in geometry.

[0059] A wearable electronic device may be summarized as including: at least one EMG sensor responsive to muscle activity corresponding to a gesture performed by a user of the wearable

electronic device and to provide signals in response thereto; at least one capacitive touch sensor responsive to physical contact between the user and an object and to provide signals in response thereto; a processor communicatively coupled to the at least one EMG sensor and to the at least one capacitive touch sensor; and a non-transitory processor-readable storage medium communicatively coupled to the processor, the non-transitory processor-readable storage medium storing: processor-executable gesture identification instructions that, when executed by the processor, cause the processor to identify a gesture performed by the user based at least in part on signals provided by the at least one EMG sensor; and processor-executable touch sensing instructions that, when executed by the processor, cause the processor to process signals provided by the at least one capacitive touch sensor. The at least one capacitive touch sensor may include a single-frequency capacitive touch sensor, a multi-frequency capacitive touch sensor, and/or a swept frequency capacitive touch sensor.

[0060] The wearable electronic device may further include at least one communication terminal communicatively coupled to the processor, the at least one communication terminal to transmit signals to a receiving device, wherein the signals are based on at least one of: signals provided by the at least one EMG sensor and/or signals provided by the at least one capacitive touch sensor. The wearable electronic device may include at least one inertial sensor communicatively coupled to the processor, the at least one inertial sensor responsive to motion corresponding to the gesture performed by the user of the wearable electronic device and to provide at least one signal in response thereto, wherein the processor-executable gesture identification instructions that, when executed by the processor, cause the processor to identify the gesture performed by the user based at least in part on signals provided by the at least one EMG sensor cause the processor to identify the gesture performed by the user based at least in part on both signals provided by the at least one EMG sensor and at least one signal provided by the at least one inertial sensor.

[0061] The wearable electronic device may comprise a set of pod structures that form physically coupled links of the wearable electronic device, wherein each pod structure in the set of pod structures is positioned adjacent and in between two other pod structures in the set of pod structures and physically coupled to the two other pod structures in the set of pod structures, and wherein the set of pod structures forms a perimeter of an annular configuration.

[0062] In some embodiments, the present systems, articles, and methods generally relate to human-electronics interfaces and particularly relate to electromyographic control of electronic devices.

[0063] As mentioned above, EMG is a process for detecting and processing the electrical signals generated by muscle activity. EMG devices employ EMG sensors that are responsive to the range of electrical potentials (typically μV - mV) involved in muscle activity. EMG signals may be used in a wide variety of applications, including: medical monitoring and diagnosis, muscle rehabilitation, exercise and training, prosthetic control, and even in controlling functions of electronic devices (e.g., in human-electronics interfaces).

[0064] A wearable EMG device may be summarized as including: at least one EMG sensor to in use detect muscle activity of a user of the wearable EMG device and provide at least one signal in response to the detected muscle activity; a processor communicatively coupled to the at least one EMG sensor, the processor to in use determine a gesture identification flag based at least in part on the at least one signal provided by the at least one EMG sensor; and an output terminal communicatively coupled to the processor to in use transmit the gesture identification flag. The gesture identification flag may be independent of any downstream processor-based device and generic to a variety of end user applications executable by a variety of downstream processor-based devices useable with the wearable EMG device.

[0065] The wearable EMG device may further include a non-transitory processor-readable storage medium communicatively coupled to the processor, wherein the non-transitory processor-readable storage medium stores at least a set of gesture identification flags. The non-transitory processor-readable storage medium may store processor-executable instructions that embody and/or

produce/effect a mapping between at least one signal provided by the at least one EMG sensor and at least one gesture identification flag and, when executed by the processor, the processor-executable instructions may cause the processor to determine a gesture identification flag in accordance with the mapping. The non-transitory processor-readable storage medium may store processor-executable instructions that, when executed by the processor, cause the processor to determine a gesture identification flag based at least in part on at least one signal provided by the at least one EMG sensor.

[0066] The wearable EMG device may further include at least one accelerometer communicatively coupled to the processor, the at least one accelerometer to in use detect motion effected by the user of the wearable EMG device and provide at least one signal in response to the detected motion, and the processor may in use determine the gesture identification flag based at least in part on both the at least one signal provided by the at least one EMG sensor and the at least one signal provided by the at least one accelerometer.

[0067] The processor may be selected from the group consisting of: a digital microprocessor, a digital microcontroller, a digital signal processor, a graphics processing unit, an application specific integrated circuit, a programmable gate array, and a programmable logic unit. The at least one EMG sensor may include a plurality of EMG sensors, and the wearable EMG device may further include a set of communicative pathways to route signals provided by the plurality of EMG sensors to the processor, wherein each EMG sensor in the plurality of EMG sensors is communicatively coupled to the processor by at least one communicative pathway from the set of communicative pathways. The wearable EMG device may further include a set of pod structures that form physically coupled links of the wearable EMG device, wherein each pod structure in the set of pod structures is positioned adjacent and physically coupled to at least one other pod structure in the set of pod structures, and wherein the set of pod structures comprises at least two sensor pods and a processor pod, each of the at least two sensor pods comprising a respective EMG sensor from the plurality of EMG sensors and the processor pod comprising the processor. Each pod structure in the set of pod structures may be positioned adjacent and in between two other pod structures in the set of pod structures and physically coupled to the two other pod structures in the set of pod structures, and the set of pod structures may form a perimeter of an annular configuration. The wearable EMG device may further include at least one adaptive coupler, wherein each respective pod structure in the set of pod structures is adaptively physically coupled to at least one adjacent pod structure in the set of pod structures by at least one adaptive coupler.

[0068] The output terminal of the wearable EMG device may include at least one of a wireless transmitter and/or a tethered connector port. The at least one EMG sensor may include at least one capacitive EMG sensor.

[0069] A method of operating a wearable electromyography (“EMG”) device to provide electromyographic control of an electronic device, wherein the wearable EMG device includes at least one EMG sensor, a processor, and an output terminal, may be summarized as including: detecting muscle activity of a user of the wearable EMG device by the at least one EMG sensor; providing at least one signal from the at least one EMG sensor to the processor in response to the detected muscle activity; determining, by the processor, a gesture identification flag based at least in part on the at least one signal provided from the at least one EMG sensor to the processor, wherein the gesture identification flag is independent of the electronic device; and transmitting the gesture identification flag to the electronic device by the output terminal. Detecting muscle activity of a user of the wearable EMG device by the at least one EMG sensor may include detecting muscle activity of the user of the wearable EMG device by a first EMG sensor and by at least a second EMG sensor. Providing at least one signal from the at least one EMG sensor to the processor in response to the detected muscle activity may include providing at least a first signal from the first EMG sensor to the processor in response to the detected muscle activity and providing at least a second signal from the second EMG sensor to the processor in response to the

detected muscle activity. Determining, by the processor, a gesture identification flag based at least in part on the at least one signal provided from the at least one EMG sensor to the processor may include determining, by the processor, a gesture identification flag based at least in part on the at least a first signal provided from the first EMG sensor to the processor and the at least a second signal provided from the at least a second EMG sensor to the processor.

[0070] The wearable EMG device may further include a non-transitory processor-readable storage medium that stores processor-executable instructions, and determining, by the processor, a gesture identification flag based at least in part on the at least one signal provided from the at least one EMG sensor to the processor may include executing the processor-executable instructions by the processor to cause the processor to determine a gesture identification flag based at least in part on the at least one signal provided from the at least one EMG sensor to the processor.

[0071] The wearable EMG device may further include at least one accelerometer, and the method may further include: detecting motion effected by the user of the wearable EMG device by the at least one accelerometer; and providing at least one signal from the at least one accelerometer to the processor in response to the detected motion. Determining a gesture identification flag based at least in part on the at least one signal provided from the at least one EMG sensor to the processor may include determining, by the processor, a gesture identification flag based at least in part on both the at least one signal provided from the at least one EMG sensor to the processor and the at least one signal provided from the at least one accelerometer to the processor. The wearable EMG device may include a non-transitory processor-readable storage medium that stores processor-executable instructions, and determining, by the processor, a gesture identification flag based at least in part on both the at least one signal provided from the at least one EMG sensor to the processor and the at least one signal provided from the at least one accelerometer to the processor may include executing the processor-executable instructions by the processor to cause the processor to determine the gesture identification flag based at least in part on both the at least one signal provided from the at least one EMG sensor to the processor and the at least one signal provided from the at least one accelerometer to the processor.

[0072] The output terminal of the wearable EMG device may include a wireless transmitter, and transmitting the gesture identification flag to the electronic device by the output terminal may include wirelessly transmitting the gesture identification flag to the electronic device by the wireless transmitter.

[0073] A system that enables electromyographic control of an electronic device may be summarized as including: a wearable electromyography (“EMG”) device comprising: at least one EMG sensor to in use detect muscle activity of a user of the wearable EMG device and provide at least one signal in response to the detected muscle activity, a first processor communicatively coupled to the at least one EMG sensor, the first processor to in use determine a gesture identification flag based at least in part on the at least one signal provided by the at least one EMG sensor, and an output terminal communicatively coupled to the first processor, the output terminal to in use transmit the gesture identification flag; and an electronic device comprising: an input terminal to in use receive the gesture identification flag, and a second processor communicatively coupled to the input terminal, the second processor to in use determine a function of the electronic device based at least in part on the gesture identification flag. The gesture identification flag may be independent of the electronic device and generic to a variety of end user applications executable by the electronic device.

[0074] The wearable EMG device of the system may further include a non-transitory processor-readable storage medium communicatively coupled to the first processor, wherein the non-transitory processor-readable storage medium stores at least a set of gesture identification flags. The non-transitory processor-readable storage medium of the wearable EMG device may store processor-executable instructions that embody and/or produce/effect a mapping between at least one signal provided by the at least one EMG sensor and at least one gesture identification flag and,

when executed by the first processor, the processor-executable instructions may cause the first processor to determine a gesture identification flag in accordance with the mapping.

[0075] The wearable EMG device of the system may include a non-transitory processor-readable storage medium communicatively coupled to the first processor, wherein the non-transitory processor-readable storage medium stores processor-executable instructions that, when executed by the first processor, cause the first processor to determine a gesture identification flag based at least in part on the at least one signal provided by the at least one EMG sensor.

[0076] The wearable EMG device of the system may include at least one accelerometer communicatively coupled to the first processor, the at least one accelerometer to in use detect motion effected by the user of the wearable EMG device and provide at least one signal in response to the detected motion, and the first processor may in use determine a gesture identification flag based at least in part on both the at least one signal provided by the at least one EMG sensor and the at least one signal provided by the at least one accelerometer.

[0077] The electronic device of the system may include a non-transitory processor-readable storage medium communicatively coupled to the second processor, wherein the non-transitory processor-readable storage medium stores at least a set of processor-executable instructions that, when executed by the second processor, cause the second processor to determine a function of the electronic device based at least in part on the gesture identification flag.

[0078] The electronic device of the system may include a non-transitory processor-readable storage medium communicatively coupled to the second processor, wherein the non-transitory processor-readable storage medium stores: a first application executable by the electronic device; at least a second application executable by the electronic device; a first set of processor-executable instructions that, when executed by the second processor, cause the second processor to determine a function of the first application based at least in part on a gesture identification flag; and a second set of processor-executable instructions that, when executed by the second processor, cause the second processor to determine a function of the second application based at least in part on a gesture identification flag.

[0079] The output terminal of the wearable EMG device may include a first tethered connector port, the input terminal of the electronic device may include a second tethered connector port, and the system may further include a communicative pathway to in use communicatively couple the first tethered connector port to the second tethered connector port and to route the gesture identification flag from the output terminal of the wearable EMG device to the input terminal of the electronic device.

[0080] The output terminal of the wearable EMG device may include a wireless transmitter to in use wirelessly transmit the gesture identification flag, the input terminal of the electronic device may include a tethered connector port, and the system may include a wireless receiver to in use communicatively couple to the tethered connector port of the electronic device and to in use wirelessly receive the gesture identification flag from the wireless transmitter of the wearable EMG device.

[0081] The output terminal of the wearable EMG device may include a wireless transmitter to in use wirelessly transmit the gesture identification flag and the input terminal of the electronic device may include a wireless receiver to in use wirelessly receive the gesture identification flag from the wireless transmitter of the wearable EMG device.

[0082] The electronic device may be selected from the group consisting of: a computer, a desktop computer, a laptop computer, a tablet computer, a mobile phone, a smartphone, a portable electronic device, an audio player, a television, a video player, a video game console, a robot, a light switch, and a vehicle.

[0083] A method of electromyographically controlling at least one function of an electronic device by a wearable electromyography (“EMG”) device, wherein the wearable EMG device includes at least one EMG sensor, a first processor, and an output terminal and the electronic device includes

an input terminal and a second processor, may be summarized as including: detecting muscle activity of a user of the wearable EMG device by the at least one EMG sensor; providing at least one signal from the at least one EMG sensor to the first processor in response to the detected muscle activity; determining, by the first processor, a gesture identification flag based at least in part on the at least one signal provided from the at least one EMG sensor to the first processor, wherein the gesture identification flag is independent of the electronic device; transmitting the gesture identification flag by the output terminal of the wearable EMG device; receiving the gesture identification flag by the input terminal of the electronic device; determining, by the second processor, a function of the electronic device based at least in part on the gesture identification flag; and performing the function by the electronic device. Detecting muscle activity of a user of the wearable EMG device by the at least one EMG sensor may include detecting muscle activity of the user of the wearable EMG device by a first EMG sensor of the wearable EMG device and by at least a second EMG sensor of the wearable EMG device. Providing at least one signal from the at least one EMG sensor to the first processor in response to the detected muscle activity may include providing at least a first signal from the first EMG sensor to the first processor in response to the detected muscle activity and providing at least a second signal from the second EMG sensor to the first processor in response to the detected muscle activity. Determining, by the first processor, a gesture identification flag based at least in part on the at least one signal provided from the at least one EMG sensor to the first processor may include determining, by the first processor, a gesture identification flag based at least in part on the at least a first signal provided from the first EMG sensor to the first processor and the at least a second signal provided from the at least a second EMG sensor to the first processor.

[0084] The wearable EMG device may include a non-transitory processor-readable medium that stores processor-executable instructions, and determining, by the first processor, a gesture identification flag based at least in part on the at least one signal provided from the at least one EMG sensor to the first processor may include executing the processor-executable instructions by the first processor to cause the first processor to determine a gesture identification flag based at least in part on the at least one signal provided from the at least one EMG sensor to the first processor.

[0085] The wearable EMG device may include at least one accelerometer, and the method may include: detecting motion effected by the user of the wearable EMG device by the at least one accelerometer; and providing at least one signal from the at least one accelerometer to the first processor in response to the detected motion. Determining, by the first processor, a gesture identification flag based at least in part on the at least one signal provided from the at least one EMG sensor to the first processor may include determining, by the first processor, a gesture identification flag based at least in part on the at least one signal provided from the at least one EMG sensor to the first processor and the at least one signal provided by the at least one accelerometer to the first processor.

[0086] The output terminal of the wearable EMG device may include a wireless transmitter and the input terminal of the electronic device may include a wireless receiver. Transmitting the gesture identification flag by the output terminal of the wearable EMG device may include wirelessly transmitting the gesture identification flag by the wireless transmitter of the wearable EMG device, and receiving the gesture identification flag by the input terminal of the electronic device may include wirelessly receiving the gesture identification flag by the wireless receiver of the electronic device.

[0087] The electronic device may include a non-transitory processor-readable storage medium that stores processor-executable instructions, and determining, by the second processor, a function of the electronic device based at least in part on the gesture identification flag may include executing the processor-executable instructions by the second processor to cause the second processor to determine a function of the electronic device based at least in part on the gesture identification flag.

[0088] In some embodiments, the present systems, articles, and methods generally relate to electromyography and particularly relate to capacitive electromyography sensors.

[0089] There are two main types of EMG sensors: intramuscular EMG sensors and surface EMG sensors. As the names suggest, intramuscular EMG sensors are designed to penetrate the skin and measure EMG signals from within the muscle tissue, while surface EMG sensors are designed to rest on an exposed surface of the skin and measure EMG signals from there. Intramuscular EMG sensor measurements can be much more precise than surface EMG sensor measurements; however, intramuscular EMG sensors must be applied by a trained professional, are obviously more invasive, and are less desirable from the patient's point of view. The use of intramuscular EMG sensors is generally limited to clinical settings.

[0090] Surface EMG sensors can be applied with ease, are much more comfortable for the patient/user, and are therefore more appropriate for non-clinical settings and uses. For example, human-electronics interfaces that employ EMG, such as those proposed in U.S. Pat. Nos. 6,244,873 and 8,170,656, usually employ surface EMG sensors. Surface EMG sensors come in two forms: resistive EMG sensors and capacitive EMG sensors. For both forms of surface EMG sensors, the sensor electrode typically includes a plate of electrically conductive material that is placed against or in very close proximity to the exposed surface of the user's skin. A resistive EMG sensor electrode is typically directly electrically coupled to the user's skin while a capacitive EMG sensor electrode is typically capacitively coupled to the user's skin. That is, for a resistive EMG sensor, the electrode typically comprises a plate of electrically conductive material that is in direct physical contact with the user's skin, while for a capacitive EMG sensor, the electrode typically comprises a plate of electrically conductive material that is electrically insulated from the user's skin by at least one thin intervening layer of dielectric material or cloth. In either case, skin and/or environmental conditions, such as hair density, humidity and moisture levels, and so on, can have a significant impact on the performance of the sensor. These parameters are generally controlled for resistive EMG sensors by preparing the user's skin before applying the sensor electrodes. For example, the region of the user's skin where a resistive electrode is to be placed is usually shaved, exfoliated, and slathered with a conductive gel to establish a suitable and stable environment before the resistive electrode is applied. This obviously limits the appeal of resistive EMG sensors to users, in particular for home and/or recreational use. Capacitive EMG sensors are advantageous because they are generally more robust against some skin and environmental conditions, such as hair density, and are typically applied without the elaborate skin preparation measures (e.g., shaving, exfoliating, and applying a conductive gel) that are employed for resistive sensors. However, capacitive EMG sensors are still very sensitive to moisture and performance can degrade considerably when, for example, a user sweats. There is a need in the art for capacitive EMG sensors with improved robustness against variations in skin and/or environmental conditions.

[0091] A capacitive electromyography ("EMG") sensor may be summarized as including a substrate; a first sensor electrode carried by the substrate, wherein the first sensor electrode comprises an electrically conductive plate having a first surface that faces the substrate and a second surface that is opposite the first surface; circuitry communicatively coupled to the first sensor electrode; and a dielectric layer formed of a dielectric material that has a relative permittivity of at least about 10, wherein the dielectric layer coats the second surface of the first sensor electrode. The first sensor electrode may be formed of a material including copper. The circuitry may include at least one circuit selected from the group consisting of: an amplification circuit, a filtering circuit, and an analog-to-digital conversion circuit. At least a portion of the circuitry may be carried by the substrate. The substrate may include a first surface and a second surface, the second surface opposite the first surface across a thickness of the substrate, and the at least a portion of the circuitry may be carried by the first surface of the substrate and the first sensor electrode may be carried by the second surface of the substrate. The dielectric layer may include a ceramic material. The dielectric layer may include an X7R ceramic material. The

substrate, the first sensor electrode, and the dielectric layer may constitute a laminate structure. The capacitive EMG sensor may further include an electrically conductive epoxy sandwiched in between the dielectric layer and the first sensor electrode, wherein the dielectric layer is adhered to the first sensor electrode by the electrically conductive epoxy. Alternatively, the capacitive EMG sensor may further include an electrically conductive solder sandwiched in between the dielectric layer and the first sensor electrode, wherein the dielectric layer is adhered to the first sensor electrode by the electrically conductive solder. The dielectric layer may have a thickness of less than about 10 micrometers. The capacitive EMG sensor may be a differential capacitive EMG sensor that further includes a second sensor electrode carried by the substrate, the second sensor electrode comprising an electrically conductive plate having a first surface that faces the substrate and a second surface that is opposite the first surface across a thickness of the second sensor electrode, wherein the second sensor electrode is communicatively coupled to the circuitry, and wherein the dielectric layer coats the second surface of the second sensor electrode. The dielectric layer may comprise a single continuous layer of dielectric material that coats both the second surface of the first sensor electrode and the second surface of the second sensor electrode. The dielectric layer may comprise a first section that coats the second surface of the first sensor electrode and at least a second section that coats the second surface of the second sensor electrode, wherein the first section of the dielectric layer is physically separate from the second section of the dielectric layer. The first sensor electrode and the second sensor electrode may be substantially coplanar. The capacitive EMG sensor may further include a ground electrode carried by the substrate, the ground electrode comprising an electrically conductive plate having a first surface that faces the substrate and a second surface that is opposite the first surface across a thickness of the ground electrode, wherein the ground electrode is communicatively coupled to the circuitry, and wherein the second surface of the ground electrode is exposed and not coated by the dielectric layer. The capacitive EMG sensor may further include at least one additional layer that is sandwiched in between the first sensor electrode and the substrate.

[0092] Resistive EMG sensors and capacitive EMG sensors both have relative advantages and disadvantages. For example, the resistive coupling to the skin realized by a resistive EMG sensor provides a relatively low impedance (compared to a capacitive coupling) between the skin and the sensor and this can greatly simplify the circuitry needed to amplify the detected EMG signals; however, because this resistive coupling is essentially galvanic and uninterrupted, it can also undesirably couple DC voltage to the amplification circuitry and/or result in a voltage applied to the skin of the user. Both of these effects potentially impact the quality of the EMG signals detected. On the other hand, the capacitive coupling to the skin realized by a capacitive EMG sensor galvanically isolates the amplification circuitry from the skin and thereby prevents a DC voltage from coupling to the amplification circuitry and prevents a voltage from being applied to the skin; however, this capacitive coupling provides a relatively high impedance between the skin and the sensor and this can complicate the circuitry needed to amplify the detected EMG signals (thus making the amplification circuitry more expensive). The strength of the capacitive coupling can also vary widely from user to user. Clearly, neither type of surface EMG sensor is ideal and there is a need in the art for improved surface EMG sensor designs.

[0093] A method of fabricating a capacitive EMG sensor may be summarized as including forming at least a portion of at least one circuit on a first surface of a substrate; forming a first sensor electrode on a second surface of the substrate, the second surface of the substrate opposite the first surface of the substrate across a thickness of the substrate, wherein the first sensor electrode comprises an electrically conductive plate; forming at least one electrically conductive pathway that communicatively couples the first sensor electrode and the at least a portion of at least one circuit; and coating the first sensor electrode with a dielectric layer comprising a dielectric material that has a relative permittivity of at least about 10. Coating the first sensor electrode with a dielectric layer may include coating at least a portion of the second surface of the substrate with the

dielectric layer. Coating the first sensor electrode with a dielectric layer may include coating the first sensor electrode with a ceramic material. Coating the first sensor electrode with a dielectric layer may include coating the first sensor electrode with an X7R ceramic material. The capacitive EMG sensor may be a differential capacitive EMG sensor and the method may further include forming a second sensor electrode on the second surface of the substrate, wherein the second sensor electrode comprises an electrically conductive plate; forming at least one electrically conductive pathway that communicatively couples the second sensor electrode and the at least a portion of at least one circuit; and coating the second sensor electrode with the dielectric layer. The method may further include forming a ground electrode on the second surface of the substrate, wherein the ground electrode comprises an electrically conductive plate; and forming at least one electrically conductive pathway that communicatively couples the ground electrode and the at least a portion of at least one circuit. Coating the first sensor electrode with a dielectric layer may include selectively coating the first sensor electrode with the dielectric layer and not coating the ground electrode with the dielectric layer. Coating the first sensor electrode with a dielectric layer may include coating both the first sensor electrode and the ground electrode with the dielectric layer, and the method may further include forming a hole in the dielectric layer to expose the ground electrode. Coating the first sensor electrode with a dielectric layer may include depositing a layer of electrically conductive epoxy on the first sensor electrode; and depositing the dielectric layer on the layer of electrically conductive epoxy. Coating the first sensor electrode with a dielectric layer may include depositing a layer of electrically conductive solder on the first sensor electrode; and depositing the dielectric layer on the layer of electrically conductive solder.

[0094] A wearable EMG device may be summarized as including at least one capacitive EMG sensor responsive to (i.e., to detect and provide one or more signal(s) in response to detecting) muscle activity corresponding to a gesture performed by a user of the wearable EMG device, wherein in response to muscle activity corresponding to a gesture performed by a user of the wearable EMG device, the at least one capacitive EMG sensor provides at least one signal, and wherein the at least one capacitive EMG sensor includes: a first sensor electrode comprising an electrically conductive plate; and a dielectric layer formed of a dielectric material that has a relative permittivity of at least about 10, wherein the dielectric layer coats the first sensor electrode; a processor communicatively coupled to the at least one capacitive EMG sensor to in use process signals provided by the at least one capacitive EMG sensor; and an output terminal communicatively coupled to the processor to transmit signals output by the processor. The dielectric layer may include a ceramic material. The ceramic material may include an X7R ceramic material. The wearable EMG device may further include circuitry that mediates communicative coupling between the at least one capacitive EMG sensor and the processor, wherein the circuitry includes at least one circuit selected from the group consisting of: an amplification circuit, a filtering circuit, and an analog-to-digital conversion circuit. The dielectric layer of the at least one capacitive EMG sensor may have a thickness of less than about 10 micrometers. The at least one capacitive EMG sensor may include at least one differential capacitive EMG sensor, and the at least one differential capacitive EMG sensor may further include a second sensor electrode comprising an electrically conductive plate, wherein the dielectric layer coats the second sensor electrode. The at least one capacitive EMG sensor may further include a ground electrode comprising an electrically conductive plate, wherein the ground electrode is exposed and not coated by the dielectric layer.

[0095] The present systems, articles, and methods generally relate to electromyography and particularly relate to capacitive electromyography sensors that resistively couple to the user's body.

[0096] An electromyography ("EMG") sensor may be summarized as including a first sensor electrode formed of an electrically conductive material; an amplifier; a first electrically conductive pathway that communicatively couples the first sensor electrode and the amplifier; a first capacitor electrically coupled in series between the first sensor electrode and the amplifier in the first

electrically conductive pathway; and a first resistor electrically coupled in series between the first sensor electrode and the amplifier in the first electrically conductive pathway. The first capacitor and the first resistor may be electrically coupled in series with one another in the first electrically conductive pathway. The EMG sensor may further include: a second electrically conductive pathway that communicatively couples to ground; a third electrically conductive pathway that communicatively couples the first electrically conductive pathway and the second electrically conductive pathway; a second capacitor electrically coupled in the third electrically conductive pathway in between the first electrically conductive pathway and the second electrically conductive pathway; a fourth electrically conductive pathway that communicatively couples the first electrically conductive pathway and the second electrically conductive pathway; and a second resistor electrically coupled in the fourth electrically conductive pathway in between the first electrically conductive pathway and the second electrically conductive pathway. The EMG sensor may be a differential EMG sensor that further includes: a second sensor electrode formed of an electrically conductive material; a fifth electrically conductive pathway that communicatively couples the second sensor electrode and the amplifier; a third capacitor electrically coupled in series between the second sensor electrode and the amplifier in the fifth electrically conductive pathway; and a third resistor electrically coupled in series between the second sensor electrode and the amplifier in the fifth electrically conductive pathway. The third capacitor and the third resistor may be electrically coupled in series with one another in the fifth electrically conductive pathway. The EMG sensor may further include: a sixth electrically conductive pathway that communicatively couples the fifth electrically conductive pathway and the second electrically conductive pathway; a fourth capacitor electrically coupled in the sixth electrically conductive pathway in between the fifth electrically conductive pathway and the second electrically conductive pathway; a seventh electrically conductive pathway that communicatively couples the fifth electrically conductive pathway and the second electrically conductive pathway; and a fourth resistor electrically coupled in the seventh electrically conductive pathway in between the fifth electrically conductive pathway and the second electrically conductive pathway. The EMG sensor may further include a ground electrode formed of an electrically conductive material and communicatively coupled to the second electrically conductive pathway.

[0097] The first sensor electrode may comprise a first layer formed of a first electrically conductive material and a second layer formed of a second electrically conductive material. The first electrically conductive material may include copper. The second electrically conductive material may include at least one material selected from the group consisting of: gold, steel, stainless steel, silver, titanium, electrically conductive rubber, and electrically conductive silicone.

[0098] The EMG sensor may further include a housing, wherein the amplifier, the first electrically conductive pathway, the first capacitor, the first resistor, and the first layer of the first sensor electrode are all substantially contained within the housing, the housing including a hole, and wherein at least a portion of the second layer of the first sensor electrode extends out of the housing through the hole. The EMG sensor may further include a substrate having a first surface and a second surface, the second surface opposite the first surface across a thickness of the substrate, wherein the first sensor electrode is carried by the first surface of the substrate and the amplifier, the first capacitor, and the first resistor are all carried by the second surface of the substrate. The first electrically conductive pathway may include at least one via that extends through the substrate. The first electrically conductive pathway may include at least one electrically conductive trace carried by the second surface of the substrate. The first capacitor and the first resistor may include respective discrete electronic components.

[0099] A method of fabricating an electromyography (“EMG”) sensor may be summarized as including: forming a first sensor electrode on a first surface of a substrate, wherein forming a first sensor electrode on a first surface of a substrate includes depositing at least a first layer of a first electrically conductive material on the first surface of the substrate; depositing an amplifier on a

second surface of the substrate, the second surface opposite the first surface across a thickness of the substrate; depositing a first capacitor on the second surface of the substrate; depositing a first resistor on the second surface of the substrate; and forming a first electrically conductive pathway that communicatively couples the first sensor electrode and the amplifier through the first capacitor and the first resistor. Forming the first electrically conductive pathway may include forming a via through the substrate. Depositing at least a first layer of a first electrically conductive material on the first surface of the substrate may include depositing a first layer including copper on the first surface of the substrate, and forming the first sensor electrode may further include depositing a second layer of a second electrically conductive material on the first layer of the first electrically conductive material, the second electrically conductive material including a material selected from the group consisting of: gold, steel, stainless steel, silver, titanium, electrically conductive rubber, and electrically conductive silicone.

[0100] The method may further include enclosing the substrate in a housing, wherein the housing includes a hole, and wherein enclosing the substrate in a housing includes enclosing the amplifier, the first capacitor, and the first resistor in the housing and aligning the first sensor electrode with the hole, wherein at least a portion of the second layer of the second electrically conductive material protrudes out of the housing through the hole.

[0101] The method may further include forming a ground electrode on the first surface of the substrate; forming a second electrically conductive pathway that communicatively couples to the ground electrode; depositing a second capacitor on the second surface of the substrate; forming a third electrically conductive pathway that communicatively couples the first electrically conductive pathway and the second electrically conductive pathway through the second capacitor; depositing a second resistor on the second surface of the substrate; and forming a fourth electrically conductive pathway that communicatively couples the first electrically conductive pathway and the second electrically conductive pathway through the second resistor. The EMG sensor may be a differential EMG sensor, and the method may further include: forming a second sensor electrode on the first surface of the substrate; depositing a third capacitor on the second surface of the substrate; depositing a third resistor on the second surface of the substrate; and forming a fifth electrically conductive pathway that communicatively couples the second sensor electrode and the amplifier through the third capacitor and the third resistor. The method may further include: depositing a fourth capacitor on the second surface of the substrate; forming a sixth electrically conductive pathway that communicatively couples the fifth electrically conductive pathway and the second electrically conductive pathway through the fourth capacitor; depositing a fourth resistor on the second surface of the substrate; and forming a seventh electrically conductive pathway that communicatively couples the fifth electrically conductive pathway and the second electrically conductive pathway through the fourth resistor.

[0102] Depositing the amplifier on the second surface of the substrate may include soldering the amplifier on the second surface of the substrate; depositing the first capacitor on the second surface of the substrate may include soldering the first capacitor on the second surface of the substrate; and/or depositing the first resistor on the second surface of the substrate may include soldering the first resistor on the second surface of the substrate.

[0103] A wearable electromyography (“EMG”) device may be summarized as including: at least one EMG sensor responsive to (i.e., to detect and provide at least one signal in response to) muscle activity corresponding to a gesture performed by a user of the wearable EMG device, wherein in response to muscle activity corresponding to a gesture performed by a user the at least one EMG sensor provides signals, and wherein the at least one EMG sensor includes: a first sensor electrode formed of an electrically conductive material; an amplifier; a first electrically conductive pathway that communicatively couples the first sensor electrode and the amplifier; a first capacitor electrically coupled in series between the first sensor electrode and the amplifier in the first electrically conductive pathway; and a first resistor electrically coupled in series between the first

sensor electrode and the amplifier in the first electrically conductive pathway; a processor communicatively coupled to the at least one EMG sensor to in use process signals provided by the at least one EMG sensor; and an output terminal communicatively coupled to the processor to transmit signals output by the processor. The at least one EMG sensor may further include: a second electrically conductive pathway that communicatively couples to ground; a third electrically conductive pathway that communicatively couples the first electrically conductive pathway and the second electrically conductive pathway; a second capacitor electrically coupled in between the first electrically conductive pathway and the second electrically conductive pathway in the third electrically conductive pathway; a fourth electrically conductive pathway that communicatively couples the first electrically conductive pathway and the second electrically conductive pathway; and a second resistor electrically coupled in between the first electrically conductive pathway and the second electrically conductive pathway in the fourth electrically conductive pathway. The at least one EMG sensor may include at least one differential EMG sensor, and the at least one differential EMG sensor may further include: a second sensor electrode formed of an electrically conductive material; a fifth electrically conductive pathway that communicatively couples the second sensor electrode and the amplifier; a third capacitor electrically coupled in between the second sensor electrode and the amplifier in the fifth electrically conductive pathway; and a third resistor electrically coupled in between the second sensor electrode and the amplifier in the fifth electrically conductive pathway. The at least one EMG sensor may further include a ground electrode formed of an electrically conductive material and communicatively coupled to the second electrically conductive pathway.

[0104] The first sensor electrode of the at least one EMG sensor may comprise a first layer formed of a first electrically conductive material and a second layer formed of a second electrically conductive material. The first electrically conductive material may include copper. The second electrically conductive material may include at least one material selected from the group consisting of: gold, steel, stainless steel, silver, titanium, electrically conductive rubber, and electrically conductive silicone. The wearable EMG device may further include: at least one housing that at least partially contains the at least one EMG sensor, wherein the amplifier, the first electrically conductive pathway, the first capacitor, the first resistor, and the first layer of the first sensor electrode are all substantially contained within the at least one housing, the at least one housing including a hole, and wherein at least a portion of the second layer of the first sensor electrode extends out of the at least one housing through the hole.

[0105] In some embodiments, a capacitive electromyography (“EMG”) sensor may be summarized as including: a first sensor electrode to in use resistively couple to a user's skin, wherein the first sensor electrode includes a plate of electrically conductive material; circuitry communicatively coupled to the first sensor electrode of the capacitive EMG sensor; and a first capacitor to in use galvanically isolate the circuitry from the user's skin, the first capacitor electrically coupled in series between the first sensor electrode and the circuitry. Resistive coupling between the first sensor electrode and the user's skin may include an impedance, and the capacitive EMG sensor may further include a first resistor to in use dominate the impedance of the resistive coupling between the first sensor electrode and the user's skin, wherein the first resistor is electrically coupled in series between the first sensor electrode and the circuitry and wherein the first resistor has a magnitude of at least 1 k Ω . The first resistor may have a magnitude of at least 10 k Ω . The circuitry may include at least a portion of at least one circuit selected from the group consisting of: an amplification circuit, a filtering circuit, and an analog-to-digital conversion circuit. The capacitive EMG sensor may further include a ground electrode to in use resistively couple to the user's skin, wherein the ground electrode includes a plate of electrically conductive material, and wherein the ground electrode is communicatively coupled to the circuitry. The circuitry may include: a high-pass filter that includes the first capacitor and a second resistor; and a low-pass filter that includes the first resistor and a second capacitor.

[0106] The first sensor electrode may comprise: a first layer of a first electrically conductive material; and a second layer of a second electrically conductive material. The first electrically conductive material may include copper. The second electrically conductive material may include at least one material selected from the group consisting of: gold, steel, stainless steel, silver, titanium, electrically conductive rubber, and electrically conductive silicone. The capacitive EMG sensor may further include a housing, wherein the circuitry, the first capacitor, and the first layer of the first sensor electrode are all substantially contained within the housing, the housing including a hole, and wherein at least a portion of the second layer of the first sensor electrode extends out of the housing through the hole. The capacitive EMG sensor may be a differential capacitive EMG sensor that further includes: a second sensor electrode to in use resistively couple to the user's skin, wherein the second sensor electrode includes a plate of electrically conductive material; and a second capacitor to in use galvanically isolate the circuitry from the user's skin, the second capacitor electrically coupled in series between the second sensor electrode and the circuitry.

[0107] A wearable electromyography ("EMG") device may be summarized as including: at least one capacitive EMG sensor responsive to (i.e., to detect and provide at least one signal in response to detecting) muscle activity corresponding to a gesture performed by a user of the wearable EMG device, wherein in response to muscle activity corresponding to a gesture performed by a user the at least one capacitive EMG sensor provides signals, and wherein the at least one capacitive EMG sensor includes: a first sensor electrode to in use resistively couple to the user's skin, wherein the first sensor electrode includes a plate of electrically conductive material; circuitry communicatively coupled to the first sensor electrode of the capacitive EMG sensor; and a first capacitor to in use galvanically isolate the circuitry from the user's skin, the first capacitor electrically coupled in series between the first sensor electrode and the circuitry; a processor communicatively coupled to the at least one capacitive EMG sensor to in use process signals provided by the at least one capacitive EMG sensor; and an output terminal communicatively coupled to the processor to transmit signals output by the processor

[0108] The present systems, devices, and methods relate generally to wearable muscle interfaces, and more specifically to a wearable muscle interface that interacts with content displayed on a wearable head-mounted display

[0109] As described above, portable electronic devices that include display screens typically require the user to use their hand(s) to carry the device and/or to orient the device so that the user may see, access, receive feedback from, and/or generally interact with the device's display screen. Occupying the user's hand(s) is an inconvenience that can significantly hinder the user's ability to interact with the portable electronic device and/or to interact with other aspects of their environment while operating the portable electronic device. However, this hindrance is at least partially overcome by making the display screen of the portable electronic device wearable. Making the display screen of the portable electronic device wearable enables the user to see, access, and/or receive feedback from the display screen without using their hand(s). In recent years, wearable head-mounted displays have begun to gain wider acceptance, with a number of recently introduced wearable head-mounted display devices having the potential for widespread adoption by consumers.

[0110] One such device disclosed in U.S. Pat. No. 8,203,3302 issued to Chi et al. utilizes a finger operable input device such as a touch pad built into the wearable head-mounted display (e.g. built into a side-arm of a pair of glasses, with one of the lenses functioning as a display screen) such that a user can interact with and control content appearing on the display screen with positioning and movement of a finger along a surface of the input device. A potential drawback of this approach is that a user is required to conspicuously raise his or her hand to touch the input device each time the user wants to interact with content displayed on the screen. Furthermore, even though the display itself is wearable, it is still controlled by touch and so is not actually hands-free (thus negating part of the benefit of making the display wearable in the first place).

[0111] Another such device is disclosed in US 2012/0293548 (Perez et al.) in which a head-mounted display provides users with supplemental information on a display screen provided in at least one of the lenses of a pair of glasses. A processing unit may be connected to the head-mounted display to provide the computing power necessary for its operation. However, the method of user interaction with the display is not specified.

[0112] Yet another example of such a device is disclosed in U.S. Pat. No. 8,212,859 issued to Tang et al. in which a source image is projected onto screens built into head-mounted displays worn by a user. Tang et al. focuses on the method and system for projection, and does not specify the manner of user interaction with the head-mounted display device.

[0113] U.S. Pat. No. 5,482,051 ('051 patent) describes a human-electronics interface in which a user's EMG signals are detected and used to interact with content that is ultimately displayed on a head-mounted visual display unit. However, the interface described in the '051 patent is not a portable system. The human-electronics interface described in the '051 patent consists of at least three disparate components that are communicatively coupled in series with one another; i) a set of EMG sensors, ii) a stand-alone processing system, and iii) a head-mounted visual display unit. Although the set of EMG sensors and the head-mounted visual display unit are both physically coupled to (i.e., worn by) the user, there is no direct communication between the set of EMG sensors and the head-mounted visual display unit. Detected EMG signals are sent from the set of EMG sensors to the stand-alone processing system (i.e., off the body of the user) where they are processed to achieve some effect, and then signals that represent the effect are sent from the processing system to the head-mounted visual display unit where the effect is displayed to the user. The stand-alone processing system mediates all communication between the set of EMG sensors and the head-mounted visual display unit. The processing system is not worn by the user and is not portable (i.e., it is stationary), and therefore the human-electronics interface described in the '051 patent is limited in that the user must be in close proximity to the stationary processing system in order to use the interface.

[0114] What is needed is a completely wearable (i.e., completely portable) user interface that enables a user to see, access and interact with an electronic display in an inconspicuous, hands-free manner.

[0115] The present disclosure relates to a muscle interface device and method for interacting with content displayed on wearable head mounted displays.

[0116] More generally, the muscle interface device comprises a sensor worn on the forearm of a user, and the sensor is adapted to recognize a plurality of gestures made by a user's hand and or wrist to interact with content displayed on the wearable head mounted display.

[0117] In an embodiment, the muscle interface device utilizes a plurality of EMG sensors to detect electrical activity produced by muscles during contraction, and convert the electrical signals for processing. The electrical signals detected from the muscles are interpreted as gestures (e.g. a combination of hand, wrist and arm movements) made by a user which provide a control input to a wearable head mounted display. The control input is preferably provided wirelessly via a wireless communication protocol, such as Near-Field Communication ("NFC") or Bluetooth™, for example.

[0118] In another embodiment, various types of sensors may be used alone or in lieu of or in combination with EMG sensors to detect gestures made by a user, for processing as a control input for interacting with a wearable head mounted display. This may be one or more mechanomyographic (MMG) sensors to detect vibrations made by muscles during contraction, or one or more accelerometer sensors to detect larger movements.

[0119] In another embodiment, the muscle interface device includes a calibration module with a routine for calibrating the muscle interface device for use with the wearable head mounted display.

[0120] Other features and advantages will become apparent from the following detailed description and accompanying drawings. It should be understood, however, that the detailed description and

specific examples are given by way of illustration and not limitation. Many modifications and changes within the scope of the present invention may be made without departing from the spirit thereof, and the invention includes all such modifications.

[0121] A wearable muscle interface device that in use interacts with content displayed on a wearable head-mounted display may be summarized as including: a plurality of muscle activity sensors to be worn on an arm of a user, the muscle activity sensors responsive to signals generated by muscles in the arm of the user; and a transmitter communicatively coupled to the plurality of muscle activity sensors, wherein in use the transmitter transmits at least one signal from the wearable muscle interface device directly to a receiver on the wearable head-mounted display based on the signals detected by the muscle activity sensors; wherein the at least one signal transmitted, in use, from the wearable muscle interface device directly to the receiver on the wearable head-mounted display effects at least one interaction with content displayed on the wearable head-mounted display. The wearable muscle interface device may further include a processor that in use interprets the signals detected by the muscle activity sensors as a gesture, wherein the processor is communicatively coupled in between the transmitter and the plurality of muscle activity sensors, and wherein the at least one signal that, in use, is transmitted from the wearable muscle interface device may be based on the gesture interpreted by the processor of the wearable muscle interface device. The wearable head-mounted display may include a processor communicatively coupled to the receiver of the wearable head-mounted display, and the at least one signal that, in use, is transmitted from the wearable muscle interface device to the wearable head-mounted display may be interpreted as a gesture by the processor of the wearable head-mounted display.

[0122] The wearable muscle interface device may further include a haptic feedback module that in use provides haptic feedback to the user, the haptic feedback module including a vibratory motor. The plurality of muscle activity sensors may include at least one muscle activity sensor selected from the group consisting of: an EMG sensor and a MMG sensor. The wearable muscle interface device may further include at least one accelerometer that in use detects signals generated by motion of the arm of the user, the at least one accelerometer communicatively coupled to the transmitter, and wherein in use the at least one signal transmitted from the transmitter of the wearable muscle interface device directly to the receiver on the wearable head-mounted display may be based on both the signals detected by the muscle activity sensors and the signals detected by the at least one accelerometer. The transmitter may include a wireless transmitter.

[0123] A wearable system that in use provides hands-free access to and control of a portable electronic display may be summarized as including: i) a wearable muscle interface device comprising: a plurality of muscle activity sensors to be worn on an arm of a user, the muscle activity sensors responsive to signals generated by muscles in the arm of the user; and a transmitter communicatively coupled to the plurality of muscle activity sensors, wherein in use the transmitter transmits at least one signal from the wearable muscle interface device based on the signals detected by the muscle activity sensors; and ii) a wearable head-mounted display comprising: at least one display screen to be worn on a head of the user, the at least one display screen arranged to be positioned in front of at least one eye of the user when worn on the head of the user; a receiver communicatively coupled to the at least one display screen, wherein in use the receiver directly receives the at least one signal transmitted from the transmitter of the wearable muscle interface device; and a processor communicatively coupled to the receiver and to the at least one display screen, wherein in use the at least one signal received directly from the transmitter of the wearable muscle interface device by the receiver of the wearable head-mounted display effects control of at least one function of the wearable head-mounted display. The transmitter of the wearable muscle interface device may include a wireless transmitter and the receiver of the wearable head-mounted display may include a wireless receiver. The wearable muscle interface device of the wearable system may further include a processor that in use interprets the signals detected by the muscle

activity sensors as a gesture, wherein the processor of the wearable muscle interface device is communicatively coupled in between the transmitter and the plurality of muscle activity sensors, and wherein the at least one signal that, in use, is transmitted from the wearable muscle interface device may be based on the gesture interpreted by the processor of the wearable muscle interface device.

[0124] The plurality of muscle activity sensors in the wearable muscle interface device of the wearable system may include at least one muscle activity sensor selected from the group consisting of: an electromyographic (EMG) sensor and a mechanomyographic (MMG) sensor. The wearable muscle interface device of the wearable system may further include at least one accelerometer that in use detects signals generated by motion of the arm of the user, the at least one accelerometer communicatively coupled to the transmitter, and wherein in use the at least one signal transmitted by the transmitter of the wearable muscle interface device may be based on both the signals detected by the muscle activity sensors and the signals detected by the at least one accelerometer.

[0125] A method of using a wearable system to achieve hands-free access to and control of a portable electronic display, wherein the wearable system includes a wearable muscle interface device and a wearable head-mounted display, may be summarized as including: detecting muscle activity corresponding to a physical gesture performed by a user of the wearable system by at least one muscle activity sensor of the wearable muscle interface device; transmitting at least one signal from the wearable muscle interface device by a transmitter of the wearable muscle interface device based at least in part on the muscle activity detected by at least one muscle activity sensor of the wearable muscle interface device; receiving the at least one signal directly from the wearable muscle interface device by a receiver of the wearable head-mounted display; processing the at least one signal by a processor of the wearable head-mounted display; and effecting at least one interaction between the user and the wearable head-mounted display by the processor of the wearable head-mounted display based on the processing of the at least one signal by the processor of the wearable head-mounted display. The method may further include, in response to detecting muscle activity corresponding to a physical gesture performed by a user of the wearable system by at least one muscle activity sensor of the wearable muscle interface device, processing the detected muscle activity by a processor of the wearable muscle interface device, and transmitting at least one signal from the wearable muscle interface device by a transmitter of the wearable muscle interface device based at least in part on the muscle activity detected by at least one muscle activity sensor of the wearable muscle interface device may include transmitting at least one signal from the wearable muscle interface device by the transmitter of the wearable muscle interface device based at least in part on processing the detected muscle activity by the processor of the wearable muscle interface device.

[0126] The method may further include detecting motion of the wearable muscle interface device corresponding to the physical gesture performed by the user of the wearable system by at least one accelerometer of the wearable muscle interface device, and transmitting at least one signal from the wearable muscle interface device by a transmitter of the wearable muscle interface device based at least in part on the muscle activity detected by at least one muscle activity sensor of the wearable muscle interface device may include transmitting at least one signal from the wearable muscle interface device by the transmitter of the wearable muscle interface device based on both the muscle activity detected by at least one muscle activity sensor of the wearable muscle interface device and the motion detected by at least one accelerometer of the wearable muscle interface device. Transmitting at least one signal from the wearable muscle interface device by a transmitter of the wearable muscle interface device may include wirelessly transmitting at least one signal from the wearable muscle interface device by a wireless transmitter of the wearable muscle interface device. Receiving the at least one signal directly from the wearable muscle interface device by a receiver of the wearable head-mounted display may include wirelessly receiving the at

least one signal directly from the wearable muscle interface device by a wireless receiver of the wearable head-mounted display.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0127] In the drawings, identical reference numbers identify similar elements or acts. The sizes and relative positions of elements in the drawings are not necessarily drawn to scale. For example, the shapes of various elements and angles are not drawn to scale, and some of these elements are arbitrarily enlarged and positioned to improve drawing legibility. Further, the particular shapes of the elements as drawn are not intended to convey any information regarding the actual shape of the particular elements, and have been solely selected for ease of recognition in the drawings.

[0128] FIG. 1 is a perspective view of an exemplary wearable electronic device that employs signal routing techniques in accordance with the present systems, articles and methods.

[0129] FIG. 2 is a side-elevation view of a wearable electronic device that employs signal routing in accordance with the present systems, articles, and methods.

[0130] FIG. 3 is an illustrative diagram of a portion of a wearable electronic device showing exemplary routing of analog signals in accordance with the present systems, articles, and methods.

[0131] FIG. 4 is an illustrative diagram of a portion of a wearable electronic device showing exemplary routing of digital signals in accordance with the present systems, articles, and methods.

[0132] FIG. 5 is a flow-diagram showing a method of routing signals within a wearable electronic device in accordance with the present systems, articles, and methods.

[0133] FIG. 6 is a perspective view of an exemplary wristwatch that includes an enhanced watchstrap employing contact sensors in accordance with the present systems, articles, and methods.

[0134] FIG. 7A is a plan view showing a contact surface of an exemplary enhanced watchstrap in accordance with the present systems, articles, and methods.

[0135] FIG. 7B is a side elevational view of the exemplary enhanced watchstrap from FIG. 7A showing the relative positions of components on the surfaces and in the inner volume thereof, in accordance with the present systems, articles, and methods.

[0136] FIG. 8 is a perspective view of an exemplary wristwatch that includes an enhanced back-plate having at least one contact sensor in accordance with the present systems, articles, and methods.

[0137] FIG. 9 is a plan view showing an underside of a wristwatch and thereby providing a clearer view (compared to the perspective view of FIG. 8) of a back-plate that is enhanced in accordance with the present systems, articles, and methods.

[0138] FIG. 10 is a perspective view of an enhanced back-plate for integration into a wristwatch in accordance with the present systems, articles, and methods.

[0139] FIG. 11 is a perspective view of an exemplary wearable electromyography (“EMG”) device that includes two contact sensor types: a set of capacitive EMG sensors and at least one capacitive touch sensor in accordance with the present systems, articles, and methods.

[0140] FIG. 12 is a perspective view of an exemplary wearable electromyography device that forms part of a human-electronics interface in accordance with the present systems, articles and methods.

[0141] FIG. 13 is an illustrative diagram of a system that enables electromyographic control of an electronic device in accordance with the present systems, articles, and methods.

[0142] FIG. 14 is a flow-diagram showing a method of operating a wearable electromyography device to provide electromyographic control of an electronic device in accordance with the present systems, articles, and methods.

[0143] FIG. **15** is a flow-diagram showing a method of operating a wearable electromyography device to provide both electromyographic and motion control of an electronic device in accordance with the present systems, articles, and methods.

[0144] FIG. **16** is a schematic illustration that shows an exemplary mapping between a set of exemplary gestures and a set of exemplary gesture identification flags in accordance with the present systems, articles, and methods.

[0145] FIG. **17** is a flow-diagram showing a method of electromyographically controlling at least one function of an electronic device by a wearable electromyography device in accordance with the present systems, articles, and methods.

[0146] FIG. **18** is a schematic illustration that shows an exemplary mapping between a set of exemplary gesture identification flags and a set of exemplary functions of an electronic device in accordance with the present systems, articles, and methods.

[0147] FIG. **19A** is a cross-sectional view of an improved capacitive EMG sensor that provides enhanced robustness against variations in skin and/or environmental conditions in accordance with the present systems, articles, and methods.

[0148] FIG. **19B** is a cross-sectional view of a laminate version of an improved capacitive EMG sensor that provides enhanced robustness against variations in skin and/or environmental conditions in accordance with the present systems, articles, and methods.

[0149] FIG. **20** is a flow-diagram showing a method of fabricating an improved capacitive EMG sensor in accordance with the present systems, articles, and methods.

[0150] FIG. **21** is a perspective view of an exemplary wearable EMG device that includes improved capacitive EMG sensors in accordance with the present systems, articles, and methods.

[0151] FIG. **22** is a schematic diagram of a capacitive EMG sensor that employs sensor electrodes that are configured to capacitively couple to the skin of a user.

[0152] FIG. **23** is a schematic diagram of a capacitive EMG sensor employing sensor electrodes that are adapted to, in use, resistively couple to the skin of a user in accordance with the present systems, articles, and methods.

[0153] FIG. **24** is a cross sectional view of a capacitive EMG sensor that resistively couples to the user's skin in accordance with the present systems, articles, and methods.

[0154] FIG. **25** is a cross sectional view of a capacitive EMG sensor packaged in a housing and employing bi-layer sensor electrodes that protrude from the housing in order to physically contact and electrically couple to a user's skin in accordance with the present systems, articles, and methods.

[0155] FIG. **26** is a flow-diagram of a method of fabricating an EMG sensor in accordance with the present systems, articles, and methods.

[0156] FIG. **27** is a perspective view of an exemplary wearable EMG device that includes capacitive EMG sensors adapted to, in use, resistively couple to the user's skin in accordance with the present systems, articles, and methods.

[0157] FIG. **28** is a side plan view that illustrates a user wearing a head mounted display and a muscle interface device in accordance with the present systems, devices, and methods.

[0158] FIG. **29** is an isometric view that illustrates a detailed view of a muscle interface device in accordance with the present systems, devices, and methods.

[0159] FIG. **30** is a data graph that illustrates an electrical signal detected by an EMG sensor.

[0160] FIG. **31** is a schematic view that illustrates wireless communication between a head mounted display and a muscle interface device in accordance with the present systems, devices, and methods.

[0161] FIG. **32** is a schematic view that illustrates a user's hand and wrist gesture processed as a control signal by the muscle interface device for interacting with content displayed on the head mounted display.

[0162] FIG. **33** is a schematic view of a system architecture of a muscle interface device in

accordance with the present systems, devices, and methods.

[0163] FIG. **34** is a flow chart of a method of using a wearable system to achieve hands-free access to and control of a portable electronic display in accordance with the present systems, devices, and methods.

[0164] FIG. **35** is a flow-diagram showing a method of using wearable system to achieve hands-free access to and control of a portable electronic display in accordance with the present systems, devices, and methods.

[0165] In the drawings, embodiments of the invention are illustrated by way of example. It is to be expressly understood that the description and drawings are only for the purpose of illustration and as an aid to understanding, and are not intended as a definition of the limits of the invention.

DETAILED DESCRIPTION

[0166] In the following description, certain specific details are set forth in order to provide a thorough understanding of various disclosed embodiments. However, one skilled in the relevant art will recognize that embodiments may be practiced without one or more of these specific details, or with other methods, components, materials, etc. In other instances, well-known structures associated with electronic devices, and in particular portable electronic devices such as wearable electronic devices, have not been shown or described in detail to avoid unnecessarily obscuring descriptions of the embodiments.

[0167] Unless the context requires otherwise, throughout the specification and claims which follow, the word “comprise” and variations thereof, such as, “comprises” and “comprising” are to be construed in an open, inclusive sense, that is as “including, but not limited to.”

[0168] Reference throughout this specification to “one embodiment” or “an embodiment” means that a particular feature, structures, or characteristics may be combined in any suitable manner in one or more embodiments.

[0169] As used in this specification and the appended claims, the singular forms “a,” “an,” and “the” include plural referents unless the content clearly dictates otherwise. It should also be noted that the term “or” is generally employed in its broadest sense, that is as meaning “and/or” unless the content clearly dictates otherwise.

[0170] The headings and Abstract of the Disclosure provided herein are for convenience only and do not interpret the scope or meaning of the embodiments.

Description For Signal Routing in Wearable Electronic Devices

[0171] The various embodiments described herein provide systems, articles, and methods for signal routing in wearable electronic devices. Throughout this specification and the appended claims, the term “routing” and its variants, such as “route,” “routes,” etc., refer to the guided transfer of a signal or signals (including but not limited to electrical signals and/or optical signals) from a first component to a second component, with or without passing over or through any number of intervening components. For example, a signal may be routed directly from component A to component B by one or more communicative pathway(s) that couple(s) component A to component B, or a signal may be routed indirectly from component A to component B via an intervening component C by one or more communicative pathway(s) having a first portion that couples component A to component C and a second portion that couples component C to component B.

[0172] Throughout this specification and the appended claims, the term “via” in the context of signal routing is generally used to indicate that a signal is routed, transmitted, or otherwise directed over or through an intervening point or structure en route from a first point or structure to a second point or structure. A signal may be routed from a first point A to a second point B “via” an intervening point C by physically and/or communicatively coupling to one or more component(s) at the intervening point C. For example, a signal may be routed from a first point A to a second point B via an intervening point C by a communicative pathway comprising a first electrically conductive trace that electrically communicatively couples a component at point A to a component at point C and a second electrically conductive trace that electrically communicatively couples the

component at point C to a component at point B. However, a signal may also be routed from a first point A to a second point B via an intervening point C by a communicative pathway comprising a single electrically conductive trace that electrically communicatively couples a component at point A to a component at point B and physically extends over or through point C in between points A and B without electrically communicatively coupling to any component(s) at point C.

[0173] Throughout this specification and the appended claims, the term “signal” is generally used to refer to information in any format and in any type of tangible, non-transitory medium that stores, represents, or otherwise embodies information and carries that information when transmitted. Exemplary signals that may be employed by and/or that may employ the present systems, articles, and methods include, but are not limited to, electrical signals, magnetic signals and/or optical signals. Similarly, throughout this specification and the appended claims the term “communicative” as in “communicative pathway,” “communicative coupling,” and in variants such as “communicatively coupled,” is generally used to refer to an engineered configuration for transferring and/or exchanging information. Exemplary communicative pathways include, but are not limited to, electrically conductive pathways (e.g., electrically conductive wires, electrically conductive traces), magnetic pathways (e.g., magnetic media), and/or optical pathways (e.g., optical fiber), and exemplary communicative couplings include, but are not limited to, electrical couplings and/or optical couplings. In general, a “communicative pathway” may include any number of serially-linked portions through which a signal is routed.

[0174] As previously described, there are at least two exemplary design factors for a wearable electronic device that influence signal routing: functionality and affordability/manufacturability. These two factors (and potentially many others) may be of great interest to potential users of wearable electronic devices, but they may each be influenced in different ways by signal routing design choices. A typical user may desire sophisticated functionality at minimal cost. The present systems, articles, and methods describe wearable electronic devices that employ signal routing techniques that achieve desired functionality without compromising manufacturability.

[0175] FIG. 1 is a perspective view of an exemplary wearable electronic device **100** that employs signal routing techniques in accordance with the present systems, articles and methods. Exemplary device **100** is an armband designed to be worn on the wrist, forearm, or upper arm of a user, though a person of skill in the art will appreciate that the teachings described herein may readily be applied in wearable electronic devices designed to be worn elsewhere on the body of the user (such as on a finger, leg, ankle, neck, or torso of the user). Device **100** includes a set of eight pod structures **101**, **102**, **103**, **104**, **105**, **106**, **107**, and **108** that form physically coupled links of the wearable electronic device **100**. Each pod structure in the set of eight pod structures **101**, **102**, **103**, **104**, **105**, **106**, **107**, and **108** is positioned adjacent and in between two other pod structures in the set of eight pod structures and the set of pod structures forms a perimeter of an annular or closed loop configuration. For example, pod structure **101** is positioned adjacent and in between pod structures **102** and **108** at least approximately on a perimeter of the annular or closed loop configuration of pod structures, pod structure **102** is positioned adjacent and in between pod structures **101** and **103** at least approximately on the perimeter of the annular or closed loop configuration, pod structure **103** is positioned adjacent and in between pod structures **102** and **104** at least approximately on the perimeter of the annular or closed loop configuration, and so on. Each of pod structures **101**, **102**, **103**, **104**, **105**, **106**, **107**, and **108** is physically coupled to the two adjacent pod structures by at least one adaptive coupler (not shown in FIG. 1). For example, pod structure **101** is physically coupled to pod structure **108** by an adaptive coupler and to pod structure **102** by an adaptive coupler. The term “adaptive coupler” is used throughout this specification and the appended claims to denote a system, article or device that provides flexible, adjustable, modifiable, extendable, extensible, or otherwise “adaptive” physical coupling. Adaptive coupling is physical coupling between two objects that permits limited motion of the two objects relative to one another. An example of an adaptive coupler is an elastic material such as an elastic band. Thus, each of pod structures **101**,

102, 103, 104, 105, 106, 107, and 108 in the set of eight pod structures may be adaptively physically coupled to the two adjacent pod structures by at least one elastic band. The set of eight pod structures may be physically bound in the annular or closed loop configuration by a single elastic band that couples over or through all pod structures or by multiple separate elastic bands that couple between adjacent pairs of pod structures or between groups of adjacent pairs of pod structures. Device **100** is depicted in FIG. **1** with the at least one adaptive coupler completely retracted and contained within the eight pod structures **101, 102, 103, 104, 105, 106, 107, and 108** (and therefore the at least one adaptive coupler is not visible in FIG. **1**). Further details of adaptive coupling in wearable electronic devices are described in, for example, U.S. Pat. No. 10,152,082, which is incorporated herein by reference in its entirety.

[0176] Throughout this specification and the appended claims, the term “pod structure” is used to refer to an individual link, segment, pod, section, structure, component, etc. of a wearable electronic device. For the purposes of the present systems, articles, and methods, an “individual link, segment, pod, section, structure, component, etc.” (i.e., a “pod structure”) of a wearable electronic device is characterized by its ability to be moved or displaced relative to another link, segment, pod, section, structure component, etc. of the wearable electronic device. For example, pod structures **101** and **102** of device **100** can each be moved or displaced relative to one another within the constraints imposed by the adaptive coupler providing adaptive physical coupling therebetween. The desire for pod structures **101** and **102** to be movable/displaceable relative to one another specifically arises because device **100** is a wearable electronic device that advantageously accommodates the movements of a user and/or different user forms.

[0177] Throughout this specification and the appended claims the term “physically coupled” is generally used to encompass both direct and indirect physical coupling. That is, in the present systems, articles, and methods, two objects are considered “physically coupled” if they are in direct physical contact with one another or if they are indirectly physically connected through one or more intervening structures, such as an adaptive coupler.

[0178] Device **100** includes eight pod structures **101, 102, 103, 104, 105, 106, 107, and 108** that form physically coupled links of the device **100**. The number of pod structures included in a wearable electronic device is dependent on at least the nature, function(s), and design of the wearable electronic device, and the present systems, articles, and methods may be applied to any wearable electronic device employing any number of pod structures, including wearable electronic devices employing more than eight pod structures and wearable electronic devices employing fewer than eight pod structures.

[0179] In exemplary device **100** of FIG. **1**, each of pod structures **101, 102, 103, 104, 105, 106, 107, and 108** comprises a respective housing having a respective inner volume. Each housing may be formed of substantially rigid material and may be optically opaque. Thus, details of the components contained within the housings (i.e., within the inner volumes of the housings) of pod structures **101, 102, 103, 104, 105, 106, 107, and 108** are not visible in FIG. **1**. To facilitate descriptions of exemplary device **100**, some internal components are depicted by dashed lines in FIG. **1** to indicate that these components are contained in the inner volume(s) of housings and not actually visible in the view depicted in FIG. **1** (unless an optically transparent or translucent housing material is used). For example, any or all of pod structures **101, 102, 103, 104, 105, 106, 107, and/or 108** may include electric circuitry. In FIG. **1**, a first pod structure **101** is shown containing electric circuitry **111** (i.e., electric circuitry **111** is contained in the inner volume of the housing of pod structure **101**), a second pod structure **102** is shown containing electric circuitry **112**, and a third pod structure **108** is shown containing electric circuitry **118**. The electric circuitry in any or all pod structures may be communicatively coupled to the electric circuitry in at least one other pod structure by at least one respective communicative pathway (e.g., by at least one electrically conductive pathway and/or by at least one optical pathway). For example, FIG. **1** shows a first communicative pathway **121** providing communicative coupling between electric circuitry

118 of pod structure **108** and electric circuitry **111** of pod structure **101**, and a second communicative pathway **122** providing communicative coupling between electric circuitry **111** of pod structure **101** and electric circuitry **112** of pod structure **102**. Communicative coupling between electric circuitries of pod structures in device **100** may include systems, articles, and methods for strain mitigation as described in U.S. patent application Ser. No. 14/335,668), which is incorporated by reference herein in its entirety.

[0180] Throughout this specification and the appended claims, the term “rigid” as in, for example, “substantially rigid material,” is used to describe a material that has an inherent tendency to maintain its shape and resist malformation/deformation under the moderate stresses and strains typically encountered by a wearable electronic device.

[0181] Each individual pod structure within a wearable electronic device may perform a particular function, or particular functions. For example, in device **100**, each of pod structures **101**, **102**, **103**, **104**, **105**, **106**, and **107** includes a respective sensor **110** (only one called out in FIG. **1** to reduce clutter) to in use detect inputs effected by a user and to provide electrical signals in response to the detected inputs. Thus, each of pod structures **101**, **102**, **103**, **104**, **105**, **106**, and **107** may be referred to as a respective “sensor pod.” Throughout this specification and the appended claims, the term “sensor pod” is used to denote an individual pod structure that includes at least one sensor or transducer to in use detect inputs effected by a user. Each sensor **110** may be any type of sensor that is capable of detecting any kind of signal produced, generated, or otherwise effected by the user, including but not limited to: an electromyography sensor, a magnetomyography sensor, a mechanomyography sensor, a blood pressure sensor, a heart rate sensor, a gyroscope, an accelerometer, a compass, and/or a thermometer. In exemplary device **100**, each of sensor pods **101**, **102**, **103**, **104**, **105**, **106**, and **107** includes a respective electromyography sensor **110** (only one called out in FIG. **1** to reduce clutter) to in use detect inputs effected by the user in the form of electrical signals produced by muscle activity. Wearable electromyography device **100** may transmit information based on the detected muscle activity to provide a human-electronics interface (e.g., an HCI). Further details of exemplary wearable electromyography device **100** are described in U.S. Pat. No. 10,528,135, U.S. patent application Ser. No. 14/186,889, and U.S. patent application Ser. No. 14/194,252, each of which is incorporated herein by reference in its entirety. Those of skill in the art will appreciate, however, that a wearable electronic device having electromyography functionality is used only as an example in the present systems, articles, and methods and that the systems, articles and methods for signal routing in wearable electronic devices described herein are in no way limited to wearable electronic devices that employ electromyography sensors unless explicitly recited in a respective claim to such.

[0182] Pod structure **108** of device **100** includes a processor **140** that processes the signals provided by the sensors **110** of sensor pods **101**, **102**, **103**, **104**, **105**, **106**, and **107** in response to user-effected input(s). Pod structure **108** may therefore be referred to as a “processor pod.” Throughout this specification and the appended claims, the term “processor pod” is used to denote an individual pod structure that includes at least one processor to in use process signals. The processor may be any type of processor, including but not limited to: a digital microprocessor or microcontroller, an application-specific integrated circuit, a field-programmable gate array, or the like, that analyzes the signals to determine at least one output, action, or function based on the signals.

[0183] As used throughout this specification and the appended claims, the terms “sensor pod” and “processor pod” are not necessarily exclusive. A single pod structure may satisfy the definitions of both a “sensor pod” and a “processor pod” and may be referred to as either type of pod structure. For greater clarity, the term “sensor pod” is used to refer to any pod structure that includes a sensor and performs at least the function(s) of a sensor pod, and the term processor pod is used to refer to any pod structure that includes a processor and performs at least the function(s) of a processor pod. In device **100**, processor pod **108** includes a sensor **110** (not visible in FIG. **1**) to in use detect inputs effected by a user, so processor pod **108** could be referred to as a sensor pod. However, in

exemplary device **100**, processor pod **108** is the only pod structure that includes a processor **140**, thus processor pod **108** is the only pod structure in exemplary device **100** that can be referred to as a processor pod. In alternative embodiments of device **100**, multiple pod structures may include processors, and thus multiple pod structures may serve as processor pods. Similarly, some pod structures may not include sensors.

[0184] As previously described, each of pod structures **101**, **102**, **103**, **104**, **105**, **106**, **107**, and **108** may include electric circuitry. FIG. **1** depicts electric circuitry **111** inside the inner volume of sensor pod **101**, electric circuitry **112** inside the inner volume of sensor pod **102**, and electric circuitry **118** inside the inner volume of processor pod **108**. Circuitry **111** in sensor pod **101** includes at least component **131**, circuitry **112** in sensor pod **102** includes at least component **132**, and circuitry **118** in processor pod **108** includes at least components **138** and **140**. The components and functions of the electric circuitry in any or all of pod structures **101**, **102**, **103**, **104**, **105**, **106**, **107**, and/or **108** depend on the nature of device **100**. As previously described, component **140** of circuitry **118** in processor pod **108** may include at least one processor (e.g., at least one microprocessor, digital signal processor (DSP), graphics processing unit (GPU), application specific integrated circuit (ASIC), programmable gate array (PGA) and/or programmable logic unit (PLU)). In the example of device **100** as an electromyography device, each of pod structures **101**, **102**, **103**, **104**, **105**, **106**, **107**, and **108** may include a respective amplification circuit to in use amplify electrical signals provided by at least one respective sensor **110**. For example, each of components **131**, **132**, and **138** may include a respective amplification circuit to in use amplify electrical signals provided by at least one respective sensor **110** in each of pod structures **101**, **102**, and **108**. In this way, sensor pod **101** (and similarly sensor pod **102** and processor pod **108**) may include an electromyography sensor **110** to provide analog signals in response to muscle activity by a user, and the sensor **110** of sensor pod **101** may be communicatively coupled to an amplification circuit **131** in electric circuitry **111** to amplify the analog signals provided by the sensor **110**.

[0185] The electric circuitry of any or all of pod structures **101**, **102**, **103**, **104**, **105**, **106**, **107**, and/or **108** may include an analog-to-digital conversion (“ADC”) circuit to in use convert analog signals into digital signals. Thus, any or all of components **131**, **132**, and **138** may further include a respective ADC circuit to in use convert analog signals provided by at least one respective sensor **110** in each of pod structures **101**, **102**, and **108** into digital signals. In this way, sensor pod **101** (and similarly sensor pod **102** and processor pod **108**) may include an electromyography sensor **110** to provide analog signals in response to muscle activity by a user, the sensor **110** of sensor pod **101** may be communicatively coupled to an amplification circuit **131** in electric circuitry **111** to amplify the analog signals provided by the sensor **110**, and the amplification circuit **131** may be communicatively coupled to an ADC circuit **131** to convert the amplified analog signals into digital signals.

[0186] As will be described in more detail later, processor pod **108** may be the only one of pod structures **101**, **102**, **103**, **104**, **105**, **106**, **107**, and **108** that includes an ADC circuit **138**. In this configuration, amplified analog signals are routed through communicative pathways (e.g., communicative pathways **121** and **122**) to processor pod **108**. Alternatively, each of pod structures **101**, **102**, **103**, **104**, **105**, **106**, **107**, and **108** may include a respective ADC circuit (e.g., **131**, **132**, and **138**) and digital signals may be routed through communicative pathways (e.g., communicative pathways **121** and **122**) to processor pod **108**.

[0187] The electric circuitry (e.g., **111**, **112**, and/or **118**) of any pod structure in device **100** may include other circuits, elements, or components, including but not limited to: filtering circuits, an optical signal generator to convert electrical signals into optical signals, an electrical signal generator to convert optical signals into electrical signals, a battery to provide a portable power source for device **100**, a wireless transmitter (e.g., a Bluetooth® transmitter) to send signals to another electronic device based on the muscle activity signals detected by electromyography sensors **110**, and/or a tethered connector port **150** (e.g., wired or optical) to provide a direct

communicative coupling to another electronic device for the purpose of power transfer (e.g., recharging the battery) and/or data transfer. Connector port **150** is illustrated in FIG. **1** as a micro-Universal Serial Bus port, though a person of skill in the art will appreciate that any connector port may similarly be used, including but not limited to: a Universal Serial Bus port, a mini-Universal Serial Bus port, a SMA port, a THUNDERBOLT® port, and the like.

[0188] Signals that are provided by sensors **110** in device **100** are routed to processor pod **108** for processing by processor **140**. The various embodiments described herein provide systems, articles, and methods to achieve this signal routing without comprising the manufacturability and/or affordability of device **100**. To this end, device **100** employs a plurality of communicative pathways (e.g., **121** and **122**) to route the signals that are provided by sensor pods **101**, **102**, **103**, **104**, **105**, **106**, and **107** to processor pod **108**. Each respective pod structure **101**, **102**, **103**, **104**, **105**, **106**, **107**, and **108** in device **100** is communicatively coupled to at least one other pod structure by at least one respective communicative pathway from the plurality of communicative pathways. Each communicative pathway (e.g., **121** and **122**) may include any number of portions (e.g., a single continuous portion or multiple serially-linked portions) realized in any communicative form, including but not limited to: electrically conductive wires or cables, ribbon cables, fiber-optic cables, optical/photonic waveguides, electrically conductive traces carried by a rigid printed circuit board, and/or electrically conductive traces carried by a flexible printed circuit board.

[0189] FIG. **2** is a side-elevation view of a wearable electronic device **200** that employs signal routing in accordance with the present systems, articles, and methods. Device **200** is substantially similar to device **100** from FIG. **1** in that device **200** comprises a set of pod structures comprising sensor pods **201**, **202**, **203**, **204**, **205**, **206**, and **207** and processor pod **208** that form physically coupled links of wearable electronic device **200**. Each pod structure is positioned adjacent at least one other pod structure (e.g., adjacent and in between two other pod structures) and the set of pod structures forms a perimeter of an annular or closed loop configuration. FIG. **2** shows device **200** in an expanded annular or closed loop configuration adapted to fit the arm of a larger user than the contracted annular or closed loop configuration of device **100** from FIG. **1**. As a result, adaptive couplers **270** (only one called out in FIG. **2**) providing adaptive physical coupling between adjacent pairs of pod structures are visible in FIG. **2**, whereas such adaptive couplers **270** are not visible in FIG. **1**. Each of sensor pods **201**, **202**, **203**, **204**, **205**, **206**, and **207** comprises a respective sensor **210** (only one called out in FIG. **2** to reduce clutter) to in use detect inputs effected by a user (e.g., an electromyography sensor to in use detect muscle activity by a user) and provide signals in response to the detected inputs. Processor pod **208** comprises a similar sensor **210** as well as a processor **240** that processes the signals provided by the respective sensors **210**. Signals provided by sensors **210** are routed from each of sensor pods **201**, **202**, **203**, **204**, **205**, **206**, and **207** (in some cases via at least one adjacent sensor pod) to processor pod **208** by communicative pathways **220** (only one called out in FIG. **2** to reduce clutter).

[0190] Each of pod structures **201**, **202**, **203**, **204**, **205**, **206**, **207**, and **208** comprises a respective housing **260** (only one called out in FIG. **2** to reduce clutter) formed of substantially rigid material and having an inner volume that contains at least a portion of respective electric circuitry **230** (only one called out in FIG. **2** to reduce clutter). Each of sensors **210** is positioned on or proximate a surface of a respective housing **260** and communicatively coupled to the electric circuitry **230** therein. For each of pod structures **201**, **202**, **203**, **204**, **205**, **206**, **207**, and/or **208**, electric circuitry **230** may include an amplification circuit and/or a filtering circuit and/or an ADC circuit. As previously described, housings **260** may be optically opaque, so some exemplary components within housings **260** (e.g., electrical circuitry **230**) are illustrated with dashed lines to indicate that such components may not actually be visible in the view illustrated in FIG. **2**. Each communicative pathway **220** provides communicative coupling between the respective electric circuitries **230** in each of two pod structures **201**, **202**, **203**, **204**, **205**, **206**, **207**, and **208**. Thus, each communicative

pathway **220** includes a respective first portion **220a** in the inner volume of the housing **260** of a respective first pod structure (e.g., sensor pod **206**), a respective second portion **220b** in the inner volume of the housing **260** of a respective second pod structure (e.g., sensor pod **207**), and a respective third portion **220c** that extends between the housing **260** of the respective first pod structure (e.g., sensor pod **206**) and the housing **260** of the respective second pod structure (e.g., sensor pod **207**).

[0191] FIG. 2 shows that communicative pathways **220** provide routes through which signals may be coupled from each of sensor pods **201**, **202**, **203**, **204**, **205**, **206**, and **207** to processor pod **208**. Specifically, in accordance with the present systems, articles, and methods, the signals provided by each of sensor pods **201**, **202**, **203**, **204**, **205**, **206**, and **207** are serially routed via successive ones of adjacent pod structures in device **200** by communicative pathways **220** until the signals provided by each sensor pod **201**, **202**, **203**, **204**, **205**, **206**, **207** are routed to processor pod **208**. For example, signals provided by a first sensor pod **201** are routed to processor pod **208** through a first communicative pathway **220** that communicatively couples first sensor pod **201** to processor pod **208**; signals provided by a second sensor pod **202** are routed to processor pod **208** via first sensor pod **201** by a second communicative pathway **220** that communicatively couples the second sensor pod **202** to processor pod **208**; signals provided by a third sensor pod **203** are routed to processor pod **208** via second sensor pod **202** and first sensor pod **201** by a third communicative pathway **220** that communicatively couples the third sensor pod **203** to processor pod **208**; and signals provided by a fourth sensor pod **204** are routed to processor pod **208** via third sensor pod **203**, second sensor pod **202**, and first sensor pod **201** by a fourth communicative pathway **220** that communicatively couples the fourth sensor pod **204** to processor pod **208**. Similar communicative pathways route signals from sensor pods **205**, **206**, and **207** to processor pod **208**. Thus, signals from sensor pods **204**, **203**, **202**, and **201** are routed “clockwise” around the annular configuration of device **200** (with respect to the view illustrated in FIG. 2) towards processor pod **208** and signals from sensor pods **205**, **206**, and **207** are routed “counter-clockwise” around the annular configuration of device **200** towards processor pod **208**. The annular configuration of pod structures **201**, **202**, **203**, **204**, **205**, **206**, **207**, and **208** allows a communicative “break” or “open” between one pair of adjacent pod structures. For example, device **200** does not include a communicative coupling between sensor pods **204** and **205** because signals from sensor pod **204** are routed to processor pod **208** by “clockwise” serial coupling between sensor pods **204**, **203**, **202**, **201**, and **208** while signals from sensor pod **205** are routed to processor pod **208** by “counter-clockwise” serial coupling between sensor pods **205**, **206**, **207**, and **208**, though a person of skill in the art will appreciate that, in alternative embodiments, a communicative coupling could be used to couple between sensor pods **204** and **205** and/or the communicative “break” or “open” may occur between any pair of adjacent pod structures in device **200**.

[0192] As previously described, processor **240** in processor pod **208** may advantageously process digital signals. Analog signals may first be provided by sensors **210** in response to user-effected inputs, and any or all of electric circuitries **230** may include an ADC circuit that in use converts the analog signals into digital signals for processing by processor **240**. When only the processor pod **208** includes an ADC circuit in its electric circuitry **230**, each of sensor pods **201**, **202**, **203**, **204**, **205**, **206**, and **207** provides analog signals and analog signals are routed over/through/between the sensor pods to processor pod **208**. When a respective ADC circuit is included in the electric circuitry **230** of each sensor pod **201**, **202**, **203**, **204**, **205**, **206**, and **207**, then each sensor pod provides digital signals and digital signals are routed over/through/between the sensor pods to processor pod **208**. The various embodiments described herein provide systems, articles, and methods for routing analog and/or digital signals within a wearable electronic device.

[0193] FIG. 3 is an illustrative diagram of a portion of a wearable electronic device **300** showing exemplary routing of analog signals in accordance with the present systems, articles, and methods. Device **300** is substantially similar to device **200** from FIG. 2 (and therefore also similar to device

100 from FIG. 1), though FIG. 3 only depicts a portion of device **300** that comprises four sensor pods **301**, **302**, **303**, and **304** and a processor pod **308**, all of which are serially communicatively coupled to route analog signals from sensor pods **301**, **302**, **303**, and **304** to processor pod **308**. Sensor pods **301**, **302**, **303**, and **304** and processor pod **308** are all also adaptively physically coupled together by at least one adaptive coupler **370**.

[0194] Each of sensor pods **301**, **302**, **303**, and **304** comprises a respective sensor (e.g., a respective electromyography sensor) **311**, **312**, **313**, and **314** communicatively coupled to respective electric circuitry **331**, **332**, **333**, and **334**. In use, sensors **311**, **312**, **313**, and **314** detect inputs effected by a user and provide analog electrical signals in response to the detected inputs. The analog signals provided by each of sensors **311**, **312**, **313**, and **314** are routed to electric circuitries **331**, **332**, **333**, and **334**, respectively. Each of electric circuitries **331**, **332**, **333**, and **334** includes a respective amplification circuit to in use amplify the analog signals, and the amplified analog signals are serially routed via successively adjacent ones of sensor pods **301**, **302**, **303**, and **304** to processor pod **308**. Processor pod **308** has electric circuitry **338** that includes an ADC circuit to in use convert the amplified analog signals from sensor pods **301**, **302**, **303**, and **304** into digital signals. The digital signals are routed to a processor **340** within processor pod **308**. As previously described, processor **340** may include any type of processor (including but not limited to a digital microprocessor, a digital microcontroller, an FPGA, etc.) that analyzes the digital signals to determine at least one output, action, or function based on the digital signals. Processor **340** may include and/or be coupled to a computer-readable, non-transitory storage medium or memory storing instructions for how to process the digital signals.

[0195] In device **300**, processor pod **308** also includes a sensor (e.g., an electromyography sensor) **318** to in use detect user-effected inputs and provide analog signals in response to the detected inputs. Sensor **318** is communicatively coupled to electric circuitry **338** in processor pod **308**, and electric circuitry **338** includes an amplification circuit to in use amplify the analog signals provided by sensor **318**. The amplified analog signals are then converted into digital signals by the ADC circuit in electric circuitry **338** and the digital signals are routed to processor **340**.

[0196] The portion of device **300** shown in FIG. 3 provides an illustrative example of routing analog signals from a set of sensor pods **301**, **302**, **303**, and **304** to a processor pod **308** within a wearable electronic device. In the illustrative example, analog signals are routed from sensor pods **301**, **302**, **303**, and **304**, respectively, through a set of four communicative pathways **351**, **352**, **353**, and **354**. Specifically: sensor pod **301** provides amplified analog signals to processor pod **308** via communicative pathway **351**, sensor pod **302** provides amplified analog signals to processor pod **308** via communicative pathway **352**, sensor pod **303** provides amplified analog signals to processor pod **308** via communicative pathway **353**, and sensor pod **304** provides amplified analog signals to processor pod **308** via communicative pathway **354**. Each of communicative pathways **351**, **352**, **353**, and **354** may include one or more respective portion(s) depending on the number of intervening pod structures via which each communicative pathway passes en route from the corresponding sensor pod (**301**, **302**, **303**, or **304**) to processor pod **308**. In the illustrated example, communicative pathway **351** routes amplified analog signals from sensor pod **301** to processor pod **308** without passing via any intervening sensor pod(s) (because sensor pod **301** is positioned immediately adjacent processor pod **308**), therefore communicative pathway **351** includes only a single portion that extends through region **321** that physically separates sensor pod **301** and processor pod **308**. However, communicative pathway **352** routes amplified analog signals via sensor pod **301** en route from sensor pod **302** to processor pod **308**, and accordingly, communicative pathway **352** includes a first portion that extends through region **322** that physically separates sensor pod **302** and sensor pod **301** and a second portion that extends through region **321**. Depending on the implementation, communicative pathway **352** may or may not electrically couple to one or more component(s) of sensor pod **301** en route from sensor pod **302** to processor pod **308**. Similarly, communicative pathway **353** routes amplified analog signals via sensor pod **302** and

sensor pod **301** en route from sensor pod **303** to processor pod **308**, and accordingly, communicative pathway **353** includes a first portion that extends through region **323** that physically separates sensor pod **303** and sensor pod **302**, a second portion that extends through region **322**, and a third portion that extends through region **321**. Depending on the implementation, communicative pathway **353** may or may not electrically couple to one or more component(s) of sensor pod **302** and/or sensor pod **301** en route from sensor pod **303** to processor pod **308**.

Likewise, communicative pathway **354** routes amplified analog signals via sensor pod **303**, sensor pod **302**, and sensor pod **301** en route from sensor pod **304** to processor pod **308**, and accordingly, communicative pathway **354** includes a first portion that extends through region **324** that physically separates sensor pod **304** and sensor pod **303**, a second portion that extends through region **323**, a third portion that extends through region **322**, and a fourth portion that extends through region **321**. Depending on the implementation, communicative pathway **354** may or may not electrically couple to one or more component(s) of sensor pod **303**, sensor pod **302**, and/or sensor pod **301** en route from sensor pod **304** to processor pod **308**. Processor pod **308** receives amplified analog signals from sensor pods **301**, **302**, **303**, and **304** through communicative pathways **351**, **352**, **353**, and **354** (respectively) and converts the amplified analog signals into digital signals by the ADC circuit in electric circuitry **338**. Digital signals are routed within processor pod **308** from electric circuitry **338** to processor **340**.

[0197] Each of communicative pathways **351**, **352**, **353**, and/or **354** may comprise one or multiple communicative pathways. The portion of device **300** shown in FIG. **3** illustrates each of communicative pathways **351**, **352**, **353**, and **354** as a single respective pathway (some of which comprise multiple portions as described above) to enhance descriptive clarity of device **300** and is not necessarily representative of the number of communicative pathways that may be implemented in practice. For example, in order to streamline manufacturing of device **300**, each of regions **321**, **322**, **323**, and **324** may comprise the same number of portions of communicative pathways such that the coupling between each pair of adjacent pod structures in device **300** is substantially the same regardless of the number of signal channels actually coupled therebetween. For example, for the portion of device **300** illustrated in FIG. **3**, each of regions **321**, **322**, **323**, and **324** may include four portions of communicative pathways even though only one pathway may be active in region **324** (corresponding to a first portion of pathway **354**), only two pathways may be active in region **323** (corresponding to a second portion of pathway **354** and a first portion of pathway **353**), and only three pathways may be active in region **322** (corresponding to a third portion of pathway **354**, a second portion of pathway **353**, and a first portion of pathway **352**). Employing the same number of communicative pathways/portions of communicative pathways in each of regions **321**, **322**, **323**, and **324** regardless of the number of actual signal channels being coupled allows substantially the same coupling configuration to be used between each pair of pod structures in device **300**, which in turn means that the coupling between each pair of pod structures in device **300** may be manufactured in substantially the same way. In other words, the manufacturing process for device **300** does not need to include pod-specific coupling configurations, pathways, and/or processes. Manufacturing costs are reduced by minimizing the number of steps in the manufacturing process, by minimizing the number of component-specific adaptations required for each manufacturing step, and/or by minimizing the number of distinct components. Thus, employing a single configuration for the coupling in each of regions **321**, **322**, **323**, and **324** means that the coupling between each respective pair of pod structures may be realized by substantially the same physical component(s). Such reduces manufacturing costs by avoiding pod-specific adaptations for each communicative pathway and/or coupling configuration between pod structures.

[0198] As previously described, each of communicative pathways **351**, **352**, **353**, and **354** may be physically realized in a variety of different ways, including but not limited to: electrically conductive wires/cables, ribbon cables, fiber-optic cables, optical/photonic waveguides, and/or electrically conductive traces on a printed circuit board. In the case of electrically conductive traces

on a printed circuit board, a flexible printed circuit board may be advantageous over a rigid printed circuit board to accommodate the limited motion afforded by adaptive coupler **370**. Thus, in some implementations each of communicative pathways **351**, **352**, **353**, and **354** may comprise a respective flexible printed circuit board. In other implementations, each of regions **321**, **322**, **323**, and **324** may include a respective flexible printed circuit board where the number of electrically conductive traces carried by (i.e., carried on and/or within) each respective flexible printed circuit board may be greater than or equal to the number of communicative pathways that include a respective portion in that region. Thus, for example, region **321** may include a flexible printed circuit board having four electrically conductive traces (a first trace corresponding to pathway **351**, a second trace corresponding to the second portion of pathway **352**, a third trace corresponding to the third portion of pathway **353**, and a fourth trace corresponding to the fourth portion of pathway **354**) and, as another example, region **324** may include a flexible printed circuit board having either one trace (corresponding to the first portion of pathway **354**) or four traces (with a first trace corresponding to the first portion of pathway **354** and the other three traces being unused but included for the purpose of simplifying manufacturing by using the same flexible printed circuit board to couple in between pod structures regardless of the number of pathways/portions of pathway that extend between the pod structures). Each flexible printed circuit board may electrically couple to a respective socket (by, for example hot-bar soldering) in each of two adjacent pod structures in device **300**. Such sockets are generally represented by terminals **380** in FIG. **3**. Thus, each sensor pod **301**, **302**, **303**, and **304** and processor pod **308** comprises a respective set of four terminals **380** (only one called out in FIG. **3** to reduce clutter). For the purpose of simplicity, each terminal **380** is used in FIG. **3** to embody both an input and an output functionality in device **300**, though a person of skill in the art will appreciate that terminals **380** may employ physically separate and/or distinct input and output terminals that are communicatively coupled together through electrical and/or optical circuitry. In alternative embodiments, any or all of pathways **351**, **352**, **353**, and/or **354** may extend via an intervening pod structure (en route to processor pod **308**) without electrically coupling to any component thereof. [0199] In device **300**, successively adjacent pod structures are effectively daisy-chained together through communicative pathways **351**, **352**, **353**, and **354**. The illustrative diagram of FIG. **3** shows that communicative pathways **351**, **352**, **353**, and/or **354** in some or each of regions **321**, **322**, **323**, and **324** may be “staggered,” “shifted,” or “offset” such that a first input terminal **380** in each sensor pod is communicatively coupled to the corresponding sensor in that sensor pod and a first output terminal **380** in each sensor pod is communicatively coupled to a second input terminal **380** in an adjacent pod structure. For example, sensor pod **302** includes a first terminal **380** that is communicatively coupled to electric circuitry **332** to receive signals from sensor **312** and communicative pathway **352** includes: a first portion (extending through region **322**) that communicatively couples between first terminal **380** in sensor pod **302** and a second terminal **380** in sensor pod **301** and a second portion (extending through region **321**) that communicatively couples between second terminal **380** in sensor pod **301** and a third terminal **380** in processor pod **308**. The shifting/offsetting of communicative connections between terminals **380** may be achieved by/within the communicative pathways themselves (as depicted in FIG. **3**) by, for example, a corresponding routing of communicative pathways such as a corresponding layout of conductive traces in a flexible printed circuit board, or this shifting/offsetting may be achieved within each pod structure by, for example, corresponding communicative couplings between terminals **380**. For example, in FIG. **3**, each terminal **380** includes both an input and an output, though in alternative embodiments electrical and/or optical pathways may route signals between inputs and outputs of terminals **380**.

[0200] Device **300** includes additional communicative pathways **355** and **356** that provide serial communicative coupling of power and ground lines through sensor pods **301**, **302**, **303**, and **304** and processor pod **308**. For example, processor pod **308** includes a battery **390** that is used to

power wearable electronic device **300** and power is routed from processor pod **308** to sensor pods **301**, **302**, **303**, and **304** through communicative pathways **355** and **356**.

[0201] FIG. **3** shows exemplary device **300** that serially routes analog signals from four sensor pods **301**, **302**, **303**, and **304** to one processor pod **308**. Each analog signal is routed through a corresponding dedicated signal channel (i.e., a corresponding communicative pathway **351**, **352**, **353**, and **354**, respectively). For example, since sensor pod **301** routes amplified analog signals from each of sensor pods **301**, **302**, **303**, and **304** to processor pod **308**, at least four analog signal channels couple from sensor pod **301** to processor pod **308** through region **321**. As previously described, manufacturing of device **300** can be simplified by providing substantially the same coupling configuration between each pair of adjacent pod structures; therefore, the number of communicative pathways in each of regions **321**, **322**, **323**, and **324** is equal to the number of sensor pods **301**, **302**, **303**, and **304** (i.e., four) that are serially routed to processor pod **308**. For this reason, each of regions **321**, **322**, **323** and **324** may include four communicative pathways and each of sensor pods **301**, **302**, **303**, and **304** may include at least four terminals **380** for electrically coupling to/from corresponding ones of the four communicative pathways.

[0202] Routing of analog signals as exemplified by device **300** may be advantageous for some applications, but in accordance with the present systems, articles, and methods, other applications may benefit from routing digital signals instead of analog signals. Routing digital signals may be done using fewer signal channels than routing analog signals, and may provide improved robustness against noise and other forms of signal degradation.

[0203] FIG. **4** is an illustrative diagram of a portion of a wearable electronic device **400** showing exemplary routing of digital signals in accordance with the present systems, articles, and methods. Device **400** is substantially similar to device **300** from FIG. **3** (and therefore also similar to device **200** from FIG. **2** and device **100** from FIG. **1**) except that device **400** is designed to route digital signals between pod structures as opposed to analog signals. FIG. **4** only depicts a portion of device **400** that comprises four sensor pods **401**, **402**, **403**, and **404** and a processor pod **408**, all of which are serially coupled together to route digital signals from sensor pods **401**, **402**, **403**, and **404** to processor pod **408**.

[0204] Each of sensor pods **401**, **402**, **403**, and **404** comprises a respective sensor (e.g., a respective electromyography sensor) **411**, **412**, **413**, and **414** communicatively coupled to respective electric circuitry **431**, **432**, **433**, and **434**. In use, sensors **411**, **412**, **413**, and **414** detect inputs effected by a user and provide analog signals in response to the detected inputs. The analog signals provided by each of sensors **411**, **412**, **413**, and **414** are communicatively routed to electric circuitries **431**, **432**, **433**, and **434**, respectively. Each of electric circuitries **431**, **432**, **433**, and **434** includes a respective amplification circuit to, in use, amplify the analog signals. Furthermore, each of electric circuitries **431**, **432**, **433**, and **434** also includes a respective ADC circuit to, in use, convert the amplified analog signals into digital signals. The resulting digital signals are serially routed via successively adjacent ones of sensor pods **401**, **402**, **403**, and **404** to processor pod **408**. The digital signals are communicatively routed to a processor **440** within processor pod **408** that, in use, determines at least one output, action, or function based on the digital signals.

[0205] In device **400**, processor pod **408** also includes a sensor (e.g., an electromyography sensor) **418** to, in use, detect user-effected inputs and provide analog signals in response to the detected inputs. Sensor **418** is communicatively coupled to electric circuitry **438** in processor pod **408**, and electric circuitry **438** includes an amplification circuit to, in use, amplify the analog signals provided by sensor **418** and an ADC circuit to, in use, convert the amplified analog signals into digital signals. The digital signals are routed to processor **440** within processor pod **408**.

[0206] The portion of device **400** shown in FIG. **4** provides an illustrative example of routing digital signals from a set of sensor pods **401**, **402**, **403**, and **404** to a processor pod **408** within a wearable electronic device. In the illustrative example: sensor pod **404** outputs digital signals corresponding to signals provided by sensor **414** towards sensor pod **403** through a first portion of

a digital signal bus **451** extending through region **424** that physically separates sensor pod **404** and sensor pod **403**; sensor pod **403** receives digital signals from sensor pod **404** through the first portion of digital signal bus **451** and outputs both the digital signals received from sensor pod **404** and digital signals corresponding to signals provided by sensor **413** towards sensor pod **402** through a second portion of digital signal bus **451** extending through region **423** that physically separates sensor pod **403** and sensor pod **402**; sensor pod **402** receives digital signals from sensor pod **403** (corresponding to signals provided by sensor **414** and signals provided by sensor **413**) through the second portion of digital signal bus **451** and outputs both the digital signals received from sensor pod **403** and digital signals corresponding to signals provided by sensor **412** towards sensor pod **401** through a third portion of digital signal bus **451** extending through region **422** that physically separates sensor pod **402** and sensor pod **401**; sensor pod **401** receives digital signals from sensor pod **402** (corresponding to signals provided by sensors **414**, **413**, and **412**) through the third portion of digital signal bus **451** and outputs both the digital signals received from sensor pod **402** and digital signals corresponding to signals provided by sensor **411** towards processor pod **408** through a fourth portion of digital signal bus **451** extending through region **421** that physically separates sensor pod **401** and processor pod **408**. Processor pod **408** receives digital signals from sensor pod **401** (corresponding to signals provided by sensors **414**, **413**, **412**, and **411**) through the fourth portion of digital signal bus **451** and routes the digital signals to processor **440**.

[0207] In device **400**, a single digital signal bus **451** communicatively couples to and between each of sensor pods **401**, **402**, **403**, and **404** and processor pod **408**. Timing and sequencing of respective digital signals in digital signal bus **451** from each of sensor pods **401**, **402**, **403**, and **404** is controlled by a second communicative pathway that communicatively couples to and between each of sensor pods **401**, **402**, **403**, and **404** and processor pod **408**: a clock signal line **452**. In accordance with the present systems, articles, and methods, digital signals may be routed between pod structures in device **400** using digital signal bus **451** and clock signal line **452** to implement any of a variety of known digital bus protocols, including but not limited to: I2C®, SMBus®, UNI/OR, 1-Wire®, HyperTransport®, etc., and/or using modifications or adaptations thereof.

[0208] FIG. **4** shows exemplary device **400** that serially routes digital signals from four sensor pods **401**, **402**, **403**, and **404** to one processor pod **408**. Unlike the analog signals routed in device **300**, all of the digital signals may be transmitted through a single digital signal bus **451** and time-separated by clock pulses on a single clock line **452**. Thus, routing of digital signals between pod structures may not use a corresponding dedicated channel for each digital signal. In device **400**, each of regions **421**, **422**, **423**, and **424** includes two communicative pathways: a respective portion of digital signal bus **451** and a respective portion of clock signal line **452**, and each of sensor pods **401**, **402**, **403**, and **404** comprises a set of two terminals **480**. In accordance with the present systems articles, and methods, routing of digital signals between pod structures can be advantageous over routing of analog signals between pod structures because such allows fewer couplings between adjacent pod structures and because digital signals are inherently more robust against noise and signal degradation compared to analog signals.

[0209] A person of skill in the art will appreciate that the illustrative diagrams of FIGS. **3** and **4** show only some simplified electrical circuit and coupling (e.g., wiring) details and many electrical and coupling details are omitted. Any such simplifications and omissions are done solely for the purpose of enhancing clarity in conjunction with the corresponding descriptions in this specification. A person of skill in the art will appreciate that the simplification/omission of any component in any Figure is for the purpose of enhancing illustrative clarity only and in no way indicates the simplified/omitted component is somehow of lesser utility or value to the present systems, articles, and methods.

[0210] The present systems, articles, and methods describe routing signals between pod structures in a wearable electronic device comprising pod structures. FIGS. **1**, **2**, **3**, and **4** provide illustrative examples of systems and articles that achieve such routing by implementing, for example, the

method described in FIG. 5.

[0211] FIG. 5 is a flow-diagram showing a method **500** of routing signals within a wearable electronic device in accordance with the present systems, articles, and methods. The wearable electronic device may include a plurality of pod structures including at least two sensor pods and a processor pod. In other words, the wearable electronic device may be substantially similar to device **100** from FIG. 1, device **200** from FIG. 2, and either device **300** from FIG. 3 or device **400** from FIG. 4. Method **500** includes four acts **501**, **502**, **503**, and **504** and one optional act **510a/b**, though those of skill in the art will appreciate that in alternative embodiments certain acts may be omitted and/or additional acts may be added. Those of skill in the art will also appreciate that the illustrated order of the acts is shown for exemplary purposes only and may change in alternative embodiments.

[0212] At **501**, inputs effected by a user are detected by a sensor in at least one sensor pod of the wearable electronic device. The sensor may be an electromyography sensor and the inputs effected by the user may be muscle activity corresponding to a gesture performed by the user. The wearable electronic device may include a plurality of sensors distributed among a plurality of sensor pods and the user-effected inputs may be detected by at least one sensor (i.e., by one or more sensors) in at least one sensor pod (i.e., in one or more sensor pods).

[0213] At **502**, signals are provided by the at least one sensor in the at least one sensor pod in response to the user-effected inputs. The signals may be amplified by at least one amplification circuit and/or filtered by at least one filtering circuit. The signals provided by the at least one sensor may be, for example, electrical signals.

[0214] At **503**, the signals are serially routed via successive ones of adjacent pod structures in the wearable electronic device by respective communicative pathways until the signals are routed to the processor pod. The signals may be routed in, for example, electrical or optical form.

[0215] At **504**, the signals are processed by a processor in the processor pod.

[0216] As previously described, the signals generated by each sensor may be analog signals and the analog signals may be amplified by a respective amplification circuit within each sensor pod.

Method **500** also includes an optional act **510a/b** that may be performed either after (i.e., **510a**) or before (i.e., **510b**) the serial routing of act **503** depending on whether the wearable electronic device routes analog signals or digital signals (i.e., depending on whether the wearable electronic device is substantially similar to device **300** from FIG. 3 or device **400** from FIG. 4).

[0217] If the wearable electronic device is substantially similar to device **300** from FIG. 3, then the device routes analog signals between pod structures and the processor pod includes an ADC circuit. In this configuration, method **500** may include act **510a** after the serial routing of act **503**. At **503**, the analog signals are serially routed via successive ones of adjacent pod structures in the wearable electronic device by respective communicative pathways until the analog signals are routed to the processor pod. As described for device **300**, analog signal routing may employ a number of communicative pathways that is equal to the number of serially-linked sensor pods. At **510a**, the analog signals are converted to digital signals by the ADC circuit in the processor pod. At **504**, the digital signals are processed by the processor in the processor pod.

[0218] If the wearable electronic device is substantially similar to device **400** from FIG. 4, then each pod structure includes a respective ADC circuit and the device routes digital signals between pod structures. In this configuration, method **500** may include act **510b** before the serial routing of act **503**. At **502**, analog signals are provided by the at least one sensor in the at least one sensor pod in response to the user-effected inputs. At **510b**, the analog signals are converted into digital signals by the respective ADC circuits in each sensor pod. At **503**, the digital signals are serially routed via successive ones of adjacent pod structures in the wearable electronic device by respective communicative pathways until the digital signals are routed to the processor pod. As described for device **400**, digital signal routing may employ two communicative pathways: one digital signal bus and one clock signal line. Digital signal routing may also employ any of a variety of known digital

bus protocols, including but not limited to: I2CO3 SMBus®, UNI/O®, 1-Wire®, HyperTransport®, etc., and/or using modifications or adaptations thereof. At **504**, the digital signals are processed by the processor in the processor pod.

Description for Wearable Electronic Devices Having On-Board Sensors Including Contact Sensors [0219] The various embodiments described herein provide systems, articles, and methods for wearable electronic devices that employ biometric contact sensors. Different types of contact sensors are employed, including without limitation electromyography (“EMG”) sensors, single-frequency capacitive touch sensors, and/or swept frequency capacitive touch sensors. Swept frequency capacitive touch sensors are described in, for example, Sato et al.; however, in accordance with the present systems, articles, and methods, the concept of probing multiple electrical frequencies of a capacitive touch sensor may be generalized to implementations that do not actually sweep the electrical frequency over a continuous range, such as implementations that simply probe two or more discrete electrical signal frequencies. Probing multiple discrete signal frequencies without continuously sweeping in between can be advantageous in some applications because such simplifies the electric circuitry involved, simplifies the signal processing involved, and can also be designed to specifically target frequencies that are of particular relevance (e.g., for pattern recognition purposes) to a specific application. Throughout this specification and the appended claims, capacitive touch sensors that implement more than a single, fixed frequency are generally referred to as “multi-frequency capacitive touch sensors,” where swept frequency capacitive touch sensors are a subset of multi-frequency capacitive touch sensors, but any implementation of a capacitive touch sensor that is operative to probe multiple distinct electrical signal frequencies (e.g., “bi-frequency capacitive touch sensors” employing two frequencies, “tri-frequency capacitive touch sensors” employing three frequencies, and so on for any number of frequencies) constitutes a multi-frequency capacitive touch sensor herein.

[0220] Contact sensors may be incorporated into a dedicated device such as a wearable electronic armband, or they may be incorporated into a device that otherwise provides a different function, such as a wristwatch. For example, the functionality of any wristwatch may be enhanced by incorporating at least one contact sensor into the watchstrap and/or watch housing back-plate. In accordance with the present systems, articles, and methods, a generic watchstrap and/or watch housing back-plate design that includes at least one contact sensor may be adapted to fit to or be used in conjunction with any known wristwatch design, and incorporated into virtually any wristwatch during manufacturing thereof. Such “enhanced” watchstraps and/or back-plates can add capacitive sensing and/or other capabilities to “traditional” watch designs (i.e., non-smart watch designs) to effectively transform the traditional watch into a smart watch, and/or can add new sensing and/or other capabilities to smart watch designs.

[0221] In accordance with the present systems, articles, and methods, one or more EMG sensor(s) may be used to detect electrical activity produced by the muscles of a user when the user performs a physical gesture and to enable a wearable electronic device that includes the one or more EMG sensor(s) to transmit gesture-specific signals to a receiving device as part of a human-electronics interface. One or more capacitive touch sensor(s) (such as one or more single-frequency capacitive touch sensor(s) and/or one or more multi-frequency capacitive touch sensor(s)) may be used to detect physical contact between a user and an object (i.e., when and/or how a user physically touches an object), to provide signals in response to the detected physical contact, and to enable a wearable electronic device that includes the one or more capacitive touch sensor(s) to transmit touch-specific signals to a receiving device as part of a human-electronics interface.

[0222] FIG. **6** is a perspective view of an exemplary wristwatch **600** that includes an enhanced watchstrap **601** in accordance with the present systems, articles, and methods. Enhanced watchstrap **601** enwraps the wrist of a user to secure wristwatch **600** in position on the user's wrist, in much the same way as any generic watchstrap. Enhanced watchstrap **601** may be elastic, fabric, cloth, leather, formed of serially-coupled links, or any other flexible material and may or may not include

a latch, clasp, or other fastening device (not shown in FIG. 6). Wristwatch **600** also includes a housing **610** having a top surface **611** and a back-plate **612**. Back-plate **612** may be a simple rigid surface with no further functionality or back-plate **612** may be an enhanced back-plate as described in U.S. patent application Ser. No. 15/882,858 and U.S. patent application Ser. No. 14/505,836, each of which is incorporated herein by reference above.

[0223] The top surface **611** of housing **610** includes a window or display that may provide a means of conveying information to a user (such as the time, etc.) and/or an interface through which the user may program and/or control functions of wristwatch **600**. For example, wristwatch **600** may be a traditional analog or mechanical watch, in which case the display of the top surface **611** of housing **610** may include a simple sheet of transparent material such as glass or plastic (commonly referred to as the “crystal”) forming a window through which the hands of an analog watch face may be seen by the user, or wristwatch **600** may be a traditional digital watch, in which case the display of the top surface **611** of housing **610** may include a digital display screen, or wristwatch **600** may be a smart watch, in which case the display of the top surface **611** of housing **610** may include a touchscreen. Housing **610** may include an inner cavity that contains a timekeeping device, including without limitation: one or more gear(s), one or more clockwork(s), one or more quartz oscillator(s), and/or any other component or device known in the art of timekeeping. In some implementations, the cavity may include circuitry (e.g., electrical and/or electronic circuitry). Wristwatch **600** may be substantially similar to any known wristwatch except that wristwatch **600** includes enhanced watchstrap **101** providing additional functions and/or capabilities in accordance with the present systems, articles, and methods.

[0224] Exemplary enhanced watchstrap **601** includes on-board devices **621**, **622**, and **630**. In principle, the enhanced watchstraps of the present systems, articles, and methods may include any number of devices. Exemplary devices **621** and **622** are contact sensors or transducers (hereafter “contact sensors”) that may be used to detect, measure, monitor, or otherwise sense one or more activity (ies), parameter(s), characteristic(s), and/or other aspect(s) of the user of (i.e., the wearer of) wristwatch **600**. Two contact sensors **621** and **622** are illustrated in FIG. 6 for exemplary purposes only. In practice, any number (e.g., one, two, three, or more than three) of contact sensors may be included in watchstrap **601**.

[0225] Contact sensors **621**, **622** may include any type or types of contact sensors, including without limitation one or more EMG sensor(s), one or more single-frequency capacitive touch sensor(s), and/or one or more multi-frequency capacitive touch sensor(s), one or more magnetomyography sensor(s), one or more acoustic myography sensor(s), one or more mechanomyography sensor(s), one or more electrocardiogram sensor(s), one or more blood pressure sensor(s), one or more thermometer(s), and/or one or more skin conductance sensor(s). Contact sensors **621**, **622** may include any type or types of biometric sensor(s) that are responsive to signals detected through physical contact with the user's skin. Enhanced watchstrap **601** may, if desired, also include one or more other form(s) of sensor(s), such as one or more pedometer(s), one or more inertial sensor(s) such as one or more accelerometer(s) and/or one or more gyroscope(s), one or more compass(es), one or more location sensor(s) such as one or more Global Positioning System (GPS) unit(s), one or more altimeter(s), and so on.

[0226] Exemplary device **630** is circuitry (e.g., electrical and/or electronic circuitry) that is communicatively coupled to contact sensors **621**, **622** and may include a wide variety of components depending on the specific implementation. In exemplary wristwatch **600**, circuitry **630** includes an amplification circuit to amplify signals provided by contact sensors **621** and **622**, a filtering circuit to filter signals provided by contact sensors **621** and **622**, an analog-to-digital converter to convert analog signals provided by contact sensors **621** and **622** into digital signals, a digital processor to process the signals provided by contact sensors **621** and **122**, and a non-transitory processor-readable storage medium or memory to store processor-executable instructions that, when executed by the digital processor in circuitry **630**, cause the digital processor in circuitry

130 to process the signals provided by contact sensors **621** and **622**. In other implementations, the circuitry of an enhanced watchstrap in accordance with the present systems, articles, and methods may include other components in addition to or instead of the components included in circuitry **630** of enhanced watchstrap **601**, including without limitation: one or more battery (ies), one or more inductive charging elements, and/or one or more communication terminal(s) such as one or more wireless transmitter(s) and/or receiver(s) (either separately or combined as a wireless transceiver) employing a wireless communication protocol such as Bluetooth®, WiFi™, and/or NFC™, one or more tethered connector port(s) (e.g., one or more Universal Serial Bus (USB) port(s), one or more mini-USB port(s), one or more micro-USB port(s), and/or one or more Thunderbolt® port(s)), and/or any other form or forms of communication terminal(s), such as without limitation: one or more socket(s), one or more bonding pad(s), one or more set(s) of pins, and the like.

[0227] Any or all of on-board devices **621**, **622**, and/or **630** may be carried, in whole or in part, on a first surface (i.e., a “contact surface” that is in contact with a user's skin when wristwatch **600** is worn directly on a wrist of the user) of enhanced watchstrap **601**. While the electrodes of contact sensors **621** and **621** generally need to contact the user's skin when enhanced watchstrap **601** is worn, further portions of sensors **621**, **622** and/or device **630** (in whole or in part), may be carried on a second surface (i.e., a “non-contact surface” that is not in contact with the user's skin when wristwatch **600** is worn directly on the wrist of the user) of enhanced watchstrap **601** and/or carried within enhanced watchstrap **601**.

[0228] Throughout this specification and the appended claims, the term “inductive charging element” is used to refer to a component of an inductive charging system that is designed to receive power transfer via inductive coupling. A person of skill in the art will appreciate that an inductive charging element may include a coil of conductive wire that receives power transfer when positioned proximate an alternating magnetic field.

[0229] Throughout this specification and the appended claims, the term “communication terminal” is generally used to refer to any physical structure that provides a communications link through which a data signal may enter and/or leave a device (or a component of a device, such as enhanced watchstrap **601**). A communication terminal represents the end (or “terminus”) of communicative signal transfer within a device (or a component of a device) and the beginning of communicative signal transfer with an external device (or a separate component of the device). In the case of a communication terminal in circuitry **630**, the term “terminal” means that the communication terminal in circuitry **630** represents the end of communicative signal transfer within/on enhanced watchstrap **601** and the beginning of communicative signal transfer with other components of wristwatch **600** and/or with one or more device(s) separate from wristwatch **600** (e.g., one or more smartphone(s), one or more desktop, laptop, or tablet computer(s), etc.).

[0230] FIG. 7A is a plan view showing a contact surface **710a** of an exemplary enhanced watchstrap **700** in accordance with the present systems, articles, and methods. Watchstrap **700** may be designed and/or adapted to fit or otherwise mate with any wristwatch (e.g., any mechanical, digital, analog, or smart watch housing, not shown in FIG. 7A) in a substantially similar way to that described for enhanced strap **101** of wristwatch **700** from FIG. 1. As FIG. 7A depicts the contact surface **710a** of watchstrap **700** (i.e., the surface of strap **700** that contacts the user when strap **700** is worn), the bottom surface of watchstrap **700** is not visible in FIG. 7A; however, some features and devices that are included on the bottom surface of watchstrap **700** and within watchstrap **700** are illustrated in FIG. 7A for discussion purposes but shown in broken, dashed lines in FIG. 7A to indicate that such features and devices may not actually be visible in the plan view of FIG. 7A.

[0231] In accordance with the present systems, articles, and methods, a watchstrap for integration with a wristwatch may include at least one contact sensor, and thereby provide enhanced functionality/capability for the wristwatch. Enhanced watchstrap **700** includes contact sensors **721** and **722**. Contact sensors **721** and **722** may include, for example, electromyography sensors such as those described in U.S. patent application Ser. No. 14/194,252, U.S. patent application Ser. No.

16/550,905, U.S. Pat. Nos. 10,429,928, 10,101,809, 10,042,422, U.S. patent application Ser. No. 17/141,646, U.S. Pat. Nos. 10,898,101, 10,251,577, and/or 10,188,309, each of which is incorporated by reference above. Either instead of or in addition to EMG sensors, contact sensors **721**, **722** may include any type or types of biometric sensor(s) that are responsive to signals detected through physical contact with the user's skin, for example, single-frequency capacitive touch sensors, multi-frequency capacitive touch sensors, magnetomyography sensor(s), and so on (i.e., as described for watchstrap **101** in FIG. **6**). In any case, at least an electrode portion of at least one contact sensor **721**, **722** is positioned on the contact surface **710a** of watchstrap **700** so that the at least one contact sensor **721**, **722** may be positioned proximate (e.g., in physical contact with) the skin of the user.

[0232] Watchstrap **700** may be sized and dimensioned to mate (e.g., via at least one latch, pin, clasp, connector, or the like) with any wristwatch design to provide a strap or band therefor. The enhanced watchstraps described in the present systems, articles, and methods may comprise a single-piece of material (e.g., elastic material, flexible material, stretchable material, etc.) or multiple segments, links, or sections of material (e.g., rigid or semi-rigid material) adaptively coupled together by at least one adaptive coupler. For ease of illustration, watchstrap **700** in FIG. **7A** is formed of a single-piece of flexible material such as fabric, cloth, leather, or similar.

Watchstrap **700** may be substantially planar when laid out flat but may generally be curved in use. [0233] The term “adaptive coupler” is used throughout this specification and the appended claims to denote a system, article or device that provides flexible, adjustable, modifiable, extendable, extensible, or otherwise “adaptive” physical coupling. Adaptive coupling is physical coupling between two objects that permits limited motion of the two objects relative to one another. An example of an adaptive coupler is an elastic material such as an elastic band.

[0234] The plan view of FIG. **7A** depicts the contact surface **710a** of watchstrap **700** which carries contact sensors **721** and **722**. Additional components (i.e., components **731**, **732**, **734**, and **735** illustrated with wide-dashed lines in FIG. **7A**) of watchstrap **700** are carried on a non-contact surface thereof (i.e., the surface of watchstrap **700** that is furthest from and does not contact the skin of the user when worn), and still further components (i.e., components **733** and **736** illustrated with dotted lines in FIG. **7A**) of watchstrap **700** are carried in an inner volume thereof. Watchstrap **700** includes communication pathways **740** (only one called out in FIG. **7A** to reduce clutter) that couple to and between various components of watchstrap **700** to provide communicative coupling therebetween. Portions of communication pathways **740** may be carried on the contact surface **710a**, the non-contact surface, and/or in the inner volume of watchstrap **700**. In some embodiments, additional components may be carried on the sides or edges of watchstrap **700**.

[0235] Throughout this specification and the appended claims the term “communicative” as in “communicative pathway,” “communicative coupling,” and in variants such as “communicatively coupled,” is generally used to refer to any engineered arrangement for transferring and/or exchanging information. Exemplary communicative pathways include, but are not limited to, electrically conductive pathways (e.g., electrically conductive wires, electrically conductive traces), magnetic pathways (e.g., magnetic media), and/or optical pathways (e.g., optical fiber), and exemplary communicative couplings include, but are not limited to, electrical couplings, magnetic couplings, and/or optical couplings. Furthermore, the term “communicatively coupled” is generally used throughout this specification and the appended claims to include direct, 1:1 communicative coupling and indirect or “mediated” communicative coupling. For example, a component A may be communicatively coupled to a component B directly by at least one communication pathway, or a component A may be communicatively coupled to a component B indirectly by at least a first communication pathway that directly couples component A to a component C and at least a second communication pathway that directly couples component C to component B. In this case, component C is said to mediate the communicative coupling between component A and component B.

[0236] To clarify the spatial arrangement of the components **721**, **722**, **731**, **732**, **733**, **734**, **735**, **736**, and **740** of watchstrap **700** illustrated in the plan view of FIG. 7A, FIG. 7B provides a side elevational view of the same exemplary watchstrap configuration.

[0237] FIG. 7B is a side elevational view of exemplary enhanced watchstrap **700** from FIG. 7A showing the relative positions of components on the surfaces and in the inner volume thereof, in accordance with the present systems, articles, and methods. In the side elevational view of FIG. 7B, both contact surface **710a** and non-contact surface **710b** of watchstrap **700** are visible. Contact surface **710a** carries contact sensors **721** and **722** while non-contact surface **710b** carries components **731**, **732**, **734**, and **735**. The inner volume of watchstrap **700** carries components **733** and **736**, which are illustrated in dotted lines in FIG. 7B to indicate that they might not be visible in the view of FIG. 7B.

[0238] Watchstrap **700** provides an illustrative example of an enhanced watchstrap in accordance with the present systems, articles, and methods. In alternative implementations, more or fewer components (including all or no components) may be carried on the contact surface, on the non-contact surface, and/or in the inner volume of an enhanced watchstrap.

[0239] With reference to both FIGS. 2A and 2B, watchstrap **700** includes contact sensors **721**, **722** that are communicatively coupled by at least one communication pathway **740** to circuitry **733**. Circuitry **733** includes at least one of an amplification circuit, a filtering circuit, and/or an analog-to-digital conversion circuit, and is communicatively coupled by at least one communication pathway **740** to an on-board processor **731**. Processor **731** is communicatively coupled to a non-transitory processor-readable storage medium or memory **732**. Memory **732** stores processor-executable contact sensing instructions that, when executed by processor **731**, cause processor **731** to process signals provided by contact sensors **721** and **722**. For example, processor-executable contact sensing instructions may, when executed by processor **731**, cause processor **731** to perform gesture identification based on EMG sensor signals as described in U.S. patent application Ser. No. 14/494,274 and/or U.S. Provisional Patent Application Ser. No. 61/894,263 (each of which is incorporated by reference herein in its entirety) and/or for processing single-frequency and/or multi-frequency capacitive touch sensor signals. Processor **731** is also communicatively coupled (by respective communication pathways **740**) to first and second communication terminals **735** and **736**. Communication terminal **735** is a wireless communication terminal (e.g., a Bluetooth® transmitter and/or receiver) that enables information from processor **731** to be sent wirelessly to any receiving device, such as a smartphone, computer, etc. Communication terminal **736** is a wired communication terminal that may, for example, provide a direct communicative coupling point between watchstrap **700** and a housing (e.g., housing **110** from FIG. 6) of a wristwatch, where the housing includes a clock face and other watch/smartwatch elements.

[0240] Watchstrap **700** also includes at least one power source **734** that is communicatively coupled to all components of watchstrap **700** that require power. Power source **734** may include at least one battery and/or at least one inductive charging element.

[0241] Communication pathways **740** may be implemented in a variety of forms. For example, communication pathways **740** may include electrical wires and/or conductive traces. In the latter case, at least one flexible printed circuit board may be carried on at least one surface **710a**, **710b** of watchstrap **700** and/or in an inner volume of watchstrap **700** and conductive traces **740** may be carried on and/or in the at least one flexible printed circuit board. Stretchable printed circuit boards may be employed, such as those described in U.S. patent application Ser. No. 14/471,982, which is incorporated by reference herein in its entirety. Elastic conductors may be employed. In some implementations, watchstrap **700** may essentially comprise a flexible printed circuit board that is formed of bio-compatible material. In implementations in which an enhanced watchstrap is formed of a set of rigid or semi-rigid links that are adaptively coupled together by at least one adaptive coupler, at least one rigid or semi-rigid link may comprise and/or include at least one rigid printed circuit board that carries communication pathways.

[0242] A person of skill in the art will appreciate that watchstrap **700** includes one type of contact sensor **721**, **722** and six components **731**, **732**, **733**, **734**, **735**, and **736**, though in practice an enhanced watchstrap may carry any number of components (including more or fewer than six components) and any number or type of sensors depending on the functionality provided by the watchstrap.

[0243] Enhanced watchstrap **700** may be integrated into any known wristwatch design by substituting for the existing strap or band in the design and, optionally, communicatively coupling to circuitry in the existing design (if such circuitry exists) through communication terminal **736**.

[0244] Throughout this specification and the appended claims, the term “rigid” as in, for example, “substantially rigid material,” is used to describe a material that has an inherent tendency to maintain its shape and resist malformation/deformation under the moderate stresses and strains typically encountered by a wearable electronic device.

[0245] The various embodiments of enhanced watchstraps described herein are generic in that they can be adapted to integrate with any known wristwatch design (including traditional watches and smart watches) by, for example, sizing and dimensioning the watchstrap to mate with existing wristwatch components (such as the housing or clock face display) and, optionally, communicatively coupling the electrical components of the watchstrap to existing electrical components of the wristwatch (if such circuitry exists) through a dedicated communication terminal (e.g., terminal **736**). In this way, the enhanced straps described herein introduce new components and associated functionality/capability into existing wristwatch designs, thereby transforming virtually any traditional wristwatch design into a smart watch and/or enhancing the functions and capabilities of virtually any smart watch design. In implementations in which an enhanced watchstrap is not communicatively coupled to electrical components of a wristwatch (i.e., in implementations in which communication terminal **736** is not used), the enhanced watchstraps described herein may still communicate with other devices (such as a smartphone, computer, etc.) wirelessly (e.g., using communication terminal **735**) and thereby provide enhanced, smart watch-like functionality in an otherwise non-smart watch design.

[0246] The present systems, articles, and methods may employ the systems, articles, and methods for processing EMG sensor data described in U.S. patent application Ser. No. 14/186,889, U.S. patent application Ser. No. 14/465,194, and/or U.S. Pat. No. 9,372,535, each of which is incorporated by reference herein in its entirety. In the case of contact sensors that are not EMG sensors (e.g., single-frequency capacitive touch sensors and/or multi-frequency capacitive touch sensors), the systems, articles, and methods of U.S. patent application Ser. No. 14/186,889, U.S. patent application Ser. No. 14/465,194, and/or U.S. Pat. No. 9,372,535 may be readily adapted to accommodate non-EMG based contact sensor data.

[0247] As previously described, contact sensors and associated circuitry may be on-board or otherwise packaged with a watch housing back-plate, either on its own or in conjunction with contact sensors packaged with a watchstrap as described in FIGS. **1**, **2A**, and **2B**. For example, the various embodiments described herein provide systems, articles, and methods for generic wristwatch back-plates that may be adapted to fit to any known wristwatch design and incorporated into virtually any wristwatch during manufacturing thereof. The back-plates described herein incorporate various types of contact sensors and thereby enhance the functions and/or capabilities of the wristwatch with which they are integrated. In this way, the back-plates described herein can add sensing and/or other capabilities to “traditional” watch designs (i.e., non-smart watch designs) to effectively transform the traditional watch into a smart watch, and/or the back-plates described herein can add new sensing and/or other capabilities to smart watch designs.

[0248] FIG. **8** is a perspective view of an exemplary wristwatch **800** that includes an enhanced back-plate **812** in accordance with the present systems, articles, and methods. Wristwatch **800** includes a wristband **801** that enwraps the wrist of a user to secure wristwatch **800** in position on the user's wrist. Wristband **801** may be elastic, fabric, cloth, leather, or formed of serially-coupled

links or any other flexible material and may or may not include a latch, clasp, or other fastening device (not shown in FIG. 8). Wristband **801** may be a traditional watchstrap or an enhanced watchstrap such as watchstrap **101** from FIG. 6, watchstrap **700** from FIGS. 2A and 2B, and/or an enhanced watchstrap as described in U.S. patent application Ser. No. 15/882,858 and U.S. patent application Ser. No. 14/505,836, which are incorporated by reference herein in its entirety. Wristwatch **800** also includes a housing **810** having a top surface **811** and an enhanced back-plate **812** in accordance with the present systems, articles, and methods. Top surface **811** includes a window or display that may provide a means of conveying information to a user (such as the time, etc.) and/or an interface through which the user may program and/or control functions of wristwatch **800**. For example, wristwatch **800** may be a traditional analog or mechanical watch, in which case the display of top surface **811** may include a simple sheet of transparent material such as glass or plastic (commonly referred to as the “crystal”) forming a window through which the hands of an analog watch face may be seen by the user, or wristwatch **800** may be a traditional digital watch, in which case the display of top surface **811** may include a digital display screen, or wristwatch **800** may be a smart watch, in which case the display of top surface **811** may include a touchscreen. Wristwatch **800** may be substantially similar to any known wristwatch except that wristwatch **800** includes enhanced back-plate **812** providing additional functions and/or capabilities in accordance with the present systems, articles, and methods.

[0249] FIG. 9 is a plan view showing an underside of a wristwatch **900** and thereby providing a clearer view (compared to the perspective view of FIG. 8) of a back-plate **912** that is enhanced in accordance with the present systems, articles, and methods. Wristwatch **900** is substantially similar to wristwatch **800** from FIG. 8 and includes a wristband **901** (similar to wristband **801** from FIG. 8) and a housing **910** (similar to housing **810** from FIG. 8). As FIG. 9 depicts the underside of housing **910**, the top surface of housing **910** is not visible in FIG. 9. The top surface of housing **910** may include a window or display, (e.g., an electronic display screen with or without a touchscreen) as seen in virtually all known wristwatch designs.

[0250] In accordance with the present systems, articles, and methods, a back-plate for integration with a wristwatch may include at least one contact sensor, and thereby provide enhanced functionality/capability for the wristwatch. Enhanced back-plate **912** includes contact sensors **921** and **922**. Contact sensors **921** and **922** may include, for example, EMG sensors, single-frequency capacitive touch sensors, multi-frequency capacitive touch sensors, magnetomyography sensors, acoustic myography sensors, electrocardiogram sensors, blood pressure sensors, one or more skin conductance sensor(s), and/or generally any type or types of biometric sensor(s) that are responsive to signals detected through physical contact with the user's skin. In any case, at least one contact sensor (**921**, **922**) is positioned on a first surface of back-plate **912** (i.e., the surface of back-plate **912** that corresponds to the underside of housing **910** in wristwatch **900**, hereafter the “contact surface”) so that the at least one contact sensor (**921**, **922**) may be positioned proximate (e.g., in physical contact with) the skin of the user.

[0251] Back-plate **912** may be sized and dimensioned to mate with any wristwatch design to provide a back-plate therefor and/or an underside thereof. For example, back-plate **912** is illustrated in FIG. 9 as having a substantially square geometry with rounded corners, while in other implementations back-plate **912** may be adapted to provide other geometries, including but not limited to: substantially square, substantially rectangular, substantially circular, and substantially polygonal. Back-plate **912** may be substantially planar (i.e., flat) or, as illustrated in wristwatch **800** of FIG. 8, back-plate **912** may be curved to better accommodate the shape of a user's wrist. In the case of back-plate **912** being curved, a two-dimensional projection of the geometry of back-plate **912** (as seen, for example, in the plan view of FIG. 9) may be any shape designed to accommodate the specifications of a particular wristwatch, including but not limited to: substantially square, substantially rectangular, substantially circular, and substantially polygonal.

[0252] The plan view of FIG. 9 depicts the underside of housing **910** in order to show the contact

surface of back-plate **912** which carries contact sensors **921** and **922**. Back-plate **912** mates with a top surface of housing **910** (either directly, or by mating with at least one sidewall that provides physical coupling between back-plate **912** and a top surface of housing **910**) to form a volume having a hollow inner cavity. Additional components of wristwatch **900** (such as, for example, gears, circuitry, a quartz oscillator, a digital processor, and so on) may be included in this inner cavity. In some embodiments, additional components may be carried on a second surface of back-plate **912** that is opposite the first surface (i.e., a “non-contact surface” of back-plate **912** that is at least partially contained within the cavity and does not physically contact the user's skin when worn), such that the additional components carried on the non-contact surface of back-plate **912** are contained in the cavity of housing **910**.

[0253] FIG. **10** is a perspective view of a back-plate **1000** for integration into a wristwatch in accordance with the present systems, articles, and methods. Back-plate **1000** comprises a plate of substantially rigid material having a first surface (i.e., a “contact surface”) **1001** and a second surface (i.e., a “non-contact surface”) **1002** opposite the contact surface. The contact surface **1001** forms the underside of a housing (e.g., housing **810** from FIG. **8** or **910** from FIG. **9**) when integrated into a wristwatch and may be immediately proximate (e.g., in physical contact with) the user's skin during use. In accordance with the present systems, articles, and methods, contact surface **1001** includes at least one contact sensor **1020** (or at least, an electrode thereof), shown in dotted lines in FIG. **10** to indicate that this component is not actually visible in the view of FIG. **10**. The non-contact surface **1002** of back-plate **1000** carries multiple components **1031**, **1032**, **1033**, and **1034**, which may take on a variety of different forms depending on the specific implementation. In general, component **1031** represents circuitry (e.g., electrical and/or electronic). Circuitry **1031** is communicatively coupled to contact sensor **1020** by, e.g., an electrically conductive path that extends through back-plate **1000**. Circuitry **1031** may include various circuits, including but not limited to: filtering circuits, amplification circuits, analog-to-digital conversion circuits, routing circuits, and so on. Components **1032**, **1033** and **1034** may each include any or all of, for example: a pedometer, an inertial sensor such as an accelerometer and/or a gyroscope, a compass, a GPS unit, a wireless transmitter (on its own or as part of a wireless transceiver) such as Bluetooth™, WiFi™, and/or NFC™, a tethered connector port such as USB, micro-USB, pins or sockets, a battery, a digital processor, and/or an inductive charging element. In applications where one of components **1032**, **1033**, and **1034** is a wireless transmitter, data may be transmitted from back-plate **1000** (e.g., data provided by contact sensor **1020**) to any receiving device, such as to a smartphone, laptop computer, tablet computer, or desktop computer. At least one of components **1032** and/or **1033** may include a non-transitory processor-readable storage medium that stores processor-executable contact sensing instructions that, when executed by a processor (e.g., either a processor on-board back-plate **1000**, for example, component **1033**, or a processor in a smart watch with which back-plate **1000** is integrated through, for example, a tethered connector port), cause the processor to process signals provided by contact sensor **1020**.

[0254] Components **1031**, **1032**, **1033**, and **1034** may include at least one of a tethered connector port for communicatively coupling to at least one electrical or electronic component of a wristwatch (e.g., at least one port for galvanically electrically coupling to one or components of the wristwatch with which back-plate **1000** is integrated (i.e., components not carried by back-plate **1000**)) and/or a wireless transmitter (e.g., wireless transceiver) for transmitting data provided by the at least one contact sensor **1020** to at least one receiving device, such as a smartphone or other computer. In either case, at least one of components **1031**, **1032**, **1033**, and **1034** provides a means through which data provided by the at least one contact sensor **1020** is transmitted to a data processing system (either on-board or separate from back-plate **1000** or the wristwatch with which back-plate **1000** is integrated) for processing, analysis, and/or storage. In the case of components **1031**, **1032**, **1033**, and **1034** including a wireless transmitter and no tethered connector port for galvanically interfacing with one or more other components of the wristwatch with which back-

plate **1000** is integrated, back-plate **1000** and all components thereof (i.e., contact sensor **1020** and components **1031**, **1032**, **1033**, and **1034**) may be communicatively isolated from all components of the wristwatch with which back-plate **1000** is integrated.

[0255] A person of skill in the art will appreciate that FIG. **10** shows four components **1031**, **1032**, **1033**, and **1034** on the second “non-contact” surface **1002** of back-plate **1000**, though in practice a back-plate may carry any number of components (including more or fewer than four components) depending on the functionality provided by the back-plate.

[0256] As back-plate **1000** is designed to be integrated into a wristwatch (e.g., as a component of the wristwatch integrated into the wristwatch during manufacturing thereof), the non-contact surface **1002** of back-plate **1000** may include a communication terminal **1034** (such as a tethered connector port) to communicatively couple with other electrical and/or electronic circuitry of the wristwatch. For example, communication terminal **1034** may communicatively couple with an electronic display screen (e.g., a touchscreen) of the wristwatch and/or communication terminal **1034** may communicatively couple with any electrical component contained within the cavity of the housing of the wristwatch. Communication terminal **1034** may include any type of electrical or optical connector, including but not limited to a zero insertion force connector, a socket, a set of pins or bonding pads, a micro-USB connector, and so on. Thus, back-plate **1000** may be integrated into any known wristwatch design by substituting for the existing back-plate in the design and, optionally, communicatively coupling to circuitry in the existing design (if such circuitry does exist) through communication terminal **1034**.

[0257] The various embodiments of wristwatch back-plates described herein are generic in that they can be adapted to integrate with any known wristwatch design by, for example, sizing and dimensioning the plate to mate with existing wristwatch components (such as the display window or screen with/without associated sidewalls) and, optionally, communicatively coupling the electrical components of the back-plate to existing electrical components of the wristwatch (if such electrical components exist) through a dedicated communication terminal (e.g., terminal **1034**). In this way, the enhanced back-plates described herein introduce new components and associated functionality/capability into existing wristwatch designs, thereby transforming virtually any traditional wristwatch design into a smart watch and/or enhancing the functions and capabilities of virtually any smart watch design.

[0258] As previously described, in accordance with the present systems, articles, and methods at least one contact sensor may be incorporated into a wearable device that otherwise provides some other functionality (such as a wristwatch) or into a dedicated wearable electronic device that is specifically designed to provide contact sensing functionality. For example, a wearable electronic device may be fitted with multiple EMG sensors that are responsive to muscle activity for the purpose of enabling gesture-based control in a human-electronics interface as described in U.S. Pat. No. 10,528,135, U.S. patent application Ser. No. 14/335,668, and/or U.S. Pat. No. 10,152,082, each of which is incorporated by reference herein in its entirety, and/or in any of the other US Provisional Patent Applications incorporated by reference herein. In accordance with the present systems, articles, and methods, such a wearable EMG device may be adapted to include at least one capacitive touch sensor, such as at least one single-frequency capacitive touch sensor and/or at least one multi-frequency capacitive touch sensor.

[0259] FIG. **11** is a perspective view of an exemplary wearable EMG device **1100** that includes two contact sensor types: a set of capacitive EMG sensors **1110** (only two called out to reduce clutter) and at least one capacitive touch sensor **1170** in accordance with the present systems, articles, and methods. Exemplary wearable EMG device **1100** may, for example, form part of a human-electronics interface. Exemplary wearable EMG device **1100** is an armband designed to be worn on the forearm of a user, though a person of skill in the art will appreciate that the teachings described herein may readily be applied in wearable EMG devices designed to be worn elsewhere on the body of the user, including without limitation: on the upper arm, wrist, hand, finger, leg, foot, torso,

or neck of the user.

[0260] Device **1100** includes a set of eight pod structures **1101**, **1102**, **1103**, **1104**, **1105**, **1106**, **1107**, and **1108** that form physically coupled links of the wearable EMG device **1100**. Each pod structure in the set of eight pod structures **1101**, **1102**, **1103**, **1104**, **1105**, **1106**, **1107**, and **1108** is positioned adjacent and in between two other pod structures in the set of eight pod structures such that the set of pod structures forms a perimeter of an annular or closed loop configuration. For example, pod structure **1101** is positioned adjacent and in between pod structures **1102** and **1108** at least approximately on a perimeter of the annular or closed loop configuration of pod structures, pod structure **1102** is positioned adjacent and in between pod structures **1101** and **1103** at least approximately on the perimeter of the annular or closed loop configuration, pod structure **1103** is positioned adjacent and in between pod structures **1102** and **1104** at least approximately on the perimeter of the annular or closed loop configuration, and so on. Each of pod structures **1101**, **1102**, **1103**, **1104**, **1105**, **1106**, **1107**, and **1108** is physically coupled to the two adjacent pod structures by at least one adaptive coupler (not visible in FIG. **11**). For example, pod structure **1101** is physically coupled to pod structure **1108** by an adaptive coupler and to pod structure **1102** by an adaptive coupler. As described previously, the term “adaptive coupler” is used throughout this specification and the appended claims to denote a system, article or device that provides flexible, adjustable, modifiable, extendable, extensible, or otherwise “adaptive” physical coupling. Adaptive coupling is physical coupling between two objects that permits limited motion of the two objects relative to one another. An example of an adaptive coupler is an elastic material such as an elastic band. Thus, each of pod structures **1101**, **1102**, **1103**, **1104**, **1105**, **1106**, **1107**, and **1108** in the set of eight pod structures may be adaptively physically coupled to the two adjacent pod structures by at least one elastic band. The set of eight pod structures may be physically bound in the annular or closed loop configuration by a single elastic band that couples over or through all pod structures or by multiple separate elastic bands that couple between adjacent pairs of pod structures or between groups of adjacent pairs of pod structures. Device **1100** is depicted in FIG. **11** with the at least one adaptive coupler completely retracted and contained within the eight pod structures **1101**, **1102**, **1103**, **1104**, **1105**, **1106**, **1107**, and **1108** (and therefore the at least one adaptive coupler is not visible in FIG. **11**).

[0261] Throughout this specification and the appended claims, the term “pod structure” is used to refer to an individual link, segment, pod, section, structure, component, etc. of a wearable EMG device. For the purposes of the present systems, articles, and methods, an “individual link, segment, pod, section, structure, component, etc.” (i.e., a “pod structure”) of a wearable EMG device is characterized by its ability to be moved or displaced relative to another link, segment, pod, section, structure component, etc. of the wearable EMG device. For example, pod structures **1101** and **1102** of device **1100** can each be moved or displaced relative to one another within the constraints imposed by the adaptive coupler providing adaptive physical coupling therebetween. The desire for pod structures **1101** and **1102** to be movable/displaceable relative to one another specifically arises because device **1100** is a wearable EMG device that advantageously accommodates the movements of a user and/or different user forms.

[0262] Device **1100** includes eight pod structures **1101**, **1102**, **1103**, **1104**, **1105**, **1106**, **1107**, and **1108** that form physically coupled links thereof. Wearable EMG devices employing pod structures (e.g., device **1100**) are used herein as exemplary wearable EMG device designs, while the present systems, articles, and methods may be applied to wearable EMG devices that do not employ pod structures (or that employ any number of pod structures). Thus, throughout this specification, descriptions relating to pod structures (e.g., functions and/or components of pod structures) should be interpreted as being applicable to any wearable EMG device design, even wearable EMG device designs that do not employ pod structures (except in cases where a pod structure is specifically recited in a claim).

[0263] In exemplary device **1100** of FIG. **11**, each of pod structures **1101**, **1102**, **1103**, **1104**, **1105**,

1106, 1107, and 1108 comprises a respective housing having a respective inner volume. Each housing may be formed of substantially rigid material and may be optically opaque. As previously described, throughout this specification and the appended claims, the term “rigid” as in, for example, “substantially rigid material,” is used to describe a material that has an inherent tendency to maintain or restore its shape and resist malformation/deformation under the moderate stresses and strains typically encountered by a wearable electronic device.

[0264] Details of the components contained within the housings (i.e., within the inner volumes of the housings) of pod structures **1101, 1102, 1103, 1104, 1105, 1106, 1107, and 1108** are not visible in FIG. **11**. To facilitate descriptions of exemplary device **1100**, some internal components are depicted by dashed lines in FIG. **11** to indicate that these components are contained in the inner volume(s) of housings and may not normally be actually visible in the view depicted in FIG. **11**, unless a transparent or translucent material is employed to form the housings. For example, any or all of pod structures **1101, 1102, 1103, 1104, 1105, 1106, 1107, and/or 1108** may include circuitry (i.e., electrical and/or electronic circuitry). In FIG. **11**, a first pod structure **1101** is shown containing circuitry **1111** (i.e., circuitry **1111** is contained in the inner volume of the housing of pod structure **1101**), a second pod structure **1102** is shown containing circuitry **1112**, and a third pod structure **1108** is shown containing circuitry **1118**. The circuitry in any or all pod structures may be communicatively coupled to the circuitry in at least one adjacent pod structure by at least one respective communicative pathway (e.g., by at least one electrically conductive pathway and/or by at least one optical pathway). For example, FIG. **11** shows a first set of communicative pathways **1121** providing communicative coupling between circuitry **1118** of pod structure **1108** and circuitry **1111** of pod structure **1101**, and a second set of communicative pathways **1122** providing communicative coupling between circuitry **1111** of pod structure **1101** and circuitry **1112** of pod structure **1102**. Communicative coupling between circuitries of adjacent pod structures in device **1100** may advantageously include systems, articles, and methods for signal routing as described in U.S. patent application Ser. No. 14/461,044, which is incorporated by reference herein in its entirety.

[0265] Each individual pod structure within a wearable EMG device may perform a particular function, or particular functions. For example, in device **1100**, each of pod structures **1101, 1102, 1103, 1104, 1105, 1106, and 1107** includes a respective contact sensor **1110** or **1170**; thus, each of pod structures **1101, 1102, 1103, 1104, 1105, 1106, and 1107** may be referred to as a respective “sensor pod.” Device **1100** employs at least two different types of contact sensors: capacitive EMG sensors **1110** and at least one capacitive touch sensor **1170**. In the illustrated example, sensor pods **1101, 1102, 1103, 1104, 1106, and 1107** each include a respective capacitive EMG sensor **1110** responsive to (e.g., to detect) muscle activity of a user that provides electrical signals in response to detected muscle activity, while sensor pod **1105** includes a capacitive touch sensor **1170** (e.g., a single-frequency capacitive touch sensor or a multi-frequency capacitive touch sensor) responsive to (e.g., to detect) physical contact between a user and an object (i.e., when and/or how a user is physically touching an object) and that provides signals in response to detected physical contact. Throughout this specification and the appended claims, the term “sensor pod” is used to denote an individual pod structure that includes at least one contact sensor.

[0266] Pod structure **1108** of device **1100** includes a processor **1130** that processes the signals provided by the contact sensors **1110** and **1170** of sensor pods **1101, 1102, 1103, 1104, 1105, 1106, and 1107**. Pod structure **1108** may therefore be referred to as a “processor pod.” Throughout this specification and the appended claims, the term “processor pod” is used to denote an individual pod structure that includes at least one processor to process signals. The processor may be any type of processor, including but not limited to: a digital microprocessor or microcontroller, an application-specific integrated circuit (ASIC), a field-programmable gate array (FPGA), a digital signal processor (DSP), a graphics processing unit (GPU), a programmable gate array (PGA), a programmable logic unit (PLU), or the like, that analyzes or otherwise processes the signals to

determine at least one output, action, or function based on the signals. A person of skill in the art will appreciate that implementations that employ a digital processor (e.g., a digital microprocessor or microcontroller, a DSP, etc.) may advantageously include a non-transitory processor-readable storage medium or memory **1140** communicatively coupled thereto and storing processor-executable instructions that control the operations thereof, whereas implementations that employ an ASIC, FPGA, or analog processor may or may not include a non-transitory processor-readable storage medium.

[0267] As used throughout this specification and the appended claims, the terms “sensor pod” and “processor pod” are not necessarily exclusive. A single pod structure may satisfy the definitions of both a “sensor pod” and a “processor pod” and may be referred to as either type of pod structure. For greater clarity, the term “sensor pod” is used to refer to any pod structure that includes a contact sensor and performs at least the function(s) of a sensor pod, and the term processor pod is used to refer to any pod structure that includes a processor and performs at least the function(s) of a processor pod. In device **1100**, processor pod **1108** includes a capacitive EMG sensor **1110** (not visible in FIG. **11**) to sense, measure, transduce or otherwise detect muscle activity of a user, so processor pod **1108** could be referred to as a sensor pod. However, in exemplary device **1100**, processor pod **1108** is the only pod structure that includes a processor **1130**, thus processor pod **1108** is the only pod structure in exemplary device **1100** that can be referred to as a processor pod. The processor **1130** in processor pod **1108** also processes the EMG signals provided by the capacitive EMG sensor **1110** of processor pod **1108**. In alternative embodiments of device **1100**, multiple pod structures may include processors, and thus multiple pod structures may serve as processor pods. Similarly, some pod structures may not include contact sensors, and/or some contact sensors and/or processors may be laid out in other configurations that do not involve pod structures.

[0268] In device **1100**, processor **1130** includes and/or is communicatively coupled to a non-transitory processor-readable storage medium or memory **1140**. Memory **1140** stores at least two sets of processor-executable instructions: processor-executable gesture identification instructions **1141** that, when executed by processor **1130**, cause processor **1130** to process the EMG signals from capacitive EMG sensors **1110** and identify a gesture to which the EMG signals correspond, and processor-executable touch sensing instructions **1142** that, when executed by processor **1130**, cause processor **1130** to process the signals from the at least one capacitive touch sensor **1170**. For communicating with a separate electronic device (not shown), wearable EMG device **1100** includes at least one communication terminal. As examples, device **1100** includes a first communication terminal **1151** and a second communication terminal **1152**. First communication terminal **1151** includes a wireless transmitter (i.e., a wireless communication terminal) and second communication terminal **1152** includes a tethered connector port **1152**. Wireless transmitter **1151** may include, for example, a Bluetooth® transmitter (or similar) and connector port **1152** may include a Universal Serial Bus port, a mini-Universal Serial Bus port, a micro-Universal Serial Bus port, a SMA port, a THUNDERBOLT® port, or the like.

[0269] For some applications, device **1100** may also include at least one inertial sensor **1160** (e.g., an inertial measurement unit, or “IMU,” that includes at least one accelerometer and/or at least one gyroscope) responsive to (e.g., to detect, sense, or measure) motion effected by a user and that provides signals in response to detected motion. Signals provided by inertial sensor **1160** may be combined or otherwise processed in conjunction with signals provided by capacitive EMG sensors **1110** and/or capacitive touch sensor(s) **1170**.

[0270] Throughout this specification and the appended claims, the term “provide” and variants such as “provided” and “providing” are frequently used in the context of signals. For example, a contact sensor is described as “providing at least one signal” and an inertial sensor is described as “providing at least one signal.” Unless the specific context requires otherwise, the term “provide” is used in a most general sense to cover any form of providing a signal, including but not limited to:

relaying a signal, outputting a signal, generating a signal, routing a signal, creating a signal, transducing a signal, and so on. For example, a capacitive EMG sensor may include at least one electrode that capacitively couples to electrical signals from muscle activity. This capacitive coupling induces a change in a charge or electrical potential of the at least one electrode which is then relayed through the sensor circuitry and output, or “provided,” by the sensor. Thus, the capacitive EMG sensor may “provide” an electrical signal by relaying an electrical signal from a muscle (or muscles) to an output (or outputs). In contrast, an inertial sensor may include components (e.g., piezoelectric, piezoresistive, capacitive, etc.) that are used to convert physical motion into electrical signals. The inertial sensor may “provide” an electrical signal by detecting motion and generating an electrical signal in response to the motion.

[0271] As previously described, each of pod structures **1101**, **1102**, **1103**, **1104**, **1105**, **1106**, **1107**, and **1108** may include circuitry (i.e., electrical and/or electronic circuitry). FIG. **11** depicts circuitry **1111** inside the inner volume of sensor pod **1101**, circuitry **1112** inside the inner volume of sensor pod **1102**, and circuitry **1118** inside the inner volume of processor pod **1118**. The circuitry in any or all of pod structures **1101**, **1102**, **1103**, **1104**, **1105**, **1106**, **1107** and **1108** (including circuitries **1111**, **1112**, and **1118**) may include any or all of: an amplification circuit to amplify electrical signals provided by at least one contact sensor **1110**, **1170**; a filtering circuit to remove unwanted signal frequencies from the signals provided by at least one contact sensor **1110**, **1170**; and/or an analog-to-digital conversion circuit to convert analog signals into digital signals. Device **1100** may also include at least one battery (not shown in FIG. **11**) to provide a portable power source for device **1100**.

[0272] Signals that are provided by contact sensors **1110**, **1170** in device **1100** are routed to processor pod **1108** for processing by processor **1130**. To this end, device **1100** employs a set of communicative pathways (e.g., **1121** and **1122**) to route the signals that are output by sensor pods **1101**, **1102**, **1103**, **1104**, **1105**, **1106**, and **1107** to processor pod **1108**. Each respective pod structure **1101**, **1102**, **1103**, **1104**, **1105**, **1106**, **1107**, and **1108** in device **1100** is communicatively coupled to, over, or through at least one of the two other pod structures between which the respective pod structure is positioned by at least one respective communicative pathway from the set of communicative pathways. Each communicative pathway (e.g., **1121** and **1122**) may be realized in any communicative form, including but not limited to: electrically conductive wires or cables, ribbon cables, fiber-optic cables, optical/photonics waveguides, electrically conductive traces carried by a rigid printed circuit board, electrically conductive traces carried by a flexible printed circuit board, and/or electrically conductive traces carried by a stretchable printed circuit board.

[0273] Device **1100** from FIG. **11** represents an example of a wearable EMG device that incorporates at least one capacitive touch sensor **1170** (e.g., at least one single-frequency capacitive touch sensor and/or at least one multi-frequency capacitive touch sensor) in accordance with the teachings of the present systems, articles, and methods, though the teachings of the present systems, articles, and methods are applicable to any wearable electronic device. In most applications, it is advantageous for the wearable device to include an on-board processor for processing contact sensor signals as described herein, but a person of skill in the art will appreciate that at least some of the acts involved in processing contact sensor signals may be performed by a processor that is separate from the wearable device (e.g., a processor in a computer that receives signals from the wearable device).

[0274] As previously described, incorporating at least one capacitive touch sensor into a wearable device (such as a wristwatch of a wearable EMG device) can enable the device to detect physical contact between a user and an object (i.e., when and/or how a user is physically interacting with an object) and to provide signals in response to the detected physical contact. Furthermore, at least two capacitive touch sensors worn on different parts of the user's body (e.g., in a first wearable device, such as a wearable EMG device, worn on a first arm of the user and a second wearable device, such as a wristwatch or a second wearable EMG device, worn on a second arm of the user)

can be used to detect poses, postures, gestures, and/or other configurations performed by the user as described in Sato et al. Such poses, postures, gestures, and/or other configurations detected by at least two capacitive touch sensors worn on different parts of the user's body (similar to, for example, U.S. Pat. No. 9,372,535) may facilitate gesture identification and/or expand the library of gestures available to a user in, for example, a human-electronics interface employing gesture-based control.

Description For Electromyographic Control Of Electronic Devices

[0275] The various embodiments described herein provide systems, articles, and methods for human-electronics interfaces employing a generalized wearable EMG device that may be readily implemented in a wide range of applications. The human-electronics interfaces described herein employ a wearable EMG device that controls functions of another electronic device not by outputting “commands” as in the known proposals previously described, but by outputting generic gesture identification signals, or “flags,” that are not specific to the particular electronic device being controlled. In this way, the wearable EMG device may be used to control virtually any other electronic device if, for example, the other electronic device (or multiple other electronic devices) is (are) programmed with instructions for how to respond to the gesture identification flags.

[0276] Throughout this specification and the appended claims, the term “gesture identification flag” is used to refer to at least a portion of a data signal (e.g., a bit string) that is defined by and transmitted from a wearable EMG device in response to the wearable EMG device identifying that a user thereof has performed a particular gesture. The gesture identification flag may be received by a “receiving” electronic device, but the “gesture identification flag” portion of the data signal does not contain any information that is specific to the receiving electronic device. A gesture identification flag is a general, universal, and/or ambiguous signal that is substantially independent of the receiving electronic device (e.g., independent of any downstream processor-based device) and/or generic to a variety of applications run on any number of receiving electronic devices (e.g., generic to a variety of end user applications executable by one or more downstream processor-based device(s) useable with the wearable EMG device). A gesture identification flag may carry no more information than the definition/identity of the flag itself. For example, a set of three gesture identification flags may include a first flag simply defined as “A,” a second flag simply defined as “B,” and a third flag simply defined as “C.” Similarly, a set of four binary gesture identification flags may include a 00 flag, a 01 flag, a 10 flag, and a 11 flag. In accordance with the present systems, articles, and methods, a gesture identification flag may be defined and output by a wearable EMG device with little to no regard for the nature or functions of the receiving electronic device. The receiving electronic device may be programmed with specific instructions for how to interpret and/or respond to one or more gesture identification flag(s). As will be understood by a person of skill in the art, in some applications a gesture identification flag may be combined with authentication data, encryption data, device ID data (i.e., transmitting electronic device ID data and/or receiving electronic device ID data), pairing data, and/or any other data to enable and/or facilitate telecommunications between the wearable EMG device and the receiving electronic device in accordance with known telecommunications protocols (e.g., Bluetooth®). For greater certainty, throughout this specification and the appended claims, the term “gesture identification flag” refers to at least a portion of a data signal that is defined by a wearable EMG device based (at least in part) on EMG and/or accelerometer data and is substantially independent of the receiving electronic device. For the purposes of transmission, a gesture identification flag may be combined with other data that is at least partially dependent on the receiving electronic device. For example, a gesture identification flag may be a 2-bit component of an 8-bit data byte, where the remaining 6 bits are used for telecommunication purposes, as in: 00101101, where the exemplary first six bits “001011” may correspond to telecommunications information such as transmitting/receiving device IDs, encryption data, pairing data, and/or the like, and the exemplary last two bits “01” may correspond to a gesture identification flag. While a bit-length of two bits is used to represent a

gesture identification flag in this example, in practice a gesture identification flag may comprise any number of bits (or other measure of signal length of a scheme not based on bits is employed). [0277] FIG. 12 is a perspective view of an exemplary wearable EMG device 1200 that may form part of a human-electronics interface in accordance with the present systems, articles, and methods. Exemplary device 1200 is an armband designed to be worn on the wrist, forearm, or upper arm of a user, though a person of skill in the art will appreciate that the teachings described herein may readily be applied in wearable EMG devices designed to be worn elsewhere on the body of the user (such as on the finger, leg, ankle, neck, and/or torso of the user). Exemplary details that may be included in exemplary wearable EMG device 1200 are described in at least related U.S. Pat. Nos. 11,009,951 and 10,528,135 incorporated by reference above. As well as, U.S. Non-Provisional patent application Ser. No. 14/186,889 and U.S. Non-Provisional patent application Ser. No. 14/194,252, each of which is incorporated herein by reference in its entirety.

[0278] Device 1200 includes a set of eight pod structures 1201, 1202, 1203, 1204, 1205, 1206, 1207, and 1208 that form physically coupled links of the wearable EMG device 1200. Each pod structure in the set of eight pod structures 1201, 1202, 1203, 1204, 1205, 1206, 1207, and 1208 is positioned adjacent and in between two other pod structures in the set of eight pod structures and the set of pod structures forms a perimeter of an annular or closed loop configuration. For example, pod structure 1201 is positioned adjacent and in between pod structures 1202 and 1208 at least approximately on a perimeter of the annular or closed loop configuration of pod structures, pod structure 1202 is positioned adjacent and in between pod structures 1201 and 1203 at least approximately on the perimeter of the annular or closed loop configuration, pod structure 1203 is positioned adjacent and in between pod structures 1202 and 1204 at least approximately on the perimeter of the annular or closed loop configuration, and so on. Each of pod structures 1201, 1202, 1203, 1204, 1205, 1206, 1207, and 1208 is physically coupled to the two adjacent pod structures by at least one adaptive coupler (not visible in FIG. 12). For example, pod structure 1201 is physically coupled to pod structure 1208 by an adaptive coupler and to pod structure 1202 by an adaptive coupler. The term “adaptive coupler” is used throughout this specification and the appended claims to denote a system, article or device that provides flexible, adjustable, modifiable, extendable, extensible, or otherwise “adaptive” physical coupling. Adaptive coupling is physical coupling between two objects that permits limited motion of the two objects relative to one another. An example of an adaptive coupler is an elastic material such as an elastic band. Thus, each of pod structures 1201, 1202, 1203, 1204, 1205, 1206, 1207, and 1208 in the set of eight pod structures may be adaptively physically coupled to the two adjacent pod structures by at least one elastic band. The set of eight pod structures may be physically bound in the annular or closed loop configuration by a single elastic band that couples over or through all pod structures or by multiple separate elastic bands that couple between adjacent pairs of pod structures or between groups of adjacent pairs of pod structures. Device 1200 is depicted in FIG. 12 with the at least one adaptive coupler completely retracted and contained within the eight pod structures 1201, 1202, 1203, 1204, 1205, 1206, 1207, and 1208 (and therefore the at least one adaptive coupler is not visible in FIG. 12). Further details of adaptive coupling in wearable electronic devices are described in, for example, U.S. Pat. No. 10,152,082, which is incorporated herein by reference in its entirety.

[0279] Throughout this specification and the appended claims, the term “pod structure” is used to refer to an individual link, segment, pod, section, structure, component, etc. of a wearable EMG device. For the purposes of the present systems, articles, and methods, an “individual link, segment, pod, section, structure, component, etc.” (i.e., a “pod structure”) of a wearable EMG device is characterized by its ability to be moved or displaced relative to another link, segment, pod, section, structure component, etc. of the wearable EMG device. For example, pod structures 1201 and 1202 of device 1200 can each be moved or displaced relative to one another within the constraints imposed by the adaptive coupler providing adaptive physical coupling therebetween. The desire for pod structures 1201 and 1202 to be movable/displaceable relative to one another

specifically arises because device **1200** is a wearable EMG device that advantageously accommodates the movements of a user and/or different user forms.

[0280] Device **1200** includes eight pod structures **1201**, **1202**, **1203**, **1204**, **1205**, **1206**, **1207**, and **1208** that form physically coupled links thereof. Wearable EMG devices employing pod structures (e.g., device **1200**) are used herein as exemplary wearable EMG device designs, while the present systems, articles, and methods may be applied to wearable EMG devices that do not employ pod structures (or that employ any number of pod structures). Thus, throughout this specification, descriptions relating to pod structures (e.g., functions and/or components of pod structures) should be interpreted as being applicable to any wearable EMG device design, even wearable EMG device designs that do not employ pod structures (except in cases where a pod structure is specifically recited in a claim).

[0281] In exemplary device **1200** of FIG. **12**, each of pod structures **1201**, **1202**, **1203**, **1204**, **1205**, **1206**, **1207**, and **1208** comprises a respective housing having a respective inner volume. Each housing may be formed of substantially rigid material and may be optically opaque. Throughout this specification and the appended claims, the term “rigid” as in, for example, “substantially rigid material,” is used to describe a material that has an inherent tendency to maintain its shape and resist malformation/deformation under the moderate stresses and strains typically encountered by a wearable electronic device.

[0282] Details of the components contained within the housings (i.e., within the inner volumes of the housings) of pod structures **1201**, **1202**, **1203**, **1204**, **1205**, **1206**, **1207**, and **1208** are not visible in FIG. **1**. To facilitate descriptions of exemplary device **1200**, some internal components are depicted by dashed lines in FIG. **12** to indicate that these components are contained in the inner volume(s) of housings and may not normally be actually visible in the view depicted in FIG. **12**, unless a transparent or translucent material is employed to form the housings. For example, any or all of pod structures **1201**, **1202**, **1203**, **1204**, **1205**, **1206**, **1207**, and/or **1208** may include electric circuitry. In FIG. **12**, a first pod structure **1201** is shown containing electric circuitry **1211** (i.e., electric circuitry **1211** is contained in the inner volume of the housing of pod structure **1201**), a second pod structure **1202** is shown containing electric circuitry **1212**, and a third pod structure **1208** is shown containing electric circuitry **1218**. The electric circuitry in any or all pod structures may be communicatively coupled to the electric circuitry in at least one other pod structure by at least one respective communicative pathway (e.g., by at least one electrically conductive pathway and/or by at least one optical pathway). For example, FIG. **12** shows a first set of communicative pathways **12221** providing communicative coupling between electric circuitry **1218** of pod structure **1208** and electric circuitry **1211** of pod structure **1201**, and a second set of communicative pathways **1222** providing communicative coupling between electric circuitry **1211** of pod structure **1201** and electric circuitry **1212** of pod structure **1202**. Communicative coupling between electric circuitries of pod structures in device **1200** may advantageously include systems, articles, and methods for signal routing as described in U.S. patent application Ser. No. 14/461,044 and/or systems, articles, and methods for strain mitigation as described in U.S. patent application Ser. No. 14/335,668, both of which are incorporated by reference herein in their entirety.

[0283] Throughout this specification and the appended claims the term “communicative” as in “communicative pathway,” “communicative coupling,” and in variants such as “communicatively coupled,” is generally used to refer to an engineered arrangement for transferring and/or exchanging information. Exemplary communicative pathways include, but are not limited to, electrically conductive pathways (e.g., electrically conductive wires, electrically conductive traces), magnetic pathways (e.g., magnetic media), and/or optical pathways (e.g., optical fiber), and exemplary communicative couplings include, but are not limited to, electrical couplings and/or optical couplings.

[0284] Each individual pod structure within a wearable EMG device may perform a particular function, or particular functions. For example, in device **1200**, each of pod structures **1201**, **1202**,

1203, 1204, 1205, 1206, and 1207 includes a respective EMG sensor **1210** (only one called out in FIG. **12** to reduce clutter) to in use detect muscle activity of a user and to in use provide electrical signals in response to the detected muscle activity. Thus, each of pod structures **1201, 1202, 1203, 1204, 1205, 1206, and 1207** may be referred to as a respective “sensor pod.” Throughout this specification and the appended claims, the term “sensor pod” is used to denote an individual pod structure that includes at least one sensor to detect muscle activity of a user. Each EMG sensor may be, for example, a respective capacitive EMG sensor that detects electrical signals generated by muscle activity through capacitive coupling, such as for example the capacitive EMG sensors described in U.S. patent application Ser. No. 14/194,252.

[0285] Pod structure **1208** of device **1200** includes a processor **1240** that in use processes the signals provided by the EMG sensors **1210** of sensor pods **1201, 1202, 1203, 1204, 1205, 1206, and 1207** in response to detected muscle activity. Pod structure **1208** may therefore be referred to as a “processor pod.” Throughout this specification and the appended claims, the term “processor pod” is used to denote an individual pod structure that includes at least one processor to process signals. The processor may be any type of processor, including but not limited to: a digital microprocessor or microcontroller, an application-specific integrated circuit (ASIC), a field-programmable gate array (FPGA), a digital signal processor (DSP), a graphics processing unit (GPU), a programmable gate array (PGA), a programmable logic unit (PLU), or the like, that in use analyzes the signals to determine at least one output, action, or function based on the signals.

[0286] As used throughout this specification and the appended claims, the terms “sensor pod” and “processor pod” are not necessarily exclusive. A single pod structure may satisfy the definitions of both a “sensor pod” and a “processor pod” and may be referred to as either type of pod structure. For greater clarity, the term “sensor pod” is used to refer to any pod structure that includes a sensor and performs at least the function(s) of a sensor pod, and the term processor pod is used to refer to any pod structure that includes a processor and performs at least the function(s) of a processor pod. In device **1200**, processor pod **1208** includes an EMG sensor **1210** (not visible in FIG. **12**) to sense, measure, transduce or otherwise detect muscle activity of a user, so processor pod **1208** could be referred to as a sensor pod. However, in exemplary device **1200**, processor pod **1208** is the only pod structure that includes a processor **1240**, thus processor pod **1208** is the only pod structure in exemplary device **1200** that can be referred to as a processor pod. In alternative embodiments of device **1200**, multiple pod structures may include processors, and thus multiple pod structures may serve as processor pods. Similarly, some pod structures may not include sensors, and/or some sensors and/or processors may be laid out in other configurations that do not involve pod structures.

[0287] Processor **1240** includes and/or is communicatively coupled to a non-transitory processor-readable storage medium or memory **1241**. As will be described in more detail later, memory **1241** may store, for example, a set of gesture identification flags to be transmitted by device **1200** and/or, for example, processor-executable instructions to be executed by processor **1240**. For transmitting gesture identification flags, a wearable EMG device may include at least one output terminal communicatively coupled to processor **1240**. Throughout this specification and the appended claims, the term “terminal” is generally used to refer to any physical structure that provides a telecommunications link through which a data signal may enter and/or leave a device. The term “output terminal” is used to describe a terminal that provides at least a signal output link and the term “input terminal” is used to describe a terminal that provides at least a signal input link; however unless the specific context requires otherwise, an output terminal may also provide the functionality of an input terminal and an input terminal may also provide the functionality of an output terminal. In general, a “communication terminal” represents the end (or “terminus”) of communicative signal transfer within a device and the beginning of communicative signal transfer to/from an external device (or external devices). As examples, communication terminal **1251** of device **1200** may include a wireless transmitter that implements a known wireless communication

protocol, such as Bluetooth®, WiFi®, or Zigbee, while communication terminal **1252** may include a tethered communication port such as Universal Serial Bus (USB) port, a micro-USB port, a Thunderbolt® port, and/or the like.

[0288] For some applications, device **1200** may also include at least one accelerometer **1260** (e.g., an inertial measurement unit, or “IMU,” that includes at least one accelerometer and/or at least one gyroscope) communicatively coupled to processor **1240**. In use, the at least one accelerometer may detect, sense, and/or measure motion effected by a user and provide signals in response to the detected motion. As will be described in more detail later, signals provided by accelerometer **1260** may be processed together with signals provided by EMG sensors **1210** by processor **1240**.

[0289] Throughout this specification and the appended claims, the term “accelerometer” is used as a general example of an inertial sensor and is not intended to limit (nor exclude) the scope of any description or implementation to “linear acceleration.”

[0290] As previously described, each of pod structures **1201**, **1202**, **1203**, **1204**, **1205**, **1206**, **1207**, and **1208** may include electric circuitry. FIG. **12** depicts electric circuitry **1211** inside the inner volume of sensor pod **1201**, electric circuitry **1212** inside the inner volume of sensor pod **1202**, and electric circuitry **1218** inside the inner volume of processor pod **1218**. The electric circuitry in any or all of pod structures **1201**, **1202**, **1203**, **1204**, **1205**, **1206**, **1207** and **1208** (including electric circuitries **12221**, **1222**, and **128**) may include any or all of: an amplification circuit to in use amplify electrical signals provided by at least one EMG sensor **1210**, a filtering circuit to in use remove unwanted signal frequencies from the signals provided by at least one EMG sensor **1210**, and/or an analog-to-digital conversion circuit to in use convert analog signals into digital signals. Device **1200** may also include a battery (not shown in FIG. **12**) to in use provide a portable power source for device **1200**.

[0291] Signals that are provided by EMG sensors **1210** in device **1200** are routed to processor pod **1208** for processing by processor **1240**. To this end, device **1200** employs a set of communicative pathways (e.g., **12221** and **1222**) to route the signals that are provided by sensor pods **1201**, **1202**, **1203**, **1204**, **1205**, **1206**, and **1207** to processor pod **1208**. Each respective pod structure **1201**, **1202**, **1203**, **1204**, **1205**, **1206**, **1207**, and **1208** in device **1200** is communicatively coupled to at least one other pod structure by at least one respective communicative pathway from the set of communicative pathways. Each communicative pathway (e.g., **12221** and **1222**) may be realized in any communicative form, including but not limited to: electrically conductive wires or cables, ribbon cables, fiber-optic cables, optical/photonic waveguides, electrically conductive traces carried by a rigid printed circuit board, and/or electrically conductive traces carried by a flexible printed circuit board.

[0292] The present systems, articles, and methods describe a human-electronics interface in which a wearable EMG device (e.g., device **1200**) is used to control another electronic device. The human-electronics interface may be characterized as a system that enables electromyographic control of an electronic device.

[0293] FIG. **13** is an illustrative diagram of a system **1300** that enables electromyographic control of an electronic device in accordance with the present systems, articles, and methods. System **1300** includes a wearable EMG device **1370** and an unspecified electronic device **1380**. Wearable EMG device **1370** may be, as an illustrative example, substantially similar to wearable EMG device **1200** from FIG. **1**. That is, exemplary wearable EMG device **1370** includes a set of pod structures **1301** (only one called out in FIG. **13** to reduce clutter) that form physically coupled links of device **1370**, where each pod structure **1301** includes a respective EMG sensor **1310** (e.g., a respective capacitive EMG sensor) to in use sense, measure, transduce or otherwise detect muscle activity of a user and provide electrical signals in response to the muscle activity. As previously described, however, the present systems, articles, and methods may be implemented using wearable EMG devices that do not employ pod structures.

[0294] Each pod structure **1301** is electrically coupled to at least one adjacent pod structure by at

least one respective communicative pathway **1320** to route signals in between pod structures (e.g., to route signals from sensor pods to a processor pod). Each pod structure **1301** is also physically coupled to two adjacent pod structures **1301** by at least one adaptive coupler **1360** and the set of pod structures forms a perimeter of an annular or closed loop configuration. FIG. **13** shows device **1370** in an expanded annular or closed loop configuration adapted to fit the arm of a larger user than the contracted annular or closed loop configuration of device **1200** from FIG. **1**. As a result, adaptive couplers **1360** (only one called out in FIG. **13**) providing adaptive physical coupling between adjacent pairs of pod structures **1301** are visible in FIG. **13**, whereas such adaptive couplers **1360** are not visible in FIG. **1**.

[0295] Each pod structure **1301** includes respective electric circuitry **1330** and at least one electric circuitry **1330** includes a first processor **1340** (e.g., akin to processor **1240** in device **1200** of FIG. **12**). At least one electric circuitry **1330** may include an IMU and/or at least one accelerometer. Device **1370** also includes an output terminal **1350** to in use interface with unspecified electronic device **1380**. For example, device **1370** is operative to in use send gesture identification flags to unspecified electronic device **1380** through output terminal **1350**.

[0296] Unspecified electronic device **1380** may be any electronic device, including but not limited to: a desktop computer, a laptop computer, a tablet computer, a mobile phone, a smartphone, a portable electronic device, an audio player, a television, a video player, a video game console, a robot, a light switch, and/or a vehicle. Electronic device **1380** is denominated as “unspecified” herein to emphasize the fact that the gesture identification flags output by wearable EMG device **1370** are generic to a variety of electronic devices and/or applications executed by the electronic devices. The electronic device **1380**, its operating characteristics and/or the operating characteristics of applications executed by the electronic device **1380** may not be a priori known by the EMG device **1370** during use, or even prior to use when a mapping between signals, gesture flags, and/or gestures is initially defined or established. As previously described, a data signal output by device **1370** through output terminal **1350** may include a gesture identification flag as a first portion thereof and may also include at least a second portion to implement known telecommunications protocols (e.g., Bluetooth®). Thus, electronic device **1380** may remain “unspecified” with respect to the gesture identification flag portion(s) of signals output by EMG device **1370** but electronic device **1380** may be “specified” by the telecommunications portion(s) of signals output by EMG device **1370** (if such specification is necessary for signal transfer, e.g., to communicatively “pair” device **1370** and device **1380** if required by the telecommunications protocol being implemented). For example, electronic device **1380** may be and remain “unspecified” while muscle activity is detected by EMG device **1370** and while the processor in EMG device **1370** determines a gesture identification flag based, at least in part, on the detected muscle activity. After a gesture identification flag is determined by the processor in EMG device **1370**, electronic device **1380** may become “specified” when the gesture identification flag is combined with telecommunication data and transmitted to electronic device **1380**. In this scenario, the gesture identification flag itself does not include any information that is specific to electronic device **1380** and therefore electronic device **1380** is “unspecified” in relation to the gesture identification flag.

[0297] Electronic device **1380** includes an input terminal **1381** to in use interface with wearable EMG device **1370**. For example, device **1380** may receive gesture identification flags from device **1370** through input terminal **1381**. Device **1380** also includes a second processor **1383** to in use process gesture identification flags received from device **1370**. Second processor **1383** may include or be communicatively coupled to a non-transitory processor-readable storage medium or memory **1384** that stores processor-executable instructions to be executed by second processor **1383**.

[0298] Wearable EMG device **1370** and electronic device **1380** are, in use, communicatively coupled by communicative link **1390**. More specifically, output terminal **1350** of wearable EMG device **1370** is, in use, communicatively coupled to input terminal **1381** of electronic device **1380**

by communicative link **1390**. Communicative link **1390** may be used to route gesture identification flags from wearable EMG device **1370** to electronic device **1380**. Communicative link **1390** may be established in variety of different ways. For example, output terminal **1350** of wearable EMG device **1370** may include a first tethered connector port (e.g., a USB port, or the like), input terminal **1381** of electronic device **1380** may include a second tethered connector port, and communicative link **1390** may be established through a communicative pathway (e.g., an electrical or optical cable, wire, circuit board, or the like) that communicatively couples the first connector port to the second connector port to route gesture identification flags from output terminal **1350** to input terminal **1381**. Alternatively, output terminal **1350** of wearable EMG device **1370** may include a wireless transmitter and communicative link **1390** may be representative of wireless communication between wearable EMG device **1370** and electronic device **1380**. In this case, input terminal **1381** of electronic device **1380** may include a wireless receiver to in use wirelessly receive gesture identification flags from the wireless transmitter of wearable EMG device **1370** (using, for example, established wireless telecommunication protocols, such as Bluetooth®); or, input terminal **1381** may be communicatively coupled to a wireless receiver **1382** (such as a USB dongle communicatively coupled to a tethered connector port of input terminal **1381**) to in use wirelessly receive gesture identification flags from the wireless transmitter of wearable EMG device **1370**.

[0299] As previously described, known proposals for human-electronics interfaces that employ a wearable EMG device are limited in their versatility because they involve mapping gestures to functions on-board the wearable EMG device itself. Thus, in known proposals, the wearable EMG device outputs control signals (i.e., “commands”) that embody pre-defined instructions to effect pre-defined functions that are specific to a pre-defined receiving device. If a user wishes to use such a wearable EMG device for a different purpose (i.e., to control a different receiving device, or a different application within the same receiving device), then the definitions of the commands themselves must be re-programmed within the wearable EMG device. Conversely, the various embodiments described herein provide systems, articles, and methods for human-electronics interfaces that employ a wearable EMG device that controls functions of another electronic device by outputting generic gesture identification flags that are not specific to the particular electronic device being controlled. The electronic device being controlled may include or may access an Application Programming Interface (i.e., an “API” including instructions and/or data or information (e.g., library) stored in a non-transitory processor-readable storage medium or memory) through which a user may define how gesture identification flags are to be interpreted by the electronic device being controlled (i.e., where the user may define how the electronic device responds to gesture identification flags). The present systems, articles, and methods greatly enhance the versatility of human-electronics interfaces by employing a wearable EMG device that outputs the same gesture identification flags regardless of what it is being used to control, and may therefore be used to control virtually any electronic receiving device. The functions or operations that are controlled by the wearable EMG devices described herein are defined within the receiving device (or within the applications within the receiving device) rather than within the wearable EMG device.

[0300] FIG. **14** is a flow-diagram showing a method **1400** of operating a wearable EMG device to provide electromyographic control of an electronic device in accordance with the present systems, articles, and methods. The electronic device may be any “unspecified” electronic device as described previously. For example, the electronic device may be any downstream processor-based device. The wearable EMG device may include at least one EMG sensor, a processor, and an output terminal (i.e., the wearable EMG device may be substantially similar to wearable EMG device **1200** from FIG. **12** and wearable EMG device **1370** from FIG. **13**). Method **1400** includes four acts **1401**, **1402**, **1403**, and **1404**, though those of skill in the art will appreciate that in alternative embodiments certain acts may be omitted and/or additional acts may be added. Those of skill in the art will also appreciate that the illustrated order of the acts is shown for exemplary purposes only

and may change in alternative embodiments.

[0301] At **1401**, muscle activity of a user (i.e., a wearer of the wearable EMG device) is sensed, measured, transduced or otherwise detected by at least one EMG sensor of the wearable EMG device. As previously described, the at least one EMG sensor may be, for example, a capacitive EMG sensor and sensing, measuring, transducing or otherwise detecting muscle activity of the user may include, for example, capacitively coupling to electrical signals generated by muscle activity of the user.

[0302] At **1402**, at least one signal is provided from the at least one EMG sensor to the processor of the wearable EMG device in response to the sensed, measured, transduced or otherwise detected muscle activity. The at least one signal may be an analog signal that is amplified, filtered, and converted to digital form by electric circuitry within the wearable EMG device. Providing the at least one signal from the at least one EMG sensor to the processor may include routing the at least one signal to the processor through one or more communicative pathway(s) as described previously.

[0303] At **1403**, a gesture identification flag is determined by the processor of the wearable EMG device, based at least in part on the at least one signal provided from the at least one EMG sensor to the processor. The gesture identification flag is substantially independent of the downstream electronic device. As will be described in more detail later (e.g., with reference to FIG. 16), determining a gesture identification flag by the processor may implement a range of different algorithms, including but not limited to: a look-up table, a mapping, a machine learning algorithm, a pattern recognition algorithm, and the like. In some applications, the wearable EMG device may include a non-transitory processor-readable medium that stores a set of gesture identification flags and/or stores processor-executable instructions that, when executed by the processor of the wearable EMG device, cause the processor to determine a gesture identification flag based at least in part on the at least one signal provided from the at least one EMG sensor to the processor. In such a case, act **1403** may include executing the processor-executable instructions by the processor to cause the processor to determine a gesture identification flag based at least in part on the at least one signal provided from the at least one EMG sensor to the processor.

[0304] At **1404**, the gesture identification flag is transmitted to the electronic device by the output terminal of the wearable EMG device. As previously described, the output terminal of the wearable EMG device may include a wireless transmitter, and transmitting the gesture identification flag to the electronic device may include wirelessly transmitting the gesture identification flag to the electronic device by the wireless transmitter.

[0305] As an example, the at least one EMG sensor may include a first EMG sensor and at least a second EMG sensor, and muscle activity of the user may be sensed, measured, transduced or otherwise detected by the first EMG sensor and by at least the second EMG sensor (at **1401**). In this case at least a first signal is provided from the first EMG sensor to the processor of the wearable EMG device in response to the detected muscle activity (at **1402**) and at least a second signal is provided from at least the second EMG sensor to the processor of the wearable EMG device in response to the detected muscle activity (at **1402**). The processor of the wearable EMG device may then determine (at **1403**) a gesture identification flag based at least in part on both the at least a first signal provided from the first EMG sensor to the processor and the at least a second signal provided from at least the second EMG sensor to the processor.

[0306] As previously described, in some applications it may be advantageous to combine or otherwise make use of both EMG signals and motion signals sensed, measured or otherwise detected, for example, by an accelerometer. To this end, the wearable EMG device may include at least one accelerometer, and an additional method employing further acts may be combined with acts **1401-1404** of method **1400** to detect and process motion signals.

[0307] FIG. 15 is a flow-diagram showing a method **1500** of operating a wearable EMG device to provide both electromyographic and motion control of an electronic device in accordance with the

present systems, articles, and methods. Method **1500** includes three acts **1501**, **1502**, and **1503**, though those of skill in the art will appreciate that in alternative embodiments certain acts may be omitted and/or additional acts may be added. Those of skill in the art will also appreciate that the illustrated order of the acts is shown for exemplary purposes only and may change in alternative embodiments. Method **1500** is optionally performed in conjunction with method **1400** from FIG. **14** and, if performed, performed using the same wearable EMG device as that used to perform method **1400**. For example, while acts **1401** and **1402** of method **1400** are performed by EMG sensors of the wearable EMG device, acts **1501** and **1502** of method **1500** may optionally be performed by at least one accelerometer of the wearable EMG device.

[0308] At **1501**, motion effected by the user of the wearable EMG device is sensed, measured, transduced or otherwise detected by at least one accelerometer in the wearable EMG device. The at least one accelerometer may be part of an IMU that includes multiple accelerometers (such as an MPU-9150 Nine-Axis MEMS MotionTracking™ Device from InvenSense). The motion effected by the user that may be detected and/or measured may include, e.g., translation in one or multiple spatial directions and/or rotation about one or more axes in one or more spatial directions. The motion(s) may be detected in terms of a presence or absence of translation and/or rotation, and/or measured in terms of a speed of translation and/or rotation and/or acceleration of translation and/or rotation.

[0309] At **1502**, at least one signal is provided from the at least one accelerometer to the processor in response to the sensed, measured, transduced or otherwise detected motion. The at least one signal may be an analog signal that is amplified, filtered, and converted to digital form by electric circuitry within the wearable EMG device. The at least one signal may be routed to the processor in the wearable EMG device via one or more communicative pathway(s) as described previously.

[0310] As previously described, act **1403** of method **1400** involves determining, by a processor of the wearable EMG device, a gesture identification flag based at least in part on the at least one signal provided from the at least one EMG sensor to the processor in response to detected muscle activity. In applications where the wearable EMG device further includes at least one accelerometer and acts **1501** and **1502** of method **1500** are performed, act **1403** of method **1400** may be replaced by act **1503** of method **1500**.

[0311] At **1503**, a gesture identification flag is determined by the processor, based at least in part on the at least one signal provided from the at least one EMG sensor to the processor and the at least one signal provided from the at least one accelerometer to the processor. The wearable EMG device may include a non-transitory processor-readable medium (e.g., memory **1384** of device **1380** from FIG. **13**) that stores processor-executable instructions that, when executed by the processor, cause the processor to determine a gesture identification flag based on the at least one signal provided from the at least one EMG sensor to the processor and the at least one signal provided from the at least one accelerometer to the processor (i.e., to perform act **1503**). Thus, act **1503** may include executing the processor-executable instructions stored in the non-transitory processor-readable medium.

[0312] In some implementations, the at least one signal provided from the at least one accelerometer to the processor (i.e., at act **1502**) may be combined with at least one signal provided from at least one EMG sensor to the processor (i.e., at act **1402** of method **1400** from FIG. **14**) by the processor of the wearable EMG device. Thus, act **1503** requires that acts **1501** and **1502** from method **1500** and acts **1401** and **1402** from method **1400** all be completed. The at least one signal from the at least one accelerometer and the at least one signal from the at least one EMG sensor may be summed, concatenated, overlaid, or otherwise combined in any way by the processor to produce, provide or output any number of signals, operations, and/or results.

[0313] After act **1503**, the gesture identification flag may be transmitted or output by an output terminal of the wearable EMG device (i.e., according to act **1404** of method **1400**) to any downstream electronic device and interpreted or otherwise processed by the downstream electronic

device to cause the downstream electronic device to perform some function(s) or operation(s), or otherwise effect an interaction with or response from the downstream electronic device, in response to the gesture identification flag.

[0314] In accordance with the present systems, articles, and methods, at least one signal provided by at least one EMG sensor (either alone or together with one or more signals provided by one or more transducers such as an accelerometer or other motion or acceleration responsive transducers) may represent or be indicative of a gesture performed by a user of a wearable EMG device. Determining a gesture identification flag corresponding to that at least one signal may involve identifying, by a processor, the gesture performed by the user based at least in part on the at least one signal(s) from the EMG and/or other sensors or transducers, and determining, by the processor, a gesture identification flag that corresponds to that determined gesture. Unless the specific context requires otherwise, throughout this specification and the appended claims “a” gesture identification flag should be interpreted in a general, inclusive sense as “at least one” gesture identification flag with the understanding that determining any number of gesture identification flags (e.g., determining one gesture identification flag, or determining multiple gesture identification flags) includes determining “a” gesture identification flag. Each gesture identification flag may include, or be represented by, one or more bits of information. Furthermore, “determining” a gesture identification flag by a processor may be achieved through a wide variety of different techniques. For example, a processor may determine a gesture identification flag by performing or otherwise effecting a mapping between gestures (e.g., between EMG and/or accelerometer signals representative of gestures) and gesture identification flags (e.g., by invoking a stored look-up table or other form of stored processor-executable instructions providing and/or effecting mappings between gestures and gesture identification flags), or a processor may determine a gesture identification flag by performing an algorithm or sequence of data processing acts (e.g., by executing stored processor-executable instructions dictating how to determine a gesture identification flag based at least in part on one or more signal(s) provided by at least one EMG sensor and/or at least one accelerometer).

[0315] FIG. **16** is a schematic illustration showing an exemplary mapping **1600** between a set of exemplary gestures and a set of exemplary gesture identification flags in accordance with the present systems, articles, and methods. Mapping **1600** may be representative of processor-executable instructions that are defined in advance of determining gesture identification flags based at least in part on at least one EMG signal (and, e.g., executed by a processor to perform the act of determining gesture identification flags based at least in part on at least one EMG signal), or mapping **1600** may be representative of the results (i.e., the mapping that is effected) when gesture identification flags are determined based at least in part on at least one EMG signal. In other words, mapping **1600** characterizes: i) a prescription, embodied in processor-executable instructions, for or definition of how gestures (e.g., EMG and/or accelerometer signals that are representative of gestures) are to be mapped to gesture identification flags by a processor when determining a gesture identification flag based at least in part on at least one signal provided from at least one EMG sensor to the processor; or ii) the end results when a processor performs an algorithm or series of data processing steps to determine a gesture identification flag based at least in part on at least one signal provided from at least one EMG sensor to the processor. In the former characterization (i.e., characterization i)), mapping **1600** may be stored as a look-up table or set of defined processor-executable “mapping instructions” in a non-transitory processor-readable storage medium and invoked/executed by the processor when determining a gesture identification flag. In the latter characterization (i.e., characterization ii)), mapping **1600** may not be stored in a non-transitory processor-readable storage medium itself, but instead processor-executable instructions to perform an algorithm or series of data processing acts may be stored in the non-transitory processor-readable storage medium and mapping **1600** may represent the results of executing the stored processor-executable instructions by the processor when determining a gesture identification

flag. In either case, the present systems, articles, and methods provide a framework in which a wearable EMG device is programmed with processor-executable instructions that embody (i.e., in accordance with characterization i)) and/or produce/effect (i.e., in accordance with characterization ii)) a mapping from gestures to gesture identification flags, such as exemplary mapping **1600** from FIG. **16**.

[0316] As shown in mapping **1600**, each gesture identification flag may, for example, comprise a bit string (e.g., an 8-bit data byte as illustrated) that uniquely maps to a corresponding gesture performed by a user. For example, a “gun” or “point” hand gesture may correspond/map to gesture identification flag 00000001 as illustrated, a “thumbs up” gesture may correspond/map to gesture identification flag 00000010 as illustrated, a “fist” gesture may correspond/map to gesture identification flag 00000011 as illustrated, and a “rock on” gesture may correspond/map to gesture identification flag 00000100 as illustrated. A person of skill in the art will appreciate that an 8-bit data byte can be used to represent 256 unique gesture identification flags (corresponding to 256 unique gestures). In practice, gesture identification flags having any number of bits may be used, and if desired, multiple gestures may map to the same gesture identification flag and/or the same gesture may map to multiple gesture identification flags. In accordance with the present systems, articles, and methods, a gesture identification flag contains only information that identifies (i.e., maps to) a gesture performed by a user of a wearable EMG device. A gesture identification flag does not contain any information about a function or operation that the corresponding gesture maybe used to control. A gesture identification flag does not contain any information about any downstream electronic device and/or application that the corresponding gesture may be used to control. A gesture identification flag may be appended, adjoined, supplemented, or otherwise combined with additional data bits as needed for, e.g., the purposes of telecommunications.

[0317] Mapping **1600** represents gestures with actual illustrations of hands solely for ease of illustration and description. In practice, a gesture may be represented by any corresponding configuration of signals provided by at least one EMG sensor and/or at least one accelerometer. For example, a gesture may be represented by a particular signal waveform, a particular signal value, or a particular configuration/arrangement/permutation/combination of signal waveforms/values.

[0318] The present systems, articles, and methods describe human-electronics interfaces. Methods **1400** and **1500** provide methods of operating a wearable EMG device to control an unspecified electronic device (e.g., methods of operating device **100** from FIG. **12** or device **1370** from FIG. **13**). A complete human-electronics interface may involve acts performed by both the controller and the receiver (e.g., methods of operating system **1300** from FIG. **13**).

[0319] FIG. **17** is a flow-diagram showing a method **1700** of electromyographically controlling at least one function of an electronic device by a wearable EMG device in accordance with the present systems, articles, and methods. The wearable EMG device includes at least one EMG sensor, a first processor, and an output terminal (with the at least one EMG sensor and the output terminal each communicatively coupled to the first processor) and the electronic device includes an input terminal and a second processor (with the input terminal communicatively coupled to the second processor). Method **1700** includes seven acts **1701**, **1702**, **1703**, **1704**, **1711**, **1712**, and **1713**, though those of skill in the art will appreciate that in alternative embodiments certain acts may be omitted and/or additional acts may be added. Those of skill in the art will also appreciate that the illustrated order of the acts is shown for exemplary purposes only and may change in alternative embodiments. Acts **1701**, **1702**, **1703**, and **1704** are performed by the wearable EMG device to produce and transmit signals and acts **1711**, **1712**, and **1713** are performed by the electronic device to receive and respond to the transmitted signals.

[0320] Acts **1701**, **1702**, **1703**, and **1704** are substantially similar to acts **1401**, **1402**, **1403**, and **1404** (respectively) of method **1400** from FIG. **14**. At **1701**, muscle activity of a user is sensed, measured, transduced or otherwise detected by at least one EMG sensor of the wearable EMG device. At **1702**, at least one signal is provided from the at least one EMG sensor to a first

processor on-board the wearable EMG device in response to the detected muscle activity. At **1703**, the first processor determines a gesture identification flag based at least in part on the at least one signal provided from the at least one EMG sensor to the first processor. At **1704**, the gesture identification flag is transmitted by the output terminal of the wearable EMG device. In some applications, the wearable EMG device may include at least one accelerometer and the wearable EMG device may be used to perform method **1500** from FIG. **15**. Therefore, act **1703** may comprise determining a gesture identification flag based at least in part on both the at least one signal provided from the at least one EMG sensor to the first processor and the at least one signal provided from the at least one accelerometer to the first processor.

[0321] At **1711**, the gesture identification flag that is transmitted or output by the output terminal of the wearable EMG device at **1704** is received by the input terminal of the electronic device. As previously described, transmission of gesture identification flags between the wearable EMG device and the electronic device may be through a wired or wireless communicative link (e.g. communicative link **1390** from FIG. **13**).

[0322] At **1712**, a second processor on-board the electronic device determines a function of the electronic device based at least in part on the gesture identification flag received by the input terminal of the electronic device at **1711**. As described previously, the electronic device may include a non-transitory processor-readable storage medium or memory that stores an API or other information or data structures (e.g., implemented as one or library (ies)) through which a user may define mappings (i.e., processor-executable instructions that embody and/or produce/effect mappings) between gesture identification flags and functions of the electronic device, and/or the non-transitory processor-readable storage medium may store processor-executable instructions that, when executed by the second processor, cause the second processor to determine a function of the electronic device based at least in part on the gesture identification flag.

[0323] At **1713**, the function determined at **1712** is performed by the electronic device. The function may be any function or operation of the electronic device. For example, if the electronic device is an audio and/or video player (or a computer running an application that performs audio and/or video playback), then the corresponding function may be a PLAY function that causes the audio/video to play, a STOP function that causes the audio/video to stop, a REWIND function that causes the audio/video to rewind, a FAST FORWARD function that causes the audio/video to fast forward, and so on.

[0324] Throughout this specification and the appended claims, reference is often made to “determining a function of an electronic device based at least in part on a gesture identification flag.” Unless the specific context requires otherwise, throughout this specification and the appended claims “a” function should be interpreted in a general, inclusive sense as “at least one” function with the understanding that determining any number of functions (e.g., determining one function, or determining multiple functions) includes determining “a” function. Furthermore, “determining” a function by a processor may be achieved through a wide variety of different techniques. For example, a processor may determine a function by employing a defined mapping between gesture identification flags and functions (e.g., by invoking a stored look-up table or other form of stored processor-executable instructions providing defined mappings between gesture identification flags and functions), or a processor may determine a function by performing an algorithm or sequence of data processing steps (e.g., by executing stored processor-executable instructions dictating how to determine a function based at least in part on one or more gesture identification flag(s)).

[0325] FIG. **18** is a schematic illustration showing an exemplary mapping **1800** between a set of exemplary gesture identification flags and a set of exemplary functions of an electronic device in accordance with the present systems, articles, and methods. Similar to mapping **1600** from FIG. **16**, mapping **1800** may be characterized as: i) a prescription for how gesture identification flags are to be mapped to functions by a processor when determining a function based at least in part on a

gesture identification flag received from a wearable EMG device; or ii) the end results when a processor performs an algorithm or series of data processing acts to determine a function based at least in part on a gesture identification flag received from a wearable EMG device. In the former characterization (i.e., characterization i)), mapping **1800** may be stored as a look-up table or set of defined processor-executable “mapping instructions” in a non-transitory processor-readable storage medium and invoked by the processor when determining a function of the electronic device. In the latter characterization (i.e., characterization ii)), mapping **1800** may not be stored in a non-transitory processor-readable storage medium itself, but instead processor-executable instructions to perform an algorithm or series of data processing acts may be stored in the non-transitory processor-readable storage medium and mapping **1800** may represent the results of executing the stored processor-executable instructions by the processor to determine a function of the electronic device. In either case, the present systems, articles, and methods provide a framework in which generic gesture identification flags are output by a wearable EMG device and a receiving device is programmed (and/or programmable through, e.g., an API or other information or data or calls) with processor-executable instructions that embody and/or produce/effect a mapping from gesture identification flags to functions of the electronic device, such as exemplary mapping **1800** from FIG. **18**.

[0326] For the illustrative example of FIG. **18**, the electronic device is an audio player; however, any electronic device may include or be communicatively coupled to (or be adapted to include or be communicatively coupled to) a non-transitory processor-readable storage medium or memory that stores processor-executable instructions that embody and/or produce/effect a mapping such as mapping **1800**. As shown in mapping **1800**, each gesture identification flag may, for example, be a bit string (e.g., an 8-bit data byte as illustrated) that uniquely maps to a corresponding function of the electronic device. For example, a 00000001 gesture identification flag may map/correspond to a REWIND function of an audio player as illustrated, a 00000010 gesture identification flag may map/correspond to a PLAY function of an audio player as illustrated, a 00000011 gesture identification flag may map/correspond to a STOP function of an audio player as illustrated, and a 00000100 gesture identification flag may map/correspond to a FAST FORWARD function of an audio player as illustrated. A person of skill in the art will appreciate that an 8-bit data byte can be used to represent 256 unique gesture identification flags (corresponding to 256 unique functions). In practice, gesture identification flags having any number of bits may be used, multiple gesture identification flags may be mapped to the same function, and/or a single gesture identification flag may map to multiple functions.

[0327] In accordance with the present systems, articles, and methods, processor-executable instructions that embody and/or produce/effect a mapping from gestures to gesture identification flags (e.g., mapping **1600** from FIG. **16**) may be stored in a non-transitory processor-readable storage medium or memory on-board a wearable EMG device (e.g., memory **1241** of device **1200** from FIG. **12**) and communicatively coupled to a first processor (e.g., processor **1240** of device **1200**), and processor-executable instructions that embody and/or produce/effect a mapping from gesture identification flags to functions of an electronic device (e.g., mapping **1800** from FIG. **18**) may be stored in a non-transitory processor-readable storage medium or memory on-board an electronic device (e.g., memory **1382** of device **1380** from FIG. **13**) and communicatively coupled to a second processor (e.g., processor **1383** of device **1380** in FIG. **13**). In this way, gesture identification flags may be determined by the first processor on-board the wearable EMG device based on signals from one or more sensor(s) (e.g., EMG sensors and/or inertial sensors) in accordance with, e.g., mapping **1600** of FIG. **16**; the gesture identification flags may be transmitted or output to a receiving device; and then functions of the receiving device may be determined by the second processor on-board the receiving device based on the gesture identification flags in accordance with, e.g., mapping **1800** from FIG. **18**. For example, signals corresponding to a “gun” or “point” gesture (e.g., outwardly extended index finger with other fingers curled upon

themselves) may be processed by the first processor of the wearable EMG device to determine gesture identification flag 00000001 according to mapping **1600** from FIG. **16**, the 00000001 flag may be transmitted to the electronic device (through a wired or wireless communicative link), and the 00000001 flag may be processed by the second processor of the electronic device to determine a REWIND function in accordance with mapping **1800**.

[0328] In accordance with the present systems, articles, and methods, an electronic device may store multiple mappings (e.g., multiple sets of processor-executable instructions that embody and/or produce/effect mappings) between gesture identification flags and functions of the electronic device, and when the electronic device receives a gesture identification flag it may perform a corresponding function based on the implementation of one of the multiple stored mappings (e.g., one or more of the multiple sets of processor-executable instructions). For example, the electronic device may be a computer such as a desktop computer, a laptop computer, a tablet computer, or the like. The computer may include a non-transitory processor-readable storage medium or memory that stores multiple mappings (e.g., multiple sets of processor-executable instructions that embody and/or produce/effect mappings) between gesture identification flags and functions of the computer (e.g., multiple variants of mapping **1800** from FIG. **18**), with each mapping corresponding to and invoked by a different application executed by the computer. For example, the non-transitory processor-readable storage medium may store a first mapping (e.g., a first set of processor-executable instructions that embody and/or produce/effect a first mapping) between gesture identification flags and functions (e.g., a first variant of mapping **1800** from FIG. **18**) to be invoked by a first application run on the computer, a second mapping (e.g., a second set of processor-executable instructions that embody and/or produce/effect a second mapping) between gesture identification flags and functions (e.g., a second variant of mapping **1800** from FIG. **18**) to be invoked by a second application run on the computer, a third mapping (e.g., a third set of processor-executable instructions that embody and/or produce/effect a third mapping) between gesture identification flags and functions (e.g., a third variant of mapping **1800** from FIG. **18**) to be invoked by a third application run on the computer, and so on. Each of the first, second, and third applications may be any application, including but not limited to: an audio/video playback application, a video game application, a drawing or modeling application, a control application, a communication application, a browsing or navigating applications, and so on. As previously described, the non-transitory processor-readable medium of the computer may store an API or other data or information through which a user may program processor-executable instructions that embody and/or produce/effect any mapping(s) between gesture identification flags and functions of any electronic device (including but not limited to the computer itself). For example, a user may use an API executed by a computer to define processor-executable instructions that embody and/or produce/effect mappings between gesture identification flags and functions of the computer itself (e.g., functions of one or multiple applications executed by the computer itself), or the user may use an API executed by a computer to define processor-executable instructions (such as firmware or embedded software instructions) that are then ported to, installed on, loaded in, or otherwise received by a separate electronic device, where the processor-executable instructions embody and/or produce/effect mappings between gesture identification flags and functions of the separate electronic device. In accordance with the present systems, articles, and methods, virtually any application run on a computer or any other electronic device may be adapted to respond to generic gesture identification flags output by a wearable EMG device. Thus, in some cases, method **1700** may include an additional act performed by the electronic device, the additional act being selecting and/or initializing a specific application of the electronic device (e.g., stored in and/or to be executed by the electronic device) to be controlled by the wearable EMG device. Selecting and/or initializing a specific application of the electronic device may include selecting/initializing a first set of processor-executable instructions that embody and/or produce/effect a first mapping from multiple sets of processor-executable instructions that embody and/or produce/effect multiple

mappings (e.g., one set of processor-executable instructions that embody and/or produce/effect a particular mapping from a plurality of sets of processor-executable instructions that embody and/or produce/effect a plurality of respective mappings).

[0329] In accordance with the present systems, articles, and methods, a wearable EMG device may be used to control multiple electronic devices, or multiple applications within a single electronic device. Such is distinct from known proposals for human-electronics interfaces that employ a wearable EMG device, at least because the known proposals typically store a direct mapping from gestures to functions within the wearable EMG device itself, whereas the present systems, articles, and methods describe an intermediate mapping from gestures (e.g., from EMG and/or accelerometer signals representative of gestures) to gesture identification flags that are stored and executed by the wearable EMG device and then mappings from gesture identification flags to functions that are stored and executed by the downstream electronic device. In accordance with the present systems, articles, and methods, the mapping from gestures to gesture identification flags stored and executed by the wearable EMG device is independent of the downstream electronic device and the same mapping from gestures to gesture identification flags may be stored and executed by the wearable EMG device regardless of the nature and/or function(s) of the downstream electronic device.

[0330] The implementation of gesture identification flags as described herein enables users to employ the same wearable EMG device to control a wide range of electronic devices and/or a wide range of applications within a single electronic device. Since the gesture identification flags output by the wearable EMG device are not tied to any specific functions or commands, a user may define their own mappings (including their own techniques for performing mappings) between gesture identification flags and electronic device functions. For example, a user may adapt the human-electronics interfaces described herein to control virtually any functions of virtually any electronic device (e.g., to control virtually any application executed by a computer) by defining processor-executable instructions that embody and/or produce a corresponding mapping between gesture identification flags and electronic device functions (such as mapping **1800** from FIG. **18**) and establishing automatic execution of the processor-executable instructions by the electronic device in response to receiving gesture identification flags. The processor-executable instructions may be defined for/within the electronic device itself without making any modifications to the wearable EMG device.

[0331] The various embodiments described herein provide human-electronics interfaces in which a wearable EMG device (i.e., a controller) provides generic signal “flags” and a downstream receiving device interprets and responds to the generic flags. The flags provided by the wearable EMG device are substantially independent of any downstream receiving device. In accordance with the present systems, articles, and methods, other forms of controllers (i.e., controllers that are not wearable and/or controllers that do not employ EMG sensors) may similarly be configured to provide generic flags in this way. For example, instead of or in addition to employing EMG sensors and/or accelerometers providing gesture control, a controller that operates in accordance with the present systems, articles, and methods may employ, for example, tactile sensors (e.g., buttons, switches, touchpads, or keys) providing manual control, acoustic sensors providing voice-control, optical/photonic sensors providing gesture control, or any other type(s) of user-activated sensors providing any other type(s) of user-activated control. Thus, the teachings of the present systems, articles, and methods may be applied using virtually any type of controller employing sensors (including gesture-based control devices that do not make use of electromyography or EMG sensors), with the acts described herein as being performed by “at least one EMG sensor” and/or “at least one accelerometer” being more generally performed by “at least one sensor.”

Description for Capacitive EMG Sensors with Improved Robustness Against Variations in Skin and/or Environmental Conditions

[0332] The various embodiments described herein provide systems, articles, and methods for

capacitive EMG sensors with improved robustness against variations in skin and/or environmental conditions. In particular, the present systems, articles, and methods describe capacitive EMG sensor designs that employ at least one capacitive electrode having a protective coating that provides a barrier to moisture and a high relative permittivity ϵ_r . These capacitive EMG sensor designs may be used in any device or method involving capacitive EMG sensing, though they are particularly well-suited for use in applications involving long-term coupling to a user's body over a range of evolving skin and/or environmental conditions. An example application in a wearable EMG device that forms part of a human-electronics interface is described.

[0333] Throughout this specification and the appended claims, the terms “coating” and “coat,” and variants thereof, are used both as nouns and as verbs to indicate a relationship (noun) or the formation of a relationship (verb) in which a layer of material overlies, underlies, or generally “covers” at least a portion of a device or component, either directly or through one or more intervening layers.

[0334] FIG. 19A is a cross-sectional view of an example of an improved capacitive EMG sensor **1900** that provides enhanced robustness against variations in skin and/or environmental conditions in accordance with the present systems, articles, and methods. Exemplary sensor **1900** is a differential capacitive EMG sensor that includes two capacitive sensor electrodes **1921** and **1931**, though the teachings described herein are also applicable to single-ended sensor systems that employ only a single capacitive sensor electrode (i.e., one of sensor electrodes **1921** or **1931**). Differential sensor **1900** comprises a substrate **1901** having a first surface **1901a** and a second surface **1901b** opposite the first surface **1901a** across a thickness of substrate **1901**. First surface **1901a** carries at least a portion of at least one circuit (generally, circuitry **1910**) and second surface **1901b** carries first sensor electrode **1921**, second sensor electrode **1931**, and a ground electrode **1940**. As will be described in more detail later, circuitry **1910** may include at least a portion of at least one electrical or electronic circuit to process signals provided by first and second sensor electrodes **1921**, **1931**, including, for example, at least a portion of at least one amplification circuit, at least a portion of at least one filtering circuit, and/or at least a portion of at least one analog-to-digital conversion circuit.

[0335] First sensor electrode **1921** includes an electrically conductive plate formed of an electrically conductive material (such as, for example, copper or a material including copper) and has a first surface **1921a** and a second surface **1921b**, second surface **1921b** being opposite first surface **1921a** across a thickness of electrode **1921**. First sensor electrode **1921** is carried by second surface **1901b** of substrate **1901** such that first surface **1921a** of first sensor electrode **1921** faces second surface **1901b** of substrate **1901**. Throughout this specification and the appended claims, the terms “carries” and “carried by” are generally used to describe a spatial relationship in which a first layer/component is positioned proximate and physically coupled to a surface of a second layer/component, either directly or through one or more intervening layers/components. For example, circuitry **1910** is carried by first surface **1901a** of substrate **1901** and first sensor electrode **1921** is carried by second surface **1901b** of substrate **1901**. Circuitry **1910** is directly carried by first surface **1901a** of substrate **1901** because there are no intervening layers/components that mediate the physical coupling between circuitry **1910** and first surface **1901a** of substrate **1901**; however, circuitry **1910** would still be considered “carried by” first surface **1901a** of substrate **1901** even if the physical coupling between circuitry **1910** and first surface **1901a** of substrate **1901** was mediated by at least one intervening layer/component. The terms “carries” and “carried by” are not intended to denote a particular orientation with respect to top and bottom and/or left and right.

[0336] First sensor electrode **1921** is communicatively coupled to circuitry **1910** by at least one electrically conductive pathway **1951**, which in the illustrated example of FIG. 19A is realized by a via connection that extends through substrate **1901**.

[0337] In accordance with the present systems, articles, and methods, first sensor electrode **1921** is coated by a dielectric layer **1923** formed of a material that has a relative permittivity ϵ_r of at least

10, and by an adhesive layer **2122** that is sandwiched in between first sensor electrode **1921** and dielectric layer **1923**. Adhesive layer **2122** serves to adhere, affix, or otherwise couple dielectric layer **1923** to the second surface **1921b** of first sensor electrode **1921**, and may comprise, for example, an electrically conductive epoxy or an electrically conductive solder. In other words, adhesive layer **2122** mediates physical and electrical coupling between dielectric layer **1923** and first sensor electrode **1921**. Referring back to the definition of the terms “carries” and “carried by,” both adhesive layer **2122** and dielectric layer **1923** are considered to be carried by second surface **1901b** of substrate **1901**.

[0338] Dielectric layer **1923** may comprise any dielectric material that has a large relative permittivity ϵ_r (e.g., a relative permittivity of about 10 or more, including a relative permittivity of about 10, about 20, about 50, about 1900, about 19000, etc.). Advantageously, dielectric layer **1923** may comprise a ceramic material, such as an X7R ceramic material. Throughout this specification and the appended claims, the term “X7R” refers to the EIA RS-198 standard three-digit code for temperature ranges and inherent change of capacitance. Specifically, the code “X7R” indicates a material that will operate in the temperature range of -55°C . to $+125^\circ\text{C}$. with a change of capacitance of $\pm 15\%$. A person of skill in the art will appreciate that the X7R EIA code is substantially equivalent to “2×1” under the IEC/EN 60384-9/22 standard. Dielectric layer **1923** may comprise a resin and/or ceramic powder such as those used in FaradFlex® products available from Oak-Mitsui Technologies.

[0339] Since capacitive EMG sensor **1900** is differential, it includes a second sensor electrode **1931**. Second sensor electrode **1931** may be substantially similar to first sensor electrode **1921** in that second sensor electrode **1931** includes an electrically conductive plate formed of an electrically conductive material (e.g., a material including copper) that has a first surface **1931a** and a second surface **1931b**, second surface **1931b** being opposite first surface **1931a** across a thickness of electrode **1931**. Second sensor electrode **1931** is carried by second surface **1901b** of substrate **1901** such that first surface **1931a** of second sensor electrode **1931** faces second surface **1901b** of substrate **1901**. Second sensor electrode **1931** is also coated by a dielectric layer **1933** that is substantially similar to dielectric layer **1923**, and dielectric layer **1933** is adhered, affixed, or otherwise coupled to second surface **1931b** of second sensor electrode **1931** by an adhesive layer **1932** that is substantially similar to adhesive layer **2122**. Second sensor electrode **1931** is communicatively coupled to circuitry **1910** by at least one electrically conductive pathway **1952**, which in the illustrated example of FIG. **19A** is realized by a via connection that extends through substrate **1901**. As is the case for the illustrated example of FIG. **19A**, first sensor electrode **1921** and second sensor electrode **1931** may be substantially coplanar.

[0340] Capacitive EMG sensor **1900** also includes a ground electrode **1940**. Ground electrode **1940** includes an electrically conductive plate formed of an electrically conductive material (e.g., the same material that makes up first sensor electrode **1921** and second sensor electrode **1931**) that has a first surface **141a** and a second surface **141b**, second surface **141b** being opposite first surface **141a** across a thickness of electrode **1940**. Ground electrode **1940** is carried by second surface **1901b** of substrate **1901** such that first surface **1940a** of ground electrode **1940** faces second surface **1901b** of substrate **1901**. Ground electrode **1940** is communicatively coupled to circuitry **1910** by at least one electrically conductive pathway **1953**, which in the illustrated example of FIG. **19A** is realized by a via connection that extends through substrate **1901**. Unlike second surface **1921b** of first sensor electrode **1921** and second surface **1931b** of second sensor electrode **1931**, second surface **1940b** of ground electrode **1940** is exposed and not coated by a dielectric layer in order that ground electrode **1940** may advantageously provide a directly electrically coupled (i.e., resistively coupled) path to ground.

[0341] In use, capacitive EMG sensor **1900** is positioned proximate a user's muscle(s) so that dielectric layers **1923**, **1933** and ground electrode **1940** are all in physical contact with the user's skin (or, in some cases, a layer of material such as clothing may mediate physical contact between

sensor **1900** and the user's skin). Dielectric layers **1923, 1933** are advantageously formed of a dielectric material that has a high relative permittivity (e.g., ϵ_r greater than or equal to about 10) in order to enhance the capacitive coupling between sensor electrodes **1921, 1931** and the user's body. For each of first sensor electrode **1921** and second sensor electrode **1931**, the respective capacitance that couples the sensor electrode (**1921, 1931**) to the user's body (e.g., skin) is at least approximately given by equation 1:

[00001] $C = \frac{\epsilon_r \epsilon_0 A}{d}$ (1) [0342] where ϵ_r is the relative permittivity of the dielectric material that coats the sensor electrode (i.e., dielectric layers **1923, 1933**), ϵ_0 is the vacuum permittivity (i.e., a constant value of $8.85211878176 \times 10^{-12}$ F/m), A is the area of the sensor electrode, and d is the distance between the sensor electrode and the user's body. Thus, if A and d are held constant, ϵ_r (i.e., the relative permittivity of dielectric layers **1923, 1933**) directly influences the capacitance between the user's body and each of first sensor electrode **1921** and second sensor electrode **1931**. A large ϵ_r may enable a capacitive EMG sensor to employ smaller sensor electrode area(s) A and/or greater separation d between the sensor electrode(s) and the user's body.

[0343] Dielectric layers **1923, 1933** are advantageously bio-compatible (e.g., non-toxic, etc.) and substantially robust against the corrosive effects of sweat and skin oils. Dielectric layers **1923, 1933** are also advantageously non-absorptive and impermeable to water, sweat, and skin oils. Ideally, dielectric layers **1923, 1933** provide hermetic barriers between the user's skin and first and second sensor electrodes **1921, 1931** such that the presence of sweat, water, and/or skin oils does not substantially degrade the performance of capacitive EMG sensor **1900**.

[0344] Even though dielectric layers **1923, 1933** may protect first sensor electrode **1921** and second sensor electrode **1931** (respectively) from moisture and/or other aspects of the user's skin, such moisture and/or other aspects that may underlie dielectric layers **1923, 1933** (e.g., sweat or skin oils that may mediate coupling between the user's body and dielectric layers **1923, 1933**) may still affect the capacitive coupling between the user's body and first and second sensor electrodes **1921, 1931**. This is a further reason why it is advantageous for dielectric layers **1923, 1933** to be formed of a dielectric material that has a high relative permittivity (i.e., $\epsilon_r \geq 10$): the larger the relative permittivity of dielectric layers **1923, 1933**, the larger the capacitance that couples the user's body to first and second sensor electrodes **1921, 1931** and the smaller the proportionate impact of variations in sweat or skin oil conditions.

[0345] Equation 1 shows that the capacitance C that couples the user's body to first and second sensor electrodes **1921, 1931** is directly proportional to the relative permittivity ϵ_r and inversely proportional to the thickness d of dielectric layers **1923, 1933**. Thus, while it is advantageous for dielectric layers **1923, 1933** to be formed of a dielectric material that has a high relative permittivity ϵ_r , it is similarly advantageous for dielectric layers **1923, 1933** to be relatively thin (i.e., for d to be small). In accordance with the present systems, articles, and methods, the thickness of dielectric layers **1923, 1933** may be, for example, approximately 10 μm or less. Approximately 10 μm or less is sufficiently thick to provide an adequate barrier to moisture (e.g., sweat/oil) and electrical insulation, and sufficiently thin to provide an adequate capacitance C as per equation 1.

[0346] In accordance with the present systems, articles, and methods, ground electrode **1940** is exposed and not coated by a dielectric layer. This is because it is advantageous for ground electrode **1940** to be resistively coupled to the user's body as opposed to capacitively coupled thereto in order to provide a lower impedance for return currents.

[0347] Even though first and second sensor electrodes **1921, 1931** are coated by dielectric layers **1923, 1933** (respectively) and ground electrode **1940** is not coated by a dielectric layer, dielectric layers **1923, 1933** and ground electrode **1940** may all still simultaneously contact a user's skin when capacitive EMG sensor **1900** is positioned on the user. This is because the surface of the user's skin may have a curvature and/or the surface of the user's skin (and/or the flesh thereunder) may be elastic and compressible such that dielectric layers **1923, 1933** can be "pressed" into the

user's skin with sufficient depth to enable physical contact between ground electrode **1940** and the user's skin. While not drawn to scale, in the illustrated example of FIG. **19A**, dielectric layers **1923**, **1933** are still thinner than the electrically conductive plates that form first and second sensor electrodes **1921**, **1931**. For example, dielectric layers **1923**, **1933** may each have a thickness of less than about 10 μm while first and second sensor electrodes **1921**, **1931** may each have a thickness of about 30 μm or more.

[0348] There are many different ways in which dielectric layers **1923**, **1933** may be applied to coat first and second sensor electrodes **1921**, **1931** (respectively) and the specific structural configuration of the corresponding capacitive EMG sensor may vary to reflect this. In exemplary capacitive EMG sensor **1900**, dielectric layers **1923**, **1933** have been individually and separately deposited on first and second sensor electrodes **1921**, **1931** (respectively). This may be achieved by, for example, brushing a liquid or fluid form of the dielectric material that constitutes dielectric layers **1923** and **1933** over second surface **1921b** of first sensor electrode **1921** and second surface **1931b** of second sensor electrode **1931**. In this case, dielectric layers **1923**, **1933** may subsequently be hardened or cured (and adhesive layers **1922**, **1932** may potentially not be required).

Alternatively, individual and separate sections of a substantially solid or non-fluid form of the dielectric material that constitutes dielectric layers **1923** and **1933** may be sized and dimensioned to at least approximately match the respective areas of first and second sensor electrodes **1921**, **1931** and then respective ones of such sections may be deposited on first and second sensor electrodes **1921** and **1931**. For example, a first section of a dielectric material (having a high relative permittivity) may be sized and dimensioned to at least approximately match the area of first sensor electrode **1921** and this first section of the dielectric material may be adhered, affixed, or otherwise coupled to first sensor electrode **1921** by adhesive layer **1922** to form dielectric layer **1923**.

Likewise, a second section of the dielectric material may be sized and dimensioned to at least approximately match the area of second sensor electrode **1931** and adhered, affixed, or otherwise coupled to second sensor electrode **1931** by adhesive layer **1932** to form dielectric layer **1933**.

[0349] As an alternative to the above examples of depositing dielectric layers **1921**, **1931** as individual, separate sections of dielectric material, a single continuous piece of dielectric material may be deposited over second surface **1901b** of substrate **1901**, first and second sensor electrodes **1921**, **1931**, and optionally ground electrode **1940**. In this case, substrate **1901**, first and second sensors electrodes **1921**, **1931**, and dielectric layers **1923**, **1933** may together constitute a laminate structure. In other words, dielectric layers **1923**, **1933** may be applied to first and second sensor electrodes **1921**, **1931** as lamination layers using a lamination process. In fabrication processes in which dielectric material coats ground electrode **1940**, the portion of dielectric material that coats ground electrode may subsequently be removed (e.g., by an etching process) to expose second surface **1940b** of ground electrode **1940**.

[0350] FIG. **19B** is a cross-sectional view of an exemplary laminate version of an improved capacitive EMG sensor **1980** that provides enhanced robustness against variations in skin and/or environmental conditions in accordance with the present systems, articles, and methods. Exemplary sensor **1980** is a differential capacitive EMG sensor that is substantially similar to sensor **1900** from FIG. **19A** in that sensor **1980** includes a substrate **1907** (substantially similar to substrate **1901** from sensor **1900**), circuitry **1915** (substantially similar to circuitry **1910** from sensor **1900**), first and second capacitive sensor electrodes **1927** and **1936** (substantially similar to first and second sensor electrodes **1921** and **1931**, respectively, from sensor **1900**), and ground electrode **1945** (substantially similar to ground electrode **1940** from sensor **1900**). Sensor **1980** also includes a dielectric layer **1950** that coats first and second sensor electrodes **1927**, **1936** in a similar way to dielectric layers **1923**, **1933** from sensor **1900**. Like dielectric layers **1923** and **1933**, dielectric layer **1950** is formed of a dielectric material that has a large relative permittivity (i.e., ϵ_r greater than or equal to about 10). However, unlike dielectric layers **1923** and **1933**, dielectric layer **1950** is deposited as a single continuous layer that coats both first and second sensor electrodes **1927**, **1936**

and also coats at least a portion of substrate **1907**. For example, sensor **1980** may be a laminate structure and dielectric layer **1950** may be deposited using a lamination process. The deposition of dielectric layer **1950** may initially coat ground electrode **1945**, in which case ground electrode **1945** may subsequently be exposed by forming (e.g., etching) a hole **1960** in dielectric layer **1950**. Otherwise, a temporary mask may cover ground electrode **1945** during deposition of dielectric layer **1950** to prevent dielectric layer **1950** from coating ground electrode **1945** and hole **1960** may be left as a result when the mask is subsequently removed.

[0351] Dielectric layer **1950** may be deposited to provide a desired thickness of, for example, less than about 10 μm measured from the interface with first and second sensor electrodes **1927**, **1936**. Though not illustrated in FIG. **19B**, an adhesive layer may be used to adhere, affix, or otherwise couple dielectric layer **1950** to any or all of substrate **1907**, first electrode **1927**, and/or second sensor electrode **1936**.

[0352] Various methods for fabricating an improved capacitive EMG sensor that includes at least one protective, high-er dielectric barrier have been described. These methods are summarized and generalized in FIG. **20**.

[0353] FIG. **20** is a flow-diagram showing a method **2000** of fabricating an improved capacitive EMG sensor (e.g., sensor **1900** and/or sensor **1980**) in accordance with the present systems, articles, and methods. Method **2000** includes four acts **2001**, **2002**, **2003**, and **2004**, though those of skill in the art will appreciate that in alternative embodiments certain acts may be omitted and/or additional acts may be added. Those of skill in the art will also appreciate that the illustrated order of the acts is shown for exemplary purposes only and may change in alternative embodiments.

[0354] At **2001**, at least a portion of at least one circuit is formed on a first surface of a substrate. The at least a portion of at least one circuit may include one or more conductive traces and/or one or more electrical or electronic circuits, such as one or more amplification circuit(s), one or more filtering circuit(s), and/or one or more analog-to-digital conversion circuit(s). As examples, sensor **1900** from FIG. **19A** includes circuitry **1910** and sensor **1980** from FIG. **19B** includes circuitry **1915**. Forming at least a portion of at least one circuit may include one or more lithography process(es) and/or soldering one or more component(s) to the substrate.

[0355] At **2002**, a first sensor electrode is formed on a second surface of the substrate. The first sensor electrode may include an electrically conductive plate formed of, for example, a material including copper. As examples, sensor **1900** from FIG. **19A** includes first sensor electrode **1921** and sensor **1980** from FIG. **19B** includes first sensor electrode **1927**. Forming the first sensor electrode may include, for example, one or more lithography process(es). As previously described, the order of the acts of method **2000** may change. For example, in some cases it may be advantageous to form the first sensor electrode per act **2002** prior to forming the at least a portion of circuitry per act **2001**.

[0356] At **2003**, at least one electrically conductive pathway that communicatively couples the at least a portion of at least one circuit and the first sensor electrode is formed. The at least one electrically conductive pathway may include at least one via through the substrate, at least one conductive trace, and/or at least one wiring component. For example, sensor **1900** includes electrically conductive pathway **1951** that communicatively couples circuitry **1910** to first sensor electrode **1921**. In some implementations, all or a portion of a via (e.g., a hole or aperture with or without electrically conductive communicative path therethrough) may be formed in the substrate before either or both of acts **2001** and/or **2002**.

[0357] At **2004**, the first sensor electrode is coated with a dielectric layer comprising a dielectric material that has a relative permittivity ϵ_r of at least 10. As previously described, the coating may be applied in a variety of different ways, including without limitation: brushing or otherwise applying a fluid form of the dielectric material on the first sensor electrode and curing the dielectric material; adhering, affixing, or otherwise coupling a substantially non-fluid form of the dielectric material to the first sensor electrode using, for example, an adhesive layer such as an electrically

conductive epoxy or an electrically conductive solder; or depositing a single continuous layer of the dielectric material over both the first sensor electrode and at least a portion of the substrate using a lamination process or other dielectric deposition process. When an adhesive layer is used, coating the first sensor electrode with a dielectric layer may include depositing a layer of electrically conductive epoxy on the first sensor electrode and depositing the dielectric layer on the layer of electrically conductive epoxy, or depositing a layer of electrically conductive solder on the first sensor electrode and depositing the dielectric layer on the layer of electrically conductive solder. As examples, sensor **1900** includes dielectric layer **1923** that is adhered to first sensor electrode **1921** by adhesive layer **2122** and sensor **1980** includes dielectric layer **1950** that is deposited over first sensor electrode **1927** and substrate **1907** to form a laminate structure. The dielectric layer may include a ceramic material, such as an X7R ceramic material.

[0358] In addition to acts **2001**, **2002**, **2003**, and **2004**, method **2000** may be extended to include further acts in order to, for example, fabricate some of the additional elements and/or features described for sensors **1900** and **1980**. For example, method **2000** may include forming a second sensor electrode on the second surface of the substrate, forming at least one electrically conductive pathway that communicatively couples the at least a portion of at least one circuit and the second sensor electrode, and coating the second sensor electrode with the dielectric layer (either with a single continuous dielectric layer or with a separate section of the dielectric layer, as described previously). Either separately or in addition to forming a second sensor electrode, method **2000** may include forming a ground electrode on the second surface of the substrate and forming at least one electrically conductive pathway that communicatively couples the ground electrode and the at least a portion of at least one circuit. In this case, coating the first sensor electrode with a dielectric layer per act **2003** may include selectively coating the first sensor electrode with the dielectric layer and not coating the ground electrode with the dielectric layer, or coating both the first sensor electrode and the ground electrode with the dielectric layer and then forming a hole in the dielectric layer to expose the ground electrode.

[0359] The improved capacitive EMG sensors described herein may be implemented in virtually any system, device, or process that makes use of capacitive EMG sensors; however, the improved capacitive EMG sensors described herein are particularly well-suited for use in EMG devices that are intended to be worn by (or otherwise coupled to) a user for an extended period of time and/or for a range of different skin and/or environmental conditions. As an example, the improved capacitive EMG sensors described herein may be implemented in a wearable EMG device that provides gesture-based control in a human-electronics interface. Some details of exemplary wearable EMG devices that may be adapted to include at least one improved capacitive EMG sensor from the present systems, articles, and methods are described in, for example, U.S. patent application Ser. No. 16/550,905, U.S. Pat. Nos. 10,429,928, 10,101,809, 10,042,422; U.S. patent application Ser. No. 14/186,889, U.S. patent application Ser. No. 14/194,252, U.S. patent application Ser. No. 14/335,668; U.S. Pat. No. 10,152,082; U.S. patent application Ser. No. 14/461,044, U.S. patent application Ser. No. 14/465,194, U.S. Pat. Nos. 9,483,123, and 9,389,694, all of which are incorporated herein by reference in their entirety.

[0360] Throughout this specification and the appended claims, the term “gesture” is used to generally refer to a physical action (e.g., a movement, a stretch, a flex, a pose, etc.) performed or otherwise effected by a user. Any physical action performed or otherwise effected by a user that involves detectable muscle activity (detectable, e.g., by at least one appropriately positioned EMG sensor) may constitute a gesture in the present systems, articles, and methods.

[0361] FIG. **21** is a perspective view of an exemplary wearable EMG device **2100** that includes improved capacitive EMG sensors in accordance with the present systems, articles, and methods. Exemplary wearable EMG device **2100** may, for example, form part of a human-electronics interface. Exemplary wearable EMG device **2100** is an armband designed to be worn on the forearm of a user, though a person of skill in the art will appreciate that the teachings described

herein may readily be applied in wearable EMG devices designed to be worn elsewhere on the body of the user, including without limitation: on the upper arm, wrist, hand, finger, leg, foot, torso, or neck of the user.

[0362] Device **2100** includes a set of eight pod structures **2101**, **2102**, **2103**, **2104**, **2105**, **2106**, **2107**, and **2108** that form physically coupled links of the wearable EMG device **2100**. Each pod structure in the set of eight pod structures **2101**, **2102**, **2103**, **2104**, **2105**, **2106**, **2107**, and **2108** is positioned adjacent and in between two other pod structures in the set of eight pod structures such that the set of pod structures forms a perimeter of an annular or closed loop configuration. For example, pod structure **2101** is positioned adjacent and in between pod structures **2102** and **2108** at least approximately on a perimeter of the annular or closed loop configuration of pod structures, pod structure **2102** is positioned adjacent and in between pod structures **2101** and **2103** at least approximately on the perimeter of the annular or closed loop configuration, pod structure **2103** is positioned adjacent and in between pod structures **2102** and **2104** at least approximately on the perimeter of the annular or closed loop configuration, and so on. Each of pod structures **2101**, **2102**, **2103**, **2104**, **2105**, **2106**, **2107**, and **2108** is physically coupled to the two adjacent pod structures by at least one adaptive coupler (not visible in FIG. **21**). For example, pod structure **2101** is physically coupled to pod structure **2108** by an adaptive coupler and to pod structure **2102** by an adaptive coupler. The term “adaptive coupler” is used throughout this specification and the appended claims to denote a system, article or device that provides flexible, adjustable, modifiable, extendable, extensible, or otherwise “adaptive” physical coupling. Adaptive coupling is physical coupling between two objects that permits limited motion of the two objects relative to one another. An example of an adaptive coupler is an elastic material such as an elastic band. Thus, each of pod structures **2101**, **2102**, **2103**, **2104**, **2105**, **2106**, **2107**, and **2108** in the set of eight pod structures may be adaptively physically coupled to the two adjacent pod structures by at least one elastic band. The set of eight pod structures may be physically bound in the annular or closed loop configuration by a single elastic band that couples over or through all pod structures or by multiple separate elastic bands that couple between adjacent pairs of pod structures or between groups of adjacent pairs of pod structures. Device **2100** is depicted in FIG. **21** with the at least one adaptive coupler completely retracted and contained within the eight pod structures **2101**, **2102**, **2103**, **2104**, **2105**, **2106**, **2107**, and **2108** (and therefore the at least one adaptive coupler is not visible in FIG. **21**).

[0363] Throughout this specification and the appended claims, the term “pod structure” is used to refer to an individual link, segment, pod, section, structure, component, etc. of a wearable EMG device. For the purposes of the present systems, articles, and methods, an “individual link, segment, pod, section, structure, component, etc.” (i.e., a “pod structure”) of a wearable EMG device is characterized by its ability to be moved or displaced relative to another link, segment, pod, section, structure component, etc. of the wearable EMG device. For example, pod structures **2101** and **2102** of device **2100** can each be moved or displaced relative to one another within the constraints imposed by the adaptive coupler providing adaptive physical coupling therebetween. The desire for pod structures **2101** and **2102** to be movable/displaceable relative to one another specifically arises because device **2100** is a wearable EMG device that advantageously accommodates the movements of a user and/or different user forms.

[0364] Device **2100** includes eight pod structures **2101**, **2102**, **2103**, **2104**, **2105**, **2106**, **2107**, and **2108** that form physically coupled links thereof. Wearable EMG devices employing pod structures (e.g., device **2100**) are used herein as exemplary wearable EMG device designs, while the present systems, articles, and methods may be applied to wearable EMG devices that do not employ pod structures (or that employ any number of pod structures). Thus, throughout this specification, descriptions relating to pod structures (e.g., functions and/or components of pod structures) should be interpreted as being applicable to any wearable EMG device design, even wearable EMG device designs that do not employ pod structures (except in cases where a pod structure is specifically

recited in a claim).

[0365] In exemplary device **2100** of FIG. **21**, each of pod structures **2101**, **2102**, **2103**, **2104**, **2105**, **2106**, **2107**, and **2108** comprises a respective housing having a respective inner volume. Each housing may be formed of substantially rigid material and may be optically opaque. Throughout this specification and the appended claims, the term “rigid” as in, for example, “substantially rigid material,” is used to describe a material that has an inherent tendency to maintain or restore its shape and resist malformation/deformation under the moderate stresses and strains typically encountered by a wearable electronic device.

[0366] Details of the components contained within the housings (i.e., within the inner volumes of the housings) of pod structures **2101**, **2102**, **2103**, **2104**, **2105**, **2106**, **2107**, and **2108** are not necessarily visible in FIG. **21**. To facilitate descriptions of exemplary device **2100**, some internal components are depicted by dashed lines in FIG. **21** to indicate that these components are contained in the inner volume(s) of housings and may not normally be actually visible in the view depicted in FIG. **21**, unless a transparent or translucent material is employed to form the housings. For example, any or all of pod structures **2101**, **2102**, **2103**, **2104**, **2105**, **2106**, **2107**, and/or **2108** may include circuitry (i.e., electrical and/or electronic circuitry). In FIG. **21**, a first pod structure **2101** is shown containing circuitry **2111** (i.e., circuitry **2111** is contained in the inner volume of the housing of pod structure **2101**), a second pod structure **2102** is shown containing circuitry **2112**, and a third pod structure **2108** is shown containing circuitry **2118**. The circuitry in any or all pod structures may be communicatively coupled to the circuitry in at least one other pod structure by at least one communicative pathway (e.g., by at least one electrically conductive pathway and/or by at least one optical pathway). For example, FIG. **21** shows a first set of communicative pathways **2121** providing communicative coupling between circuitry **2118** of pod structure **2108** and circuitry **2111** of pod structure **2101**, and a second set of communicative pathways **2122** providing communicative coupling between circuitry **2111** of pod structure **2101** and circuitry **2112** of pod structure **2102**.

[0367] Throughout this specification and the appended claims the term “communicative” as in “communicative pathway,” “communicative coupling,” and in variants such as “communicatively coupled,” is generally used to refer to any engineered arrangement for transferring and/or exchanging information. Exemplary communicative pathways include, but are not limited to, electrically conductive pathways (e.g., electrically conductive wires, electrically conductive traces), magnetic pathways (e.g., magnetic media), and/or optical pathways (e.g., optical fiber), and exemplary communicative couplings include, but are not limited to, electrical couplings, magnetic couplings, and/or optical couplings.

[0368] Each individual pod structure within a wearable EMG device may perform a particular function, or particular functions. For example, in device **2100**, each of pod structures **2101**, **2102**, **2103**, **2104**, **2105**, **2106**, and **2107** includes a respective improved capacitive EMG sensor **2110** (only one called out in FIG. **21** to reduce clutter) in accordance with the present systems, articles, and methods. Each improved capacitive EMG sensor **2110** is responsive to muscle activity corresponding to a gesture performed by a user of wearable EMG device **2100**. Thus, each improved capacitive EMG sensor **2110** is included in device **2100** to detect muscle activity of a user and to provide electrical signals in response to the detected muscle activity. Thus, each of pod structures **2101**, **2102**, **2103**, **2104**, **2105**, **2106**, and **2107** may be referred to as a respective “sensor pod.” Throughout this specification and the appended claims, the term “sensor pod” is used to denote an individual pod structure that includes at least one sensor to detect muscle activity of a user.

[0369] Pod structure **2108** of device **2100** includes a processor **2130** that processes the signals provided by the improved capacitive EMG sensors **2110** of sensor pods **2101**, **2102**, **2103**, **2104**, **2105**, **2106**, and **2107** in response to detected muscle activity. Pod structure **2108** may therefore be referred to as a “processor pod.” Throughout this specification and the appended claims, the term

“processor pod” is used to denote an individual pod structure that includes at least one processor to process signals. The processor may be any type of processor, including but not limited to: a digital microprocessor or microcontroller, an application-specific integrated circuit (ASIC), a field-programmable gate array (FPGA), a digital signal processor (DSP), a graphics processing unit (GPU), a programmable gate array (PGA), a programmable logic unit (PLU), or the like, that analyzes or otherwise processes the signals to determine at least one output, action, or function based on the signals. A person of skill in the art will appreciate that implementations that employ a digital processor (e.g., a digital microprocessor or microcontroller, a DSP, etc.) may advantageously include a non-transitory processor-readable storage medium or memory communicatively coupled thereto and storing processor-executable instructions that control the operations thereof, whereas implementations that employ an ASIC, FPGA, or analog processor may or may optionally not include a non-transitory processor-readable storage medium, or may include on-board registers or other non-transitory storage structures.

[0370] As used throughout this specification and the appended claims, the terms “sensor pod” and “processor pod” are not necessarily exclusive. A single pod structure may satisfy the definitions of both a “sensor pod” and a “processor pod” and may be referred to as either type of pod structure. For greater clarity, the term “sensor pod” is used to refer to any pod structure that includes a sensor and performs at least the function(s) of a sensor pod, and the term processor pod is used to refer to any pod structure that includes a processor and performs at least the function(s) of a processor pod. In device **2100**, processor pod **2108** includes an improved capacitive EMG sensor **2110** (not visible in FIG. **21**) responsive to (i.e., to sense, measure, transduce or otherwise detect and provide one or more signal(s) in response to sensing, measuring, transducing, or otherwise detecting) muscle activity of a user, so processor pod **2108** could be referred to as a sensor pod. However, in exemplary device **2100**, processor pod **2108** is the only pod structure that includes a processor **2130**, thus processor pod **2108** is the only pod structure in exemplary device **2100** that can be referred to as a processor pod. The processor **2130** in processor pod **2108** also processes the EMG signals provided by the improved capacitive EMG sensor **2110** of processor pod **2108**. In alternative embodiments of device **2100**, multiple pod structures may include processors, and thus multiple pod structures may serve as processor pods. Similarly, some pod structures may not include sensors, and/or some sensors and/or processors may be laid out in other configurations that do not involve pod structures.

[0371] In device **2100**, processor **2130** includes and/or is communicatively coupled to a non-transitory processor-readable storage medium or memory **2140**. Memory **2140** may store processor-executable gesture identification instructions and/or data that, when executed by processor **2130**, cause processor **2130** to process the EMG signals from improved capacitive EMG sensors **2110** and identify a gesture to which the EMG signals correspond. For communicating with a separate electronic device (not shown), wearable EMG device **2100** includes at least one communication terminal. Throughout this specification and the appended claims, the term “communication terminal” is generally used to refer to any physical structure that provides a telecommunications link through which a data signal may enter and/or leave a device. A communication terminal represents the end (or “terminus”) of communicative signal transfer within a device and the beginning of communicative signal transfer to/from an external device (or external devices). As examples, device **2100** includes a first communication terminal **2151** and a second communication terminal **2152**. First communication terminal **2151** includes a wireless transmitter (i.e., a wireless communication terminal) and second communication terminal **2152** includes a tethered connector port **2152**. Wireless transmitter **2151** may include, for example, a Bluetooth® transmitter (or similar) and connector port **2152** may include a Universal Serial Bus port, a mini-Universal Serial Bus port, a micro-Universal Serial Bus port, a SMA port, a THUNDERBOLT® port, or the like.

[0372] For some applications, device **2100** may also include at least one inertial sensor **2160** (e.g.,

an inertial measurement unit, or “IMU,” that includes at least one accelerometer and/or at least one gyroscope) responsive to (i.e., to detect, sense, or measure and provide one or more signal(s) in response to detecting, sensing, or measuring) motion effected by a user and provide signals in response to the detected motion. Signals provided by inertial sensor **2160** may be combined or otherwise processed in conjunction with signals provided by improved capacitive EMG sensors **2110**.

[0373] As previously described, each of pod structures **2101**, **2102**, **2103**, **2104**, **2105**, **2106**, **2107**, and **2108** may include circuitry (i.e., electrical and/or electronic circuitry). FIG. **21** depicts circuitry **2111** inside the inner volume of sensor pod **2101**, circuitry **2112** inside the inner volume of sensor pod **2102**, and circuitry **2118** inside the inner volume of processor pod **2118**. The circuitry in any or all of pod structures **2101**, **2102**, **2103**, **2104**, **2105**, **2106**, **2107** and **2108** (including circuitries **2111**, **2112**, and **2118**) may include any or all of: an amplification circuit to amplify electrical signals provided by at least one EMG sensor **2110**, a filtering circuit to remove unwanted signal frequencies from the signals provided by at least one EMG sensor **2110**, and/or an analog-to-digital conversion circuit to convert analog signals into digital signals. Device **2100** may also include at least one battery (not shown in FIG. **21**) to provide a portable power source for device **2100**.

[0374] Each of EMG sensors **2110** includes a respective improved capacitive EMG sensor per the present systems, articles, and methods, such as for example sensor **1900** from FIG. **19A** or sensor **1980** from FIG. **2**. In particular, each EMG sensor **2110** includes a respective first capacitive sensor electrode **2171** (only one called out to reduce clutter) that is coated with a dielectric layer formed of a dielectric material having a relative permittivity greater than or equal to about 10, a second capacitive sensor electrode **2172** (only one called out to reduce clutter) that is also coated with a dielectric layer formed of a dielectric material having a relative permittivity greater than or equal to about 10, and a ground electrode **2173** (only one called out to reduce clutter) that is exposed and not coated by a dielectric layer. Each the electrodes **2171**, **2172**, and **2173** of each EMG sensor **2110** may be carried by a respective substrate, and the respective circuitry (e.g., **2111**, **2112**, and **2118**) of each pod structure **2101**, **2102**, **2103**, **2104**, **2105**, **2106**, **2107**, and **2108** may be carried by the same substrate. For example, each respective EMG sensor **2110** of each pod structure **2101**, **2102**, **2103**, **2104**, **2105**, **2106**, **2107**, and **2108** may include a respective substrate, with the circuitry **2111**, **2112**, **2118** of each pod structure **2101**, **2102**, **2103**, **2104**, **2105**, **2106**, **2107**, and **2108** carried by a first surface of the substrate and the first and second sensor electrodes **2171**, **2172** and the ground electrode **2173** carried by a second surface of the substrate, the second surface being opposite the first surface.

[0375] The improved capacitive EMG sensors **2110** of wearable EMG device **2100** are differential sensors that each implement two respective sensor electrodes **2171**, **2172**, though the teachings herein may similarly be applied to wearable EMG devices that employ single-ended improved capacitive EMG sensors that each implement a respective single sensor electrode.

[0376] Signals that are provided by improved capacitive EMG sensors **2110** in device **2100** are routed to processor pod **2108** for processing by processor **2130**. To this end, device **2100** employs a set of communicative pathways (e.g., **2121** and **2122**) to route the signals that are output by sensor pods **2101**, **2102**, **2103**, **2104**, **2105**, **2106**, and **2107** to processor pod **2108**. Each respective pod structure **2101**, **2102**, **2103**, **2104**, **2105**, **2106**, **2107**, and **2108** in device **2100** is communicatively coupled to, over, or through at least one of the two other pod structures between which the respective pod structure is positioned by at least one respective communicative pathway from the set of communicative pathways. Each communicative pathway (e.g., **2121** and **2122**) may be realized in any communicative form, including but not limited to: electrically conductive wires or cables, ribbon cables, fiber-optic cables, optical/photonics waveguides, electrically conductive traces carried by a rigid printed circuit board, electrically conductive traces carried by a flexible printed circuit board, and/or electrically conductive traces carried by a stretchable printed circuit board.

[0377] Device **2100** from FIG. **21** represents an example of a wearable EMG device that incorporates the teachings of the present systems, articles, and methods, though the teachings of the present systems, articles, and methods may be applicable to any wearable EMG device that includes at least one EMG sensor.

[0378] In accordance with the present systems, articles, and methods, a capacitive EMG sensor may be fabricated directly on a substrate that has a high relative permittivity ϵ_r , such as on a ceramic substrate. For example, referring back to sensor **1980** of FIG. **19B** using this alternative fabrication approach (which results in re-defining some of the labelled elements of FIG. **19B**), a capacitive EMG sensor **1980** may comprise: a substrate **1950** that is formed of a material that has a high relative permittivity (i.e., ϵ_r greater than or equal to about 10) such as a ceramic material including but not limited to an X7R ceramic material, at least one sensor electrode **1927**, **1936** deposited on and carried by the substrate **1950**, a dielectric layer **1907** deposited on and carried by the at least one sensor electrode **1927**, **1936** and the substrate **1950**, circuitry **1915** deposited on and carried by the dielectric layer **1907**, and one or more electrically conductive pathway(s) (e.g., via(s)) that communicatively couple the circuitry **1915** to the at least one sensor electrode **1927**, **1936**. In this case, the substrate **1950** may be thin (e.g., with a thickness of about 10 μm or less) and/or the at least one sensor electrode **1927**, **1936** may be deposited on the substrate **1950** by first etching a trench into the substrate **1950** (to a depth that leaves a thickness of 10 μm or less of substrate material **1950** beneath the trench) and then filling the trench with the sensor electrode material. If the sensor **1980** further includes a ground electrode **1945**, a hole **1960** may be etched in the substrate **1950** to expose the ground electrode **1945**.

Description for Improved Capacitive EMG Sensors that Resistively Couple to the User's Body

[0379] The various embodiments described herein provide systems, articles, and methods for surface EMG sensors that improve upon existing resistive and capacitive EMG sensor designs. The surface EMG sensors described herein may be understood as hybrid surface EMG sensors that incorporate elements from both resistive EMG sensors and capacitive EMG sensors. In particular, the present systems, articles, and methods describe capacitive EMG sensors that employ at least one sensor electrode that resistively couples to the user's body (e.g., skin) and at least one discrete component capacitor that interrupts the signal path between the at least one sensor electrode and the sensor circuitry. In this way, the capacitive element of the capacitive EMG sensor remains but is essentially moved downstream in the sensor circuit, affording many benefits discussed in detail below. An example application in a wearable EMG device that forms part of a human-electronics interface is also described.

[0380] Throughout this specification and the appended claims, the term “capacitive EMG sensor” is used to describe a surface EMG sensor in which communicative coupling between the user's body (e.g., skin) and the sensor circuitry is mediated by at least one capacitive element such that the sensor circuitry is galvanically isolated from the body of the user. In the art, this at least one capacitive element is typically realized at the sensor electrode by configuring the sensor electrode to capacitively couple to the user's skin (e.g., by coating the electrically conductive plate of the sensor electrode with a thin layer of dielectric material). In accordance with the present systems, articles, and methods, the at least one capacitive element may be moved downstream in the sensor such that the sensor electrode resistively/galvanically couples to the user's skin but at least one discrete component capacitor mediates communicative coupling between the sensor electrode and the sensor circuitry.

[0381] For comparison purposes, the elements of a capacitive EMG sensor that implements a sensor electrode that capacitively couples to the user's skin are first described.

[0382] FIG. **22** is a schematic diagram of a capacitive EMG sensor **2200** that employs sensor electrodes **2201 a**, **2201 b** that are configured to capacitively couple to the skin of a user. Sensor **2200** is a differential capacitive EMG sensor that employs two sensor electrodes **2201 a**, **2201 b** as described in, for example, U.S. patent application Ser. No. 14/194,252 which is incorporated by

reference herein in its entirety. However, a person of skill in the art will appreciate that the basic description of sensor **2200** herein is also applicable to single-ended sensor systems that employ only a single sensor electrode (i.e., one of sensor electrodes **2201 a** or **2201 b**). Sensor electrodes **2201 a** and **2201 b** each comprise a respective electrically conductive plate **2271 a**, **2271 b** coated with a respective layer of dielectric material **2272 a**, **2272 b**. Sensor **2200** also includes a ground electrode **2240** that comprises an electrically conductive plate that is exposed (i.e., not coated with dielectric material) so that ground electrode **2240** resistively couples to the user's skin as described in U.S. Pat. No. 10,042,422, which is incorporated herein by reference in its entirety.

[0383] Sensor **2200** includes circuitry that comprises, at least: electrically conductive pathways **2211 a**, **2211 b**, **2212**, **2213 a**, **2213 b**; resistors **2230 a**, **2230 b**; and amplifier **2250**. First sensor electrode **2201 a** is communicatively coupled to amplifier **2250** through electrically conductive pathway **2211 a** and to ground electrode **2240** through a path that comprises electrically conductive pathway **2213 a**, resistor **2230 a**, and electrically conductive pathway **2212**. Second sensor electrode **2201 b** is communicatively coupled to amplifier **2250** through electrically conductive pathway **2211 b** and to ground electrode **2240** through a path that comprises electrically conductive pathway **2213 b**, resistor **2230 b**, and electrically conductive pathway **2212**.

[0384] Sensor **2200** is a capacitive EMG sensor in the traditional sense because it implements sensor electrodes **2201 a**, **2201 b** that are configured to capacitively couple to the skin of the user. Amplifier **2250** is galvanically isolated from the user's skin by the dielectric layers **2272 a**, **2272 b** that coat sensor electrodes **2201 a**, **2201 b**, respectively. As discussed previously, this galvanic isolation is advantageous, at least because it prevents DC voltage(s) from coupling to amplifier **2250** and prevents voltage(s) from being applied to the user's skin. However, the capacitive coupling to the skin through sensor electrodes **2201 a**, **2201 b** introduces a relatively large impedance between the user's skin and amplifier **2250**. This impedance imposes stringent requirements on amplifier **2250** and, ultimately, increases the cost of amplifier **2250** in sensor **2200**. Furthermore, the magnitude of the capacitive coupling between sensor electrodes **2201 a**, **2201 b** and the user's skin is highly dependent on parameters such as skin conductance, skin moisture/sweat levels, hair density, and so on, all of which can vary considerably from user to user (and even in different scenarios for the same user, such as at different levels of physical activity). Thus, even though the galvanic isolation realized by dielectric layers **2272 a** and **2272 b** is desirable in a surface EMG sensor, capacitive coupling between sensor electrodes **2201 a**, **2201 b** and the user's skin has undesirable consequences. In accordance with the present systems, articles, and methods, the benefits of galvanically isolating the amplifier (e.g., **2250**) from the user's skin may be realized without the drawbacks of capacitively coupling the sensor electrode(s) to the user's skin by a capacitive EMG sensor design in which the capacitive interruption between the user's skin and the amplifier is moved downstream in the sensor circuit and realized by a discrete component capacitor coupled in between a resistive sensor electrode and an amplification circuit.

[0385] FIG. **23** is a schematic diagram of a capacitive EMG sensor **2300** employing sensor electrodes **2301 a**, **2301 b** that are adapted to, in use, resistively couple to the body (e.g., skin) of a user in accordance with the present systems, articles, and methods. Each of sensor electrodes **2301 a** and **2301 b** comprises a respective plate of electrically conductive material, but unlike electrodes **2201 a** and **2201 b** from sensor **2200**, electrodes **2301 a** and **2301 b** are not coated with dielectric material. Instead, each of electrodes **2301 a** and **2301 b** includes a respective bare/exposed electrically conductive surface to directly physically contact the user's skin during use. Thus, capacitive EMG sensor **2300** implements sensor electrodes **2301 a**, **2301 b** that resemble the sensor electrodes that would typically be found in a resistive EMG sensor. However, in accordance with the present systems, articles, and methods, sensor **2300** is still a capacitive EMG sensor because sensor **2300** includes discrete component capacitors **2321 a** and **2321 b** that galvanically isolate the rest of the sensor circuitry from the user's body (e.g., skin).

[0386] Sensor **2300** is illustrated as a differential capacitive EMG sensor that employs a first sensor

electrode **2301 a** and a second sensor electrode **2301 b**, though a person of skill in the art will appreciate that the description of sensor **2300** herein is also applicable to single-ended sensor systems that employ only a single sensor electrode (i.e., one of sensor electrodes **2301 a** or **2301 b**). [0387] Sensor **2300** includes an amplification circuit (i.e., an amplifier) **2350**. First sensor electrode **2301 a** is communicatively coupled to amplifier **2350** by a first electrically conductive pathway **2311 a**. A first capacitor **2321 a** is electrically coupled in series between first sensor electrode **2301 a** and amplifier **2350** in first electrically conductive pathway **2311 a**. First capacitor **2321 a** galvanically isolates amplifier **2350** from the user's body (e.g., skin) and thereby affords some of the benefits typically associated with a capacitive EMG sensor (i.e., capacitor **2321 a** prevents DC voltage(s) from coupling to amplifier **2350** and prevents voltage(s) from being applied to the user's skin). While a traditional capacitive EMG sensor achieves this galvanic isolation by capacitively coupling to the user's skin at the sensor electrode (e.g., as per sensor electrode **2201 a** from sensor **2200**), in sensor **2300** electrode **2301 a** is resistively coupled to the user's skin and galvanic isolation is moved downstream to discrete component capacitor **2321 a**. As previously described, resistive coupling to the user's skin as per electrode **2301 a** from sensor **2300** provides a lower impedance between the user's skin and amplifier **2350** than capacitive coupling to the user's skin as in electrode **2201 a** from sensor **2200**, and this lower impedance simplifies and lowers the cost of amplifier **2350** in sensor **2300** compared to amplifier **2250** in sensor **2200**. Furthermore, because capacitor **2321 a** is a discrete component, the magnitude of its capacitance can be selected and will remain essentially constant from user to user, regardless of variations such as skin conductance, moisture/sweat levels, hair density, and so on. An example implementation may employ, as capacitors **2321 a** (and similarly as capacitor **2321 b**), a discrete component capacitor having a magnitude of about 2200 nF. Typical capacitive coupling between a dielectric-coated cEMG sensor and a user's skin is significantly less than this, thus 2200 nF may dominate the range of variations in skin: electrode capacitance typically seen in cEMG across different users and/or use conditions. The incorporation of a discrete component capacitor **2321 a** in lieu of condition-dependent capacitive coupling between the electrode and the user's skin is very easy and inexpensive to manufacture and provides an essentially fixed capacitance to which the rest of the sensor circuitry may be tuned for improved performance.

[0388] In addition to first capacitor **2321 a**, sensor **2300** also includes a first resistor **2331 a** that is electrically coupled in series between first sensor electrode **2301 a** and amplifier **2350** in first electrically conductive pathway **2311 a**. Similar to first capacitor **2321 a**, first resistor **2331 a** may be a discrete electronic component with a magnitude that can be selected, accurately embodied, and held substantially constant during use. In the illustrated example of FIG. 23, first capacitor **2321 a** and first resistor **2331 a** are electrically coupled in series with one another in first electrically conductive pathway **2311 a**. First resistor **2331 a** is included, at least in part, to dominate the impedance between electrode **2301 a** and the user's skin such that variations in the impedance between electrode **2301 a** and the user's skin due to fluctuations in skin and/or environmental conditions (e.g., skin conductance, moisture/sweat levels, hair density, etc.) are rendered essentially negligible. For example, fluctuations in skin and/or environmental conditions may cause the impedance between electrode **2301 a** and the user's skin to vary by a magnitude of on the order of 1 Ω , 10 Ω , 100 Ω , or 1000 Ω , but first resistor **2331 a** may be selected to have a resistance of on the order of at least 1 k Ω , at least 10 k Ω , at least 100 k Ω , or more such that the impedance of first resistor **2331 a** dominates the impedance (and, more specifically, dominates variations in the impedance) between sensor electrode **2301 a** and the user's skin. The sensor circuitry, including amplifier **2350**, may be tuned to accommodate the relatively large impedance of first resistor **2331 a** such that the relatively small variations in the impedance between sensor electrode **2301 a** and the user's skin from user to user (and/or under different use conditions for the same user) have a diminished effect on the performance of sensor **2300**. First resistor **2331 a** also serves to limit current into amplifier **2350** and thereby improves the ESD protection of amplifier **2350**.

[0389] The amplifier(s) used in the capacitive EMG sensors described herein may include one or more of various types of amplifier(s), including one or more instrumentation amplifier(s) and/or one or more single or dual operational amplifier(s), depending, for example, on whether the EMG sensor is single-ended or differential. As sensor **2300** is differential, amplifier **2350** may include a dual operational amplifier (e.g., a “two-op-amp instrumentation amplifier”) such as the MAX9916 or the MAX9917, both available from Maxim Integrated, or any of various other amplifier configurations, including but not limited to amplifiers embodied in integrated circuits. A person of skill in the art will appreciate that the output(s) and/or some of the inputs of amplifier **2350** may be connected through various resistor configurations for at least the purpose of determining the gain of amplifier **2350**.

[0390] Sensor **2300** includes a second electrically conductive pathway **2312** that communicatively couples to ground through a ground electrode **2340**. Ground electrode **2340** comprises a plate of electrically conductive material that resistively couples to the user's skin. As sensor **2300** is differential, ground electrode **2340** may not necessarily be used as a reference potential but may primarily provide a path for electrical currents to return to the user's body (e.g., skin). Using second electrically conductive pathway **2312**, together with first capacitor **2321 a** and first resistor **2331 a**, circuitry connected to first sensor electrode **2301 a** also includes both a low-pass filtering configuration and a high-pass filtering configuration “in front of” or upstream of amplifier **2350** in a direction in which signals pass. Specifically, sensor **2300** includes a third electrically conductive pathway **2313 a** that communicatively couples first electrically conductive pathway **2311 a** and second electrically conductive pathway **2312**. Third electrically conductive pathway **2313 a** includes a second capacitor **2322 a** electrically coupled in between first electrically conductive pathway **2311 a** and second electrically conductive pathway **2312**. The configuration of first resistor **2331 a** and second capacitor **2322 a** (with respect to sensor electrode **2301 a**, amplifier **2350**, and ground electrode **2340**) forms a low-pass filtering circuit. As an example, when first resistor **2331 a** has a magnitude of about 100 k Ω , second capacitor **2322 a** may have a magnitude of about 10 pF in order to provide desirable low-pass filtering performance. Similarly, sensor **2300** includes a fourth electrically conductive pathway **2314 a** that communicatively couples first electrically conductive pathway **2311 a** and second electrically conductive pathway **2312**. Fourth electrically conductive pathway **2314 a** includes a second resistor **2332 a** electrically coupled in between first electrically conductive pathway **2311 a** and second electrically conductive pathway **2312**. The configuration of first capacitor **2321 a** and second resistor **2332 a** (with respect to sensor electrode **2301 a**, amplifier **2350**, and ground electrode **2340**) forms a high-pass filtering circuit.

[0391] In comparing sensor **2300** from FIG. 23 to sensor **2200** from FIG. 22, second resistor **2332 a** in sensor **2300** is similar in position and function to resistor **2230 a** in sensor **2200**. The magnitude of a resistor in this position (i.e., the magnitude of second resistor **2332 a** in sensor **2300** or resistor **2230 a** in sensor **2200**) directly influences the filtering performance of the corresponding high-pass filter; however, as the magnitude of a resistor in this position increases, the stability of the circuit may degrade and more noise may appear. This introduces a further benefit of first capacitor **2321 a** in sensor **2300**: first capacitor **2321 a** compensates for a decrease in the magnitude of second resistor **2332 a** and thereby allows a lower-magnitude resistor to be used for second resistor **2332 a** in sensor **2300** compared to resistor **2230 a** in sensor **2200**. The lower magnitude of second resistor **2332 a** in sensor **2300** compared to resistor **2230 a** in sensor **2200** results in both reduced noise and enhanced stability in sensor **2300** compared to sensor **2200**. As an example, second resistor **2332 a** may have a magnitude of about 10 MO or less (e.g., about 1 MO) and first capacitor **2321 a** may have a magnitude of about 2200 nF.

[0392] As previously described, the illustrated example in FIG. 23 of capacitive EMG sensor **2300** is a differential capacitive EMG sensor. To this end, sensor **2300** includes: a second sensor electrode **2301 b** that is substantially similar to first sensor electrode **2301 a**; a fifth electrically conductive pathway **2311 b** (analogous to first electrically conductive pathway **2311 a**) that

communicatively couples second sensor electrode **2301 b** to amplifier **2350**; a third capacitor **2321 b** (analogous to first capacitor **2321 a**) electrically coupled in series between second sensor electrode **2301 b** and amplifier **2350** in fifth electrically conductive pathway **2311 b**; and a third resistor **2331 b** (analogous to first resistor **2331 a**) electrically coupled in series between second sensor electrode **2301 b** and amplifier **2350** in fifth electrically conductive pathway **2311 b**. In the illustrated example of FIG. **23**, third capacitor **2321 b** and third resistor **2331 b** are electrically coupled in series with one another in fifth electrically conductive pathway **2311 b**. Third capacitor **2321 b** may be substantially similar to first capacitor **2321 a** and third resistor **2331 b** may be substantially similar to first resistor **2331 a**. Sensor **2300** also includes: a sixth electrically conductive pathway **2313 b** (analogous to third electrically conductive pathway **2313 a**) that communicatively couples fifth electrically conductive pathway **2311 b** and second electrically conductive pathway **2312**; a fourth capacitor **2322 b** (analogous to third capacitor **2322 a**) electrically coupled in sixth electrically conductive pathway **2313 b** in between fifth electrically conductive pathway **2311 b** and second electrically conductive pathway **2312**; a seventh electrically conductive pathway **2314 b** (analogous to fourth electrically conductive pathway **2314 a**) that communicatively couples fifth electrically conductive pathway **2311 b** and second electrically conductive pathway **2312**; and a fourth resistor **2332 b** (analogous to second resistor **2332 a**) electrically coupled in seventh electrically conductive pathway **2314 b** in between fifth electrically conductive pathway **2311 b** and second electrically conductive pathway **2312**. Third capacitor **2321 b** and fourth resistor **2332 b** form a high-pass filter configuration with respect to sensor electrode **2301 b**, amplifier **2350**, and ground electrode **2340** while third resistor **2331 b** and fourth capacitor **2322 b** form a low-pass filter configuration with respect to sensor electrode **2301 b**, amplifier **2350**, and ground electrode **2340**. Fourth capacitor **2322 b** may be substantially similar to second capacitor **2322 a** and fourth resistor **2332 b** may be substantially similar to second resistor **2332 a**. [0393] The various examples of capacitive EMG sensors described herein, including sensor **2300** from FIG. **23**, may be formed as a printed circuit board, formed as an integrated circuit, or otherwise carried by a substrate. In this case, one or more electrically conductive pathways (e.g., electrically conductive pathways **2311 a**, **2311 b**, **2312**, **2313 a**, **2313 b**, **2314 a**, and/or **2314 b**) may be embodied by one or more electrically conductive trace(s) carried by a substrate and formed using one or more lithography process(es).

[0394] FIG. **24** is a cross sectional view of a capacitive EMG sensor **2400** that resistively couples to the user's skin in accordance with the present systems, articles, and methods. Sensor **2400** is an example of a physical embodiment of the schematic diagram for sensor **2300** shown in FIG. **23**. Sensor **2400** includes elements of sensor **2300** and, in general, the descriptions of the elements of sensor **2300** apply to the analogous elements in sensor **2400** and vice versa.

[0395] Sensor **2400** includes a substrate **2460** formed of an insulating material (e.g., FR-4) and having a first surface **2460 a** and a second surface **2460 b**. Second surface **2460 b** is opposite first surface **2460 a** across a thickness of substrate **2460**. Sensor **2400** is a differential EMG sensor comprising two sensor electrodes **2401 a**, **2401 b** (analogous to sensor electrodes **2301 a**, **2301 b** of sensor **2300**), both carried by first surface **2460 a** of substrate **2460**. The circuitry that comprises the other elements of sensor **2400** (e.g., an amplifier **2450** analogous to amplifier **2350** of sensor **2300**, capacitors **2421 a**, **2421 b** analogous to capacitors **2321 a**, **2321 b** of sensor **2300**, and resistors **2431 a**, **2431 b** analogous to resistors **2331 a**, **2331 b** of sensor **2300**) is carried by second surface **2460 b** of substrate **2460** and communicatively coupled to electrodes **2401 a**, **2401 b** by electrically conductive pathways **2411 a**, **2411 b** (analogous to electrically conductive pathways **2311 a**, **2311 b** of sensor **2300**), which include via portions that extend through the thickness of substrate **2460** and electrically conductive trace portions that are carried by second surface **2460 b** of substrate **2460**.

[0396] Throughout this specification and the appended claims, the terms “carries” and “carried by” are generally used to describe a spatial relationship in which a first layer/component is positioned

proximate and physically coupled to a surface of a second layer/component, either directly or through one or more intervening layers/components. For example, electrode **2401 a** is carried by first surface **2460 a** of substrate **2460** and amplifier **2450** is carried by second surface **2460 b** of substrate **2460**. Amplifier **2450** is directly carried by second surface **2460 b** of substrate **2460** because there are no intervening layers/components that mediate the physical coupling between amplifier **2450** and second surface **2460 b** of substrate **2460**; however, amplifier **2450** would still be considered “carried by” second surface **2460 b** of substrate **2460** even if the physical coupling between amplifier **2450** and second surface **2460 b** of substrate **2460** was mediated by at least one intervening layer/component. The terms “carries” and “carried by” are not intended to denote a particular orientation with respect to top and bottom and/or left and right.

[0397] Each resistive sensor electrode of the capacitive EMG sensors described herein (e.g., electrodes **2401 a**, **2401 b** of sensor **2400**) comprises a respective electrically conductive plate that physically and electrically (i.e., galvanically/resistively) couples to the user's skin during use. For each such sensor electrode, the electrically conductive plate may be formed of, for example, a material that includes copper (such as pure elemental copper or a copper alloy), deposited and etched in accordance with established lithography techniques. While copper is an excellent material from which to form sensor electrodes **2401 a**, **2401 b** from a manufacturing point of view (because lithography techniques for processing copper are very well established in the art), an exposed surface of pure copper will ultimately form an insulating oxide layer and/or react with the skin of a user in other undesirable ways. This effect may be acceptable for traditional capacitive sensor electrodes that capacitively couple to the user because, as described previously, such electrodes are typically coated with an insulating dielectric layer anyway. However, the formation of such an insulating layer can undesirably effect the operation of a sensor electrode that resistively couples to the user's skin. In some cases, a user's skin may even react with copper, resulting in a rash or other discomfort for the user. For at least these reasons, in accordance with the present systems, articles, and methods it can be advantageous to form each of sensor electrodes **2401 a**, **2401 b** (and likewise electrodes **2301 a** and **2301 b** of FIG. 23) as a respective multilayer (e.g., bi-layer) structure comprising a first layer **2471 a**, **2471 b** formed of a first electrically conductive material (e.g., copper or a material including copper) and at least a second layer **2472 a**, **2472 b** formed of a second electrically conductive material. In accordance with the present systems, articles, and methods, the second electrically conductive material may be an inert, non-reactive, and/or biocompatible material. For example, the second electrically conductive material may include: gold, steel (e.g., a stainless steel such as a 316 stainless steel or a low-nickel stainless steel to mitigate dermatological nickel allergies, such as 430 stainless steel), silver, titanium, electrically conductive rubber, and/or electrically conductive silicone.

[0398] The use of multilayer (e.g., bi-layer) structures for sensor electrodes **2401 a**, **2401 b** is advantageous because it enables the first layer **2471 a**, **2471 b** to be formed of copper using established lithography techniques and the second layer **2472 a**, **2472 b** to be subsequently applied in order to protect the copper from exposure to the user/environment and to protect the user from exposure to the copper. Furthermore, an EMG sensor (e.g., sensor **2400**) may be packaged in a housing for both protective and aesthetic purposes, and a second layer **2472 a**, **2472 b** of electrically conductive material may be used to effectively increase the thickness of sensor electrodes **2401 a**, **2401 b** such that they protrude outwards from the housing to resistively couple to the user's skin during use.

[0399] FIG. 25 is a cross sectional view of a capacitive EMG sensor **2500** packaged in a housing **2590** and employing bi-layer sensor electrodes **2501 a**, **2501 b** that protrude from the housing in order to physically contact and electrically (i.e., resistively/galvanically) couple to a user's skin in accordance with the present systems, articles, and methods. Sensor **2500** is substantially similar to sensor **2400** from FIG. 24 and includes the same or similar elements (e.g., a substrate **2560** having a first surface **2560 a** and a second surface **2560 b**, where first surface **2560 a** carries first and

second sensor electrodes **2501 a**, **2501 b** and second surface **2560 b** carries an amplifier **2550**, first and second capacitors **2521 a**, **2521 b**, first and second resistors **2531 a**, **2531 b**, etc.), all at least partially contained within the inner volume of a housing **2590**. Housing **2590** may be formed of substantially rigid material. Throughout this specification and the appended claims, the term “rigid” as in, for example, “substantially rigid material,” is used to describe a material that has an inherent tendency to maintain or restore its shape and resist malformation/deformation under, for example, the moderate stresses and strains typically encountered by a wearable electronic device.

[0400] Bi-layer sensor electrodes **2501 a**, **2501 b** are similar to bi-layer sensor electrodes **2401 a**, **2401 b** of sensor **2400** in that they each comprise a respective first layer **a2571 a**, **2571 b** formed of a first electrically conductive material (e.g., copper, or a material including copper) and a respective second layer **2572 a**, **2572 b** formed of a second electrically conductive material (e.g., gold, steel, stainless steel, conductive rubber, etc.); however, in sensor **2500** the respective second layer **2572 a**, **2572 b** of each of electrodes **2501 a**, **2501 b** is substantially thicker than the respective first layer **a2571 a**, **2571 b** of each of electrodes **2501 a**, **2501 b**. At least two holes **2580 a**, **2580 b** in housing **2590** provide access to the inner volume of housing **2590**, and the thickness of second layers **2572 a**, **2572 b** of electrodes **2501 a**, **2501 b** (respectively) is sufficient such that at least respective portions of second layers **2572 a**, **2572 b** protrude out of housing **2590** through holes **2580 a**, **2580 b**. More specifically, first sensor electrode **2501 a** includes a first layer **a2571 a** and a second layer **2572 a**, housing **2590** includes a first hole **2580 a**, and at least a portion of second layer **2572 a** of first sensor electrode **2501 a** extends out of housing **2590** through first hole **2580 a**. Likewise, second sensor electrode **2501 b** includes a first layer **2571 b** and a second layer **2572 b**, housing **2590** includes a second hole **2580 b**, and at least a portion of second layer **2572 b** of second sensor electrode **2501 b** extends out of housing **2590** through second hole **2580 b**. In this way, housing **2590** protects sensor **2500** from the elements and affords opportunities to enhance aesthetic appeal, while the protruding portions of second layers **2572 a**, **2572 b** of sensor electrodes **2501 a**, **2501 b** are still able to resistively couple to the skin of the user during use. Housing **2590** also helps to electrically insulate electrodes **2501 a**, **2501 b** from one another. In some applications, it can be advantageous to seal any gap between the perimeter of first hole **2580 a** and the protruding portion of second layer **2572 a** of first electrode **2501 a** (using, e.g., a gasket, an epoxy or other sealant or, in the case of electrically conductive rubber or electrically conductive silicone as the material forming second layer **2572 a** of first electrode **2501 a**, a tight interference fit between the perimeter of first hole **2580 a** and the protruding portion of second layer **2572 a** of first electrode **2501 a**) to prevent moisture or contaminants from entering housing **2590**. Likewise, it can be advantageous to seal any gap between the perimeter of second hole **2580 b** and the protruding portion of second layer **2572 b** of second electrode **2501 b**.

[0401] As previously described, the various embodiments of capacitive EMG sensors described herein may include at least one ground electrode. For example, sensor **2300** from FIG. 23 depicts ground electrode **2340**. Sensor **2400** from FIG. 24 and sensor **2500** from FIG. 25 each do not illustrate a ground electrode for two reasons: a) to reduce clutter; and b) because in various embodiments, a ground electrode may or may not be carried by the same substrate as the sensor electrode(s). Sensor electrodes (such as electrodes **2301 a**, **2301 b**, **2401 a**, **2401 b**, and **2501 a**, **2501 b**) are advantageously positioned near muscle groups in order to detect EMG signals therefrom, but in some applications it is advantageous for ground electrodes (such as electrode **2340**) to be positioned distant from the sensor electrodes and/or near bone instead of near muscle groups. For this reason, one or more ground electrode(s) may, in some applications, be separate from the substrate which carries the sensor electrodes but still communicatively coupled to the sensor circuitry by one or more electrically conductive pathways (e.g., electrical wires). However, in some applications one or more ground electrode(s) may be carried by the same substrate that carries the sensor electrodes, at least in part because doing so greatly simplifies the design and manufacture of the EMG sensor. For example, sensor **2400** from FIG. 24 may further include a

ground electrode carried by first surface **2460 a** of substrate **2500** and/or sensor **2500** from FIG. **25** may further include a ground electrode carried by first surface **2560 a** of substrate **2560**. In either case, the ground electrode may comprise a first layer formed of a first electrically conductive material (e.g., copper, or a material including copper) and a second layer formed of a second electrically conductive material (e.g., gold, steel, stainless steel, electrically conductive rubber, etc.). In applications that employ a housing, such as housing **2590** of sensor **2500**, the housing may include a hole (e.g., a third hole) and at least a portion of the second layer of the ground electrode may protrude through the hole to physically contact and electrically (i.e., resistively/galvanically) couple to the skin of the user during use.

[0402] In accordance with the present systems, articles, and methods, multilayer (e.g., bi-layer) electrodes, including multilayer sensor electrodes and/or multilayer ground electrodes, may be formed by, for example: electroplating a second layer of electrically conductive material on a first layer of electrically conductive material; depositing a second layer of electrically conductive material on a first layer of electrically conductive material using deposition or growth techniques such as chemical vapor deposition, physical vapor deposition thermal oxidation, or epitaxy; adhering a second layer of electrically conductive material to a first layer of electrically conductive material using, for example, an electrically conductive epoxy or an electrically conductive solder; pressing a second layer of electrically conductive material against a first layer of electrically conductive material using, for example, an interference fit, one or more spring(s), or one or more elastic band(s); or otherwise generally bonding a second electrically conductive material to a first electrically conductive material in such a way that the second electrically conductive material is electrically coupled to the first electrically coupled material.

[0403] FIG. **26** is a flow-diagram of a method **2600** of fabricating an EMG sensor in accordance with the present systems, articles, and methods. Method **2600** includes five acts **2601**, **2602**, **2603**, **2604**, and **2605**, though those of skill in the art will appreciate that in alternative embodiments certain acts may be omitted and/or additional acts may be added. Those of skill in the art will also appreciate that the illustrated order of the acts is shown for exemplary purposes only and may change in alternative embodiments.

[0404] At **2601**, a first sensor electrode is formed on a first surface of a substrate. The first sensor electrode may comprise an electrically conductive plate such as for example electrode **2401 a** of sensor **2400** or electrode **2501 a** of sensor **2500**, formed using, as an example, lithography techniques. The first sensor electrode may include a single layer of electrically conductive material or multiple (i.e., at least two) layers of one or more electrically conductive material(s). Forming the first sensor electrode may therefore include depositing at least a first layer of a first electrically conductive material (e.g., copper) on the first surface of the substrate. Where, in accordance with the present systems, articles, and methods, it is desirable for the first sensor electrode to comprise multiple layers, forming the first sensor electrode may further include depositing a second layer of a second electrically conductive material (e.g., gold, steel, stainless steel, electrically conductive rubber, etc.) on the first layer of the first electrically conductive material (either directly by, for example, a plating process or indirectly by, for example, employing an intervening adhesive layer such as an electrically conductive epoxy or an electrically conductive solder).

[0405] At **2602**, an amplifier (e.g., amplifier **2350** of sensor **2300**, amplifier **2450** of sensor **2400**, or amplifier **2550** of sensor **2500**) is deposited on a second surface of the substrate. The amplifier may include an amplification circuit and/or one or more discrete electronic component amplifier(s), such as for example on or more operational amplifier(s), differential amplifier(s), and/or instrumentation amplifier(s). Depositing the amplifier on the second surface of the substrate may include soldering a discrete component amplifier to one or more electrically conductive trace(s) and/or bonding pad(s) carried by the second surface of the substrate (i.e., soldering the amplifier on the second surface of the substrate using, for example, a surface-mount technology, or “SMT,” process).

[0406] At **2603**, a first capacitor (e.g., capacitor **2321 a** of sensor **2300**, capacitor **2421 a** of sensor **2400**, or capacitor **2521 a** of sensor **2500**) is deposited on the second surface of the substrate. The first capacitor may include a discrete electronic component capacitor and depositing the first capacitor on the second surface of the substrate may include soldering the first capacitor to one or more electrically conductive trace(s) and/or bonding pad(s) carried by the second surface of the substrate (i.e., soldering the first capacitor on the second surface of the substrate using, for example, a SMT process).

[0407] At **2604**, a first resistor (e.g., resistor **2331 a** of sensor **2300**, resistor **2431 a** of sensor **2400**, or resistor **2531 a** of sensor **2500**) is deposited on the second surface of the substrate. The first resistor may include a discrete electronic component resistor and depositing the first resistor on the second surface of the substrate may include soldering the first resistor to one or more electrically conductive trace(s) and/or bonding pad(s) carried by the second surface of the substrate (i.e., soldering the first resistor on the second surface of the substrate using, for example, a SMT process).

[0408] As described previously, a person of skill in the art will appreciate that the order of the acts in method **2600**, and in particular the order of acts **2601**, **2602**, **2603**, and **2604**, is provided as an example only and in practice acts **2601**, **2602**, **2603**, and **2604** may be carried out in virtually any order or combination, and any/all of acts **2601**, **2602**, **2603**, and **2604** may be carried out substantially concurrently or even simultaneously (in, for example, an SMT process).

[0409] At **2605**, a first electrically conductive pathway (e.g., pathway **2311 a** of sensor **2300** or pathway **2411 a** of sensor **2400**) that communicatively couples the first sensor electrode to the amplifier through the first capacitor and the first resistor is formed. The first electrically conductive pathway may include one or more section(s) of electrically conductive trace carried by the second surface of the substrate and at least one via that electrically couples at least one of the one or more section(s) of electrically conductive trace to the first sensor electrode carried by the first surface of the substrate. Thus, forming the first electrically conductive pathway may employ established lithography techniques to form the one or more section(s) of electrically conductive trace and to form a via through the substrate.

[0410] As previously described, the EMG sensor may include or otherwise be packaged in a housing, such as housing **2590** of sensor **2500**. In this case, method **2600** may be extended to include enclosing the substrate in a housing. Enclosing the substrate in the housing includes enclosing the amplifier, the first capacitor, and the first resistor in the housing. The housing may include a hole providing access to the inner volume thereof, and enclosing the substrate in the housing may include aligning the first sensor electrode with the hole so that at least a portion of the first sensor electrode protrudes out of the housing through the hole. For implementations in which the first sensor electrode comprises a first layer and a second layer, aligning the first sensor electrode with the hole may include aligning the first sensor electrode with the hole so that at least a portion of the second layer protrudes out of the housing through the hole.

[0411] As previously described, the EMG sensor may include a ground electrode. For example, sensor **2300** from FIG. **23** includes ground electrode **2340**. In order to include a ground electrode (**2340**) and associated circuitry in an EMG sensor, method **2600** may be extended to include: forming the ground electrode (**2340**) on the first surface of the substrate; forming a second electrically conductive pathway (**2312**) that communicatively couples to the ground electrode (**2340**); depositing a second capacitor (**2322 a**) on the second surface of the substrate; forming a third electrically conductive pathway (**2313 a**) that communicatively couples the first electrically conductive pathway (**2311 a**) and the second electrically conductive pathway (**2312**) through the second capacitor (**2322 a**); depositing a second resistor (**2332 a**) on the second surface of the substrate; and forming a fourth electrically conductive pathway (**2314 a**) that communicatively couples the first electrically conductive pathway (**2311 a**) and the second electrically conductive pathway (**2312**) through the second resistor (**2332 a**). Forming the ground electrode and the second,

third, and fourth electrically conductive pathways may employ established lithography processes. Depositing the second capacitor and the second resistor may involve soldering discrete circuit components on the substrate (e.g., using a SMT process).

[0412] With or without a ground electrode (**2340**), the EMG sensor may be differential. For example, sensor **2300** from FIG. **23** includes second sensor electrode **2301 b**. In order to include a second sensor electrode (**2301 b**) and associated circuitry in an EMG sensor, method **2600** may be extended to include: forming a second sensor electrode (**2301 b**) on the first surface of the substrate; depositing a third capacitor (**2321 b**) on the second surface of the substrate; depositing a third resistor (**2331 b**) on the second surface of the substrate; and forming a fifth electrically conductive pathway (**2311 b**) that communicatively couples the second sensor electrode (**2301 b**) and the amplifier (**2350**) through the third capacitor (**2321 b**) and the third resistor (**2331 b**). Forming the second sensor electrode and the fifth electrically conductive pathway may employ established lithography processes. Depositing the third capacitor and the third resistor may involve soldering discrete circuit components on the substrate (e.g., using a SMT process). For a differential EMG sensor that includes a ground electrode (e.g., as in sensor **2300** from FIG. **23**), method **2600** may be extended to include: depositing a fourth capacitor (**2322 b**) on the second surface of the substrate; forming a sixth electrically conductive pathway (**2313 b**) that communicatively couples the fifth electrically conductive pathway (**2311 b**) and the second electrically conductive pathway (**2312**) through the fourth capacitor (**2322 b**); depositing a fourth resistor (**2332 b**) on the second surface of the substrate; and forming a seventh electrically conductive pathway (**2314 b**) that communicatively couples the fifth electrically conductive pathway (**2311 b**) and the second electrically conductive pathway (**2312**) through the fourth resistor (**2332 b**). Forming the sixth and seventh electrically conductive pathways may employ established lithography processes. Depositing the fourth capacitor and the fourth resistor may involve soldering discrete circuit components on the substrate (e.g., using a SMT process).

[0413] Capacitive EMG sensors having sensor electrodes that resistively couple to the user's skin as described herein may be implemented in virtually any system, device, or process that makes use of capacitive EMG sensors; however, the capacitive EMG sensors described herein are particularly well-suited for use in EMG devices that are intended to be worn by (or otherwise coupled to) a user for an extended period of time and/or for a range of different skin and/or environmental conditions. As an example, the capacitive EMG sensors described herein may be implemented in a wearable EMG device that provides gesture-based control in a human-electronics interface. Some details of exemplary wearable EMG devices that may be adapted to include at least one capacitive EMG sensor from the present systems, articles, and methods are described in, for example, U.S. patent application Ser. No. 14/186,889; U.S. patent application Ser. No. 14/335,668; U.S. Pat. No. 10,152,082, U.S. patent application Ser. No. 14/461,044, U.S. patent application Ser. No. 14/465,194, U.S. Pat. Nos. 9,483,123, and 9,389,694, all of which are incorporated herein by reference in their entirety.

[0414] Throughout this specification and the appended claims, the term “gesture” is used to generally refer to a physical action (e.g., a movement, a stretch, a flex, a pose, etc.) performed or otherwise effected by a user. Any physical action performed or otherwise effected by a user that involves detectable muscle activity (detectable, e.g., by at least one appropriately positioned EMG sensor) may constitute a gesture in the present systems, articles, and methods.

[0415] FIG. **27** is a perspective view of an exemplary wearable EMG device **2700** that includes capacitive EMG sensors adapted to, in use, resistively couple to the user's skin in accordance with the present systems, articles, and methods. Exemplary wearable EMG device **2700** may, for example, form part of a human-electronics interface. Exemplary wearable EMG device **2700** is an armband designed to be worn on the forearm of a user, though a person of skill in the art will appreciate that the teachings described herein may readily be applied in wearable EMG devices designed to be worn elsewhere on the body of the user, including without limitation: on the upper

arm, wrist, hand, finger, leg, foot, torso, or neck of the user.

[0416] Device **2700** includes a set of eight pod structures **2701**, **2702**, **2703**, **2704**, **2705**, **2706**, **2707**, and **2708** that form physically coupled links of the wearable EMG device **2700**. Each pod structure in the set of eight pod structures **2701**, **2702**, **2703**, **2704**, **2705**, **2706**, **2707**, and **2708** is positioned adjacent and in between two other pod structures in the set of eight pod structures such that the set of pod structures forms a perimeter of an annular or closed loop configuration. For example, pod structure **2701** is positioned adjacent and in between pod structures **2702** and **2708** at least approximately on a perimeter of the annular or closed loop configuration of pod structures, pod structure **2702** is positioned adjacent and in between pod structures **2701** and **2703** at least approximately on the perimeter of the annular or closed loop configuration, pod structure **2703** is positioned adjacent and in between pod structures **2702** and **2704** at least approximately on the perimeter of the annular or closed loop configuration, and so on. Each of pod structures **2701**, **2702**, **2703**, **2704**, **2705**, **2706**, **2707**, and **2708** is physically coupled to the two adjacent pod structures by at least one adaptive coupler (not visible in FIG. 27). For example, pod structure **2701** is physically coupled to pod structure **2708** by an adaptive coupler and to pod structure **2702** by an adaptive coupler. The term “adaptive coupler” is used throughout this specification and the appended claims to denote a system, article or device that provides flexible, adjustable, modifiable, extendable, extensible, or otherwise “adaptive” physical coupling. Adaptive coupling is physical coupling between two objects that permits limited motion of the two objects relative to one another. An example of an adaptive coupler is an elastic material such as an elastic band. Thus, each of pod structures **2701**, **2702**, **2703**, **2704**, **2705**, **2706**, **2707**, and **2708** in the set of eight pod structures may be adaptively physically coupled to the two adjacent pod structures by at least one elastic band. The set of eight pod structures may be physically bound in the annular or closed loop configuration by a single elastic band that couples over or through all pod structures or by multiple separate elastic bands that couple between adjacent pairs of pod structures or between groups of adjacent pairs of pod structures. Device **2700** is depicted in FIG. 27 with the at least one adaptive coupler completely retracted and contained within the eight pod structures **2701**, **2702**, **2703**, **2704**, **2705**, **2706**, **2707**, and **2708** (and therefore the at least one adaptive coupler is not visible in FIG. 27).

[0417] Throughout this specification and the appended claims, the term “pod structure” is used to refer to an individual link, segment, pod, section, structure, component, etc. of a wearable EMG device. For the purposes of the present systems, articles, and methods, an “individual link, segment, pod, section, structure, component, etc.” (i.e., a “pod structure”) of a wearable EMG device is characterized by its ability to be moved or displaced relative to another link, segment, pod, section, structure component, etc. of the wearable EMG device. For example, pod structures **2701** and **2702** of device **2700** can each be moved or displaced relative to one another within the constraints imposed by the adaptive coupler providing adaptive physical coupling therebetween. The desire for pod structures **2701** and **2702** to be movable/displaceable relative to one another specifically arises because device **2700** is a wearable EMG device that advantageously accommodates the movements of a user and/or different user forms. As described in more detail later on, each of pod structures **2701**, **2702**, **2703**, **2704**, **2705**, **2706**, **2707**, and **2708** may correspond to a respective housing (e.g., housing **2590** of sensor **2500**) of a respective capacitive EMG sensor adapted to, in use, resistively couple to the user's skin in accordance with the present systems, articles, and methods.

[0418] Device **2700** includes eight pod structures **2701**, **2702**, **2703**, **2704**, **2705**, **2706**, **2707**, and **2708** that form physically coupled links thereof. Wearable EMG devices employing pod structures (e.g., device **2700**) are used herein as exemplary wearable EMG device designs, while the present systems, articles, and methods may be applied to wearable EMG devices that do not employ pod structures (or that employ any number of pod structures). Thus, throughout this specification, descriptions relating to pod structures (e.g., functions and/or components of pod structures) should

be interpreted as being applicable to any wearable EMG device design, even wearable EMG device designs that do not employ pod structures (except in cases where a pod structure is specifically recited in a claim).

[0419] In exemplary device **2700** of FIG. **27**, each of pod structures **2701**, **2702**, **2703**, **2704**, **2705**, **2706**, **2707**, and **2708** comprises a respective housing, with each housing being akin to a respective one of housing **2590** from sensor **2500**. Each housing may comprise substantially rigid material that encloses a respective inner volume. Details of the components contained within the housings (i.e., within the inner volumes of the housings) of pod structures **2701**, **2702**, **2703**, **2704**, **2705**, **2706**, **2707**, and **2708** are not necessarily visible in FIG. **27** (e.g., the housings may be formed of material that is optically opaque). To facilitate descriptions of exemplary device **2700**, some internal components are depicted by dashed lines in FIG. **27** to indicate that these components are contained in the inner volume(s) of housings and may not normally be actually visible in the view depicted in FIG. **27**, unless a transparent or translucent material is employed to form the housings. For example, any or all of pod structures **2701**, **2702**, **2703**, **2704**, **2705**, **2706**, **2707**, and/or **2708** may include circuitry (i.e., electrical and/or electronic circuitry). In FIG. **27**, a first pod structure **2701** is shown containing circuitry **2711** (i.e., circuitry **2711** is contained in the inner volume of the housing of pod structure **2701**), a second pod structure **2702** is shown containing circuitry **2712**, and a third pod structure **2708** is shown containing circuitry **2718**. The circuitry in any or all pod structures may be communicatively coupled to the circuitry in at least one other pod structure by at least one communicative pathway (e.g., by at least one electrically conductive pathway and/or by at least one optical pathway). For example, FIG. **27** shows a first set of communicative pathways **2721** providing communicative coupling between circuitry **2718** of pod structure **2708** and circuitry **2711** of pod structure **2701**, and a second set of communicative pathways **2722** providing communicative coupling between circuitry **2711** of pod structure **2701** and circuitry **2712** of pod structure **2702**.

[0420] Throughout this specification and the appended claims the term “communicative” as in “communicative pathway,” “communicative coupling,” and in variants such as “communicatively coupled,” is generally used to refer to any engineered arrangement for transferring and/or exchanging information. Exemplary communicative pathways include, but are not limited to, electrically conductive pathways (e.g., electrically conductive wires, electrically conductive traces), magnetic pathways (e.g., magnetic media), and/or optical pathways (e.g., optical fiber), and exemplary communicative couplings include, but are not limited to, electrical couplings, magnetic couplings, and/or optical couplings.

[0421] Each individual pod structure within a wearable EMG device may perform a particular function, or particular functions. For example, in device **2700**, each of pod structures **2701**, **2702**, **2703**, **2704**, **2705**, **2706**, and **2707** includes a respective capacitive EMG sensor **2710** (akin to sensor **2300** from FIG. **23**, sensor **2400** from FIG. **24**, and/or sensor **2500** from FIG. **25**; only one called out in FIG. **27** to reduce clutter) adapted to, in use, resistively couple to the user's skin in accordance with the present systems, articles, and methods. Each capacitive EMG sensor **2710** is responsive to muscle activity of the user, meaning that each capacitive EMG sensor **2710** included in device **2700** to detect muscle activity of a user and to provide electrical signals in response to the detected muscle activity. Thus, each of pod structures **2701**, **2702**, **2703**, **2704**, **2705**, **2706**, and **2707** may be referred to as a respective “sensor pod.” Throughout this specification and the appended claims, the term “sensor pod” is used to denote an individual pod structure that includes at least one sensor responsive to (i.e., to detect and provide at least one signal in response to) muscle activity of a user.

[0422] Pod structure **2708** of device **2700** includes a processor **2730** that processes the signals provided by the capacitive EMG sensors **2710** of sensor pods **2701**, **2702**, **2703**, **2704**, **2705**, **2706**, and **2707** in response to detected muscle activity. Pod structure **2708** may therefore be referred to as a “processor pod.” Throughout this specification and the appended claims, the term “processor

pod” is used to denote an individual pod structure that includes at least one processor to process signals. The processor may be any type of processor, including but not limited to: a digital microprocessor or microcontroller, an application-specific integrated circuit (ASIC), a field-programmable gate array (FPGA), a digital signal processor (DSP), a graphics processing unit (GPU), a programmable gate array (PGA), a programmable logic unit (PLU), or the like, that analyzes or otherwise processes the signals to determine at least one output, action, or function based on the signals. A person of skill in the art will appreciate that implementations that employ a digital processor (e.g., a digital microprocessor or microcontroller, a DSP, etc.) may advantageously include a non-transitory processor-readable storage medium or memory communicatively coupled thereto and storing data and/or processor-executable instructions that control the operations thereof, whereas implementations that employ an ASIC, FPGA, or analog processor may or may optionally not include a non-transitory processor-readable storage medium, or may include on-board registers or other non-transitory storage structures.

[0423] As used throughout this specification and the appended claims, the terms “sensor pod” and “processor pod” are not necessarily exclusive. A single pod structure may satisfy the definitions of both a “sensor pod” and a “processor pod” and may be referred to as either type of pod structure. For greater clarity, the term “sensor pod” is used to refer to any pod structure that includes a sensor and performs at least the function(s) of a sensor pod, and the term processor pod is used to refer to any pod structure that includes a processor and performs at least the function(s) of a processor pod. In device **2700**, processor pod **2708** includes a capacitive EMG sensor **2710** (not visible in FIG. 27) adapted to, in use, resistively couple to the user's skin in order to sense, measure, transduce or otherwise detect muscle activity of the user, so processor pod **2708** could be referred to as a sensor pod. However, in exemplary device **2700**, processor pod **2708** is the only pod structure that includes a processor **2730**, thus processor pod **2708** is the only pod structure in exemplary device **2700** that can be referred to as a processor pod. The processor **2730** in processor pod **2708** also processes the EMG signals provided by the capacitive EMG sensor **2710** of processor pod **2708**. In alternative embodiments of device **2700**, multiple pod structures may include processors, and thus multiple pod structures may serve as processor pods. Similarly, some pod structures may not include sensors, and/or some sensors and/or processors may be laid out in other configurations that do not involve pod structures.

[0424] In device **2700**, processor **2730** includes and/or is communicatively coupled to a non-transitory processor-readable storage medium or memory **2740**. Memory **2740** may store processor-executable gesture identification instructions that, when executed by processor **2730**, cause processor **2730** to process the EMG signals from capacitive EMG sensors **2710** and identify a gesture to which the EMG signals correspond. For communicating with a separate electronic device (not shown), wearable EMG device **2700** includes at least one communication terminal. Throughout this specification and the appended claims, the term “communication terminal” is generally used to refer to any physical structure that provides a telecommunications link through which a data signal may enter and/or leave a device. A communication terminal represents the end (or “terminus”) of communicative signal transfer within a device and the beginning of communicative signal transfer to/from an external device (or external devices). As examples, device **2700** includes a first communication terminal **2751** and a second communication terminal **2752**. First communication terminal **2751** includes a wireless transmitter (i.e., a wireless communication terminal) and second communication terminal **2752** includes a tethered connector port **2752**. Wireless transmitter **2751** may include, for example, a Bluetooth® transmitter (or similar) and connector port **2752** may include a Universal Serial Bus port, a mini-Universal Serial Bus port, a micro-Universal Serial Bus port, a SMA port, a THUNDERBOLT® port, or the like.

[0425] For some applications, device **2700** may also include at least one inertial sensor **2702760** (e.g., an inertial measurement unit, or “IMU,” that includes at least one accelerometer and/or at least one gyroscope) responsive to (i.e., to detect, sense, or measure and provide at least one signal

in response to detecting, sensing, or measuring) motion effected by a user. Signals provided by inertial sensor **2702760** may be combined or otherwise processed in conjunction with signals provided by capacitive EMG sensors **2710**.

[0426] As previously described, each of pod structures **2701**, **2702**, **2703**, **2704**, **2705**, **2706**, **2707**, and **2708** may include circuitry (i.e., electrical and/or electronic circuitry). FIG. **27** depicts circuitry **2711** inside the inner volume of sensor pod **2701**, circuitry **2712** inside the inner volume of sensor pod **2702**, and circuitry **2718** inside the inner volume of processor pod **2718**. The circuitry in any or all of pod structures **2701**, **2702**, **2703**, **2704**, **2705**, **2706**, **2707** and **2708** (including circuitries **2711**, **2712**, and **2718**) may include any or all of: an amplification circuit to amplify electrical signals provided by at least one EMG sensor **2710**, a filtering circuit to remove unwanted signal frequencies from the signals provided by at least one EMG sensor **2710**, and/or an analog-to-digital conversion circuit to convert analog signals into digital signals. The circuitry in any or all of pod structures **2701**, **2702**, **2703**, **2704**, **2705**, **2706**, **2707**, and **2708** may include one or more discrete component capacitor(s), resistor(s), and/or amplifier(s) in the configuration(s) previously described for sensors **2300**, **2400**, and/or **2500**. Device **2700** may also include at least one battery (not shown in FIG. **27**) to provide a portable power source for device **2700**.

[0427] Each of EMG sensors **2710** includes a respective capacitive EMG sensor responsive to muscle activity corresponding to a gesture performed by the user, wherein in response to muscle activity corresponding to a gesture performed by the user each of EMG sensors **2710** provides signals. EMG sensors **2710** are capacitive EMG sensors that are adapted to, in use, resistively couple to the user's skin per the present systems, articles, and methods, as described for sensor **2300** from FIG. **23**, sensor **2400** from FIG. **24**, or sensor **2500** from FIG. **25**. In particular, each EMG sensor **2710** includes a respective first resistive sensor electrode **2771** (only one called out to reduce clutter) that is communicatively coupled to an amplifier (not visible in FIG. **27**, but similar to amplifier **2350** of sensor **2300**) through a discrete component capacitor (not visible in FIG. **27**, but akin to first capacitor **2321 a** of sensor **2300**) and a discrete component resistor (also not visible in FIG. **27**, but akin to first resistor **2331 a** of sensor **2300**), a second resistive sensor electrode **2772** (only one called out to reduce clutter) that is also communicatively coupled to the amplifier through a discrete component capacitor (not visible in FIG. **27**, but akin to third capacitor **2321 b** of sensor **2300**) and a discrete component resistor (also not visible in FIG. **27**, but akin to third resistor **2331 b** of sensor **2300**), and a ground electrode **2773** (only one called out to reduce clutter). Each of the electrodes **2771**, **2772**, and **2773** of each EMG sensor **2710** may be carried by a respective substrate, and the respective circuitry (e.g., **2711**, **2712**, and **2718**) of each pod structure **2701**, **2702**, **2703**, **2704**, **2705**, **2706**, **2707**, and **2708** may be carried by the same substrate and include the communicative pathway, amplifier, capacitor, and resistor elements previously described for sensors **2300**, **2400**, and **2500**. For example, each respective EMG sensor **2710** of each pod structure **2701**, **2702**, **2703**, **2704**, **2705**, **2706**, **2707**, and **2708** may include a respective substrate, with the first and second sensor electrodes **2771**, **2772** and the ground electrode **2773** of each pod structure **2701**, **2702**, **2703**, **2704**, **2705**, **2706**, **2707**, and **2708** carried by a first surface of the substrate and circuitry **2711**, **2712**, **2718** carried by a second surface of the substrate, the second surface being opposite the first surface across a thickness of the substrate. For each sensor **2710**, the circuitry respectively includes at least an amplifier (e.g., **2350**, **2450**, **2550**), a first electrically conductive pathway (e.g., **2311 a**, **2411 a**, **411 a**) that communicatively couples the first sensor electrode **2771** and the amplifier, a first capacitor (e.g., **2321 a**, **2421 a**, **2521 a**) electrically coupled in series between the first sensor electrode **2771** and the amplifier in the first electrically conductive pathway, and a first resistor (e.g., **2331 a**, **2431 a**, **2531 a**) electrically coupled in series between the first sensor electrode and the amplifier in the first electrically conductive pathway.

[0428] The capacitive EMG sensors **2710** of wearable EMG device **2700** are differential sensors that each implement two respective sensor electrodes **2771**, **2772** and a respective ground electrode **2773**, though the teachings herein may similarly be applied to wearable EMG devices that employ

single-ended capacitive EMG sensors that each implement a respective single sensor electrode and/or capacitive EMG sensors that share a common ground electrode.

[0429] Signals that are provided by capacitive EMG sensors **2710** in device **2700** are routed to processor pod **2708** for processing by processor **2730**. To this end, device **2700** employs a set of communicative pathways (e.g., **2721** and **2722**) to route the signals that are output by sensor pods **2701**, **2702**, **2703**, **2704**, **2705**, **2706**, and **2707** to processor pod **2708**. Each respective pod structure **2701**, **2702**, **2703**, **2704**, **2705**, **2706**, **2707**, and **2708** in device **2700** is communicatively coupled to, over, or through at least one of the two other pod structures between which the respective pod structure is positioned by at least one respective communicative pathway from the set of communicative pathways. Each communicative pathway (e.g., **2721** and **2722**) may be realized in any communicative form, including but not limited to: electrically conductive wires or cables, ribbon cables, fiber-optic cables, optical/photonics waveguides, electrically conductive traces carried by a rigid printed circuit board, electrically conductive traces carried by a flexible printed circuit board, and/or electrically conductive traces carried by a stretchable printed circuit board.

[0430] Device **2700** from FIG. **27** represents an example of a wearable EMG device that incorporates the teachings of the present systems, articles, and methods, though the teachings of the present systems, articles, and methods may be applicable to any wearable EMG device that includes at least one EMG sensor.

Description for Improved Wearable Muscle Interfaces

[0431] The below disclosure relates to muscle interface systems, devices and methods that enable a user to access and interact with content displayed on an electronic display in an inconspicuous, hands-free manner.

[0432] In an aspect, a wearable system includes a wearable muscle interface device comprising a plurality of muscle activity sensors worn on an arm of a user. The plurality of muscle activity sensors are responsive to signals generated by muscles in the arm of the user. For example, when the user performs a physical gesture that involves one or more muscle(s) in the arm upon which the muscle interface device is worn, at least one of the muscle activity sensors may detect signals generated by the one or more muscle(s). The wearable muscle interface device is adapted to recognize gestures made by the user and to interact with content displayed on a wearable head-mounted display in response to the recognized gestures. To this end, the wearable system further includes a wearable head-mounted display and the wearable muscle interface device includes a transmitter communicatively coupled to the plurality of muscle activity sensors. In use, the transmitter of the wearable muscle interface device transmits at least one signal from the wearable muscle interface device directly to a receiver on the wearable head-mounted display based on the signals detected by the muscle activity sensors. The at least one signal transmitted from the wearable muscle interface device directly to the receiver on the wearable head-mounted display effects at least one interaction with content displayed on the wearable head-mounted display.

[0433] In another aspect, a muscle interface method comprises processing at least one signal based on one or more gesture(s) made by a user's hand, wrist and/or arm movements to interact with content displayed on the wearable head-mounted display.

[0434] The plurality of muscle activity sensors in and/or on-board the wearable muscle interface device may include electromyography (EMG) sensors and/or mechanomyography (MMG) sensors to detect electrical signals and/or vibrations, respectively, produced by muscles in the user's arm and to provide one or more signal(s) in response to the detected electrical signals and/or vibrations. The electrical signals and/or vibrations detected from the muscles are interpreted as gestures made by the user which provide a direct control input to a wearable head-mounted display.

[0435] The control input is provided directly from the wearable muscle interface device to the wearable head-mounted display. Preferably, the control input is provided wirelessly from the wearable muscle interface device directly to the wearable head-mounted display via a wireless

communication protocol, such as NFC or Bluetooth™, for example. However, it will be appreciated that other types of wireless communications may be used, including any wireless communication protocol developed for smart phones and similar devices. In some applications, a direct wire connection between the wearable muscle interface device and the wearable head-mounted display may be used.

[0436] In addition to EMG and/or MMG sensors, various other types of sensors may be used to detect gestures made by the user. For example, inertial sensors such as accelerometers and/or gyroscopes may be used to detect signals generated by motion of the arm of the user in response to the user performing the physical gesture. The wearable muscle interface device may include one or more accelerometer sensors that, in use, detect signals generated by motion of the arm of the user and/or measure characteristics of gestures made by the user, including gestures involving the elbow or even the shoulders of the user. When used together with EMG and/or MMG sensors for detecting gestures, the accelerometer sensors may be utilized to increase the variety of control inputs that may be generated for direct interaction with a wearable head-mounted display.

[0437] An illustrative example will now be described with reference to the drawings.

[0438] Shown in FIG. 28 is an illustrative user 2800 wearing a wearable system 2850 that in use provides hands-free access to and control of a portable electronic display 3110 in accordance with the present systems, devices, and methods. Wearable system 2850 includes a wearable head-mounted display 3110 with on-board display control 300, and a wearable muscle interface device 2900 having a plurality of muscle activity sensors in accordance with the present systems, devices, and methods. In this illustrative example, wearable muscle interface device 2900 is a flexible, stretchable band that may be worn on the arm (e.g., the forearm) of user 2800 as shown. As discussed in more detail herein, wearable muscle interface device 2900 includes a transmitter (e.g., a wireless transmitter) and wearable head-mounted display 3110 includes a receiver (e.g., a wireless receiver) such that at least one signal may be transmitted from wearable muscle interface device 2900 directly to wearable head-mounted display 3110 (i.e., without being received and re-transmitted by any intervening device, such as a stationary, non-portable intervening device) in response to signals detected by the muscle activity sensors of wearable muscle interface device 2900 in order to effect interactions with and/or control of content displayed on or by wearable head-mounted display 3110.

[0439] FIG. 29 illustrates a detailed view of wearable muscle interface device 2900 from wearable system 2850 of FIG. 28 in accordance with the present systems, devices, and methods. As shown, wearable muscle interface device 2900 may comprise a processor 2910 (e.g., a central processing unit, a digital microcontroller, a digital signal processor, or similar), and one or more batteries 2920, which may be rechargeable, and which may be utilized concurrently or sequentially in conventional manner. As shown, wearable muscle interface device 2900 is a band to be worn on an arm of a user (e.g., a forearm of a user) and includes a plurality of muscle activity sensors 2930 which may be positioned radially around the circumference of the band, such that the sensors 2930 can, when in use, detect signals generated by muscles in the arm of user 2800 in response to user 2800 performing a physical gesture. Wearable muscle interface device 2900 may further include transmitter 2950 (e.g., a wireless transmitter) communicatively coupled to the plurality of muscle activity sensors 2930 which, in use, transmits at least one signal from wearable muscle interface device 2900 directly to a receiver on a wearable head-mounted display 3110 based on the signals detected by muscle activity sensors 2930. Wearable muscle interface device 2900 may include a feedback mechanism (e.g., a haptic feedback module) such as a vibratory motor 2940 to provide haptic feedback as described further below.

[0440] Wearable muscle interface device 2900 may be calibrated when first worn, prior to operation, such that muscle interface device 2900 may perform reliable gesture identification regardless of the exact positioning of the muscle activity sensors 2930 on the user's arm.

[0441] By way of example, muscle activity sensors 2930 may include one or more EMG sensor(s),

each of which may provide a respective EMG signal in the form of an oscillating waveform that varies in both frequency and amplitude. A majority of signal information that is needed for reliable gesture identification may be contained within a limited bandwidth of such an oscillating waveform, such as in the 5 Hz to 250 Hz frequency band. An illustrative example of an EMG signal **2900B** is shown in FIG. **30**.

[0442] As previously described, the plurality of muscle activity sensors **2930** may include one or more MMG sensor(s) comprising piezoelectric sensors, which may be used to measure the vibrations at the surface of the skin produced by the underlying muscles when contracted. By way of example, the MMG signal generated may be an oscillating waveform that varies in both frequency and amplitude, and a majority of signal information that is needed for reliable gesture identification may be contained within a limited bandwidth, such as in the 5 Hz to 250 Hz frequency band. Because the MMG signal is acquired via mechanical means, electrical variations like skin impedance may not have a significant effect on the signal. The MMG signal may be very similar to the illustrative example of EMG signal **2900B** shown in FIG. **30**.

[0443] As previously described, wearable muscle interface device **2900** may include one or more accelerometer sensor(s) **2960** that, in use, detect additional aspects of gestures made by user **2800** in, for example, three degrees of freedom. For example, at least one accelerometer **2960** may be communicatively coupled to transmitter **2950** of wearable muscle interface device **2900** and, in use, the at least one signal transmitted from transmitter **2950** directly to the receiver on the wearable head-mounted display **3110** may be based on both the signals detected by muscle activity sensors **2930** and the signals detected by the at least one accelerometer **2960**. An accelerometer signal may, for example, consist of three digital channels of data, each representing the acceleration in a respective one of three orthogonal directions (e.g., the x, y, and z directions). The signal may be representative of all of the accelerations that the user's arm is subject to, and may further represent motion of the body as a whole.

[0444] Now referring to FIG. **31**, shown is wearable system **2850** from FIG. **28** with an illustration of direct wireless communication (e.g., Bluetooth™, NFC, etc.) between wearable muscle interface device **2900** and wearable head-mounted display **3110** in accordance with the present systems, devices, and methods. This wireless communication is utilized to transmit one or more signal(s) from wearable muscle interface device **2900** directly to wearable head-mounted display **3110** (e.g., to a wireless receiver **3150** located in or on display control **300** of wearable head-mounted display **3110**) without any intervening communicative couplings or links. In this way, the user **2800** may access and control or otherwise interact with a portable electronic display in an inconspicuous and hands-free manner. User **2800** does not need to use his or her hand(s) to position or orient the portable electronic display of wearable head-mounted display **3110** in order to be able to see, access, receive feedback from, or otherwise interact with the portable electronic display of wearable head-mounted display **3110** because wearable head-mounted display **3110** is arranged such that at least one display screen is positioned in front of at least one eye of user **2800** at all times while wearable head-mounted display **3110** is worn on user **2800**'s head, regardless of the direction that user **2800** is facing. Furthermore, wearable muscle interface device **2900** enables user **2800** to control or otherwise interact with content displayed on wearable head-mounted display **3110** in an inconspicuous manner by using touchless gestures.

[0445] Inconspicuous gesture-based control of and/or interactions with wearable head-mounted display **3110** is illustrated by way of example in FIG. **32**, in which user **2800**'s hand and wrist gesture is detected and processed by wearable muscle interface device **2900** and transmitted directly from transmitter **2950** to receiver **3150** of wearable head-mounted display **3110** for interacting with content displayed thereon.

[0446] In this particular example, a gesture **3210** made by the user (**2800**) extending an index finger, and making a wrist flexion motion **3120** is detected by the muscle activity sensors **2930** (and/or accelerometer sensors **2960** if included) of wearable muscle interface device **2900** (not

visible in FIG. 32). Signals provided by the muscle activity sensors 2930 in response to the detected gesture 3210 are processed by processor 2910 (FIG. 29) which interprets the signals to identify gesture 3210 performed by user 2800. A corresponding signal is produced based on the gesture 3210 interpreted by the processor 2910 and the signal is transmitted from transmitter 2950 directly to receiver 3150 of wearable head-mounted display 3110, which causes a menu appearing on wearable head-mounted display 3110 to scroll downwards.

[0447] As another example, a similar gesture in which user 2800 extends the index finger and makes a wrist extension motion may be detected by muscle activity sensors 2930 (and/or accelerometer sensors 2960 if included) of wearable muscle interface device 2900 and processed by processor 2910 (FIG. 29). Processor 2910 may interpret the detected muscle activity to identify the gesture performed, and a corresponding signal may be transmitted from transmitter 2950 directly to receiver 3150 of wearable head-mounted display 3110 to cause a menu appearing on wearable head-mounted display 3110 to scroll upwards.

[0448] As yet another example, a gesture in which user 2800 extends the index finger and makes a poking motion involving a slight movement of the elbow and shoulder may be detected by muscle activity sensors 2930 (and/or accelerometer sensors 2960 if included) of wearable muscle interface device 2900 and processed by processor 2910 (FIG. 29). Processor 2910 may interpret the detected muscle activity to identify the gesture performed, and a corresponding signal may be transmitted from transmitter 2950 directly to receiver 3150 of wearable head-mounted display 3110 to cause a highlighted menu item appearing on wearable head-mounted display 3110 to be selected.

[0449] If the user extends a different finger other than the index finger, muscle activity sensors 2930 may detect this, a different gesture may be identified by wearable muscle interface device 2900, and a different signal may be transmitted directly to wearable head-mounted display 3110 to effect a different interaction or function thereof. For example, extending the little finger or “pinky” finger instead of the index finger may cause wearable system 2850 to interpret the user's gestures with functions analogous to clicking a right mouse button rather than a left mouse button in a conventional mouse user interface. Extending both the index and pinky fingers at the same time may cause wearable system 2850 to interpret the user's gestures with yet other functions analogous to clicking a third mouse button in a conventional mouse user interface.

[0450] Thus, wearable muscle interface device 2900 may be adapted and/or calibrated to recognize a wide range of gestures made by a user 2800, based on measurements from a plurality of muscle activity sensors 2930 (and, in some implementations, one or more accelerometer sensor(s) 2960) in the wearable muscle interface device 2900.

[0451] Wearable muscle interface device 2900 may itself be operative to interpret the gestures from the detected signals as described above by, for example, using an on-board processor 2910 to process the EMG signals and interpret the EMG signals as a gesture via a gesture identification process (e.g., by invoking data and/or instructions stored in an on-board non-transitory computer-readable storage medium that, when executed by processor 2910, cause processor 2910 to identify the gesture performed by user 2800). Wearable muscle interface device 2900 may then transmit one or more signal(s) from transmitter 2950 directly to receiver 3150 of wearable head-mounted display 3110 in order to effect some interaction with wearable head-mounted display 3110 based on the interpreted gesture. In this example, the processor 2910 may be communicatively coupled in between the transmitter 2950 and the plurality of muscle activity sensors 2930 such that transmitter 2950 transmits one or more signal(s) provided by processor 2910 (e.g., corresponding to an interpreted gesture) based at least in part on the signals provided by muscle activity sensors 2930.

[0452] However, in an alternative implementation, the detected EMG signals may be transmitted directly to the receiver 3150 of wearable head-mounted display 3110 from transmitter 2950 (e.g., without being processed by processor 2910, which may or may not be included in device 2900 in this example) and wearable head-mounted display 3110 may include a processor 320 (e.g., a central processing unit, a digital microcontroller, a digital signal processor, or similar, located in or on

display control **300**) communicatively coupled to receiver **3150** to process the EMG signals and interpret the EMG signals as a gesture via a gesture identification process (e.g., by invoking data and/or instructions stored in an on-board non-transitory computer-readable storage medium that, when executed by processor **320**, cause processor **320** to identify the gesture performed by user **2800**). Wearable head-mounted display **3110** may then effect some interaction with content displayed thereon based on the interpreted gesture. Whether the detected EMG signals are interpreted at the device **2900** or at the display **3110**, the detected EMG signals are first interpreted as a recognized gesture in order to interact with content displayed on the display **3110**.

[0453] Wearable muscle interface device **2900** may include a haptic feedback module to provide feedback that a gesture has been recognized. This haptic feedback may provide a user **2800** with confirmation that the user **2800**'s gesture has been recognized, and successfully converted to a signal to interact with content displayed on wearable head-mounted display **3110**. The haptic feedback module may comprise, for example, a vibrating mechanism such as a vibratory motor **2940** built into the wearable muscle interface device **2900**.

[0454] Alternatively, rather than haptic feedback provided by the wearable muscle interface device **2900**, confirmation of recognition of a gesture may be provided by auditory feedback, either generated by a speaker on the wearable muscle interface device **2900**, or operatively connected to the wearable head-mounted display **3110**.

[0455] As another alternative, confirmation of recognition of a gesture may be provided visually on the wearable head-mounted display **3110** itself. If there is more than one possible gesture that may be interpreted from the detected signals, rather than providing a possibly erroneous signal, the wearable muscle interface device **2900** and/or the wearable head-mounted display **3110** may provide a selection of two or more possible gestures as possible interpretations, and the user may be prompted to select from one of them to confirm the intended gesture and corresponding control.

[0456] Now referring to FIG. **33**, shown is an illustrative schematic system architecture **3300** of the wearable muscle interface device **2900** component of a wearable system **2850** providing inconspicuous and hands-free access to and control of a portable electronic display in accordance with the present systems, device, and methods. As shown, system architecture **3300** includes a CPU **3302** (e.g., a processor, such as a digital microprocessor or microcontroller), non-transitory computer-readable memory **3304**, system clock **3306**, a wireless communication module **3308** (e.g., Bluetooth™, NFC, or the like), and a direct memory access (DMA) controller **33110**. As shown, DMA controller **33110** is adapted to receive inputs from various sensors on-board the wearable muscle interface device **2900**, including one or more EMG sensors **3320**, MMG sensors **3330** and/or accelerometer sensors **3340**.

[0457] In the illustrative example of system architecture **3300**, detected signals from one or more EMG sensors **3320** are processed through signal filter **3322** and converted from analog to digital signals by ADC **3324**. If one or more MMG sensors **3330** are used (either in addition to or instead of EMG sensors **3320**), then the detected signals from the MMG sensors **3330** are processed through signal filter **3332** and converted from analog to digital signals by ADC **3334**. Digital signals from one or more accelerometer sensors **3340** may also be processed through signal filter **3342** and received by DMA controller **33110**.

[0458] The data from the various types of sensors **3320**, **3330**, **3340** may be acquired through an analog filtering chain. The data may be band-passed through filters **3322**, **3332** between about 10 Hz to about 500 Hz, and amplified (e.g. by a total of about 28000 times). This filtering and amplification can be altered to whatever is required to be within software parameters. A notch filter at 60 Hz, or at any other relevant frequency, may also be used to remove powerline noise.

[0459] Data from the sensors **3320**, **3330** may be converted to, e.g., 12-bit digital data by ADCs **3324**, **3334**, and then clocked into onboard memory **3304** using clock **3306** by the DMA controller **33110** to be processed by the CPU **3302**.

[0460] Now referring to FIG. **34**, shown is a schematic flow chart of a method **3400** of using a

wearable system (e.g., **2850**) to achieve hands-free access to and control of a portable electronic display in accordance with the present systems, devices, and methods. As shown, method **3400** begins at block **3402**, where method **3400** pairs a wearable muscle interface device **2900** with a wearable head-mounted display **3110**. Method **3400** then proceeds to block **3404**, where content and/or user interface (UI) is displayed on the wearable head-mounted display **3110**.

[0461] Method **3400** then proceeds to block **3406**, where method **3400** determines if the displayed content and/or UI is navigable. If no, method **3400** returns to block **3404**. If yes, method **3400** proceeds to block **3408**, where the wearable muscle interface device **2900** detects muscle activity corresponding to a physical gesture performed by a user of the wearable system **2850** (i.e., at least one muscle activity sensor **2930** of the wearable muscle interface device **2900** detects the user's intentional hand/arm movements and positions), and wirelessly sends/transmits at least one signal corresponding to an identified gesture from the wearable muscle interface device **2900** to the wearable head-mounted display **3110**. The at least one signal may be sent by a transmitter **2950** of the wearable muscle interface device **2900** based on the muscle activity detected by at least one muscle activity sensor **2930** of the wearable muscle interface device **2900**.

[0462] Method **3400** then proceeds to block **33210**, where a receiver **3150** on the wearable head-mounted display **3110** receives the at least one signal directly from the transmitter **2950** of the wearable muscle interface device **2900**. A processor **320** of the wearable head-mounted display **3110** processes the at least one signal, and effects at least one interaction between the user **2800** and the wearable head-mounted display **3110** based on the processing of the at least one signal by processor **320** of the wearable head-mounted display **3110**.

[0463] Another example of a method employing a wearable system in accordance with the present systems, devices, and methods is illustrated in FIG. **35**. FIG. **35** is a flow-diagram showing a method **3500** of using wearable system **2850** to achieve hands-free access to and control of a portable electronic display. The wearable system **2850** includes a wearable muscle interface device **2900** and a wearable head-mounted display **3110**. Method **3500** includes five acts **3501**, **3502**, **3503**, **3504**, and **3505**, although those of skill in the art will appreciate that in alternative embodiments certain acts may be omitted and/or additional acts may be added. Those of skill in the art will also appreciate that the illustrated order of the acts is shown for exemplary purposes only and may change in alternative embodiments. For the purpose of method **3500**, the term “user” refers to a person that is wearing both the wearable muscle interface device **2900** (e.g., worn on at least one of the user's arms) and the wearable head-mounted display **3110** of the wearable system **2850** (e.g., worn on the user's head).

[0464] At **3501**, the user performs a physical gesture and muscle activity corresponding to the physical gesture is detected by at least muscle activity sensor **2930** of the wearable interface device **2900**. The muscle activity sensors **2930** may include at least one EMG sensor that detects electrical signals generated by the muscle activity and/or at least one MMG sensor that detects vibrations generated by the muscle activity. In addition to muscle activity, motion of the wearable muscle interface device **2900** corresponding to the physical gesture may be detected by at least one accelerometer **2960** on-board the wearable muscle interface device **2900**.

[0465] At **3502**, at least one signal is transmitted by a transmitter **2950** of the wearable muscle interface device **2900** based at least in part on the muscle activity detected at **3501**. As previously described, transmitter **2950** may be a wireless transmitter such that transmitting at least one signal by transmitter **2950** includes wirelessly transmitting the at least one signal by transmitter **2950**. In implementations in which motion of the wearable muscle interface device **2900** is also detected by at least one accelerometer **2960**, transmitting at least one signal by transmitter **2950** based at least in part on the muscle activity detected at **3501** may include transmitting at least one signal by transmitter **2950** based on both the muscle activity detected by at least one muscle activity sensor **2930** and the motion detected by at least one accelerometer **2960**.

[0466] In response to detecting muscle activity corresponding to a physical gesture performed by

the user at **3501**, method **3500** may include processing the detected muscle activity by a processor **2910** communicatively coupled in between the muscle activity sensors **2930** and the transmitter **2950** (e.g., to interpret the signals provided by the muscle activity sensors **2930** and/or to identify the user-performed gesture). In this case, transmitting at least one signal by transmitter **2950** based at least in part on the muscle activity detected at **3501** may include transmitting at least one signal by transmitter **2950** based at least in part on processing the detected muscle activity by the processor **2910** of the wearable muscle interface device **2900**.

[0467] At **3503**, the at least one signal is received directly from transmitter **2950** by a receiver **3150** of the wearable head-mounted display **3110**. In implementations where transmitter **2950** is a wireless transmitter, receiver **3150** may include a wireless receiver such that receiving the at least one signal by receiver **3150** includes wirelessly receiving the at least one signal by receiver **3150**. The at least one signal is transmitted directly from transmitter **2950** to receiver **3150** without routing through any intervening devices or systems.

[0468] At **3504**, the at least one signal received by receiver **3150** is processed by a processor **320** of the wearable head-mounted display **320**. Processing the at least one signal by the processor **320** of the wearable head-mounted display may include, for example, mapping or otherwise associating the at least one signal to/with one or more function(s) of the wearable head-mounted display **3110** based on data and/or instructions stored in a non-transitory computer-readable storage medium on-board the wearable head-mounted display **3110** (data and/or instructions which, when executed by the processor **320** of the wearable head-mounted display **3110**, cause the processor **320** of the wearable head-mounted display to effect one or more function(s) of the wearable head-mounted display **3110**).

[0469] At **3505**, at least one interaction between the user and the wearable head-mounted display **3110** is effected by the processor **320** of the wearable head-mounted display **3110** based on the processing of the at least one signal at **3504**. The at least one interaction may include any function or operation that prompts, modifies, changes, elicits, or otherwise involves visual information provided to the user by the wearable head-mounted display **3110**, including without limitation: interacting with visual material such as a photograph or video, navigating a menu, interacting with visually displayed elements such as a map or an element of a video game, and so on. Depending on the specific application, elements displayed on the wearable head-mounted display **3110** may or may not accommodate or otherwise take into account aspects of the user's environment that may be visible to the user. For example, elements displayed on the wearable head-mounted display **3110** may obscure, overlay, augment, highlight, block, be superimposed on, and/or semi-transparently project in front of elements of the user's environment.

[0470] As will be appreciated, the systems, devices, and methods that enable a user to access and interact with content displayed on an electronic display in an inconspicuous, hands-free manner described herein may be used for interaction with a portable electronic display in a wide range of applications, in virtually any application in which portable electronic displays are contemplated. By providing a discreet method of interacting with a wearable head-mounted display, a user is able to interact with such a display in any operating environment, including situations where overt gesturing (e.g. raising the hand to touch an input device provided on the wearable head-mounted display itself) is not desirable.

[0471] While various embodiments and illustrative examples have been described above, it will be appreciated that these embodiments and illustrative examples are not limiting, and the scope of the invention is defined by the following claims.

[0472] The various embodiments described herein provide, at least, a wearable system (e.g., **2850**) including a wearable muscle interface device (e.g., **2900**) that, in use, is to be worn on an arm of a user in order to enable hands-free access to, and control of, a wearable head-mounted display (e.g., **3110**). As described previously, the singular forms “a,” “an,” and “the” used in this specification and the appended claims include plural referents unless the content clearly dictates otherwise. In

some applications, it can be advantageous or otherwise desirable for such a wearable system (2850) to employ two or more wearable muscle interface devices (e.g., two or more wearable muscle interface devices 2900) worn on both of the user's arms (e.g., at least a respective wearable muscle interface device 2900 worn on each of the user's arms) as described in U.S. Pat. No. 9,372,535. Such may enable a greater number and/or diversity of gestures to be used to interact with content displayed on the wearable head-mounted display (e.g., 3110). Furthermore, in various embodiments the gesture-based interaction systems, devices, and methods described herein may be combined with other forms of touchless control, including without limitation: voice/speech-based control techniques such as Siri®, control techniques based on eye/vision tracking and/or blinking, electroencephalography (EEG), or the like.

[0473] Throughout this specification and the appended claims, the terms “head-mounted display” and “heads-up display” are used substantially interchangeably to refer to an electronic display that is worn on the head of a user and arranged so that at least one electronic display is positioned in front of at least one eye of the user when the head-mounted/heads-up display is worn on the head of the user. For greater clarity, “positioned in front of at least one eye of the user” means that the content displayed on or by the electronic display is displayed, projected, or otherwise provided generally in front of at least one eye of the user and is visible by that at least one eye regardless of the orientation or position of the user's head. An electronic display that is “positioned in front of at least one eye of the user” may correspond to a projection, reflection, refraction, diffraction, or direct display of optical signals and may be located in the user's direct line of sight or may be located off of the user's direct line of sight such that the user may or may not need to deliberately direct one or more eye(s), without necessarily moving their head, towards the electronic display in order to see (i.e., access) the content displayed thereby.

[0474] Throughout this specification and the appended claims, the term “gesture” is used to generally refer to a physical action (e.g., a movement, a stretch, a flex, a pose) performed or otherwise effected by a user. Any physical action performed or otherwise effected by a user that involves detectable muscle activity (detectable, e.g., by at least one appropriately positioned muscle activity sensor) and/or detectable motion (detectable, e.g., by at least one appropriately positioned inertial sensor, such as an accelerometer and/or a gyroscope) may constitute a gesture in the present systems, articles, and methods.

[0475] Throughout this specification and the appended claims the term “communicative” as in “communicative pathway,” “communicative coupling,” and in variants such as “communicatively coupled,” is generally used to refer to any arrangement for transferring and/or exchanging information. Exemplary communicative pathways include, but are not limited to, electrically conductive pathways (e.g., electrically conductive wires, electrically conductive traces), magnetic pathways (e.g., magnetic media), and/or optical pathways (e.g., optical fiber), and exemplary communicative couplings include, but are not limited to, electrical couplings, magnetic couplings, and/or optical couplings.

[0476] Throughout this specification and the appended claims, the term “provide” and variants such as “provided” and “providing” are frequently used in the context of signals. For example, a muscle activity sensor is described as “providing at least one signal” and an inertial sensor is described as “providing at least one signal.” Unless the specific context requires otherwise, the term “provide” is used in a most general sense to cover any form of providing a signal, including but not limited to: relaying a signal, outputting a signal, generating a signal, routing a signal, creating a signal, transducing a signal, and so on. For example, a surface EMG sensor may include at least one electrode that resistively or capacitively couples to electrical signals from muscle activity. This coupling induces a change in a charge or electrical potential of the at least one electrode which is then relayed through the sensor circuitry and output, or “provided,” by the sensor. Thus, the surface EMG sensor may “provide” an electrical signal by relaying an electrical signal from a muscle (or muscles) to an output (or outputs). In contrast, an inertial sensor may

include components (e.g., piezoelectric, piezoresistive, capacitive, etc.) that are used to convert physical motion into electrical signals. The inertial sensor may “provide” an electrical signal by detecting motion and generating an electrical signal in response to the motion.

[0477] Throughout this specification and the appended claims, “identifying” or “interpreting signals as” a gesture means associating a set of signals provided by one or more sensors (e.g., neuromuscular-signal sensors, such as EMG sensors, MMG sensors, muscle activity sensor(s), etc.) with a particular gesture. In the various embodiments described herein, “identifying” or “interpreting signals as” a gesture includes determining which gesture in a gesture library is most probable (relative to the other gestures in the gesture library) of being the gesture that a user has performed or is performing in order to produce the signals upon which the gesture identification is at least partially based. The wearable muscle interface devices described herein are generally not operative to identify any arbitrary gesture performed by a user. Rather, the wearable muscle interface devices described herein are operative to identify when a user performs one of a specified set of gestures, and that specified set of gestures is referred to herein as a gesture library. A gesture library may include any number of gestures, though a person of skill in the art will appreciate that the precision/accuracy of gesture identification may be inversely related to the number of gestures in the gesture library. A gesture library may be expanded by adding one or more gesture(s) or reduced by removing one or more gesture(s). Furthermore, in accordance with the present systems, articles, and methods, a gesture library may include a “rest” gesture corresponding to a state for which no activity is detected and/or an “unknown” gesture corresponding to a state for which activity is detected but the activity does not correspond to any other gesture in the gesture library.

[0478] Throughout this specification and the appended claims, infinitive verb forms are often used. Examples include, without limitation: “to detect,” “to provide,” “to transmit,” “to communicate,” “to process,” “to route,” and the like. Unless the specific context requires otherwise, such infinitive verb forms are used in an open, inclusive sense, that is as “to, at least, detect,” “to, at least, provide,” “to, at least, transmit,” and so on.

[0479] The above description of illustrated embodiments, including what is described in the Abstract, is not intended to be exhaustive or to limit the embodiments to the precise forms disclosed. Although specific embodiments of and examples are described herein for illustrative purposes, various equivalent modifications can be made without departing from the spirit and scope of the disclosure, as will be recognized by those skilled in the relevant art. The teachings provided herein of the various embodiments can be applied to other portable and/or wearable electronic devices, not necessarily the exemplary wearable electronic devices generally described above.

[0480] For instance, the foregoing detailed description has set forth various embodiments of the devices and/or processes via the use of block diagrams, schematics, and examples. Insofar as such block diagrams, schematics, and examples contain one or more functions and/or operations, it will be understood by those skilled in the art that each function and/or operation within such block diagrams, flowcharts, or examples can be implemented, individually and/or collectively, by a wide range of hardware, software, firmware, or virtually any combination thereof. In one embodiment, the present subject matter may be implemented via Application Specific Integrated Circuits (ASICs). However, those skilled in the art will recognize that the embodiments disclosed herein, in whole or in part, can be equivalently implemented in standard integrated circuits, as one or more computer programs executed by one or more computers (e.g., as one or more programs running on one or more computer systems), as one or more programs executed by one or more controllers (e.g., microcontrollers) as one or more programs executed by one or more processors (e.g., microprocessors, central processing units, graphical processing units), as firmware, or as virtually any combination thereof, and that designing the circuitry and/or writing the code for the software and or firmware would be well within the skill of one of ordinary skill in the art in light of the teachings of this disclosure.

[0481] When logic is implemented as software and stored in memory, logic or information can be

stored on any computer-readable medium for use by or in connection with any processor-related system or method. In the context of this disclosure, a memory is a computer-readable medium that is an electronic, magnetic, optical, or other physical device or means that contains or stores a computer and/or processor program. Logic and/or the information can be embodied in any computer-readable medium for use by or in connection with an instruction execution system, apparatus, or device, such as a computer-based system, processor-containing system, or other system that can fetch the instructions from the instruction execution system, apparatus, or device and execute the instructions associated with logic and/or information.

[0482] In the context of this specification, a “non-transitory computer-readable medium” can be any element that can store the program associated with logic and/or information for use by or in connection with the instruction execution system, apparatus, and/or device. The computer-readable medium can be, for example, but is not limited to, an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system, apparatus or device. More specific examples (a non-exhaustive list) of the computer readable medium would include the following: a portable computer diskette (magnetic, compact flash card, secure digital, or the like), a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM, EEPROM, or Flash memory), a portable compact disc read-only memory (CDROM), digital tape, and other non-transitory media.

[0483] The various embodiments described above can be combined to provide further embodiments. To the extent that they are not inconsistent with the specific teachings and definitions herein, all of the U.S. patents, U.S. patent application publications, U.S. patent applications, foreign patents, foreign patent applications and non-patent publications referred to in this specification and/or listed in the Application Data Sheet, including but not limited to U.S. patent application Ser. No. 14/505,836, U.S. Provisional Patent Application Ser. No. 61/897,097, U.S. Pat. No. 10,528,135, U.S. patent application Ser. No. 14/186,889, U.S. patent application Ser. No. 14/194,252, U.S. patent application Ser. No. 14/335,668, U.S. Pat. No. 10,152,082, U.S. patent application Ser. No. 14/461,044, U.S. patent application Ser. No. 14/465,194, U.S. Pat. Nos. 9,372,535, 9,788,789, 9,483,123, U.S. Provisional Patent Application Ser. No. 61/894,263, U.S. Provisional Patent Application Ser. No. 61/887,193, U.S. Provisional Patent Application Ser. No. 61/887,812, U.S. Pat. Nos. 10,101,809, 10,042,422, 9,389,694, 10,188,309, U.S. Provisional Patent Application Ser. No. 61/822,740, U.S. Pat. No. 10,188,309, U.S. Provisional Patent Application Ser. No. 61/915,338, and U.S. Provisional Patent Application Ser. No. 61/891,694, are incorporated herein by reference, in their entirety. Aspects of the embodiments can be modified, if necessary, to employ systems, circuits and concepts of the various patents, applications and publications to provide yet further embodiments.

[0484] These and other changes can be made to the embodiments in light of the above-detailed description. In general, in the following claims, the terms used should not be construed to limit the claims to the specific embodiments disclosed in the specification and the claims, but should be construed to include all possible embodiments along with the full scope of equivalents to which such claims are entitled. Accordingly, the claims are not limited by the disclosure.

Claims

1. A wearable apparatus for gesture control, comprising: one or more first sensors configured to contact skin on a wrist of a user when the wearable apparatus is worn by the user, wherein the one or more first sensors are configured to generate first signals associated with muscle activity of the user; an inertial sensor configured to generate second signals associated with a motion of the user; one or more processors configured to: receive the first signals generated by the one or more first sensors; receive the second signals generated by the inertial sensor; determine a gesture of the user based at least in part on an analysis of the first signals and the second signals; perform an action

associated with the gesture.

2. The apparatus of claim 1, wherein the one or more first sensors are positioned on a back-plate of a wristwatch.

3. The apparatus of claim 2, wherein the one or more first sensors comprise at least two contact sensors configured to contact the skin on the wrist of the user.

4. The apparatus of claim 2, wherein the one or more first sensors comprise an electromyography (EMG) sensor configured to detect electrical signals generated by the muscle activity of the user.

5. The apparatus of claim 4, wherein the EMG sensor comprises a first sensor electrode comprising a first electrically conductive plate and a second sensor electrode comprising a second electrically conductive plate.

6. The apparatus of claim 5, wherein the second sensor electrode is a ground electrode.

7. The apparatus of claim 1, wherein the second signals comprise rotation information associated with the motion of the user.

8. The apparatus of claim 1, wherein the analysis of the first signals and the second signals uses a machine learning algorithm to determine the gesture.

9. The apparatus of claim 1, wherein the action comprises outputting a flag that identifies the gesture.

10. The apparatus of claim 1, wherein the action comprises controlling an electronic device distinct from the wearable apparatus.

11. A method of gesture control with a wearable apparatus, the method comprising: generating, by one or more first sensors configured to contact skin on a wrist of a user when the wearable apparatus is worn by the user, first signals associated with muscle activity of the user; generating, by an inertial sensor, second signals associated with a motion of the user; receiving the first signals generated by the one or more first sensors; receiving the second signals generated by the inertial sensor; determining a gesture of the user based at least in part on an analysis of the first signals and the second signals; and performing an action associated with the gesture.

12. The method of claim 11, wherein the one or more first sensors are positioned on a back-plate of a wristwatch.

13. The method of claim 12, wherein the one or more first sensors comprise at least two contact sensors configured to contact the skin on the wrist of the user.

14. The method of claim 12, wherein the one or more first sensors comprise an electromyography (EMG) sensor configured to detect electrical signals generated by the muscle activity of the user.

15. The method of claim 14, wherein the EMG sensor comprises a first sensor electrode comprising a first electrically conductive plate and a second sensor electrode comprising a second electrically conductive plate.

16. The method of claim 15, wherein the second sensor electrode is a ground electrode.

17. The method of claim 11, wherein the second signals comprise rotation information associated with the motion of the user.

18. The method of claim 11, wherein the analysis of the first signals and the second signals comprises using a machine learning algorithm to determine the gesture.

19. The method of claim 11, wherein the action comprises outputting a flag that identifies the gesture.

20. A non-transitory computer-readable medium comprising one or more computer-executable instructions that, when executed by at least one processor of a computing device, cause the computing device to: generate, by one or more first sensors configured to contact skin on a wrist of a user when the wearable apparatus is worn by the user, first signals associated with muscle activity of the user; generate, by an inertial sensor, second signals associated with a motion of the user; receive the first signals generated by the one or more first sensors; receive the second signals generated by the inertial sensor; determine a gesture of the user based at least in part on an analysis of the first signals and the second signals; and perform an action associated with the gesture.

