

# US Patent & Trademark Office

## Patent Public Search | Text View

---

|                      |                      |
|----------------------|----------------------|
| United States Patent | 12397159             |
| Kind Code            | B2                   |
| Date of Patent       | August 26, 2025      |
| Inventor(s)          | Rondoni; John et al. |

---

### Microstimulation sleep disordered breathing (SDB) therapy device

---

#### Abstract

An apparatus includes an implantable stimulator to treat sleep disordered breathing (SDB) and at least one electrode associated with the stimulator. The apparatus may include a microstimulator including a housing to encapsulate at least stimulation circuitry and a control portion including a therapy manager to control the stimulation circuitry based on at least control information.

---

**Inventors:** Rondoni; John (Plymouth, MN), Dieken; David (Minneapolis, MN), Verzal; Kevin (Lino Lakes, MN)

**Applicant:** INSPIRE MEDICAL SYSTEMS, INC. (Golden Valley, MN)

**Family ID:** 1000008779718

**Assignee:** INSPIRE MEDICAL SYSTEMS, INC. (Golden Valley, MN)

**Appl. No.:** 18/231894

**Filed:** August 09, 2023

#### Prior Publication Data

| Document Identifier | Publication Date |
|---------------------|------------------|
| US 20230381518 A1   | Nov. 30, 2023    |

#### Related U.S. Application Data

continuation parent-doc US 17525458 20211112 US 11771901 child-doc US 18231894  
continuation parent-doc US 15774471 ABANDONED WO PCT/US2016/062546 20161117 child-doc US 17525458  
us-provisional-application US 62256680 20151117

---

#### Publication Classification

**Int. Cl.: A61N1/05 (20060101); A61N1/36 (20060101); A61N1/372 (20060101); A61N1/378 (20060101)**

**U.S. Cl.:**

**CPC A61N1/3611 (20130101); A61N1/0551 (20130101); A61N1/0558 (20130101); A61N1/36139 (20130101); A61N1/3614 (20170801); A61N1/37205 (20130101); A61N1/3787 (20130101);**

## **Field of Classification Search**

**CPC:** A61N (1/3611); A61N (1/0551); A61N (1/0558); A61N (1/36139); A61N (1/3614); A61N (1/37205); A61N (1/3787); A61N (1/3601); A61N (1/3605); A61N (1/36053); A61N (2005/0612); A61N (2005/0626); A61N (2005/0627); A61N (2005/063); A61N (2005/0631); A61N (2005/0643); A61N (2005/0651); A61N (2005/0653); A61N (2005/0665); A61N (5/0601); A61N (5/062); A61N (5/0622); A61N (5/067); A61N (1/0556); A61N (1/36078); A61N (1/36125); A61N (1/37229); A61N (1/375); A61N (1/37518); A61N (1/3756); A61N (1/36071); A61N (1/05); A61N (1/36007); A61N (1/0573); A61N (1/36021); A61N (1/37247); A61N (1/02); A61N (1/36057); A61N (1/36067); A61N (1/37211); A61N (1/37223); A61N (1/37235); A61N (1/3727); A61N (1/3754); A61P (11/00); A61P (11/16); A61B (17/00234); A61B (17/3403); A61B (2017/3413); A61B (2562/0219); A61B (5/08); A61B (5/11); A61B (5/4836)

---

## **References Cited**

### **U.S. PATENT DOCUMENTS**

| <b>Patent No.</b> | <b>Issued Date</b> | <b>Patentee Name</b> | <b>U.S. Cl.</b> | <b>CPC</b> |
|-------------------|--------------------|----------------------|-----------------|------------|
| 3456134           | 12/1968            | Ko                   | N/A             | N/A        |
| 3563245           | 12/1970            | McLean               | N/A             | N/A        |
| 3659615           | 12/1971            | Enger                | N/A             | N/A        |
| 3693625           | 12/1971            | Auphan               | N/A             | N/A        |
| 3807411           | 12/1973            | Harris et al.        | N/A             | N/A        |
| 4119103           | 12/1977            | Jirak                | N/A             | N/A        |
| 4613784           | 12/1985            | Haun et al.          | N/A             | N/A        |
| 4690143           | 12/1986            | Schroeppel           | N/A             | N/A        |
| 4780638           | 12/1987            | Reinelt et al.       | N/A             | N/A        |
| 4798206           | 12/1988            | Maddison et al.      | N/A             | N/A        |
| 5193540           | 12/1992            | Schulman et al.      | N/A             | N/A        |
| 5314451           | 12/1993            | Mulier               | N/A             | N/A        |
| 5324316           | 12/1993            | Schulman             | N/A             | N/A        |
| 5358514           | 12/1993            | Schulman et al.      | N/A             | N/A        |
| 5411538           | 12/1994            | Lin                  | N/A             | N/A        |
| 5431694           | 12/1994            | Snaper et al.        | N/A             | N/A        |
| 5489225           | 12/1995            | Julian               | N/A             | N/A        |
| 5615466           | 12/1996            | Safari et al.        | N/A             | N/A        |
| 5869189           | 12/1998            | Hagood, IV et al.    | N/A             | N/A        |
| 5906634           | 12/1998            | Flynn et al.         | N/A             | N/A        |
| 6131581           | 12/1999            | Leysieffer et al.    | N/A             | N/A        |
| 6185452           | 12/2000            | Schulman et al.      | N/A             | N/A        |

|         |         |                   |     |                 |
|---------|---------|-------------------|-----|-----------------|
| 6240316 | 12/2000 | Richmond et al.   | N/A | N/A             |
| 6269266 | 12/2000 | Leysieffer        | N/A | N/A             |
| 6337835 | 12/2001 | Sporn et al.      | N/A | N/A             |
| 6442413 | 12/2001 | Silver            | N/A | N/A             |
| 6470212 | 12/2001 | Weijand et al.    | N/A | N/A             |
| 6636767 | 12/2002 | Knudson et al.    | N/A | N/A             |
| 6764446 | 12/2003 | Wolinsky et al.   | N/A | N/A             |
| 6822343 | 12/2003 | Estevez           | N/A | N/A             |
| 6899976 | 12/2004 | Larson et al.     | N/A | N/A             |
| 6963157 | 12/2004 | Sato et al.       | N/A | N/A             |
| 7054692 | 12/2005 | Whitehurst        | N/A | N/A             |
| 7084605 | 12/2005 | Mickle et al.     | N/A | N/A             |
| 7130681 | 12/2005 | Gebhardt et al.   | N/A | N/A             |
| 7283874 | 12/2006 | Penner            | N/A | N/A             |
| 7292888 | 12/2006 | Deno et al.       | N/A | N/A             |
| 7365455 | 12/2007 | Hamel et al.      | N/A | N/A             |
| 7442465 | 12/2007 | Kim et al.        | N/A | N/A             |
| 7530956 | 12/2008 | Lewicke et al.    | N/A | N/A             |
| 7620451 | 12/2008 | Demarais et al.   | N/A | N/A             |
| 7629727 | 12/2008 | Whinnery          | N/A | N/A             |
| 7640061 | 12/2008 | He et al.         | N/A | N/A             |
| 7649305 | 12/2009 | Priya et al.      | N/A | N/A             |
| 7734343 | 12/2009 | Ransbury          | N/A | N/A             |
| 7881796 | 12/2010 | Scott et al.      | N/A | N/A             |
| 7896813 | 12/2010 | Sowelam et al.    | N/A | N/A             |
| 8039834 | 12/2010 | Wang et al.       | N/A | N/A             |
| 8108045 | 12/2011 | Biggs, Jr. et al. | N/A | N/A             |
| 8204595 | 12/2011 | Pianca et al.     | N/A | N/A             |
| 8224449 | 12/2011 | Carbunaru et al.  | N/A | N/A             |
| 8311632 | 12/2011 | Pless et al.      | N/A | N/A             |
| 8352025 | 12/2012 | Jacobson          | N/A | N/A             |
| 8359098 | 12/2012 | Lund et al.       | N/A | N/A             |
| 8406877 | 12/2012 | Smith et al.      | N/A | N/A             |
| 8433409 | 12/2012 | Johnson et al.    | N/A | N/A             |
| 8506495 | 12/2012 | Mi et al.         | N/A | N/A             |
| 8527068 | 12/2012 | Ostroff           | N/A | N/A             |
| 8666497 | 12/2013 | Janzig et al.     | N/A | N/A             |
| 8670823 | 12/2013 | Murtonen          | N/A | N/A             |
| 8682438 | 12/2013 | Schliecher et al. | N/A | N/A             |
| 8777863 | 12/2013 | Piaget et al.     | N/A | N/A             |
| 8923963 | 12/2013 | Bonner et al.     | N/A | N/A             |
| 9002470 | 12/2014 | Reinke et al.     | N/A | N/A             |
| 9078610 | 12/2014 | McKenna           | N/A | N/A             |
| 9084859 | 12/2014 | Connor            | N/A | N/A             |
| 9149644 | 12/2014 | Biggs, Jr. et al. | N/A | N/A             |
| 9168383 | 12/2014 | Jacobson et al.   | N/A | N/A             |
| 9186504 | 12/2014 | Gross             | N/A | A61N<br>1/37223 |
| 9216285 | 12/2014 | Boling et al.     | N/A | N/A             |
| 9220911 | 12/2014 | Gordon et al.     | N/A | N/A             |

|              |         |                    |        |                 |
|--------------|---------|--------------------|--------|-----------------|
| 9276348      | 12/2015 | Vadlamudi et al.   | N/A    | N/A             |
| 9364675      | 12/2015 | Deterre et al.     | N/A    | N/A             |
| 9398901      | 12/2015 | Tischendorf et al. | N/A    | N/A             |
| 9616242      | 12/2016 | Imran              | N/A    | N/A             |
| 9662066      | 12/2016 | Ledet et al.       | N/A    | N/A             |
| 9821159      | 12/2016 | Ackermann et al.   | N/A    | N/A             |
| 9889299      | 12/2017 | Ni                 | N/A    | N/A             |
| 9956398      | 12/2017 | Callegari et al.   | N/A    | N/A             |
| 9987488      | 12/2017 | Gelfand et al.     | N/A    | N/A             |
| 10195428     | 12/2018 | Scheiner           | N/A    | N/A             |
| 10716947     | 12/2019 | Sheldon et al.     | N/A    | N/A             |
| 2001/0010010 | 12/2000 | Richmond et al.    | N/A    | N/A             |
| 2002/0011300 | 12/2001 | Cass               | N/A    | N/A             |
| 2002/0053801 | 12/2001 | Herman             | N/A    | N/A             |
| 2002/0183791 | 12/2001 | Denker             | N/A    | N/A             |
| 2003/0056351 | 12/2002 | Wilkie et al.      | N/A    | N/A             |
| 2003/0141785 | 12/2002 | Sato et al.        | N/A    | N/A             |
| 2003/0153953 | 12/2002 | Park               | N/A    | N/A             |
| 2003/0171783 | 12/2002 | Tsukamoto et al.   | N/A    | N/A             |
| 2004/0015204 | 12/2003 | Whitehurst et al.  | N/A    | N/A             |
| 2004/0073267 | 12/2003 | Holzer             | N/A    | N/A             |
| 2004/0153127 | 12/2003 | Gordon et al.      | N/A    | N/A             |
| 2004/0185337 | 12/2003 | Ishizaki           | N/A    | N/A             |
| 2005/0012434 | 12/2004 | Pizzochero et al.  | N/A    | N/A             |
| 2005/0021100 | 12/2004 | Tsukamoto et al.   | N/A    | N/A             |
| 2005/0021108 | 12/2004 | Klosterman et al.  | N/A    | N/A             |
| 2005/0080349 | 12/2004 | Okada et al.       | N/A    | N/A             |
| 2005/0080472 | 12/2004 | Atkinson           | N/A    | N/A             |
| 2005/0085874 | 12/2004 | Davis et al.       | N/A    | N/A             |
| 2005/0110277 | 12/2004 | Adamson et al.     | N/A    | N/A             |
| 2005/0113710 | 12/2004 | Stahmann et al.    | N/A    | N/A             |
| 2005/0165465 | 12/2004 | Pianca et al.      | N/A    | N/A             |
| 2005/0251216 | 12/2004 | Hill               | N/A    | N/A             |
| 2005/0267547 | 12/2004 | Knudson et al.     | N/A    | N/A             |
| 2005/0274176 | 12/2004 | Thiesen et al.     | N/A    | N/A             |
| 2006/0009830 | 12/2005 | Atkinson           | N/A    | N/A             |
| 2006/0020297 | 12/2005 | Gerber et al.      | N/A    | N/A             |
| 2006/0041277 | 12/2005 | Deem               | 607/3  | A61N<br>1/36117 |
| 2006/0136004 | 12/2005 | Cowan              | N/A    | N/A             |
| 2006/0167523 | 12/2005 | Tehrani            | N/A    | N/A             |
| 2006/0184204 | 12/2005 | He                 | N/A    | N/A             |
| 2006/0184206 | 12/2005 | Baker, III et al.  | N/A    | N/A             |
| 2006/0217776 | 12/2005 | White et al.       | N/A    | N/A             |
| 2006/0252976 | 12/2005 | Rosero             | N/A    | N/A             |
| 2007/0007473 | 12/2006 | Kumagai            | N/A    | N/A             |
| 2007/0049842 | 12/2006 | Hill et al.        | N/A    | N/A             |
| 2007/0067000 | 12/2006 | Strother           | 607/36 | A61N 1/375      |
| 2007/0078492 | 12/2006 | Tozzi et al.       | N/A    | N/A             |
| 2007/0118183 | 12/2006 | Gelfand et al.     | N/A    | N/A             |

|              |         |                  |         |                 |
|--------------|---------|------------------|---------|-----------------|
| 2007/0150020 | 12/2006 | Hokanson et al.  | N/A     | N/A             |
| 2007/0173893 | 12/2006 | Pitts            | N/A     | N/A             |
| 2007/0179581 | 12/2006 | Dennis et al.    | N/A     | N/A             |
| 2007/0255333 | 12/2006 | Giftakis et al.  | N/A     | N/A             |
| 2007/0255379 | 12/2006 | Williams         | 607/116 | A61N 1/05       |
| 2007/0284969 | 12/2006 | Xu               | N/A     | N/A             |
| 2007/0288077 | 12/2006 | Bulkes et al.    | N/A     | N/A             |
| 2007/0293904 | 12/2006 | Gelbart et al.   | N/A     | N/A             |
| 2007/0293906 | 12/2006 | Cowan            | 607/41  | A61N<br>1/36071 |
| 2008/0004904 | 12/2007 | Tran             | N/A     | N/A             |
| 2008/0039904 | 12/2007 | Bulkes           | N/A     | N/A             |
| 2008/0067618 | 12/2007 | Wang et al.      | N/A     | N/A             |
| 2008/0103407 | 12/2007 | Bolea            | N/A     | N/A             |
| 2008/0103545 | 12/2007 | Bolea            | N/A     | N/A             |
| 2008/0109044 | 12/2007 | Gramse et al.    | N/A     | N/A             |
| 2008/0119421 | 12/2007 | Tuszynski et al. | N/A     | N/A             |
| 2008/0119911 | 12/2007 | Rosero           | N/A     | N/A             |
| 2008/0136292 | 12/2007 | Thiesen          | N/A     | N/A             |
| 2008/0150396 | 12/2007 | Clingman et al.  | N/A     | N/A             |
| 2008/0200963 | 12/2007 | Pless et al.     | N/A     | N/A             |
| 2008/0203849 | 12/2007 | Hagg             | N/A     | N/A             |
| 2008/0262562 | 12/2007 | Roberts et al.   | N/A     | N/A             |
| 2008/0312720 | 12/2007 | Tran et al.      | N/A     | N/A             |
| 2008/0312725 | 12/2007 | Penner           | N/A     | N/A             |
| 2009/0025773 | 12/2008 | Stark            | N/A     | N/A             |
| 2009/0152990 | 12/2008 | Brown et al.     | N/A     | N/A             |
| 2009/0160292 | 12/2008 | Whinnery         | N/A     | N/A             |
| 2009/0167034 | 12/2008 | Waters et al.    | N/A     | N/A             |
| 2009/0167110 | 12/2008 | Berkcan et al.   | N/A     | N/A             |
| 2009/0171404 | 12/2008 | Irani et al.     | N/A     | N/A             |
| 2009/0171408 | 12/2008 | Solem            | N/A     | N/A             |
| 2009/0171448 | 12/2008 | Eli              | N/A     | N/A             |
| 2009/0179523 | 12/2008 | Wang et al.      | N/A     | N/A             |
| 2009/0216292 | 12/2008 | Pless et al.     | N/A     | N/A             |
| 2010/0049269 | 12/2009 | Tran et al.      | N/A     | N/A             |
| 2010/0063557 | 12/2009 | Imran            | N/A     | N/A             |
| 2010/0076517 | 12/2009 | Imran            | N/A     | N/A             |
| 2010/0117488 | 12/2009 | Wang et al.      | N/A     | N/A             |
| 2010/0133954 | 12/2009 | Despesse et al.  | N/A     | N/A             |
| 2010/0160994 | 12/2009 | Feldman et al.   | N/A     | N/A             |
| 2010/0171394 | 12/2009 | Glenn et al.     | N/A     | N/A             |
| 2010/0317929 | 12/2009 | Mi et al.        | N/A     | N/A             |
| 2010/0317977 | 12/2009 | Piaget et al.    | N/A     | N/A             |
| 2010/0317978 | 12/2009 | Maile et al.     | N/A     | N/A             |
| 2011/0034811 | 12/2010 | Naujokat et al.  | N/A     | N/A             |
| 2011/0046506 | 12/2010 | Durand et al.    | N/A     | N/A             |
| 2011/0077708 | 12/2010 | Ostroff          | N/A     | N/A             |
| 2011/0112601 | 12/2010 | Meadows          | 607/42  | A61N<br>1/37223 |

|              |         |                           |     |     |
|--------------|---------|---------------------------|-----|-----|
| 2011/0152706 | 12/2010 | Christopherson et al.     | N/A | N/A |
| 2011/0202119 | 12/2010 | Ni et al.                 | N/A | N/A |
| 2011/0208010 | 12/2010 | McKenna                   | N/A | N/A |
| 2012/0089153 | 12/2011 | Christopherson et al.     | N/A | N/A |
| 2012/0089199 | 12/2011 | Bolea et al.              | N/A | N/A |
| 2013/0066393 | 12/2012 | Gross et al.              | N/A | N/A |
| 2013/0085537 | 12/2012 | Mashiach                  | N/A | N/A |
| 2013/0231726 | 12/2012 | Johnson et al.            | N/A | N/A |
| 2014/0330331 | 12/2013 | Thompson-Nauman<br>et al. | N/A | N/A |
| 2015/0012059 | 12/2014 | Kim et al.                | N/A | N/A |
| 2015/0012063 | 12/2014 | Chen                      | N/A | N/A |
| 2015/0073247 | 12/2014 | Gordon et al.             | N/A | N/A |
| 2015/0105836 | 12/2014 | Bonner et al.             | N/A | N/A |
| 2015/0224325 | 12/2014 | Imran                     | N/A | N/A |
| 2016/0067497 | 12/2015 | Levine et al.             | N/A | N/A |
| 2020/0147377 | 12/2019 | Hoffer                    | N/A | N/A |

## FOREIGN PATENT DOCUMENTS

| Patent No.  | Application<br>Date | Country | CPC |
|-------------|---------------------|---------|-----|
| 1175919     | 12/2001             | EP      | N/A |
| 2007281015  | 12/2006             | JP      | N/A |
| 98/43700    | 12/1997             | WO      | N/A |
| 20060244868 | 12/2005             | WO      | N/A |
| 2007059343  | 12/2006             | WO      | N/A |
| 2007059343  | 12/2006             | WO      | N/A |
| 2007068284  | 12/2006             | WO      | N/A |
| 2007080487  | 12/2006             | WO      | N/A |
| 2007109272  | 12/2006             | WO      | N/A |
| 2007149462  | 12/2006             | WO      | N/A |
| 2008019384  | 12/2007             | WO      | N/A |
| 2008085886  | 12/2007             | WO      | N/A |
| 2009048385  | 12/2008             | WO      | N/A |
| 2010030700  | 12/2009             | WO      | N/A |
| 2010039853  | 12/2009             | WO      | N/A |
| 2012112186  | 12/2011             | WO      | N/A |
| 2013067496  | 12/2012             | WO      | N/A |
| 2014169145  | 12/2013             | WO      | N/A |
| 2015200720  | 12/2014             | WO      | N/A |

## OTHER PUBLICATIONS

US 8,886,318 B2, 11/2014, Jacobson et al. (withdrawn) cited by applicant

Boston Scientific, Precision Spectra™ System Implantable Pulse Generator, Directions for Use, 2015, 18 pages. cited by applicant

Bal Seal Engineering Inc., Next-Generation IPGs Integrate Connector System Components, Sep. 17, 2014, 3 pages. cited by applicant

Bal Seal Engineering Inc., The Technologies behind the Next Generation of Neuromodulation Devices, May 3, 2016, 3 pages. cited by applicant

Loeb, Gerald E., et al., "BION TM System for Distributed Neural Prosthetic Interfaces.", Medical

Engineering & Physics, vol. 23, No. 1, 2001, pp. 9-18, [https://doi.org/10.1016/S1350-4533\(01\)00011-X](https://doi.org/10.1016/S1350-4533(01)00011-X). cited by applicant

Medtronic, "Medtronic Announces First Human Implant of World's Smallest, Minimally Invasive Cardiac Pacemaker", Dec. 9, 2013, (2 pages). cited by applicant

Zheng et al., In Vivo Self-Powered Wireless Cardiac Monitoring via Implantable Triboelectric Nanogenerator, ACS Nano, Jun. 2, 2016, pp. 1-2. cited by applicant

Bai et al., Membrane-Based Self-Powered Triboelectric Sensors for Pressure Change Detection and Its Uses in Security Surveillance and Healthcare Monitoring, Advanced Functional Materials Journal, 2014, pp. 5807-5813. cited by applicant

Ye Ma et al., Self-Powered, One-Stop, and Multifunctional Implantable Triboelectric Active Sensor for Real-Time Biomedical Monitoring, Nano Letters, Sep. 8, 2016, pp. 1-2. cited by applicant

Clark et al., Piezoelectric Energy Harvesting for Bio-MEMS Applications, University of Pittsburgh, 2009, pp. 405-430. cited by applicant

---

*Primary Examiner:* Layno; Carl H

*Assistant Examiner:* Dinh; Ahn-Khoa N

*Attorney, Agent or Firm:* DICKE, BILLIG & CZAJA, PLLC

---

## **Background/Summary**

CROSS-REFERENCE (1) This application is a continuation of U.S. patent application Ser. No. 17/525,458, filed Nov. 12, 2021, now U.S. Pat. No. 11,771,901 B2, which is a continuation application of U.S. patent application Ser. No. 15/774,471, filed May 8, 2018, and abandoned, which is a National Stage Application of, and that claims priority to PCT Application No. PCT/US2016/062546, filed Nov. 17, 2016, which claims the benefit of U.S. Provisional Patent Application No. 62/256,680, filed Nov. 17, 2015, all of which are incorporated herein by reference.

### **BACKGROUND**

(1) Treating sleep disordered breathing has led to improved sleep quality for some patients.

---

## **Description**

### **BRIEF DESCRIPTION OF THE DRAWINGS**

- (1) FIG. 1 is a block diagram schematically representing a microstimulation therapy device as implanted within a patient's body, according to one example of the present disclosure.
- (2) FIG. 2 is a block diagram schematically representing an implanted microstimulation therapy device, according to one example of the present disclosure.
- (3) FIG. 3 is a block diagram schematically representing a microstimulation therapy device juxtaposed relative to a nerve, according to one example of the present disclosure.
- (4) FIG. 4 is a block diagram schematically representing a microstimulation therapy device juxtaposed relative to a nerve, according to one example of the present disclosure.
- (5) FIG. 5 is a block diagram schematically representing a microstimulator of microstimulation therapy device, according to one example of the present disclosure.
- (6) FIG. 6A is a block diagram schematically representing a power element, according to one example of the present disclosure.
- (7) FIG. 6B is a block diagram schematically representing an energy harvesting arrangement, according to one example of the present disclosure.

(8) FIG. 6C is a diagram schematically representing at least a charging station in association with a patient support, according to one example of the present disclosure.

(9) FIG. 7 is a block diagram schematically representing a communication element, according to one example of the present disclosure.

(10) FIG. 8 is a diagram schematically representing a microstimulator of a microstimulation therapy device including a sensing function, according to one example of the present disclosure.

(11) FIG. 9A is a block diagram schematically representing a sensor, according to one example of the present disclosure.

(12) FIG. 9B is a block diagram schematically representing different sensing arrangements, according to one example of the present disclosure.

(13) FIG. 10 is a block diagram schematically representing sensor types, according to one example of the present disclosure.

(14) FIG. 11 is a diagram schematically representing a sensor array implanted in a head/neck region, according to one example of the present disclosure.

(15) FIG. 12 is a block diagram schematically representing mechanical coupling arrangements, according to one example of the present disclosure.

(16) FIG. 13 is a block diagram schematically representing electrical coupling arrangements, according to one example of the present disclosure.

(17) FIG. 14A is a diagram schematically representing a microstimulation therapy device implanted relative to a nerve, according to one example of the present disclosure.

(18) FIG. 14B is a sectional view schematically representing the implanted microstimulation therapy device of FIG. 14A, according to one example of the present disclosure.

(19) FIG. 15A is a diagram schematically representing a microstimulation therapy device implanted relative to a nerve, according to one example of the present disclosure.

(20) FIG. 15B is a sectional view schematically representing the implanted microstimulation therapy device of FIG. 15A, according to one example of the present disclosure.

(21) FIG. 16A is a diagram schematically representing a microstimulation therapy device implanted relative to a nerve, according to one example of the present disclosure.

(22) FIG. 16B is a sectional view schematically representing the implanted microstimulation therapy device of FIG. 16A, according to one example of the present disclosure.

(23) FIG. 17A is a diagram schematically representing a microstimulation therapy device implanted relative to a nerve, according to one example of the present disclosure.

(24) FIG. 17B is a sectional view schematically representing the implanted microstimulation therapy device of FIG. 17A, according to one example of the present disclosure.

(25) FIG. 17C is a perspective view schematically representing a helically-shaped flange of the therapy device of FIG. 17A-17B, according to one example of the present disclosure.

(26) FIG. 17D is a sectional view as taken along lines 17D-17D of FIG. 17C and schematically representing an axial array of electrodes, according to one example of the present disclosure.

(27) FIG. 18A is a diagram schematically representing a microstimulation therapy device implanted relative to a nerve, according to one example of the present disclosure.

(28) FIG. 18B is a perspective view schematically representing the microstimulation therapy device of FIG. 18A, according to one example of the present disclosure.

(29) FIG. 18C is a sectional view schematically representing the implanted microstimulation therapy device of FIG. 18A, according to one example of the present disclosure.

(30) FIG. 19A is a perspective view schematically representing an electrode cuff of a stimulation therapy device, according to one example of the present disclosure.

(31) FIG. 19B is a sectional view as taken along lines 19B-19B in FIG. 19A, which schematically represents a cuff electrode, according to one example of the present disclosure.

(32) FIG. 19C is a sectional view as taken along lines 19C-19C in FIG. 19A, which schematically represents a cuff electrode, according to one example of the present disclosure.



- (33) FIG. 20A is a perspective view schematically representing an electrode cuff for a stimulation therapy device, according to one example of the present disclosure.
- (34) FIG. 20B is a perspective view schematically representing an electrode cuff for a stimulation therapy device, according to one example of the present disclosure.
- (35) FIG. 20C is a partial end view schematically representing an electrode cuff, according to one example of the present disclosure.
- (36) FIG. 21A is a diagram schematically representing a microstimulation therapy device, according to one example of the present disclosure.
- (37) FIG. 21B is a diagram schematically representing an implanted microstimulation therapy device secured relative to a bony structure, according to one example of the present disclosure.
- (38) FIG. 22 is a diagram schematically representing antenna arrangements associated with a microstimulation therapy device, according to one example of the present disclosure.
- (39) FIG. 23A is a diagram schematically representing a microstimulation therapy device implanted within at least a portion of the vasculature, according to one example of the present disclosure.
- (40) FIG. 23B is a diagram schematically representing a microstimulation therapy device implanted within at least a portion of the vasculature, according to one example of the present disclosure.
- (41) FIG. 24 is a block diagram schematically representing a therapy manager, according to one example of the present disclosure.
- (42) FIG. 25A is a block diagram schematically representing a control portion, according to one example of the present disclosure.
- (43) FIG. 25B is a block diagram schematically representing a user interface, according to one example of the present disclosure.
- (44) FIG. 26 is a flow diagram schematically representing aspects associated with a method for microstimulation, according to one example of the present disclosure.
- (45) FIG. 27 is a block diagram schematically representing aspects associated with a method for microstimulation, according to one example of the present disclosure.

#### DETAILED DESCRIPTION

(46) In the following Detailed Description, reference is made to the accompanying drawings which form a part hereof, and in which is shown by way of illustration specific examples of the present disclosure which may be practiced. In this regard, directional terminology, such as “top,” “bottom,” “front,” “back,” “leading,” “trailing,” etc., is used with reference to the orientation of the Figure(s) being described. Because components of at least some examples of the present disclosure can be positioned in a number of different orientations, the directional terminology is used for purposes of illustration and is in no way limiting. It is to be understood that other examples may be utilized and structural or logical changes may be made without departing from the scope of the present disclosure. The following detailed description, therefore, is not to be taken in a limiting sense.

(47) In at least some examples of the present disclosure, an implantable microstimulation therapy device is employed in association with a therapy for sleep disordered breathing. In some examples, the microstimulation therapy device includes a microstimulator defining a housing sized (e.g. a volume) and/or shaped to facilitate a minimally invasive implantation that is performed in close proximity to a nerve to be stimulated by the microstimulator. In some examples, at least the housing of the microstimulator has a volume and a shape to enable the microstimulator to be secured directly against the nerve to be stimulated. In some examples, an electrode structure extends from the housing and is also directly secured against, or at least coupled relative to, the nerve to be stimulated.

(48) In some examples, a housing of the microstimulator has a volume and a shape to enable the microstimulator to be secured against or relative to other body structures in proximity to the nerve to be stimulated while circuitry within the housing is electrically coupled relative to the nerve via an electrode structure extending outwardly from a housing of the microstimulator.

(49) With this in mind, the terms “microstimulation” and/or “microstimulator” refer to the size (e.g.

including but not limited to volume) and/or shape of a housing of a therapy device which enable its placement in a minimally invasive manner and/or fixation in close proximity to a target nerve. In some examples, a microstimulator is sized and/or shaped to be fully implantable via a single incision. In some examples, the single incision is located in a head/neck region of the patient. In some examples, the housing of the microstimulator has a volume at least one order of magnitude less than a volume of commercially available, pectorally implantable pulse generator, such as traditional pacemakers, cardio-defibrillators, etc. In some examples, the housing of the microstimulator has a volume at least two orders of magnitude less than a volume of commercially available, pectorally implantable pulse generator, such as traditional pacemakers, cardio-defibrillators, etc.

(50) In some examples, an outer surface of the housing of the microstimulator is electrically nonconductive such that even direct contact against the target nerve does not electrically couple circuitry within the microstimulator relative to the target nerve. Instead, such electrical coupling is implemented via an electrode structure extending outwardly from the housing of the microstimulator. However, in some examples, at least one electrically conductive element is present on the outer surface of the housing of the microstimulator such that direct contact against the target nerve does at least partially electrically couple the circuitry within the microstimulator relative to the target nerve.

(51) In some examples, the microstimulator is implanted via nonvascular techniques and/or implanted in a subcutaneous location which is also extravascular, i.e. not within the vasculature (e.g. veins, arteries), cardiac structures, etc. In some examples, the microstimulator is implanted in a head/neck region, which is non-pectoral and as such also is a non-cardiac implantation.

(52) These examples, and additional examples, are described in more detail in association with at least FIGS. 1-27.

(53) FIG. 1 is diagram schematically representing a patient environment 20 including a patient 22 having a microstimulation therapy device 32 implanted within a head/neck region 24 of the patient, according to one example of the present disclosure. As shown in FIG. 1, in some examples, therapy device 32 is implanted subcutaneously in proximity to a target nerve 30. Stimulation of the target nerve 30 via therapy device 32 causes contraction of at least some muscles innervated via the target nerve 30. In some examples, the target nerve 30 and associated muscle(s) are associated with maintaining and/or restoring patency of the upper airway 36. Various aspects regarding the implantation and deployment of microstimulation therapy device 32 are described in association with at least FIGS. 2-25.

(54) FIG. 2 is a diagram of a patient environment 50 in the head/neck region 24 (FIG. 1), according to one example of the present disclosure. As shown in FIG. 2, in some examples therapy device 32 (e.g. a microstimulator device) is sized and/or shaped to be fully implanted within a subcutaneous environment 74 below at least the skin 70 through a single incision 72. Accordingly, FIG. 2 at least partially illustrates and represents the result of a minimally invasive implantation of therapy device 32 via a percutaneous pathway, non-vascular pathway, or analogous technique to place therapy device 32 in proximity to target nerve 30.

(55) This arrangement avoids several factors associated with implantation of a commercially available, pectorally implanted pulse generator and associated leads. For instance, such pectoral implantation involves more incisions, creating a pouch in the body to receive the pulse generator, tunneling a path for a lead to extend from the pulse generator to the target nerve, etc. While generally effective, such procedures involve a larger surgical field, more incisions, a long duration surgical event, etc. Moreover, because the lead will extend from the pectoral region into and through substantially the entire neck region, the lead may be subject to stresses and/or stability challenges associated with normal movements of the neck. Both the implantation and/or location of these various elements may contribute to patient comfort and long term effectiveness.

(56) Accordingly, via at least some examples of the present disclosure, a minimally invasive

implantation technique is implemented, thereby avoiding a number of challenges posed by pectoral implantation techniques of a pulse generator and associated lead(s).

(57) In addition, in some examples, employing a minimally invasive implant procedure in a head/neck region in proximity to the target nerve to be stimulated, with the implant comprising a relatively small microstimulation therapy device locatable in proximity to the target nerve, may enable increased patient eligibility for receiving magnetic resonance imaging (MRI). For instance, in such examples, the patient may be eligible for a body coil MR scan since no components of the microstimulation therapy device would be present in the torso. This arrangement stands in sharp contrast to at least some commercially available pectorally implanted therapy devices, which may prohibit such body coil MR scans. As such, at least some examples of the present disclosure may enable the microstimulation therapy device to be eligible to be labeled as conditionally acceptable for a body coil MR scan or other limited form of MR imaging.

(58) With further reference to at least FIGS. 1-2, in some examples, such as the case of obstructive sleep apnea, the nerve(s) 30 may include (but are not limited to) the nerve(s) and muscles related to causing movement of the tongue and related musculature to restore upper airway patency. In some examples, the nerve(s) 30 may include (but are not limited to) the hypoglossal nerve and the muscles may include (but are not limited to) the genioglossus muscle.

(59) As further shown in FIG. 2, microstimulation therapy device 32 is coupled (via coupling 62) relative to target nerve 30 within the subcutaneous environment 74. Notably, with the subcutaneous environment 74 being in the head/neck region 24, complications associated with a cardiac environment are avoided. Moreover, the microstimulation therapy device 32 is implanted in an extravascular manner, i.e. without the complications of introducing and delivering a device into and through the vasculature of the body.

(60) In some examples, the microstimulation therapy device 32 is mechanically coupled relative to the nerve 30, thereby at least partially securing the therapy device 32 within the subcutaneous environment 74. At least some specific examples of such mechanical coupling are shown and described later in association with at least FIGS. 12 and 14A-18D.

(61) In some examples, the microstimulation therapy device 32 is electrically coupled relative to the nerve 30, thereby at least partially electrically coupling the therapy device 32 relative to the nerve 30 within the subcutaneous environment 74. At least some specific examples of such electrical coupling are shown and described later in association with at least FIGS. 13 and 14A-18D.

(62) In some examples, such mechanical coupling and electrical coupling may be implemented via a single element or via multiple elements, with some elements providing both mechanical and electrical coupling.

(63) FIG. 3 is a block diagram schematically representing a therapy arrangement 80, according to one example of the present disclosure. As shown in FIG. 3, in arrangement 80, the microstimulation therapy device 32 is directly coupled relative to the nerve 30. In some examples, such coupling includes a direct mechanical coupling without a direct electrical coupling. In some examples, such coupling includes a direct mechanical coupling and a direct electrical coupling. At least some instances of the arrangement 80 are shown and described later in association with at least FIGS. 12-13 and 14A-18D.

(64) FIG. 4 is a block diagram schematically representing a therapy arrangement 90, according to one example of the present disclosure. As shown in FIG. 4, in arrangement 90, the microstimulation therapy device 32 is not directly coupled relative to the nerve 30. In some examples, such coupling includes an indirect electrical coupling of the therapy device 32 and nerve 30. For instance, in some examples, the indirect electrical coupling includes circuitry within therapy device 32 being electrically coupled to the nerve 30 via conductive elements located at some distance from a surface of a housing of the therapy device. In some examples, such coupling includes an indirect mechanical coupling of therapy device 32 relative to nerve 30 via the therapy

device mechanically engaging at least some portion of the subcutaneous environment **74** other than nerve **30**. At least some instances of the arrangement **90** are shown and described later in association with at least FIGS. **12-13** and **14A-18D**.

(65) With this general arrangement of FIGS. **1-4** in mind, it will be understood that at least some implementations associated with FIGS. **5-25** provide more specific examples of various implementations and details regarding the operation and interaction of at least some aspects of a microstimulation therapy device relative to a target nerve **30**.

(66) Moreover, at least some examples of the present disclosure result in a more comfortable placement of the therapy device than commercially available injectable stimulators. In addition, at least some example therapy devices of the present disclosure are more securely fixed in place within the patient's body than a commercially available injectable stimulator, which tend to migrate within the patient's body. In another aspect, applying nerve stimulation via at least some examples of the present disclosure enhances patient comfort as compared to at least some commercially available direct muscle stimulators, which may tend to inhibit patient comfort and/or which may ineffectively engage the patient anatomy.

(67) FIG. **5** is a block diagram schematically representing a microstimulation therapy device **100**, according to one example of the present disclosure. In some examples, therapy device **100** comprises at least some of substantially the same features and attributes as the previously described microstimulation therapy devices and arrangements (**32** in FIGS. **1-4**).

(68) As shown in FIG. **5**, therapy device **100** includes power element **110**, stimulation circuitry **112**, communication element **114**, and a control portion **120** having therapy manager **122**. In some examples, the control portion **120** comprises at least some of substantially the same features and attributes as control portion **1700** as described in association with FIG. **25A** and/or therapy manager **122** comprises at least some of substantially the same features and attributes as therapy manager **1705** as described in association with FIG. **25A** (or therapy manager **1600** in FIG. **24**).

(69) In some examples, power element **110** provides power for the operation of microstimulation therapy device **100**. At least some aspects of power element **110** are further described later in association with at least FIG. **6A**.

(70) In some examples, stimulation circuitry **112** can generate electrical signals deliverable through a stimulation element suitable for exciting a target nerve associated with muscles that can restore airway patency. In some examples, stimulation circuitry **112** produces at least substantially the same type and manner of stimulation signals as a commercially available implantable pulse generator, but with therapy device **100** having a substantially smaller size and/or shape as previously noted. For instance, in some examples, the therapy device **100** (including stimulator circuitry **112**) has a volume at least one order of magnitude less than a volume of a commercially available implantable pulse generator (IPG) which is used for treating sleep disordered breathing and which is implanted at a pectoral location. In some examples, therapy device **100** has a volume at least two orders of magnitude less than a volume of such commercially available, pectorally implantable pulse generators.

(71) In some examples, the signals are adapted to directly stimulate nerve **30** innervating upper-airway-related muscles. In some examples, such as the case of obstructive sleep apnea, the nerves **30** may include (but are not limited to) the nerve **30** and associated muscles responsible for causing movement of the tongue and related musculature to restore airway patency. In some examples, the nerves **76** may include (but are not limited to) the hypoglossal nerve and the muscles may include (but are not limited to) the genioglossus muscle.

(72) With further reference to FIG. **5**, in some examples communication element **114** enables at least some of the components of microstimulation therapy device **100** to communicate with devices, components, modules, etc. which are external to therapy device **100**, whether such devices, components, modules, etc. are located elsewhere within the patient's body and/or located external to the patient's body. At least some aspects of the communication element **114** are further

described later in association with at least FIG. 7.

(73) In some examples, a therapy manager **122** comprises part of or is incorporated within the therapy device **100**, such as being part of control portion **120**. As such, therapy manager **122** is “on board” the therapy device **100**. In some examples, a therapy manager is external to the therapy device **100** but is at least intermittently coupled to and/or in communication with the on-board therapy manager **122**. In some examples, therapy manager **122** implements sleep disordered breathing (SDB) stimulation therapy but, as part of control portion **120**, is also responsible for managing at least some general operations of therapy device **100**.

(74) FIG. 6A is a block diagram schematically representing the power element **110**, according to one example of the present disclosure. As represented in FIG. 6A, in some examples power element **110** may be implemented via at least one of various power modalities such as a rechargeable modality **140**, a storage modality **142**, and/or an energy harvesting modality **144**.

(75) In some examples, the rechargeable modality **140** employs a handheld battery-operated charger external to the patient's body. On a periodic basis, the charger is placed in close proximity to the implanted microstimulation therapy device **100** to apply a fast charging protocol to ensure the therapy device **32** has sufficient power for implementing the therapy overnight. In some examples, the periodic basis is daily, weekly, or monthly.

(76) In some examples, the rechargeable modality **140** includes an inductive element (e.g. antenna) within or associated with the microstimulation therapy device **100** and via a magnetic alignment of an antenna within the handheld charger, energy is transferred from the charger to the power element **110** within the therapy device **100**. In some examples, the rechargeable modality **140** employs piezoelectric transducer(s) associated with the power element **110** to affect an ultrasonic energy transfer from the handheld charger to the power element **110** within the therapy device **100**.

(77) In some examples, the rechargeable modality **140** involves generally continuous charging in which an object in the patient's sleep environment (such as a pillow, bed, garment, etc.) includes a power source/element having an antenna to implement energy transfer to the power element **110** within the therapy device **100**. In some examples, the power element **110** includes multiple antennas, each oriented in a different direction or position, and the external object (e.g. pillow, bed, etc.) includes multiple antennas oriented in different directions or positions, thereby reducing alignment sensitivity of the charging elements. In one aspect, this form of generally continuous charging is sometimes referred to as an automatic charging mode.

(78) In some examples, the power element **110** includes a rectenna, which is a form of antenna that receives electromagnetic waves (e.g. radiofrequency waves) applied via an external device and converts those waves into direct current electricity for use by the therapy device **110**.

(79) It will be understood that in at least some of the various examples of the rechargeable modality **140**, the power element **110** includes at least some short-term energy storage capability sufficient to enable stimulation therapy for at least one treatment period (e.g. a daily sleep period).

(80) As further shown in FIG. 6A, in some examples the power element **110** comprises a storage modality **142**. In some examples, the energy storage modality **142** is implemented via a long term rechargeable battery, such as but not limited to, a Lithium-Ion battery having high energy density. In some examples, the energy storage modality **142** is implemented via a supercapacitor, which provides a high charge rate and low mass, enabling a fast charging protocol of rechargeable modality **140**.

(81) As further shown in FIG. 6A, in some examples power element **110** comprises an energy harvesting modality **144**. In some examples, the energy harvesting modality **144** is implemented via a thermopile-based energy harvester. In some examples, the energy harvesting modality **144** is implemented via a piezoelectric motion/deflection technique. In some instances, the energy harvesting modality **144** may enable the power element **110** to be referred to as an on-board power source (e.g. on-board power generation element), thus freeing the therapy device **100** from having to be recharged via sources external to the body via rechargeable modality **140**. Accordingly, in

some examples, the energy harvesting modality **144** may sometimes be referred to as a non-rechargeable modality because instead of re-charging a depleted power element, new power is generated (e.g. energy harvesting) on-board the stimulator. Stated differently, via energy harvesting modality **144**, therapy device **100** may operate without involving any external charging.

(82) In some examples, the therapy device **100** may combine various aspects of the different modalities **140**, **142**, **144**.

(83) Via at least some of the examples of the present disclosure, expensive recharging of a power element **110** of a therapy device is at least minimized or avoided and/or typical patient non-compliance with recharging is at least minimized or avoided. Moreover, in some examples, some of the more bulky components associated with traditional recharging schemes may be minimized and/or avoided, thereby facilitating a minimally invasive implantation and/or minimal profile within the subcutaneous environment (which in turn enables direct placement in close proximity to a target nerve).

(84) FIG. **6B** is a block diagram schematically representing a power element arrangement **150**, according to one example of the present disclosure. In some examples, power element arrangement **150** provides one example implementation of power element **110** and at least energy harvesting modality **144** in FIG. **6A**. As shown in FIG. **6B**, in some examples the power element arrangement **150** comprises a power element **152**, which includes an energy harvesting element **154**, mass **160**, and energy storage element **162**.

(85) In some examples, the energy harvesting element **154** comprises a mechanical energy harvesting element. In some examples, the energy harvesting element **154** comprises a piezoelectric capacitor element **156** while in some examples, the energy harvesting element **154** comprises a microelectromechanical system (MEMS) capacitor element **158**. In some examples, the MEMS capacitor element **158** comprises a MEMS electret capacitor. In some examples, the energy harvesting element **154** comprises an element other than piezoelectric capacitor and/or MEMS capacitor to harvest mechanical energy.

(86) In some examples, the energy harvesting element **154** is associated with, is operably coupled to, and/or comprises mass **160**. In some such examples, one side of the energy harvesting element **154** (e.g. piezoelectric capacitor or MEMS capacitor) is directly mechanically coupled to a stimulator (to provide power), while the other side of the energy harvesting element **154** is directly mechanically coupled to mass **160**. Via such arrangement, mechanical vibrations, mechanical stress, and/or mechanical strain is converted via the energy harvesting element **154** (in association with mass **160**) into electrical energy which is then transferred to the stimulator and/or stored in energy storage element **162**, as shown in FIG. **6B**.

(87) In some examples, energy storage element **162** comprises a battery **164**, a capacitor **166**, and/or other storage modality **168**.

(88) The power element **152** comprises is implantable (**157B**) within a patient's body, at least below skin **157A**. In some examples, the power element **152** may be at least partially contained within or otherwise incorporated with another implantable component, such as a housing of a stimulator or therapy device.

(89) In some examples, the power element arrangement **150** comprises components external (**157C**) to skin **157C**, and selectively operably coupled relative to the implantable power element **152**. In some examples, the external components may comprise an external power element **170** which provides a supplemental or alternate source of power or energy to implantable components. In some examples, the external power element **170** comprises a battery **172** (which may be permanent or rechargeable), a line voltage **174**, and/or other power source **176**. In some instances, a control portion or a patient may select the stimulator (**100**, **200** in FIGS. **5**, **8**) to receive power from external power element **170** prior to a treatment period (e.g. sleep period) if recent energy harvesting has been insufficient to provide sufficient energy for an upcoming treatment period.

(90) In some examples, external components associated with power element arrangement **150** may

include a coupling element **180** to facilitate operable coupling of external power element **170** relative to the implantable components, e.g. power element **152**. In general terms, the coupling element **180** can take a wide variety of forms, which may indirectly couple the external power element **170** through tissue to the implantable power element **152**. In some examples, the coupling element **180** comprises an ultrasonic transducer **182** while in some examples, the coupling element **180** comprises other forms **184** of indirect coupling.

(91) FIG. **6C** is a side plan view schematically representing a nerve stimulation system **2600** for treating sleep disordered breathing (SDB), such as obstructive sleep apnea, according to one example of the present disclosure. As shown in FIG. **6C**, in some examples system **2600** may provide therapy to a patient **26002** reclined on a support **2604**. The patient support **2604** may comprise a bed **26005** and/or a headrest structure **2006** (e.g., pillow, neck support, etc). In some examples, the patient support **2604** houses at least power source **2600**. In some examples, the patient support **2604** also houses and/or provides radiofrequency transmission coils **2620**.

(92) It will be understood that patient support **2604** is not strictly limited to a bed and/or pillow, but extends to other configurations in which the patient **2602** can remain stationary for an extended period of time.

(93) As further illustrated in FIG. **6C**, system **2600** includes a microstimulator **2635** which is implanted within the patient's body. In some examples, the microstimulator **2035** is implanted in the patient's head-neck region. In one aspect, FIG. **6C** also depicts microstimulator **2635** in block diagram form (labeled as **2610**). In some examples, microstimulator **2635** comprises any one of the stimulators (e.g. at least **100**, **200** in FIG. **5**, **8**) and associated electrodes, cuffs, housings, flanges, etc. in any of the various forms as described throughout the examples of the present disclosure in association with FIGS. **1-27**.

(94) Referring again to FIG. **6C**, in some examples system **2600** also includes at least one sensor arrangement **2680**. The sensor arrangement **2680** may comprise a single sensor or multiple sensors as implemented via at least one of the sensors (e.g. types of sensors, sensing arrangements, etc.) as previously described in association with at least sensors **210** in FIG. **9A**, **250** in FIG. **9B**, and/or **300** in FIG. **10**. As further described later, sensed information obtained via the sensor arrangement **2680** may be communicated to the implanted microstimulator **2635** via at least a sensor information transmission function **2670** of the charging station **2650**.

(95) As just one example of the many different forms and modes of sensing via sensor arrangement, FIG. **6C** schematically represents at least some aspects of external sensing. In some examples, such sensing may be suitable for detection of an apnea and for triggering application of the stimulation signal synchronous with respiration, such as with inspiration. However, it will be understood that the sensed information may be used for other purposes and does not necessitate closed loop operation of the system **2600**. Accordingly, in some examples, at least some sensing is provided via an externally securable belt **2630** including a wearable, external sensor **2631**. In some examples, signals sensed at sensor **2631** are transmitted wirelessly to a control portion (e.g. **1700** in FIG. **25B**) for use in apnea detection and treatment, etc. In some examples, the control portion **1700** is associated with, incorporated with, and/or coupled to power element **2622**.

(96) In some examples, sensing is provided via a sensor **2640** secured on an external surface of a chest via a patch or even implanted subcutaneously. Sensor **2640** communicates wirelessly with power element **2622** and/or control portion **1700**. In some embodiments, belt **2630** or the other sensor **2640** includes an accelerometer or piezoelectric transducer for detecting body motion/position and/or many other types of physiologic information, with such sensed information also being used within system **2600**.

(97) In some examples, system **2600** comprises a charging station **2650** to supply power to a power element (e.g. at least **140** in FIG. **6A**, **152** in FIG. **6B**, **110** in FIGS. **5**, **8**) **6B** in microstimulator **2635**. In some examples, system **2600** transmits the power to the implantable microstimulator **2635** via coils **2620**. It is also understood that in some examples, coils **2620** also may be used to transmit

and/or receive control information relative to the microstimulator **2635**. In some examples, coils **2620** may be used to transmit and/or receive sensor information relative to the microstimulator **2635**.

(98) In some examples, a power element (e.g. **110** in FIGS. **5**, **6A**, **8**) associated with the microstimulator **2635** comprises an implantable, re-chargeable first portion and an external second portion to selectively re-charge the first portion. The second portion is external to the patient. The first portion may comprise a power element contained within or otherwise coupled to implantable microstimulator **2635**. In some examples, the second portion is implemented via at least some of the features and attributes of charging station **2650** whether alone or in association with patient support **2604**, **2606**, coils **2620**, etc.

(99) In some examples, charging station **2650** comprises an inductive charging arrangement **2652** by which power is transmitted to rechargeable power element in microstimulator **2635** via coils **2620** according to a general induction element(s) **2654** or a highly resonant induction element(s) **2656**.

(100) In some examples, charging station **2650** comprises a radiofrequency (RF) charging arrangement **2660** by which power is transmitted to rechargeable power element in microstimulator **2635** according to an RF rectification element(s) **2662** or a low power microwave element(s) **2664**.

(101) As previously noted, in some examples the charging station **2650** includes a sensor information transmission function **2670** by which sensed information may be transmitted to the microstimulator **2635**. In some examples, the sensor information transmission function **2670** transmits the sensed information as part of a re-charging signal transmitted in association with the re-charging functions of charging station **2650**.

(102) In some examples, at least some aspects of the charging station **2650** may provide one example implementation of the external power element **170** in the arrangement of FIG. **6B**.

(103) In some examples, it will be understood that at least a portion and/or at least some functions of the charging station may be implemented via a handheld device.

(104) FIG. **7** is a block diagram schematically representing communication element **112**, according to one example of the present disclosure. As represented in FIG. **7**, in some examples communication element **112** may be implemented via at least one of various communication modalities such as an external communication modality **190**, an inductive communication modality **192**, and/or a radiofrequency communication modality **194**. It will be understood that in some examples these various modalities are not mutually exclusive.

(105) In some examples, communication element **112** is implemented via an external communication modality **190** in which a device external to the patient communicates information to, and receives information from, the therapy device **100**. In some examples, this modality enables the external device to configure various therapy parameters by programming and/or adjusting parameters of the therapy manager **122** and/or control portion **120** of therapy device **100**.

(106) In some examples, the inductive communication modality **192** performs communication via a set of coils separate from, and different from, any coils implemented as part of power element **110** (e.g. FIGS. **5-6**). In some examples, the inductive communication modality **192** performs communication via at least some coils which are common with at least some coils implemented as part of one of the modalities of power element **110** (FIGS. **5-6**).

(107) In some examples, the radiofrequency modality **194** shown in FIG. **7** enables reducing power requirements during communication via an asymmetric protocol in which transmissions from the implanted therapy device **100** to the external device uses a lower data rate.

(108) In some examples, the radiofrequency modality **194** enables reduced power usage via wakeup rate optimization. In some examples, an increase wakeup rate is used to decrease communication latency. In some examples, application of an external magnet is used to increase wakeup rate. In some examples, prediction of onset of sleep is used to increase wakeup rate. In some examples, these arrangements are employed via an external power source with a



radiofrequency (RF) link.

(109) Accordingly, it will be understood that in some examples, at least some of these aspects of communication element **112** enhance and/or may define at least a portion of power element **110**. Similarly, in some examples and as noted elsewhere throughout at least some examples of the present disclosure, power element **110** may define at least a portion of communication element **112**.

(110) FIG. **8** is a block diagram schematically representing components of a microstimulation therapy device **200**, according to one example of the present disclosure. As shown in FIG. **8**, microstimulation therapy device **200** includes power element **110**, stimulation circuitry **112**, communication element **114**, and a control portion **120** having therapy manager **122**. In some examples, microstimulation therapy device **200** includes at least some of substantially the same features and attributes as microstimulation therapy device **100** as previously described in association with at least FIG. **5**, except for microstimulation therapy device **200** further including a sensing function **205**. In some examples, sensing function **205** receives sensed information for further use by therapy manager **122** and/or control portion **120** to evaluate and/or perform therapy. As such, in some examples, sensing function **205** provides feedback to enable operation of therapy device **200** in a closed loop system. One such closed loop function **1630** is described later in association with at least FIG. **24**, while other aspects associated with closed loop functioning are described throughout at least some examples of the present disclosure.

(111) In some examples, sensing function **205** is implemented via a sensor (**210** in FIG. **9A**; **250** in FIG. **9B**; **300** in FIG. **10**) forming part of microstimulation therapy device **200**. However, in some examples, a sensor (**210** in FIG. **9A**; **250** in FIG. **9B**; **300** in FIG. **10**) may be separate from, and independent of a therapy device (FIG. **8**), according to one example of the present disclosure. In some examples, while separate from and independent of therapy device **200**, a sensor (**210** in FIG. **9A**; **250** in FIG. **9B**; **300** in FIG. **10**) is dedicated to providing sensed information to therapy device **200**.

(112) In some examples, a sensor (**210** in FIG. **9A**; **250** in FIG. **9B**; **300** in FIG. **10**) is not dedicated to providing sensed information to microstimulation therapy device **200**. As such sensor **210/250/300** may be part of a system which is independent of therapy device **200** or sensor **210/250/300** may be a standalone sensor not associated with any other system or device. For instance, in some examples, a sensor (**210**, **250**, and **300**) comprises a portion of a cardiac device.

(113) In either case, further details regarding at least some examples of such sensors are described later in association with at least FIGS. **9-10**.

(114) With further reference to FIG. **8**, the sensing function **205** receives and tracks signals from various physiologic sensors in order to determine respiratory information, sleep quality information, sleep disordered breathing (SDB) information, cardiac information, etc. This information may be received from either a single sensor or any multiple of sensors, or combination of various physiologic sensors which may provide a more reliable and accurate signal. In some examples, sensing function **205** receives this information from sensor(s) **210**, **250** **300**, as later described in association with at least FIGS. **9-10**.

(115) FIG. **9A** is a block diagram schematically representing a sensor **210**, according to one example of the present disclosure. In some examples, sensor **210** corresponds to a sensor external to microstimulation therapy device **200** which cooperates with sensing function **205** of microstimulation therapy device **200** in FIG. **8** and/or corresponds to a sensor incorporated within the microstimulation therapy device **200** which at least partially implements the sensing function **205** in FIG. **8**, as previously described or later described in the examples of the present disclosure.

(116) In some examples, sensor **210** is an implantable sensor implanted within a patient's body separately from microstimulation therapy device **200**, as represented by **226** in FIG. **9A**. In some examples, an implantable sensor forms part of another component implanted within the patient's body, such as on-board the microstimulation therapy device **200** in FIG. **8**, and as such is represented by **220** in FIG. **9**. In such examples, the on-board sensor **220** may form part of the

housing of the microstimulation therapy device **200** and therefore may be exposed to the internal environment of the patient. On the other hand, in such examples, the on-board sensor **220** may be housed internally within the microstimulation therapy device **200** and be isolated from the internal environment of the patient. While a fuller discussion of sensor types **300** is reserved until a later discussion of FIG. **10**, it will be noted that an accelerometer (e.g. **306** in FIG. **10**) is one example of an implantable sensor, which may be internally housed within a microstimulation device as an on-board sensor **220**.

(117) In some examples, implantable sensor **226** may comprise stand-alone implantable sensors distributed throughout the patient's body and which communicate wirelessly to a microstimulation therapy device **200** or to an external device that integrates the sensed data. For instance, one stand-alone implantable sensor may comprise an oxygen sensor.

(118) With further reference to FIG. **9A**, in some examples sensor **210** comprises an external sensor **222** that remains external to a patient's body. The external sensor **222** may be a wearable sensor **230** or an environment sensor **232**, which is part of the patient's environment and which senses information from the patient and/or regarding the environment in which the patient is present. In some examples, a wearable sensor **230** may be used to sense heart rate variability such that the wearable sensor **230** need not be part of an implantable microstimulation therapy device **200** or external therapy device. Rather, one may simply add the wearable sensor **230** at a later time to monitor parameters associated with a therapy performed to alleviate sleep disordered breathing.

(119) In some examples, a wearable sensor **230** may comprise a commercially available wearable sensor which includes an array of sensors for measuring heart rate (e.g. LED, optical sensor), sleep quality/motion (e.g. 3D accelerometer), ambient light, etc. In some instances, the wearable sensor **230** includes a touchscreen display to facilitate tracking and monitoring of the sensed conditions. In some instances, the wearable sensor **230** includes a wireless communication tool for communicating with a dongle, mobile device, etc. via a wireless communication protocol (e.g. Bluetooth, NFC, etc.). In one instance, such a wearable sensor **230** is available from FitBit, Inc. of San Francisco, California. In some examples, such a system may include a single sensor or array of sensors which provide respiratory information, cardiac information, sleep quality information, sleep disordered breathing (SDB) information, and/or other information. In some examples, this information may be coordinated with information sensed or determined via the microstimulation therapy device **200**. In some examples, the therapy manager **122** may include a sensor profile manager to coordinate information sensed via the wearable sensor **230**.

(120) In some examples, information from external sensors **222** can be coordinated with information from implantable sensors **220**, **226**.

(121) In some examples, external sensor **222** comprises an integrated external sensing system for tracking sleep quality, heart rate, breathing rhythm, movement, sleep stages, snoring, and sleep environment (e.g., noise level and light). One example system comprises the Beddit® system available from [www.beddit.com](http://www.beddit.com). In some examples, such a system may provide respiratory information, cardiac information, sleep quality information, sleep disordered breathing (SDB) information, and/or other information. In some examples, this information may be coordinated with information sensed or determined via the microstimulation therapy device **200**. In some examples, the therapy manager **122** may include a sensor profile manager to coordinate information sensed via the external sensor **220**.

(122) In some examples, an external sensor(s) **222** may comprise clinically available diagnostic equipment such as ECG sensors, a blood pressure cuff, oxygen sensor, etc.

(123) In some instances, the environment sensor **232** shown in FIG. **9** comprises a non-contact sensor **234**, which does not make contact with the patient. In one instance, non-contact sensor **234** comprises at least some of substantially the same features and attributes as the non-contact sensor paradigm described in Heneghan et al. U.S. Pat. No. 5,562,526, which may be used by microstimulator device **200** to provide respiratory information, cardiac information, sleep quality

information, sleep disordered breathing (SDB) information, and/or other information. In one instance, one such system is available from Resmed Corporation of San Diego, California.

(124) In some instances, the non-contact sensor **234** incorporates or cooperates with one of the sensor modalities described in association with at least FIG. **10**, such as but not limited to, a radiofrequency sensor **308**. The signal produced by sensing via the radiofrequency sensor **308** may be processed to detect patient motion/activity, breathing (e.g. respiratory rate), heart rate, and/or a sleep stage of the patient.

(125) In some examples, sensor **210** may comprise a sensor providing a combination sensor or combination sensor array, which combines at least some aspects of the various implantable sensors and external sensors.

(126) In some examples, sensor **210** comprises an electrode associated with the microstimulation therapy device (**100** in FIG. **5**; **200** in FIG. **8**) and as later further described in association with at least FIGS. **14A-18B**, **19A-20B**, **21A-23B**, in which a stimulation signal generated via the stimulation circuitry of one of the microstimulation therapy devices **100**, **200** is applied to a target nerve via such an electrode. In some instances, such electrodes may sometimes also be used as a sensor, such as but not limited to, sensing a bio-impedance of the patient to obtain respiratory information, cardiac information, sleep quality information, sleep disordered breathing (SDB) information, etc.

(127) In some examples, sensor **210** includes and/or utilizes inductive coupling to effectuate communication between sensor **210** and at least some components (e.g. communication element **114** in FIG. **8**) of the microstimulation therapy device **200** (FIG. **8**).

(128) FIG. **9B** is a block diagram schematically representing a sensor type **250**, according to one example of the present disclosure. In some examples, at least some of the sensing arrangements **252-272** in FIG. **9B** may be implemented via at least some of the sensor types **220-234** in FIG. **9A** and/or sensor types **302-322** in FIG. **10**. As shown in FIG. **9B**, in some examples one sensor type comprises an airway position sensing arrangement **252** provide sensed information regarding an airway position while airflow obstruction sensing arrangement **254** provides sensed information regarding airflow obstructions. In some examples, airflow sensing arrangement **256** provides sensed general airflow information. As further shown in FIG. **9B**, in some examples respiratory sensing arrangement **258** provides general and/or specific sensed respiratory information while in some examples, sleep disordered breathing (SDB) sensing arrangement **260** provides sensed information regarding at least sleep disordered breathing (SDB) events, such as but not limited to apneas **262** and/or hypopneas **264**. In some examples, body position sensing arrangement **270** provides sensed information related to at least body position, which may involve posture, motion, activity, body orientation, etc. In some examples, implant temperature sensing arrangement **272** provides sensed information regarding at least a temperature of an implant. In some examples, such sensed implant temperature information facilitates recharging modalities and functionalities.

(129) In some examples, sensed information may be obtained via a combination of at least some of the various sensing arrangements **252-272** in FIG. **9B**.

(130) FIG. **10** is a block diagram schematically representing a sensor type **300** according to one example of the present disclosure. In some examples, sensor type **300** corresponds to a sensor (e.g., **210** in FIG. **9**) and/or a sensing function (**205** in FIG. **8**), as previously described or later described in the examples of the present disclosure.

(131) As shown in FIG. **10**, sensor type **300** comprises various types of sensor modalities **302-320**, any one of which may be used for determining, obtaining, and/or monitoring respiratory information, cardiac information, sleep quality information, sleep disordered breathing-related information, and/or other information related to providing patient therapy.

(132) As shown in FIG. **10**, in some examples sensor type **300** comprises the modalities of pressure **302**, impedance **304**, accelerometer **306**, airflow **307**, radiofrequency (RF) **308**, optical **310**, electromyography (EMG) **312**, electrocardiography (ECG) **314**, ultrasonic **316**, acoustic **318**,

image **319**, and/or other **320**. In some examples, sensor type **300** comprises a combination **322** of at least some of the various sensor modalities **302-320**.

(133) It will be understood that, depending upon the attribute being sensed, in some instances a given sensor modality identified within FIG. **10** may include multiple sensing components while in some instances, a given sensor modality may include a single sensing component. Moreover, in some instances, a given sensor modality identified within FIG. **10** may include power circuitry, monitoring circuitry, and/or communication circuitry. However, in some instances a given sensor modality in FIG. **10** may omit some power, monitoring, and/or communication circuitry but may cooperate with such monitoring or communication circuitry located elsewhere.

(134) In some examples, a pressure sensor **302** may sense pressure associated with respiration and can be implemented as an external sensor **222** (FIG. **9**) and/or an implantable sensor **226** (FIG. **9**). In some instances, such pressures may include an extrapleural pressure, intrapleural pressures, etc. For example, one pressure sensor **302** may comprise an implantable respiratory sensor, such as that disclosed in Ni et al. U.S. Patent Publication 2011-0152706, published on Jun. 23, 2011, titled METHOD AND APPARATUS FOR SENSING RESPIRATORY PRESSURE IN AN IMPLANTABLE STIMULATION SYSTEM.

(135) In some instances, pressure sensor **302** may include a respiratory pressure belt worn about the patient's body.

(136) In some examples, a pressure sensor **302** can sense sound and/or pressure waves at a different frequency than occur for respiration (e.g. inspiration, exhalation, etc.). In some instances, this data can be used to track cardiac parameters of patients via a respiratory rate and/or a heart rate. In some instances, such data can be used to approximate electrocardiogram information, such as a QRS complex. In some instances, the detected heart rate is used to identify a relative degree of organized heart rate variability, in which organized heart rate variability may enable detecting apneas or other sleep disordered breathing events, which may enable evaluating efficacy of sleep disordered breathing.

(137) In some examples, pressure sensor **302** comprises piezoelectric element(s) and may be used to detect sleep disordered breathing (SDB) events (e.g. apnea-hypopnea events), to detect onset of inspiration, and/or detection of an inspiratory rate, etc.

(138) As shown in FIG. **10**, in some examples one sensor modality includes air flow sensor **307**, which can be used to sense respiratory information, sleep disordered breathing-related information, sleep quality information, etc. In some instances, air flow sensor **307** detects a rate or volume of upper respiratory air flow.

(139) As shown in FIG. **10**, in some examples one sensor modality includes impedance sensor **304**. In some examples, impedance sensor **304** may be implemented in some examples via various sensors distributed about the upper body for measuring a bio-impedance signal, whether the sensors are internal and/or external. In some examples, the impedance sensor **304** senses an impedance indicative of an upper airway collapse.

(140) In some instances, the sensors are positioned about a chest region to measure a trans-thoracic bio-impedance to produce at least a respiratory waveform.

(141) In some instances, at least one sensor involved in measuring bio-impedance can form part of a pulse generator, whether implantable or external. In some instances, at least one sensor involved in measuring bio-impedance can form part of a stimulation element and/or stimulation circuitry. In some instances, at least one sensor forms part of a lead extending between a pulse generator and a stimulation element.

(142) In some examples, impedance sensor **304** is implemented via a pair of elements on opposite sides of an upper airway. Some example implementations of such an arrangement are further described later in association with at least FIG. **11**.

(143) In some examples, impedance sensor **304** may take the form of electrical components not used in a microstimulation therapy device **200**. For instance, some patients may already have a

cardiac therapy device (e.g. pacemaker, defibrillator, etc.) implanted within their bodies, and therefore have some cardiac leads implanted within their body. Accordingly, the cardiac leads may function together or in cooperation with other resistive/electrical elements to provide impedance sensing.

(144) In some examples, whether internal and/or external, impedance sensor(s) **304** may be used to sense an electrocardiogram (ECG) signal.

(145) In some examples, impedance sensor **304** is used to detect sleep disordered breathing (SDB) events (e.g. apnea-hypopnea events), to detect onset of inspiration, and/or detection of an inspiratory rate, etc.

(146) As shown in FIG. **10**, in some examples one sensor modality includes an accelerometer **306**. In some instances, accelerometer **306** is generally incorporated within or associated with microstimulation therapy device **200**. For instance, in some examples of a therapy device **200**, a housing (e.g. can) contains numerous components such as control circuitry, stimulation, and also may contain an accelerometer **306** within the housing. However, in some examples, the accelerometer **306** may be separate from, and independent of, the microstimulation therapy device **200**. In some examples, accelerometer **306** can enable sensing body position, body posture, and/or body activity/motion regarding the patient, which may be indicative of behaviors from which sleep quality information or sleep disordered breathing (SDB) information may be determined. In some instances, body posture/position is sensed via at least the accelerometer **306** and is used to detect start of sleep.

(147) For instance, as further addressed in association with at least FIG. **24**, sleep position (e.g. left side, right side, supine, etc.) may be used to determine the effectiveness of SDB therapy according to sleep position, and in some instances, the SDB therapy may be automatically adjusted based on the orientation (i.e. sleep position) of the patient. In some instances, this information regarding sleep position may be communicated to the patient during a sleep period in order to induce the patient to change their sleep position into one more conducive to efficacious therapy. In some examples, the communication may occur by an audible or vibratory alarm implemented via wireless communication to a patient remote or via direct muscle stimulation via wireless communication to a wearable muscle stimulation device.

(148) Among other uses, the information obtained via the accelerometer **306** may be employed by a clinician to adjust stimulation therapy and/or employed by a therapy device (and/or manager) to automatically adjust stimulation therapy to cause a decrease in the moving average of the sleep apnea index (e.g. AHI). Moreover, as previously mentioned this information may be used to communicate to the patient via audio or non-audio techniques to change their sleep position to a position (e.g. left side) more amenable to regular respiration.

(149) In some examples, accelerometer **306** enables acoustic detection of cardiac information, such as heart rate via motion of tissue in the head/neck region, similar to ballistocardiogram and/or seismocardiogram techniques. In some examples, measuring the heart rate includes sensing heart rate variability. In some examples, accelerometer **306** can sense respiratory information, such as but not limited to, a respiratory rate. In some examples, whether sensed via an accelerometer **306** alone or in conjunction with other sensors, one can track cardiac information and respiratory information simultaneously by exploiting the behavior of the cardiac signal in which a cardiac waveform can vary with respiration.

(150) In some examples, accelerometer **306** enables detection of sleep/awake via the sensing of motion, position, posture and/or activity of the patient, along with other parameters determinable via the accelerometer **406**. In some instance, this information may be used to implement automatic control of stimulation therapy to enhance therapeutic efficacy and/or reduce power requirements.

(151) In some examples, accelerometer **306** is used to detect sleep disordered breathing (SDB) events (e.g. apnea-hypopnea events), to detect onset of inspiration, and/or detection of an inspiratory rate, etc.

(152) In some examples, the accelerometer **306** comprises an external sensor **222** (FIG. **9**). In some instances, when embodied as an external sensor, the accelerometer **306** may comprise a wearable sensor, such as an accelerometer incorporated into a band or belt worn about a portion of the body (e.g. wrist, chest, arm, leg, torso, etc.).

(153) In some examples, the accelerometer **306** may be used to detect sleep disordered breathing events during the sleep period and may be used continuously to detect arrhythmias.

(154) In some examples, radiofrequency sensor **308** shown in FIG. **10** enables non-contact sensing of various physiologic parameters and information, such as but not limited to respiratory information, cardiac information, motion/activity, and/or sleep quality, such as previously described regarding non-contact sensor **234** in association with at least FIG. **9**. In some examples, radiofrequency sensor **308** enables non-contact sensing of other physiologic information. In some examples, radio-frequency (RF) sensor **308** determines chest motion based on Doppler principles. The sensor **308** can be located anywhere within the vicinity of the patient, such as various locations within the room (e.g. bedroom) in which the patient is sleeping. In some examples, the sensor **308** is coupled to a monitoring device to enable data transmission relative to other components of a microstimulation therapy device **200** and storage in such other components.

(155) In some examples, one sensor modality may comprise an optical sensor **310** as shown in FIG. **10**. In some instances, optical sensor **310** may be an implantable sensor **226** and/or external sensor **222** (FIG. **9**). For instance, one implementation of an optical sensor **310** comprises an external optical sensor for sensing heart rate and/or oxygen saturation via pulse oximetry. In some instances, the optical sensor **310** enables measuring oxygen desaturation index (ODI). In some examples, the optical sensor **310** comprises an external sensor removably couplable on the finger of the patient.

(156) In some examples, optical sensor **310** can be used to measure ambient light in the patient's sleep environment, thereby enabling an evaluation of the effectiveness of the patient's sleep hygiene and/or sleeping patterns.

(157) As shown in FIG. **10**, in some examples one sensor modality comprises EMG sensor **312**, which records and evaluates electrical activity produced by muscles, whether the muscles are activated electrically or neurologically. In some instances, the EMG sensor **312** is used to sense respiratory information, such as but not limited to, respiratory rate, apnea events, hypopnea events, whether the apnea is obstructive or central in origin, etc. For instance, central apneas may show no respiratory EMG effort.

(158) In some instances, the EMG sensor **312** may comprise a surface EMG sensor while, in some instances, the EMG sensor **312** may comprise an intramuscular sensor. In some instances, at least a portion of the EMG sensor **312** is implantable within the patient's body and therefore remains available for performing electromyography on a long term basis.

(159) In some examples, one sensor modality may comprise ECG sensor **314** which produces an electrocardiogram (ECG) signal. In some instances, the ECG sensor **314** comprises a plurality of electrodes distributable about a chest region of the patient and from which the ECG signal is obtainable. In some instances, a dedicated ECG sensor(s) **314** is not employed, but other sensors such as an array of bio-impedance sensors **304** are employed to obtain an ECG signal. In some instances, a dedicated ECG sensor(s) is not employed but ECG information is derived from a respiratory waveform, which may be obtained via any one or several of the sensor modalities in sensor type **300** in FIG. **10**. In some examples, ECG sensor **314** is embodied as an accelerometer **306** as previously described in association with FIGS. **9-10**.

(160) In some examples, an ECG signal obtained via ECG sensor **314** may be combined with respiratory sensing (via pressure sensor **302** or impedance sensor **304**) to determine minute ventilation, as well as a rate and phase of respiration. In some examples, the ECG sensor **314** may be exploited to obtain respiratory information (e.g. at least **1660** in FIG. **24**). In some examples, as noted elsewhere, ECG sensor **314** may be implemented, at least in part, as an accelerometer **306** (FIG. **10**).

(161) In some examples, ECG sensor **314** is used to detect sleep disordered breathing (SDB) events (e.g. apnea-hypopnea events), to detect onset of inspiration, and/or detection of an inspiratory rate, etc.

(162) As shown in FIG. **10**, in some examples one sensor modality includes an ultrasonic sensor **316**. In some instances, ultrasonic sensor **316** is locatable in close proximity to an opening (e.g. nose, mouth) of the patient's upper airway and via ultrasonic signal detection and processing, may sense exhaled air to enable determining respiratory information, sleep quality information, sleep disordered breathing information, etc. In some instances, ultrasonic sensor **316** may comprise at least some of substantially the same features and attributes as described in association with at least Arlotto et al. PCT Published Patent Application 2015-014915 published on Feb. 5, 2015.

(163) In some examples, acoustic sensor **318** comprises piezoelectric element(s), which sense acoustic vibration. In some implementations, such acoustic vibratory sensing may be used to detect sleep disordered breathing (SDB) events (e.g. apnea-hypopnea events), to detect onset of inspiration, and/or detection of an inspiratory rate, etc.

(164) In some examples, acoustic sensor **318** detects snoring information, which may be used in detection, evaluation, and/or modification of sleep-related information and/or therapy parameters.

(165) In some examples, one of the sensor types **300** (and/or sensors **200**) or a combination of such sensors senses local or gross motion, such as snoring, inspiration/expiration, etc., which may be indicative to sleep quality, sleep disordered breathing events, general respiratory information, etc.

(166) In some examples, information sensed via sensor **210** in FIG. **9** and/or via sensor types **300** in FIG. **10**, such as but not limited to motion information, can be used in a training mode of the microstimulation therapy device (**200** in FIG. **8**) to correlate the patient's respiration with the sensed motion.

(167) In some examples, several sensor modalities of the sensory types **300** are combined, as represented via combination identifier **322**.

(168) FIG. **11** is a diagram **350** schematically representing an impedance sensor array **360** implanted in a head/neck region **352**, according to one example of the present disclosure. In some examples, impedance sensor array **360** comprises at least some of substantially the same features and attributes as impedance sensor **304** (FIG. **10**). As shown in FIG. **11**, sensor array **360** includes a first sensing element **361** and a second sensing element **362**. In some examples, both sensing elements **361**, **362** comprise some form of electrically conductive element such that a bio-impedance can be measured between the respective sensing elements **361**, **362** positioned on opposite sides of an upper airway in the head/neck region **352**. In some examples, the measured bio-impedance may indicate a relative degree of upper airway patency or collapse. In some examples, one or both of sensing elements **361**, **362** may comprise tines to prevent migration of the respective sensing elements **361**, **362**.

(169) In some examples, the sensing element **361** comprises at least a conductive element of a microstimulation therapy device, such as therapy device **200** in FIG. **8**. Accordingly, the therapy device **200** itself may form part of the impedance sensor array **360**. In this arrangement, in some examples, the other sensing element **362** is inserted at the opposite side of the head/neck region **352** via use of a tunneling tool.

(170) In some examples, the sensing element **361** comprises a housing of a first microstimulation therapy device, such as therapy device **200** in FIG. **8** and the other sensing element **362** comprises a housing of a second microstimulation therapy device, which is separate from, and independent of the first microstimulation therapy device **200**. In some implementations, these sensing elements **361**, **362** function as an impedance sensor **304**. In some implementations, the two sensing elements **361**, **362** (implemented via two independent microstimulation therapy devices **200**) are placed on opposite sides of the throat of the patient and communicate wirelessly with each other to sense inhalation and exhalation.

(171) FIG. **12** is a block diagram schematically representing mechanical coupling arrangements

**400** for securing at least a microstimulation therapy device within a subcutaneous environment, according to one example of the present disclosure. As shown in FIG. 12, one coupling arrangement includes a bony structure coupling arrangement **402** in which at least a portion of the housing of the microstimulation therapy device (e.g. **100** in FIG. 5, **200** in FIG. 8) is secured via a fixation mechanism relative to a bony structure accessible within a subcutaneous environment. In this arrangement, a stimulation element such as a contact electrode is located at a target nerve while the housing of the microstimulation therapy device (e.g. **100**, **200**) is spaced apart from the target nerve stimulation site. In some instances, the housing may be considered to be located remotely from the target nerve site.

(172) For instance, in some examples, the bony structure may comprise the mandible. In some instances, the housing of the therapy device **100**, **200** is fixed via screws or other fastening mechanism(s). In some instances, fixation occurs at an inferior portion of the mandible and may potentially involve bone removal to facilitate the fixation. In some instances, fixation occurs at inner portion of the mandible but without involving bone removal.

(173) In some examples, the housing of the microstimulation therapy device **100**, **200** can be placed behind the ear, or elsewhere on the cranium. In such arrangements, fixation may occur via a screw associated with the housing of the therapy device **100**, **200** and/or via other fixation mechanisms.

(174) As shown in FIG. 12, one coupling arrangement includes a non-nerve, non-bony structure coupling arrangement **404** in which at least a portion of the housing of the microstimulation therapy device **100**, **200** is secured via a fixation mechanism relative to a non-bony structure accessible within a subcutaneous environment. In this arrangement, a stimulation element such as a contact electrode is located at a target nerve while the housing of the microstimulation therapy device (e.g. **100**, **200**) is spaced apart from the target nerve stimulation site. In some instances, the housing is located remotely from the target nerve stimulation site. In some instances, the housing of the microstimulation therapy device (e.g. **100**, **200**) can be placed superior to the mylohyoid, which in some instances, further involves the use of tines for mechanical fixation to prevent migration.

(175) In some examples, a microstimulation therapy device **100**, **200** secured via arrangements **402** or **404** can communicate with either an implanted generator (e.g. pectoral) or external generator module which can contain a power source accessible by the implanted microstimulation therapy device.

(176) In some examples, a microstimulation therapy device **100**, **200** secured via arrangements **402** or **404** can communicate with a sensor **210**, **300**, whether implanted or external. In some implementations, the sensor **210**, **300** can be passively powered or can have an internal primary/rechargeable power source.

(177) As shown in FIG. 12, one coupling arrangement includes a nerve structure coupling arrangement **410** in which at least a portion of the housing of the microstimulation therapy device **100**, **200** is secured via a fixation mechanism relative to a nerve within a subcutaneous environment. In this arrangement, at least a housing of the microstimulation therapy device **100**, **200** is located directly at the target nerve stimulation site. In some examples in which a stimulation element (e.g. contact electrode) extends from the housing of the microstimulation therapy device, both the microstimulation therapy device **100**, **200** and stimulation element may be located in close proximity to a target stimulation site, as later shown and described in association with at least FIGS. 14A-18D.

(178) FIG. 13 is a block diagram schematically representing electrical coupling arrangements **422-434** for a microstimulation therapy device, according to one example of the present disclosure. In general terms, the various electrical coupling arrangements **422-434** provide a means by which stimulation pulses from the microstimulation therapy device **100**, **200** are coupled to a target nerve.

(179) As shown in FIG. 13, one coupling arrangement includes a direct coupling arrangement **422** in which a housing of the microstimulation therapy device **100**, **200** includes at least one exposed



electrically conductive element that directly contacts the target nerve. In one aspect, one such arrangement is further described later in association with at least FIGS. **16A-16C**. In some examples, an array of such conductive elements is present on an outer surface of the housing of the microstimulation therapy device. In one aspect, one such arrangement is further described later in association with at least FIGS. **14A-14B**.

(180) As shown in FIG. **13**, one coupling arrangement includes an indirect coupling arrangement **424** in which an outer surface of the housing of the microstimulation therapy device **100, 200** does not include any exposed electrically conductive elements. In one aspect, one such arrangement is further described later in association with at least FIGS. **15A-15B** in which an electrode array extends outwardly from the housing of the microstimulation therapy device to establish contact with the target nerve.

(181) As shown in FIG. **13**, one coupling arrangement includes an axial array coupling arrangement **430** in which an array of electrically conductive elements is arranged to be axially aligned with a length of the target nerve. In some examples, the axial array of conductive elements is located on an outer surface of a housing of the microstimulation therapy device. In one aspect, one such arrangement is further described later in association with at least FIGS. **14A-14B**. In some examples, the axial array of conductive elements is not located on an outer surface of a housing of the microstimulation therapy device, but forms a structure extending outwardly from the housing of the therapy device. In one aspect, one such arrangement is further described later in association with at least FIGS. **17A-17C**.

(182) As shown in FIG. **13**, one coupling arrangement includes a radial array coupling arrangement **432** in which an array of electrically conductive elements is arranged in an arcuate pattern to be spaced apart and extend about a circumference of a target nerve. In one aspect, the electrically conductive elements may be considered to be radially arranged to the extent that each electrically conductive element is positioned at the end of a virtual radius from a center point (e.g. a center of the cross-section of the nerve), with the ends of the virtual radii spaced apart from each other about a circumference of the nerve.

(183) In some examples, the radial array of conductive elements is deployed as part of a structure extending outwardly from the housing of the therapy device, such as at least one flange of a pair of flanges used to mechanically couple the therapy device relative to the target nerve. In one aspect, one such arrangement is further described later in association with at least FIGS. **15A-15B**.

(184) As shown in FIG. **13**, one coupling arrangement includes a grid array coupling arrangement **434** in which an array of electrically conductive elements is arranged in a grid. In some examples, the grid array of conductive elements forms a structure extending outwardly from the housing of the therapy device, such as a paddle extending about a portion of the target nerve. In one aspect, one such arrangement is further described later in association with at least FIGS. **16A-16B**.

However, in some examples, the grid array of conductive elements is located on an outer surface of the housing of the microstimulation therapy device. In one aspect, one such arrangement is further described later in association with at least FIGS. **18A-18B**.

(185) It will be understood that at least some of the examples of mechanical coupling arrangements (FIG. **12**) may be combined with at least some examples of electrical coupling arrangements (FIG. **13**). Moreover, in some examples, more than one electrical coupling arrangement may be implemented and in some examples, more than one mechanical coupling arrangement may be implemented. In other words, in some examples, at least some of the various mechanical are not mutually exclusive and at least some of the various electrical coupling arrangements are not mutually exclusive.

(186) FIG. **14A** is a diagram **500** schematically representing a microstimulation therapy device **520** implanted relative to a nerve **512** of array **510** of nerves within a subcutaneous, extravascular environment **502**, according to one example of the present disclosure. In some examples the microstimulation therapy device **520** comprises at least some of substantially the same features and

attributes as the previously described microstimulation therapy devices **100**, **200**. As shown in FIG. **14A**, therapy device **520** includes a housing **522** extending between opposite ends **523A**, **523B** with housing **522** having a generally electrically non-conductive outer surface **524**. Housing **522** contains a stimulator (**100**, **200** in FIGS. **5**, **8**) and may sometimes be referred to as defining or including a body of the therapy device **520**.

(187) An array **530** of three ring electrodes **532** are arranged in an axially spaced apart manner along a length of the housing **522**. In some examples, a fewer number or greater number of ring electrodes **532** may be used. In some examples, the electrodes **532** may be implemented as partial ring electrodes **532**, and thus not extend about a complete circumference of the housing **522** provided that at least a portion of the respective partial ring electrodes **522** can establish contact against the nerve **512**.

(188) In some examples, the non-conductive area of the housing **522** defines a first portion. Each respective electrode **532** defines one of three second portions, each of which is surrounded by the non-conductive first portion.

(189) As further shown in FIG. **14B**, a pair of flanges **540A**, **540B** extend outwardly from the housing **522** of therapy device **520** and are biased to encircle and releasably engage nerve **512** to mechanically (and directly) secure the housing **522** relative to, and in contact against, nerve **512** such that electrodes **532** become directly electrically coupled relative to the nerve **512** (e.g. nerve bundle). In some instances, the flanges **540A**, **540B** may be sometimes be referred to as wrapping around or about the nerve **512**. In some examples, each flange **540A**, **540B** may sometimes be referred to as an at least partially flexible element. In some examples, the flanges **540A**, **540B** are made from a polymer material, such as but not limited to a polyurethane material or one of several biocompatible materials, alone or in combination. In at least some examples, this arrangement enables application of stimulation therapy for treating sleep disordered breathing (SDB).

(190) In some examples, the housing **522** of therapy device **520** has a length at least two times a diameter or width of the housing **522** with the elongate configuration enhancing stability of the housing **522** when secured against nerve **512**.

(191) In some examples, the body **522** has a volume less than about cubic centimeters.

(192) With general reference to at least FIGS. **14A-14B**, in some examples, housing **522** of microstimulation therapy device **520** has opposite ends **523A**, **523B** formed of electrically non-conductive material, and therefore in some examples, no electrical transmission of stimulation pulse occurs through the ends **523A**, **523B** of housing **522**.

(193) With further general reference to at least FIGS. **14A-14B**, in some examples, the housing **522** of microstimulation therapy device **520** has opposite ends **523A**, **523B** devoid of fixation elements. In other words, in such examples the housing **522** lacks any mechanical element (such as but not limited to a screw) protruding axially from end of housing **522** or otherwise configured at end(s) of housing **522** for fixating solely the end of the housing **522** relative to a bony structure.

(194) With further general reference to FIGS. **14A-14B**, in some examples, housing **522** of microstimulation therapy device **520** is not invasively fixed relative to the tissue (e.g. nerve **512**) to which electrical stimulation is to be applied and/or is located remotely from the muscle targeted for contraction. Accordingly, in some instances, the housing **522** may sometimes be referred to as being non-nerve-invasively secured or being non-invasively secured relative to the nerve to be electrically stimulated.

(195) In sharp contrast to at least some examples of the present disclosure, some commercially available implantable stimulators are attached to the to-be-stimulated tissue (e.g. cardiac wall) via a screw which is invasively implanted within the to-be-stimulated tissue (e.g. cardiac wall), where a to-be-stimulated tissue is a muscle targeted for contraction. In such examples, the fixation mechanism penetrates the tissue to which electrical stimulation is applied.

(196) In sharp contrast to some commercially available injectable stimulators, the housing **522** of therapy device **520** (of at least some examples of the present disclosure) is secured relative to the

tissue (e.g. nerve) to be stimulated, thereby minimizing and/or avoiding migration while enhancing patient comfort.

(197) With further general reference to at least FIGS. **14A-14B**, in some examples, a contact interface between housing **522** of the microstimulation therapy device **520** and nerve **512** does not define a primary securing interface. Instead, the flanges **540A**, **540B** extending outward from the housing **522** primarily define a securing interface relative to the nerve with the flanges **540A**, **540B** omitting any electrically conductive elements. In some examples, suture loops may be installed to further secure the flanges **540A**, **540B** in their closed position about the nerve **512**.

(198) However, in some examples, a differently shaped housing may be substituted for the generally cylindrical shaped housing **522**. For instance, housing **522** may be replaced with a housing **1522** having an external surface with an arcuate nerve-engaging portion, such as described and illustrated in association with at least FIGS. **19A-20B**. With such an arrangement, the arcuate shape of the nerve-engaging portion enhances maintaining a stable, secure position of the housing **1522** relative to the nerve. In this way, the housing **1522** complements the action of flanges **540A**, **540B** in securing the stimulation therapy device **520** relative to nerve **512**.

(199) FIG. **15A** is a diagram **600** schematically representing a microstimulation therapy device **620** implanted relative to a nerve **512** of array **510** of nerves within a subcutaneous, extravascular environment **502**, according to one example of the present disclosure. In some examples, the microstimulation therapy device **620** comprises at least some of substantially the same features and attributes as the previously described microstimulation therapy devices **100**, **200** and/or therapy device **520** (FIGS. **14A-14B**). As shown in FIG. **15A**, therapy device **620** includes a housing **622** extending between opposite ends **623A**, **623B** with housing **622** having a generally electrically non-conductive outer surface **624**. In some examples, no electrically conductive elements (such as ring electrodes **532** in FIG. **14A**) are present on external surface **624**. However, in some examples, the entire external surface **624** or substantially the entire external surface **624** can be electrically conductive and serve as a single electrode.

(200) As shown in both FIGS. **15A-15B**, a pair of flanges **640A**, **640B** extends outwardly from the housing **622** of therapy device **620** and are biased to encircle and releasably engage nerve **512** to mechanically (and directly) secure the housing **622** relative to, and in contact against, nerve **512** such that electrodes **644** on the flange **640B** become directly electrically coupled relative to the nerve **512**. In one aspect, the array **642** of electrodes **644** are spaced apart from each other and arranged in a radial pattern along the length of the flanges **640A**, **640B** to at least partially surround or encircle the circumference of the nerve **512** for applying a stimulation therapy to treat sleep disordered breathing (SDB). Accordingly, in some examples, the array **642** provides one example implementation of the radial array **432** in FIG. **13**.

(201) It will be understood that housing **622** contains a stimulator (e.g. **100**, **200** in FIGS. **5**, **8**) and that an electrical connection extends from the stimulation circuitry (within housing **622**) through the flange **640B** to the respective electrodes **644** and/or through flange **640A** if some electrodes **644** are located on flange **640A**. In some examples, each electrode **644** may be independently controlled in applying a stimulation signal to the nerve **512**. As noted elsewhere, in at least some examples, the stimulator is encapsulated within non-conductive material within the housing **622**.

(202) In one aspect, the housing **622** of microstimulation therapy device **620** is held directly against nerve **512** (which is to be stimulated) even though no stimulation is applied via the external surface **624** of the housing **622** of the therapy device **620**. As previously described in association with at least FIGS. **14A-14B**, the housing **622** may be substituted for a housing having a concave, arcuate cross-sectional shape which better conforms or complements the arcuate outer surface of the nerve **512**. One such substitute housing may correspond to the housing in at least the example(s) later described and illustrated in association with at least FIGS. **19A-20B**.

(203) With general reference to at least some examples of FIGS. **15A-15B**, no electrically conductive element extends axially beyond either end **623A**, **623B** of the housing **622**. In one

aspect, this arrangement gives the therapy device **620** (including electrodes **644**) a small footprint. In one aspect, this small footprint may enable a small electromagnetic footprint, at least in the sense that less heating may result from the relatively short lead loop length, thereby mitigating potential nerve damage that might otherwise occur in the presence of relatively larger lead loop lengths. In addition, this arrangement may minimize and/or avoid a patient-to-patient variability that commonly occurs in routing a lead in pectorally implanted therapy devices, in which such patient-to-patient variability may produce uncertainty in MR-conditional testing. Accordingly, at least some examples of the present disclosure, such as at least the arrangement in FIGS. **15A-15B**, may enable a microstimulation therapy device to receive a MR-conditional rating, in which the patient may be eligible for at least some types of MR scanning.

(204) With general reference to at least some examples of FIGS. **14A-14B**, **15A-15B**, in some implementations, the flanges (**540A**, **540B** in FIGS. **14A-14B**; **640A**, **640B** in FIGS. **15A-15B**) do not extend a distance from the housing **522**, **622** more than a length of housing **522**, **622**.

(205) With general reference to at least some examples of FIGS. **15A-15**, in its closed position, the electrically conductive portions of the flange **640B** do not extend a distance from the housing **622** more than a diameter of nerve **512** or more than a diameter of the housing **622**.

(206) FIG. **16A** is a diagram **700** schematically representing a microstimulation therapy device **720** implanted relative to a nerve **512** of array **510** of nerves within a subcutaneous, extravascular environment **502**, according to one example of the present disclosure. In some examples, the microstimulation therapy device **720** comprises at least some of substantially the same features and attributes as the previously described microstimulation therapy devices **100**, **200**. As shown in FIG. **16A**, therapy device **720** includes a housing **722** extending between opposite ends **723A**, **723B** with housing **722** having a generally electrically non-conductive surface **724**. In some examples, at least one electrically conductive element (e.g. an electrode **747**) is located on surface **724** in a position to directly engage nerve **512** when housing **722** is secured relative to nerve **512**.

(207) As further shown in FIGS. **16A-16B**, a paddle **741** supports a grid array **742** of electrodes **744**, which face nerve **512** and which are opposite the electrode **747** on housing **722** thereby creating an arrangement in which various electrical vectors may be established across/through nerve **512**. Via independent programming of the various electrodes **744**, **747**, stimulation electrical vectors may be established among and between the electrodes **744** on paddle **741** and/or stimulation electrical vectors may be established between electrode **747** and at least one of the electrodes **744** on paddle **741**. The paddle **741** is supported by arm(s) **745** which extend outwardly from housing **722** of therapy device **720** by a distance to place the paddle **741** on an opposite side of the nerve **512** from housing **722** (and therefore electrode **747**). The grid array **742** may comprise a 2×2, 3×3, etc. array of independently programmable electrodes **744**.

(208) In some examples, this arrangement is secured within the subcutaneous environment **502** and/or relative to nerve **512** via mechanical tines (similar to FIG. **18B**). Alternatively, in some examples the arrangement in FIGS. **16A-16B** can be secured relative to nerve **512** or another structure within subcutaneous environment **502** via a suture affixed directly on the stimulator housing **722** or affixed on a separate arm extends from housing **722**.

(209) It will be understood that the schematic representation in FIG. **16A-16B** provides generous spacing between the paddle **741** and nerve **512** for illustrative clarity, but in at least some examples, in practice the arm **745** has a size (e.g. length) and/or shape to cause the paddle **741** (and electrodes **744** thereon) to be in releasable contact against nerve **512** to at least partially secure the device **720** relative to the nerve **512** and to implement operative electrical coupling of the electrodes **747**, **744** relative to nerve **512**.

(210) FIG. **17A** is a diagram **800** schematically representing a microstimulation therapy device **820** implanted relative to a nerve **512** of array **510** of nerves within a subcutaneous, extravascular environment **502**, according to one example of the present disclosure. In some examples, the microstimulation therapy device **820** comprises at least some of substantially the same features and

attributes as the previously described microstimulation therapy devices **100**, **200**. As shown in FIG. **17A**, therapy device **820** includes a housing **822** extending between opposite ends **823A**, **823B** with housing **822** having a generally electrically non-conductive outer surface **824**. In some examples, at least one electrically conductive element (e.g. an electrode **847**) is located on outer surface **824** in a position to directly engage nerve **512** when housing **822** is secured relative to nerve **512**. In some examples, the entire surface or substantially the entire surface **824** can be electrically conductive and thereby serve as a single electrode

(211) As further shown in FIG. **17A**, one end **849A** of a corkscrew-shaped flange **848** extends axially from one end **823B** of housing **822** and supports an axially spaced apart array **842** of electrodes **844**, which wrap about a surface of nerve **512**. In some examples, the flange **848** may sometimes be referred to as being helical. In some examples, flange **848** is biased to self-wrap about nerve **512**, which is further schematically depicted in FIG. **17B**, thereby placing the electrodes **844** in direct contact against nerve **512**. FIG. **17C** provides further information **850** regarding at least some examples associated with the arrangement of FIGS. **17A-17B**.

(212) In one aspect, at least the biasing force and self-wrapping behavior of the helical flange **848** at least partially secures the electrodes **844** relative to the nerve and at least partially secures the housing **822** of the therapy device **820** relative to the nerve **512**. In some examples, mechanical tines (similar to FIG. **18B**) can be used to further secure the housing **822** relative to nerve **512**. Alternatively, in some examples the arrangement in FIGS. **17A-17B** can be secured relative to nerve **512** or another structure within subcutaneous environment **502** via a suture affixed directly on the stimulator housing **822** or affixed on a separate arm extends from housing **822**. Accordingly, these arrangements act to further secure the housing **822** relative to the nerve **512** and/or relative to the subcutaneous environment **502** to facilitate direct engagement of electrode **847** on housing **822** against nerve **512**.

(213) Via independent programming of the various electrodes **844**, **847**, stimulation electrical vectors may be established among and between the electrodes **844** on flange **848** and/or stimulation electrical vectors may be established between electrode **847** (on housing **822**) and at least one of the electrodes **844** on flange **848**.

(214) While FIG. **17A-17B** provide one schematic representation of the helical flange **848** in relation to nerve to illustrate the axial spacing of the electrodes, extension from housing, etc., FIGS. **17C-17D** provide a further schematic representation to more fully illustrate the helical configuration of flange **848** and to illustrate that in at least some examples, the flange **848** may have a width (**W2**) generally corresponding to or greater than a width (**W1**) of the electrodes **844** located on or forming part of flange **848**. As shown in at least FIG. **17D**, in some examples the electrodes **844** are located on an inner, nerve-engaging surface **845** of flange **848** and that outer surface **843** lacks such electrodes **844** (in at least some examples).

(215) Moreover, it will be understood that the generous spacing shown in FIG. **17A** between the flange **848** (including electrodes **844** thereon) and nerve **512** is provided for illustrative clarity and that in practice the flange **848** would directly contact and releasably engage the nerve **512**, such as depicted in at least FIG. **17B**.

(216) In some examples, the device **820** may comprise more than one helical flange **848**, such as having two such flanges extend from opposite ends of the housing **822**. In some examples, both flanges **848** comprise at least one electrode along the length of the respective flange. However, in some examples, just one of the flanges **848** includes at least one electrode along its length, as shown in FIGS. **17A-17D**.

(217) In some examples, the housing **822** is positioned to contact nerve **512** even when the housing **822** omits an electrode **847**.

(218) In some examples, housing **822** omits electrode **847** and is not in contact with nerve. In some such examples, housing **822** is secured relative to a non-nerve structure, which may be some distance from nerve **512**. In such examples, the flange **848** may have a length sufficient to extend

from the housing **822** to the nerve **512** while still permitting a more distal portion of the flange **848** to engage nerve **512** both mechanically and electrically via electrodes **844**. It will be understood in some such examples that an electrical connection extends through the length of flange **848** between the stimulator in housing **822** and the electrodes **844**.

(219) In some examples, at least some of the above-described examples associated with the device **820** of FIGS. **17A-17D** may be implemented via and/or complement at least some of the examples associated with the arrangement(s) described and illustrated in association with at least FIG. **21A** and/or FIG. **21B**. Accordingly, various features associated with the arrangements in FIGS. **17A-17D**, **21A** and/or **21B** may be combined in a complementary manner.

(220) FIG. **18A** is a diagram **900** schematically representing a microstimulation therapy device **920** implanted relative to a nerve **512** of array **510** of nerves within a subcutaneous, extravascular environment **502**, according to one example of the present disclosure. In some examples, the microstimulation therapy device **920** comprises at least some of substantially the same features and attributes as the previously described microstimulation therapy devices **100**, **200**. As shown in FIGS. **18A-18B**, therapy device **920** includes a housing **922** extending between opposite ends **923A**, **923B** and opposite side edges **924A**, **924B**. In one aspect, housing **922** has a generally electrically non-conductive surface **924** supporting an array **945** of electrically conductive elements **947** (e.g. electrodes) for stimulating nerve **512** when housing **922** is secured relative to nerve **512**, as shown in FIG. **18C**.

(221) As further shown in FIGS. **18A-18C**, an array **925** of tines **926** extend from the housing **922** to facilitate mechanical fixation of the therapy device **920** relative to the subcutaneous environment **502** in a manner to juxtapose electrodes **947** in close proximity and/or contact against nerve **512**. In some examples, tines **926** are positioned at and extend from the opposite side edges **924A**, **924B** of housing **922**. In some examples, each tine is biased to extend in a particular orientation adapted to facilitate fixation within the subcutaneous environment **502**. While FIGS. **18A-18C** depict tines **926** having a particular orientation, it will be understood that tines **926** may be formed, attached, or constructed with any orientation within a generally 360 degree orientation depending upon the particular fixation scheme. In some examples, all of the tines **926** have the same general orientation (e.g. angle) while in some examples, at least some of the tines **926** have an angle/orientation different than at least some other tines **926**. FIG. **18D** provides further information **950** regarding at least some examples associated with the arrangement of FIGS. **18A-18C**.

(222) Among other features, the housing **922** of therapy device **920** in FIGS. **18A-18C** is provided in a generally planar shape having minimal thickness, which may enhance implantation by maintaining a relatively low profile. Moreover, in some examples, the housing **922** has a width extending between side edges **924A**, **924B** that is substantially greater (e.g. 2×, 3×, etc.) than a diameter of the nerve **512**, thereby providing enhanced lateral stability upon deployment of tines **926**.

(223) With general reference to at least some examples associated with at least FIGS. **14A-18D** as well as at least FIGS. **19A-20B**, the compact arrangement in which the housing of a stimulator of the microstimulation therapy device is located directly against the target nerve or in proximity to the nerve (as opposed to a pectoral location of a pulse generator) may enhance patient comfort and ease surgical implantation.

(224) In at least some examples of the microstimulation therapy device described throughout the present disclosure, such as but not limited to, FIGS. **5**, **8**, and **14A-18B**, at least some of the electronics (e.g. circuitry, components, elements) within the housing of the stimulator of microstimulation therapy device **100**, **200** and/or at least some electronic components external to the housing of the stimulator of therapy device **100,200** may be implemented as integrated passive devices on silicon, via chip stacking, and/or via flexible substrates.

(225) In at least some examples of the microstimulation therapy device described throughout the present disclosure, such as but not limited to, FIGS. **5**, **8**, **14A-18B**, and **19A-20C** at least some

examples of the housing of the stimulator of microstimulation therapy device **100**, **200** includes: (A) feedthroughs mounted directly onto a printed circuit board (PCB) or electronics package; (B) feedthroughs connected to electronics via a process similar to solder reflow once there is direct contact between the feedthroughs and the board; and/or (C) active or smart lead technology that allows one or two feedthroughs to be multiplexed outside of the hermetic sealed assembly.

(226) In at least some examples of the microstimulation therapy device described throughout the present disclosure, such as but not limited to, FIGS. **5**, **8**, **14A-18B**, and **19A-20C**, at least some examples of the electrodes external to the housing of the stimulator microstimulation therapy device include at least the following characteristics. For instance, in some examples an electrode structure (e.g. a lead) is integrated with the hermetically sealed housing, such as at least partially depicted in at least FIGS. **15B**, **16B**, **17A-17B** in which a proximal end of a structure carrying electrodes (which are spaced apart from the housing) is electrically and mechanically coupled relative to (and extending outwardly from) the hermetic housing.

(227) In another instance, in some examples, at least some electrodes are mounted directly on the hermetic housing so the housing acts like a paddle lead, such as at least partially depicted in FIGS. **14A** and **16A-18A**, **19A-19C**. In some such examples in which such electrodes form an array of electrodes, these electrodes can be attached to the electronics package (within housing) with a direct contact process like that used for electronics surface mount technologies (SMT) to avoid the need to utilize space for larger interconnect technologies like printed circuit board (PCB) through-hole soldering.

(228) In another instance, in some examples in which at least a portion of the outer surface of the housing is not conductive, conductive traces (e.g. ceramic) and electrodes could be directly integrated into the housing so the housing could be used to distribute stimulation and/or sensing signals from the electronic package within the housing to electrode arrays along the housing or on an electrode structure or lead extending from the housing.

(229) In some examples, at least the stimulation circuitry of a stimulator comprises flexible circuitry. In some such examples, a power element is not incorporated within such flexible circuitry. In some such examples, the power element is located along a centerline of a housing containing the flexible stimulation circuitry, and in some instances, this centerline may sometimes be referred to as a spine of the housing.

(230) FIG. **19A** is a perspective view schematically representing a cuff electrode **975** of a stimulation therapy device **976**, according to one example of the present disclosure.

(231) As shown in FIG. **19A**, cuff electrode **975** comprises a housing **980** to contain at least some features and attributes of a stimulator (e.g. **100** in FIG. **5**; **200** in FIG. **8**) with housing **980** having an arcuate nerve-engaging surface **982** shaped (e.g. an arcuate cross-sectional shape) to correspond to an arcuate outer surface (e.g. circumference) of a nerve **989**. The arcuate nerve-engaging surface **982** facilitates robust, secure engagement of the housing **980** relative to nerve **989**. Housing **980** extends between a first end **981A** and an opposite second end **981B**. In some examples, housing **980** comprises a non-engaging surface **983** opposite the nerve-engaging surface **982**. In some examples, the non-nerve-engaging surface **983** comprises an arcuate cross-sectional shape. In some examples, this arcuate cross-sectional shape of non-nerve-engaging surface corresponds to the arcuate cross-sectional shape of the nerve-engaging surface **982**.

(232) In some examples, the housing **980** may comprise a generally uniform thickness over at least 50 percent of a cross-sectional area of the housing **980**.

(233) In some examples, cuff electrode **975** comprises a flange **990**. The flange **990** comprises a first side portion **992** extending from a first side **984A** of an outer surface **983** of housing **982** and an opposite second side portion **993** releasably engageable relative to an opposite second side **984B** of outer surface **983** of housing **982**. The flange **990** has a generally arcuate cross-sectional shape including a nerve-engaging surface **997** sized to extend across the opening **987** defined between opposite end portions **988A**, **988B** of housing **980**.

(234) In some examples, the flange **990** is a separate member and the first side portion **992** of flange **990** is then secured relative to the first side **984A** of housing **982**. However, in some examples, the first side portion **992** of flange **990** is molded with housing **982** such that housing **980** and flange **990** together form a single unitary molded piece (e.g. a monolithic structure).

(235) In either case, the first side portion **992** of flange **990** is flexibly bendable relative to first side **984A** of housing **982** to enable moving the flange **990** between a closed position (represented in FIG. **19A** via solid lines) covering the opening **987** between end portions **988A**, **988B** of housing **980** and an open position (represented via dashed lines **999**) pivoted away from opening **987** to permit maneuvering the housing **982** on and off the nerve **989** during implantation. In some examples, the flexibly bendable functionality may sometimes be referred to as being a living hinge.

(236) In some examples, in cooperation with first side **984A** of housing **982**, the flange **990** is biased in the closed position (represented by solid lines) but can be moved into the open position to mount or dismount the relative to the nerve **989**.

(237) In some examples, cuff electrode **975** forms at least a portion of a therapy device having at least some of substantially the same features and attributes as therapy device **520** in FIGS. **14A-14B**. In some examples, cuff electrode **975** comprises at least a partial implementation of the therapy device **520** of FIGS. **14A-14B**. However, in the example shown in FIG. **19A**, the therapy device **975** comprises just one flange **990** instead of two flanges **540A**, **540B** in FIG. **14A-14B**. However, it will be understood that in some examples, instead of having a single flange **990**, cuff electrode **975** may include two flanges **990** oriented in opposite directions to at least partially overlap each other.

(238) In addition, in the example shown in FIG. **19A**, the cuff electrode **975** omits ring electrodes **532** on housing **980** and instead provides at least one electrode on nerve-engaging surface **982** while omitting electrodes on outer surface **983** (e.g. a non-nerve engaging surface) of housing **980**. For illustrative clarity, the at least one electrode is omitted from FIG. **19A**.

(239) However, as shown in the sectional views of FIGS. **19B** and **19C**, in some examples the at least one electrode comprises an array **1000** of electrodes **1001**. In some examples, as shown in FIG. **19B**, the electrodes **1001** may be axially spaced apart along a length (L) nerve-engaging surface **982** of the housing **980**. In some examples, as shown in FIG. **19B**, an array **1005** of electrodes **1006** may be spaced apart in a radial pattern extending transversely along nerve-engaging surface **982**. In some examples, the at least one electrode may comprise a grid array like that in FIGS. **18A-18B** such that both axially spaced apart electrodes **1001** and radially spaced apart electrodes **1005** are present in a grid (e.g. 2×2, 3×3, etc.) on nerve-engaging surface **982**. In some examples, other than having different locations, there is no difference between the functionality of electrodes **1001** as compared to electrodes **1005**, with any various combination of electrodes **1001** and/or electrodes **1005** functioning in a complementary manner. In some examples, electrodes **1001** and/or electrodes **1005** are independently programmable to implement a neurostimulation therapy.

(240) In some examples, just a single electrode **1001** or **1005** is located on nerve-engaging surface **982**. In some such examples, cuff electrode **975** comprises additional electrodes, such as on nerve-engaging surface **997** of flange **990**, which function in a complementary manner with the single electrode (**1001** or **1005**) on nerve-engaging surface **982**.

(241) In some examples, the at least one electrode of cuff electrode **975** is located on the nerve-engaging surface **997** of flange **990** instead of on nerve-engaging surface **982** of the housing **982**. In some examples, the at least one electrode on nerve-engaging surface **997** may comprise an axially spaced apart array **1000** of electrodes **1001** as shown in the sectional view of FIG. **19B** and/or a radially spaced apart array **1005** of electrodes **1005** as shown in the sectional view of FIG. **19C**.

(242) In some examples, both the nerve-engaging surface **982** of housing **980** and the nerve-engaging surface **997** of flange **990** include at least one electrode (e.g. **1001** or **1005**), which may



be a single electrode on each respective nerve-engaging surface **982, 997** or which may be an array (**1000** and/or **1005**) of electrodes on each of nerve-engaging surface **982, 997**

(243) It will be understood that the schematic representation in FIG. **19A** provides generous spacing between an outer surface of nerve **989** and the nerve-engaging surface **982** (of housing **980**) and nerve-engaging surface **997** (of flange **990**) for illustrative clarity. However, in at least some examples, in practice the housing **980** and/or flange **990** are sized and shaped to, cause nerve-engaging surfaces **982, 997** to directly contact and releasably engage the arcuate outer surface of nerve **989** to grippingly secure the cuff electrode **975** about the nerve **989**.

(244) In some examples, at least a portion of the housing **980** and/or flange **990** comprises a flexible, resilient material which may enable at least one of the nerve-engaging surfaces **982, 997** to at least partially conform about the nerve **989** to more securely engage the nerve **989**.

(245) As further shown in the sectional view of FIG. **19B**, in some examples housing **980** comprises a body **987** internal to outer surface **983** and nerve-engaging surface **982**. In some examples, as schematically represented via FIG. **19B**, a stimulator **1003** (e.g. **100, 200** in FIGS. **5, 8**) is located within body **987** and thereby contained within housing **980**. It will be understood that in some examples, the various elements comprising a stimulator **1003** may be distributed throughout body **987** and are not necessarily consolidated in a single monolithic structure. The stimulator **1003** is electrically connected to the electrodes **1001** (or **1005** in FIG. **19C**) via body **987** so that nerve-engaging surface **982** is non-conductive except of the surfaces of electrodes **1001, 1005**.

(246) FIG. **20A** is a perspective view schematically representing a cuff electrode **1021** of a stimulation therapy device **1020** in an open position (A) and a closed position (B), according to one example of the present disclosure.

(247) In some examples, the cuff electrode **1021** comprises at least some of substantially the same features as cuff electrode **975** with a few exceptions. In one exception, cuff electrode **1021** provides a flange **1030** like flange **990** except with a hinge **1033** at a junction of an end portion **988B** of the housing **982** and an end portion **1031A** of flange **1030**. In some examples the flange **1030** comprises a generally rigid member. In some examples, flange **1030** comprises a semi-rigid, resilient member. In view of the end-to-end connection of the flange **1030** relative to the housing, the flange **1030** may sometimes be referred to as a cover.

(248) Together with hinge **1033**, this cover **1030** may sometimes be referred to as a closable clasp which releasably locks into the closed position (B) in which end portion **1031B** of flange **1030** is firmly engaged against end portion **988A** of housing **982**. Accordingly, in some examples, the hinge **1033** permits rotation of cover **1030** between the open and closed position, with cover **1030** biased to remain in the closed position until or unless a sufficient force is applied to overcoming the biasing force of hinge **1033** such that the cover **1030** moves to the open position (A).

(249) In some examples, the structure and functionality of hinge **1033** is implemented via a shape memory material formed as part of housing **982** and/or flange **1030**, and with such material extending between and/or forming the junction of the end portion **988B** of housing **982** and end portion **1031A** of flange **1030**. In some examples, the shape memory material may comprise a metal material such as, but not limited to, Nitinol while in some examples, the shape memory material may comprise a non-metal material.

(250) In some examples of the cuff electrode **1021** of FIG. **20A**, the axial array of electrodes **1001** (FIG. **19B**) and/or the radial array of electrodes **1005** (FIG. **19C**) may be implemented on a nerve-engaging surface **982** of the housing **980**. In some examples, the axial array of electrodes **1001** (FIG. **19B**) and/or the radial array of electrodes **1005** (FIG. **19C**) may be implemented on a nerve-engaging surface **1037** of the flange **1030**. In some examples, both respective nerve-engaging surfaces **982, 1037** includes at least some electrodes, whether in the axial array configuration (FIG. **19B**), the radial array configuration (FIG. **19C**), or some other combination of electrodes.

(251) FIG. **20B** is a perspective view schematically representing a cuff electrode **1051** of a

stimulation therapy device **1050**, according to one example of the present disclosure. In some examples, the cuff electrode **1051** comprises at least some of substantially the same features and attributes as the stimulators of the therapy devices described in association with FIGS. **1-18** and/or in association with FIG. **21A-25B**. In some examples, the cuff electrode **1051** comprises one example implementation of at least some of the features and attributes of the therapy device described in association with at least FIG. **14A-14B** or **15A-15B**.

(252) In some examples, cuff electrode **1051** comprises a housing **1060** defining a nerve-engaging surface **1062**, including a first nerve-engaging portion **1065**, a pair of second nerve-engaging portions **1067A**, **1067B**, and a third pair of nerve-engaging portions **1069A**, **1069B**. In one aspect, these various nerve-engaging portions **1065**, **1067A**, **1067B**, **1069A**, **1069B** work together to releasably engage a nerve **989**. In some examples, the portion of cuff electrode **1051** including nerve-engaging portions **1067A**, **1067B**, and **1069A**, **1069B** may sometimes be referred to as arms **1059A**, **1059B** which extend from a body **1064** of housing **1060**. In some examples, in their open position (A), the arms **1059A**, **1059B** may extend generally parallel to each other, or even diverge from each other to provide an ample opening **1087** to mount and dismount cuff electrode **1051** relative to nerve **989** such as during implantation, etc.

(253) In a manner similar to that shown in FIG. **19B**, body **1064** may contain (e.g. encapsulate) a stimulator (e.g. at least **100**, **200** in FIGS. **5**, **8** **1003** in FIG. **19B**). As noted elsewhere and as applicable to any of the examples of the present disclosure, in some examples, except for any electrodes present on a nerve-engaging surface of the housing **1060**, the entire external surface **1063** of housing **1060** defines a non-conductive surface. As noted elsewhere and as applicable to any of the examples of the present disclosure, in some examples body **1064** comprises a non-conductive material in which the stimulator is contained or encapsulated internally within housing **1060**.

(254) In some examples, the respective pivot portions **1071A**, **1071B** and pivot portions **1070A**, **1070B** permit rotation of end portions **1088A**, **1088B** of arms **1059A**, **1059B** between the open position (A) and closed position (B). Once cuff electrode **1051** is installed onto nerve **989** in a closed position (B), the arms **1059A**, **1059B** are biased to remain in the closed position (B) until or unless a sufficient force is applied to overcoming the biasing force of hinge **1033** such that the end portions **1088A**, **1088B** move to the open position (A). However, it will be understood that the open position (A) may be typically employed primarily during initial implantation and maneuvering of the cuff electrode **1051** relative to nerve **989**.

(255) In some examples, the structure and functionality of pivot portions **1070A**, **1070B**, **1071A**, and **1071B** may be implemented via a shape memory material formed as part of housing **1060**. In some examples, the shape memory material may comprise a metal material such as, but not limited to, Nitinol while in some examples, the shape memory material may comprise a non-metal material. In some examples, at least some of the pivot portions **1070A**, **1070B**, **1071A**, **1071B** may be sometimes be referred to as a living hinge.

(256) While not shown in FIG. **20B**, in some examples, the first nerve-engaging portion **1065** of housing **1060** comprises an arcuate shaped surface in a manner similar to nerve-engaging surface **982** of housing **980** in FIGS. **19A-19C**. In some examples, the respective second nerve-engaging portions **1067A**, **1067B** of housing **1060** comprise an arcuate shaped surface in a manner similar to nerve-engaging surface **982** of housing **980** in FIGS. **19A-19C**. In some examples, the respective third nerve-engaging portions **1069A**, **1069B** of housing **1060** comprise an arcuate shaped surface in a manner similar to nerve-engaging surface **982** of housing **980** in FIGS. **19A-19C**.

(257) In some examples, the respective first, second and third nerve-engaging surfaces **1065**, **1067A**, **1067B**, **1069A**, **1069B** have a contour which gradually blends into the adjacent respective nerve-engaging surface such that the respective first, second, and third nerve-engaging surfaces do not act as discretely different surfaces.

(258) In some examples, the cuff electrode **1051** provides an arrangement in which the arms

**1059A**, **1059B** and body **1064** form a single unitary piece (e.g. a monolithic element) which can releasably engage a nerve.

(259) FIG. **20C** is a partial end view schematically representing two arms of cuff electrode **1090** for a microstimulation therapy device **1060**, according to one example of the present disclosure. As shown in FIG. **20C**, the two end portions **1088A**, **1088B** of arms **1059A**, **1059B** point toward each other, and even may contact in some examples. In some examples, the two end portions **1088A**, **1088B** may even overlap.

(260) In some examples of the cuff electrode **1061** of FIG. **20B**, the axial array of electrodes **1001** (FIG. **19B**) and/or the radial array of electrodes **1005** (FIG. **19C**) may be implemented on a nerve-engaging surface **1062** of the housing **1060**, whether on portion **1065**, portions **1067A**, **1067B**, and/or portions **1069A**, **1069B**.

(261) FIG. **21A** is a diagram **1100** schematically representing a microstimulation therapy device **1120** implantable relative to a nerve within a subcutaneous, extravascular environment **1102**, according to one example of the present disclosure. In some examples, the microstimulation therapy device **1120** comprises at least some of substantially the same features and attributes as the previously described microstimulation therapy devices **100**, **200**.

(262) As shown in some examples, the microstimulation therapy device **1120** forms part of an arrangement **1121** including a lead **1130** and a cuff electrode **1140**.

(263) In general terms, cuff electrode **1140** includes some non-conductive structures biased to (or otherwise configurable to) releasably secure the cuff electrode **1140** about a target nerve **30** (FIGS. **1-4**) and includes an array of electrodes to deliver a stimulation signal to the target nerve. In some examples, the cuff electrode **1140** may comprise at least some of substantially the same features and attributes as described within at least U.S. Pat. No. 8,340,785 issued on Dec. 25, 2012 and/or U.S. Patent Publication 2011/0147046 published on Jun. 23, 2011.

(264) The lead **1130** extends between the cuff electrode **1140** and microstimulator **1120** with lead **1130** having a length (X1). In some examples, length X1 may be up to 20 centimeters to enable anchoring the microstimulator to a bony structure (or other sturdy tissue) a short distance from the target nerve and cuff electrode **1140**. In some examples, length X1 may be 10 centimeters or less for other anchoring arrangements and/or electrode cuff deployments.

(265) As further shown in FIG. **21A**, the arrangement **1121** may further include an anchor(s) **1160** by which microstimulator **1120** is secured relative to a bodily structure **1162** (e.g. bony structure or other sturdy tissue) within the subcutaneous environment **1102**. In some examples, the anchor **1160** may include a loop element to facilitate deployment of fastening mechanism relative to the bodily structure **1162**.

(266) FIG. **21B** is a diagram **1200** schematically representing an implanted microstimulation therapy device **1220** secured relative to a bony structure **1230** within a subcutaneous environment **1202**, according to one example of the present disclosure. In some examples, the microstimulation therapy device **1220** comprises at least some of substantially the same features and attributes as the previously described microstimulation therapy devices **100**, **200**. As shown in FIG. **21B**, a screw **1240** or analogous mechanical fastener fixes the microstimulator **1220** against a bony structure **1230**, which may be a mandible **1232**, cranium **1234**, or other bony tissue **1236**.

(267) FIG. **22** is a diagram **1300** schematically representing arrangements for an antenna associated with a microstimulation therapy device **1320**, according to one example of the present disclosure. In some examples, the microstimulation therapy device **1320** comprises at least some of substantially the same features and attributes as the previously described microstimulation therapy devices **100**, **200**. In some examples, as shown in FIG. **22** in some examples, microstimulator **1320** forms part of an arrangement including an antenna **1333A** or **1333B**, and which may include other elements (e.g. lead, electrodes, anchors, etc.) as described throughout the present disclosure.

(268) As shown in FIG. **22**, in a manner at least consistent with at least some previously described examples, the microstimulator **1320** is electrically coupled and mechanically coupled relative to a

nerve **30** for applying a therapeutic stimulation signal to nerve **30**. Moreover, microstimulator **1320** receives energy via an antenna arranged to facilitate fast charging and/or energy harvesting protocols. Accordingly, in one arrangement an antenna **1333A** is positioned (e.g. secured) within the subcutaneous environment **1302** close to skin **70** in a general location **1343** of the head/neck region so that the antenna **1333A** is readily accessible by an externally located energizing device **1343** for charging and/or energy harvesting. In this arrangement, antenna **1333A** is in electrical communication with microstimulator **1320** via a pathway **1325**, which may be wired or wireless. (269) In another arrangement, an antenna **1333B** is positioned (e.g. secured) within the subcutaneous environment **1302** close to skin **70** but in a cochlear location **1346** of the head/neck region so that the antenna **1333B** is readily accessible by an externally located energizing device **1343** for charging and/or energy harvesting. In this arrangement, antenna **1333B** is in electrical communication with microstimulator **130** via a pathway **1327**, which may be a wired pathway. (270) In either arrangement, in some examples, the antenna is reasonably close to the skin to facilitate a fast rate of energy transfer relative to the energizing device **1343** and/or the antenna is relatively remote from the nerve **30** and/or microstimulator **1320**. (271) It will be understood that in at least some examples, various features and attributes among the different examples throughout at least FIGS. **1-22** and/or throughout FIGS. **23A-27**, may be combined in different configurations on a feature-by-feature manner. (272) It also will be understood that in the examples described throughout the present disclosure, at least any implantable elements exposed to tissue, fluids, etc. within the human body will be made of biocompatible materials, whether polymer and/or metal. (273) FIG. **23A** is a diagram **1400** schematically representing a microstimulation therapy device **1420** implanted within at least a portion of the vasculature within a head/neck region **24**, according to one example of the present disclosure. In some examples, the microstimulation therapy device **1420** comprises at least some of substantially the same features and attributes as the previously described microstimulation therapy devices **100, 200**. (274) As shown in FIG. **23A**, microstimulation therapy device **1420** forms part of an arrangement **1421** also including a lead **1430** and an electrode array **1434**. The lead **1430** extends distally from a housing of the therapy device **1420** and with a distal portion **1432** of the lead **1430** supporting the electrode array **1434** of electrodes **1436**. In some examples, the array **1434** includes several axially spaced apart electrodes **1436**, although other electrode configurations may be used. (275) As shown in FIG. **23A**, microstimulation therapy device **1420** has been implanted such that the entire arrangement **1421** resides within the vasculature **1404**, with distal electrode array **1434** positioned within a vein **1406** adjacent a target nerve **1412** of an array **1410** of nerves, such that electrical stimulation may be applied to nerve **1412** from the intravascular location of the distal electrode array **1434**. Accordingly, in some instances, such stimulation may sometimes be referred to as a transvascular application of a therapeutic stimulation signal. (276) In one aspect, in a manner similar to at least some examples previously described herein, the relatively small size and/or shape of the microstimulator device **1420** facilitates a minimally invasive implantation procedure in which the arrangement **1421** may be implanted within the vasculature **1404** within the head/neck region **24** without involving other parts of the patient's body. Accordingly, in some examples, the entire arrangement **1421** (including microstimulation therapy device **1420**) resides entirely within the peripheral vasculature. (277) In some examples, the housing of the microstimulation therapy device **1420** is secured within the vasculature via an anchor **1422**, which may comprise at least one of tines, barbs, stents, and/or other fixation mechanisms. (278) However, it will be understood that in some examples, the microstimulation therapy device **1420** may be secured within a more central portion of the patient's vasculature to accommodate some implementations in which a housing of the therapy device **1420** has a relatively larger size. As such, in some implementations, the therapy device **1420** may reside within a portion of the

vasculature extending in a portion of the body other than the head/neck region.

(279) FIG. 23B is a diagram 1450 schematically representing a microstimulation therapy device 1470 implanted within at least a portion of the vasculature within a head/neck region, according to one example of the present disclosure. In some examples, the microstimulation therapy device 1470 comprises at least some of substantially the same features and attributes as the previously described microstimulation therapy devices 100, 200.

(280) As shown in FIG. 23B, microstimulation therapy device 1470 forms part of an arrangement 1471 also including a lead 1460 and an electrode array 1434. The lead 1460 extends distally from a housing of the therapy device 1470 and with a distal portion 1432 of the lead 1460 supporting the electrode array 1434 of electrodes 1436. In some examples, the array 1434 includes several axially spaced apart electrodes 1436, although other electrode configurations may be used.

(281) As shown in FIG. 23B, microstimulation therapy device 1470 has been implanted such that the just the distal electrode array 1434 (and a portion of lead 1460) resides within the vasculature 1404, and in particular within vein 1406 adjacent the target nerve 1412 of an array 1410 of nerves, such that electrical stimulation may be applied to nerve 1412 from the intravascular location of the distal electrode array 1434. Accordingly, in some instances, such stimulation may sometimes be referred to as a transvascular application of a therapeutic stimulation signal.

(282) In some examples, the housing of the microstimulation therapy device 1470 is secured external to the vasculature 1404 within the subcutaneous environment 1402 via an anchor 1472, which may comprise at least one of tines, barbs, screws, and/or other fixation mechanisms. In some examples, when the anchor comprises a screw(s), the housing of the therapy device 1470 is secured relative to a bony structure, such as but not limited to, the mandible (either modified or unmodified), the cranium, and/or other bony structures suited to position the microstimulation therapy device 1470 in reasonably close proximity to the target nerve 1412 and vein 1406 in which lead 1460 and electrode array 1434 extend.

(283) In one aspect, in a manner similar to at least some examples previously described herein, the relatively small size and/or shape of the microstimulator device 1470 facilitates a minimally invasive implantation procedure in which the arrangement 1471 may be implanted within the subcutaneous environment 1402 within the head/neck region 24 without involving other parts of the patient's body and via a location reasonably close the target nerve 412 to be stimulated. Accordingly, in some examples, the entire arrangement 1471 (including microstimulation therapy device 1420) resides entirely within head/neck region 24. In addition, the relatively small size of the microstimulation therapy device 1470 enables its subcutaneous implantation (via a percutaneous access or analogous minimally invasive technique) in a location reasonably close to the vascular entry point 1407 at which distal electrode array 1434 can be placed promptly adjacent the targeted nerve 1412, thereby saving much time and effort in achieving a therapeutically efficacious implantation.

(284) FIG. 24 is a block diagram of a therapy manager 1600, according to one example of the present disclosure. In some examples, therapy manager 1600 may be implemented as therapy manager 122 in the therapy devices 100, 200 of FIGS. 5 and 8 and/or therapy manager 1600 comprises at least substantially the same features and attributes as therapy manager 122 in therapy devices 100, 200. In some examples, therapy manager 1600 is implemented as therapy manager 1705 in control portion 1700 in FIG. 25A and/or comprises at least some of substantially the same features and attributes as therapy manager 1705 in FIG. 25A. While not necessarily expressly stated directly in association with FIG. 24, it will be understood that therapy manager 1600 may utilize and/or coordinate with at least some of the therapy-related features, functions, attributes, parameters, etc. as described throughout at least some examples of the present disclosure.

(285) In some examples, at least some of the features and functions of therapy manager 1600 are accessed via user interface 1710 in FIG. 25B.

(286) As shown in FIG. 24, in some examples, therapy manager 1600 includes a stimulation

intensity function **1610**, an open loop module **1620**, and a closed loop module **1630**.

(287) In some examples, once therapy is initiated during a daily treatment period, stimulation is performed generally continuously. In some examples, once therapy is initiated during a daily sleep period, stimulation is performed on an “as-needed” basis, such that stimulation occurs when needed but is otherwise suspended.

(288) In some examples, the open loop module **1620** causes a microstimulation therapy device to apply therapeutic stimulation without receiving and/or sensing physiologic information.

(289) In some examples, the closed loop module **1630** causes a microstimulation therapy device to apply therapeutic stimulation, at least in part, based on received and/or sensed physiologic information related to the intended therapy. As shown in FIG. 24, in some examples the closed loop module **1630** includes a stimulation timing function **1640**, an automatic stimulation on/off function **1650**, a respiratory information parameter **1660**, an auto-titrate function **1662**, a power management function **1664**, and/or a sleep position parameter **1670**.

(290) In some examples, via at least stimulation timing function **1640**, stimulation is synchronized relative to a sensed onset of inspiration in the respiratory cycle. In some instances, via at least stimulation timing function **1640** initiation, termination, and/or duration of stimulation are based on a sensed respiratory waveform but are not synchronized relative to each inspiratory phase.

(291) However, in some instances, via at least stimulation timing function **1640**, stimulation is generally synchronized with inspiration.

(292) In some instances, via at least stimulation timing function **1640**, whether or not stimulation is synchronized with inspiration, stimulation is triggered according to a time sequence at least partially based on at least one of a beginning of inspiration, an end of inspiration, a beginning of expiration, and/or an end of expiration.

(293) In some examples, via an automatic stimulation state function **1650**, stimulation is enabled and disabled (e.g. turned on and off) automatically according to various parameters. In some examples, such parameters include posture, respiratory rate, apnea-hypopnea event count, etc. However, in some examples, because sleep disordered breathing is generally associated with sleep periods of the patient, in some examples a treatment period automatically coincides with a daily sleep period of the patient with the automatic stimulation state function **1650** then enabling/disabling stimulation according to the above-identified parameters. In some instances, the daily sleep period is identified via sensing technology which detects motion, activity, posture, position of the patient, as well as other indicia, such as heart rate, breathing patterns, etc. However, in some instances, the daily sleep period is selectably preset, such as from 10 pm to 6 am or other suitable times.

(294) In some examples, the respiratory information parameter **1660** includes respiratory waveform information and/or tracks respiratory effort including respiratory patterns (e.g., inspiration, expiration, respiratory pause, etc.) and is obtained via a sensing function (e.g. **205** in FIG. 8). In some examples, this respiratory information is employed to trigger activation of stimulation circuitry (e.g. **112** in FIG. 8) to stimulate a target nerve (e.g. **30** in FIGS. 1-4) and/or is employed in various ways as described throughout at least some examples of the present disclosure.

(295) In some examples, via at least the power management parameter **1664**, a characteristic of a sensed respiratory waveform (e.g. via respiratory information parameter **1660**) is used to reduce at least one parameter regarding an intensity of stimulation pulses (per stimulation intensity function **1610**) to reduce power requirements. In some examples, such respiratory characteristics include apnea-hypopnea event detection, inspiratory onset detection, etc. In some examples, the at least one parameter of stimulation intensity function **1610** includes a pulse amplitude, number of pulses, pulse width, burst time, and/or electrode configuration.

(296) In some examples, via at least the sleep position parameter **1670**, the therapy manager includes a posture-adjustment function to enable adjusting stimulation timing (per **1640**) and/or intensity (per **1610**) in accordance with changing sleep postures/positions throughout the night.

(297) In some examples, via an auto-titrate parameter **1662**, a characteristic of a sensed respiratory waveform (per parameter **1660**) enables performing an auto-titration protocol via at least one parameter of stimulation intensity (per function **1610**). In some examples, such characteristics include apnea-hypopnea event detection, inspiratory onset detection, etc. In some examples, the at least one parameter of stimulation intensity (**1610**) includes a pulse amplitude, number of pulses, pulse width, burst time, and/or electrode configuration.

(298) FIG. **25A** is a block diagram schematically representing a control portion **1700**, according to one example of the present disclosure. In some examples, control portion **1700** includes a controller **1702** and a memory **1704**. In some examples, control portion **1700** provides one example implementation of a control portion forming a part of, or implementing, any one of managers, control portions, and/or therapy devices/systems, as represented throughout the present disclosure in association with FIGS. **1-23**.

(299) In general terms, controller **1702** of control portion **1700** comprises at least one processor **1703** and associated memories. The controller **1702** is electrically couplable to, and in communication with, memory **1704** to generate control signals to direct operation of at least some components of the systems, devices, components, functions, and/or modules described throughout the present disclosure. In some examples, these generated control signals include, but are not limited to, employing manager **1705** stored in memory **1704** to manage therapy for sleep disordered breathing in the manner described in at least some examples of the present disclosure. It will be further understood that control portion **1700** (or another control portion) may also be employed to operate general functions of the various therapy devices/systems described throughout the present disclosure.

(300) In response to or based upon commands received via a user interface (e.g. user interface **1710** in FIG. **25B**) and/or via machine readable instructions, controller **1702** generates control signals to implement therapy implementation, monitoring, and/or management in accordance with at least some of the previously described examples of the present disclosure. In some examples, controller **1702** is embodied in a general purpose computing device while in some examples, controller **1702** is incorporated into or associated with at least some of the associated components of the therapy devices and/or managers described throughout the present disclosure.

(301) For purposes of this application, in reference to the controller **1702**, the term “processor” shall mean a presently developed or future developed processor (or processing resources) that executes sequences of machine readable instructions contained in a memory. In some examples, execution of the sequences of machine readable instructions, such as those provided via memory **1704** of control portion **1700** cause the processor to perform actions, such as operating controller **1702** to implement sleep disordered breathing (SDS) therapy and/or monitoring, as generally described in (or consistent with) at least some examples of the present disclosure. The machine readable instructions may be loaded in a random access memory (RAM) for execution by the processor from their stored location in a read only memory (ROM), a mass storage device, or some other persistent storage (e.g., non-transitory tangible medium or non-volatile tangible medium, as represented by memory **1704**. In some examples, memory **1704** comprises a computer readable tangible medium providing non-volatile storage of the machine readable instructions executable by a process of controller **1702**. In other examples, hard wired circuitry may be used in place of or in combination with machine readable instructions to implement the functions described. For example, controller **1702** may be embodied as part of at least one application-specific integrated circuit (ASIC). In at least some examples, the controller **1702** is not limited to any specific combination of hardware circuitry and machine readable instructions, nor limited to any particular source for the machine readable instructions executed by the controller **1702**.

(302) FIG. **25B** is a block diagram schematically representing user interface **1710**, according to one example of the present disclosure. In some examples, user interface **1710** forms part or and/or is accessible via a device external to the patient and by which the microstimulation therapy device

**100, 200** may be at least partially controlled and/or monitored. The external device housing user interface **1710** may be a patient remote and/or a clinician portal.

(303) In some examples, user interface **1710** comprises a user interface or other display that provides for the simultaneous display, activation, and/or operation of at least some of the various components, modules, functions, parameters, features, and attributes of manager (**122** in FIGS. **5, 8; 1600** in FIG. **24**) and/or control portion (**120** in FIGS. **5, 8; 1700** in FIG. **25A**). In some examples, at least some portions or aspects of the user interface **1710** are provided via a graphical user interface (GUI). In some examples, as shown in FIG. **25B**, user interface **1710** includes display **1712** and input **1714**.

(304) In some instances, at least some examples of a microstimulation therapy device as described in association with at least FIGS. **1-25** may be employed to perform vagal nerve stimulation and/or baroreceptor-based therapy.

(305) FIG. **26** is a block diagram schematically representing aspects of a method **2500** of microstimulation, according to one example of the present disclosure. In some examples, at least some aspects of method **2500** may be implemented via at least some of the systems, apparatuses, devices, stimulators (including microstimulators), sensors, power elements, functions, parameters, components, elements, etc. as described throughout the examples of the present disclosure in association with FIGS. **1-25B**. In some examples, at least some aspects of method **2500** may be implemented via at least some systems, apparatuses, devices, stimulators (including microstimulators), sensors, power elements, functions, parameters, components, elements, etc. other than those described throughout the examples of the present disclosure in association with FIGS. **1-25B**.

(306) As shown at **2502** in FIG. **26**, in some examples one aspect of a method **2500** comprises fully implanting a microstimulator via single incision. As shown at **2504** in FIG. **26**, in some examples one aspect of a method **2500** comprises encapsulating a microstimulator in a non-conductive portion of a housing. As shown at **2506** in FIG. **26**, in some examples one aspect of a method **2500** comprises arranging at least one partially flexible element to extend from a housing. As shown at **2508** in FIG. **26**, in some examples one aspect of a method **2500** comprises arranging the at least one partially flexible element to include a nerve-engaging element. As shown at **2510** in FIG. **26**, in some examples one aspect of a method **2500** comprises arranging the housing to include a nerve-engaging portion. As shown at **2512** in FIG. **26**, in some examples one aspect of a method **2500** comprises arranging at least one electrode on at least one of a housing and an at least partially flexible nerve-engaging element extending from the housing.

(307) In some examples, the various aspects **2502-2512** may be performed together or in various combinations, with it being understood that any methods performed according to examples of the present disclosure are not limited to the aspects **2502-2512** associated with the method(s) implementable as schematically represented via FIG. **26**.

(308) FIG. **27** is a block diagram schematically representing aspects of a method **2600** of microstimulation, according to one example of the present disclosure. In some examples, at least some aspects of method **2600** may be implemented via at least some of the systems, apparatuses, devices, stimulators (including microstimulators), sensors, power elements, functions, parameters, components, elements, etc. as described throughout the examples of the present disclosure in association with FIGS. **1-25B**. In some examples, at least some aspects of method **2600** may be implemented via at least some systems, apparatuses, devices, stimulators (including microstimulators), sensors, power elements, functions, parameters, components, elements, etc. other than those described throughout the examples of the present disclosure in association with FIGS. **1-25B**.

(309) As shown at **2602** in FIG. **27**, in some examples one aspect of a method **2600** comprises arranging a first portion of a power element to be implantable and to be rechargeable. As shown at **2604** in FIG. **27**, in some examples one aspect of a method **2600** comprises arranging a second



portion of the power element to be external to the patient and to selectively recharge the first portion. As shown at **2606** in FIG. 27, in some examples one aspect of a method **2600** comprises arranging the second portion as a charging station comprising at least one of an inductive-based station and a radiofrequency-based station. As shown at **2608** in FIG. 27, in some examples one aspect of a method **2600** comprises arranging the charging station as a patient support. As shown at **2610** in FIG. 27, in some examples one aspect of a method **2600** comprises arranging the patient support to include at least one sensor for physiologic and/or patient-related environmental information.

(310) In some examples, the various aspects **2502-2512** may be performed together or in various combinations, with it being understood that any methods performed according to examples of the present disclosure are not limited to the aspects **2502-2512** associated with the method(s) implementable as schematically represented via FIG. 26.

(311) Although specific examples have been illustrated and described herein, it will be appreciated by those of ordinary skill in the art that a variety of alternate and/or equivalent implementations may be substituted for the specific examples shown and described without departing from the scope of the present disclosure. This application is intended to cover any adaptations or variations of the specific examples discussed herein.

## Claims

1. A system comprising: a therapy device arranged to be implanted within a head/neck region of a patient, comprising: a microstimulator sized and/or shaped to be fully implanted within the head/neck region of the patient, the microstimulator including a housing to encapsulate at least: stimulation circuitry inside the housing; a rechargeable power element inside the housing; and a control portion inside the housing including a therapy manager to control the stimulation circuitry based on at least control information; a stimulation electrode array; and a flexible lead to be fully implanted within the head/neck region of the patient extending between, and electrically connecting, the stimulation electrode array and the microstimulator, the therapy device being arranged to be implanted in a non-muscle, extravascular location with the stimulation electrode array coupled relative to a nerve to cause contraction of an upper-airway-patency muscle to treat obstructive sleep apnea.
2. The system of claim 1, wherein the therapy device is sized to be fully implantable via a single incision.
3. The system of claim 1, further comprising: a charging device external to the patient and including an external power element, the charging device configured to wirelessly transmit power from the external power element to the rechargeable power element of the microstimulator.
4. The system of claim 3, wherein the charging device comprises a handheld charger.
5. The system of claim 4, wherein the charging device comprises a handheld battery-operated charger.
6. The system of claim 4, wherein the rechargeable power element of the microstimulator comprises a short-term storage capacity corresponding to energy sufficient for one daily treatment period, and wherein the handheld charger is configured to apply a charging protocol to transmit the power to the rechargeable power element of the microstimulator on a periodic basis.
7. The system of claim 3, wherein the charging device comprises at least one antenna to transmit the power, and wherein the rechargeable power element of the microstimulator comprises multiple antennas each oriented in a different direction to reduce alignment sensitivity relative to the at least one antenna of the charging device.
8. The system of claim 7, wherein the charging device comprises multiple antennas including the at least one antenna, each oriented in a different direction to reduce alignment sensitivity relative to the multiple antennas of the rechargeable power element.

9. The system of claim 3, further comprising a patient support external to the patient including the charging device.
10. The system of claim 9, wherein the patient support comprises a bed and/or a headrest structure.
11. The system of claim 3, further comprising at least one external sensor external to the patient to sense physiologic information, wherein the charging device is configured to wirelessly transmit to the microstimulator, via at least coils, the sensed physiologic information from the at least one external sensor.
12. The system of claim 11, wherein the sensed physiologic information comprises respiratory information, and wherein the control information is at least partially based on the respiratory information.
13. The system of claim 3, further comprising an object in the patient's sleep environment including the charging device.
14. The system of claim 13, wherein the object in the patient's sleep environment comprises a garment.
15. A system comprising: a therapy device arranged to be implanted within a head/neck region of a patient, comprising: a microstimulator sized and/or shaped to be fully implanted within the head/neck region of the patient, the microstimulator including a housing to encapsulate at least: stimulation circuitry inside the housing; and a control portion inside the housing including a therapy manager to control the stimulation circuitry based on at least control information; a stimulation electrode array; and a flexible lead to be fully implanted within the head/neck region of the patient extending between, and electrically connecting, the stimulation electrode array and the microstimulator, the therapy device being arranged to be implanted in a non-muscle, extravascular location with the stimulation electrode array coupled relative to a nerve to cause contraction of an upper-airway-patency muscle to treat obstructive sleep apnea.
16. The system of claim 15, further comprising a further electrode mounted on the housing separate from the stimulation electrode array.
17. The system of claim 15, further comprising at least one external sensor comprising at least one of: a pressure sensor; an accelerometer; a piezoelectric sensor; or a non-contact sensor.
18. The system of claim 17, wherein the at least one external sensor comprises: an airway position sensing arrangement; an airflow sensing arrangement; an airflow obstruction sensing arrangement; a sleep disordered breathing (SDB) sensing arrangement to sense at least apneas and hypopneas; a respiratory sensing arrangement; or a body position sensing arrangement.
19. The system of claim 15, wherein the therapy device further comprises at least one internal sensor comprising at least one of: an accelerometer; an acoustic sensor; an EMG sensor; or a piezoelectric sensor.
20. The system of claim 15, further comprising a cuff electrode including the stimulation electrode array.
21. The system of claim 15, wherein the therapy device comprises a mechanical fixation mechanism to secure the housing of the microstimulator within a subcutaneous environment of the patient separate from the stimulation electrode array relative to at least one of: a non-nerve, non-bony structure; or a non-nerve, bony structure.
22. The system of claim 21, wherein the mechanical fixation mechanism comprises at least one of fasteners, tines, or barbs.
23. A system comprising: a therapy device arranged to be implanted within a head/neck region of a patient, comprising: a microstimulator sized and/or shaped to be fully implanted within the head/neck region of the patient, the microstimulator including a housing to encapsulate at least: stimulation circuitry inside the housing; and a control portion inside the housing to control the stimulation circuitry; a stimulation electrode array; and a flexible lead extending between, and electrically connecting, the stimulation electrode array and the microstimulator, the therapy device being arranged to be implanted in a non-muscle, extravascular location with the stimulation

electrode array coupled relative to a nerve to cause contraction of an upper-airway-patency muscle to treat obstructive sleep apnea; at least one external sensor external to the patient to sense physiologic information; and a charging device external to the patient and including coils and an external power element, the charging device configured to wirelessly transmit to the microstimulator and via the same coils: power from the external power element to the microstimulator; and the sensed physiologic information from the at least one external sensor to at least partially control the microstimulator based on the sensed physiologic information.

24. The system of claim 23, wherein the charging device is configured to transmit the sensed physiologic information via inductive communication.

25. The system of claim 23, wherein the microstimulator comprises a rechargeable power element, and wherein the charging device is configured to transmit the power to the rechargeable power element via inductive charging.

26. The system of claim 23, wherein the microstimulator comprises a power element, and wherein the charging device is configured to transmit the power to the power element via radiofrequency charging.

---