

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399373
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Kamakura; Kazuya

Image display device

Abstract

A display element including a light emitting portion of imaging light, an optical system configured to emit imaging light from the display element, a resin-made cover member configured to cover the optical system, and a heat dissipation material attached from the cover member to the display element and configured to conduct heat of the display element to the cover member are included.

Inventors:	Kamakura; Kazuya (Matsumoto, JP)
Applicant:	SEIKO EPSON CORPORATION (Tokyo, JP)
Family ID:	1000008779654
Assignee:	SEIKO EPSON CORPORATION (Tokyo, JP)
Appl. No.:	17/587222
Filed:	January 28, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220244548 A1	Aug. 04, 2022

Foreign Application Priority Data

JP	2021-012680	Jan. 29, 2021
----	-------------	---------------

Publication Classification

Int. Cl.: G02B27/01 (20060101)

U.S. Cl.:

CPC G02B27/0176 (20130101); G02B2027/0178 (20130101)

Field of Classification Search

CPC: G02B (27/01-0189); G02B (2027/0105-0198)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2002/0158813	12/2001	Kiyokawa et al.	N/A	N/A
2008/0186586	12/2007	Yamamoto	N/A	N/A
2015/0177522	12/2014	Yajima	345/8	G09G 3/3208
2016/0179148	12/2015	Takagi et al.	N/A	N/A
2016/0212889	12/2015	Nikkhoo	N/A	H05K 7/20963
2017/0097509	12/2016	Yoshida	N/A	N/A
2017/0227779	12/2016	Kato	N/A	H04N 5/64
2017/0237935	12/2016	Totani et al.	N/A	N/A
2018/0017798	12/2017	Yoshida	N/A	N/A
2018/0373035	12/2017	Yee	N/A	G02B 6/005
2020/0073125	12/2019	Kimura et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
110873965	12/2019	CN	N/A
2001-281593	12/2000	JP	N/A
2004-287190	12/2003	JP	N/A
2006-054618	12/2005	JP	N/A
2016-054468	12/2015	JP	N/A
2016-195313	12/2015	JP	N/A
2017-063322	12/2016	JP	N/A
2018-054979	12/2017	JP	N/A
2015/083316	12/2014	WO	N/A
2019/225759	12/2018	WO	N/A

Primary Examiner: Lamb, II; Christopher A

Attorney, Agent or Firm: Oliff PLC

Background/Summary

(1) The present application is based on, and claims priority from JP Application Serial Number 2021-012680, filed Jan. 29, 2021, the disclosure of which is hereby incorporated by reference herein in its entirety.

BACKGROUND

1. Technical Field

(2) The present disclosure relates to an image display device that enables observation of a virtual image formed by a display element, etc. having a light emitting portion.

2. Related Art

(3) A virtual image display device having a structure in which a metal frame member supporting an optical system and a display element are coupled using a heat dissipating sheet to perform heat dissipation (JP-A-2018-54979). Furthermore, JP-A-2018-54979 also describes, as an aspect, providing a noise reduction sheet that reduces noise generated in the display element (see FIG. 21 of JP-A-2018-54979).

(4) In the device of JP-A-2018-54979, it is disclosed that the noise reducing sheet is disposed between the display element and the heat dissipation sheet so as to reduce spreading of noise generated by the display element through the heat dissipation sheet; in this case, heat transfer from the display element to the heat dissipation sheet is suppressed by the noise reducing sheet, and thus sufficient heat dissipation may not be possible depending on the configuration of the device.

SUMMARY

(5) An image display device according to one aspect of the present disclosure includes a first display element that emits first imaging light, a first optical member that emits the first imaging light from the first display element, a first cover member that covers the first optical member and a first heat dissipation material that extends from the first cover member to the first display element and that conducts heat of the first display element to the first cover member.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is an external perspective view illustrating a wearing state of an image display device according to a first exemplary embodiment.

(2) FIG. 2 is a plan view, front view, side view, and bottom view of the image display device.

(3) FIG. 3 is a front view, side view, perspective view, etc. illustrating an interior of the image display device with an exterior member removed.

(4) FIG. 4 is an exploded perspective view of the remainder of the portion where the exterior member is removed from the image display device.

(5) FIG. 5 is a perspective view illustrating the image display device in which a sheet type heat dissipation material is attached.

(6) FIG. 6 is a plan view and a bottom view of an optical unit at which left and right display units are combined.

(7) FIG. 7 is a perspective view describing a coupling between a first frame and a fixing member, a perspective view describing a positional relationship between the fixing member and a first cover member, and a perspective view describing a positional relationship between the first frame, the fixing member, and the first cover member.

(8) FIG. 8 illustrates a bottom view of an upper exterior member and a plan view of a lower exterior member.

(9) FIG. 9 is a conceptual side cross-sectional view illustrating an optical system inside the image display device.

(10) FIG. 10 is a diagram illustrating distortion correction of a display image.

(11) FIG. 11 is a conceptual side cross-sectional view illustrating an image display device of a second exemplary embodiment.

(12) FIG. 12 is a conceptual drawing for explaining a structure of heat insulation in the image display device.

(13) FIG. 13 is a conceptual side cross-sectional view illustrating an image display device of one modified example.

DESCRIPTION OF EXEMPLARY EMBODIMENTS

First Exemplary Embodiment

(14) Hereinafter, a structure, operation, etc. of an image display device according to the present

disclosure will be described with reference to FIGS. 1 to 3, etc.

(15) FIG. 1 is a diagram illustrating a wearing state of an image display device **200**. The image display device **200** is a head-mounted display (hereinafter, also referred to as HMD) **201**, and causes an observer or a wearer US who wears the head-mounted display **201** to recognize an image as a virtual image. In FIG. 1, etc., X, Y, and Z correspond to an orthogonal coordinate system, a +X direction corresponds to a lateral direction in which the two eyes EY of the observer or wearer US who is wearing the image display device **200** or HMD **201** are arranged, a +Y direction corresponds to an upward direction orthogonal to the lateral direction in which the two eyes EY of the wearer US are arranged, and a +Z direction corresponds to a direction to the front or a forward direction for the wearer US. A $\pm Y$ direction is parallel to a vertical axis or a vertical direction.

(16) The image display device **200** includes a main body **200a** disposed to cover the front of the wearer US and a pair of temple support devices **200b** that support the main body **200a**. The main body **200a**, when functionally viewed, includes a first display device **100A** for the right eye and a second display device **100B** for the left eye. The first display device **100A** includes a display driving unit **102** disposed at an upper portion thereof, and a combiner **103a** that is shaped like a spectacle lens and covers the front of the eye. Similarly, the second display device **100B** includes a display driving unit **102** disposed at an upper portion thereof, and a combiner **103b** that is shaped like a spectacle lens and covers the front of the eye.

(17) The appearance of the main body **200a** of the image display device **200** will be described with reference to FIG. 2. In FIG. 2, a region AR1 is a plan view of the main body **200a**, a region AR2 is a front view of the main body **200a**, a region AR3 is a side view of the main body **200a**, and a region AR4 is a bottom view of the main body **200a**. A pair of the display driving units **102** disposed on the +Y side or the upper side of the main body **200a** are coupled and integrated, and are covered by a dome-shaped upper exterior member **107a** elongated in the lateral direction and a flat plate-shaped lower exterior member **107b**. The first combiner **103a** and the second combiner **103b** have a shape such that an upper portion of a hemisphere protruding in the forward or the +Z direction is cut, and is disposed so as to protrude downward from the lower exterior member **107b**.

(18) With reference to FIG. 3, an overview of an internal structure in which the upper exterior member **107a** and the lower exterior member **107b** have been removed from the main body **200a** illustrated in FIG. 2 will be described. In FIG. 3, a region BR1 is a front view with an upper portion of the main body **200a** exposed, a region BR2 is a side view with the upper portion of the main body **200a** exposed, a region BR3 is a perspective view with the upper portion of the main body **200a** exposed, and a region BR4 is a perspective view with an internal optical system of the main body **200a** exposed. The first display device **100A** for the right eye includes a first display element **11a**, a first optical system **12a**, and the first combiner **103a**, as the first display unit **100a**. The first optical system **12a** is covered with a resin-made first cover member **71a**, which is an inner cover. The first display element **11a** is disposed so as to close an opening **710** of the first cover member **71a**, and is fixed to an outer frame of the first optical system **12a** via a first holder **72a** having a rectangular frame shape. Note that the first display element **11a** is, for example, a spontaneous light emission type display device, and includes a light emitting portion to generate first imaging light as imaging light. The first optical system **12a** emits the imaging light (first imaging light) from the first display element **11a**. In other words, the first display unit **100a** includes the first display element **11a**, and performs image display by the first imaging light.

(19) As illustrated in FIG. 4, the first optical system **12a** is fixed to an upper surface of the plate-shaped first frame **61a** by adhesion, etc., and the first combiner **103a** is fixed to the front half of the periphery of the first frame **61a** by adhesion, etc. at an upper end thereof. In other words, the first optical system **12a** and the first combiner **103a** are supported by the first frame **61a**. Note that the first frame **61a** is a semi-circular plate-shaped metal member, and is formed, for example, from a magnesium alloy.

(20) Referring back to FIG. 3, the second display device **100B** includes a second display element

11b, a second optical system **12b**, and the second combiner **103b**, as the second display unit **100b**. The second optical system **12b** is covered with a resin-made second cover member **71b**, which is an inner cover. The second display element **11b** is disposed so as to close the opening **71o** of the second cover member **71b**, and is fixed to an outer frame of the second optical system **12b** via the second holder **72b** having a rectangular frame shape. The second display device **100B** for the left eye has the same structure and function as the first display device **100A** for the right eye. In other words, the second display element **11b** is the same as the first display element **11a**, the second optical system **12b** is the same as the first optical system **12a**, and the second combiner **103b** is the same as the first combiner **103a**. Thus, for example, the second display element **11b** includes a light emitting portion to generate second imaging light as imaging light, and the second optical system **12b** emits the second imaging light from the second display element **11b**. The second display unit **100b** includes the second display element **11b**, and performs image display by the second imaging light. However, in a case where the first optical system **12a**, the first combiner **103a**, etc. have asymmetry with respect to the left and right X direction, the second optical system **12b**, the second combiner **103b**, etc. are obtained by laterally inverting the first optical system **12a**, the first combiner **103a**, etc.

(21) As illustrated in FIG. 4, the second optical system **12b** is fixed to an upper surface of the plate-shaped second frame **61b** by adhesion, etc., and the second combiner **103b** is fixed to the front half of the periphery of the second frame **61b** by adhesion, etc. at an upper end thereof. In other words, the second optical system **12b** and the second combiner **103b** are supported by the second frame **61b**. Note that the second frame **61b** is a semi-circular plate-shaped metal member, and is formed, for example, from a magnesium alloy.

(22) Referring back to FIG. 3, the first display device **100A** and the second display device **100B** are coupled via a fixing member **78** therein. The fixing member **78** is a rod-shaped metal member, and is formed from, for example, a magnesium alloy. By forming the fixing member **78** from the magnesium alloy, the first frame **61a** and the second frame **61b** can be cooled by heat dissipation. The fixing member **78** fixes the first display unit **100a** and the second display unit **100b** relative to each other at both ends thereof. The fixing member **78** is a member corresponding to an arm of a balance, and supports a pair of the display units **100a**, **100b** corresponding to a pair of plates in the center. The fixing member **78** has a shape that allows the first optical system **12a** and the second optical system **12b** to rotate in rotational directions around two or more axes when the first display unit **100a** and the second display unit **100b** are aligned prior to fixing.

(23) Here, as illustrated in the perspective view illustrated in FIG. 5, in the image display device **200** according to the present exemplary embodiment, a first sheet type heat dissipation material **SDa** and a second sheet type heat dissipation material **SDb** are attached to the first display element **11a** and the second display element **11b**. For example, the first sheet type heat dissipation material **SDa** is a heat conduction member that is attached from the resin-made first cover member **71a** to the first display element **11a** to conduct the heat of the first display element **11a** to the first cover member **71a**. Similarly, the second sheet type heat dissipation material **SDb** is a heat conduction member that conducts the heat of the second display element **11b** to the resin-made second cover member **71b**.

(24) Each of the sheet type heat dissipation materials **SDa**, **SDb** is a thermally conductive tape constituted by a graphite sheet having an adhesive surface, and is directly attached to the first display element **11a**, etc. to perform heat conduction. In other words, in the above-described aspect, sufficient heat dissipation is ensured by conducting the heat generated by the display elements **11a**, **11b** to the cover members **71a**, **71b** by the sheet type heat dissipation materials **SDa**, **SDb**.

(25) Here, in the first display element **11a** and the second display element **11b**, the generated noise is a problem. Specifically, electromagnetic waves are generated by weak electrical power, etc. in the circuit board of the organic EL panel constituting the first display element **11a**, etc., and this may be noise and transmitted to the other member, which may cause an influence, etc. In order to

avoid or suppress such a situation, in the above-described example, as the cover members **71a**, **71b**, which are heat dissipation destinations, cover members made of resin having low conductivity are adopted. In other words, in the case described above, by interposing a material having low conductivity during heat conduction by the sheet type heat dissipation materials **SDa**, **SDb**, the conduction of noise generated in the first display element **11a** and the second display element **11b** is avoided or suppressed.

(26) Further, the first sheet type heat dissipation material **SDa** and the second sheet type heat dissipation material **SDb** are separated from the first frame **61a** and the second frame **61b**, which are metal frames that support the first optical system **12a** and the second optical system **12b**. This prevents noise generated by the first display element **11a**, etc. from being conducted to the first frame **61a**, etc. via the first sheet type heat dissipation material **SDa**, etc.

(27) Additionally, the first sheet type heat dissipation material **SDa** and the second sheet type heat dissipation material **SDb** are provided so as not to overlap with each other. In other words, the graphite sheets do not overlap with each other. This suppresses transmission of one noise to the other.

(28) Furthermore, in the illustrated example, a first cover member heat dissipation material **CDa** and a second cover member heat dissipation material **CDb** are attached to the first cover member **71a** and the second cover member **71b**. Each of the cover member heat dissipation materials **CDa**, **CDb** is a thermally conductive tape constituted by a graphite sheet having an adhesive surface, and is a heat conduction member that conducts heat conduction by being directly attached to the first cover member **71a**, etc. In one example illustrated in the drawings, the cover member heat dissipation materials **CDa**, **CDb** are attached to outer surfaces of the cover members **71a**, **71b**, and are provided along the first optical system **12a** and the second optical system **12b** accommodated within the cover members **71a**, **71b**. The heat dissipation due to heat conduction with the cover member heat dissipation materials **CDa**, **CDb** can reduce the increase in temperature inside the cover members **71a**, **71b**. In other words, degradation of image distortion, etc. caused by changes in the temperature of the first optical system **12a** and the second optical system **12b** can be avoided or suppressed.

(29) Also here, the graphite sheets do not overlap with each other. That is, the first cover member heat dissipation material **CDa** and the second cover member heat dissipation material **CDb** are provided so as not to overlap with each other, and these are provided so as not to overlap with the first sheet type heat dissipation material **SDa** and the second sheet type heat dissipation material **SDb**.

(30) The support of the first display unit **100a** and the second display unit **100b** by the fixing member **78** will be described with reference to FIGS. **4**, **6** and **7**. In FIG. **6**, a region **CR1** is a plan view of an optical unit **OU** coupled to the left and right display units **100a**, **100b**, and a region **CR2** is a bottom view of the optical unit **OU**. In FIG. **7**, a region **DR1** is a perspective view describing a coupling between the first display unit **100a** and the fixing member **78**, a region **DR2** is a perspective view describing a positional relationship between the fixing member **78** and the first cover member **71a**, and a region **DR3** is a perspective view describing a positional relationship between the first display unit **100a**, the fixing member **78**, and the first cover member **71a**. Fixing portions **81a**, **82a**, which are spherical members similar to those of the ball joint components, are formed at both ends of the fixing member **78**. After the first display unit **100a** and the second display unit **100b** are aligned, these fixing portions **81a**, **82a** are adhered to concave portions **81b**, **82b**, which are hemispherical indentation members provided at the inner ends of the display units **100a**, **100b** or the frame **61a**, **61b** by an adhesive material, etc., whereby the rotation is stopped. A coupling member **81** that combines the fixing portion **81a** and the concave portion **81b** is covered by an extending portion **71c** of the first cover member **71a**. A coupling member **82** that combines the fixing portion **82a** and the concave portion **82b** is also covered by an extending portion **71c** of the second cover member **71b**.

(31) As described above, the first frame **61a** is a semi-circular plate-shaped metal member, and is formed, for example, from a magnesium alloy. By forming the first frame **61a** from the magnesium alloy, heat dissipation efficiency of heat generated by the display element **11a**, etc. can be increased. The concave portions **81b** are formed at both the left and right ends of the first frame **61a**, but only one of the concave portions **81b** is used for coupling with the fixing member **78**. An optical aperture OA is formed at the first frame **61a**, and a plate-shaped optical element **28** that seals the optical aperture OA is disposed. The plate-shaped optical element **28** is part of the first optical system **12a**. As described above, the second frame **61b** is a semi-circular metal member, and is formed, for example, from a magnesium alloy. By forming the second frame **61b** from the magnesium alloy, heat dissipation efficiency of heat generated by the display element **11b**, etc. can be increased. The concave portions **82b** are formed at both the left and right ends of the second frame **61b**, but only one of the concave portions **82b** is used for coupling with the fixing member **78**. An optical aperture OA is also formed at the second frame **61b**, and a plate-shaped optical element **28** that seals the optical aperture OA is disposed.

(32) The upper exterior member **107a** and the lower exterior member **107b** will be described with reference to FIG. 8. In FIG. 8, a region ER1 is a bottom view illustrating the inside of the upper exterior member **107a**, and a region ER2 is a plan view illustrating the inside of the lower exterior member **107b**. The upper exterior member **107a** and the lower exterior member **107b** are formed from a resin material. An outer edge **7a** of the upper exterior member **107a** and an outer edge **7b** of the lower exterior member **107b** have the same shape. By abutting them, a space for accommodating the first optical system **12a** and the second optical system **12b** illustrated in FIG. 3 can be formed. The upper exterior member **107a** and the lower exterior member **107b** are fixed using fastening portions **7f**, **7g**, which are screw holes, etc. The lower exterior member **107b** has a pair of openings OP1, and the first frame **61a** and the second frame **61b** can be disposed at the openings OP1, as indicated by a dotted lines. Gaps GP are provided between the openings OP1 and the frames **61a**, **61b**, and allows the frames **61a**, **61b** to shift in position with respect to the X-Y plane or the Y direction within the openings OP1. That is, the first display unit **100a** and the second display unit **100b** illustrated in FIG. 3, etc. are fixed to the lower exterior member **107b** while remaining aligned with each other, and even in a state of being accommodated in the upper exterior member **107a** and the lower exterior member **107b**, the positional relationship between the display units **100a**, **100b** upon completion of positioning is maintained. Screwing hole **7j** are formed at the lower exterior member **107b** and can be fixed by screwing to a pair of fastening portions **78z** (See FIGS. 6 and 7) provided at a bridge **78a** of the fixing member **78**.

(33) Referring to FIGS. 3 and 4, an elastic sheet **75** is disposed above the first frame **61a** and the second frame **61b**. An outer circumferential portion **75a** of the elastic sheet **75** is sandwiched between the outer edge **7a** of the upper exterior member **107a** illustrated in FIG. 8 and the outer edge **7b** of the lower exterior member **107b** to allow hermetic or liquid-tight sealing between the outer exterior members **107a**, **107b**. A pair of openings OP21 and OP22 are formed at the elastic sheet **75**. An inner circumferential portion **75b** around one opening OP21 is sandwiched between the upper surface of the first frame **61a** and the lower end of the first cover member **71a**, to allow hermetic or liquid-tight sealing between the first frame **61a** and the first cover member **71a**. An inner circumferential portion **75c** around the other opening OP22 is sandwiched between the upper surface of the second frame **61b** and the lower end of the second cover member **71b**, to allow hermetic or liquid-tight sealing between the second frame **61b** and the second cover member **71b**.

(34) With reference to FIG. 3, a rectangular plate-shaped circuit board **91** is disposed above the fixing member **78** between the left and right display units **100a**, **100b**. The circuit board **91** includes a control device **92** that controls display operation of the first display element **11a** and the second display element **11b**. The control device **92** outputs a drive signal corresponding to the display image to the left and right display elements **11a**, **11b** to control the display operation of the left and right display elements **11a**, **11b**. The control device **92** includes, for example, an IF circuit, a signal

processing circuit, etc., and causes the left and right display elements **11a**, **11b** to display a two-dimensional image according to the image data or the image signal received from the outside. Although not shown, the control device **92** includes a main board that controls the operation of the first display device **100A** and the operation of the second display device **100B**. The main substrate may have, for example, an interface function that communicates with an external device (not shown) and performs signal conversion on a signal received from the external device, and an integrated function that links between the display operation of the first display device **100A** and the display operation of the second display device **100B**.

(35) The circuit board **91** is supported on the fixing member **78** by a substrate support portion **74**. The circuit board **91** is fixed at the substrate support portion **74**. The substrate support portion **74** is a member made of resin covering the fixing member **78** from the upper, front, and rear, and is detachable from the fixing member **78** together with the circuit board **91** by a snap fit using a fitting portion **51**.

(36) FIG. **9** is a side cross-sectional view illustrating an optical structure of the first display unit **100a**. The first display unit **100a** includes the first display element **11a** and an imaging optical system **20**. The imaging optical system **20** is also referred to as a light guide optical device. The imaging optical system **20** includes a projection lens **21**, a prism mirror **22**, the plate-shaped optical element **28**, and a see-through mirror **23**. The projection lens **21**, the prism mirror **22**, and the plate-shaped optical element **28** of the imaging optical system **20** correspond to the first optical system **12a** illustrated in FIG. **3**, etc., and the see-through mirror **23** corresponds to the first combiner **103a**. The first display element **11a**, the projection lens **21**, and the prism mirror **22** are fixed to the first frame **61a** in a state of being aligned with each other by a frame body (not illustrated), and is accommodated in a space **SP1** sandwiched between the first cover member **71a** and the first frame **61a**. The plate-shaped optical element **28** is disposed so as to be fitted into a step formed at the optical aperture **OA** of the first frame **61a**, and the periphery of the optical aperture **OA** is kept airtight state.

(37) As described above, the first display element **11a** is a spontaneous light emission type display device having a light emitting portion. The first display element **11a** is, for example, an organic EL (Organic Electro-luminescence) display, and forms a color still image or moving image on a two-dimensional display surface **11d**. The first display element **11a** is disposed along an x-y plane that is inclined by being slightly rotated about the X axis with respect to an X-Y plane. The first display element **11a** is driven by the control device **92** provided at the circuit board **91** to perform display operation. The first display element **11a** is not limited to the organic EL display, and can be replaced with a micro LED display or a display device using an inorganic EL, an organic LED, a laser array, a quantum dot light emitting element, etc. The first display element **11a** is not limited to a spontaneous light emission type imaging light generation device, and may include an LCD and another light modulation element, and may form an image by illuminating the light modulation element with a light source (light emitting portion) such as a backlight. As the first display element **11a**, a LCOS (Liquid crystal on silicon, LCoS is a registered trademark), a digital micro-mirror device, etc. may be used instead of an LCD.

(38) The projection lens **21** causes the imaging light (first imaging light) **ML** emitted from the first display element **11a** to pass therethrough and then to be incident on the prism mirror **22**. The projection lens **21** focuses the imaging light **ML** emitted from the first display element **11a** into a state close to a parallel luminous flux. The projection lens **21** includes a first lens **21p** and a second lens **21q**. The prism mirror **22** has an inner reflection surface **22b**, and causes the imaging light **ML** emitted from the projection lens **21** to be incident on a light incident surface **22a**, to be totally reflected by the inner reflection surface **22b**, and to be emitted from a light emission surface **22c**. At this time, the prism mirror **22** emits the imaging light **ML** incident from the front such that it is bent in a direction inclined with respect to a direction in which an incident direction is reversed (a direction of the light source seen from the prism mirror **22**). The plate-shaped optical element **28**

causes the imaging light ML from the prism mirror **22** to pass therethrough while being refracted, and the see-through mirror **23** reflects the image light ML emitted from the prism mirror **22** toward a pupil position PP. The pupil position PP is a position at which the imaging light ML from each of points on the display surface **11d** is incident so as to be overlapped from an angular direction corresponding to a position of each of points on the display surface **11d** in a predetermined divergent state or a parallel state.

(39) The see-through mirror **23** is a curved plate-shaped optical member that serves as a concave surface mirror, and reflects the imaging light ML incident from the prism mirror **22** via the plate-shaped optical element **28** toward a pupil position PP. The see-through mirror **23** covers the pupil position PP at which the eye EY or the pupil is disposed, has a concave shape toward the pupil position PP, and has a convex shape toward the outside. The see-through mirror **23** is a mirror plate having a structure in which a mirror film **23c** is formed at a front surface or a back surface of a plate-shaped body **23b**. The reflection surface **23a** of the see-through mirror **23** has transmissive properties. The external light OL that has passed through the see-through mirror **23** and a support plate **41** therearound is also incident on the pupil position PP. In other words, the wearer US wearing the image display device **200** can observe a virtual image of the imaging light ML in a state in which the imaging light ML overlaps with the external image.

(40) In the above, optical surfaces constituting the projection lens **21**, the prism mirror **22**, the plate-shaped optical element **28**, and the see-through mirror **23** includes a free-form surface, and at least some of the optical surfaces may be replaced with an aspheric surface or a spherical surface.

(41) The imaging optical system **20** is an off-axis optical system OS due to the see-through mirror **23** being a concave mirror, etc. In the case of the present exemplary embodiment, the projection lens **21**, the prism mirror **22**, the plate-shaped optical element **28**, and the see-through mirror **23** are disposed non-axisymmetric and have a non-axisymmetric optical surface. In the imaging optical system **20**, that is, the off-axis optical system OS, an optical axis AX is bent so that the optical axis AX extends along an off-axis surface (a surface parallel to the Y-Z surface) corresponding to a plane of the drawing. In the imaging optical system **20**, the optical elements **21**, **22**, and **23** are arranged along the off-axis surface by bending the optical axis AX in the off-axis plane parallel to the Y-Z plane. The imaging optical system **20** includes optical axis portions AX1, AX2, and AX3 that are disposed along the off-axis surface (a surface parallel to the Y-Z plane) which is a reference surface extending in the longitudinal direction and are inclined with respect to each other before and after the reflection surface. The optical axis AX as a whole extends along an optical path of the main rays emitted from the center of the display element **11a** and passes through the center of the eye ring ER or the pupil corresponding to an eye point. The optical axis AX is disposed in a Z shape by the plurality of optical axis portions AX1, AX2, and AX3 when seen in a transverse cross section parallel to the Y-Z plane. In other words, in the off-axis surface parallel to the Y-Z plane, an optical path P1 from the projection lens **21** to an inner reflection surface **22b**, an optical path P2 from the inner reflection surface **22b** to the see-through mirror **23**, and an optical path P3 from the see-through mirror **23** to the pupil position PP are arranged to be bent in a Z shape in two stages.

(42) As illustrated in FIG. 10, the display image formed at the display surface **11d** of the first display element **11a** is set to a modified image DA1 having a distortion such as trapezoidal distortion. That is, since the imaging optical system **20** is the off-axis optical system OS, it is not easy for the optical system itself to remove distortion such as trapezoidal distortion. In this way, a pixel array of a projected image IG1 of the virtual image observed at the pupil position PP via the imaging optical system **20** can be made into a grid pattern corresponding to an original display image DA0, and the outline thereof can be made rectangular by causing the image displayed on the first display element **11a** to have reverse distortion that cancels out the distortion formed by the projection lens **21**, the prism mirror **22**, the plate-shaped optical element **28**, and the see-through mirror **23**. In other words, the first display element **11a** corrects the distortion formed by the projection lens **21**, the prism mirror **22**, the plate-shaped optical element **28**, and the see-through

mirror **23**. As a result, aberrations can be suppressed as a whole including the first display element **11a** while allowing the distortion generated by the see-through mirror **23**, etc. Thus, the degree of freedom in the arrangement and size of optical elements such as the prism mirror **22** is increased, and it is possible to easily secure the optical performance of the first display unit **100a** while achieving miniaturization of the first display unit **100a**.

(43) Although the first display unit **100a** has been described above, the second display unit **100b** has a similar structure to that of the first display unit **100a**, and similarly guides the image light (second image light) to form a virtual image. Therefore, a description of the specific structure thereof will be omitted.

(44) As described above, the image display device **200** according to the present exemplary embodiment includes the display elements **11a**, **11b** including the light emitting portion of the imaging light ML, the optical systems **12a**, **12b** configured to emit the imaging light ML from the display elements **11a**, **11b**, the resin-made cover members **71a**, **71b** configured to cover the optical systems **12a**, **12b**, the sheet type heat dissipation materials SDa, SDb attached from the cover members **71a**, **71b** to the display elements **11a**, **11b**, and configured to conduct the heat of the display elements **11a**, **11b** to the cover members **71a**, **71b**. In this case, in the image display device **200**, sufficient heat dissipation is ensured by conducting the heat generated by the display elements **11a**, **11b** to the cover members **71a**, **71b** by the sheet type heat dissipation materials SDa, SDb. In addition, by adopting the resin-made cover members **71a**, **71b** as heat dissipation destinations, the conduction of noise generated by the display elements **11a**, **11b** is suppressed. In other words, in the image display device **200**, the conduction of noise generated by the display elements **11a**, **11b** is suppressed by interposing a material having low conductivity during heat conduction.

Second Exemplary Embodiment

(45) Hereinafter, an image display device according to a second exemplary embodiment will be described with reference to FIG. **11**, etc. Note that the image display device according to the present exemplary embodiment is a partial modification of the image display device of the first exemplary embodiment, and is the same for other configurations except for the structure related to heat dissipation. Therefore, for those having the same reference numerals as other drawings for the overall configuration, detailed illustrations and explanations shall be omitted, and the matters explained with reference to other drawings shall be incorporated as necessary.

(46) FIG. **11** is a conceptual side cross-sectional view illustrating the image display device **200** of the present exemplary embodiment, corresponding to FIG. **9**. Here, of the left-right symmetric first display unit **100a** and the second display unit **100b** constituting the image display device **200**, the first display unit **100a** will be described as representative.

(47) In the present exemplary embodiment, a concave portion RE is provided in the vicinity of the first display element **11a** of the first frame **61a**, which is a metal frame that supports the first optical system **12a**. As illustrated, the concave portion RE is a concave portion formed at the first frame **61a** having a flat plate shape, into which a portion of the first display element **11a** is inserted. In other words, the concave portion RE forms a space that functions as an adjustment margin for assembling and adjusting the first display element **11a**, for example.

(48) In the present exemplary embodiment, after the assembly adjustment of the first display element **11a** is performed, the concave portion RE of the first frame **61a** is filled with a grease, and thus a grease-like heat dissipation material GDa is provided. The grease-like heat dissipation material GDa is formed from the first display element **11a** to the first frame **61a**, and conduct the heat generated by the first display element **11a** to the first frame **61a**. In other words, the image display device **200** includes the grease-like heat dissipation material GDa as a heat conduction member filled into the concave portion RE of the first frame **61a** and conducting heat of the first display element **11a** to the first frame **61a**.

(49) As described above, the first frame **61a** functions as a heat dissipating body that dissipates the heat of the first display element **11a**. In other words, in addition to being formed of a magnesium

alloy and being in close proximity to the first display element **11a**, in the above-described exemplary embodiment, the grease-like heat dissipation material GDa is filled and coupled therebetween, thereby the first frame **61a** has further improved heat dissipation efficiency of the heat generated by the display element **11a**, etc.

(50) Here, the grease-like heat dissipation material GDa is constituted by substances (insulators) having low electrical conductivity, and in the heat conduction, the conduction of noise generated by the first display element **11a** to the first frame **61a** is suppressed.

(51) Furthermore, in the case of the above-described configuration, as conceptually illustrated in FIG. **12**, the elastic sheet **75** functions as a heat insulating member provided between the first frame **61a** as a heat dissipation material and the first optical system **12a**. In other words, in the case of the above-described configuration, the elastic sheet **75** is in a state of being interposed between the first frame **61a** and the first optical system **12a**, so that the elastic sheet **75** can block or suppress the heat transferred to the first frame **61a** via the grease-like heat dissipation material GDa from flowing toward the first optical system **12a**, the electronic circuit for image formation (not illustrated), etc. It is also conceivable to deform the shape of the elastic sheet **75** in various ways so as to further demonstrate the effects described above.

(52) Although the first display unit **100a** has been described above, the second display unit **100b** has a similar structure to that of the first display unit **100a**, and thus a description of the specific structure thereof will be omitted. In other words, similar grease-like heat dissipation material GDb can also be provided at the second display unit **100b**.

(53) Note that, in the exemplary embodiment described above, instead of the sheet type heat dissipation material SDa, etc. of the first exemplary embodiment described with reference to FIG. **5**, the present disclosure is configured to employ the grease-like heat dissipation material GDa, etc.; as illustrated in FIG. **13** corresponding to FIG. **11**, in addition to the grease-like heat dissipation material GDa, a configuration is possible in which the cover member heat dissipation material SDa and the cover member heat dissipation material CDa are provided.

(54) As described above, the image display device **200** according to the present exemplary embodiment includes the display elements **11a**, **11b** including the light emitting portion of the imaging light ML, the optical systems **12a**, **12b** configured to emit the imaging light ML from the display elements **11a**, **11b**, the metal frames **61a**, **61b** including the concave portion RE into which portions of the display elements **11a**, **11b** are inserted, the metal frames **61a**, **61b** being configured to support the optical systems **12a**, **12b**, and the grease-like heat dissipation materials GDa, GDb filled into the concave portion RE of the frames **61a**, **61b** and configured to conduct the heat of the display elements **11a**, **11b** to the frames **61a**, **61b**. In this case, in the image display device **200**, sufficient heat dissipation is ensured by conducting the heat of the display elements **11a**, **11b** to the frames **61a**, **61b** by the grease-like heat dissipation materials GDa, GDb. In addition, by adopting the grease-like member as the heat conduction medium, the conduction of noise generated by the display elements **11a**, **11b** is suppressed. In other words, in the image display device **200**, the conduction of noise generated by the display elements **11a**, **11b** is suppressed by interposing a material having low conductivity during heat conduction.

MODIFIED EXAMPLES AND OTHERS

(55) The present disclosure is described according to each of the above-described embodiments, but the present exemplary disclosure is not limited to the above-described embodiments. The present exemplary disclosure may be carried out in various modes without departing from the gist of the present disclosure, and, for example, the following modifications may be carried out.

(56) The imaging optical system **20** incorporated into the first display unit **100a** is not limited to that illustrated, and may have various configurations. Specifically, the imaging optical system **20** described above is the off-axis optical system OS that is asymmetric in the Y direction or the longitudinal direction, but may also be an off-axis optical system that is asymmetric in the X direction or the lateral direction. The optical elements constituting the imaging optical system **20**

are merely exemplary in FIG. 9, and changes can be made, such as increasing or decreasing the number of lenses, adding a light-guiding member, etc.

(57) A light control device that controls light by limiting the transmitted light of the combiners **103a**, **103b** can be attached on an external side of the combiners **103a**, **103b**. The light control device adjusts a transmittance, for example, electrically. Mirror liquid crystals, electronic shades, etc. may be used as the light control device. The light control device may adjust a transmittance according to outside light brightness.

(58) The combiner **103a**, **103b** may be replaced with a mirror having light blocking properties. In this case, the optical system is a non-see-through type optical system that does not assume direct observation of an external image.

(59) The first frame **61a**, the second frame **61b**, and the fixing member **78** are not limited to being formed from a metal material, and may be formed from fiber-reinforced plastic (FRP).

(60) The structure of the coupling members **81**, **82** is not limited to one having a ball joint shape, and can be replaced with various mechanisms having increased rotational degrees of freedom along two or more axes.

(61) In the description above, although it was assumed that the image display device **200** was worn on the head and is used, the image display device **200** may also be used as a handheld display that is not worn on the head and is to be looked into like binoculars. In other words, the head-mounted display also includes a hand-held display in the present disclosure.

(62) In the above-described aspect, the heat dissipation material SDa, etc. may be disposed between the left and right display units **100a**, **100b**, and may be configured to suppress the conduction of noise generated by the display elements **11a**, **11b** to the circuit board **91** that controls the display operation.

(63) In the above, the light is guided in the vertical direction or the Y direction, but a configuration in which the light is guided in the horizontal direction or the X direction is also possible.

(64) Note that, the image display device **200** for both eyes is used in the above description, but for the image display device **200**, one of the portions for the right eye and the portion for the left eye can be omitted. In this case, it becomes a monocular head-mounted display.

(65) Further, in the above-described aspect, it is also conceivable to extend the first sheet type heat dissipation material SDa attached to the display element **11a**, the first cover member heat dissipation material CDa attached to the first cover member **71a**, etc., to the upper exterior member **107a** and the lower exterior member **107b** made of a resin material, to conduct heat to the upper exterior member **107a** and the lower exterior member **107b**.

(66) In addition, in the example of FIG. 5, the first sheet type heat dissipation material SDa and the second sheet type heat dissipation material SDb are extended and attached in both left and right directions (the +X direction and the -X direction) from the first display element **11a** and the second display element **11b**, however, it is also conceivable to extend them in either direction. Note that by extending in the left-right direction and opening in the upper direction (+Y direction), the FPC (flexible printed circuit) of the first display element **11a** and the second display element **11b**, which are not illustrated, can be extended in this direction to avoid interference from the first sheet type heat dissipation material SDa, etc.

(67) In the above, the cover member heat dissipation materials CDa, CDb do not overlap with the sheet type heat dissipation materials SDa, SDb. However, if the occurrence of noise, for example, can be suppressed, the first sheet type heat dissipation material SDa and the cover member heat dissipation material CDa may be joined together to accelerate the time of heat transfer (increase the performance of heat conduction).

(68) A first image display device according to a specific aspect includes a display element including a light emitting portion of imaging light, an optical system configured to emit imaging light from the display element, a resin-made cover member configured to cover the optical system, and a sheet type heat dissipation material attached from the cover member to the display element

and configured to conduct heat of the display element to the cover member.

(69) In the above-described image display device, sufficient heat dissipation is ensured by conducting the heat of the display element to the cover member by the sheet type heat dissipation material. In addition, a resin is used as the cover member that is the heat dissipation destination, that is, a material having low electrical conductivity is interposed during heat conduction, whereby, conduction of noise generated by the display element is suppressed.

(70) In a specific aspect, the display element includes a first display element configured to generate first imaging light as imaging light, and a second display element configured to generate second imaging light as imaging light, wherein the sheet type heat dissipation material includes a first sheet type heat dissipation material configured to conduct heat of the first display element, and a second sheet type heat dissipation material configured to conduct heat of the second display element. In this case, the first imaging light and the second imaging light allow for binocular vision image formation.

(71) In a specific aspect, a first display unit including a first display element and configured to display an image by first imaging light, a second display unit including a second display element and configured to display an image by second imaging light, and a fixing member configured to fix the first display unit and the second display unit relative to each other are included, wherein the fixing member has a shape configured to rotate the first optical system and the second optical system in rotational directions around two or more axes when the first display unit and the second display unit are aligned prior to fixing. In this case, the fixing member has a shape configured to rotate the first optical system and the second optical system in rotational directions around two or more axes, thus, prior to fixing, the first display unit and the second display unit can be disposed and aligned at a high degree of freedom with respect to the fixing member. Note that after alignment, the first display unit and the second display unit are fixed to the fixing member using an adhesive material or a fastener, so that these relative positional relationships can be stably maintained.

(72) In a specific aspect, a metal frame configured to support the optical system is included, wherein the sheet type heat dissipation material is separated from the frame. In this case, conduction of noise generated by the display element to the frame via the sheet type heat dissipation material can be avoided.

(73) In a specific aspect, the frame includes a concave portion into which a portion of the display element is inserted. In this case, the position of the display element can be adjusted.

(74) In a specific aspect, a grease-like heat dissipation material filled into the concave portion of the frame and configured to conduct the heat of the display element to the frame is included. In this case, heat conduction by the grease-like heat dissipation material is possible.

(75) In a specific aspect, the cover member includes a cover member heat dissipation material provided along the optical system on the outer surface of the cover member, the cover member heat dissipation material being configured to accommodate the optical system therein and conduct heat of the cover member. In this case, the cover member heat dissipation material avoids or suppresses the increase in the temperature of the optical system contained inside the cover member, whereby distortion, etc. of the image are suppressed.

(76) In a specific aspect, the sheet type heat dissipation material is a graphite sheet. In this case, high efficiency heat conduction is possible.

(77) A second image display device according to a specific aspect includes a display element including a light emitting portion of imaging light, an optical system configured to emit imaging light from the display element, a metal frame including a concave portion into which a portion of the display element is inserted, the metal frame being configured to support the optical system, and a grease-like heat dissipation material filled into the concave portion of the frame and configured to conduct heat of the display element to the frame.

(78) In the above-described image display device, sufficient heat dissipation is ensured by

conducting the heat of the display element to the frame by the grease-like heat dissipation material. In addition, a grease-like member is used as the heat conduction medium, that is, a material having low electrical conductivity is interposed during heat conduction, whereby, conduction of noise generated by the display element is suppressed.

(79) In a specific aspect, an insulating member is provided between the frame and the optical system. In this case, it is possible to block or suppress the heat conducted to the frame from flowing toward the optical system by the heat insulating member.

Claims

1. An image display device comprising: a first display that emits a first imaging light; a first optical member that emits the first imaging light from the first display; a first cover that defines an inner space in which the first optical member is disposed, and covers the first optical member over at least two sides thereof; a combiner configured to direct the first imaging light from the first optical member towards a user; and a first heat dissipation material that is directly attached to the first display, and that extends from the first cover to the first display and that conducts heat of the first display to the first cover, wherein the first cover is directly attached to the first heat dissipation material, but does not cover the first heat dissipation material.
2. The image display device according to claim 1, further comprising: a second display that emits a second imaging light; a second optical member that emits the second imaging light from the second display; a second cover that covers the second optical member; and a second heat dissipation material that extends from the second cover to the second display and that conducts heat of the second display to the second cover.
3. The image display device according to claim 2, further comprising a fixing member that fixes the first display and the second display to each other, wherein the fixing member has a shape that rotates the first display and the second display in rotational directions around two or more axes.
4. The image display device according to claim 1, further comprising a frame that supports the first optical member, wherein the first heat dissipation material is separated from the frame.
5. The image display device according to claim 4, wherein the frame includes a concave portion into which a portion of the first display is inserted.
6. The image display device according to claim 5, further comprising a heat dissipation material that is filled into the concave portion of the frame, and that conducts heat of the first display to the frame.
7. The image display device according to claim 1, further comprising a cover heat dissipation material that is provided at a surface of the first cover along a direction from the first display toward the first optical member, the cover heat dissipation material that dissipates heat of the first cover.
8. The image display device according to claim 1, wherein the first heat dissipation material is a graphite sheet.
9. The image display device according to claim 1, further comprising: a frame that includes a concave portion into which a portion of the first display is inserted and that supports the first optical member, wherein grease is filled into the concave portion of the frame, the grease being another heat dissipation material that conducts heat of the first display to the frame.
10. The image display device according to claim 9, further comprising a heat insulating member between the frame and the first optical member.
11. The image display device according to claim 1, wherein the first display is disposed so as to close an opening of the first cover.
12. The image display device according to claim 1, further comprising a second heat dissipation

material, the second heat dissipation material being directly attached to a different side of the first cover than the first heat dissipation material.
