

# US Patent & Trademark Office

## Patent Public Search | Text View

---

|                      |                          |
|----------------------|--------------------------|
| United States Patent | 12400049                 |
| Kind Code            | B2                       |
| Date of Patent       | August 26, 2025          |
| Inventor(s)          | Lewis; Jeffery D. et al. |

---

### System and method for generating computerized models of structures using geometry extraction and reconstruction techniques

---

#### Abstract

Described in detail herein are systems and methods for generating computerized models of structures using geometry extraction and reconstruction techniques. The system includes a computing device coupled to a input device. The input device obtains raw data scanned by a sensor. The computing device is programmed to execute a data fusion process is applied to fuse the raw data, and a geometry extraction process is performed on the fused data to extract features such as walls, floors, ceilings, roof planes, etc. Large- and small-scale features of the structure are reconstructed using the extracted features. The large- and small-scale features are reconstructed by the system into a floor plan (contour) and/or a polyhedron corresponding to the structure. The system can also process exterior features of the structure to automatically identify condition and areas of roof damage.

---

|                   |                                                                      |
|-------------------|----------------------------------------------------------------------|
| <b>Inventors:</b> | <b>Lewis; Jeffery D. (Orem, UT), Taylor; Jeffrey C. (Alpine, UT)</b> |
| <b>Applicant:</b> | <b>Xactware Solutions, Inc. (Lehi, UT)</b>                           |
| <b>Family ID:</b> | <b>1000008779724</b>                                                 |
| <b>Assignee:</b>  | <b>Xactware Solutions, Inc. (Lehi, UT)</b>                           |
| <b>Appl. No.:</b> | <b>18/236728</b>                                                     |
| <b>Filed:</b>     | <b>August 22, 2023</b>                                               |

#### Prior Publication Data

|                            |                         |
|----------------------------|-------------------------|
| <b>Document Identifier</b> | <b>Publication Date</b> |
| US 20230409769 A1          | Dec. 21, 2023           |

#### Related U.S. Application Data

**Publication Classification**

**Int. Cl.:** **G06F30/13** (20200101); **G06T7/12** (20170101); **G06T7/55** (20170101)

**U.S. Cl.:**

**CPC** **G06F30/13** (20200101); **G06T7/12** (20170101); **G06T7/55** (20170101);  
G06T2207/10028 (20130101)

**Field of Classification Search**

**USPC:** None

---

**References Cited**

**U.S. PATENT DOCUMENTS**

| <b>Patent No.</b> | <b>Issued Date</b> | <b>Patentee Name</b> | <b>U.S. Cl.</b> | <b>CPC</b> |
|-------------------|--------------------|----------------------|-----------------|------------|
| 5701403           | 12/1996            | Watanabe et al.      | N/A             | N/A        |
| 6446030           | 12/2001            | Hoffman et al.       | N/A             | N/A        |
| 6448964           | 12/2001            | Isaacs et al.        | N/A             | N/A        |
| 8533063           | 12/2012            | Erickson             | N/A             | N/A        |
| 8843304           | 12/2013            | Dupont et al.        | N/A             | N/A        |
| 8868375           | 12/2013            | Christian            | N/A             | N/A        |
| 8983806           | 12/2014            | Labrie et al.        | N/A             | N/A        |
| 9158869           | 12/2014            | Labrie et al.        | N/A             | N/A        |
| 9430871           | 12/2015            | Neophytou et al.     | N/A             | N/A        |
| 9501700           | 12/2015            | Loveland et al.      | N/A             | N/A        |
| 9679227           | 12/2016            | Taylor et al.        | N/A             | N/A        |
| 10127670          | 12/2017            | Lewis et al.         | N/A             | N/A        |
| 10181079          | 12/2018            | Labrie et al.        | N/A             | N/A        |
| 10289760          | 12/2018            | Oakes, III et al.    | N/A             | N/A        |
| 10387582          | 12/2018            | Lewis et al.         | N/A             | N/A        |
| 10445438          | 12/2018            | Motonaga et al.      | N/A             | N/A        |
| 10529028          | 12/2019            | Davis et al.         | N/A             | N/A        |
| 11314905          | 12/2021            | Childs et al.        | N/A             | N/A        |
| 11688135          | 12/2022            | Lewis et al.         | N/A             | N/A        |
| 11688186          | 12/2022            | Harris et al.        | N/A             | N/A        |
| 11734468          | 12/2022            | Lewis et al.         | N/A             | N/A        |
| 12124775          | 12/2023            | Childs et al.        | N/A             | N/A        |
| 12125139          | 12/2023            | Lewis et al.         | N/A             | N/A        |
| 2002/0116254      | 12/2001            | Stein et al.         | N/A             | N/A        |
| 2003/0009315      | 12/2002            | Thomas et al.        | N/A             | N/A        |
| 2007/0080961      | 12/2006            | Inzinga et al.       | N/A             | N/A        |
| 2007/0276626      | 12/2006            | Bruffey              | N/A             | N/A        |

|              |         |                     |       |            |
|--------------|---------|---------------------|-------|------------|
| 2009/0179895 | 12/2008 | Zhu et al.          | N/A   | N/A        |
| 2010/0110074 | 12/2009 | Pershing            | N/A   | N/A        |
| 2010/0114537 | 12/2009 | Pershing            | N/A   | N/A        |
| 2010/0296693 | 12/2009 | Thornberry et al.   | N/A   | N/A        |
| 2011/0056286 | 12/2010 | Jansen              | N/A   | N/A        |
| 2011/0157213 | 12/2010 | Takeyama et al.     | N/A   | N/A        |
| 2011/0191738 | 12/2010 | Walker et al.       | N/A   | N/A        |
| 2012/0026322 | 12/2011 | Malka et al.        | N/A   | N/A        |
| 2012/0179431 | 12/2011 | Labrie et al.       | N/A   | N/A        |
| 2012/0253725 | 12/2011 | Malka et al.        | N/A   | N/A        |
| 2012/0253751 | 12/2011 | Malka et al.        | N/A   | N/A        |
| 2013/0201167 | 12/2012 | Oh et al.           | N/A   | N/A        |
| 2013/0206177 | 12/2012 | Burlutskiy          | N/A   | N/A        |
| 2013/0226451 | 12/2012 | O'Neill et al.      | N/A   | N/A        |
| 2013/0262029 | 12/2012 | Pershing            | N/A   | N/A        |
| 2013/0267260 | 12/2012 | Chao et al.         | N/A   | N/A        |
| 2013/0314688 | 12/2012 | Likholyot           | N/A   | N/A        |
| 2014/0043436 | 12/2013 | Bell et al.         | N/A   | N/A        |
| 2014/0195275 | 12/2013 | Pershing et al.     | N/A   | N/A        |
| 2014/0301633 | 12/2013 | Furukawa et al.     | N/A   | N/A        |
| 2014/0320661 | 12/2013 | Sankar et al.       | N/A   | N/A        |
| 2015/0029182 | 12/2014 | Sun et al.          | N/A   | N/A        |
| 2015/0073864 | 12/2014 | Labrie et al.       | N/A   | N/A        |
| 2015/0081252 | 12/2014 | Loss                | 703/1 | G06F 30/13 |
| 2015/0093047 | 12/2014 | Battcher et al.     | N/A   | N/A        |
| 2015/0116509 | 12/2014 | Birkler et al.      | N/A   | N/A        |
| 2015/0153172 | 12/2014 | Starns et al.       | N/A   | N/A        |
| 2015/0193971 | 12/2014 | Dryanovski et al.   | N/A   | N/A        |
| 2015/0213558 | 12/2014 | Nelson              | N/A   | N/A        |
| 2015/0227645 | 12/2014 | Childs et al.       | N/A   | N/A        |
| 2015/0269438 | 12/2014 | Samarasekera et al. | N/A   | N/A        |
| 2015/0302529 | 12/2014 | Jagannathan         | N/A   | N/A        |
| 2016/0098802 | 12/2015 | Bruffey et al.      | N/A   | N/A        |
| 2016/0110480 | 12/2015 | Randolph            | N/A   | N/A        |
| 2016/0246767 | 12/2015 | Makadia et al.      | N/A   | N/A        |
| 2016/0282107 | 12/2015 | Roland et al.       | N/A   | N/A        |
| 2017/0124713 | 12/2016 | Jurgenson et al.    | N/A   | N/A        |
| 2017/0132711 | 12/2016 | Bruffey et al.      | N/A   | N/A        |
| 2017/0132835 | 12/2016 | Halliday et al.     | N/A   | N/A        |
| 2017/0169459 | 12/2016 | Bruffey et al.      | N/A   | N/A        |
| 2017/0193297 | 12/2016 | Michini et al.      | N/A   | N/A        |
| 2017/0206648 | 12/2016 | Marra et al.        | N/A   | N/A        |
| 2017/0221152 | 12/2016 | Nelson et al.       | N/A   | N/A        |
| 2017/0316115 | 12/2016 | Lewis et al.        | N/A   | N/A        |
| 2017/0330207 | 12/2016 | Labrie et al.       | N/A   | N/A        |
| 2017/0345069 | 12/2016 | Labrie et al.       | N/A   | N/A        |
| 2018/0053329 | 12/2017 | Roberts et al.      | N/A   | N/A        |
| 2018/0067593 | 12/2017 | Tiwari et al.       | N/A   | N/A        |
| 2018/0089833 | 12/2017 | Lewis et al.        | N/A   | N/A        |
| 2018/0286098 | 12/2017 | Lorenzo             | N/A   | N/A        |

|              |         |                   |     |     |
|--------------|---------|-------------------|-----|-----|
| 2018/0330528 | 12/2017 | Loveland et al.   | N/A | N/A |
| 2018/0357819 | 12/2017 | Oprea             | N/A | N/A |
| 2018/0373931 | 12/2017 | Li                | N/A | N/A |
| 2019/0114717 | 12/2018 | Labrie et al.     | N/A | N/A |
| 2019/0147247 | 12/2018 | Harris et al.     | N/A | N/A |
| 2019/0221040 | 12/2018 | Shantharam et al. | N/A | N/A |
| 2019/0340692 | 12/2018 | Labrie et al.     | N/A | N/A |
| 2019/0347859 | 12/2018 | Jovanovic et al.  | N/A | N/A |
| 2019/0377837 | 12/2018 | Lewis et al.      | N/A | N/A |
| 2020/0100066 | 12/2019 | Lewis et al.      | N/A | N/A |
| 2020/0143481 | 12/2019 | Brown et al.      | N/A | N/A |
| 2021/0076162 | 12/2020 | Wang et al.       | N/A | N/A |
| 2021/0103687 | 12/2020 | Harris et al.     | N/A | N/A |
| 2021/0350038 | 12/2020 | Jenson et al.     | N/A | N/A |
| 2022/0309204 | 12/2021 | Childs et al.     | N/A | N/A |
| 2022/0309748 | 12/2021 | Lewis et al.      | N/A | N/A |
| 2022/0414980 | 12/2021 | Lewis et al.      | N/A | N/A |
| 2023/0343030 | 12/2022 | Lewis et al.      | N/A | N/A |

#### **FOREIGN PATENT DOCUMENTS**

| <b>Patent No.</b> | <b>Application Date</b> | <b>Country</b> | <b>CPC</b> |
|-------------------|-------------------------|----------------|------------|
| 2014/151122       | 12/2013                 | WO             | N/A        |
| 2016/154306       | 12/2015                 | WO             | N/A        |
| 2017/100658       | 12/2016                 | WO             | N/A        |

#### **OTHER PUBLICATIONS**

Office Action mailed Oct. 13, 2022, issued in connection with U.S. Appl. No. 16/545,607 (53 pages). cited by applicant

International Search Report of the International Searching Authority mailed on Nov. 18, 2022, issued in connection with International Application No. PCT/US22/030691 (6 pages). cited by applicant

Written Opinion of the International Searching Authority mailed on Nov. 18, 2022, issued in connection with International Application No. PCT/US22/030691 (11 pages). cited by applicant

Notice of Allowance mailed Dec. 9, 2022, issued in connection with U.S. Appl. No. 17/705,130 (10 pages). cited by applicant

Examination Report No. 1 mailed Dec. 15, 2022, issued by the Australian Patent Office in connection with Australian Patent Application No. 2021282413 (3 pages). cited by applicant

Communication Pursuant to Article 94(3) EPC mailed Jan. 31, 2023, issued in connection with European Patent Application No. 16873975.3 (8 pages). cited by applicant

Notice of Allowance mailed Feb. 14, 2023, issued in connection with U.S. Appl. No. 17/705,130 (5 pages). cited by applicant

Notice of Allowance mailed Mar. 22, 2023, issued in connection with U.S. Appl. No. 16/545,607 (9 pages). cited by applicant

Communication Pursuant to Article 94(3) EPC issued by the European Patent Office mailed on Apr. 28, 2023, issued in connection with European Patent Application No. 19866788.3 (5 pages). cited by applicant

Office Action mailed Jun. 30, 2023, issued in connection with U.S. Appl. No. 17/729,613 (49 pages). cited by applicant

Examination Report No. 1 mailed Apr. 12, 2023, issued by the Australian Patent Office in connection with Australian Patent Application No. 2018364813 (3 pages). cited by applicant

International Search Report of the International Searching Authority mailed on Mar. 27, 2017, issued in connection with International Application No. PCT/US2016/65947 (3 pages). cited by applicant

Written Opinion of the International Searching Authority mailed on Mar. 27, 2017, issued in connection with International Application No. PCT/US2016/65947 (7 pages). cited by applicant  
Office Action mailed Sep. 26, 2018, issued in connection with U.S. Appl. No. 15/374,695 (33 pages). cited by applicant

Notice of Allowance mailed May 13, 2019, issued in connection with U.S. Appl. No. 15/374,695 (7 pages). cited by applicant

Extended European Search Report mailed Jun. 11, 2019, issued in connection with European Patent Application No. 16873975.3 (8 pages). cited by applicant

Communication Pursuant to Article 94(3) EPC issued by the European Patent Office mailed on Apr. 22, 2020, issued in connection with European Patent Application No. 16873975.3 (6 pages). cited by applicant

International Search Report of the International Searching Authority mailed on Dec. 12, 2019, issued in connection with International Application No. PCT/US2019/52670 (3 pages). cited by applicant

Written Opinion of the International Searching Authority mailed on Dec. 12, 2019, issued in connection with International Application No. PCT/US2019/52670 (5 pages). cited by applicant  
Office Action mailed Feb. 5, 2020, issued in connection with U.S. Appl. No. 16/580,741 (15 pages). cited by applicant

International Search Report of the International Searching Authority mailed on May 14, 2015, issued in connection with International Application No. PCT/US15/015491(3 pages). cited by applicant

Written Opinion of the International Searching Authority mailed on May 14, 2015, issued in connection with International Application No. PCT/US15/015491 (9 pages). cited by applicant  
Fung, et al., "A Mobile Assisted Localization Scheme for Augmented Reality," Department of Computer Science and Engineering, The Chinese University of Hong Kong, 2012 (76 pages). cited by applicant

Sankar, et al., "Capturing Indoor Scenes With Smartphones," UIST'12, Oct. 7-10, 2012, Cambridge, Massachusetts (9 pages). cited by applicant

Office Action mailed Aug. 8, 2017, issued in connection with U.S. Appl. No. 14/620,004 (26 pages). cited by applicant

Office Action mailed Aug. 28, 2018, issued in connection with U.S. Appl. No. 14/620,004 (33 pages). cited by applicant

Farin, et al., "Floor-Plan Reconstruction from Panoramic Images," Sep. 23-28, 2007, MM '07, ACM (4 pages). cited by applicant

Office Action mailed Mar. 29, 2019, issued in connection with U.S. Appl. No. 14/620,004 (22 pages). cited by applicant

Office Action mailed Dec. 10, 2019, issued in connection with U.S. Appl. No. 14/620,004 (27 pages). cited by applicant

Zhang, et al., "Wallk&Sketch: Create Floor Plans with an RGB-D Camera," Sep. 5-8, 2012, UbiComp '12, ACM (10 pages). cited by applicant

Office Action mailed Jul. 8, 2020, issued in connection with U.S. Appl. No. 14/620,004 (27 pages). cited by applicant

Office Action mailed Sep. 22, 2020, issued in connection with U.S. Appl. No. 16/580,741 (14 pages). cited by applicant

Office Action mailed Feb. 2, 2021, issued in connection with U.S. Appl. No. 14/620,004 (28 pages). cited by applicant

Communication Pursuant to Article 94(3) EPC issued by the European Patent Office mailed on

Feb. 18, 2021, issued in connection with European Patent Application No. 16873975.3 (5 pages). cited by applicant

Examination Report No. 1 mailed Mar. 30, 2021, issued by the Australian Patent Office in connection with Australian Patent Application No. 2016366537 (6 pages). cited by applicant

Office Action mailed Apr. 21, 2021, issued in connection with U.S. Appl. No. 16/580,741 (15 pages). cited by applicant

Notice of Allowance mailed Aug. 19, 2021, issued in connection with U.S. Appl. No. 14/620,004 (11 pages). cited by applicant

Examiner-Initiated Interview Summary dated Aug. 10, 2021, issued in connection with U.S. Appl. No. 14/620,004 (1 page). cited by applicant

International Search Report of the International Searching Authority mailed on Feb. 11, 2019, issued in connection with International Application No. PCT/US18/60762 (3 pages). cited by applicant

Written Opinion of the International Searching Authority mailed on Feb. 11, 2019, issued in connection with International Application No. PCT/US18/60762 (7 pages). cited by applicant

Office Action mailed Apr. 16, 2020, issued in connection with U.S. Appl. No. 16/189,512 (10 pages). cited by applicant

U.S. Appl. No. 62/512,989, filed May 31, 2017 entitled, "Systems and Methods for Rapidly Developing Annotated Computer Models of Structures" (47 pages). cited by applicant

Office Action mailed Dec. 14, 2020, issued in connection with U.S. Appl. No. 16/189,512 (10 pages). cited by applicant

Extended European Search Report dated Jul. 1, 2021, issued by the European Patent Office in connection with European Application No. 18876121.7 (8 pages). cited by applicant

Office Action mailed Jul. 20, 2021, issued in connection with U.S. Appl. No. 16/189,512 (11 pages). cited by applicant

Office Action mailed Dec. 27, 2021, issued in connection with U.S. Appl. No. 16/580,741 (13 pages). cited by applicant

Notice of Allowance mailed Dec. 16, 2021, issued in connection with U.S. Appl. No. 14/620,004 (12 pages). cited by applicant

Invitation to Pay Additional Fees issued by the International Searching Authority mailed on Feb. 2, 2022, issued in connection with International Application No. PCT/US21/63469 (2 pages). cited by applicant

Extended European Search Report dated Feb. 18, 2022, issued in connection with European Patent Application No. 19866788.3 (9 pages). cited by applicant

Office Action dated Feb. 3, 2022, issued by the Canadian Intellectual Property Office in connection with Canadian Application No. 3,007,968 (5 pages). cited by applicant

Office Action dated Mar. 25, 2022, issued in connection with U.S. Appl. No. 16/545,607 (56 pages). cited by applicant

International Search Report of the International Searching Authority mailed on Apr. 8, 2022, issued in connection with International Application No. PCT/US21/63469 (5 pages). cited by applicant

Written Opinion of the International Searching Authority mailed on Apr. 8, 2022, issued in connection with International Application No. PCT/US21/63469 (6 pages). cited by applicant

Notice of Allowance mailed Apr. 8, 2022, issued in connection with U.S. Appl. No. 16/189,512 (8 pages). cited by applicant

Notice of Allowance mailed Jun. 21, 2022, issued in connection with U.S. Appl. No. 16/189,512 (7 pages). cited by applicant

Dino, et al., "Image-Based Construction of Building Energy Models Using Computer Vision," Automation in Construction (2020) (15 pages). cited by applicant

Fathi, et al., "Automated As-Built 3D Reconstruction of Civil Infrastructure Using Computer Vision: Achievements, Opportunities, and Challenges," Advanced Engineering Informatics (2015)

(13 pages). cited by applicant  
International Search Report of the International Searching Authority mailed on Jul. 25, 2022, issued in connection with International Application No. PCT/US22/22024 (3 pages). cited by applicant  
Written Opinion of the International Searching Authority mailed on Jul. 25, 2022, issued in connection with International Application No. PCT/US22/22024 (5 pages). cited by applicant  
Office Action dated Sep. 2, 2022, issued in connection with U.S. Appl. No. 16/580,741 (13 pages). cited by applicant  
Notice of Allowance mailed Sep. 6, 2022, issued in connection with U.S. Appl. No. 16/189,512 (7 pages). cited by applicant  
Office Action mailed Dec. 7, 2023, issued by the Canadian Patent Office in connection with Canadian Patent Application No. 3,082,516 (6 pages). cited by applicant  
Office Action dated Jan. 12, 2024, issued in connection with U.S. Appl. No. 18/214,842 (4 pages). cited by applicant  
International Search Report of the International Searching Authority mailed on Dec. 15, 2023, issued in connection with International Application No. PCT/US2023/031123 (6 pages). cited by applicant  
Written Opinion of the International Searching Authority mailed on Dec. 15, 2023, issued in connection with International Application No. PCT/US2023/031123 (7 pages). cited by applicant  
Office Action dated Jan. 30, 2024, issued in connection with U.S. Appl. No. 17/895,500 (16 pages). cited by applicant  
Office Action dated Mar. 12, 2024, issued in connection with U.S. Appl. No. 17/122,080 (10 pages). cited by applicant  
Sampaio, et al., "Maintenance of Building Components Supported in Interactive Environments," 10th Iberian Conference on Information Systems and Technologies, Jun. 17, 2015 (7 pages). cited by applicant  
Notice of Allowance dated Mar. 18, 2024, issued in connection with U.S. Appl. No. 17/729,613 (10 pages). cited by applicant  
Communication Pursuant to Article 94(3) EPC mailed Jan. 23, 2024, issued by the European Patent Office in connection with European Patent Application No. 19866788.3 (5 pages). cited by applicant  
Office Action dated Jun. 4, 2024, issued by the Canadian Intellectual Property Office in connection with Canadian Application No. 3,082,516 (4 pages). cited by applicant  
Notice of Allowance dated Jul. 3, 2024, issued in connection with U.S. Appl. No. 17/895,500 (6 pages). cited by applicant  
Notice of Allowance dated Jul. 12, 2024, issued in connection with U.S. Appl. No. 17/729,613 (9 pages). cited by applicant  
Examination Report No. 1 mailed May 20, 2025, issued by the Australian Patent Office in connection with Australian Patent Application No. 2024201803 (3 pages). cited by applicant  
Communication Pursuant to Article 94(3) EPC mailed Jun. 6, 2025, issued by the European Patent Office in connection with European Patent Application No. 16873975.3 (9 pages). cited by applicant

---

*Primary Examiner:* Chen; Frank S

*Attorney, Agent or Firm:* McCarter & English, LLP

---

## **Background/Summary**

RELATED APPLICATIONS (1) This application is a continuation of, and claims the benefit of priority to, U.S. patent application Ser. No. 16/545,607 filed on Aug. 20, 2019, now U.S. Pat. No. 11,734,468, issued on Aug. 22, 2023, which is a continuation of, and claims the benefit of priority to, U.S. patent application Ser. No. 15/374,695 filed on Dec. 9, 2016, now U.S. Pat. No. 10,387,582, issued on Aug. 20, 2019, which claims priority to U.S. Provisional Application No. 62/265,359 filed on Dec. 9, 2015, the entire disclosures of which are expressly incorporated herein by reference.

## BACKGROUND OF INVENTION

### Field of Disclosure

(1) The present disclosure relates generally to a system and method for generating computerized models of structures using computing devices. More specifically, the present disclosure relates to a system and method for generating computerized models of structures using geometry extraction and reconstruction techniques.

### Related Art

(2) In the insurance underwriting, building construction, solar, and real estate industries, computer-based systems for generating models of physical structures such as residential homes, commercial buildings, etc., is becoming increasingly important. In particular, in order to create an accurate model of a physical structure, one must have an accurate set of data which adequately describes that structure. Moreover, it is becoming increasingly important to provide computer-based systems which have adequate capabilities to generate three-dimensional (3D) models of both the interior and exterior features of buildings, as well as to identify specific features of such buildings (e.g., interior wall/floor/ceiling features, etc.) and condition (exterior wall damage, roof damage, etc.).

(3) With the advent of mobile data capturing devices including phones, tablets and unmanned aerial and ground based vehicles, it is now possible to gather and process accurate data from sites located anywhere in the world. The data can be processed either directly on a hand-held computing device or some other type of device, such as an unmanned aerial vehicle (UAV) or system (UAS) (provided that such devices have adequate computing power), or remotely on a data processing server.

(4) Accordingly, what would be desirable is a system and method for generating three-dimensional models of structures using geometry extraction (such as feature growing) and feature reconstruction techniques.

## SUMMARY OF THE INVENTION

(5) The present invention relates to a system and method for generating computerized models of structures (such as interior and exterior features of buildings, homes, dwellings, etc., including interior and exterior features of such structures) using geometry extraction and reconstruction techniques. The system includes a structure modeling engine executed by a computing device, such as a mobile smart phone. The system obtains raw data scanned by a sensor in communication with the smart phone, such as a series of photos, RGB image data (still, fisheye, panoramic, video, etc.), infrared (IR) image data, mobile sensor data (gyroscope/accelerometer/barometer, etc.), laser range data (point cloud data), LIDAR, global positioning system (GPS) data, X-ray data, magnetic field data, depth maps, and other types of data. A data fusion process is applied to fuse the raw data, and a geometry extraction process is performed on the fused data to extract features such as walls, floors, ceilings, roof planes, etc. Large-scale features of the structure are then reconstructed by the system using the extracted features. Optionally, small-scale features of the structure could also be reconstructed by the system. The large- and small-scale features are reconstructed by the system into a floor plan (contour) and/or a polyhedron corresponding to the structure. Optionally, the system can also process exterior features such as roof and wall image data to automatically identify condition and areas of roof damage.

---



## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The foregoing features of the invention will be apparent from the following Detailed Description, taken in connection with the accompanying drawings, in which:
- (2) FIG. 1 is a diagram illustrating hardware and software components of the system of the present disclosure;
- (3) FIG. 2 is a diagram illustrating software components of the system in greater detail;
- (4) FIGS. 3-4 are flowcharts illustrating high-level processing steps carried out by the system for generating a three-dimensional computer model of a physical structure;
- (5) FIG. 5 is a flowchart illustrating processing steps carried out by the system for reconstructing large scale features;
- (6) FIG. 6 is a flowchart illustrating processing steps carried out by the system for generating a computerized floor plan of a physical structure;
- (7) FIGS. 7A-7C are images illustrating the processing steps of FIG. 6;
- (8) FIG. 8 is a flowchart illustrating processing steps carried out by the system for generating a computerized floor contour and/or polyhedron corresponding to a physical structure;
- (9) FIGS. 9A-9F are screenshots illustrating the processing steps of FIG. 8 carried out by the system;
- (10) FIG. 10 is a flowchart illustrating processing steps carried out by the system for detecting and identifying damage to roof surfaces of a structure;
- (11) FIG. 11 is a flowchart illustrating additional processing steps carried out by the system for identifying individual rooms and floor plans from point cloud data;
- (12) FIGS. 12A-12H are screenshots illustrating the processing steps of FIG. 11;
- (13) FIG. 13 is a flowchart illustrating another embodiment of the present disclosure for generating floorplans from point cloud data; and
- (14) FIGS. 14A-14H are screenshots illustrating the processing steps of FIG. 13.

### DETAILED DESCRIPTION

- (15) The present disclosure relates to a system and method for generating three-dimensional computer models of structures using geometry extraction and reconstruction techniques, as described in detail below in connection with FIGS. 1-14H. As used herein, the term “structure” refers to physical structures such as homes, dwellings, buildings, etc.
- (16) FIG. 1 is a diagram, indicated generally at 10, illustrating hardware and software components of the system of the present disclosure. The system includes a structure modeling engine 12 which is embodied as specially-programmed software code that executes on a suitable computing device, such as a smart phone 14. As will be discussed in greater detail below, the modeling engine 12 allows a user of the smart phone 14 to quickly and conveniently generate three-dimensional computer models of structures. It is noted that the smart phone 14 could be substitute for another type of computing device, such as a tablet computer, a laptop computer, a personal (standalone) computer, etc., without departing from the spirit or scope of the present disclosure. In the case of a smart phone, the smart phone 14 could execute any suitable operating system. The modeling engine 12 is stored in non-volatile memory of the smart phone 14, and is executed by a processor of the smart phone 14. As will be discussed in greater detail below, the modeling engine processes raw data obtained by one or more sensors associated with the phone 14, such as the phone's camera and/or other sensors such as a light detection and ranging (LIDAR) camera, etc. It is also noted that the engine 12 could be programmed into and executed by an unmanned aerial vehicle (UAV) and/or system (UAS), if desired, such that the UAV/UAS is capable of flying around a structure, taking digital imagery or LIDAR data using on-board sensors, and processing the data in accordance with the present disclosure to generate three-dimensional models of the structure.

(17) The smart phone **14** can communicate via a network **16** with a remote user's computer system **18**, and/or with a remote structure modeling server **20**. The remote structure modeling server **20** could also be programmed with and execute the structure modeling engine **12**, if desired. Such an arrangement is particularly advantageous where the smart phone **14** does not have sufficient processing power to rapidly generate three-dimensional models of structures, in which case the server **20** can remotely perform such functions. In such circumstances, the remote server **20** would receive raw captured data from the smart phone **14** via the network **16**. The network **16** could include the Internet, a cellular data network, a wireless network, a wired network, etc. Of course, the server **20** could be a stand-alone server, or it could be part of a "cloud" computing environment/platform, if desired.

(18) FIG. **2** is a diagram illustrating the structure modeling engine **12** in greater detail. The structure modeling engine **12** includes a plurality of software modules **22-30** which perform various functions in accordance with the present disclosure. For example, the engine **12** includes a data fusion module **22**, a geometry extraction module **24**, a large-scale structure feature reconstruction module **26**, a small-scale structure feature reconstruction module **28**, and a database management module **30**. The functions of each of these modules are discussed in greater detail below. It is noted that the modules **22-30** and the engine **12** could be programmed using any suitable high- or low-level programming language, such as Java, C, C #, C++, Python, etc., without departing from the spirit or scope of the present disclosure.

(19) FIG. **3** is a flowchart illustrating high-level processing steps carried out by the system, and indicated generally at **40**. Beginning in step **42**, the user begins scanning a structure using one or more sensors of the smart phone **14**. Then, in step **44**, the system determines whether the user is inside or outside. It is noted that step **44** could be carried out by a user of the system, i.e., the user can specify (e.g., using one or more user interface controls displayed by the system) whether the user is located inside or outside of a structure. If the user is outside, step **46** occurs, wherein the smart phone **14** is moved around the structure (e.g., by the user walking around the structure and pointing the smart phone **14** at the structure, or, in the case of a UAV or UAS, by flying the UAV/UAS around the structure). In step **48**, the system takes overlapping photos, videos, and/or LIDAR point clouds of the structure. In step **50**, a determination is made as to whether sufficient coverage of the structure has been provided. This could be accomplished by tracking that data has been captured in a 360 degree circle, or by processing a user input, such that the user signals to the system that he or she has captured what is believed to be enough coverage. If a negative determination is made, control returns to step **46**. Otherwise, step **52** occurs, wherein a determination is made as to whether capturing of inside and/or outside images is complete. If a negative determination is made, control returns to step **44**. Otherwise, step **54** occurs, wherein a determination is made as to whether the captured data can be processed on the device (e.g., using the processor of the smart phone **14**, the processor of the UAV/UAS, the processor of the laptop/tablet computer, etc.). If a positive determination is made, step **56** occurs, wherein the data is processed on the device. Otherwise, step **66** occurs, wherein the data is uploaded to a cloud platform (e.g., to a cloud service provider, to the server **20** of FIG. **1**, etc.). Then, in step **68**, the data is processed on the cloud platform (e.g., on the server **20**), including aerial data, satellite data, obtained imagery, etc. In step **58**, the data package is complete.

(20) In the event that a determination is made in step **44** that scanning of the inside of a structure is to be done, step **60** occurs wherein the user moves through each room of the structure using the smart phone **14**. Then, in step **62**, as the user moves through a room, the user takes overlapping photos, videos, and/or LIDAR point clouds using the phone **14** and/or sensor associated with the phone **14**. Then, in step **64**, a determination is made as to whether the last room has been captured. If a positive determination is made, step **52** occurs; otherwise, control returns to step **60**.

(21) FIG. **4** is a further flowchart illustrating high-level processing steps carried out by the system, indicated generally at **70**. Beginning in step **72**, the engine **12** receives raw data from one or more

sensors associated with the phone **14** (or, in the case of a UAS/UAV, from on-board sensors of such devices). Such data can be obtained from many devices with the appropriate sensors and the capability of storing, processing and/or transmitting the data. Examples of such devices includes, but is not limited to, image capturing devices such as digital cameras and video cameras, smart phones, tablet computers, laptop computers, wearable computers, laser scanners, scanning range finders, RGB-D sensors, mobile sensors such as those mounted on robots or UAVs, and/or other types of sensors. Also, the system can process many types of data which can be utilized to generate models of structures. Examples of such data include, but is not limited to, RGB image data (still, fisheye, panoramic, video, etc.), infrared (IR) image data, mobile sensor data (gyroscope/accelerometer/barometer, etc.), laser range data (point cloud data), LIDAR, global positioning system (GPS) data, X-ray data, magnetic field data, depth maps, and other types of data.

(22) In step **74**, a data fusion process is performed on the raw data. In order to utilize the raw data, it must be collated/fused into a coherent data set. For example, if the structure data is captured a frame at a time, the data from one frame is not sufficient to reconstruct the entire structure. The data from each frame must be merged, aligned and made to be consistent with the rest of the frame data from the entire structure. This process is called frame registration and may use position and orientation to calculate the sensor's position for each frame. In addition, data from multiple sources must be synchronized. For example, the color image data must be synchronized with the fisheye, IR, range, gyro/accelerometer and GPS data. The end result is a coherent data set from which meaningful information about the structure can be extracted. The processed data is stored in a fused data set database **76**.

(23) In step **78**, the fused data is processed by the system to extract geometry features therefrom. Data extraction depends on the ability to identify specific geometric elements in the data set. Specific algorithms with optimal pipeline and parameters could be utilized depending on the nature of input and estimated input accuracy, and could include the following steps: 1. Data filtering: removing noise, sensor distortions, inaccuracies and elements that are not required during the capture process (e.g., wall paintings, keys in a table, etc.) 2. Calculate geometries from source data. The geometries could be calculated iteratively as follows: a. Find the most evident raw geometry: lines, planes, intersections, etc. Otherwise, this step is completed. b. Remove data that describes this geometry from input data. c. Go back to point a. 3. Reconsider captured geometries iteratively: a. Square up geometries: aligning them to Cartesian axis XYZ as possible. b. Join or discard elements that are geometrically impossible. Remove degenerated geometries, merge parallel lines and planes. c. Find obstructed details from intersections and coalescence of different planes and lines. Such as wall corners behind a lamp, glass windows/doors not detected by the sensor or window/doors openings.

(24) The geometries could be classified as real elements by assigning them a meaning, discarding, adapting or merging geometries from step **3** above, e.g., extract structure façade and rooms using concave and convex hull algorithms, identify geometries as real objects using neural networks and then, refine polyhedral geometry, etc. In addition, geometry extraction can be performed using publicly-available software algorithm libraries such as Point Cloud Library (PCL), Eigen Math Library, Open Computer Vision library (OpenCV), and others. Examples of features which can be extracted in step **76** include, but are not limited to, edges, lines, planes, points, corners (where lines and/or planes intersect), and other features.

(25) In step **80**, the system reconstructs large-scale structure features, such as walls, ceilings, floors, etc., from the extracted geometry features. This process is described in greater detail below in connection with FIG. 5. Then, in step **82**, the system reconstructs small-scale structure features (such as room types, materials, wall features, fixtures, etc.) from the extracted geometry features. In step **84**, the system stores the reconstructed structure features in a feature database **86**, for subsequent retrieval and usage. The system also displays the extracted features to the user via a

user interface generated by the phone **14** and/or the remote user computer system **18**.

(26) FIG. 5 is a flowchart illustrating process step **80** of FIG. 4 in greater detail. As mentioned above, in step **80**, the system reconstructs large-scale structure features from the extracted geometry. Once the basic geometric elements have been identified, they can be used to create a 3D model of the structure. This involves identifying the wall, floor, ceiling planes and roof planes and then determining the relationship between them. In step **90**, the system processes planes to determine which planes correspond to the floor and ceiling of the structure. It is noted that this step need not be carried out with planes. Further, this step can be accomplished by using a PCL library to identify the major planes of the room, by snapping all points in plane to the “best fit” plane equation (e.g., correct inaccuracies), and by identifying planes that are parallel to the plane  $Y=0$  as the floor and ceiling planes. Next, in step **92**, the system straightens vertical walls to correct for sensor inaccuracies. This can be accomplished by using a PCL library to identify the major planes of the room, by finding the best fit plane equation for each plane, and by snapping each point in the plane to the new plane equation.

(27) In step **94**, the system squares angles formed by adjacent walls. This can be accomplished by using a PCL library to identify the major planes of the room, finding plane centroids, finding an angle between two plane normals vectors in the X-Z plane, adjusting the normal vectors to be an increment of 22.5 degrees, re-computing plane equations (dot product of new normal and centroid), and eliminating obstructions such as cabinets and furniture.

(28) In step **96**, the system eliminates vertical walls which do not contribute to the room structure, such as walls from other rooms seen through doorways. This can be accomplished by using a PCL library to identify the major planes of the room, identifying possible candidates (two planes that are parallel and exist in the same quadrant when the camera is positioned at the origin), finding the two planes' bounding boxes, and creating a pyramid for each plane. The top point of the pyramid is identified as the camera location, and the base is the plane's bounding box. Additionally, the system could identify closer and farther planes, and could automatically remove the farther plane if its pyramid is completely contained inside the closer plane's pyramid. The pyramid discussed herein can be seen and described in greater detail below in connection with FIGS. 9B-9C.

(29) Referring to both FIGS. 6 and 7A-7C, FIG. 6 is a flowchart illustrating processing steps in accordance with the present disclosure, indicated generally at **100**, for automatically identifying a floor plan for a room from point cloud data. Beginning in step **102**, the system processes the point cloud data to identify major planes of a room. This can be accomplished by using a PCL library to identify the major planes of the room. Then, in step **104**, the system flattens the plane by projecting all points of the plane directly onto the plane. In step **106**, the system identifies the floor plane and all wall (vertical) planes. In step **108**, the system adjusts all wall planes to be perfectly vertical. This can be accomplished by projecting all points to be on the common plane. In step **110**, the system identifies all possible corner points where 2 wall planes and the floor plane meet. This step is illustrated by the image **130** in FIG. 7A, which shows a point cloud with all possible corner points identified. Then, in step **112**, the system creates a fine mesh horizontal grid which covers the entire point cloud. In step **114**, the system assigns values to the grid cells. As illustrated in the image **132** in FIG. 7B, the values correspond with the number of points from the cloud which project onto that cell in the horizontal grid (e.g., flattening the point cloud). In step **116**, the system identifies all possible floor plans which connect corner points to form an outline of a room. This step is illustrated in the image **134** in FIG. 7C, and can be accomplished using a recursive depth first search technique.

(30) In step **118**, the system assigns a score to each possible floor plan. The score reflects how well the edges of the floor plan line up with high value cells in the grid. Then, in step **120**, the system sorts the scores. In step **122**, the system identifies the floor plan having the highest score as the most likely to reflect the actual floor plan of the room.

(31) The processing steps **100** illustrated in FIGS. 6 and 7A-7C could be carried out as follows:

First, the user captures the entire room in a 3D point cloud, using a suitable sensor (e.g., a LIDAR scanner connected to a portable computer or to the smart phone **14**). While viewing the captured cloud on the device, the user identifies where the major walls are located by tapping the screen at the respective locations. The position of the tap location on the cloud is then used by the system to calculate a 3D position which is stored as a user selected point. Then, the system uses a region growing algorithm in connection with the user selected points to extract major planes from the point cloud. The system correlates user-supplied “assist” points with the extracted planes to determine which are the wall planes. Then, the system intersects planes that are identified as wall planes to create intersection lines. Finally, the system intersects each intersection line with the floor plane to create floor plan. Additionally, it is noted that the processing steps illustrated in FIGS. **6** and **7A-7C** can be carried out while the user is capturing data, by clicking on the screen to identify planes or after the fact, and/or by viewing a point cloud and clicking on “important” items.

(32) Referring to FIGS. **8** and **9A-9F**, FIG. **8** is a flowchart illustrating processing steps, indicated generally at **140**, carried out by the system for automatically generating floor contours and/or polyhedrons representing a structure. Beginning in step **142**, the system begins by displaying to the user (e.g., on a display of the smart phone **14**) a first-person perspective view of the point cloud data produced by the device. This is illustrated in FIG. **9A**, which shows the perspective view of the point cloud **160**. Then, in step **144**, the user touches a location on the screen in the point cloud that is a representative location in the world for where the wall surface is located. This is illustrated in FIG. **9B**. Then, in step **146**, the system projects an infinite ray into the scene to find the point where the ray intersects the point cloud. The infinite ray **162** is shown in FIG. **9B**, and projects through the point cloud **160**. It is noted that the triangle shown in FIG. **9B** corresponds to the smart phone camera and illustrates its location within the scene, such that the apex (tip) of the triangle corresponds to the camera location.

(33) In step **148**, the point of intersection between the ray **162** and the point cloud **160** is used by the system as a seed for a region growing plane extraction algorithm, such that the system processes the point cloud data using such an algorithm. The region growing algorithm can be described in two stages. The first stage initializes the region to extract and finds an arbitrary number of new region candidates. The region is initialized with the seed from the point cloud and its nearest neighbor in the point cloud **160**. At this stage, the region is two points, and from this information, the system calculates the center and normal for an optimal plane of the region. Then, a set of candidates to be added to the region is initialized. The nearest neighbors to the seed of the region are tested to determine if they are close enough to be good region candidates. The second stage grows the region incrementally by evaluating each region candidate. In order for a region candidate to be added to the region, it must meet the following criteria: (1) the region candidate is within a distance threshold of the region; (2) if the region candidate is added to the region, the new mean squared error of the region must be less than a mean squared error threshold; and (3) if the region candidate is added to the region, it must be within a distance threshold to the new optimal plane calculated for the region. Many of these checks are computationally-intense if there are thousands of points being evaluated. Therefore, in order to optimize this portion so that it can run on mobile devices, the mean squared error and principle component analysis are calculated incrementally as candidates are added to a region. If a region candidate meets the above criteria, then it is added to the region. The candidate added to the region is then used to update the list of region candidates. In this way the region can continue to grow beyond the immediate neighbors of the seed.

(34) The region continues growing until there are no more candidates or it has reached a maximum region size. If a grown region does not meet a minimum threshold for region size it is not considered a valid planar region. Thus, as is shown in step **152**, a determination is made as to whether there are more walls (planes) to extract. This is illustrated in FIG. **9C**, wherein an additional point cloud **164** is processed in the manner described herein to extract walls. If a positive

determination is made, control returns to step **148**. Otherwise, step **152** occurs, wherein the system attempts to build a coherent structure from the captured planes. This is done by calculating where the walls intersect each other as well as where each wall intersects the floor and ceiling. If the entire structure is captured, this will give finite segments that form the geometry of the room. In step **154**, the system constructs a floor contour and/or polyhedron representing the structure of the room. This is illustrated in FIG. **9D**, wherein the extracted walls **166** and floor plane (or, contour) **168** is “assembled” by the system to create a polyhedron representing the interior structure of a room.

(35) In steps **156** and **158**, the generated floor contour and/or polyhedron can be displayed to the user, and optionally downloaded or exported by the user for use in another program (such as a computer-aided design (CAD) program), if desired. As illustrated in FIG. **9E**, the generated polyhedron **172** is displayed by the system in a graphical user interface screen **170**. The screen **170** also includes controls **174** for allowing the user to re-capture the room, if desired, finish capturing the room, send the captured polyhedron **172** to another program (such as the XACTIMATE software package by XACTWARE SOLUTIONS, INC.), and/or delete the polyhedron **172**. Additionally, button **176** allows the user to view a top-down view of the polyhedron **172**, and the “1.sup.st person” button **178** allows the user to view the polyhedron from a first person perspective view. Also, as shown in FIG. **9F**, controls **180** allow the user to manipulate the polyhedron **172** (e.g., add features to the polyhedron, change wall/plane parameters (e.g., sizes, shapes, etc.). Additionally, controls **182** allow the user to perform other functions such as to view other items (e.g., other polyhedrons generated by the system).

(36) It is noted that, in addition to identifying the basic size and shape of the structure, other relevant data can be extracted by the system as well. This step is illustrated in step **82** of FIG. **4**. For example, for indoor rooms, the type of room could be identified as well as the layout and dimensions. Identification of the following small-scale features can be accomplished by training and utilizing neural networks (e.g., deep convolutional neural networks): living rooms, dining rooms, kitchens, bathrooms, bedrooms, garages, living vs. non-living spaces, flooring materials (carpet, tile, hard wood, cement, linoleum), wall materials (drywall, brick, stone, wood panel), etc. Additionally, the following specific wall features could be identified: windows, doors, pass-through from one room to another, baseboard and crown molding, columns, pillars, etc. Other significant features which could be extracted include: stoves, toilet bowls, sinks, electrical outlets, lighting fixtures, smoke alarms, thermostats, sprinklers, HVAC vents, etc. In addition, personal items could also be identified. These include: furniture, televisions/home electronics, lamps, appliances, books, etc. Still further, with appropriate sensors, the following types of damage may also be detected: mold, dry rot, termites, water damage, structural issues, etc.

(37) Once the 3D models and all associated data have been extracted, this information can be made available through a database maintained by the system. The information can also be requested by specifying an individual property via an address, a geocode, etc. The information can also be aggregated and reports generated on multiple structures. For example, the system could be queried to display a list of all properties in postal code 84097 that have more than 4,000 square feet of living space and a pool. Properties in the database can be viewed online or on any mobile or desktop device.

(38) FIG. **10** is a flowchart illustrating processing steps, indicated generally at **190**, for identifying areas of damage in roof surfaces of a structure. It is assumed that, prior to steps **190** being carried out, the system has already modeled a structure in accordance with the present disclosure.

Beginning in step **192**, the user takes one or more photos of the roof face(s). This can be accomplished using a digital camera, mobile device, or UAV/UAS. Next, in step **194**, the system processes the images (photos) and determines the size of the pixels in the images. This can be accomplished in multiple ways. For example, a target of a known size can be placed on the faces prior to taking the photos and is included in the imagery. The target can be anything from a sticker

to a piece of paper, etc. The target should be something that can be easily identified and measured with common CV algorithms—a QR code or similar works well, but it could be a logo, etc. SIFT (Scale Invariant Feature Transform), SURF (Speeded Up Robust Features), Hough transform and other algorithms could also be used. Further, if multiple photos are taken and there is additional metadata associated with the photos (including, but not limited to GPS location, accelerometer/gyroscope/compass readings, etc.), such metadata may be able to be used to determine scale in combination with additional configuration on the device or camera. Moreover, it is noted that step **194** could be carried out by determining physical camera characteristics such as focal length and pixel size, and/or by identifying photo geolocation using sensors from a user device such as a GPS receiver, accelerometer, compass, etc.

(39) In step **196**, the system optionally maps the imagery to a data model. For example, it is possible to extract only the portions of the imagery that are roof and wall faces, or attempt to segment the images using roof/wall material detection algorithms or known “grabcut” algorithms. These imagery clips could be sent through neural networks/algorithms to identify possible areas of wind and hail damage and can return a list of coordinates tied to the imagery where the damage is suspected. The user can then be walked through a wizard-like process where they see the possible damage locations highlighted and review, edit and confirm the results. It is noted that step **196** could be carried out by projecting the property in three dimensions in the photo. For each roof plane in the photo, the system could identify suspected damaged areas using segmentation and neural networks to classify suspected areas as corresponding to actual damage, as well as identifying importance of the damage.

(40) In step **198**, the system processes the photo(s) to identify areas of roof damage. Based on the number of shingles damaged and pre-defined threshold parameters, the system can determine whether a particular face needs to be repaired or replaced. As shown in step **200**, the areas requiring repair can be displayed to the user, if desired. The damaged area information could also be utilized to obtain full estimate details and produce a line item and labor list detailing the costs to do the repairs, using another software package such as the PROPERTY INSIGHT package by XACTWARE SOLUTIONS, INC.

(41) FIG. **11** is a flowchart illustrating additional processing steps, indicated generally at **210**, that can be carried out by the system for extracting floor plans from point cloud data. In describing the steps **210** of FIG. **11**, reference is also made to the screenshots illustrated in FIGS. **12A-12H**. Beginning in step **212**, the system prepares source point clouds for processing from the system. This can be accomplished by removing Z-axis data from the points in the point cloud so that they are in the same plane, and by removing outliers and non-wall points. This step is illustrated in screenshot **250** in FIG. **12A**. Then, in step **214**, the system calculates raw lines from all point clouds processed by the system. This can be accomplished by calculating base lines from the X-Y point cloud data, using the following steps: clusterizing every point cloud by normal data, clusterizing every cluster by region growing and segmentation, calculating the concave hull for every cluster, and calculating the maximum segment from every cluster. This step is illustrated in screenshot **252** in FIG. **12B**.

(42) In step **216**, the system calculates main guidelines. This can be accomplished by calculating the most important axis from the point cloud data and rotating the model so that it is aligned with Cartesian lines, splitting raw lines and grouping them over horizontal and vertical lines, identifying line subgroups by adjacency, creating a guideline per subgroup, removing outliers from raw lines using the guidelines, and calculating main guidelines using the filtered lines. This step is illustrated in screenshot **254** in FIG. **12C**. Next, in step **218**, the system calculates a pivot point from the intersection of the guidelines. This is illustrated in screenshot **256** in FIG. **12D**. Next, in step **220**, the system identifies an orthogonal façade for the structure, as illustrated in screenshot **258** in FIG. **12E**. This can be accomplished by calculating the convex hull from the guidelines, refining the convex hull using pivot points, calculating the orthogonal façade from the refined convex hull, and

identifying whether each segment is a convex or concave line strip if the segment is not horizontal or vertical (depending on whether the closest pivot points are inside or outside of the convex hull). (43) In step **222**, the system identifies individual rooms, as shown in screenshots **260-262** in FIGS. **12F-12G**. This can be accomplished by: defining rooms from the guidelines and the pivot points by using the pivot points as potential corners of the rooms and using the guidelines to obtain coverage of the potential room; calculating all potential rooms and associated coverage and identifying a rectangular room with the most coverage found; and repeating this step until the most coverage of a room below a threshold is obtained. Finally, in step **224**, the system displays the final result. As shown in the screenshot **264** in FIG. **12H**, the identified rooms could be superimposed on the raw point cloud data.

(44) Referring to FIGS. **13** and **14A-14H**, shown are additional processing steps in accordance with another embodiment of the present disclosure, indicated generally at **1000**, for automatically identifying a floor plan for a room from point cloud data. Beginning in step **1001**, the system prepares the point cloud data to extract point cloud normals, to remove outliers, and to remove clearly non-wall points. This can be accomplished using a PCL algorithm. Then, the system removes Z coordinates so that geometry is in a two-dimensional (2-D) space, as shown the images **1010-1011** of FIG. **14A**. In step **1002**, PCL can be used on point data to extract the main axis for every cloud. Then, all point clouds are rotated so that all points are aligned with a Cartesian axis, as shown in FIG. **14B**. Then, in step **1003**, the system creates a fine mesh horizontal grid which covers the entire point cloud, assigns values to the grid cells, and calculates main guidelines. As illustrated in FIG. **14C**, the values correspond with the number of points from the cloud which project onto the cell in the horizontal grid (e.g., flattening the point cloud). Lines are created on the grid based on consecutive cells with point population. These lines are weighted based on cell point population and intersections with neighbor lines, etc. As shown in FIG. **14D**, it can be seen that these lines are filtered and adjusted to better fit the real world, displacing them a bit out of the grid. Once this information is obtained, the grid is no longer necessary.

(45) In step **1004**, lines are extended and trimmed to create intersections with each other, as illustrated in FIG. **14E**. Then, each intersection is considered as four quadrant, or eight octants, and each one is classified as a corner candidate. Each quadrant is weighted depending on multiple factors, including but not limited to, line weight, line extensions/trimmings that may be required to create intersections, angles between lines, etc. This process is illustrated in FIG. **14F**. In step **1005**, the walls are identified by joining corners with existing lines, and maximizing weight sums of corners and lines, as illustrated in FIG. **14G**. This will generate a floorplan candidate as illustrated FIG. **14H**. In step **1006**, further analysis can be done on each room to determine completeness. Completeness can be determined using additional evidence from point clouds, as needed. Several floor plan candidates can be generated with different levels of confidence. In step **1007**, the system assigns a score to each possible floor plan. The score reflects how well the edges of the floor plan line up with the input point cloud. Then, in step **1008**, the system sorts the floorplans by scores. In step **1009**, system identifies the floor plan having the highest score as the most likely to reflect the actual floor plan of the room.

(46) It is noted that the system of the present disclosure could compensate for the presence of objects in a space undergoing floorplan estimation. For example, if particular objects (such as appliances, etc.) have known measurements, then the system can compensate for the presence of such objects, and/or include estimates of such objects into floorplans generated by the system. Such measurements could be obtained by looking up dimensions of objects (e.g., refrigerators, stoves, washing machines, toilets, etc.) in a database using detected makes/brands of such objects. Further, the system could utilize measurements of other objects, such as countertop measurements, in order to estimate measurements of room features, such as wall measurements. Still further, the floorplans estimated by the present system could be utilized to estimate other parameters of a particular structure, such as the type of construction of the structure. Additionally, it is contemplated that



previous (stored) information relating to building/construction materials could be utilized with the system in order to predict materials in a particular structure undergoing estimation by the system. Finally, it is noted that the system could generate multiple floorplans of a particular structure, which floorplans could then be “assembled” to form a model of the entire structure (e.g., assembling floorplans of each room in the structure until an entire model of the structure is generated).

(47) Having thus described the system and method in detail, it is to be understood that the foregoing description is not intended to limit the spirit or scope thereof. It will be understood that the embodiments of the present disclosure described herein are merely exemplary and that a person skilled in the art may make any variations and modification without departing from the spirit and scope of the disclosure. All such variations and modifications, including those discussed above, are intended to be included within the scope of the disclosure.

## Claims

1. A system for generating computerized models of structures, the system comprising: an input device including one or more sensors, the input device configured to: capture, via the one or more sensors, raw data of at least one structure disposed in a physical space and including a plurality of large-scale structure features and a plurality of small-scale structure features, wherein the large-scale structure features and small-scale structure features include geometric features; a computing system coupled to the input device and including, a processor, a display, and a memory, the computing system programmed to: receive the raw data; process the raw data using a data fusion process to produce fused data; extract the geometric features from the fused data; reconstruct the plurality of large-scale structure features using the extracted geometric features to generate a floor contour or polyhedron representing the plurality of large-scale structure features; reconstruct the small-scale structure features within the floor contour or polyhedron using the extracted geometric features; store the large-scale structure features and small-scale features; generate a three-dimensional visual representation of a reconstructed model of the at least one structure using the large-scale structure features and small-scale features; and display, on the display, the three-dimensional visual representation of the reconstructed model of the at least one structure; wherein the raw data comprises one or more of: RGB image data, infrared image data, mobile sensors data, point cloud data, LIDAR data, global positioning system (GPS) data, X-ray data, magnetic field data, and depth maps data; and wherein the computing system is programmed to: detect the type of raw data is point cloud data, in response to receiving the raw data; identify one or more major planes in the raw data; flatten the one or more planes by projecting points of the one or more plane onto the one or more planes; identify at least one floor plane and at least one wall plane; identify one or more corner points formed by the joining of the at least one floor plane and at least one wall plane; generate a fine mesh horizontal grid including a plurality of cells; assign values to the plurality of cells in the grid; identify one or more floor plans including a plurality of edges, based on the identified one or more corner points; and assign a score to each of the one or more floor plans, wherein the score is calculated based on a comparison of the plurality of edges and the plurality of the cells in the grid.

2. The system of claim 1, wherein the geometry features include one or more of: edges lines, planes, points and corners.

3. The system of claim 1, wherein the large-scale structure features include one or more of: walls, ceilings and floors.

4. The system of claim 1, wherein the computing system reconstructs the large-scale structure features using the extracted geometry features by: identifying one or more of the extracted geometry features corresponding a ceiling and floor of the at least one structure; identifying one or more of the extracted geometry features corresponding to one or more walls of the at least one

structure; straightening the one or more walls; identifying adjacent walls from the one or more walls; and squaring an angle formed by adjacent walls.

5. The system of claim 1, wherein the small-scale structure features include one or more of: room types, materials, wall features and fixtures.

6. The system of claim 1, wherein the computing system is configured to identify the at least one floor plane and the at least one wall plane based on a user interaction with the display.

7. The system of claim 1, further comprising an image capturing device coupled to the input device, the image capturing device configured to: capture one or more images of a roof face of the at least one structure; and transmit the one or more images of the roof face of the at least one structure.

8. The system in claim 7, wherein in response to displaying on the display the reconstructed model of the at least one structure, the computing system further programmed to: receive the one or more images of the roof face of the at least one structure; determine a pixel size of the one or more images; map the one or more images to the reconstructed model of the at least one structure; identify one or more areas of damage in the one or more images; and determine an amount of the one or more areas of damage exceeds a predetermined threshold amount.

9. The system of claim 1, wherein the computing system is one of: a mobile device or a remote structure modeling server.

10. The system of claim 1, wherein the one or more sensors are one or more of: image capturing device, laser scanners, scanning range finders, RGB-D sensors, mobile sensors.

11. The system of claim 1, wherein the input device is one of: smart phones, tablet computers, laptop computers, wearable computers, robots or Unmanned Aerial Vehicle (UAVs).

12. A method for generating computerized models of structures, the method comprising: capturing, via an input device including one or more sensors, using the one or more sensors, raw data of at least one structure disposed in physical space and including a plurality of large-scale structure features and a plurality of small-scale structure features, wherein the large-scale structure features and small-scale structure features include geometric features, and wherein the raw data comprises one or more of: RGB image data, infrared image data, mobile sensors data, point cloud data, LIDAR data, global positioning system (GPS) data, X-ray data, magnetic field data, and depth maps data; transmitting, via the input device, the raw data; receiving, via the computing system, the raw data; processing the raw data using a data fusion process to produce fused data; storing, via the computing system, the fused data; extracting, via the computing system, the geometric features from the fused data; reconstructing, via the computing system, the plurality of large-scale structure features using the extracted geometric features to generate a floor contour or polyhedron representing the plurality of large-scale structure features; reconstructing, via the computing system, the small-scale structure features within the floor contour or polyhedron using the extracted geometric features; storing, via the computing system, the large-scale structure features and small-scale features; generating, via the computing system, a three-dimensional visual representation of a reconstructed model of the at least one structure using the large-scale structure features and small-scale features; and displaying, via the computing system, on the display the three-dimensional visual representation of the reconstructed model the reconstructed model of the at least one structure; detecting, via the computing system, the type of raw data is point cloud data, in response to receiving the raw data; identifying, via the computing system, one or more major planes in the raw data; flattening, via the computing system, the one or more planes by projecting points of the one or more plane onto the one or more planes; identifying, via the computing system, at least one floor plane and at least one wall plane; identifying, via the computing system, one or more corner points formed by the joining of the at least one floor plane and at least one wall plane; generating, via the computing system, a fine mesh horizontal grid including a plurality of cells; assigning, via the computing system, values to the plurality of cells in the grid; identifying, via the computing system, one or more floor plans including a plurality of edges, based on the identified one or more

corner points; and assigning, via the computing system, a score to each of the one or more floor plans, wherein the score is calculated based on a comparison of the plurality of edges and the plurality of the cells in the grid.

13. The method of claim 12, wherein reconstructing the large-scale structure features using the extracted geometry features further comprising: identifying, via the computing system, one or more of the extracted geometry features corresponding a ceiling and a floor of the at least one structure; identifying, via the computing system, one or more of the extracted geometry features corresponding to one or more walls of the at least one structure; straightening, via the computing system, the one or more walls; identifying, via the computing system, adjacent walls from the one or more walls; and squaring, via the computing system, an angle formed by adjacent walls.

14. The method of claim 12, further comprising: capturing, via an image capturing device coupled to the input device, one or more images of a roof face of the at least one structure; and transmitting, via the input device, the one or more images of the roof face of the at least one structure.

15. The method in claim 14, wherein in response to displaying on the display the reconstructed model of the at least one structure, the method further comprising: receiving, via the computing system, the one or more images of the roof face of the at least one structure; determining, via the computing system, a pixel size of the one or more images; mapping, via the computing system, the one or more images to the reconstructed model of the at least one structure; identifying, via the computing system, one or more areas of damage in the one or more images; and determining, via the computing system, an amount of the one or more areas of damage exceeds a predetermined threshold amount.

16. A non-transitory computer readable medium storing computer executable instructions thereupon for generating computerized models of structures, the instructions when executed by a processor cause the processor to: capture, via an input device including one or more sensors, using the one or more sensors, raw data of at least one structure disposed in a physical space and including a plurality of large-scale structure features and a plurality of small-scale structure features, wherein the large-scale structure features and small-scale structure features include geometric features; transmit, via the input device, the raw data; receive, via the computing system, the raw data; processing the raw data using a data fusion process to produce fused data; store, via the computing system, the fused data; extract, via the computing system, the geometry features from the fused data; reconstruct, via the computing system, the plurality of large-scale structure features using the extracted geometry features to generate a floor contour or polyhedron representing the plurality of large-scale structure features; reconstruct, via the computing system, the small-scale structure features within the floor contour or the polyhedron using the extracted geometry features; store, via the computing system, the large-scale structure features and small-scale features; generate, via the computing system, a three-dimensional visual representation of a reconstructed model of the at least one structure using the large-scale structure features and small-scale features; and display, via the computing system, on the display the three-dimensional visual representation of the reconstructed model of the at least one structure; wherein the raw data comprises one or more of: RGB image data, infrared image data, mobile sensors data, point cloud data, LIDAR data, global positioning system (GPS) data, X-ray data, magnetic field data, and depth maps data; and wherein the instructions, when executed by the processor, further cause the processor to: detect, via the computing system, the type of raw data is point cloud data, in response to receiving the raw data; calculate, via the computing system, one or more raw lines from the point cloud data; calculate, via the computing system, main guidelines based on the one or more raw lines; calculate, via the computing system, a pivot point from one or more intersection points of the main guidelines; identify, via the computing system, an orthogonal facade for the at least one structure; identify, via the computing system, one or more rooms of the at least one structure based on the main guidelines, the pivot point and orthogonal facade; generate, via the computing system, a visual representation of the one or more rooms of the at least on structure; and display, via the

computing system, on the display the visual representation of the one or more rooms of the at least one structure.

17. The non-transitory computer readable medium of claim 16, wherein reconstructing the large-scale structure features using the extracted geometry features, when executed by the processor, further cause the processor to: identify, via the computing system, one or more of the extracted geometry features corresponding a ceiling and a floor of the at least one structure; identify, via the computing system, one or more of the extracted geometry features corresponding to one or more walls of the at least one structure; straighten, via the computing system, the one or more walls; identify, via the computing system, adjacent walls from the one or more walls; and square, via the computing system, an angle formed by adjacent walls.

18. The non-transitory computer readable medium of claim 16, wherein the instructions, when executed by the processor, further cause the processor to: capture, via an image capturing device coupled to the input device, one or more images of a roof face of the at least one structure; and transmit, via the input device, the one or more images of the roof face of the at least one structure.

19. The non-transitory computer readable medium of claim 18, wherein the instructions, when executed by the processor, further cause the processor to: receive, via the computing system, the one or more images of the roof face of the at least one structure; determine, via the computing system, a pixel size of the one or more images; map, via the computing system, the one or more images to the reconstructed model of the at least one structure; identify, via the computing system, one or more areas of damage in the one or more images; and determine, via the computing system, an amount of the one or more areas of damage exceeds a predetermined threshold amount.

20. A system for generating computerized models of structures, the system comprising: an input device including one or more sensors, the input device configured to: capture, via the one or more sensors, raw data of at least one structure disposed in a physical space and including a plurality of large-scale structure features and a plurality of small-scale structure features, wherein the large-scale structure features and small-scale structure features include geometric features; a computing system coupled to the input device and including, a processor, a display, and a memory, the computing system programmed to: receive the raw data; process the raw data using a data fusion process to produce fused data; extract the geometric features from the fused data; reconstruct the plurality of large-scale structure features using the extracted geometric features to generate a floor contour or polyhedron representing the plurality of large-scale structure features; reconstruct the small-scale structure features within the floor contour or polyhedron using the extracted geometric features; store the large-scale structure features and small-scale features; generate a three-dimensional visual representation of a reconstructed model of the at least one structure using the large-scale structure features and small-scale features; and display, on the display, the three-dimensional visual representation of the reconstructed model of the at least one structure; wherein the raw data comprises one or more of: RGB image data, infrared image data, mobile sensors data, point cloud data, LIDAR data, global positioning system (GPS) data, X-ray data, magnetic field data, and depth maps data; and wherein the computing system is programmed to: detect the type of raw data is point cloud data, in response to receiving the raw data; calculate one or more raw lines from the point cloud data; calculate main guidelines based on the one or more raw lines; calculate a pivot point from one or more intersection points of the main guidelines; identify an orthogonal façade for the at least one structure; identify one or more rooms of the at least one structure based on the main guidelines, the pivot point and orthogonal façade; generate a visual representation of the one or more rooms of the at least on structure; and display on the display the visual representation of the one or more rooms of the at least one structure.

21. A system for generating computerized models of structures, the system comprising: an input device including one or more sensors, the input device configured to: capture, via the one or more sensors, raw data of at least one structure disposed in a physical space and including a plurality of large-scale structure features and a plurality of small-scale structure features, wherein the large-

scale structure features and small-scale structure features include geometric features; a computing system coupled to the input device and including, a processor, a display, and a memory, the computing system programmed to: receive the raw data; process the raw data using a data fusion process to produce fused data; extract the geometric features from the fused data; reconstruct the plurality of large-scale structure features using the extracted geometric features to generate a floor contour or polyhedron representing the plurality of large-scale structure features; reconstruct the small-scale structure features within the floor contour or polyhedron using the extracted geometric features; store the large-scale structure features and small-scale features; generate a three-dimensional visual representation of a reconstructed model of the at least one structure using the large-scale structure features and small-scale features; and display, on the display, the three-dimensional visual representation of the reconstructed model of the at least one structure; wherein the raw data comprises one or more of: RGB image data, infrared image data, mobile sensors data, point cloud data, LIDAR data, global positioning system (GPS) data, X-ray data, magnetic field data, and depth maps data; and wherein the computing system is programmed to: detect the type of raw data is point cloud data, in response to receiving the raw data; extract a main axis from the point cloud data; create a fine mesh horizontal grid including a plurality of cells; assign a value to each of the plurality of cells; calculate main guidelines; calculate corners based on one or more intersection points of one or more lines; identify one or more walls of the least one structure based on the calculated corners; generate a first floor plan of the at least one structure; compare a second floor plan to the first floor plan of the at least one structure; and assign a score to the second floor plan based on the comparison of the second floor plan and the first plan of the at least one structure.

22. A system for generating computerized models of structures, the system comprising: an input device including one or more sensors, the input device configured to: capture, via the one or more sensors, raw data of at least one structure disposed in a physical space and including a plurality of large-scale structure features and a plurality of small-scale structure features, wherein the large-scale structure features and small-scale structure features include geometric features; a computing system coupled to the input device and including, a processor, a display, and a memory, the computing system programmed to: receive the raw data; process the raw data using a data fusion process to produce fused data; extract the geometric features from the fused data; reconstruct the plurality of large-scale structure features using the extracted geometric features to generate a floor contour or polyhedron representing the plurality of large-scale structure features; reconstruct the small-scale structure features within the floor contour or polyhedron using the extracted geometric features; store the large-scale structure features and small-scale features; generate a three-dimensional visual representation of a reconstructed model of the at least one structure using the large-scale structure features and small-scale features; and display, on the display, the three-dimensional visual representation of the reconstructed model of the at least one structure; wherein the raw data comprises one or more of: RGB image data, infrared image data, mobile sensors data, point cloud data, LIDAR data, global positioning system (GPS) data, X-ray data, magnetic field data, and depth maps data; and wherein the computing system is programmed to: detect the type of raw data is point cloud data captured at a first-person perspective view, in response to receiving the raw data; receiving a user interaction on the display identifying at least one wall of the at least one structure in the point cloud data; project an infinite ray into the point cloud data; determine one or more intersection points of the infinite ray and the point cloud data; execute a region growing plane algorithm based on the one or more intersection points of the infinite ray and the point cloud data; extract at least one plane of the at least one wall in response to the execution of the region growing plane algorithm; calculate one or more intersection points of the at least one wall and at least one floor or at least one ceiling of the at least one structure; and display, on the display, the floor contour or the polyhedron.

23. A method for generating computerized models of structures, the method comprising: capturing, via an input device including one or more sensors, using the one or more sensors, raw data of at

least one structure disposed in physical space and including a plurality of large-scale structure features and a plurality of small-scale structure features, wherein the large-scale structure features and small-scale structure features include geometric features, and wherein the raw data comprises one or more of: RGB image data, infrared image data, mobile sensors data, point cloud data, LIDAR data, global positioning system (GPS) data, X-ray data, magnetic field data, and depth maps data; transmitting, via the input device, the raw data; receiving, via the computing system, the raw data; processing the raw data using a data fusion process to produce fused data; storing, via the computing system, the fused data; extracting, via the computing system, the geometric features from the fused data; reconstructing, via the computing system, the plurality of large-scale structure features using the extracted geometric features to generate a floor contour or polyhedron representing the plurality of large-scale structure features; reconstructing, via the computing system, the small-scale structure features within the floor contour or polyhedron using the extracted geometric features; storing, via the computing system, the large-scale structure features and small-scale features; generating, via the computing system, a three-dimensional visual representation of a reconstructed model of the at least one structure using the large-scale structure features and small-scale features; displaying, via the computing system, on the display the three-dimensional visual representation of the reconstructed model the reconstructed model of the at least one structure; detecting, via the computing system, the type of raw data is point cloud data, in response to receiving the raw data; calculating, via the computing system, one or more raw lines from the point cloud data; calculating, via the computing system, main guidelines based on the one or more raw lines; calculating, via the computing system, a pivot point from one or more intersection points of the main guidelines; identifying, via the computing system, an orthogonal façade for the at least one structure; identifying, via the computing system, one or more rooms of the at least one structure based on the main guidelines, the pivot point and orthogonal façade; generating, via the computing system, a visual representation of the one or more rooms of the at least on structure; and displaying, via the computing system, on the display the visual representation of the one or more rooms of the at least one structure.

24. A method for generating computerized models of structures, the method comprising: capturing, via an input device including one or more sensors, using the one or more sensors, raw data of at least one structure disposed in physical space and including a plurality of large-scale structure features and a plurality of small-scale structure features, wherein the large-scale structure features and small-scale structure features include geometric features, and wherein the raw data comprises one or more of: RGB image data, infrared image data, mobile sensors data, point cloud data, LIDAR data, global positioning system (GPS) data, X-ray data, magnetic field data, and depth maps data; transmitting, via the input device, the raw data; receiving, via the computing system, the raw data; processing the raw data using a data fusion process to produce fused data; storing, via the computing system, the fused data; extracting, via the computing system, the geometric features from the fused data; reconstructing, via the computing system, the plurality of large-scale structure features using the extracted geometric features to generate a floor contour or polyhedron representing the plurality of large-scale structure features; reconstructing, via the computing system, the small-scale structure features within the floor contour or polyhedron using the extracted geometric features; storing, via the computing system, the large-scale structure features and small-scale features; generating, via the computing system, a three-dimensional visual representation of a reconstructed model of the at least one structure using the large-scale structure features and small-scale features; displaying, via the computing system, on the display the three-dimensional visual representation of the reconstructed model the reconstructed model of the at least one structure; detecting, via the computing system, the type of raw data is point cloud data, in response to receiving the raw data; extracting, via the computing system, a main axis from the point cloud data; creating, via the computing system, a fine mesh horizontal grid including a plurality of cells; assigning, via the computing system, a value to each of the plurality of cells; calculating, via the

computing system, main guidelines; calculating, via the computing system, corners based on one or more intersection points of one or more lines; identifying, via the computing system, one or more walls of the least one structure based on the calculated corners; generating, via the computing system, a first floor plan of the at least one structure; comparing, via the computing system, a second floor plan to the first floor plan of the at least one structure; and assigning, via the computing system, a score to the second floor plan based on the comparison of the second floor plan and the first plan of the at least one structure.

25. A method for generating computerized models of structures, the method comprising: capturing, via an input device including one or more sensors, using the one or more sensors, raw data of at least one structure disposed in physical space and including a plurality of large-scale structure features and a plurality of small-scale structure features, wherein the large-scale structure features and small-scale structure features include geometric features, and wherein the raw data comprises one or more of: RGB image data, infrared image data, mobile sensors data, point cloud data, LIDAR data, global positioning system (GPS) data, X-ray data, magnetic field data, and depth maps data; transmitting, via the input device, the raw data; receiving, via the computing system, the raw data; processing the raw data using a data fusion process to produce fused data; storing, via the computing system, the fused data; extracting, via the computing system, the geometric features from the fused data; reconstructing, via the computing system, the plurality of large-scale structure features using the extracted geometric features to generate a floor contour or polyhedron representing the plurality of large-scale structure features; reconstructing, via the computing system, the small-scale structure features within the floor contour or polyhedron using the extracted geometric features; storing, via the computing system, the large-scale structure features and small-scale features; generating, via the computing system, a three-dimensional visual representation of a reconstructed model of the at least one structure using the large-scale structure features and small-scale features; displaying, via the computing system, on the display the three-dimensional visual representation of the reconstructed model the reconstructed model of the at least one structure; detecting, via the computing system, the type of raw data is point cloud data captured at a first-person perspective view, in response to receiving the raw data; receiving, via the computing system, a user interaction on the display identifying at least one wall of the at least one structure in the point cloud data; projecting, via the computing system, an infinite ray into the point cloud data; determining, via the computing system, one or more intersection points of the infinite ray and the point cloud data; executing, via the computing system, a region growing plane algorithm based on the one or more intersection points of the infinite ray and the point cloud data; extracting, via the computing system, at least one plane of the at least one wall in response to the execution of the region growing plane algorithm; calculating, via the computing system, one or more intersection points of the at least one wall and at least one floor or at least one ceiling of the at least one structure; and displaying, via the computing system, on the display, the floor contour or the polyhedron.

26. A non-transitory computer readable medium storing computer executable instructions thereupon for generating computerized models of structures, the instructions when executed by a processor cause the processor to: capture, via an input device including one or more sensors, using the one or more sensors, raw data of at least one structure disposed in a physical space and including a plurality of large-scale structure features and a plurality of small-scale structure features, wherein the large-scale structure features and small-scale structure features include geometric features, and wherein the raw data comprises one or more of: RGB image data, infrared image data, mobile sensors data, point cloud data, LIDAR data, global positioning system (GPS) data, X-ray data, magnetic field data, and depth maps data; transmit, via the input device, the raw data; receive, via the computing system, the raw data; processing the raw data using a data fusion process to produce fused data; store, via the computing system, the fused data; extract, via the computing system, the geometry features from the fused data; reconstruct, via the computing

system, the plurality of large-scale structure features using the extracted geometry features to generate a floor contour or polyhedron representing the plurality of large-scale structure features; reconstruct, via the computing system, the small-scale structure features within the floor contour or the polyhedron using the extracted geometry features; store, via the computing system, the large-scale structure features and small-scale features; generate, via the computing system, a three-dimensional visual representation of a reconstructed model of the at least one structure using the large-scale structure features and small-scale features; display, via the computing system, on the display the three-dimensional visual representation of the reconstructed model of the at least one structure; wherein the instructions, when executed by the processor, further cause the processor to: detect, via the computing system, the type of raw data is point cloud data, in response to receiving the raw data; extract, via the computing system, a main axis from the point cloud data; create, via the computing system, a fine mesh horizontal grid including a plurality of cells; assign, via the computing system, a value to each of the plurality of cells; calculate, via the computing system, main guidelines; calculate, via the computing system, corners based on one or more intersection points of one or more lines; identify, via the computing system, one or more walls of the least one structure based on the calculated corners; generate, via the computing system, a first floor plan of the at least one structure; compare, via the computing system, a second floor plan to the first floor plan of the at least one structure; and assign, via the computing system, a score to the second floor plan based on the comparison of the second floor plan and the first plan of the at least one structure.

27. A non-transitory computer readable medium storing computer executable instructions thereupon for generating computerized models of structures, the instructions when executed by a processor cause the processor to: capture, via an input device including one or more sensors, using the one or more sensors, raw data of at least one structure disposed in a physical space and including a plurality of large-scale structure features and a plurality of small-scale structure features, wherein the large-scale structure features and small-scale structure features include geometric features, and wherein the raw data comprises one or more of: RGB image data, infrared image data, mobile sensors data, point cloud data, LIDAR data, global positioning system (GPS) data, X-ray data, magnetic field data, and depth maps data; transmit, via the input device, the raw data; receive, via the computing system, the raw data; processing the raw data using a data fusion process to produce fused data; store, via the computing system, the fused data; extract, via the computing system, the geometry features from the fused data; reconstruct, via the computing system, the plurality of large-scale structure features using the extracted geometry features to generate a floor contour or polyhedron representing the plurality of large-scale structure features; reconstruct, via the computing system, the small-scale structure features within the floor contour or the polyhedron using the extracted geometry features; store, via the computing system, the large-scale structure features and small-scale features; generate, via the computing system, a three-dimensional visual representation of a reconstructed model of the at least one structure using the large-scale structure features and small-scale features; display, via the computing system, on the display the three-dimensional visual representation of the reconstructed model of the at least one structure; wherein the instructions, when executed by the processor, further cause the processor to: detect, via the computing system, the type of raw data is point cloud data captured at a first-person perspective view, in response to receiving the raw data; receive, via the computing system, a user interaction on the display identifying at least one wall of the at least one structure in the point cloud data; project, via the computing system, an infinite ray into the point cloud data; determine, via the computing system, one or more intersection points of the infinite ray and the point cloud data; execute, via the computing system, a region growing plane algorithm based on the one or more intersection points of the infinite ray and the point cloud data; extract, via the computing system, at least one plane of the at least one wall in response to the execution of the region growing plane algorithm; calculate, via the computing system, one or more intersection points of the at least one



wall and at least one floor or at least one ceiling of the at least one structure; and display, via the computing system, on the display, the floor contour or the polyhedron.

---