

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12401224
B2
August 26, 2025
Fujimoto; Hiroshi et al.

Wireless power reception system, moving body, and wheel

Abstract

A wireless power reception system **1** includes: a power reception device **5** including a power reception coil **51** that receives power supplied wirelessly from a power transmission coil **41** of a power transmission device **4** installed in a road surface, at least a portion of the power reception coil **51** being housed in a wheel **3** of a moving body **2**; and a driving device **61** which is installed in the wheel **3** and which drives the wheel **3** with power received by the power reception device **5**, wherein the power reception device **5** is provided with a converter **56a** and an inverter **56b**, at least a portion of the converter **56a** and at least a portion of the inverter **56b** are housed in the wheel **3**, the converter **56a** is positioned vertically above the power reception coil **51**, and the inverter **56b** is positioned vertically above the converter **56a**.

Inventors:	Fujimoto; Hiroshi (Tokyo, JP), Shimizu; Osamu (Tokyo, JP), Akutagawa; Keizo (Tokyo, JP), Wakao; Yasumichi (Tokyo, JP), Kuwayama; Isao (Tokyo, JP), Gunji; Daisuke (Fujisawa, JP)
Applicant:	THE UNIVERSITY OF TOKYO (Tokyo, JP); BRIDGESTONE CORPORATION (Tokyo, JP); NSK Ltd. (Tokyo, JP)
Family ID:	1000008779717
Assignee:	THE UNIVERSITY OF TOKYO (Tokyo, JP); BRIDGESTONE CORPORATION (Tokyo, JP); NSK Ltd. (Tokyo, JP)
Appl. No.:	17/754671
Filed (or PCT Filed):	September 10, 2020
PCT No.:	PCT/JP2020/034378
PCT Pub. No.:	WO2021/070555
PCT Pub. Date:	April 15, 2021

Prior Publication Data

Document Identifier

US 20220416580 A1

Publication Date

Dec. 29, 2022

Foreign Application Priority Data

JP 2019-186311 Oct. 09, 2019

Publication Classification

Int. Cl.: B60L53/20 (20190101); B60L9/18 (20060101); H02J50/00 (20160101); H02J50/10 (20160101)

U.S. Cl.:

CPC H02J50/10 (20160201); B60L9/18 (20130101); B60L53/20 (20190201); H02J50/005 (20200101); H02J2310/48 (20200101)

Field of Classification Search

CPC: H02J (50/005)

USPC: 320/108

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8975864	12/2014	Kim	N/A	N/A
10008881	12/2017	Lee et al.	N/A	N/A
11171520	12/2020	Kanno	N/A	N/A
2018/0111473	12/2017	Fujimoto et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102648110	12/2014	CN	N/A
106143185	12/2015	CN	N/A
107979183	12/2017	CN	N/A
2005269735	12/2004	JP	N/A
2014195350	12/2013	JP	N/A
2015116068	12/2014	JP	N/A
2016076605	12/2015	JP	N/A
6298509	12/2017	JP	N/A
2018050363	12/2017	JP	N/A
2018068077	12/2017	JP	N/A
2019047691	12/2018	JP	N/A
2019057959	12/2018	JP	N/A
2019170017	12/2018	JP	N/A

OTHER PUBLICATIONS

Jun. 5, 2024, search result of Office Action issued by the China National Intellectual Property Administration in the corresponding Chinese Patent Application No. 202080071068.2. cited by applicant

Apr. 12, 2022, International Preliminary Report on Patentability issued in the International Patent Application No. PCT/JP2020/034378. cited by applicant

Sep. 28, 2023, search result of the Extended European Search Report issued by the European Patent Office in the corresponding European Patent Application No. 20874599.2. cited by applicant

Osamu Shimizu et al., Mutual Inductance Modeling of In-wheel Arc-shaped Coil for In-motion WPT, 2019 IEEE Wireless Power Transfer Conference (WPTC), 2019, pp. 624-628, XP033753519. cited by applicant

Oct. 27, 2023, search result of Office Action issued by the China National Intellectual Property Administration in the corresponding Chinese Patent Application No. 202080071068.2. cited by applicant

Nov. 17, 2020, International Search Report issued in the International Patent Application No. PCT/JP2020/034378. cited by applicant

Primary Examiner: Tso; Edward

Assistant Examiner: Omar; Ahmed H

Attorney, Agent or Firm: KENJA IP LAW PC

Background/Summary**TECHNICAL FIELD**

(1) The present disclosure relates to a wireless power reception system, a moving body, and a wheel.

BACKGROUND

(2) In the related art, a wireless power transfer technology is known in which a power transmission device provided in a road surface, such as a road or a parking lot, supplies power wirelessly to a power reception device installed in a vehicle. For example, PTL 1 discloses a vehicle provided with a power reception device on the underside of the vehicle, which enables the vehicle to receive power from a power transmission device provided in a road surface.

CITATION LIST**Patent Literature**

(3) PTL 1: Japanese Patent Laid-Open No. 2018-068077

SUMMARY**Technical Problem**

(4) However, in the wireless power transfer technology of the related art described above, if the power transmission device provided in a road surface such as a road and the power reception device installed in a vehicle that travels on the road are too far apart, an obstacle such as a small animal or piece of metal may come into the space between the power transmission device and the power reception device, eddy currents may be generated around the obstacle, and the power reception efficiency may be lowered. Moreover, the small animal, piece of metal, or the like that has come between the power transmission device and the power reception device may heat up and

catch fire.

(5) A purpose of the present disclosure devised in the light of such circumstances is to provide a wireless power reception system, a moving body, and a wheel that can improve the power reception efficiency in wireless power transfer.

Solution to Problem

(6) A wireless power reception system according to the present disclosure includes: a power reception device including a power reception coil that receives power supplied wirelessly from a power transmission coil of a power transmission device installed in a road surface, at least a portion of the power reception coil being housed in a wheel of a moving body; and a driving device which is installed in the wheel and which drives the wheel with power received by the power reception device, wherein the power reception device is provided with a converter that converts AC power generated in the power reception coil into DC power and an inverter that can convert DC power from the converter into AC power to transmit power to the driving device, at least a portion of the converter and at least a portion of the inverter are housed in the wheel, the converter is positioned vertically above the power reception coil, and the inverter is positioned vertically above the converter.

(7) A moving body according to the present disclosure includes: a wheel; a power reception device including a power reception coil that receives power supplied wirelessly from a power transmission coil of a power transmission device installed in a road surface, at least a portion of the power reception coil being housed in the wheel; and a driving device which is installed in the wheel and which drives the wheel with power received by the power reception device, wherein the power reception device is provided with a converter that converts AC power generated in the power reception coil into DC power and an inverter that can convert DC power from the converter into AC power to transmit power to the driving device, at least a portion of the converter and at least a portion of the inverter are housed in the wheel, the converter is positioned vertically above the power reception coil, and the inverter is positioned vertically above the converter.

(8) A wheel according to the present disclosure is a wheel of a moving body and includes: a power reception device including a power reception coil that receives power supplied wirelessly from a power transmission coil of a power transmission device installed in a road surface; and a driving device that drives the wheel with power received by the power reception device, wherein the power reception device is provided with a converter that converts AC power generated in the power reception coil into DC power and an inverter that can convert DC power from the converter into AC power to transmit power to the driving device, at least a portion of the converter and at least a portion of the inverter are housed in the wheel, the converter is positioned vertically above the power reception coil, and the inverter is positioned vertically above the converter.

Advantageous Effect

(9) According to the present disclosure, it is possible to provide a wireless power reception system, a moving body, and a wheel that can improve the power reception efficiency in wireless power transfer.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In the accompanying drawings:

(2) FIG. 1 is a schematic diagram that uses a lateral cross section of wheels to generally illustrate a wireless power reception system according to an embodiment of the present disclosure;

(3) FIG. 2 is a plan view illustrating one example of a power reception coil as viewed from the axial direction;

(4) FIG. 3 is a cross section of the power reception coil taken along the line A-A in FIG. 2;

- (5) FIG. 4 is a cross section of the power reception coil taken along the line B-B in FIG. 3;
- (6) FIG. 5 is a cross section of the power reception coil taken along the line C-C in FIG. 3;
- (7) FIG. 6 is a perspective view schematically illustrating the winding structure of a wire rod of the power reception coil in FIG. 3;
- (8) FIG. 7 is a schematic diagram that uses a lateral cross section of a wheel to generally illustrate a tire and wheel assembly as one example of a wheel in a wireless power reception system according to an embodiment of the present disclosure;
- (9) FIG. 8 is a schematic diagram that generally illustrates a converter and an inverter of a power reception device housed in the wheel in FIG. 7;
- (10) FIG. 9 is a schematic diagram that generally illustrates an example of a power reception coil installed in a wheel; and
- (11) FIG. 10 is a schematic diagram that generally illustrates another example of a power reception coil installed in a wheel.

DETAILED DESCRIPTION

(12) Hereinafter, a wireless power reception system, moving body, and wheel according to an embodiment of the present disclosure will be described with reference to the drawings. In the drawings, common components and parts are denoted with the same signs. In this specification, the lateral direction of a wheel refers to the direction parallel to the rotation axis of the wheel. The radial direction of a wheel refers to the direction orthogonal to the rotation axis of the wheel.

(13) (Configuration of Wireless Power Reception System)

(14) FIG. 1 illustrates a schematic diagram that uses a lateral cross section of wheels to generally illustrate a wireless power reception system 1 according to an embodiment of the present disclosure. The wireless power reception system 1 is used so that a moving body 2 provided with a wheel 3 receives power from a power transmission device 4 installed in a road surface. The wireless power reception system 1 includes a power reception device 5 and an onboard device 6. The power reception device 5 is housed, at least in part, in the wheel 3 of the moving body 2, and receives power supplied wirelessly from a power transmission device 4 installed in a road surface. The onboard device 6 is installed in the moving body 2 and is electrically connected to the power reception device 5. When the moving body 2 travels or stops over the road surface in which the power transmission device 4 is installed, the power reception device 5 receives power wirelessly from the power transmission device 4. The power reception device 5 transmits the received power to the onboard device 6.

(15) The wireless power reception system 1 may further include a control device 7. The control device 7 is communicably connected to the power reception device 5 and the onboard device 6 through an in-vehicle network such as a controller area network (CAN). The control device 7 can control the power reception device 5 and the onboard device 6 such that power received wirelessly by the power reception device 5 is transmitted to the onboard device 6. The positions and numbers of the wheel 3, power reception device 5, onboard device 6, and control device 7 in the moving body 2 illustrated in FIG. 1 are an example and may be determined freely to suit the purpose and the like of each device.

(16) The moving body 2 can travel over a road surface such as a road via the wheel 3. The moving body 2 is an automobile for example, but is not limited thereto. The moving body 2 may be any vehicle capable of traveling over a road surface via the wheel 3, including an automobile such as a passenger vehicle, a truck, a bus, or a motorcycle, an agricultural vehicle such as a tractor, an industrial or construction vehicle such as a dump truck, an aircraft, a bicycle, or a wheelchair.

(17) The wheel 3 is used to move the moving body 2. The wheel 3 has a contact patch that contacts the road surface such as a road while attached to the moving body 2. In the present embodiment, each wheel 3 is a tire and wheel assembly obtained by mounting a tire 31 onto a wheel 32, but the wheel 3 is not limited thereto and may be any wheel that can be attached to the moving body 2 described above. In the case where the wheel 3 is a tire and wheel assembly, the “contact patch” of

the wheel **3** refers to the contact patch of the tire **31**, or in other words, the surface of the tire **31** that touches the road surface in the state in which the tire **31** is mounted onto an applicable rim, inflated to a prescribed internal pressure, and subjected to a maximum load.

(18) In this specification, an “applicable rim” refers to a valid industrial standard in the region where a pneumatic tire is manufactured and used, namely, an approved rim for an applicable size described in a publication such as the JATMA Year Book of the Japan Automobile Tyre Manufacturers Association (JATMA) in Japan, the Standards Manual of the European Tyre and Rim Technical Organization (ETRTO) in Europe, or the Year Book of the Tire and Rim Association, Inc. (TRA) in the United States or to be described in the future (the Measuring Rim in the ETRTO Standards Manual or the Design Rim in the TRA Year Book), but in the case of a size not described in the above industrial standards, the applicable rim refers to a rim of a width corresponding to the bead width of the pneumatic tire. The “applicable rim” includes current sizes in addition to sizes that may be included in the above industrial standards in the future. The “sizes to be described in the future” may include the sizes described as “Future Developments” in the ETRTO 2013 edition, for example.

(19) In this specification, the “prescribed internal pressure” refers to the air pressure (maximum air pressure) corresponding to the maximum load capability of a single wheel for the applicable size and ply rating described in an industrial standard such as the JATMA Year Book described above, but in the case of a size not described in the above industrial standards, the prescribed internal pressure refers to the air pressure (maximum air pressure) corresponding to the maximum load capability prescribed for each vehicle on which the tires are mounted. Also, in this specification, the “maximum load” refers to the load corresponding to the maximum load capability for a tire of applicable size described in the above industrial standards, or in the case of a size not described in the above industrial standards, the load corresponding to the maximum load capability prescribed for each vehicle on which the tires are mounted.

(20) FIG. **1** illustrates a schematic diagram that uses a lateral cross section of the wheels **3** to generally illustrate a tire and wheel assembly as one example of the wheel **3** in the wireless power reception system **1** according to an embodiment of the present disclosure.

(21) As illustrated in FIG. **1**, each tire **31** includes a pair of bead portions **311**, a pair of sidewall portions **312**, and a tread portion **313**. The bead portions **311** are configured such that the inner radial side and outer lateral side touch a rim portion **321** of the wheel **32** when the tire **31** is mounted onto the rim portion **321**. The sidewall portions **312** extend between the tread portion **313** and the bead portions **311**. The sidewall portions **312** are positioned farther radially outward than the bead portions **311**. The tread portion **313** is positioned farther radially outward than the sidewall portions **312**, and may include the contact patch of the tire **31**.

(22) The tire **31** is formed using a rubber such as natural rubber or synthetic rubber, and may include parts such as a carcass, a belt, and bead wires formed using a metal such as steel. For example, at least a portion of the parts such as the carcass, belt, and bead wires may also be formed using a nonmagnetic material. With this configuration, the strength of the tire **31** can be maintained, while in addition, due to the existence of a metal between the power transmission device **4** and the power reception device **5**, the tire **31** can lessen the attenuation of a magnetic field generated by the power transmission device **4** before the magnetic field reaches the power reception device **5**, and by extension, improve the power reception efficiency of the power reception device **5** when wireless power transfer from the power transmission device **4** to the power reception device **5** is performed by electromagnetic induction, as described later. However, at least a portion of the parts such as the carcass, belt, and bead wires does not have to be formed using a nonmagnetic material.

(23) The nonmagnetic material may include a paramagnetic material or a diamagnetic material having a low permeability. For example, a resin material containing a thermoplastic resin such as polyester or nylon, a thermosetting resin such as a vinyl ester resin or an unsaturated polyester resin, or some other synthetic resin can be used as the nonmagnetic material. Furthermore, fibers of

a material such as glass, carbon, graphite, aramid, polyethylene, or ceramic can be included in the resin material as reinforcing fibers. The nonmagnetic material is not limited to a resin, and any nonmetallic material containing rubber, glass, carbon, graphite, aramid, polyethylene, ceramic, or the like can be used. Furthermore, a metal material containing a paramagnetic material such as aluminum or a diamagnetic material such as copper can be used as the nonmagnetic material.

(24) The wheel **32** includes a cylindrical rim portion **321** for mounting the tire **31** and a disc portion **322** which is provided on the inner radial side of the rim portion **321** and which is supported by and secured to a hub **21** of the moving body **2**.

(25) The wheel **32** may be formed using a metal such as steel, but is not limited thereto. At least a portion of the rim portion **321** of the wheel **32** may also be formed using the nonmagnetic material described above. With this configuration, the strength of the wheel **32** can be maintained, while in addition, due to the existence of a metal such as steel between the power transmission device **4** and the power reception device **5**, the wheel **32** can lessen the attenuation of a magnetic field generated by the power transmission device **4** before the magnetic field reaches the power reception device **5**, and by extension, improve the power reception efficiency of the power reception device **5**.

However, at least a portion of the rim portion **321** of the wheel **32** does not have to be formed using a nonmagnetic material.

(26) Referring to FIG. **1**, the power transmission device **4** is provided with a power transmission coil (primary coil) **41**. The power transmission device **4** is installed in a road surface such as a road or a parking lot. In the present embodiment, the power transmission device **4** is embedded in a road or the like, but may also be installed such that at least a portion is exposed on the road surface. In the diagram, the power transmission coil **41** is illustrated schematically for simplicity.

(27) The power transmission coil **41** generates an AC magnetic field on the basis of an AC current supplied from a power source. In the present embodiment, the power transmission coil **41** is configured into a loop overall. In this specification, the plane enclosed by the looped power transmission coil **41** is also referred to as the coil plane of the power transmission coil **41**. To generate an AC magnetic field directed above the road surface, the power transmission coil **41** is disposed such that the coil plane of the power transmission coil **41** is approximately parallel to the road surface (in other words, the axial direction of the power transmission coil **41** is approximately perpendicular to the road surface). The power transmission coil **41** provided in the power transmission device **4** is wound around a core such as a ferrite core and configured into a loop overall, for example, but is not limited thereto, and may be any type of coil that can generate an AC magnetic field, such as a coil spring or an air core coil. With this configuration, when the wheel **3** passes over the power transmission device **4** while the moving body **2** is traveling or the like, wireless power transfer from the power transmission coil **41** to a power reception coil **51** may be performed by electromagnetic induction.

(28) The power reception device **5** is provided with a power reception coil (secondary coil) **51**. The power reception coil **51** receives power supplied wirelessly from the power transmission coil **41** of the power transmission device **4**. In the present embodiment, the power reception coil **51** is configured into a loop overall. In this specification, the plane enclosed by the looped power reception coil **51** is also referred to as the coil plane of the power reception coil **51**. The power reception coil **51** is disposed such that the coil plane of the power reception coil **51** is approximately parallel to the contact patch of the wheel **3** (in other words, the axial direction of the power reception coil **51** is approximately perpendicular to the road surface). With this arrangement, an electromotive force is generated by electromagnetic induction and a current flows in the power reception coil **51** on the basis of the AC magnetic field generated by the power transmission coil **41**. In the diagram, the power reception coil **51** is illustrated schematically for simplicity.

(29) At least a portion of the power reception coil **51** is housed in the wheel **3** of the moving body **2**. In the present embodiment, at least a portion (preferably all) of the coil plane of the power reception coil **51** faces the contact patch of the wheel **3**. With this arrangement, in the case where

the contact patch of the wheel 3 is positioned above the power transmission coil 41, including the case where the coil plane of the power reception coil 51 does not extend approximately parallel to the contact patch of the wheel 3, at least a portion of the coil plane of the power reception coil 51 can face at least a portion of the coil plane of the power transmission coil 41 with the contact patch of the wheel 3 in between. Consequently, the possibility of an obstacle coming between the power transmission coil 41 and the power reception coil 51 may be lowered, and additionally, the magnetic field lines emitted from the power transmission coil 41 can be received appropriately by the power reception coil 51. Consequently, the power reception efficiency in wireless power transfer may be improved further.

(30) Here, in this specification, (at least a portion of) a plane A “facing” a plane B for example refers to (at least a portion of) the plane A overlapping inside a region extending perpendicular to the plane B in the range over which the plane B extends (in other words, inside the pillar-shaped region having the plane B as its cross section).

(31) In this specification, at least a portion (preferably all) of the contact patch of the wheel 3 faces the coil plane of the power reception coil 51. From the standpoint of further raising the power reception efficiency, it is preferable if at least a portion (preferably all) of the coil plane of the power reception coil 51 faces the contact patch of the wheel 3, and/or at least a portion (preferably all) of the contact patch of the wheel 3 faces the coil plane of the power reception coil 51, like in the present embodiment.

(32) The power reception coil 51 of the power reception device 5 is housed in the wheel 3 of the moving body 2 so as not to rotate together with the wheel 3. For example, as illustrated in FIG. 1, the power reception coil 51 may be installed in a portion that is attached to the wheel 3 from the inner radial side of the wheel 3, such as a cover 21a of the hub 21 in the moving body 2. With this arrangement, at least a portion of the power reception coil 51 is housed on the inner radial side of the wheel 32 in the state where the wheel 32 of the wheel 3 is attached to the hub 21 of the moving body 2.

(33) In addition to the power reception coil 51, the power reception device 5 additionally may be provided with a power converter, a power storage unit, a measurement unit, and the like.

(34) The power converter is provided with a converter that converts AC power to DC power, an inverter that converts DC power to AC power, and the like.

(35) The power storage unit stores power generated in the power reception coil 51. The power storage unit may be a capacitor, for example. In the case where the power storage unit is a capacitor, charging and discharging can be performed in a short time compared to a storage battery or the like, which is advantageous in situations demanding high responsiveness.

(36) The measurement unit measures the strength of the power received by the power reception device 5. The measurement unit is a voltmeter or an ammeter for example, but is not limited thereto. The strength of the power measured by the measurement unit may include numerical information of any type, such as electric power, electric energy, voltage, current, magnetic flux, or magnetic flux density for example.

(37) Hereinafter, FIGS. 2 to 6 will be referenced to describe an example of the power reception device 5 more specifically. The power reception device 5 is provided with the power reception coil 51 and a coil case 55. FIG. 2 is a plan view illustrating the power reception coil 51 as viewed from the direction orthogonal to the coil plane. FIG. 3 is a cross section of the power reception coil 51 and the coil case 55 taken along the line A-A in FIG. 2. FIG. 4 is a cross section of the power reception coil 51 and the coil case 55 taken along the line B-B in FIG. 3, and FIG. 5 is a cross section of the power reception coil 51 and the coil case 55 taken along the line C-C in FIG. 3. FIG. 6 is a perspective view schematically illustrating the winding structure of a wire rod 53 forming the power reception coil 51. Note that in FIGS. 4 and 5, the wire rod 53 is omitted from illustration to make it easy to understand the shapes of spiral grooves 55g and 55h. In FIG. 6, a first spiral coil layer 52a is indicated by dashed lines and a second spiral coil layer 52b is indicated by solid lines.

(38) The power reception coil **51** can be configured in a multilayer structure including a stacked plurality of spiral coil layers **52a** and **52b**. The power reception coil **51** illustrated in FIGS. 2 to 6 has a two-layer structure including a first spiral coil layer **52a** and a second spiral coil layer **52b** stacked on top of one another. The power reception coil **51** is disposed such that the first spiral coil layer **52a** faces the power transmission coil **41**. In the power reception coil **51** installed in the moving body **2**, the first spiral coil layer **52a** is positioned lower than the second spiral coil layer **52b** in the vertical direction. Note that the power reception coil **51** may also have three or more stacked spiral coil layers.

(39) As illustrated in FIG. 2, the first spiral coil layer **52a** and the second spiral coil layer **52b** are placed on top of each other such that their central axes are positioned on the same straight line.

(40) The spiral coil layers **52a** and **52b** are formed by winding the wire rod **53** into a spiral shape on the same surface (in this example, in the same plane). The extension direction of the central axes of the spiral coil layers **52a** and **52b** obtained by the winding of the wire rod **53** is treated as the axial direction of the power reception coil **51**.

(41) The wire rod **53** forming each of the spiral coil layers **52a** and **52b** is continuous throughout. The wire rod **53** forming the first spiral coil layer **52a** and the wire rod **53** forming the second spiral coil layer **52b** are continuous in an inner circumferential peripheral portion of each of the spiral coil layers **52a** and **52b**. In other words, a connecting portion **54** between the first spiral coil layer **52a** and the second spiral coil layer **52b** is positioned in an inner circumferential peripheral portion of the power reception coil **51** (an inner circumferential peripheral portion of each of the spiral coil layers **52a** and **52b**). Note that the wire rod **53** forming the first spiral coil layer **52a** and the wire rod **53** forming the second spiral coil layer **52b** do not have to be continuous in an inner circumferential peripheral portion of each of the spiral coil layers **52a** and **52b**. Moreover, the position of the connecting portion **54** is not limited to the inner circumferential peripheral portion of the power reception coil **51**, and may also be provided in an outer circumferential peripheral portion of the power reception coil **51**, for example. The wire rod **53** forming the first spiral coil layer **52a** and the wire rod **53** forming the second spiral coil layer **52b** may be joined by welding, pressure welding, or the like in the connecting portion **54**, or as described later, the first spiral coil layer **52a** and the second spiral coil layer **52b**, including the connecting portion **54**, may be formed by winding a single continuous wire rod **53**.

(42) The connecting portion **54** is preferably inclined with respect to the axial direction of the power reception coil **51**, but may also be parallel to the axial direction of the power reception coil **51** (perpendicular to the coil plane of the power reception coil **51**). In this example, the connecting portion **54** is inclined gently in the thickness direction of the power reception coil **51**. Specifically, the connecting portion **54** is inclined so as to intersect with both the wire rod **53** forming the first spiral coil layer **52a** and the wire rod **53** forming the second spiral coil layer **52b** at obtuse angles (angles greater than 90° and less than 180°).

(43) The first spiral coil layer **52a** and the second spiral coil layer **52b** are formed by winding a single continuous wire rod **53**. That is, the first spiral coil layer **52a** and the second spiral coil layer **52b**, including the connecting portion **54**, are formed by a single continuous wire rod **53**. Note that a “single continuous wire rod **53**” means a wire rod formed integrally as a whole, and includes litz wire containing multiple twisted strands of enameled wires, for example. Moreover, the wire rod **53** is preferably litz wire, but is not limited thereto and may also be solid wire, for example.

(44) As illustrated in FIG. 6, the wire rod **53** forming the power reception coil **51** extends in a spiral from a winding start end (an end **53a** of the wire rod **53**) positioned on the outer circumferential peripheral side of the first spiral coil layer **52a** and proceeding radially inward to form an approximately rectangular (more specifically, an approximately square) coil plane overall, joins the connecting portion **54** inclined with respect to the coil plane in the inner circumferential peripheral portion, and the connecting portion **54** smoothly joins the inner circumferential peripheral portion of the second spiral coil layer **52b**. In addition, the wire rod **53** extends in a spiral shape from the

inner circumferential peripheral portion of the second spiral coil layer 52b proceeding radially outward similarly to the first spiral coil layer 52a, and a winding terminal end (another end 53b of the wire rod 53) is positioned on the outer circumferential peripheral side. The end 53a and the other end 53b of the wire rod 53 are disposed on the same side surface 55f of the rectangular plate-shaped coil case 55 described later. Also, the end 53a and the other end 53b of the wire rod 53 are respectively positioned near either end of the side surface 55f in the longitudinal direction. By adopting such a configuration, the end 53a and the other end 53b can be disposed at positions that are farther apart.

(45) The power reception device 5 is provided with the coil case 55 that supports the wire rod 53. The coil case 55 includes a case body 55a (wire rod support portion) formed using a resin containing an insulating material, a first cover 55b that covers the front surface of the case body 55a, and a second cover 55c that covers the back surface of the case body 55a. The first cover 55b and the second cover 55c are formed using a resin containing an insulating material. The coil case 55 in this example includes a third cover 55d provided on the outside (back side) of the second cover 55c. The third cover 55d may be formed using a resin or a metal such as aluminum.

(46) The first spiral coil layer 52a is held between the case body 55a and the first cover 55b, while the second spiral coil layer 52b is held between the case body 55a and the second cover 55c. With this arrangement, the wire rod 53 forming the power reception coil 51 is housed inside the coil case 55, except for the ends 53a and 53b on either side. Consequently, it is possible to keep dust and the like from adhering to the wire rod 53.

(47) The case body 55a, first cover 55b, second cover 55c, and third cover 55d forming the coil case 55 are fastened to one another by fastening members such as screws, or secured to one another by gluing, welding, or the like.

(48) The coil case 55 has a space 55e between the second cover 55c and the third cover 55d, into which a plate-shaped magnetic body (ferrite member) or the like can be placed. By placing a magnetic body in the space 55e, or in other words, by providing a magnetic body on the back side of the second spiral coil layer 52b, the power reception efficiency of the power reception coil 51 can be raised.

(49) Note that a magnetic body such as a ferrite core may also be provided farther inward (toward the central axis) than the inner circumferential peripheral portion of the power reception coil 51. In this case, a space for placing a magnetic body can be provided in the central portion of the case body 55a, for example.

(50) The coil case 55 is formed into a flat plate shape overall. In addition, the coil case 55 has a rectangular shape, more specifically an approximately square shape, in a planar view from the axial direction of the power reception coil 51. However, the coil case 55 may also have a different shape in the same planar view. Also, the case body 55a, first cover 55b, second cover 55c, and third cover 55d forming the coil case 55 similarly have a rectangular plate shape in a planar view, and are disposed overlapping in the thickness direction of the coil case 55. Note that the coil case 55 is not limited to a flat case like in this example and may also be curved, bent, or have depressed or raised portions.

(51) The spiral grooves 55g and 55h are formed on the front surface and the back surface, respectively, of the case body 55a, and the wire rod 53 is disposed to follow the spiral grooves 55g and 55h. The wire rod 53 disposed to follow the spiral groove 55g on the front surface of the case body 55a forms the first spiral coil layer 52a, and the wire rod 53 disposed to follow the spiral groove 55h on the back surface of the case body 55a forms the second spiral coil layer 52b. A partition wall 55j is provided between the spiral groove 55g on the front surface and the spiral groove 55h on the back surface of the case body 55a.

(52) The spiral groove 55g on the front surface and the spiral groove 55h on the back surface of the case body 55a are spaced apart by a predetermined distance (at least the thickness of the partition wall 55j or more) in the thickness direction (axial direction of the power reception coil 51) of the

case body 55a by the partition wall 55j. Additionally, the spiral groove 55g on the front surface and the spiral groove 55h on the back surface communicate through a through-hole 55k formed in the partition wall 55j. The through-hole 55k penetrates from the groove bottom of the spiral groove 55g on the front surface (front surface of the partition wall 55j) to the groove bottom of the spiral groove 55h on the back surface (back surface of the partition wall 55j).

(53) The through-hole 55k is formed at a position corresponding to the connecting portion 54 of the power reception coil 51. Consequently, the position of the through-hole 55k can be adjusted, as appropriate, in correspondence with the position of the connecting portion 54 of the power reception coil 51. In this example, the through-hole 55k is positioned in the central part of the case body 55a, and more specifically, at a position corresponding to the inner circumferential peripheral portion of the power reception coil 51. With this arrangement, the connecting portion 54 of the power reception coil 51 can be disposed in the through-hole 55k.

(54) Referring to FIG. 1 again, the onboard device 6 is installed in the moving body 2 and is electrically connected to the power reception device 5. The power reception device 5 and the onboard device 6 may be electrically connected in a wired way. In such a case, the power transmission efficiency from the power reception device 5 to the onboard device 6 is improved compared to the case of a wireless connection. Also, the power reception device 5 and the onboard device 6 may be electrically connected in a wireless way. In such a case, for example, it is unnecessary to run power lines for transmitting power from the power reception device 5 to the onboard device 6 installed in the body of the moving body 2 away from the wheel 3, thereby lowering the possibility that the power lines may be severed in association with the rotation of the wheel 3.

(55) The onboard device 6 may also include a driving device 61 that drives the wheel 3 with electric power, for example. In such a case, the driving device 61 consumes power supplied from the power reception device 5 to drive the wheel 3. In the present embodiment, the driving device 61 is an in-wheel motor housed, at least in part, in the wheel 3, but is not limited thereto. The driving device 61 may also be an onboard motor which is installed in the body of the moving body 2 and which causes the wheel 3 to be driven by driving a shaft 22 of the moving body 2.

(56) As another example, the onboard device 6 may also include a power storage device 62 that stores electric power. The power storage device 62 can store electric power supplied from the power reception device 5 and also supply electric power to other onboard devices 6. For example, the power storage device 62 may be a storage battery of any type, such as a lead storage battery, a nickel hydride battery, a lithium-ion battery, a sodium-sulfur battery, or a combination of the above.

(57) The onboard device 6 is not limited to the examples described above and may also include any electronic devices installed in the moving body 2, such as a communication device for the moving body 2, a car navigation system, a media player, and in-vehicle sensors. The onboard device 6 may be integrated into the moving body 2 or removably installed in the moving body 2.

(58) Hereinafter, FIGS. 7 and 8 will be referenced to describe an example of the power reception device 5 and the driving device 61 specifically. FIG. 7 is a schematic diagram that uses a lateral cross section of the wheel 3 to generally illustrate a tire and wheel assembly as one example of the wheel 3 in the wireless power reception system 1. FIG. 8 is a schematic diagram that generally illustrates a converter 56a and an inverter 56b of the power reception device 5 housed in the wheel 3 in FIG. 7. In this example, the driving device 61 is an in-wheel motor installed in the wheel 3, and is housed, at least in part, in the wheel 3.

(59) The power reception device 5 is provided with a converter 56a and an inverter 56b as power converters. The converter 56a is connected to the power reception coil 51 and the inverter 56b. The converter 56a can convert AC power generated in the power reception coil 51 into DC power, and transmit power to the inverter 56b. The inverter 56b is connected to the converter 56a and the driving device 61. The inverter 56b can convert DC power from the converter 56a into AC power, and transmit power to the driving device 61.

(60) The converter **56a** is positioned vertically above the power reception coil **51**, and the inverter **56b** is positioned vertically above the converter **56a**. In this example, the entire converter **56a** and the entire inverter **56b** are housed in the wheel **3**. Note that it is sufficient if at least a portion of the converter **56a** and the inverter **56b** are housed in the wheel **3**.

(61) The converter **56a** and the inverter **56b** are provided on an annular substrate **56c** disposed coaxially with the wheel **3**. The power reception coil **51** is positioned below the substrate **56c**. Note that the power reception coil **51** may also at a position that overlaps with the substrate **56c** in the vertical direction.

(62) As illustrated in FIG. **8**, the converter **56a** and the inverter **56b** are disposed at different circumferential positions on the annular substrate **56c**. The converter **56a** and the inverter **56b** are disposed concentrically on the substrate **56c**. The converter **56a** is positioned in a lower portion of the substrate **56c**, and the inverter **56b** is positioned in an upper portion of the substrate **56c**.

(63) The driving device **61** is a direct drive motor **63** disposed coaxially with the wheel **3**. The direct drive motor **63** is disposed coaxially with the wheel **3**. In addition, the direct drive motor **63** is housed entirely in the wheel **3**. Note that it is sufficient if at least a portion of the direct drive motor **63** is housed in the wheel **3**.

(64) The power reception device **5** includes the coil case **55** housing the power reception coil **51**. The coil case **55** is provided integrally with a case **56d** that houses the converter **56a**. Note that the coil case **55** may also be joined to the case **56d**. Also, the coil case **55** may be provided independently from the case **56d** that houses the converter **56a**. The case **56d** is housed entirely in the wheel **3**. The case **56d** encloses the substrate **56c**, the converter **56a**, the inverter **56b**, and the direct drive motor **63** from the outside. Note that the case **56d** that houses the converter **56a** is not a required component.

(65) The control device **7** controls at least one of the power reception device **5** or the onboard device **6**. The control device **7** is an electronic control unit (ECU), for example, but is not limited thereto and may be electronic equipment of any type. The control device **7** may also be electrically connected to the power reception device **5** as one of the onboard devices **6** described above.

(66) The control device **7** may be provided with a control unit, a storage unit, a communication unit, an output unit, an input unit, and the like, for example. For example, the control device **7** can cause the power reception device **5** to transmit power received wirelessly by the power reception device **5** to at least one of a plurality of onboard devices **6**, including the driving device **61** and the power storage device **62** for example, on the basis of a predetermined condition.

(67) As described above, the wireless power reception system **1** according to an embodiment of the present disclosure includes: the power reception device **5** including the power reception coil **51** that receives power supplied wirelessly from the power transmission coil **41** of the power transmission device **4** installed in a road surface, at least a portion of the power reception coil **51** being housed in the wheel **3** of the moving body **2**; and the driving device **61** which is installed in the wheel **3** and which drives the wheel **3** with power received by the power reception device **5**, wherein the power reception device **5** is provided with the converter **56a** that converts AC power generated in the power reception coil **51** into DC power and the inverter **56b** that can convert DC power from the converter **56a** into AC power to transmit power to the driving device **61**, at least a portion of the converter **56a** and at least a portion of the inverter **56b** are housed in the wheel **3**, the converter **56a** is positioned vertically above the power reception coil **51**, and the inverter **56b** is positioned vertically above the converter **56a**. According to such a configuration, by housing at least a portion of the power reception coil **51** in the wheel **3** that directly contacts the road surface, it is possible to lower the possibility that an obstacle will come into the space between the power transmission coil **41** provided in the road surface and the power reception coil **51**. For this reason, the wireless power reception system **1** can improve the power reception efficiency in wireless power transfer.

(68) Also, by positioning the converter **56a** vertically above the power reception coil **51** and positioning the inverter **56b** vertically above the converter **56a**, it is easier to dispose the power

reception coil **51** close to the power transmission coil **41**, and in addition, the power transfer from the power transmission coil **41** to the power reception coil **51** is not inhibited as much by the inverter **56b** and the converter **56a**. Therefore, the power reception efficiency can be raised. Also, since it is easier to dispose the power reception coil **51** and the converter **56a** close to each other, power transmission loss occurring when transmitting power from the power reception coil **51** to the converter **56a** can be reduced. Moreover, it is easy to shorten the power transmission pathway from the power reception coil **51** to the driving device **61** through the converter **56a** and the inverter **56b**. For this reason, the power transmission loss can be reduced, and it is easier to utilize the space inside the wheel **3** effectively.

(69) In the wireless power reception system **1** according to an embodiment of the present disclosure, the converter **56a** and the inverter **56b** are provided on the annular substrate **56c** disposed coaxially with the wheel **3**. According to such a configuration, the converter **56a** and the inverter **56b** can be installed efficiently around the axial part of the wheel **3**, and the space inside the wheel **3** can be utilized effectively.

(70) In the wireless power reception system **1** according to an embodiment of the present disclosure, the driving device **61** is the direct drive motor **63** disposed coaxially with the wheel **3**. According to such a configuration, the torque of the direct drive motor **63** can be transferred to the wheel **3** directly without going through an indirect mechanism (such as a gearbox), and therefore motive power loss can be reduced to drive the wheel **3** efficiently.

(71) In the wireless power reception system **1** according to an embodiment of the present disclosure, the power reception device **5** includes the coil case **55** that houses the power reception coil **51**, and the coil case **55** is integrated with or joined to the case **56d** that houses the converter **56a**. According to such a configuration, it is easier to stabilize the positional relationship between the power reception coil **51** and the converter **56a**. Moreover, integrating the coil case **55** with the case **56d** that houses the converter **56a** makes it easier to configure a compact power reception device **5**.

(72) The moving body **2** according to an embodiment of the present disclosure includes: the wheel **3**; the power reception device **5** including the power reception coil **51** that receives power supplied wirelessly from the power transmission coil **41** of the power transmission device **4** installed in a road surface, at least a portion of the power reception coil **51** being housed in the wheel **3**; and the driving device **61** which is installed in the wheel **3** and which drives the wheel **3** with power received by the power reception device **5**, wherein the power reception device **5** is provided with the converter **56a** that converts AC power generated in the power reception coil **51** into DC power and the inverter **56b** that can convert DC power from the converter **56a** into AC power to transmit power to the driving device **61**, at least a portion of the converter **56a** and at least a portion of the inverter **56b** are housed in the wheel **3**, the converter **56a** is positioned vertically above the power reception coil **51**, and the inverter **56b** is positioned vertically above the converter **56a**. According to such a configuration, by housing at least a portion of the power reception coil **51** in the wheel **3** that directly contacts the road surface, it is possible to lower the possibility that an obstacle will come into the space between the power transmission coil **41** provided in the road surface and the power reception coil **51**. For this reason, the wireless power reception system **1** can improve the power reception efficiency in wireless power transfer. Also, by positioning the converter **56a** vertically above the power reception coil **51** and positioning the inverter **56b** vertically above the converter **56a**, it is easier to dispose the power reception coil **51** close to the power transmission coil **41**, and in addition, the power transfer from the power transmission coil **41** to the power reception coil **51** is not inhibited as much by the inverter **56b** and the converter **56a**. Therefore, the power reception efficiency can be raised. Also, since it is easier to dispose the power reception coil **51** and the converter **56a** close to each other, power transmission loss occurring when transmitting power from the power reception coil **51** to the converter **56a** can be reduced. Moreover, it is easy to shorten the power transmission pathway from the power reception coil **51** to the driving device **61**.

through the converter **56a** and the inverter **56b**. For this reason, the power transmission loss can be reduced, and it is easier to utilize the space inside the wheel **3** effectively.

(73) The wheel **3** according to an embodiment of the present disclosure is a wheel **3** of the moving body **2** and includes: the power reception device **5** including the power reception coil **51** that receives power supplied wirelessly from the power transmission coil **41** of the power transmission device **4** installed in a road surface; and the driving device **61** that drives the wheel **3** with power received by the power reception device **5**, wherein the power reception device **5** is provided with the converter **56a** that converts AC power generated in the power reception coil **51** into DC power and the inverter **56b** that can convert DC power from the converter **56a** into AC power to transmit power to the driving device **61**, the wheel **3** internally houses at least a portion of the converter **56a** and at least a portion of the inverter **56b**, the converter **56a** is positioned vertically above the power reception coil **51**, and the inverter **56b** is positioned vertically above the converter **56a**. According to such a configuration, by housing at least a portion of the power reception coil **51** in the wheel **3** that directly contacts the road surface, it is possible to lower the possibility that an obstacle will come into the space between the power transmission coil **41** provided in the road surface and the power reception coil **51**. For this reason, the wireless power reception system **1** can improve the power reception efficiency in wireless power transfer. Also, by positioning the converter **56a** vertically above the power reception coil **51** and positioning the inverter **56b** vertically above the converter **56a**, it is easier to dispose the power reception coil **51** close to the power transmission coil **41**, and in addition, the power transfer from the power transmission coil **41** to the power reception coil **51** is not inhibited as much by the inverter **56b** and the converter **56a**. Therefore, the power reception efficiency can be raised. Also, since it is easier to dispose the power reception coil **51** and the converter **56a** close to each other, power transmission loss occurring when transmitting power from the power reception coil **51** to the converter **56a** can be reduced. Moreover, it is easy to shorten the power transmission pathway from the power reception coil **51** to the driving device **61** through the converter **56a** and the inverter **56b**. For this reason, the power transmission loss can be reduced, and it is easier to utilize the space inside the wheel **3** effectively.

(74) Also, the wireless power reception system **1** embodied as illustrated in FIGS. **2** to **6** includes: the power reception device **5** including the power reception coil **51** that receives power supplied wirelessly from the power transmission coil **41** of the power transmission device **4** installed in a road surface, at least a portion of the power reception coil **51** being housed in the wheel **3** of the moving body **2**; and the onboard device **6** which is installed in the moving body **2** and which is electrically connected to the power reception device **5**, wherein the power reception device **5** transmits received power to the onboard device **6**. According to such a configuration, by housing at least a portion of the power reception coil **51** in the wheel **3** that directly contacts the road surface, it is possible to lower the possibility that an obstacle will come into the space between the power transmission coil **41** provided in the road surface and the power reception coil **51**. For this reason, the wireless power reception system **1** can improve the power reception efficiency in wireless power transfer.

(75) Also, according to the wireless power reception system **1** embodied as illustrated in FIGS. **2** to **6**, the power reception coil **51** includes the stacked plurality of spiral coil layers **52a** and **52b**, and therefore the area of the coil surface can be reduced compared to a power reception coil with a single-layer structure (a power reception coil having only a single spiral coil layer) having similar power reception capability. In other words, the number of windings in the power reception coil **51** overall can be secured to obtain the power reception capability with the plurality of spiral coil layers **52a** and **52b**, while at the same time, the area of the coil surface of the power reception coil **51** can be restrained. For this reason, the degree of freedom with respect to the installation range of the power reception coil **51** is improved, making it possible to house the power reception coil **51** over a wide range in the wheel **3**. Also, since the area of the coil surface can be reduced, installation at a position close to the power transmission coil **41** is easier, thereby further improving the power

reception efficiency of the power reception device **5**.

(76) In the wireless power reception system **1** embodied as illustrated in FIGS. **2** to **6**, the power reception coil **51** has a two-layer structure including the first spiral coil layer **52a** and the second spiral coil layer **52b**. According to such a configuration, the winding structure of the wire rod does not become complicated as readily as in the case of providing three or more spiral coil layers, making it easy to manufacture the power reception coil **51**.

(77) In the wireless power reception system **1** embodied as illustrated in FIGS. **2** to **6**, the wire rod **53** forming the first spiral coil layer **52a** and the wire rod **53** forming the second spiral coil layer **52b** are continuous in the inner circumferential peripheral portion of the power reception coil **51**. According to such a configuration, a complicated configuration of the power reception device **5** can be prevented compared to the case where the first spiral coil layer **52a** and the second spiral coil layer **52b** are independent from each other, and the overall power reception device **5** can be given a simple configuration. Moreover, by providing the connecting portion **54** on the inner circumferential peripheral portion of the power reception coil **51**, it is easier to dispose the ends **53a** and **53b** of the wire rod **53** of the power reception coil **51** apart from each other. For this reason, since the distance between portions of the wire rod **53** can be secured appropriately, loss arising from a proximity effect can be reduced. As a result, the power reception efficiency of the power reception device **5** can be improved further.

(78) In the wireless power reception system **1** embodied as illustrated in FIGS. **2** to **6**, the wire rod **53** forming the first spiral coil layer **52a** and the wire rod **53** forming the second spiral coil layer **52b** are formed by a single, continuous wire rod **53**. According to such a configuration, the power transmission loss can be reduced compared to the case of forming the power reception coil **51** by joining a plurality of wire rods **53**. Furthermore, since joining a plurality of wire rods **53** is unnecessary, the manufacturing of the power reception coil **51** is also easy.

(79) In the wireless power reception system **1** embodied as illustrated in FIGS. **2** to **6**, the power reception coil **51** is provided with the plate-shaped case body **55a** (wire rod support portion) containing an insulating material, and the wire rod **53** is disposed to follow the spiral grooves **55g** and **55h** formed in the case body **55a**. According to such a configuration, the wire rod **53** forming the power reception coil **51** can be held in a stable state. Additionally, since the distance between portions of the wire rod **53** forming the power reception coil **51** can be secured appropriately, loss arising from a proximity effect can be reduced. As a result, the power reception efficiency of the power reception device **5** can be improved further.

(80) In the wireless power reception system **1** embodied as illustrated in FIGS. **2** to **6**, the spiral grooves **55g** and **55h** are formed on the front and back surfaces, respectively, of the case body **55a**, such that the spiral groove **55g** formed on the front surface and the spiral groove **55h** formed on the back surface communicate through the through-hole **55k** formed in the case body **55a**. According to such a configuration, by disposing the wire rod **53** to follow the spiral groove **55g** on the front surface and the spiral groove **55h** on the back surface of the case body **55a**, the stacked plurality of spiral coil layers **52a** and **52b** can be formed easily. Moreover, by passing the wire rod **53** through the through-hole **55k**, the first spiral coil layer **52a** on the front side and the second spiral coil layer **52b** on the back side of the case body **55a** can be made to be continuous easily.

(81) The moving body **2** embodied as illustrated in FIGS. **2** to **6** includes: the wheel **3**; the power reception device **5** including the power reception coil **51** that receives power supplied wirelessly from the power transmission coil **41** of the power transmission device **4** installed in a road surface, at least a portion of the power reception coil **51** being housed in the wheel **3**; and the onboard device **6** electrically connected to the power reception device **5**, wherein the power reception device **5** can transmit received power to the onboard device **6**, and the power reception coil **51** includes the stacked plurality of spiral coil layers **52a** and **52b**. According to such a configuration, by housing at least a portion of the power reception coil **51** in the wheel **3** that directly contacts the road surface, it is possible to lower the possibility that an obstacle will come into the space between

the power transmission coil **41** provided in the road surface and the power reception coil **51**. For this reason, the moving body **2** can improve the power reception efficiency in wireless power transfer. Also, the power reception coil **51** includes the stacked plurality of spiral coil layers **52a** and **52b**, and therefore the area of the coil surface as viewed from the axial direction of the power reception coil **51** can be reduced compared to a power reception coil with a single-layer structure having similar power reception capability. For this reason, the degree of freedom with respect to the installation range of the power reception coil **51** is improved, making it possible to house the power reception coil **51** over a wide range in the wheel **3**. Also, installation at a position close to the power transmission coil **41** is easier, thereby further improving the power reception efficiency of the power reception device **5**.

(82) The wheel **3** embodied as illustrated in FIGS. **2** to **6** is a wheel **3** of the moving body **2** and includes: the power reception device **5** including the power reception coil **51** that receives power supplied wirelessly from the power transmission coil **41** of the power transmission device **4** installed in a road surface, wherein at least a portion of the power reception coil **51** is housed in the wheel **3**, and the power reception coil **51** includes the stacked plurality of spiral coil layers **52a** and **52b**. According to such a configuration, by housing at least a portion of the power reception coil **51** in the wheel **3** that directly contacts the road surface, it is possible to lower the possibility that an obstacle will come into the space between the power transmission coil **41** provided in the road surface and the power reception coil **51**. For this reason, the wheel **3** can improve the power reception efficiency in wireless power transfer. Also, the power reception coil **51** includes the stacked plurality of spiral coil layers **52a** and **52b**, and therefore the area of the coil surface as viewed from the axial direction of the power reception coil **51** can be reduced compared to a power reception coil with a single-layer structure having similar power reception capability. For this reason, the degree of freedom with respect to the installation range of the power reception coil **51** is improved, making it possible to house the power reception coil **51** over a wide range in the wheel **3**. Also, installation at a position close to the power transmission coil **41** is easier, thereby further improving the power reception efficiency of the power reception device **5**.

(83) Hereinafter, FIGS. **9** and **10** will be referenced to describe another example of the power reception coil **51** specifically. The power reception coil **51** illustrated in FIG. **9** has a convex shape pointing downward in a side view as seen from the axial direction of the wheel **3**. FIG. **9** schematically illustrates only the wheel **3** and the power reception coil **51**. Also, in FIG. **9**, a power reception coil **51a** having a flat shape extending horizontally in a side view as seen from the axial direction of the wheel **3** is indicated by a chain double-dashed line for comparison. Also, in FIG. **9**, a power reception coil **51b** having a convex bent shape pointing downward in a side view is indicated by a chain double-dashed line for comparison. The power reception coil **51b** has the same width and the same height as the power reception coil **51** in a side view. Note that the power reception coil **51** illustrated in FIG. **9** has a single-layer structure including a single spiral coil layer, but is not limited thereto.

(84) The power reception coil **51** illustrated in FIG. **9** is curved into an arc shape overall in a side view. The power reception coil **51** is not limited to a shape curved into an arc and may be configured to have at least a convex, non-flat shape pointing downward overall, such as by being bent into a downward-pointing V-shape like the power reception coil **51b**, for example. Also, although omitted from illustration in the diagram, the power reception device **5** may also include a curved coil case corresponding to the shape of the power reception coil **51**.

(85) In the power reception coil **51** illustrated in FIG. **9**, the center of curvature **P** of the power reception coil **51** in a side view is located on the central axis of the wheel **3**. With this arrangement, the power reception coil **51** can be disposed to follow the inner circumferential surface **3a** of the wheel **3**. Note that the inner circumferential surface **3a** of the wheel **3** can be taken to be the inner circumferential surface of the rim portion **321**, for example, but is not limited thereto.

(86) The power reception coil **51** illustrated in FIG. **10** includes a stacked plurality of spiral coil

layers **52c** and **52d**. FIG. **10** schematically illustrates only the wheel **3** and the power reception coil **51**. Also, in FIG. **10**, a power reception coil **51c** having a single-layer structure including a single spiral coil layer is indicated by a chain double-dashed line for comparison. In the case where the power reception coil is long in the wheel circumferential direction like the power reception coil **51c**, the ends of the power reception coil **51c** in the wheel circumferential direction become distant from the power transmission coil **41** more easily. For this reason, by configuring the power reception coil **51** to have a multilayer structure including the plurality of spiral coil layers **52c** and **52d** to reduce the length in the wheel circumferential direction, the average distance between the power transmission coil **41** installed in a road surface and the power reception coil **51** can be reduced, as illustrated in FIG. **10**. Note that in the power reception coil **51** illustrated in FIG. **10**, the center of curvature **P** of the power reception coil **51** in a side view likewise is located on the central axis of the wheel **3**, but is not limited thereto. Also, the power reception coil **51** in FIG. **10** has two layers including the spiral coil layers **52c** and **52d**, but may also have three or more spiral coil layers.

(87) Other than being curved in a side view, the power reception coil **51** illustrated in FIG. **10** can be configured similarly to the power reception coil **51** having the multilayer structure described with reference to FIGS. **2** to **6**. For example, the two spiral coil layers **52c** and **52d** may be wound using a single, continuous wire rod **53**. Additionally, the power reception device **5** may be provided with a curved coil case **55** in correspondence with the power reception coil **51**. In this case, the coil case **55** may be provided with the case body **55a** (wire rod support portion), the first cover **55b**, the second cover **55c**, the third cover **55d**, and the like having curved shapes corresponding to the shape of the power reception coil **51**. Moreover, the two spiral coil layers **52c** and **52d** may also be formed by disposing the wire rod **53** to follow spiral grooves provided on the front and back surfaces of the case body **55a**.

(88) As described above, the wireless power reception system **1** embodied as illustrated in FIGS. **9** and **10** includes: the power reception device **5** including the power reception coil **51** that receives power supplied wirelessly from the power transmission coil **41** of the power transmission device **4** installed in a road surface, at least a portion of the power reception coil **51** being housed in the wheel **3** of the moving body **2**; and the onboard device **6** which is installed in the moving body **2** and which is electrically connected to the power reception device **5**, wherein the power reception device **5** can transmit received power to the onboard device **6**, and the power reception coil **51** has a convex shape pointing downward in a side view as seen from the axial direction of the wheel **3**. According to such a configuration, by housing at least a portion of the power reception coil **51** in the wheel **3** that directly contacts the road surface, it is possible to lower the possibility that an obstacle will come into the space between the power transmission coil **41** provided in the road surface and the power reception coil **51**. For this reason, the wireless power reception system **1** can improve the power reception efficiency in wireless power transfer.

(89) Also, according to the wireless power reception system **1** embodied as illustrated in FIGS. **9** and **10**, since the power reception coil **51** has a convex shape pointed downward in a side view as seen from the axial direction of the wheel **3**, the average distance between the power transmission coil **41** installed in a road surface and the power reception coil **51** can be reduced compared to the power reception coil **51a** having a flat shape extending horizontally in a side view. As a result, the power transfer efficiency of the wireless power reception system **1** including the power reception coil **51** can be raised.

(90) In the wireless power reception system **1** embodied as illustrated in FIGS. **9** and **10**, the power reception coil **51** is curved into an arc shape in a side view. According to such a configuration, the average distance between the power transmission coil **41** and the power reception coil **51** can be reduced further, and the power transfer efficiency of the wireless power reception system **1** can be raised further compared to the power reception coil **51b** bent into a V-shape with the same width and the same height in a side view, for example.

(91) In the wireless power reception system **1** embodied as illustrated in FIGS. **9** and **10**, the center of curvature P of the power reception coil **51** in a side view is located on the central axis of the wheel **3**. According to such a configuration, since the power reception coil **51** can be disposed to follow the inner circumferential surface **3a** of the wheel **3**, the average distance between the power transmission coil **41** and the power reception coil **51** can be reduced further, and the power transfer efficiency of the wireless power reception system **1** can be raised further. In addition, by disposing the power reception coil **51** to follow the inner circumferential surface **3a** of the wheel **3**, the space inside the wheel **3** can be utilized effectively.

(92) In the wireless power reception system **1** embodied as illustrated in FIG. **10**, the power reception coil **51** includes a stacked plurality of spiral coil layers **52c** and **52d**. According to such a configuration, the length of the power reception coil **51** in the circumferential direction of the wheel **3** in a side view can be reduced compared to the power reception coil **51c** having a single-layer structure including a single spiral coil layer. For this reason, the average distance between the power transmission coil **41** installed in a road surface and the power reception coil **51** can be reduced further, and the power transfer efficiency can be raised further.

(93) The moving body **2** embodied as illustrated in FIGS. **9** and **10** includes: the wheel **3**; the power reception device **5** including the power reception coil **51** that receives power supplied wirelessly from the power transmission coil **41** of the power transmission device **4** installed in a road surface, at least a portion of the power reception coil **51** being housed in the wheel **3**; and the onboard device **6** electrically connected to the power reception device **5**, wherein the power reception device **5** can transmit received power to the onboard device **6**, and the power reception coil **51** has a convex shape pointing downward in a side view as seen from the axial direction of the wheel **3**. According to such a configuration, by housing at least a portion of the power reception coil **51** in the wheel **3** that directly contacts the road surface, it is possible to lower the possibility that an obstacle will come into the space between the power transmission coil **41** provided in the road surface and the power reception coil **51**. For this reason, the moving body **2** can improve the power reception efficiency in wireless power transfer. Also, since the power reception coil **51** has a convex shape pointed downward in a side view as seen from the axial direction of the wheel **3**, the average distance between the power transmission coil **41** installed in a road surface and the power reception coil **51** can be reduced compared to the power reception coil **51a** having a flat shape extending horizontally in a side view. As a result, the power transfer efficiency of the wireless power reception system **1** including the power reception coil **51** can be raised.

(94) The wheel **3** embodied as illustrated in FIGS. **9** and **10** is a wheel **3** of the moving body **2** and includes: the power reception device **5** including the power reception coil **51** that receives power supplied wirelessly from the power transmission coil **41** of the power transmission device **4** installed in a road surface, wherein at least a portion of the power reception coil **51** is housed in the wheel **3**, and the power reception coil **51** has a convex shape pointing downward in a side view as seen from the axial direction of the wheel **3**. According to such a configuration, by housing at least a portion of the power reception coil **51** in the wheel **3** that directly contacts the road surface, it is possible to lower the possibility that an obstacle will come into the space between the power transmission coil **41** provided in the road surface and the power reception coil **51**. For this reason, the wheel **3** can improve the power reception efficiency in wireless power transfer. Also, since the power reception coil **51** has a convex shape pointed downward in a side view as seen from the axial direction of the wheel **3**, the average distance between the power transmission coil **41** installed in a road surface and the power reception coil **51** can be reduced compared to the power reception coil **51a** having a flat shape extending horizontally in a side view. As a result, the power transfer efficiency of the wireless power reception system **1** including the power reception coil **51** can be raised.

(95) The present disclosure has been described on the basis of the drawings and embodiments, but it should be noted that a person skilled in the art could make various modifications and revisions on

the basis of the present disclosure. Consequently, it should be appreciated that any such modifications or revisions are included in the scope of the present disclosure. For example, the components, functions, and the like included in each embodiment or practical example may be rearranged in logically non-contradictory ways. Moreover, the components, functions, and the like included in each embodiment can be used in combination with another embodiment or practical example, and a plurality of components, functions, and the like may be combined into one, divided, or partially omitted.

(96) For example, in the embodiments described above, some or all of the functions or processes described as functions or processes of the control device **7** may also be achieved as functions or processes of the power reception device **5** or the onboard device **6**. For example, a program stating processing content for achieving each function of the control device **7** according to an embodiment may be stored in a memory or the like provided in the power reception device **5** or the onboard device **6**, and the program may be read out and executed by a processor or the like of the power reception device **5** or the onboard device **6**.

(97) As another example, in the embodiments described above, the coil surface of the power reception device **5** is described as being disposed approximately parallel to the contact patch of the wheel **3**, but is not limited thereto. The coil surface of the power reception coil **51** may also be disposed at any angle from 0 degrees to 90 degrees with respect to the contact patch of the wheel **3**. The angle between the coil surface of the power reception coil **51** and the contact patch of the wheel **3** may be freely determined according to the purpose of the power reception device **5**, the amount of power to be received, and the like.

(98) As another example, in the embodiments described above, the tire **31** is described as being filled with air, but is not limited thereto. For example, the tire **31** may be filled with a gas such as nitrogen. As another example, instead of or in addition to air, the tire **31** may be filled with any fluid, such as a liquid, a gelatinous material, or particulate matter.

REFERENCE SIGNS LIST

(99) **1** wireless power reception system **2** moving body **21** hub **22** shaft **3** wheel **31** tire **311** bead portion **312** sidewall portion **313** tread portion **32** wheel **321** rim portion **322** disc portion **4** power transmission device **41** power transmission coil **5** power reception device **51** power reception coil **52a** first spiral coil layer **52b** second spiral coil layer **56a** converter **56b** inverter **6** onboard device **61** driving device **62** power storage device **7** control device **71** control unit **72** storage unit **73** communication unit **74** output unit **75** input unit

Claims

1. A wireless power reception system comprising: a wheel of a moving body including a rim portion for mounting a tire; a power reception device including a power reception coil configured to receive power supplied wirelessly from a power transmission coil of a power transmission device installed in a road surface, at least a portion of the power reception coil being housed in the wheel of the moving body; and a driving device installed in the wheel and configured to drive the wheel with power received by the power reception device, wherein the power reception device is provided with a converter configured to convert AC power generated in the power reception coil into DC power and an inverter configured to convert DC power from the converter into AC power to transmit power to the driving device, at least a portion of the converter and at least a portion of the inverter are housed in the wheel, the converter is positioned vertically above the power reception coil, the inverter is positioned vertically above the converter, the converter and the inverter are provided on an annular substrate disposed coaxially with the wheel, the converter, the inverter, and the annular substrate are enclosed in a case which is housed entirely in the wheel, radially inward of the rim portion, and the power reception coil is attached to a radially outer side of the case so as not to rotate together with the wheel.

2. The wireless power reception system according to claim 1, wherein the driving device is a direct drive motor disposed coaxially with the wheel.
 3. The wireless power reception system according to claim 2, wherein the power reception device includes a coil case housing the power reception coil, and the coil case is integrated with or joined to the case.
 4. The wireless power reception system according to claim 1, wherein the power reception device includes a coil case housing the power reception coil, and the coil case is integrated with or joined to the case.
 5. A moving body comprising: a wheel including a rim portion for mounting a tire; a power reception device including a power reception coil configured to receive power supplied wirelessly from a power transmission coil of a power transmission device installed in a road surface, at least a portion of the power reception coil being housed in the wheel; and a driving device installed in the wheel and configured to drive the wheel with power received by the power reception device, wherein the power reception device is provided with a converter configured to convert AC power generated in the power reception coil into DC power and an inverter configured to convert DC power from the converter into AC power to transmit power to the driving device, at least a portion of the converter and at least a portion of the inverter are housed in the wheel, the converter is positioned vertically above the power reception coil, the inverter is positioned vertically above the converter, the converter and the inverter are provided on an annular substrate disposed coaxially with the wheel, the converter, the inverter, and the annular substrate are enclosed in a case which is housed entirely in the wheel, radially inward of the rim portion, and the power reception coil is attached to a radially outer side of the case so as not to rotate together with the wheel.
 6. A wheel of a moving body including a rim portion for mounting a tire, the wheel comprising: a power reception device including a power reception coil configured to receive power supplied wirelessly from a power transmission coil of a power transmission device installed in a road surface, at least a portion of the power reception coil being housed in the wheel; and a driving device installed in the wheel and configured to drive the wheel with power received by the power reception device, wherein the power reception device is provided with a converter configured to convert AC power generated in the power reception coil into DC power and an inverter configured to convert DC power from the converter into AC power to transmit power to the driving device, at least a portion of the converter and at least a portion of the inverter are housed in the wheel, the converter is positioned vertically above the power reception coil, the inverter is positioned vertically above the converter, the converter and the inverter are provided on an annular substrate disposed coaxially with the wheel, the converter, the inverter, and the annular substrate are enclosed in a case which is housed entirely in the wheel, radially inward of the rim portion, and the power reception coil is attached to a radially outer side of the case so as not to rotate together with the wheel.
-