

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408724
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Chudasama; Shivamkumar Dharmendrasinh et al.

Interactive protection system

Abstract

An interactive protection system of a vehicle includes: a voice assistant that is a combination of a voice assistant application on a user device and a voice cloud platform; an instrument cluster including a cluster controller configured to generate vehicle information based on one or more vehicular sensor data and at least one vehicle wireless transceiver configured to communicate the generated vehicle information to a voice assistant; an audio system disposed in proximity to a head of a user and configured to generate user information; and an audio wireless transceiver configured for receiving a vehicle information from the voice assistant and transmitting the user information to the instrument cluster through the voice assistant for generating subsequent vehicle information.

Inventors:	Chudasama; Shivamkumar Dharmendrasinh (Chennai, IN), Ramalingam; V (Chennai, IN), Vasu; Ajay Kumar (Chennai, IN), Sagare; Datta Rajaram (Chennai, IN)
Applicant:	TVS MOTOR COMPANY LIMITED (Chennai, IN)
Family ID:	73131791
Assignee:	TVS Motor Company Limited (Chennai, IN)
Appl. No.:	18/010772
Filed (or PCT Filed):	October 02, 2020
PCT No.:	PCT/IN2020/050849
PCT Pub. No.:	WO2021/260714
PCT Pub. Date:	December 30, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230263258 A1	Aug. 24, 2023

Foreign Application Priority Data

IN 202041026642 Jun. 24, 2020

Publication Classification

Int. Cl.: **B60Q1/00** (20060101); **A41D1/00** (20180101); **A42B3/30** (20060101); **G06F3/16** (20060101); **G10L13/02** (20130101); **G10L15/18** (20130101); **G10L15/22** (20060101); **H04R1/02** (20060101); **H04R3/00** (20060101)

U.S. Cl.:

CPC **A42B3/30** (20130101); **A41D1/002** (20130101); **G06F3/165** (20130101); **G06F3/167** (20130101); **G10L13/02** (20130101); **G10L15/1815** (20130101); **G10L15/22** (20130101); **H04R1/028** (20130101); **H04R3/00** (20130101); **G10L2015/223** (20130101); **H04R2420/07** (20130101)

Field of Classification Search

CPC: A42B (3/30); A41D (1/002); G06F (3/165); G06F (3/167); G10L (13/02); G10L (15/1815); G10L (15/22); G10L (2015/223); H04R (1/028); H04R (3/00); H04R (2420/07)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6876845	12/2004	Tabata	455/344	H04B 1/3822
6978162	12/2004	Russell	455/66.1	H04R 1/083
10525985	12/2019	Kinuhata	N/A	B60W 50/14
10773764	12/2019	Kinuhata	N/A	B62J 50/21
10959479	12/2020	Babu	N/A	B62J 45/41
2003/0036360	12/2002	Russell et al.	N/A	N/A
2019/0111940	12/2018	Kinuhata et al.	N/A	N/A
2019/0118887	12/2018	Kinuhata et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
206822084	12/2017	CN	N/A

OTHER PUBLICATIONS

International Search Report issued in corresponding International Application No. PCT/IN2020/050849 mailed Mar. 4, 2021 (4 pages). cited by applicant

Written Opinion issued in corresponding International Application No. PCT/IN2020/050849 mailed Mar. 4, 2021 (8 pages). cited by applicant

Primary Examiner: Pham; Toan N

Background/Summary

TECHNICAL FIELD

(1) The present subject matter relates to a vehicle rider protection system. More particularly, an interactive protection and navigation assistance system for the rider of the vehicle is disclosed.

BACKGROUND

(2) There is a huge rise in usage of two wheelers and three wheelers as modes of transport in recent years. Also, accidents due to distraction while riding or riding without a protective gear have also seen a spike in numbers. Rider assistance system, causing reduced distractions, during riding the vehicle is needed to improve rider experience in terms of comfort and safety. Also, with increased safety features, head gears are being manufactured using various types of foams and hard plastics to reduce extent of head injury that occurs during accidents. Implementations for improved safety of the rider involve embedding intelligent electronics into the head gear, while offering physical protection to the head and providing rider assistance to the user.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) The detailed description is described with reference to the accompanying figures. The same numbers are used throughout the drawings to reference like features and components.

(2) FIG. 1 exemplarily illustrates a schematic diagram of an interactive protection system showing wireless communication of vehicle information and user information between an instrument cluster of a vehicle, an audio system, and a voice assistant;

(3) FIG. 2 exemplarily illustrates a block diagram showing an architecture of the instrument cluster of the vehicle;

(4) FIG. 3 exemplarily illustrates a block diagram showing an architecture of the head gear worn by the user of the vehicle;

(5) FIG. 4 exemplarily illustrates a perspective view of the head gear;

(6) FIG. 5 exemplarily illustrates a flowchart showing a method for the wireless communication between the vehicle and the user executed by the interactive protection system exemplarily illustrated in FIG. 1;

(7) FIG. 6 exemplarily illustrates a flowchart showing invoking of the voice assistant from a vehicle interface;

(8) FIG. 7 exemplarily illustrates a flowchart showing invoking of the voice assistant using a voice command;

(9) FIG. 8 exemplarily illustrates a flowchart showing invoking of the voice assistant from the voice assistant application; and

(10) FIG. 9 exemplarily illustrates a flowchart showing invoking of the voice assistant from the vehicle interface.

DETAILED DESCRIPTION OF THE INVENTION

(11) At present manufacturers embed communication capabilities into the head gears. Some variants have cord running between the head gear and a base unit installed elsewhere. In some variants, a wireless communication means along with antennae is incorporated inside shell, on the shell, and padding of the head gear for communication between the user, the vehicle, and the head gear. The communication means include wireless communication modules, location tracking

modules, processor enabling the wireless communication, energy source to drive the modules, etc. Using the wireless communication means of the head gear, the user communicates with the vehicle about the state of the user, the state of the vehicle, call alerts, and navigational guidance in audio form, etc.

(12) However, in such variants, the head gear is bulky with the components crowded in the space available in the head gear and uncomfortable for the user to wear it. Also, the head gear does not provide adequate shock absorption and the communication means distract the user. The energy source driving the modules in the head gear will be of lesser capacity to incorporate it within the head gear. Such less capacity energy source may result in power shortage after a long run and may need recharging during the course of the ride, thereby perturbing the ride. The wireless communication means may be consuming power continuously, even when not in use and need to be invoked only when required, during the course of a trip.

(13) Further, positioning the wireless communication modules, such as, GSM, Wi-Fi, Bluetooth and their respective antennae in close proximity to the head of the user may also inflict the user with radiation related abnormalities in long run, which is not advised. Also, the wireless signal communicated between the head gear and the vehicle may be susceptible to interference with signals from different frequency range. Also, safety of the head gear will be a concern as the head gear and its modules may be stolen, as usually the head gears are tied with the vehicle, while parking. In case of positioning the wireless modules beneath the padding of the head gear, smoothness of the padding has to be ensured to not cause discomfort to the user as well as no compromise on the impact absorbing ability of the head gear.

(14) In some implementations of wireless communication between the head gear and the vehicle, the modules, such as, GSM, GPS, Wi-Fi, and Bluetooth and their antennae, and sensors, such as, an accelerometer, a gyroscope, and a vibration detector are mounted in the vehicle. However, mounting them in a convenient place in the vehicle requires enclosures for water and dust protection and additional power supply routing to the modules. In case the modules are located proximal to handle bar of the vehicle and communicate with the head gear via infrared communication, the region around the handle bar may be crowded distracting the user of the vehicle and infrared is not a secure and efficient way of communication.

(15) For providing navigation guidance to the user, many existing solutions include using a user device with GPS capability mounted in the vehicle, using a separate GPS navigator in the vehicle, using a wireless communication module in the vehicle and wirelessly transmitting the navigation guidance into the head gear using the wireless communication means mounted on the head gear. However, using a user device or a separate GPS navigator device on the vehicle may be distractive while riding, as continuous monitoring of display is necessary. Additionally, mounting the user device is not advisable as the user device is not automotive grade compatible and its durability is not sufficient to withstand shocks, vibration and heat exposure. Mounting the wireless communication means on the head gear has the disadvantages discussed previously. Further to that, cost of the head gear increase with the increase in the complexity of the head gear with the wireless communication means. Thus, manufacturing cost of the head gear also increases.

(16) Further, if call alerts and alerts about the state of the vehicle are communicated to the user using haptic feedback, the haptic feedback may minimally distract the user and convey less information. Also, during the course of a trip, the user may want to control actuation and settings of certain vehicular components, such as, indicators of the vehicle, head lamps, etc. However, physical operation or a user device to control actuation and settings of certain vehicle components may distract the user, affecting the safety of the vehicle and the user. If control information is accessible from a dedicated display unit, such as, an instrument cluster of the vehicle, the cognitive effort required to avail the information from the instrument cluster is quite high, with a limitation on the quality of information presented through this medium.

(17) In cases where wireless audio communication of signals, like navigational guidance, call

alerts, control information to the user using a head gear or a wireless enabled head set, is performed, number of queries that can be understood by the processor of the head gear or the controller of the vehicle and the responses to the queries is limited by the memory in the processor. Also, the processors lack the ability to understand the context of the queries, hold a conversation with the user, and learn from the conversations over time.

(18) Therefore, there exists a need for an improved wireless communication of user information, vehicle information, and control information between the user and the vehicle via an audio system with wireless capabilities, providing durability, comfort, safety, and reducing distractions to the user, while overcoming all problems disclosed above as well as other problems of known art.

(19) With the above objective in view, present invention discloses a vehicle with an instrument cluster incorporated on it and communicates with an audio system or an audio system in the head gear via a wireless transmission medium. The head gear comprises an outer shell, an inner shell, a wireless transceiver affixed into the inner shell, such that, the wireless transceiver monitors the rider's capability to ride and gives vehicle information about location, alerts etc. to the user via the audio system. This in-turn increases the rider's safety and comfort. In an embodiment, the present invention utilizes an existing instrument cluster with wireless capability available in vehicles. The vehicle instrument cluster with wireless capability displays vehicle information as well as implements the navigation guidance system, transmitting audio signals to the audio system.

(20) In an embodiment, an interactive protection system of a vehicle comprising an instrument cluster, an audio system, and an audio wireless transceiver is disclosed. The system as per the present subject matter consists of the instrument cluster comprises a cluster controller for generating vehicle information based on vehicular sensor data, and at least one vehicle wireless transceiver for communicating the generated vehicle information to a voice assistant partially embodied in a user device. The audio system is disposed proximal to a head of a user and generates user information and the audio wireless transceiver receives the vehicle information from the voice assistant and transmits the user information to the instrument cluster through the voice assistant for subsequent generation of the vehicle information. In an embodiment, the voice assistant is a combination of a voice assistant application on the user device and a voice cloud platform. The voice assistant comprises a speech to text engine, a domain identification and an intent matching engine, and a text to speech engine for converting the user information into text and the vehicle information into audio form. In an embodiment, the audio system is disposed proximal to an inner surface of a protective gear worn by the user of the vehicle. In another embodiment, the audio system is worn by the user directly on the head of the user.

(21) The protective gear further comprises one or more second sensors for generating second sensor data and a power supply to supply power to the audio system and the audio wireless transceiver. The one or more second sensors are one or more of a sleep sensor and a breath analyzer. The user information comprises an audio input from the audio system and the second sensor data from the one or more second sensors.

(22) A control knob for controlling the operation of the audio system is disposed on at least one surface of the protective gear and a region proximal to the instrument cluster in the vehicle. The voice assistant receives an audio input from the audio system and communicates the vehicle information to the audio system based on processing of the user information and the vehicular sensor data by the cluster controller, at real-time. The voice assistant is invoked using one or more of an interface of the instrument cluster, a voice command, and a control knob of the audio system. The voice assistant controls actuators of a plurality of vehicle components, based on the user information from the audio system. The audio system comprises a microphone for receiving an audio input from the user and at least one speaker transmitting the vehicle information to the user.

(23) The vehicular sensor data is generated by at least one of one or more speed sensors, one or more accelerometers, one or more level sensors, one or more vibration detectors, one or more gyroscope, one or more temperature sensors, one or more location sensors, and one or more

pressure sensors mounted on either body of the vehicle or the instrument cluster. The vehicular sensor data comprises indicator status, speed of the vehicle, energy levels of the vehicle, location of the vehicle, vibration of the vehicle, acceleration of the vehicle, tilt of the vehicle, data on ambient conditions, temperature, air pressure of wheels, and gear position. The vehicle information comprises alerts on energy levels of the vehicle, alerts on speed of the vehicle, alerts on indicator status, alerts in tilt of the vehicle, alerts on location of the vehicle, navigation guidance, call alerts, ambient weather, trip information, news coverage, alerts on drop of user device, service history, group ride status, and emergency service assistance.

(24) In another embodiment, an interactive protection system of a vehicle comprising an instrument cluster and a protective gear worn by a user of the vehicle is disclosed. The instrument cluster comprising a cluster controller for generating vehicle information based on vehicular sensor data, and at least one vehicle wireless transceiver for communicating the generated vehicle information to the protective gear of the user. The protective gear comprises an audio system, disposed proximal to an inner surface of the protective gear, for generating user information, and an audio wireless transceiver for receiving the vehicle information from the instrument cluster through the at least one vehicle wireless transceiver and transmitting the user information to the instrument cluster for subsequent generation of the vehicle information.

(25) The protective gear further comprises one or more second sensors for generating second sensor data and a power supply to source power to the audio system and the audio wireless transceiver. The one or more second sensors are one or more of a sleep sensor and a breath analyzer. The user information comprises an audio input from the audio system and the second sensor data from the one or more second sensors. The audio system comprises a microphone for receiving an audio input from the user and at least one speaker transmitting the vehicle information to the user.

(26) In this embodiment, the vehicular sensor data comprises at least one of the parameters from speed of the vehicle, energy levels of the vehicle, location of the vehicle, vibration of the vehicle, acceleration of the vehicle, tilt of the vehicle, data on ambient conditions temperature, air pressure of wheels, and gear position. The vehicle information comprises at least one of the information from alerts on energy levels of the vehicle, alerts on speed of the vehicle, alerts on location of the vehicle, navigation guidance, and call alerts. The vehicular sensor data is generated by at least one of one or more speed sensors, one or more accelerometers, one or more level sensors, one or more vibration detectors, one or more gyroscope, one or more temperature sensors, one or more location sensors, and one or more pressure sensors mounted on one of a body of the vehicle or the instrument cluster.

(27) This embodiment of the interactive protection system comprises a user device, connected with the audio system through the instrument cluster, for receiving calls, receiving messages, and storing media. A control knob for controlling the operation of the audio system is disposed on a surface of the protective gear and/or a region proximal to the instrument cluster in the vehicle.

(28) The cluster controller wirelessly receives the user information from the protective gear and communicates the vehicle information based on processing the user information and the vehicular sensor data at real-time. The protective gear further comprises a heads-up display unit for displaying the vehicle information in augmented reality.

(29) An embodiment of a protective gear worn by a user of a vehicle comprising an audio system and an audio wireless transceiver is disclosed. The audio system, disposed proximal to an inner surface of the protective gear, generates user information and the audio wireless transceiver receives vehicle information from an instrument cluster of the vehicle and communicates the user information to the instrument cluster for subsequent generation of the vehicle information. In this embodiment, the protective gear comprises one or more second sensors for generating second sensor data and a power supply to supply power to the audio system and the audio wireless transceiver. The one or more second sensors comprise a sleep sensor and a breath analyzer. In this

embodiment, the vehicle information comprises at least one of an alert on energy levels of the vehicle, alert on speed of the vehicle, alerts on location of the vehicle, navigation guidance, and call alerts based on vehicular sensor data. The vehicular sensor data comprises at least one of a speed of the vehicle, energy levels of the vehicle, location of the vehicle, vibration of the vehicle, acceleration of the vehicle, tilt of the vehicle, data on ambient conditions temperature, air pressure of wheels, and gear position. The vehicular sensor data is generated by at least one of one or more speed sensors, one or more accelerometers, one or more level sensors, one or more vibration detectors, one or more gyroscope, one or more temperature sensors, one or more location sensors, and one or more pressure sensors mounted on one of a body of the vehicle or the instrument cluster.

(30) In an embodiment, a method for wireless communication between a vehicle and a user of the vehicle, executed by an interactive protection system, is disclosed. The embodiment of the interactive protection system comprises an instrument cluster which consists of a cluster controller for generating vehicle information based on vehicular sensor data and at least one vehicle wireless transceiver for communicating the generated vehicle information to a voice assistant partially embodied in a user device, an audio system which is disposed proximal to a head of the user, for generating user information, and an audio wireless transceiver for receiving the vehicle information from the voice assistant and transmitting the user information to the instrument cluster through the voice assistant for subsequent generation of the vehicle information. The method comprises the steps of: invoking the voice assistant using one of an interface of the instrument cluster, a voice command from the audio system, and a control knob of the audio system; receiving the user information from the audio system by the voice assistant; converting the user information to a compatible format of the cluster controller; controlling one or more actuators of a plurality of vehicle components by the cluster controller, based on the converted user information from the audio system; generating vehicle information by the cluster controller from the vehicular sensor data, based on the converted user information; and transmitting vehicle information to the audio system by the voice assistant.

(31) The audio system is disposed proximal to an inner surface of a protective gear worn by the user of the vehicle. A control knob for controlling the operation of the audio system is disposed on at least one surface of the protective gear and a region proximal to the instrument cluster in the vehicle. The voice assistant is a combination of a voice assistant application on the user device and a voice cloud platform.

(32) FIG. 1 exemplarily illustrates a schematic diagram of an interactive protection system **100** showing wireless communication of vehicle information as well as user information between an instrument cluster **101** of a vehicle, an audio system **103b**, and a voice assistant **111**. The audio system **103b** and an audio wireless transceiver **103a** together may be a Bluetooth headset with a microphone worn by the user. The Bluetooth headset may comprise at least one speaker. In an embodiment, the audio system **103b** and the audio wireless transceiver **103a** may be attached to a protective gear **103** worn by the user. The audio system **103b** and the audio wireless transceiver **103a** transmit user information to the instrument cluster **101**. In an embodiment, the protective gear **103** may be a safety gear worn by the user proximal to the head of the user, such as, a collared jacket on the back of the user, a neck support, etc. In a preferred embodiment, the protective gear **103** is a head gear worn by the user. Henceforth, the protective gear **103** is referred to as a head gear, but the implementation of the interactive protection system **100** is not limited to a head gear alone. The vehicle is one of a two-wheeled vehicle, a three-wheeled vehicle, an IC engine vehicle, an electric vehicle, a hybrid electric vehicle, and an autonomous vehicle. The instrument cluster **101** in the vehicle is a display unit of the vehicle that accesses vehicular sensor data, displays, and transmits vehicle information to the user via the audio system **103b**, the wireless transceiver **103a**, and the user device **104**. The vehicular sensor data is generated by at least one of one or more speed sensors, one or more accelerometers, one or more level sensors, one or more vibration detectors, one or more gyroscope, one or more temperature sensors, one or more location sensors, and one or

more pressure sensors mounted on one of a body of the vehicle or the instrument cluster **101**. The vehicular sensor data comprises at least one of the indicator status, speed of the vehicle, energy levels of the vehicle, location of the vehicle, vibration of the vehicle, acceleration of the vehicle, tilt of the vehicle, data on ambient conditions temperature, air pressure of wheels, and gear position.

(33) The user device **104** is, for example, a cellular phone, a smart phone, a tablet computing device, an Ultrabook®, a laptop, a personal digital assistant, a touch centric device, etc., or any other mobile device configured for a wireless network **102**. In an embodiment, the wireless network **102** is a mobile communication network, the Internet, a local area network (LAN), a wide area network (WAN) or the Ethernet, a token ring, or via any appropriate communications media, etc. In a preferred embodiment, the wireless network **102** is Bluetooth® of Bluetooth Sig, Inc. The instrument cluster **101** comprises a vehicle wireless transceiver **101b** that enables wireless communication of vehicle information either to the audio system **103b** and the audio wireless transceiver **103a** or a voice assistant **111** in the user device **104**. In an embodiment, the audio wireless transceiver **103a** receives the vehicle information directly from the instrument cluster **101**. In another embodiment, the vehicle wireless transceiver **101b** communicates the vehicle information to the voice assistant **111**. The voice assistant **111** is partially embodied in the user device **104** and the voice assistant **111** utilizes the wireless transceiver of the user device **104** to transmit the vehicle information to the audio system **103b** through the audio wireless transceiver **103a**.

(34) In an embodiment, the voice assistant **111** is a combination of a voice assistant application **105** on the user device **104** and a voice cloud platform **108**. The voice assistant application **105** may be an Android based application, an iOS application, a Windows based application, etc. In an embodiment, the voice assistant application **105** is an application provided by an original equipment manufacturer (OEM) of the vehicle, the head gear **103**, and the instrument cluster **101**, that is available in the Application Store of the user device **104**. In an embodiment, the voice assistant application **105** acts as a central node which provides gateway between the instrument cluster **101**, the head gear **103**, and the voice cloud platform **108**. The user device **104** has other applications for call, messaging, and media storage capabilities.

(35) The voice cloud platform **108** is a natural language understanding platform and may be provided as service by service providers. The voice cloud platform **108** carries out speech to text conversion and finding intent of the user. The voice cloud platform **108** comprises a speech to text engine **109** converting an audio input to the text and a domain identification and intent matching engine **110** that finds the intent of the audio input. The voice assistant **111** receives the audio input from the user through the voice assistant application **105**. The voice assistant application **105** comprises a vehicle interface system **107** that acquires vehicle information from the instrument cluster **101** and a text to speech engine **106** to convert the vehicle information into audio output. The audio output is transmitted to the audio system **103b** via the wireless network **102**.

(36) The instrument cluster **101** further comprises a cluster controller **101a** that receives vehicular sensor data and generates the vehicle information to be transmitted. In an embodiment, the audio system **103b** in the head gear **103** is disposed proximal to an inner surface of the head gear **103**. The audio input from the user wearing the head gear **103** is transmitted to the voice assistant **111** through the audio wireless transceiver **103a**. The audio system **103b** generates user information comprising the audio input. The audio system **103b** communicates the vehicle information to the user. The head gear **103** further comprises multiple second sensors, such as, a sleep sensor and a breath analyzer for generating the second sensor data and a power supply to source power to the audio system **103b** and the audio wireless transceiver **103a** as will be described in FIGS. 3-4. In addition to the audio input, the user information comprises the second sensor data. The user information comprising the second sensor data is processed by the cluster controller **101a** for subsequent generation of the vehicle information. The second sensors may be electrically connected to the audio system **103b** and thus, the audio system **103b** generates the user

information.

(37) FIG. 2 exemplarily illustrates a block diagram showing an architecture of the instrument cluster **101** of the vehicle. As exemplarily illustrated, the instrument cluster **101** comprises the cluster controller **101a**, a memory unit **208**, a power supply **205**, the vehicle wireless transceiver **101b** as shown in FIG. 1, antennae (not shown) for the wireless transmission, the sensors, such as, an accelerometer and/or a gyroscope **203**, a vibration detector **204**, a location sensor (not shown?), and a control knob **201**. The vehicle wireless transceiver **101b** caters to different types of the wireless network **102**. The vehicle wireless transceiver **101b** may comprise a wireless communication module **202** for any one of the communication media including a Bluetooth, Wireless Fidelity (Wi-Fi) or Infrared means and a Global System for Mobile Communications (GSM) module **206** to communicate the vehicle information to the audio system **103b** wirelessly. The GSM module **206** has a corresponding GSM antenna **209**. The location sensor is a Global Positioning System (GPS) module **207** with a GPS antenna **210**. The power supply **205** drives the operation of the components of the instrument cluster **101**.

(38) The cluster controller **101a** receives the vehicular sensor data from a controller of the vehicle via a Controller Area Network (CAN) bus of the vehicle and generates the vehicle information. The cluster controller **101a** is at least one of a microprocessor, central processing unit (CPU) device, finite state machine, microcontroller, digital signal processor, logic, a logic device, an user circuit, an application specific integrated circuit (ASIC), a field-programmable gate array (FPGA), a chip, a digital circuit, an analog circuit, etc., or any combination thereof, capable of executing a series of commands, instructions, or state transitions. The components such as the GPS module **207**, the GSM module **206**, and the Wi-Fi/Bluetooth (any wireless communication medium) modules **202**, the accelerometer and/or the gyroscope **203**, the vibration detector, **204**, etc. are fitted inside a casing of the instrument cluster **101**. The respective antennae **209** and **210** are placed outside or inside the casing of the instrument cluster **101**, or anywhere on the vehicle body according to convenience and efficiency. The instrument cluster **101** further comprises a display unit with a cluster interface (not shown) for displaying the vehicular sensor data and the vehicle information. The cluster controller **101a** processes the vehicular sensor data and the sensor data from the sensors **203** and **204** in the instrument cluster **101** and generates vehicle information. The vehicular sensor data and the vehicle information are synchronized with a cloud database **211**.

(39) In an embodiment, a region proximal to the instrument cluster **101** comprises the control knob **201** for controlling the operation of the audio system **103b**. In another embodiment, the control knob **201** may be located on a surface of the head gear **103**. The control knob **201** controls audio levels inside the audio system **103b**, call accept/decline, turning on/off the audio system **103b**, without losing control of the vehicle. The control knob **201** is placed on the handlebar proximal to the indicator switches of the vehicle. The control knob **201**, may be hard press buttons or a joystick, has wired connection with the instrument cluster **101**. In an embodiment, the control knob **201** may be a soft press button on the cluster interface of the instrument cluster **101**. In an embodiment, the voice assistant **111** is invoked using the selection in the cluster interface and/or the control knob **201**. The voice assistant **111** is woken up only when needed to reduce the power consumption of the user device **104**.

(40) The GPS module **207** collects satellite data (real-time location data) and transfers it via serial communication to the cluster controller **101a**. The satellite data may be in the form of NMEA (National Marine Electronics Association) lines (worldwide standard for location data) which is parsed by the cluster controller **101a**, and the cluster controller **101a** analyses for navigation guidelines and the cluster controller **101a** transmits those navigational guidelines to the audio system **103b** via the Bluetooth/Wi-Fi (any wireless communication medium) module **202** in the form of audio. The voice assistant **111** reads out the warnings to the user in a language chosen in the audio system **103b**. In an embodiment, cluster controller **101a** transfers the real-time location data to the GSM module **206** to be synced on cloud database **211**. In an embodiment, the real-time

location data may also be stored in the flash memory **208**, in case where the GSM network is not available and later on synchronized with the cloud database **211** via the GSM antenna **209**, when the GSM network is available.

(41) The accelerometer and/or the gyroscope **203** send orientation and movement related data of the vehicle to the cluster controller **101a** which is processed and the cluster controller **101a** generates vehicle information comprising alerts and warnings to the user of the vehicle, such as, unusual tilt, unusual acceleration or deceleration. The cluster controller **101a** further transmits the alerts and the warnings to the audio system **103b** via the Bluetooth/Wi-Fi module (any wireless communication medium) **202** in the form of audio. The voice assistant **111** reads out the warnings to the user in a language chosen in the audio system **103b**.

(42) The vibration detector **204** sends sensor data which is further analyzed by the cluster controller **101a** to detect accident or predict part failure in the vehicle that comprises the vehicle information. The predicted part failure is indicated to the user as a warning inside the audio system **103b**. The voice assistant **111** reads out the warnings to the user in the audio system **103b**. In the case of an accident, the cluster controller **101a**, based on the sensor data of the vibration detector **204**, actuates the user device **104** to dial up emergency contacts of the user and emergency services for earliest assistance to the user.

(43) Vehicular sensor data is collected from any one of an engine control unit (ECU), a controller, a battery management system (BMS), etc. of the vehicle by the cluster controller **101a** via the CAN bus. The cluster controller **101a** analyses and generates vehicle information comprising critical warnings like low battery/fuel, overheat, part failure, over speed, rash driving, etc. and transmits to the audio system **103b** in the form of audio. The voice assistant **111** reads out the warnings to the user in a language chosen, for example, English, Hindi, etc., in the audio system **103b**.

(44) The GSM module **206** synchronizes all the vehicular sensor data and the generated vehicle information with the cloud database **211**. Any call, SMS or any other notification generated from the user device **104** is visible in the instrument cluster **101** and read out in the audio system **103b** and a required action can be taken as per user's wish with the help of the control knob **201**. For example, if the user gets a call from one of his/her contact, then the call alerts constituting the vehicle information is notified to the user inside head gear **103** or in the audio system **103b** as a voice notification. He/she gets to choose whether to accept/decline the call and take the necessary action with the help of control knob **201**. If the user gets a SMS, then the user may be instructed via audio about the same and given an option whether he/she wants to hear the SMS. In an embodiment, the voice assistant **111** reads out the SMS or the call alerts to the user. The user can choose to hear the SMS either with the help of control knob **201** or with audio input and after hearing the SMS, he/she can even choose to send a quick reply back to the sender. The voice assistant **111** facilitates all the operations mentioned above and holds a conversation with the user using the voice cloud platform **108**.

(45) FIG. 3 exemplarily illustrates a block diagram showing an architecture of the head gear **103** worn by the user of the vehicle. The head gear **103** comprises a driver or a controller **303**, second sensors **301** and **302**, a microphone **306** and at least one speaker, for example, a pair of speakers **304**, the audio wireless transceiver **103a**, the power supply **305**, and the control knob **201**. The wireless transceiver **103a** is a Bluetooth/Wi-Fi Tx/Rx (any wireless communication medium) module which can connect the head gear **103** with the instrument cluster **101**. The second sensors **301** and **302** detect the state of the user, such as, the drowsy state of the user, drunken state of the user using the sleep sensor **302** and the breath analyzer **301**. The second sensors **301** and **302** are mounted to the inner surface of the inner shell of the head gear **103** and connected to the controller **303**.

(46) The microphone **306** and the pair of speakers **304** constitute the audio system **103b**. The speakers **304** are attached on both sides to the inner surface of the inner shell of the head gear **103**. The microphone **306** is attached to a front portion of the head gear **103**. The speakers **304** and the

microphone **306** are wired to the controller. The power supply **305** is a low capacity battery that powers the speakers **304**, the microphone **306**, the controller **303**, and the second sensors **301** and **302**. In an embodiment, the control knob **201** is positioned to a side of the inner surface of the inner shell of the head gear **103**. The microphone **306** receives the audio input from the user and the speakers **304** deliver the vehicle information to the user. The audio system **103b** receives the audio input and the second sensor data from the second sensors **301** and **302** and generates the user information to be transmitted to the voice assistant **111** through the wireless transceiver **103a**. In an embodiment, the instrument cluster **101** transmits the vehicle information, such as, call alert to the speakers **304** through the wireless transceivers **101b** and **103a** of the instrument cluster **101** and the head gear **103**. In this embodiment, in response to the call alert, the audio input from the user is transmitted to the instrument cluster **101** through the wireless transceivers **101b** and **103a** of the instrument cluster **101** and the head gear **103**.

(47) The breath analyzer **301** ensures the user is not drunk while riding. The drunk state of the user is transmitted to the cluster controller **101a** and based on an analysis of the second sensor data comprising the drunk state, the cluster controller **101a** generates a warning and plays the warning in the speakers **304** of the audio system **103b** worn by the user alone or the audio system **103b** in the head gear **103**. The sleep sensor **302** continuously monitors eye movement of the user and detects a pattern in the eye movement and transmits it to the cluster controller **101a**. The cluster controller **101a** analyses the pattern of the eye movement and detects whether the user is sleepy or not. The cluster controller **101a** generates warnings and plays the warning in the speakers **304**. The voice assistant **111** reads out the warnings to the user in the speakers **304** of the head gear **103**.

(48) The pair of speakers **304** may play songs from the user device **104**, give alerts and warnings about the incoming and/or ongoing call, the navigation guidance, etc. In an embodiment, the controller **303** on the head gear **103** will transmit/receive all the above mentioned audio to and from the instrument cluster **101**. The microphone **306** will receive the audio input from the user to answer the ongoing call and accept voice commands from the user. The voice assistant **111** may be invoked using a voice command, for example, a wake word from the user.

(49) FIG. 4 exemplarily illustrates a perspective view of the head gear **103**. The head gear **103** comprises an outer shell **401**, an inner shell **402**, a shield **403**, and a strap (not shown) to fasten the head gear **103**. The head gear **103** comprises the pair of speakers **304** on the two opposite sides of the inner surface **402a** of the inner shell **402** of the head gear **103**. The microphone **306** is at the front portion **404** of the head gear **103**. The microphone **306** and the speakers **304** are connected to the wireless transceiver **103a** with an antenna **405**, the controller **303** illustrated in FIG. 3, and the control knob **201**. In an embodiment, the wireless transceiver **103a** and the controller **303** are housed in a casing and the antenna **405** and the control knob **201** are disposed on the casing. Additionally, the breath analyzer **301** is proximal to the microphone **306** of the audio system **103b** of the head gear **103** and the sleep sensor **302** is positioned closer to the eyes of the user, on the shield **403** of the head gear **103**. In an embodiment, a camera may be mounted on the vehicle body and a video feed can be transmitted to a heads-up display (not shown) inside the head gear **103** ahead of the shield **403** of the head gear **103**. The heads-up display may be helpful, when a rear view camera is mounted on the rear of the vehicle. The heads-up display with the audio system **103b** may support augmented reality and be helpful to improve navigation of the vehicle. The heads-up display may also display the vehicle information in the text format, such as, vehicle speed, gear position, fuel remaining, alerts related to vehicle etc.

(50) FIG. 5 exemplarily illustrates a flowchart showing a method for the wireless communication between the vehicle and the user executed by the interactive protection system **100** exemplarily illustrated in FIG. 1. At step **501**, the voice assistant **111** is invoked using at least one of an interface of the cluster interface of the instrument cluster **101**, a wake word from the microphone **306** of the audio system **103b**, and the control knob **201** of the audio system **103b**. The methods of invoking the voice assistant **111** vary for high speed and low speed of the vehicle. At high speeds,

hands-free invoking of the voice assistant **111** using the wake word or the control knob **201** on the handle bar will be used. At low speeds and stand still condition of the vehicle, the voice assistant **111** is invoked using the cluster interface or the control knob **201** in the head gear **103** is used. The voice assistant **111** indicates the invoking of the voice assistant **111** by a start-listening tone in the speakers **304** of the audio system **103b**. In an embodiment, the cluster controller **101a** indicates the invoking of the voice assistant **111** by playing a predetermined start-listening tone in the speakers **304** of the audio system **103b**. At step **502**, the voice assistant **111** receives user information from the audio system **103b**. That is, the voice assistant **111** receives audio input from the microphone **306** of the audio system **103b**. At step **503**, the voice assistant **111** converts the audio input to a compatible format of the cluster controller **101a** using the speech to text engine **109**. The text corresponding to the audio input is transmitted to the cluster controller **101a**. The audio input may be an instruction to the cluster controller **101a** to control actuation and settings of vehicle components, such as, headlamps, instrument cluster **101**, head light beam, illumination logo, seat lock, fuel lock, mode of the vehicle, turn signal indicators, vehicle ride modes etc.

(51) At step **504**, the cluster controller **101a** controls the actuators of the vehicle components based on the converted audio input. Based on the instruction in the audio input to adjust the settings or turn ON/ OFF of the vehicle components, the cluster controller **101a** controls the actuators of the instructed vehicle component. The audio input is identified to identify the vehicle component instructed by the speech to text engine **109**. Consider for example, the user wants to change the brightness setting of the instrument, change ride mode of engine or electric motor, control vehicle lamps, the user indicates the same as an audio input in the microphone **306** of the audio system **103b**. The speech to text engine **109** and the domain identification and intent matching engine **110** parses the audio input, identifies the vehicle component to be actuated, and the action to be performed. The speech to text engine **109** communicates the actuation to be performed to the cluster controller **101a**. The cluster controller **101a** may turn ON a LEFT/RIGHT turn signal lamp, turn ON a headlight, switch to high beam headlight, switch to low beam headlight, controls orientation of the headlamp-look up/down/left/right, turn ON illumination logo light, turn ON/OFF hazard switch, ENABLE/DISABLE sport mode, ENABLE/DISABLE limp home mode, change theme of the instrument cluster **101**, LOCK/UNLOCK the vehicle, ENABLE/DISABLE park mode or reverse mode of the vehicle etc.

(52) At step **505**, the cluster controller **101a** generates vehicle information from the vehicular sensor data, based on the audio input. The vehicle information comprises the alerts on energy levels of the vehicle, alerts on speed of the vehicle, alerts on indicator status, alerts in tilt of the vehicle, alerts on location of the vehicle, navigation guidance, call alerts, ambient weather, trip information, news coverage, alerts on drop of user device **104**, service history, group ride status, and emergency service assistance. Based on the audio input, the cluster controller **101a** processes the vehicular sensor data and generates the vehicle information corresponding to the audio input. The processing of the vehicular sensor data involves comparing the vehicular sensor data with thresholds and performing mathematical computations on the vehicular sensor data and the second sensor data from the head gear **103**. At step **506**, the voice assistant **111** transmits the generated vehicle information to the speakers **304** of the audio system **103b**.

(53) In an embodiment, voice assistant **111** may greet back the user, when the audio input from the user is a greeting, such as, a "HELLO". The voice assistant **111** may introduce itself when asked by the user. When the audio input is an enquiry about tire pressure, the voice assistant **111** access the tire pressure from the cluster controller **101a** and responds with the value for the tire pressure and asks the user to refill air if required. When the audio input is about planning a trip, the voice assistant **111** in communication with the cluster controller **101a** responds with the duration and distance left for the ongoing trip. When the audio input is about notifications on missed calls from contacts or favorite contacts, SMS or social media notifications, the cluster controller **101a** accesses the call and SMS alerts of the user device **104** and generates vehicle information. The

voice assistant **111** will spell out the call alert, SMS alert, and social media notification details, such as, contact name, number of missed notifications, etc. in the speakers **304** of the audio system **103b**. When the audio input in an enquiry on the weather conditions during the course of the trip, the voice assistant **111** responds accordingly, in co-ordination with the cluster controller **101a**. Similarly, the audio input may be an inquiry about the reminders, air quality, navigation, news, service history, medical appointments, personal health, etc. The voice assistant **111** fetches the vehicle information corresponding to each of these and responds to the user in the speakers **304** of the audio system **103b**. The audio input may pertain to requests to set alter or reset a reminder, planning, re-planning, rerouting a trip, initiate emergency assistance, positions of fellow riders in a group ride, pay toll, bills, book ticket, order food, switch ON/OFF appliances at home, book vehicle service appointment, etc. The voice assistant **111** communicates with the cluster controller **101a** and performs the actions requested. The voice assistant **111** transmits the status of the requested activity to the speakers **304** of the audio system **103b** in co-ordination with the cluster controller **101a**. The audio inputs are not limited to the list mentioned above and may be updated remotely by a service engineer or an OEM of the vehicle, the head gear **103**, and the instrument cluster **101** in due course of time. In an embodiment, the audio input may include multiple queries, request, or a combination of queries and requests, such as, a request for planning a trip merged with personal health information, vehicle health information, traffic information, weather information and air pollution information to provide appropriate navigational directions to the user.

(54) FIG. 6 exemplarily illustrates a flowchart showing invoking of the voice assistant **111** from a vehicle interface, for example, the control knob **201** proximal to the indicator switches, a hard press button on the instrument cluster **101**, or the cluster interface. As exemplarily illustrated, at step **601**, the vehicle ignition is turned ON and step **602**, a Bluetooth connection between the instrument cluster **101** of the vehicle and the user device **104** is established. If establishing the Bluetooth connection is unsuccessful, another attempt to establish the connection is done by the user of the vehicle. If the Bluetooth connection between the instrument cluster **101** and the user device **104** is established, at step **603**, the Bluetooth connection between the user device **104** and the head gear **103** or the audio system **103b** is established. If successful, at step **604**, the voice assistant **111** is enabled over the Bluetooth head gear **103** or the Bluetooth audio system **103b**. If unsuccessful at step **603**, then at step **605**, the voice assistant **111** is enabled over the audio I/O of the user device **104**. At step **606**, the control knob **201** is actuated. The control knob **201** on the handle bar, proximal to the indicator switches is triggered. In an embodiment, a hard press button on the instrument cluster **101**, or the cluster interface is actuated. The voice assistant **111** is invoked. At step **607**, the voice assistant **111** prompts the user to speak with a start-listening tone playing in the speakers **304** of the audio system **103b**. At step **608**, the voice assistant **111** receives the audio input from the user in the microphone **306** of the audio system **103b**. The voice assistant **111** performs parsing and speech to text conversion of the audio input and transmits the instructions to the cluster controller **101a**. At step **609**, the cluster controller **101a** performs the vehicle level action as described in detailed description of FIG. 5 and communicates the vehicle information to the voice assistant **111**. The voice assistant **111** performs text to speech conversion using the text to speech engine **106** and transmits the vehicle information as an audio response over Bluetooth to the speakers **304** of the audio system **103b** at step **610**. If at step **608** the audio input from the user is not received, the voice assistant **111** has to be invoked again.

(55) FIG. 7 exemplarily illustrates a flowchart showing invoking of the voice assistant **111** using a voice command or wake word, for example, "Hi Ntorq". As exemplarily illustrated, at step **701**, the vehicle ignition is turned ON and at step **702**, a Bluetooth connection between the instrument cluster **101** of the vehicle and the user device **104** is established. If establishing the Bluetooth connection is unsuccessful, another attempt to establish the connection is done by the user of the vehicle. If the Bluetooth connection between the instrument cluster **101** and the user device **104** is established, at step **703**, the Bluetooth connection between the user device **104** and the head gear

103 or the audio system **103b** is established. If successful, at step **704**, the voice assistant **111** is enabled over the Bluetooth head gear **103** or the Bluetooth audio system **103b**. If unsuccessful at step **703**, then at step **705**, the voice assistant **111** is enabled over the audio I/O of the user device **104**. At step **706**, the voice assistant **111** starts listening for the wake word from the audio system **103b**. At step **707**, the voice assistant **111** stops listening for the wake word from the audio system **103b**. At step **708**, the voice assistant **111** prompts the user to speak with a start-listening tone playing in the speakers **304** of the audio system **103b**. At step **709**, the voice assistant **111** receives the audio input from the user in the microphone **306** of the audio system **103b**. The voice assistant **111** performs parsing and speech to text conversion of the audio input and transmits the instructions to the cluster controller **101a**. At step **710**, the cluster controller **101a** performs the vehicle level action as described in detailed description of FIG. 5 and communicates the vehicle information to the voice assistant **111**. The voice assistant **111** performs text to speech conversion using the text to speech engine **106** and transmits the vehicle information as an audio response over Bluetooth to the speakers **304** of the audio system **103b** at step **711**.

(56) FIG. 8 exemplarily illustrates a flowchart showing invoking of the voice assistant **111** from the voice assistant application **105**. As exemplarily illustrated, at step **801**, the vehicle ignition is turned ON and at step **802**, a Bluetooth connection between the instrument cluster **101** of the vehicle and the user device **104** is established. If establishing the Bluetooth connection is unsuccessful, another attempt to establish the connection is done by the user of the vehicle. If the Bluetooth connection between the instrument cluster **101** and the user device **104** is established, at step **803**, a soft press in the interface of the voice assistant application **105** in the user device **104** is pressed and the voice assistant **111** is invoked. At step **804**, the voice assistant **111** prompts the user to speak with a start-listening tone playing in the speakers **304** of the audio system **103b**. At step **805**, the voice assistant **111** receives the audio input from the user in the microphone **306** of the audio system **103b**. The voice assistant **111** performs parsing and speech to text conversion of the audio input and transmits the instructions to the cluster controller **101a**. At step **806**, the cluster controller **101a** performs the vehicle level action as described in detailed description of FIG. 5 and communicates the vehicle information to the voice assistant **111**. The voice assistant **111** performs text to speech conversion using the text to speech engine **106** and transmits the vehicle information as an audio response over Bluetooth to the speakers **304** of the audio system **103b** at step **807**.

(57) FIG. 9 exemplarily illustrates a flowchart showing invoking of the voice assistant **111** from a vehicle interface, when the connection between the voice assistant application **105** and the voice cloud platform **108** is not established due to loss of the wireless network connectivity. The vehicle interface may be one of the control knob **201** proximal to the indicator switches on the handle bar, or a hard press button on the instrument cluster **101**, or the cluster interface. As exemplarily illustrated, at step **901**, the vehicle ignition is turned ON and at step **902**, a Bluetooth connection between the instrument cluster **101** of the vehicle and the user device **104** is established. If establishing the Bluetooth connection is unsuccessful, another attempt to establish the connection is done by the user of the vehicle. If the Bluetooth connection between the instrument cluster **101** and the user device **104** is established, at step **903**, the Bluetooth connection between the user device **104** and the head gear **103** or the audio system **103b** is established. If successful, at step **904**, the voice assistant **111** is enabled over the Bluetooth head gear **103** or the Bluetooth audio system **103b**. If unsuccessful at step **903**, then at step **905**, the voice assistant **111** is enabled over the audio I/O of the user device **104**. At step **906**, the voice assistant application **105** determines if wireless network connection, for example, internet connection, is available. If internet connection is not available, the voice assistant **111** on the user device **104** is enabled at step **907**. At step **908**, either the control knob **201** proximal to the indicator switches, or the hard press button on the instrument cluster **101**, or the cluster interface is actuated and the voice assistant **111** on the user device **104** is invoked. At step **909**, the voice assistant **111** prompts the user to speak with a start-listening tone playing in the speakers **304** of the audio system **103b**. At step **910**, the voice assistant **111** receives

the audio input from the user in the microphone **306** of the audio system **103b**. The voice assistant **111** performs parsing and speech to text conversion of the audio input on the user device **104** and transmits the instructions to the cluster controller **101a**. At step **911**, the cluster controller **101a** performs the vehicle level action as described in detailed description of FIG. 5 and communicates the vehicle information to the voice assistant **111**. The voice assistant **111** performs text to speech conversion using the text to speech engine **106** on the user device **104** itself, locally stores the vehicle information, and transmits the vehicle information as an audio response over Bluetooth to the speakers **304** of the audio system **103b** at step **912**. If at step **910** the audio input from the user is not received, the voice assistant **111** has to be invoked again.

(58) Embodiments of the interactive protection system discussed above provides technical advancement in the domain of rider assistance as follows: The concept of configuring the vehicle instrument cluster with additional features like GPS, GSM, Wi-Fi/Bluetooth etc. along with their respective antennae, accelerometer and gyroscope etc., is simple, most power efficient, and most compact solution for communicating with the user device. The power supply needed to power the instrument cluster supplies power to all these modules. In the head gear, there is only one communication module mounted, thus manufacturing the head gear is not complex and much smaller low capacity battery will be needed. Efficiently navigation related guidance can be transferred to the audio system or the head gear, without distracting the user. Intra-module signal interference in the head gear can be avoided as now all the modules which require antennae are placed together inside the instrument cluster and antennae are placed separate enough so that signals cannot create undesirable interference. Since all the modules like GPS, GSM, Wi-Fi/Bluetooth (any wireless communication medium) etc. along with their respective antennae, accelerometer & gyroscope, vibration detector etc. are intentionally incorporated inside the instrument cluster of the vehicle, there is no need to provide extra sealing from water and dust as the instrument cluster is already a sealed module. As the head gear/audio system requires Wi-Fi/Bluetooth (any wireless communication medium) and the other modules, such as, GPS, GSM, are part of the vehicle instrument cluster, the head gear is compact and cost effective as no extra set of microprocessor/microcontrollers are needed separately for head gear and there is no need to provide a high capacity battery for head gear/audio system. Additionally, radiation induced disorders may be prevented as the antennae for the GPS/GSM module is avoided in the head gear.

(59) Also, controlling the audio levels of the speakers, call accept/decline buttons are avoided/optional to give on an outer body of the head gear, as the control knob mounted on the handlebar, next to the indicator switches which is more convenient to use as a rider and doesn't require him/her to leave the handlebar for controlling audio system. The breath analyzer and the sleep sensor in the head gear warn the user and keep him awake until he reaches his destination to ensure safe journey. The option to enquire about the group ride status using the voice assistant allows for keeping a track of location and welfare of mates on a trip together.

(60) Using the audio system/head gear, during a trip, the user can control vehicle settings like brightness control of the instrument cluster, the headlamp control, enquire about call information, SMS notifications, etc., navigation assistance, traffic alert, POI, change settings of vehicle interface without physically halt the vehicle or removing his/her hand from the handle bar. The voice assistant efficiently performs all these functions based on the audio input from the user. The voice assistant learns from the audio inputs and the responses everyday and holds a conversation based on the context and intent identified in the audio input. In one embodiment, the vehicular sensor data is generated from the vehicle and may be transferred over Bluetooth to the user device. The voice assistant partly embodied on the voice cloud platform avoids local storage of speech to text, text to speech data, predefined queries and corresponding responses used by the voice assistant, in the user device. Since the intelligence of the voice assistant resides in the cloud platform, the voice assistant may be easily scaled up and updated with additional queries and responses to the queries. The method to invoke the voice assistant is easy and instructions to invoke may be displayed on cluster

interface, prior to start of the trip.

(61) In an embodiment, the methods of invoking the voice assistant vary for high speed and low speed of the vehicle. At high speeds, hands-free invoking of the voice assistant using the wake word or the control knob on the handle bar will be used. At low speeds and stand still condition of the vehicle, the voice assistant is invoked using the cluster interface. The voice processing as well as query response set resides on the voice cloud platform and this thereby eliminates the constraint of memory for in-vehicle systems, such as, the instrument cluster or the user device. The voice assistant can have conversations with rider on multiple domains as part of the architecture by understanding the context of the queries. Additional query response can be added remotely and deployed without hardware or software change at mobile application or vehicle level.

(62) Improvements and modifications may be incorporated herein without deviating from the scope of the invention.

LIST OF REFERENCE NUMERALS

(63) **101** Instrument Cluster **101a** Cluster controller **101b** Vehicle Wireless Transceiver **102** Wireless Network **103** Protective gear/Head gear **103a** Audio Wireless transceiver **103b** Audio system **104** User device **105** Voice assistant application **106** Text to Speech Engine **107** Vehicle Interface system **108** Cloud Platform **109** Speech to text Engine **110** Domain Identification and Intent Matching engine **111** Voice Assistant **201** Control Knob **202** Wireless communication module **203** Accelerometer and/or Gyroscope **204** Vibration detector **205** Power supply **206** GSM module **207** GPS module **208** Flash Memory **209** GSM antenna **210** GPS antenna **211** Cloud database **301** Breath Analyzer **302** Sleep Sensor **303** Controller **304** Speaker **305** Battery **306** Microphone **401** Outer shell **402** Inner shell **402a** Inner surface of inner shell **403** Shield **404** front portion of the protective gear **405** Antenna

Claims

1. An interactive protection system of a vehicle, the interactive protection system comprising: a voice assistant that comprises a voice assistant application on a user device and a voice cloud platform; an instrument cluster comprising: a cluster controller configured to generate vehicle information based on one or more vehicular sensor data, and at least one vehicle wireless transceiver comprising a Global System for Mobile Communication (GSM) module and configured to communicate the vehicle information to the voice assistant via a Global System for Mobile Communication (GSM) network; an audio system disposed in proximity to a head of a user and configured to generate user information; and an audio wireless transceiver configured to receive a vehicle information from the voice assistant via the GSM network, and transmitting the user information to the instrument cluster through the voice assistant for generating subsequent vehicle information, wherein the voice assistant is configured to communicate the vehicle information to the audio system based on a real time output that is processed from the one or more vehicular sensor data by the cluster controller, and the cluster controller: transfers satellite data to the GSM module and syncs the satellite data on a cloud database when the GSM network is available, and stores the satellite data in a flash memory when the GSM network is unavailable.

2. The interactive protection system as claimed in claim 1, wherein the voice assistant is partially embodied in the user device and comprises: a speech to text engine; a domain identification and an intent matching engine that are provided for converting the user information into compatible signal format for the cluster controller; and a text to speech engine provided for converting the vehicle information into audio form.

3. The interactive protection system as claimed in claim 1, wherein the audio system is disposed in proximity to the head of the user within the protective gear worn by the user directly over their head and disposed proximal to an inner surface of a protective gear worn by the user of the vehicle, the audio system comprises a microphone provided for receiving an audio input from the user, and

at least one speaker configured to transmit the vehicle information to the user, and the protective gear is one of a collared jacket on a back of the user, a neck support, and a head gear.

4. The interactive protection system as claimed in claim 3, wherein the protective gear further comprises: one or more second sensors for generating a second sensor data; a power supply to source power to the audio system and the audio wireless transceiver; and a control knob configured to control an operation of the audio system and disposed on at least one of a surface of the protective gear and a region in proximity to the instrument cluster of the vehicle, wherein the one or more second sensors are one or more of a sleep sensor and a breath analyzer, and the user information comprises at least one of an audio input from the audio system and the second sensor data from the one or more second sensors.

5. The interactive protection system as claimed in claim 1, wherein the voice assistant is configured to: receive an audio input from the audio system, be activated using one or more of an interface of the instrument cluster, a voice command as an audio input, and a control knob of the audio system, and control one or more actuators of a plurality of vehicle components based on the user information from the audio system.

6. The interactive protection system as claimed in claim 1, wherein the one or more vehicular sensor data is generated by at least one of one or more speed sensors, one or more accelerometers, one or more level sensors, one or more vibration detectors, one or more gyroscope, one or more temperature sensors, one or more location sensors, and one or more pressure sensors, one or more of the sensors being mounted on one of a body of the vehicle and the instrument cluster of the vehicle, the one or more vehicular sensor data comprises one or more of an indicator status, speed of the vehicle, energy levels of the vehicle, location of the vehicle, vibration in the vehicle, acceleration of the vehicle, tilt of the vehicle, and data on ambient conditions surrounding the vehicle including temperature, air pressure of wheels, and gear position, and the vehicle information comprises one or more of an alert on the energy levels of the vehicle, alert on speed of the vehicle, alert on indicator status, alert in tilt of the vehicle, alert on location of the vehicle, navigation guidance, call alert, ambient weather, trip information, news coverage, alert on drop of the user device, service history of the vehicle, group ride status, and emergency service assistance.

7. An interactive protection system of a vehicle comprising: an instrument cluster comprising: a cluster controller configured to generate vehicle information that is based on one or more vehicular sensor data, and at least one vehicle wireless transceiver comprising a Global System for Mobile Communication (GSM) module and configured to communicate the vehicle information to a protective gear of a user via a Global System for Mobile Communication (GSM) network, the protective gear being worn by the user; and the protective gear comprising: an audio system disposed in proximity to an inner surface of the protective gear for generating user information, and an audio wireless transceiver configured to receive the vehicle information from the instrument cluster through the at least one vehicle wireless transceiver and transmitting the user information to the instrument cluster for generating subsequent vehicle information, wherein the cluster controller: communicates the vehicle information to the audio system based on a real time output that is processed from the one or more vehicular sensor data, transfers satellite data to the GSM module and syncs the transferred satellite data on a cloud database when the GSM network is available, and stores satellite data in a flash memory when the GSM network is unavailable.

8. The interactive protection system as claimed in claim 7, wherein the protective gear further comprises one or more second sensors for generating a second sensor data, a power supply to source power to the audio system and the audio wireless transceiver, and a heads-up display unit for displaying the vehicle information as augmented reality, the one or more second sensors are one or more of a sleep sensor and a breath analyzer, the user information comprises an audio input from the audio system and the second sensor data from the one or more second sensors, and the audio system comprises a microphone provided for receiving an audio input from the user, and at least one speaker configured to transmit the vehicle information to the user, wherein, the protective gear

is one of a collared jacket on a back of the user, a neck support, and a head gear, the audio system is connected with a user device through the instrument cluster for one or more of receiving calls, receiving messages, and storing media, and a control knob is configured to control an operation of the audio system and disposed on at least one of a surface of the protective gear and a region in proximity to the instrument cluster of the vehicle.

9. The interactive protection system as claimed in claim 8, wherein the cluster controller is configured to: wirelessly receive the user information from the protective gear.

10. The interactive protection system as claimed in claim 7, wherein the one or more vehicular sensor data comprises one or more of a speed of the vehicle, energy levels of the vehicle, location of the vehicle, vibration of the vehicle, acceleration of the vehicle, tilt of the vehicle, and data on ambient conditions surrounding the vehicle, the data on ambient conditions including temperature, air pressure of wheels, and gear position, the one or more vehicular sensor data is generated by at least one of one or more speed sensors, one or more accelerometers, one or more level sensors, one or more vibration detectors, one or more gyroscope, one or more temperature sensors, one or more location sensors, and one or more pressure sensors, one or more of the sensors being mounted on one of a body of the vehicle and the instrument cluster of the vehicle, and the vehicle information comprises one or more of an alert on the energy levels of the vehicle, alert on speed of the vehicle, alert on location of the vehicle, navigation guidance, and call alert.

11. A protective gear, the protective gear being worn by a user of a vehicle, the protective gear comprising: an audio system disposed in proximity to an inner surface of the protective gear for generating user information; and an audio wireless transceiver configured to receive vehicle information from an instrument cluster of the vehicle and transmitting the user information to the instrument cluster for generating subsequent vehicle information.

12. The protective gear as claimed in claim 11, wherein the protective gear further comprises one or more second sensors for generating a second sensor data and a power supply to source power to the audio system, the one or more second sensors are one or more of a sleep sensor and a breath analyzer, and the protective gear is one of a collared jacket on a back of the user, a neck support, and a head gear.

13. The protective gear as claimed in claim 11, wherein the vehicle information comprises one or more of an alert on energy levels of the vehicle, alert on speed of the vehicle, alert on location of the vehicle, navigation guidance, and call alert based on the one or more vehicular sensor data, the one or more vehicular sensor data comprises one or more of a speed of the vehicle, the energy levels of the vehicle, location of the vehicle, vibration of the vehicle, acceleration of the vehicle, tilt of the vehicle, data on ambient conditions temperature, air pressure of wheels, and gear position, and the one or more vehicular sensor data is generated by at least one of one or more speed sensors, one or more accelerometers, one or more level sensors, one or more vibration detectors, one or more gyroscope, one or more temperature sensors, one or more location sensors, and one or more pressure sensors, one or more of the sensors being mounted on one of a body of the vehicle and the instrument cluster of the vehicle.

14. A method for wireless communication between a vehicle and a user of the vehicle, the method being executed by an interactive protection system that comprises: an instrument cluster comprising a cluster controller configured to generate vehicle information based on one or more vehicular sensor data and at least one vehicle wireless transceiver comprising a Global System for Mobile Communication (GSM) module and configured to communicate the vehicle information to a voice assistant partially embodied in a user device via a Global System for Mobile Communication (GSM) network; an audio system disposed in proximity to a head of the user and configured to generate user information; and an audio wireless transceiver configured to receive a vehicle information from the voice assistant via the GSM network, and communicating the user information to the instrument cluster through the voice assistant for generating subsequent vehicle information, the method comprising the steps of: invoking the voice assistant using one of an

interface of the instrument cluster, a voice command from the audio system, and a control knob of the audio system; receiving the user information from the audio system by the voice assistant; converting the user information to a compatible format of the cluster controller, by the voice assistant; controlling actuators of a plurality of vehicle components by the cluster controller, based on the converted user information from the audio system; generating vehicle information by the cluster controller from the one or more vehicular sensor data, based on the converted user information; transmitting the vehicle information to the audio system by the voice assistant; communicating, by voice assistant, the vehicle information to the audio system based on a real time output that is processed from the one or more vehicular sensor data by the cluster controller; transferring, by the cluster controller, satellite data to the GSM module and syncing the satellite data on a cloud database when the GSM network is available; and storing, by the cluster controller, the satellite data in a flash memory when the GSM network is unavailable.

15. The method as claimed in claim 14, wherein the audio system is disposed in proximity to a head of the user within a protective gear worn by the user directly over their head and disposed in proximity to an inner surface of the protective gear worn by the user of the vehicle, a control knob is configured to control an operation of the audio system and disposed on at least one of a surface of the protective gear and a region in proximity to the instrument cluster of the vehicle, the voice assistant comprises a voice assistant application on the user device and a voice cloud platform, and the protective gear is one of a collared jacket on a back of the user, a neck support, and a head gear.
