

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408947
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Vicenzi; Federico et al.

External fixator for calcaneus fractures

Abstract

The present disclosure relates to an external fixator for orthopedic use, in particular for the treatment of calcaneus fractures, comprising: a rigid support for a first clamp for fixing bone screws; a second support for a second clamp that is hinged at an end of the rigid support; a third support for a third clamp that is hinged at an end of the rigid support; the rigid support being configured as a guide with the first clamp slidingly mounted thereon. The fixator according to the invention is made of radiolucent material with joint elements comprising partially radiolucent or radiopaque materials and configured to allow orienting the bone screws held by the clamps in directions that are tilted to each other.

Inventors:	Vicenzi; Federico (Verona, IT), Caiaffa; Vincenzo (Bari, IT), Venturini; Daniele (Povegliano Veronese, IT)
Applicant:	Orthofix S.R.L. (Bussolengo, IT)
Family ID:	74194888
Assignee:	Orthofix S.R.L. (Bussolengo, IT)
Appl. No.:	18/250488
Filed (or PCT Filed):	October 28, 2021
PCT No.:	PCT/EP2021/080024
PCT Pub. No.:	WO2022/090410
PCT Pub. Date:	May 05, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230404623 A1	Dec. 21, 2023

Foreign Application Priority Data

IT 102020000025933 Oct. 30, 2020

Publication Classification

Int. Cl.: A61B17/64 (20060101)

U.S. Cl.:

CPC A61B17/6416 (20130101);

Field of Classification Search

CPC: A61B (17/6416); A61B (17/6425); A61B (17/6466); A61B (17/6475); A61B (17/6483)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2006/0229604	12/2005	Olsen	606/54	A61B 17/6425
2010/0222778	12/2009	Bagnasco	606/58	A61B 17/66
2014/0257288	12/2013	Chang	606/59	A61B 17/645
2014/0371801	12/2013	Dall	606/86R	A61B 17/6441
2016/0151099	12/2015	Olsen	606/289	A61B 17/6458
2017/0209177	12/2016	Kachooei	N/A	A61B 17/6458
2018/0103987	12/2017	Mullaney	N/A	A61B 17/6475

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2945553	12/2014	EP	N/A
UB20159689	12/2016	IT	N/A
2004167062	12/2003	JP	A61B 17/6425

OTHER PUBLICATIONS

English translation of JP-2004167062-A (Year: 2004). cited by examiner
European Patent Office International Searching Authority, International Search Report for PCT/EP2021/080024, Dec. 1, 2021, 3 pages. cited by applicant

Primary Examiner: Harvey; Julianna N

Background/Summary

(1) This application is a national phase application of PCT/EP2021/080024, filed Oct. 28, 2021, which claims priority to and the benefit of Italy Application No. 102020000025933, filed Oct. 30, 2020, both of which are incorporated herein in their entireties.

FIELD OF APPLICATION

(2) The present invention relates to an external fixator for orthopedic use, in particular for the treatment of calcaneus fractures.

(3) More particularly, the present disclosure relates to an external fixator comprising at least three clamps for bone screws supported independently of each other.

PRIOR ART

(4) Calcaneus fractures are about 1% or 2% of all fractures that require orthopedic surgery.

(5) In professional literature, the treatment of calcaneus fractures has always been considered a difficult challenge for an orthopedic surgeon. The anatomy and biomechanics of the calcaneus explain the difficulties in treating this type of fractures since the bone is constantly subjected to compressive forces. Indeed the calcaneus works as sesamoid bone in the plantar achilleo-calcaneus system during the execution of the step and is loaded by the body weight; moreover, it has delicate cartilage surfaces that are part of complex joints such as the Chopard and the subtalar.

(6) There are currently two methodologies of approach to calcaneus fractures, and which can be defined conservative or surgical. In the first case, surgery is avoided, and an attempt is made to reduce the fracture from the outside by minimizing manipulation.

(7) However, this methodology has little chances of effective fracture reduction and fixation and often involves a high risk of complications.

(8) In the second case, an open reduction surgical technique is performed with an internal fixation at least in fractures of the II, III and IV type, according to a well-known Sanders classification; however, even this solution is not entirely without risks or complications.

(9) To date, the diatribe between the adoption of a conservative treatment or surgical treatment of this type of fracture remains unsolved since neither of the two methodologies can guarantee good results and the absence of early or late major complications.

(10) In recent years, the so-called minimally invasive surgery is being imposed, which aims at achieving the best functional results by minimizing the access routes and exposure of the calcaneus, while preserving the anatomical structures and the hematoma following the fracture. This technique has led to a decrease in surgical times and related complications.

(11) If the main objective of the treatment of calcaneus articular fractures is the restoration of the three-dimensionality of the calcaneus, with particular regard to the correct alignment on the axial and coronal plane and to the height of the calcaneal body, rather than the reconstruction of the articular congruence of the sub-talus region, the use of a minimally invasive technique of percutaneous reduction and synthesis by means of external fixation appears more than suitable in order to obtain these objectives, also allowing to obtain a stable fixation with a reduced risk of major complications.

(12) The known technique already provides a so-called mini-external fixator comprising three clamps for holding at least six bone screws, two per clamp, and with one of the clamps supported by an arm that can be angularly displaced with respect to the other two clamps to allow the fixation of thalamic fragments.

(13) By using six screws with the external fixator the incidence of screw loosening and the resulting loss of reduction appear to reduce. In some selected cases, the high stability of the device

allows early mobilization and an initial partial weight, reducing the risk of stiffness and the healing time.

(14) Although advantageous under various aspects, and substantially satisfying the purpose, this mini-fixator already on the market still has some drawbacks.

(15) First of all, the clamps are rigidly interconnected substantially on a same plane and only one of them can rotate with respect to the other two but always only on the same plane.

(16) Secondly, the calcaneus area is relatively small to be treated, and the use of a mini-fixator also represents an important encumbrance that hinders the surgeon's visualization both during the surgical phase and during subsequent radiographic checks.

(17) Furthermore, the mini-fixators currently available do not allow the screws to be applied independently of each other in the same clamp, making the surgical technique more complex.

(18) Documents IT UB20 159 689 A1 and EP 2 945 553 A1 disclose fixators according to the prior art. In particular, it is observed that the fixator according to IT UB20 159 689 A1 is composed of a main body and two auxiliary bodies hinged thereto, the two hinging axis being parallel to each other.

(19) The technical problem underlying the present invention is to provide a new external fixator for orthopedic use, in particular for the treatment of calcaneus fractures, having structural and functional features such as to overcome the drawbacks of the solutions currently proposed by the prior art.

(20) Such a fixator would allow more suitably treating fractures of at least two if not more fragments of the calcaneus, also allowing a faster reduction of these fractures and an improved restoration of the patient's walking function.

SUMMARY OF THE INVENTION

(21) The solution idea underlying the present disclosure is to provide a rigid structure supporting only one clamp and to articulate the support arms of the other two clamps to this rigid structure so that they are free to be angularly moved independently from each other. Furthermore, at least one clamp is slidingly mounted on the respective support arm.

(22) Based on the above solution idea, the technical problem is solved by an external fixator for orthopedic use, in particular for the treatment of calcaneus fractures, comprising: a rigid support for a first clamp for fixing bone screws; a second support for a second clamp hinged at an end of the rigid support; a third support for a third clamp, which is in turn hinged at an end of the rigid support; the rigid support being configured as a guide with the first clamp slidingly mounted thereon.

(23) Advantageously, the end of the rigid support for connection with the second and third supports is configured to house respective hinges having axes that are orthogonal to each other, so as to allow adjusting at will the angle of the second and third supports with respect to the rigid support.

(24) It should be noted that the third support is also configured as a guide with the third clamp sliding thereon.

(25) More particularly, the third clamp is mounted on an "L"-shaped element having a slider base side sliding on the third support and an elevated portion that is perpendicular to the base side whereon a jaw lid of the third clamp is coupled.

(26) The rigid support has a "U"-shaped cross-section, with the valley of the U shape provided with an internal longitudinal thread and the open ends provided with opposite guides; an externally threaded cylindrical carriage is sliding by screwing into the longitudinal thread of the rigid support.

(27) The first clamp has a base with a portion that is projecting downwards to be held in an annular recess formed on said threaded cylindrical carriage.

(28) Furthermore, the rigid support is made of a partially radiolucent material.

(29) This particular conformation is also common to the third support and to the related sliding clamp.

(30) Advantageously, the rigid support and said second and third supports are made of radiolucent

material, whereas the hinge elements and the cylindrical carriage are made of partially radiolucent or radiopaque material.

(31) It should also be noted that at least one clamp has a seat for receiving a bone screw that has angular recesses to allow housing the corresponding bone screw in a tilted manner with respect to the other bone screw that is transversally held by the clamp itself.

(32) The seat with angular recesses is the one facing towards the outside of the fixator.

(33) A cage element inserted in the seat with angular recesses to guide and angularly orient a corresponding bone screw into the corresponding angled seat of the clamp is also provided.

(34) Essentially at least one of the clamps has two seats for receiving respective bone screws, one of which is transversal and the other one tilted with respect to the first seat.

(35) In a preferred embodiment the second clamp has a base corresponding to the second support and a removable jaw lid that is mounted on the base by means of a tightening screw coupling.

(36) This tightening screw is inserted in a threaded hole passing through the base portion and the head of the tightening screw is hiddenly received into the base portion of the second support.

(37) Finally, each clamp comprises a respective transversal through-hole placed at one end of the clamp towards the outside of the fixator to house a corresponding K-wire.

(38) The features and advantages of the external fixator according to the present disclosure will become apparent from the following description of an embodiment given by way of non-limiting example with reference to the appended drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 shows a perspective and schematic view of an external fixator for orthopedic use made according to the present disclosure to treat in particular calcaneus fractures;

(2) FIG. 2A shows a perspective view of an initial application of the fixator of FIG. 1 and a calcaneus shown by schematic lines;

(3) FIG. 2B shows a perspective view of the final application of the fixator of FIG. 1 and a calcaneus shown by schematic lines;

(4) FIG. 3 shows a perspective and schematic view of the fixator of the present disclosure according to a different observation point;

(5) FIG. 4 shows a perspective and schematic view of the fixator of the present disclosure according to a further and different observation point;

(6) FIG. 5 shows a longitudinal sectional view of the fixator of the present disclosure;

(7) FIG. 6 shows a perspective, schematic and partial view of a central portion of the fixator of the present disclosure;

(8) FIG. 7 shows a perspective view in detached parts of the fixator of FIG. 1;

(9) FIGS. 8, 9 and 10 show respective perspective and schematic views of portions of clamps constituting the fixator of FIG. 1;

(10) FIGS. 11 and 12 show respective perspective and schematic views of further and conjugated portions of the clamps constituting the fixator of FIG. 1;

(11) FIGS. 13A and 13B show respective perspective views of internal components of the fixator of FIG. 1;

(12) FIG. 14 shows a top view of the fixator of FIG. 1 applied to a calcaneus shown by schematic lines;

(13) FIG. 15 shows a perspective view of the fixator of FIG. 1 with indicated the handling possibilities represented by arrows.

DETAILED DESCRIPTION

(14) With reference to these figures, reference number 1 globally and schematically indicates an

external fixator for orthopedic use made according to the present disclosure for the treatment of calcaneus fractures and any way of the achilleo-calcaneus plantar region.

(15) The fixator **1** comprises three clamps, **11**, **21**, **31**, each intended to receive and hold at least one pair of conventional implanted bone screws **2** of the foot bone.

(16) The fixator **1** comprises a rigid support **10** for a first clamp **11** for holding bone screws **2**.

(17) This rigid support **10** is a kind of track section whereon the clamp **11** is mounted sliding as a slider, though it may be constrained in a pre-fixed position along the support **10** by means of a fixing adjustment screw, as it will be seen hereinafter.

(18) More particularly, as shown in FIG. **4**, the rigid support **10** has a “U”-shaped cross-section, with the valley of the U provided with an internal longitudinal threading **14** and the open ends provided with opposite guides **16** and **17**. In the following description the support **10** extended according to a generic longitudinal axis X-X will be considered.

(19) The first clamp **11** comprises a base **12** mounted sliding on the guides **16** and **17** and a jaw lid **13** on top of the base **12** and holds therewith the transversally extended bone screws **2**.

(20) A fixing screw **41** is provided to constrain the jaw lid **13** on the base **12**. This screw **41** has an enlarged head with an Allen seat and a threaded stem inserted by screwing in a corresponding hole centrally obtained in the base **12** between the seats for receiving the transversal bone screws **2**.

(21) The base **12** of clamp **11** has a central portion **19** protruding downwards to be held in an annular recess **18** centrally formed on a threaded cylindrical carriage **15**.

(22) The smooth stem **46** of the screw **44** is received and is rotatable in the hole of the tapered end **55** of the third support **30**.

(23) The externally threaded cylindrical carriage **15** is sliding by screwing in the longitudinal threading **14** of the rigid support **10** along the X-X axis. A polygonal-section Allen seat **6** is formed at a free end of the carriage **15** and allows moving the carriage **15** by screwing by means of a maneuvering stem (not shown). The carriage **15** is substantially a sliding screw in the nut screw **14**.

(24) The carriage **15** is shown in a perspective view in FIG. **13B** and comprises at an end thereof **85** an elastic-prong crown that allows generating a friction on the rotation during the advancement. The friction obtained with this elastic interference prevents the free rotation of the screw carriage so that it does not accidentally unscrew, losing its position or preload on the fracture gap.

(25) The annular recess **18** of the carriage **15** supports and holds the central portion **19** of the base **12** which as a whole slides along the guides **16** and **17**. Therefore, the advancement or retraction of the cylindrical carriage **15** below the base **12** along the X-X axis of the support **10** also moves the whole clamp **11** in the same axial direction.

(26) Advantageously, a solid end **4** of the rigid support **10** is shaped so as to receive a first joint hinge **5** between the rigid support **10** and a second support **20** for a second clamp **21** for holding bone screws **2**.

(27) The hinge **5** is visible in the section of FIG. **5** and has the peculiarity of being a screw **8** of non-magnetic material, for instance aluminum, titanium alloy or non-magnetic steel.

(28) A second joint hinge **7** is also provided between the rigid support **10** and a third support **30** for a third clamp **31**.

(29) This second hinge **7** is received still in the end solid portion **4** of the rigid support **10** and is extended according to a rotation axis indicated in FIG. **1** as Axis1.

(30) The other joint hinge **5** with the second support is instead extended according to a rotation axis indicated as Axis2, which is orthogonal to the preceding axis Axis1.

(31) The two rotation axes Axis **1** and Axis **2** are orthogonal to each other, as shown in FIG. **1**. In particular, the third support has the Y-Y axis normally arranged with respect to the perpendicular to the sliding plane of the first horizontal clamp **11**. The side clamp **21** has the hinge **5** that allows the varus-valgus correction and may be rotated even at the end of the surgery once the fixator **1** has already been positioned.

(32) To ensure a high seal of the hinge **5**, a conical coupling has been designed, which is forced by

a screw, similar to a morse cone, thus creating a stable construction.

(33) This configuration of the hinges **5**, **7** allows the second support **20** and the third support **30** to be angularly tiltable with respect to the resting plane of the first rigid support **10** which also the X-X axis belongs to.

(34) In the drawings, Z-Z and Y-Y indicate the longitudinal extension axes of the second **20** and third supports **30**, respectively.

(35) Returning to the structure of the second support **20**, it should be noted that said second support **20** is shorter than the rigid support **10** being extended along the Z-Z axis by a tract that is smaller than the extension of the first support along own X-X axis.

(36) Thanks to the joint represented by the hinge **5**, the second support **20** may be angularly displaced with respect to the resting plane of the first support **10** and the respective X-X and Z-Z axes form an angle between them.

(37) The second clamp **21** comprises a base **22** and a jaw lid **23** on top of the base **22** and holds therewith the transversally extended bone screws **2**.

(38) The second support **20** itself represents the base **22** of the second clamp **21** and comprises at an end, which will be defined external, a transversal through-hole **52** to receive a first stabilization Kirschner wire (or K-wire).

(39) A screw **24** with enlarged head **26** having an Allen seat is provided to constrain the jaw lid **23** on the base **22** of the second clamp **21**.

(40) The screw **24** is inserted in a threaded hole **25** passing through the base portion **22** and the jaw lid **23** according to a direction orthogonal to the Z-Z axis of the second support **20**.

(41) An enlarged portion **27** of the hole **25** hiddenly receives the enlarged head **26** of the screw **24** in the base portion **22** of the second support **20**.

(42) Essentially, the head of the fixing screw is hiddenly housed in the base portion **22** of the second support **20** and operated from below.

(43) As well shown in FIG. **6**, the third support **30** is articulated to the solid end portion **4** of the rigid support **10** by means of the coupling with the hinge **7**.

(44) A fork formed by a pair of annular prongs **28**, **29** on top of the solid portion **4** holds a tapered and perforated end **55** of the third support **30**, also receiving the hinge **7**.

(45) The hinge **7** is structured as a kind of bolt having a screw portion **44** with smooth stem **46** and threaded end and a nut **45** that is internally polygonal-shaped, for instance hexagonal. The screw **44** and the nut **45** are coupled by screwing to form the hinge **7** body, with interposition of an elastic element **47**.

(46) At least one of the annular prongs **28**, **29** has a polygonal shaped hole **3**, for instance hexagonal, so as to receive by shape coupling the corresponding nut **45** shape, thus preventing it from rotating in the hole **3**.

(47) Advantageously, this conformation of the hinge **7** makes the fixator **1** ambidextrous thanks to the particular design of the screw **44** for blocking the hinge of the third support extended in a tilted direction.

(48) Let us now examine the structure of the third support **30** in greater detail.

(49) The fixator **1** comprises a rigid support **10** for a first clamp **11** for holding bone screws **2**.

(50) Analogously to the first support **10**, the third support **30** is a kind of track whereon the third clamp **31** is mounted sliding as a slider.

(51) In this case as well, the clamp **31** may be constrained in a pre-fixed position along the third support **30** by means of a fixing adjustment screw, as it will be seen hereinafter.

(52) More particularly, as shown in FIGS. **4** and **5**, the third support **30** has a "U"-shaped cross-section, with the valley of the U shape provided with an internal longitudinal threading **34** and the open ends provided with opposite guides **36** and **37**. As seen previously, the third support **30** is extended according to a longitudinal Y-Y axis that is oblique to the extension X-X axis of the rigid support **10**.

(53) The third clamp **31** comprises a base **32** mounted sliding on the guides **36** and **37** and a jaw lid **33** on top of the base **32** and holds therewith the transversally extended bone screws **2**.

(54) Advantageously, the base **32** is “L”-shaped with a slider side **38** of the “L” shape sliding on the guides **36**, **37** and the other side **39** that is a perpendicularly extended elevated portion and whereon the jaw lid **33** is coupled.

(55) Therefore, with respect to the first clamp **11** of the rigid support **10**, the third clamp **31** of the third support **30** is supported by the portion **39** that is elevated perpendicularly to the direction of the Y-Y extension axis of the third support **30** itself.

(56) A fixing screw **42** is provided to constrain the jaw lid **33** on the elevated portion **39** of the base **32**. This screw **42** has an enlarged head with Allen seat and threaded stem inserted by screwing in a corresponding hole centrally obtained in the elevated portion **39** of the base **32** between the seats for receiving the transversal bone screws **2**.

(57) The slider portion **38** of the base **32** of the clamp **31** has a central portion **49** protruding downwards to be held in an annular recess **48** centrally formed on a threaded cylindrical carriage **35**.

(58) The cylindrical carriage **35** is sliding by screwing in the longitudinal threading **34** of the third rigid support **30** along the Y-Y axis. Said screw carriage **35** has a structure that is totally identical to that of the carriage **15** and is shown in FIG. **13B** with the end **85** provided with an elastic-prong crown.

(59) A polygonal-sectioned Allen seat **46** is formed at a free end of the carriage **35** and allows moving the carriage **35** by screwing by means of a maneuvering stem (not shown). The carriage **35** is substantially a sliding screw in the nut screw **34**.

(60) The annular recess **48** of the carriage **35** supports and holds the central portion **49** of the slider base **32**, which as a whole is sliding along the guides **36** and **37**. Therefore, the advancement or retreat of the cylindrical carriage **35** below the slider base **32** along the Y-Y axis of the third support **30** also moves in the same axial direction along the third clamp **31**.

(61) In a preferred embodiment, the supporting structure of the fixator **1** is made of radiolucent material for instance of a composite material, (for instance Peek or Ultem) loaded with carbon fiber.

(62) Load-bearing structure indicates both the rigid support **10** and the second and third supports **20** and **30**, as well as the clamps **11**, **21** and **31**.

(63) Moreover, even the structure of the hinges **5** and **7** and/or of the screws **15** and **35**, which allow the clamps **11** and **31** to slide, may be made of an X-rays partially transparent material, such as for instance aluminum.

(64) Now, with particular reference to the examples of FIGS. **8**, **9** and **10**, the housing seats of the bone screws **2** extended transversally in each clamps **11**, **21** or **31** are described in greater detail.

(65) FIG. **8** shows in a perspective view the internal surface of the jaw lid **13** of the first clamp **11**. From this figure it can be observed how a seat **61** for bone screw is conventionally configured as a semi-circular section channel whereas the other seat **62** is instead shaped with angular recesses.

(66) More particularly, the seat **62** comprises an almost hemispherical-shaped central portion **63** joined with two opposite flared and semi conical-shaped seats **64**.

(67) This set of shaped seats **63**, **64** defines and delimits with corresponding and joined shaped seats formed in the other base component **12** of the clamp **11** a maneuvering space schematized by the double cone identified by the dotted lines in FIG. **8**.

(68) A small cage **65** for holding a bone screw **2** is housed in this maneuvering space which helps angularly positioning the bone screw located in the outermost seat of the clamp with respect to the central body of the fixator **1**.

(69) The cage **65** is shown in a perspective view in FIG. **13** and is structured with a spheroidal central portion **68** joined to two opposite truncated-cone portions **69** to adhere to the internal walls of the receiving seats **63**, **64** and allow rotating the bone screw housed in said seats with

predetermined angular excursion.

(70) In a completely analogous way, even the other two clamps **21** and **31** have shaped seats with angular recesses to allow the bone screws **2** located more outside the fixator to be angularly movable with respect to an alignment transversal to the clamp of the innermost bone screw.

(71) In FIG. **9** the shape of the elevated portion **39** of the “L”-shaped clamp is shown, which also has in this case as well a seat **71** for bone screw **2** conventionally configured as a semi-circular section channel whereas the other seat **72** is instead shaped with a semi-spherical central portion **73** and opposite angular recesses defined by the flared and semi-conical seats **74**.

(72) In FIG. **10** the shape of the base portion **20** of the second clamp **21** is shown, which has in this case as well a seat **81** for bone screw **2** conventionally configured as a semi-circular section channel whereas the other seat **82** is instead shaped with a semi-spherical central portion **83** and opposite angular recesses defined by the flared and semi-conical shaped seats **84**.

(73) In FIG. **11** the base portion **12** of the first clamp is schematically shown with seats for the respective bone screws **2** joined to the seats of the lid shown in FIG. **8**. In this figure the cage **65** is shown in section.

(74) Let us now briefly see the operation and advantages of the orthopedic fixator **1** according to the present disclosure.

(75) The fixator **1** offers a high mechanical stability due to the possibility of positioning and holding at least three distinct pairs of two bone screws **2**, with each pair held by one of the respective clamps **11**, **21** and **31**.

(76) The three pairs of bone screws **2** are intended to connect to each other, through the rigid structure of the body of the fixator **1**, three different areas of the calcaneus close to each other.

(77) As shown in FIG. **2**, the fixator is easier to apply thanks to the possibility of an initial temporary positioning with K-wires, indicated with reference number **70**, placed at the ends of the clamps in the respective holes **51**, **52** and **53**. These K-wires allow the fixator **1** to be temporarily fixed according to the orthopedic surgeon's judgment and do not interfere with the subsequent insertion of the final stabilization bone screws **2**, being positioned at the extreme and peripheral dimensions of the fixator **1**. The K-wires are removed upon insertion of the bone screws **2**.

(78) The structure of the fixator **1** allows at least two clamps to slide independently, the first **11** and the third **31** clamps mounted sliding on their respective supports **10** and **30**.

(79) The first clamp **11** is sliding on a substantially horizontal guide, extended along the X-X axis, whereas the third clamp is sliding on the oblique guide represented by the third support **30** extended along the Y-Y axis, which is oblique with respect to the previous one.

(80) The lead screws **15** and/or **45**, placed inside the tracks **10** and **30** supporting the respective sliders **12** and **32**, allow the axial movement of the respective clamps and thus of the fragments of the fracture in order to generate preload on the fracture gap and a reconstruction of the calcaneal geometry. The particular elastic interference shape, thanks to suitable cuts in the end part of the thread of the lead screw, further allows friction of the screw itself, thus preventing the accidental unscrewing thereof.

(81) Furthermore, the fixator **1** offers the possibility to orient the position of the second support **20** and of the related second side clamp **21** in the most adherent varus valgus position to the anatomy of the calcaneus, this arrangement is schematically shown in the top view of FIG. **12**.

(82) This possibility, along with that of orienting at least one of the two bone screws **2** with respect to the other, in particular the external screws held by the clamps, allow encountering the various anatomical sites with simplicity and safety.

(83) With respect to the known solutions, the fixator **1** application technique is therefore facilitated due to the following factors: the screws **15**, **35** for moving the sliding clamps **11**, **31** are also smaller in size than the current screws for moving the clamps, thus making the fixator body substantially transparent in radiographs; the insertion of K-wires **70** allows delimiting the intervention field and keeping the position of the fixator stable, allowing the surgeon to check

before inserting the bone screws **2**; the closure from below of the jaw lid **23** of the second clamp **21** favors the assembly in situ since the tilted third support that bears the upper clamp represents an encumbrance that would make it difficult to close the lid by means of a screw inserted on top; the possibility of orienting the outermost bone screws to the fixator at the ends makes it easier to select the desired anatomical site.

(84) The closure of the jaw lid **23** of the second clamp **21** by means of the tightening screw **24** inserted and operated from below in the through-hole **25** requires keeping the lid in position while closing the screw, thus avoiding the rotation of the second clamp. This has been solved with a particular shape of the lid which keeps the rotation stable during the closing phase.

(85) It should also be noted that the possibility of adjusting the axial excursion of the screw carriages **15**, **35**, by laterally operating the respective Allen heads **6**, **46**, allows having a simple assembly phase and a stability in movement that is practically free of clearance.

(86) The outermost bone screws **2** are orientable with an angular movement whose axis is contained in a cone of about 40°. Alternatively, even an angular movement on the same plane as the other innermost bone screw **2** to the fixator **1** is providable, with an angle of approximately $\pm 20^\circ$, represented in FIG. **11** with a flat **67** supporting the ring nut **65** of the base **12**; all this ensures application flexibility and system stability at the same time. Moreover, this configuration allows orienting the screws on a single plane parallel to the resting axis of the rigid support **10**.

(87) The clamps **11**, **21**, **31** are designed in such a way as to have the outermost bone screw of each clamp orientable, whereas the other innermost bone screw of the clamp has a fixed seat that is transversal to the clamp in order to ensure greater stability.

(88) The fixator of the present disclosure makes it easy to identify the insertion position of the bone screws **2** in the respective clamp thanks to the visible part of the screw holder seat that is always accessible.

(89) It should also be noted that to meet the need for greater X-ray visibility, an axial movement of the sliding clamps was opted for, offered by a screw carriage **15**, **35** attached to the clamp itself and screwable into the nut screw seat of the respective support **10**, **30**. The use of aluminum for the carriage structure **15**, **35** makes everything partially transparent to X-rays depending on the thickness and intensity of the rays. The fixator in this case is more radiolucent in the very area where the fractures are located.

(90) By operating by screwing the carriages **15**, **35** through the respective Allen heads **6**, **46**, by means of a control key, it is possible to adjust the movement along the guide of each sliding clamp, making the surgeon able to apply compression or distraction on the fracture gap and at the same time to restore the geometry of the calcaneus by regenerating the anatomical angles of reference.

(91) The clamps **10**, **30** are in any case guided on the profiles **16**, **17** or **36**, **37** of the respective supports **10**, **30** ensuring stability during sliding. The shape of the clamp in fact has a longitudinal projection or tooth **77**, highlighted in FIG. **9**, which helps guiding the clamp but also mitigating the risk of clamp-rigid support disassembly due to bending stresses deriving from the screws. A pair of opposite teeth **77** is sliding in opposing grooves **78** visible in FIG. **11** and located above the nut screw longitudinal threading **14** of the rigid support **10**.

(92) The need to keep the clamps in position during application is achieved by generating a friction on the rotation of the screw carriages **15**, **35**. The friction obtained by means of the elastic-prong crown end **85** with and the elastic interference exerted thereby prevents the free rotation of the respective screw carriage **15**, **35**, so that it does not accidentally unscrew, losing the position or preload on the fracture gap.

(93) The elastic interference exerted by the elastic-prong crown **85** is expressed towards the internal profile of the nut screw seat **16** or **36**.

(94) The dimensions of the fixator **1** are proportionate to the anatomical dimensions of the calcaneus, based on the clinical experiences so far conducted.

(95) In understanding the scope of the present invention, the term “comprising” and its derivatives,

as herein used, are intended as open terms that specify the presence of the features, elements, components, groups, whole numbers and/or specified steps, but do not exclude the presence of other features, elements, components, groups, whole numbers and/or specified steps. The foregoing also applies to words with similar meanings such as for instance the terms, “including”, “having” and derivatives thereof. Moreover, the terms “part”, “section”, “portion”, “member” or “element”, when used in the singular, may have the double meaning of a single part or a plurality of parts unless otherwise specified.

(96) It will also be understood that, though the terms “first” and “second” or “semi” may be herein used to describe various components, these components should not be limited by these terms.

These terms are only used to distinguish a component from another.

(97) Although only selected embodiments were chosen to illustrate the present invention, it will be clear to the skilled in the art from this disclosure that various changes and modifications may be performed without departing from the scope of the invention as defined in the appended claims.

Claims

1. An external fixator for orthopedic use, in particular for treatment of calcaneus fractures, comprising: a first clamp for fixing bone screws; a second clamp; a third clamp; a rigid support for the first clamp; a second support for the second clamp, said second support being hinged at an end of the rigid support; and a third support for the third clamp, said third support being hinged at the end of the rigid support; and the rigid support being configured as at least one guide with the first clamp slidably mounted thereon; wherein the end of the rigid support for connection with the second and third supports is configured to house respective hinges, wherein the rotational axes of said hinges are orthogonal to each other.
2. The fixator according to claim 1, wherein the third support is also configured as a guide with the third clamp sliding thereon.
3. The fixator according to claim 2, wherein the third clamp is mounted on an “L”-shaped element having a slider base side sliding on the third support and an elevated portion that is perpendicular to the base side whereon a jaw lid of the third clamp is coupled.
4. The fixator according to claim 1, wherein the at least one guide comprises two opposite guides and the rigid support has a U-shaped cross-section, with a bottom of the U shape provided with an internal longitudinal thread and open ends of the U shape provided with the opposite guides; and an externally threaded cylindrical carriage is slidable by screwing into the longitudinal thread of the rigid support.
5. The fixator according to claim 4, wherein the first clamp has a base with a portion that is projecting downwards to be held in an annular recess formed on said threaded cylindrical carriage and is further provided with at least one guide and anti-disassembly longitudinal tooth.
6. The fixator according to claim 4, wherein said cylindrical carriage is configured with a self-friction structure.
7. The fixator according to claim 1, wherein the rigid support and said second and third supports are made of radiolucent material, and the hinges are made of partially radiolucent material.
8. The fixator according to claim 1, wherein at least one of the first clamp, the second clamp, and the third clamp has a first seat for receiving a first bone screw and a second seat for receiving a second bone screw, the first seat having angular recesses to allow housing the first bone screw in a tilted manner with respect to the second bone screw that is transversally held by the clamp.
9. The fixator according to claim 8, wherein the first seat is positioned outwards with respect to the second seat.
10. The fixator according to claim 8, wherein the first seat allows orienting the screws on only one plane that is parallel to a resting axis of the rigid support.
11. The fixator according to claim 8, wherein the fixator comprises a cage element inserted in the

first seat with angular recesses to guide and angularly orient the first bone screw into a corresponding angled seat of the clamp.

12. The fixator according to claim 1, wherein at least one of the first clamp, the second clamp, and the third clamp has a first seat and a second seat for receiving respective bone screws, the second seat being transversal and the first seat being tilted with respect to the second seat.

13. The fixator according to claim 1, wherein the second clamp has a base corresponding to the second support and a removable jaw lid that is mounted on the base by means of a tightening screw coupling.

14. The fixator according to claim 13, wherein said tightening screw is inserted in a threaded hole passing through the base and that a head of the tightening screw is hiddenly received into the base.

15. The fixator according to claim 1, wherein each clamp comprises a respective transversal through-hole placed at one end of the clamp towards the outside of the fixator to house a corresponding K-wire.
