

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414242
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Hahn; David et al.

Method for ink jet printing of a substrate

Abstract

A method for ink jet printing of a substrate, as well as an ink jet printed layer. To provide a method for ink jet printing of a substrate that is particularly fast and energy-conserving and does not require any systems with high procurement and operating costs, initially a substrate is supplied, which is then coated with a layer of a print medium on at least one surface. A labeling of the substrate is carried out by applying the same print medium to result in a different color shade of the printed layer.

Inventors: Hahn; David (Heidelberg, DE), Volk; David (Heidelberg, DE), Schönefeld; Jan (Leimen, DE), Schimansky; Carsten (Sinsheim, DE)

Applicant: NOTION SYSTEMS GMBH (Schwetzingen, DE)

Family ID: 73546750

Assignee: NOTION SYSTEMS GMBH (Schwetzingen, DE)

Appl. No.: 17/523747

Filed: November 10, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220192035 A1	Jun. 16, 2022

Foreign Application Priority Data

DE	102019116103.7	Jun. 13, 2019
----	----------------	---------------

Related U.S. Application Data

continuation parent-doc US 16900184 20200612 US 11330719 child-doc US 17523747

Publication Classification

Int. Cl.: **H05K1/02** (20060101); **B05D7/26** (20060101); **H05K1/09** (20060101); **H05K3/00** (20060101); **H05K3/22** (20060101); **H05K3/34** (20060101); **H05K3/40** (20060101); **H05K3/46** (20060101); **H05K7/00** (20060101)

U.S. Cl.:

CPC **H05K3/22** (20130101); **B05D7/26** (20130101); **H05K1/0266** (20130101); **H05K3/4664** (20130101); H05K2201/09936 (20130101); H05K2203/013 (20130101)

Field of Classification Search

CPC: H05K (1/02); H05K (1/0266); H05K (1/09); H05K (1/11); H05K (1/18); H05K (3/00); H05K (3/22); H05K (3/34); H05K (3/40); H05K (3/4664); H05K (7/00); H05K (2201/09936); H05K (2203/013); B05D (7/26)

USPC: 29/829; 427/96.1; 427/163.1; 427/256; 427/511; 427/553; 427/585; 174/250; 174/258; 174/260-264; 430/257-260; 430/262; 430/263; 430/291; 430/331; 430/461

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3867493	12/1974	Seki	264/177.17	B29C 44/468
3909282	12/1974	Gray	N/A	N/A
4088828	12/1977	Yamamoto	N/A	N/A
4210346	12/1979	Mowry, Jr.	N/A	N/A
4265469	12/1980	Mowry, Jr.	N/A	N/A
4301232	12/1980	Kullen	N/A	N/A
4474725	12/1983	Sands	N/A	N/A
4801768	12/1988	Sugiyama	N/A	N/A
4935264	12/1989	Tsujino	N/A	N/A
5119115	12/1991	Buat	N/A	N/A
5225900	12/1992	Wright	382/312	H04N 1/38
5266748	12/1992	Kawakami	N/A	N/A
5292613	12/1993	Sato	N/A	N/A
5397678	12/1994	Sato	N/A	N/A
5562975	12/1995	Sugai	428/32.5	B41M 5/5218
5867826	12/1998	Wilkinson	N/A	N/A
5877895	12/1998	Shaw	359/589	G02B 5/286
6092947	12/1999	Nunokawa	400/615.2	B41J 11/26
6109798	12/1999	Nunokawa	400/615.2	F16G 11/10
6172688	12/2000	Iwasaki	N/A	N/A
6180018	12/2000	Miyagawa	N/A	N/A
6219912	12/2000	Shimizu	N/A	N/A
6264747	12/2000	Shaw	N/A	N/A
6386674	12/2001	Corrigan, III	N/A	N/A
6503307	12/2002	Noguchi	N/A	N/A

6514621	12/2002	Marietti	N/A	N/A
6666983	12/2002	Marietti	N/A	N/A
6670091	12/2002	Hatakeyama	N/A	N/A
7200259	12/2006	Gold	N/A	N/A
8362363	12/2012	Okada	N/A	N/A
9259762	12/2015	Mizuno	N/A	N/A
2001/0040598	12/2000	Dunand	N/A	N/A
2002/0061723	12/2001	Duescher	N/A	N/A
2002/0102289	12/2001	Drucks	N/A	N/A
2002/0138920	12/2001	Pepitone	N/A	N/A
2002/0150737	12/2001	Nakashima	N/A	N/A
2003/0157305	12/2002	Abraham	N/A	N/A
2003/0170558	12/2002	Hatakeyama	N/A	N/A
2004/0106061	12/2003	Gotoh	N/A	N/A
2004/0194653	12/2003	Taffinder	N/A	N/A
2005/0057599	12/2004	Takenaka	N/A	N/A
2005/0206866	12/2004	Ozaki	355/53	G03F 7/70283
2006/0159635	12/2005	Meyer	N/A	N/A
2006/0159637	12/2005	Meyer	N/A	N/A
2006/0246149	12/2005	Buchholz	N/A	N/A
2007/0159581	12/2006	Moriya	N/A	N/A
2008/0002079	12/2007	Kimura	349/141	G02F 1/134363
2008/0038213	12/2007	Carola	N/A	N/A
2008/0049277	12/2007	Usui	N/A	N/A
2008/0055355	12/2007	Hersch	N/A	N/A
2008/0080165	12/2007	Kim	N/A	N/A
2008/0110858	12/2007	Itoh	216/41	H01L 27/1214
2008/0121413	12/2007	Cardona	N/A	N/A
2008/0259120	12/2007	Misumi	N/A	N/A
2008/0265254	12/2007	Nishiura	257/E27.113	H01L 27/1255
2009/0008645	12/2008	Yamazaki	257/59	H01L 29/78678
2009/0009677	12/2008	Yamazaki	349/43	H01L 29/78696
2009/0110843	12/2008	Halahmi	N/A	N/A
2009/0194154	12/2008	Takahashi	N/A	N/A
2009/0267173	12/2008	Takahashi	N/A	N/A
2009/0268566	12/2008	Hiroe	N/A	N/A
2010/0028067	12/2009	Wanibuchi	N/A	N/A
2010/0051988	12/2009	Mitsuishi	N/A	N/A
2010/0065317	12/2009	Okada	N/A	N/A
2010/0067163	12/2009	Nozoe	N/A	N/A
2010/0231646	12/2009	Misumi	N/A	N/A
2010/0238219	12/2009	Rueby	N/A	N/A
2010/0238511	12/2009	Neese	N/A	N/A
2010/0271411	12/2009	Iritani	N/A	N/A
2010/0296127	12/2009	Barndt	N/A	N/A
2010/0315458	12/2009	Kato	N/A	N/A
2011/0003418	12/2010	Sakata	438/34	H01L 29/66969
2011/0018088	12/2010	Seike	N/A	N/A
2011/0186982	12/2010	Kitani	N/A	N/A
2011/0206916	12/2010	Siebert	N/A	N/A

2011/0222278	12/2010	Lee	N/A	N/A
2012/0050407	12/2011	Sekino	N/A	N/A
2012/0050537	12/2011	Ringermacher	N/A	N/A
2012/0152400	12/2011	Michishita	N/A	N/A
2012/0268658	12/2011	Hasegawa	N/A	N/A
2013/0209818	12/2012	Fairclough	N/A	N/A
2014/0098152	12/2013	Mishima	347/15	B41J 2/2054
2014/0166354	12/2013	Fan	N/A	N/A
2014/0168673	12/2013	Barndt	N/A	N/A
2014/0202749	12/2013	Saitou	N/A	N/A
2014/0225362	12/2013	Quinn	101/483	B42D 25/435
2014/0318846	12/2013	Hayashi	N/A	N/A
2015/0015650	12/2014	Landa	N/A	N/A
2015/0042736	12/2014	Landa	N/A	N/A
2015/0044431	12/2014	Landa	N/A	N/A
2015/0165759	12/2014	Landa	N/A	N/A
2015/0262048	12/2014	Barndt	N/A	N/A
2015/0262962	12/2014	Matsumoto	N/A	N/A
2015/0296627	12/2014	Ben-Abu	174/250	H05K 1/0254
2015/0339824	12/2014	Uliyar	348/46	G06T 7/557
2016/0075130	12/2015	Landa	N/A	N/A
2016/0143150	12/2015	Happoya	N/A	N/A
2016/0205771	12/2015	Hashimoto	N/A	N/A
2016/0207306	12/2015	Landa	N/A	N/A
2017/0008272	12/2016	Landa	N/A	N/A
2017/0021638	12/2016	Barndt	N/A	N/A
2017/0080706	12/2016	Landa	N/A	N/A
2017/0113455	12/2016	Landa	N/A	N/A
2017/0145606	12/2016	Toye	N/A	D04B 21/10
2017/0208689	12/2016	Fukuzumi	N/A	N/A
2017/0361602	12/2016	Landa	N/A	N/A
2018/0065358	12/2017	Landa	N/A	N/A
2018/0079201	12/2017	Landa	N/A	N/A
2018/0117906	12/2017	Landa	N/A	N/A
2018/0154628	12/2017	Landa	N/A	N/A
2019/0023000	12/2018	Landa	N/A	N/A
2019/0059855	12/2018	Jin	N/A	N/A
2019/0118530	12/2018	Landa	N/A	N/A
2019/0157503	12/2018	Hung	N/A	N/A
2019/0189001	12/2018	Smothers	N/A	N/A
2019/0193391	12/2018	Landa	N/A	N/A
2019/0202198	12/2018	Shmaiser	N/A	N/A
2019/0301891	12/2018	Rowitch	N/A	G01C 21/3694
2019/0329568	12/2018	Barndt	N/A	N/A
2019/0366705	12/2018	Landa	N/A	N/A
2020/0194518	12/2019	Myung	N/A	H10K 59/10

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2000-158787	12/1999	JP	N/A

Primary Examiner: Dole; Timothy J.

Attorney, Agent or Firm: Caesar Rivise, PC

Background/Summary

- (1) The invention relates to a method for ink jet printing of a substrate.
- (2) Various methods are known from the prior art for producing and labeling electric printed circuit boards, as well as corresponding printed circuit boards. In so doing, typically holes as well as vias, if applicable, are initially created in a substrate consisting of fiber-reinforced plastic, and then the conductive tracks are produced on the substrate by illumination and by etching.
- (3) Subsequently, a coating with a solder resist is then typically created in order to help with subsequently populating the printed circuit board with electronic components, and with soldering these components. The solder resist coating is applied for example by a screen-printing method, or in a photographic manner in the form of a surface coating. Afterwards, this solder resist layer must be left to dry, or actively dried by means of an oven.
- (4) After this coating with a solder resist, the printed circuit board is labeled by printing on the surface of the solder resist which in particular is also done in a screen-printing method or photographically. The labeling must also be left to dry before further use or before packing the coated and labeled printed circuit boards.
- (5) Said drying typically lasts at least 30 minutes, which leads to a disadvantageous delay in production. Alternatively, the drying can be accelerated by means of a drying oven whose performance however lies within a range of a multiple of 10 kW and therefore has high operating costs. In general, a corresponding system which is expensive to procure and operate and requires a corresponding setup site due to its size must be used for such labeling and subsequent drying of the printed circuit boards.
- (6) The object of the invention is therefore to provide a method for producing a labeled printed circuit board that is particularly fast and energy-saving and does not require any systems with high procurement and operating costs.
- (7) The object is achieved by a method as well as an electrical printed circuit board of the invention.
- (8) In the method for producing a labeled printed circuit board according to the invention, first a substrate provided with conductive tracks is supplied and is subsequently coated on at least one surface with a functional lacquer coating, wherein moreover a labeling of the substrate is created in different color shades of the functional lacquer layer.
- (9) The electric printed circuit board according to the invention has conductive tracks arranged at least on the surface of a substrate, and an at least partial surface coating with a functional lacquer layer as well as a labeling of the printed circuit board created by different color shades of the functional lacquer layer.
- (10) The inventors have found that the separate method step of labeling by means of a labeling lacquer can also be omitted if the functional lacquer layer is previously applied on the substrate in particular by means of a solder resist in different layer thicknesses, whereby thicker regions of the functional lacquer layer are more strongly visible and therefore can be used for a labeling, in particular when a colored or partially transparent lacquer is used. Advantageously, the expensive and large systems for labeling after coating with the functional lacquer layer are no longer needed,

and moreover the method for producing a printed circuit board is significantly shortened since not just the separate method step of coating, but also the prolonged drying of the labeling can be omitted. Moreover, significant energy conservation can be achieved since drying the labeling, which generally occurs in an oven, is no longer necessary.

(11) The printed circuit board is in principle a part or an assembly for mechanically affixing and/or at least partially, preferably completely, electrically connecting electronic parts and components. The printed circuit board can have any size, be produced in one or several parts, and be made of any desired material. The printed circuit board is preferably a board, a printed circuit, or a part thereof. Preferably, the printed circuit board is formed flat, and/or at least one surface is provided flat for receiving electrical parts.

(12) The base of the printed circuit board is thereby formed by the substrate that forms at least the mechanical basic structure of the printed circuit board, and/or is provided to receive all of the further components of the printed circuit board. The substrate preferably extends over the entire surface of the printed circuit board. In principle, the substrate can be formed from any desired material, wherein a substrate consisting of a fiber-reinforced plastic or hard paper is preferred. Moreover, the substrate can be formed from one or several layers.

(13) In order to be able to electrically connect the individual electronic components to be arranged on the printed circuit board with each other, the substrate is provided with at least one, preferably with a plurality, of conductive tracks separate from each other. The conductive tracks preferably also comprise soldering surfaces, or respectively lands in order to be able to conductively connect the electronic components to the conductive tracks. The conductive tracks are preferably produced by illumination and/or by etching. Each conductive track is particularly preferably formed from a thin layer of copper or a copper-containing alloy, wherein a conductive track most preferably has a thickness of 35 μm .

(14) According to the invention, at least one surface of the substrate is coated with a functional lacquer layer, wherein this can be both a partial surface as well as a full surface coating of the surface. Preferably, there is a substantially full-surface coating, in particular with the exception of connecting points for electrical components, electrical conductors or the like. Particularly preferably at least one surface, and most preferably each surface of the substrate having conductive tracks is coated entirely, with the exception of the connecting points, in particular the lands. The surface of the substrate to be coated can be a surface of the material of the substrate itself, and/or a surface of one or more of the materials applied to the substrate, such as for example conductive tracks. Likewise preferably, the printed circuit board is cleaned and/or dried before being coated with the functional lacquer layer.

(15) First of all, the functional lacquer layer can have any desired function that deviates from a labeling of the substrate, or respectively of the printed circuit board. The functional lacquer layer can have one or simultaneously several functions. These functions can for example be a mechanical and/or electrical protection of the components lying underneath, in particular of the conductive tracks. Furthermore, soldering components can be assisted by the functional lacquer layer in that the lacquer layer contains a flux. Alternatively, the functional lacquer layer can have a repulsive effect for flux and/or for the soldering agent, in particular a tin solder, and thereby assist the isolation of the individual conductive tracks and/or the soldering points from each other. The lacquer layer can be formed of any desired material, in particular any desired lacquer composition. The lacquer composition and/or the cured or dried lacquer of the functional lacquer layer is preferably not entirely transparent and/or not color-free. Particularly preferably, the lacquer composition and/or the cured or dried lacquer is however colored, and most preferably partially transparent so that the conductive tracks are visible through the partially transparent lacquer, and simultaneously there is a colored appearance of the lacquer layer.

(16) The labeling can in principle be formed in any desired manner and contain lettering, numbers, other characters, brand logos, barcodes, QR codes, pictograms or other markings. The labeling can

inter alia be provided for dimensions, for instructing a user or manufacturer of an electronic component, for brand identification, or for any other purposes. The labeling can be in any desired fonts and/or desired font sizes, as well as at any desired position on the surface of the substrate, or respectively the printed circuit board.

(17) The labeling according to the invention has different color shades in order to distinguish the coating with the functional lacquer layer and the labeling from each other so that the labeling is haptically and/or visually perceptible. Preferably, the labeling is visually perceptible. "Different color shades" only means in the first place that there are at least two different color shades, wherein a first shade forms the background, and a second shade forms the labeling. Preferably, the labeling is darker than the background. More preferably, the entire background has an extensive and/or uniform color shade that is particularly preferably brighter than all the labeling. In principle, it is however also conceivable to create the background coating in several color shades, for example in order to depict a graphic, a brand logo and/or a pictogram. Although the labeling in principle only has to be produced from a single color shade deviating from the background color shade, it is preferable to use several color shades in the labeling that differ from each other. Preferably, all color shades of the labelings are fashioned darker than the color shades of the background surrounding the labeling in each case, and particularly preferably darker than all color shades of the background.

(18) In a preferred embodiment of the method according to the invention, coating with the functional lacquer layer and labeling by means of the functional lacquer layer is simultaneous; consequently, a separate labeling system is unnecessary, and particularly fast and easy production of the labeled printed circuit board is moreover enabled. A "simultaneous coating and labeling" is first of all understood to merely mean that the labeling occurs before the coating is completely dry so that the coating and the labeling preferably form a single layer on the surface of the substrate, or respectively of the printed circuit board. Particularly preferably, the coating and the labeling occur in a single simultaneous application method and/or without a temporal delay from each other.

(19) According to an advantageous further embodiment of the method according to the invention, the at least one different color shade of the labeling is achieved with a different layer thickness or a different color density of the applied functional lacquer layer, which also enables particularly simple, energy-conserving and fast production of the labeled printed circuit board. The "layer thickness of the lacquer layer" is understood to mean the thickness of the dried lacquer vertically on the surface of the substrate, or respectively the printed circuit board, and the color density describes in principle the applied amount of paint per area, wherein this can be achieved not just by a greater layer thickness, but also by a closer distance between adjacent printing points.

(20) Although the substrate can in principle be coated with the functional lacquer layer in any desired manner, for example by screen printing, it is preferred for the coating and/or the labeling with the functional lacquer layer to occur by means of an inkjet printing method, which enables particularly precise, fast and energy-conserving application of the functional coating. This is preferably done in particular by means of a single inkjet printer. It is also preferable for the inkjet printing method to be an ink, or respectively lacquer jet printing method that particularly preferably generates a printed image, or respectively a coating in matrix printing, and/or by specifically discharging small ink, or respectively lacquer drops. Correspondingly, it is also particularly preferred to generate the different color shades of the coating and the labeling by a local variation in the printing density, in particular the inkjet print points per area.

(21) A preferred embodiment of the method according to the invention provides using a solder resist to produce the functional lacquer layer, whereby the labeling advantageously occurs together with the production of the printed circuit board and the preparation for populating with electronic components. It is preferable for the solder resist to cover the conductive tracks and to leave the soldering points free. In principle, the solder resist can have any desired composition and any desired color. Preferably, the solder resist has a green, red, blue or white color. A multi-color

coating, in particular with solder resist, is also conceivable, in particular by means of an inkjet printing method, with at least one nozzle per color in each case. Preferably, exclusively one single coating composition, particularly preferably one single lacquer, and most preferably one single solder resist is used when coating.

(22) According to an advantageous further embodiment of the method according to the invention, the functional lacquer layer forms the outer surface of the printed circuit board, and/or no further labeling is applied to the functional lacquer layer and/or to the outer surface of the printed circuit board, which enables particularly fast and energy-conserving production of the labeled printed circuit board. Also preferably, there is also no labeling layer under the functional lacquer layer. Particularly preferably, the functional lacquer layer is the only lacquer layer on the surface of the substrate, or respectively the printed circuit board. Most preferably, the functional lacquer layer forms the final coating and/or the final surface layer of the printed circuit board. Correspondingly, an embodiment of the method is preferred in which no further treatment of the functional lacquer layer is necessary after applying the coating and the labeling, wherein in particular there is no modification of the surface of the printed circuit board by applying additional materials or additional labelings, or by removing part of the functional lacquer layer.

(23) In order to produce a particularly distinctive labeling, however, it can be provided to produce or reinforce the labeling by a second application of material of the functional lacquer layer, in particular solder resist. In a corresponding embodiment of the method, in this case it is however preferred that both lacquer layers have an identical composition and/or are made of an identical lacquer. In particular, it is preferred for the second coating to occur before the first coating is dry so that particularly preferably, a single, in particular homogeneous functional coating results on the finished, labeled printed circuit board.

(24) In a preferred embodiment of the method according to the invention, an individual labeling is made for each individual substrate to be coated and labeled, whereby in a particularly advantageous manner, for example an individual labeling, but also a progressive labeling, for example with serial numbers, is easily possible. The coating is particularly preferably without an invariable template, which in particular is possible by means of an inkjet printing application of the functional lacquer coating.

(25) Finally, an advantageous further embodiment of the method according to the invention provides that the labeling occurs at an even and/or unchanged printing speed which enables particularly fast and easy production of the labeled printed circuit board. A method, in particular using an inkjet printer with an even printing throughput, in particular independent of the color shade of the functional lacquer coating, is particularly preferred.

Description

(1) An exemplary embodiment of the method according to the invention is explained in greater detail below with reference to the drawing. In the FIGURE:

(2) FIG. 1 shows a schematic sectional view of a coated and labeled printed circuit board.

(3) A labeled printed circuit board 1 shown in FIG. 1 is produced according to an embodiment of the method according to the invention. To accomplish this, a substrate 3 consisting of fiber-reinforced plastic and coated with copper conductive tracks 2 is fed to an inkjet printing system. The conductive tracks 2 are produced by illumination and subsequent etching.

(4) In the inkjet printing system, there is a substantially extensive coating of the surface of the substrate 3 as well as the conductive tracks 2 with a functional solder resist 4, in particular based on epoxy resin, to ensure a precise soldered connection when populating the printed circuit board 1 with electronic components and subsequently soldering the components, and to avoid the formation of undesirable solder bridges. Moreover, the solder resist 4 increases the electric strength, protects

the conductive tracks 2 from corrosion, and reduces the consumption of tin solder while soldering the electronic components.

(5) The coating with the functional solder resist 4 is done nearly of the entire surface, wherein the lands 7 on the surface of the conductive tracks 2 are omitted to allow components to be soldered.

(6) Moreover, a labeling of the substrate 3 is also carried out simultaneous to the extensive coating by means of the inkjet printing system. To accomplish this, a solder resist 4 is used that cures colored and partially transparent. At the positions at which labeling is to occur on the surface of the substrate 3, the solder resist 4 is applied with a high printing density during the extensive coating so that a contrast in color results in comparison to the other coated surface. By means of different print densities in individual regions in comparison to the functional solder resist layer 4, it is possible to produce labelings with darker color shades 5, 6.

(7) These labelings can be both batch or lot IDs, as well as comprise any characters, trademarks or other information such as barcodes or QR codes. Given the greater layer thickness of the regions labeled with a higher print density, a quite visually apparent and haptically perceptible labeling results with a darker color shade 5, 6.

Claims

1. A method for producing a labeled printed circuit board comprising: supplying a substrate provided with conductive tracks, coating at least one surface of the substrate with a functional lacquer to result in a functional lacquer layer having a first color shade of a color, wherein the conductive tracks are at least partially coated with the same functional lacquer, and wherein a labeling of the substrate is carried out by applying the same functional lacquer on a part of said at least one surface of the substrate to result in a second color shade of the same color of the functional lacquer layer achieved by a different layer thickness, or a different color density of the coating and the labeling to distinguish the coating and the labeling made from the same functional lacquer from each other, wherein the labeling is haptically perceptible, visually perceptible, or haptically and visually perceptible.
2. The method for producing a labeled printed circuit board according to claim 1, wherein the coating and the labeling are simultaneous.
3. The method for producing a labeled printed circuit board according to claim 1, wherein the coating and labeling are both carried out using an inkjet printing method.
4. The method for producing a labeled printed circuit board according to claim 1, wherein the different color shades of the coating and the labeling are achieved by a local variation in the inkjet print points per area.
5. The method for producing a labeled printed circuit board according to claim 1, wherein the functional lacquer layer forms the outer surface of the substrate, and/or no additional labeling is applied on the functional lacquer layer.
6. The method for producing a labeled printed circuit board according to claim 1, wherein the labeling is produced or reinforced by a second application of the same print medium of the layer.
7. The method for producing a labeled printed circuit board according to claim 1, wherein an individual labeling is carried out for each individual substrate to be coated and to be labeled.
8. The method for producing a labeled printed circuit board according to claim 1, wherein labeling occurs at an even and/or unchanged printing speed.
9. A labeled printed circuit board, comprising: at least one surface of a substrate provided with conductive tracks at least partially coated with a functional lacquer, an at least partial surface coating with the same functional lacquer resulting in a functional lacquer layer on the surface of the substrate having a first color shade of a color, and a labeling of the substrate carried out by applying the same functional lacquer on a part of said surface of the substrate to result in a second color shade of the same color of the functional lacquer layer achieved by a different layer

thickness, or a different color density of the coating and the labeling to distinguish the coating and the labeling made from the same functional lacquer from each other, wherein the labeling is haptically perceptible, visually perceptible, or haptically and visually perceptible.
