

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414377
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Kao; Chi-Lun et al.

Electronic device

Abstract

The present disclosure provides an electronic device including a substrate, a semiconductor disposed on the substrate, and a conductive layer disposed on the semiconductor. The conductive layer has a first electrode and a second electrode, in which the first electrode is electrically connected to the semiconductor, and the second electrode surrounds the first electrode in a top view direction of the electronic device.

Inventors: Kao; Chi-Lun (Miao-Li County, TW), Kao; Ker-Yih (Miao-Li County, TW), Tseng; Ming-Chun (Miao-Li County, TW), Kuo; Kung-Chen (Miao-Li County, TW)

Applicant: InnoLux Corporation (Miao-Li County, TW)

Family ID: 73891825

Assignee: InnoLux Corporation (Miao-Li County, TW)

Appl. No.: 18/420794

Filed: January 24, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240162241 A1	May. 16, 2024

Foreign Application Priority Data

CN	202010174846.2	Mar. 13, 2020
----	----------------	---------------

Related U.S. Application Data

continuation parent-doc US 18111606 20230220 US 11923378 child-doc US 18420794
division parent-doc US 16885308 20200528 US 11616084 20230328 child-doc US 18111606

Publication Classification

Int. Cl.: **H10D86/60** (20250101); **H01L23/60** (20060101); **H01L25/16** (20230101); **H10D86/40** (20250101); **H10D89/60** (20250101)

U.S. Cl.:

CPC **H10D86/60** (20250101); **H01L23/60** (20130101); **H01L25/167** (20130101); **H10D86/441** (20250101); **H10D89/921** (20250101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2008/0197778	12/2007	Kubota	315/73	H10K 59/131

Primary Examiner: Jang; Bo B

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation application of U.S. application Ser. No. 18/111,606, filed on Feb. 20, 2023, which is a division of U.S. application Ser. No. 16/885,308, filed on May 28, 2020, which claims the benefit of U.S. Provisional Application No. 62/867,899, filed on Jun. 28, 2019. The contents of these applications are incorporated herein by reference.

BACKGROUND OF THE DISCLOSURE

1. Field of the Disclosure

(1) The present disclosure relates to an electronic device, and more particularly to an electronic device in which an auxiliary electrode is disposed in a pixel.

2. Description of the Prior Art

(2) With the advance of technology, electronic devices with display function have been developed to have properties of light weight, low power consumption, no radiation pollution, etc., such that the electronic devices may be widely applied in various levels of products in everyday life, for example applied in modern information apparatus, such as television, note book, laptop computer, mobile phone, smart phone, etc. In conventional electronic devices, it is required to have many thin-film transistors for controlling the display of the pixels. However, during manufacturing the electronic device or when the manufacture is completed, a lot of electrostatic charges may exist, for example the electrostatic charges accumulated on manufacturing machines or tools or on devices to be disposed on the thin-film transistors. Accordingly, electrical characteristics of the thin-film transistors may be shifted or the thin-film transistors may be damaged due to the electrostatic discharge (ESD), resulting in poor display of the electronic device.

SUMMARY OF THE DISCLOSURE

(3) An embodiment of the present disclosure provides an electronic device including a substrate, a semiconductor disposed on the substrate, and a conductive layer disposed on the semiconductor. The conductive layer has a first electrode and a second electrode, in which the first electrode is electrically connected to the semiconductor, and the second electrode surrounds the first electrode in a top view direction of the electronic device.

(4) These and other objectives of the present disclosure will no doubt become obvious to those of ordinary skill in the art after reading the following detailed description of the embodiment that is illustrated in the various figures and drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1A schematically illustrates a top view of an electronic device according to a first embodiment of the present disclosure.

(2) FIG. 1B schematically illustrates a cross-sectional view taken along a line A-A' of FIG. 1.

(3) FIG. 2 schematically illustrates a top view of an electronic device according to a variant embodiment of the first embodiment of the present disclosure.

(4) FIG. 3A schematically illustrates a top view of an electronic device according to a second embodiment of the present disclosure.

(5) FIG. 3B schematically illustrates a cross-sectional view taken along a line B-B' of FIG. 3A.

(6) FIG. 4 schematically illustrates a top view of an electronic device according to a variant embodiment of the second embodiment of the present disclosure.

(7) FIG. 5 schematically illustrates a top view of an electronic device according to another variant embodiment of the second embodiment of the present disclosure.

(8) FIG. 6 schematically illustrates top views of auxiliary electrodes according to other variant embodiments of the present disclosure.

DETAILED DESCRIPTION

(9) The present disclosure may be understood by reference to the following detailed description, taken in conjunction with the drawings as described below, and for purposes of illustrative clarity and being easily understood by the readers, various drawings of this disclosure may be simplified, and the elements in various drawings may not be drawn to scale. In addition, the number and dimension of each element shown in drawings are only illustrative and are not intended to limit the scope of the present disclosure.

(10) Certain terms are used throughout the description and following claims to refer to particular elements. As one skilled in the art will understand, electronic equipment manufacturers may refer to an element by different names. This document does not intend to distinguish between elements that differ in name but not function. In the following description and in the claims, the terms “comprise”, “include” and “have” are used in an open-ended fashion, and thus should be interpreted to mean “include, but not limited to . . .”.

(11) The direction terms used in the following embodiments such as up, down, left, right, in front of or behind are only the directions referring to the attached figures. Thus, the direction terms used in the present disclosure are for illustration, and are not intended to limit the scope of the present disclosure. It should be noted that the elements which are specifically described or labeled may exist in various forms for those skilled in the art. Besides, when a layer is referred to as being “on” another element or layer, or is referred to as being “connected” to another element or layer, it may be directly on or connected to the other element or layer, or intervening layers or elements may be included between the layer and the other element or layer (indirectly). In contrast, when an element or layer is referred to as being “directly on” or “directly connected to” another element or layer,

there are no intervening elements or layers present.

(12) The ordinal numbers such as “first”, “second”, etc. are used in the specification and claims to modify the elements in the claims. It does not mean that the required element has any previous ordinal number, and it does not represent the order of a required element and another required element or the order in the manufacturing method. The ordinal number is only used to distinguish the required element with a certain name and another required element with the same certain name.

(13) It should be noted that the technical features in different embodiments described in the following may be replaced, recombined, or mixed with one another to constitute another embodiment without departing from the spirit of the present disclosure.

(14) The electronic device of the present disclosure may include display device, light emitting device, antenna device, sensing device, touch electronic device (touch display), curved electronic device (curved display) or non-rectangular electronic device (free shape display), but not limited thereto. The electronic device may include foldable electronic device or flexible electronic device. The electronic device may for example include light-emitting diode (LED), fluorescence, phosphor, other suitable display medium or combinations thereof, but not limited thereto. For instance, the LED may include organic LED (OLED), mini LED, micro LED or quantum dot LED (QLED or QDLED), other suitable material or any combination thereof, but not limited thereto. The display device of an example may be a tiled display device, but is not limited thereto. The antenna device may for example be a liquid crystal antenna, but not limited thereto. Also, outer shape of the electric device may be rectangular, circular, polygonal, shape with curved edge or other suitable shapes. The electronic device may include peripheral system, such as driving system, control system, light source system, frame system, etc., for supporting the display device or tiled device. It should be noted that the electronic device may be combinations of the above-mentioned electronic devices, but not limited thereto. The electronic device as mentioned herein takes the display device as an example to detail the content of the present disclosure, but the present disclosure is not limited thereto.

(15) FIG. 1A schematically illustrates a top view of an electronic device according to a first embodiment of the present disclosure, and FIG. 1B schematically illustrates a cross-sectional view taken along a line A-A' of FIG. 1. For clearly showing the technical features of the present disclosure, FIG. 1A mainly illustrates a common electrode and a relationship between a first electrode and a second electrode in one pixel, and a right portion of FIG. 1A schematically depicts an enlarged view of a region R in a left portion of FIG. 1A, but the present disclosure is not limited thereto. As shown in FIG. 1A and FIG. 1B, the electronic device **1** includes a substrate **12**, a common electrode **14**, and a plurality of pixels **16**, in which the common electrode **14** and the pixels **16** may be disposed on a top surface **12S** of the substrate **12**. The substrate **12** may for example include flexible substrate or inflexible substrate. The material of the substrate **12** may include for instance glass, ceramic, quartz, sapphire, acrylic, polyimide (PI), polyethylene terephthalate (PET), polycarbonate (PC), polyethersulfone (PES), polybutylene terephthalate (PBT), polyethylene naphthalate (PEN), polyarylate (PAR), other suitable materials or combinations thereof, but the present disclosure is not limited thereto.

(16) As shown in FIG. 1A, as viewed along a top view direction TD of the electronic device **1**, the common electrode **14** may include strip portions **14A** extending along a first direction D1 and strip portions **14B** extending along a second direction D2, and the strip portions **14A** may cross and be connected to the strip portions **14B**, such that the common electrode **14** may be mesh-shaped. The common electrode **14** may include a plurality of first openings **14C**, and as viewed along the top view direction TD, the plurality of pixels **16** may be disposed in the plurality of first openings **14C**. For example, at least one pixel **16** may be disposed in one first opening **14C**. Taking the embodiment shown in FIG. 1A as an example, one pixel **16** may be disposed one first opening **14C**, but is not limited thereto. In some embodiments, there may be at least two pixels **16** disposed in one first opening **14C**. In some embodiments, the pixel **16** may be for example a sub-pixel for

generating single color or a pixel for generating plural colors, but is not limited thereto. The top view direction TD of the present disclosure may for example be a normal direction perpendicular to the top surface **12S** of the substrate **12** shown in FIG. **1B**. The first direction **D1** and the second direction **D2** may be perpendicular to the top view direction TD, and for example be perpendicular to each other, but are not limited thereto. The common electrode **14** may be used for guiding or eliminating electrostatic charges. As an example, the common electrode **14** may be electrically connected to a ground voltage or a common voltage after the electronic device **1** is manufactured, but is not limited thereto. The ground voltage and the common voltage may be same or different.

(17) Please continue referring to FIG. **1A** and FIG. **1B**. At least one pixel **16** may include a thin-film transistor **18**, a first electrode **20**, a second electrode **22**, and an auxiliary electrode **24**, in which the first electrode **20** is electrically connected to the thin-film transistor **18**, and the auxiliary electrode **24** is electrically connected to the common electrode **14** and electrically isolated from the first electrode **20**. It should be noted that the first electrode **20** and the auxiliary electrode **24** have a minimum distance MD1 therebetween, and the minimum distance MD1 is less than a minimum distance MD2 between the first electrode **20** and the common electrode **14**, such that plenty of electrostatic charges flowing into the first electrode **20** may be discharged to the common electrode **14** with larger area through the auxiliary electrode **24**, thereby mitigating damage to the thin-film transistor **18** by the ESD. Accordingly, ESD protection of the electronic device **1** may be improved.

(18) In the embodiment of FIG. **1A** and FIG. **1B**, the auxiliary electrode **24**, the first electrode **20** and the second electrode **22** may be formed in the same layer (such as a conductive layer M). In the present disclosure, “formed in the same layer” may refer to include the same material, formed by the same process, formed of the same layer or both sandwiched between the same two layers (such as between planarization layer **38** and insulation layer **40** shown in FIG. **1B**). Besides, in the top view direction TD of the electronic device **1**, the auxiliary electrode **24** may surround the first electrode **20**, so as to be disposed between the first electrode **20** and the common electrode **14**, and accordingly, the minimum distance MD1 between the first electrode **20** and the auxiliary electrode **24** may be located in a horizontal direction perpendicular to the top view direction TD, but is not limited thereto. In other words, as viewed along the top view direction TD of the electronic device **1**, the auxiliary electrode **24** may include at least one second opening **24A**, and the first electrode **20** is disposed in the second opening **24A**. In the embodiment of FIG. **1A**, the minimum distance MD1 may be located in the first direction **D1**, but not limited thereto. In some embodiments, the minimum distance MD1 may be located in the second direction **D2** or other horizontal direction different from the first direction **D1** and the second direction **D2**. In some embodiments, in the top view direction TD of the electronic device **1**, the auxiliary electrode **24** may surround the first electrode **20** and the second electrode **22** and be located between the second electrode **22** and the common electrode **14**; that is, the first electrode **20** and the second electrode **22** may be located in the second opening **24A**, but is not limited thereto. In some embodiments, the auxiliary electrode **24** may surround the first electrode **20** and may not surround the second electrode **22**. In some embodiments, the auxiliary electrode **24** may not surround the first electrode **20** and may be disposed on at least one side of the first electrode **20**. In some embodiments, the minimum distance MD1 between the first electrode **20** and the auxiliary electrode **24** may also be less than a minimum distance MD3 between the first electrode **20** and the second electrode **22**, so as to reduce the electrostatic charges flowing into the second electrode **22**. In some embodiments, the minimum distance MD1 between the first electrode **20** and the auxiliary electrode **24**, the minimum distance MD2 between the first electrode **20** and the common electrode **14** and the minimum distance MD3 between the first electrode **20** and the second electrode **22** may be obtained by measuring the minimum distance between two electrodes mentioned above when viewed along the top view direction TD, or by measuring the minimum distance between two electrodes mentioned above along a cross-sectional direction, but the present disclosure is not limited thereto. For example, in the situation that the minimum distance is measured along the cross-sectional direction, when the

minimum distance is measured along the cross-sectional direction, the minimum distance between two electrodes that are formed in different layers may be measured along the second direction D2 or along the first direction D1.

(19) In the embodiment of FIG. 1A, the second electrode 22 may be electrically connected to the auxiliary electrode 24, but is not limited thereto. For instance, the second electrode 22 may be directly connected to the auxiliary electrode 24, but is not limited herein. In some embodiments, the second electrode 22 may be electrically connected to the auxiliary electrode 24 through a wire formed by a conductive layer different from the conductive layer M (such as the wire 350 shown in FIG. 3A). In the embodiment of FIG. 1A, the common electrode 14 and the first electrode 20 may be formed in the same conductive layer M, and as viewed along the top view direction TD of the electronic device 1, the first electrode 20, the second electrode 22 and the auxiliary electrode 24 may be located in the first opening 14C and separated from the common electrode 14. In such situation, the pixel 16 may further include a wire 42 formed in a conductive layer different from the conductive layer M, and the wire 42 may be electrically connected to the second electrode 22 and the common electrode 14, such that the auxiliary electrode 24 may be electrically connected to the common electrode 14 through the second electrode 22 and the wire 42. In some embodiments, the auxiliary electrode 24 may be directly connected to the common electrode 14, or when the second electrode 22 is electrically connected the auxiliary electrode 24, the second electrode 22 may be directly connected to the common electrode 14 without the wire 42. In some embodiments, the auxiliary electrode 24 and the second electrode 22 may be electrically isolated from each other and be separated from each other. In such situation, voltage (such as the common voltage) provided to the auxiliary electrode 24 and the common electrode 14 may be different from voltage (such as the ground voltage) provided to the second electrode 22, but is not limited thereto. In some embodiments, the common electrode 14, the auxiliary electrode 24, the first electrode 20 and the second electrode 22 may respectively include conductive material, and the conductive material may for example include aluminum, molybdenum nitride, copper, titanium, other suitable materials or combinations thereof, but not limited thereto.

(20) In detail, in the embodiment of FIG. 1A and FIG. 1B, the electronic device 1 takes a self-emissive display device as an example, in which one pixel 16 may include at least two thin-film transistors 18 and at least one light-emitting element 26, but the present disclosure is not limited thereto. The number of the thin-film transistors 18 and the number of the light-emitting element 26 in the pixel 16 are not limited to be shown in FIG. 1B and may be altered based on demands. It is noted that the range of single pixel 16 may be defined by a distribution range of elements included in the pixel 16. Taking FIG. 1B as an example, the range of the pixel 16 may be from outer side of the outmost thin-film transistor 18 to an outer side of the wire 42, but is not limited thereto. One of the thin-film transistors 18 may be a switch element 18S, another one of the thin-film transistors 18 may be a driving element 18D, and the light-emitting element 26 may be electrically connected to the driving element 18D through the first electrode 20. In some embodiments, the positions of the switch element 18S and the driving element 18D and the electrical relationship among the switch element 18S, the driving element 18D and the first electrode 20 may be adjusted based on the circuit designs.

(21) In some embodiments, the light-emitting element 26 may include light-emitting body 26A and two conductive pads 26B, in which the light-emitting body 26A may be used for generating light, and the conductive pads 26B are disposed on bottom surfaces of the light-emitting body 26A and used for electrically connecting the light-emitting body 26A to the first electrode 20 and the second electrode 22 respectively. The conductive pads 26B may be disposed on the first electrode 20 and the second electrode 22 respectively, and the conductive pads 26B may be electrically connected to the first electrode 20 and the second electrode 22 respectively. As an example, the light-emitting element 26 may include LED package, LED chip or other suitable light-emitting elements. The LED package or the LED chip may for example include an organic LED, a mini LED, a micro

LED, quantum dot LED, nano-wire LED or quantum rod LED, but is not limited thereto. The LED package may for example include one or more LED chip. The first electrode **20** and the second electrode **22** may be electrically connected to anode and cathode of the light-emitting element **26** respectively, but not limited thereto. In some embodiments, the first electrode **20** and the second electrode **22** may be electrically connected to the cathode and anode of the light-emitting element **26** respectively. In some embodiments, the electronic device **1** may include for example organic LED display device or non-self-emissive display device, but not limited thereto. The non-self-emissive display device may include for example liquid crystal display device, but not limited thereto.

(22) In some embodiments, as shown in FIG. **1B**, when the thin-film transistor **18** is top-gate type, the electronic device **1** may include a semiconductor layer **28**, an insulation layer **30**, a conductive layer **32**, an insulation layer **34**, a conductive layer **36**, and a planarization layer **38**, but is not limited thereto. In such situation, the semiconductor layer **28** may be disposed on the substrate **12** and include a channel layer **181** of the thin-film transistor **18**; the insulation layer **30** may be disposed on the semiconductor layer **28** and the substrate **12** and be regarded as a gate insulation layer of the thin-film transistor **18**; the conductive layer **32** may be disposed on the insulation layer **30** and include a gate **182** of the thin-film transistor **18**; the insulation layer **34** may be disposed on the conductive layer **32** and the insulation layer **30**; the conductive layer **36** may be disposed on the insulation layer **34** and include source/drains **183** of the thin-film transistor **18**, and the source/drains **183** are electrically connected to the channel layer **181** via through holes of the insulation layer **34** and the insulation layer **30**; and the planarization layer **38** may be disposed on the conductive layer **36** and the insulation layer **34**. The planarization layer **38** may include a through hole **381**, such that the first electrode **20** may be electrically connected to one of the source/drains **183** of the corresponding thin-film transistor **18** via the through hole **381**. In the embodiment of FIG. **1B**, the common electrode **14**, the auxiliary electrode **24**, the first electrode **20** and the second electrode **22** are disposed on the planarization layer **38**, but are not limited thereto. In one embodiment, as shown in FIG. **1B**, the electronic device **1** may further include a passivation layer **40** disposed on the common electrode **14**, the auxiliary electrode **24**, the first electrode **20**, the second electrode **22** and the planarization layer **38** and used for protecting the common electrode **14**, the auxiliary electrode **24**, the first electrode **20** and the second electrode **22**. The passivation layer **40** may include two openings **40A** respectively exposing the first electrode **20** and the second electrode **22**, such that the first electrode **20** and the second electrode **22** may be electrically connected to the conductive pads **26B** of the light-emitting element **26** through the openings **40A** respectively.

(23) In some embodiments, the conductive layer **32** and the conductive layer **36** may include conductive material respectively, and the conductive material for example include aluminum, molybdenum nitride, copper, titanium, other suitable materials or combinations thereof, but not limited thereto. The insulation layer **30**, the insulation layer **34** and the passivation layer **40** may respectively include for example silicon oxide, silicon nitride, other suitable materials or combinations thereof, but not limited thereto. The planarization layer **38** may include for example acrylic-based organic material, silicon-based organic material, other suitable organic materials or combinations thereof, but not limited thereto.

(24) The type of thin-film transistor **18** in the present disclosure is not limited to be the top-gate type shown in FIG. **1B**, and in some embodiments, the thin-film transistor **18** may be for example a bottom-gate type transistor, or may be a dual-gate type transistor or other suitable transistors depending on requirements. Alternatively, the thin-film transistor **18** may include for example amorphous silicon transistor, low-temperature poly-silicon (LTPS) transistor, metal-oxide semiconductor (IGZO) transistor, but is not limited thereto. According to the type of the thin-film transistor **18**, the number of the insulation layers in the electronic device **1** may be altered. In some embodiments, different thin-film transistors **18** may include the semiconductor layers **28** of

different materials, but not limited thereto.

(25) In the embodiment of FIG. 1A and FIG. 1B, besides the through hole **381**, the planarization layer **38** may further include a through hole **382** and a through hole **383**, and the wire **42** may be disposed between the planarization layer **38** and the insulation layer **34**, such that the second electrode **22** may be electrically connected to the wire **42** via the through hole **382**, and the common electrode **14** may be electrically connected to the wire **42** via through hole **383**.

Accordingly, the electrical connection between the auxiliary electrode **24** and the common electrode **14** may be achieved. For example, the wire **42** may be formed in the conductive layer **36**, the conductive layer **32** or other conductive layer different from the conductive layer **M**, but is not limited thereto. The electrical connection from the auxiliary electrode **24** to the common electrode **14** in the present disclosure is not limited to the mentioned above. In some embodiments, when the common electrode **14** and the second electrode **22** are formed in the same conductive layer **M**, the auxiliary electrode **24** may be formed in the conductive layer **36** or located in any conductive layer on the conductive layer **36**. In some embodiments, when the auxiliary electrode **24** and the second electrode **22** are formed in the same conductive layer **M**, the common electrode **14** may be formed in a conductive layer different from the conductive layer **M**. For example, the common electrode **14** may be formed in the conductive layer **36**, but not limited thereto.

(26) It is noted that when the thin-film transistor **18** is not operated yet, the channel layer **181** of the thin-film transistor **18** has a certain resistance, and by means of disposing the auxiliary electrode **24** to be adjacent to the first electrode **20**, plenty of electrostatic charges in the first electrode **20** may be discharged to the common electrode **14** through the auxiliary electrode **24**, so as to mitigate the damage to the structure of the thin-film transistor **18** (such as the channel layer **181**), thereby improving the ESD protection of the electronic device **1**.

(27) In some embodiments, as shown in FIG. 1B, the pixel **16** may optionally further include at least two pads **44** disposed on the insulation layer **40**, and the pads **44** are electrically connected to the first electrode **20** and the second electrode **22** respectively through the openings **40A**. The conductive pads **26B** of the light-emitting element **26** may be bonded to the first electrode **20** and the second electrode **22** through the pads **44** respectively, but are not limited thereto. In some embodiments, the pixel **16** may optionally include conductive material for adhering and electrically connecting the conductive pads **26B** to the corresponding pads **44**. For example, the conductive material may include solder ball, but is not limited thereto. In some embodiments, the conductive pads **26B** may be directly bonded to the corresponding pads **44** through eutectic bonding or other suitable bonding method only if the conductive pads **26B** can be electrically connected to the corresponding pads **44**.

(28) In some embodiments, as shown in FIG. 1B, the electronic device **1** may optionally further include a buffer layer **48** disposed between the thin-film transistor **18** and the substrate **12**. The buffer layer **48** may for example be used for blocking moisture or oxygen from entering the electronic device **1**. The buffer layer **48** may be single layer or multilayer. The material of the buffer layer **48** may include for example silicon nitride, silicon oxide, silicon oxynitride, aluminum oxide, resin, other suitable materials or combinations thereof, but not limited thereto.

(29) The electronic device of the present disclosure is not limited to the above-mentioned embodiment and may include different embodiments or variant embodiments. In order to simplify the description, the elements of different embodiments and variant embodiments and the same element of the first embodiment will use the same label. In order to clearly describe different embodiments and variant embodiments, the following contents would focus on the difference between the first embodiment and different embodiments or variant embodiments, and the repeated portion will not be redundantly described.

(30) FIG. 2 schematically illustrates a top view of an electronic device according to a variant embodiment of the first embodiment of the present disclosure. For clearly showing the technical features of the present disclosure, FIG. 2 mainly illustrates a top view of the variant embodiment

corresponding to the region R of FIG. 1, but the present disclosure is not limited thereto. In the embodiment of FIG. 2, the auxiliary electrode 224 may not surround the first electrode 20. In some embodiments, the auxiliary electrode 224 and the second electrode 22 may be electrically connected to the common electrode 14 respectively through wire 42A and wire 42B different from each other. In some embodiments, the wire 42A and the wire 42B may be located in different layers. In some embodiments, the wire 42B may not be electrically connected to the common electrode 14, and the second electrode 22 may be electrically connected to ground through the wire 42B, such that the second electrode 22 and the common electrode 14 may be respectively electrically connected to the ground voltage and the common voltage different from each other.

(31) FIG. 3A schematically illustrates a top view of an electronic device according to a second embodiment of the present disclosure, and FIG. 3B schematically illustrates a cross-sectional view taken along a line B-B' of FIG. 3A. For clearly showing the technical features of the present disclosure, FIG. 3A mainly illustrates a top view of the second embodiment corresponding to the region R of FIG. 1, but the present disclosure is not limited thereto. In the embodiment of FIG. 3A and FIG. 3B, the electronic device 3 is different from the previous embodiment in that the auxiliary electrode 324 is formed in the conductive layer different from the conductive layer M, and the auxiliary electrode 324 is partially overlapped with the first electrode 20 in the top view direction TD of the electronic device 3. In other words, the size of the second opening 324A of the auxiliary electrode 324 may be less than the area of the first electrode 20. For example, the auxiliary electrode 324 may be formed in the same layer as the conductive layer 36, but is not limited thereto. In some embodiments, the auxiliary electrode 324 may be disposed between the planarization layer 38 and the insulation layer 34 and be formed in the conductive layer different from the conductive layer 36. Accordingly, in the electronic device 3, the minimum distance MD1 may for example be located in the top view direction TD or located in a direction that is not parallel to the horizontal direction, but not limited thereto. In some embodiments, when the minimum distance between the source/drain 183 electrically connected to the first electrode 20 and the auxiliary electrode 324 may be less than the minimum distance between the auxiliary electrode 324 and the first electrode 20 in the situation that the minimum distance between the source/drain 183 and the auxiliary electrode 324 is within the range of limit of process machine for patterning, the minimum distance between the source/drain 183 and the auxiliary electrode 324 may be determined by the limit of the process machine.

(32) As shown in FIG. 3A, in one embodiment, the pixel 16 may further include another wire 350 electrically connected to the wire 42. For example, the wire 42 may include a portion that is overlapped with the second electrode 22 in the top view direction TD of the electronic device 3, and the wire 350 may extend to be connected to the wire 42 (the portion overlapped with the second electrode 22), but is not limited thereto. In some embodiments, the wire 350 may extend to be overlapped with the common electrode 14, such that the auxiliary electrode 324 is electrically connected to the common electrode 14 through the wire 350. In some embodiments, in the top view direction TD of the electronic device 3, the auxiliary electrode 324 may not include second opening 324A, that is the auxiliary electrode 324 is at least not overlapped with a side of a portion of the first electrode 20; for example, the auxiliary electrode 324 may be U-shaped, and a side of a portion of the auxiliary electrode 324 may not be overlapped with the first electrode 20.

(33) It should be noted that in the electronic device 3 shown in FIG. 3A and FIG. 3B, because the auxiliary electrode 324 that is electrically connected to the common electrode 14 with larger area is overlapped with the first electrode 20 in the top view direction TD of the electronic device 3 to increase coupling capacitor between the auxiliary electrode 324 and the first electrode 20, the coupling capacitor may facilitate the discharge of the electrostatic charges to the common electrode 14 when plenty of electrostatic charges flow into the first electrode 20, thereby improving the ESD protection of the electronic device 1.

(34) FIG. 4 schematically illustrates a top view of an electronic device according to a variant

embodiment of the second embodiment of the present disclosure. For clearly showing the technical features of the present disclosure, FIG. 4 mainly illustrates a top view of the variant embodiment corresponding to the region R of FIG. 1, but the present disclosure is not limited thereto. In the variant embodiment of FIG. 4, the second electrode 422 may be directly connected to the common electrode 14, such that the electronic device 4 may not require the wire 42 shown in FIG. 3A.

(35) FIG. 5 schematically illustrates a top view of an electronic device according to another variant embodiment of the second embodiment of the present disclosure. The electronic device 5 of the present variant embodiment is different from the embodiment shown in FIG. 3B in that the common electrode 514 may be formed in a conductive layer different from the conductive layer M. For example, the common electrode 514 may be formed in the conductive layer 36, but not limited thereto. When the auxiliary electrode 324 is formed in the conductive layer 36, the auxiliary electrode 324 may be connected to the common electrode 514 directly through the wire 350 (as shown in FIG. 3A), but is not limited thereto. It is noted that during manufacturing the electronic device 5, the common electrode 514 is not electrically connected to the ground voltage or the common voltage yet, and the auxiliary electrode 324 and the common electrode 514 may be formed when the thin-film transistor 18 is manufactured, so that the common electrode 514 with larger area may facilitate the discharge of the electrostatic charges accumulated in the manufacturing processes to itself from the first electrode 20, thereby reducing damage of the electrostatic charges.

(36) In some embodiments, besides the common electrode 514, the electronic device 5 may further include the common electrode 14 formed in the conductive layer M shown in FIG. 1B. In some embodiments, when the common electrode 514 is formed in the conductive layer 36, the auxiliary electrode may adopt the design of the auxiliary electrode 24 shown in FIG. 1B. In such situation, the auxiliary electrode 24 may be electrically connected to the common electrode 514 for example through the second electrode 22 and the wire 42, but not limited thereto.

(37) FIG. 6 schematically illustrates top views of auxiliary electrodes according to other variant embodiments of the present disclosure. For clearly showing the technical features of the present disclosure, FIG. 6 illustrates top views of the auxiliary electrodes of different examples, but not limited thereto. As an example (i) shown in FIG. 6, the auxiliary electrode 624 may be ring-shaped and include a second opening 624A. For example, an outline of the outer side of the auxiliary electrode 624 may be rectangular or other suitable geometric shapes, but not limited thereto. As an example (ii) shown in FIG. 6, the auxiliary electrode 724 may be mesh-shaped and include a plurality of second openings 724A. The shape of the second opening 724A may be for example rectangular or other suitable geometric shapes, but not limited thereto. As an example (iii) shown in FIG. 6, the auxiliary electrode 824 may be block-shaped and include no opening. In such situation, it is required to dispose the auxiliary electrode 824 on a side of the first electrode. As an example (iv) shown in FIG. 6, the auxiliary electrode 924 may include a plurality of second openings 924A, and the second opening 924A may for example be diamond-shaped or other suitable geometric shape. As an example (v) shown in FIG. 6, when the outline of the outer side of the auxiliary electrode 1024 is rectangular or other suitable geometric shapes, the second opening 1024A of the auxiliary electrode 1024 may be irregular shape. In such situation, the second opening 1124A may be for example geometric shape or irregular shape. In some embodiments, any one of the auxiliary electrode 624, the auxiliary electrode 724, the auxiliary electrode 824, the auxiliary electrode 924, the auxiliary electrode 1024, and the auxiliary electrode 1124 mentioned above may be adapted to any one of the embodiments or variant embodiments mentioned above. As viewed along the top view direction, in some embodiments, the example (i), the example (v), the example (vi) of FIG. 6 may replace the auxiliary electrode 24 shown in FIG. 1A, and the first electrode 20 and the second electrode 22 may be disposed in the second opening 624A, the second opening 1024A or the second opening 1124A, in which the difference between the auxiliary electrode of example (i) of FIG. 6 and the auxiliary electrode of FIG. 1A is the auxiliary electrode 624 may not be electrically connected to the second electrode 22 in the example (i) of FIG. 6. In some other embodiments, the

first electrode **20** may be disposed in the second opening **624A**, the second opening **1024A** or the second opening **1124A**. In more detail, the first electrode **20** or the second electrode **22** that is connected to the pad **44** or conductive material **46** may optionally be electrically connected to the auxiliary electrode **624**, the auxiliary electrode **1024** or the auxiliary electrode **1124** or not, and when the light-emitting element is disposed on the substrate **12**, the pad **44** or conductive material **46** of the light-emitting element may be connected to the first electrode **20** or the second electrode **22**. During this process, the electrostatic charges may occur and be discharged through the second opening. In some embodiments, the shape of the auxiliary electrode or the arrangement of the second opening may be designed to avoid peripheral electronic element except for the light-emitting element and the thin-film transistor. For example, in the designs of the auxiliary electrodes of the example (v) and the example (vi) of FIG. **6**, since the auxiliary electrode close to the peripheral electronic element except for the light-emitting element and the thin-film transistor, the auxiliary electrode may discharge the electrostatic charges generated in the process of manufacturing the peripheral electronic element. As viewed along the top view direction, in some embodiments, the example (i), the example (v), the example (vi) of FIG. **6** may replace the auxiliary electrode **324** shown in FIG. **3A** and be partially overlapped with the first electrode **20**. In other words, as viewed along the top view direction, at least a portion of the auxiliary electrode is overlapped with the first electrode **20**, which may be regarded as partially overlapping. In some other embodiments, the auxiliary electrode **724** of the example (ii), the auxiliary electrode **824** of the example (iii) and the auxiliary electrode **924** of the example (iv) of FIG. **6** may be a portion of the auxiliary electrode **324** shown in FIG. **3A**. For example, the auxiliary electrode **724** of the example (ii) of FIG. **6** and the auxiliary electrode **924** of the example (iv) of FIG. **6** may be a portion of the auxiliary electrode **324** shown in FIG. **3A**, and the shape designs of the their openings may be arbitrary changed. In some other embodiments, the second opening **724A** of the example (ii) of FIG. **6** and the second opening of the example (iv) of FIG. **6** may be through holes, and wires may penetrate through the through holes and through different layers based on design requirements. It is noted that the first electrode is close to the opening of the auxiliary electrode mentioned above, such that the minimum distance between the auxiliary electrode and the first electrode is less than the minimum distance between the auxiliary electrode and the second electrode.

(38) In summary, in the electronic device of the present disclosure, by means of disposing the auxiliary electrode to be adjacent to the first electrode, the minimum distance between the first electrode and the auxiliary electrode may be less than the minimum distance between the first electrode and the common electrode, so that plenty of electrostatic charges flowing into the first electrode can be discharged to the common electrode with larger area. Thus, damage to the thin-film transistor by the ESD may be reduced, and the ESD protection of the electronic device is improved.

(39) Those skilled in the art will readily observe that numerous modifications and alterations of the device and method may be made while retaining the teachings of the disclosure. Accordingly, the above disclosure should be construed as limited only by the metes and bounds of the appended claims.

Claims

1. An electronic device, comprising: a substrate; a semiconductor disposed on the substrate; and a conductive layer disposed on the semiconductor and having a first electrode and a second electrode; wherein the first electrode is electrically connected to the semiconductor, and the second electrode surrounds the first electrode in a top view direction of the electronic device, wherein the conductive layer further has a third electrode, in a cross-sectional view of the electronic device, the first electrode is separated from the second electrode with a first distance, the first electrode is

- separated from the third electrode with a second distance, and the first distance is different from the second distance.
2. The electronic device as claimed in claim 1, further comprising a chip electrically connected to the first electrode.
 3. The electronic device as claimed in claim 2, wherein the chip is configured to emit an electromagnetic wave.
 4. The electronic device as claimed in claim 2, wherein the chip is configured to emit a light.
 5. The electronic device as claimed in claim 1, further comprising a diode electrically connected to the first electrode.
 6. The electronic device as claimed in claim 5, wherein the diode is configured to emit a light.
 7. The electronic device as claimed in claim 1, wherein the first distance is less than the second distance.
 8. The electronic device as claimed in claim 1, wherein the third electrode is separated from the second electrode with a third distance, and the third distance is different from the second distance.
 9. The electronic device as claimed in claim 8, wherein the third distance is less than the second distance.
 10. The electronic device as claimed in claim 1, wherein the second electrode surrounds the third electrode.
 11. The electronic device as claimed in claim 1, further comprising a common electrode, wherein the third electrode and the common electrode are electrically connected to different voltages.
 12. The electronic device as claimed in claim 1, wherein the third electrode is electrically connected to the second electrode.
 13. The electronic device as claimed in claim 1, further comprising a fourth electrode disposed between the conductive layer and the semiconductor.
 14. The electronic device as claimed in claim 13, wherein the first electrode is electrically connected to the semiconductor via the fourth electrode.
-