

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12387444
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Boroujerdi; Rastan et al.

Integrating augmented reality experiences with other components

Abstract

Methods and systems are disclosed for generating AR experiences. The methods and systems access a first component of a plurality of components implemented by the messaging application, the plurality of components comprising an AR experience, each of the plurality of components being configured to be separately launched by the messaging application. The methods and systems store a first state of the first component in a data structure that is shared across the plurality of components; launching. The methods and system launch, by the messaging application, a second component of the plurality of components in response to determining that an interaction has been performed using the first component; and configure a second state of the second component based on the interaction that has been performed using the first component.

Inventors: Boroujerdi; Rastan (Hermosa Beach, CA), Evans; Michael John (Auckland, NZ), Haritatos; Panayoti (Rocklin, CA)

Applicant: Snap Inc. (Santa Monica, CA)

Family ID: 87419168

Assignee: Snap Inc. (Santa Monica, CA)

Appl. No.: 18/665388

Filed: May 15, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240303945 A1	Sep. 12, 2024

Related U.S. Application Data

continuation parent-doc US 17845496 20220621 US 12020384 child-doc US 18665388

Publication Classification

Int. Cl.: **G06F3/04815** (20220101); **G01C21/36** (20060101); **G06F3/04842** (20220101); **G06T19/00** (20110101); **H04L9/40** (20220101)

U.S. Cl.:

CPC **G06T19/006** (20130101); **G01C21/3647** (20130101); **G06F3/04815** (20130101); **G06F3/04842** (20130101); **H04L63/083** (20130101); G06T2200/24 (20130101); G06T2219/024 (20130101)

Field of Classification Search

CPC: G06T (19/006); G06T (2200/24); G06T (2219/024); G01C (21/3647); G06F (3/04815); G06F (3/04842); H04L (63/083)

USPC: 345/633

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
666223	12/1900	Shedlock	N/A	N/A
4581634	12/1985	Williams	N/A	N/A
4975690	12/1989	Torres	N/A	N/A
5072412	12/1990	Henderson, Jr. et al.	N/A	N/A
5493692	12/1995	Theimer et al.	N/A	N/A
5604843	12/1996	Shaw et al.	N/A	N/A
5689559	12/1996	Park	N/A	N/A
5713073	12/1997	Warsta	N/A	N/A
5754939	12/1997	Herz et al.	N/A	N/A
5855008	12/1997	Goldhaber et al.	N/A	N/A
5880731	12/1998	Liles et al.	N/A	N/A
5883639	12/1998	Walton et al.	N/A	N/A
5999932	12/1998	Paul	N/A	N/A
6012098	12/1999	Bayeh et al.	N/A	N/A
6014090	12/1999	Rosen et al.	N/A	N/A
6023270	12/1999	Brush, II et al.	N/A	N/A
6029141	12/1999	Bezos et al.	N/A	N/A
6038295	12/1999	Mattes	N/A	N/A
6049711	12/1999	Yehezkel et al.	N/A	N/A
RE36919	12/1999	Park	N/A	N/A
6154764	12/1999	Nitta et al.	N/A	N/A
6167435	12/1999	Druckenmiller et al.	N/A	N/A
RE37052	12/2000	Park	N/A	N/A
6204840	12/2000	Petelycky et al.	N/A	N/A
6205432	12/2000	Gabbard et al.	N/A	N/A
6216141	12/2000	Straub et al.	N/A	N/A
6223165	12/2000	Lauffer	N/A	N/A

6285381	12/2000	Sawano et al.	N/A	N/A
6285987	12/2000	Roth et al.	N/A	N/A
6310694	12/2000	Okimoto et al.	N/A	N/A
6317789	12/2000	Rakavy et al.	N/A	N/A
6334149	12/2000	Davis, Jr. et al.	N/A	N/A
6349203	12/2001	Asaoka et al.	N/A	N/A
6353170	12/2001	Eyzaguirre et al.	N/A	N/A
6446004	12/2001	Cao et al.	N/A	N/A
6449657	12/2001	Stanbach et al.	N/A	N/A
6456852	12/2001	Bar et al.	N/A	N/A
6484196	12/2001	Maurille	N/A	N/A
6487601	12/2001	Hubacher et al.	N/A	N/A
6523008	12/2002	Avrunin	N/A	N/A
6542749	12/2002	Tanaka et al.	N/A	N/A
6549768	12/2002	Fraccaroli	N/A	N/A
6618593	12/2002	Drutman et al.	N/A	N/A
6622174	12/2002	Ukita et al.	N/A	N/A
6631463	12/2002	Floyd et al.	N/A	N/A
6636247	12/2002	Hamzy et al.	N/A	N/A
6636855	12/2002	Holloway et al.	N/A	N/A
6643684	12/2002	Malkin et al.	N/A	N/A
6650793	12/2002	Lund et al.	N/A	N/A
6658095	12/2002	Yoakum et al.	N/A	N/A
6665531	12/2002	Soderbacka et al.	N/A	N/A
6668173	12/2002	Greene	N/A	N/A
6684238	12/2003	Dutta	N/A	N/A
6684257	12/2003	Camut et al.	N/A	N/A
6698020	12/2003	Zigmond et al.	N/A	N/A
6700506	12/2003	Winkler	N/A	N/A
6720860	12/2003	Narayanaswami	N/A	N/A
6724403	12/2003	Santoro et al.	N/A	N/A
6757713	12/2003	Ogilvie et al.	N/A	N/A
6772195	12/2003	Hatlelid et al.	N/A	N/A
6804417	12/2003	Lund et al.	N/A	N/A
6832222	12/2003	Zimowski	N/A	N/A
6834195	12/2003	Brandenberg et al.	N/A	N/A
6836792	12/2003	Chen	N/A	N/A
6842779	12/2004	Nishizawa	N/A	N/A
6898626	12/2004	Ohashi	N/A	N/A
6959324	12/2004	Kubik et al.	N/A	N/A
6970088	12/2004	Kovach	N/A	N/A
6970907	12/2004	Ullmann et al.	N/A	N/A
6980909	12/2004	Root et al.	N/A	N/A
6981040	12/2004	Konig et al.	N/A	N/A
7020494	12/2005	Spriestersbach et al.	N/A	N/A
7027124	12/2005	Foote et al.	N/A	N/A
7072963	12/2005	Anderson et al.	N/A	N/A
7085571	12/2005	Kalhan et al.	N/A	N/A
7110744	12/2005	Freeny, Jr.	N/A	N/A
7124164	12/2005	Chemtob	N/A	N/A

7149893	12/2005	Leonard et al.	N/A	N/A
7173651	12/2006	Knowles	N/A	N/A
7188143	12/2006	Szeto	N/A	N/A
7203380	12/2006	Chiu et al.	N/A	N/A
7206568	12/2006	Sudit	N/A	N/A
7227937	12/2006	Yoakum et al.	N/A	N/A
7237002	12/2006	Estrada et al.	N/A	N/A
7240089	12/2006	Boudreau	N/A	N/A
7269426	12/2006	Kokkonen et al.	N/A	N/A
7280658	12/2006	Amini et al.	N/A	N/A
7315823	12/2007	Brondrup	N/A	N/A
7342587	12/2007	Danzig et al.	N/A	N/A
7349768	12/2007	Bruce et al.	N/A	N/A
7356564	12/2007	Hartselle et al.	N/A	N/A
7394345	12/2007	Ehlinger et al.	N/A	N/A
7411493	12/2007	Smith	N/A	N/A
7423580	12/2007	Markhovsky et al.	N/A	N/A
7454442	12/2007	Cobleigh et al.	N/A	N/A
7468729	12/2007	Levinson	N/A	N/A
7508419	12/2008	Toyama et al.	N/A	N/A
7519670	12/2008	Hagale et al.	N/A	N/A
7535890	12/2008	Rojas	N/A	N/A
7546554	12/2008	Chiu et al.	N/A	N/A
7607096	12/2008	Oreizy et al.	N/A	N/A
7636755	12/2008	Blattner et al.	N/A	N/A
7639251	12/2008	Gu et al.	N/A	N/A
7639943	12/2008	Kalajan	N/A	N/A
7650231	12/2009	Gadler	N/A	N/A
7668537	12/2009	DeVries	N/A	N/A
7770137	12/2009	Forbes et al.	N/A	N/A
7775885	12/2009	Van et al.	N/A	N/A
7778973	12/2009	Choi	N/A	N/A
7779444	12/2009	Glad	N/A	N/A
7787886	12/2009	Markhovsky et al.	N/A	N/A
7796946	12/2009	Eisenbach	N/A	N/A
7801954	12/2009	Cadiz et al.	N/A	N/A
7856360	12/2009	Kramer et al.	N/A	N/A
7859551	12/2009	Bulman et al.	N/A	N/A
7885931	12/2010	Seo et al.	N/A	N/A
7925703	12/2010	Dinan et al.	N/A	N/A
8001204	12/2010	Burtner et al.	N/A	N/A
8032586	12/2010	Challenger et al.	N/A	N/A
8082255	12/2010	Carlson, Jr. et al.	N/A	N/A
8088044	12/2011	Tchao et al.	N/A	N/A
8090351	12/2011	Klein	N/A	N/A
8095878	12/2011	Bates et al.	N/A	N/A
8098904	12/2011	Ioffe et al.	N/A	N/A
8099109	12/2011	Altman et al.	N/A	N/A
8108774	12/2011	Finn et al.	N/A	N/A
8112716	12/2011	Kobayashi	N/A	N/A

8117281	12/2011	Robinson et al.	N/A	N/A
8130219	12/2011	Fleury et al.	N/A	N/A
8131597	12/2011	Hudetz	N/A	N/A
8135166	12/2011	Rhoads	N/A	N/A
8136028	12/2011	Loeb et al.	N/A	N/A
8146001	12/2011	Reese	N/A	N/A
8146005	12/2011	Jones et al.	N/A	N/A
8151191	12/2011	Nicol	N/A	N/A
8161115	12/2011	Yamamoto	N/A	N/A
8161417	12/2011	Lee	N/A	N/A
8195203	12/2011	Tseng	N/A	N/A
8199747	12/2011	Rojas et al.	N/A	N/A
8208943	12/2011	Petersen	N/A	N/A
8214443	12/2011	Hamburg	N/A	N/A
8234350	12/2011	Gu et al.	N/A	N/A
8276092	12/2011	Narayanan et al.	N/A	N/A
8279319	12/2011	Date	N/A	N/A
8280406	12/2011	Ziskind et al.	N/A	N/A
8285199	12/2011	Hsu et al.	N/A	N/A
8287380	12/2011	Nguyen et al.	N/A	N/A
8301159	12/2011	Hamynen et al.	N/A	N/A
8306922	12/2011	Kunal et al.	N/A	N/A
8312086	12/2011	Velusamy et al.	N/A	N/A
8312097	12/2011	Siegel et al.	N/A	N/A
8326315	12/2011	Phillips et al.	N/A	N/A
8326327	12/2011	Hymel et al.	N/A	N/A
8332475	12/2011	Rosen et al.	N/A	N/A
8352546	12/2012	Dollard	N/A	N/A
RE43993	12/2012	Park	N/A	N/A
8379130	12/2012	Forutanpour et al.	N/A	N/A
8384719	12/2012	Reville et al.	N/A	N/A
8385950	12/2012	Wagner et al.	N/A	N/A
RE44054	12/2012	Kim	N/A	N/A
RE44068	12/2012	Park	N/A	N/A
RE44106	12/2012	Park	N/A	N/A
8396708	12/2012	Park et al.	N/A	N/A
8402097	12/2012	Szeto	N/A	N/A
8405773	12/2012	Hayashi et al.	N/A	N/A
RE44121	12/2012	Park	N/A	N/A
8418067	12/2012	Cheng et al.	N/A	N/A
8423409	12/2012	Rao	N/A	N/A
8425322	12/2012	Gillo et al.	N/A	N/A
8458601	12/2012	Castelli et al.	N/A	N/A
8462198	12/2012	Lin et al.	N/A	N/A
8471914	12/2012	Sakiyama et al.	N/A	N/A
8472935	12/2012	Fujisaki	N/A	N/A
8484158	12/2012	Deluca et al.	N/A	N/A
8495503	12/2012	Brown et al.	N/A	N/A
8495505	12/2012	Smith et al.	N/A	N/A
8504926	12/2012	Wolf	N/A	N/A

8510383	12/2012	Hurley et al.	N/A	N/A
8527345	12/2012	Rothschild et al.	N/A	N/A
8554627	12/2012	Svendsen et al.	N/A	N/A
8559980	12/2012	Pujol	N/A	N/A
8560612	12/2012	Kilmer et al.	N/A	N/A
8564621	12/2012	Branson et al.	N/A	N/A
8564710	12/2012	Nonaka et al.	N/A	N/A
8581911	12/2012	Becker et al.	N/A	N/A
8594680	12/2012	Ledlie et al.	N/A	N/A
8597121	12/2012	del Valle	N/A	N/A
8601051	12/2012	Wang	N/A	N/A
8601379	12/2012	Marks et al.	N/A	N/A
8613089	12/2012	Holloway et al.	N/A	N/A
8632408	12/2013	Gillo et al.	N/A	N/A
8648865	12/2013	Dawson et al.	N/A	N/A
8659548	12/2013	Hildreth	N/A	N/A
8660358	12/2013	Bergboer et al.	N/A	N/A
8660369	12/2013	Llano et al.	N/A	N/A
8660793	12/2013	Ngo et al.	N/A	N/A
8682350	12/2013	Altman et al.	N/A	N/A
8683354	12/2013	Khandelwal et al.	N/A	N/A
8692830	12/2013	Nelson et al.	N/A	N/A
8718333	12/2013	Wolf et al.	N/A	N/A
8724622	12/2013	Rojas	N/A	N/A
8732168	12/2013	Johnson	N/A	N/A
8744523	12/2013	Fan et al.	N/A	N/A
8745132	12/2013	Obradovich	N/A	N/A
8761800	12/2013	Kuwahara	N/A	N/A
8768876	12/2013	Shim et al.	N/A	N/A
8775972	12/2013	Spiegel	N/A	N/A
8788680	12/2013	Naik	N/A	N/A
8790187	12/2013	Walker et al.	N/A	N/A
8797415	12/2013	Arnold	N/A	N/A
8798646	12/2013	Wang et al.	N/A	N/A
8810513	12/2013	Ptucha et al.	N/A	N/A
8812171	12/2013	Filev et al.	N/A	N/A
8832201	12/2013	Wall	N/A	N/A
8832552	12/2013	Arrasvuori et al.	N/A	N/A
8839327	12/2013	Amento et al.	N/A	N/A
8856349	12/2013	Jain et al.	N/A	N/A
8874677	12/2013	Rosen et al.	N/A	N/A
8886227	12/2013	Schmidt et al.	N/A	N/A
8890926	12/2013	Tandon et al.	N/A	N/A
8892999	12/2013	Nims et al.	N/A	N/A
8909679	12/2013	Root et al.	N/A	N/A
8909725	12/2013	Sehn	N/A	N/A
8924250	12/2013	Bates et al.	N/A	N/A
8963926	12/2014	Brown et al.	N/A	N/A
8972357	12/2014	Shim et al.	N/A	N/A
8989786	12/2014	Feghali	N/A	N/A

8995433	12/2014	Rojas	N/A	N/A
9015285	12/2014	Ebsen et al.	N/A	N/A
9020745	12/2014	Johnston et al.	N/A	N/A
9040574	12/2014	Wang et al.	N/A	N/A
9055416	12/2014	Rosen et al.	N/A	N/A
9086776	12/2014	Ye et al.	N/A	N/A
9094137	12/2014	Sehn et al.	N/A	N/A
9100806	12/2014	Rosen et al.	N/A	N/A
9100807	12/2014	Rosen et al.	N/A	N/A
9105014	12/2014	Collet et al.	N/A	N/A
9113301	12/2014	Spiegel et al.	N/A	N/A
9119027	12/2014	Sharon et al.	N/A	N/A
9123074	12/2014	Jacobs et al.	N/A	N/A
9143382	12/2014	Bhogal et al.	N/A	N/A
9143681	12/2014	Ebsen et al.	N/A	N/A
9152477	12/2014	Campbell et al.	N/A	N/A
9191776	12/2014	Root et al.	N/A	N/A
9204252	12/2014	Root	N/A	N/A
9225897	12/2014	Sehn et al.	N/A	N/A
9241184	12/2015	Weerasinghe	N/A	N/A
9256860	12/2015	Herger et al.	N/A	N/A
9258459	12/2015	Hartley	N/A	N/A
9298257	12/2015	Hwang et al.	N/A	N/A
9314692	12/2015	Konoplev et al.	N/A	N/A
9330483	12/2015	Du et al.	N/A	N/A
9344606	12/2015	Hartley et al.	N/A	N/A
9357174	12/2015	Li et al.	N/A	N/A
9361510	12/2015	Yao et al.	N/A	N/A
9378576	12/2015	Bouaziz et al.	N/A	N/A
9385983	12/2015	Sehn	N/A	N/A
9396354	12/2015	Murphy et al.	N/A	N/A
9402057	12/2015	Kaytaz et al.	N/A	N/A
9407712	12/2015	Sehn	N/A	N/A
9407816	12/2015	Sehn	N/A	N/A
9412192	12/2015	Mandel et al.	N/A	N/A
9430783	12/2015	Sehn	N/A	N/A
9439041	12/2015	Parvizi et al.	N/A	N/A
9443227	12/2015	Evans et al.	N/A	N/A
9450907	12/2015	Pridmore et al.	N/A	N/A
9459778	12/2015	Hogeg et al.	N/A	N/A
9460541	12/2015	Li et al.	N/A	N/A
9489661	12/2015	Evans et al.	N/A	N/A
9489760	12/2015	Li et al.	N/A	N/A
9491134	12/2015	Rosen et al.	N/A	N/A
9503845	12/2015	Vincent	N/A	N/A
9508197	12/2015	Quinn et al.	N/A	N/A
9532171	12/2015	Allen et al.	N/A	N/A
9532364	12/2015	Fujito	N/A	N/A
9537811	12/2016	Allen et al.	N/A	N/A
9544257	12/2016	Ogundokun et al.	N/A	N/A

9576400	12/2016	Van Os et al.	N/A	N/A
9589357	12/2016	Li et al.	N/A	N/A
9592449	12/2016	Barbalet et al.	N/A	N/A
9628950	12/2016	Noeth et al.	N/A	N/A
9648376	12/2016	Chang et al.	N/A	N/A
9697635	12/2016	Quinn et al.	N/A	N/A
9706040	12/2016	Kadirvel et al.	N/A	N/A
9710821	12/2016	Heath	N/A	N/A
9744466	12/2016	Fujioka	N/A	N/A
9746990	12/2016	Anderson et al.	N/A	N/A
9749270	12/2016	Collet et al.	N/A	N/A
9792714	12/2016	Li et al.	N/A	N/A
9839844	12/2016	Dunstan et al.	N/A	N/A
9854219	12/2016	Sehn	N/A	N/A
9883838	12/2017	Kaleal, III et al.	N/A	N/A
9898849	12/2017	Du et al.	N/A	N/A
9911073	12/2017	Spiegel et al.	N/A	N/A
9936165	12/2017	Li et al.	N/A	N/A
9959037	12/2017	Chaudhri et al.	N/A	N/A
9980100	12/2017	Charlton et al.	N/A	N/A
9990373	12/2017	Fortkort	N/A	N/A
10039988	12/2017	Lobb et al.	N/A	N/A
10097492	12/2017	Tsuda et al.	N/A	N/A
10116598	12/2017	Tucker et al.	N/A	N/A
10155168	12/2017	Blackstock et al.	N/A	N/A
10158589	12/2017	Collet et al.	N/A	N/A
10242477	12/2018	Charlton et al.	N/A	N/A
10242503	12/2018	McPhee et al.	N/A	N/A
10262250	12/2018	Spiegel et al.	N/A	N/A
10348662	12/2018	Baldwin et al.	N/A	N/A
10362219	12/2018	Wilson et al.	N/A	N/A
10432559	12/2018	Baldwin et al.	N/A	N/A
10454857	12/2018	Blackstock et al.	N/A	N/A
10475225	12/2018	Park et al.	N/A	N/A
10504266	12/2018	Blattner et al.	N/A	N/A
10554596	12/2019	Fish et al.	N/A	N/A
10573048	12/2019	Ni et al.	N/A	N/A
10656797	12/2019	Alvi et al.	N/A	N/A
10657695	12/2019	Chand et al.	N/A	N/A
10657701	12/2019	Osman et al.	N/A	N/A
10674311	12/2019	Bouba et al.	N/A	N/A
10762174	12/2019	Denton et al.	N/A	N/A
10805248	12/2019	Luo et al.	N/A	N/A
10872451	12/2019	Sheth et al.	N/A	N/A
10880246	12/2019	Baldwin et al.	N/A	N/A
10893385	12/2020	Berardino et al.	N/A	N/A
10895964	12/2020	Grantham et al.	N/A	N/A
10896534	12/2020	Smith et al.	N/A	N/A
10933311	12/2020	Brody et al.	N/A	N/A
10936066	12/2020	Jaureguiberry et al.	N/A	N/A

10938758	12/2020	Allen et al.	N/A	N/A
10939246	12/2020	Dancie et al.	N/A	N/A
10945098	12/2020	Dancie et al.	N/A	N/A
10964082	12/2020	Amitay et al.	N/A	N/A
10979752	12/2020	Brody et al.	N/A	N/A
10984575	12/2020	Assouline et al.	N/A	N/A
10992619	12/2020	Antmen et al.	N/A	N/A
11010022	12/2020	Alvi et al.	N/A	N/A
11030789	12/2020	Chand et al.	N/A	N/A
11032670	12/2020	Baylin et al.	N/A	N/A
11036781	12/2020	Baril et al.	N/A	N/A
11039270	12/2020	Bouba et al.	N/A	N/A
11063891	12/2020	Voss	N/A	N/A
11069103	12/2020	Blackstock et al.	N/A	N/A
11080917	12/2020	Monroy-hernández et al.	N/A	N/A
11128586	12/2020	Al Majid et al.	N/A	N/A
11166123	12/2020	Guillaume	N/A	N/A
11188190	12/2020	Blackstock et al.	N/A	N/A
11189070	12/2020	Jahangiri et al.	N/A	N/A
11199957	12/2020	Alvi et al.	N/A	N/A
11218433	12/2021	Baldwin et al.	N/A	N/A
11229849	12/2021	Blackstock et al.	N/A	N/A
11245658	12/2021	Grantham et al.	N/A	N/A
11249614	12/2021	Brody	N/A	N/A
11263254	12/2021	Baril et al.	N/A	N/A
11270491	12/2021	Monroy-Hernández et al.	N/A	N/A
11275439	12/2021	Jaureguiberry et al.	N/A	N/A
11284144	12/2021	Kotsopoulos et al.	N/A	N/A
11294936	12/2021	Jaureguiberry	N/A	N/A
11307747	12/2021	Dancie et al.	N/A	N/A
2002/0047868	12/2001	Miyazawa	N/A	N/A
2002/0067362	12/2001	Agostino Nocera et al.	N/A	N/A
2002/0078456	12/2001	Hudson et al.	N/A	N/A
2002/0087631	12/2001	Sharma	N/A	N/A
2002/0097257	12/2001	Miller et al.	N/A	N/A
2002/0122659	12/2001	Mcgrath et al.	N/A	N/A
2002/0128047	12/2001	Gates	N/A	N/A
2002/0144154	12/2001	Tomkow	N/A	N/A
2002/0169644	12/2001	Greene	N/A	N/A
2003/0001846	12/2002	Davis et al.	N/A	N/A
2003/0016247	12/2002	Lai et al.	N/A	N/A
2003/0017823	12/2002	Mager et al.	N/A	N/A
2003/0020623	12/2002	Cao et al.	N/A	N/A
2003/0023874	12/2002	Prokupets et al.	N/A	N/A
2003/0037124	12/2002	Yamaura et al.	N/A	N/A
2003/0052925	12/2002	Daimon et al.	N/A	N/A
2003/0101230	12/2002	Benschoter et al.	N/A	N/A

2003/0110503	12/2002	Perkes	N/A	N/A
2003/0126215	12/2002	Udell	N/A	N/A
2003/0148773	12/2002	Spriestersbach et al.	N/A	N/A
2003/0164856	12/2002	Prager et al.	N/A	N/A
2003/0229607	12/2002	Zellweger et al.	N/A	N/A
2004/0027371	12/2003	Jaeger	N/A	N/A
2004/0064429	12/2003	Hirstius et al.	N/A	N/A
2004/0078367	12/2003	Anderson et al.	N/A	N/A
2004/0111467	12/2003	Willis	N/A	N/A
2004/0158739	12/2003	Wakai et al.	N/A	N/A
2004/0189465	12/2003	Capobianco et al.	N/A	N/A
2004/0203959	12/2003	Coombes	N/A	N/A
2004/0215625	12/2003	Svendsen et al.	N/A	N/A
2004/0243531	12/2003	Dean	N/A	N/A
2004/0243688	12/2003	Wugofski	N/A	N/A
2005/0021444	12/2004	Bauer et al.	N/A	N/A
2005/0022211	12/2004	Veselov et al.	N/A	N/A
2005/0048989	12/2004	Jung	N/A	N/A
2005/0078804	12/2004	Yomoda	N/A	N/A
2005/0097176	12/2004	Schatz et al.	N/A	N/A
2005/0102381	12/2004	Jiang et al.	N/A	N/A
2005/0104976	12/2004	Currans	N/A	N/A
2005/0114783	12/2004	Szeto	N/A	N/A
2005/0119936	12/2004	Buchanan et al.	N/A	N/A
2005/0122405	12/2004	Voss et al.	N/A	N/A
2005/0162419	12/2004	Kim et al.	N/A	N/A
2005/0193340	12/2004	Amburgey et al.	N/A	N/A
2005/0193345	12/2004	Klassen et al.	N/A	N/A
2005/0198128	12/2004	Anderson	N/A	N/A
2005/0206610	12/2004	Cordelli	N/A	N/A
2005/0223066	12/2004	Buchheit et al.	N/A	N/A
2005/0288954	12/2004	McCarthy et al.	N/A	N/A
2006/0026067	12/2005	Nicholas et al.	N/A	N/A
2006/0107297	12/2005	Toyama et al.	N/A	N/A
2006/0114338	12/2005	Rothschild	N/A	N/A
2006/0119882	12/2005	Harris et al.	N/A	N/A
2006/0242239	12/2005	Morishima et al.	N/A	N/A
2006/0252438	12/2005	Ansamaa et al.	N/A	N/A
2006/0265417	12/2005	Amato et al.	N/A	N/A
2006/0270419	12/2005	Crowley et al.	N/A	N/A
2006/0287878	12/2005	Wadhwa et al.	N/A	N/A
2006/0294465	12/2005	Ronen et al.	N/A	N/A
2007/0004426	12/2006	Pfleging et al.	N/A	N/A
2007/0038715	12/2006	Collins et al.	N/A	N/A
2007/0040931	12/2006	Nishizawa	N/A	N/A
2007/0073517	12/2006	Panje	N/A	N/A
2007/0073823	12/2006	Cohen et al.	N/A	N/A
2007/0075898	12/2006	Markhovsky et al.	N/A	N/A
2007/0082707	12/2006	Flynt et al.	N/A	N/A
2007/0113181	12/2006	Blattner et al.	N/A	N/A

2007/0136228	12/2006	Petersen	N/A	N/A
2007/0168863	12/2006	Blattner et al.	N/A	N/A
2007/0176921	12/2006	Iwasaki et al.	N/A	N/A
2007/0192128	12/2006	Celestini	N/A	N/A
2007/0198340	12/2006	Lucovsky et al.	N/A	N/A
2007/0198495	12/2006	Buron et al.	N/A	N/A
2007/0208751	12/2006	Cowan et al.	N/A	N/A
2007/0210936	12/2006	Nicholson	N/A	N/A
2007/0214180	12/2006	Crawford	N/A	N/A
2007/0214216	12/2006	Carrer et al.	N/A	N/A
2007/0233556	12/2006	Koningstein	N/A	N/A
2007/0233801	12/2006	Eren et al.	N/A	N/A
2007/0233859	12/2006	Zhao et al.	N/A	N/A
2007/0243887	12/2006	Bandhole et al.	N/A	N/A
2007/0244750	12/2006	Grannan et al.	N/A	N/A
2007/0255456	12/2006	Funayama	N/A	N/A
2007/0281690	12/2006	Altman et al.	N/A	N/A
2008/0022329	12/2007	Glad	N/A	N/A
2008/0025701	12/2007	Ikeda	N/A	N/A
2008/0032703	12/2007	Krumm et al.	N/A	N/A
2008/0033930	12/2007	Warren	N/A	N/A
2008/0043041	12/2007	Hedenstroem et al.	N/A	N/A
2008/0049704	12/2007	Witteman et al.	N/A	N/A
2008/0062141	12/2007	Chandhri	N/A	N/A
2008/0076505	12/2007	Ngyen et al.	N/A	N/A
2008/0092233	12/2007	Tian et al.	N/A	N/A
2008/0094387	12/2007	Chen	N/A	N/A
2008/0104503	12/2007	Beall et al.	N/A	N/A
2008/0109844	12/2007	Baldeschweiler et al.	N/A	N/A
2008/0120409	12/2007	Sun et al.	N/A	N/A
2008/0147730	12/2007	Lee et al.	N/A	N/A
2008/0148150	12/2007	Mall	N/A	N/A
2008/0158222	12/2007	Li et al.	N/A	N/A
2008/0158230	12/2007	Sharma et al.	N/A	N/A
2008/0168033	12/2007	Ott et al.	N/A	N/A
2008/0168489	12/2007	Schraga	N/A	N/A
2008/0189177	12/2007	Anderton et al.	N/A	N/A
2008/0207176	12/2007	Brackbill et al.	N/A	N/A
2008/0208692	12/2007	Garaventi et al.	N/A	N/A
2008/0214210	12/2007	Rasanen et al.	N/A	N/A
2008/0222545	12/2007	Lemay	N/A	N/A
2008/0255976	12/2007	Altberg et al.	N/A	N/A
2008/0256446	12/2007	Yamamoto	N/A	N/A
2008/0256577	12/2007	Funaki et al.	N/A	N/A
2008/0266421	12/2007	Takahata et al.	N/A	N/A
2008/0270938	12/2007	Carlson	N/A	N/A
2008/0288338	12/2007	Wiseman et al.	N/A	N/A
2008/0306826	12/2007	Kramer et al.	N/A	N/A
2008/0313329	12/2007	Wang et al.	N/A	N/A
2008/0313346	12/2007	Kujawa et al.	N/A	N/A

2008/0318616	12/2007	Chipalkatti et al.	N/A	N/A
2009/0006191	12/2008	Arankalle et al.	N/A	N/A
2009/0006565	12/2008	Velusamy et al.	N/A	N/A
2009/0015703	12/2008	Kim et al.	N/A	N/A
2009/0016617	12/2008	Bregman-amitai et al.	N/A	N/A
2009/0024956	12/2008	Kobayashi	N/A	N/A
2009/0030774	12/2008	Rothschild et al.	N/A	N/A
2009/0030999	12/2008	Gatzke et al.	N/A	N/A
2009/0040324	12/2008	Nonaka	N/A	N/A
2009/0042588	12/2008	Lottin et al.	N/A	N/A
2009/0055484	12/2008	Vuong et al.	N/A	N/A
2009/0058822	12/2008	Chaudhri	N/A	N/A
2009/0070688	12/2008	Gyorfi et al.	N/A	N/A
2009/0079846	12/2008	Chou	N/A	N/A
2009/0089678	12/2008	Sacco et al.	N/A	N/A
2009/0089710	12/2008	Wood et al.	N/A	N/A
2009/0093261	12/2008	Ziskind	N/A	N/A
2009/0099925	12/2008	Mehta et al.	N/A	N/A
2009/0106672	12/2008	Burstrom	N/A	N/A
2009/0132341	12/2008	Klinger	N/A	N/A
2009/0132453	12/2008	Hangartner et al.	N/A	N/A
2009/0132665	12/2008	Thomsen et al.	N/A	N/A
2009/0148045	12/2008	Lee et al.	N/A	N/A
2009/0153492	12/2008	Popp	N/A	N/A
2009/0157450	12/2008	Athsani et al.	N/A	N/A
2009/0157752	12/2008	Gonzalez	N/A	N/A
2009/0158170	12/2008	Narayanan et al.	N/A	N/A
2009/0160970	12/2008	Fredlund et al.	N/A	N/A
2009/0163182	12/2008	Gatti et al.	N/A	N/A
2009/0177299	12/2008	Van De Sluis	N/A	N/A
2009/0177976	12/2008	Bokor et al.	N/A	N/A
2009/0192900	12/2008	Collision	N/A	N/A
2009/0199242	12/2008	Johnson et al.	N/A	N/A
2009/0202114	12/2008	Morin et al.	N/A	N/A
2009/0215469	12/2008	Fisher et al.	N/A	N/A
2009/0232354	12/2008	Camp, Jr. et al.	N/A	N/A
2009/0234815	12/2008	Boerries et al.	N/A	N/A
2009/0239552	12/2008	Churchill et al.	N/A	N/A
2009/0249222	12/2008	Schmidt et al.	N/A	N/A
2009/0249244	12/2008	Robinson et al.	N/A	N/A
2009/0265604	12/2008	Howard et al.	N/A	N/A
2009/0265647	12/2008	Martin et al.	N/A	N/A
2009/0288022	12/2008	Almstrand et al.	N/A	N/A
2009/0291672	12/2008	Treves et al.	N/A	N/A
2009/0292608	12/2008	Polachek	N/A	N/A
2009/0300525	12/2008	Jolliff et al.	N/A	N/A
2009/0303984	12/2008	Clark et al.	N/A	N/A
2009/0319607	12/2008	Belz et al.	N/A	N/A
2009/0327073	12/2008	Li	N/A	N/A

2010/0011422	12/2009	Mason et al.	N/A	N/A
2010/0023885	12/2009	Reville et al.	N/A	N/A
2010/0062794	12/2009	Han	N/A	N/A
2010/0082427	12/2009	Burgener et al.	N/A	N/A
2010/0082693	12/2009	Hugg et al.	N/A	N/A
2010/0100568	12/2009	Papin et al.	N/A	N/A
2010/0113065	12/2009	Narayan et al.	N/A	N/A
2010/0115426	12/2009	Liu et al.	N/A	N/A
2010/0130233	12/2009	Parker	N/A	N/A
2010/0131880	12/2009	Lee et al.	N/A	N/A
2010/0131895	12/2009	Wohlert	N/A	N/A
2010/0153144	12/2009	Miller et al.	N/A	N/A
2010/0159944	12/2009	Pascal et al.	N/A	N/A
2010/0161658	12/2009	Hamynen et al.	N/A	N/A
2010/0161831	12/2009	Haas et al.	N/A	N/A
2010/0162149	12/2009	Sheleheda et al.	N/A	N/A
2010/0183280	12/2009	Beauregard et al.	N/A	N/A
2010/0185552	12/2009	Deluca et al.	N/A	N/A
2010/0185665	12/2009	Horn et al.	N/A	N/A
2010/0191631	12/2009	Weidmann	N/A	N/A
2010/0197318	12/2009	Petersen et al.	N/A	N/A
2010/0197319	12/2009	Petersen et al.	N/A	N/A
2010/0198683	12/2009	Aarabi	N/A	N/A
2010/0198694	12/2009	Muthukrishnan	N/A	N/A
2010/0198826	12/2009	Petersen et al.	N/A	N/A
2010/0198828	12/2009	Petersen et al.	N/A	N/A
2010/0198862	12/2009	Jennings et al.	N/A	N/A
2010/0198870	12/2009	Petersen et al.	N/A	N/A
2010/0198917	12/2009	Petersen et al.	N/A	N/A
2010/0201482	12/2009	Robertson et al.	N/A	N/A
2010/0201536	12/2009	Robertson et al.	N/A	N/A
2010/0203968	12/2009	Gill et al.	N/A	N/A
2010/0214436	12/2009	Kim et al.	N/A	N/A
2010/0223128	12/2009	Dukellis et al.	N/A	N/A
2010/0223343	12/2009	Bosan et al.	N/A	N/A
2010/0227682	12/2009	Reville et al.	N/A	N/A
2010/0250109	12/2009	Johnston et al.	N/A	N/A
2010/0257196	12/2009	Waters et al.	N/A	N/A
2010/0259386	12/2009	Holley et al.	N/A	N/A
2010/0273509	12/2009	Sweeney et al.	N/A	N/A
2010/0281045	12/2009	Dean	N/A	N/A
2010/0306669	12/2009	Della Pasqua	N/A	N/A
2011/0004071	12/2010	Faiola et al.	N/A	N/A
2011/0010205	12/2010	Richards	N/A	N/A
2011/0029512	12/2010	Folgnier et al.	N/A	N/A
2011/0040783	12/2010	Uemichi et al.	N/A	N/A
2011/0040804	12/2010	Peirce et al.	N/A	N/A
2011/0050909	12/2010	Ellenby et al.	N/A	N/A
2011/0050915	12/2010	Wang et al.	N/A	N/A
2011/0064388	12/2010	Brown et al.	N/A	N/A

2011/0066743	12/2010	Hurley et al.	N/A	N/A
2011/0083101	12/2010	Sharon et al.	N/A	N/A
2011/0093780	12/2010	Dunn	N/A	N/A
2011/0102630	12/2010	Rukes	N/A	N/A
2011/0115798	12/2010	Nayar et al.	N/A	N/A
2011/0119133	12/2010	Igelman et al.	N/A	N/A
2011/0137881	12/2010	Cheng et al.	N/A	N/A
2011/0145564	12/2010	Moshir et al.	N/A	N/A
2011/0148864	12/2010	Lee et al.	N/A	N/A
2011/0159890	12/2010	Fortescue et al.	N/A	N/A
2011/0164163	12/2010	Bilbrey et al.	N/A	N/A
2011/0197194	12/2010	D'Angelo et al.	N/A	N/A
2011/0202598	12/2010	Evans et al.	N/A	N/A
2011/0202968	12/2010	Nurmi	N/A	N/A
2011/0211534	12/2010	Schmidt et al.	N/A	N/A
2011/0213845	12/2010	Logan et al.	N/A	N/A
2011/0215966	12/2010	Kim et al.	N/A	N/A
2011/0225048	12/2010	Nair	N/A	N/A
2011/0238763	12/2010	Shin et al.	N/A	N/A
2011/0239136	12/2010	Goldman et al.	N/A	N/A
2011/0255736	12/2010	Thompson et al.	N/A	N/A
2011/0273575	12/2010	Lee	N/A	N/A
2011/0282799	12/2010	Huston	N/A	N/A
2011/0283188	12/2010	Farrenkopf	N/A	N/A
2011/0314419	12/2010	Dunn et al.	N/A	N/A
2011/0320373	12/2010	Lee et al.	N/A	N/A
2012/0028659	12/2011	Whitney et al.	N/A	N/A
2012/0033718	12/2011	Kauffman et al.	N/A	N/A
2012/0036015	12/2011	Sheikh	N/A	N/A
2012/0036443	12/2011	Ohmori et al.	N/A	N/A
2012/0054797	12/2011	Skog et al.	N/A	N/A
2012/0059722	12/2011	Rao	N/A	N/A
2012/0062805	12/2011	Candelore	N/A	N/A
2012/0084731	12/2011	Filman et al.	N/A	N/A
2012/0084835	12/2011	Thomas et al.	N/A	N/A
2012/0099800	12/2011	Llano et al.	N/A	N/A
2012/0108293	12/2011	Law et al.	N/A	N/A
2012/0110096	12/2011	Smarr et al.	N/A	N/A
2012/0113106	12/2011	Choi et al.	N/A	N/A
2012/0113143	12/2011	Adhikari et al.	N/A	N/A
2012/0113272	12/2011	Hata	N/A	N/A
2012/0123830	12/2011	Svendsen et al.	N/A	N/A
2012/0123871	12/2011	Svendsen et al.	N/A	N/A
2012/0123875	12/2011	Svendsen et al.	N/A	N/A
2012/0124126	12/2011	Alcazar et al.	N/A	N/A
2012/0124176	12/2011	Curtis et al.	N/A	N/A
2012/0124458	12/2011	Cruzada	N/A	N/A
2012/0130717	12/2011	Xu et al.	N/A	N/A
2012/0131507	12/2011	Sparandara et al.	N/A	N/A
2012/0131512	12/2011	Takeuchi et al.	N/A	N/A

2012/0143760	12/2011	Abulafia et al.	N/A	N/A
2012/0150978	12/2011	Monaco	N/A	N/A
2012/0165100	12/2011	Lalancette et al.	N/A	N/A
2012/0166971	12/2011	Sachson et al.	N/A	N/A
2012/0169855	12/2011	Oh	N/A	N/A
2012/0172062	12/2011	Altman et al.	N/A	N/A
2012/0173991	12/2011	Roberts et al.	N/A	N/A
2012/0176401	12/2011	Hayward et al.	N/A	N/A
2012/0184248	12/2011	Speede	N/A	N/A
2012/0197724	12/2011	Kendall	N/A	N/A
2012/0200743	12/2011	Blanchflower et al.	N/A	N/A
2012/0209924	12/2011	Evans et al.	N/A	N/A
2012/0210244	12/2011	De Francisco et al.	N/A	N/A
2012/0212632	12/2011	Mate et al.	N/A	N/A
2012/0220264	12/2011	Kawabata	N/A	N/A
2012/0226748	12/2011	Bosworth et al.	N/A	N/A
2012/0233000	12/2011	Fisher et al.	N/A	N/A
2012/0236162	12/2011	Imamura	N/A	N/A
2012/0239761	12/2011	Linner et al.	N/A	N/A
2012/0250951	12/2011	Chen	N/A	N/A
2012/0252418	12/2011	Kandekar et al.	N/A	N/A
2012/0254325	12/2011	Majeti et al.	N/A	N/A
2012/0278387	12/2011	Garcia et al.	N/A	N/A
2012/0278692	12/2011	Shi	N/A	N/A
2012/0290637	12/2011	Perantatos et al.	N/A	N/A
2012/0299954	12/2011	Wada et al.	N/A	N/A
2012/0304052	12/2011	Tanaka et al.	N/A	N/A
2012/0304080	12/2011	Wormald et al.	N/A	N/A
2012/0307096	12/2011	Ford et al.	N/A	N/A
2012/0307112	12/2011	Kunishige et al.	N/A	N/A
2012/0319904	12/2011	Lee et al.	N/A	N/A
2012/0323933	12/2011	He et al.	N/A	N/A
2012/0324018	12/2011	Metcalf et al.	N/A	N/A
2013/0006759	12/2012	Srivastava et al.	N/A	N/A
2013/0024757	12/2012	Doll et al.	N/A	N/A
2013/0036364	12/2012	Johnson	N/A	N/A
2013/0045753	12/2012	Obermeyer et al.	N/A	N/A
2013/0050260	12/2012	Reitan	N/A	N/A
2013/0055083	12/2012	Fino	N/A	N/A
2013/0057587	12/2012	Leonard et al.	N/A	N/A
2013/0059607	12/2012	Herz et al.	N/A	N/A
2013/0060690	12/2012	Oskolkov et al.	N/A	N/A
2013/0063369	12/2012	Malhotra et al.	N/A	N/A
2013/0067027	12/2012	Song et al.	N/A	N/A
2013/0071093	12/2012	Hanks et al.	N/A	N/A
2013/0080254	12/2012	Thramann	N/A	N/A
2013/0085790	12/2012	Palmer et al.	N/A	N/A
2013/0086072	12/2012	Peng et al.	N/A	N/A
2013/0090171	12/2012	Holton et al.	N/A	N/A
2013/0095857	12/2012	Garcia et al.	N/A	N/A

2013/0103760	12/2012	Golding et al.	N/A	N/A
2013/0104053	12/2012	Thornton et al.	N/A	N/A
2013/0110885	12/2012	Brundrett, III	N/A	N/A
2013/0111514	12/2012	Slavin et al.	N/A	N/A
2013/0128059	12/2012	Kristensson	N/A	N/A
2013/0129252	12/2012	Lauper	N/A	N/A
2013/0132477	12/2012	Bosworth et al.	N/A	N/A
2013/0145286	12/2012	Feng et al.	N/A	N/A
2013/0159110	12/2012	Rajaram et al.	N/A	N/A
2013/0159919	12/2012	Leydon	N/A	N/A
2013/0169822	12/2012	Zhu et al.	N/A	N/A
2013/0173729	12/2012	Starenky et al.	N/A	N/A
2013/0182133	12/2012	Tanabe	N/A	N/A
2013/0185131	12/2012	Sinha et al.	N/A	N/A
2013/0191198	12/2012	Carlson et al.	N/A	N/A
2013/0194301	12/2012	Robbins et al.	N/A	N/A
2013/0198176	12/2012	Kim	N/A	N/A
2013/0201187	12/2012	Tong et al.	N/A	N/A
2013/0218965	12/2012	Abrol et al.	N/A	N/A
2013/0218968	12/2012	Mcevilley et al.	N/A	N/A
2013/0222323	12/2012	Mckenzie	N/A	N/A
2013/0227476	12/2012	Frey	N/A	N/A
2013/0232194	12/2012	Knapp et al.	N/A	N/A
2013/0249948	12/2012	Reitan	N/A	N/A
2013/0257877	12/2012	Davis	N/A	N/A
2013/0263031	12/2012	Oshiro et al.	N/A	N/A
2013/0265450	12/2012	Barnes, Jr.	N/A	N/A
2013/0267253	12/2012	Case et al.	N/A	N/A
2013/0275505	12/2012	Gauglitz et al.	N/A	N/A
2013/0290443	12/2012	Collins et al.	N/A	N/A
2013/0304646	12/2012	De Geer	N/A	N/A
2013/0311255	12/2012	Cummins et al.	N/A	N/A
2013/0325964	12/2012	Berberat	N/A	N/A
2013/0344896	12/2012	Kirmse et al.	N/A	N/A
2013/0346869	12/2012	Asver et al.	N/A	N/A
2013/0346877	12/2012	Borovoy et al.	N/A	N/A
2014/0006129	12/2013	Heath	N/A	N/A
2014/0011538	12/2013	Mulcahy et al.	N/A	N/A
2014/0019264	12/2013	Wachman et al.	N/A	N/A
2014/0032682	12/2013	Prado et al.	N/A	N/A
2014/0043204	12/2013	Basnayake et al.	N/A	N/A
2014/0043329	12/2013	Wang et al.	N/A	N/A
2014/0045530	12/2013	Gordon et al.	N/A	N/A
2014/0047016	12/2013	Rao	N/A	N/A
2014/0047045	12/2013	Baldwin et al.	N/A	N/A
2014/0047335	12/2013	Lewis et al.	N/A	N/A
2014/0049652	12/2013	Moon et al.	N/A	N/A
2014/0052485	12/2013	Shidfar	N/A	N/A
2014/0052633	12/2013	Gandhi	N/A	N/A
2014/0055554	12/2013	Du et al.	N/A	N/A

2014/0057660	12/2013	Wager	N/A	N/A
2014/0082651	12/2013	Sharifi	N/A	N/A
2014/0092130	12/2013	Anderson et al.	N/A	N/A
2014/0096029	12/2013	Schultz	N/A	N/A
2014/0114565	12/2013	Aziz et al.	N/A	N/A
2014/0122658	12/2013	Haeger et al.	N/A	N/A
2014/0122787	12/2013	Shalvi et al.	N/A	N/A
2014/0125678	12/2013	Wang et al.	N/A	N/A
2014/0129343	12/2013	Finster et al.	N/A	N/A
2014/0129953	12/2013	Spiegel	N/A	N/A
2014/0143143	12/2013	Fasoli et al.	N/A	N/A
2014/0149519	12/2013	Redfern et al.	N/A	N/A
2014/0155102	12/2013	Cooper et al.	N/A	N/A
2014/0173424	12/2013	Hogeg et al.	N/A	N/A
2014/0173457	12/2013	Wang et al.	N/A	N/A
2014/0189592	12/2013	Benchenaar et al.	N/A	N/A
2014/0207679	12/2013	Cho	N/A	N/A
2014/0214471	12/2013	Schreiner, III	N/A	N/A
2014/0222564	12/2013	Kranendonk et al.	N/A	N/A
2014/0258405	12/2013	Perkin	N/A	N/A
2014/0265359	12/2013	Cheng et al.	N/A	N/A
2014/0266703	12/2013	Dalley, Jr. et al.	N/A	N/A
2014/0279061	12/2013	Elimeliah et al.	N/A	N/A
2014/0279436	12/2013	Dorsey et al.	N/A	N/A
2014/0279540	12/2013	Jackson	N/A	N/A
2014/0280537	12/2013	Pridmore et al.	N/A	N/A
2014/0282096	12/2013	Rubinstein et al.	N/A	N/A
2014/0287779	12/2013	O'keefe et al.	N/A	N/A
2014/0289833	12/2013	Briceno	N/A	N/A
2014/0306986	12/2013	Gottesman et al.	N/A	N/A
2014/0317302	12/2013	Naik	N/A	N/A
2014/0324627	12/2013	Haver et al.	N/A	N/A
2014/0324629	12/2013	Jacobs	N/A	N/A
2014/0325383	12/2013	Brown et al.	N/A	N/A
2015/0020086	12/2014	Chen et al.	N/A	N/A
2015/0046278	12/2014	Pei et al.	N/A	N/A
2015/0071619	12/2014	Brough	N/A	N/A
2015/0087263	12/2014	Branscomb et al.	N/A	N/A
2015/0088622	12/2014	Ganschow et al.	N/A	N/A
2015/0095020	12/2014	Leydon	N/A	N/A
2015/0096042	12/2014	Mizrachi	N/A	N/A
2015/0116529	12/2014	Wu et al.	N/A	N/A
2015/0169827	12/2014	Laborde	N/A	N/A
2015/0172534	12/2014	Miyakawaa et al.	N/A	N/A
2015/0178260	12/2014	Brunson	N/A	N/A
2015/0206349	12/2014	Rosenthal et al.	N/A	N/A
2015/0222814	12/2014	Li et al.	N/A	N/A
2015/0261917	12/2014	Smith	N/A	N/A
2015/0312184	12/2014	Langholz et al.	N/A	N/A
2015/0350136	12/2014	Flynn, III et al.	N/A	N/A

2015/0365795	12/2014	Allen et al.	N/A	N/A
2015/0378502	12/2014	Hu et al.	N/A	N/A
2016/0006927	12/2015	Sehn	N/A	N/A
2016/0014063	12/2015	Hogeg et al.	N/A	N/A
2016/0085773	12/2015	Chang et al.	N/A	N/A
2016/0085863	12/2015	Allen et al.	N/A	N/A
2016/0099901	12/2015	Allen et al.	N/A	N/A
2016/0134840	12/2015	Mcculloch	N/A	N/A
2016/0180887	12/2015	Sehn	N/A	N/A
2016/0182422	12/2015	Sehn et al.	N/A	N/A
2016/0182875	12/2015	Sehn	N/A	N/A
2016/0234149	12/2015	Tsuda et al.	N/A	N/A
2016/0239248	12/2015	Sehn	N/A	N/A
2016/0277419	12/2015	Allen et al.	N/A	N/A
2016/0321708	12/2015	Sehn	N/A	N/A
2017/0006094	12/2016	Abou Mahmoud et al.	N/A	N/A
2017/0061308	12/2016	Chen et al.	N/A	N/A
2017/0080346	12/2016	Abbas	N/A	N/A
2017/0087473	12/2016	Siegel et al.	N/A	N/A
2017/0113140	12/2016	Blackstock et al.	N/A	N/A
2017/0118145	12/2016	Aittoniemi et al.	N/A	N/A
2017/0199855	12/2016	Fishbeck	N/A	N/A
2017/0235848	12/2016	Van Deusen et al.	N/A	N/A
2017/0287006	12/2016	Azmoodeh et al.	N/A	N/A
2017/0310934	12/2016	Du et al.	N/A	N/A
2017/0312634	12/2016	Ledoux et al.	N/A	N/A
2018/0047200	12/2017	O'hara et al.	N/A	N/A
2018/0113587	12/2017	Allen et al.	N/A	N/A
2018/0115503	12/2017	Baldwin et al.	N/A	N/A
2018/0198743	12/2017	Blackstock et al.	N/A	N/A
2018/0315076	12/2017	Andreou	N/A	N/A
2018/0315133	12/2017	Brody et al.	N/A	N/A
2018/0315134	12/2017	Amitay et al.	N/A	N/A
2019/0001223	12/2018	Blackstock et al.	N/A	N/A
2019/0030436	12/2018	Miyamoto	N/A	A63F 13/67
2019/0057616	12/2018	Cohen et al.	N/A	N/A
2019/0097958	12/2018	Collet et al.	N/A	N/A
2019/0114061	12/2018	Daniels	N/A	G06F 3/048
2019/0179405	12/2018	Sun	N/A	G06F 1/1686
2019/0188920	12/2018	Mcphee et al.	N/A	N/A
2019/0280997	12/2018	Baldwin et al.	N/A	N/A
2020/0306637	12/2019	Baldwin et al.	N/A	N/A
2020/0309037	12/2019	Bortoli	N/A	F02K 3/06
2020/0314046	12/2019	Jung	N/A	N/A
2020/0314586	12/2019	Bouba et al.	N/A	N/A
2020/0372127	12/2019	Denton et al.	N/A	N/A

2020/0382912	12/2019	Dancie et al.	N/A	N/A
2020/0401225	12/2019	Jaureguiberry et al.	N/A	N/A
2020/0410575	12/2019	Grantham et al.	N/A	N/A
2021/0011612	12/2020	Dancie et al.	N/A	N/A
2021/0074047	12/2020	Sheth et al.	N/A	N/A
2021/0089179	12/2020	Grantham et al.	N/A	N/A
2021/0104087	12/2020	Smith et al.	N/A	N/A
2021/0152979	12/2020	Berardino et al.	N/A	N/A
2021/0168108	12/2020	Antmen et al.	N/A	N/A
2021/0170270	12/2020	Brody et al.	N/A	N/A
2021/0192823	12/2020	Amitay et al.	N/A	N/A
2021/0209825	12/2020	Assouline et al.	N/A	N/A
2021/0225058	12/2020	Chand et al.	N/A	N/A
2021/0240315	12/2020	Alvi et al.	N/A	N/A
2021/0243482	12/2020	Baril et al.	N/A	N/A
2021/0243503	12/2020	Kotsopoulos et al.	N/A	N/A
2021/0266277	12/2020	Allen et al.	N/A	N/A
2021/0266704	12/2020	Dancie et al.	N/A	N/A
2021/0281897	12/2020	Brody et al.	N/A	N/A
2021/0285774	12/2020	Collins et al.	N/A	N/A
2021/0306290	12/2020	Voss	N/A	N/A
2021/0306451	12/2020	Heikkinen et al.	N/A	N/A
2021/0377693	12/2020	Bouba et al.	N/A	N/A
2021/0385180	12/2020	Al Majid	N/A	G06F 40/169
2021/0405831	12/2020	Mourkogiannis et al.	N/A	N/A
2021/0409535	12/2020	Mourkogiannis et al.	N/A	N/A
2021/0409610	12/2020	Mandia	N/A	H04N 5/272
2021/0409904	12/2020	Baylin et al.	N/A	N/A
2022/0012929	12/2021	Blackstock et al.	N/A	N/A
2022/0084295	12/2021	Smith et al.	N/A	N/A
2022/0103969	12/2021	Drummond	N/A	H04L 67/125
2022/0130119	12/2021	Charlton	N/A	H04L 51/046
2022/0174455	12/2021	Guillaume	N/A	N/A
2022/0269345	12/2021	Jaureguiberry et al.	N/A	N/A
2022/0309037	12/2021	Gutierrez et al.	N/A	N/A
2023/0410440	12/2022	Boroujerdi et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2887596	12/2014	CA	N/A
109863532	12/2018	CN	N/A
110168478	12/2018	CN	N/A
2051480	12/2008	EP	N/A
2151797	12/2009	EP	N/A
2184092	12/2009	EP	N/A

2399928	12/2003	GB	N/A
2001230801	12/2000	JP	N/A
5497931	12/2013	JP	N/A
19990073076	12/1998	KR	N/A
20010078417	12/2000	KR	N/A
101445263	12/2013	KR	N/A
WO-1996024213	12/1995	WO	N/A
WO-1999063453	12/1998	WO	N/A
WO-2000058882	12/1999	WO	N/A
WO-2001029642	12/2000	WO	N/A
WO-2001050703	12/2000	WO	N/A
WO-2003094072	12/2002	WO	N/A
WO-2004095308	12/2003	WO	N/A
WO-2006107182	12/2005	WO	N/A
WO-2006118755	12/2005	WO	N/A
WO-2007092668	12/2006	WO	N/A
WO-2007134402	12/2006	WO	N/A
WO-2009043020	12/2008	WO	N/A
WO-2011040821	12/2010	WO	N/A
WO-2011119407	12/2010	WO	N/A
WO-2012139276	12/2011	WO	N/A
WO-2013008238	12/2012	WO	N/A
WO-2013027893	12/2012	WO	N/A
WO-2013045753	12/2012	WO	N/A
WO-2013152454	12/2012	WO	N/A
WO-2013166588	12/2012	WO	N/A
WO-2014006129	12/2013	WO	N/A
WO-2014031899	12/2013	WO	N/A
WO-2014068573	12/2013	WO	N/A
WO-2014115136	12/2013	WO	N/A
WO-2014194262	12/2013	WO	N/A
WO-2014194439	12/2013	WO	N/A
WO-2015192026	12/2014	WO	N/A
WO-2016044424	12/2015	WO	N/A
WO-2016054562	12/2015	WO	N/A
WO-2016065131	12/2015	WO	N/A
WO-2016090605	12/2015	WO	N/A
WO-2016100318	12/2015	WO	N/A
WO-2016100318	12/2015	WO	N/A
WO-2016100342	12/2015	WO	N/A
WO-2016149594	12/2015	WO	N/A
WO-2016179166	12/2015	WO	N/A
WO-2018081013	12/2017	WO	N/A
WO-2018102562	12/2017	WO	N/A
WO-2018129531	12/2017	WO	N/A
WO-2019089613	12/2018	WO	N/A
WO-2023249984	12/2022	WO	N/A

OTHER PUBLICATIONS

“A Whole New Story”, Snap, Inc., [Online] Retrieved from the Internet: <URL: <https://www.snap.com/en-US/news/>>, (2017), 13 pgs. cited by applicant

“Adding photos to your listing”, eBay, [Online] Retrieved from the Internet: <URL: <http://pages.ebay.com/help/sell/pictures.html>>, (accessed May 24, 2017), 4 pgs. cited by applicant

“U.S. Appl. No. 17/845,496, Non Final Office Action mailed Jan. 8, 2024”, 31 pgs. cited by applicant

“U.S. Appl. No. 17/845,496, Notice of Allowance mailed Feb. 15, 2024”, 8 pgs. cited by applicant

“U.S. Appl. No. 17/845,496, Response filed Feb. 1, 2024 to Non Final Office Action mailed Jan. 8, 2024”, 12 pgs. cited by applicant

“Bitmoji”, Snapchat Support, [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20190503063620/https://support.snapchat.com/en-US/a/bitmoji>>, (captured May 3, 2019), 2 pgs. cited by applicant

“Bitmoji Chrome Extension”, [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20200919024925/https://support.bimoji.com/hc/en-us/articles/360001494066>>, (Sep. 19, 2020), 5 pgs. cited by applicant

“Bitmoji Customize text”, [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20210225200456/https://support.bitmoji.com/hc/en-us/articles/360034632291-Customize-Text-on-Bitmoji-Stickers>>, (captured Feb. 25, 2021), 3 pgs. cited by applicant

“Bitmoji Family”, Snapchat Support, [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20190503063620/https://support.snapchat.com/en-US/article/bitmoji-family>>, (captured May 3, 2019), 4 pgs. cited by applicant

“BlogStomp”, StompSoftware, [Online] Retrieved from the Internet: <URL: <http://stompsoftware.com/blogstomp>>, (accessed May 24, 2017), 12 pgs. cited by applicant

“Cup Magic Starbucks Holiday Red Cups come to life with AR app”, Blast Radius, [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20160711202454/http://www.blastradius.com/work/cup-magic>>, (2016), 7 pgs. cited by applicant

“Daily App: InstaPlace (iOS/Android): Give Pictures a Sense of Place”, TechPP, [Online] Retrieved from the Internet: <URL: <http://techpp.com/2013/02/15/instaplace-app-review>>, (2013), 13 pgs. cited by applicant

“Instant Comics Starring You & Your Friends”, Bitstrips Inc, [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20150206000940/http://company.bitstrips.com/bitstrips-app.html>>, (captured Feb. 6, 2015), 3 pgs. cited by applicant

“InstaPlace Photo App Tell The Whole Story”, [Online] Retrieved from the Internet: <URL: youtu.be/uF_gFkg1hBM>, (Nov. 8, 2013), 113 pgs., 1:02 min. cited by applicant

“International Application Serial No. PCT/US2015/037251, International Search Report mailed Sep. 29, 2015”, 2 pgs. cited by applicant

“International Application Serial No. PCT/US2023/025818, International Search Report mailed Sep. 28, 2023”, 4 pgs. cited by applicant

“International Application Serial No. PCT/US2023/025818, Written Opinion mailed Sep. 28, 2023”, 4 pgs. cited by applicant

“Introducing Snapchat Stories”, [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20131026084921/https://www.youtube.com/watch?v=88Cu3yN-LIM>>, (Oct. 3, 2013), 92 pgs.; 00:47 min. cited by applicant

“Macy's Believe-o-Magic”, [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20190422101854/https://www.youtube.com/watch?v=xvzRXy3J0Z0&feature=youtu.be>>, (Nov. 7, 2011), 102 pgs.; 00:51 min. cited by applicant

“Macy's Introduces Augmented Reality Experience in Stores across Country as Part of Its 2011

Believe Campaign”, Business Wire, [Online] Retrieved from the Internet: <URL: <https://www.businesswire.com/news/home/20111102006759/en/Macys-Introduces-Augmented-Reality-Experience-Stores-Country>>, (Nov. 2, 2011), 6 pgs. cited by applicant

“Manage Your Bitmoji”, Snapchat Support, [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20190503063620/https://support.snapchat.com/en-US/a/manage-bitmoji>>, (captured May 3, 2019), 3 pgs. cited by applicant

“Starbucks Cup Magic”, [Online] Retrieved from the Internet: <URL: <https://www.youtube.com/watch?v=RWwQXi9RGOW>>, (Nov. 8, 2011), 87 pgs.; 00:47 min. cited by applicant

“Starbucks Cup Magic for Valentine's Day”, [Online] Retrieved from the Internet: <URL: <https://www.youtube.com/watch?v=8nvqOzjq10w>>, (Feb. 6, 2012), 88 pgs.; 00:45 min. cited by applicant

“Starbucks Holiday Red Cups Come to Life, Signaling the Return of the Merriest Season”, Business Wire, [Online] Retrieved from the Internet: <URL: <http://www.businesswire.com/news/home/20111115005744/en/2479513/Starbucks-Holiday-Red-Cups-Life-Signaling-Return>>, (Nov. 15, 2011), 5 pgs. cited by applicant

“Your Own Personal Emoji”, Bitstrips Inc, [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20150205232004/http://bitmoji.com/>>, (captured Feb. 5, 2015), 3 pgs. cited by applicant

Carnahan, Daniel, “Snap is Offering Personalized Video Content Through Bitmoji TV”, Business Insider, [Online] Retrieved from the Internet: <URL: <https://www.businessinsider.com/snap-offers-personalized-video-content-through-bitmoji-tv-2019-12>>, (2019), 10 pgs. cited by applicant

Carthy, Roi, “Dear All Photo Apps: Mobli Just Won Filters”, TechCrunch, [Online] Retrieved from the Internet: <URL: <https://techcrunch.com/2011/09/08/mobli-filters>>, (Sep. 8, 2011), 10 pgs. cited by applicant

Constine, Josh, “Snapchat launches Bitmoji merch and comic strips starring your avatar”, TechCrunch, [Online] Retrieved from the Internet: <URL: <https://techcrunch.com/2018/11/13/bitmoji-store/>>, (Nov. 13, 2018), 16 pgs. cited by applicant

Constine, Josh, “Snapchat Launches Bitmoji TV: Zany 4-min Cartoons of Your Avatar”, TechCrunch, [Online] Retrieved from the Internet: <URL: <https://techcrunch.com/2020/01/30/bitmoji-tv/>>, (Jan. 30, 2020), 13 pgs. cited by applicant

Janthong, Isaranu, “Instaplace ready on Android Google Play store”, Android App Review Thailand, [Online] Retrieved from the Internet: <URL: <http://www.android-free-app-review.com/2013/01/instaplace-android-google-play-store.html>>, (Jan. 23, 2013), 9 pgs. cited by applicant

Macleod, Duncan, “Macys Believe-o-Magic App”, [Online] Retrieved from the Internet: <URL: <http://theinspirationroom.com/daily/2011/macys-believe-o-magic-app>>, (Nov. 14, 2011), 10 pgs. cited by applicant

Macleod, Duncan, “Starbucks Cup Magic Lets Merry”, [Online] Retrieved from the Internet: <URL: <http://theinspirationroom.com/daily/2011/starbucks-cup-magic>>, (Nov. 12, 2011), 8 pgs. cited by applicant

Macmillan, Douglas, “Snapchat Buys Bitmoji App for More Than \$100 Million”, The Wallstreet Journal, [Online] Retrieved from the Internet: <URL: <https://www.wsj.com/articles/snapchat-buys-bitmoji-app-for-more-than-100-million-1458876017>>, (Mar. 25, 2016), 5 pgs. cited by applicant

Newton, Casey, “Your Snapchat friendships now have their own profiles—and merchandise”, The Verge, [Online] Retrieved from the Internet: <URL: <https://www.theverge.com/2018/11/13/18088772/snapchat-friendship-profiles-bitmoji-merchandise-comics>>, (Nov. 13, 2018), 5 pgs. cited by applicant

Notopoulos, Katie, “A Guide To The New Snapchat Filters And Big Fonts”, [Online] Retrieved from the Internet: <URL: <https://www.buzzfeed.com/katienotopoulos/a-guide-to-the-new-snapchat>>

filters-and-big-fonts?utm_term=.bkQ9qVZWWe#.nv58YXpkV>, (Dec. 22, 2013), 13 pgs. cited by applicant

Ong, Thuy, “Snapchat takes Bitmoji deluxe with hundreds of new customization options”, The Verge, [Online] Retrieved from the Internet on Nov. 2, 2018: <URL: <https://www.theverge.com/2018/1/30/16949402/bitmoji-deluxe-snapchat-customization>>, (Jan. 30, 2018), 2 pgs. cited by applicant

Panzarino, Matthew, “Snapchat Adds Filters, A Replay Function And For Whatever Reason, Time, Temperature And Speed Overlays”, TechCrunch, [Online] Retrieved form the Internet: <URL: <https://techcrunch.com/2013/12/20/snapchat-adds-filters-new-font-and-for-some-reason-time-temperature-and-speed-overlays/>>, (Dec. 20, 2013), 12 pgs. cited by applicant

Reign, Ashley, “How To Add My Friend's Bitmoji To My Snapchat”, Women.com, [Online] Retrieved from the Internet: <URL: <https://www.women.com/ashleyreign/lists/how-to-add-my-friends-bitmoji-to-my-snapchat>>, (Jun. 30, 2017), 7 pgs. cited by applicant

Tripathi, Rohit, “Watermark Images in PHP And Save File on Server”, [Online] Retrieved from the Internet: <URL: <http://code.rohitink.com/2012/12/28/watermark-images-in-php-and- save-file-on-server>>, (Dec. 28, 2012), 4 pgs. cited by applicant

Tumbokon, Karen, “Snapchat Update: How To Add Bitmoji To Customizable Geofilters”, International Business Times, [Online] Retrieved from the Internet : <URL: <https://www.ibtimes.com/snapchat-update-how-add-bitmoji-customizable-geofilters-2448152>>, (Nov. 18, 2016), 6 pgs. cited by applicant

Primary Examiner: Ge; Jin

Attorney, Agent or Firm: Schwegman Lundberg & Woessner, P.A.

Background/Summary

CLAIM OF PRIORITY (1) This application is a continuation of U.S. patent application Ser. No. 17/845,496, filed on Jun. 21, 2022, the benefit of priority of which is claimed hereby, and which is incorporated by reference herein in its entirety.

TECHNICAL FIELD

(1) The present disclosure relates generally to generating augmented reality (AR) experiences on messaging applications.

BACKGROUND

(2) Augmented-Reality (AR) is a modification of a virtual environment. For example, in Virtual Reality (VR), a user is completely immersed in a virtual world, whereas in AR, the user is immersed in a world where virtual objects are combined or superimposed on the real world. An AR system aims to generate and present virtual objects that interact realistically with a real-world environment and with each other. Examples of AR applications can include single or multiple player video games, instant messaging systems, and the like.

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

(1) In the drawings, which are not necessarily drawn to scale, like numerals may describe similar components in different views. To easily identify the discussion of any particular element or act, the most significant digit or digits in a reference number refer to the figure number in which that

element is first introduced. Some nonlimiting examples are illustrated in the figures of the accompanying drawings in which:

- (2) FIG. 1 is a diagrammatic representation of a networked environment in which the present disclosure may be deployed, in accordance with some examples.
- (3) FIG. 2 is a diagrammatic representation of a messaging client application, in accordance with some examples.
- (4) FIG. 3 is a diagrammatic representation of a data structure as maintained in a database, in accordance with some examples.
- (5) FIG. 4 is a diagrammatic representation of a message, in accordance with some examples.
- (6) FIG. 5 is a block diagram showing an example component integration system, according to some examples.
- (7) FIGS. 6, 7, 8A and 8B are diagrammatic representations of outputs of the component integration system, in accordance with some examples.
- (8) FIG. 9 is a flowchart illustrating example operations of the component integration system, according to some examples.
- (9) FIG. 10 is a diagrammatic representation of a machine in the form of a computer system within which a set of instructions may be executed for causing the machine to perform any one or more of the methodologies discussed herein, in accordance with some examples.
- (10) FIG. 11 is a block diagram showing a software architecture within which examples may be implemented.

DETAILED DESCRIPTION

(11) The description that follows includes systems, methods, techniques, instruction sequences, and computing machine program products that embody illustrative examples of the disclosure. In the following description, for the purposes of explanation, numerous specific details are set forth in order to provide an understanding of various examples. It will be evident, however, to those skilled in the art, that examples may be practiced without these specific details. In general, well-known instruction instances, protocols, structures, and techniques are not necessarily shown in detail.

(12) Messaging applications typically enable end users to access various AR experiences by launching an AR experience bundle or package that includes the AR content associated with the AR experiences. The AR experiences typically present AR elements that are animated or that are anchored to particular positions. This allows the users to move around in the real-world and have the AR elements remain in place or move around in a similar manner. Messaging applications also allow users to access other features or components, such as messaging functions, map applications, avatar applications, and/or web-based applications (e.g., web-based gaming applications). Each of these features or components typically functions independently of each other so that operations performed on one component usually do not reflect operations performed by another component.

(13) Because of the lack of interoperability between the various components available for use on the messaging applications, users are provided with disjoint experiences and can become frustrated having to repeat certain operations across multiple components. For example, a user may communicate with a friend on one component and may be interested in also interacting with the friend on an AR experience. To do so, the user has to re-establish a connection with the same friend on the AR experience by navigating through various pages of information and then having to wait for the friend to join the user in the AR experience. This type of interaction wastes a great deal of time and resources and causes users to lose interest in using the messaging applications and to become frustrated. Some typical systems attempt to address these issues by providing a limited amount of shared information between different components. However, the amount and type of data that can be shared between the components is predetermined and limited, which restricts developers from creating a diverse set of useful and engaging interactions, such as interactions involving AR experiences. This can reduce the interest level end users have in accessing the AR experiences, which causes missed opportunities.

(14) The disclosed techniques solve these technical issues by providing a system that enables any type of data to be shared across all or some subset of components implemented by messaging applications. To do so, the disclosed techniques, executing on a computing system, access, by a messaging application implemented on a client device, a first component of a plurality of components implemented by the messaging application. The plurality of components include an AR experience and each of the plurality of components is configured to be separately launched by the messaging application. The disclosed techniques store a first state of the first component in a data structure that is shared across the plurality of components and launch, by the messaging application, a second component of the plurality of components in response to determining that an interaction has been performed using the first component. The disclosed techniques access, by the second component, the data structure to retrieve the first state of the first component and configure a second state of the second component that has been launched based on the first state of the first component. In some cases, the interaction with the first component can directly be communicated to the second component to configure the state of the second component (e.g., with or without being passed through the shared data structure).

(15) For example, the user can interact with a web-based application (and/or mapping application) to reach a certain objective or goal or perform a task. Once that objective or goal is reached, the web-based application can launch the AR experience passing one or more parameters of the web-based application. The AR experience can be launched automatically (programmatically) in response to the objective or goal being reached and/or in response to presenting an option to the user to launch the AR experience. Once the AR experience is launched, the AR experience presents one or more AR elements related to the parameters received from the web-based gaming application. When a certain objective, goal, criterion, or level is reached in the AR experience, the AR experience automatically (programmatically) and/or in response to a specific request, resumes the web-based application and/or launches a new or different web-based application. The AR experience can provide one or more parameters of the AR experience that were generated during interaction and launch of the AR experience to the web-based application and/or the new or different web-based application. The user can continue interacting with the web-based application and/or the new or different web-based application based on the interactions the user performed with the AR experience.

(16) In some examples, the user can interact with an AR experience to reach a certain objective or goal or perform a task. Once that objective or goal is reached, the AR experience can launch a web-based application (and/or mapping application) passing one or more parameters of the AR experience. The web-based application can be launched automatically (programmatically) in response to the objective or goal being reached and/or in response to presenting an option to the user to launch the web-based application. Once the web-based application is launched, the web-based application presents a display of a user interface related to the parameters received from the AR experience. When a certain objective, goal, criterion, or level is reached in the web-based application, the web-based application automatically (programmatically) and/or in response to a specific request, resumes the AR experience. The user can continue interacting with the AR experience based on the interactions the user performed with the web-based application.

(17) In this way, the disclosed techniques provide an integrated, unified and seamless experience to a user allowing the user to dynamically interact with multiple components of the messaging application. This reduces the amount of information that needs to be re-entered and thereby reduces the overall amount of resources needed to accomplish a task.

(18) In some examples, an AR development platform is provided to an AR experience developer. The AR development platform can present a user interface to the AR experience developer that enables the AR developer to select how various different components (implemented by different platforms of the messaging application) interact with each other and share data with each other to provide a unified experience to a user. This provides a greater amount of flexibility for a developer

to create useful, interesting and engaging AR experiences without being restricted by the resource constraints of the messaging applications and/or client devices that run the AR experiences. In this way, the disclosed techniques improve the efficiency of using the electronic device and the overall experience of the user in using the electronic device.

(19) Networked Computing Environment

(20) FIG. 1 is a block diagram showing an example messaging system **100** for exchanging data (e.g., messages and associated content) over a network. The messaging system **100** includes multiple instances of a client device **102**, each of which hosts a number of applications, including a client application **104** and other external applications **109** (e.g., third-party applications). Each client application **104** is communicatively coupled to other instances of the client application **104** (e.g., hosted on respective other client devices **102**), a messaging server system **108** and external app(s) servers **110** via a network **112** (e.g., the Internet). A client application **104** can also communicate with locally-hosted third-party applications, such as external apps **109**, using Application Programming Interfaces (APIs). The client application **104** can include a messaging client, messaging application, and/or an AR developer application or an AR development client.

(21) The messaging client or client application **104** can function as an operating system (or main application) and can implement and coordinate operation across multiple components including an AR experience, a map application, an avatar application, and/or a web-based application, such as a web-based gaming application. Each of the components, from a front-end user interface of the messaging client or client application **104**, can be separately launched, such as by selecting a respective option from the front-end user interface. In some implementations, a first component can launch a second component and pass initialization parameters to the second component automatically, programmatically, in response to user input, and/or upon reaching a goal within the first component. This provides a seamless and unified user experience across multiple components to the user.

(22) To ensure user data privacy, the client device **102** (or client application **104** implemented on the client device **102**) may notify the user regarding the type of information that may be collected and prompt the user to choose whether to opt-in prior to collecting the data. The system will not collect the data if the user declines to opt-in and does not give consent. If the user opts-in, the data is stored securely in an encrypted manner on the server. To further ensure user data privacy, the client device **102** can notify a user if a given component launches or can be used to launch another component that uses a camera or microphone or other input device of the client device **102** that is not used by the given component.

(23) The client device **102** may operate as a standalone device or may be coupled (e.g., networked) to other machines. In a networked deployment, the client device **102** may operate in the capacity of a server machine or a client machine in a server-client network environment, or as a peer machine in a peer-to-peer (or distributed) network environment. The client device **102** may comprise, but not be limited to, a server computer, a client computer, a personal computer (PC), a tablet computer, a laptop computer, a netbook, a set-top box (STB), a personal digital assistant (PDA), an entertainment media system, a cellular telephone, a smartphone, a mobile device, a wearable device (e.g., a smartwatch), a smart home device (e.g., a smart appliance), other smart devices, a web appliance, a network router, a network switch, a network bridge, or any machine capable of executing the disclosed operations. Further, while only a single client device **102** is illustrated, the term “client device” shall also be taken to include a collection of machines that individually or jointly execute the disclosed operations.

(24) In some examples, the client device **102** can include AR glasses or an AR headset in which virtual content is displayed within lenses of the glasses while a user views a real-world environment through the lenses. For example, an image can be presented on a transparent display that allows a user to simultaneously view content presented on the display and real-world objects.

(25) In some examples, the client device **102** can be operated by an AR experience developer. In

such cases, the AR experience developer (or AR developer) accesses an AR experience development platform. The AR experience development platform allows the AR developer to generate an AR experience bundle that includes a set of AR elements and events or triggers of different types that are used to control launching of another component, such as a web-based application, avatar application, or map application. In some examples, the AR developer can specify conditions under which the other component(s) is/are launched. The AR experience can access a shared data structure (e.g., storage location, file or element) that is also accessible to other components implemented by the client application **104**. The shared data structure can store state information for one or more of the components and can be used to control a user interface and operation of any of the components. In this way, a specified set of operations that are performed by one component, such as an AR experience, can be used to modify operations performed by another component implemented by the same client application **104**.

(26) In some examples, the conditions used to launch one or more other components of the client application **104** that are tracked by a given component currently being accessed can include geographical locations, levels in a gaming application or AR experience, accomplishment of one or more goals, views or depictions of real-world environment portions, time, time of day, client device type, user type, user account type, location markers, image markers, or any other suitable condition. In some examples, the conditions can be manually programmed and stored as part of the AR experience bundle. In some examples, the conditions are set by the AR developer selecting between various options for setting certain conditions in association with a component.

(27) The client application **104** is able to communicate and exchange data with other client applications **104** and with the messaging server system **108** via the network **112**. The data exchanged between client applications **104**, and between a client application **104** and the messaging server system **108**, includes functions (e.g., commands to invoke functions) as well as payload data (e.g., text, audio, video or other multimedia data).

(28) The messaging server system **108** provides server-side functionality via the network **112** to a particular client application **104**. While certain functions of the messaging system **100** are described herein as being performed by either a client application **104** or by the messaging server system **108**, the location of certain functionality either within the client application **104** or the messaging server system **108** may be a design choice. For example, it may be technically preferable to initially deploy certain technology and functionality within the messaging server system **108** but to later migrate this technology and functionality to the client application **104** where a client device **102** has sufficient processing capacity.

(29) The messaging server system **108** supports various services and operations that are provided to the client application **104**. Such operations include transmitting data to, receiving data from, and processing data generated by the client application **104**. This data may include message content, client device information, geolocation information, media augmentation and overlays, message content persistence conditions, social network information, and live event information, as examples. Data exchanges within the messaging system **100** are invoked and controlled through functions available via user interfaces (UIs) of the client application **104**.

(30) Turning now specifically to the messaging server system **108**, an Application Programming Interface (API) server **116** is coupled to, and provides a programmatic interface to, application servers **114**. The application servers **114** are communicatively coupled to a database server **120**, which facilitates access to a database **126** that stores data associated with messages processed by the application servers **114**. Similarly, a web server **128** is coupled to the application servers **114**, and provides web-based interfaces to the application servers **114**. To this end, the web server **128** processes incoming network requests over the Hypertext Transfer Protocol (HTTP) and several other related protocols.

(31) The API server **116** receives and transmits message data (e.g., commands and message payloads) between the client device **102** and the application servers **114**. Specifically, the API

server **116** provides a set of interfaces (e.g., routines and protocols) that can be called or queried by the client application **104** in order to invoke functionality of the application servers **114**. The API server **116** exposes various functions supported by the application servers **114**, including account registration, login functionality, the sending of messages, via the application servers **114**, from a particular client application **104** to another client application **104**, the sending of media files (e.g., images or video) from a client application **104** to a messaging server **118**, and for possible access by another client application **104**, the settings of a collection of media data (e.g., story), the retrieval of a list of friends of a user of a client device **102**, the retrieval of such collections, the retrieval of messages and content, the addition and deletion of entities (e.g., friends) to an entity graph (e.g., a social graph), the location of friends within a social graph, and opening an application event (e.g., relating to the client application **104**). In some examples, the API provides a set of interfaces that can be called or queried to pass or share parameters/data between different components of the client application **104**.

(32) The application servers **114** host a number of server applications and subsystems, including for example a messaging server **118**, an image processing server **122**, and a social network server **124**. The messaging server **118** implements a number of message processing technologies and functions, particularly related to the aggregation and other processing of content (e.g., textual and multimedia content) included in messages received from multiple instances of the client application **104**. As will be described in further detail, the text and media content from multiple sources may be aggregated into collections of content (e.g., called stories or galleries). These collections are then made available to the client application **104**. Other processor- and memory-intensive processing of data may also be performed server-side by the messaging server **118**, in view of the hardware requirements for such processing.

(33) The application servers **114** also include an image processing server **122** that is dedicated to performing various image processing operations, typically with respect to images or video within the payload of a message sent from or received at the messaging server **118**.

(34) Image processing server **122** is used to implement scan functionality of the augmentation system **208** (shown in FIG. 2). Scan functionality includes activating and providing one or more augmented reality experiences on a client device **102** when an image is captured by the client device **102**. Specifically, the client application **104** on the client device **102** can be used to activate a camera. The camera displays one or more real-time images or a video to a user along with one or more icons or identifiers of one or more augmented reality experiences. The user can select a given one of the identifiers to launch the corresponding AR experience or perform a desired image modification (e.g., replacing a garment being worn by a user in a video or recoloring the garment worn by the user in the video or modifying the garment based on a gesture performed by the user).

(35) The social network server **124** supports various social networking functions and services and makes these functions and services available to the messaging server **118**. To this end, the social network server **124** maintains and accesses an entity graph **308** (as shown in FIG. 3) within the database **126**. Examples of functions and services supported by the social network server **124** include the identification of other users of the messaging system **100** with which a particular user has relationships or is “following,” and also the identification of other entities and interests of a particular user.

(36) Returning to the client application **104**, features and functions of an external resource (e.g., a third-party application **109** or applet) are made available to a user via an interface of the client application **104**. The client application **104** receives a user selection of an option to launch or access features of an external resource (e.g., a third-party resource), such as external apps **109**. The external resource may be a third-party application (external apps **109**) installed on the client device **102** (e.g., a “native app”), or a small-scale version of the third-party application (e.g., an “applet”) that is hosted on the client device **102** or remote of the client device **102** (e.g., on third-party servers **110**). The small-scale version of the third-party application includes a subset of features and

functions of the third-party application (e.g., the full-scale, native version of the third-party standalone application) and is implemented using a markup-language document. In one example, the small-scale version of the third-party application (e.g., an “applet”) is a web-based, markup-language version of the third-party application and is embedded in the client application **104**. In addition to using markup-language documents (e.g., a *.ml file), an applet may incorporate a scripting language (e.g., a *.js file or a .json file) and a style sheet (e.g., a *.ss file).

(37) In response to receiving a user selection of the option to launch or access features of the external resource (external app **109**), also referred to as a component, the client application **104** determines whether the selected external resource is a web-based external resource or a locally-installed external application. In some cases, external applications **109** that are locally installed on the client device **102** can be launched independently of and separately from the client application **104**, such as by selecting an icon, corresponding to the external application **109**, on a home screen of the client device **102**. Small-scale versions of such external applications (e.g., components) can be launched or accessed via the client application **104** and, in some examples, no or limited portions of the small-scale external application can be accessed outside of the client application **104**. The small-scale external application can be launched by the client application **104** receiving, from an external app(s) server **110**, a markup-language document associated with the small-scale external application and processing such a document. In some examples, the small-scale external application can be launched by another component, such as an AR experience, currently being accessed by the client application **104**.

(38) In response to determining that the external resource is a locally-installed external application **109**, the client application **104** (e.g., in response to a command received from a given component, such as an AR experience running on the client device **102**) instructs the client device **102** to launch the external application **109** by executing locally-stored code corresponding to the external application **109**. In response to determining that the external resource is a web-based resource, the client application **104** communicates with the external app(s) servers **110** to obtain a markup-language document corresponding to the selected resource. The client application **104** then processes the obtained markup-language document to present the web-based external resource within a user interface of the client application **104**.

(39) The client application **104** can notify a user of the client device **102**, or other users related to such a user (e.g., “friends”), of activity taking place in one or more external resources. For example, the client application **104** can provide participants in a conversation (e.g., a chat session) in the client application **104** with notifications relating to the current or recent use of an external resource by one or more members of a group of users. One or more users can be invited to join in an active external resource or to launch a recently-used but currently inactive (in the group of friends) external resource. The external resource can provide participants in a conversation, each using a respective client application **104**, with the ability to share an item, status, state, or location in an external resource with one or more members of a group of users into a chat session. The shared item may be an interactive chat card with which members of the chat can interact, for example, to launch the corresponding external resource, view specific information within the external resource, or take the member of the chat to a specific location or state within the external resource. Within a given external resource, response messages can be sent to users on the client application **104**. The external resource can selectively include different media items in the responses, based on a current context of the external resource.

(40) The client application **104** can present a list of the available external resources (e.g., components, third-party or external applications **109** or applets) to a user to launch or access a given external resource. This list can be presented in a context-sensitive menu. For example, the icons representing different ones of the external application **109** (or applets) can vary based on how the menu is launched by the user (e.g., from a conversation interface or from a non-conversation interface).

(41) The client application **104** can allow users to launch AR experiences with AR elements or events of different types. Specifically, the client application **104** can receive a request to access an AR experience. In response to receiving the request to access the AR experience, the client application **104** launches an AR experience bundle associated with the AR experience. As part of the AR experience bundle, the client application **104** accesses a list of event types or conditions associated with the AR experience used to launch another component, such as a map application or web-based application or resource. The list can include event types or conditions that are predefined and/or event types that are specifically configured and selected by the AR developer.

(42) The client application **104** can determine that an interaction associated with the AR experience corresponds to a first event type of the list of event types or a first condition. The client application **104**, in response to detecting the interaction, identifies one or more components associated with the first condition. The client application **104** can access current state information associated with the AR experience and launches the one or more components based on the current state information of the AR experience. The one or more components can be launched programmatically, automatically (without user input), or in response to presenting a prompt with a call to action option for the user to select to launch the one or more components. This allows the AR experience developer to enhance or improve certain features of the AR experience and unify such an experience across other components of the client application **104** (used to implement the AR experience) which improves the overall experience of end users.

(43) In some examples, the client application **104** can present an AR developer interface. In such cases, the client application **104** can be operated by an AR developer to develop and create one or more AR experiences, as discussed below.

(44) System Architecture

(45) FIG. 2 is a block diagram illustrating further details regarding the messaging system **100**, according to some examples. Specifically, the messaging system **100** is shown to comprise the client application **104** and the application servers **114**. The messaging system **100** embodies a number of subsystems (also referred to as components), which are supported on the client side by the client application **104** and on the sever side by the application servers **114**. These subsystems (or components) include, for example, an ephemeral timer system **202**, a collection management system **204**, an augmentation system **208**, a map system **210**, a game system **212**, and an external resource system **220** (also referred to as a web-based application system).

(46) The ephemeral timer system **202** is responsible for enforcing the temporary or time-limited access to content by the client application **104** and the messaging server **118**. The ephemeral timer system **202** incorporates a number of timers that, based on duration and display parameters associated with a message, or collection of messages (e.g., a story), selectively enable access (e.g., for presentation and display) to messages and associated content via the client application **104**. Further details regarding the operation of the ephemeral timer system **202** are provided below.

(47) The collection management system **204** is responsible for managing sets or collections of media (e.g., collections of text, image video, and audio data). A collection of content (e.g., messages, including images, video, text, and audio) may be organized into an “event gallery” or an “event story.” Such a collection may be made available for a specified time period, such as the duration of an event to which the content relates. For example, content relating to a music concert may be made available as a “story” for the duration of that music concert. The collection management system **204** may also be responsible for publishing an icon that provides notification of the existence of a particular collection to the user interface of the client application **104**.

(48) The collection management system **204** further includes a curation interface **206** that allows a collection manager to manage and curate a particular collection of content. For example, the curation interface **206** enables an event organizer to curate a collection of content relating to a specific event (e.g., delete inappropriate content or redundant messages). Additionally, the collection management system **204** employs machine vision (or image recognition technology) and

content rules to automatically curate a content collection. In certain examples, compensation may be paid to a user for the inclusion of user-generated content into a collection. In such cases, the collection management system **204** operates to automatically make payments to such users for the use of their content.

(49) The augmentation system **208** provides various functions that enable a user to augment (e.g., annotate or otherwise modify or edit) media content associated with a message. For example, the augmentation system **208** provides functions related to the generation and publishing of media overlays for messages processed by the messaging system **100**. The augmentation system **208** operatively supplies a media overlay or augmentation (e.g., an image filter) to the client application **104** based on a geolocation of the client device **102**. In another example, the augmentation system **208** operatively supplies a media overlay to the client application **104** based on other information, such as social network information of the user of the client device **102**. A media overlay may include audio and visual content and visual effects. Examples of audio and visual content include pictures, texts, logos, animations, and sound effects. An example of a visual effect includes color overlaying. The audio and visual content or the visual effects can be applied to a media content item (e.g., a photo) at the client device **102**. For example, the media overlay may include text, a graphical element, or image that can be overlaid on top of a photograph taken by the client device **102**. In another example, the media overlay includes an identification of a location overlay (e.g., Venice beach), a name of a live event, or a name of a merchant overlay (e.g., Beach Coffee House). In another example, the augmentation system **208** uses the geolocation of the client device **102** to identify a media overlay that includes the name of a merchant at the geolocation of the client device **102**. The media overlay may include other indicia associated with the merchant. The media overlays may be stored in the database **126** and accessed through the database server **120**.

(50) In some examples, the augmentation system **208** provides a user-based publication platform that enables users to select a geolocation on a map and upload content associated with the selected geolocation. The user may also specify circumstances under which a particular media overlay should be offered to other users. The augmentation system **208** generates a media overlay that includes the uploaded content and associates the uploaded content with the selected geolocation.

(51) In other examples, the augmentation system **208** provides a merchant-based publication platform that enables merchants to select a particular media overlay associated with a geolocation via a bidding process. For example, the augmentation system **208** associates the media overlay of the highest bidding merchant with a corresponding geolocation for a predefined amount of time. The augmentation system **208** communicates with the image processing server **122** to obtain augmented reality experiences and presents identifiers of such experiences in one or more user interfaces (e.g., as icons over a real-time image or video or as thumbnails or icons in interfaces dedicated for presented identifiers of augmented reality experiences). Once an augmented reality experience is selected, one or more images, videos, or augmented reality graphical elements are retrieved and presented as an overlay on top of the images or video captured by the client device **102**. In some cases, the camera is switched to a front-facing view (e.g., the front-facing camera of the client device **102** is activated in response to activation of a particular augmented reality experience) and the images from the front-facing camera of the client device **102** start being displayed on the client device **102** instead of the rear-facing camera of the client device **102**. The one or more images, videos, or augmented reality graphical elements are retrieved and presented as an overlay on top of the images that are captured and displayed by the front-facing camera of the client device **102**.

(52) In other examples, the augmentation system **208** is able to communicate and exchange data with another augmentation system **208** on another client device **102** and with the server via the network **112**. The data exchanged can include a session identifier that identifies the shared AR session, a transformation between a first client device **102** and a second client device **102** (e.g., a plurality of client devices **102** include the first and second devices) that is used to align the shared

AR session to a common point of origin, a common coordinate frame, functions (e.g., commands to invoke functions) as well as other payload data (e.g., text, audio, video or other multimedia data), such as during a video call between a plurality of users or participants.

(53) The augmentation system **208** sends the transformation to the second client device **102** so that the second client device **102** can adjust the AR coordinate system based on the transformation. In this way, the first and second client devices **102** synch up their coordinate systems and frames for displaying content in the AR session. Specifically, the augmentation system **208** computes the point of origin of the second client device **102** in the coordinate system of the first client device **102**. The augmentation system **208** can then determine an offset in the coordinate system of the second client device **102** based on the position of the point of origin from the perspective of the second client device **102** in the coordinate system of the second client device **102**. This offset is used to generate the transformation so that the second client device **102** generates AR content according to a common coordinate system or frame as the first client device **102**.

(54) The augmentation system **208** can communicate with the client device **102** to establish individual or shared AR sessions. The augmentation system **208** can also be coupled to the messaging server **118** to establish an electronic group communication session (e.g., group chat, instant messaging, video call, group video call, and so forth) for the client devices **102** in a shared AR session. The electronic group communication session can be associated with a session identifier provided by the client devices **102** to gain access to the electronic group communication session and to the shared AR session. In one example, the client devices **102** first gain access to the electronic group communication session and then obtain the session identifier in the electronic group communication session that allows the client devices **102** to access the shared AR session. In some examples, the client devices **102** are able to access the shared AR session without aid or communication with the augmentation system **208** in the application servers **114**.

(55) The map system **210** provides various geographic location functions, and supports the presentation of map-based media content and messages by the client application **104**. For example, the map system **210** enables the display of user icons or avatars (e.g., stored in profile data **316**, shown in FIG. 3) on a map to indicate a current or past location of “friends” of a user, as well as media content (e.g., collections of messages including photographs and videos) generated by such friends, within the context of a map. For example, a message posted by a user to the messaging system **100** from a specific geographic location may be displayed within the context of a map at that particular location to “friends” of a specific user on a map interface of the client application **104**. A user can furthermore share his or her location and status information (e.g., using an appropriate status avatar) with other users of the messaging system **100** via the client application **104**, with this location and status information being similarly displayed within the context of a map interface of the client application **104** to selected users.

(56) The game system **212** provides various gaming functions within the context of the client application **104**. The client application **104** provides a game interface providing a list of available games (e.g., web-based games or web-based applications) that can be launched by a user within the context of the client application **104**, and played with other users of the messaging system **100**. The messaging system **100** further enables a particular user to invite other users to participate in the play of a specific game, by issuing invitations to such other users from the client application **104**. The client application **104** also supports both voice and text messaging (e.g., chats) within the context of gameplay, provides a leaderboard for the games, and also supports the provision of in-game rewards (e.g., coins and items).

(57) The external resource system **220** provides an interface for the client application **104** to communicate with external app(s) servers **110** to launch or access external resources. Each external resource (apps) server **110** hosts, for example, a markup language (e.g., HTML5) based application or small-scale version of an external application (e.g., game, utility, payment, or ride-sharing application that is external to the client application **104**). The client application **104** may launch a

web-based resource (e.g., application) by accessing the HTML5 file from the external resource (apps) servers **110** associated with the web-based resource. In certain examples, applications hosted by external resource servers **110** are programmed in JavaScript leveraging a Software Development Kit (SDK) provided by the messaging server **118**. The SDK includes Application Programming Interfaces (APIs) with functions that can be called or invoked by the web-based application. In certain examples, the messaging server **118** includes a JavaScript library that provides a given third-party resource access to certain user data of the client application **104**. HTML5 is used as an example technology for programming games, but applications and resources programmed based on other technologies can be used.

(58) In order to integrate the functions of the SDK into the web-based resource, the SDK is downloaded by an external resource (apps) server **110** from the messaging server **118** or is otherwise received by the external resource (apps) server **110**. Once downloaded or received, the SDK is included as part of the application code of a web-based external resource. The code of the web-based resource can then call or invoke certain functions of the SDK to integrate features of the client application **104** into the web-based resource.

(59) The SDK stored on the messaging server **118** effectively provides the bridge between an external resource (e.g., third-party or external applications **109** or applets and the client application **104**). This provides the user with a seamless experience of communicating with other users on the client application **104**, while also preserving the look and feel of the client application **104**. To bridge communications between an external resource and a client application **104**, in certain examples, the SDK facilitates communication between external resource servers **110** and the client application **104**. In certain examples, a WebViewJavaScriptBridge running on a client device **102** establishes two one-way communication channels between an external resource and the client application **104**. Messages are sent between the external resource and the client application **104** via these communication channels asynchronously. Each SDK function invocation is sent as a message and callback. Each SDK function is implemented by constructing a unique callback identifier and sending a message with that callback identifier.

(60) By using the SDK, not all information from the client application **104** is shared with external resource servers **110**. The SDK limits which information is shared based on the needs of the external resource. In certain examples, each external resource server **110** provides an HTML5 file corresponding to the web-based external resource to the messaging server **118**. The messaging server **118** can add a visual representation (such as a box art or other graphic) of the web-based external resource in the client application **104**. Once the user selects the visual representation or instructs the client application **104** through a GUI of the client application **104** to access features of the web-based external resource, the client application **104** obtains the HTML5 file and instantiates the resources necessary to access the features of the web-based external resource.

(61) The client application **104** presents a graphical user interface (e.g., a landing page or title screen) for an external resource. During, before, or after presenting the landing page or title screen, the client application **104** determines whether the launched external resource has been previously authorized to access user data of the client application **104**. In response to determining that the launched external resource has been previously authorized to access user data of the client application **104**, the client application **104** presents another graphical user interface of the external resource that includes functions and features of the external resource. In response to determining that the launched external resource has not been previously authorized to access user data of the client application **104**, after a threshold period of time (e.g., 3 seconds) of displaying the landing page or title screen of the external resource, the client application **104** slides up (e.g., animates a menu as surfacing from a bottom of the screen to a middle or other portion of the screen) a menu for authorizing the external resource to access the user data. The menu identifies the type of user data that the external resource will be authorized to use. In response to receiving a user selection of an accept option, the client application **104** adds the external resource to a list of authorized

external resources and allows the external resource to access user data from the client application **104**. In some examples, the external resource is authorized by the client application **104** to access the user data in accordance with an OAuth 2 framework.

(62) The client application **104** controls the type of user data that is shared with external resources and between components implemented by the client application **104** based on the type of external resource or component being authorized. For example, external resources that include full-scale external applications (e.g., a third-party or external application **109**) are provided with access to a first type of user data (e.g., only two-dimensional avatars of users with or without different avatar characteristics). As another example, external resources that include small-scale versions of external applications (e.g., web-based versions of third-party applications) are provided with access to a second type of user data (e.g., payment information, two-dimensional avatars of users, three-dimensional avatars of users, and avatars with various avatar characteristics). Avatar characteristics include different ways to customize a look and feel of an avatar, such as different poses, facial features, clothing, and so forth.

(63) The component integration system **224** can access, by a messaging application implemented on a client device **102**, a first component of a plurality of components implemented by the messaging application. The plurality of components can include an AR experience and each of the plurality of components can be configured to be separately launched by the messaging application. The component integration system **224** stores a first state of the first component in a data structure that is shared across the plurality of components, such as in one of the data structures **300** (FIG. 3). The component integration system **224** launches, by the messaging application, a second component of the plurality of components in response to determining that an interaction has been performed using the first component. The component integration system **224** accesses, by the second component, the data structure to retrieve the first state of the first component and configures a second state of the second component that has been launched based on the first state of the first component. An integration between the plurality of components including at least the AR experience can be developed using an AR developer platform.

(64) In some examples, the first component includes the AR experience and the second component includes at least one of a web-based application, a map application, or an avatar application. In some examples, the second component includes the AR experience and the first component includes at least one of a web-based application, a map application, or an avatar application.

(65) The component integration system **224** can determine that the interaction has been performed using the first component by determining that input has been received from a user corresponding to a specified gesture. In such cases, the component integration system **224** executes, by the first component, a call to action operation associated with the second component to launch the second component. The component integration system **224**, in response to determining that the input has been received corresponding to the specified gesture, displays by the first component a prompt with an option to execute the call to action operation. The component integration system **224** receives a second input that selects the option to execute the call to action operation.

(66) The component integration system **224** can determine that the interaction has been performed using the first component by determining that a goal has been reached during use of the first component. In such cases, the component integration system **224**, in response to determining that the goal has been reached, automatically executes, by the first component, a call to action operation associated with the second component to launch the second component.

(67) In some examples, the component integration system **224** replaces a display of the first component with a display of the second component in response to launching the second component. In such cases, the component integration system **224** detects a specified interaction performed using the second component and updates the data structure to represent a current state of the second component. The component integration system **224** re-accesses the first component based on the updated data structure in response to detecting the specified interaction performed

using the second component. The display of the second component can be replaced with the display of the first component after the first component is re-accessed.

(68) In some examples, the component integration system **224** detects a specified interaction performed using the second component and updates the data structure to represent a current state of the second component. In such cases, the component integration system **224** launches, by the second component, a third component of the plurality of components based on the updated data structure in response to detecting the specified interaction performed using the second component. The display of the second component can be replaced with a display of the third component after the third component is launched.

(69) In some examples, the first component includes the AR experience and the second component includes a web-based application. The state of the first component can include a payload of parameters of the AR experience which is used to adjust one or more parameters of the second component to provide a unified multi-component experience to a user.

(70) In some examples, the component integration system **224** generates for display a first user interface associated with the AR experience in response to receiving a user selection of an option to separately launch the second component comprising the AR experience. The component integration system **224** generates for display a second user interface associated with the AR experience in response to launching the second component in response to the interaction performed using the first component. One or more options available in the first user interface can be disabled in the second user interface.

(71) In some examples, the first component includes the AR experience and the second component comprises a map application. In such cases, the component integration system **224** applies, by the first component, one or more AR elements to a real-world object depicted in an image captured by a camera of the client device **102**, the real-world object being associated with real-world location. The component integration system **224** stores data representing the one or more AR elements and the real-world location as the first state in the data structure and navigates a map displayed by the map application to a region including the real-world location. The component integration system **224** modifies a portion of the region of the map corresponding to the real-world object to include the one or more AR elements. The client device **102** can include a first client device **102** associated with a first user, wherein the first component includes the AR experience being accessed by the first client device **102** and the map application being accessed by a second client device **102** to display the modified portion of the region of the map on the second client device associated with a second user. In this way, operations performed by the first client device **102** with respect to an AR experience can be reflected by another component, such as a map application (that is distinct from the AR experience), that is accessed by another user on the second client device **102**.

(72) In some examples, the first component includes a web-based application and the second component includes the AR experience. In such cases, the component integration system **224** navigates an avatar in the web-based application to a virtual location and determines a condition indicating that the virtual location is associated with the AR experience including activation of a front-facing camera of the client device. The component integration system **224**, in response to navigating the avatar in the web-based application to the virtual location, adds one or more AR elements of the AR experience to a real-time video feed captured by the front-facing camera of the client device **102**. The component integration system **224** presents the real-time video feed that includes the one or more AR elements within a display of the web-based application.

(73) In some examples, the first component includes a web-based application and the second component includes the AR experience. In such cases, the component integration system **224** receives input by the web-based application comprising selection of a virtual item and determines that the selection of the virtual item is associated with the AR experience including activation of a rear-facing camera of the client device. The component integration system **224**, in response to receiving the input by the web-based application comprising selection of the virtual item, adds one

or more AR elements of the AR experience representing the virtual item to a real-time video feed captured by the rear-facing camera of the client device. The component integration system **224** presents the real-time video feed that includes the one or more AR elements representing the virtual item of the web-based application.

(74) In some examples, the first component includes the AR experience and the second component includes a web-based application. In such cases, component integration system **224** performs a series of operations including: presenting, by the AR experience, a first AR element comprising a virtual device; in response to receiving input by the AR experience to unlock the virtual device, causing the web-based application to present a keypad; receiving, by the web-based application, a request for a passcode hint; in response to receiving the request for the passcode hint, causing the AR experience to present one or more AR elements representing the passcode hint over a real-time video feed captured by a camera of the client device; receiving, by the web-based application, interaction with the keypad comprising a correct passcode associated with the passcode hint represented by the one or more AR elements; and enabling, by the web-based application, a user to interact with the virtual device in response to receiving the interaction with the keypad.

(75) The component integration system **224** can also perform one or more interactions with the AR experience after access to the virtual device has been enabled and determines, by the AR experience, that the one or more interactions correspond to a goal. In such cases, the component integration system **224**, in response to determining that the one or more interactions correspond to the goal, can unlock access, by the web-based application, to other features of the virtual device.

(76) This functionality provides a greater amount of flexibility for a developer to create useful, interesting, unified, and engaging AR experiences across different components without being restricted by the resource constraints of the messaging applications and/or client devices that run the AR experiences.

(77) Data Architecture

(78) FIG. **3** is a schematic diagram illustrating data structures **300**, which may be stored in the database **126** of the messaging server system **108**, according to certain examples. While the content of the database **126** is shown to comprise a number of tables, it will be appreciated that the data could be stored in other types of data structures (e.g., as an object-oriented database).

(79) The database **126** includes message data stored within a message table **302**. This message data includes, for any particular one message, at least message sender data, message recipient (or receiver) data, and a payload. Further details regarding information that may be included in a message, and included within the message data stored in the message table **302**, are described below with reference to FIG. **4**.

(80) An entity table **306** stores entity data, and is linked (e.g., referentially) to an entity graph **308** and profile data **316**. Entities for which records are maintained within the entity table **306** may include individuals, corporate entities, organizations, objects, places, events, and so forth. Regardless of entity type, any entity regarding which the messaging server system **108** stores data may be a recognized entity. Each entity is provided with a unique identifier, as well as an entity type identifier (not shown).

(81) The entity graph **308** stores information regarding relationships and associations between entities. Such relationships may be social, professional (e.g., work at a common corporation or organization) interested-based or activity-based, merely for example.

(82) The profile data **316** stores multiple types of profile data about a particular entity. The profile data **316** may be selectively used and presented to other users of the messaging system **100**, based on privacy settings specified by a particular entity. Where the entity is an individual, the profile data **316** includes, for example, a username, telephone number, address, settings (e.g., notification and privacy settings), as well as a user-selected avatar representation (or collection of such avatar representations). A particular user may then selectively include one or more of these avatar representations within the content of messages communicated via the messaging system **100**, and

on map interfaces displayed by client applications **104** to other users. The collection of avatar representations may include “status avatars,” which present a graphical representation of a status or activity that the user may select to communicate at a particular time.

(83) Where the entity is a group, the profile data **316** for the group may similarly include one or more avatar representations associated with the group, in addition to the group name, members, and various settings (e.g., notifications) for the relevant group.

(84) The database **126** also stores augmentation data, such as overlays or filters, in an augmentation table **310**. The augmentation data is associated with and applied to videos (for which data is stored in a video table **304**) and images (for which data is stored in an image table **312**).

(85) The database **126** can also store data pertaining to individual and shared AR sessions. This data can include data communicated between an AR session client controller of a first client device **102** and another AR session client controller of a second client device **102**, and data communicated between the AR session client controller and the augmentation system **208**. Data can include data used to establish the common coordinate frame of the shared AR scene, the transformation between the devices, the session identifier, images depicting a body, skeletal joint positions, wrist joint positions, feet, and so forth.

(86) Filters, in one example, are overlays that are displayed as overlaid on an image or video during presentation to a recipient user. Filters may be of various types, including user-selected filters from a set of filters presented to a sending user by the client application **104** when the sending user is composing a message. Other types of filters include geolocation filters (also known as geo-filters), which may be presented to a sending user based on geographic location. For example, geolocation filters specific to a neighborhood or special location may be presented within a user interface by the client application **104**, based on geolocation information determined by a Global Positioning System (GPS) unit of the client device **102**.

(87) Another type of filter is a data filter, which may be selectively presented to a sending user by the client application **104**, based on other inputs or information gathered by the client device **102** during the message creation process. Examples of data filters include current temperature at a specific location, a current speed at which a sending user is traveling, battery life for a client device **102**, or the current time.

(88) Other augmentation data that may be stored within the image table **312** includes augmented reality content items (e.g., corresponding to applying augmented reality experiences). An augmented reality content item or augmented reality item may be a real-time special effect and sound that may be added to an image or a video.

(89) As described above, augmentation data includes augmented reality content items, overlays, image transformations, AR images, AR logos or emblems, and similar terms that refer to modifications that may be applied to image data (e.g., videos or images). This includes real-time modifications, which modify an image as it is captured using device sensors (e.g., one or multiple cameras) of a client device **102** and then displayed on a screen of the client device **102** with the modifications. This also includes modifications to stored content, such as video clips in a gallery that may be modified. For example, in a client device **102** with access to multiple augmented reality content items, a user can use a single video clip with multiple augmented reality content items to see how the different augmented reality content items will modify the stored clip. For example, multiple augmented reality content items that apply different pseudorandom movement models can be applied to the same content by selecting different augmented reality content items for the content. Similarly, real-time video capture may be used with an illustrated modification to show how video images currently being captured by sensors of a client device **102** would modify the captured data. Such data may simply be displayed on the screen and not stored in memory, or the content captured by the device sensors may be recorded and stored in memory with or without the modifications (or both). In some systems, a preview feature can show how different augmented reality content items will look within different windows in a display at the same time. This can, for

example, enable multiple windows with different pseudorandom animations to be viewed on a display at the same time.

(90) Data and various systems using augmented reality content items or other such transform systems to modify content using this data can thus involve detection of objects (e.g., faces, hands, bodies, cats, dogs, surfaces, objects, etc.), tracking of such objects as they leave, enter, and move around the field of view in video frames, and the modification or transformation of such objects as they are tracked. In various examples, different methods for achieving such transformations may be used. Some examples may involve generating a three-dimensional mesh model of the object or objects, and using transformations and animated textures of the model within the video to achieve the transformation. In other examples, tracking of points on an object may be used to place an image or texture (which may be two dimensional or three dimensional) at the tracked position. In still further examples, neural network analysis of video frames may be used to place images, models, or textures in content (e.g., images or frames of video). Augmented reality content items thus refer both to the images, models, and textures used to create transformations in content, as well as to additional modeling and analysis information needed to achieve such transformations with object detection, tracking, and placement.

(91) Real-time video processing can be performed with any kind of video data (e.g., video streams, video files, etc.) saved in a memory of a computerized system of any kind. For example, a user can load video files and save them in a memory of a device, or can generate a video stream using sensors of the device. Additionally, any objects can be processed using a computer animation model, such as a human's face and parts of a human body, animals, or non-living things such as chairs, cars, or other objects.

(92) In some examples, when a particular modification is selected along with content to be transformed, elements to be transformed are identified by the computing device, and then detected and tracked if they are present in the frames of the video. The elements of the object are modified according to the request for modification, thus transforming the frames of the video stream. Transformation of frames of a video stream can be performed by different methods for different kinds of transformation. For example, for transformations of frames mostly referring to changing forms of an object's elements, characteristic points for each element of an object are calculated (e.g., using an Active Shape Model (ASM) or other known methods). Then, a mesh based on the characteristic points is generated for each of the at least one element of the object. This mesh is used in the following stage of tracking the elements of the object in the video stream. In the process of tracking, the mentioned mesh for each element is aligned with a position of each element. Then, additional points are generated on the mesh. A first set of first points is generated for each element based on a request for modification, and a set of second points is generated for each element based on the set of first points and the request for modification. Then, the frames of the video stream can be transformed by modifying the elements of the object on the basis of the sets of first and second points and the mesh. In such method, a background of the modified object can be changed or distorted as well by tracking and modifying the background.

(93) In some examples, transformations changing some areas of an object using its elements can be performed by calculating characteristic points for each element of an object and generating a mesh based on the calculated characteristic points. Points are generated on the mesh, and then various areas based on the points are generated. The elements of the object are then tracked by aligning the area for each element with a position for each of the at least one element, and properties of the areas can be modified based on the request for modification, thus transforming the frames of the video stream. Depending on the specific request for modification, properties of the mentioned areas can be transformed in different ways. Such modifications may involve changing color of areas; removing at least some part of areas from the frames of the video stream; including one or more new objects into areas which are based on a request for modification; and modifying or distorting the elements of an area or object. In various examples, any combination of such modifications or

other similar modifications may be used. For certain models to be animated, some characteristic points can be selected as control points to be used in determining the entire state-space of options for the model animation.

(94) In some examples of a computer animation model to transform image data using face detection, the face is detected on an image with use of a specific face detection algorithm (e.g., Viola-Jones). Then, an Active Shape Model (ASM) algorithm is applied to the face region of an image to detect facial feature reference points.

(95) Other methods and algorithms suitable for face detection can be used. For example, in some examples, features are located using a landmark, which represents a distinguishable point present in most of the images under consideration. For facial landmarks, for example, the location of the left eye pupil may be used. If an initial landmark is not identifiable (e.g., if a person has an eyepatch), secondary landmarks may be used. Such landmark identification procedures may be used for any such objects. In some examples, a set of landmarks forms a shape. Shapes can be represented as vectors using the coordinates of the points in the shape. One shape is aligned to another with a similarity transform (allowing translation, scaling, and rotation) that minimizes the average Euclidean distance between shape points. The mean shape is the mean of the aligned training shapes.

(96) In some examples, a search is started for landmarks from the mean shape aligned to the position and size of the face determined by a global face detector. Such a search then repeats the steps of suggesting a tentative shape by adjusting the locations of shape points by template matching of the image texture around each point and then conforming the tentative shape to a global shape model until convergence occurs. In some systems, individual template matches are unreliable, and the shape model pools the results of the weak template matches to form a stronger overall classifier. The entire search is repeated at each level in an image pyramid, from coarse to fine resolution.

(97) A transformation system can capture an image or video stream on a client device (e.g., the client device **102**) and perform complex image manipulations locally on the client device **102** while maintaining a suitable user experience, computation time, and power consumption. The complex image manipulations may include size and shape changes, emotion transfers (e.g., changing a face from a frown to a smile), state transfers (e.g., aging a subject, reducing apparent age, changing gender), style transfers, graphical element application, and any other suitable image or video manipulation implemented by a convolutional neural network that has been configured to execute efficiently on the client device **102**.

(98) In some examples, a computer animation model to transform image data can be used by a system where a user may capture an image or video stream of the user (e.g., a selfie) using a client device **102** having a neural network operating as part of a client application **104** operating on the client device **102**. The transformation system operating within the client application **104** determines the presence of a face within the image or video stream and provides modification icons associated with a computer animation model to transform image data, or the computer animation model can be present as associated with an interface described herein. The modification icons include changes that may be the basis for modifying the user's face within the image or video stream as part of the modification operation. Once a modification icon is selected, the transformation system initiates a process to convert the image of the user to reflect the selected modification icon (e.g., generate a smiling face on the user). A modified image or video stream may be presented in a graphical user interface displayed on the client device **102** as soon as the image or video stream is captured, and a specified modification is selected. The transformation system may implement a complex convolutional neural network on a portion of the image or video stream to generate and apply the selected modification. That is, the user may capture the image or video stream and be presented with a modified result in real-time or near real-time once a modification icon has been selected. Further, the modification may be persistent while the video stream is being captured, and the

selected modification icon remains toggled. Machine-taught neural networks may be used to enable such modifications.

(99) The graphical user interface, presenting the modification performed by the transformation system, may supply the user with additional interaction options. Such options may be based on the interface used to initiate the content capture and selection of a particular computer animation model (e.g., initiation from a content creator user interface). In various examples, a modification may be persistent after an initial selection of a modification icon. The user may toggle the modification on or off by tapping or otherwise selecting the face being modified by the transformation system and store it for later viewing or browse to other areas of the imaging application. Where multiple faces are modified by the transformation system, the user may toggle the modification on or off globally by tapping or selecting a single face modified and displayed within a graphical user interface. In some examples, individual faces, among a group of multiple faces, may be individually modified, or such modifications may be individually toggled by tapping or selecting the individual face or a series of individual faces displayed within the graphical user interface.

(100) A story table **314** stores data regarding collections of messages and associated image, video, or audio data, which are compiled into a collection (e.g., a story or a gallery). The creation of a particular collection may be initiated by a particular user (e.g., each user for which a record is maintained in the entity table **306**). A user may create a “personal story” in the form of a collection of content that has been created and sent/broadcast by that user. To this end, the user interface of the client application **104** may include an icon that is user-selectable to enable a sending user to add specific content to his or her personal story.

(101) A collection may also constitute a “live story,” which is a collection of content from multiple users that is created manually, automatically, or using a combination of manual and automatic techniques. For example, a “live story” may constitute a curated stream of user-submitted content from various locations and events. users whose client devices have location services enabled and are at a common location event at a particular time may, for example, be presented with an option, via a user interface of the client application **104**, to contribute content to a particular live story. The live story may be identified to the user by the client application **104**, based on his or her location. The end result is a “live story” told from a community perspective.

(102) A further type of content collection is known as a “location story,” which enables a user whose client device **102** is located within a specific geographic location (e.g., on a college or university campus) to contribute to a particular collection. In some examples, a contribution to a location story may require a second degree of authentication to verify that the end user belongs to a specific organization or other entity (e.g., is a student on the university campus).

(103) As mentioned above, the video table **304** stores video data that, in one example, is associated with messages for which records are maintained within the message table **302**. Similarly, the image table **312** stores image data associated with messages for which message data is stored in the entity table **306**. The entity table **306** may associate various augmentations from the augmentation table **310** with various images and videos stored in the image table **312** and the video table **304**.

(104) Data Communications Architecture

(105) FIG. **4** is a schematic diagram illustrating a structure of a message **400**, according to some examples, generated by a client application **104** for communication to a further client application **104** or the messaging server **118**. The content of a particular message **400** is used to populate the message table **302** stored within the database **126**, accessible by the messaging server **118**.

Similarly, the content of a message **400** is stored in memory as “in-transit” or “in-flight” data of the client device **102** or the application servers **114**. A message **400** is shown to include the following example components: message identifier **402**: a unique identifier that identifies the message **400**. message text payload **404**: text, to be generated by a user via a user interface of the client device **102**, and that is included in the message **400**. message image payload **406**: image data, captured by a camera component of a client device **102** or retrieved from a memory component of a client

device **102**, and that is included in the message **400**. Image data for a sent or received message **400** may be stored in the image table **312**. message video payload **408**: video data, captured by a camera component or retrieved from a memory component of the client device **102**, and that is included in the message **400**. Video data for a sent or received message **400** may be stored in the video table **304**. message audio payload **410**: audio data, captured by a microphone or retrieved from a memory component of the client device **102**, and that is included in the message **400**. message augmentation data **412**: augmentation data (e.g., filters, stickers, or other annotations or enhancements) that represents augmentations to be applied to message image payload **406**, message video payload **408**, or message audio payload **410** of the message **400**. Augmentation data for a sent or received message **400** may be stored in the augmentation table **310**. message duration parameter **414**: parameter value indicating, in seconds, the amount of time for which content of the message (e.g., the message image payload **406**, message video payload **408**, message audio payload **410**) is to be presented or made accessible to a user via the client application **104**. message geolocation parameter **416**: geolocation data (e.g., latitudinal and longitudinal coordinates) associated with the content payload of the message. Multiple message geolocation parameter **416** values may be included in the payload, each of these parameter values being associated with respect to content items included in the content (e.g., a specific image within the message image payload **406**, or a specific video in the message video payload **408**). message story identifier **418**: identifier values identifying one or more content collections (e.g., “stories” identified in the story table **314**) with which a particular content item in the message image payload **406** of the message **400** is associated. For example, multiple images within the message image payload **406** may each be associated with multiple content collections using identifier values. message tag **420**: each message **400** may be tagged with multiple tags, each of which is indicative of the subject matter of content included in the message payload. For example, where a particular image included in the message image payload **406** depicts an animal (e.g., a lion), a tag value may be included within the message tag **420** that is indicative of the relevant animal. Tag values may be generated manually, based on user input, or may be automatically generated using, for example, image recognition. message sender identifier **422**: an identifier (e.g., a messaging system identifier, email address, or device identifier) indicative of a user of the client device **102** on which the message **400** was generated and from which the message **400** was sent. message receiver identifier **424**: an identifier (e.g., a messaging system identifier, email address, or device identifier) indicative of a user of the client device **102** to which the message **400** is addressed.

(106) The contents (e.g., values) of the various components of message **400** may be pointers to locations in tables within which content data values are stored. For example, an image value in the message image payload **406** may be a pointer to (or address of) a location within an image table **312**. Similarly, values within the message video payload **408** may point to data stored within a video table **304**, values stored within the message augmentation data **412** may point to data stored in an augmentation table **310**, values stored within the message story identifier **418** may point to data stored in a story table **314**, and values stored within the message sender identifier **422** and the message receiver identifier **424** may point to user records stored within an entity table **306**.

(107) Component Integration System

(108) FIG. 5 is a block diagram showing an example component integration system **224**, according to some examples. The component integration system **224** includes an AR experience development module **500**, a component access module **510**, and a component synchronization module **520**.

(109) The AR experience development module **500** generates user interfaces for presentation to an AR developer on an AR developer client device **102**. The user interfaces enable the AR developer to select AR events and conditions to control launching of other components on one or more client devices **102**. As referred to herein, an “AR experience bundle” or “AR bundle” represents a set of AR elements (including standard AR elements and linked AR elements) and corresponding code that indicates the visual appearance, interaction and behavior of each of the AR elements. The AR

bundle includes the code necessary for a client device **102** to launch and execute the AR experience associated with the AR bundle. The AR bundle includes conditions or parameters that are tracked and used to store a current state of the AR experience. The conditions are consistently or periodically tracked to identify one or more other components to launch on the client device **102** based on one or more interactions performed on the AR experience. In some cases, another component can pass parameters to the AR bundle which are used by the other component to initiate and launch the AR experience in a particular state.

(110) In some examples, the AR experience development module **500** receives a request from a developer client device **102** to access a developer user interface. For example, the AR experience development module **500** receives login credentials from the developer client device **102**. The AR experience development module **500** can search for an account associated with the login credentials and generate a graphical user interface associated with the account for presentation to the developer client device **102**. The AR experience development module **500** presents, in the graphical user interface, a plurality of AR experience bundles associated with the account. In some cases, the account is accessible to an organization, in which case multiple users within the organization can share access to the account and can view the same set of AR experience bundles.

(111) The AR experience development module **500** can receive input from the developer client device **102** that selects a given AR experience bundle. In response to receiving the input, the AR experience development module **500** presents a graphical user interface. The AR experience development module **500** includes, in the graphical user interface, an identifier of the AR experience bundle and a list of AR events, conditions or triggers that are included in the AR experience bundle and which control launching of another component during execution of the AR experience.

(112) An AR event, condition, or trigger can include or represent a specified action, goal, or object that is associated with the AR experience. For example, the AR event, condition, or trigger can include any combination of a custom event, a camera event (specifying activation of a front or rear facing camera), a face found event, a face lost event, an object tracking criterion, a 3D object tracking criterion, a marker tracking component, a tap event, a touch started event, a touch moved event, a touch ended event, a shared session event, a shared session joined event, a voice command event, a voice transcription event, and/or a language event. The list can also include one or more AR elements or objects. The AR elements can include 2D meshes, 3D meshes, videos, audio files, image files, and/or machine learning models. The AR event, condition, or trigger can include combinatorial logic that is used to determine when to assert an operation or call to action for launching another component. For example, when the combinatorial logic asserts an output, the AR bundle identifies a second component (e.g., map application or web-based application) associated with the combinatorial logic. The AR bundle writes or stores a current state of the AR experience in a shared data structure for access by the second component. Then, the AR bundle instructs the client device **102** to launch the second component which uses the data structure to configure a state of the second component.

(113) The AR experience development module **500** can receive input that selects a given AR event or condition or combinatorial logic. For example, the conditions or combinatorial logic specify a level of subscription of an end user, a geographical region associated with the end user, a time of day, a type of AR experience, geographical locations, goal, levels in a gaming application or AR experience, views or depictions of real-world environment portions, a request from an end user to enable persisting the AR object or element, time, location markers, image markers, or any other suitable condition.

(114) In some examples, the client device **102** determines that a particular interaction (e.g., a particular camera view, such as a front-facing camera view, a rear-facing camera view, or that a specified real-world object is detected in a captured image) corresponds to a given condition associated with the AR experience. In such cases, the client device **102** aggregates the interaction

into an entity or data structure associated with the given condition. If the condition is satisfied, the client device **102** identifies a second component associated with the condition and launches the second component using the aggregated interaction.

(115) In some examples, the component access module **510** launches a first component, such as a web-based application, avatar application, map application, or AR experience. The first component can be launched on a first client device **102**. For example, the client application **104** presents a user interface to a first user on the first client device **102**. In one example, the user interface includes a plurality of options each associated with a different component implemented by the client application **104**. In response to receiving a user selection of an option associated with the first component, the client application **104** launches the first component and presents or generates a display that includes a user interface of the first component.

(116) The component access module **510** can retrieve a set of conditions associated with the first component. The set of conditions control when and which parameters to pass to a second and/or third component of the client application **104** during access of the first component. The set of conditions can be stored or configured into the component synchronization module **520**. The set of conditions can also control what type of data or information is shared between the various components during access of the first component. The data or information is stored in a shared data structure by the component synchronization module **520**.

(117) The component synchronization module **520** can monitor progress or interactions performed by a user during access of the first component on the first client device **102**. For example, the component synchronization module **520** detects that a particular interaction or set of interactions corresponds to a condition stored by the component synchronization module **520**. For example, the first component includes a web-based application and the condition represents a level, virtual room, or set of actions, such as navigating an avatar to a particular virtual location within the web-based application. In such cases, the component synchronization module **520** identifies a second component (which can be of a different type than the first component) that is associated with the condition. The component synchronization module **520** programmatically, automatically, or in response to a user confirmation or selection of an option from a displayed prompt, launches the second component. The component synchronization module **520** provides, to the component access module **510**, an identification of the second component and a set of configuration data from the shared data structure to initiate the launch of the second component into a particular state. The component access module **510** launches the second component in the particular state. For example, the second component can be an AR experience which presents one or more AR elements corresponding to the level, virtual room, or set of actions, such as navigating an avatar to a particular virtual location within the web-based application that was performed on the web-based application.

(118) The component access module **510** can monitor progress or interactions performed by a user during access of the second component on the first client device **102**. For example, the component synchronization module **520** detects that a particular interaction or set of interactions corresponds to a condition stored by the component synchronization module **520** for the second component. For example, the second component includes the AR experience and the condition can represent a user interaction with one or more of the AR elements presented within a real-time video feed captured by the first client device **102** and presented on the first client device **102**. In such cases, the component synchronization module **520** identifies the first component and/or a third component (which can be of a different type than the first/second components) that is associated with the condition satisfied by the interaction with the second component. The component synchronization module **520** programmatically, automatically, or in response to a user confirmation or selection of an option from a displayed prompt, launches the first and/or third components. The component synchronization module **520** provides, to the component access module **510**, an identification of the first and/or third components and a set of configuration data from the shared data structure to

initiate the launch of the first and/or third component into a particular state. The component access module **510** launches the first and/or third component in the particular state. In this way, interactions performed on one component are used to control a state of another component in a seamless and unified manner.

(119) In some examples, the first component includes an AR experience and the condition represents a level, goal, set of interactions with virtual elements or AR elements displayed in the AR experience over a real-world environment depicted in a captured video stream, virtual room, or set of actions. In such cases, the component synchronization module **520** identifies a second component (which can be of a different type than the first component) that is associated with the condition. The component synchronization module **520** programmatically, automatically, or in response to a user confirmation or selection of an option from a displayed prompt, launches the second component. The component synchronization module **520** provides, to the component access module **510**, an identification of the second component and a set of configuration data from the shared data structure to initiate the launch of the second component into a particular state. The component access module **510** launches the second component in the particular state. For example, the second component is a web-based application which presents a user interface associated with the one or more AR elements interacted with using the AR experience.

(120) The component access module **510** monitors progress or interactions performed by a user during access of the second component on the first client device **102**. For example, the component synchronization module **520** detects that a particular interaction or set of interactions corresponds to a condition stored by the component synchronization module **520** for the second component. When a condition is satisfied by the interactions performed using the second component, the component synchronization module **520** identifies the first component and/or a third component (which can be of a different type than the first/second components) that is associated with the condition satisfied by the interaction with the second component. The component synchronization module **520** programmatically, automatically, or in response to a user confirmation or selection of an option from a displayed prompt, launches the first and/or third components. The component synchronization module **520** provides, to the component access module **510**, an identification of the first and/or third components and a set of configuration data from the shared data structure to initiate the launch of the first and/or third component into a particular state. The component access module **510** launches the first and/or third component in the particular state. In this way, interactions performed on one component are used to control a state of another component in a seamless and unified manner.

(121) FIGS. **6**, **7**, **8A** and **8B** are diagrammatic representations of outputs of the component integration system **224**, in accordance with some examples. For example, as shown in the set of user interfaces **600** of FIG. **6**, a user input may be received requesting to launch a web-based application. The component integration system **224** receives the input and launches the web-based application. In response, the component integration system **224** presents a first user interface **610** in which graphical elements of the web-based application are displayed. The first user interface **610** includes an avatar that a user can control. In some examples, the avatar is controlled by the user to walk to a virtual location, such as a virtual bathroom. This can be in response to a message informing the user to check out the face of the avatar in the mirror.

(122) In response to determining that the avatar has been moved or navigated to the virtual bathroom location, the component integration system **224** can determine that a condition is satisfied. The condition can be associated with launching an AR experience. In such cases, the component integration system **224** presents one or more graphical elements of the web-based application corresponding to the virtual bathroom location. For example, as shown in the user interface **620**, the component integration system **224** displays a graphical mirror **626** which is part of the web-based application. The component integration system **224** also launches the AR experience with an indication of AR elements to present on a particular portion of a face.

(123) The component integration system **224** can instruct the AR experience to activate a front-facing camera of the client device **102**. In one example, the component integration system **224** requests input from the user to allow access to the front-facing camera (e.g., before the web-based application is launched and/or in response to triggering the condition that launches the AR experience). If the user allows the front-facing camera to be used, the component integration system **224** captures a real-time video stream from the camera and displays the real-time video stream in a specified portion of the user interface of the web-based application, such as in a portion surrounded by the virtual mirror **626**. The AR experience can detect a real-world facial element, such as eyes of the user **622**, in the video stream and display one or more animated AR elements **624** over or adjacent to the detected facial element. In this way, the component integration system **224** integrates some visual elements of the web-based application together with visual elements of the AR experience to provide a unified experience.

(124) The component integration system **224** can detect that a certain condition is met, such as a user selecting an exit option or performing certain movement detected by the front-facing camera. In response, the component integration system **224** exits the AR experience and returns the user to the display of the web-based application, shown in user interface **630**.

(125) In some examples, as shown in the set of user interfaces **700** of FIG. 7, a user input may be received requesting to launch a web-based application. The component integration system **224** receives the input and launches the web-based application. In response, the component integration system **224** presents a first user interface **710** in which graphical elements **712** of the web-based application are displayed. The first user interface **710** includes a menu of virtual items, such as virtual flowers. The web-based application detects a selection of a given one of the graphical elements **712**. This triggers a condition for launching an AR experience.

(126) Specifically, in response to determining that the given one of the graphical elements **712** has been selected, the component integration system **224** determines that a condition is satisfied. In one example, the condition is associated with launching an AR experience. In such cases, the component integration system **224** instructs the AR experience to activate a rear-facing camera of the client device **102**. The component integration system **224** passes one or more parameters of the web-based application that identify the given one of the graphical elements **712** that has been selected. The component integration system **224** requests input from the user to allow access to the rear-facing camera (e.g., before the web-based application is launched and/or in response to triggering the condition that launches the AR experience). If the user allows the rear-facing camera to be used, the component integration system **224** captures a real-time video stream from the rear-facing camera and displays the real-time video stream in a user interface **720**. The AR experience can display one or more animated AR elements **724** over or adjacent to one or more real-world objects **722** depicted in the video stream. The AR elements **724** can represent AR counterparts (e.g., 3D flowers) of the virtual item (e.g., virtual flower) corresponding to the given one of the graphical elements **712** that was selected from the user interface of the web-based application. In this way, the component integration system **224** integrates some features of the visual elements of the web-based application into the visual elements of the AR experience to provide a unified experience.

(127) In some examples, as shown in FIG. 8A, a user input is received requesting to launch an AR experience. The component integration system **224** receives the input and launches the AR experience. In response, the component integration system **224** presents a first user interface **800** in which AR elements of the AR experience are displayed. The AR elements can include a virtual device, such as a virtual phone displayed over a real-world environment depicted in a real-time video feed captured by a front-facing or rear-facing camera of the client device **102** and presented on the screen.

(128) The AR experience detects a an interaction, such as a user selection of the virtual AR device that is displayed. This interaction triggers a condition for launching a web-based application. In this case, the interaction includes a request to access or use the virtual AR device. The component

integration system **224** provides parameters of the virtual AR device to the web-based application with an instruction to launch the web-based application. The web-based application presents a user interface **810** in place of the user interface **800** associated with the AR experience. The user interface **810** includes graphical elements of the web-based application, such as a virtual keypad. The web-based application receives input that selects a certain combination of keys of the virtual keypad and determines if the combination matches a predetermined combination or code. In response to the web-based application determining that the combination fails to match the predetermined combination or code, the web-based application presents a message indicating that the facepass is invalid.

(129) In response to determining the number of times combinations entered by the user fail to match the predetermined combination or code, the web-based application determines that a condition for launching or re-accessing the AR experience is satisfied. In such cases, the web-based application retrieves a set of characters and pass those characters to the AR experience for presentation as AR elements. The web-based application launches the AR experience with instruction to activate a front-facing camera of the client device **102** in which a real-world environment is captured. The web-based application also instructs the AR experience to display an animated representation of the set of characters, such as using animated 3D AR elements. For example, as shown in user interface **820**, the AR experience presents a real-time video feed depicting a face of a user **822** and one or more 3D AR elements **824** corresponding to the set of characters received from the web-based application. After a threshold period of time elapses or in response to input from a user, the AR experience is terminated and the web-based application user interface **810** is re-displayed. The web-based application allows the user to input the combination again corresponding to the 3D AR elements that were presented by the AR experience.

(130) In response to the web-based application determining that the combination matches the predetermined combination or code, the web-based application presents a user interface **830**, shown in FIG. **8B**. The user interface **830** represents visual elements of an unlocked virtual device. The web-based application receives input from the user interacting with an option presented on the virtual device to access an AR gaming experience. In response, the web-based application instructs the AR gaming experience to activate a rear-facing camera of the client device **102**. The web-based application provides data for rendering one or more AR elements over the real-time video feed received from the rear-facing camera, as shown in user interface **840**. The AR gaming experience can monitor progress of the user interacting with the one or more AR elements. In response to determining that a goal has been reached, such as capturing a certain set or number of ghosts or AR elements, the AR gaming application determines that a condition is satisfied. At this time, the AR gaming experience passes parameters to the web-based application indicating the goal that was reached. In response to receiving the parameters, the web-based application user interface **850** is displayed replacing the display of the AR gaming experience. Based on the interactions of the user with the AR gaming experience, the user interface **850** identifies a new virtual game or mode that has become unlocked and available to use as part of the virtual device provided by the web-based application and presents a message informing the user about the new virtual game or mode.

(131) In some examples, an AR experience is presented on a first client device **102**. The AR experience can correspond to a capture the flag game. The first client device **102** captures real-time video using a rear-facing camera of one or more real-world buildings in a real-world environment. In response to detecting that a condition associated with a first real-world building has been satisfied, the AR experience renders an AR element, such as a color, animation or pattern over the first real-world building. The AR experience also stores real-world location information, such as GPS coordinates of the first real-world building. The real-world location information is shared with a map application (another component of the client application **104**) by the AR experience. The AR experience also shares the visual elements associated with the first real-world building with the map application.

(132) At a later time or concurrently while the AR experience is accessed on the first client device **102**, a second client device **102** can access the map application. The map application on the second client device **102** can access the shared information from the AR experience, such as because the first client device **102** authorized sharing of the information with a certain set or group of other client devices **102** including the second client device **102**. The map application on the second client device **102** displays a map and receives input from a user that navigates the map to a region that includes the GPS coordinates of the first real-world building. In response, the map application displays a representation of the first real-world building on the map along with a representation of the visual elements associated with the first real-world building generated by the AR experience. For example, the map application displays an indicator or icon with a certain color over the GPS coordinates of the first real-world building on the displayed map region. This allows users who are not involved in the AR experience to track progress of the game and users on the AR experience by looking at a different component, such as a map that is external to the AR experience.

(133) FIG. **9** is a flowchart of a process **900** performed by the component integration system **224**, in accordance with some examples. Although the flowchart can describe the operations as a sequential process, many of the operations can be performed in parallel or concurrently. In addition, the order of the operations may be re-arranged. A process is terminated when its operations are completed. A process may correspond to a method, a procedure, and the like. The steps of methods may be performed in whole or in part, may be performed in conjunction with some or all of the steps in other methods, and may be performed by any number of different systems or any portion thereof, such as a processor included in any of the systems.

(134) At operation **901**, the component integration system **224** (e.g., a client device **102** or a server) accesses, by a messaging application implemented on a client device, a first component of a plurality of components implemented by the messaging application, the plurality of components comprising an augmented reality (AR) experience, each of the plurality of components being configured to be separately launched by the messaging application, as discussed above.

(135) At operation **902**, the component integration system **224** stores a first state of the first component in a data structure that is shared across the plurality of components, as discussed above.

(136) At operation **903**, the component integration system **224** launches, by the messaging application, a second component of the plurality of components in response to determining that an interaction has been performed using the first component, as discussed above.

(137) At operation **904**, the component integration system **224** accesses, by the second component, the data structure to retrieve the first state of the first component, as discussed above.

(138) At operation **905**, the component integration system **224** configures a second state of the second component that has been launched based on the first state of the first component, as discussed above.

(139) Machine Architecture

(140) FIG. **10** is a diagrammatic representation of a machine **1000** within which instructions **1008** (e.g., software, a program, an application, an applet, an app, or other executable code) for causing the machine **1000** to perform any one or more of the methodologies discussed herein may be executed. For example, the instructions **1008** may cause the machine **1000** to execute any one or more of the methods described herein. The instructions **1008** transform the general, non-programmed machine **1000** into a particular machine **1000** programmed to carry out the described and illustrated functions in the manner described. The machine **1000** may operate as a standalone device or may be coupled (e.g., networked) to other machines. In a networked deployment, the machine **1000** may operate in the capacity of a server machine or a client machine in a server-client network environment, or as a peer machine in a peer-to-peer (or distributed) network environment. The machine **1000** may comprise, but not be limited to, a server computer, a client computer, a personal computer (PC), a tablet computer, a laptop computer, a netbook, a set-top box (STB), a personal digital assistant (PDA), an entertainment media system, a cellular telephone, a

smartphone, a mobile device, a wearable device (e.g., a smartwatch), a smart home device (e.g., a smart appliance), other smart devices, a web appliance, a network router, a network switch, a network bridge, or any machine capable of executing the instructions **1008**, sequentially or otherwise, that specify actions to be taken by the machine **1000**. Further, while only a single machine **1000** is illustrated, the term “machine” shall also be taken to include a collection of machines that individually or jointly execute the instructions **1008** to perform any one or more of the methodologies discussed herein. The machine **1000**, for example, may comprise the client device **102** or any one of a number of server devices forming part of the messaging server system **108**. In some examples, the machine **1000** may also comprise both client and server systems, with certain operations of a particular method or algorithm being performed on the server-side and with certain operations of the particular method or algorithm being performed on the client-side.

(141) The machine **1000** may include processors **1002**, memory **1004**, and input/output (I/O) components **1038**, which may be configured to communicate with each other via a bus **1040**. In an example, the processors **1002** (e.g., a Central Processing Unit (CPU), a Reduced Instruction Set Computing (RISC) Processor, a Complex Instruction Set Computing (CISC) Processor, a Graphics Processing Unit (GPU), a Digital Signal Processor (DSP), an Application Specific Integrated Circuit (ASIC), a Radio-Frequency Integrated Circuit (RFIC), another processor, or any suitable combination thereof) may include, for example, a processor **1006** and a processor **1010** that execute the instructions **1008**. The term “processor” is intended to include multi-core processors that may comprise two or more independent processors (sometimes referred to as “cores”) that may execute instructions contemporaneously. Although FIG. **10** shows multiple processors **1002**, the machine **1000** may include a single processor with a single-core, a single processor with multiple cores (e.g., a multi-core processor), multiple processors with a single core, multiple processors with multiples cores, or any combination thereof.

(142) The memory **1004** includes a main memory **1012**, a static memory **1014**, and a storage unit **1016**, all accessible to the processors **1002** via the bus **1040**. The main memory **1012**, the static memory **1014**, and the storage unit **1016** store the instructions **1008** embodying any one or more of the methodologies or functions described herein. The instructions **1008** may also reside, completely or partially, within the main memory **1012**, within the static memory **1014**, within a machine-readable medium within the storage unit **1016**, within at least one of the processors **1002** (e.g., within the processor's cache memory), or any suitable combination thereof, during execution thereof by the machine **1000**.

(143) The I/O components **1038** may include a wide variety of components to receive input, provide output, produce output, transmit information, exchange information, capture measurements, and so on. The specific I/O components **1038** that are included in a particular machine will depend on the type of machine. For example, portable machines such as mobile phones may include a touch input device or other such input mechanisms, while a headless server machine will likely not include such a touch input device. It will be appreciated that the I/O components **1038** may include many other components that are not shown in FIG. **10**. In various examples, the I/O components **1038** may include user output components **1024** and user input components **1026**. The user output components **1024** may include visual components (e.g., a display such as a plasma display panel (PDP), a light-emitting diode (LED) display, a liquid crystal display (LCD), a projector, or a cathode ray tube (CRT)), acoustic components (e.g., speakers), haptic components (e.g., a vibratory motor, resistance mechanisms), other signal generators, and so forth. The user input components **1026** may include alphanumeric input components (e.g., a keyboard, a touch screen configured to receive alphanumeric input, a photo-optical keyboard, or other alphanumeric input components), point-based input components (e.g., a mouse, a touchpad, a trackball, a joystick, a motion sensor, or another pointing instrument), tactile input components (e.g., a physical button, a touch screen that provides location and force of touches or touch gestures, or other tactile input components), audio input components (e.g., a microphone), and the

like.

(144) In further examples, the I/O components **1038** may include biometric components **1028**, motion components **1030**, environmental components **1032**, or position components **1034**, among a wide array of other components. For example, the biometric components **1028** include components to detect expressions (e.g., hand expressions, facial expressions, vocal expressions, body gestures, or eye-tracking), measure biosignals (e.g., blood pressure, heart rate, body temperature, perspiration, or brain waves), identify a person (e.g., voice identification, retinal identification, facial identification, fingerprint identification, or electroencephalogram-based identification), and the like. The motion components **1030** include acceleration sensor components (e.g., accelerometer), gravitation sensor components, rotation sensor components (e.g., gyroscope).

(145) The environmental components **1032** include, for example, one or cameras (with still image/photograph and video capabilities), illumination sensor components (e.g., photometer), temperature sensor components (e.g., one or more thermometers that detect ambient temperature), humidity sensor components, pressure sensor components (e.g., barometer), acoustic sensor components (e.g., one or more microphones that detect background noise), proximity sensor components (e.g., infrared sensors that detect nearby objects), gas sensors (e.g., gas detection sensors to detection concentrations of hazardous gases for safety or to measure pollutants in the atmosphere), or other components that may provide indications, measurements, or signals corresponding to a surrounding physical environment.

(146) With respect to cameras, the client device **102** may have a camera system comprising, for example, front cameras on a front surface of the client device **102** and rear cameras on a rear surface of the client device **102**. The front cameras may, for example, be used to capture still images and video of a user of the client device **102** (e.g., “selfies”), which may then be augmented with augmentation data (e.g., filters) described above. The rear cameras may, for example, be used to capture still images and videos in a more traditional camera mode, with these images similarly being augmented with augmentation data. In addition to front and rear cameras, the client device **102** may also include a 360° camera for capturing 360° photographs and videos.

(147) Further, the camera system of a client device **102** may include dual rear cameras (e.g., a primary camera as well as a depth-sensing camera), or even triple, quad or penta rear camera configurations on the front and rear sides of the client device **102**. These multiple cameras systems may include a wide camera, an ultra-wide camera, a telephoto camera, a macro camera, and a depth sensor, for example.

(148) The position components **1034** include location sensor components (e.g., a GPS receiver component), altitude sensor components (e.g., altimeters or barometers that detect air pressure from which altitude may be derived), orientation sensor components (e.g., magnetometers), and the like.

(149) Communication may be implemented using a wide variety of technologies. The I/O components **1038** further include communication components **1036** operable to couple the machine **1000** to a network **1020** or devices **1022** via respective coupling or connections. For example, the communication components **1036** may include a network interface component or another suitable device to interface with the network **1020**. In further examples, the communication components **1036** may include wired communication components, wireless communication components, cellular communication components, Near Field Communication (NFC) components, Bluetooth® components (e.g., Bluetooth® Low Energy), Wi-Fi® components, and other communication components to provide communication via other modalities. The devices **1022** may be another machine or any of a wide variety of peripheral devices (e.g., a peripheral device coupled via a USB).

(150) Moreover, the communication components **1036** may detect identifiers or include components operable to detect identifiers. For example, the communication components **1036** may include Radio Frequency Identification (RFID) tag reader components, NFC smart tag detection components, optical reader components (e.g., an optical sensor to detect one-dimensional bar codes

such as Universal Product Code (UPC) bar code, multi-dimensional bar codes such as Quick Response (QR) code, Aztec code, Data Matrix, Dataglyph, MaxiCode, PDF417, Ultra Code, UCC RSS-2D bar code, and other optical codes), or acoustic detection components (e.g., microphones to identify tagged audio signals). In addition, a variety of information may be derived via the communication components **1036**, such as location via Internet Protocol (IP) geolocation, location via Wi-Fi® signal triangulation, location via detecting an NFC beacon signal that may indicate a particular location, and so forth.

(151) The various memories (e.g., main memory **1012**, static memory **1014**, and memory of the processors **1002**) and storage unit **1016** may store one or more sets of instructions and data structures (e.g., software) embodying or used by any one or more of the methodologies or functions described herein. These instructions (e.g., the instructions **1008**), when executed by processors **1002**, cause various operations to implement the disclosed examples.

(152) The instructions **1008** may be transmitted or received over the network **1020**, using a transmission medium, via a network interface device (e.g., a network interface component included in the communication components **1036**) and using any one of several well-known transfer protocols (e.g., hypertext transfer protocol (HTTP)). Similarly, the instructions **1008** may be transmitted or received using a transmission medium via a coupling (e.g., a peer-to-peer coupling) to the devices **1022**.

(153) Software Architecture

(154) FIG. **11** is a block diagram **1100** illustrating a software architecture **1104**, which can be installed on any one or more of the devices described herein. The software architecture **1104** is supported by hardware such as a machine **1102** that includes processors **1120**, memory **1126**, and I/O components **1138**. In this example, the software architecture **1104** can be conceptualized as a stack of layers, where each layer provides a particular functionality. The software architecture **1104** includes layers such as an operating system **1112**, libraries **1110**, frameworks **1108**, and applications **1106**. Operationally, the applications **1106** invoke API calls **1150** through the software stack and receive messages **1152** in response to the API calls **1150**.

(155) The operating system **1112** manages hardware resources and provides common services. The operating system **1112** includes, for example, a kernel **1114**, services **1116**, and drivers **1122**. The kernel **1114** acts as an abstraction layer between the hardware and the other software layers. For example, the kernel **1114** provides memory management, processor management (e.g., scheduling), component management, networking, and security settings, among other functionality. The services **1116** can provide other common services for the other software layers. The drivers **1122** are responsible for controlling or interfacing with the underlying hardware. For instance, the drivers **1122** can include display drivers, camera drivers, BLUETOOTH® or BLUETOOTH® Low Energy drivers, flash memory drivers, serial communication drivers (e.g., USB drivers), WI-FI® drivers, audio drivers, power management drivers, and so forth.

(156) The libraries **1110** provide a common low-level infrastructure used by applications **1106**. The libraries **1110** can include system libraries **1118** (e.g., C standard library) that provide functions such as memory allocation functions, string manipulation functions, mathematic functions, and the like. In addition, the libraries **1110** can include API libraries **1124** such as media libraries (e.g., libraries to support presentation and manipulation of various media formats such as Moving Picture Experts Group-4 (MPEG4), Advanced Video Coding (H.264 or AVC), Moving Picture Experts Group Layer-3 (MP3), Advanced Audio Coding (AAC), Adaptive Multi-Rate (AMR) audio codec, Joint Photographic Experts Group (JPEG or JPG), or Portable Network Graphics (PNG)), graphics libraries (e.g., an OpenGL framework used to render in two dimensions (2D) and three dimensions (3D) in a graphic content on a display), database libraries (e.g., SQLite to provide various relational database functions), web libraries (e.g., WebKit to provide web browsing functionality), and the like. The libraries **1110** can also include a wide variety of other libraries **1128** to provide many other APIs to the applications **1106**.

(157) The frameworks **1108** provide a common high-level infrastructure that is used by the applications **1106**. For example, the frameworks **1108** provide various graphical user interface (GUI) functions, high-level resource management, and high-level location services. The frameworks **1108** can provide a broad spectrum of other APIs that can be used by the applications **1106**, some of which may be specific to a particular operating system or platform.

(158) In an example, the applications **1106** may include a home application **1136**, a contacts application **1130**, a browser application **1132**, a book reader application **1134**, a location application **1142**, a media application **1144**, a messaging application **1146**, a game application **1148**, and a broad assortment of other applications such as an external application **1140**. The applications **1106** are programs that execute functions defined in the programs. Various programming languages can be employed to create one or more of the applications **1106**, structured in a variety of manners, such as object-oriented programming languages (e.g., Objective-C, Java, or C++) or procedural programming languages (e.g., C or assembly language). In a specific example, the external application **1140** (e.g., an application developed using the ANDROID™ or IOS™ software development kit (SDK) by an entity other than the vendor of the particular platform) may be mobile software running on a mobile operating system such as IOS™, ANDROID™, WINDOWS® Phone, or another mobile operating system. In this example, the external application **1140** can invoke the API calls **1150** provided by the operating system **1112** to facilitate functionality described herein.

GLOSSARY

(159) “Carrier signal” refers to any intangible medium that is capable of storing, encoding, or carrying instructions for execution by the machine, and includes digital or analog communications signals or other intangible media to facilitate communication of such instructions. Instructions may be transmitted or received over a network using a transmission medium via a network interface device.

(160) “Client device” refers to any machine that interfaces to a communications network to obtain resources from one or more server systems or other client devices. A client device may be, but is not limited to, a mobile phone, desktop computer, laptop, portable digital assistants (PDAs), smartphones, tablets, ultrabooks, netbooks, laptops, multi-processor systems, microprocessor-based or programmable consumer electronics, game consoles, set-top boxes, or any other communication device that a user may use to access a network.

(161) “Communication network” refers to one or more portions of a network that may be an ad hoc network, an intranet, an extranet, a virtual private network (VPN), a local area network (LAN), a wireless LAN (WLAN), a wide area network (WAN), a wireless WAN (WWAN), a metropolitan area network (MAN), the Internet, a portion of the Internet, a portion of the Public Switched Telephone Network (PSTN), a plain old telephone service (POTS) network, a cellular telephone network, a wireless network, a Wi-Fi® network, another type of network, or a combination of two or more such networks. For example, a network or a portion of a network may include a wireless or cellular network and the coupling may be a Code Division Multiple Access (CDMA) connection, a Global System for Mobile communications (GSM) connection, or other types of cellular or wireless coupling. In this example, the coupling may implement any of a variety of types of data transfer technology, such as Single Carrier Radio Transmission Technology (1×RTT), Evolution-Data Optimized (EVDO) technology, General Packet Radio Service (GPRS) technology, Enhanced Data rates for GSM Evolution (EDGE) technology, third Generation Partnership Project (3GPP) including 3G, fourth generation wireless (4G) networks, Universal Mobile Telecommunications System (UMTS), High Speed Packet Access (HSPA), Worldwide Interoperability for Microwave Access (WiMAX), Long Term Evolution (LTE) standard, others defined by various standard-setting organizations, other long-range protocols, or other data transfer technology.

(162) “Component” refers to a device, physical entity, or logic having boundaries defined by function or subroutine calls, branch points, APIs, or other technologies that provide for the

partitioning or modularization of particular processing or control functions. Components may be combined via their interfaces with other components to carry out a machine process. A component may be a packaged functional hardware unit designed for use with other components and a part of a program that usually performs a particular function of related functions.

(163) Components may constitute either software components (e.g., code embodied on a machine-readable medium) or hardware components. A “hardware component” is a tangible unit capable of performing certain operations and may be configured or arranged in a certain physical manner. In various examples, one or more computer systems (e.g., a standalone computer system, a client computer system, or a server computer system) or one or more hardware components of a computer system (e.g., a processor or a group of processors) may be configured by software (e.g., an application or application portion) as a hardware component that operates to perform certain operations as described herein.

(164) A hardware component may also be implemented mechanically, electronically, or any suitable combination thereof. For example, a hardware component may include dedicated circuitry or logic that is permanently configured to perform certain operations. A hardware component may be a special-purpose processor, such as a field-programmable gate array (FPGA) or an application specific integrated circuit (ASIC). A hardware component may also include programmable logic or circuitry that is temporarily configured by software to perform certain operations. For example, a hardware component may include software executed by a general-purpose processor or other programmable processor. Once configured by such software, hardware components become specific machines (or specific components of a machine) uniquely tailored to perform the configured functions and are no longer general-purpose processors. It will be appreciated that the decision to implement a hardware component mechanically, in dedicated and permanently configured circuitry, or in temporarily configured circuitry (e.g., configured by software), may be driven by cost and time considerations. Accordingly, the phrase “hardware component” (or “hardware-implemented component”) should be understood to encompass a tangible entity, be that an entity that is physically constructed, permanently configured (e.g., hardwired), or temporarily configured (e.g., programmed) to operate in a certain manner or to perform certain operations described herein.

(165) Considering examples in which hardware components are temporarily configured (e.g., programmed), each of the hardware components need not be configured or instantiated at any one instance in time. For example, where a hardware component comprises a general-purpose processor configured by software to become a special-purpose processor, the general-purpose processor may be configured as respectively different special-purpose processors (e.g., comprising different hardware components) at different times. Software accordingly configures a particular processor or processors, for example, to constitute a particular hardware component at one instance of time and to constitute a different hardware component at a different instance of time.

(166) Hardware components can provide information to, and receive information from, other hardware components. Accordingly, the described hardware components may be regarded as being communicatively coupled. Where multiple hardware components exist contemporaneously, communications may be achieved through signal transmission (e.g., over appropriate circuits and buses) between or among two or more of the hardware components. In examples in which multiple hardware components are configured or instantiated at different times, communications between such hardware components may be achieved, for example, through the storage and retrieval of information in memory structures to which the multiple hardware components have access. For example, one hardware component may perform an operation and store the output of that operation in a memory device to which it is communicatively coupled. A further hardware component may then, at a later time, access the memory device to retrieve and process the stored output. Hardware components may also initiate communications with input or output devices, and can operate on a resource (e.g., a collection of information).

(167) The various operations of example methods described herein may be performed, at least partially, by one or more processors that are temporarily configured (e.g., by software) or permanently configured to perform the relevant operations. Whether temporarily or permanently configured, such processors may constitute processor-implemented components that operate to perform one or more operations or functions described herein. As used herein, “processor-implemented component” refers to a hardware component implemented using one or more processors. Similarly, the methods described herein may be at least partially processor-implemented, with a particular processor or processors being an example of hardware. For example, at least some of the operations of a method may be performed by one or more processors **1002** or processor-implemented components. Moreover, the one or more processors may also operate to support performance of the relevant operations in a “cloud computing” environment or as a “software as a service” (SaaS). For example, at least some of the operations may be performed by a group of computers (as examples of machines including processors), with these operations being accessible via a network (e.g., the Internet) and via one or more appropriate interfaces (e.g., an API). The performance of certain of the operations may be distributed among the processors, not only residing within a single machine, but deployed across a number of machines. In some examples, the processors or processor-implemented components may be located in a single geographic location (e.g., within a home environment, an office environment, or a server farm). In other examples, the processors or processor-implemented components may be distributed across a number of geographic locations.

(168) “Computer-readable storage medium” refers to both machine-storage media and transmission media. Thus, the terms include both storage devices/media and carrier waves/modulated data signals. The terms “machine-readable medium,” “computer-readable medium” and “device-readable medium” mean the same thing and may be used interchangeably in this disclosure.

(169) “Ephemeral message” refers to a message that is accessible for a time-limited duration. An ephemeral message may be a text, an image, a video and the like. The access time for the ephemeral message may be set by the message sender. Alternatively, the access time may be a default setting or a setting specified by the recipient. Regardless of the setting technique, the message is transitory.

(170) “Machine storage medium” refers to a single or multiple storage devices and media (e.g., a centralized or distributed database, and associated caches and servers) that store executable instructions, routines and data. The term shall accordingly be taken to include, but not be limited to, solid-state memories, and optical and magnetic media, including memory internal or external to processors. Specific examples of machine-storage media, computer-storage media and device-storage media include non-volatile memory, including by way of example semiconductor memory devices, e.g., erasable programmable read-only memory (EPROM), electrically erasable programmable read-only memory (EEPROM), FPGA, and flash memory devices; magnetic disks such as internal hard disks and removable disks; magneto-optical disks; and CD-ROM and DVD-ROM disks. The terms “machine-storage medium,” “device-storage medium,” “computer-storage medium” mean the same thing and may be used interchangeably in this disclosure. The terms “machine-storage media,” “computer-storage media,” and “device-storage media” specifically exclude carrier waves, modulated data signals, and other such media, at least some of which are covered under the term “signal medium.”

(171) “Non-transitory computer-readable storage medium” refers to a tangible medium that is capable of storing, encoding, or carrying the instructions for execution by a machine.

(172) “Signal medium” refers to any intangible medium that is capable of storing, encoding, or carrying the instructions for execution by a machine and includes digital or analog communications signals or other intangible media to facilitate communication of software or data. The term “signal medium” shall be taken to include any form of a modulated data signal, carrier wave, and so forth. The term “modulated data signal” means a signal that has one or more of its characteristics set or

changed in such a manner as to encode information in the signal. The terms “transmission medium” and “signal medium” mean the same thing and may be used interchangeably in this disclosure. (173) Changes and modifications may be made to the disclosed examples without departing from the scope of the present disclosure. These and other changes or modifications are intended to be included within the scope of the present disclosure, as expressed in the following claims.

Claims

1. A method comprising: accessing, by a device associated with an application developer, an application development platform; receiving, via the application development platform, input that defines a set of events associated with an application comprising a first component that controls launching of a second component; defining, by the application development platform, a data structure that is shared across a plurality of components comprising the first and second components, the data structure comprising the set of events associated with the first component that control when one or more parameters of the first component are passed to the second component and which of the one or more parameters are passed to the second component; and storing the application and the data structure in a library accessible to a user device.
2. The method of claim 1, wherein the application development platform comprises an augmented reality (AR) experience development platform, wherein the application comprises an AR experience, and wherein the second component comprises at least one of a web-based application, a map application, or an avatar application.
3. The method of claim 1, further comprising: receiving, from the device as one or more of the set of events, one or more conditions under which the second component is launched.
4. The method of claim 3, wherein the one or more conditions comprise geographical locations, levels in a gaming application or AR experience, accomplishment of one or more goals, views or depictions of real-world environment portions, time, time of day, client device type, user type, user account type, location markers, or image markers.
5. The method of claim 3, wherein the one or more conditions are manually programmed by the application developer.
6. The method of claim 3, wherein the one or more conditions are selected from a list of conditions.
7. The method of claim 1, wherein the set of events comprises combinatorial logic.
8. The method of claim 1, further comprising: accessing, by an application implemented on the user device, the first component; storing a first state of the first component in the data structure that is shared across the plurality of components; launching, by the application, the second component in response to determining that an interaction has been performed using the first component; and configuring a second state of the second component based on the interaction that has been performed using the first component.
9. The method of claim 8, further comprising: determining that a particular interaction has been performed using the first component comprising at least one of a web-based application, a map application, or an avatar application; determining that the particular interaction performed using the first component corresponds to a given condition associated with an AR experience; and in response to determining that the particular interaction performed using the first component corresponds to the given condition associated with an AR experience, launching the second component comprising the AR experience.
10. The method of claim 8, wherein determining that the interaction has been performed using the first component comprises: determining that input has been received from a user corresponding to a specified gesture; and executing, by the first component, a call to action operation associated with the second component to launch the second component.
11. The method of claim 10, further comprising: in response to determining that the input has been received corresponding to the specified gesture, displaying by the first component a prompt with an

option to execute the call to action operation; and receiving a second input that selects the option to execute the call to action operation.

12. The method of claim 10, wherein determining that the interaction has been performed using the first component comprises: determining that a goal has been reached during use of the first component; and in response to determining that the goal has been reached, automatically executing, by the first component, a call to action operation associated with the second component to launch the second component.

13. The method of claim 1, further comprising: replacing a display of the first component with a display of the second component in response to launching the second component.

14. The method of claim 13, further comprising: detecting a specified interaction performed using the second component; updating the data structure to represent a current state of the second component, and re-accessing the first component based on the updated data structure in response to detecting the specified interaction performed using the second component, wherein the display of the second component is replaced with the display of the first component after the first component is re-accessed.

15. The method of claim 13, further comprising: detecting a specified interaction performed using the second component, updating the data structure to represent a current state of the second component; and launching, by the second component, a third component of the plurality of components based on the updated data structure in response to detecting the specified interaction performed using the second component, wherein the display of the second component is replaced with a display of the third component after the third component is launched.

16. The method of claim 1, further comprising: presenting, by the first component, a first AR element comprising a virtual device; and in response to receiving input by the application to unlock the virtual device, causing the second component comprising a web-based application to present a keypad.

17. The method of claim 16, further comprising: receiving, by the web-based application, a request for a passcode hint; and in response to receiving the request for the passcode hint, causing the application to present one or more elements representing the passcode hint.

18. The method of claim 17, further comprising: receiving, by the web-based application, interaction with the keypad comprising a correct passcode associated with a passcode hint represented by the application; and enabling, by the web-based application, a user to interact with the virtual device in response to receiving the interaction with the keypad.

19. A system comprising: at least one processor; and a memory component having instructions stored thereon that, when executed by the at least one processor, cause the at least one processor to perform operations comprising: accessing, by a device associated with an application developer, an application development platform; receiving, via the application development platform, input that defines a set of events associated with an application comprising a first component that controls launching of a second component; defining, by the application development platform, a data structure that is shared across a plurality of components comprising the first and second components, the data structure comprising the set of events associated with the first component that control when one or more parameters of the first component are passed to the second component and which of the one or more parameters are passed to the second component; and storing the application and the data structure in a library accessible to a user device.

20. A non-transitory computer-readable storage medium having stored thereon instructions that, when executed by at least one processor, cause the at least one processor to perform operations comprising: accessing, by a device associated with an application developer, an application development platform; receiving, via the application development platform, input that defines a set of events associated with an application comprising a first component that controls launching of a second component; defining, by the application development platform, a data structure that is shared across a plurality of components comprising the first and second components, the data

structure comprising the set of events associated with the first component that control when one or more parameters of the first component are passed to the second component and which of the one or more parameters are passed to the second component; and storing the application and the data structure in a library accessible to a user device.
