

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12389158
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Li; Guangpeng et al.

Speaker module and electronic device

Abstract

A speaker module includes a device casing, a speaker, a fixing structure, and a cushion unit. The fixing structure includes first, second and third fixing parts. The first fixing part is fixedly disposed on the device casing. The second fixing part is fixedly connected with the speaker. The cushion unit includes a cushion body and a plurality of positioning protrusions. The cushion body has a through hole, a first end surface, and a second end surface opposite to the first end surface. The positioning protrusions are disposed on the second end surface. Therein, the cushion body prevents the first fixing part and the second fixing part from directly touching each other. An electronic device has the above speaker module.

Inventors: Li; Guangpeng (Suzhou, CN), Hao; Wenguang (Suzhou, CN)

Applicant: QISDA (SUZHOU) CO., Ltd. (Suzhou, CN); QISDA OPTRONICS (SUZHOU) CO., LTD. (Suzhou, CN)

Family ID: 87012095

Assignee: QISDA (SUZHOU) CO., Ltd. (Suzhou, CN); QISDA OPTRONICS (SUZHOU) CO., LTD. (Suzhou, CN)

Appl. No.: 18/218609

Filed: July 06, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240348973 A1	Oct. 17, 2024

Foreign Application Priority Data

CN	202310396884.6	Apr. 14, 2023
----	----------------	---------------

Publication Classification

Int. Cl.: H04R1/28 (20060101); H04R1/02 (20060101)

U.S. Cl.:

CPC H04R1/2896 (20130101); H04R1/025 (20130101); H04R1/028 (20130101); H04R2400/11 (20130101)

Field of Classification Search

CPC: H04R (1/2896); H04R (1/025); H04R (1/028); H04R (1/02); H04R (2400/11); H04R (2499/11); H04R (2499/15); H04R (9/06)

USPC: 381/332; 381/333; 381/334; 381/87

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2021/0176559	12/2020	Shen	N/A	H04R 1/026

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
202023106523	12/2023	DE	F16F 1/3732

Primary Examiner: Matar; Ahmad F.

Assistant Examiner: Diaz; Sabrina

Background/Summary

BACKGROUND OF THE INVENTION

1. Field of the Invention

(1) The present invention relates to an electronic device, and more particularly to a speaker module and an electronic device therewith.

2. Description of the Prior Art

(2) Common electronic devices can play sound through speakers (such as speakers, stereos, etc.). With the advancement of technology, today's consumers pay more and more attention to the quality and enjoyment of life, and have higher and higher requirements for the sound quality of the speakers. Taking projectors as an example, as consumers have higher and higher requirements for the quality of electronic products, projectors are gradually adding speakers with good sound quality. The size of the speakers is getting bigger and bigger, and the amplitude is also getting higher and higher. As a result, upgrading the projector with the rest of the components unchanged will cause a series of adverse reactions, such as resonance causing picture jitter. Take a notebook as an example, because the speaker (or horn) will vibrate when it makes a sound, the vibration will be transmitted to other parts of the device through the casing. The device contains a mechanical hard disk and an optical drive, both with motors. When the speaker vibrates and sounds, it may resonate

with the hard disk and the optical drive, causing problems with the readings of the hard disk and the optical drive, which affects the operation of the programs.

(3) At present, the most common way is to install the speaker on the device casing through a silicone sleeve. However, this way cannot completely isolate the transmission of vibration. Especially with the increase of the power of the speaker unit, the improvement of the sound effect, and the enhancement of the bass sound effect, the effect of the traditional cushioning sleeve design on reducing vibration is not significant.

SUMMARY OF THE INVENTION

(4) In view of the above problems, the present invention is to provide a speaker module and an electronic device, which can effectively reduce the amount of vibration transmitted from the speaker to the device casing, thereby avoiding problems such as resonance or image jitter.

(5) To achieve the above purpose, the present invention is to provide a speaker module. The speaker module includes a device casing and a speaker. The speaker module also includes a fixing structure and a cushion unit. The fixing structure includes a first fixing part, a second fixing part, and a third fixing part. The first fixing part is fixedly disposed on the device casing. The second fixing part is fixedly connected with the speaker. The cushion unit includes a cushion body and a plurality of positioning protrusions. The cushion body has a through hole, a first end surface, and a second end surface opposite to the first end surface. The through hole runs through from the first end surface to the second end surface. The positioning protrusions are disposed on the second end surface. Therein, the speaker is fixedly connected to the cushion body through the second fixing part. The third fixing part passes through the through hole along a first direction from the first end surface to connect with the first fixing part. The second end surface laps a third end surface of the first fixing part. A space is formed between the positioning protrusions. The space encloses the first fixing part to limit the first fixing part in a radial direction perpendicular to the first direction. The third end surface of the first fixing part faces the second end surface of the cushion body. The cushion body blocks direct contact between the first fixing part and the second fixing part.

(6) As an optional technical solution, a height of each positioning protrusion is less than a height of the first fixing part.

(7) As an optional technical solution, the third fixing part includes an abutting portion, a middle portion, and a fixing portion connected in sequence. The third fixing part passes through the through hole to be detachably connected with the first fixing part. The abutting portion is against the first end surface of the cushion body. There is a gap between the middle portion and an inner wall of the cushion body.

(8) As an optional technical solution, a diameter of the fixing portion is less than a diameter of the middle portion. The third fixing part is detachably connected to the first fixing part through the fixing portion.

(9) As an optional technical solution, an inwardly-protruding structure is formed along the radial direction on the inner wall of the cushion body near the second end surface. A first vertical projection of the middle portion on the third end surface is located inside a second vertical projection of an inner wall of the inwardly-protruding structure on the third end surface. There is no contact or overlap between the first vertical projection and the second vertical projection.

(10) As an optional technical solution, an axial direction of the through hole is perpendicular to a sound output direction of the speaker and is parallel to the first direction.

(11) As an optional technical solution, the positioning protrusions are evenly spaced in a circumferential direction of the second end surface. The positioning protrusions are elastic.

(12) As an optional technical solution, the second fixing part has an installation hole. An annular connection groove is formed on an outer periphery of the cushion body. The cushion body is disposed in the installation hole through the annular connection groove.

(13) As an optional technical solution, a first area of the through hole near the second end surface has a first hole diameter. An outer diameter of the third end surface of the first fixing part is greater

than the first hole diameter of the through hole.

(14) The present invention is also to provide an electronic device. The electronic device the speaker module as described above.

(15) Compared with the prior art, through the special structural design, the present invention uses the cooperation between the cushion unit and the fixing structure to ensure that the hole of the cushion unit is centered. Besides, since the cushion body of the cushion unit is placed flat on the third end surface of the first fixing part, the problems such as resonance or image jitter caused by the speaker shifting and touching the first fixing part in the vibration can be effectively avoided. Moreover, the speaker module of the present invention has the advantages of simple structure, easy assembly and low cost.

(16) These and other objectives of the present invention will no doubt become obvious to those of ordinary skill in the art after reading the following detailed description of the preferred embodiment that is illustrated in the various figures and drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a schematic diagram illustrating an electronic device of an embodiment according to the invention.

(2) FIG. 2 is a sectional view along the line AA in FIG. 1.

(3) FIG. 3 is an enlarged view of the area B in FIG. 2.

(4) FIG. 4 is an enlarged view of the area C in FIG. 3.

(5) FIG. 5 is a schematic diagram illustrating a cushion unit of an embodiment according to the invention.

DETAILED DESCRIPTION

(6) In the following description, it should be noted that the technical terms such as “center”, “upper”, “lower”, “left”, “right”, “vertical”, “horizontal”, “inner”, “outer”, etc. that indicate orientations or positional relationships are based on the orientations or positional relationships shown in the figures. These terms are only used for the convenience of describing the present invention and simplifying the description, rather than indicating or implying that the referred device or element referred to must have a specific orientation, be constructed and operated in a specific orientation. Therefore, they should not be construed as limiting the present invention.

(7) Please refer to FIG. 1 to FIG. 4. FIG. 1 is a schematic diagram illustrating an electronic device of an embodiment according to the invention. FIG. 2 is a sectional view along the line AA in FIG. 1. FIG. 3 is an enlarged view of the area B in FIG. 2. FIG. 4 is an enlarged view of the area C in FIG. 3. FIG. 5 is a schematic diagram illustrating a cushion unit of an embodiment according to the invention. An electronic device according to the present invention is provided. The electronic device has a speaker module 1 as described in the following. The speaker module 1 includes a device casing 10 and a speaker 20. The device casing 10 is a casing of the electronic device. Therein, the electronic device may be, for example but not limited to, a personal computer, a notebook computer, a stereo, a projector, a display, etc., which can emit sound through the speaker module 1. The number of speaker modules 1 installed in the electronic device can be determined according to actual usage requirements. As shown by FIG. 1, in the embodiment, one speaker module 1 is arranged on opposite sides of the electronic device. The speaker 20 is fixed on the device casing 10 by using the cooperation of a fixing structure with a cushion unit on both sides of each speaker module 1.

(8) Therein, the speaker module 1 also includes a fixing structure and a cushion unit 14. The fixing structure includes a first fixing part 11, a second fixing part 12, and a third fixing part 13. The first fixing part 11 is fixedly disposed on the device casing 10. The second fixing part 12 is fixedly

connected with the speaker **20**. The cushion unit **14** includes a cushion body **15** and a plurality of positioning protrusions **16**. The cushion body **15** has a through hole **151**, a first end surface **152**, and a second end surface **153** opposite to the first end surface **152**. The through hole **151** runs through from the first end surface **152** to the second end surface **153**. The positioning protrusions **16** are disposed on the second end surface **153**.

(9) Therein, the speaker **20** is fixedly connected to the cushion body **15** through the second fixing part **12**. The third fixing part **13** passes through the through hole **151** along a first direction **D1** from the first end surface **152** to detachably connect with the first fixing part **11**. The second end surface **153** laps a third end surface **111** of the first fixing part **11**. A space is formed between the positioning protrusions **16**. The space encloses the first fixing part **11**; that is, the positioning protrusion **16** surround an outer periphery **112** of the first fixing part **11**, for limiting the movement of the first fixing part **11** in a radial direction **D3** (as shown in FIG. 3) perpendicular to the first direction **D1**. The third end surface **111** of the first fixing part **11** faces the second end surface **153** of the cushion body **15**. Thereby, the cushion body **15** can effectively blocks direct contact between the first fixing part **11** and the second fixing part **12**. Moreover, according to the actual application situation, the positioning protrusions **16** can be configured to be close enough to the first fixing part **11** or keep a certain distance from the first fixing part **11**, so as to better perform the limiting and fixing and not affect the cushion body **15** to effectively block direct contact between the fixing part **11** and the second fixing part **12**.

(10) Besides, in the embodiment, as shown by FIG. 2, a sound output direction **D2** of the speaker **20** is perpendicular to an axial direction of the through hole **151**. The first direction **D1** is parallel to the axial direction of the through hole **151**. In actual applications, the sound output direction **D2** of the speaker **20** often corresponds to the opening orientation of the speaker or stereo in the electronic device. In general, the sound output direction **D2** of the speaker **20** is the vibration direction of the speaker diaphragm.

(11) In addition, the number of the positioning protrusions **16** is preferably determined to limit the first fixing part **11**; for example, it can be 5 or 6. Specifically, the number can be determined according to actual conditions. Furthermore, preferably, a height of each positioning protrusion **16** is less than a height of the first fixing part **11** protruding from the device casing **10**; that is, as shown by FIG. 3, after the fixing structure is assembled with the cushion unit **14**, there is a gap **17** between the positioning protrusions **16** and the device casing **10**, which shows that the positioning protrusions **16** will not directly touch the device casing **10** in the first direction **D1** (i.e. the axial direction). This is because in this embodiment, the positioning protrusions **16** play the role of positioning the first fixing part **11**, and the positioning protrusions **16** will not directly touch the device casing **10** (including the first fixing part **11**). So, even if the speaker **20** vibrates, the vibration will not be transmitted to the device casing **10** via the positioning protrusions **16**. In addition, preferably, the positioning protrusions **16** are evenly spaced in a circumferential direction of the second end surface **153**, so that the first fixing part **11** can be more firmly limited. Moreover, preferably, the positioning protrusion **16** may be, for example, elastic positioning protrusions.

(12) In the embodiment, the first fixing part **11** may be, for example, integrated with the device casing **10** to form a one-piece structure. However, the present invention is not limited thereto. In other embodiments, the first fixing part **11** can also be fixed on the device casing **10** by other fixing parts.

(13) In addition, the second fixing part **12** may be a portion extended from the speaker **20**, or may be fixed on the speaker **20** through other fixing parts. Moreover, the second fixing part **12** also has an installation hole; correspondingly, an annular connection groove **154** (as shown in FIG. 5) is formed on an outer periphery of the cushion body **15**. The cushion body **15** is disposed in the installation hole by the annular connection groove **154**.

(14) Besides, preferably, in order to have a cushioning effect, the cushion unit **14** can be made of, for example, silicone, rubber or foam, or other elastic materials.

(15) Please continue to refer to FIG. 3. In the embodiment, the third fixing part 13 includes an abutting portion 131, a middle portion 132, and a fixing portion 133 connected in sequence. The third fixing part 13 passes through the through hole 151 to be detachably connected with the first fixing part 11. The abutting portion 131 is against the first end surface 152 of the cushion body 15. There is a gap 18 between the middle portion 132 and an inner wall 156 of the cushion body 15. The fixing portion 133 is detachably connected to the first fixing part 11. Specifically, the third fixing part 13 is, for example, a step screw. The fixing portion 133 has a threaded structure. A corresponding center portion of the first fixing part 11 has an installation hole 113. The installation hole 113 is provided with a threaded structure for screwing with the threaded structure of the fixing portion 133. Moreover, since the gap 18 exists between the middle portion 132 and the inner wall 156 of the cushion body 15, that is, the third fixing part 13 will not directly touch the inner wall 156 of the cushion body 15 of the cushion unit 14, so the vibration of the speaker 20 will be reduced or prevented from being transmitted to the device casing 10 through the third fixing part 13 as much as possible. Besides, a diameter of the fixing portion 133 is less than a diameter of the middle portion 132, so that as long as the fixing portion 133 is fixedly connected with the first fixing part 11, the hole of the cushion unit 14 can be kept centered.

(16) In addition, a first area 155 of the through hole 151 near the second end surface 153 (in which the first area 155 is actually a portion of the through hole 151) has a first hole diameter. An outer diameter of the third end surface 111 of the first fixing part 11 is greater than the first hole diameter of the through hole 151. In other words, a vertical projection of an inner wall of the first area 155 forming the through hole 151 on the third end surface 111 of the first fixing part 11 is located within the third end surface 111. Further, as shown by FIG. 3, an inwardly-protruding structure 157 is formed along the radial direction D3 on the inner wall 156 of the cushion body 15 near the second end surface 153. The inwardly-protruding structure 157 is disposed near the second end surface 153 and defines the first area 155; that is, the inner diameter of the inwardly-protruding structure 157 is the first hole diameter of the first area 155. Moreover, in the embodiment, the gap 18 exists between the middle portion 132 of the third fixing part 13 and the inner wall 156 of the cushion body 15; similarly, there is a gap between the inner wall of the inwardly-protruding structure 157 and the middle portion 132. In other words, a first vertical projection of the middle portion 132 on the third end surface 111 is located inside a second vertical projection of the inner wall of the inwardly-protruding structure 157 on the third end surface 111. There is no contact or overlap between the first vertical projection and the second vertical projection. Please continue to refer to FIG. 3. The first hole diameter of the first area 155 is less than the outer diameter of the third end surface 111, which ensures that the second end surface 153 of the cushion body 15 can be placed flat on the third end surface 111 of first fixing part 11. Besides, the gap 18 exists between the middle portion 132 of the third fixing part 13 and the inner wall 156 of the cushion body 15, and the sound output direction of the speaker 20 is perpendicular to the axial direction of the through hole 151. Such configuration prevents the speaker 20 from directly interacting with the first fixing part 11 in the vibration direction of the speaker diaphragm, so that the problems can be effectively avoided that resonance or image jitter caused by the speaker 20 shifting and touching the first fixing part 11 in the vibration.

(17) Please continue to refer to FIG. 4. After the third fixing part 13 is assembled with the first fixing part 11, starting from the middle portion 132, along the radial direction D3, there are the middle portion 132, the inwardly-protruding structure 157 and the second fixing part 12 in sequence. Since there are gaps between the middle portion 132 and the inwardly-protruding structure 157 and between the middle portion 132 and the inner wall 156 of the cushion body 15, the vibration of the speaker 20 will not be directly transmitted to the first fixing part 11, but will be transmitted to the cushion body 15 through the second fixing part 12 and be absorbed by the cushion body 15 first. Moreover, starting from the fixing portion 133, along the radial direction D3, there are the fixing portion 133, the first fixing portion 11, the positioning protrusion 16, and the

second fixing part **12** in sequence. The cushion body **15** laps the third end surface **111** of the first fixing part **11**, so that the first fixing part **11** can achieve the precise positioning and centering through the positioning protrusions **16**, and the positioning protrusions **16** connected to the second end surface of the cushion body **15** will not be completely in close contact with the first fixing part **11**. Thereby, the cushion body **15** can effectively block direct contact between the first fixing part **11** and the second fixing part **12** in the radial direction **D3**, improving the cushioning effect.

(18) That is, in the speaker module **1** of the present invention, through the above configuration, the cushion body **15** of the cushion unit **14** is limited between the abutting portion **131** of the third fixing part **13** and the third end surface **111** of the first fixing part **11**, the first fixing part **11** is limited between the positioning protrusions **16** on the cushion unit **14**, there is no direct contact between the cushion body **15** and the fixing portion **133** and the middle portion **132** of the third fixing part **13**, and the positioning protrusions **16** on cushion unit **14** are not in direct contact with the device casing **10**, so that the vibration generated by the speaker **20** will not be directly transmitted to the device casing **10**, but will be mostly absorbed by the cushion unit **14** while the probability of the vibration being transmitted to the device casing **10** will be reduced.

(19) As discussed above, through the special structural design, the present invention uses the cooperation between the cushion unit and the fixing structure to ensure that the hole of the cushion unit is centered. Besides, since the cushion body of the cushion unit is placed flat on the third end surface of the first fixing part, the problems such as resonance or image jitter caused by the speaker shifting and touching the first fixing part in the vibration can be effectively avoided. Moreover, the speaker module of the present invention has the advantages of simple structure, easy assembly and low cost.

(20) Those skilled in the art will readily observe that numerous modifications and alterations of the device and method may be made while retaining the teachings of the invention. Accordingly, the above disclosure should be construed as limited only by the metes and bounds of the appended claims.

Claims

1. A speaker module, comprising: a device casing; a speaker; a fixing structure, the fixing structure comprising a first fixing part, a second fixing part, and a third fixing part, the first fixing part being fixedly disposed on the device casing, the second fixing part being fixedly connected with the speaker; and a cushion unit, the cushion unit comprising a cushion body and a plurality of positioning protrusions, the cushion body having a through hole, a first end surface, and a second end surface opposite to the first end surface, the through hole running through from the first end surface to the second end surface, the positioning protrusions being disposed on the second end surface; wherein the speaker is fixedly connected to the cushion body through the second fixing part, the third fixing part passes through the through hole along a first direction from the first end surface to connect with the first fixing part, the second end surface laps a third end surface of the first fixing part, a space is formed between the positioning protrusions, the space encloses the first fixing part to limit the first fixing part in a radial direction perpendicular to the first direction, the third end surface of the first fixing part faces the second end surface of the cushion body, and the cushion body blocks direct contact between the first fixing part and the second fixing part; wherein an inwardly-protruding structure is formed along the radial direction on an inner wall of the cushion body near the second end surface, a first vertical projection of a portion of the third fixing part located in the through hole on the third end surface is located inside a second vertical projection of an inner wall of the inwardly-protruding structure on the third end surface, and there is no contact or overlap between the first vertical projection and the second vertical projection.

2. The speaker module according to claim 1, wherein a height of each positioning protrusion is less than a height of the first fixing part.

3. The speaker module according to claim 1, wherein the third fixing part comprises an abutting portion, a middle portion, and a fixing portion connected in sequence, the third fixing part passes through the through hole to be detachably connected with the first fixing part, the abutting portion is against the first end surface of the cushion body, and there is a gap between the middle portion and the inner wall of the cushion body.
4. The speaker module according to claim 3, wherein a diameter of the fixing portion is less than a diameter of the middle portion, and the third fixing part is detachably connected to the first fixing part through the fixing portion.
5. The speaker module according to claim 1, wherein an axial direction of the through hole is perpendicular to a sound output direction of the speaker and is parallel to the first direction.
6. The speaker module according to claim 1, wherein the positioning protrusions are evenly spaced in a circumferential direction of the second end surface, and the positioning protrusions are elastic.
7. The speaker module according to claim 1, wherein the second fixing part has an installation hole, an annular connection groove is formed on an outer periphery of the cushion body, and the cushion body is disposed in the installation hole through the annular connection groove.
8. The speaker module according to claim 1, wherein a first area of the through hole near the second end surface has a first hole diameter, and an outer diameter of the third end surface of the first fixing part is greater than the first hole diameter of the through hole.
9. An electronic device comprising: a speaker module, comprising: a device casing; a speaker; a fixing structure, the fixing structure comprising a first fixing part, a second fixing part, and a third fixing part, the first fixing part being fixedly disposed on the device casing, the second fixing part being fixedly connected with the speaker; and a cushion unit, the cushion unit comprising a cushion body and a plurality of positioning protrusions, the cushion body having a through hole, a first end surface, and a second end surface opposite to the first end surface, the through hole running through from the first end surface to the second end surface, the positioning protrusions being disposed on the second end surface; wherein the speaker is fixedly connected to the cushion body through the second fixing part, the third fixing part passes through the through hole along a first direction from the first end surface to connect with the first fixing part, the second end surface laps a third end surface of the first fixing part, a space is formed between the positioning protrusions, the space encloses the first fixing part to limit the first fixing part in a radial direction perpendicular to the first direction, the third end surface of the first fixing part faces the second end surface of the cushion body, and the cushion body blocks direct contact between the first fixing part and the second fixing part; wherein an inwardly-protruding structure is formed along the radial direction on an inner wall of the cushion body near the second end surface, a first vertical projection of a portion of the third fixing part located in the through hole on the third end surface is located inside a second vertical projection of an inner wall of the inwardly-protruding structure on the third end surface, and there is no contact or overlap between the first vertical projection and the second vertical projection.
10. The electronic device according to claim 9, wherein a height of each positioning protrusion is less than a height of the first fixing part.
11. The electronic device according to claim 9, wherein the third fixing part comprises an abutting portion, a middle portion, and a fixing portion connected in sequence, the third fixing part passes through the through hole to be detachably connected with the first fixing part, the abutting portion is against the first end surface of the cushion body, and there is a gap between the middle portion and the inner wall of the cushion body.
12. The electronic device according to claim 11, wherein a diameter of the fixing portion is less than a diameter of the middle portion, and the third fixing part is detachably connected to the first fixing part through the fixing portion.
13. The electronic device according to claim 9, wherein an axial direction of the through hole is perpendicular to a sound output direction of the speaker and is parallel to the first direction.

14. The electronic device according to claim 9, wherein the positioning protrusions are evenly spaced in a circumferential direction of the second end surface, and the positioning protrusions are elastic.

15. The electronic device according to claim 9, wherein the second fixing part has an installation hole, an annular connection groove is formed on an outer periphery of the cushion body, and the cushion body is disposed in the installation hole through the annular connection groove.

16. The electronic device according to claim 9, wherein a first area of the through hole near the second end surface has a first hole diameter, and an outer diameter of the third end surface of the first fixing part is greater than the first hole diameter of the through hole.
