

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12385576
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Al Essa; Abdulrahman Anwar

Smart back pressure valve and methods of use

Abstract

A smart back pressure valve includes a valve body having opposing upper and lower ends, and a pressure testing system extending from the lower end of the valve body and including a pressure housing defining an interior at least partially filled with a compressible fluid, a piston axially translatable within the interior and including a piston head, and a piston rod extending distally from the piston head, a motor operatively coupled to the piston rod and operable to drive the piston toward and away from the valve body, and a pressure gauge assembly that monitors a pressure within the interior. As the motor advances within the interior, the compressible fluid is compressed and increases the pressure within the interior. When the pressure gauge assembly reports that the pressure remains stable after a predetermined time interval, that is a positive indication that the valve body properly holds pressure.

Inventors:	Al Essa; Abdulrahman Anwar (Dammam, SA)
Applicant:	SAUDI ARABIAN OIL COMPANY (Dhahran, SA)
Family ID:	93293198
Assignee:	SAUDI ARABIAN OIL COMPANY (Dhahran, SA)
Appl. No.:	18/310576
Filed:	May 02, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240369157 A1	Nov. 07, 2024

Publication Classification

Int. Cl.: G01M3/28 (20060101); F16K37/00 (20060101)

U.S. Cl.:

CPC **F16K37/0091** (20130101); **G01M3/2876** (20130101);

Field of Classification Search

CPC: G01M (3/2876); F16K (37/0091)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4274438	12/1980	La Coste	91/1	G01L 5/0061
4766765	12/1987	Ezekoye	73/1.72	G01M 3/2876
5174321	12/1991	Danzy	137/489	F16K 37/0091
5856615	12/1998	Easter	73/1.72	F16K 37/0091
7146844	12/2005	Hyme	73/1.72	F15B 19/002
8539976	12/2012	Rodgers, Jr.	137/512	F16K 15/066
2021/0341078	12/2020	Kalyanasundaram	N/A	F16K 17/087
2024/0318745	12/2023	Stokke	N/A	G01M 3/2876

Primary Examiner: Mercado; Alexander A

Attorney, Agent or Firm: Vorys, Sater, Seymour and Pease LLP

Background/Summary

FIELD OF THE DISCLOSURE

(1) The present disclosure relates generally to oil and gas tubing valves and, more particularly, to a smart back pressure valve for post-installation wellhead pressure testing.

BACKGROUND OF THE DISCLOSURE

(2) Throughout the lifetime of an oil and gas well, proper sealing and pressure isolation equipment is required to prevent undesirable fluid flow out of the system, including oil, gas, injection fluids, and formation water. One common mechanical barrier utilized in sealing the wellhead of an oil and gas well is a back pressure valve, which is typically secured within a tubing hanger arranged within a tubing head adapter, which forms part of the wellhead. A production tree (alternately referred to as a “Christmas tree”) is commonly attached to the top of the tubing head adapter to control flow into and out of the wellbore.

(3) The back pressure valve operates as a one-way check valve designed to isolate well pressure from below while enabling at least a small amount of fluid flow from above; i.e., from the Christmas tree. Conventional back pressure valves, however, are not able to be pressure tested from below following installation since there are typically no pump inlets to pressure test from the tubing-casing annulus. Pressure testing after installation may enable confirmation of proper installation and operation of the back pressure valve to prevent upward flow from within the wellbore. Therefore, without the ability to pressure test a back pressure valve after installation, the back pressure valve may not be used with confidence in a live well.

(4) Accordingly, a back pressure valve which can be pressure-tested once installed within a tubing

hanger and wellhead is desirable.

SUMMARY OF THE DISCLOSURE

(5) Various details of the present disclosure are hereinafter summarized to provide a basic understanding. This summary is not an exhaustive overview of the disclosure and is neither intended to identify certain elements of the disclosure, nor to delineate the scope thereof. Rather, the primary purpose of this summary is to present some concepts of the disclosure in a simplified form prior to the more detailed description that is presented hereinafter.

(6) According to an embodiment in accordance with the present disclosure, a smart back pressure valve includes a valve body having opposing upper and lower ends, and a pressure testing system extending from the lower end of the valve body and including a pressure housing defining an interior at least partially filled with a compressible fluid, a piston axially translatable within the interior and including a piston head, and a piston rod extending distally from the piston head, a motor operatively coupled to the piston rod and operable to drive the piston toward and away from the valve body, and a pressure gauge assembly that monitors a pressure within the interior. As the motor advances within the interior, the compressible fluid is compressed and increases the pressure within the interior. When the pressure gauge assembly reports that the pressure remains stable after a predetermined time interval, that is a positive indication that the valve body properly holds pressure.

(7) In a further embodiment, a method of testing a back pressure valve includes installing the back pressure valve in a tubing hanger of a wellhead, the back pressure valve including a valve body having opposing upper and lower ends, and a pressure testing system extending from the lower end of the valve body, the pressure testing system providing a pressure housing defining an interior at least partially filled with a compressible fluid, a piston axially translatable within the interior and including a piston head that forms a seal against an inner wall of the pressure housing, and a piston rod extending distally from the piston head, a motor operatively coupled to the piston rod, and a pressure gauge assembly. The method further includes operating the motor and thereby driving the piston toward the valve body, compressing the compressible fluid within the interior as the piston moves toward the valve body, monitoring and reporting a pressure within the interior with the pressure gauge assembly, and providing a positive indication that the valve body properly holds pressure when the pressure gauge assembly reports that the pressure remains stable after a predetermined time interval.

(8) Any combinations of the various embodiments and implementations disclosed herein can be used in a further embodiment, consistent with the disclosure. These and other aspects and features can be appreciated from the following description of certain embodiments presented herein in accordance with the disclosure and the accompanying drawings and claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1A is a cross-sectional side view of an example tubing hanger.

(2) FIG. 1B is a cross-sectional side view of an example tubing hanger with a pressure valve installed.

(3) FIG. 2 is a cross-sectional side view of a smart back pressure valve, according to one or more embodiments of the present disclosure.

(4) FIG. 3 is a cross-sectional side view of the smart back pressure valve following pressure testing and during operation, according to one or more embodiments of the present disclosure.

(5) FIG. 4 is an example wellhead that may incorporate the principles of the present disclosure.

(6) FIG. 5 is a schematic flowchart of an example method for installing and testing a back pressure valve within a tubing hanger of a wellhead.

DETAILED DESCRIPTION

(7) Embodiments of the present disclosure will now be described in detail with reference to the accompanying Figures. Like elements in the various figures may be denoted by like reference numerals for consistency. Further, in the following detailed description of embodiments of the present disclosure, numerous specific details are set forth in order to provide a more thorough understanding of the claimed subject matter. However, it will be apparent to one of ordinary skill in the art that the embodiments disclosed herein may be practiced without these specific details. In other instances, well-known features have not been described in detail to avoid unnecessarily complicating the description. Additionally, it will be apparent to one of ordinary skill in the art that the scale of the elements presented in the accompanying Figures may vary without departing from the scope of the present disclosure.

(8) Embodiments in accordance with the present disclosure generally relate to oil and gas tubing valves and, more particularly, to smart back pressure valves capable of post-installation wellhead pressure testing. The disclosed embodiments may enable pressure testing of a back pressure valve while installed within a tubing hanger and corresponding wellhead without the need for additional equipment, flow paths, or modifications to the existing wellhead infrastructure. The smart back pressure valves described herein may enable remote actuation of pressure testing, as well as remote monitoring of one or more integrated pressure gauges. The smart back pressure valves described herein may further include actuatable, deformable, or shearable components to enable downward flow past the pressure testing apparatus following confirmation of correct installation. As such, the pressure testing apparatus may remain in place or be subsequently removed without interrupting operation of the back pressure valve and wellhead system.

(9) FIG. 1A is a cross-sectional side view of an example tubing hanger **100**, which may be used in accordance with the principles of the present disclosure. The tubing hanger **100** may include a solid, elongate body **102** having a first or “uphole” end **104a** and a second or “downhole” end **104b** opposite the uphole end **104a**. An interior channel **106** is defined within the body **102** and extends between the uphole and downhole ends **104a,b**. The tubing hanger **100** may be installed within a tubing head adapter (not shown) that forms part of a wellhead (not shown), and a production tree (or “Christmas tree”) may be secured atop the tubing head adapter.

(10) The tubing hanger **100** may include or define a landing joint profile **108** within the interior channel **106** at or near the uphole end **104a**. The landing joint profile **108** provides a landing shoulder and threaded interface used to attach, or latch to, a running tool in order to run a tubing string during the drilling or completion running phases of the well's operational life. The tubing hanger **100** may also include or define a tubing profile **110** within the interior channel **106** at or near the downhole end **104b**. The tubing profile **110** may be configured to mate with or otherwise couple to tubing extending below, such as production tubing. In some embodiments, the tubing profile **110** includes tapered threads for mating with the tubing. In alternate embodiments, an adapter pipe may be utilized for connection between the tubing profile **110** and the tubing.

(11) The tubing hanger **100** may further include or define a back pressure valve profile **112** within the interior channel **106** at a location between the uphole and downhole ends **104a,b**. The back pressure valve profile **112** is configured to receive and mate with a back pressure valve operable to control fluid flow through the tubing hanger **100**. As illustrated, the back pressure valve profile **112** may include or define a landing shoulder **114** and internal threads **116**. The landing shoulder **114** may be configured to receive an opposing shoulder provided on the back pressure valve, and the internal threads **116** may be configured to threadably mate with external threads provided on the exterior of the back pressure valve.

(12) The back pressure valve profile **112** may be used to receive and mate with traditional or conventional back pressure valves commonly used in oil and gas wellhead installations. As described herein, however, the back pressure valve profile **112** may also be used to receive and mate with a smart back pressure valve. Accordingly, in at least one embodiment, the tubing hanger

100 may comprise a traditional or conventional tubing hanger **100** forming part of a traditional or conventional wellhead, but is capable of accommodating the embodiments of the smart back pressure valves described herein.

(13) FIG. 1B is a cross-sectional side view of the tubing hanger **100** with a prior art or conventional back pressure valve **118** installed therein. As illustrated, the back pressure valve **118** may include external threads **120** configured to threadably mate with the internal threads **116** (FIG. 1A) provided by the back pressure valve profile **112**, such that the back pressure valve **118** may be retained within the interior channel **106** during fluid flow or any other applied load.

(14) The back pressure valve **118** may also include an actuatable valve element **122** operable to move between closed and open positions and thereby prevent or allow fluid flow through the back pressure valve **118**. In some applications, the actuatable valve element **122** may comprise a poppet valve that enables unidirectional flow from above while preventing back flow from below. The actuatable valve element **122** may be spring-loaded such that the back pressure valve **118** is held closed until pressure forces overcome the spring forces of the actuatable valve element **122**. More specifically, the back pressure valve **118** is oriented within the tubing hanger **100** such that the actuatable valve element **122** will compress (open) after a large enough force is applied from above the back pressure valve **118**, such that flow from above may pass through the back pressure valve **118** and through the interior channel **106**. Once the pressure above the back pressure valve **118** is reduced, the actuatable valve element **122** is naturally biased back to the closed position via spring force of the actuatable valve element **122**, thus maintaining a closed back pressure valve **118**.

(15) The inside diameter of the actuatable valve element **122** is smaller than the diameter of the interior channel **106**. Further, the valve face, or “poppet” may include an elastomer seal (not shown) which may ensure proper sealing within the body of the back pressure valve **118**.

Following installation of the back pressure valve **118** within the interior channel **106** of the tubing hanger **100**, the back pressure valve **118** may require modifications to the hanger **100**, the wellhead (not shown) or the tubing further downhole to verify proper installation and operation of the back pressure valve **118**. As installed, the back pressure valve **118** acts as a one-way barrier to flow rising from below while enabling at least a small amount of flow from above.

(16) Without any system modifications, the seal generated by the back pressure valve **118** cannot be tested or confirmed until formation fluids rise from below during active operation. In the event of errors in installation or manufacturing of the back pressure valve **118**, the one-way barrier may fail during active operation and may lead to a blowout event or equipment damage. According to embodiments of the present disclosure, conventional back pressure valves, such as the back pressure valve **118**, may be replaced with a smart back pressure valve. The smart back pressure valve may be similar in some respects to conventional back pressure valves, except the smart back pressure valve may be designed to apply fluid pressure from below to test the installation and integrity of the smart back pressure valve and thereby confirm whether a proper seal has been made.

(17) FIG. 2 is a cross-sectional side view of an example smart back pressure valve **200** according to one or more embodiments of the present disclosure. As illustrated, the smart back pressure valve **200** may define or include a valve body **202** having a first or “upper” end **204a** and a second or “lower” end **204b** opposite the upper end **204a**. A plurality of threads **206** may be defined on the exterior of the valve body **202** and extend at least partially between the upper and lower ends **204a,b**. The threads **206** may be configured to threadably mate with the internal threads **116** (FIGS. 1A-1B) provided by the back pressure valve profile **112** (FIG. 1A), such that the smart back pressure valve **200** may be retained within the interior channel **106** (FIGS. 1A-1B) during fluid flow. Accordingly, the smart back pressure valve **200** may be installed in pre-existing tubing hangers that utilize conventional back pressure valves without further modification.

(18) In some embodiments, as illustrated, the valve body **202** may house a poppet assembly **208**, which acts as a one-way barrier for the smart back pressure valve **200**. The poppet assembly **208**

may generate the one-way barrier or seal within the valve body **202** such that the flow of fluid from below (downhole from) the poppet assembly **208** is prevented. In one or more embodiments, the poppet assembly **208** may include or otherwise be mated to an actuatable valve element **210**, which may be similar to the actuatable valve element **122** of FIG. **1B**. The actuatable valve element **210** may include a coil spring **212** and may otherwise be spring-loaded such that flow from above may pass through the smart back pressure valve **200** if the pressure from above exceeds the spring force of the coil spring **212** and/or the actuatable valve element **210**.

(19) The actuatable valve element **210** may extend distally from the poppet assembly **208** or the valve body **202** and into a pressure testing system **214**, which may be mated to or otherwise form an integral extension of the valve body **202**. More specifically, the pressure testing system **214** may define or include a cylindrical pressure housing **216** extending from the lower end **204b** of the valve body **202**. In some embodiments, the pressure housing **216** may be attached to the valve body **202** at the lower end **204b**. In such embodiments, the pressure housing **216** may be attached to the valve body **202** via at least one of threading, mechanical fasteners, welding, brazing, a mechanical connection, or any combination thereof. In other embodiments, however, the pressure housing **216** may form an integral extension of the valve body **202** and extend distally therefrom. In such embodiments, the valve body **202** and the pressure housing **216** may be made of the same material.

(20) As illustrated, at least a portion of the actuatable valve element **210** may extend into an interior **218** of the pressure housing **216**. In other embodiments, however, the poppet assembly **208** and associated actuatable valve element **210** may be housed within the interior of the valve body **202**, without a departing from the scope of the disclosure.

(21) As illustrated, the pressure testing system **214** may further include a piston **220** axially translatable within the interior **218** of the pressure housing **216** and configured to pressurize the interior **218**. More specifically, the piston **220** may include a piston head **222** and a piston rod **224** extending distally from the piston head **222**. The piston head **222** may be sized to form a seal (or sealed interface) with an inner wall **226** of the pressure housing **216**. The piston rod **224** may be operatively coupled to a motor **228** that is actuatable and otherwise operable to drive the piston rod **224** towards and away from the valve body **202**.

(22) The interior **218** of the pressure housing **216** may be at least temporarily filled with a compressible fluid **230**, such as corrosion-inhibited water. When it is desired to perform a pressure test of the smart back pressure valve **200**, actuation of the motor **228** may be triggered to pressurize the interior **218** of the pressure housing **216**. When operation of the motor **228** is triggered, the motor **228** drives the piston rod **224** and the piston head **222** upwards and towards the valve body **202**, and as the piston **220** travels towards the valve body **202** the compressible fluid **230** will compress against the poppet assembly **208** from below.

(23) In some embodiments, as illustrated, the motor **228** may be communicatively coupled to a control module **232**, and the control module **232** may be configured to operate the motor **228**. In some embodiments, the control module **232** may be attached to any portion of the pressure housing **216** or the valve body **202**. In other embodiments, however, the control module **232** may be housed within a protected chamber **234** provided within or otherwise forming part of the pressure housing **216**. In at least one embodiment, the protected chamber **234** may be made of a similar material as the pressure housing **216**, but may define or include a fluid-tight (hermetically sealed) space for protection of the control module **232**. In some embodiments, the control module **232** may be physically connected to the motor **228** via a wire, but may alternatively wirelessly communicate with the motor **228** via a wireless signal.

(24) In some embodiments, the control module **232** may communicate with a remote control station or computer system (not shown) where an operator may be able to program or control operation of the control module **232**. In such embodiments, the control module **232** may communicate with the remote control station or computer system via any wired or wireless means. In other embodiments, however, the control module **232** may be configured to operate autonomously. In such

embodiments, for example, the control module **232** may include a timer programmed and otherwise set to trigger operation of the motor **228** upon expiration of a predetermined time limit. Actuating the motor **228** may advance the piston **220** and thereby pressurize the interior **218** of the pressure housing **216** when it is desired to perform a pressure test of the smart back pressure valve **200**.

(25) Once the smart back pressure valve **200** is installed in the tubing hanger **100** (FIGS. 1A-1B), the motor **228** may be actuated to pressure test the smart back pressure valve **200** from below to ensure that the valve body **202** is properly holding pressure and is properly secured within the tubing hanger **100**. To accomplish this, the pressure testing system **214** may further include a pressure gauge assembly **236** operable and otherwise configured to monitor and report the pressure within the interior **218** of the pressure housing **216**.

(26) As illustrated, the pressure gauge assembly **236** may include or define a pressure tube **238** in fluid communication with the interior **218** of the pressure housing **216**. In at least one embodiment, the pressure tube **238** may extend to the lower end **204b** of the valve body **202** to fluidly communicate with the interior **218**. The pressure tube **238** may communicate with a pressure gauge **240** secured to the valve body **202** at or near the upper end **204a**. The pressure gauge **240** may be configured to monitor and measure the pressure within the interior **218** as the piston **220** is actuated and the fluid pressure within the interior **218** increases. If the fluid pressure remains stable after a predetermined time interval, that may be a positive indication that the valve body **202** is properly holding pressure and properly secured within the tubing hanger **100** (FIGS. 1A-1B). The predetermined time interval may comprise any time interval required to sufficiently monitor the pressure within the interior **218**. Example predetermined time intervals include, but are not limited to 5 seconds, 10 seconds, 30 seconds, 1 minute, 5 minutes, 10 minutes, a half-hour, 1 hour, 24 hours, more than 24 hours, or any time interval subset between any of the foregoing intervals.

(27) In some embodiments, the pressure gauge **240** may wirelessly communicate with a remote control station or computer system operated by an operator. In such embodiments, the operator may receive real-time measurements from the pressure gauge **240**. In other embodiments, however, the pressure gauge assembly **236** may further include a port **242** defined in the valve body **202** and in communication with the pressure gauge **240**. In such embodiments, a hydraulic line **244** may be communicably coupled to the pressure gauge **240** and extend to a remote location, such as the remote control station or the computer system, and the pressure gauge **240** may be configured to communicate the real-time pressure measurements from the interior **218** to the remote control station or the computer system via the hydraulic line **244**. This may prove advantageous in being able to monitor the pressure within the interior **218** from a safe, remote distance. In at least one embodiment, the hydraulic line **244** may be extended through a “Christmas tree” of the wellhead (e.g., the Christmas tree **414** of FIG. 4) for remote pressure monitoring. In these embodiments, a running tool for installation of the smart back pressure valve **200** may further facilitate running or extension of the hydraulic line **244**. As such, the running tool may remain attached to the smart back pressure valve **200** during pressure testing for active monitoring via the hydraulic line **244**. Following pressure testing, the running tool and incorporated hydraulic line **244** may be detached from the smart back pressure valve **200** and returned to the surface.

(28) Following pressure testing, the smart back pressure valve **200** may be employed as a common back pressure valve in active operation. However, when it is desired to inject the fluid through the smart back pressure valve **200**, a flowpath between the valve body **202** and the bottom of the pressure housing **216** may need to be formed to enable injection operations. To accomplish this, in some embodiments, the motor **228** may be configured to retract the piston **220** within the pressure housing **216** until the piston head **222** advances past the bottom (downhole) end of the pressure housing **216**. Once the piston head **222** advances past the bottom end of the pressure housing **216**, a flow path around the piston **220** may be formed that allows the compressible fluid **230** within the interior **218** to drain from the interior **218**, and any fluids injected downhole through the valve body **202** may flow into the interior **218** and past the piston **220** via the newly formed flow path.

(29) In some embodiments, however, or in addition thereto, a portion of the piston **220** may be able to be opened to allow fluid flow past the piston **220**. More specifically, in some embodiments, the piston head **222** may further include a collapsible portion **246** pivotably attached to the remainder of the piston head **222**. The collapsible portion **246** may be mated to or operatively coupled with a collapsing mechanism **248**, which may pivotably couple the collapsible portion **246** to the remainder of the piston head **222**. In some embodiments, the collapsing mechanism **248** may include an electronically actuated hinge that responds to a signal from the control module **232**. In such embodiments, once the signal is received from the control module **232**, the collapsing mechanism **248** may be configured to actuate and thereby allow the collapsible portion **246** to pivot from a first or “closed” state, as shown in FIG. 2, to a second or “open” state, as shown in FIG. 3. When in the closed state, the collapsible portion **246** substantially prevents fluid flow past the piston **220** in the downhole direction. In contrast, when the collapsible portion **246** transitions to the open state, fluids are able to flow past the piston **220** in the downhole direction. However, when the collapsible portion **246** transitions to the open state, the one-way barrier is still provided by the poppet assembly **208**.

(30) In other embodiments, the control module **232** may include an internal timer programmed with a preset time limit. In such embodiments, upon expiration of the preset time limit, the collapsing mechanism **248** may be actuated to move the collapsible portion **246** from the closed state to the open state. In at least one embodiment, the preset time limit may be about 30 minutes to about one hour. However, those skilled in the art will readily appreciate that the preset time limit may be less than 30 minutes or greater than an hour without departing from the scope of this disclosure.

(31) In one or more embodiments, the collapsing mechanism **248** may comprise a pivotable hinge held in place with one or more shear pins configured to shear upon experiencing a predetermined pressure force. In such embodiments, the collapsible portion **246** may be moved from the closed state to the open state by increasing the pressure within the interior **218** through operation of the motor **228**. Once the pressure within the interior **218** reaches the predetermined pressure of the shear pins, the shear pins will shear and otherwise fail, thereby allowing the collapsible portion **246** to pivot from the closed state, as shown in FIG. 2, to the open state, as shown in FIG. 3. As will be appreciated, the pressure required to shear the shear pins will be greater than the pressure used to test the smart back pressure valve **200**, thus preventing the inadvertent or premature actuation of the collapsing mechanism **248**.

(32) In some embodiments, the smart back pressure valve **200** may further include a flapper valve **250** positioned at or near the bottom of the pressure housing **216**. The flapper valve **250** may be movable between a first or “closed” position, as shown in FIG. 2, and a second or “open” position, as shown in FIG. 3. Movement of the flapper valve **250** may be controlled or pivoted using a pivot mechanism **252** operatively coupled to the flapper valve **250**. The pivot mechanism **252** may enable pivoting of the flapper valve **250** between the closed and open positions, and thereby enable a flowpath to form through a bottom of the pressure housing **216**.

(33) In some embodiments, the pivot mechanism **252** may comprise a torsion spring configured to open the flapper valve **250** upon assuming a predetermined fluid pressure force on the flapper valve **250**. In such embodiments, the pivot mechanism **252** may include one or more shear pins configured to shear or fail upon experiencing a prescribed (predetermined) pressure force, and thereby enable the pivoting of the flapper valve **250**. In other embodiments, the pivot mechanism **252** may include an electronically actuated hinge which responds to a signal from the control module **232**. In yet other embodiments, the control module **232** may include an internal timer programmed with a preset time limit. In such embodiments, upon expiration of the present time limit, control module **232** may send a signal to the pivot mechanism **252** to actuate the lower the flapper valve **250**.

(34) Example operation of the smart back pressure valve **200** may begin with installation of the smart back pressure valve **200** within the tubing hanger **100** (FIGS. 1A-1B) via threadably mating

the plurality of threads **206** with the internal threads **116** (FIGS. 1A-1B) provided by the back pressure valve profile **112** (FIG. 1A). When it is desired to pressure test the smart back pressure valve **200**, the control module **232** may send a signal to the motor **228** to begin upward motion of the piston **220** within the interior **218** and toward the valve body **202**. The motor **228** may drive the piston **220** upward and thereby pressurize the compressible fluid **230** stored within the interior **218** of the pressure housing **216**. The increased fluid pressure within the interior **218** may exert a corresponding pressure on the underside of the poppet assembly **208** and the valve body **202**. This pressure may be measured using the pressure gauge assembly **236**, which includes the pressure gauge **240**. In at least one embodiment, the pressure gauge **240** may be omitted from the pressure gauge assembly **236**. In these embodiments, one end of the hydraulic line **244** may be connected to the port **242** and the opposing end may be attached to an external pressure gauge on the surface. The pressure gauge assembly **236** may then facilitate external pressure monitoring via the hydraulic line **244**.

(35) Following the pressure testing and confirmation of successful installation and operation under pressure, the piston **220** may be retracted within the pressure housing **216**. In some cases, the piston **220** may be retracted sufficiently within the pressure housing **216** to provide a flowpath around the piston **220**. Alternatively, or in addition thereto, the collapsible portion **246** of the piston head **222** may be pivotably collapsed via the collapsing mechanism **248**, as generally described above. Moreover, the flapper valve **250** may be pivoted to the open position, as also generally described above, thereby creating a flowpath between the valve body **202** and the remainder of the interior channel **106** (FIGS. 1A-1B) of the tubing hanger **100** (FIGS. 1A-1B). Any compressible fluid **230** may be circulated downhole, and the smart back pressure valve **200** may be ready for operation as a back pressure valve within the wellhead (not shown), enabling injection from above while preventing flow from the well below.

(36) FIG. 3 is a cross-sectional side view of the smart back pressure valve **200** following pressure testing and during operation, according to one or more embodiments of the present disclosure. More specifically, FIG. 3 depicts the smart back pressure valve **200** in a flow-through orientation following pressure testing confirmation. Accordingly, FIG. 3 shows the operational orientation of the smart back pressure valve **200** during active operation, such that a flowpath is defined through the smart back pressure valve **200** to enable injection of fluids **230** from above the valve body **202**.

(37) As illustrated, the collapsible portion **246** of the piston head **222** is pivoted downward from the closed state to the open state, thereby allowing flow of injection fluids **230** from above and past the piston **220**. While the illustrated embodiment depicts the collapsible portion **246** positioned at the bottom of the pressure housing **216**, those skilled in the art will readily appreciate that the collapsible portion **246** would enable flow past the piston head **222** while the piston **220** is positioned within the interior **218** of the pressure housing **216**.

(38) In the illustrated embodiment, the flapper valve **250** is pivoted from the closed position to the open position by the pivot mechanism **252**, thus placing the interior of the smart back pressure valve **200** in fluid communication with the remainder of the interior channel **106** (FIGS. 1A-1B) of the tubing hanger **100** (FIGS. 1A-1B). As such, the injection fluid **302** may pass through the valve body **202**, through the interior **218** of the pressure housing **216**, and past the flapper valve **250** to exit the smart back pressure valve **200** while simultaneously preventing upward flow of formation fluids (not shown) during active operation.

(39) FIG. 4 is an example wellhead **400** that may incorporate the principles of the present disclosure. While the wellhead **400** shown in FIG. 4 includes specific components, those skilled in the art will readily appreciate that the wellhead **400** may alternatively include other components or tools, without departing from the scope of the disclosure. As illustrated, the wellhead **400** includes a casing head housing **402** with a casing hanger **404** secured therein. The wellhead **400** may further include a casing head **406** secured to the top of the casing head housing **402**, and a casing hanger **408** may be secured within the casing head housing **406**. The wellhead **400** may also include a

tubing head adapter **410** secured to the top of the casing head housing **406**, and a tubing hanger **412** may be secured within the tubing adapter **410**. A production tree (or “Christmas tree”) **414** may be attached to the top of the tubing head adapter **410**, and may include a plurality of valves, such as a lower master valve **416a**, and upper master valve **416b**, and a swab valve **416c**.

(40) The tubing hanger **412** may be the same as or similar to the tubing hanger **100** of FIGS. 1A-1B. In the illustrated embodiment, the smart back pressure valve **200**, as generally described herein, is secured within the tubing hanger **412** and is able to operate as generally described above.

(41) FIG. 5 is a schematic flowchart of an example method **500** for installing and testing a back pressure valve (e.g., the smart back pressure valve **200** of FIGS. 2-3) within a tubing hanger of a wellhead. The method **500** may begin at **502** with installing a back pressure valve within a tubing hanger (e.g., the tubing hanger **100** of FIGS. 1A-1B) of a wellhead (e.g., the wellhead **400** of FIG. 4). At **504**, a motor within the back pressure valve (e.g., the motor **228** of FIG. 2) may begin operating to drive a piston (e.g., the piston **220** of FIG. 2) towards the valve body (e.g., the valve body **202** of FIG. 2). In at least one embodiment, the motor may be signaled via a control module (e.g., the control module **232** of FIG. 2) and/or a timer, as at **506**. The control module or timer may provide a signal for operation of the motor, such that the motor will only operate once conditions have been met, such as the expiration of a predetermined time interval following installation.

(42) At **508**, as the motor drives the piston towards the valve body, a compressible fluid (e.g., the compressible fluid **230** of FIG. 2) within the back pressure valve is compressed by the piston. Compression of the compressible fluid at **508** may increase pressure within the back pressure valve, and particularly within a pressure housing (e.g., the pressure housing **216** of FIG. 2) below a poppet assembly (e.g., the poppet assembly **208** of FIG. 2). As such, the integrity of the poppet assembly and back pressure valve may be tested from below while installed within the tubing hanger of the wellhead. Accordingly, at **510** a pressure is monitored and reported within the back pressure valve via a pressure gauge assembly (e.g., the pressure gauge assembly **236** of FIG. 2). In at least one embodiment of the present disclosure, at **512** a hydraulic line (e.g., the hydraulic line **244** of FIG. 2) may be coupled to the pressure gauge assembly and run to a remote location, such that monitoring and reporting of the pressure may be remotely performed.

(43) At **514**, if the monitoring and reporting of the pressure indicated an issue, the method **500** may include reporting a faulty back pressure valve or a failed installation of the back pressure valve, such that attention or maintenance may be required prior to operation. Conversely, if the monitoring and reporting of the pressure indicated no issues, the method **500** may include providing a positive indication of back pressure valve operation and installation at **516**. The positive indication of back pressure valve operation and installation at **516** may be determined following a predetermined time interval, such that operation of the back pressure valve may be confirmed after a duration under pressure. At **518**, a collapsible portion (e.g., the collapsible portion **246** of FIG. 2) of the piston head (e.g., the piston head **222** of FIG. 2) may be collapsed to enable the compressible fluid to flow past the piston head and piston. The collapsible portion may be collapsed following shearing of one or more shear pins included in the collapsible portion, and configured to shear upon experiencing a predetermined pressure force. At **520**, a flapper valve (e.g., the flapper valve **250** of FIG. 2) positioned at or near a bottom of the pressure housing may actuate, and may place the back pressure valve in fluid communication with the tubing hanger and any tubing below. As such, actuating the flapper valve at **520** may further include releasing the compressible fluid from the back pressure valve through the flapper valve.

(44) The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, for example, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “contains,” “containing,” “includes,” “including,” “comprises,” and/or “comprising,” and variations thereof, when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or

components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

(45) Terms of orientation used herein are merely for purposes of convention and referencing and are not to be construed as limiting. However, it is recognized these terms could be used with reference to an operator or user. Accordingly, no limitations are implied or to be inferred. In addition, the use of ordinal numbers (e.g., first, second, third, etc.) is for distinction and not counting. For example, the use of “third” does not imply there must be a corresponding “first” or “second.” Also, if used herein, the terms “coupled” or “coupled to” or “connected” or “connected to” or “attached” or “attached to” may indicate establishing either a direct or indirect connection, and is not limited to either unless expressly referenced as such.

(46) The use of directional terms such as above, below, upper, lower, upward, downward, left, right, uphole, downhole and the like are used in relation to the illustrative embodiments as they are depicted in the figures, the upward direction being toward the top of the corresponding figure and the downward direction being toward the bottom of the corresponding figure, the uphole direction being toward the surface of the well and the downhole direction being toward the toe of the well.

(47) While the disclosure has described several exemplary embodiments, it will be understood by those skilled in the art that various changes can be made, and equivalents can be substituted for elements thereof, without departing from the spirit and scope of the invention. In addition, many modifications will be appreciated by those skilled in the art to adapt a particular instrument, situation, or material to embodiments of the disclosure without departing from the essential scope thereof. Therefore, it is intended that the invention not be limited to the particular embodiments disclosed, or to the best mode contemplated for carrying out this invention, but that the invention will include all embodiments falling within the scope of the appended claims. Moreover, reference in the appended claims to an apparatus or system or a component of an apparatus or system being adapted to, arranged to, capable of, configured to, enabled to, operable to, or operative to perform a particular function encompasses that apparatus, system, or component, whether or not it or that particular function is activated, turned on, or unlocked, as long as that apparatus, system, or component is so adapted, arranged, capable, configured, enabled, operable, or operative.

Claims

1. A back pressure valve, comprising: a valve body having opposing upper and lower ends; and a pressure testing system extending from the lower end of the valve body and providing: a pressure housing defining an interior at least partially filled with a compressible fluid; a piston axially translatable within the interior and including a piston head that forms a seal against an inner wall of the pressure housing, and a piston rod extending distally from the piston head; a motor operatively coupled to the piston rod and operable to drive the piston toward and away from the valve body; and a pressure gauge assembly configured to monitor and report a pressure within the interior, wherein, as the motor advances within the interior, the compressible fluid is compressed and the pressure within the interior increases, and wherein, the pressure gauge assembly reporting that the pressure stabilizes after a predetermined time interval is a positive indication that the valve body properly holds pressure.

2. The back pressure valve of claim 1, further comprising a control module communicably coupled to the motor and programmed to operate the motor.

3. The back pressure valve of claim 2, wherein the control module is housed within a hermetically sealed protected chamber provided within the pressure housing.

4. The back pressure valve of claim 2, wherein the control module includes a timer programmed to trigger operation of the motor upon expiration of a predetermined time limit.

5. The back pressure valve of claim 1, wherein the pressure gauge assembly includes: a pressure tube in fluid communication with the interior; and a pressure gauge in communication with the

pressure tube and configured to measure the pressure within the interior.

6. The back pressure valve of claim 5, wherein the pressure gauge assembly further includes: a port defined in the valve body and in communication with the pressure gauge; and a hydraulic line communicably coupled to the pressure gauge and extending to a remote location to communicate real-time pressure measurements of the interior.

7. The back pressure valve of claim 1, wherein the piston head includes a collapsible portion pivotably attached to a remainder of the piston head.

8. The back pressure valve of claim 7, wherein the collapsible portion is pivotably attached with a collapsing mechanism comprising a pivotable hinge held in place with one or more shear pins configured to shear upon experiencing a predetermined pressure force.

9. The back pressure valve of claim 1, further comprising a flapper valve positioned at or near a bottom of the pressure housing.

10. The back pressure valve of claim 1, wherein the pressure gauge assembly is in communication with a remote location to communicate real-time pressure measurements of the interior.

11. The back pressure valve of claim 10, wherein the pressure gauge assembly provides the positive indication to the remote location indicating that the valve body does not enable backflow therethrough if the real-time pressure measurement does not decrease after a predetermined time interval.

12. A method of testing a back pressure valve, comprising: installing the back pressure valve in a tubing hanger of a wellhead, the back pressure valve including a valve body having opposing upper and lower ends, and a pressure testing system extending from the lower end of the valve body, the pressure testing system providing: a pressure housing defining an interior at least partially filled with a compressible fluid; a piston axially translatable within the interior and including a piston head that forms a seal against an inner wall of the pressure housing, and a piston rod extending distally from the piston head; a motor operatively coupled to the piston rod; and a pressure gauge assembly, operating the motor and thereby driving the piston toward the valve body; compressing the compressible fluid within the interior as the piston moves toward the valve body; monitoring and reporting a pressure within the interior with the pressure gauge assembly; and determining that the valve body properly holds pressure when the pressure gauge assembly reports that the pressure stabilizes after a predetermined time interval.

13. The method of claim 12, wherein the motor is communicably coupled to a control module housed within a hermetically sealed protected chamber provided within the pressure housing, the method further comprising sending a signal to the motor with the control module to begin operation of the motor.

14. The method of claim 13, wherein the control module includes a timer and sending the signal comprises: programming the timer with a predetermined time limit; and sending the signal upon expiration of the predetermined time limit.

15. The method of claim 12, further comprising coupling a hydraulic line to the pressure gauge assembly, wherein the hydraulic line extends to a remote location for monitoring and reporting the pressure within the interior with the pressure gauge assembly.

16. The method of claim 12, further comprising: collapsing a collapsible portion of the piston head pivotably attached to a remainder of the piston head; actuating a flapper valve positioned at or near a bottom of the pressure housing; and releasing the compressible fluid from the back pressure valve through the flapper valve.

17. The method of claim 16, wherein collapsing the collapsible portion of the piston head comprises shearing one or more shear pins configured to shear upon experiencing a predetermined pressure force.

18. The method of claim 12, further comprising providing the positive indication to a remote location in communication with the pressure gauge assembly if the pressure gauge assembly

reports that the pressure does not decrease after a predetermined time interval, the positive indication indicating that the valve body does not enable backflow therethrough.
