

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408814
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Lin; Chengchuan

Air tube of shoe dryer

Abstract

An air tube of a shoe dryer is provided. A top of the air tube has at least one air outlet. An air passage is formed in the air tube. A top surface of the air tube is provided with at least one support rib. At least one guide passage is provided on an outer side wall of the air tube or inside the air tube. The guide passage is independent of the air passage of the air tube. The air tube of the shoe dryer can prevent the backflow of warm air when the air tube is in operation and improve the convective drying efficiency.

Inventors:	Lin; Chengchuan (Xiamen, CN)
Applicant:	Lin; Chengchuan (Xiamen, CN)
Family ID:	80857791
Appl. No.:	17/696832
Filed:	March 16, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220304547 A1	Sep. 29, 2022

Foreign Application Priority Data

CN	202120635268.8	Mar. 29, 2021
----	----------------	---------------

Publication Classification

Int. Cl.: **A47L23/20 (20060101)**

U.S. Cl.:

CPC **A47L23/20 (20130101);**

Field of Classification Search

CPC: A47L (23/20)

USPC: 34/104

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
386746	12/1887	Hess	34/104	F26B 21/006
2614337	12/1951	Darbo	34/104	A47L 23/205
3417482	12/1967	Peet	392/347	A47L 23/20
4768293	12/1987	Kaffka	392/383	A47L 23/205
5287636	12/1993	Lafleur	34/239	F26B 21/006
5555640	12/1995	Ou	312/249.9	F26B 25/066
9890997	12/2017	Montes	N/A	F26B 21/004
11723460	12/2022	Allen	211/85.7	D06F 58/00
11957293	12/2023	Lin	N/A	A47L 23/205
2022/0304547	12/2021	Lin	N/A	A47L 23/20
2023/0380658	12/2022	Lin	N/A	A47L 23/205
2024/0263381	12/2023	Lin	N/A	D06F 59/04
2024/0295206	12/2023	Svensson	N/A	F02M 61/14

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
216205106	12/2021	CN	A47L 23/20
220269861	12/2022	CN	D06F 59/04

Primary Examiner: Gravini; Stephen M

Background/Summary

BACKGROUND OF THE INVENTION

1. Field of the Invention
- (1) The present invention relates to a shoe dryer, and more particularly to an air tube of a shoe dryer.
2. Description of the Prior Art
- (2) In daily life, shoes may be damped due to sweat. In rainy and snowy weather, it is easier to wet the shoes. The inside of wet shoes cannot be dried in a short time by natural air drying. A shoe dryer is developed accordingly. For some cold-proof boots, the boots are tall and have fluff in the boots. It is more difficult to dry the boots after getting wet.
- (3) A conventional shoe dryer is provided with an air tube for warm air to flow out of the shoe dryer. The top of the air tube has multiple air outlets. When the shoe is placed on the air tube, the air outlets are easily blocked and jammed by the fabric on the inner surface of the shoe, especially the shoe having fluff inside the shoe. In the process of heating the air, the fluff is expanded due to heat or static electricity, which is easy to block the air outlets. The wind resistance is formed on the

wall of the air tube, which blocks the convection. It will cause the warm air to flow back into the air tube to generate heat accumulation and cause the wind wheel to be deformed or damaged by heat. The high temperature is more likely to cause safety hazards. Furthermore, since the air in the shoe cannot form an airflow circulation, the convective drying efficiency inside the shoe will be low. In addition, most of the air tubes of the conventional shoe dryers need a separate shoe support or a support member as a support to form a convection space. Many parts need to be assembled separately. It is not easy to store and carry the shoe dryer. The effect is not good.

(4) Accordingly, the inventor of the present invention has devoted himself based on his many years of practical experiences to solve these problems.

SUMMARY OF THE INVENTION

(5) The primary object of the present invention is to provide an air tube of a shoe dryer, which can prevent the backflow of wane air when the air tube is in operation and improve the convective drying efficiency.

(6) In order to achieve the above-mentioned object, the technical solutions of the present invention are as follows:

(7) An air tube of a shoe dryer is provided. A top of the air tube has at least one air outlet. An air passage is formed in the air tube. A top surface of the air tube is provided with at least one support rib. At least one guide passage is provided on an outer side wall of the air tube or inside the air tube. The guide passage is independent of the air passage of the air tube.

(8) Preferably, both ends of the guide passage are formed with openings. The openings are located on the outer side wall of the air tube. The opening at the upper end of the guide passage is lower than the air outlet on the top of the air tube.

(9) Preferably, the guide passage is integrally formed with the air tube.

(10) Preferably, the guide passage is formed through a half-closed shell surrounding the wall of the air tube.

(11) Preferably, at least one end of the support rib extends downward to form a guide rib, and the guide rib is integrally formed on the outer side wall of the air tube.

(12) Preferably, the top surface of the air tube is provided with two support ribs. At least one end of each support rib extends downward to a side wall of the air tube. The side wall of the air tube is formed with at least one pair of guide ribs extending downward to a lower end of the air tube. The guide passage on the outer wall of the air tube is located between the two guide ribs.

(13) Preferably, the top surface of the air tube is provided with two support ribs extending forward. A baffle is provided between the two support ribs. The baffle is located at a front end of the top surface of the air tube. The baffle is located above the guide passage.

(14) Preferably, the air outlet includes a top air outlet area on the top surface of the air tube and a side air outlet area on a front side of the air tube. The baffle is located in front of the side air outlet area.

(15) Preferably, the baffle has at least one ventilation hole.

(16) Preferably, front ends of the two support ribs are provided with a bar. A ventilation area is formed between the bar and the baffle.

(17) Preferably, the air tube is a hollow round, square or oval tube.

(18) With the above-mentioned technical solutions, in the present invention, the top surface of the air tube is provided with a support rib, and at least one guide passage is provided on the outer side wall of the air tube or inside the air tube. When in use, a shoe is placed on the top of the air tube, and a support space is defined between the support rib and the side wall of the air tube. Due to the guide passage on the side wall of the air tube, an airflow channel for air circulation is formed inside the shoe body, which can effectively avoid the backflow of warm air and improve the convective drying efficiency inside the shoe. It is safer to use shoe dryer.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIGS. 1-3 are perspective views according to a first embodiment of the present invention;
- (2) FIG. 4 is a bottom view according to the first embodiment of the present invention;
- (3) FIG. 5 and FIG. 6 are perspective views according to a second embodiment of the present invention;
- (4) FIG. 7 is a bottom view according to the second embodiment of the present invention;
- (5) FIG. 8 and FIG. 9 are perspective views according to a third embodiment of the present invention;
- (6) FIG. 10 is a bottom view according to the third embodiment of the present invention;
- (7) FIG. 11 is a perspective view according to a fourth embodiment of the present invention; and
- (8) FIG. 12 is a bottom view according to the fourth embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

(9) Embodiments of the present invention will now be described, by way of example only, with reference to the accompanying drawings.

(10) As shown in FIG. 1 through FIG. 4, the present invention discloses an air tube **1** of a shoe dryer. The top of the air tube **1** has at least one air outlet **11**. An air passage **10** is formed in the air tube **1**. The warm air is discharged from the air outlet **11** after passing through the air passage **10**. When in use, the air tube **1** is inserted in a shoe for drying the shoe. The present invention can not only be used for drying shoes, but also can be used for drying items that are easily damped, such as helmets, socks and gloves. The top surface of the air tube **1** is provided with at least one support rib **12**. When the shoe is placed on the top of the air tube **1**, a support space is defined between the support rib **12** and the side wall of the air tube **1**. The inner surface of the shoe is supported to be away from the air outlet **11**, so as to prevent the air outlet **11** from being blocked or jammed by the cloth or fluff on the inner surface of the shoe. The air outlet **11** may include a top air outlet area **111** on the top of the air tube **1** and a side air outlet area **112** on the side of the air tube **1**. The air outlet **11** may be in the form of a plurality of elongated air outlets on the top and the side of the air tube **1**. As shown in FIG. 2, the top surface of the air tube **1** is an inclined surface. The higher end is defined as the front end. The top surface of the air tube **1** is provided with two support ribs **12** extending forward. The air outlet **11** is disposed between the two support ribs **12**. An air flow channel may be formed through the support of the two support ribs **12**. The front end of the support rib **12** forms an inclined support surface **120** which is gradually inclined upward along the length direction and is located at the front end of the air tube **1**. By extending the support rib **12**, the support space is enlarged and extends to the shoe body.

(11) In the present invention, at least one guide passage **13** is provided inside the air tube **1** and is independent of the air passage **10**. Through the guide passage, when the air tube is in operation, the air in the shoe body or the drying cavity can be prevented from being blocked, resulting in the backflow of warm air. It is avoided that the air in the shoe or the cavity cannot form airflow circulation, resulting in low efficiency of internal convective drying.

(12) Specifically, FIGS. 1 to 4 illustrate a first embodiment of the present invention. In this embodiment, the air tube **1** is a hollow round tube. The guide passage **13** is disposed inside the air tube **1**. The guide passage **13** is integrally formed with the air tube **10**. The guide passage **13** may be formed through a half-closed shell surrounding the wall of the air tube. In this embodiment, as shown in FIG. 3 and FIG. 4, the interior of the air tube **1** is directly divided into the air passage **10** and the guide passage **13** by a plate **100**. Only the top of the air passage **10** is provided with the air outlet **11**. Both ends of the guide passage **13** are formed with openings. The opening at the lower end is located at the lower end of the air tube **1**, and the opening **131** at the upper end is located on the outer side wall of the air tube **1**. The opening **131** at the upper end is lower than the air outlet **11**

on the top of the air tube **1**. After the warm air is blown out from the air outlet **11**, the air flow can be guided by the guide passage **13** because the opening **131** at the upper end of the guide passage **13** is located on the wall of the air tube **1**. The internal air in the drying process can be circulated to the outside of the air tube **1**, thereby avoiding the backflow of warm air and improving the convective drying efficiency inside the shoe or other drying cavities.

(13) The guide passage **13** may be a passage having a semicircular cross-section, which is partitioned and formed inside the air tube **1**. Alternatively, a semi-closed shell in the form of a plate having other shapes is formed on the inner wall of the air tube **10**. An independent passage in other shapes is formed inside the air tube **1**.

(14) Further, a baffle **121** is provided between the two support ribs **12** on the top surface of the air tube **1**. The baffle **121** is located at the front end of the top surface of the air tube **1**, and the baffle **121** is located above the guide passage **13**. The arrangement of the baffle **121** may be changed according to the position of the guide passage located below the baffle **121**. The baffle is located above the opening **131** of the guide passage **13**. The baffle **121** is configured to provide separation and support between the guide passage **13** and the support ribs **12** for guiding the warm air flow to the front end of the shoe body and extending the area where the warm air flow passes, so that the warm air flow is maintained above the guide opening, and the warm air flow is turned over before being led out to the guide passage.

(15) FIGS. **5** to **7** illustrate a second embodiment of the present invention. The second embodiment is substantially similar to the first embodiment with the exceptions described hereinafter. In this embodiment, the guide passage **14** is located on the outer side wall of the circular air tube **1**. The guide passage **14** is formed through an arc-shaped plate surrounding the outer side wall of the air tube **1**. The upper opening **141** of the guide passage **14** is located on the outer side wall of the air tube **1** and below the air outlet **11**. In addition, as shown in FIG. **6**, the air outlet **11** of the air tube **1** may include a top air outlet area **111** and a side air outlet area **112** on the side of the air tube **1**. The side air outlet area **112** may be located on both sides of the top air outlet area. The side air outlet area **112** may be located at the front side and/or the rear side of the air tube **1**. The front side of the air tube **1** is provided with the side air outlet area **112** as an emergency drainage passage. If the air outlet **111** on the top surface of the air tube **1** is blocked, the warm air is blown from the side air outlet area **112** toward the toe cap in front of the air tube. A baffle **121** is provided between the two support ribs **12** on the top surface of the air tube **1**. The baffle **121** is located at the front end of the top surface of the air tube **1**. The baffle **121** is also located in front of the side air outlet area **112**. The baffle **121** is located above the guide passage **14**.

(16) FIGS. **8** to **10** illustrate a third embodiment of the present invention. In this embodiment, the guide passage **15** is located on the outer side wall of the air tube **1**, which is formed through a three-piece enclosure plate **150** formed on the outer side wall of the air tube **1**. The three-piece enclosure plate **150** includes two side plates **1501** connected to the outer side walls of the air tube **1** and a connecting plate **1502** connected between the two side plates **1501**. The connecting plate may be a curved plate. The guide passage **15** is formed on the outer side wall of the air tube **1**, having a curved outer side.

(17) As shown in FIG. **9**, the top surface of the air tube **1** has a top air outlet area **111**, and the front end of the air tube **1** has a side air outlet area **112**. A baffle **121** is provided between the two support ribs **12** on the top surface of the air tube **1**. The baffle **121** is located at the front end of the side air outlet area **112**, and the baffle **121** is located above the guide passage **15**. Further, the baffle **121** has at least one ventilation hole **1211**. In this embodiment, the baffle **121** has four ventilation holes **1211**. The two support ribs **12** support the front end of the shoe body. When the front end is blocked by the fluff in the shoe, the warm air can be discharged through the ventilation hole **1211** after coining out from the side air outlet area **112**, so that the ventilation hole **1211** functions as an emergency exhaust to prevent the air outlet of the air tube from being blocked. The front ends of the two support ribs **12** are provided with a bar **124**. The bar **124** is configured to block the long

fluff at the toe cap of the shoe. A ventilation area **125** is formed between the bar **124** and the baffle **121**. The bar **124** can prevent fuzz from blocking the ventilation area **125**. After the warm air flow is turned over, it comes out from the ventilation area **125**. The warm air flow is then guided through the guide passage, so that the utilization efficiency of the warm air flow can be improved.

(18) FIG. **11** and FIG. **12** illustrate a fourth embodiment of the present invention. The fourth embodiment is substantially similar to the above embodiments with the exceptions described hereinafter. A guide rib is provided on the outer side wall of the circular air tube **1** to speed up the warm air flow. At least one end of each support rib **12** extends downward to form a guide rib. The guide rib is integrally formed on the outer side wall of the air tube **1**. In this embodiment, the top surface of the air tube **1** is provided with two support ribs **12**. Both ends of each support rib **12** extend downward to form guide ribs **122**, **123**. A pair of parallel guide ribs are formed at the front end and the rear end of the air tube **1**. The side air outlet area of the air outlet of the air tube **1** is located at the inner sides of the two air guide ribs **123** (not shown in the figures). As shown in FIG. **12**, the guide passage **13** in this embodiment is the same as that of the first embodiment. The guide passage **13** is independently located in the air tube **1**. The guide ribs **122**, **123** are configured to support the space between the wall of the air tube and the inner surface of the ankle and calf area of the shoe to form an air exhaust and guide channel.

(19) In addition, the guide passage is disposed on the outer side wall of the air tube. At least one pair of guide ribs extending downward to the lower end of the air tube are formed on the side wall of the air tube, so that the guide passage is located between the two guide ribs on the outer wall of the air tube. Since the guide passage will not be affected by the adsorption of cloth or fluff in the shoe, it can further accelerate the warm air flow and avoid blockage. Of course, the guide ribs may be separately formed on the side wall of the air tube. The support ribs and the guide ribs may be interlaced and formed separately.

(20) Similarly, the air tube may be a hollow square tube or an oval tube, etc. The interior or the outer side wall of the air tube is provided with a guide passage in a different shape. When the air tube is provided with a guide rib, the air tube is provided with a variety of guide passages.

(21) In summary, regardless of the shape of the air tube and whether there is a guide rib on the air tube, the shape of the guide passage formed on the air tube may be a semicircle, a circle, a square or other polygons, but not limited thereto. The interior or the outer wall of the air tube may be combined with a closed structure to form the air passage. The number of guide passages may be two or more.

(22) Although particular embodiments of the present invention have been described in detail for purposes of illustration, various modifications and enhancements may be made without departing from the spirit and scope of the present invention. Accordingly, the present invention is not to be limited except as by the appended claims.

Claims

1. An air tube of a shoe dryer, a top of the air tube having at least one air outlet, an air passage being formed in the air tube, a top surface of the air tube being provided with at least one support rib; at least one guide passage being provided on an outer side wall of the air tube defined by an enclosure formed by a plate that encloses an area on the outer side wall of the air tube, or inside the air tube, the guide passage being independent of the air passage of the air tube.
2. The air tube of the shoe dryer as claimed in claim 1, wherein both ends of the guide passage are formed with openings, the openings are located on the outer side wall of the air tube, and a respective one of the openings at an upper end of the guide passage is lower than the air outlet on the top of the air tube.
3. The air tube of the shoe dryer as claimed in claim 1, wherein the guide passage is integrally formed with the air tube.

4. The air tube of the shoe dryer as claimed in claim 3, wherein the guide passage is formed through a half-closed shell surrounding the wall of the air tube.
 5. The air tube of the shoe dryer as claimed in claim 1, wherein the guide passage has a semicircular, circular or square cross-section.
 6. The air tube of the shoe dryer as claimed in claim 1, wherein at least one end of the support rib extends downward to form a guide rib, and the guide rib is integrally formed on the outer side wall of the air tube.
 7. The air tube of the shoe dryer as claimed in claim 6, wherein the top surface of the air tube is provided with two support ribs, at least one end of each support rib extends downward to a side wall of the air tube, the side wall of the air tube is formed with at least one pair of guide ribs extending downward to a lower end of the air tube, and the guide passage on the outer side wall of the air tube is located between the two guide ribs.
 8. The air tube of the shoe dryer as claimed in claim 1, wherein the top surface of the air tube is provided with two support ribs extending forward, a baffle is provided between the two support ribs, the baffle is located at a front end of the top surface of the air tube, and the baffle is located above the guide passage.
 9. The air tube of the shoe dryer as claimed in claim 8, wherein the air outlet includes a top air outlet area on the top surface of the air tube and a side air outlet area on a front side of the air tube, and the baffle is located in front of the side air outlet area.
 10. The air tube of the shoe dryer as claimed in claim 8, wherein the baffle has at least one ventilation hole.
 11. The air tube of the shoe dryer as claimed in claim 8, wherein front ends of the two support ribs are provided with a bar, and a ventilation area is formed between the bar and the baffle.
 12. The air tube of the shoe dryer as claimed in claim 1, wherein the air tube is a hollow round, square or oval tube.
-